

**Remedial Design, Phase II
Pre-Design Investigation
Supplemental Sampling
Letter Report Number 2
for
Site 1
Former Drum Marshaling Area
Naval Weapons Industrial Reserve
Plant (NWIRP)
Bethpage, New York**



**Northern Division
Naval Facilities Engineering Command
Contract Number N62472-90-D-1298
Contract Task Order 0213**

September 1995

C F BRAUN ENGINEERING CORPORATION

TABLE OF CONTENTS

<u>SECTION</u>	<u>PAGE</u>
1.0 INTRODUCTION	1-1
1.1 PURPOSE	1-1
1.2 ORGANIZATION OF REPORT	1-1
2.0 FIELD INVESTIGATION	2-1
2.1 SOIL BORINGS AND SUBSURFACE SOIL SAMPLING	2-1
3.0 INVESTIGATION RESULTS	3-1
3.1 FIELD EVALUATION	3-1
3.1.1 Physical Characteristics	3-1
3.1.2 Chemical Characteristics	3-2
3.2 ANALYTICAL RESULTS	3-2
4.0 SUMMARY AND RECOMMENDATIONS	4-1
REFERENCES	R-1
 <u>APPENDICES</u>	
A	SOIL BORING LOGS
B	SAMPLE LOG SHEETS
C	CHAIN OF CUSTODY RECORDS
D	DAILY ACTIVITIES RECORD
E	CHEMICAL ANALYSIS RESULTS

TABLES

<u>NUMBER</u>		<u>PAGE</u>
1-1	Remedial Action Levels for Groundwater and Soils at Site 1	1-2
3-1	HNu Readings from August 1995 Sampling Event	3-3
3-2	Soil Sample Analytical Results, August, 1995 Sampling Event	3-6

FIGURES

<u>NUMBER</u>		<u>PAGE</u>
3-1	Site 1 - Soil Boring Locations	3-5

1.0 INTRODUCTION

This Letter Report has been prepared under the Comprehensive Long-Term Environmental Action Navy (Clean) Contract No. N6247-90-D-1298, Contract Task Order (CTO) 0213. C F Braun Engineering Corporation (C F Braun) conducted soil sampling activities during the period of August 29, 1995 through September 1, 1995 (August 1995) as part of the Remedial Design, Phase II, for Site 1 at the Naval Weapons Industrial Reserve Plant (NWIRP) in Bethpage, New York. The Remedial Design, Phase II, for Site 1 includes an air sparging/vapor extraction (AS/VE) system for source contamination located in the soils and shallow groundwater beneath the site. To support design activities soil sampling and analysis has been conducted to determine the level of volatile organic compounds (VOC) contamination at the site and to assist in selecting a location for the installation of a pilot-scale AS/VE system.

Prior to the August 1995 sampling and analysis event, which is discussed in this Letter Report, sampling and analysis was performed during the month of May 1995. The information obtained from the May investigation and pertinent information from the Remedial Investigations were summarized in the Remedial Design, Phase II Pre-Design Investigation Letter Report for Site 1 (C F Braun, July 1995).

1.1 PURPOSE

The purpose of this Letter Report is to summarize the results of the August 1995 sampling and analysis pre-design investigation. Sampling activities were required at Site 1 because the available analytical data for the subsurface soil were not adequate to conduct the Remedial Design which includes determining a location for the pilot-scale AS/VE system. The objective of the sampling effort was to determine the location of elevated levels of VOC contamination within Site 1 in order to proceed with the design effort. Remedial Action levels for groundwater and soils at Site 1 were previously established and are presented in Table 1-1.

This report will summarize the results of the August 1995 sampling and analysis activities and make recommendations for future project activities.

1.2 ORGANIZATION OF REPORT

This report consists of four sections. Section 1.0 consists of this introduction. Section 2.0 describes the field activities. Section 3.0 summarizes the results of the sampling activities. Section 4.0 provides conclusions and recommendations.

TABLE 1-1
REMEDIAL ACTION LEVELS FOR
GROUNDWATER AND SOILS AT SITE 1
NWIRP BETHPAGE, NEW YORK

Chemical of Concern	New York State Standards for Groundwater ($\mu\text{g/L}$)	Remedial Action Levels for Soils⁽¹⁾ ($\mu\text{g/kg}$)
Trichloroethene	5	30
Toluene	5	NA
1,1-Dichloroethane	5	NA
1,2-Dichloroethene	5	NA
1,1,1-Trichloroethane	5	30
Tetrachloroethene	5	81
1,1-Dichloroethene	5	NA
Carbon tetrachloride	5	NA
Xylenes	5	NA
Vinyl chloride	2	NA

1 Remedial Action Levels developed for the protection of groundwater

NA Not developed for Site 1

2.0 FIELD INVESTIGATION

This section describes the supplemental field investigation activities conducted at Site 1 - Former Drum Marshaling Area, NWIRP, Bethpage, New York. The field investigation activities consisted of drilling five soil borings to the groundwater and the collection and analysis of 15 subsurface soil samples. The sampling and analysis plan (C F Braun, August 1995) also proposed the collection of three groundwater samples from three shallow groundwater monitoring wells (HN-27, HN-28, and HN-29). During the field activities these wells were discovered to be dry, therefore, no groundwater samples were collected during the event.

2.1 SOIL BORINGS AND SUBSURFACE SOIL SAMPLING

A total of five soil borings (DSB10 through DSB14) were drilled during this investigation. The soil borings were advanced with 4¼-inch inside diameter hollow stem augers. Soil samples were collected at 5-foot intervals with 2-inch outside diameter split-barrel samplers. Physical characteristics (density, color, lithology, and moisture content) of each sample were recorded on boring logs maintained by C F Braun. Boring logs are provided in Appendix A. The headspace from each soil sample was field screened with an HNu organic vapor monitor, and the readings were recorded on the boring logs.

A total of 15 soil samples were collected and analyzed for Target Compound List (TCL) volatile organic compounds (VOC). Three soil samples were collected from each soil boring. One sample was collected from the first 10 feet below ground surface, the second sample was collected from the middle of the soil boring based on the highest headspace reading, and the third sample was collected from immediately above the soil/groundwater interface. A copy of the sample log sheet listing the samples submitted to the laboratory for analysis is provided in Appendix B. The chain of custody forms which correspond to these samples are provided in Appendix C.

All downhole drilling equipment and the rear of the drilling rig were decontaminated with pressurized steam prior to drilling, between boreholes, and prior to leaving the site, at a decontamination pad. All sampling equipment (split-barrel samplers and stainless steel trowels) were decontaminated in accordance with the Sampling and Analysis Plan. The boreholes were backfilled with the soil cuttings. A daily record of activities performed were recorded and a copy of this record is provided in Appendix D.

3.0 INVESTIGATION RESULTS

This section provides the results of the field investigation activities and laboratory analyses of the samples collected during the field activities. Results of the investigation includes field and laboratory analysis of the soil.

3.1 FIELD EVALUATION

3.1.1 Physical Characteristics

Split spoons were used to collect samples and evaluate the physical characteristics of the soils. A sample from each split spoon was examined and lithology information was recorded on the log sheets provided in Appendix A.

NWIRP is located in Nassau County in east-central Long Island, New York. Long Island lies within the Coastal Plains Physiographic Province and is a glacial outwash plain. The topography of the site is relatively flat and featureless and slopes gently to the south. The site and surrounding area are urbanized, and almost all natural physical features have been altered or destroyed. NWIRP and the surrounding area are underlain by approximately 1,100 feet of unconsolidated sediments overlying crystalline bedrock. The sediments consist of four stratigraphic units: the Upper Glacial Formation, the Magothy Formation, the Raritan Clay Member of the Raritan Formation, and the Lloyd Sand Member of the Raritan Formation. The Upper Glacial Formation consists of sand and gravel of Pleistocene age (Lindner and Reilly, 1983). The Magothy Formation is composed of sand, silt, and clay and is Cretaceous in age. The two members of the Raritan Formation were not encountered during this investigation.

The surficial glacial deposits of the Upper Glacial Formation encountered during this investigation were 25 to 40 feet thick and consisted of well-graded, fine to coarse sand and fine to coarse gravel with varying amounts of silt. The Magothy Formation was encountered below the surficial glacial deposit and consisted of fine to medium, variegated sand with intermittent silt and clay layers. Groundwater elevations were approximately 60 feet (mean sea level).

3.1.2 Chemical Characteristics

Field analysis of the split spoon samples included recording the organic vapor head space results of the soil. HNu organic vapor headspace readings varied from 0 to 62 ppm and are summarized in Table 3-1. The highest readings were encountered at depths of 0 to 2 feet in the borings.

3.2 ANALYTICAL RESULTS

This section summarizes the analytical results of the soil analysis. The locations of the five soil borings where the soil samples were collected are shown on Figure 3-1.

The results of the analysis are provided in Table 3-2. Four of the five samples had VOC concentrations above established remedial action levels. The complete analytical package provided by the laboratory is provided in Appendix E.

The results for DSB10 indicated all VOCs were below the detection limits with the exception of TCE. TCE was detected at 26 $\mu\text{g/Kg}$ which is below the remedial action level of 30 $\mu\text{g/Kg}$. TCE was detected at the 0 to 2 foot interval.

DSB11 also indicated that all volatile organics analyzed were below the detection limits with the exception of PCE. PCE was detected at a concentration of 62 $\mu\text{g/Kg}$. A duplicate sample was analyzed, also determining that concentrations were below detection limits for all VOCs except PCE. PCE was detected at a concentration of 190 $\mu\text{g/Kg}$. The positive detections were found at an interval of 0 to 2 feet. The established action level for PCE is 81 $\mu\text{g/Kg}$.

The results for DSB12 indicated that all VOCs were below the detection limits except for PCE. PCE was detected at a concentration of 27 $\mu\text{g/Kg}$ which is below the remedial action level.

The soil boring with the highest levels of volatile organic contamination was DSB13. Field analysis with the HNu indicated elevated readings throughout the full depth of the boring. Laboratory analysis indicated PCE and TCE had concentrations above the established remedial action levels. The remedial action level

TABLE 3-1

**HNu READINGS FROM AUGUST 1995 SAMPLING EVENT
NWIRP BETHPAGE, NEW YORK**


Soil Boring	Depth of Sample (feet)	HNu Head Space Reading (ppm)	Sample Submitted for Fixed Base Laboratory Analysis
DSB10	0 - 2	5	*
	5 - 7	<1	
	10 - 12	<1	
	15 - 17	1	*
	20 - 22	<1	
	25 - 27	<1	
	30 - 32	<1	
	35 - 37	<1	
	40 - 42	<1	
	45 - 47	<1	
	52 - 54	<1	
	55 - 57	<1	
	60 - 62	<1	*
	62 - 64	<1	
DSB11	0 - 2	34	*
	5 - 7	34	
	10 - 12	<1	
	15 - 17	0	
	20 - 22	1.5	
	25 - 27	<1	
	30 - 32	36	*
	35 - 37	2	
	40 - 42	1.8	
	45 - 47	34	
	50 - 52	34	
	55 - 57	38	
	60 - 62	0	*
	62 - 64	NR	
DSB12	0 - 2	54	*
	5 - 7	7	
	10 - 12	3	
	15 - 17	2	
	20 - 22	3.2	
	25 - 27	1	

TABLE 3-1 (Continued)
HNu READINGS FROM AUGUST 1995 SAMPLING EVENT
NWIRP BETHPAGE, NEW YORK

Soil Boring	Depth of Sample (feet)	HNu Head Space Reading (ppm)	Sample Submitted for Fixed Base Laboratory Analysis
	30 - 32	1	
	35 - 37	1	
	40 - 42	4	*
	45 - 47	<1	
	50 - 52	1.5	
	55 - 57	1	
	60 - 62	NR	*
DSB13	0 - 2	62	*
	5 - 7	36	
	10 - 12	42	
	15 - 17	28	
	20 - 22	28	
	25 - 27	12	
	30 - 32	38	
	35 - 37	30	
	40 - 42	50	*
	45 - 47	30	
	50 - 52	28	
	55 - 57	52	*
	60 - 62	NR	
DSB14	1 - 3	<1	
	5 - 7	40	*
	10 - 12	18	
	15 - 17	4	
	20 - 22	NR	
	25 - 27	0	
	30 - 32	1	
	35 - 37	1.8	
	40 - 42	2	*
	45 - 47	1.8	
	50 - 52	NR	*
	55 - 57	NR	
	60 - 62	NR	

NR No Reading Taken

* Indicates sample was submitted for laboraotry analysis. Results of the analysis is provided in Table 3-2.



SITE 1
SOIL BORING LOCATIONS
NWIRP, BETHPAGE, NEW YORK

0 100 200
SCALE IN FEET

FIGURE 3-1

C.F. BRAUN
ENGINEERING CORP.

TABLE 3-2

**SOIL SAMPLE ANALYTICAL RESULTS
AUGUST, 1995 SAMPLING EVENT
NWIRP BETHPAGE, NEW YORK**

	1,1,1- Trichloroethane	Trichloroethene (TCE)	Tetrachloroethene (PCE)	Toluene	Xylene
Soil Boring #10 (DSB10)					
0' to 2'	BDL	26 µg/Kg	BDL	BDL	BDL
15' to 17'	BDL	BDL	BDL	BDL	BDL
60' to 62'	BDL	BDL	BDL	BDL	BDL
Soil Boring #11 (DSB11)					
0' to 2' (Dup)	BDL	BDL	62 (190) µg/Kg	BDL	BDL
30' to 32'	BDL	BDL	BDL	BDL	BDL
60' to 62'	BDL	BDL	BDL	BDL	BDL
Soil Boring #12 (DSB12)					
0' to 2'	BDL	BDL	27 µg/Kg	BDL	BDL
40' to 42'	BDL	BDL	BDL	BDL	BDL
60' to 62'	BDL	BDL	BDL	BDL	BDL
Soil Boring #13 (DSB13)					
0' to 2'	BDL	44 µg/Kg	490 µg/Kg	BDL	BDL
40' to 42'	BDL	BDL	44 µg/Kg	BDL	BDL
55' to 57'	27 µg/Kg	BDL	BDL	14 µg/Kg	12 µg/Kg
Soil Boring #14 (DSB14)					
5' to 7'	BDL	BDL	BDL	BDL	BDL
40' to 42'	BDL	BDL	BDL	BDL	BDL
50' to 52'	BDL	BDL	BDL	BDL	BDL

 Shaded area exceeds action level.

BDL Below Detection Limit

for TCE is 30 $\mu\text{g}/\text{Kg}$. The sample collected in the 0 to 2 foot interval indicated that the TCE and PCE concentrations were 44 $\mu\text{g}/\text{Kg}$ and 490 $\mu\text{g}/\text{Kg}$, respectively. At the 40 to 42 foot interval PCE was observed at 44 $\mu\text{g}/\text{Kg}$ and at the 55 to 57 foot interval 1,1,1-Trichloroethene, toluene, and xylene were observed at 27 $\mu\text{g}/\text{Kg}$, 14 $\mu\text{g}/\text{Kg}$, and 12 $\mu\text{g}/\text{Kg}$, respectively. All other volatile organics were below the detection limits.

Analytical results for DSB14, which was located by the former concrete staging pad, indicated that all VOC concentrations were below detection limits.

4.0 SUMMARY AND RECOMMENDATIONS

Two of the five soil boring locations (SB11 and SB13) indicated volatile contamination above the remedial action levels. The highest concentrations have been determined to be in the top several feet. During the previous RI investigation, SB119 was found to contain elevated levels of volatile contamination. These boring locations constitute the areas of contamination at Site 1.

Based on the sampling results, it is recommended that a pilot-scale system be installed within the area of contamination shown on Figure 3-1. The exact location of the system will be determined based on review of all historic data as well as minimizing conflicts with the proposed remediation effort for Phase I.

The purpose of the pilot-scale study will be to evaluate the success of the air sparging system to achieve concentration reductions for the chlorinated volatiles in the soil and in the upper 10 feet of the aquifer. Additionally, various design parameters will be determined such as radius of influence, air flow rates, and carbon efficiency for use during the design of a full scale system.

REFERENCES

Lindner, Julie B. and Thomas E. Reilly, 1983, Analysis of Three Tests of the Unconfined Aquifer in Southern Nassau County, Long Island, New York. Syosset, New York: USGS Water Resources Investigations Report 82-4021.

C F Braun Engineering Corporation; August 1995. Sampling and Analysis Plan Addendum for Additional Sampling at Site 1 - Former Drum Marshalling Area Naval Weapons Industrial Reserve Plant (NWIRP). Bethpage, New York.

C F Braun Engineering Corporation; July 1995. Remedial Design, Phase II, Pre-Design Investigation Letter Report for Site 1 - Former Drum Marshalling Area Naval Weapons Industrial Reserve Plant (NWIRP). Bethpage, New York.

APPENDIX

- A SOIL BORING LOGS**
- B SAMPLE LOG SHEETS**
- C CHAIN OF CUSTODY RECORDS**
- D DAILY ACTIVITIES RECORD**
- E CHEMICAL ANALYSIS RESULTS**

APPENDIX A
SOIL BORING LOGS

BORING LOG

HALLIBURTON NUS

PROJECT: NWIRP Beta page BORING NO.: DSP 10
 PROJECT NO.: 5253 DATE: 8-30-95 DRILLER: Steve Wolf
 ELEVATION: _____ FIELD GEOLOGIST: Tim Evans
 WATER LEVEL DATA: _____
 (Date, Time & Conditions) _____

SAMPLE NO. & TYPE	DEPTH (ft.) OR RUN NO.	BLOWE 6" OR ROD (ft.)	SAMPLE RECOVERY - SAMPLE LENGTH	LITHOLOGY CHANGE (DOWN FT.)	MATERIAL DESCRIPTION*			ROCK BR. OR USCS	REMARKS Time Headspace HMu
					SOIL DENSITY CONSISTENCY OR ROCK HARDNESS	COLOR	MATERIAL CLASSIFICATION		
S-1	1.0	10 12	1.6/8.0	0.8	M Dense	Dark Gray	Gravelly Sand Fine	SN	1007 5 ppm
0/2	2.0	15 15				Black Grn	Clayey Sand	SC	
	3.0								
	4.0								
	5.0								
S-2		17 12	0.8/2.0		Dense				1016 <1
5/7	7.0	15 21				orange brown	Coarse Gravelly Sand	SW	
	10.0								
S-3		17 14	0.9/2.0		Dense	orange brn	Coarse GRAVELLY M-c gr SAND	SW	1024 <1
10/12	12.0	22 28							
	15.0								
S-4		6 6	1.2/2.0		M Dense	yellow tan	Coarse GRAVELLY M-c gr SAND	SW	1032 1
15/17	17.0	10 11					F-gr SAND FINE TR GRAVEL	SP	
	20.0								
S-5		10 9	1.2/2.0		M Dense	Tan	Coarse GRAVELLY F-c gr SAND	SW	1038 <1
20/22	22.0	13 16							
	25.0								

REMARKS Mobile B-61 HSA Rig
2" SS 4 1/4" ID Augers, Down hole Hammer

BORING DSB 10PAGE 1 OF 3

BORING LOG

HALLIBURTON NUS

PROJECT: NWIRP Beth page BORING NO.: DSB 10
 PROJECT NO.: 5253 DATE: 8-30-95 DRILLER: Steve Wolf
 ELEVATION: _____ FIELD GEOLOGIST: Tim Evans
 WATER LEVEL DATA: _____
 (Date, Time & Conditions) _____

SAMPLE NO. & TYPE	DEPTH (ft) OR RUN NO.	BLOW 6" OR ROD (ft)	SAMPLE RECOVERY .SAMPLE LENGTH	LITHOLOGY CHANGE (Depth, ft)	MATERIAL DESCRIPTION*			ROCK BR. OR USCS	REMARKS Time Headspace H.Nu
					SOL. DENSITY, CONSISTENCY OR ROCK HARDNESS	COLOR	MATERIAL CLASSIFICATION		
S-6 25/27		8 11	1.0 2.0		Dense	Tan	Fine-gr SAND Trace FINE GRAVEL	SP	1045 <1 pm
	27.0	15 16							
	30.0								
S-7 30/32		10 8	1.5 2.0		M Dense	Tan	M-gr SAND Some FINE gravel	SW	1052 Brown mottling <1
	32.0	10 16							
	35.0								
S-8 35/37		18 22	1.5 2.0		Dense	Brn	M-gr SAND Tr Iron (rust) Nodules	SW	1100 <1
	37.0	20 20							
	40.0								
S-9 40/42		15 16	1.4 2.0		Dense	Yellow Orange	M-gr SAND upoonly grade	SP	1110 <1
	42.0	27 21							
	45.0		1.2 2.0					SP	1117 <1
S-10 45/47		16 17			Dense	lt Gray	Fine-gr SAND		
	47.0	21 20							
	50.0								

REMARKS _____

BORING DSB 10PAGE 2 OF 3

* See Legend on Back

HALLIBURTON NUS

[illegible]

PAGE 3 OF 3

BORING LOG

HALLIBURTON NUS

PROJECT: NWIRP Beth page BORING NO.: DSB11
 PROJECT NO.: 5257 DATE: 8/30/95 DRILLER: Steve Wolf
 ELEVATION: _____ FIELD GEOLOGIST: Tim Evans
 WATER LEVEL DATA: _____
 (Date, Time & Conditions) _____

SAMPLE NO. & TYPE	DEPTH (ft.) OR RUN NO.	BLOWE 6" OR ROD (ft.)	SAMPLE RECOVERY - SAMPLE LENGTH	LITHOLOGY CHANGE (Downhole)	MATERIAL DESCRIPTION*			ROCK BR. OR USCS	REMARKS	
					SOIL DENSITY, CONSISTENCY OR ROCK HARDNESS	COLOR	MATERIAL CLASSIFICATION		Time	Headspace H ₂ O
S-1 8/12	1.0	5 21	1.4 0.0		M Dense	Dark Gray	Silty Sand Tr FGR GRAVEL	SC	1347	34 ppm
	2.0	19 8								
	5.0									
S-2 5/17		3 2	1.2 0.0		M Dense	orange brn	Mgr SAND Some FINE GRAVEL	SW	1355	34 ppm
	7.0	12 14				gray-brn tan	Silt Sand Some Gravel	SW		
	10.0									
S-3 10/12		9 9	1.0 0.0		M Dense	yellow orange	M-C gr SAND Some Gravel	SW	1404	<1
	12.0	11 14								
	15.0									
S-4 15/17		10 9	0.9 0.0		M Dense	yellow orange	M-C gr SAND Some Fine Gravel	SW	1414	0
	17.0	10 9								
	20.0									
S-5 20/22		8 10	1.1 0.0		M Dense	Brn	Gravelly M-C gr SAND	SW	1424	1.5
	22.0	9 10								
	25.0									

REMARKS Mobile B61HSA Rig
2" SS, 4 1/4" ID Augers, Downhole Hammer

* See Legend on Back

BORING DSB11PAGE 1 OF 3

BORING LOG

HALLIBURTON NUS

PROJECT: NWIRP Beth page BORING NO.: DSB11
 PROJECT NO.: 5253 DATE: 8-30-95 DRILLER: Steve Wolf
 ELEVATION: _____ FIELD GEOLOGIST: T Evans
 WATER LEVEL DATA: _____
 (Date, Time & Conditions) _____

SAMPLE NO. & TYPE	DEPTH (FL) OR RUN NO.	BLOWS 6" OR ROD (Ft)	SAMPLE RECOVERY - SAMPLE LENGTH	LITHOLOGY (CHANGE DOWN FL)	MATERIAL DESCRIPTION*			ROCK BR OR USCS	REMARKS Time
					SOIL DENSITY, CONSISTENCY OR ROCK HARDNESS	COLOR	MATERIAL CLASSIFICATION		
S-6 25/27	26.0	10 14	1 1/2 / 2.0	---	Dense	Tan	Fgr SAND	SP	1430 <1
	27.0	19 20					cravelly SAND	SW	
	30.0								
S-7 30/32		8 11	1 1/2 / 5.0	??	Dense	ltv			1437 30 *
	32.0	12 11				ltgray	Fgr SAND vpoorly graded	SP	
	35.0								
S-8 35/37		12 12	1.3 / 2.0	??	Dense	LtBrn	Mgr SAND	SP	1445 2
	37.0	11 16							
	40.0								
S-9 40/42		11 7	1.4 / 0.0		Dense	Ltgray	Fgr SAND	SP	1453 1.8
	42.0	12 10							
	45.0								
S-10 45/47		12 12	1.7 / 2.0		M Dense	Ltgray	Fgr SAND	SP	1501 34
	47.0	19 20							
	50.0								

REMARKS _____

BORING DSB11

* See Legend on Back

PAGE 2 OF 3

BORING LOG

HALLIBURTON NUS

PROJECT: NW 1/4 P. 34th Ave.

BORING NO.: DSB 11

PROJECT NO.: 5253

DATE: 8-30-95

DRILLER: Steve Wolf

ELEVATION:

FIELD GEOLOGIST: Tim Evans

WATER LEVEL DATA:

(Date, Time & Conditions)

SAMPLE NO. & TYPE	DEPTH (ft) OR RUN NO.	BLOWS 6" OR ROD (ft)	SAMPLE RECOVERY .SAMPLE LENGTH	LITHOLOGY CHANGE (Depth ft.)	MATERIAL DESCRIPTION*			ROCK BR OR USCS	REMARKS	
					SOIL DENSITY, CONSISTENCY OR ROCK HARDNESS	COLOR	MATERIAL CLASSIFICATION		Time	Handspace ft/min
S-11 50/52	51.0	9 8	1.4 / 2.0		V Dense	Tan	Fgy SAND	SP	1508	34
	52.0	21 21								
	55.0									
S-12 55/57		11 15	1.4 / 2.0		V Dense	orange Brn	MSR SAND	SP	1515	38
	57.0	23 38								
	60.0									
S-13 60/62		7 14	1.3 / 2.0		V Dense	gray	Silt + MSR SAND	SP SM	1525	Damp 0
	62.0	22 22				Brn		SP		
S-14 62/64		11 12	1.2 / 2.0						1530	Saturated -
	64.0	11 15								
				TD 64			HSA 60'			
							Samples			
							DSB 11 - 00/02			
							DSB 11 - 30/32			
							DSB 11 - 60/62			
							sent to Pace Labs			
							for TCL VOC			

REMARKS

BORING DSB 11

* See Legend on Back

PAGE 3 OF 3

BORING LOG

HALLIBURTON NUS

PROJECT: NW 128 Beth page.BORING NO.: DSB12PROJECT NO.: 5253DATE: 8.31.95DRILLER: Steve Wolf

ELEVATION: _____

FIELD GEOLOGIST: Tim Evans

WATER LEVEL DATA: _____

(Date, Time & Conditions) _____

SAMPLE NO. & TYPE	DEPTH (FL) OR RUN NO.	BLOW 6" OR ROD (ft)	SAMPLE RECOVERY .SAMPLE LENGTH	LITHOLOGY CHANGE (Depth, FL)	MATERIAL DESCRIPTION*			ROCK BR OR USCS	REMARKS
					SOIL DENSITY CONSISTENCY OR ROCK HARDNESS	COLOR	MATERIAL CLASSIFICATION		
S-1 01/2	1.0	7 8	1.7/2.0	---	M Dense	Gray D.Brn	Sand some gravel Silty Sand	SW SC	1235 54 ppm *
	2.0	7 9		---		Brn	Fine Gravelly SAND	SW	
	5.0								
S-2 51/2		3 3	2.0	---	M Dense	Gray	Silt Tr SAND & Fine gravel	SM	1241 Damp 7
	7.0	9 6		---		Tan	Mgr SAND Tr Fine gravel	SP	
	10.0								
S-3 101/2		9 7	1.0/2.0		M Dense	orange brn	Fine - Coarse Gravelly Mgr SAND	SW	1248 3
	12.0	11 13							
	15.0								
S-4 151/2		9 9	0.12/2.0		M Dense	orange brn	Gravelly Sand	SW	1257 Moist 2
	17.0	11 17							Poor recovery
	20.0								
S-5 201/2		7 9	1.2/2.0		M Dense	orange brn	Gravelly SAND	SW	1304 Moist 3.2
	22.0	10 8							
	25.0								

REMARKS Mobile B-61 HSA Rig
4 1/4" ID Augers, 2" SS, Down Hole HammerBORING DSB12PAGE 1 OF 3

BORING LOG

HALLIBURTON NUS

PROJECT: NW 1 R P Beth page BORING NO.: DSB12
 PROJECT NO.: 5253 DATE: 8-31-95 DRILLER: Steve Wolf
 ELEVATION: _____ FIELD GEOLOGIST: Tim Evans
 WATER LEVEL DATA: _____
 (Date, Time & Conditions) _____

SAMPLE NO. & TYPE	DEPTH (ft) OR RUN NO.	BLOW 6" OR 200 (ft)	SAMPLE RECOVERY - SAMPLE LENGTH	LITHOLOGY CHANGE (Depth, ft)	MATERIAL DESCRIPTION*		ROCK BR OR USES	REMARKS
					SOIL DENSITY, CONSISTENCY OR ROCK HARDNESS	COLOR		
S-6 25/27	26.0	8 10	1 1/2 / 2.0		M Dense	Tan	F-C or SAND Tr fine gravel	SW 1309 1 ppm
	27.0	11						
	30.0							
S-7 30/32		6 11	1 1/2 / 2.0		M Dense	Tan	M-C or SAND Tr iron (rust) nodules (.20")	SW 1316 1 ppm
	32.0	13 13						
	35.0							
S-8 35/37		11 17	1.8 / 2.0		Dense	orange brn	SAND Tr rust nodules	SW 1323 1
	37.0	18 21			Tan		silty sand	SM
	40.0							
S-9 40/42		8 8	1.5 / 2.0		M Dense	white tan	Fgr SAND Tr mica	SP 1330 4
	42.0	9 10						
	45.0							
S-10 45/47		9 11	1.5 / 2.0		M Dense	wh. & tan	Fgr SAND Tr mica	SP 1332 <1
	47.0	10 17						
	50.0							

REMARKS _____

BORING DSB12

* See Legend on Back

PAGE 2 OF 3

HALLIBURTON NUS

SAMPLE NO. & TYPE	DEPTH (ft) OR RUN NO.	BLOWE 6" OR 800 (%)	SAMPLE RECOVERY SAMPLE LENGTH	LITHOLOGY CHANGE (DOWN ft.)	MATERIAL DESCRIPTION*			ROCK BR OR USCS	REMARKS	
					SOIL DENSITY CONSISTENCY OR ROCK HARDNESS	COLOR	MATERIAL CLASSIFICATION		Time	Head H ₂ O
S-11 50/52	51.0	11 12 14	1.4 2.0		M Dense	Pink Tan	Moist SAND V poorly grade	SP	1345	1.5
	52.0									
	55.0									
S-12 55/57		16 14 20 18	1.3 2.0		Dense	Yellow brn	SAND	SP	1553	Damp 1ppm
	57.0						Tr Silt & gravel			
	60.0									
S-13 60/62			1.6 2.0	8/31		Tan Brn	Sand w/ Silt layer	SP	1402	-
	62.0			7-61.5'						Saturated
				70-62						
							HSA 60'			
							Samples:			
							DSB12 - 00/02			
							DSB12 - 40/42			
							DSB12 - 60/62			
							sent to Pace Labs			
							for TCL VUC			

BORING DSB 12

PAGE 3 OF 3

BORING LOG

HALLIBURTON NUS

PROJECT: NWIRP Beth page BORING NO.: DSB 13
 PROJECT NO.: 5253 DATE: 8.31.95 DRILLER: Steve Wolf
 ELEVATION: _____ FIELD GEOLOGIST: Tim Evans
 WATER LEVEL DATA: _____
 (Date, Time & Conditions) _____

SAMPLE NO. & TYPE	DEPTH (ft) OR RUN NO.	BLOWS 5" OR 800 PSI	SAMPLE RECOVERY - SAMPLE LENGTH	LITHOLOGY (CHANGE (Depth, ft.))	MATERIAL DESCRIPTION*			ROCK BR. OR USES	REMARKS
					SOIL DENSITY, CONSISTENCY OR ROCK HARDNESS	COLOR	MATERIAL CLASSIFICATION		
S-1 0/12	1.0	5 2	1.1/2.0	---	M Dense	Tan	Sand to gravel Clayey Sand	SP SC	time 0903 62 ppm*
	2.0	8							
	5.0								
S-2 5/7		12 10	1.0/2.0		Dense	Tan	Fine Gravelly Sand	SW	0909 36 ppm
	7.0	15 16							
	10.0								
S-3 10/12		11 9	1.0/2.0		M Dense	Tan	Gravelly SAND	SW	0915 42
	12.0	10 13							
	15.0								
S-4 15/17		9 9	1.3/2.0		M Dense	Tan	FGR SAND	SP	0921 28
	17.0	8 9					F-CGR SAND	SW	
	20.0								
S-5 20/22		14 12	1.3/2.0		M Dense	Tan	Fine GRAVELLY SAND	SW	0928 28
	22.0	13 16							
	25.0								

REMARKS Mobile B-61 HSA Rig
4 1/4" 10 Augers, 2" Split Spoon, Downhole
Hammer

* See Legend on Back

BORING DSB 13PAGE 1 OF 3

BORING LOG

HALLIBURTON NUS

PROJECT: NWIRP Beth page BORING NO.: DSB 13
 PROJECT NO.: 5253 DATE: 8.31.93 DRILLER: Steve Wolf
 ELEVATION: _____ FIELD GEOLOGIST: Tim Evans
 WATER LEVEL DATA: _____
 (Date, Time & Conditions) _____

SAMPLE NO. & TYPE	DEPTH (ft) OR RUN NO.	BLOWS 6" OR ROD (ft)	SAMPLE RECOVERY - SAMPLE LENGTH	LITHOLOGY CHANGE (DOWN PL)	MATERIAL DESCRIPTION*			REMARKS
					SOIL DENSITY, CONSISTENCY OR ROCK HARDNESS	COLOR	MATERIAL CLASSIFICATION	
S-6 35/37	26.0	7 7 9	1.5/8.0		M Dense	Tan	Mgr SAND Tr Fine gravel	SP/SW 0935 12
	27.0	12						
	30.0							
S-7 30/32		10 8 8	1.4/6.0		M Dense	orange brown	FMgr SAND Tr/Some Iron Nodules Cgr	SP 0940 38
	32.0	7						
	35.0							
S-8 35/37		5 7 11	1.6/2.0		M Dense	orange yellow	Mgr SAND Tr Iron Nodules (.20")	SP 0947 30
	37.0	10				yellow orange	Sandy Silt	SM
	40.0							
S-9 40/42		9 12 16	1.3/8.0		Dense	Gray	Fgr SAND	SP 0955 50 *
	42.0	20						
	45.0							
S-10 45/47		13 22 21	1.3/6.0		V Dense	D Gray	Mgr SAND	SP 1007 "Coal" Odor 30
	47.0	22						
	50.0							

REMARKS _____

BORING DSB 13

* See Legend on Back

PAGE 2 OF 3

HALLIBURTON NUS

SAMPLE NO. & TYPE	DEPTH (ft) OR RUN NO.	BLOWE 6" OR ROD (in)	SAMPLE RECOVERY - SAMPLE LENGTH	LITHOLOGY CHANGE (Depth ft.)	MATERIAL DESCRIPTION*			ROCK BR. OR USES	REMARKS		
					SOIL DENSITY, CONSISTENCY OR ROCK HARDNESS	COLOR	MATERIAL CLASSIFICATION.		Time	Head #/IN	
S-11 SD/SZ		14 18 19	1.3 / 2.0		Dense	Brown to gray	F. Mg SAND Mg SAND	SP	1014	'Loai' odor	28
	55.0										
S-12 S/S7		14 18 20 20	1.3 / 2.0		Dense	Brown gray	Mg SAND	SA	1028	odor (amine like)	52
	55.7									Damp	
	60.0										
S-13 SD/SZ		10 11 9 12	1.6 / 2.0	8/31 = 61'	M Dense	Tan	Mg SAND	SP	1028	odor Saturated	-
	62.0			TO 62'							
							HSA 60'				
							2nd				
							Samples:				
							DSB13 - 00/02				
							DSB13 - 40/42				
							DSB13 - 55/57				
							said to Face Lab				
							for TEL VOC				

PAGE 3 OF 3

BORING LOG

HALLIBURTON NUS

PROJECT: NWIRP Bethpage BORING NO.: DSB14
 PROJECT NO.: 5253 DATE: 9-1-95 DRILLER: Steve Wolf
 ELEVATION: _____ FIELD GEOLOGIST: Tim Evans
 WATER LEVEL DATA: _____
 (Date, Time & Conditions) rain 8-31-95 late PM

SAMPLE NO. & TYPE	DEPTH (FLI OR RUN NO.)	BLOWS 6" OR ROD (1-1)	SAMPLE RECOVERY .SAMPLE LENGTH	LITHOLOGY (CHANGE (1000 ft.))	MATERIAL DESCRIPTION*			ROCK BR. OR USES	REMARKS Time Head Jitter
					SOIL DENSITY CONSISTENCY OR ROCK HARDNESS	COLOR	MATERIAL CLASSIFICATION		
	1.0	7	1.5/8.0	0.0			concrete sand Tr saw	SP	
S-1 1/3	2.0	11			M Dense	Dark	Clayey sand	SC	0718 41 ppm
	3.0					Brn	Fine GRAVELLY SAND	SW	
	5.0								
S-2 5/7		5	1.0/2.0		Dense	yellow tan	GRAVELLY SAND	SW	0722 40 ppm *
	7.0	17							
	10.0								
S-3 10/12		8	1.1/2.0		Dense	yellow tan	GRAVELLY SAND	SW	0729 18
	12.0	15							
	15.0								
S-4 15/17		7	1.0/2.0		M Dense	yellow tan	Fine GRAVEL ? M-Gr SAND	SW	0734 4
	17.0	16							
	20.0								
S-5 20/22		11	0.10/2.0				- NO Recovery -		0740 -
	22.0	17							1-2" SC
		19							1-3" SC
	25.0								

REMARKS Mobile B-61 HSA Rig
4 1/4" ID Augers, 2" SS Down hole Hammer

BORING DSB14

* See Legend on Back

PAGE 1 OF 3

HALLIBURTON NUS

SAMPLE NO. & TYPE	DEPTH (ft.) OR RUN NO.	BLOWS 6" OR ROD (%)	SAMPLE RECOVERY - SAMPLE LENGTH	LITHOLOGY CHANGE (Depth, ft.)	MATERIAL DESCRIPTION*			ROCK BR. OR USCS	REMARKS	
					SOIL DENSITY CONSISTENCY OR ROCK HARDNESS	COLOR	MATERIAL CLASSIFICATION		Time	Head DOWN
S-6 5/27	26.0	9	1.7/2.0		M loose	Tan	Fine GRAVELLY M-gr SAND Tr Iron Nodules (<.20")	SW	0751	0 p.m.
	27.0									
	30.0									
S-7 5/31	32.0	11	1.4/2.0		M Dense	Tan → Brn	E-Mgr SAND Tr Fine Gravel Tr Iron / Rust	SW/ SP	0757	1
	35.0									
S-8 5/31	37.0	26	1.5/2.0		Dense	Tan Brn	Mgr SAND SAND Tr Rust & Gravel	SP SW	0806	1.8
	40.0									
S-9 5/42	42.0	27	1.6/2.0		Dense	Tan to Pink brn	Fgr SAND	SP	0813	2
	45.0									
S-10 5/47	47.0	18	1.3/2.0		Brn to tan		Mgr SAND Fgr SAND	SP SP	0820	1.8
	50.0			▽ 9/1						

REMARKS

BORING DSB 14

PAGE 2 OF 3

* See Legend on Back

APPENDIX B
SAMPLE LOG SHEETS



HALLIBURTON NUS
Environmental Corporation

SAMPLE LOG SHEET



SURFACE SOIL
SUBSURFACE SOIL
SEDIMENT



LAGOON/POND
OTHER

SAMPLERS SIGNATURE

GE 1 OF 1
[Signature]

SITE NAME NWIRP Bethpage

SITE NUMBER 5053

SAMPLE No.	SAMPLE METHOD	DEPTH (FT)	DATE	TIME	SAMPLED BY	CONCENTRATION (L/L) OR (M/M)	(G/100G) COMPOSITE	60 mL glass TEL VOC	ANALYSES								No. OF CONT TOTAL	SOIL DESCRIPTION
DSB 1φ - φφ/φ2	2"SS	0-2	8.30.95	1007	TSE	L	G	✓									1	Gravelly to Clayey Sand
DSB 1φ - 15/17	2"SS	15-17	8.30.95	1032	TSE	L	G	✓									1	Gravelly Sand / Sand Tr C
DSB 1φ - 6φ/62	2"SS	60-62	8.30.95	1140	TSE	L	G	✓									1	Sand
DSB 11 - φφ/φ2	2"SS	0-2	8.30.95	1347	TSE	L	G	✓									1	Silty Sand Tr Gravel
DSB 11 - 3φ/32	2"SS	30-32	8.30.95	1437	TSE	L	G	✓									1	Gravelly Sand / Sand
DSB 11 - 6φ/62	2"SS	60-62	8.30.95	1525	BE	L	G	✓									1	Silt & Sand
DSB 13 - φφ/φ2	2"SS	0-2	8.31.95	0903	TSE	L	G	✓									1	Sand Tr Gravel / Clayey S.
DSB 13 - 4φ/42	2"SS	40-42	8.31.95	0955	TSE	L	G	✓									1	Sand
DSB 13 - 55/57	2"SS	55-57	8.31.95	1023	TSE	L	G	✓									1	Sand
DSB 12 - φφ/φ2	2"SS	0-2	8.31.95	1235	TSE	L	G	✓									1	Silty Sand / Gravelly S.
DSB 12 - 4φ/42	2"SS	40-42	8.31.95	1330	TSE	L	G	✓									1	Sand
DSB 12 - 6φ/62	2"SS	60-62	8.31.95	1402	TSE	L	G	✓									1	Sand & Silt
DSB 14 - φ5/φ7	2"SS	5-7	9.1.95	0722	TSE	L	G	✓									1	SAND
DSB 14 - 4φ/42	2"SS	40-42	9.1.95	0813	BE	L	G	✓									1	Sand
DSB 14 - 5φ/52	2"SS	50-52	9.1.95	0824	TSE	L	G	✓									1	Sand

REMARKS: Shipped RDEX (AG # 5461991101)
(8/30 + 8/31) →
(9/1) AB# 8797930890

LAB: Pace, Inc.
Hampton, NH

Project Site Name: NW 12P Bethpage

Project No.: 5253

☐ Domestic Well Data

☒ Monitoring Well Data

☐ Other Well Type: _____

☐ QA Sample Type: _____

Sample ID No.: DGW28

Sample Location: Site 1

Sampled By: Tim Evans

C.O.C. No.: _____

Sampling Data								
Date: _____	pH	E.C.	Temp. (°C)	Turbidity	Color	TSD	TSD	TSD
Time: _____								
Method: _____								

	Purge Data
Date: <u>9-1-95</u>	
Method: _____	
Monitor Reading (ppm): <u>—</u>	
Well Casing Dia. & Material Type: <u>4" PVC</u>	
Total Well Depth (TD): <u>50.86</u>	
Static Water Level (WL): <u>—</u>	
TD-WL (ft.) = _____	
One Casing Volume: (gal/L) _____	
Start Purge (hrs.): _____	
End Purge (hrs.): _____	
Total Purge Time (min): _____	
Total Amount Purged (gal/L): _____	

[illegible]

Observations/Notes: Well Dry @ 1030 hrs No sample collected		
Circle if Applicable:		Signature(s):
MS/MSD	Duplicate ID No:	Tunstall

TBD: To Be Determined

APPENDIX C
CHAIN OF CUSTODY RECORDS



ENVIRONMENTAL LABORATORIES

SAMPLES FROM
NEW YORK SITE

YE. ✓ NO

241010

CHAIN-OF-CUSTODY RECORD
Analytical Request

Client Halliburton NUS
Address 661 Anderson Dr
Foster Plaza #7
Pittsburgh PA 15211
Phone (412) 921-7090

Report To: Mark Speranza

Pace Client No.

Bill To:

Pace Project Manager

P.O. # / Billing Reference

Pace Project No.

Project Name / No. CTO 213

*Requested Due Date:

Sampled By (PRINT) [Signature] 8.31.95
Sampler Signature TIMOTHY S EVANS Date Sampled

ITEM NO.	SAMPLE DESCRIPTION	TIME	MATRIX	PACE NO.	NO. OF CONTAINERS	PRESERVATIVES					ANALYSES REQUESTED	REMARKS
						UNPRESERVED	H ₂ SO ₄	HNO ₃	VOA			
1	DSB13 - 0φ/φ2	0903	Soil		1	✓					✓	APPENDIX C
2	DSB13 - 4φ/42	0955	Soil		1	✓					✓	
3	DSB13 - 55/57	1023	Soil		1	✓					✓	
4	DSB12 - 0φ/φ2	1235	Soil		1	✓					✓	
5	DSB12 - 4φ/42	1330	Soil		1	✓					✓	
6	DSB12 - 6φ/62	1402	Soil		1	✓					✓	
7												
8												

COOLER NOS.	BAILERS	SHIPMENT METHOD	ITEM NUMBER	RELINQUISHED BY AFFILIATION	ACCEPTED BY AFFILIATION	DATE	TIME
1				1-6 <u>[Signature]</u> / HUS			

Additional Comments Fedex AB# 5461991161

8.31.95 1600

2 of 2

SEE REVERSE SIDE FOR INSTRUCTIONS



YES ☒ NO ☐

CHAIN-OF-CUSTODY RECORD

Analytical Request

Report To: *[Signature]* *[Signature]*

Pace Client No. _____

Bill To: _____

Pace Project Manager

P.O. # / Billing Reference

Pace Project No. _____

Project Name / No. CTO 213

*Requested Due Date: _____

Client Halliburton NUS

Address 661 Anderson Dr
Foster Plaza #7
Pittsburgh PA 15220

Phone (412) 921-7090

Sampled By (PRINT): _____

Sampler Signature Timothy S Evans Date Sampled 8.30.95

Sampled By (PRINT):					NO. OF CONTAINERS		PRESERVATIVES				ANALYSES REQUEST			
Sampler Signature		Date Sampled					UNPRESERVED	H ₂ SO ₄	HNO ₃	VOA				
TIMOTHY S EVANS											TCL VOC			
TMS		8.30.95												
ITEM NO.	SAMPLE DESCRIPTION				TIME	MATRIX	PAGE NO.					REMARKS		
1	DSB 1φ - φφ/φ2				1007	Soil		1	✓					
2	DSB 1φ - 15/17				1032	Soil		1	✓					
3	DSB 1φ - 6φ/62				1140	Soil		1	✓					
4	DSB 11 - φφ/φ2				1347	Soil		1	✓					
5	DSB 11 - 3φ/32				1437	Soil		1	✓					
6	DSB 11 - 6φ/62				1525	Soil		1	✓					
7														
8														

COOLER NOS.	BAILERS	SHIPMENT METHOD		ITEM NUMBER	RELINQUISHED BY AFFILIATION	ACCEPTED BY AFFILIATION	DATE	TIME
		OUT DATE	RETURNED DATE					
1				1-6	Timothy Shaw/HWS			

Additional Comments FedEx AB# 3461991161

1-6 Timothy Shaw/Haus
8.31.95 1600

SEE REVERSE SIDE FOR INSTRUCTIONS



ENVIRONMENTAL LABORATORIES

SAMPLES FROM
NEW YORK SITE

YES ☒ NO ☐

2-1075

CHAIN-OF-CUSTODY RECORD
Analytical Request

Client Thalliburton NUS
Address 661 Anderson Dr
Foster Plaza #7
Pittsburgh PA 15011
Phone (412) 921-7090

Report To: Mark Speranza

Pace Client No. _____

Bill To: _____

Pace Project Manager _____

P.O. # / Billing Reference _____

Pace Project No. _____

Project Name / No. _____

*Requested Due Date: _____

Sampled By (PRINT): Timothy S Evans

Sampler Signature Timothy S Evans Date Sampled 9.1.95

ITEM NO.	SAMPLE DESCRIPTION	TIME	MATRIX	PACE NO.	NO. OF CONTAINERS	PRESERVATIVES					ANALYSES REQUESTED	REMARKS
						UNPRESERVED	H ₂ SO ₄	HNO ₃	VOA			
1	DSB 14 - Ø5/Ø7	0722	Soil		1	✓					✓	APPENDIX C
2	DSB 14 - 4Ø/42	0813	Soil		1	✓					✓	
3	DSB 14 - 5Ø/52	0849	Soil		1	✓					✓	
4												
5												
6												
7												
8												

COOLER NOS.	BAILERS	SHIPMENT METHOD		ITEM NUMBER	RELINQUISHED BY AFFILIATION	ACCEPTED BY AFFILIATION	DATE	TIME
		OUT DATE	RETURNED DATE					
1				1-3	<u>Timothy S Evans</u> / HNU			
Additional Comments <u>FedEx AB # 8797930890</u>					<u>19.1.95</u> <u>1500</u>			

SEE REVERSE SIDE FOR INSTRUCTIONS

APPENDIX D
DAILY ACTIVITIES RECORD

Halliburton NUS
CORPORATION

[illegible]

COMMENTS	<u>HSA</u>	<u>2"</u>
DSB 10	60 ps	14
DSB 11	60	14
	<u>120</u>	<u>28</u>

APPROVED BY:  120

HNUS FIELD REPRESENTATIVE

DRILLER Steve Wolf
DATE 8/30/95

Halliburton NUS
CORPORATION

[illegible]

COMMENTS	HSA	2" SS
DSB 13	60'	13
DSB 12	60'	13
	<u>120</u>	<u>26</u>

DRILLER Steve Wolf
DATE 8/31/95

CF BRAUN ENGINEERING CORPORATION

[illegible]

COMMENTS	HSA	2" SS
DSB 14	60	13

DATE _____

Aquifer Drilling & Testing, Inc.

51-41 59th Place • Woodside • New York 11377

DAILY JOB REPORT

DATE 8/30/95 CLIENT Halliburton DRILLER S. Wolf HELPER Tom For
JOB LOCATION Grumman EQUIPMENT: DRILL B61 SUPPORT TRUCK Int Box
DESCRIPTION OF WORK

4 1/2 H.S.A. to 60' 14 Spoons to 64'

4 1/2 H.S.A. to 60' 14 Spoons to 64'

ITEMIZATION:

Soil Borings: HSA / Mud / Air
(Circle One)

Well Construction: HSA / MUD / AIR / DRIVE / WASH (Circle One)

BORING	DEPTH	TOTAL #SPOONS	WELL	SIZE (DIA)	RISER (FT)	SCREEN (FT)	TOTAL DEPTH	SAND (LBS)	PLTS(P) CHIPS(C)	CEMENT (LBS)	BENTONITE (LBS)	MANHOLE (M) STANDPIPE(P)
No. 1	<u>60</u>	<u>14</u>	No.									
No. 2	<u>60</u>	<u>14</u>	No.									
No.			No.									
No.			No.									
No.			No.									
No.			No.									

Surface Casing (Ft) _____

Steam Cleaning (Hrs) 1

Drum No. _____

Nx Coring (Ft) _____

Well Develop (Hrs.) _____

Drum Soils (Hrs) _____

Drive Wash w/Tripod (Hrs) _____

Standby (Hrs) 1 (9-10 am)

Stage Drums (Hrs) _____

Concrete Coring (Ft) _____

PERSONNEL	SHOP/HOME	ONSITE	LUNCH	OFFSITE	SHOP/HOME	TOTAL HOURS
<u>Steve</u>	<u>7</u>	<u>8:30</u>		<u>4:30</u>	<u>5:30</u>	<u>10 1/2</u>
<u>Tom For</u>						

Approved _____

Date 8.30.95

Print Name: _____

CLIENT REPRESENTATIVE

Client Representative to sign Onsite Lunch & Offsite times.

NOTE: Actual onsite lunch is to be recorded.

WHITE (Client)

YELLOW (Accounting)

PINK (Admin)

Aquifer Drilling & Testing, Inc.

51-41 59th Place • Woodside • New York 11377

DAILY JOB REPORT

DATE 8/31/95 CLIENT Halliburton DRILLER Steve Wolf HELPER Tom Focina
JOB LOCATION Common Bethany EQUIPMENT: DRILL B-61 SUPPORT TRUCK Box
DESCRIPTION OF WORK _____

4 1/4 H.S.A. to 60' 13 Spoons to 62'
4 1/4 H.S.A. to 60' 13 Spoons to 62'

ITEMIZATION:Soil Borings: HSA / Mud / Air
(Circle One)

Well Construction: HSA / MUD / AIR / DRIVE / WASH (Circle One)

BORING	DEPTH	TOTAL #SPOONS	WELL	SIZE (DIA)	RISER (FT)	SCREEN (FT)	TOTAL DEPTH	SAND (LBS)	PLTS(P) CHIPS(C)	CEMENT (LBS)	BENTONITE (LBS)	MANHOLE (M) STANDPIPE(P)
No. <u>1</u>	<u>60</u>	<u>13</u>	No. _____	_____	_____	_____	_____	_____	_____	_____	_____	_____
No. <u>2</u>	<u>60</u>	<u>13</u>	No. _____	_____	_____	_____	_____	_____	_____	_____	_____	_____
No. _____	_____	_____	No. _____	_____	_____	_____	_____	_____	_____	_____	_____	_____
No. _____	_____	_____	No. _____	_____	_____	_____	_____	_____	_____	_____	_____	_____
No. _____	_____	_____	No. _____	_____	_____	_____	_____	_____	_____	_____	_____	_____
No. _____	_____	_____	No. _____	_____	_____	_____	_____	_____	_____	_____	_____	_____

Surface Casing (Ft) _____

Steam Cleaning (Hrs) 1

Drum No. _____

Nx Coring (Ft) _____

Well Develop (Hrs.) _____

Drum Soils (Hrs) _____

Drive Wash w/Tripod (Hrs) _____

Standby (Hrs) _____

Stage Drums (Hrs) _____

Concrete Coring (Ft) 1

PERSONNEL	SHOP/HOME	ONSITE	LUNCH	OFFSITE	SHOP/HOME	TOTAL HOURS
-----------	-----------	--------	-------	---------	-----------	-------------

<u>Steve</u>	<u>7</u>	<u>8:15</u>		<u>3:30</u>		
<u>Tom Focina</u>	<u>7</u>					

Approved _____

CLIENT REPRESENTATIVE

Print Name: Tim EvansDate 8-31-95Client Representative to sign Onsite Lunch & Offsite times.

NOTE: Actual onsite lunch is to be recorded.

WHITE (Client)

YELLOW (Accounting)

PINK (Admin)

Aquifer Drilling & Testing, Inc.

51-41 59th Place • Woodside • New York 11377

DAILY JOB REPORT

DATE 9/1/95 CLIENT Halliburton DRILLER S Wolf HELPER Tom Farcin
JOB LOCATION Grumman EQUIPMENT: DRILL B61 SUPPORT TRUCK Box
DESCRIPTION OF WORK _____

4 1/4 H.S.A. to 60' 13 spoons to 62'
Steam Cleaned
Back filled All Holes

ITEMIZATION:

Soil Borings: HSA / Mud / Air
(Circle One)

Well Construction: HSA / MUD / AIR / DRIVE / WASH (Circle One)

BORING	DEPTH	TOTAL #SPOONS	WELL	SIZE (DIA)	RISER (FT)	SCREEN (FT)	TOTAL DEPTH	SAND (LBS)	PLTS(P) CHIPS(C)	CEMENT (LBS)	BENTONITE (LBS)	MANHOLE (M) STANDPIPE(P)
No. <u>1</u>	<u>60</u>	<u>13</u>	No. _____	_____	_____	_____	_____	_____	_____	_____	_____	_____
No. _____	_____	_____	No. _____	_____	_____	_____	_____	_____	_____	_____	_____	_____
No. _____	_____	_____	No. _____	_____	_____	_____	_____	_____	_____	_____	_____	_____
No. _____	_____	_____	No. _____	_____	_____	_____	_____	_____	_____	_____	_____	_____
No. _____	_____	_____	No. _____	_____	_____	_____	_____	_____	_____	_____	_____	_____
No. _____	_____	_____	No. _____	_____	_____	_____	_____	_____	_____	_____	_____	_____

Surface Casing (Ft) _____

Steam Cleaning (Hrs) 1

Drum No. _____

Nx Coring (Ft) _____

Well Develop (Hrs.) _____

Drum Soils (Hrs) _____

Drive Wash w/Tripod (Hrs) _____

Standby (Hrs) _____

Stage Drums (Hrs) _____

Concrete Coring (Ft) _____

PERSONNEL	SHOP/HOME	ONSITE	LUNCH	OFFSITE	SHOP/HOME	TOTAL HOURS
<u>Steve</u>	<u>6</u>	<u>7</u>		<u>11</u>		
<u>Tom Far</u>	<u>6:15</u>					

Approved _____

CLIENT REPRESENTATIVE

Date _____

Print Name: _____

Client Representative to sign Onsite Lunch & Offsite times.

NOTE: Actual onsite lunch is to be recorded.

WHITE (Client)

YELLOW (Accounting)

PINK (Admin)

APPENDIX E
CHEMICAL ANALYSIS RESULTS

September 14, 1995

Halliburton NUS Corporation
Mr. Mark Speranza
661 Andersen Drive
Pittsburgh, PA 15220

SAMPLE DELIVERY GROUP NARRATIVE

Project: NWIRP Bethpage, CTO 0213
Laboratory: PACE New England, Inc. of Hampton, NH

Lab Numbers: 45205
Protocol: SW846 Methodologies with NEESA Level C package and LOTUS diskette.


Sample Receipt: Samples were received at PACE, Inc. on 9/1/95. Laboratory sample numbers were assigned for test parameters as listed on the sample table which follows this narrative. Sample shipments were checked for custody seal integrity and cooler temperature. Samples were checked for appropriate preservation and accuracy against the Chains-of-Custody provided. Other than the exceptions noted below, samples were received between 2-6° C and in good condition. In addition, Sample Receipt Condition Reports can be found with the Chains-of-Custody. No spike sample was submitted for analysis.


Shipment received 9/1/95 (45205): One cooler was received with one Chain-of-Custody form. The cooler was received without a temperature blank present. The samples were packed in ice. Custody seals were present and intact.

Volatile Organic Analysis: Samples were analyzed within a project specific holding time of 7 days from sampling as directed by Ms. Kelly Johnson. The method 8240 blank "BC090595A1" "BC090695A1" and "BV1123" contained low levels of methylene chloride. The sample results for this analyte should be used with due consideration.

Statement of Compliancy and Data Authorization

I certify that this data package is in compliance with the terms and conditions of the contract, both technically and for completeness, for other than the conditions detailed above. Release of the data contained in this hardcopy data package and in the computer-readable data submitted on diskette has been authorized by the Laboratory Manager or his designee, as verified by the following signature.


Richard Wellman, Operations Manager
PACE Incorporated, New England-New Hampshire


September 14, 1995



SAMPLE RECEIPT CONDITION REPORT

Tel. (603) 926-7777
FAX (603) 926-7939PAGE _____ of _____
COOLER _____ of _____
COC# _____
SDG# _____
CASE# _____CLIENT H NUSDATE/TIME RECEIVED 9/1/95 0930LIMS ENTRY BY SBDELIVERED BY felxTRANSCRIPTION REVIEW BY SBRECEIVED BY SBLIMS REVIEW BY/PM SB

	NA	YES	EXCEPTION	COMMENT	RESOLUTION			
1. CUSTODY SEALS PRESENT/INTACT	☐	☒	☐					
2. CHAIN OF CUSTODY PRESENT IN THIS COOLER	☐	☒	☐					
3. CHAIN OF CUSTODY SIGNED	☐	☒	☐					
4. CHAIN OF CUSTODY MATCHES SAMPLES	☐	☒	☐					
5. SAMPLES RECEIVED AT 2° - 6° C	☐	☐	☒	No temp h/c. ked well				
Ice/Ice Packs Present? <u>Y</u> or N								
6. VOLATILES FREE OF HEAD SPACE	☒	☐	☐	SPIS. ok				
7. TRIP BLANK PRESENT IN THIS COOLER	☐	☐	☒	none				
8. PROPER SAMPLE CONTAINERS AND VOLUME	☐	☒	☐					
9. SAMPLES WITHIN HOLD TIME	☐	☒	☐					
10. SAMPLES PROPERLY PRESERVED	☐	☒	☐					
11. ANALYTICAL PROGRAMS (circle one)	<u>COMMERCIAL</u>	CLP	EPA-CLP	NYASP	NJ ISRA	<u>NEESA</u>	AFCEE	Other
12. NUMBER OF PACE FILTRATIONS:								
13. CORRECTIVE ACTIONS REPORT #								

44361

Log-in Notes:

SW246/NEESA-C

14 day h/c

7 day H.I.

NUS Disk

000002

CLIENT AUTHORIZATION SIGNATURE _____ DATE _____

SAMPLE TABLE

CLIENT ID.	MATRIX	PAGE #	PARAMETERS
DSB10-00/02	SOLID	45205-001	GC/MS VOA
DSB10-15/17	SOLID	45205-002	GC/MS VOA
DSB10-60/62	SOLID	45205-003	GC/MS VOA
DSB11-00/02	SOLID	45205-004	GC/MS VOA
DSB11-30/32	SOLID	45205-005	GC/MS VOA
DSB11-60/62	SOLID	45205-006	GC/MS VOA
DSB13-00/02	SOLID	45205-007	GC/MS VOA
DSB13-40/42	SOLID	45205-008	GC/MS VOA
DSB13-55/57	SOLID	45205-009	GC/MS VOA
DSB12-00/02	SOLID	45205-010	GC/MS VOA
DSB12-40/42	SOLID	45205-011	GC/MS VOA
DSB12-60/62	SOLID	45205-012	GC/MS VOA

~~SDG:~~ 45205

TABLE 1: MANUAL INTEGRATIONS PERFORMED

[illegible]

Manual integrations were performed as required to correct faulty integrations made by the automated software. The manual integrations began and ended at the point where the peak intersected the baseline (unless otherwise indicated), in order that the entire peak and only the peak would be integrated. Hardcopies of the manually-integrated peaks have been provided with the data.

Analyst Signature, PACE Incorporated
PACE Incorporated

000004

9/8/95
Date

ref: PACE SOP ALL-Q-013-A c:\document\manint.frm

Laboratory number: 45205-001
Sample Designation: DSB10-00/02
Date Analyzed: 09/05/95
Matrix: SOLID

Instrument File Name: >C1066

Results are expressed on a dry (103 degrees C) basis.
Moisture content was 11 % , elevating the reporting limits
by a factor of 1.13 .

VOLATILE ORGANICS	CONCENTRATION (ug/Kg)	REPORTING LIMIT (ug/Kg)
Chloromethane	BDL	11
Bromomethane	BDL	11
Vinyl chloride	BDL	11
Chloroethane	BDL	6
Methylene chloride	7 JB	11
Acetone	BDL	28
Carbon disulfide	BDL	6
Tetrahydrofuran	BDL	28
Trichlorofluoromethane	BDL	6
1,1-Dichloroethene	BDL	6
1,1-Dichloroethane	BDL	6
1,2-Dichloroethene (total)	BDL	6
Chloroform	BDL	6
1,2-Dichloroethane	BDL	6
2-Butanone	BDL	28
1,1,1-Trichloroethane	BDL	6
Carbon Tetrachloride	BDL	6
Vinyl acetate	BDL	11
Bromodichloromethane	BDL	6
1,2-Dichloropropane	BDL	6
cis-1,3-Dichloropropene	BDL	6
trans-1,3-Dichloropropene	BDL	6
Trichloroethene	26	6
Dibromochloromethane	BDL	6
1,1,2-Trichloroethane	BDL	6
Benzene	BDL	6
2-Chloroethyl vinyl ether	BDL	6
Bromoform	BDL	6
4-Methyl-2-Pentanone	BDL	28
2-Hexanone	BDL	28
Tetrachloroethene	BDL	6
1,1,2,2-Tetrachloroethane	BDL	6
Toluene	BDL	6
Chlorobenzene	BDL	6
Ethylbenzene	BDL	6
Styrene	BDL	6
Xylene (total)	BDL	6

METHOD REFERENCE: EPA SW 846, 3rd Edition
METHOD 8240

BDL = Below reporting limit

J = Probable presence below listed detection limit



000005

Laboratory number: 45205-002
Sample Designation: DSB10-15/17
Date Analyzed: 09/05/95
Matrix: SOLID

Instrument File Name: >C1067

Results are expressed on a dry (103 degrees C) basis.
Moisture content was 9 % , elevating the reporting limits
by a factor of 1.1 .

VOLATILE ORGANICS	CONCENTRATION (ug/Kg)	REPORTING LIMIT (ug/Kg)
Chloromethane	BDL	10
Bromomethane	BDL	10
Vinyl chloride	BDL	10
Chloroethane	BDL	5
Methylene chloride	5 JB	10
Acetone	BDL	26
Carbon disulfide	BDL	5
Tetrahydrofuran	BDL	26
Trichlorofluoromethane	BDL	5
1,1-Dichloroethene	BDL	5
1,1-Dichloroethane	BDL	5
1,2-Dichloroethene (total)	BDL	5
Chloroform	BDL	5
1,2-Dichloroethane	BDL	5
2-Butanone	BDL	26
1,1,1-Trichloroethane	BDL	5
Carbon Tetrachloride	BDL	5
Vinyl acetate	BDL	10
Bromodichloromethane	BDL	5
1,2-Dichloropropane	BDL	5
cis-1,3-Dichloropropene	BDL	5
trans-1,3-Dichloropropene	BDL	5
Trichloroethene	BDL	5
Dibromochloromethane	BDL	5
1,1,2-Trichloroethane	BDL	5
Benzene	BDL	5
2-Chloroethyl vinyl ether	BDL	5
Bromoform	BDL	5
4-Methyl-2-Pentanone	BDL	26
2-Hexanone	BDL	26
Tetrachloroethene	BDL	5
1,1,2,2-Tetrachloroethane	BDL	5
Toluene	BDL	5
Chlorobenzene	BDL	5
Ethylbenzene	BDL	5
Styrene	BDL	5
Xylene (total)	BDL	5

METHOD REFERENCE: EPA SW 846, 3rd Edition
METHOD 8240

BDL = Below reporting limit
J = Probable presence below listed detection limit



000006

Laboratory number: 45205-003
Sample Designation: DSB10-60/62
Date Analyzed: 09/05/95
Matrix: SOLID

Instrument File Name: >C1068

Results are expressed on a dry (103 degrees C) basis.
Moisture content was 5 % , elevating the reporting limits
by a factor of 1.05 .

VOLATILE ORGANICS	CONCENTRATION (ug/Kg)	REPORTING LIMIT (ug/Kg)
Chloromethane	BDL	11
Bromomethane	BDL	11
Vinyl chloride	BDL	11
Chloroethane	BDL	5
Methylene chloride	6 JB	11
Acetone	BDL	26
Carbon disulfide	BDL	5
Tetrahydrofuran	BDL	26
Trichlorofluoromethane	BDL	5
1,1-Dichloroethene	BDL	5
1,1-Dichloroethane	BDL	5
1,2-Dichloroethene (total)	BDL	5
Chloroform	BDL	5
1,2-Dichloroethane	BDL	5
2-Butanone	BDL	26
1,1,1-Trichloroethane	BDL	5
Carbon Tetrachloride	BDL	5
Vinyl acetate	BDL	11
Bromodichloromethane	BDL	5
1,2-Dichloropropane	BDL	5
cis-1,3-Dichloropropene	BDL	5
trans-1,3-Dichloropropene	BDL	5
Trichloroethene	BDL	5
Dibromochloromethane	BDL	5
1,1,2-Trichloroethane	BDL	5
Benzene	BDL	5
2-Chloroethyl vinyl ether	BDL	5
Bromoform	BDL	5
4-Methyl-2-Pentanone	BDL	26
2-Hexanone	BDL	26
Tetrachloroethene	BDL	5
1,1,2,2-Tetrachloroethane	BDL	5
Toluene	BDL	5
Chlorobenzene	BDL	5
Ethylbenzene	BDL	5
Styrene	BDL	5
Xylene (total)	BDL	5

METHOD REFERENCE: EPA SW 846, 3rd Edition
METHOD 8240

BDL = Below reporting limit

J = Probable presence below listed detection limit



000007

Laboratory number: 45205-004
Sample Designation: DSB11-00/02
Date Analyzed: 09/06/95
Matrix: SOLID

Instrument File Name: >C1083

Results are expressed on a dry (103 degrees C) basis.
Moisture content was 12 % , elevating the reporting limits
by a factor of 1.13 .

VOLATILE ORGANICS	CONCENTRATION (ug/Kg)	REPORTING LIMIT (ug/Kg)
Chloromethane	BDL	14
Bromomethane	BDL	14
Vinyl chloride	BDL	14
Chloroethane	BDL	7
Methylene chloride	BDL	14
Acetone	BDL	35
Carbon disulfide	BDL	7
Tetrahydrofuran	BDL	35
Trichlorofluoromethane	BDL	7
1,1-Dichloroethene	BDL	7
1,1-Dichloroethane	BDL	7
1,2-Dichloroethene (total)	BDL	7
Chloroform	BDL	7
1,2-Dichloroethane	BDL	7
2-Butanone	BDL	35
1,1,1-Trichloroethane	BDL	7
Carbon Tetrachloride	BDL	7
Vinyl acetate	BDL	14
Bromodichloromethane	BDL	7
1,2-Dichloropropane	BDL	7
cis-1,3-Dichloropropene	BDL	7
trans-1,3-Dichloropropene	BDL	7
Trichloroethene	BDL	7
Dibromochloromethane	BDL	7
1,1,2-Trichloroethane	BDL	7
Benzene	BDL	7
2-Chloroethyl vinyl ether	BDL	7
Bromoform	BDL	7
4-Methyl-2-Pentanone	BDL	35
2-Hexanone	BDL	35
Tetrachloroethene	62	7
1,1,2,2-Tetrachloroethane	BDL	7
Toluene	BDL	7
Chlorobenzene	BDL	7
Ethylbenzene	BDL	7
Styrene	BDL	7
Xylene (total)	BDL	7

METHOD REFERENCE: EPA SW 846, 3rd Edition
METHOD 8240

BDL = Below reporting limit

J = Probable presence below listed detection limit



000008

Laboratory number: 45205-004DL
Sample Designation: DSB11-00/02
Date Analyzed: 09/05/95
Matrix: SOLID

Instrument File Name: >C1069

Results are expressed on a dry (103 degrees C) basis.
Moisture content was 12 % , elevating the reporting limits
by a factor of 1.13 .

VOLATILE ORGANICS	CONCENTRATION (ug/Kg)	REPORTING LIMIT (ug/Kg)
Chloromethane	BDL	52
Bromomethane	BDL	52
Vinyl chloride	BDL	52
Chloroethane	BDL	26
Methylene chloride	31 J B	52
Acetone	BDL	130
Carbon disulfide	BDL	26
Tetrahydrofuran	BDL	130
Trichlorofluoromethane	BDL	26
1,1-Dichloroethene	BDL	26
1,1-Dichloroethane	BDL	26
1,2-Dichloroethene (total)	BDL	26
Chloroform	BDL	26
1,2-Dichloroethane	BDL	26
2-Butanone	BDL	130
1,1,1-Trichloroethane	BDL	26
Carbon Tetrachloride	BDL	26
Vinyl acetate	BDL	52
Bromodichloromethane	BDL	26
1,2-Dichloropropane	BDL	26
cis-1,3-Dichloropropene	BDL	26
trans-1,3-Dichloropropene	BDL	26
Trichloroethene	BDL	26
Dibromochloromethane	BDL	26
1,1,2-Trichloroethane	BDL	26
Benzene	BDL	26
2-Chloroethyl vinyl ether	BDL	26
Bromoform	BDL	26
4-Methyl-2-Pentanone	BDL	130
2-Hexanone	BDL	130
Tetrachloroethene	190	26
1,1,2,2-Tetrachloroethane	BDL	26
Toluene	BDL	26
Chlorobenzene	BDL	26
Ethylbenzene	BDL	26
Styrene	BDL	26
Xylene (total)	BDL	26

METHOD REFERENCE: EPA SW 846, 3rd Edition
METHOD 8240

BDL = Below reporting limit

J = Probable presence below listed detection limit



000009

Laboratory number: 45205-005
Sample Designation: DSB11-30/32
Date Analyzed: 09/06/95
Matrix: SOLID

Instrument File Name: >C1084

Results are expressed on a dry (103 degrees C) basis.
Moisture content was 3 % , elevating the reporting limits
by a factor of 1.03 .

VOLATILE ORGANICS	CONCENTRATION (ug/Kg)	REPORTING LIMIT (ug/Kg)
Chloromethane	BDL	10
Bromomethane	BDL	10
Vinyl chloride	BDL	10
Chloroethane	BDL	5
Methylene chloride	BDL	10
Acetone	BDL	25
Carbon disulfide	BDL	5
Tetrahydrofuran	BDL	25
Trichlorofluoromethane	BDL	5
1,1-Dichloroethene	BDL	5
1,1-Dichloroethane	BDL	5
1,2-Dichloroethene (total)	BDL	5
Chloroform	BDL	5
1,2-Dichloroethane	BDL	5
2-Butanone	BDL	25
1,1,1-Trichloroethane	BDL	5
Carbon Tetrachloride	BDL	5
Vinyl acetate	BDL	10
Bromodichloromethane	BDL	5
1,2-Dichloropropane	BDL	5
cis-1,3-Dichloropropene	BDL	5
trans-1,3-Dichloropropene	BDL	5
Trichloroethene	BDL	5
Dibromochloromethane	BDL	5
1,1,2-Trichloroethane	BDL	5
Benzene	BDL	5
2-Chloroethyl vinyl ether	BDL	5
Bromoform	BDL	5
4-Methyl-2-Pentanone	BDL	25
2-Hexanone	BDL	25
Tetrachloroethene	BDL	5
1,1,2,2-Tetrachloroethane	BDL	5
Toluene	BDL	5
Chlorobenzene	BDL	5
Ethylbenzene	BDL	5
Styrene	BDL	5
Xylene (total)	BDL	5

METHOD REFERENCE: EPA SW 846, 3rd Edition
METHOD 8240

BDL = Below reporting limit
J = Probable presence below listed detection limit



000010

Laboratory number: 45205-006
Sample Designation: DSB11-60/62
Date Analyzed: 09/06/95
Matrix: SOLID

Instrument File Name: >C1085

Results are expressed on a dry (103 degrees C) basis.
Moisture content was 10 % , elevating the reporting limits
by a factor of 1.11 .

VOLATILE ORGANICS	CONCENTRATION (ug/Kg)	REPORTING LIMIT (ug/Kg)
Chloromethane	BDL	11
Bromomethane	BDL	11
Vinyl chloride	BDL	11
Chloroethane	BDL	5
Methylene chloride	BDL	11
Acetone	BDL	27
Carbon disulfide	BDL	5
Tetrahydrofuran	BDL	27
Trichlorofluoromethane	BDL	5
1,1-Dichloroethene	BDL	5
1,1-Dichloroethane	BDL	5
1,2-Dichloroethene (total)	BDL	5
Chloroform	BDL	5
1,2-Dichloroethane	BDL	5
2-Butanone	BDL	27
1,1,1-Trichloroethane	BDL	5
Carbon Tetrachloride	BDL	5
Vinyl acetate	BDL	11
Bromodichloromethane	BDL	5
1,2-Dichloropropane	BDL	5
cis-1,3-Dichloropropene	BDL	5
trans-1,3-Dichloropropene	BDL	5
Trichloroethene	BDL	5
Dibromochloromethane	BDL	5
1,1,2-Trichloroethane	BDL	5
Benzene	BDL	5
2-Chloroethyl vinyl ether	BDL	5
Bromoform	BDL	5
4-Methyl-2-Pentanone	BDL	27
2-Hexanone	BDL	27
Tetrachloroethene	BDL	5
1,1,2,2-Tetrachloroethane	BDL	5
Toluene	BDL	5
Chlorobenzene	BDL	5
Ethylbenzene	BDL	5
Styrene	BDL	5
Xylene (total)	BDL	5

METHOD REFERENCE: EPA SW 846, 3rd Edition
METHOD 8240

BDL = Below reporting limit



000011

Laboratory number: 45205-010
Sample Designation: DSB12-00/02
Date Analyzed: 09/06/95
Matrix: SOLID

Instrument File Name: >C1088

Results are expressed on a dry (103 degrees C) basis.
Moisture content was 12 % , elevating the reporting limits
by a factor of 1.13 .

VOLATILE ORGANICS	CONCENTRATION (ug/Kg)	REPORTING LIMIT (ug/Kg)
Chloromethane	BDL	11
Bromomethane	BDL	11
Vinyl chloride	BDL	11
Chloroethane	BDL	6
Methylene chloride	BDL	11
Acetone	BDL	28
Carbon disulfide	BDL	6
Tetrahydrofuran	BDL	28
Trichlorofluoromethane	BDL	6
1,1-Dichloroethene	BDL	6
1,1-Dichloroethane	BDL	6
1,2-Dichloroethene (total)	BDL	6
Chloroform	BDL	6
1,2-Dichloroethane	BDL	6
2-Butanone	BDL	28
1,1,1-Trichloroethane	BDL	6
Carbon Tetrachloride	BDL	6
Vinyl acetate	BDL	11
Bromodichloromethane	BDL	6
1,2-Dichloropropane	BDL	6
cis-1,3-Dichloropropene	BDL	6
trans-1,3-Dichloropropene	BDL	6
Trichloroethene	BDL	6
Dibromochloromethane	BDL	6
1,1,2-Trichloroethane	BDL	6
Benzene	BDL	6
2-Chloroethyl vinyl ether	BDL	6
Bromoform	BDL	6
4-Methyl-2-Pentanone	BDL	28
2-Hexanone	BDL	28
Tetrachloroethene	27	6
1,1,2,2-Tetrachloroethane	BDL	6
Toluene	BDL	6
Chlorobenzene	BDL	6
Ethylbenzene	BDL	6
Styrene	BDL	6
Xylene (total)	BDL	6

METHOD REFERENCE: EPA SW 846, 3rd Edition
METHOD 8240

BDL = Below reporting limit

J = Probable presence below listed detection limit



000017

Laboratory number: 45205-007
 Sample Designation: DSB13-00/02
 Date Analyzed: 09/05/95
 Matrix: SOLID

Instrument File Name: >C1072

Results are expressed on a dry (103 degrees C) basis.
 Moisture content was 16 % , elevating the reporting limits
 by a factor of 1.19 .

VOLATILE ORGANICS	CONCENTRATION (ug/Kg)	REPORTING LIMIT (ug/Kg)
Chloromethane	BDL	50
Bromomethane	BDL	50
Vinyl chloride	BDL	50
Chloroethane	BDL	25
Methylene chloride	32 JB	50
Acetone	BDL	120
Carbon disulfide	BDL	25
Tetrahydrofuran	BDL	120
Trichlorofluoromethane	BDL	25
1,1-Dichloroethene	BDL	25
1,1-Dichloroethane	BDL	25
1,2-Dichloroethene (total)	BDL	25
Chloroform	BDL	25
1,2-Dichloroethane	BDL	25
2-Butanone	BDL	120
1,1,1-Trichloroethane	BDL	25
Carbon Tetrachloride	BDL	25
Vinyl acetate	BDL	50
Bromodichloromethane	BDL	25
1,2-Dichloropropane	BDL	25
cis-1,3-Dichloropropene	BDL	25
trans-1,3-Dichloropropene	BDL	25
Trichloroethene	44	25
Dibromochloromethane	BDL	25
1,1,2-Trichloroethane	BDL	25
Benzene	BDL	25
2-Chloroethyl vinyl ether	BDL	25
Bromoform	BDL	25
4-Methyl-2-Pentanone	BDL	120
2-Hexanone	BDL	120
Tetrachloroethene	490	25
1,1,2,2-Tetrachloroethane	BDL	25
Toluene	BDL	25
Chlorobenzene	BDL	25
Ethylbenzene	BDL	25
Styrene	BDL	25
Xylene (total)	BDL	25

METHOD REFERENCE: EPA SW 846, 3rd Edition
 METHOD 8240

BDL = Below reporting limit

J = Probable presence below listed detection limit

000012



Laboratory number: 45205-008
Sample Designation: DSB13-40/42
Date Analyzed: 09/05/95
Matrix: SOLID

Instrument File Name: >C1073

Results are expressed on a dry (103 degrees C) basis.
Moisture content was 9 % , elevating the reporting limits
by a factor of 1.09 .

VOLATILE ORGANICS	CONCENTRATION (ug/Kg)	REPORTING LIMIT (ug/Kg)
Chloromethane	BDL	46
Bromomethane	BDL	46
Vinyl chloride	BDL	46
Chloroethane	BDL	23
Methylene chloride	23 JB	46
Acetone	BDL	110
Carbon disulfide	BDL	23
Tetrahydrofuran	BDL	110
Trichlorofluoromethane	BDL	23
1,1-Dichloroethene	BDL	23
1,1-Dichloroethane	BDL	23
1,2-Dichloroethene (total)	BDL	23
Chloroform	BDL	23
1,2-Dichloroethane	BDL	23
2-Butanone	BDL	110
1,1,1-Trichloroethane	BDL	23
Carbon Tetrachloride	BDL	23
Vinyl acetate	BDL	46
Bromodichloromethane	BDL	23
1,2-Dichloropropane	BDL	23
cis-1,3-Dichloropropene	BDL	23
trans-1,3-Dichloropropene	BDL	23
Trichloroethene	BDL	23
Dibromochloromethane	BDL	23
1,1,2-Trichloroethane	BDL	23
Benzene	BDL	23
2-Chloroethyl vinyl ether	BDL	23
Bromoform	BDL	23
4-Methyl-2-Pentanone	BDL	110
2-Hexanone	BDL	110
Tetrachloroethene	44	23
1,1,2,2-Tetrachloroethane	BDL	23
Toluene	BDL	23
Chlorobenzene	BDL	23
Ethylbenzene	BDL	23
Styrene	BDL	23
Xylene (total)	BDL	23

METHOD REFERENCE: EPA SW 846, 3rd Edition
METHOD 8240

BDL = Below reporting limit
J = Probable presence below listed detection limit



000013

Laboratory number: 45205-011
Sample Designation: DSB12-40/42
Date Analyzed: 09/06/95
Matrix: SOLID

Instrument File Name: >C1086

Results are expressed on a dry (103 degrees C) basis.
Moisture content was 13 % , elevating the reporting limits
by a factor of 1.14 .

VOLATILE ORGANICS	CONCENTRATION (ug/Kg)	REPORTING LIMIT (ug/Kg)
Chloromethane	BDL	11
Bromomethane	BDL	11
Vinyl chloride	BDL	11
Chloroethane	BDL	6
Methylene chloride	BDL	11
Acetone	BDL	28
Carbon disulfide	BDL	6
Tetrahydrofuran	BDL	28
Trichlorofluoromethane	BDL	6
1,1-Dichloroethene	BDL	6
1,1-Dichloroethane	BDL	6
1,2-Dichloroethene (total)	BDL	6
Chloroform	BDL	6
1,2-Dichloroethane	BDL	6
2-Butanone	BDL	28
1,1,1-Trichloroethane	BDL	6
Carbon Tetrachloride	BDL	6
Vinyl acetate	BDL	11
Bromodichloromethane	BDL	6
1,2-Dichloropropane	BDL	6
cis-1,3-Dichloropropene	BDL	6
trans-1,3-Dichloropropene	BDL	6
Trichloroethene	BDL	6
Dibromochloromethane	BDL	6
1,1,2-Trichloroethane	BDL	6
Benzene	BDL	6
2-Chloroethyl vinyl ether	BDL	6
Bromoform	BDL	6
4-Methyl-2-Pentanone	BDL	28
2-Hexanone	BDL	28
Tetrachloroethene	BDL	6
1,1,2,2-Tetrachloroethane	BDL	6
Toluene	BDL	6
Chlorobenzene	BDL	6
Ethylbenzene	BDL	6
Styrene	BDL	6
Xylene (total)	BDL	6

METHOD REFERENCE: EPA SW 846, 3rd Edition
METHOD 8240

BDL = Below reporting limit
J = Probable presence below listed detection limit



000016

Laboratory number: 45205-012
Sample Designation: DSB12-60/62
Date Analyzed: 09/06/95
Matrix: SOLID

Instrument File Name: >C1087

Results are expressed on a dry (103 degrees C) basis.
Moisture content was 13 % , elevating the reporting limits
by a factor of 1.14 .

VOLATILE ORGANICS	CONCENTRATION (ug/Kg)	REPORTING LIMIT (ug/Kg)
Chloromethane	BDL	11
Bromomethane	BDL	11
Vinyl chloride	BDL	11
Chloroethane	BDL	6
Methylene chloride	BDL	11
Acetone	BDL	29
Carbon disulfide	BDL	6
Tetrahydrofuran	BDL	29
Trichlorofluoromethane	BDL	6
1,1-Dichloroethene	BDL	6
1,1-Dichloroethane	BDL	6
1,2-Dichloroethene (total)	BDL	6
Chloroform	BDL	6
1,2-Dichloroethane	BDL	6
2-Butanone	BDL	29
1,1,1-Trichloroethane	BDL	6
Carbon Tetrachloride	BDL	6
Vinyl acetate	BDL	11
Bromodichloromethane	BDL	6
1,2-Dichloropropane	BDL	6
cis-1,3-Dichloropropene	BDL	6
trans-1,3-Dichloropropene	BDL	6
Trichloroethene	BDL	6
Dibromochloromethane	BDL	6
1,1,2-Trichloroethane	BDL	6
Benzene	BDL	6
2-Chloroethyl vinyl ether	BDL	6
Bromoform	BDL	6
4-Methyl-2-Pentanone	BDL	29
2-Hexanone	BDL	29
Tetrachloroethene	BDL	6
1,1,2,2-Tetrachloroethane	BDL	6
Toluene	BDL	6
Chlorobenzene	BDL	6
Ethylbenzene	BDL	6
Styrene	BDL	6
Xylene (total)	BDL	6

METHOD REFERENCE: EPA SW 846, 3rd Edition
METHOD 8240

BDL = Below reporting limit

J = Probable presence below listed detection limit



000017

Laboratory number: 45205-009
Sample Designation: DSB13-55/57
Date Analyzed: 09/06/95
Matrix: SOLID

Instrument File Name: >G4431

Results are expressed on a dry (103 degrees C) basis.
Moisture content was 6 % , elevating the reporting limits
by a factor of 1.06 .

VOLATILE ORGANICS	CONCENTRATION (ug/g)	REPORTING LIMIT (ug/g)
Chloromethane	BDL	7
Bromomethane	BDL	7
Vinyl chloride	BDL	7
Chloroethane	BDL	3.2
Methylene chloride	BDL	7
Acetone	BDL	16
Carbon disulfide	BDL	3.2
1,1-Dichloroethene	BDL	3.2
Tetrahydrofuran	BDL	16
1,1-Dichloroethane	BDL	3.2
1,2-Dichloroethene (total)	BDL	3.2
Chloroform	BDL	3.2
Methyl ethyl ketone	BDL	16
1,2-Dichloroethane	BDL	3.2
1,1,1-Trichloroethane	27	3.2
Carbon Tetrachloride	BDL	3.2
Vinyl acetate	BDL	7
Bromodichloromethane	BDL	3.2
cis-1,3-Dichloropropene	BDL	3.2
trans-1,3-Dichloropropene	BDL	3.2
Trichloroethene	BDL	3.2
Benzene	BDL	3.2
Dibromochloromethane	BDL	3.2
1,1,2-Trichloroethane	BDL	3.2
1,2-Dichloropropane	BDL	3.2
2-Chloroethyl vinyl ether	BDL	3.2
Bromoform	BDL	3.2
Methyl isobutyl ketone	BDL	16
2-Hexanone	BDL	16
1,1,2,2-Tetrachloroethane	BDL	3.2
Tetrachloroethene	BDL	3.2
Toluene	14	3.2
Chlorobenzene	BDL	3.2
Ethylbenzene	2.0 J	3.2
Xylene (total)	12	3.2
Styrene	BDL	3.2

METHOD REFERENCE: EPA SW 846, 3rd Edition
METHOD 8240

BDL = Below reporting limit

J = Probable presence below listed detection limit

Detection limit raised by the presence of non-listed compounds.

000014



Lab No.: 45205

[illegible]

```
# Column to be used to flag recovery values with an asterisk
* Values outside of designated QC limits
D Surrogates diluted out
```

Laboratory number: BC090595A1
 Sample Designation: LABORATORY BLANK
 Date Analyzed: 09/05/95
 Matrix: SOLID

VOLATILE ORGANICS	CONCENTRATION (ug/Kg)	REPORTING LIMIT (ug/Kg)
Chloromethane	BDL	10
Bromomethane	BDL	10
Vinyl chloride	BDL	10
Chloroethane	BDL	5
Methylene chloride	4 J	10
Acetone	BDL	25
Carbon disulfide	BDL	5
1,1-Dichloroethene	BDL	5
Tetrahydrofuran	BDL	25
1,1-Dichloroethane	BDL	5
1,2-Dichloroethene (total)	BDL	5
Chloroform	BDL	5
Methyl ethyl ketone	BDL	25
1,2-Dichloroethane	BDL	5
1,1,1-Trichloroethane	BDL	5
Carbon Tetrachloride	BDL	5
Vinyl acetate	BDL	10
Bromodichloromethane	BDL	5
cis-1,3-Dichloropropene	BDL	5
trans-1,3-Dichloropropene	BDL	5
Trichloroethene	BDL	5
Benzene	BDL	5
Dibromochloromethane	BDL	5
1,1,2-Trichloroethane	BDL	5
1,2-Dichloropropane	BDL	5
2-Chloroethyl vinyl ether	BDL	5
Bromoform	BDL	5
Methyl isobutyl ketone	BDL	25
2-Hexanone	BDL	25
1,1,2,2-Tetrachloroethane	BDL	5
Tetrachloroethene	BDL	5
Toluene	BDL	5
Chlorobenzene	BDL	5
Ethylbenzene	BDL	5
m-Xylene	BDL	5
o,p-Xylene	BDL	5
Styrene	BDL	5

METHOD REFERENCE: EPA SW 846 2ND EDITION
 METHOD 8240

BDL = Below detection limit

J = Probable presence below listed detection limit.



000020

Laboratory number: BC090695A1
 Sample Designation: LABORATORY BLANK
 Date Analyzed: 09/06/95
 Matrix: SOLID

VOLATILE ORGANICS	CONCENTRATION (ug/Kg)	REPORTING LIMIT (ug/Kg)
Chloromethane	BDL	10
Bromomethane	BDL	10
Vinyl chloride	BDL	10
Chloroethane	BDL	5
Methylene chloride	3 J	10
Acetone	BDL	25
Carbon disulfide	BDL	5
1,1-Dichloroethene	BDL	5
Tetrahydrofuran	BDL	25
1,1-Dichloroethane	BDL	5
1,2-Dichloroethene (total)	BDL	5
Chloroform	BDL	5
Methyl ethyl ketone	BDL	25
1,2-Dichloroethane	BDL	5
1,1,1-Trichloroethane	BDL	5
Carbon Tetrachloride	BDL	5
Vinyl acetate	BDL	10
Bromodichloromethane	BDL	5
cis-1,3-Dichloropropene	BDL	5
trans-1,3-Dichloropropene	BDL	5
Trichloroethene	BDL	5
Benzene	BDL	5
Dibromochloromethane	BDL	5
1,1,2-Trichloroethane	BDL	5
1,2-Dichloropropane	BDL	5
2-Chloroethyl vinyl ether	BDL	5
Bromoform	BDL	5
Methyl isobutyl ketone	BDL	25
2-Hexanone	BDL	25
1,1,2,2-Tetrachloroethane	BDL	5
Tetrachloroethene	BDL	5
Toluene	BDL	5
Chlorobenzene	BDL	5
Ethylbenzene	BDL	5
m-Xylene	BDL	5
o,p-Xylene	BDL	5
Styrene	BDL	5

METHOD REFERENCE: EPA SW 846 2ND EDITION
 METHOD 8240

BDL = Below detection limit

J = Probable presence below listed detection limit.



000021

Laboratory number: BV1123
Sample Designation: LABORATORY BLANK
Date Analyzed: 09/07/95
Matrix: SOLID

VOLATILE ORGANICS	CONCENTRATION (ug/g)	DETECTION LIMIT (ug/g)
Chloromethane	BDL	1.0
Bromomethane	BDL	1.0
Vinyl chloride	BDL	1.0
Chloroethane	BDL	0.5
Methylene chloride	0.8 J	1.0
Acetone	BDL	2.5
Carbon disulfide	BDL	0.5
1,1-Dichloroethene	BDL	0.5
Tetrahydrofuran	BDL	2.5
1,1-Dichloroethane	BDL	0.5
Chloroform	BDL	0.5
Methyl ethyl ketone	BDL	2.5
1,2-Dichloroethane	BDL	0.5
1,1,1-Trichloroethane	BDL	0.5
Carbon Tetrachloride	BDL	0.5
Vinyl acetate	BDL	1.0
Bromodichloromethane	BDL	0.5
cis-1,3-Dichloropropene	BDL	0.5
cis-1,3-Dichloropropene	BDL	0.5
trans-1,3-Dichloropropene	BDL	0.5
Trichloroethene	BDL	0.5
Benzene	BDL	0.5
Dibromochloromethane	BDL	0.5
1,1,2-Trichloroethane	BDL	0.5
1,2-Dichloropropane	BDL	0.5
2-Chloroethyl vinyl ether	BDL	0.5
Bromoform	BDL	0.5
Methyl isobutyl ketone	BDL	2.5
2-Hexanone	BDL	2.5
1,1,2,2-Tetrachloroethane	BDL	0.5
Tetrachloroethene	BDL	0.5
Toluene	BDL	0.5
Chlorobenzene	BDL	0.5
Ethylbenzene	BDL	0.5
m-Xylene	BDL	0.5
o,p-Xylene	BDL	0.5
Styrene	BDL	0.5

METHOD REFERENCE: EPA SW 846, 3RD EDITION
METHOD 8240

BDL = Below detection limit

000022



MATRIX SPIKE RECOVERY
VOLATILE ORGANIC COMPOUNDS

Laboratory Number: LCC090595A1
Sample Designation: LABORATORY CONTROL SAMPLE
Date Analyzed: 09/05/95
Matrix: LOW SOIL

COMPOUND	ug/Kg SAMPLE	ug/Kg SPIKE	ug/kg FOUND	%REC- OVERY
1,1-DICHLOROETHENE	0	50	51	101
TRICHLOROETHYLENE	0	50	47	93
BENZENE	0	50	43	87
TOLUENE	0	50	47	93
CHLOROBENZENE	0	50	51	101

METHOD REFERENCE: EPA SW 846, 3RD EDITION
METHOD 8240

000023

MATRIX SPIKE RECOVERY
VOLATILE ORGANIC COMPOUNDS

Laboratory Number: LCC090695A1
Sample Designation: LABORATORY CONTROL SAMPLE
Date Analyzed: 09/06/95
Matrix: LOW SOIL

COMPOUND	ug/Kg SAMPLE	ug/Kg SPIKE	ug/kg FOUND	%REC- OVERY
1,1-DICHLOROETHENE	0	50	46	93
TRICHLOROETHYLENE	0	50	46	91
BENZENE	0	50	44	87
TOLUENE	0	50	47	94
CHLOROBENZENE	0	50	49	98

METHOD REFERENCE: EPA SW 846, 3RD EDITION
METHOD 8240

000024

MATRIX SPIKE RECOVERY
VOLATILE ORGANIC COMPOUNDS

Laboratory Number: LS1123
Sample Designation: LABORATORY CONTROL SAMPLE
Date Analyzed: 09/06/95
Matrix: SOLID

COMPOUND	ug/g IN SAMPLE	ug/g SPIKE	ug/g FOUND	%REC- OVERY
1,1-DICHLOROETHENE	0	6.25	6.02	96
TRICHLOROETHYLENE	0	6.25	5.83	93
BENZENE	0	6.25	5.69	91
TOLUENE	0	6.25	5.35	86
CHLOROBENZENE	0	6.25	6.07	97

METHOD REFERENCE: EPA SW 846, 3RD EDITION
METHOD 8240

Re: 5/18/94 bak

5A
VOLATILE ORGANIC GC/MS TUNING AND MASS
CALIBRATION - BROMOFLUOROBENZENE (BFB)

Lab Name: PACE New England

Project: BETHPAGE

Lab File ID: >C1022

BFB Injection Date: 08/31/95

Instrument ID: CMS

BFB Injection Time: 13:07

ION ABUNDANCE CRITERIA for C1022 are reported on a separate sheet.

THIS TUNE APPLIES TO THE FOLLOWING SAMPLES, MS, MSD, BLANKS, AND STANDARDS

CLIENT I.D.	LAB SAMPLE ID	LAB FILE ID	DATE ANALYZED	DATE ANALYZED
=====	=====	=====	=====	=====
VSTD200	VSTD200	C1028	08/31/95	16:55
VSTD100	VSTD100	C1029	08/31/95	17:30
VSTD050	VSTD050	C1030	08/31/95	18:05
VSTD020	VSTD020	C1031	08/31/95	18:39
VSTD010	VSTD010	C1032	08/31/95	19:14

000027

pace.
INCORPORATED
THE ASSURANCE OF QUALITY

GC/MS PERFORMANCE STANDARD

Bromofluorobenzene (BFB) '88

m/z	Ion Abundance Criteria	% Relative Abundance		Status
		Base Peak	Appropriate Peak	
50	15-40% of mass 95	20.56	20.56	Ok
75	30-60% of mass 95	46.25	46.25	Ok
95	Base peak, 100% relative abundance	100.00	100.00	Ok
96	5-9% of mass 95	8.63	8.63	Ok
173	Less than 2% of mass 174	0.00	0.00	Ok
174	Greater than 50% of mass 95	85.93	85.93	Ok
175	5-9% of mass 174	6.79	7.90	Ok
176	95-101% of mass 174	81.82	95.22	Ok
177	5-9% of mass 176	6.98	8.53	Ok

Injection Date: 08/31/95

Injection Time: 13:07

Data File: >C1022

Scan: 188



THIS IS THE RESULT OF AVERAGING
AND SUBTRACTING BACKGROUND SCAN

187.00

188.00

189.00

168.00



000028

5A
VOLATILE ORGANIC GC/MS TUNING AND MASS
CALIBRATION - BROMOFLUOROBENZENE (BFB)

Lab Name: PACE New England

Project: BETHPAGE

Lab File ID: >C1061

BFB Injection Date: 09/05/95

Instrument ID: CMS

BFB Injection Time: 13:44

ION ABUNDANCE CRITERIA for C1061 are reported on a separate sheet.

THIS TUNE APPLIES TO THE FOLLOWING SAMPLES, MS, MSD, BLANKS, AND STANDARDS

CLIENT I.D.	LAB SAMPLE ID	LAB FILE ID	DATE ANALYZED	DATE ANALYZED
=====	=====	=====	=====	=====
VSTD050	VSTD050	C1063	09/05/95	14:41
BC090595A1	90182-089	C1064	09/05/95	15:16
LCC090595A1	90182-089MS	C1065	09/05/95	16:02
DSB10-00/02	45205-001	C1066	09/05/95	16:46
DSB10-15/17	45205-002	C1067	09/05/95	17:20
DSB10-60/62	45205-003	C1068	09/05/95	17:55
DSB11-00/02DL	45205-004DL	C1069	09/05/95	18:30
DSB13-00/02	45205-007	C1072	09/05/95	21:00
DSB13-40/42	45205-008	C1073	09/05/95	21:50

000029

pace
INCORPORATED
THE ASSURANCE OF QUALITY

GC/MS PERFORMANCE STANDARD

Bromofluorobenzene (BFB) '88

m/z	Ion Abundance Criteria	% Relative Abundance Base Peak	Appropriate Peak	Status
50	15-40% of mass 95	20.35	20.35	Ok
75	30-60% of mass 95	52.23	52.23	Ok
95	Base peak, 100% relative abundance	100.00	100.00	Ok
96	5-9% of mass 95	7.73	7.73	Ok
173	Less than 2% of mass 174	0.00	0.00	Ok
174	Greater than 50% of mass 95	84.87	84.87	Ok
175	5-9% of mass 174	4.86	5.73	Ok
176	95-101% of mass 174	83.04	97.84	Ok
177	5-9% of mass 176	7.27	8.75	Ok

Injection Date: 09/05/95

Injection Time: 13:44



Data File: >C1061

Scan: 189

THIS IS THE RESULT OF AVERAGING
AND SUBTRACTING BACKGROUND SCAN188.00
169.00

189.00

190.00

TV
9/2/95

000030

5A
VOLATILE ORGANIC GC/MS TUNING AND MASS
CALIBRATION - BROMOFLUOROBENZENE (BFB)

Lab Name: PACE New England

Project: BETHPAGE

Lab File ID: >C1078

BFB Injection Date: 09/06/95

Instrument ID: CMS

BFB Injection Time: 12:16

ION ABUNDANCE CRITERIA for C1078 are reported on a separate sheet.

THIS TUNE APPLIES TO THE FOLLOWING SAMPLES, MS, MSD, BLANKS, AND STANDARDS

CLIENT I.D.	LAB SAMPLE ID	LAB FILE ID	DATE ANALYZED	DATE ANALYZED
-----	-----	-----	-----	-----
VSTD050	VSTD050	C1080	09/06/95	13:13
BC090695A1	90182-090	C1081	09/06/95	13:48
LCC090695A1	90182-090MS	C1082	09/06/95	14:33
DSB11-00/02	45205-004	C1083	09/06/95	16:02
DSB11-30/32	45205-005	C1084	09/06/95	16:52
DSB11-60/62	45205-006	C1085	09/06/95	17:42
DSB12-40/42	45205-011	C1086	09/06/95	18:32
DSB12-60/62	45205-012	C1087	09/06/95	19:22
DSB12-00/02	45205-010	C1088	09/06/95	20:12

000031

GC/MS PERFORMANCE STANDARD

Bromofluorobenzene (BFB) '88

m/z	Ion Abundance Criteria	% Relative Abundance		Status
		Base Peak	Appropriate Peak	
50	15-40% of mass 95	17.75	17.75	Ok
75	30-60% of mass 95	49.20	49.20	Ok
95	Base peak, 100% relative abundance	100.00	100.00	Ok
96	5-9% of mass 95	6.80	6.80	Ok
173	Less than 2% of mass 174	0.00	0.00	Ok
174	Greater than 50% of mass 95	87.57	87.57	Ok
175	5-9% of mass 174	5.15	5.89	Ok
176	95-101% of mass 174	85.51	97.65	Ok
177	5-9% of mass 176	7.40	8.66	Ok

Injection Date: 09/06/95


Injection Time: 12:16

Data File: >C1078

Scan: 191

THIS IS THE RESULT OF AVERAGING 190.00 191.00 192.00
AND SUBTRACTING BACKGROUND SCAN 171.00

9/8/95



000032

5A
VOLATILE ORGANIC GC/MS TUNING AND MASS
CALIBRATION - BROMOFLUOROBENZENE (BFB)

Lab Name: PACE New England

Project: BETHPAGE

Lab File ID: >G4403

BFB Injection Date: 09/05/95

Instrument ID: GMS

BFB Injection Time: 14:11

ION ABUNDANCE CRITERIA for G4403 are reported on a separate sheet.

THIS TUNE APPLIES TO THE FOLLOWING SAMPLES, MS, MSD, BLANKS, AND STANDARDS

CLIENT I.D.	LAB SAMPLE ID	LAB FILE ID	DATE ANALYZED	DATE ANALYZED
=====	=====	=====	=====	=====
VSTD200	VSTD200	G4404	09/05/95	14:40
VSTD100	VSTD100	G4405	09/05/95	15:19
VSTD050	VSTD050	G4406	09/05/95	15:58
VSTD020	VSTD020	G4409	09/05/95	18:18
VSTD010	VSTD010	G4410	09/05/95	18:57

000033



GC/MS PERFORMANCE STANDARD

Bromofluorobenzene (BFB) '88

PUL
9/8/95


m/z	Ion Abundance Criteria	% Relative Abundance		Status
		Base Peak	Appropriate Peak	
50	15-40% of mass 95	22.60	22.60	Ok
75	30-60% of mass 95	56.00	56.00	Ok
95	Base peak. 100% relative abundance	100.00	100.00	Ok
96	5-9% of mass 95	7.40	7.40	Ok
173	Less than 2% of mass 174	.24	.31	Ok
174	Greater than 50% of mass 95	77.05	77.05	Ok
175	5-9% of mass 174	5.02	6.52	Ok
176	95-101% of mass 174	73.63	95.57	Ok
177	5-9% of mass 176	4.87	6.62	Ok

Injection Date: 09/05/95

Injection Time: 14:11

Data File: >G4403

Scan: 151 + 150 + 152 - 100



000034

5A
VOLATILE ORGANIC GC/MS TUNING AND MASS
CALIBRATION - BROMOFLUOROBENZENE (BFB)

Lab Name: PACE New England

Project: BETHPAGE

Lab File ID: >G4424

BFB Injection Date: 09/06/95

Instrument ID: GMS

BFB Injection Time: 10:32

ION ABUNDANCE CRITERIA for G4424 are reported on a separate sheet.

THIS TUNE APPLIES TO THE FOLLOWING SAMPLES, MS, MSD, BLANKS, AND STANDARDS

CLIENT I.D.	LAB SAMPLE ID	LAB FILE ID	DATE ANALYZED	DATE ANALYZED
=====	=====	=====	=====	=====
VSTD050	VSTD050	G4426	09/06/95	11:35
BG090695A1	90184-110	G4427	09/06/95	12:15
LSV1123		G4430	09/06/95	14:43
DSB13-55/57	45205-009	G4431	09/06/95	15:25
DSB13-55/57MS	45205-009MS	G4432	09/06/95	16:22
DSB13-55/57MSD	45205-009MSD	G4433	09/06/95	17:20

GC/MS PERFORMANCE STANDARD

Bromofluorobenzene (BFB) '88

PWC
9/8/95


m/z	Ion Abundance Criteria	% Relative Abundance		Status
		Base Peak	Appropriate Peak	
50	15-40% of mass 95	20.46	20.46	Ok
75	30-60% of mass 95	58.23	58.23	Ok
95	Base peak. 100% relative abundance	100.00	100.00	Ok
96	5-9% of mass 95	6.94	6.94	Ok
173	Less than 2% of mass 174	0.00	0.00	Ok
174	Greater than 50% of mass 95	74.05	74.05	Ok
175	5-9% of mass 174	5.71	7.71	Ok
176	95-101% of mass 174	74.57	100.69	Ok
177	5-9% of mass 176	5.36	7.19	Ok

Injection Date: 09/06/95

Injection Time: 10:32

Data File: >64424

Scan: 146 +145+147-100



000036

5A
VOLATILE ORGANIC GC/MS TUNING AND MASS
CALIBRATION - BROMOFLUOROBENZENE (BFB)

Lab Name: PACE New England

Project: BETHPAGE

Lab File ID: >G4444

BFB Injection Date: 09/07/95

Instrument ID: GMS

BFB Injection Time: 11:08

ION ABUNDANCE CRITERIA for G4444 are reported on a separate sheet.

THIS TUNE APPLIES TO THE FOLLOWING SAMPLES, MS, MSD, BLANKS, AND STANDARDS

CLIENT I.D.	LAB SAMPLE ID	LAB FILE ID	DATE ANALYZED	DATE ANALYZED
-----	-----	-----	-----	-----
VSTD050	VSTD050	G4447	09/07/95	12:57
BV1123A	90186-052	G4458	09/07/95	21:09

000037

GC/MS PERFORMANCE STANDARD

Bromofluorobenzene (BFB) '88

A. L.
9/11/95



m/z	Ion Abundance Criteria	% Relative Abundance		Status
		Base Peak	Appropriate Peak	
50	15-40% of mass 95	21.01	21.01	Ok
75	30-60% of mass 95	55.54	55.54	Ok
95	Base peak, 100% relative abundance	100.00	100.00	Ok
96	5-9% of mass 95	7.44	7.44	Ok
173	Less than 2% of mass 174	.35	.43	Ok
174	Greater than 50% of mass 95	81.61	81.61	Ok
175	5-9% of mass 174	5.95	7.29	Ok
176	95-101% of mass 174	77.55	95.02	Ok
177	5-9% of mass 176	4.81	6.21	Ok

Injection Date: 09/07/95

Injection Time: 11:08

Data File: >G4444

Scan: 147 + 146 + 148 - 100



000038

VOLATILE INTERNAL STANDARD AREA SUMMARY

Lab Name: PACE New England

Project: BETHPAGE

Lab File ID (Standard): >C1063

Date Analyzed: 09/05/95

Instrument ID: CMS

Time Analyzed: 14:41

	IS1 (BCM)		IS2 (DFB)		IS3 (CBZ)	
	AREA #	RT #	AREA #	RT #	AREA #	RT #
=====	=====	=====	=====	=====	=====	=====
12 HOUR STD	63686	7.34	249452	18.03	203654	22.84
=====	=====	=====	=====	=====	=====	=====
UPPER LIMIT	127372	7.84	498904	18.53	407308	23.34
=====	=====	=====	=====	=====	=====	=====
LOWER LIMIT	31843	6.84	124726	17.53	101827	22.34
=====	=====	=====	=====	=====	=====	=====
CLIENT I.D.						
=====	=====	=====	=====	=====	=====	=====
BC090595A1	62832	7.36	243480	18.04	202036	22.84
LCC090595A1	69526	7.32	270924	18.02	220724	22.86
DSB10-00/02	55272	7.39	214674	18.02	169780	22.90
DSB10-15/17	63857	7.44	258812	18.03	212489	22.88
DSB10-60/62	65010	7.43	250191	18.03	204996	22.89
DSB11-00/02DL	66660	7.29	241165	18.04	182317	22.85
DSB13-00/02	70232	7.40	266010	18.05	188221	22.89
DSB13-40/42	79429	7.41	298602	18.04	238827	22.83

IS1 (BCM) = Bromochloromethane
 IS2 (DFB) = 1,4-Difluorobenzene
 IS3 (CBZ) = Chlorobenzene

UPPER LIMIT = + 100%
 of internal standard area.
 LOWER LIMIT = - 50%

Column used to flag internal standard area values outside of
 UPPER and LOWER LIMIT with an asterisk

000039

8A
VOLATILE INTERNAL STANDARD AREA SUMMARY

Lab Name: PACE New England

Project: BETHPAGE

Lab File ID (Standard): >C1080

Date Analyzed: 09/06/95

Instrument ID: CMS

Time Analyzed: 13:13

	IS1 (BCM)		IS2 (DFB)		IS3 (CBZ)	
	AREA #	RT #	AREA #	RT #	AREA #	RT #
12 HOUR STD	85898	7.35	318580	17.99	277456	22.83
UPPER LIMIT	171796	7.85	637160	18.49	554912	23.33
LOWER LIMIT	42949	6.85	159290	17.49	138728	22.33
CLIENT I.D.						
BC090695A1	83310	7.37	314310	18.00	267404	22.86
LCC090695A1	83844	7.39	314727	18.00	262106	22.88
DSB11-00/02	63891	7.48	234491	18.02	186131	22.88
DSB11-30/32	74345	7.38	281071	18.04	228897	22.89
DSB11-60/62	73255	7.43	275969	18.03	221169	22.91
DSB12-40/42	72352	7.46	270965	18.07	229059	22.90
DSB12-60/62	77303	7.43	293556	18.04	243288	22.89
DSB12-00/02	62640	7.38	218478	18.03	166028	22.89

IS1 (BCM) = Bromochloromethane
IS2 (DFB) = 1,4-Difluorobenzene
IS3 (CBZ) = Chlorobenzene

UPPER LIMIT = + 100%
of internal standard area.
LOWER LIMIT = - 50%

Column used to flag internal standard area values outside of
UPPER and LOWER LIMIT with an asterisk

000040

pace
INCORPORATED
THE ASSURANCE OF DATA

VOLATILE INTERNAL STANDARD AREA SUMMARY

Lab Name: PACE New England

Project: BETHPAGE

Lab File ID (Standard): >G4426

Date Analyzed: 09/06/95

Instrument ID: GMS

Time Analyzed: 11:35

	IS1 (BCM)		IS2 (DFB)		IS3 (CBZ)	
	AREA #	RT #	AREA #	RT #	AREA #	RT #
=====	=====	=====	=====	=====	=====	=====
12 HOUR STD	90088	11.43	424786	13.55	323645	21.05
=====	=====	=====	=====	=====	=====	=====
UPPER LIMIT	180176	11.93	849572	14.05	647290	21.55
=====	=====	=====	=====	=====	=====	=====
LOWER LIMIT	45044	10.93	212393	13.05	161823	20.55
=====	=====	=====	=====	=====	=====	=====
CLIENT I.D.						
=====	=====	=====	=====	=====	=====	=====
BG090695A1	81279	11.45	374131	13.56	294638	21.11
LSV1123	72512	11.45	334820	13.56	290100	21.13
DSB13-55/57	72542	11.43	328495	13.54	300448	21.09
DSB13-55/57MS	71690	11.31	340048	13.44	322916	21.04
DSB13-55/57MSD	75959	11.29	373167	13.43	320542	21.05

IS1 (BCM) = Bromochloromethane
 IS2 (DFB) = 1,4-Difluorobenzene
 IS3 (CBZ) = Chlorobenzene

UPPER LIMIT = + 100%
 of internal standard area.
 LOWER LIMIT = - 50%

Column used to flag internal standard area values outside of
 UPPER and LOWER LIMIT with an asterisk

000041

VOLATILE INTERNAL STANDARD AREA SUMMARY

Lab Name: PACE New England

Project: BETHPAGE

Lab File ID (Standard): >G4447

Date Analyzed: 09/07/95

Instrument ID: GMS

Time Analyzed: 12:57

	IS1 (BCM)		IS2 (DFB)		IS3 (CBZ)	
	AREA #	RT #	AREA #	RT #	AREA #	RT #
12 HOUR STD	103582	11.48	475974	13.57	366897	21.10
UPPER LIMIT	207164	11.98	951948	14.07	733794	21.60
LOWER LIMIT	51791	10.98	237987	13.07	183449	20.60
CLIENT I.D.						
BV1123A	77474	11.41	359697	13.52	325330	21.07

IS1 (BCM) = Bromochloromethane

IS2 (DFB) = 1,4-Difluorobenzene

IS3 (CBZ) = Chlorobenzene

UPPER LIMIT = + 100%

of internal standard area.

LOWER LIMIT = - 50%

Column used to flag internal standard area values outside of
UPPER and LOWER LIMIT with an asterisk

00004?

SC0831 / LC0831

TU
9/11/95Initial Calibration Data
MSL Compounds

Case No:

Instrument ID: CMS-HP

Contractor: RESAM

Calibration Date: 09/01/95

083195

Contract No: 68020026

③ TU

Minimum RF for SPEC is .30

Maximum X RSD for CCC is 30%

Compound	Laboratory ID: >C1032 >C1031 >C1030 >C1029 >C1028					RRT	RF	X RSD	CCC SPEC
	RF	RF	RF	RF	RF				
	10.00	20.00	50.00	100.00	200.00				
C010 CHLOROMETHANE	.46763	.47577	.36171	.32007	.35693	.209	.39642	17.819	** ✓
C015 BROMOMETHANE	1.17488	1.26312	1.06945	1.05207	1.15280	.287	1.14246	7.481	
C020 VINYL CHLORIDE	.85723	.87690	.81362	.74692	.87721	.357	.83438	6.631	* ✓
C025 CHLOROETHANE	.46232	.54392	.49169	.47947	.54935	.439	.50535	7.748	
C030 METHYLENE CHLORIDE	2.19924	1.63239	1.15780	1.06405	1.11119	.624	1.43293	33.872	
C035 ACETONE	.85161	.63688	.45944	.41946	.41366	.756	.55605	33.887	
C040 CARBON DISULFIDE	2.31313	2.35907	2.05976	1.99473	2.34228	.855	2.21379	7.798	
C042 TRICHLOROFLUOROMETHANE	2.48403	2.43315	2.25633	2.09547	2.51744	.908	2.35728	7.535	
C045 1,1-DICHLOROETHENE	.94318	.98063	.91438	.84931	1.00126	.997	.93775	6.369	* ✓
C058 TETRAHYDROFURAN	.17106	.17957	.15996	.15837	.15310	1.154	.16441	6.510	
C050 1,1-DICHLOROETHANE	2.03857	2.01826	1.76173	1.74080	1.92570	1.138	1.89701	7.374	** ✓
C053 1,2-DICHLOROETHENE (total)	.91402	1.11611	.99562	.98137	1.09662	1.241	1.02075	8.258	
C060 CHLOROFORM	2.33560	2.69706	2.39838	2.37748	2.61724	1.277	2.48515	6.483	* ✓
C110 2-BUTANONE	1.20181	1.16612	.91318	.86723	.89908	1.434	1.00148	16.808	
C065 1,2-DICHLOROETHANE	1.79133	1.84748	1.63573	1.62509	1.71709	1.397	1.72335	5.611	
MTBE	2.34098	2.57509	2.08308	2.10044	2.06032	1.561	2.23198	9.982	
C515 1,2-DICHLOROETHANE-d4	1.05607	1.73800	1.16489	1.27859	1.50126	1.383	1.34776	20.291	
C115 1,1,1-TRICHLOROETHANE	.60252	.60827	.55422	.51984	.63875	.636	.58472	8.081	
C120 CARBON TETRACHLORIDE	.53983	.53752	.50913	.47799	.59072	.657	.53104	7.864	
C125 VINYL ACETATE	.78683	.80853	.64410	.66794	.69662	.685	.72080	10.128	
C130 BROMODICHLOROMETHANE	.83209	.85322	.73630	.73184	.84131	.677	.79895	7.475	
C140 1,2-DICHLOROPROPANE	.34939	.36698	.31842	.30021	.33195	.767	.33339	7.809	* ✓
C143 CIS-1,3-DICHLOROPROPENE	.54570	.60788	.52951	.50110	.56224	.779	.54928	7.240	
C150 TRICHLOROETHENE	.42172	.44504	.38913	.36968	.41594	.815	.40830	7.190	
C155 DIBROMOCHLOROMETHANE	.66968	.75967	.65723	.64338	.72563	.830	.69112	7.154	
C160 1,1,2-TRICHLOROETHANE	.37814	.42059	.35094	.32740	.36041	.844	.36750	9.489	
C165 BENZENE	.78322	.84693	.73497	.70810	.79945	.856	.77453	7.047	
C172 TRANS-1,3-DICHLOROPROPENE	.48499	.55231	.48195	.46238	.51095	.852	.49852	6.957	
C176 2-CHLOROETHYL METHYL ETHER	.19253	.18379	.17714	.18595	.20643	.919	.18917	5.870	
C180 BROMOFORM	.50373	.57870	.50054	.50231	.56201	.981	.52946	7.142	** ✓

(Conc=20.0, 40.0, 100.0, 200)

RF - Response Factor (Subscript is amount in ug/Kg)

RRT - Average Relative Retention Time (RT Std/RT Istd)

RF - Average Response Factor

XRSD - Percent Relative Standard Deviation

CCC - Calibration Check Compounds (*) SPEC - System Performance Check Compounds (**)

000043

Initial Calibration Data
MSL Compounds

Case No: _____ Instrument ID: CMS-HP
Contractor: RESAM _____ Calibration Date: 09/01/95
Contract No: 68020026 _____

Minimum RF for SPCC is .30 Maximum % RSD for CCC is 30%

Compound	Laboratory ID: >C1032 >C1031 >C1030 >C1029 >C1028					RRT	RF	% RSD	CCC	SPCC
	RF	RF	RF	RF	RF					
	10.00	20.00	50.00	100.00	200.00					
CS05 TOLUENE-d8	.71650	1.07788	.73729	.77261	.93100	.953	.84705	18.190		
C205 4-METHYL-2-PENTANONE	.82257	.81170	.65178	.64867	.65534	.818	.71801	12.618		
C210 2-HEXANONE	.72633	.61534	.52162	.50467	.48353	.891	.57030	17.661		
C220 TETRACHLOROETHENE	.42697	.40162	.37565	.34880	.40835	.893	.39228	7.770		
C225 1,1,2,2-TETRACHLOROETHANE	.97846	1.01699	.85729	.83387	.88008	.881	.91334	8.750	**	/
C230 TOLUENE	1.37299	1.27557	1.09803	1.02495	1.14467	.961	1.18324	11.827	*	/
C235 CHLOROBENZENE	1.00980	.97789	.85743	.81547	.89260	1.006	.91064	8.950	**	/
C240 ETHYLBENZENE	.49943	.47791	.41320	.39264	.45719	1.089	.44807	9.918	*	/
C245 STYRENE	1.05884	1.02502	.87025	.85975	.94908	1.211	.95259	9.382		
C251 XYLENE	.54416	.54445	.47309	.42934	.49776	1.218	.49776	9.854		
C250 XYLENE (total)	.58592	.57284	.49423	.46112	.51907	1.244	.52663	9.980		
CS10 BROMOFLUOROBENZENE	.78323	1.06717	.71560	.73315	.87997	1.164	.83582	17.258		

(Conc=20.0, 40.0, 100.0, 200)

RF - Response Factor (Subscript is amount in ug/Kg)

RRT - Average Relative Retention Time (RT Std/RT Istd)

RF - Average Response Factor

%RSD - Percent Relative Standard Deviation

CCC - Calibration Check Compounds (*) SPCC - System Performance Check Compounds (**)

000044

Continuing Calibration Check
HSL Compounds

LC0905

Case No: _____ Calibration Date: 09/05/95
Contractor: RESAN _____ Time: 14:41
Contract No: 68020026 _____ Laboratory ID: >C1063
Instrument ID: CMS-HP _____ Initial Calibration Date: ~~09-01-95~~ 8/3/95
8/3/95

Minimum RF for SPCC is .30 Maximum X Diff for CCC is 25X

Compound	RF	RF	XDiff	CCC	SPCC
C010 CHLOROMETHANE	.39642	.42531	7.29	**	✓
C015 BROMOMETHANE	1.14246	1.21529	6.37		
C020 VINYL CHLORIDE	.83438	.79379	4.87	*	✓
C025 CHLOROETHANE	.50535	.51002	.92		
C030 METHYLENE CHLORIDE	1.43293	1.25026	12.75		
C035 ACETONE	.55605	.43377	21.99		
C040 CARBON DISULFIDE	2.21379	2.31110	4.40		
C042 TRICHLOROFLUOROMETHANE	2.35728	2.61929	11.11		
C045 1,1-DICHLOROETHENE	.93775	.98771	5.33	*	✓
C050 TETRAHYDROFURAN	.16441	.19282	17.28		
C050 1,1-DICHLOROETHANE	1.89701	1.95297	2.95	**	✓
C053 1,2-DICHLOROETHENE (total)	1.02075	1.15666	13.32		(Conc=100.00)
C060 CHLOROFORM	2.48515	2.74376	10.41	*	✓
C110 2-BUTANONE	1.00148	.96233	3.91		
C065 1,2-DICHLOROETHANE	1.72335	1.93920	12.53		
MTBE	2.23198	2.65457	18.93		(Conc=50.00)
C515 1,2-DICHLOROETHANE-d4	1.34776	1.57053	16.53		
C115 1,1,1-TRICHLOROETHANE	.58472	.61815	5.72		
C120 CARBON TETRACHLORIDE	.53104	.59290	11.65		
C125 VINYL ACETATE	.72080	.68954	4.34		
C130 BROMODICHLOROMETHANE	.79895	.83675	4.73		
C140 1,2-DICHLOROPROPANE	.33339	.34696	4.07	*	✓
C143 CIS-1,3-DICHLOROPROPENE	.54928	.58860	7.16		(Conc=50.00)
C150 TRICHLOROETHENE	.40830	.45552	11.56		
C155 DIBROMOCHLOROMETHANE	.69112	.80015	15.78		
C160 1,1,2-TRICHLOROETHANE	.36750	.40574	10.41		
C165 BENZENE	.77453	.82491	6.50		
C172 TRANS-1,3-DICHLOROPROPENE	.49852	.53743	7.81		(Conc=50.00)
C176 2-CHLOROETHYL VINYL ETHER	.18917	.20574	8.76		
C180 BROMOFORM	.52946	.70040	32.29	**	✓
C505 TOLUENE-d8	.84705	.98681	16.50		
C205 4-METHYL-2-PENTANONE	.71801	.75123	4.63		

RF - Response Factor from daily standard file at 50.00 ug/Kg

RF - Average Response Factor from Initial Calibration Form VI

XDiff - X Difference from original average or curve

CCC - Calibration Check Compounds (*) SPCC - System Performance Check Compounds (**)

000045

Continuing Calibration Check
HSL Compounds

Case No: _____ Calibration Date: 09/05/95
Contractor: RESAM _____ Time: 14:41
Contract No: 68020026 _____ Laboratory ID: JCI063
Instrument ID: CMS-HP _____ Initial Calibration Date: 09/01/95

Minimum RF for SPCC is .30

Maximum % Diff for CCC is 25%

Compound	RF	RF	%Diff	CCC	SPCC
C210 2-HEXANONE	.57030	.58100	1.88		
C220 TETRACHLOROETHENE	.39228	.48810	24.43		
C225 1,1,2,2-TETRACHLOROETHANE	.91334	.96947	6.15	**	
C230 TOLUENE	1.18324	1.25202	5.81	*	
C235 CHLOROBENZENE	.91064	.98515	8.18	**	
C240 ETHYLBENZENE	.44807	.45751	2.10	*	
C245 STYRENE	.95259	.92201	3.21		
C251 XYLENE	.49776	.51846	4.16		
C250 XYLENE (total)	.52663	.52580	.16		(Conc=100.00)
C510 BROMOFLUOROBENZENE	.83582	.90396	8.15		

RF - Response Factor from daily standard file at 50.00 ug/Kg

RF - Average Response Factor from Initial Calibration Form VI

%Diff - % Difference from original average or curve

CCC - Calibration Check Compounds (*) SPCC - System Performance Check Compounds (**)

000046

LC0906

Continuing Calibration Check
HSL Compounds

Case No: _____ Calibration Date: 09/06/95
 Contractor: RESAM _____ Time: 13:13
 Contract No: 68020026 _____ Laboratory ID: >C1080
 Instrument ID: CMS-HP _____ Initial Calibration Date: 09/01/95

8/31/95
TU
9/6/95

Minimum RF for SPCC is .30 Maximum % Diff for CCC is 25%

Compound	RF	RF	%Diff	CCC	SPCC
C010 CHLOROMETHANE	.39642	.46913	18.34	**	✓
C015 BROMOMETHANE	1.14246	1.25873	10.18		
C020 VINYL CHLORIDE	.83438	.83725	.34	*	✓
C025 CHLOROETHANE	.50535	.51945	2.79		
C030 METHYLENE CHLORIDE	1.43293	1.18492	17.31		
C035 ACETONE	.55605	.44683	19.64		
C040 CARBON DISULFIDE	2.21379	2.31147	4.41		
C042 TRICHLOROFLUOROMETHANE	2.35728	2.53279	7.45		
C045 1,1-DICHLOROETHENE	.93775	1.04383	11.31	*	✓
C058 TETRAHYDROFURAN	.16441	.16422	.12		
C050 1,1-DICHLOROETHANE	1.89701	1.91457	.93	**	✓
C053 1,2-DICHLOROETHENE (total)	1.02075	1.16644	14.27		(Conc=100.00)
C060 CHLOROFORM	2.98515	2.63003	5.83	*	✓
C110 2-BUTANONE	1.00148	.85790	14.34		
C065 1,2-DICHLOROETHANE	1.72335	1.77279	2.87		
MTBE	2.23198	2.43497	9.09		(Conc=50.00)
C515 1,2-DICHLOROETHANE-d4	1.34776	1.47470	9.42		
C115 1,1,1-TRICHLOROETHANE	.58472	.62814	7.43		
C120 CARBON TETRACHLORIDE	.53104	.58543	10.24		
C125 VINYL ACETATE	.72080	.63205	12.31		
C130 BROMODICHLOROMETHANE	.79895	.82806	3.64		
C140 1,2-DICHLOROPROPANE	.33339	.32954	1.16	*	✓
C143 CIS-1,3-DICHLOROPROPENE	.54928	.57199	4.13		(Conc=50.00)
C150 TRICHLOROETHENE	.40830	.44981	10.17		
C155 DIBROMOCHLOROMETHANE	.69112	.78400	13.44		
C160 1,1,2-TRICHLOROETHANE	.36750	.37950	3.27		
C165 BENZENE	.77453	.76477	1.26		
C172 TRANS-1,3-DICHLOROPROPENE	.49852	.48756	2.20		(Conc=50.00)
C176 2-CHLOROETHYL VINYL ETHER	.18917	.19149	1.23		
C180 BROMOFORM	.52946	.64708	22.22	**	✓
C505 TOLUENE-d8	.84705	.96058	13.40		
C205 4-METHYL-2-PENTANONE	.71801	.59373	17.31		

RF - Response Factor from daily standard file at 50.00 ug/Kg

RF - Average Response Factor from Initial Calibration Form VI

%Diff - % Difference from original average or curve

CCC - Calibration Check Compounds (*) SPCC - System Performance Check Compounds (**)

000047

Continuing Calibration Check
HSL Compounds

Case No: _____ Calibration Date: 09/06/95
Contractor: RESAM _____ Time: 13:13
Contract No: 68020026 _____ Laboratory ID: >C1080
Instrument ID: CMS-HP _____ Initial Calibration Date: 09/01/95

Minimum RF for SPCC is .30 Maximum % Diff for CCC is 25%

Compound	RF	RF	%Diff	CCC	SPCC
C210 2-HEXANONE	.57030	.48204	15.48		
C220 TETRACHLOROETHENE	.39228	.46486	18.50		
C225 1,1,2,2-TETRACHLOROETHANE	.91334	.93293	2.15	**	
C230 TOLUENE	1.18324	1.21568	2.74	*	
C235 CHLOROBENZENE	.91064	.96583	6.06	**	
C240 ETHYLBENZENE	.44807	.45297	1.09	*	
C245 STYRENE	.95259	.94256	1.05		
C251 XYLENE	.99776	.51880	4.23		
C250 XYLENE (total)	.52663	.52348	.60		(Conc=100.00)
C510 BROMOFLUOROBENZENE	.83582	.92397	10.55		

RF - Response Factor from daily standard file at 50.00 ug/Kg

RF - Average Response Factor from Initial Calibration Form VI

%Diff - % Difference from original average or curve

CCC - Calibration Check Compounds (*) SPCC - System Performance Check Compounds (**)

000048

Initial Calibration Data
HSL Compounds

Case No: _____
Contractor: RESAM
Contract No: 68020026

Instrument ID: GMS-HP
Calibration Date: 09/06/95 9/5/95
AUC
9/8/95
③

C 60905
I 60905

Minimum RF for SPCC is .3 Maximum % RSD for CCC is 30X

Compound	Laboratory ID: >64410 >64409 >64406 >64405 >64404					RRT	RF	% RSD	CCC	SPCC
	RF	RF	RF	RF	RF					
	10.00	20.00	50.00	100.00	200.00					
C010 CHLOROMETHANE	.88418	.85974	.69749	.83291	.84460	.413	.82378	8.880	**	
C015 BROMOMETHANE	1.87401	1.68176	1.35527	1.24775	.95392	.490	1.42254	25.485		
C020 VINYL CHLORIDE	1.06202	1.03536	.93305	.96411	.92160	.428	.98323	6.353	*	
C025 CHLOROETHANE	.66711	.66062	.57899	.57022	.52587	.502	.60056	10.197		
C030 METHYLENE CHLORIDE	1.77653	1.55278	1.24255	1.32963	1.20858	.708	1.42201	16.829		
C035 ACETONE	.34860	.30523	.24734	.31566	.32046	.612	.30746	12.113		
C040 CARBON DISULFIDE	2.36621	2.49439	2.55028	2.76706	2.72075	.713	2.57974	6.391		
C042 TRICHLOROFLUOROMETHANE	3.57853	3.91128	3.64027	3.66605	3.21056	.540	3.60134	7.011		
C045 1,1-DICHLOROETHENE	1.22310	1.22896	1.17068	1.20584	1.14531	.633	1.19478	2.994	*	
C058 TETRAHYDROFURAN	.07884	.07838	.08282	.09252	.07935	1.012	.08238	7.201		
C050 1,1-DICHLOROETHANE	2.40916	2.57134	2.40131	2.38079	2.23779	.832	2.40008	4.935	**	
C054 1,2-DICHLOROETHENE(cis)	1.42257	1.43460	1.31367	1.37622	1.38657	.942	1.38673	3.425		
C053 1,2-DICHLOROETHENE(trans)	1.46259	1.48385	1.41906	1.45478	1.45500	.760	1.45506	1.605		
MTBE	2.83947	3.01495	2.92072	2.99057	2.55294	.738	2.86373	6.518		
C060 CHLOROFORM	3.52876	3.76132	3.44987	3.56727	3.39365	.971	3.54017	3.980	*	
C110 2-BUTANONE	.46588	.47624	.48929	.50911	.43327	.909	.47476	5.952		
C065 1,2-DICHLOROETHANE	2.79913	2.88617	2.67471	2.71510	2.50300	1.126	2.71562	5.303		
C515 1,2-DICHLOROETHANE-d4	2.58316	2.44250	2.17451	2.15953	2.03042	1.107	2.27802	9.967		
C115 1,1,1-TRICHLOROETHANE	.74860	.77458	.77671	.80959	.78949	.884	.77979	2.861		
C120 CARBON TETRACHLORIDE	.64600	.68358	.69228	.72771	.70373	.927	.69066	4.338		
C125 VINYL ACETATE	.32178	.28802	.38109	.40978	.36634	.702	.35340	13.707		
C130 BROMODICHLOROMETHANE	.75683	.78283	.80907	.88230	.88794	1.128	.82379	7.160		
C140 1,2-DICHLOROPROPANE	.33384	.32803	.31471	.33569	.33114	1.088	.32868	2.535	*	
C143 CIS-1,3-DICHLOROPROPENE	.47407	.48371	.50025	.53090	.49342	1.227	.49647	4.359		
C150 TRICHLOROETHENE	.43992	.43292	.41283	.43914	.45601	1.058	.43616	3.574		
C155 DIBROMODICHLOROMETHANE	.57091	.60072	.64138	.73867	.76896	1.444	.66413	12.991		
C160 1,1,2-TRICHLOROETHANE	.32184	.31593	.31463	.33582	.33891	1.348	.32542	3.468		
C165 BENZENE	.88691	.83596	.84460	.88335	.87884	.954	.86593	2.747		
C172 TRANS-1,3-DICHLOROPROPENE	.38395	.40997	.43506	.47418	.45328	1.320	.43129	8.224		
C176 2-CHLOROETHYLVINYLETHER	.06562	.13902	.15257	.16878	.08468	1.186	.12213	36.580		

RF - Response Factor (Subscript is amount in ug/L)

RRT - Average Relative Retention Time (RT Std/RT Istd)

RF - Average Response Factor

XRSD - Percent Relative Standard Deviation

CCC - Calibration Check Compounds (*) SPCC - System Performance Check Compounds (**)

000049

Initial Calibration Data
HSL Compounds

Case No: _____ Instrument ID: GMS-HP
Contractor: RESAM Calibration Date: 09/06/95 9/5/95
Contract No: 68020026
NR 9/8/95 (3)

C60905/I60905

Minimum RF for SPCC is .3 Maximum % RSD for CCC is 30%

Compound	Laboratory ID: >64410 >64409 >64406 >64405 >64404					RRT	RF	% RSD	CCC	SPCC
	RF	RF	RF	RF	RF					
	10.00	20.00	50.00	100.00	200.00					
C180 BROMOFORM	.42085	.44231	.50723	.62849	.67873	1.749	.53552	21.248	**	
C505 TOLUENE-d8	1.09691	1.06221	.99871	1.02343	.95996	.817	1.02824	5.198		
C205 4-METHYL-2-PENTANONE	.36255	.46332	.49966	.55594	.41990	.765	.46027	16.074		
C210 2-HEXANONE	.16853	.19390	.20861	.26860	.25607	.870	.21914	19.251		
C220 TETRACHLOROETHENE	.51976	.49819	.48957	.50736	.47019	.905	.49701	3.765		
C225 1,1,2,2-TETRACHLOROETHANE	.68463	.66242	.72142	.81269	.75625	1.146	.72748	8.188	**	
C230 TOLUENE	1.41187	1.39855	1.29163	1.36676	1.30562	.826	1.35489	3.996	*	
C235 CHLOROBENZENE	1.07497	1.03518	.96250	1.01542	.99424	1.005	1.01646	4.168	**	
C240 ETHYLBENZENE	.46875	.45061	.43401	.45974	.48122	1.013	.45887	3.905	*	
C245 STYRENE	.95544	.96532	.94162	1.00034	1.01913	1.083	.97637	3.307		
C251 XYLENE (D)	.57311	.54868	.51549	.56545	.56170	1.078	.55289	4.105		
C250 XYLENE (total)	.56963	.55155	.52172	.55673	.54691	1.023	.54931	3.205		(Conc=20.0,40.0,100.0,200
C510 BROMOFLUOROBENZENE	1.03529	.93146	.90863	.93857	.97381	1.157	.95755	5.154		

RF - Response Factor (Subscript is amount in ug/L)

RRT - Average Relative Retention Time (RT Std/RT Istd)

RF - Average Response Factor

%RSD - Percent Relative Standard Deviation

CCC - Calibration Check Compounds (*) SPCC - System Performance Check Compounds (**)

HSL Compounds

Case No: _____ Calibration Date: 09/06/95
 Contractor: RESAN _____ Time: 11:35
 Contract No: 68020026 _____ Laboratory ID: >64426
 Instrument ID: GMS-HP _____ Initial Calibration Date: 09/06/95

I60906

Minimum RF for SPCC is .3

Maximum % Diff for CCC is 25%

Compound	RF	RF	%Diff	CCC	SPCC
C010 CHLOROMETHANE	.82378	.78827	4.31	**	
C015 BROMOMETHANE	1.42254	1.33146	6.40		
C020 VINYL CHLORIDE	.98323	1.00956	2.66	*	
C025 CHLOROETHANE	.60856	.60436	.63		
C030 METHYLENE CHLORIDE	1.42201	1.29650	8.82		
C035 ACETONE	.30746	.26655	13.31		
C040 CARBON DISULFIDE	2.57974	2.61429	1.34		
C042 TRICHLOROFLUOROMETHANE	3.60134	3.82134	6.11		
C045 1,1-DICHLOROETHENE	1.19478	1.18405	.90	*	
C058 TETRAHYDROFURAN	.08238	.07424	9.89		
C050 1,1-DICHLOROETHANE	2.40008	2.41100	.45	**	
C054 1,2-DICHLOROETHENE(cis)	1.38673	1.36443	1.61		
C053 1,2-DICHLOROETHENE(trans)	1.45506	1.47078	1.08		
MTBE	2.86373	2.65823	7.18		
C060 CHLOROFORM	3.54017	3.53356	.19	*	
C110 2-BUTANONE	.47476	.37571	20.86		
C065 1,2-DICHLOROETHANE	2.71562	2.59807	4.33		
C515 1,2-DICHLOROETHANE-d4	2.27802	2.16871	4.80		
C115 1,1,1-TRICHLOROETHANE	.77979	.77500	.61		
C120 CARBON TETRACHLORIDE	.69066	.70602	2.22		
C125 VINYL ACETATE	.35340	.33021	6.56		
C130 BROMODICHLOROMETHANE	.82379	.78020	5.29		
C140 1,2-DICHLOROPROPANE	.32868	.31506	4.15	*	
C143 CIS-1,3-DICHLOROPROPENE	.49647	.48370	2.57		
C150 TRICHLOROETHENE	.43616	.41636	4.54		
C155 DIBROMOCHLOROMETHANE	.66413	.61359	7.61		
C160 1,1,2-TRICHLOROETHANE	.32542	.28853	11.34		
C165 BENZENE	.86593	.84001	2.99		
C172 TRANS-1,3-DICHLOROPROPENE	.43129	.41687	3.34		
C176 2-CHLOROETHYL VINYLETHER	.12213	.12352	1.13		
C180 BROMOFORM	.53552	.46358	13.43	**	
C505 TOLUENE-d8	1.02824	1.05556	2.66		

RF - Response Factor from daily standard file at 50.00 ug/L

RF - Average Response Factor from Initial Calibration Form VI

%Diff - % Difference from original average or curve

CCC - Calibration Check Compounds (*) SPCC - System Performance Check Compounds (**)

000051

HSL Compounds

Case No: _____ Calibration Date: 09/06/95
 Contractor: RESAM _____ Time: 11:35
 Contract No: 68020026 _____ Laboratory ID: >G4426
 Instrument ID: GMS-HP _____ Initial Calibration Date: 09/06/95

Minimum RF for SPCC is .3

Maximum % Diff for CCC is 25%

Compound	RF	RF	%Diff	CCC	SPCC
C205 4-METHYL-2-PENTANONE	.46027	.42987	6.61		
C210 2-HEXANONE	.21914	.16933	22.73		
C220 TETRACHLOROETHENE	.49701	.52370	5.37		
C225 1,1,2,2-TETRACHLOROETHANE	.72748	.67264	7.54	**	
C230 TOLUENE	1.35489	1.36826	.99	*	
C235 CHLOROBENZENE	1.01646	1.00808	.82	**	
C240 ETHYLBENZENE	.45887	.46974	2.37	*	
C245 STYRENE	.97637	.94194	3.53		
C251 XYLENE (O)	.55289	.53904	2.50		
C250 XYLENE (total)	.54931	.53650	2.33		(Conc=100.00)
CS10 BROMOFLUOROBENZENE	.95755	.93856	1.98		

RF - Response Factor from daily standard file at 50.00 ug/L

RF - Average Response Factor from Initial Calibration Form VI

%Diff - % Difference from original average or curve

CCC - Calibration Check Compounds (*) SPCC - System Performance Check Compounds (**)

Case No:

Calibration Date: 09/07/95

Contractor: RESAN

Time: 12:57

Contract No: 68020026

Laboratory ID: 264447

Instrument ID: GMS-RF

Initial Calibration Date: 09/06/95

I60907

Minimum RF for SPECC is .3

Maximum % Diff for CCC is 25%

Compound	RF	RF	%Diff	CCC	SPECC
C010 CHLOROMETHANE	.62378	.64128	22.15	**	
C015 BROMOMETHANE	1.42254	1.16998	17.75		
C020 VINYL CHLORIDE	.98323	.88501	9.99	*	
C025 CHLOROETHANE	.60056	.55445	7.68		
C030 METHYLENE CHLORIDE	1.42201	1.19006	16.31		
C035 ACETONE	.30746	.25447	17.24		
C040 CARBON DISULFIDE	2.57974	2.32636	9.82		
C042 TRICHLOROFLUOROMETHANE	3.60134	3.36786	6.48		
C045 1,1-DICHLOROETHENE	1.19478	1.11574	6.62	*	
C050 TETRAHYDROFURAN	.08238	.08188	.61		
C050 1,1-DICHLOROETHANE	2.40006	2.26671	5.56	**	
C054 1,2-DICHLOROETHENE(cis)	1.36673	1.28415	7.40		
C053 1,2-DICHLOROETHENE(trans)	1.45506	1.35797	6.67		
MTBC	2.86373	2.76597	3.41		
C060 CHLOROFORM	3.54017	3.31682	6.31	*	
C110 2-BUTANONE	.47476	.39600	16.46		
C065 1,2-DICHLOROETHANE	2.71562	2.43607	10.27		
C015 1,2-DICHLOROETHANE-d4	2.27802	2.15059	5.59		
C115 1,1,1-TRICHLOROETHANE	.77779	.74021	5.08		
C120 CARBON TETRACHLORIDE	.69066	.65904	4.58		
C125 VINYL ACETATE	.35340	.33284	5.82		
C130 BROMODICHLOROMETHANE	.82379	.76922	6.63		
C140 1,2-DICHLOROPROPANE	.32868	.31833	3.15	*	
C143 CIS-1,3-DICHLOROPROPENE	.49647	.47837	3.65		
C150 TRICHLOROETHENE	.43616	.40720	6.64		
C155 DIBROMOCHLOROMETHANE	.66413	.59132	10.96		
C160 1,1,2-TRICHLOROETHANE	.32542	.29994	7.83		
C165 BENZENE	.86593	.81929	5.39		
C172 TRANS-1,3-DICHLOROPROPENE	.43129	.41299	4.24		
C176 2-CHLOROETHYL VINYLETHER	.12213	.10648	12.82		
C180 BROMOFORM	.53552	.45129	15.73	**	
C505 TOLUENE-d8	1.02824	1.06793	3.86		

RF - Response Factor from daily standard file at 50.00 ug/L

RF - Average Response Factor from Initial Calibration Form VI

%Diff - % Difference from original average or curve

CCC - Calibration Check Compounds (*) SPECC - System Performance Check Compounds (**)

HSL Compounds

Case No: _____ Calibration Date: 09/07/95
Contractor: RESAN _____ Time: 12:57
Contract No: 68020026 _____ Laboratory ID: >G4447
Instrument ID: GMS-HP _____ Initial Calibration Date: 09/06/95

Minimum RF for SPCC is .3

Maximum % Diff for CCC is 25%

Compound	RF	RF	%Diff	CCC	SPCC
C205 4-METHYL-2-PENTANONE	.46027	.42506	7.65		
C210 2-HEXANONE	.21914	.20099	8.28		
C220 TETRACHLOROETHENE	.49701	.47980	3.46		
C225 1,1,2,2-TETRACHLOROETHANE	.72748	.67271	7.53	**	
C230 TOLUENE	1.35489	1.40560	3.74	*	
C235 CHLOROBENZENE	1.01646	.96600	4.96	**	
C240 ETHYLBENZENE	.45887	.43633	4.91	*	
C245 STYRENE	.97637	.91129	6.67		
C251 XYLENE (o)	.55289	.54544	1.35		
C250 XYLENE (total)	.54931	.56019	1.98		(Conc=100.00)
C310 BROMOFLUOROBENZENE	.95755	.91748	4.18		

RF - Response Factor from daily standard file at 50.00 ug/L

RF - Average Response Factor from Initial Calibration Form VI

%Diff - % Difference from original average or curve

CCC - Calibration Check Compounds (*) SPCC - System Performance Check Compounds (**)

000054

PACE New England

GCMS/VOA

Instr MS-HP Analyst/Date TW 8/31/75

STD Lot # V. 6314A.

FRN	Area	ID File	Tube	SAMPLE	AMT	COMMENTS	pH	A	R
7C1072	474	-	-	SFB - 35	50mg	MTH 1 95 m/2 - 24K		Y	✓
				TIME: 13:07					
				SCAN 187-188-189	- 168	- 88 2 a. + NY			
7C1073		IC0824	1	VS0050	5ml	NOT USED		N	
24			2	VS0050	↓	C-13 (MS)		Y	
25		IC0831	3	IC083195 M1		VBKCN C-6 (M2)		Y	✓
26			4	LC083195 A1	5ml	V-6392 RE 4		N	
27		LC0831	5	VS00200	↓	HEATED PURGE (LOW 200'S) CSTD 2		N	
28			6	VS00200	↓	SC0831 (LC0831 C-13 (MS)		Y	✓
29			7	VS00100	↓			Y	✓
30			8	VS00050	↓			Y	✓
31			9	VS00020	↓			Y	✓
32			10	VS00010	↓	C-13 (MS)		Y	✓
33			1	VS00010	↓			N	
34		IC0831	2	LCC083195 A2	5ml	V-6392 CSTD 3		Y	✓
35			3	45141-1 T(3) GOLF BAK 303	5ml			Y	✓
36			4	45146-3	↓			Y	✓
37			5	-3MS	↓			Y	✓
38			6	-4	↓			Y	✓
39			7	-4MS	↓			Y	✓
40			8	-2	2ml			Y	✓
41			9	-2MS	↓			Y	✓
42			10	45141-1	3ml	LR		Y	✓
43				-BAKE-					

000055

624(8240

VOLTAGE = 1100

Page 26 of 100

PACE New England

GCMS/VOA

Instr C MS-HP Analyst/Date TW 9/3/95STD Lot # V-6312

FRN	Area	ID File	Tube	SAMPLE	AMT	COMMENTS	pH	A	R
>C1052		—	—	BFB -DI	50mg			N	
53		—	—	BFB -DI	50mg			N	
54		—	—	BFB -DI	50mg			N	
				MANUAL TUNE ADJUSTED					
55		—	—	BFB -DI	50mg			N	
56		—	—	BFB -DI	50mg			N	
57		—	—			CHANGED INS PARTS ETC			
58		—	—						
59		—	—			UP VOLTAGE > 2000			
60		—	—	BFB -DI	50mg	CHANGE SPRING		Y	
61	434	—	—	BFB -DI	50mg	MTH 1 95 1/2 = 22K		Y	
				TIME: 13:44					
				SCAN: 188+189+ 190-162		88 191			
>C1062		LC0931	1	USDO50	5ml	NOT USED		N	
63			2	USDO50		C-13 (NS)		Y	
64		LC0905	3	BC090595A1		VALKCO		Y	✓
65			4	LC090595A1	5ml	V-6312		Y	✓
66			5	45205-1	5.0g			Y	✓
67			6	-2	5.3g			Y	✓
68			7	-3	5.0g			Y	✓
69			8	-4	1.1g	L.R. RE 4g		N	
70			9	-5	1.2g	RE 5g		N	
71			10	-6	1.3g	RE 5g		N	
72			1	-7	1.2g	RE 5g 10g/10g		Y	✓
73			2	-8	1.2g			Y	✓
74			3	-11	1.1g	RE 5g		N	
75			4	-12	1.2g			N	
76			5	45219-1	5.1g			Y	✓
77				BAKE					
				000055					

VOLTAGE = 1900

Instr C **MS-HP** Analyst/Date TGP alcley

STD Lot # V-6394B

FRN	Arev	ID #16	Tub#	SAMPLE	AMT	COMMENTS	pH	A	R
7C1078	474	-	-	BFD DI TIME: 12:16 SCAN: 140+191+192	5mg	MTH 1 1/2 95 - 29K		Y	✓
>C1079		LC0831	1	VSD050	5ml	NOT USED		N	
80			2	VSD050	↓	C-13 MS		Y	✓
81		LC0906	3	RC090695A1	↓	VALUCCP		Y	✓
82			4	LC090695 A1	5ml	V-C372		Y	✓
83			5	45205-4	4.0g	LR		Y	✓
84			6	-5	5.1g	↓		Y	✓
85			7	-6	5.2g	↓		Y	✓
86			8	-11	5.1g	↓		Y	✓
87			9	-12	5.0g	↓		Y	✓
88			10	-10	5.1g	↓		Y	✓
89			1	45219-2	5.2g	↓		Y	✓
90			2	-3	5.3g	↓		Y	✓
91			3	45205-(MS)	5.2g	SR.		Y	
92			4	-1MSD	↓	↓		Y	
93				-BAKE-		CHANCE OF PLUG TO 96/TS			
94			5	45205-4	5.0g	IS FAILURE		N	
95				-BAKE-					

000057

6-24
11:50
5 pt

MSG-SAM
Voltage = 2100

PACE New England

082895SEL

GCMS/VOA

Instr G MS-HP Analyst/Date NR 9/5/95 STD Lot # V6394

FRN	Acq	ID File	Tube	SAMPLE	AMT	COMMENTS	pH	A	R
>64398	#	—	—	BFB-DI	50mg	M+H1 ^M /e95 = 37K		N	
99	#	—	—	BFB-DI	50mg	M+H1 ^M /e95 =		Y	
				SCAN: 154 + 155 + 156 time: 11:52					
>64400		IG0410	1	VSTD050	5mls	Next used		N	
01			2	VSTD050		↑ vinyl chloride		N	
02		IG0905	3	B6090595A1		VBLKGE		N	
Voltage = 2075									
>64403	#338	—	—	BFB-DI	50mg	M+H1 ^M /e95 = 31k		Y	
				SCAN: 150 + 151 + 152 - 100		V-605X 1X91 + 58X			
				time: 1411					
>64404		IG0905	1	VSTD200	5mls			Y	
05			2	VSTD100		IG0905/CG0905		Y	
06			3	VSTD050				Y	
07			4	VSTD020		ITS		N	
08			5	VSTD010		ITS		N	
09			6	VSTD020	5mls			Y	
10			7	VSTD010		M2 = C32		Y	
11		IG0905	8	B6090595A1		VBLKGE		Y	
12			9	CC6090595A1				Y	
13			10	45, 193-1	1.8mls	(R624) R4H Source	72	Y	
14			11	-4	930.6s	↓ ↓ ↓	72	Y	
15			12	VSTD FREN	5mls	V-		Y	
16			13	45, 171-1	1.2mls	(R624 FREN) ^{R24.5mls} + C5-DCS		N	
17			14	-2	5mls			Y	
18			1	-3	5mls			Y	
19			2	-4	2mls			Y	
20	⓪			NR 9/5/95 (3) ^{NR} 4X				Y	
20 21	9/5/95		3	-5	1.9mls			Y	
21 22			4	-10	5mls			Y	
22 23			5	-11	5mls			Y	
23 24			—	BAKE				Y	
						000058			

PACE New England

Voltage = 2015

08289558 L

GCMS/VOA

Instr G MS-HP Analyst/Date AK 9/16/95

STD Lot # V-1037413

[illegible]

Voltage = 2075-

682895585

GCMS/VOA

Instr G MS-HP Analyst/Date ALR 9/7/95 STD Lot # V-639

[illegible]

Voltage = 2075

PACE New England

08.25.95.52L


GCMS/VOA

Instr G MS-HP Analyst/Date ALR 9/7/95 STD Lot # V-6394B


STD Lot # V-6394B

FRN	Arcv	ID File	Tub#	SAMPLE	AMT	COMMENTS	pH	A	R
>G4444	#358	-	-	BFB-DI Scan: 146+147 + 148-100 time : 1108	50mg	MIR 1 "195 = 36K V-6088' OK '88 + '91		y	
>G4446	I60905	1	VSTDO5O	5mls	No + used				
47	↓	2	VSTDO5O		+ Freon			'y	
48	I60907	3	B609079SA1	✓	VBULKGG mg=Clp			'y	✓
>G4449	I60907	4	L608079SA1	5mls					
SO		5	BV1123 ⁽³⁾	100ME	! Tol-dr same tube? as before.		N		
SI		6	45,171-1	4nls	(R624FRE)		y		✓
SZ		7	45,211-9	2050ms	(R624LW) RESoups		N		
S3		8	VSTD0Q3	5mls			y		✓
S4		9	45,189-1		(R624)	Kw	y		✓
S5		10	- 2		(R603)		y		✓
S6		11	- 3		(R624)	k2	y		✓
S7		12	- 4	✓	(R603)		y		✓
S8		13	BFB-Pinged	25mls	mSGS24				
S9		14	VSTDOTO						
G0		1	B609079SD1						
G1		2	45,234-3	✓					
G2		/	BAKE						
S8		13	BV112.3	100ME	PASSED		y		✓
S9		-	BAKE	-					
Run 9/2/95									
000061									


VOA MED SOLIDS - SURR DCE LIMIT SET 8/95



VOA MED SOLIDS - SURR TOL LIMIT SET 8/95



VOA MED SOLIDS - SURR BFB LIMIT SET 8/95



STD DEV = 6.86 MEAN = 104.4

MED SOIL BLANK # LIST

POINT / BLANK


1	MB021693A
2	MB022193B
3	MB022993B
4	MB030193A
5	MB040293A
6	MB050493A
7	MB050493A
8	MB050593A
9	MB050693A
10	MB052793B
11	MB052593A
12	MB101293A
13	MB100993A
14	MB111793A
15	MB121393A
16	MB121393A
17	MB020694A
18	MB021094A
19	MB021594A
20	MB021594A
21	MB021594A
22	MB042994B
23	MB050494A
24	MB050494A
25	B-V1005A
26	B-V1021A
27	B-V1027B
28	B-V1027C
29	B-V1034C
30	B-V1039
31	B-V1044A
32	B-V1045A
33	B-V1044B
34	B-V1050
35	B-V1066 EMS
36	B-V1066 CMS
37	B-V1070 12/30/94
38	B-V1070 1/3/95
39	B-V1085
40	B-V1084
41	B-V1085
42	B-V1084
43	B-V1087
44	B-V1085
45	B-V1084
46	B-V1084
47	B-V1117A
48	B-V1117B
49	B-V1118A
50	B-V1118D
51	B-V1118B
52	B-V1118A CMS
53	B-V1117A
54	B-V1123

000065


集川



VOA LOW SOLIDS - SURR TOL-D8 EPA SW846 LIMITS SET 9/94



VOA LOW SOLIDS - SURR BFB EPA SW846 LIMITS SET 9/94



STD DEV = 2.62 MEAN = 99.4

SW846 8240 LOW LEVEL SOLIDS

1 BC081794A
 2 BC081894A
 3 BC082594A
 4 BC082694A
 5 BC083094A
 6 BG081994A
 7 BG082394B
 8 BG082494A
 9 BG082594A
 10 BG082694C
 11 BG082994A
 12 BC083194A
 13 BC090194A
 14 BC090294A
 15 BG083094A
 16 BG083194A
 17 BG090194A
 18 BG090294A
 19 BG090694A
 20 BG090894A
 21 BC090694A
 22 BC090894B
 23 BC090994A
 24 BG090994A
 25 BG091294A
 26 BG091394A
 27 BG091494B
 28 BG091594A
 29 BG091694A
 30 BG091994A
 31 BE092094A
 32 BE092194A
 33 BC092194B
 34 BC092294B
 35 BC092394B
 36 BC092694B
 37 BG100794A
 38 BE092294A
 39 BE092394A
 40 BC092794B
 41 BC101094A
 42 BC101194A
 43 BG101194A
 44 BC101294A
 45 BG101294A
 46 BG101394A
 47 BE101894A
 48 BE101994A
 49 BG101994C
 50 BC101794A

51 BC101894A
 52 BC101994A
 53 BG102094A
 54 BG102194A
 55 BG102494A
 56 BG100594D
 57 BG100794A
 58 BG101194A
 59 BG102594A
 60 BE101794A
 61 BG101294B
 62 BG112394C
 63 BG120694C
 64 BG120794B
 65 BG120894B
 66 BG120994B
 67 BG121494A
 68 BG121594A
 69 BG121694A
 70 BG121994A
 71 BG122094B
 72 BG122394A
 73 BG122794A
 74 BG123094B
 75 ~~6~~
 76 ~~BC021095A~~
 77 ~~BC021395A~~
 78 BG040695B
 79 BG040795B
 80 BG040995A
 81 BC061395C (93, 101, 102)
 82 BC061495C (98, 99, 103)
 83 BC061595A (100, 102, 100)
 84 BC061695A (95, 102, 102)
 85 BC062195A (100, 106, 107)
 86 BC062895B2 (98, 100, 97)
 87 BC062995A1 (99, 100, 100)
 88 BC072595A1 (95, 99, 103)
 89 BC081495A1 (99, 105, 101)
 90 BC090595A1 (95, 98, 100)
 91 BC090695A1 (96, 97, 99)
 92
 93
 94
 95
 96
 97
 98
 99
 100

000069



ENVIRONMENTAL LABORATORIES

SAMPLES FROM
NEW YORK SITE

YES ☒ NO ☐

241077

CHAIN-OF-CUSTODY RECORD
Analytical Request

Client Halliburton NUS

Report To: Mark Speranza
Russa Brumback

Pace Client No. _____

Address 661 Anderson Dr
Foster Plaza #7
Pittsburgh PA 15220

Bill To: _____

Pace Project Manager _____

Phone (412) 921-7090

P.O. # / Billing Reference _____

Pace Project No. _____

Project Name / No. CTD 213

*Requested Due Date: _____

Sampled By (PRINT):

Timothy S Evans

Sampler Signature

Date Sampled

Timothy S Evans 8.30.95

ITEM NO.	SAMPLE DESCRIPTION	TIME	MATRIX	PACE NO.	NO. C	UNPPT	H ₂ SO ₄	HNO ₃	VOA											REMARKS
1	DSB 1φ - 0φ/02	1007	Soil	45205-1	1	✓														
2	DSB 1φ - 15/17	1032	Soil	-2	1	✓														
3	DSB 1φ - 6φ/62	1140	Soil	-3	1	✓														
4	DSB 11 - 0φ/02	1347	Soil	-4	1	✓														
5	DSB 11 - 3φ/32	1437	Soil	-5	1	✓														
6	DSB 11 - 6φ/62	1525	Soil	-6	1	✓														
7																				
8																				

COOLER NOS.	BAILERS	SHIPMENT METHOD		ITEM NUMBER	RELINQUISHED BY / AFFILIATION	ACCEPTED BY / AFFILIATION	DATE	TIME
		OUT DATE	RETURNED DATE					
1				1-6	Timothy S Evans HNS S Brumback/Pace		9/1/95	0930
Additional Comments					8.31.95 1600			
FedEx AB# 3461991101								
1 of 2								

SEE REVERSE SIDE FOR INSTRUCTIONS

ORIGINAL



SAMPLES FROM
NEW YORK SITE

YES ☒

NO ☐

2 1078

ENVIRONMENTAL LABORATORIES

CHAIN-OF-CUSTODY RECORD
Analytical Request

Client Halliburton NUS

Report To: Mark Speranza

Pace Client No. _____

Address 661 Anderson Dr
Foster Plaza #7
Pittsburgh PA 15211

Bill To: _____

Pace Project Manager _____

Phone (412) 921-7090

P.O. # / Billing Reference _____

Pace Project No. _____

Project Name / No. CTO 213

*Requested Due Date: _____

Sampled By (PRINT) [Signature] 8.31.95
Sampler Signature Date Sampled

TIMOTHY S EVANS

ITEM NO.	SAMPLE DESCRIPTION	TIME	MATRIX	PACE NO.	NO. OF CONTAINERS	PRESERVATIVES					ANALYSES REQUEST	REMARKS
						UNPRESERVED	H ₂ SO ₄	HNO ₃	VOC			
1	DSB13 - $\phi\phi/\phi2$	0903	Soil	45205-7	1	✓					✓	
2	DSB13 - 4 ϕ /42	0955	Soil	-8	1	✓					✓	
3	DSB13 - 55/57	1023	Soil	-9	1	✓					✓	
4	DSB12 - $\phi\phi/\phi2$	1235	Soil	-10	1	✓					✓	
5	DSB12 - 4 ϕ /42	1330	Soil	-11	1	✓					✓	
6	DSB12 - 6 ϕ /62	1402	Soil	-12	1	✓					✓	
7												
8												

COOLER NOS.	BAILERS	SHIPMENT METHOD		ITEM NUMBER	RELINQUISHED BY / AFFILIATION	ACCEPTED BY / AFFILIATION	DATE	TIME
1		OUT DATE	RETURNED DATE					

Additional Comments FedEx AB# 3461991161

1-6 [Signature] / HUS Shannon/pace 9/1/95 0930
8.31.95 1600

000071

2 of 2

Final Page

SEE REVERSE SIDE FOR INSTRUCTIONS

ORIGINAL

September 18, 1995

Halliburton NUS Corporation
Mr. Mark Speranza
661 Andersen Drive
Pittsburgh, PA 15220

SAMPLE DELIVERY GROUP NARRATIVE

Project: NWIRP Bethpage, CTO 0213
Laboratory: PACE New England, Inc. of Hampton, NH

Lab Numbers: 45219

Protocol: SW846 Methodologies with NEESA Level C package and LOTUS diskette.


Sample Receipt: Samples were received at PACE, Inc. on 9/5/95. Laboratory sample numbers were assigned for test parameters as listed on the sample table which follows this narrative. Sample shipments were checked for custody seal integrity and cooler temperature. Samples were checked for appropriate preservation and accuracy against the Chains-of-Custody provided. Other than the exceptions noted below, samples were received between 2-6° C and in good condition. In addition, Sample Receipt Condition Reports can be found with the Chains-of-Custody. No spike sample was submitted for analysis.


Shipment received 9/5/95 (45219): One cooler was received with one Chain-of-Custody form. The cooler was received without a temperature blank present. The samples were packed in ice with the ice melted upon receipt at PACE. Custody seals were present and intact.

Volatile Organic Analysis: Samples were analyzed within a project specific holding time of 7 days from sampling as directed by Ms. Kelly Johnson. The method 8240 blank "BC060595A1" and "BC060695A1" contained low levels of methylene chloride. The sample results for this analyte should be used with due consideration.

Statement of Compliancy and Data Authorization

I certify that this data package is in compliance with the terms and conditions of the contract, both technically and for completeness, for other than the conditions detailed above. Release of the data contained in this hardcopy data package and in the computer-readable data submitted on diskette has been authorized by the Laboratory Manager or his designee, as verified by the following signature.


Richard Wellman, Operations Manager
PACE Incorporated, New England-New Hampshire


September 18, 1995



SAMPLE RECEIPT CONDITION REPORT

Tel. (603) 926-7777

FAX (603) 926-7939

PAGE 1 of 1
COOLER 1 of 1
COC# 241079
SDG#
CASE#CLIENT HNVSDATE/TIME RECEIVED 9/5/95 0930LIMS ENTRY BY SBDELIVERED BY fedxTRANSCRIPTION REVIEW BY SBRECEIVED BY SBLIMS REVIEW BY/PM SB

	NA	YES	EXCEPTION	COMMENT	RESOLUTION
1. CUSTODY SEALS PRESENT/INTACT	☐	☒	☐		
2. CHAIN OF CUSTODY PRESENT IN THIS COOLER	☐	☒	☐		
3. CHAIN OF CUSTODY SIGNED	☐	☒	☐		
4. CHAIN OF CUSTODY MATCHES SAMPLES	☐	☐	☒	<u>See Below</u>	
5. SAMPLES RECEIVED AT 2° - 6° C <u>Ice</u> /Ice Packs Present? <u>Y</u> or N	☐	☐	☒	<u>No temp b/k. Ice completely melted. Samples at room temp.</u>	
6. VOLATILES FREE OF HEAD SPACE	☐	☒	☐		
7. TRIP BLANK PRESENT IN THIS COOLER	☐	☐	☒	<u>None Present w/soil samples.</u>	
8. PROPER SAMPLE CONTAINERS AND VOLUME	☐	☒	☐		
9. SAMPLES WITHIN HOLD TIME	☐	☒	☐		
10. SAMPLES PROPERLY PRESERVED	☐	☒	☐		
11. ANALYTICAL PROGRAMS (circle one) <u>COMMERCIAL</u> CLP EPA-CLP NYASP NJ ISRA <u>NEESA</u> AFCEE Other					
12. NUMBER OF PACE FILTRATIONS: _____					
13. CORRECTIVE ACTIONS REPORT # _____					

Log-in Notes:

Sample DSB14 - 05/07 has DSB14-00/02 on jar label.
COC is correct per Tim Evans

Sampled 9/1/95. 7 day project H.T.

SW846/neesa-c

CLIENT AUTHORIZATION SIGNATURE _____ DATE _____ 00000002

SAMPLE TABLE

CLIENT ID.	MATRIX	PAGE #	PARAMETERS
-----	-----	-----	-----
DSB14-05/07	SOLID	45219-001	GC/MS VOA
DSB14-40/42	SOLID	45219-002	GC/MS VOA
DSB14-50/52	SOLID	45219-003	GC/MS VOA

~~SDG:~~ 45219

[illegible]

Manual integrations were performed as required to correct faulty integrations made by the automated software. The manual integrations began and ended at the point where the peak intersected the baseline (unless otherwise indicated), in order that the entire peak and only the peak would be integrated. Hardcopies of the manually-integrated peaks have been provided with the data.

9/8/95
Date

Laboratory number: 45219-001
Sample Designation: DSB14-05/07
Date Analyzed: 09/06/95
Matrix: SOLID

Instrument File Name: >C1076

Results are expressed on a dry (103 degrees C) basis.
Moisture content was 3 % , elevating the reporting limits
by a factor of 1.03 .

VOLATILE ORGANICS	CONCENTRATION (ug/Kg)	REPORTING LIMIT (ug/Kg)
Chloromethane	BDL	10
Bromomethane	BDL	10
Vinyl chloride	BDL	10
Chloroethane	BDL	5
Methylene chloride	BDL	10
Acetone	BDL	25
Carbon disulfide	BDL	5
Tetrahydrofuran	BDL	25
Trichlorofluoromethane	BDL	5
1,1-Dichloroethene	BDL	5
1,1-Dichloroethane	BDL	5
1,2-Dichloroethene (total)	BDL	5
Chloroform	BDL	5
1,2-Dichloroethane	BDL	5
2-Butanone	BDL	25
1,1,1-Trichloroethane	BDL	5
Carbon Tetrachloride	BDL	5
Vinyl acetate	BDL	10
Bromodichloromethane	BDL	5
1,2-Dichloropropane	BDL	5
cis-1,3-Dichloropropene	BDL	5
trans-1,3-Dichloropropene	BDL	5
Trichloroethene	BDL	5
Dibromochloromethane	BDL	5
1,1,2-Trichloroethane	BDL	5
Benzene	BDL	5
2-Chloroethyl vinyl ether	BDL	5
Bromoform	BDL	5
4-Methyl-2-Pentanone	BDL	25
2-Hexanone	BDL	25
Tetrachloroethene	BDL	5
1,1,2,2-Tetrachloroethane	BDL	5
Toluene	BDL	5
Chlorobenzene	BDL	5
Ethylbenzene	BDL	5
Styrene	BDL	5
Xylene (total)	BDL	5

METHOD REFERENCE: EPA SW 846, 3rd Edition
METHOD 8240

BDL - Below reporting limit

J - Probable presence below listed detection limit



0000005

Laboratory number: 45219-002
Sample Designation: DSB14-40/42
Date Analyzed: 09/06/95
Matrix: SOLID

Instrument File Name: >C1089

Results are expressed on a dry (103 degrees C) basis.
Moisture content was 5 % , elevating the reporting limits
by a factor of 1.05 .

VOLATILE ORGANICS	CONCENTRATION (ug/Kg)	REPORTING LIMIT (ug/Kg)
Chloromethane	BDL	10
Bromomethane	BDL	10
Vinyl chloride	BDL	10
Chloroethane	BDL	5
Methylene chloride	8 JB	10
Acetone	BDL	25
Carbon disulfide	BDL	5
Tetrahydrofuran	BDL	25
Trichlorofluoromethane	BDL	5
1,1-Dichloroethene	BDL	5
1,1-Dichloroethane	BDL	5
1,2-Dichloroethene (total)	BDL	5
Chloroform	BDL	5
1,2-Dichloroethane	BDL	5
2-Butanone	BDL	25
1,1,1-Trichloroethane	BDL	5
Carbon Tetrachloride	BDL	5
Vinyl acetate	BDL	10
Bromodichloromethane	BDL	5
1,2-Dichloropropane	BDL	5
cis-1,3-Dichloropropene	BDL	5
trans-1,3-Dichloropropene	BDL	5
Trichloroethene	BDL	5
Dibromochloromethane	BDL	5
1,1,2-Trichloroethane	BDL	5
Benzene	BDL	5
2-Chloroethyl vinyl ether	BDL	5
Bromoform	BDL	5
4-Methyl-2-Pentanone	BDL	25
2-Hexanone	BDL	25
Tetrachloroethene	BDL	5
1,1,2,2-Tetrachloroethane	BDL	5
Toluene	BDL	5
Chlorobenzene	BDL	5
Ethylbenzene	BDL	5
Styrene	BDL	5
Xylene (total)	BDL	5

METHOD REFERENCE: EPA SW 846, 3rd Edition
METHOD 8240

BDL = Below reporting limit
J = Probable presence below listed detection limit



0000006

Laboratory number: 45219-003
Sample Designation: DSB14-50/52
Date Analyzed: 09/06/95
Matrix: SOLID

Instrument File Name: >C1090

Results are expressed on a dry (103 degrees C) basis.
Moisture content was 10 % , elevating the reporting limits
by a factor of 1.11 .

VOLATILE ORGANICS	CONCENTRATION (ug/Kg)	REPORTING LIMIT (ug/Kg)
Chloromethane	BDL	10
Bromomethane	BDL	10
Vinyl chloride	BDL	10
Chloroethane	BDL	5
Methylene chloride	8 JB	10
Acetone	BDL	26
Carbon disulfide	BDL	5
Tetrahydrofuran	BDL	26
Trichlorofluoromethane	BDL	5
1,1-Dichloroethene	BDL	5
1,1-Dichloroethane	BDL	5
1,2-Dichloroethene (total)	BDL	5
Chloroform	BDL	5
1,2-Dichloroethane	BDL	5
2-Butanone	BDL	26
1,1,1-Trichloroethane	BDL	5
Carbon Tetrachloride	BDL	5
Vinyl acetate	BDL	10
Bromodichloromethane	BDL	5
1,2-Dichloropropane	BDL	5
cis-1,3-Dichloropropene	BDL	5
trans-1,3-Dichloropropene	BDL	5
Trichloroethene	BDL	5
Dibromochloromethane	BDL	5
1,1,2-Trichloroethane	BDL	5
Benzene	BDL	5
2-Chloroethyl vinyl ether	BDL	5
Bromoform	BDL	5
4-Methyl-2-Pentanone	BDL	26
2-Hexanone	BDL	26
Tetrachloroethene	BDL	5
1,1,2,2-Tetrachloroethane	BDL	5
Toluene	BDL	5
Chlorobenzene	BDL	5
Ethylbenzene	BDL	5
Styrene	BDL	5
Xylene (total)	BDL	5

METHOD REFERENCE: EPA SW 846, 3rd Edition
METHOD 8240

BDL = Below reporting limit
J = Probable presence below listed detection limit



0000007

Lab No. : 45219

[illegible]

S1	(TOL)	= Toluene-d8	86	-	114
S2	(BFB)	= Bromofluorobenzene	72	-	132
S3	(DCE)	= 1,2-Dichloroethane-d4	70	-	138

```
# Column to be used to flag recovery values with an asterisk
* Values outside of designated QC limits
D Surrogates diluted out
```



0000008

Laboratory number: BC060595A1
 Sample Designation: LABORATORY BLANK
 Date Analyzed: 06/05/95
 Matrix: SOLID

VOLATILE ORGANICS	CONCENTRATION (ug/Kg)	REPORTING LIMIT (ug/Kg)
Chloromethane	BDL	10
Bromomethane	BDL	10
Vinyl chloride	BDL	10
Chloroethane	BDL	5
Methylene chloride	4 J	10
Acetone	BDL	25
Carbon disulfide	BDL	5
1,1-Dichloroethene	BDL	5
Tetrahydrofuran	BDL	25
1,1-Dichloroethane	BDL	5
1,2-Dichloroethene (total)	BDL	5
Chloroform	BDL	5
Methyl ethyl ketone	BDL	25
1,2-Dichloroethane	BDL	5
1,1,1-Trichloroethane	BDL	5
Carbon Tetrachloride	BDL	5
Vinyl acetate	BDL	10
Bromodichloromethane	BDL	5
cis-1,3-Dichloropropene	BDL	5
trans-1,3-Dichloropropene	BDL	5
Trichloroethene	BDL	5
Benzene	BDL	5
Dibromochloromethane	BDL	5
1,1,2-Trichloroethane	BDL	5
1,2-Dichloropropane	BDL	5
2-Chloroethyl vinyl ether	BDL	5
Bromoform	BDL	5
Methyl isobutyl ketone	BDL	25
2-Hexanone	BDL	25
1,1,2,2-Tetrachloroethane	BDL	5
Tetrachloroethene	BDL	5
Toluene	BDL	5
Chlorobenzene	BDL	5
Ethylbenzene	BDL	5
m-Xylene	BDL	5
o,p-Xylene	BDL	5
Styrene	BDL	5

METHOD REFERENCE: EPA SW 846 2ND EDITION
 METHOD 8240

BDL = Below detection limit

J = Probable presence below listed detection limit.



0000009

Laboratory number: BC060695A1
Sample Designation: LABORATORY BLANK
Date Analyzed: 06/06/95
Matrix: SOLID

VOLATILE ORGANICS	CONCENTRATION (ug/Kg)	REPORTING LIMIT (ug/Kg)
Chloromethane	BDL	10
Bromomethane	BDL	10
Vinyl chloride	BDL	10
Chloroethane	BDL	5
Methylene chloride	3 J	10
Acetone	BDL	25
Carbon disulfide	BDL	5
1,1-Dichloroethene	BDL	5
Tetrahydrofuran	BDL	25
1,1-Dichloroethane	BDL	5
1,2-Dichloroethene (total)	BDL	5
Chloroform	BDL	5
Methyl ethyl ketone	BDL	25
1,2-Dichloroethane	BDL	5
1,1,1-Trichloroethane	BDL	5
Carbon Tetrachloride	BDL	5
Vinyl acetate	BDL	10
Bromodichloromethane	BDL	5
cis-1,3-Dichloropropene	BDL	5
trans-1,3-Dichloropropene	BDL	5
Trichloroethene	BDL	5
Benzene	BDL	5
Dibromochloromethane	BDL	5
1,1,2-Trichloroethane	BDL	5
1,2-Dichloropropane	BDL	5
2-Chloroethyl vinyl ether	BDL	5
Bromoform	BDL	5
Methyl isobutyl ketone	BDL	25
2-Hexanone	BDL	25
1,1,2,2-Tetrachloroethane	BDL	5
Tetrachloroethene	BDL	5
Toluene	BDL	5
Chlorobenzene	BDL	5
Ethylbenzene	BDL	5
m-Xylene	BDL	5
o,p-Xylene	BDL	5
Styrene	BDL	5

METHOD REFERENCE: EPA SW 846 2ND EDITION
METHOD 8240

BDL = Below detection limit

J = Probable presence below listed detection limit.



0000010

MATRIX SPIKE RECOVERY
VOLATILE ORGANIC COMPOUNDS

Laboratory Number: LCC090595A1
Sample Designation: LABORATORY CONTROL SAMPLE
Date Analyzed: 09/05/95
Matrix: LOW SOIL

COMPOUND	ug/Kg SAMPLE	ug/Kg SPIKE	ug/kg FOUND	%REC- OVERY
1,1-DICHLOROETHENE	0	50	51	101
TRICHLOROETHYLENE	0	50	47	93
BENZENE	0	50	43	87
TOLUENE	0	50	47	93
CHLOROBENZENE	0	50	50	101

METHOD REFERENCE: EPA SW 846, 3RD EDITION
METHOD 8240

MATRIX SPIKE RECOVERY
VOLATILE ORGANIC COMPOUNDS

Laboratory Number: LCC090695A1
Sample Designation: LABORATORY CONTROL SAMPLE
Date Analyzed: 09/06/95
Matrix: LOW SOIL

COMPOUND	ug/Kg SAMPLE	ug/Kg SPIKE	ug/kg FOUND	%REC- OVERY
1,1-DICHLOROETHENE	0	50	46	93
TRICHLOROETHYLENE	0	50	46	91
BENZENE	0	50	44	87
TOLUENE	0	50	47	94
CHLOROBENZENE	0	50	49	98

METHOD REFERENCE: EPA SW 846, 3RD EDITION
METHOD 8240

5A
VOLATILE ORGANIC GC/MS TUNING AND MASS
CALIBRATION - BROMOFLUOROBENZENE (BFB)

Lab Name: PACE New England

Project: BETHPAGE

Lab File ID: >C1022

BFB Injection Date: 08/31/95

Instrument ID: CMS

BFB Injection Time: 13:07

ION ABUNDANCE CRITERIA for C1022 are reported on a separate sheet.

THIS TUNE APPLIES TO THE FOLLOWING SAMPLES, MS, MSD, BLANKS, AND STANDARDS

CLIENT I.D.	LAB SAMPLE ID	LAB FILE ID	DATE ANALYZED	DATE ANALYZED
-----	-----	-----	-----	-----
VSTD200	VSTD200	C1028	08/31/95	16:55
VSTD100	VSTD100	C1029	08/31/95	17:30
VSTD050	VSTD050	C1030	08/31/95	18:05
VSTD020	VSTD020	C1031	08/31/95	18:39
VSTD010	VSTD010	C1032	08/31/95	19:14

GC/MS PERFORMANCE STANDARD

Bromofluorobenzene (BFB) '88

m/z	Ion Abundance Criteria	% Relative Abundance Base Peak	% Relative Abundance Appropriate Peak	Status
50	15-40% of mass 95	20.56	20.56	Ok
75	30-60% of mass 95	46.25	46.25	Ok
95	Base peak, 100% relative abundance	100.00	100.00	Ok
96	5-9% of mass 95	8.63	8.63	Ok
173	Less than 2% of mass 174	0.00	0.00	Ok
174	Greater than 50% of mass 95	85.93	85.93	Ok
175	5-9% of mass 174	6.79	7.90	Ok
176	95-101% of mass 174	81.82	95.22	Ok
177	5-9% of mass 176	6.98	8.53	Ok

Injection Date: 08/31/95

Injection Time: 13:07

Data File: >C1022



Scan: 188

THIS IS THE RESULT OF AVERAGING
AND SUBTRACTING BACKGROUND SCAN

187.00
168.00

188.00

189.00



0000014

5A
VOLATILE ORGANIC GC/MS TUNING AND MASS
CALIBRATION - BROMOFLUOROBENZENE (BFB)

Lab Name: PACE New England

Project: BETHPAGE

Lab File ID: >C1061

BFB Injection Date: 09/05/95

Instrument ID: CMS

BFB Injection Time: 13:44

ION ABUNDANCE CRITERIA for C1061 are reported on a separate sheet.

THIS TUNE APPLIES TO THE FOLLOWING SAMPLES, MS, MSD, BLANKS, AND STANDARDS

CLIENT I.D.	LAB SAMPLE ID	LAB FILE ID	DATE ANALYZED	DATE ANALYZED
-----	-----	-----	-----	-----
VSTD050	VSTD050	C1063	09/05/95	14:41
BC090595A1	90182-089	C1064	09/05/95	15:16
LCC090595A1	90182-089MS	C1065	09/05/95	16:02
DSB14-05/07	45219-001	C1076	09/06/95	00:20



GC/MS PERFORMANCE STANDARD

Bromofluorobenzene (BFB) '88

m/z	Ion Abundance Criteria	% Relative Abundance		Status
		Base Peak	Appropriate Peak	
50	15-40% of mass 95	20.35	20.35	Ok
75	30-60% of mass 95	52.23	52.23	Ok
95	Base peak, 100% relative abundance	100.00	100.00	Ok
96	5-9% of mass 95	7.73	7.73	Ok
173	Less than 2% of mass 174	0.00	0.00	Ok
174	Greater than 50% of mass 95	84.87	84.87	Ok
175	5-9% of mass 174	4.86	5.73	Ok
176	95-101% of mass 174	83.04	97.84	Ok
177	5-9% of mass 176	7.27	8.75	Ok

Injection Date: 09/05/95
Injection Time: 13:44
Data File: >C1061
Scan: 189

THIS IS THE RESULT OF AVERAGING 188.00 189.00 190.00
AND SUBTRACTING BACKGROUND SCAN 169.00



0000016

5A
VOLATILE ORGANIC GC/MS TUNING AND MASS
CALIBRATION - BROMOFLUOROBENZENE (BFB)

Lab Name: PACE New England

Project: BETHPAGE

Lab File ID: >C1078

BFB Injection Date: 09/06/95

Instrument ID: CMS

BFB Injection Time: 12:16

ION ABUNDANCE CRITERIA for C1078 are reported on a separate sheet.

THIS TUNE APPLIES TO THE FOLLOWING SAMPLES, MS, MSD, BLANKS, AND STANDARDS

CLIENT I.D.	LAB SAMPLE ID	LAB FILE ID	DATE ANALYZED	DATE ANALYZED
-----	-----	-----	-----	-----
VSTD050	VSTD050	C1080	09/06/95	13:13
BC090695A1	90182-090	C1081	09/06/95	13:48
LCC090695A1	90182-090MS	C1082	09/06/95	14:33
DSB14-40/42	45219-002	C1089	09/06/95	21:02
DSB14-50/52	45219-003	C1090	09/06/95	21:52



0000017

GC/MS PERFORMANCE STANDARD

Bromofluorobenzene (BFB) '88

m/z	Ion Abundance Criteria	% Relative Abundance		Status
		Base Peak	Appropriate Peak	
50	15-40% of mass 95	17.75	17.75	Ok
75	30-60% of mass 95	49.20	49.20	Ok
95	Base peak, 100% relative abundance	100.00	100.00	Ok
96	5-9% of mass 95	6.80	6.80	Ok
173	Less than 2% of mass 174	0.00	0.00	Ok
174	Greater than 50% of mass 95	87.57	87.57	Ok
175	5-9% of mass 174	5.15	5.89	Ok
176	95-101% of mass 174	85.51	97.65	Ok
177	5-9% of mass 176	7.40	8.66	Ok

Injection Date: 09/06/95



Injection Time: 12:16

Data File: >C1078

Scan: 191

THIS IS THE RESULT OF AVERAGING 190.00 191.00 192.00
AND SUBTRACTING BACKGROUND SCAN 171.00

9/8/95



0000018

8A
VOLATILE INTERNAL STANDARD AREA SUMMARY

Lab Name: PACE New England

Project: BETHPAGE

Lab File ID (Standard): >C1063

Date Analyzed: 09/05/95

Instrument ID: CMS

Time Analyzed: 14:41

	IS1 (BCM)		IS2 (DFB)		IS3 (CBZ)	
	AREA #	RT #	AREA #	RT #	AREA #	RT #
=====	=====	=====	=====	=====	=====	=====
12 HOUR STD	63686	7.34	249452	18.03	203654	22.84
=====	=====	=====	=====	=====	=====	=====
UPPER LIMIT	127372	7.84	498904	18.53	407308	23.34
=====	=====	=====	=====	=====	=====	=====
LOWER LIMIT	31843	6.84	124726	17.53	101827	22.34
=====	=====	=====	=====	=====	=====	=====
CLIENT I.D.						
=====	=====	=====	=====	=====	=====	=====
BC090595A1	62832	7.36	243480	18.04	202036	22.84
LCC090595A1	69526	7.32	270924	18.02	220724	22.86
DSB14-05/07	68998	7.48	270256	18.07	224988	22.88

IS1 (BCM) = Bromochloromethane UPPER LIMIT = + 100%
 IS2 (DFB) = 1,4-Difluorobenzene of internal standard area.
 IS3 (CBZ) = Chlorobenzene LOWER LIMIT = - 50%

Column used to flag internal standard area values outside of
 UPPER and LOWER LIMIT with an asterisk

VOLATILE INTERNAL STANDARD AREA SUMMARY

Lab Name: PACE New England

Project: BETHPAGE

Lab File ID (Standard): >C1080

Date Analyzed: 09/06/95

Instrument ID: CMS

Time Analyzed: 13:13

	IS1 (BCM)		IS2 (DFB)		IS3 (CBZ)	
	AREA #	RT #	AREA #	RT #	AREA #	RT #
12 HOUR STD	85898	7.35	318580	17.99	277456	22.83
UPPER LIMIT	171796	7.85	637160	18.49	554912	23.33
LOWER LIMIT	42949	6.85	159290	17.49	138728	22.33
CLIENT I.D.						
BC090695A1	83310	7.37	314310	18.00	267404	22.86
LCC090695A1	83844	7.39	314727	18.00	262106	22.88
DSB14-40/42	63310	7.38	240851	18.04	199154	22.89
DSB14-50/52	71966	7.32	277542	18.04	235748	22.85

IS1 (BCM) = Bromochloromethane
 IS2 (DFB) = 1,4-Difluorobenzene
 IS3 (CBZ) = Chlorobenzene

UPPER LIMIT = + 100%
 of internal standard area.
 LOWER LIMIT = - 50%

Column used to flag internal standard area values outside of
 UPPER and LOWER LIMIT with an asterisk

SC0831 / LC0831

TW
9/11/95Initial Calibration Data
HSL Compounds

Case No:

Instrument ID: CMS-HP

Contractor: RESAM

Calibration Date: 08/01/95

Contract No: 68020026

083195

③ TW

Minimum RF for SPCC is .30

Maximum X RSD for CCC is 30%

Compound	Laboratory ID: >C1032 >C1031 >C1030 >C1029 >C1028					RRT	RF	X RSD	CCC	SPCC
	RF	RF	RF	RF	RF					
	10.00	20.00	50.00	100.00	200.00					
C010 CHLOROMETHANE	.46763	.47577	.36171	.32007	.35693	.209	.39642	17.819	**	✓
C015 BROMOMETHANE	1.17488	1.26312	1.06945	1.05207	1.15280	.287	1.14246	7.481		
C020 VINYL CHLORIDE	.85723	.87690	.81362	.74692	.87721	.357	.83438	6.631	*	✓
C025 CHLOROETHANE	.46232	.54392	.49169	.47947	.54935	.439	.50535	7.748		
C030 METHYLENE CHLORIDE	2.19924	1.63239	1.15780	1.06405	1.11119	.624	1.43293	33.872		
C035 ACETONE	.85161	.63608	.45944	.41946	.41366	.756	.55605	33.887		
C040 CARBON DISULFIDE	2.31313	2.35907	2.05976	1.99473	2.34228	.855	2.21379	7.798		
C042 TRICHLOROFLUOROMETHANE	2.48403	2.43315	2.25633	2.09547	2.51744	.908	2.35728	7.535		
C045 1,1-DICHLOROETHENE	.94318	.98063	.91438	.84931	1.00126	.997	.93775	6.369	*	✓
C058 TETRAHYDROFURAN	.17106	.17957	.15996	.15837	.15310	1.154	.16441	6.510		
C050 1,1-DICHLOROETHANE	2.03857	2.01826	1.76173	1.74080	1.92570	1.138	1.89701	7.374	**	✓
C053 1,2-DICHLOROETHENE (total)	.91402	1.11611	.99562	.98137	1.09662	1.241	1.02075	8.258		(Conc=20.0, 40.0, 100.0, 200
C060 CHLOROFORM	2.33560	2.69706	2.39838	2.37748	2.61724	1.277	2.48515	6.483	*	✓
C110 2-BUTANONE	1.20181	1.16612	.91318	.86723	.89908	1.434	1.00148	16.808		
C065 1,2-DICHLOROETHANE	1.79133	1.84748	1.63573	1.62509	1.71709	1.397	1.72335	5.611		
MIBK	2.34098	2.57509	2.08308	2.10044	2.06032	1.561	2.23198	9.982		
C515 1,2-DICHLOROETHANE-d4	1.05607	1.73800	1.16489	1.27859	1.50126	1.383	1.34776	20.291		
C115 1,1,1-TRICHLOROETHANE	.60252	.60827	.55422	.51984	.63875	.636	.58472	8.081		
C120 CARBON TETRACHLORIDE	.53983	.53752	.50913	.47799	.59072	.657	.53104	7.864		
C125 VINYL ACETATE	.78683	.80853	.64410	.66794	.69662	.685	.72080	10.128		
C130 BROMODICHLOROMETHANE	.83209	.85322	.73630	.73184	.84131	.677	.79895	7.475		
C140 1,2-DICHLOROPROPANE	.34939	.36698	.31842	.30021	.33195	.767	.33339	7.809	*	✓
C143 CIS-1,3-DICHLOROPROPENE	.54570	.60788	.52951	.50110	.56224	.779	.54928	7.240		
C150 TRICHLOROETHENE	.42172	.44504	.38913	.36968	.41594	.815	.40830	7.190		
C155 DIBROMODICHLOROMETHANE	.66968	.75967	.65723	.64338	.72563	.830	.69112	7.154		
C160 1,1,2-TRICHLOROETHANE	.37814	.42059	.35094	.32740	.36041	.844	.36750	9.489		
C165 BENZENE	.78322	.84693	.73497	.70810	.79945	.856	.77453	7.047		
C172 TRANS-1,3-DICHLOROPROPENE	.48499	.55231	.48195	.46238	.51095	.852	.49852	6.957		
C176 2-CHLOROETHYL VINYL ETHER	.19253	.18379	.17714	.18595	.20643	.919	.18917	5.870		
C180 BROMODIFORM	.50373	.57870	.50054	.50231	.56201	.981	.52946	7.142	**	✓

RF - Response Factor (Subscript is amount in ug/Kg)

RRT - Average Relative Retention Time (RT Std/RT Istd)

RF - Average Response Factor

XRSD - Percent Relative Standard Deviation

CCC - Calibration Check Compounds (*) SPCC - System Performance Check Compounds (**)

0000021

Initial Calibration Data
HSL Compounds

Case No: _____ Instrument ID: CMS-HP
Contractor: RESAM Calibration Date: 09/01/95
Contract No: 68020026

Minimum RF for SPCC is .30 Maximum % RSD for CCC is 30%

Compound	Laboratory ID: >C1032 >C1031 >C1030 >C1029 >C1028					RR1	RF	% RSD	CCC	SPEC
	RF	RF	RF	RF	RF					
	10.00	20.00	50.00	100.00	200.00					
C505 TOLUENE-d8	.71650	1.07788	.73729	.77261	.93100	.953	.84705	18.190		
C205 4-METHYL-2-PENTANONE	.82257	.81170	.65178	.64867	.65534	.818	.71801	12.618		
C210 2-HEXANONE	.72633	.61534	.52162	.50467	.48353	.891	.57030	17.661		
C220 TETRACHLOROETHENE	.42697	.40162	.37565	.34880	.40835	.893	.39228	7.770		
C225 1,1,2,2-TETRACHLOROETHANE	.97846	1.01699	.85729	.83387	.88008	.881	.91334	8.750	**	/
C230 TOLUENE	1.37299	1.27557	1.09803	1.02495	1.14467	.961	1.18324	11.827	*	/
C235 CHLOROBENZENE	1.00980	.97789	.85743	.81547	.89260	1.006	.91064	8.950	**	/
C240 ETHYLBENZENE	.49943	.47791	.41320	.39264	.45719	1.089	.44807	9.918	*	/
C245 STYRENE	1.05884	1.02502	.87025	.85975	.94908	1.211	.95259	9.382		
C251 XYLENE	.54416	.54445	.47309	.42934	.49776	1.218	.49776	9.854		
C250 XYLENE (total)	.58592	.57284	.49423	.46112	.51907	1.244	.52663	9.980		
C510 BROMOFLUOROBENZENE	.78323	1.06717	.71560	.73315	.87997	1.164	.83582	17.258		

(Conc=20.0,40.0,100.0,200)

RF - Response Factor (Subscript is amount in ug/Kg)

RR1 - Average Relative Retention Time (RT Std/RT Istd)

RF - Average Response Factor

%RSD - Percent Relative Standard Deviation

CCC - Calibration Check Compounds (*) SPCC - System Performance Check Compounds (**)

0000022

Continuing Calibration Check
HSL Compounds

LC0905

Case No: Calibration Date: 09/05/95

Contractor: RESAM Time: 14:41

Contract No: 68020026 Laboratory ID: >C1063

Instrument ID: CMS-HP Initial Calibration Date: ~~09/01/95~~ 8/3/95

Minimum RF for SPCC is .30

Maximum % Diff for CCC is 25%

Compound	RF	RF	%Diff	CCC	SPCC
C010 CHLOROMETHANE	.39642	.42531	7.29	**	✓
C015 BROMOMETHANE	1.14246	1.21529	6.37		
C020 VINYL CHLORIDE	.83438	.79379	4.87	*	✓
C025 CHLOROETHANE	.50535	.51002	.92		
C030 METHYLENE CHLORIDE	1.43293	1.25026	12.75		
C035 ACETONE	.55605	.43377	21.99		
C040 CARBON DISULFIDE	2.21379	2.31110	4.40		
C042 TRICHLOROFLUOROMETHANE	2.35728	2.61929	11.11		
C045 1,1-DICHLOROETHENE	.93775	.98771	5.33	*	✓
C050 TETRAHYDROFURAN	.16441	.19282	17.28		
C050 1,1-DICHLOROETHANE	1.89701	1.95297	2.95	**	✓
C053 1,2-DICHLOROETHENE (total)	1.02075	1.15666	13.32		(Conc=100.00)
C060 CHLOROFORM	2.48515	2.74376	10.41	*	✓
C110 2-BUTANONE	1.00148	.96233	3.91		
C065 1,2-DICHLOROETHANE	1.72335	1.93920	12.53		
MTBE	2.23198	2.65457	18.93		(Conc=50.00)
C515 1,2-DICHLOROETHANE-d4	1.34776	1.57053	16.53		
C115 1,1,1-TRICHLOROETHANE	.58472	.61815	5.72		
C120 CARBON TETRACHLORIDE	.53104	.59290	11.65		
C125 VINYL ACETATE	.72080	.68954	4.34		
C130 BROMODICHLOROMETHANE	.79895	.83675	4.73		
C140 1,2-DICHLOROPROPANE	.33339	.34696	4.07	*	✓
C143 CIS-1,3-DICHLOROPROPENE	.54928	.58860	7.16		(Conc=50.00)
C150 TRICHLOROETHENE	.40830	.45552	11.56		
C155 DIBROMOCHLOROMETHANE	.69112	.80015	15.78		
C160 1,1,2-TRICHLOROETHANE	.36750	.40574	10.41		
C165 BENZENE	.77453	.82491	6.50		
C172 TRANS-1,3-DICHLOROPROPENE	.49852	.53743	7.81		(Conc=50.00)
C176 2-CHLOROETHYL VINYL ETHER	.18917	.20574	8.76		
C180 BROMOFORM	.52946	.70040	32.29	**	✓
C505 TOLUENE-d8	.84705	.98681	16.50		
C205 4-METHYL-2-PENTANONE	.71801	.75123	4.63		

RF - Response Factor from daily standard file at 50.00 ug/Kg

RF - Average Response Factor from Initial Calibration Form VI

%Diff - % Difference from original average or curve

CCC - Calibration Check Compounds (*) SPCC - System Performance Check Compounds (**)

Continuing Calibration Check
HSL Compounds

Case No: _____ Calibration Date: 09/05/95
Contractor: RESAM _____ Time: 14:41
Contract No: 68020026 _____ Laboratory ID: >C1063
Instrument ID: CMS-MP _____ Initial Calibration Date: 09/01/95

Minimum RF for SPCC is .30 Maximum % Diff for CCC is 25%

Compound	RF	RF	%Diff	CCC	SPCC
C210 2-HEXANONE	.57030	.58100	1.88		
C220 TETRACHLOROETHENE	.39228	.40810	24.43		
C225 1,1,2,2-TETRACHLOROETHANE	.91334	.96947	6.15	**	
C230 TOLUENE	1.18324	1.25202	5.81	*	
C235 CHLOROBENZENE	.91064	.98515	8.18	**	
C240 ETHYLBENZENE	.44807	.45751	2.10	*	
C245 STYRENE	.95259	.92201	3.21		
C251 XYLENE	.49776	.51846	4.16		
C250 XYLENE (total)	.52663	.52580	.16		(Conc=100.00)
C510 BROMOFLUOROBENZENE	.83582	.90396	8.15		

RF - Response Factor from daily standard file at 50.00 ug/Kg

RF - Average Response Factor from Initial Calibration Form VI

%Diff - % Difference from original average or curve

CCC - Calibration Check Compounds (*) SPCC - System Performance Check Compounds (**)

LC0906

Continuing Calibration Check
HSL Compounds

Case No: _____ Calibration Date: 09/06/95
Contractor: RESAM _____ Time: 13:13
Contract No: 68020026 _____ Laboratory ID: >C1080
Instrument ID: CMS-HP _____ Initial Calibration Date: ~~09/01/95~~ 8/31/95
TW 8/31/95
alcl95

Minimum RF for SPCC is .30 Maximum % Diff for CCC is 25%

Compound	RF	RF	XDiff	CCC	SPCC
C010 CHLOROMETHANE	.39642	.46913	18.34	**	✓
C015 BROMOMETHANE	1.14246	1.25873	10.18		
C020 VINYL CHLORIDE	.83438	.83725	.34	*	✓
C025 CHLOROETHANE	.50535	.51945	2.79		
C030 METHYLENE CHLORIDE	1.43293	1.18492	17.31		
C035 ACETONE	.55605	.44683	19.64		
C040 CARBON DISULFIDE	2.21379	2.31147	4.41		
C042 TRICHLOROFLUOROMETHANE	2.35728	2.53279	7.45		
C045 1,1-DICHLOROETHENE	.93775	1.04383	11.31	*	✓
C050 TETRAHYDROFURAN	.16441	.16422	.12		
C050 1,1-DICHLOROETHANE	1.89701	1.91457	.93	**	✓
C053 1,2-DICHLOROETHENE (total)	1.02075	1.16644	14.27		(Conc=100.00)
C060 CHLOROFORM	2.48515	2.63003	5.83	*	✓
C110 2-BUTANONE	1.00148	.85790	14.34		
C065 1,2-DICHLOROETHANE	1.72335	1.77279	2.87		
MTBE	2.23198	2.43497	9.09		(Conc=50.00)
C015 1,2-DICHLOROETHANE-d4	1.34776	1.47470	9.42		
C115 1,1,1-TRICHLOROETHANE	.58472	.62814	7.43		
C120 CARBON TETRACHLORIDE	.53104	.58543	10.24		
C125 VINYL ACETATE	.72080	.63205	12.31		
C130 BROMODICHLOROMETHANE	.79895	.82806	3.64		
C140 1,2-DICHLOROPROPANE	.33339	.32954	1.16	*	✓
C143 CIS-1,3-DICHLOROPROPENE	.54928	.57199	4.13		(Conc=50.00)
C150 TRICHLOROETHENE	.40830	.44981	10.17		
C155 DIBROMOCHLOROMETHANE	.69112	.78400	13.44		
C160 1,1,2-TRICHLOROETHANE	.36750	.37950	3.27		
C165 BENZENE	.77453	.76477	1.26		
C172 TRANS-1,3-DICHLOROPROPENE	.49852	.48756	2.20		(Conc=50.00)
C176 2-CHLOROETHYL VINYL ETHER	.18917	.19149	1.23		
C180 BROMOFORM	.52946	.64708	22.22	**	✓
C505 TOLUENE-d8	.84705	.96058	13.40		
C205 4-METHYL-2-PENTANONE	.71801	.59373	17.31		

RF - Response Factor from daily standard file at 50.00 ug/Kg

RF - Average Response Factor from Initial Calibration Form UI

XDiff - % Difference from original average or curve

CCC - Calibration Check Compounds (*) SPCC - System Performance Check Compounds (**)

0000025

Continuing Calibration Check
HSL Compounds

Case No: _____ Calibration Date: 09/06/95
Contractor: RESAM _____ Time: 13:13
Contract No: 68020026 _____ Laboratory ID: >C1080
Instrument ID: CMS-HP _____ Initial Calibration Date: 09/01/95

Minimum RF for SPCC is .30 Maximum X Diff for CCC is 25%

Compound	RF	RF	XDiff	CCC	SPCC
C210 2-HEXANONE	.57030	.48204	15.48		
C220 TETRACHLOROETHENE	.39228	.46486	18.50		
C225 1,1,2,2-TETRACHLOROETHANE	.91334	.93293	2.15	**	
C230 TOLUENE	1.18324	1.21568	2.74	*	
C235 CHLOROBENZENE	.91064	.96583	6.06	**	
C240 ETHYLBENZENE	.44807	.45297	1.09	*	
C245 STYRENE	.95259	.94256	1.05		
C251 XYLENE	.49776	.51880	4.23		
C250 XYLENE (total)	.52663	.52348	.60		(Conc=100.00)
C510 BROMOFLUOROBENZENE	.83582	.92397	10.55		

RF - Response Factor from daily standard file at 50.00 ug/Kg

RF - Average Response Factor from Initial Calibration form VI

XDiff - X Difference from original average or curve

CCC - Calibration Check Compounds (*) SPCC - System Performance Check Compounds (**)

0000026

IS - V - 6389
SS - V - 6390

GCMS/VOA

Instr. MS-HP Analyst/Date TW 8/31/75

STD Lot # V. 6314A.

FRN	Acry	ID File	Tube	SAMPLE	AMT	COMMENTS	pH	A	R
7C1072	474	-	-	BFB - 32	50mg	MTH 1 95 1/2 - 24K		Y	✓
				TIME: 13:07					
				SCAN 187-1881 189	- 168	- 88 2 a. 1 NY			
7C1073		IC0824	1	USED 050	5ml	NOT USED		N	
24			2	USED 050	↓	C-13 (H3)		Y	
25		IC0831	3	IC0831 95 H1		VALKEN C-6 (H2)		Y	✓
26			4	LC0831 95 A1	5ml	V-6392 RE 4		N	
27		LC0831	5	USED 200	↓	HEATED PUMP (LOW 300'S) C-13 2		N	
28			6	USED 200	↓	SC0831 / LC0831 C-13 (H3)		Y	✓
29			7	USED 100	↓			Y	✓
30			8	USED 050	↓			Y	✓
31			9	USED 020	↓			Y	✓
32			10	USED 010	↓	C-13 (H3)		Y	✓
33			1	USED 010	↓			N	
34		IC0831	2	LC0831 95 A2	5ml	V-6392 C-13 3		Y	✓
35			3	45141-1 T-13 BOLF BULK 313	5ml 3ml			Y	✓
36			4	45146-3	↓			Y	✓
37			5	-3MS	↓			Y	✓
38			6	-4	↓			Y	✓
39			7	-4MS	↓			Y	✓
40			8	-2	2ml			Y	✓
41			9	-2MS	↓			Y	✓
42			10	45141-1	3ml	LR	2	Y	✓
43				-BULK-					

624(8240

MSCSM / MSCOIL

VOLTAGE = 1100

Page 26 of 100

PACE New England

GCMS/VOA

Instr C MS-HP Analyst/Date TW 9/3/95STD Lot # V-

0822501

FRN	Acq	ID File	Tube	SAMPLE	AMT	COMMENTS	pH	A	I
<C1052		—	—	BFB -DI	Song			N	—
53		—	—	BFB -DI	Song			N	—
54		—	—	BFB -DI	Song			N	—
				MANUAL TUNE ADJUSTED					
55		—	—	BFB -DI	Song			N	—
56		—	—	BFB -DI	Song			N	—
57		—	—	↓	↓	CHANGED INJ PARTS ETC			—
58		—	—	↓	↓				—
59		—	—	↓	↓	OF VOLTAGE → 2000			—
60		—	—	BFB -DI	Song	CHANGE SPARGE		Y	—
61	434	—	—	BFB -DI	Song	MTM 1 95 1/2 = 22K		Y	—
				TIME: 13.44					—
				SCAN: 188+189+190-162		88 191			—
>C1062		LC0931	1	VS0050	Sm	NOT USED		N	—
63			2	VS0050	↓	C-13 (13)			—
64		LC0905	3	BC0905A5A1	↓	VALKCO		Y	✓
65			4	LC090595A1	Sm	V-6392		Y	✓
66			5	45205-1	5.0g			Y	✓
67			6	-2	5.3g			Y	✓
68			7	-3	5.0g			Y	✓
69			8	-4	1.1g	L.R. RE 4g		N	—
70			9	-5	1.2g	RE 5g		N	—
71			10	-6	1.3g	RE 5g		N	—
72			1	-7	1.2g	RE 5g w/ Qalder		Y	✓
73			2	-8	1.2g			Y	✓
74			3	-11	1.1g	RE 5g		N	—
75			4	-12	1.2g	↓		N	—
76			5	45219-1	5.1g			Y	✓
77				BACK					—

0000028

MSC SAM

VOLTAGE = 1900

Page 27 of 100

PACE New England


GCMS/VOA

Instr C **MS-HP** Analyst/Date TGP 9/6/95082895CL
STD Lot # V-6394B


FRN	Area	ID #	Tube	SAMPLE	AMT	COMMENTS	pH	A	R
7C1078	4474	-	-	BFB DI	5mg	MTH 1 1/2 95 - 29K		Y	✓
				TIME: 12:16					
				SCN: 140+141+142	-121	80-91			
>C1079		LC0831	1	VSD050	5ml	NOT USED		N	
80			2	VSD050		C-13(MS)		Y	✓
81		LC0906	3	BC090695A1		UNLCCP		Y	✓
82			4	LC090695A1	5ml	V-6392		Y	✓
83			5	45205-4	4.0g	LR		Y	✓
84			6	-5	5.1g			Y	✓
85			7	-6	5.2g			Y	✓
86			8	-11	5.1g			Y	✓
87			9	-12	5.0g			Y	✓
88			10	-10	5.1g			Y	✓
89			1	45219-2	5.2g			Y	✓
90			2	-3	5.3g			Y	✓
91			3	45205-(MS)	5.2g	SR		Y	
92			4	-1(MS)				Y	
93				-BAKE-		CHANGE OF PACE TO 9/6/95			
94			5	45205-4	5.0g	IS FAILURE		N	
95				-BAKE-					

0000029

VOA LOW SOLIDS - SURR DCE EPA SW846 LIMIT SET 9/94




VOA LOW SOLIDS - SURR TOL-D8 EPA SW846 LIMITS SET 9/94



STD DEV = 2.68 MEAN = 100.7

VOA LOW SOLIDS - SURR BFB EPA SW846 LIMITS SET 9/94



STD DEV = 7.62 MEAN = 99.4

SW846 8240 LOW LEVEL SOLIDS

1 BC081794A
 2 BC081894A
 3 BC082594A
 4 BC082694A
 5 BC083094A
 6 BG081994A
 7 BG082394B
 8 BG082494A
 9 BG082594A
 10 BG082694C
 11 BG082994A
 12 BC083194A
 13 BC090194A
 14 BC090294A
 15 BG083094A
 16 BG083194A
 17 BG090194A
 18 BG090294A
 19 BG090694A
 20 BG090894A
 21 BC090694A
 22 BC090894B
 23 BC090994A
 24 BG090994A
 25 BG091294A
 26 BG091394A
 27 BG091494B
 28 BG091594A
 29 BG091694A
 30 BG091994A
 31 BE092094A
 32 BE092194A
 33 BC092194B
 34 BC092294B
 35 BC092394B
 36 BC092694B
 37 BG100794A
 38 BE092294A
 39 BE092394A
 40 BC092794B
 41 BC101094A
 42 BC101194A
 43 BG101194A
 44 BC101294A
 45 BG101294A
 46 BG101394A
 47 BE101894A
 48 BE101994A
 49 BG101994C
 50 BC101794A

51 BC101894A
 52 BC101994A
 53 BG102094A
 54 BG102194A
 55 BG102494A
 56 BG100594D
 57 BG100794A
 58 BG101194A
 59 BG102594A
 60 BE101794A
 61 BG101294B
 62 BG112394C
 63 BG120694C
 64 BG120794B
 65 BG120894B
 66 BG120994B
 67 BG121494A
 68 BG121594A
 69 BG121694A
 70 BG121994A
 71 BG122094B
 72 BG122394A
 73 BG122794A
 74 BG123094B
 75 ~~B~~
 76 ~~BC021095B~~
 77 ~~BC021395A~~
 78 BG040695B
 79 BG040795B
 80 BC040995A
 81 BC061395C (93, 101, 102)
 82 BC061495C (98, 99, 103)
 83 BC061595A (100, 102, 100)
 84 BC061695A (95, 102, 102)
 85 BC062795A (100, 106, 107)
 86 BC062895B2 (98, 100, 97)
 87 BC062995A1 (99, 100, 100)
 88 BC072595A1 (95, 99, 103)
 89 BC081495A1 (99, 105, 101)
 90 BC090595A1 (95, 98, 100)
 91 BC090695A1 (96, 97, 99)
 92
 93
 94
 95
 96
 97
 98
 99
 100



ENVIRONMENTAL LABORATORIES

SAMPLES FROM
NEW YORK SITE

YES ☒ NO ☐

241079

CHAIN-OF-CUSTODY RECORD
Analytical Request

Client Halliburton NUS
Address 661 Anderson Dr
Foster Plaza #7
Pittsburgh PA 15211
Phone (412) 921-7090

Report To: Mark Speranza
Bill To: _____
P.O. # / Billing Reference _____
Project Name / No. _____

Pace Client No. _____
Pace Project Manager _____
Pace Project No. _____
*Requested Due Date: _____

Sampled By (PRINT):

Timothy J Evans

Sampler Signature

Date Sampled

Timothy J Evans

9-1-95

ITEM NO.	SAMPLE DESCRIPTION	TIME	MATRIX	PACE NO.	NO. OF CONTAINERS	PRESERVATIVES					ANALYSES REQUESTED	REMARKS
						UNPRESERVED	H ₂ SO ₄	HNO ₃	VOA			
1	DSB 14 - Ø5/Ø7	0722	Soil	452194	1	✓					✓	
2	DSB 14 - 4Ø/42	0813	Soil	-2	1	✓					✓	
3	DSB 14 - 5Ø/52	0829	Soil	-3	1	✓					✓	
4												
5												
6												
7												
8												

COOLER NOS.	BAILERS	SHIPMENT METHOD		ITEM NUMBER	RELINQUISHED BY	AFFILIATION	ACCEPTED BY	AFFILIATION	DATE	TIME
1		OUT DATE	RETURNED DATE	1-3	<u>Timothy J Evans</u>	/HNUS	<u>SBronson</u>	/pace	<u>9/5/95</u>	<u>0930</u>

Additional Comments

FedEx AB # 8797930890

1-3

19-1-95 1500

SBronson /pace

9/5/95 0930

SEE REVERSE SIDE FOR INSTRUCTIONS

ORIGINAL