



- CEILING: ONE LAYER OF 5/8" FIRE RATED TYPE X GYPSUM WALL

BOARD (ASTM C36) ON EACH SIDE OF 2"x8"x43 MIL


EQUIPMENT PAD SCHEDULE															
EQUIP No	DESCRIPTION	TYPE	Α	В	С	D		E	F	G	Н	T/PAD EL	ANCHOR BOLTS		REMARKS
-	AIR COMPRESSOR	-	4'-0"	8'-9"	-	=		-	-	-		100'-8"	HILTI	-	
-	SUPPLEMENT BLENDING UNIT	-	2'-0"	3'-4"	-	-		-	-	-	-	100'-8"	HILTI	-	






## **NOTES**

- HILTI ANCHOR BOLTS SHALL CONSIST OF HVA ANCHORING SYSTEM (HVU ADHESIVE AND HAS STAINLESS STEEL ROD) WITH SPECIFIED BOLT DIAMETER AND MINIMUM CONCRETE EMBEDMENT.
- 2. HILTI ANCHORS SHALL BE SUPPLIED AND INSTALLED BY MECHANICAL CONTRACTOR.
- 3. LAYOUT, SIZE AND NUMBER OF ANCHORS SHALL BE AS PER MECHANICAL REQUIREMENTS.





DATE PRINTED 05/25/05

100% REVIEW DRAWINGS
NOT FOR CONSTRUCTION

SCALE VERIFICATION: THIS BAR MEASURES 1" ON ORIGINAL. ADJUST SCALE ACCORDINGLY.

WARNING: ALTERING THIS DOCUMENT IS IN VIOLATION OF THE NEW YORK STATE EDUCATION LAW EXCEPTING AS PROVIDED

IN SECTION 7209, PART 2 OF THE LAW.

HOOKER/RUCO SITE HICKSVILLE, NEW YORK

BIOSPARGE TREATMENT SYSTEM

CONTROL BUILDING
MISCELLANEOUS DETAILS



CRA Infrastructure & Engineering, Inc.

06883-10(045)ST-NF007 MAY 25/2005