

330 Crossways Park Drive, Woodbury, New York 11797-2015 516-364-9890 • 718-460-3634 • Fax: 516-364-9045 www.dvirkaandbartilucci.com

July 14, 2011

Board of Directors

Henry J. Chlupsa, P.E. President & Chairman Steven A. Fangmann, P.E., BCEE

Executive Vice President

Robert L. Raab, P.E. Vice President

Vice Presidents

Richard M. Walka Senior Vice President

Dennis F. Koehler, P.E. Senior Vice President

Joseph H. Marturano Senior Vice President

Garrett M. Byrnes, P.E. Vice President

Thomas P. Fox, P.G. Vice President

William D. Merklin, P.E. Vice President

Harvey P. Moutal, P.E., BCEE Vice President

Michael Neuberger, P.E. Vice President

Kenneth J. Pritchard, P.E.

Theodore S. Pytlar, Jr.

Vice President Michael E. Urtnowski Vice President

Brian M. Veith, P.E.

Vice President
Charles J. Wachsmuth, P.E. Vice President

Senior Associates

Steven M. Cabrera
Christopher M. Clement
Rob J. DeGlorgio, P.E., CPESC
Joseph A. Fioraliso, P.E.
Michael R. Hofgren
Richard W. Lenz, P.E.
Philip R. Sachs, P.E.
Daniel Shabat, P.E.

Associates

Joseph F. Baader
Rudolph F. Cannavale
Ellen R. DeOrsay
Matthew R. DeVinney, P.E.
Frank DeVita
Christopher W. Francis
Christopher Koegel
Christopher M. LeHanka
James J. Magda
Olga Mubarak-Jaramillo
Roger W. Owens
Robbin A. Petrella
Edward J. Reilly
Jason R. Tonne

Mr. David Gardner
Division of Environmental Remediation
New York State Department of Environmental Conservation
625 Broadway, 12th Floor
Albany, NY 12233-7013

Re: Franklin Cleaners Site (Site No. 1-30-050)
D&B Work Assignment No. D004446-01
Groundwater Sampling Report No. 4
D&B No. 2531-08

Dear Mr. Gardner:

Groundwater Sampling Report (No. 4) presents a summary of the groundwater sampling activities performed at the Franklin Cleaners site located in Rockville Centre, New York (see Attachment A, Figure 1) on January 10 and 11, 2011 (Quarter 26 of D&B's Work Assignment). This groundwater sampling event was completed during the operating period beginning December 1, 2010 through February 28, 2011.

Monitoring and sampling activities were conducted by a New York State Department of Environmental Conservation (NYSDEC) "call-out" contractor, Environmental Assessment and Remediations (EAR), under direct contract with the NYSDEC. Reporting, data management and assessment, and additional consulting and engineering/technical evaluation services were performed by Dvirka and Bartilucci Consulting Engineers (D&B).

Groundwater Monitoring Well Conditions

The network of groundwater monitoring wells was sampled to determine groundwater quality at, and in the vicinity of, the site. Groundwater samples were collected from three groundwater monitoring wells (ASMW-1 through ASMW-3) located in close proximity to the leading edge of the Franklin Cleaners plume, and four groundwater monitoring wells (ASMW-4 through ASMW-7), located downgradient of the leading edge of the plume. Note that groundwater monitoring wells ASMW-4 through ASMW-7 act as early warning or "sentinel" wells for a cluster of Village of Rockville Centre production wells located downgradient of the treatment system building. The locations of the groundwater monitoring wells are shown on Figure 2, provided in Attachment A.

CONSULTING ENGINEERS

Mr. David Gardner
Division of Environmental Remediation
New York State Department of Environmental Conservation
July 14, 2011

Page 2

All seven groundwater monitoring wells were accessible during field inspection activities. The groundwater monitoring wells were located as indicated on the site map and well IDs were visible on all groundwater monitoring wells with the exception of groundwater monitoring well ASMW-7. All seven groundwater monitoring wells were observed to be in usable condition and were sealed at the surface, with the exception of ASMW-6 and ASMW-7, where the surface seal and/or the protective casing were damaged. Specific damage noted at each well is detailed in Groundwater Sampling Report No. 3.

The casings for all of the groundwater monitoring wells were observed to be in good condition. Well caps and locks were present and functional on all the groundwater monitoring wells, with the exception of groundwater monitoring well ASMW-6, which was observed to have a malfunctioning lock at the time of the sampling; however, as noted by EAR on the monitoring well field inspection log, the lock was frozen and may still be functional. The well measuring point was visible on all the groundwater monitoring wells.

A headspace reading was collected at each groundwater monitoring well immediately after the removal of the well caps utilizing a photoionization detector (PID). The groundwater monitoring wells exhibited concentrations of total volatile organic compounds (VOCs) ranging from 0.1 parts per million (ppm) to a maximum concentration of 2.8 ppm, detected at groundwater monitoring well ASMW-5. Headspace readings have substantially decreased from a maximum VOC concentration of 96.1 ppm recorded during the previous groundwater monitoring event completed in August 2010. Also, note PID headspace readings are generally erratic and show no trends or consistency.

As detailed in previous groundwater sampling reports, chlorinated VOCs were not detected in laboratory analyzed headspace vapor samples. As such, these headspace VOCs are not attributable to the Franklin Cleaners site.

A summary of groundwater monitoring well conditions and field inspection logs for all groundwater monitoring wells assessed during this period are provided in Attachment B.

Groundwater Quality Data

The network of groundwater monitoring wells was sampled to evaluate the effectiveness and protectiveness of the groundwater extraction and treatment system. Groundwater samples were collected from groundwater monitoring wells ASMW-1 through ASMW-7 on January 10 and 11, 2011. The groundwater samples were analyzed for VOCs utilizing United States Department of Environmental Protection (USEPA) Method 624.

CONSULTING ENGINEERS

Mr. David Gardner
Division of Environmental Remediation
New York State Department of Environmental Conservation
July 14, 2011

Page 3

The results of the analyses of the groundwater samples collected from the monitoring wells this reporting period are provided in Attachment C and are summarized on Figure 2 provided in Attachment A. The results are compared to the NYSDEC Class GA Groundwater Standards and Guidance Values.

Tetrachloroethene (PCE) was detected at a concentration of 31.0 ug/l in groundwater monitoring well ASMW-1, which represents an increased from a concentration of 8.2 ug/l detected during the previous groundwater reporting event (August 2010). PCE, at a concentration of 3.0 ug/l, was detected in groundwater monitoring well ASMW-2, increasing from a concentration of 2.1 ug/l detected during the previous groundwater sampling event. PCE, at a concentration of 0.25 ug/l, was detected in groundwater monitoring well ASMW-3, increasing from a non-detect concentration during the previous groundwater sampling event. The Class GA standard for PCE is 5.0 ug/l. However, PCE concentrations have continued to maintain a decreasing trend since 2003 in monitoring wells ASMW-1 through ASMW-3.

PCE, at a concentration of 0.27 ug/l, was also detected in groundwater sample ASMW-4, increasing from a non-detect concentration during the previous groundwater sampling event. This detection marks the second PCE detection in groundwater monitoring well ASMW-4 since system start-up. The first detection was noted during the May 2010 sampling event. This can be attributed to the change of analytical methods for VOCs from USEPA Method 8260 to Method 624. Method 624 utilizes a lower PCE method detection limit (MDL) of 0.12 ug/l, as compared to Method 8260, which utilizes a PCE MDL of 0.81 ug/l. Note that this detection is significantly less than the PCE Class GA groundwater standard of 5.0 ug/l.

VOCs were not detected in the groundwater samples collected from groundwater monitoring wells ASMW-5, ASMW-6 and ASMW-7 during this reporting period. Attachment D includes graphic representations which summarize PCE concentrations detected in groundwater samples collected from groundwater monitoring wells ASMW-1, ASMW-2 and ASMW-3 since February 2004. Attachment D also includes a table which summarizes historical PCE concentrations detected in groundwater samples collected from all groundwater monitoring wells.

A gross plume model depicting the estimated extent of the PCE plume is provided as Figure 3 in Attachment A. Note that, due to the limited number of sample and data points within the vicinity of the treatment system, the plume extent depicted on Figure 3 is based on a PCE concentration of 5.0 ug/l. In addition, note that, due to the limited number of sample and data points within the vicinity of the treatment system, the overall extent of the PCE plume is estimated. In comparison to Quarter 24, when the last groundwater sampling activities were performed, the plume extent has slightly increased south due to an increase in the PCE concentrations detected in groundwater monitoring wells ASMW-1 and ASMW-2. PCE was detected at respective concentrations of 31.0 ug/l and 3.0 ug/l in groundwater monitoring wells ASMW-1 and ASMW-2 during this

CONSULTING ENGINEERS

Mr. David Gardner
Division of Environmental Remediation
New York State Department of Environmental Conservation
July 14, 2011

Page 4

reporting period, compared to respective concentrations of 8.2 ug/l and 2.1 ug/l detected during the previous reporting period.

Lastly, a review of sample data associated with the Rockville Center production wells indicates that VOCs have not been detected in any production well since system start-up.

Groundwater sampling for Quarter 27 is scheduled for May 2011.

Data Validation

All groundwater samples have been analyzed by Test America Laboratories (TAL), Shelton, CT. All groundwater samples were analyzed for VOCs. The data packages submitted by TAL have been reviewed for completeness and compliance with the NYSDEC Analytical Services Protocol (ASP) Quality Assurance/Quality Control (QA/QC) requirements. All sample results have been deemed valid and usable for environmental assessment purposes.

Data Validation Checklists are presented in Attachment E.

Findings

Based on the results of the groundwater sampling conducted during this reporting period, D&B offers the following findings:

- All groundwater monitoring wells were sealed at the surface and competent, with the
 exception of ASMW-6 and ASMW-7. In addition, all groundwater monitoring wells
 had visible well IDs, with the exception of groundwater monitoring well ASMW-7.
- Groundwater monitoring well headspace VOC readings ranged from 0.0 ppm to 2.8 ppm. However, as chlorinated VOCs were not detected in previously collected laboratory analyzed headspace vapor samples, these headspace VOC readings are not attributable to the Franklin Cleaners Site.
- Concentrations of PCE detected in groundwater monitoring well ASMW-1 increased from 8.2 ug/l (detected August 20, 2010) to 31.0 ug/l. PCE concentrations have shown an overall decrease from 380 ug/l detected after startup of the treatment system in September 2003, and have remained relatively stable since February 2004.
- Concentrations of PCE detected in groundwater monitoring well ASMW-2 increased from 2.1 ug/l (detected August 20, 2010) to 3.0 ug/l. PCE concentrations have shown an overall decrease from 250 ug/l detected after startup of the treatment system in September 2003, and appears to have plateaued over the last 2 years.

CONSULTING ENGINEERS

Mr. David Gardner
Division of Environmental Remediation
New York State Department of Environmental Conservation
July 14, 2011

Page 5

- Concentrations of PCE detected in groundwater monitoring well ASMW-3 increased from non-detect during the previous groundwater sampling period (August 20, 2010) to 0.25 ug/l. Note, PCE concentrations have been detected below the Class GA Standard of 5.0 ug/l in ASMW-3 since October 2003.
- Concentrations of PCE detected in groundwater monitoring well ASMW-4 increased from non-detect during the previous groundwater sampling period (August 20, 2010) to 0.27 ug/l. This marks the second detection since startup of the treatment system in September 2003, and is attributed to the change of analytical methods for VOCs from USEPA Method 8260 to 40 CFR Method 624, which utilizes a lower method detection limit (MDL) (0.12 ug/l) than USEPA Method 8260 (0.81 ug/l).
- PCE concentrations continue to remain non-detect in downgradient groundwater monitoring wells ASMW-5, ASMW-6 and ASMW-7.
- As the downgradient early warning "sentinel" groundwater monitoring wells for the Rockville Center Water District, with the exception of ASMW-4 as detailed above, exhibited non-detect VOC concentrations this reporting period, D&B concludes that the selected remedy is functioning as intended by the Record of Decision (ROD). In addition, based on review of analytical data received from the Village of Rockville Centre, the Village's Public Supply Well located to the south of Molloy College and downgradient of the groundwater extraction and treatment system continues to exhibit non-detect concentrations of chlorinated VOCs.
- According to information received from the Director of Facilities at Molloy College, no new groundwater irrigation wells have been installed on the Molloy College property, which is located immediately downgradient of the Franklin Cleaners off-site groundwater extraction and treatment system.
- A new DER-10 document, dated May 2010, has been implemented since the March 1998 ROD was issued.
- The toxicity data, cleanup levels and remedial action objectives, as defined in the March 1998 ROD, remain unchanged.

Recommendations

Based on the results and findings of the groundwater sampling event conducted during this reporting period, D&B offers the following recommendations:

Continue groundwater monitoring through the existing groundwater monitoring well
network to determine contaminant concentration trends over time and to evaluate the
continued effectiveness of the remediation system.

CONSULTING ENGINEERS

Mr. David Gardner
Division of Environmental Remediation
New York State Department of Environmental Conservation
July 14, 2011

Page 6

- Assess the non-functional lock on groundwater monitoring well ASMW-6 during the next groundwater sampling event and replace if warranted.
- Continue to closely monitor PCE concentration in groundwater monitoring well ASMW-4 and all "sentinel" wells.
- Install and sample up to five temporary Geoprobe wells to the south and west of the treatment system building in order to more accurately define the current location of the PCE plume. Based on the results of the temporary well sampling, it may be warranted to install additional permanent monitoring wells in these areas and/or modify the current extraction well configuration in order to ensure the entire plume is captured and monitored.

Please do not hesitate to contact me at (516) 364-9890, Ext. 3094, if you have any questions.

Very truly yours,

Shoperan

Stephen Tauss Project Manager

SET/OI(t)/lf,kap,j,lf Attachments

cc: J. Trad (NYSDEC)

J. Multari (Molloy College)

J. Neri (H2M)

R. Walka (D&B)


F. DeVita (D&B)

P. Martorano (D&B)

◆2531\SET050411PL_GW RPT 4.DOC(R09)

ATTACHMENT A

FIGURES



FRANKLIN CLEANERS SITE VILLAGE OF HEMPSTEAD, NEW YORK

Dvirka and


A DIVISION OF WILLIAM F. COSULICH ASSOCIATES, P.C.

Bartilucci

CONSULTING ENGINEERS



FIGURE 1




THROUGH FEBRUARY 28, 2011

FIGURE 2

ASMW-2

ASMW-1

F:2531DWGiQuarterly Reports/Quarter 28FIGURE 2.dwg, 6/16/2011 1:00:19 PM, AStrau





VILLAGE OF HEMPSTEAD, NEW YORK

GROSS PLUME MODEL

FIGURE 3

ATTACHMENT B

GROUNDWATER MONITORING WELL INSPECTION LOGS AND SUMMARY OF CONDITIONS

Franklin Cleaners Site NYSDEC CONTRACT No. D004446 / SITE No. 1-30-050 Summary of Monitoring Well Conditions

Monitoring Well I.D.	ASMW-1	ASMW-2	ASMW-3	ASMW-4	ASMW-5	ASMW-6	ASMW-7
Date of inspection	1/11/2011	1/11/2011	1/11/2011	1/11/2011	1/11/2011	1/11/2011	1/10/11
Well visible?	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Well I.D. visible?	Yes	Yes	Yes	Yes	Yes	Yes	No
Well location match site map?	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Surface seal present?	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Surface seal competent?	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Protective casing in good condition?	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Headspace reading (ppm)	0.3	0.1	0.3	1.5	2.8	0.7	0.5
Protective casing material type	Steel	Steel	Steel	Steel	Steel	Steel	Steel
Lock present?	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Lock functional?	Yes	Yes	Yes	Yes	Yes	No	Yes
Lock replaced?						No	
Evidence that the well is double cased?	No	No	No	No	No	No	No
Well measuring point visible?	Yes	Yes	Yes	Yes	Yes	Yes	
Total depth from TOC (feet)	89.83	89.31	89.79	107.38	132.7	130.3	246.6
DTW from TOC (feet)	21.59	20.89	20.80	19.85	20.38	17.7	19.88
TOC Elevation (feet amsl)	47.29	46.25	46.99	44.06	44.25	43.33	43.21
Groundwater Elevation (feet amsl)	25.70	25.36	26.19	24.21	23.87	25.63	23.33
Well diameter (inches)	2	2	2	2	2	2	6
Well casing material	PVC	PVC	PVC	PVC	PVC	PVC	PVC
Physical condition of visible well casing	Good	Good	Good	Good	Good	Good	Good

ABBREVIATIONS:

TOC - Top of casing DTW - Depth to water

AMSL - Above mean sea level

--: Not established

SITE NAME: DEC-Hempsterd 206	SITE ID.:		130050
MONITORING WELL FIELD INSPECTION LOG	INSPECTO DATE/TIN WEII ID.:		KMK 1/11/11 SMW-
WELL VISIBLE? (If not, provide directions below)		YES YES YES YES	NO
LOCK PRESENT? LOCK FUNCTIONAL? DID YOU REPLACE THE LOCK? IS THERE EVIDENCE THAT THE WELL IS DOUBLE CASED? (If yes,describe below) WELL MEASURING POINT VISIBLE? MEASURE WELL DEPTH FROM MEASURING POINT (Feet): MEASURE DEPTH TO WATER FROM MEASURING POINT (Feet): MEASURE WELL DIAMETER (Inches): WELL CASING MATERIAL: PHYSICAL CONDITION OF VISIBLE WELL CASING: ATTACH ID MARKER (if well ID is confirmed) and IDENTIFY MARKER TYPE PROXIMITY TO UNDERGROUND OR OVERHEAD UTILITIES. DESCRIBE ACCESS TO WELL: (Include accessibility to truck mounted rig, natural obstructions, overhepower lines, proximity to permanent structures, etc.); ADD SKETCH OF LOCATION ON BACK, IF NEW YORLD AND STRUCTURE OF LOCATION ON BACK, IF NEW YORLD AND STRUCTURES.	- - ad	89.8 21.5 PVC	3 9
DESCRIBE WELL SETTING (For example, located in a field, in a playground, on pavement, in a garden, AND ASSESS THE TYPE OF RESTORATION REQUIRED. 110 9 955 9 000 fonce	etc.)		
IDENTIFY ANY NEARBY POTENTIAL SOURCES OF CONTAMINATION, IF PRESENT (e.g. Gas station, salt pile, etc.):			
REMARKS:			

	SITE ID.:	130050
MONITORING WELL FIELD INSPECTION LOG	INSPECTOR: DATE/TIME: WEII ID.:	KMK IIIII ASMW-2
WELL VISIBLE? (If not, provide directions below) WELL COORDINATES? NYTM X NYTM Y PDOP Reading from Trimble Pathfinder: Satelites:, GPS Method (circle) Trimble And/Or Magellan	YE	
WELL I.D. VISIBLE?	YES	S NO
WELL I.D. AS IT APPEARS ON PROTECTIVE CASING OR WELL: ASMW-)		
SURFACE SEAL PRESENT? SURFACE SEAL COMPETENT? (If cracked, heaved etc., describe below) PROTECTIVE CASING IN GOOD CONDITION? (If damaged, describe below) HEADSPACE READING (ppm) AND INSTRUMENT USED. PID 09 TYPE OF PROTECTIVE CASING AND HEIGHT OF STICKUP IN FEET (If applicable)	YES	S NO
PROTECTIVE CASING MATERIAL TYPE:		
LOCK FUNCTIONAL? LOCK FUNCTIONAL? DID YOU REPLACE THE LOCK? IS THERE EVIDENCE THAT THE WELL IS DOUBLE CASED? (If yes, describe below) WELL MEASURING POINT VISIBLE? MEASURE WELL DEPTH FROM MEASURING POINT (Feet): MEASURE DEPTH TO WATER FROM MEASURING POINT (Feet): MEASURE WELL DIAMETER (Inches): WELL CASING MATERIAL: PHYSICAL CONDITION OF VISIBLE WELL CASING: ATTACH ID MARKER (if well ID is confirmed) and IDENTIFY MARKER TYPE PROXIMITY TO UNDERGROUND OR OVERHEAD UTILITIES. DESCRIBE ACCESS TO WELL: (Include accessibility to truck mounted rig, natural obstructions, overheap over lines, proximity to permanent structures, etc.); ADD SKETCH OF LOCATION ON BACK, IF NECKLY AND SKETCH OF LO	Jo Design January Janu	3/.89
DESCRIBE WELL SETTING (For example, located in a field, in a playground, on pavement, in a garden, AND ASSESS THE TYPE OF RESTORATION REQUIRED.	etc.)	
IDENTIFY ANY NEARBY POTENTIAL SOURCES OF CONTAMINATION, IF PRESENT (e.g. Gas station, salt pile, etc.):		
REMARKS:		

SITE NAME: DEL- Hempstead 206	SITE ID.: /30050
MONITORING WELL FIELD INSPECTION LOG	INSPECTOR: KMK. DATE/TIME: I/II/II WEII ID.: ASMW-
WELL VISIBLE? (If not, provide directions below)	YES NO
WELL LOCATION MATCH SITE MAP? (if not, sketch actual location on back)ASMA	YES NO
WELL I.D. AS IT APPEARS ON PROTECTIVE CASING OR WELL: ASMW-3	
SURFACE SEAL PRESENT? SURFACE SEAL COMPETENT? (If cracked, heaved etc., describe below) PROTECTIVE CASING IN GOOD CONDITION? (If damaged, describe below)	YES NO
HEADSPACE READING (ppm) AND INSTRUMENT USED. PID 09 TYPE OF PROTECTIVE CASING AND HEIGHT OF STICKUP IN FEET (If applicable) PROTECTIVE CASING MATERIAL TYPE: MEASURE PROTECTIVE CASING INSIDE DIAMETER (Inches):	<u>0.3</u>
LOCK PRESENT? LOCK FUNCTIONAL? DID YOU REPLACE THE LOCK? IS THERE EVIDENCE THAT THE WELL IS DOUBLE CASED? (If yes,describe below) WELL MEASURING POINT VISIBLE?	YES NO
MEASURE WELL DEPTH FROM MEASURING POINT (Feet): MEASURE DEPTH TO WATER FROM MEASURING POINT (Feet): MEASURE WELL DIAMETER (Inches): WELL CASING MATERIAL: PHYSICAL CONDITION OF VISIBLE WELL CASING: ATTACH ID MARKER (if well ID is confirmed) and IDENTIFY MARKER TYPE PROXIMITY TO UNDERGROUND OR OVERHEAD UTILITIES.	89.79 20.80 2 PVC 3500
DESCRIBE ACCESS TO WELL: (Include accessibility to truck mounted rig, natural obstructions, overhopower lines, proximity to permanent structures, etc.); ADD SKETCH OF LOCATION ON BACK, IF NE	
DESCRIBE WELL SETTING (For example, located in a field, in a playground, on pavement, in a garden AND ASSESS THE TYPE OF RESTORATION REQUIRED. 10 5 955 9 1000 Brash / Inc.	ı, etc.)
IDENTIFY ANY NEARBY POTENTIAL SOURCES OF CONTAMINATION, IF PRESENT (e.g. Gas station, salt pile, etc.):	
REMARKS:	

SITE NAME: DEL-Hempstead 206	_SITE ID.:	130059
MONITORING WELL FIELD INSPECTION LOG	INSPECTOR: DATE/TIME: WEII ID.:	KMK 1/4/11 ASMW-4
WELL VISIBLE? (If not, provide directions below) WELL COORDINATES? NYTM X PDOP Reading from Trimble Pathfinder: GPS Method (circle) Trimble And/Or Magellan		ES NO
WELL I.D. VISIBLE?	Y 2	ES NO
WELL LD. AS IT APPEARS ON PROTECTIVE CASING OR WELL: ASMU-4 SURFACE SEAL PRESENT?	Y	ES NO
PROTECTIVE CASING IN GOOD CONDITION? (If damaged, describe below) HEADSPACE READING (ppm) AND INSTRUMENT USED		<u>/.5′</u>
LOCK PRESENT? LOCK FUNCTIONAL? DID YOU REPLACE THE LOCK? IS THERE EVIDENCE THAT THE WELL IS DOUBLE CASED? (If yes,describe below) WELL MEASURING POINT VISIBLE?	Y) >	ES NO
MEASURE WELL DEPTH FROM MEASURING POINT (Feet): MEASURE DEPTH TO WATER FROM MEASURING POINT (Feet): MEASURE WELL DIAMETER (Inches): WELL CASING MATERIAL: PHYSICAL CONDITION OF VISIBLE WELL CASING: ATTACH ID MARKER (if well ID is confirmed) and IDENTIFY MARKER TYPE PROXIMITY TO UNDERGROUND OR OVERHEAD UTILITIES.	19 PU	7,38 1.85 2 100 d
DESCRIBE ACCESS TO WELL: (Include accessibility to truck mounted rig, natural obstructions, overhower lines, proximity to permanent structures, etc.); ADD SKETCH OF LOCATION ON BACK, IF NE West End of parking late of in the m. dade of		Lane
DESCRIBE WELL SETTING (For example, located in a field, in a playground, on pavement, in a garder AND ASSESS THE TYPE OF RESTORATION REQUIRED. ACCUEUM 1	1, etc.)	
IDENTIFY ANY NEARBY POTENTIAL SOURCES OF CONTAMINATION, IF PRESENT (e.g. Gas station, salt pile, etc.):		•
REMARKS:		

MONITORING WHILE FIELD WARDERTON LOC	SITE ID.: INSPECTOR: DATE/TIME: WEII ID.:	130050 KMK 1/11/11 ASMW-
WELL VISIBLE? (If not, provide directions below)	YES	S NO
WELL I.D. VISIBLE?	YES	S NO
WELL I.D. AS IT APPEARS ON PROTECTIVE CASING OR WELL: ASMW-S	YES	S NO
SURFACE SEAL PRESENT?		
HEADSPACE READING (ppm) AND INSTRUMENT USED		.8
LOCK PRESENT? LOCK FUNCTIONAL? DID YOU REPLACE THE LOCK? IS THERE EVIDENCE THAT THE WELL IS DOUBLE CASED? (If yes,describe below) WELL MEASURING POINT VISIBLE?	YES	
MEASURE WELL DEPTH FROM MEASURING POINT (Feet): MEASURE DEPTH TO WATER FROM MEASURING POINT (Feet): MEASURE WELL DIAMETER (Inches): WELL CASING MATERIAL: PHYSICAL CONDITION OF VISIBLE WELL CASING: ATTACH ID MARKER (if well ID is confirmed) and IDENTIFY MARKER TYPE	13, 20	7, 40 .38
DESCRIBE ACCESS TO WELL: (Include accessibility to truck mounted rig, natural obstructions, overher power lines, proximity to permanent structures, etc.); ADD SKETCH OF LOCATION ON BACK, IF NEW Cond of porking 10+ in Road in between 2 Center	CESSARY.	nd caps
DESCRIBE WELL SETTING (For example, located in a field, in a playground, on pavement, in a garden, AND ASSESS THE TYPE OF RESTORATION REQUIRED. Pavement	etc.)	
IDENTIFY ANY NEARBY POTENTIAL SOURCES OF CONTAMINATION, IF PRESENT (e.g. Gas station, salt pile, etc.):		
REMARKS:		

MONITORING WELL FIELD INSPECTION LOG	SITE ID.: INSPECT DATE/TI WEII ID.:	OR: ME:	13:050 KMK 1 fufu
	WEII ID		<u> 23/4W - </u>
WELL VISIBLE? (If not, provide directions below)		YES	NO
WELL I.D. VISIBLE?		YES	NO
WELL I.D. AS IT APPEARS ON PROTECTIVE CASING OR WELL: ASMW-6		YES	T NO 1
SURFACE SEAL PRESENT?		X X X	NO
HEADSPACE READING (ppm) AND INSTRUMENT USED		<i>O</i> :-	7 -
LOCK PRESENT? LOCK FUNCTIONAL? DID YOU REPLACE THE LOCK? IS THERE EVIDENCE THAT THE WELL IS DOUBLE CASED? (If yes,describe below) WELL MEASURING POINT VISIBLE?		YES	NO X
MEASURE WELL DEPTH FROM MEASURING POINT (Feet): MEASURE DEPTH TO WATER FROM MEASURING POINT (Feet): MEASURE WELL DIAMETER (Inches): WELL CASING MATERIAL: PHYSICAL CONDITION OF VISIBLE WELL CASING: ATTACH ID MARKER (if well ID is confirmed) and IDENTIFY MARKER TYPE PROXIMITY TO UNDERGROUND OR OVERHEAD UTILITIES.		130. 17.5 2 PVC 3000	Z <i>o</i>
DESCRIBE ACCESS TO WELL: (Include accessibility to truck mounted rig, natural obstructions, overhopower lines, proximity to permanent structures, etc.); ADD SKETCH OF LOCATION ON BACK, IF NE Ni hale of perking of in case filled is land between parking spits. Is for from large free.	CESSARY	rows	ō£
DESCRIBE WELL SETTING (For example, located in a field, in a playground, on pavement, in a garden AND ASSESS THE TYPE OF RESTORATION REQUIRED. Privement Cock garden	, etc.)	4	
IDENTIFY ANY NEARBY POTENTIAL SOURCES OF CONTAMINATION, IF PRESENT (e.g. Gas station, salt pile, etc.):			

REMARKS:

Lock might work, but it was frozen shut;

Locking well cap was loose on PVC Rises and was removed to access well

it was put back when sample completed

SITE NAME: DEC - HEMPSTEAD 206	SITE ID.:	130050
, , , , , , , , , , , , , , , , , , ,	INSPECTOR:	KMK
MONITORING WELL FIELD INSPECTION LOG	DATE/TIME:	1/10/11 0930
· ·	WEII ID.:	ASMW-7
	Y	ES NO
WELL VISIBLE? (If not, provide directions below)		<u> </u>
WELL COORDINATES? NYTM X NYTM Y		
PDOP Reading from Trimble Pathfinder: Satelites:		
GPS Method (circle) Trimble And/Or Magellan		
WELL I.D. VISIBLE?	<u> </u>	ES NO
WELL LOCATION MATCH SITE MAP? (if not, sketch actual location on back)	 	- ×
WELL LOCATION WATCH SITE MAP! (It flot, sketch actual location on back)	<i>-</i>	<u>× </u>
WELL I.D. AS IT APPEARS ON PROTECTIVE CASING OR WELL:	 	
SURFACE SEAL PRESENT?	-	ES NO
SURFACE SEAL COMPETENT? (If cracked, heaved etc., describe below)		
PROTECTIVE CASING IN GOOD CONDITION? (If damaged, describe below)		
, , , , , , , , , , , , , , , , , , ,	<u> </u>	<u>-</u>
HEADSPACE READING (ppm) AND INSTRUMENT USED		0.5
TYPE OF PROTECTIVE CASING AND HEIGHT OF STICKUP IN FEET (If applicable)		
PROTECTIVE CASING MATERIAL TYPE:		
MEASURE PROTECTIVE CASING INSIDE DIAMETER (Inches):	V	ES NO
LOCK PRESENT?	***************************************	< NO
LOCK FUNCTIONAL?		`
DID YOU REPLACE THE LOCK?		
IS THERE EVIDENCE THAT THE WELL IS DOUBLE CASED? (If yes, describe below)		T V
WELL MEASURING POINT VISIBLE?		
MEASURE WELL DEPTH FROM MEASURING POINT (Feet):		341 10
MEASURE DEPTH TO WATER FROM MEASURING POINT (Feet):	**********	246.60
MEASURE WELL DIAMETER (Inches):		7.88
WELL CASING MATERIAL:		Cornel
PHYSICAL CONDITION OF VISIBLE WELL CASING:	<i></i>	ouc.
ATTACH ID MARKER (if well ID is confirmed) and IDENTIFY MARKER TYPE	_ 1	લ્ં લ્
PROXIMITY TO UNDERGROUND OR OVERHEAD UTILITIES		
DESCRIBE ACCESS TO WELL: (Include accessibility to truck mounted rig, natural obstructions, overhea	ł d	
power lines, proximity to permanent structures, etc.); ADD SKETCH OF LOCATION ON BACK, IF NEC	ESSARY.	
located in "Island" in parking lot between 2 rows		
DESCRIBE WELL SETTING (For example, located in a field, in a playground, on payement, in a garden,	ata)	
AND ASSESS THE TYPE OF RESTORATION REQUIRED.	ыс. <i>)</i>	
Rocky ground surrounded by powement.		
·		
IDENTIFY ANY NEARBY POTENTIAL SOURCES OF CONTAMINATION, IF PRESENT		
(e.g. Gas station, salt pile, etc.):		
(v.g. ous surrou, surr prio, oto. j.		
REMARKS:	/ /	
Manhole cover collar is not permanently of	laced	

ATTACHMENT C

RESULTS OF GROUNDWATER ANALYSIS

FRANKLIN CLEANERS SITE NYSDEC CONTRACT No. D004446 / SITE No. 1-30-050 RESULTS OF GROUNDWATER SAMPLING

SAMPLE ID	ASMW-1	ASMW-2	ASMW-3	ASMW-4	ASMW-5	ASMW-6	ASMW-7	NYSDEC CLASS GA
SAMPLE	WATER	GROUNDWATER						
DATE OF	1/11/2011	1/11/2011	1/11/2011	1/11/2011	1/11/2011	1/11/2011	1/10/2011	STANDARDS AND
COLLECTED	EAR	GUIDANCE VALUES						
UNITS	(ug/L)							
Dichlorodifluoromethane	U	Ü	Ü	U	U	Ü	U	5 ST
Chloromethane	U	U	U	U	U	U	U	
Vinyl chloride	U	U	U	U	U	U	U	2 ST
Bromomethane	U	U	U	U	U	U	U	5 ST
Chloroethane	U	U	U	U	U	U	U	5 ST
Trichlorofluoromethane	U	U	U	U	U	U	U	5 ST
1,1-Dichloroethene	0.51 J	U	U	U	U	U	U	5 ST
Methylene chloride	U	U	U	U	U	U	U	5 ST
trans 1,2-Dichloroethene	U	U	U	U	U	U	U	5 ST
1,1-Dichloroethane	U	U	U	U	U	U	U	5 ST
Chloroform	0.17 J	U	U	0.12 J	U	U	U	7 ST
1,1,1-Trichloroethane	1.9 J	U	U	U	U	U	U	5 ST
Carbon tetrachloride	U	U	U	U	U	U	U	5 ST
1,2-Dichloroethane	U	U	U	U	U	U	U	0.6 ST
Trichloroethene	U	U	U	U	U	U	U	5 ST
1,2-Dichloropropane	U	U	U	U	U	U	U	1 ST
Bromodichloromethane	U	U	U	U	U	U	U	50 GV
cis-1,3-Dichloropropene	U	U	U	U	U	U	U	0.4 ST
trans-1,3-Dichloropropene	U	U	U	U	U	U	U	0.4 ST
1,1,2-Trichloroethane	U	U	U	U	U	U	U	1 ST
Tetrachloroethene	31	3.0 J	0.25 J	0.27 J	U	U	U	5 ST
Dibromochloromethane	U	U	U	U	U	U	U	50 GV
Chlorobenzene	U	U	U	U	U	U	U	5 ST
Bromoform	U	U	U	U	U	U	U	50 GV
1,1,2,2-Tetrachloroethane	U	U	U	U	U	U	U	5 ST
1,3-Dichlorobenzene	U	U	U	U	U	U	U	3 ST
1,4-Dichlorobenzene	U	U	U	U	U	U	U	3 ST
1,2-Dichlorobenzene	U	U	U	U	U	U	U	3 ST
2-Chloroethyl vinyl ether	U	U	U	U	U	U	U	5 ST

NOTES:

Concentration exceeds NYSDEC

Class GA Groundwater

ABBREVIATIONS:

Ug/L = Micrograms per liter
Class GA Groundwater

ST: Standard Value
GV: Guidance Value
GV: Guidance Value
GV: Guidance Value
J: Compound analyzed for but not detected
J: Compound found at a concentration below CRDL, value estimated

Standards or Guidance Values

ATTACHMENT D

MONITORING WELL TREND LINE GRAPHS AND HISTORIC CONCENTRATION TABLE

Franklin Cleaners Site NYSDEC CONTRACT No. D004446 / SITE No. 1-30-050 **Groundwater Monitoring Wells PCE Concentrations**

				thene (PCE) in ug/l Standard = 5 ug/l			
SAMPLE ID	ASMW-1	ASMW-2	ASMW-3	ASMW-4	ASMW-5	ASMW-6	ASMW-7
SAMPLE TYPE	WATER	WATER	WATER	WATER	WATER	WATER	WATER
DATE							
6/23/03	510	87	23	U	U	NA	NA
9/25/03	380	250	13	U	U	NA	NA
10/21/03	340	140	1.4	U	U	NA	NA
11/25/03	120	250	2.1	U	U	NA	NA
2/23/04	66	51	1.7	U	U	NA	NA
5/25/04	6.8	42	1.9	U	U	NA	NA
8/11/04	22	46	U	U	U	NA	NA
11/12/04	9.0	27	2.0	U	U	NA	NA
2/24/05	21	100	U	U	U	U	U
5/16/05	30	44	U	U	U	U	U
8/15/05	14	46	U	U	U	U	U
11/11/05	27	69	1.0	U	U	U	U
2/23/06	13	53	U	U	U	U	U
5/23/06	6.0	36	1.0	U	U	U	U
8/31/06	6.0 J	29	U	U	U	U	U
11/27/06	7.0 J	17	U	U	U	U	U
2/2/07	3.0 J	23	U	U	U	U	U
5/17/07	U	44	U	U	U	U	U
8/15/07	4.0 J	26	U	U	U	U	U
11/20/07	15	4.0 J	U	U	U	U	U
2/28/08	13	10	3.0 J	U	U	U	U
5/20/08	17	16	3.2 J	U	U	U	U
8/19/08	5.6 J	3.5 J	2.7 J	U	U	U	U
12/3/08	9.1 J	5.0 J	2.0 J	U	U	U	U
3/19/09	16	16	U	U	U	U	U
5/18/09	11	10	U	U	U	U	U
8/13/09	10	4.2	U	U	U	U	U
11/20/09	11	3.5	U	U	U	U	U
2/25/10	22	7.5	U	U	U	U	U
5/12/10	14	8.8	0.35 J	0.16 J	U	U	U
8/31/10	8.2	2.1 J	U	U	U	U	U
1/11/11	31	3 J	0.25 J	0.27 J	U	U	U



ABBREVIATIONS:

ug/L = Micrograms per liter


--: Not established ST: Standard Value GV: Guidance Value


QUALIFIERS:


- U: Compound analyzed for but not detected
- J: Compound found at a concentration below CRDL, value

estimated

NA: Not analyzed







ATTACHMENT E

DATA VALIDATION CHECKLISTS

DATA VALIDATION CHECK LIST

Project Name:	Franklin Cleaners aka F	lempstead
Project Number:	2531-03	
Sample Date(s):	January 11, 2011	
Matrix/Number of Samples:	Water/ 6 (ASMW-1 to a Field Duplicate/ 1	ASMW-6)
Analyzing Laboratory:	TestAmerica Laborator	ies, Shelton, CT
Analyses:	Volatile Organic Comp	ounds (VOCs): 40 CFR 136A 624
Laboratory Report No:	220-14558	Date:1/24/2011

ORGANIC ANALYSES VOCS

	Reported			rmance eptable	Not
	No	Yes	No	Yes	Required
1. Holding times		X		X	
2. Blanks				,	
A. Method blanks		X		X	
B. Trip blanks					
C. Field blanks					
3. Laboratory Control Sample (LCS) %R		X		Х	
4. Surrogate spike recoveries		X		Х	
5. Field duplicates RPD		X		Х	

VOCs - volatile organic compounds

%R - percent recovery

RPD - relative percent difference

Comments:

Performance was acceptable.

5. Sample ASMW-1 was field duplicated and labeled ASMW-X. The field duplicate results were acceptable.

VALIDATION PERFORMED BY & DATE:	Donna M. Brown 3/7/2011
VALIDATION PERFORMED BY SIGNATURE:	10-R

DATA VALIDATION CHECK LIST

Project Name:	Franklin Cleaners aka Hempstead		
Project Number:	2531-03		
Sample Date(s):	January 10, 2011		
Matrix/Number of Samples:	Water/ 1 (ASMW-7) Trip Blank/0	•	
Analyzing Laboratory:	TestAmerica Laboratories, Shelton, CT		
Analyses:	Volatile Organic Compounds (VOCs): 40 CFR Part 136A method 624		
Laboratory Report No:	220-14154	Date:1/17/2011	

ORGANIC ANALYSES VOCS

	Reported		Performance Acceptable		Not
	No	Yes	No	Yes	Required
Holding times		X		X	
2. Blanks					
A. Method blanks		X		X	
B. Trip blanks					
C. Field blanks					
3. Laboratory Control Sample (LCS) %R					X
4. Surrogate spike recoveries		X		Х	
5. Field duplicates RPD					X

VOCs - volatile organic compounds

%R - percent recovery

RPD - relative percent difference

Comments:

Performance was acceptable.

VALIDATION PERFORMED BY & DATE:	Donna M. Brown 3/7/2011
VALIDATION PERFORMED BY SIGNATURE:	anger