

330 Crossways Park Drive, Woodbury, New York 11797-2015 516-364-9890 • 718-460-3634 • Fax: 516-364-9045 www.dvirkaandbartilucci.com July 15, 2011

Board of Directors

Henry J. Chlupsa, P.E. President & Chairman

Steven A. Fangmann, P.E., BCEE Executive Vice President

Robert L. Raab, P.E. Vice President

Vice Presidents

Richard M. Walka Senior Vice President

Dennis F. Koehler, P.E. Senior Vice President

Joseph H. Marturano Senior Vice President

Garrett M. Byrnes, P.E. Vice President

Thomas P. Fox, P.G. Vice President

William D. Merklin, P.E.

Harvey P. Moutal, P.E., BCEE Vice President

Michael Neuberger, P.E. Vice President

Kenneth J. Pritchard, P.E. Vice President

Theodore S. Pytlar, Jr. Vice President

Michael E. Urtnowski

Brian M. Veith, P.E. Vice President

Charles J. Wachsmuth, P.E. Vice President

Senior Associates

Steven M. Cabrera
Christopher M. Clement
Rob J. DeGiorgio, P.E., CPESC
Joseph A. Fioraliso, P.E.
Michael R. Hofgren
Richard W. Lenz, P.E.
Philip R. Sachs, P.E.
Daniel Shabat, P.E.

Associates

Joseph F. Baader Rudolph F. Cannavale Ellen R. DeOrsay Matthew R. DeVinney, P.E. Frank DeVita Christopher W. Francis Christopher Koegel Christopher M. LeHanka James J. Magda Olga Mubarak-Jaramillo Roger W. Owens Robbin A. Petrella Edward J. Reilly Jason R. Tonne Mr. David Gardner
Division of Environmental Remediation
New York State Department of Environmental Conservation
625 Broadway, 12th Floor
Albany, NY 12233-7013

Re: Franklin Cleaners Site (Site No. 1-30-050)
D&B Work Assignment No. D004446-01
Quarterly Report No. 26
D&B No. 2531-08

Dear Mr. Gardner:

Quarterly Report (No. 26) presents a summary of the quarterly purpose of this letter is to summarize the quarterly operation, maintenance, monitoring and sampling activities performed at the off-site Franklin Cleaners groundwater extraction and treatment system (see Attachment A, Figure 1), for the period beginning December 1, 2010 through February 28, 2011.

Operation, maintenance, system monitoring and sampling activities were conducted by a New York State Department of Environmental Conservation (NYSDEC) call-out contractor, Environmental Assessment and Remediations (EAR), under direct contract with the NYSDEC. Reporting, data management and assessment, and additional engineering/technical evaluation services were performed by Dvirka and Bartilucci Consulting Engineers (D&B).

Presented below is a summary of the system operation and maintenance completed during the quarter, as well as the analytical results and interpretation of the sample collection and analysis completed during this reporting period at the off-site Franklin Cleaners groundwater extraction and treatment system. Note that groundwater monitoring well sample data is discussed in the Groundwater Sampling Report No. 4. In addition, a Site Management Plan (SMP) for the off-site Franklin Cleaners groundwater extraction and treatment system is currently being prepared by D&B.

CONSULTING ENGINEERS

Mr. David Gardner Division of Environmental Remediation New York State Department of Environmental Conservation July 15, 2011 Page 2

Groundwater Extraction and Treatment System Operation and Maintenance

During this period, extraction well EW-1 operated at an average pumping rate of 31.3 gallons per minute (gpm) and extraction well EW-2 operated at an average pumping rate of 7.0 gpm. Note, due to repeated malfunctions of the EW-2 flow meter, which is likely caused by iron buildup and fouling, the extraction well flow meter did not record accurate flow rate or total flow measurements from January 4, 2011 through the end of this reporting period. Periodic disassembly and cleaning of the influent flow meter paddle wheels has been completed since Quarter 21; however, this has not been effective at correcting this issue. As directed by the NYSDEC, the EW-2 flow meter will no longer be periodically cleaned and will not be replaced at this time.

Normalized graphs of the average flow rate for EW-1 and EW-2 since September 2006 are presented in Attachment B. Based on a review of the data, the flow rate for EW-1 continues to exhibit an overall slightly decreasing trend, while the flow rate for EW-2 exhibits an overall slightly increasing trend. EW-1's slightly decreasing trend may be attributable to iron buildup at the well screen and/or slight pump wear over time.

Approximately 1.0 pound of tetrachloroethene (PCE) was removed from the extracted groundwater by the treatment system during this reporting period and approximately 42.73 pounds of PCE have been removed since start-up of the treatment system in September 2003. The average PCE removal efficiency for this reporting period was greater than 99 percent. A graph of the average PCE removal rate is provided in Attachment C. Overall, the PCE removal rate is exhibiting a very slightly decreasing trend, which may be attributable to a shift in the plume location. As detailed below, it is recommended to install up to five temporary Geoprobe wells to the south and west of the treatment system building in order to define the current plume location, which may have shifted since system startup.

Based on measurements recorded at the treatment system discharge flow meter, approximately 7,526,000 gallons of treated groundwater were discharged to the Nassau County Department of Public Works (NCDPW) storm sewer system during this reporting period. This volume is inconsistent with data collected from the influent flow meters for EW-1 and EW-2, which recorded a combined total flow of approximately 4,840,800 gallons of groundwater entering the treatment system. Note that the total gallons pumped for EW-2 was approximated based on the last recorded volume and the average flow rate at the beginning of the reporting period.

During this reporting period, the groundwater extraction and treatment system was operational for a total of approximately 2,150 hours and inoperative for a total of approximately 10 hours due to system alarm conditions, routine system maintenance and non-routine system maintenance.

CONSULTING ENGINEERS

Mr. David Gardner
Division of Environmental Remediation
New York State Department of Environmental Conservation
July 15, 2011

Page 3

One system shutdown alarm condition, likely related to severe weather conditions and associated electrical interruptions, and one system shutdown alarm condition due to a general failure of extraction well EW-1's VFD, were responded to during this reporting period. On both occasions the treatment system was restarted and no system maintenance was required.

Routine system maintenance performed during this reporting period included blower maintenance on January 6 and February 17, 2011. Note that during the January 6, 2011 blower maintenance event, EAR reported that the center fan belt may need to be replaced in the near future.

Non-routine system maintenance performed during this reporting period included the following:

- Maintenance of influent flow sensor for EW-2 on December 22, 2010; and
- Removal of snow around gate/site entrance on December 27, 2010, and January 13, January 28 and February 2, 2011.

A copy of the Site Activities Logs, System Monitoring Logs and a System Operations and Downtime Log for this reporting period, which includes a summary of system maintenance events and alarm responses as prepared by EAR, are provided in Attachment D. A table summarizing the routine maintenance events completed this reporting period and the scheduled routine maintenance events for Quarter 27 is provided in Attachment E.

Groundwater Extraction and Treatment System Sampling

Groundwater samples were collected from the EW-1 and EW-2 well influent piping sample taps, as well as from the air stripper (liquid) discharge sample tap, at a frequency of twice per month during each of the 3 months comprising this reporting period. Each sample was analyzed for volatile organic compounds (VOCs) utilizing United States Environmental Protection Agency (USEPA) Method 624. In addition, the samples collected from the air stripper discharge sample tap were also analyzed for iron and manganese utilizing USEPA Method 6010 and for pH utilizing USEPA Method 9040.

The analytical results of samples collected from the aqueous phase system influent are compared to the New York State Department of Environmental Conservation (NYSDEC) Class GA Groundwater Standards and Guidance Values, and the analytical results of samples collected from the aqueous phase air stripper discharge are compared to the site-specific NYSDEC State Pollutant Discharge Elimination System (SPDES) permit equivalency effluent limitations. Analytical results are presented in Attachment F.

Based on review and evaluation of the analytical results of groundwater samples collected from extraction well EW-1, PCE was detected at concentrations ranging from 16.0 micrograms per liter (ug/l) to a maximum of 19.0 ug/l, detected on February 24, 2011. Groundwater samples collected from extraction well EW-2 exhibited PCE concentrations ranging from 51.0 ug/l to a maximum of

CONSULTING ENGINEERS

Mr. David Gardner
Division of Environmental Remediation
New York State Department of Environmental Conservation
July 15, 2011

Page 4

60.0 ug/l, detected on February 24, 2011. The NYSDEC Class GA Standard for PCE is 5.0 ug/l. Based on the maximum concentrations detected and extraction well flow rates for EW-1 (33.4 gpm) and EW-2 (7.0 gpm), extraction well EW-1 is removing PCE at a rate of 3.01 x 10⁻⁴ pounds per hour (lb/hr) and extraction well EW-2 is removing PCE at a rate of 2.04 x 10⁻⁴ lb/hr.

The analytical results for the aqueous phase discharge samples collected this reporting period exhibited VOCs and metals concentrations below the effluent limitations. It should also be noted that while the effluent VOCs were detected at concentrations well below the effluent limits, concentrations of PCE ranging from 0.13 ug/l to a maximum of 0.24 ug/l were detected in discharge water. The site-specific effluent limit for PCE is 5.0 ug/l. Laboratory analyzed pH values were detected at concentrations within the site-specific effluent range of 6.5 to 8.5; however, the field readings collected from the wet well on December 2, 2010 (8.97) and January 28 (6.48) and February 3, 2011 (4.89) exhibited pH values slightly above and below the site specific effluent range.

A summary of the extraction and treatment system performance results since March 2009 is provided in Attachment G.

Vapor phase samples were collected from the two carbon adsorption unit influent and effluent sample taps at a general frequency of once per week. Each sample was collected by filling a Tedlar bag directly from each of the influent and effluent sample taps located on the two carbon adsorption units. The samples were screened using a calibrated, hand-held photoionization detector (PID). During this reporting period, PID readings collected from the influent of Carbon Vessel No. 1 vapor phase influent ranged from 0.0 parts per million (ppm) to 22.0 ppm, while PID readings collected from the Carbon Vessel No. 1 effluent ranged from 0.0 ppm to 38.2 ppm. Both maximum concentrations were detected on February, 3 2011. PID readings collected from the influent of Carbon Vessel No. 2 vapor phase influent ranged from 0.0 ppm to 10.7 ppm, while PID readings collected from the Carbon Vessel No. 2 effluent ranged from 0.0 ppm to 25.0 ppm. Both maximum concentrations were detected on February 3, 2011.

The NYSDEC was immediately notified of the PID reading exceedances upon review of the data. In addition, and as recommended below, EAR's sample technicians should notify the NYSDEC and D&B if an effluent exceedance is noted during future monitoring events.

Based on these PID exceedances, D&B recommended vapor phase samples be collected from the carbon adsorption system lead-influent, lead-effluent and lag-effluent sample taps for laboratory analysis of VOCs by USEPA Method TO-15. Vapor phase effluent samples were collected on February 3, 2011. The results of the vapor phase samples analysis are provided in Attachment F. Based on review and evaluation of the analytical results, several VOCs, including PCE, were detected. PCE was detected at the lead-influent, lead-effluent and lag-effluent at concentrations of 210 micrograms per cubic meter (ug/m³) (32 parts per billion [ppb]), 130 ug/m³ (19 ppb) and 180 ug/m³ (27 ppb), respectively, and total VOCs were detected at concentrations of 40.2 ppb,

CONSULTING ENGINEERS

Mr. David Gardner
Division of Environmental Remediation
New York State Department of Environmental Conservation
July 15, 2011

Page 5

21.0 ppb and 29.0 ppb, respectively. Based on the PCE results, the lead vapor phase carbon adsorption vessel is capturing PCE at a rate of 40%, while the lag vapor phase carbon adsorption vessel is not capturing any PCE. In addition, based on the total VOC laboratory analytical results compared to the total VOC PID readings collected in the field, the PID readings appear to be biased high and are generally erratic, and may be indicative of a malfunction with the PID. However, based on the reduced ability of the Granular Activated Carbon (GAC) to capture PCE, the GAC is exhausted. It was initially recommended to replace the GAC material; however, based on the NYSDEC's evaluation of the laboratory-analyzed effluent vapor samples, the NYSDEC has decided to remove the GAC material and vent the effluent vapor directly to the atmosphere, with no GAC treatment.

Data Validation

All samples collected during this quarter have been analyzed by Test America Laboratories (TAL), located in Shelton, CT. The biweekly aqueous phase system samples and the vapor phase samples were analyzed for VOCs. In addition, the aqueous phase effluent sample (AS-1) was analyzed for iron, manganese and pH. The data packages submitted to TAL have been reviewed for completeness and compliance with the NYSDEC Analytical Services Protocol (ASP) Quality Assurance/Quality Control (QA/QC) requirements. All sample results have been deemed valid and usable for environmental assessment purposes.

It should be noted that the samples collected on February 24, 2011 were analyzed on two separate occasions by the laboratory. The original analysis was inadvertently analyzed utilizing the incorrect sample IDs. In order to confirm the results of the original analysis, the samples were reanalyzed outside of their holding times, and the results were used to validate the sample IDs from the original analysis. The results reported are from the revised original sample analysis.

Data Validation Checklists are presented in Attachment H.

Findings

Based on the results of the performance monitoring conducted during this reporting period, D&B offers the following findings:

• The analytical results of the system influent samples show that groundwater extraction wells EW-1 and EW-2 continue to capture VOC-contaminated groundwater at an average combined total flow rate of 38.3 gpm, which is greater than the minimum required pumping rate of 20 gpm, as specified in the December 2000 Groundwater Extraction and Treatment System Design Report.

CONSULTING ENGINEERS

Mr. David Gardner
Division of Environmental Remediation
New York State Department of Environmental Conservation
July 15, 2011

Page 6

- Inconsistencies were again noted between the influent total gallons pumped for EW-1 and EW-2 and the treatment system discharge total gallons pumped. The flow meters continue to intermittently malfunction and non-routine cleaning and maintenance of the flow meters does not appear to be an effective remedy.
- The laboratory and field screening of the effluent water continues to detect intermittent pH values above and below the site specific effluent range of 6.5 to 8.5.
- Based on the influent mass loading rate and the blower air flow rate, the carbon vessels are currently being loaded at a maximum rate of approximately 5.05 x 10⁻⁴ lbs of PCE/hr. Given an average blower flow rate of 630 ft³/min, this equates to a maximum influent PCE air concentration of 0.03 ppm.
- The PID readings collected from the carbon vessel effluent sample taps during this reporting period consistently exhibited total VOCs greater than the site specific effluent limit of 1.0 ppm. Note that the vapor phase laboratory analyzed air samples collected from the lead-influent, lead-effluent and lag-effluent carbon vessel sample taps exhibited total VOC concentrations of 40.2 ppb, 21.0 ppb and 29.0 ppb, which are not consistent with the collected PID readings and may indicate a malfunction with the PID used for the measurements.
- The vapor phase laboratory analyzed air samples collected from the lead-influent, lead-effluent and lag-effluent carbon vessel sample taps exhibited relatively similar PCE concentrations. Based on the concentrations, the lead carbon vessel is removing approximately 40% of the influent PCE, while the lag vessel is not removing any PCE.
- A new DER-10 document, dated May 2010, has been implemented since the March 1998 ROD was issued.
- The toxicity data, cleanup levels and remedial action objectives, as defined in the March 1998 ROD, remain unchanged.

Recommendations

Based on the results of performance monitoring conducted during this reporting period, D&B offers the following recommendations:

- Continue operation of the groundwater extraction and treatment system to minimize downgradient migration of PCE, currently being captured by the system.
- It is recommended that the NYSDEC call-out contractor diagnose the inconsistencies noted between the influent and effluent flow meters or replace the paddle-style flow meters with mag-style flow meters.

CONSULTING ENGINEERS

Mr. David Gardner
Division of Environmental Remediation
New York State Department of Environmental Conservation
July 15, 2011

Page 7

- It is recommended to continue field monitoring of the influent and effluent pH and closely monitor the results. If field monitoring effluent pH values are consistently detected outside of the effluent limit range of 6.5 to 8.5, it may be warranted to perform a post-treatment pH adjustment of the effluent water.
- Based on the observed inconsistency noted between the laboratory analyzed and PID vapor phase total VOC concentrations, it is recommended to further investigate these inconsistencies and/or diagnose any instrument malfunctions.
- Based on the NYSDEC's evaluation of the laboratory-analyzed effluent vapor samples, the NYSDEC has decided to remove the GAC material and vent the effluent vapor directly to the atmosphere, with no GAC treatment. As such, it is recommended to collect effluent vapor samples for laboratory analysis by Method TO-15 on a monthly basis.
- Install and sample up to five temporary Geoprobe wells to the south and west of the
 treatment system building in order to more accurately define the current location of the
 PCE plume. Based on the results of the temporary well sampling, it may be warranted to
 install additional permanent monitoring wells in these areas and/or modify the current
 extraction well configuration in order to ensure the entire plume is captured and
 monitored.

Please do not hesitate to contact me at (516) 364-9890, Ext. 3094, if you have any questions.

Very truly yours,

Stephen Tauss Project Manager


SET/OI(t)/lf,j Attachments

cc:

- J. Trad (NYSDEC)
- J. Multari (Molloy College)
- J. Neri (H2M)
- R. Walka (D&B)
- F. DeVita (D&B)
- P. Martorano (D&B)
- ♦2531\SET050311-PL_26.doc(R10)

ATTACHMENT A

FIGURES



FRANKLIN CLEANERS SITE VILLAGE OF HEMPSTEAD, NEW YORK

Dvirka and

A DIVISION OF WILLIAM F. COSULICH ASSOCIATES, P.C.

Bartilucci


CONSULTING ENGINEERS




FIGURE 1

ATTACHMENT B


NORMALIZED EXTRACTION WELL FLOW RATE GRAPHS





ATTACHMENT C

AVERAGE PCE REMOVAL RATE GRAPH



ATTACHMENT D

SITE LOGS

PERSONNEL ON-SITE	DATE/TIME ON-SITE	TIME OFFSITE		REASON FOR SI	TE VIS	IT (CHECK BOX BELOW)
PL+6W	11/30/10 08/5	1300	\bigcirc	Monitoring		Maintenance
			X	Sampling		Other (Provide Description)
	eed Dr.C. missealine en folio disconsommatives soverveet datatum delibus traus us paar suurisconsist particule en paaresee paares			Alarm Response		
Description: Day 2	GWS.					
KS	12/2/10 0845	1245	K	Monitoring	K	Maintenance
			X	Sampling		Other (Provide Description)
Description: ಉ೯೯೪೩५ ಕ				Alarm Response	Marco Constant	
		``				
K 5	12/9/10 0930	1145	X	Monitoring	Ţ	Maintenance
		XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX		Sampling		Other (Provide Description)
				Alarm Response		
Description: 승니용수는M	check;					

PERSONNEL ON-SITE	DATE/TIMI	E ON-SITE	TIME OFFSITE		REASON FOR SITE VISIT (CHECK BOX BELOW)			
KS.	12/16/16	U30	1300	X	Monitoring	X	Maintenance	
	ACCUSANCE SAME RESIDENCE AND ADDRESS AND A			X	Sampling		Other (Provide Description)	
		ONEN WHO I'M ET TO COME OUT WITH THE ACT OF THE TOTAL THE THE TOTAL THE TOTA	TO THE		Alarm Response			
Description: WEEKY	offer cha	ck, b/	-weekly syst	T.W	- Sampling	2		
			,					
KS	12/22/10	1030	1300		Monitoring	TW	Maintenance	
	Security Security 1				Sampling		Other (Provide Description)	
Дек инс. шта производно до провод в со в сольком намерам и посторина до на доцин в настройно в на выпада на до	 Obligation of the second control of the second contro		MOTION PROCESSES AND SECURITION AND AN ARTHUR SECURITION AND ARTHUR SECURITIES AND ARTHUR SECURITION AND ARTHU		Alarm Response		The second secon	
Description: いたましい	she c	CCK-	shut system d	(574	110 @ 1134	CD	HANIZER 56817131 System @	
MOTIVIENHANCE O	K Flow	Sensor	= = = = (REPI	AC.	ed restact	rti(System @	
^	1 1		,, m \		,			
GW RBA 10	2/27/10	1900	1130 SNO	TW,	LEMOUAL-	**************************************		
ES.	12-30-1	0 1015	1880-1315	\angle	Monitoring	×	Maintenance	
	control and the second sec	TO STATE OF THE ST		4	Sampling		Other (Provide Description)	
	akan kana manakan mekan di kalan kana penampunan menengan kengan kengan pengan pengan pengan pengan pengan pen	*****			Alarm Response			
Description:	a) site c	1 5 -	glad Elevi, Elevi	Z. , e	49			
					· mangage s			

PERSONNEL ON-SITE	DATE/TIME ON-SITE	TIME OFFSITE	REASON FOR SITE VISIT (CHECK BOX BELOW)			
¥5	1-6-10 0900	1 The Contract	X	Monitoring	K	Maintenance
				Sampling		Other (Provide Description)
				Alarm Response		
BEHMAYNEED	she check/mon Linenge soon.	HOR System B	O mark	ruer main		rowced. Center
KMK	1/10/11 0900	/330		Monitoring		Maintenance
PM	aanimafaniminen ofaniminen mineraren mithemaalisees samaan maanaan d		X	Sampling		Other (Provide Description)
GW				Alarm Response		При в применения в произвершиния применения применения применения в применения в применения применения в пр
Description: Sampli on 5; he	system.	Pargewater	60	ntainerized a	nd	pumped through
KS	1045	1400	X	Monitoring		Maintenance
Стиров (т.) и под при не	remijung financisme financisma av e e e e e e e e e e e e e e e e e e	анного и да не под Ссе и острои в се тупесе на чести водин вода и ураст сом заслада по до се об осточна на прои	X	Sampling		Other (Provide Description)
				Alarm Response		
Description: WEEKLY	site check t sy:	ition Souping, Pl	BEL	Sensor @ E	11-2	pot Recording

	DATE/TIME ON-SITE	TIME OFFSITE	Strangenste	VISIT (CHECK BOX BELOW)	
KMK. GW+ PM	1/11/11 0900	1330		Monitoring	Maintenance
ия вые нем и подмерт на предости под выполнения в под предости на предости на предости на предости на предости			¥	Sampling	Other (Provide Description)
ок выболее (по стиновку урски моски урски сотори в соторы до выполняе в ученующего сученую сочил отчество в ученую в социалист в сочин в сочи		MELECULES IN PROPERTY OF THE CONTRACT OF THE C		Alarm Response	
escription: ႕ ಟ 💲	1800 W/S 6, 5 H			Marketine de trainine de la companya	
	**				
1					
1/13/11 PM+RE	3A 1030	1330	51	NOW REMOV	A \
VIIII BC	1300	1430		Monitoring	Maintenance
		20		Sampling	Other (Provide Description)
nutro (2 se para especial de un un tipo de se se para e ancom a conte es poros e expressente en tra es para especial de donos el control e en consequence de control e en cont		DECEMBENT OF THE PROPERTY OF T	V	Alarm Response	
			economic de la companya de la compa		
1125/11 KS	0915	///5	K	Monitoring	Maintenance
1/25/11 KS	0915	///5	K	Monitoring Sampling	Maintenance Other (Provide Description)
1/20/11 KS	09/5	///5	. K		AMERICAN PROPERTY OF THE PROPE
de figlishe til til film de kennessen om som til				Sampling	AND THE PROPERTY OF THE PROPER
de figlishe til til film de kennessen om som til		ALCKI MONBAR		Sampling	AND THE PROPERTY OF THE PROPER
de figlishe til til finde de skelen en e				Sampling	AND THE PROPERTY OF THE PROPER
by falleritte fan kriennen en en fallerite fan				Sampling	AND THE PROPERTY OF THE PROPER
by falleritte fan kriennen en en fallerite fan				Sampling	

PERSONNEL ON-SITE	DATE/TIME ON-SITE	TIME OFFSITE		REASON FOR SITE VISIT (CHECK BOX BELOW)			
169	1-20-1/ 101/2	1930	N X	Monitoring		Maintenance	
RBA-			Χs	Sampling		Other (Provide Description)	
			A	Alarm Response	pomorpovanajumen		
Description: Sus Stul	U						
RBA+6W	1/28/11 0845	1030 SNC	ブレビ	REMOUA!	,		
KS	1/31/11 @ 1000	// 00	Iv	Monitoring		Maintenance	
			s	Sampling		Other (Provide Description)	
				larm Response	SAN TROUBLE CONTROL OF		
Monitor.	The state of the s	general grander grande	- Agguero		9	estant system	
			M	lonitoring		Maintenance	
		TO THE STATE OF TH	s	ampling		Other (Provide Description)	
			Al	larm Response	www.nooten.ma		
Description:							

PERSONNEL ON-SITE	DATE/TIME ON-SITE	TIME OFFSITE	REASON FOR S	ITE VISIT (CHECK BOX BELOW)
DorGRAFM	2/2/11 10:00	12:00	Monitoring	Maintenance
(Sampling	Other (Provide Description)
			Alarm Response	
Description: Sogate	Renoral -	pened Clo	on from Jed	gate oppos
KS, KAS	2/3/11 1000	12/5	⋈ Monitoring	Maintenance
	į.		Sampling	Other (Provide Description)
			Alarm Response	
K5	21011 0915	1230		Maintenance
		, o C D		Other (Provide Description)
		***************************************	Alarm Response	Other (Flovide Description)
Description: WEEKly	site check, B	1 WEETU SQS	tèm Stamplin	J.

PERSONNEL ON-SITE	DATE/TIME ON-SITE	TIME OFFSITE	REASON FOR SITE VISIT (CHECK BOX BELOW)			
ES	2-17-11 1030- 1	1145	\geq	Monitoring	X	Maintenance
				Sampling .		Other (Provide Description)
				Alarm Response		
Description: weekly so	150, grased Blaver					
ES	2-24-11 945	1730	X	Monitoring		Maintenance
			X	Sampling		Other (Provide Description)
Description:				Alarm Response		
Sys V + San						•
<u>ES</u>	3-3-1/ 1015	1200	X	Monitoring		Maintenance
				Sampling		Other (Provide Description)
				Alarm Response		
Description: Sys						

DATE	11/19/10 KS	Maylo R5	liz z lio KS	12/9/10 KS	12/16 KS
TIME	0842	6900	0845	0930	1030
EW-1					
Flow Rate (gpm)	25, Ó	33,4	32.6	31.8	31,5
Total Flow (gal)	117777802@095	2/1200643@0947		12692059@0957	THE RESERVE OF THE PERSON OF T
Influent pH (grab sample field reading)	5.97	6.37	7.22	5,81	5.77
VFD Operating Frequency (Hz)	80,0 Hz	80 ·0	86.0	80.0	80.0
Pump Runtime (hrs @ time)	506613080945	5078124 @0945	50772920036	5114086@0955	513099701100
Bicycle Pump Pressure Reading (psi)		Control and Control of		Constitution of the second of	
Water Column Above Pump (ft H ₂ O)(psi x 2.31)	ally moderation had being	majori (il regionopori dal lindo programa	A COMPANY TO A COM	Shiphotopy algorithm (Anne contract and the grant and the contract and the cont
Routine Sampling Performed (YES/NO)	YES @ 1013	NO	YES @ 1056	NO MARKETON	VES de 1139
EW-2					
Flow Rate (gpm)	6.7	6.4	0/6.9	7.1	0
Total Flow (gal)	1265/613@0952	1269902000147	12754795@0938 12734870@1222	12824497@0957	128435350 1103
Influent pH (grab sample field reading)	\$.45	5.44	7.01	5143	5,26
VFD Operating Frequency (Hz)	60:6 Hz	60.0	60.0	6010	60.0
Pump Runtime (hrs @ time)	31885318 0915	3200524@0945	3219693@0936	323648980955	325339701100
Bicycle Pump Pressure Reading (psi)	ermonyogs#1	**************************************	companies and an analysis and	e-re- 	TRPPTSSAGGGGGGGGGGGGGGGGGGGGGGGGGGGGGG
Water Column Above Pump (ft H ₂ O)(psi x 2.31)		CONTRACTOR (CONTRACTOR)	was considerated in the constant of the consta	Anthropographic Control	waters and the second and the second deposits of the second secon
Routine Sampling Performed (YES/NO)	Nes @ 1029	NO.	YESE 1105	No	YES @ 1149
Air Stripper	gazonen angeriat i distribut (Corto di Association de Corto di Association de Corto de Corto de Corto de Corto				1
Sump Level (inches)	6"	6 "	6 ''	6"	6"
Effluent pH (grab sample field reading)	6.74	6.88	9, 25	7.04	6.99
Fresh Air Inlet Vacuum (in H ₂ O)	1.5	1.5	X	1:65	1.6
Blower Suction (in H ₂ O)	30	21	<u> 20.5</u>	2015	20, S
Blower Discharge (in H ₂ O)	25	25	24	24.5	24
Blower Runtime (hrs @ time)	3952729€6945	39 6482 2 @ 0945	3983991@ 0136	4000787 @ 0955	4017694@ 1100
Routine Sampling Performed (YES/NO)	<u>Yes @ 1042 </u>	W	YES @ 1125	N 0	Y5@1205

		SYSTEM MONITORING L	<u>. 70</u>		
DATE	Illialio KS	11/24/10 KS	12/2/10 KS	129/10 KS	Izliblo KS
TIME	094 5	6900	0.845	0930	1030
Vapor Phase Carbon		THE PROPERTY OF THE PROPERTY O	PROCESSOR DESCRIPTION OF THE PROCESSOR O		
Lead/Lag Unit					
Lead pressure Inlet/Outlet (psi)	12/19	25/19	24/19	24.5/19	24/19
Lead Total VOC Conc. Inlet/Outlet (ppm)	1.3/1.2	1,5 / 1,5	22/27	1.6 /2.0	1.6 /1.6
Lag pressure Inlet/Outlet (psi)	976.5	9/6.5	9/6	9/6.5	9/6
Lag Total VOC Conc. Inlet/Outlet (ppm)	1.3/1.1	1,5/1,6	3.3 /3.5	3.2 /5.1	16/16
Exhaust Flow Rate (scfm)	76716	620.	615	630	630
Exhaust Temperature (°F)	81.	810	20°	798	750
Wet Well					
Pump No. 1 Runtime (hrs)	184299 60950	184898 @ 0946	185958 E 0957	186713@0956	187577 @ 1101
Pump No. 2 Runtime (hrs)	172190 @ 0950	172676 @ 0946	173456 @ 6937	174131@0256	174869 @ 1101
Wet Well pH (grab sample field reading)	6.90	7.31	8.97	7.24	1.10
Valve Vault					
Pump No. 1 Operating Pressure (psi)	9. 2	10	9	9	9
Pump No. 1 Flow Rate (gpm)	60	64	64	64	63
Pump No. 2 Operating Pressure (psi)	9.8	10.1	10	16	10
Pump No. 2 Flow Rate (gpm)	<u> </u>	64	65	64	61
Flow Meter Vault					Control of the second s
Total Flow (gallons @ time)	54848914@ 1004	5446793861016	55135670@n943	557 2285061009	56313184 @ 1116
Jet Pump			-		The second secon
Line Pressure (psi)		٥	0	0	٥

COMMENTS

1/19/10 System operating Normal on Arrival + Departure.

12/2/10 System running upon Arrival - Flow Sensor EWZ not recording System shirt-down@1150

to maintenance flow Senor. 55143396 Totalized System on @ 1212 = monitor system

For 20 min forward EU-2 Rendings After Cleaning Sensor. Turned Heaterson-50"

Turned outside lighting on Auto"

12/16/10 Flow Sensor & Flor Not Working.

SYSTEM MONITORING LOG									
DATE	12210 KS	12-30-10 85	1/6/11 KS	111111 KS	1/18/11 BC				
TIME	1030	1015	5900	1045	1330				
EW-1			TOOMS COOL OWN AREA TO THE CONTRACT AND AN AREA TO THE CONTRACT AND THE CONTRACT AND AREA TO THE CONTRACT AND T						
Flow Rate (gpm)	23.6	33.Y	30.1	29.0	1				
Total Flow (gal)	132888626167	13651805 0009	139 67615 609/3	141965560057					
Influent pH (grab sample field reading)	5.76	5.81	5.56	5.82	distribution of the state of th				
VFD Operating Frequency (Hz)	800	900	80.0	80.0					
Pump Runtime (hrs @ time)	5145405 @ 1105	516449.1501025	S18 1/45@69/5	5193268 @ 1055					
Bicycle Pump Pressure Reading (psi)				No. of Concession, Name of					
Water Column Above Pump (ft H₂O)(psi x 2.31)				All the same of th					
Routine Sampling Performed (YES/NO)	MO	<u>V</u> -a	NO	YES 40 1118					
EW-2									
Flow Rate (gpm)	0	6.70 1009	7.4	0	\$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$				
Total Flow (gal)	12843535 61108		1299417080912	130355278 1057					
Influent pH (grab sample field reading)	<i>5.33</i>	5.49	5.15	5.42					
VFD Operating Frequency (Hz)	60.0	66. Ò	60.0	60.0					
Pump Runtime (hrs @ time)	32 67806 @ 1105	328689.25006	33055(50910	3315668@ 1055					
Bicycle Pump Pressure Reading (psi)		A ST THE COLUMN TO STATE OF THE	Contract of the Contract of th						
Water Column Above Pump (ft H ₂ O)(psi x 2.31)		The state of the s	A CONTRACTOR OF THE PROPERTY O						
Routine Sampling Performed (YES/NO)	NO	Yes	N6	YES @ 1125					
Air Stripper			2003-02-0-0-0-0-0-0-0-0-0-0-0-0-0-0-0-0-		77888				
Sump Level (inches)	6"	6,0	6"	61					
Effluent pH (grab sample field reading)	6.00	<u> </u>	6.32	6.81					
Fresh Air Inlet Vacuum (in H ₂ O)	C & Martin	2.0	<u> 2</u>	1.5					
Blower Suction (in H ₂ O)	30	N-0	21	20.5					
Blower Discharge (in H₂O)	at	5K0	25	25					
Blower Runtime (hrs @ time)	103a103@1105	405119.0 erak	4667862000	4079965 @ 1055					
Routine Sampling Performed (YES/NO)	MO	You	NSA	YES@ 1131					

		SYSTEM MONITORING			
DATE	121210 KS	12/20:10 15	116/11 KS	Inlin KS	1/18/14 BC N
TIME	1030	1015	6900	1,1042	1/333
/apor Phase Carbon					
Lead/Lag Unit				, , , , , , , , , , , , , , , , , , ,	
Lead pressure Inlet/Outlet (psi)	24/19	24/19	25/19	25/19	25 /19
Lead Total VOC Conc. Inlet/Outlet (ppm)	17.0/10.0	4.5/3.7	0.3/1.2	2.6 /23	
Lag pressure Inlet/Outlet (psi)	17/1/	9.15/60	9/6	9/6.5	9/6-5
Lag Total VOC Conc. Inlet/Outlet (ppm)	9.4/7.9	4.2/4.6	11.6/1.7	2.2/3.5	
Exhaust Flow Rate (scfm)	620	630	420	630	620
Exhaust Temperature (°F)	71°	7716	790	79°	640
Wet Well				NO	
Pump No. 1 Runtime (hrs)	1883186 1106	18929.7 CIOL	196153 @ 6911	190780 @ 1056	191661 @ 1919
Pump No. 2 Runtime (hrs)	1753840 1186	(7614.7 p 1026)	17681480911	177296 € 1056	1779430 1414
Wet Well pH (grab sample field reading)	7.(%		6.59	7.11	
/alve Vault	NO SUCCESSA DE PROPERANTO ANNO DE RELEXACIONACIONACIONACIONACIONACIONACIONACION			equantouvatamistations de la constitución de la con	
Pump No. 1 Operating Pressure (psi)	9	lo.0	1.5	10	
Pump No. 1 Flow Rate (gpm)	63	64.0 8(09	60	62	<i>7</i>
Pump No. 2 Operating Pressure (psi)	16	0.01	10	10,1	
Pump No. 2 Flow Rate (gpm)	166	is of the second	61	64	
Flow Meter Vault			£		
Total Flow (gallons @ time)	s 6×14026€1115	57479890 01045	58659296027	5848161801105	59062981/8/
Jet Pump				4	
Line Pressure (psi)	0	0	ĺÔ	O	Ö

COMMENTS

Plan Sensor @ EW-2 Not working - Shot system down @ 1134 Totalizer

56817131. Cleaned Iron From prodult wheel-papered & Restarted system@ 1204.

MONITOR System for 12 he for wormal operation- Plaw Rate@ EW-2 7.6 gpms

1-6-11 Blomer Matintonances

1/11 11 Flow sousce @ ew-z stopped recording refter last wisit. Will not be replaced @ this time (suppled system)

		SYSTEM MONITORING L	.00		
DATE	1120/11 KS	1-29-11 /ES	2/3/11 155	21d11 KS	2-12-11 55
TIME	0915	1045	1000	0915	/03-0
EW-1					
Flow Rate (gpm)	32.6	32.0	30.0	30.9	31.3
Total Flow (gal)	145937040 112Z	14957810 @ 1110	ाई ३,३३३% हा ०३	15540035	15858840
Influent pH (grab sample field reading)	5.58	5.67	4.89	7:03	
VFD Operating Frequency (Hz)	80.0	80 .V	80.0	80.0	NO 751 avail
Pump Runtime (hrs @ time)	5214275 @ 1020	52455.5 Q 1109	924759361034	5264346@100b	528119.6 @1637
Bicycle Pump Pressure Reading (psi)			psical (************************************		
Water Column Above Pump (ft H₂O)(psi x 2.31)		- Margare	*/madamatima		
Routine Sampling Performed (YES/NO)	40	105	And Sand	YES	25
EW-2			***************************************		
Flow Rate (gpm)	Not recording	Not reported	- Criming (1999) majoring		
Total Flow (gal)	13035528	13055578	4-interpretational solution		
Influent pH (grab sample field reading)	5.40	5.51	4.67	6.70	De YSI arreil
VFD Operating Frequency (Hz)	60.0	009	60.00	60.0	60.0
Pump Runtime (hrs @ time)	3336676@1020	3355955 61109	336994 @ 1034	338674 @ 1006	· 340359.701
Bicycle Pump Pressure Reading (psi)			a production state of the state		
Water Column Above Pump (ft H₂O)(psi x 2.31)	₹		P. M. Commission		
Routine Sampling Performed (YES/NO)	NO	tor	WO	YES	UD
Air Stripper					
Sump Level (inches)	6"	Į «	6"	6"	6 ' '
Effluent pH (grab sample field reading)	6.35	k 31	5.86	7.3/	No 751
Fresh Air Inlet Vacuum (in H ₂ O)	1,5	<u>J</u> 0	1.5	1.5	3.0
Blower Suction (in H ₂ O)	20.5	$y \mathcal{Y}_{i,0}$	2015	20.5	205
Blower Discharge (in H₂O)	15	१९०	26	25	190
Blower Runtime (hrs @ time)	4101007@ 1021	AUT 05.8:1 6 1108	4134333e 1034	4151085@1006	41679350057
Routine Sampling Performed (YES/NO)	NO	100	100	YES	60

		SYSTEM MONITORING L	.00 ,		
DATE	1/20/11 KS	1-28 n E5	2/3/11 KS	2/10/11 KS	2-17-11
TIME	୍ର ଓଟ	lous	1600	0915	1030
Vapor Phase Carbon					. *************************************
Lead/Lag Unit					
Lead pressure Inlet/Outlet (psi)	25/19	18/23	26/19	25/19	19/24
Lead Total VOC Conc. Inlet/Outlet (ppm)		14/24	22/38,2	0.0 10.0	2.5/2.6
Lag pressure Inlet/Outlet (psi)	9/6	0.0/80	9/7	9/6	6.25/9.5
Lag Total VOC Conc. Inlet/Outlet (ppm)		2.5/2.6	10.7 /25	6.0/0.0	2.4/2-7
Exhaust Flow Rate (scfm)	630	DY0	630	630	630
Exhaust Temperature (°F)	790	J6.£	74 "	79°	78°∓
Wet Well					
Pump No. 1 Runtime (hrs)	191897 @ 1021	19797 4 61110	193673@1034	194574@1006	19548.45 @105
Pump No. 2 Runtime (hrs)	178/16€ 1022	17881.8 6 1110	179415 6 1034	180062@1007	180713 0057
Wet Well pH (grab sample field reading)	[6.8]	648	4.8	7.38	NO 451 aven
Valve Vault					
Pump No. 1 Operating Pressure (psi)	9	9.9	9.5	9.9	16.0
Pump No. 1 Flow Rate (gpm)	62	~62	63	62	10-64
Pump No. 2 Operating Pressure (psi)	16	10.\	10	10,5	10.2
Pump No. 2 Flow Rate (gpm)	62	*U)\	65	63	60-65
Flow Meter Vault		3			
Total Flow (gallons @ time)	592175640 1634	59893110 0, 1115	60386069@1059	6097671301024	61569387C100
Jet Pump	*		***************************************	,	
Line Pressure (psi)	-0-	- 0 -	0	6	6

COMMENTS

PID-12 LAMP BAd. C	ould not monitor pom's @ CARDON VESSEIS.	
Noster EM. I the Hill but marger :	KI KIND oh (al- prior to use. Proble Cal prior to use.	
2/3/11 CADDON ATR SAU	uples Collected - Lend Inlet, Lend notlet, + LAG outlet.	

		SYSTEM MONITORING LO	UG	
DATE	2-24-11	3-3-11	3-11-11	
TIME	0945	1015	1045	
EW-1				
Flow Rate (gpm)	32.6	32.7	32.7	
Total Flow (gal)	161759260952	16496336 CM3	1686232301051	
Influent pH (grab sample field reading)	6.08	5,97	5.93 80	
VFD Operating Frequency (Hz)	80 th	80	80	
Pump Runtime (hrs @ time)	529791.9 c950	531478-1 @ 1027	533401.000	
Bicycle Pump Pressure Reading (psi)	/		_	
Water Column Above Pump (ft H₂O)(psi x 2.31)		7		
Routine Sampling Performed (YES/NO)	L WI	W	Yes	
EW-2				
Flow Rate (gpm)	0.0 (Not openty Paris)	00(Notworks)	O O / Not Open Preport	
Total Flow (gal)	13035528 e 952	130355780108	1303552801050	
Influent pH (grab sample field reading)	5.56	T.02	5,49	
VFD Operating Frequency (Hz)	60 Hz	60 KI	60 Hz	
Pump Runtime (hrs @ time)	342032-1 @ 950	343718.10,008	345641.90,000	•
Bicycle Pump Pressure Reading (psi)	/			
Water Column Above Pump (ft H ₂ O)(psi x 2.31)				
Routine Sampling Performed (YES/NO)	4es	V_0	Yes	
Air Stripper				
Sump Level (inches)	60"	60	6.0	
Effluent pH (grab sample field reading)	6.86	6.86	6.90	
Fresh Air Inlet Vacuum (in H₂O)	1.15	1.75	1-75	
Blower Suction (in H₂O)	21.0 "1/20	21.0	23.5	
Blower Discharge (in H₂O)	24.0	<u>14.5</u>	23.5	
Blower Runtime (hrs @ time)	418465.90950	4201520 (11/18	422075.8 C1050	
Routine Sampling Performed (FES/NO)	Val	00/	V15	

		SYSTEM MONITORING	LUG		
DATE	2-24:11	5-3-11	3-11-11		· · · · · · · · · · · · · · · · · · ·
TIME	१५५	1015	1045		
Vapor Phase Carbon		· · · · · · · · · · · · · · · · · · ·			WHILE WILL
Lead/Lag Unit					
Lead pressure Inlet/Outlet (psi)	24.0/19.5	24.5/19.0	23.5/19.0	×*************************************	**************************************
Lead Total VOC Conc. Inlet/Outlet (ppm)	1.2/1.3	0.3/0.3	07/0.7	· · · · · · · · · · · · · · · · · · ·	
Lag pressure Inlet/Outlet (psi)	9.5/6.0	9.5/60	9.0/6.0		
Lag Total VOC Conc. Inlet/Outlet (ppm)	1.2/1.4	0.7/13	0.9/10	······	
Exhaust Flow Rate (scfm)	630	640	620	·····	
Exhaust Temperature (°F)	79. t	79°P	80. E		
Wet Well					
Pump No. 1 Runtime (hrs)	19639.5 @ 951	19732.10 100	7 19839501050		
Pump No. 2 Runtime (hrs)	18135.5 @ 951	18199.90 (027			
Wet Well pH (grab sample field reading)	7.08	7.41	7.07		
Valve Vault				*****	
Pump No. 1 Operating Pressure (psi)	9.8	10.0	9.7		
Pump No. 1 Flow Rate (gpm)	62.0 5000 1030	66,0 (184	61001055		•
Pump No. 2 Operating Pressure (psi)	9.9	10.2	9.9		
Pump No. 2 Flow Rate (gpm)	13.0 gregg	630 CW)	63-0 C/14		**************************************
Flow Meter Vault	, , , , , , , , , , , , , , , , , , ,	/			
Total Flow (gallons @ time)	621591900959	62155 324 86	33 63435760 C 1055		
Jet Pump					-1
Line Pressure (psi)					

COMMENTS

1 P10 12 Cal. prior	to one. Y	e-108 chilud	manist Ph Sold	han to verile	acturbon,	17-24
11 019		512-107		(", 0	8	(3.2.4)
· PIPIZ Cal- porce	to use.	YSI RIOG Ph Leck	idas trioss (al	de la Solition	miled to LCC	./3-8-11)
•			0		V 100	

FRANKLIN CLEANERS SITE, NYSDEC SITE NO. 1-30-050 SYSTEM OPERATIONS AND DOWNTIME SHEET

SUF OFF DATE/TIME	RESTART DATE/TIME	CAUSE	ACTIONS TAKEN	TOTALIZER READING
SHUT-OFF DATE/TIME	7/19/10		Panodoun Restrobed	45934965@ 1233
7/21/10 1022	de la companya de la	LEADER O	EW-2 Shuldmun	11941158
7/23/10 1323				075 07601
i	7/26/10 1315		RESTART SUSTERM	07507612 EW
	7/27/10 1410	Melnierance	ESTACE EWZ	11941158 EWZ
7/30/10 0955	7/30/10 1045	Welninge	Flow sensor 2- Cleaning who	46564937
8/26/10 1635	8/26/19 1110	MBINICARMICE	PRESTURE SEW-2 INTER FOR PARCEL PROST VICTORIAN SEW-2 INTER FOR PARCEL PARCET VICTORIAN SEW-2 INTER FOR PARCEL PARCE	48837586 49,202,338 system
8/30/10 1915	8/31/10	Alarm-3		49,202,338 01
	9/22/10/1030	PERSONNEL	Preshair inlet Screen to	53466842
11/12/10 1028	11/12/10 1036	Shot down Flow sensor Buz notwood	de bodde usbeets	54897868
112910 1322		Flow SENSOR	due I and I Alocal Back in Costion	55143396
12/2/10 1/50	12/22/10 1204	Flansenge Votabling	CTEMBER IRON FROM products wheel Replaced Monitored.	56817131
12/22/10/1134	16/11 1160	House f	Garrese, In speci Builts.	5806 2265

FRANKLIN CLEANERS SITE, NYSDEC SITE NO. 1-30-050 SYSTEM OPERATIONS AND DOWNTIME SHEET

SHUT-OFF DATE/TIME	RESTART DATE/TIME	CAUSE	ACTIONS TAKEN	TOTALIZER READING
1/18/1 0836	1/18/1 1405	Alpanisk	SHATER EINSTERTS RESET	5906 1732
1/31/11 0734	1/31/11	Alaem 3+3	RESET VEW EW. (60132328
1 (/ /			
	Managare and another facilities and a second			

ATTACHMENT E

ROUTINE MAINTENANCE SCHEDULE

FRANKLIN CLEANERS SITE NYSDEC CONTRACT No. D004446 / SITE No. 1-30-050 SUMMARY OF MAINTENANCE ACTIVITIES

	Dec-2010	Jan-2011	Feb-2011	Mar-2011	Apr-2011	May-2011
Activity	26th Qtr	26th Qtr	26th Qtr	27th Qtr	27th Qtr	27th Qtr
Blower Maintenance		01/06/11	02/17/11			
Air Stripper Maintenance						
GAC Removal and Replacement						
Wet Well Pumps Maintenance						

##/##/##	Activity Completed
	Activity to Complete

ATTACHMENT F

ANALYTICAL RESULTS

FRANKLIN CLEANERS SITE NYSDEC CONTRACT No. D004446 / SITE No. 1-30-050 **RESULTS OF ANALYSIS OF EW-1 INFLUENT**

	SYSTEM	NIVODEO OL AGO OA						
SAMPLE ID	INFLUENT (EW-1)	NYSDEC CLASS GA GROUNDWATER						
SAMPLE TYPE	WATER	STANDARDS AND						
DATE OF COLLECTION	12/2/2010	12/16/2010	12/30/2010	1/11/2011	1/28/2011	2/10/2011	2/24/2011	GUIDANCE VALUES
COLLECTED BY	EAR	GUIDANCE VALUES						
UNITS	(ug/L)							
VOCs								
Dichlorodifluoromethane	U	U	U	U	U	U	U	5 ST
Chloromethane	0.82 J	0.34 J	U	U	U	U	U	
Vinyl chloride	U	U	U	U	U	U	U	2 ST
Bromomethane	U	U	U	U	U	U	U	5 ST
Chloroethane	U	U	U	U	U	U	U	5 ST
Trichlorofluoromethane	U	U	U	U	U	U	U	5 ST
1,1-Dichloroethene	U	U	U	U	U	U	U	5 ST
Methylene chloride	U	U	U	U	U	U	U	5 ST
trans 1,2-Dichloroethene	U	U	U	U	U	U	U	5 ST
1,1-Dichloroethane	U	U	U	U	U	U	U	5 ST
Chloroform	0.14 J	0.13 J	0.12 J	0.14 J	0.11 J	U	U	7 ST
1,1,1-Trichloroethane	U	U	U	U	U	U	U	5 ST
Carbon tetrachloride	U	U	U	U	U	U	U	5 ST
1,2-Dichloroethane	U	U	U	U	U	U	U	0.6 ST
Trichloroethene	U	U	U	U	U	U	U	5 ST
1,2-Dichloropropane	U	U	U	U	U	U	U	1 ST
Bromodichloromethane	U	U	U	U	U	U	U	50 GV
cis-1,3-Dichloropropene	U	U	U	U	U	U	U	0.4 ST
trans-1,3-Dichloropropene	U	U	U	U	U	U	U	0.4 ST
1,1,2-Trichloroethane	U	U	U	U	U	U	U	1 ST
Tetrachloroethene	17	16	18	18	16	16	19	5 ST
Dibromochloromethane	U	U	U	U	U	U	U	50 GV
Chlorobenzene	U	U	U	U	U	U	U	5 ST
Bromoform	U	U	U	U	U	U	U	50 GV
1,1,2,2-Tetrachloroethane	U	U	U	U	U	U	U	5 ST
1,3-Dichlorobenzene	U	U	U	U	U	U	U	3 ST
1,4-Dichlorobenzene	U	U	U	U	U	U	U	3 ST
1,2-Dichlorobenzene	U	U	U	U	U	U	U	3 ST
2-Chloroethyl vinyl ether	U	U	U	U	U	U	U	5 ST



ABBREVIATIONS:

ug/L = Micrograms per liter ST: Standard Value

--: Not established

GV: Guidance Value

QUALIFIERS:

U: Compound analyzed for but not detected

J: Compound found at a concentration below CRDL, value estimated

FRANKLIN CLEANERS SITE NYSDEC CONTRACT No. D004446 / SITE No. 1-30-050 **RESULTS OF ANALYSIS OF EW-2 INFLUENT**

	SYSTEM	NIVEDEC OLACCIOA						
SAMPLE ID	INFLUENT (EW-2)	NYSDEC CLASS GA GROUNDWATER						
SAMPLE TYPE	WATER	STANDARDS AND						
DATE OF COLLECTION	12/2/2010	12/16/2010	12/30/2010	1/11/2011	1/28/2011	2/10/2011	2/24/2011	GUIDANCE VALUES
COLLECTED BY	EAR	GUIDANCE VALUES						
UNITS	(ug/L)							
VOCs								
Dichlorodifluoromethane	U	U	U	U	U	U	U	5 ST
Chloromethane	U	0.53 J	U	U	U	U	U	
Vinyl chloride	U	U	U	U	U	U	U	2 ST
Bromomethane	U	U	U	U	U	U	U	5 ST
Chloroethane	U	U	U	U	1.90 J	U	U	5 ST
Trichlorofluoromethane	U	U	U	U	U	U	U	5 ST
1,1-Dichloroethene	0.20 J	0.24 J	0.24 J	0.21 J	U	0.30 J	0.19 J	5 ST
Methylene chloride	U	U	U	U	U	U	U	5 ST
trans 1,2-Dichloroethene	U	U	U	U	U	U	U	5 ST
1,1-Dichloroethane	U	U	U	0.11 J	U	0.12 J	U	5 ST
Chloroform	0.16 J	0.16 U	0.16 U	U	U	0.15 J	U	7 ST
1,1,1-Trichloroethane	U	U	U	0.20 J	0.18 J	U	U	5 ST
Carbon tetrachloride	U	U	U	U	U	U	U	5 ST
1,2-Dichloroethane	U	U	U	U	U	U	U	0.6 ST
Trichloroethene	U	U	U	U	U	U	U	5 ST
1,2-Dichloropropane	U	U	U	U	U	U	U	1 ST
Bromodichloromethane	U	U	U	U	U	U	U	50 GV
cis-1,3-Dichloropropene	U	U	U	U	U	U	U	0.4 ST
trans-1,3-Dichloropropene	U	U	U	U	U	U	U	0.4 ST
1,1,2-Trichloroethane	U	U	U	U	U	U	U	1 ST
Tetrachloroethene	55	56	57	58	52	51	60	5 ST
Dibromochloromethane	U	U	U	U	U	U	U	50 GV
Chlorobenzene	U	U	U	U	U	U	U	5 ST
Bromoform	U	U	U	U	U	U	U	50 GV
1,1,2,2-Tetrachloroethane	U	U	U	U	U	U	U	5 ST
1,3-Dichlorobenzene	U	U	U	U	U	U	U	3 ST
1,4-Dichlorobenzene	U	U	U	U	U	U	U	3 ST
1,2-Dichlorobenzene	U	U	U	U	U	U	U	3 ST
2-Chloroethyl vinyl ether	U	U	U	U	U	U	U	5 ST

NOTES: **ABBREVIATIONS: QUALIFIERS:**

Concentration exceeds NYSDEC Class GA ug/L = Micrograms per liter ST: Standard Value U: Compound analyzed for but not detected Groundwater Standards or Guidance Values --: Not established

GV: Guidance Value J: Compound found at a concentration below CRDL, value estimated

FRANKLIN CLEANERS SITE NYSDEC CONTRACT No. D004446 / SITE No. 1-30-050 RESULTS OF ANALYSIS OF AIR STRIPPER EFFLUENT FOR VOCS

	SYSTEM	SYSTEM	SYSTEM	SYSTEM	SYSTEM	SYSTEM	SYSTEM	EFFLUENT	
	EFFLUENT	EFFLUENT	EFFLUENT	EFFLUENT	EFFLUENT	EFFLUENT	INFLUENT	LIMITATIONS	NYSDEC CLASS GA
SAMPLE ID	(AS-1)	(AS-1)	(AS-1)	(AS-1)	(AS-1)	(AS-1)	(AS-1)		GROUNDWATER
SAMPLE TYPE	WATER	WATER	WATER	WATER	WATER	WATER	WATER		STANDARDS AND
DATE OF COLLECTION	12/2/2010	12/16/2010	12/30/2010	1/1/2011	1/28/2011	2/10/2011	2/24/2011		GUIDANCE VALUES
COLLECTED BY	EAR	EAR	EAR	EAR	EAR	EAR	EAR		
UNITS	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)	(ug/L)
VOCs									_
Dichlorodifluoromethane	U	U	U	U	U	U	U		5 ST
Chloromethane	U	U	U	U	U	U	U		
Vinyl chloride	U	U	U	U	U	U	U		2 ST
Bromomethane	U	U	U	U	U	U	U		5 ST
Chloroethane	U	U	0.56 J	U	U	U	U		5 ST
Trichlorofluoromethane	U	U	U	U	U	U	U		5 ST
1,1-Dichloroethene	U	U	U	U	U	U	U		5 ST
Methylene chloride	U	U	U	U	U	U	U		5 ST
trans 1,2-Dichloroethene	U	U	U	U	U	U	U		5 ST
1,1-Dichloroethane	U	U	U	U	U	U	U	10	5 ST
Chloroform	U	U	U	U	U	U	U		7 ST
1,1,1-Trichloroethane	U	U	U	U	U	U	U	10	5 ST
Carbon tetrachloride	U	U	U	U	U	U	U		5 ST
1,2-Dichloroethane	U	U	U	U	U	U	U		0.6 ST
Trichloroethene	U	U	U	U	U	U	U	10	5 ST
1,2-Dichloropropane	U	U	U	U	U	U	U		1 ST
Bromodichloromethane	U	U	U	U	U	U	U		50 GV
cis-1,3-Dichloropropene	U	U	U	U	U	U	U		0.4 ST
trans-1,3-Dichloropropene	U	U	U	U	U	U	U		0.4 ST
1,1,2-Trichloroethane	U	U	U	U	U	U	U		1 ST
Tetrachloroethene	0.18 J	0.24 J	U	0.13 J	U	0.19 J	U	5	5 ST
Dibromochloromethane	U	U	U	U	U	U	U		50 GV
Chlorobenzene	U	U	U	U	U	U	U		5 ST
Bromoform	U	U	U	U	U	U	U		50 GV
1,1,2,2-Tetrachloroethane	Ū	Ū	Ū	Ū	Ū	Ū	Ū		5 ST
1,3-Dichlorobenzene	U	U	U	U	U	U	U		3 ST
1,4-Dichlorobenzene	Ū	Ū	Ū	Ū	Ū	Ū	Ū		3 ST
1,2-Dichlorobenzene	Ū	Ū	Ū	Ū	Ū	Ū	Ū		3 ST
2-Chloroethyl vinyl ether	Ü	Ū	Ū	Ū	Ū	Ū	Ū		5 ST

NOTES: ABBREVIATIONS QUALIFIERS:

Concentration exceeds Site Specific Effluent Limitation

ug/L = Micrograms p ST: Standard \ U: Compound analyzed for but not detected

--: Not established GV: Guidance J: Compound found at a concentration below

FRANKLIN CLEANERS SITE NYSDEC CONTRACT No. D004446 / SITE No. 1-30-050 RESULTS OF ANALYSIS OF AIR STRIPPER EFFLUENT IRON, MANGANESE AND pH

	SYSTEM							
SAMPLE ID	EFFLUENT (AS-1)	EFFLUENT						
SAMPLE TYPE	WATER	LIMITATIONS						
DATE OF COLLECTION	12/2/2010	12/16/2010	12/30/2010	1/11/2011	1/28/2011	2/10/2011	2/24/2011	
COLLECTED BY	EAR							
UNITS	(ug/L)	(ug/L)						
METALS								
Iron	52.7 J	132 J	144 J	390	U	154 J	U	1000
Manganese	19.9	29.9	53.2	67.2	18.9	35.8	18.8	1000
pH (S.U.)	7.19	7.30	7.11	7.02	7.12	7.13	7.05	6.5 to 8.5

ABBREVIATIONS: QUALIFIERS:

U: Compound analyzed for but not detected

ug/L: Micrograms per liter J: Compound found at a concentration below Contract Required Detection Limit, value estimated

FRANKLIN CLEANERS SITE NYSDEC CONTRACT No. D004446 / SITE No. 1-30-050 VAPOR PHASE SAMPLE RESULTS

	CARBON VESSEL NO. 1	CARBON VESSEL NO. 1	CARBON VESSEL NO. 2	CARBON VESSEL NO. 2
SAMPLE ID	INFLUENT	EFFLUENT	INFLUENT	EFFLUENT
SAMPLE TYPE	AIR	AIR	AIR	AIR
COLLECTED BY	EAR	EAR	EAR	EAR
UNITS	(ppm)	(ppm)	(ppm)	(ppm)
DATE OF COLLECTION	PID Reading	PID Reading	PID Reading	PID Reading
12/2/2010	2.2	2.9	3.3	3.5
12/9/2010	1.6	2.0	3.2	5.1
12/16/2010	1.6	1.6	1.6	1.6
12/22/2010	17.0	10.0	9.4	7.9
12/30/2010	4.5	3.7	4.2	4.6
1/6/2011	0.3	1.2	1.6	1.7
1/11/2011	2.6	2.4	2.2	3.5
1/28/2011	2.4	2.4	2.5	2.6
2/3/2011	22.0	38.2	10.7	25.0
2/10/2011	0.0	0.0	0.0	0.0
2/17/2011	2.5	2.6	2.4	2.7
2/24/2011	1.2	1.3	1.2	1.4

NOTES:

Samples were collected by filling a Tedlar bag at each of the sampling locations. Samples were tested using a handheld photoionization detector (PID).

Exceeds site-specific effluent limit of 1.0 ppm total VOCs.

FRANKLIN CLEANERS SITE

NYSDEC SITE No. 1-52-125

RESULTS OF ANALYSIS OF VAPOR PHASE CARBON VESSELS - VOLATILE ORGANIC COMPOUNDS (VOCs)

SAMPLE TYPE	[aa.							
DATE OF COLLECTION	SAMPLE TYPE		LUENT				UENT	
BLOWER FLOW RATE (FT*AMN)			11			1		
Concentration			11				11	
UNTS	BEOWERT LOW RATE (1.1.7/MIN)		Loading Rate				Emission Rate	
VOCS	UNITS							
Feon 114		(#g/// /	(10,111)	(#3,*** /	(=,)	(#g,)	(12,111)	
Acetane	t 1,3 Dichloropropene	U		U		U		
Ethanol	l ·	U		U		U		
Ethylocate	Acetone	U		U		U		
Ethybenzene	Ethanol	U		U		U		
Trichlorofucormethane	Ethyl Acetate	U		U		U		
Heptane	Ethylbenzene	U				_		
Hexanionononononononononononononononononono			2.8E-06			_		
Hexane								
2-Hexanone U U U U U U U U U						_		
Isopropy Alcohol						_		
Methylene Chloride						_		
Benzene		_				_		
Benzyl Chloride U			0.05.05			_	4.05.00	
Styrene			3.3⊵-05				1.9೬-06	
1.1.2.2 Tetrachloroethane U 4.9E-04 130 3.0E-04 180 4.2E-04 Tetrachlydrofuran U 4.9E-04 130 3.0E-04 180 4.2E-04 Toluene 1.1 2.6E-06 U	*							
Tetrachloroethene						_		
Tetralydrofuran			4 9F-04		3.0F-04	_	4 2F-04	
Tolurie		-	4.96-04		3.0⊆-04		4.26-04	
1,2,4 Tritchlorobenzene	*		2 6F-06	_				
1.1.1 Trichloroethane U U U U U U U U 1.4E-06 0.63 1.5E-06 0.6 1.4E-06 1.4E-06 0.63 1.5E-06 0.6 1.4E-06 0.63 1.5E-06 0.6 1.4E-06 0.6 0.6 1.4E-06 0.6 0.6 1.4E-06 0.6 0.6 1.4E-06 0.7 0.6 0.7 0.6 0.7 0.6 0.7 0.6 0.7 0.7 0.6 0.7 0.7 0.7 0.7 0.7 0.7			2.02 00			_		
1,12 Trichloroethane								
Trichroethlyene				Ü				
1,2,4 Trimethylbenzene U		0.62	1.4E-06		1.5E-06	0.6	1.4E-06	
1,3,5 Trimethylbenzene U U U U U U U U U U U U U U U U U U U U U U U U </td <td> </td> <td>U</td> <td></td> <td>U</td> <td></td> <td>U</td> <td></td>		U		U		U		
Vinyl Chloride		U		U		U		
o-Xylene U Methyl tert-butyl ether 1.6 3.7E-06 U	Vinyl Acetate	U		U		U		
Methyl tert-butyl ether	Vinyl Chloride	U		U		U		
1,2,2 Trifluoro-1,1,2 Tricloroethane U	o-Xylene	U		U		U		
m + p Xylene U	Methyl tert-butyl ether	1.6	3.7E-06			_		
Bromodichloromethane						_		
1,2 Dibromoethane U						_		
Methyl Ethyl Ketone U						_		
4-Methyl-2-Pentanone U						_		
Bromoform U U U U U U U U U						_		
Bromomethane		_		_		_		
1,3 Butadiene		_				_		
A-Ethyltoluene		_				_		
Carbon Disulfide U						_		
Carbon Tetrachloride U						_		
Chlorobenzene								
Dibromochloromethane		_		_		_		
Chloroethane U <t< td=""><td></td><td>_</td><td></td><td>_</td><td></td><td>_</td><td></td></t<>		_		_		_		
Chloroform 1.1 2.6E-06 U U U Chloromethane 1.2 2.8E-06 1.3 3.0E-06 1.6 3.7E-06 Propene 2.4 5.6E-06 1.1 J 2.6E-06 1.1 J 2.6E-06 Cyclohexane U U U U U U 1,2 Dichlorobenzene U								
Chloromethane 1.2 2.8E-06 1.3 3.0E-06 1.6 3.7E-06 Propene 2.4 5.6E-06 1.1 J 2.6E-06 1.1 J 2.6E-06 Cyclohexane U U U U U U 1,2 Dichlorobenzene U 0			2.6E-06					
Propene				_	3.0E-06	_	3.7E-06	
Cyclohexane U U U U 1,2 Dichlorobenzene U U U U 1,3 Dichlorobenzene U U U U 1,4 Dichlorobenzene U U U U Dichlorodifluoromethane 2.7 6.3E-06 2.6 6.0E-06 1,1 Dichloroethane U U U U 1,2 Dichloroethane U U U U 1,1 Dichloroethene U U U U 1,2 Dichloroethene U U U U trans-1,2-Dichloroethene U U U U							2.6E-06	
1,3 Dichlorobenzene U U U U U U U U U U U U U U U U U U U 0.0E-06 2.6 6.0E-06 2.6 6.0E-06 2.6 6.0E-06 0.0E-06								
1,4 Dichlorobenzene U U U U U U U U U 0.0E-06 2.6 6.0E-06 6.0E-06 6.0E-06 1.0E-06 0.0E-06 0.0E-06	,	U		U		U		
Dichlorodifluoromethane	1,3 Dichlorobenzene	U		U		U		
1,1 Dichloroethane U U U 1,2 Dichloroethane U U U 1,1 Dichloroethene U U U cis-1,2-Dichloroethene U U U trans-1,2-Dichloroethene U U U								
1,2 Dichloroethane U U U 1,1 Dichloroethene U U U cis-1,2-Dichloroethene U U U trans-1,2-Dichloroethene U U U			6.3E-06		6.3E-06		6.0E-06	
1,1 Dichloroethene U								
cis-1,2-Dichloroethene U U U trans-1,2-Dichloroethene U U U		_				_		
trans-1,2-Dichloroethene U U U		-				_		
14.2 Dishloroothono (total)		-				U		
1,2-Dichloroethene (total) U U U 1,2 Dichloropropane U U U								
c 1,3 Dichloropropene U U U								
Total BTEX U U U								
Total VOCs 236 5.5E-04 136 3.2E-04 187 4.3E-04			5.5E-04		3.2E-04		4.3E-04	

ABBREVIATIONS: ug/m³ - Micrograms per cubic meter

- QUALIFIERS:
 U: Compound analyzed for but not detected.
 J: Analyte detected at or below quantitation limits
- D: Result taken from reanalysis at a secondary dilution

ATTACHMENT G

PERFORMANCE SUMMARY

FRANKLIN CLEANERS SITE NYSDEC CONTRACT No. D004446 / SITE No. 1-30-050 EXTRACTION AND TREATMENT SYSTEM PERFORMANCE RESULTS

	SYSTEM INFLUENT	SYSTEM INFLUENT	SYSTEM INFLUENT	SYSTEM INFLUENT	SYSTEM EFFLUENT		ESTIMATED	ESTIMATED	
	(EW-1) AVERAGE	(EW-1) PCE	(EW-2) AVERAGE	(EW-2) PCE	(AS-1) PCE	PCE REMOVAL	AVERAGE PCE	SYSTEM	ESTIMATED CUMULATIVE
DATE OF SAMPLE	EXTRACTION RATE	CONCENTRATION	EXTRACTION RATE	CONCENTRATION	CONCENTRATION	EFFICIENCY	REMOVAL RATE(3)	RUNTIME	PCE REMOVAL
COLLECTION	(gpm)	(ug/l)	(gpm)	(ug/l)	(ug/l)	(%)	(lb/hr)	(hr)	(lbs)
3/11/2009	40.1	18	5.7	92	< 0.5	99.54	6.24E-04	253	36.13
3/25/2009	39.0	16	5.3	74	< 0.5	99.48	5.09E-04	335	36.30
4/8/2009	39.2	16	5.3	61	< 0.5	99.44	4.76E-04	334	36.46
4/24/2009	40.4	13	5.2	61	< 0.5	99.38	4.22E-04	277	36.58
5/5/2009	39.5	16	5.2	63	< 0.5	99.46	4.81E-04	186	36.67
5/18/2009	40.5	13	5.5	53	< 0.5	99.33	4.10E-04	554	36.89 ⁽¹⁾
6/3/2009	39.5	15	5.3	56	< 0.5	99.40	4.45E-04	65	36.92
6/18/2009	39.1	13	5.2	55	< 0.5	99.35	3.98E-04	326	37.05
7/1/2009	40.3	8	5.5	48	< 0.5	99.09	3.02E-04	308	37.14
7/15/2009	40.3	11	5.3	47	< 0.5	99.23	3.47E-04	144	37.19
7/28/2009	40.6	13	5.4	61	< 0.5	99.37	4.29E-04	458	37.39
8/13/2009	40.4	13	5.3	51	< 0.5	99.33	3.98E-04	382	37.54
8/24/2009	40.2	11	5.3	50	< 0.5	99.25	3.54E-04	449	37.70 ⁽¹⁾
9/8/2009	39.9	13	5.8	53	< 0.5	99.30	4.14E-04	141	37.76
9/25/2009	39.8	12	5.8	57	< 0.5	99.28	4.05E-04	412	37.93
10/5/2009	39.0	10	5.8	54	< 0.5	99.17	3.50E-04	241	38.01
10/26/2009	39.5	12	5.7	56	< 0.5	99.28	3.97E-04	495	38.21
11/9/2009	36.0	8	5.4	48	< 0.5	99.03	2.79E-04	324	38.30
11/24/2009	37.5	11	5.5	51	< 0.5	99.21	3.47E-04	502	38.47 ⁽¹⁾
12/8/2009	36.2	12	5.4	50	< 0.5	99.23	3.53E-04	172	38.53
12/26/2009	36.3	13	5.2	55	< 0.5	99.31	3.80E-04	307	38.65
1/4/2010	36.8	13	5.1	54	< 0.5	99.32	3.77E-04	256	38.75
1/21/2010	37.5	14	5.3	62	< 0.5	99.38	4.27E-04	408	38.92
2/5/2010	32.9	12	5.3	47	< 0.5	99.18	3.22E-04	343	39.03
2/19/2010	31.4	15	6.3	55	0.82	98.74	4.09E-04	564	39.26 ⁽¹⁾
3/4/2010	34.4	16	5.8	60	< 0.5	99.35	4.50E-04	251	39.38
3/18/2010	33.1	14	6.2	48	< 0.5	99.19	3.81E-04	104	39.42
4/1/2010	33.8	11	5.7	47	< 0.5	99.11	3.20E-04	328	39.52
4/15/2010	34.0	14	6.3	58	< 0.5	99.25	4.21E-04	336	39.66
4/30/2010	33.6	15	6.3	59	< 0.5	99.28	4.21E-04 4.39E-04	342	39.81
5/13/2010	32.2	16	6.4	68	0.52	99.28	4.76E-04	299	39.95
5/28/2010	33.3	14	5.7	76	0.52	98.77	4.76E-04 4.50E-04	440	40.15 ⁽¹⁾
6/10/2010	33.2	16	6.6	65	0.97	99.30	4.81E-04	226	40.15
6/25/2010	33.0	17	6.3	61	< 0.5	99.33	4.61E-04 4.73E-04	322	40.26
7/7/2010	32.8	16	4.8	57	< 0.5 < 0.5	99.33	4.73E-04 4.00E-04	322 148	40.41
			5.3						
7/21/2010 8/5/2010	32.0 31.5	14	4.7	53 52	< 0.5 0.5	99.27	3.65E-04	330 289	40.59 40.70
8/5/2010	33.7	15 16	5.0		0.5	99.34 99.41	3.59E-04 4.25E-04	289 607	40.70 40.95 ⁽¹⁾
	33.7 32.4	16 25		62					
9/23/2010			6.3	58	< 0.12	99.87	5.89E-04	24	40.97
10/7/2010	31.0	19	7.0	63	0.35	99.52	5.16E-04	336	41.14
10/21/2010	31.9	14 17	7.0	51	0.19	99.67	4.02E-04	336	41.28
11/4/2010	31.2		6.3	60	0.20	99.72	4.55E-04	336	41.43
11/19/2010	35.0	16	6.7	56	0.18	99.74	4.68E-04	639	41.73 (1)
12/2/2010	32.6	17	6.9	55	0.18	99.73	4.68E-04	34	41.74
12/16/2010	31.5	16	7.1	56	0.24	99.62	4.51E-04	337	41.90
12/30/2010	33.4	18	6.7	57	< 0.12	99.84	4.92E-04	335	42.06
1/11/2011	29.0	18	7.0 (4)	58	0.13	99.80	4.66E-04	288	42.20
1/28/2011	32.0	16	7.0 (4)	52	< 0.12	99.81	4.39E-04	403	42.37
2/10/2011	30.9	16	7.0 (4)	51	0.19	99.69	4.27E-04	308	42.50
2/24/2011	32.6	18	7.0 (4)	60	< 0.12	99.83	5.05E-04	446	42.73 ⁽¹⁾

NOTES:

ABBREVIATIONS:

gpm: gallons per minute ug/L: micrograms per liter

lb/hr: pounds per hour NS: Not sampled

QUALIFIERS:

- J: Compound found at a concentration below CRDL, value estimated
- B: Compound detected in method blank as well as the sample, value estimated

1. Estimated through the end of the reporting period.

- 2. Performance results for the reporting period are shaded.
- 3. Mass removal rate(lb/hr) = flow(gpm)*concentration(ug/l)*3.79(liters/gallon)*1E-6(g/ug)*2.2E-3(lb/g)*60(min/hr)
- 4. Extraction well EW-2 flow meter malfunctioning and not recording flow rate. Value based on average flow rate for the reporting period.

ATTACHMENT H

DATA VALIDATION CHECKLISTS

Project Name:	Franklin Cleaners aka Hem	pstead
Project Number:	2531-08	
Sample Date(s):	December 2,2010	
Matrix/Number of Samples:	Water/3 (EW-1, EW-2 and Trip Blank/0	1 AS)
Analyzing Laboratory:	TestAmerica Laboratories,	Shelton, CT
Analyses:		nds (VOCs): 40 CFR Part 136 method 624 te by USEPA SW846 Method 6010B
Laboratory Report No:	220-14217	Date:12/17/2010

ORGANIC ANALYSES vocs

	Reported		Performance Acceptable		Not	
,	No	Yes	No	Yes	Required	
1. Holding times	1	Х		X		
2. Blanks						
A. Method blanks		Х		X	•	
B. Trip blanks					X	
C. Field blanks	1				X	
3. Laboratory Control Sample (LCS) %R		X	X		-	
4. Surrogate spike recoveries		X		Х		
5. Field duplicates RPD					X	

VOCs - volatile organic compounds

%R - percent recovery

RPD - relative percent difference

Comments:

Performance was acceptable.

INORGANIC ANALYSES

Metals

	Reported		Performance Acceptable		Not
	No	Yes	No	Yes	Required
Holding times		X		X	
2. Blanks					
A. Method blanks		X		X	
B. Field blanks					X
3. Laboratory Control Sample (LCS) %R					X
4. Field duplicates RPD					X
R - percent recovery	RPD - re	lative percent	difference		

Comments:

VALIDATION PERFORMED BY & DATE:	Donna M. Brown	3/7/2011
VALIDATION PERFORMED BY SIGNATURE:	2	72

Project Name:	Franklin Cleaners aka H	empstead
Project Number:	2531-08	
Sample Date(s):	December 16, 2010	
Matrix/Number of Samples:	Water/ 3 (EW-1, EW-2 Trip Blank/0	and AS)
Analyzing Laboratory:	TestAmerica Laboratori	es, Shelton, CT
Analyses:		ounds (VOCs): 40 CFR Part 136 method 624 nese by USEPA SW846 Method 6010B
Laboratory Report No:	220-14391	Date:01/03/2011

ORGANIC ANALYSES VOCS

	Rep	Reported		rmance eptable	Not	
	No	Yes	No	Yes	Required	
Holding times		X		X		
2. Blanks						
A. Method blanks		X		X		
B. Trip blanks					X	
C. Field blanks	*.				X	
3. Laboratory Control Sample (LCS) %R					X	
4. Surrogate spike recoveries		X		X		
5. Field duplicates RPD			-		X	

VOCs - volatile organic compounds

%R - percent recovery

RPD - relative percent difference

Comments:

Performance was acceptable.

INORGANIC ANALYSES

Metals

	Reported		Performance Acceptable		Not
	No	Yes	No	Yes	Required
Holding times		X		X	
2. Blanks					
A. Method blanks		X		X	
B. Field blanks			·		X
3. Laboratory Control Sample (LCS) %R	-				X
4. Field duplicates RPD					X
R - percent recovery	RPD - re	lative percent	difference		

Comments:

VALIDATION PERFORMED BY & DATE:	Donna M. Brown 3/7/2011
VALIDATION PERFORMED BY SIGNATURE:	el -R-

Project Name:	Franklin Cleaners aka Her	npstead
Project Number:	2531-08	
Sample Date(s):	December 30,2010	
Matrix/Number of Samples:	Water/ 3 (EW-1, EW-2 an Trip Blank/0	d AS)
Analyzing Laboratory:	TestAmerica Laboratories	, Shelton, CT
Analyses:		nds (VOCs): 40 CFR Part 136 method 624 se by USEPA SW846 Method 6010B
Laboratory Report No:	220-14483	Date:1/13/2011

ORGANIC ANALYSES VOCS

	Reported		Performance Acceptable		Not	
	No	Yes	No	Yes	Required	
1. Holding times		X		X		
2. Blanks						
A. Method blanks		X		X		
B. Trip blanks					Х	
C. Field blanks					X	
3. Laboratory Control Sample (LCS) %R					X	
4. Surrogate spike recoveries		X		Х		
5. Field duplicates RPD					X	

VOCs - volatile organic compounds

%R - percent recovery

RPD - relative percent difference

Comments:

Performance was acceptable.

INORGANIC ANALYSES

Metals

	Reported		Performance Acceptable		Not
	No	Yes	No	Yes	Required
1. Holding times		X		X	
2. Blanks					
A. Method blanks		X		X	
B. Field blanks					X
3. Laboratory Control Sample (LCS) %R					X
4. Field duplicates RPD					X
%R - percent recovery	RPD - re	lative percent	difference		

Comments:

VALIDATION PERFORMED BY & DATE:	Donna M. Brown	3/7/2011
VALIDATION PERFORMED BY SIGNATURE:	29	Par

Project Name:	Franklin Cleaners aka Her	mpstead
Project Number:	2531-08	
Sample Date(s):	January 11,2011	
Matrix/Number of Samples:	Water/ 3 (EW-1, EW-2 and Trip Blank/0	d AS)
Analyzing Laboratory:	TestAmerica Laboratories	, Shelton, CT
Analyses:		nds (VOCs): 40 CFR Part 136 method 624 se by USEPA SW846 Method 6010B
Laboratory Report No:	220-14557	Date:1/24/2011

ORGANIC ANALYSES VOCS

	Reported		Performance Acceptable		Not
	No	Yes	No	Yes	Required
1. Holding times		X		X	
2. Blanks					
A. Method blanks		Х		X	
B. Trip blanks					X
C. Field blanks					X
3. Laboratory Control Sample (LCS) %R					X
4. Surrogate spike recoveries		X		X	
5. Field duplicates RPD					X

VOCs - volatile organic compounds

%R - percent recovery

RPD - relative percent difference

Comments:

Performance was acceptable.

INORGANIC ANALYSES

Metals

	Reported		Performance Acceptable		Not
	No	Yes	No	Yes	Required
1. Holding times		X		X	
2. Blanks					
A. Method blanks		X		X	
B. Field blanks					X
3. Laboratory Control Sample (LCS) %R					X
4. Field duplicates RPD					X
%R - percent recovery	RPD - re	lative percent	difference		

Comments:

VALIDATION PERFORMED BY & DATE:	Donna M. Brown 3/7/2011
VALIDATION PERFORMED BY SIGNATURE:	ee ~ R

Project Name:	Franklin Cleaners aka He	empstead
Project Number:	2531-08	
Sample Date(s):	January 28,2011	
Matrix/Number of Samples:	Water/ 3 (EW-1, EW-2 a Trip Blank/0	and AS)
Analyzing Laboratory:	TestAmerica Laboratorio	es, Shelton, CT
Analyses:		unds (VOCs): 40 CFR Part 136 method 624 lese by USEPA SW846 Method 6010B
Laboratory Report No:	220-14665	Date:02/08/2011

ORGANIC ANALYSES VOCS

	Rep	Reported		rmance eptable	Not
	No	Yes	No	Yes	Required
1. Holding times		X		X	
2. Blanks					
A. Method blanks		X		X	
B. Trip blanks					X
C. Field blanks					X
3. Laboratory Control Sample (LCS) %R					X
4. Surrogate spike recoveries		X		X	
5. Field duplicates RPD				,	X

VOCs - volatile organic compounds

%R - percent recovery

RPD - relative percent difference

Comments:

Performance was acceptable.

INORGANIC ANALYSES

Metals

	Reported		Performance Acceptable		Not
	No	Yes	No	Yes	Required
Holding times		X		X	
2. Blanks					
A. Method blanks		X		. X	
B. Field blanks					X
3. Laboratory Control Sample (LCS) %R					X
4. Field duplicates RPD					X
R - percent recovery	RPD - re	lative percent	difference		

Comments:

VALIDATION PERFORMED BY & DATE:	Donna M. Brown 3/7/2011
VALIDATION PERFORMED BY SIGNATURE:	en man

Project Name:	Franklin Cleaners aka Hen	pstead
Project Number:	2531-03	
Sample Date(s):	February 3, 2011	
Matrix/Number of Samples:	Air/3 (Carbon Inlet and O	utlets)
Analyzing Laboratory:	TestAmerica Laboratories	Knoxville, TN
Analyses:	Volatile Organic Compou	nds (VOCs): TO15
Laboratory Report No:	H1B080494	Date:2/16/2011

ORGANIC ANALYSES

VOCS

	Reported		Performance Acceptable		Not
	No	Yes	No	Yes	Required
1. Holding times		X		X	
2. Method blanks		X		X	
3. Laboratory Control Sample (LCS) %R		X		X	
4. Surrogate spike recovery		X		X	
5. Field duplicates RPD					X

VOCs - volatile organic compounds

%R - percent recovery

Comments:

Performance was acceptable with the following exceptions:

The laboratory used a one-point calibration for ethanol and ethanol was qualified as estimated (J/UJ) in all samples.

Propene was qualified as estimated (J) in LAG CARBON OUTLET and LEAD CARBON OUTLET due to an interfering non-target analyte.

VALIDATION PERFORMED BY & DATE:	Donna M. Brown 3/7/2011
VALIDATION PERFORMED BY SIGNATURE:	e R

Project Name:	Franklin Cleaners aka	Hempstead
Project Number:	2531-08	
Sample Date(s):	February 10,2011	·
Matrix/Number of Samples:	Water/ 3 (EW-1, EW-2 Trip Blank/0	2 and AS)
Analyzing Laboratory:	TestAmerica Laborato	ries, Shelton, CT
Analyses:		counds (VOCs): 40 CFR Part 136 method 624 anese by USEPA SW846 Method 6010B
Laboratory Report No:	220-14734	Date:3/1/2011

ORGANIC ANALYSES

	Reported		Performance Acceptable		Not
	No	Yes	No	Yes	Required
1. Holding times		X		X	
2. Blanks					
A. Method blanks		X		X	·
B. Trip blanks					X
C. Field blanks					X
3. Laboratory Control Sample (LCS) %R		X	X		
4. Surrogate spike recoveries		X		X	
5. Field duplicates RPD					X

VOCs - volatile organic compounds

%R - percent recovery

RPD - relative percent difference

Comments:

Performance was acceptable with the following exception:

3. The %R exceeded QC limits for carbon tetrachloride in the laboratory control sample. It was not detected in the associated samples and therefore the data was acceptable.

INORGANIC ANALYSES

Metals

	Rep	Reported		rmance eptable	Not
	No	Yes	No	Yes	Required
1. Holding times		X		X	
2. Blanks					
A. Method blanks		X		X	
B. Field blanks					X
3. Laboratory Control Sample (LCS) %R					X
4. Field duplicates RPD					X

%R - percent recovery

RPD - relative percent difference

Comments:

VALIDATION PERFORMED BY & DATE:	Donna M. Brown 3/7/2011
VALIDATION PERFORMED BY SIGNATURE:	el-p

Project Name:	Franklin Cleaners aka Hempstead
Project Number:	2531-08
Sample Date(s):	February 24,2011
Matrix/Number of Samples:	Water/3 (EW-1, EW-2 and AS) Trip Blank/0
Analyzing Laboratory:	TestAmerica Laboratories, Shelton, CT
Analyses:	Volatile Organic Compounds (VOCs): 40 CFR Part 136 method 624 Metals: Iron and manganese by USEPA SW846 Method 6010B
Laboratory Report No:	220-14809 Date:3/16/2011

ORGANIC ANALYSES VOCS

	Reported		Performance Acceptable		Not
	No	Yes	No	Yes	Required
1. Holding times		X		X	
2. Blanks					
A. Method blanks		X		X	
B. Trip blanks					X
C. Field blanks					X
3. Laboratory Control Sample (LCS) %R	1	X		X	
4. Surrogate spike recoveries		Х		X	
5. Field duplicates RPD					X

VOCs - volatile organic compounds

%R - percent recovery

RPD - relative percent difference

Comments:

Performance was acceptable with the following exception:

These samples were analyzed twice by the laboratory. The original analysis was inadvertently loaded with the incorrect sample ids. The samples were reanalyzed outside of holding times and used to confirm the correct sample ids in the original analysis. The results were reported from the revised original sample run.

INORGANIC ANALYSES

Metals

	Reported		Performance Acceptable		Not
	No	Yes	No	Yes	Required
Holding times		X		X	
2. Blanks					
A. Method blanks		X		X	
B. Field blanks					X
3. Laboratory Control Sample (LCS) %R					X
4. Field duplicates RPD					X

%R - percent recovery

RPD - relative percent difference

Comments:

 e was deceptable:				
VALIDATION PERFORMED BY & DATE:	Donna M. Brown 3/31/2011			
VALIDATION PERFORMED BY SIGNATURE:	10-mp-			