SUB SLAB VAPOR MITIGATION SYSTEM STARTUP REPORT

SUBMITTED TO:

New York State Department of Environmental Conservation Department of Environmental Remediation 625 Broadway Albany, New York 11207

ON BEHALF OF:

BAE Systems Greenlawn, New York

PREPARED BY:



P.W. Grosser Consulting, Inc. 630 Johnson Avenue, Suite 7 Bohemia, New York 11716 Phone: 631-589-6353 Fax: 631-589-8705

Frank P. Castellano, COO John D. Eichler, Project Manager

PWGC Project Number: BAE1102

frankc@pwgrosser.com johne@pwgrosser.com

P.W. GROSSER CONSULTING INC.

SUB SLAB VAPOR MITIGATION SYSTEM STARTUP REPORT

BAE SYSTEMS BUILDING 2 GREENLAWN, NEW YORK

NYSDEC Site Number: 1-52-005

SEPTEMBER 2013

TABLE OF CONTENTS

1.0		
1.1	Site Description	4
1.2	Background	4
2.0	SSVM INSTALLATION	6
2.1	System Description	6
2.2	System Details	6
2.3	Vacuum Blower Systems	7
2.4	BMS and VFD Functionality	
3.0	SYSTEM STARTUP	8
3.1	Pre-Commissioning Check	8
3.2	Pre-Startup Functional Performance System Inspection	
3.3	System Startup / Full Scale Demonstration	8
4.0	CARBON TREATMENT	12
5.0	CONCLUSIONS	13

LIST OF FIGURES

Figure 1 Vicinity Map
Figure 2 Site Facility Map

Figure 3 Site Plan

Figure 4 Site Plan with Optimal Pressure Readings

LIST OF APPENDICIES

Appendix A SSVM Detail Drawing Appendix B Photographs

Appendix C Pre-Commissioning Check List
Appendix D Blower #4 Function Test Results

Appendix E Startup Log
Appendix F Air Screen Results

1.0 INTRODUCTION

P.W. Grosser Consulting, Inc. (PWGC) has prepared this Sub-Slab Vapor Mitigation System Startup Report on behalf of BAE Systems (BAE) in order to document the startup activities for the sub-slab vapor mitigation (SSVM) system installed at BAE Systems Building 2 in Greenlawn, New York. The site is currently listed on the New York State Department of Environmental Conservation (NYSDEC) Legacy Site Listing (Site Code 1-52-005), due to the detection of chlorinated volatile organic compounds (VOCs) in the subject building's sub-slab vapors.

1.1 Site Description

BAE Building 2 is one of five main buildings located at a facility which covers approximately 23 acres in Greenlawn, New York. The facility is located southeast of the intersection of Cuba Hill Road and the Port Jefferson Branch of the Long Island Railroad as illustrated on **Figure 1**. Building 2 resides on the east side of Cuba Hill Road as illustrated on **Figure 2**.

1.2 Background

The BAE site was classified as a Class 2 Inactive Hazardous Waste Disposal site in March 1994 as a result of the detection of VOCs, specifically tetrachloroethylene (PCE), in shallow soils beneath the former Alodine Room. The site was reclassified as a Class 4 site in May 1995 and delisted in September 1997. The presence of the PCE was documented in the early 1990s during a Resource Conservation Recovery Act (RCRA) Closure of the Alodine Room by BAE's predecessor, Hazeltine Corp. While the conditions at the site were known to the NYSDEC at that time, the conditions were not actionable by the Department and no action beyond an application of an epoxy floor coating for the Alodine Room was required. Recent (2006) guidance policy changes in the New York State Department of Health (NYSDOH) regarding the potential for soil vapor intrusion has required the NYSDEC to review their closed case files to identify known sites where previously documented conditions have the potential to create a vapor intrusion problem. Over 400 sites are currently listed as Legacy Sites as a result of the vapor intrusion policy changes.

In March and April of 2010, the NYSDEC, through its subcontractor AECOM Technical Services Northeast, Inc of Bloomfield, NJ, performed an investigation in and around

Building 2 to evaluate current subsurface conditions. The investigation primarily focused on the soil quality and soil vapor conditions beneath, and in the vicinity of, the former Alodine Room. While the investigation revealed the presence of PCE in soil samples, the detected concentrations were not actionable as they were below NYSDEC's Industrial Soil Cleanup Objectives (SCOs). The investigation did confirm the presence of soil vapor conditions beneath portions of the Building 2 floor slab that, when compared to NYSDOH soil vapor criteria, would require mitigation measures to prevent the potential for migration of the soil vapors into the occupied building space. The results of the AECOM investigation are contained in their draft report entitled *Draft Soil Vapor Evaluation*, *Hazeltine Corporation*, *Site No. 1-52-005*, *June 2010*.

BAE met with the NYSDEC in September 2010 to discuss the project and gain their concurrence for the path forward. In response to the findings of AECOM's investigation, BAE voluntarily performed extensive investigation in order to define the extent of the soil vapor condition at Building 2 and design a mitigation measure, the SSVM system. The system was installed in December 2012.

2.0 SSVM INSTALLATION

2.1 System Description

The engineering control installed at the site consists of the installation of four SSVM pits which are utilized to create a negative pressure gradient in the sub-slab environment of Building 2 through the use of four high-flow vacuum pumps. Each system creates a radius of influence (ROI) which covers a portion of the building's sub-slab.

Each system is comprised of an SSVM pit with indoor and outdoor piping running to a dedicated roof mounted blower unit. A detail drawing of the system is included as **Appendix A**. Photos of the system and its construction are included as **Appendix B**.

Each blower system has integral local and remote monitoring capabilities tied to Building 2's Building Management System (BMS). The variable frequency drives (VFDs) operate the blower's electric motors, allowing the vacuum and flow rate produced by the blower to be adjusted manually or remotely via the BMS. Each individual blower system operates at a vacuum and flow rate which has been field-calibrated to provide the ROI required for each respective blower system. The BMS monitors pressure transmitters within each of the systems' process streams to provide operating consistency.

2.2 System Details

The initial pit (pit location 3) was constructed for the pilot test with the intent of incorporating it into the final system design. The design of the pit is based on EPA/625/R-92/016, June 1994. As the final design called for a total of four main SSVM pits, three additional pits were constructed identical to the pilot test pit as described below.

At each pit location, a 4'x4' square was saw cut out of the concrete floor slab. The underlying material was excavated to a depth of approximately 19 inches. A 3" thick non-reinforced concrete support slab was installed at the bottom of the excavation. Once the concrete cured, a 3'x3'x1' prefabricated metal box, consisting of a 2"x 2"x1/4" metal frame with 304 stainless steel expanded metal welded to the frame on all six sides, was placed upon the concrete support slab. A 4" diameter galvanized steel pipe penetrates the expanded metal on one side, extending approximately 10" into the center

of the prefabricated box. On the exterior of the box, the steel pipe angles up at 90 degrees to run parallel to the nearest wall. The excavation was backfilled around the box and riser pipe with crushed aggregate meeting specifications as defined in ASTMC-33-90. A vapor barrier was installed above the metal box and surrounding aggregate backfill. A new 4" thick, reinforced concrete slab was poured flush with the existing slab. The riser pipe penetration through the new slab was sealed with non-voc emitting elastomeric joint sealant. The riser pipes penetrate the roof and run horizontally to the blower assembly and ultimately the final exhaust stack location.

2.3 Vacuum Blower Systems

Four (4) 2-HP Ametek Rotron regenerative vacuum blower systems are located on the roof in the vicinity of the riser pipe roof penetrations. The blower assemblies were fabricated off-site by J. E. Gasho and Associates, Inc. and are housed in a custom steel weatherproof blower enclosure. A rubber vibration pad was installed between the roof and the blower assembly to reduce potential noise and vibration created by the blower.

2.4 BMS and VFD Functionality

The vacuum blower system electric motors are operated by VFD. The operating speeds of the VFDs were adjusted during start-up so that the blower systems provide optimal coverage for vapor mitigation while operating most efficiently. The optimization process for the subject system is described in Section 3.3.

Each vacuum blower process stream is equipped with pressure transmitters. These transmitters are connected to the BMS. The BMS is programmed with adjustable set points which are utilized to indicate if the vacuum blower systems are functioning outside of the field-calibrated operation parameters. The BMS is programmed to provide an alarm to alert facilities management personnel of deviations from the operational set points. The setting of these system alarms is currently in the calibration stage.

3.0 SYSTEM STARTUP

The objectives of the commissioning and start-up phase of the SSVM system were to:

- Confirm that the system has been constructed as designed;
- Check that the equipment operates as specified;
- Facilitate modifications to the system based on observations of site conditions that were different than expected during system installation; and
- Gather and evaluate operational data.

3.1 Pre-Commissioning Check

The pre-commissioning check is an inspection performed in order to verify that components of the system have been properly installed. A checklist for pre-commissioning activities was prepared by PWGC based upon the final system design. The initial checklist is included as **Appendix C**. The pre-commissioning checklist is a working document that determines if an aspect of the system meets requirements or requires further action. The components of the system were properly installed. The functionality of the pressure alarms is in the calibration stage.

3.2 Pre-Startup Functional Performance System Inspection

After the pre-commissioning checks and individual component testing were successfully completed, the entire system was inspected to verify integrity prior to actual operation. The system was inspected for piping leaks, loose equipment, and to verify that individual components do not interfere with each other. No such deficiencies were noted during the pre-startup functional performance inspection.

3.3 System Startup / Full Scale Demonstration

During the start-up phase, the entire system was put into operation beginning in March 2013. The strategy for start-up was to conduct activities sequentially, comparing observations and test data against design and performance criteria. This allowed the system to be brought on line in a systematic and safe manner.

The initial speed for each blower was set at 45 Hz. To test the system's performance, communication testing was performed utilizing a digital manometer, which measures the pressure differential between the indoor air and the sub-slab of the subject building. The

initial communication testing was performed utilizing 10 permanent sub-slab vapor monitoring points and 6 temporary sub-slab monitoring points. Monitoring points are indicated on **Figure 3**. The permanent points are the sampling ports previously utilized for VOC vapor sampling, while the temporary points were installed specifically to test the SSVM system and are generally in areas furthest from the suction pits, where the influence would most likely be weakest.

During startup, leaks were audible in the areas of each of the suction pits. The leaks were due to the vapor barrier and adhesive along the edge of the slab creating a pathway for air along the border between the existing floor and the newly-poured floor above the suction pits. In April 2013, the leaks were sealed with StegoTack™ and Stego™ vapor retarding tape. Subsequent communication testing results indicated improved functionality of the system.

Following leak sealing, temperature readings at blower #4 became significantly higher, putting into question the operational ability of blower #4. Therefore, an individual function test was performed on the blower #4 and, for comparison, blower #1. Based on the results of the test, blower #4 is operating correctly and within specifications.

The procedure for the tests was to operate the blower with the pit valve closed and the dilution valve on the roof open. This setup enabled the blower to be run with minimal head loss on the system and no effect from the subsurface pit. The dilution valve was opened incrementally at each blower to create different flow conditions. Pressure and flow rates were measured at each increment to generate the flow rate vs. pressure curve shown in **Appendix D**. The test was repeated with each blower running at 45Hz and at 51Hz, then compared to the manufacturer's blower curve.

The tests show no difference in functionality between the two blowers and that the performance of each blower was in accordance with the manufacturer's specifications. The blowers at pits #4 and #1 were determined to be operating as expected. The increased temperature at the blower #4 location appears to be the result of an unexpectedly tight soil formation in Pit #4, limiting vapor flow through the system. In order to reduce the effluent temperature, the blower speed was reduced to 30 Hz.

Subsequent temperature readings confirmed that the temperature reduced to an acceptable level.

The blower #1 speed was increased to 51 Hz in an attempt to increase the area of influence in the southern area of the model shop (the area of MP-8 and TMP-9). The results obtained from TMP-9 following the speed increase indicated a greater negative pressure differential, indicating that the system was operating more effectively in that area.

Negative pressure readings were measured in a majority of the monitoring points. A table indicating the results of the communication testing is included as **Appendix E.** However, there was no pressure differential measured at temporary measuring points TMP-1 (Facilities Storage), TMP-2 (Compressor Room), TMP-3 (Loading Dock), TMP-4 (Model Shop Storage), and TMP-5 (Model Shop). During drilling, it was noted that the soils at monitoring points TMP-1, TMP-4, and TMP-5 consisted of clay. It appears that clay soils prevail near the building footings, where these monitoring points are located. The clay prevents a pathway for sub-slab vapors at these locations and therefore no further response is deemed necessary in these areas.

Based on the initial rounds of communication testing, the effectiveness of the system was confirmed for most of the building. However, PWGC concluded that additional monitoring points would be necessary to further evaluate system effectiveness.

In August 2013, five additional temporary monitoring points TMP-7 (Metrology), TMP-8 (Metrology), TMP-9 (Model Shop), TMP-10 (Model Shop), and TMP-11 (Mail Room) were installed to obtain additional data regarding system functionality in areas that exhibited low to no pressure gradients in the preliminary communication testing. Due to weak responses at location MP-2 in the Facilities Storage garage, and at MP-3 in the mail room, temporary points TMP-7, TMP-8, and TMP-11 were installed to further evaluate the areas between blower Pits 3 and 4. Results indicated negative pressure beneath the slab at these locations. Based on these readings, the system is functioning as intended in the area between Pits 3 and 4. The results suggest that a blockage may have developed in the MP-3 tubing.

Temporary monitoring points TMP-9 were installed to confirm the results obtained from permanent monitoring point MP-8 located in the Model Shop, where a pressure difference was not detectable. Upon re-testing, an acceptable pressure differential was measured at TMP-9 suggesting a blockage may have developed in the MP-8 tubing.

Temporary monitoring point TMP-10 confirmed the system effectiveness in the northwest area of the building.

Temporary monitoring point TMP-2 is located in the Compressor room. This room is located in what is suspected to be a separate building from Building 2, with a separate foundation. PWGC will perform indoor air sampling in this building as part of the operations and maintenance phase for the system. Specifically, a sample will be collected in the security office adjacent to the compressor room, to determine if elevated VOCs are present in that space.

A monitoring point was not installed in the office located in the southwest corner of the building as this space is a former loading dock which currently has a raised wood floor. PWGC will perform indoor air sampling in this office during the operations and maintenance phase for the system, to determine if elevated VOCs are present in that space.

Temporary monitoring point TMP-3 is located in the building's current loading dock which is surrounded by footings. It is likely that these footings prevent the system from effecting the loading dock.

Figure 4 indicates the pressure differentials at monitoring locations throughout the building. The negative pressure readings indicate that the system is operating as intended. Based on this, the startup phase for the system is complete and the system is ready for transition into the operations and maintenance phase.

4.0 CARBON TREATMENT


PWGC used data from the SSVM pilot test input into the NYSDEC Division of Air Resources DAR-1 software version 3.6 for initial impact screening. The highest PCE concentration from the pilot test was used in determining emission rates. Based on the DAR-1 impact screening analysis, there was one predicted exceedence above NYSDEC Annual and Short-term Guideline Concentrations (AGC/SGC) thresholds. Therefore, carbon treatment was placed on Blower 3.


Emissions samples were collected from each of the four blowers following startup. Screening results indicated that emissions were within AGC/SGC thresholds for Blowers 1,2, and 4. Sampling and carbon treatment of Blower 3 continued on a monthly basis until the Blower 3 screening results indicated that levels decreased below the AGC/SGC thresholds. Screening results are included as **Appendix F.** Based on these results, carbon treatment is no longer required for Blower 3.


5.0 CONCLUSIONS


An SSVM system was installed at BAE Systems Building 2 which creates a negative pressure beneath the building's slab, mitigating potential VOC vapors from intruding into the indoor air. Extensive communication testing performed throughout the building has confirmed the effectiveness of the system. Based on the results, the startup phase for the system is complete and the system is ready for transition into the operations and maintenance phase. Tasks included for the O&M phase will include calibration and testing of the pressure alarms, indoor air sampling to confirm system effectiveness, and routine inspection of SSVM components.

FIGURES










APPENDIX A SSVM Detail Drawing



APPENDIX B Photographs



SSVM Suction Pit with expanded steel cage



SSVM Suction Pit with surrounding stone



SSVM suction pit with vapor barrier and re-bar



SSVM suction pit with new floor



Blower #2 within enclosure




Variable Frequency Drives

APPENDIX C Pre-Commissioning Check List

BAE SSVM Start-Up Pre-Operation Checklist

		Pit 1 - Model Shop	Pit 2 - Oracle Training Room	Pit 3 - Tool Crib	Pit 4 - Facilities Storage	Comments
	Inspect Electrical Connec	•	,	,		
1	At VFD	Connections are as designed	All electrical connections appear to be connected as designed			
	At Blower	Connections are as designed	All electrical connections appear to be connected as designed			
	Inspect Mechanical Pipir	ng Connections				
2	Inside	Connections are as designed	All piping connections appear to be connected as designed			
	On Roof	Connections are as designed	All piping connections appear to be connected as designed			
	Inspect Monitoring Equi	pment Connections				
3	Vacuum Transmitter	Not connected to BMS	The vacuum transmitters are NOT connected to the BMS as designed			
	Flow Meter	Not connected to BMS	The flow meters are NOT connected to the BMS as designed			
4	Start all four blowers simultaneously at 50% capacity	Blower started up as expected	All blowers started up at 50% and appear to run as expected			
	Inspect exhaust piping for	or leaks				
5	Inside	Whistling through the concrete slab needs to be sealed	Whistling through the concrete slab needs to be sealed	Whistling through the concrete slab needs to be sealed	Whistling through the concrete slab needs to be sealed	Whistling through the concrete slab needs to be sealed, especially for Pits 1 and 4
	On Roof	No leaks detected				
6	Increase VFD to attain desired ROI	Blower speeds adjusted	Blower speeds adjusted	Blower speeds adjusted	Blower speeds adjusted	Blower speeds adjusted, see communication testing log for details

APPENDIX D Blower #4 Function Test Results



APPENDIX E Startup Log

			Pit 1 -	Pit 2 -		Pit 4 -							Vacuu	m at Monit	oring Point	("WC)						
Date	Iteration #	Parameter	Model	Oracle	Pit 3 -	Facilities	MP-1	MP-2	TMP-1	MP-3	MP-4	TMP-2	MP-5	MP-6	MP-7	MP-8	TMP-3	TMP-4	MP-9	MP-10	TMP-5	TMP-6
	#		Shop	Training	Tool Crib	Storage	Comp.	Fac. Stor.	Facilities	Mail	Fac. EH&S	Sec. out	Reprog.	Mat. Lab.	Oracle	Model	Load. Bay	Storage	PIF Lab	Model	Model	Alodine
Tuesday March 26, 2013		VFD Motor Speed	OFF	OFF	OFF	OFF															0	
		VFD Current		Bas	l seline															+0.379		
sda) 26, 2	1	Flow Rate					0	0	+0.012	+0.025	0	0	0	+0.008	0	0	0	0	0			0
Tue,	1	Temperature					O		10.012	10.023	0	O	O	10.008	O	O		O		10.575		0
ā ⊠		Vacuum at Blower																				
		PID																				
	ł	VFD Motor Speed	OFF	OFF	45 Hz	OFF																
13		VFD Current		0	13 112																	
Tuesday March 26, 2013		Flow Rate																				
iesd h 26	2	Temperature			80 F		0	0	0	0	-0.042	0	-0.358	-0.245	-0.009	0	0	0	-0.080	+0.386	+0.004	-0.016
T.		•			-18" WC						1		1									
_ ≥		Vacuum at Blower PID			-18 VVC																	
			45 11-	45 11-	45 11-	45 11-														1		
m		VFD Motor Speed	45 Hz	45 Hz	45 Hz	45 Hz					-0.060	0			-0.195	0	0	0	-0.256			
201		VFD Current						-0.007	-0.015	-0.006			-0.225	-0.491						+0.328		
esda 26,	3	Flow Rate					0														0	-0.032
Tuesday March 26, 2013		Temperature	90 F	90 F	95 F	97 F																
		Vacuum at Blower	-26" WC	-22" WC	-18" WC	-34" WC																
		PID	+		61.4 ppmV																	
		VFD Motor Speed	45 Hz 2570 rpm	45 Hz	45 Hz	45 Hz	0	-0.007	-0.005				-0.233		-0.18	0 0				 	İ	
013		VFD Current	4.5 A	2580 rpm 4.3 A	2568 rpm 4.7 A	2555 rpm 5.0 A								0.454								
ay 9, 2		Flow Rate	4.5 A	4.5 A	4.7 A	3.0 A				0		_					_	_	0.25	.0.207	_	
Friday March 29, 2013	4		96 F	94 F	98 F	104 F					-0.054	0		-0.451			0	0	-0.25	+0.297	0	-0.02
Marc		Temperature	-27" WC	-20" WC	-18" WC	-37" WC					-0.044			1 -0.715								
		Vacuum at Blower																				
		PID	0.5 ppmV 45 Hz	0.5 ppmV 45 Hz	27.9 ppmV 45 Hz	45 Hz											+	 	+			
		VFD Motor Speed	2560 rpm	2570 rpm	2570 rpm	2570 rpm			0										-0.431	-0.120		
13		VFD Current	4.9 A	4.5 A	4.7 A	4.9 A											0	0			0	-0.016
Monday May 6, 2013	5	Flow Rate																				
Mor ay 6	_	Temperature	114 F	110 F	106 F	138 F																
Σ		Vacuum at Blower	-34" WC		-19" WC	-40" WC																
		PID																				
	<u> </u>		50 Hz	45 Hz	45 Hz	0==																
		VFD Motor Speed	3000 rpm			OFF																
Monday May 6, 2013		VFD Current	5.6 A	4.5 A	4.7 A																	
nda 6, 2	6	Flow Rate												-0.716		-0.010	0	-0.028	-0.428	-0.137	0	-0.003
Mc //ay		Temperature																				
		Vacuum at Blower																				
		PID																				
		VFD Motor Speed	50 Hz 3000 rpm	52 Hz 3100 rpm	45 Hz 2570 rpm	OFF																
Monday May 6, 2013		VFD Current	5.6 A	5.6 A	4.7 A																	
nda 5, 20	7	Flow Rate										0		-0.781	-0.297	-0.002	0	0	-0.479	-0.148		-0.018
Mo lay (1 '	Temperature	125 F	110 F								Ť				-0.002		Ĭ	5.175	0.2.10		3.010
M		Vacuum at Blower	-38" WC																			
		PID																				
	1		<u> </u>	1	l .	l		1	l										1	1	1	l

Date Ite	eration #	Danamata:	Pit 1 -	Pit 2 -	D D	Pit 4 -																					
	# 1	Parameter	Model	Oracle	Pit 3 -	Facilities	MP-1	MP-2 T	MP-1	MP-3	MP-4	TMP-2	MP-5	MP-6	MP-7	MP-8	Monitoring TMP-3	TMP-4	MP-9	MP-10	TMP-5	TMP-6	TMP-7	TMP-8	TMP-9	TMP-10	TMP-11
	TT .		Shop	Training		Storage	Comp.		cilities		Fac. EH&S			Mat. Lab.		Model	Load. Bay		PIF Lab	Model	Model		Metrology			Model	Mail
	,	VFD Motor Speed	50 Hz 3000 rpm	45 Hz 2574 rpm	45 Hz 2570 rpm	OFF																					
× 113	Ī	VFD Current	5.6 A																								i
Thursday May 9, 2013	8	Flow Rate								-0.007	-0.026	0	-0.364	-0.740	-0.276	0	0	0	-0.426	-0.187	0	-0.064					i
Thui lay 9	F	Temperature	110 F							0.007	0.020	Ü	0.00	0.7.10	0.270	ŭ			01.120	0.207	Ü	0.001					I
2	Ī	Vacuum at Blower	-38" WC	-26" WC	-20" WC																						I
	Ī	PID																									i
	,	VFD Motor Speed	50%	50%	50%	OFF																					ı
13	-	VFD Current																									I
Thursday May 9, 2013	_ [Flow Rate									0.000			0.700					0.40=	0.440							1
hurs ay 9,	9	Temperature	104 F							0	-0.026		-0.369	-0.790	-0.315	0	0	0	-0.495	-0.148	0	0					I
⊢≌	Ī	Vacuum at Blower	-34" WC																								1
	ľ	PID																									1
		VFD Motor Speed	50 Hz	45 Hz	45 Hz	30 Hz																					i
Monday August 19, 2013	Ī	VFD Current																									I
day .9, 2		Flow Rate																					2.55	0.000			
Jon 1st 1	10	Temperature																					-3.66	-0.068	-0.095	-0.034	-0.007
Nugr	-	Vacuum at Blower																									I
1	ŀ	PID																									I
		VFD Motor Speed																									
	-	VFD Current																									İ
	11	Flow Rate																									I
		Temperature																									1
	Ī	Vacuum at Blower																									1
	ľ	PID																									I
		VFD Motor Speed																									1
	Ī	VFD Current																									1
	12	Flow Rate																									I
		Temperature																									1
	Ī	Vacuum at Blower																									I
	Ī	PID																									I
		VFD Motor Speed																									
	Ī	VFD Current																									1
	13	Flow Rate																									I
		Temperature																									1
	-	Vacuum at Blower																									I
	Ī	PID																									I
		VFD Motor Speed																									
	ļ	VFD Current																									1
		Flow Rate																									1
		Temperature																									1
		Vacuum at Blower																									1
	-	PID																									1

APPENDIX F Air Screen Results

```
*** SCREEN3 MODEL RUN ***
*** VERSION DATED 13043 ***
```

No Title

```
SIMPLE TERRAIN INPUTS:

SOURCE TYPE = POINT

EMISSION RATE (G/S) = 0.250000E-02

STACK HEIGHT (M) = 7.3152

STK INSIDE DIAM (M) = 0.0509

STK EXIT VELOCITY (M/S) = 18.6257

STK GAS EXIT TEMP (K) = 293.1500

AMBIENT AIR TEMP (K) = 293.1500

RECEPTOR HEIGHT (M) = 0.0000

URBAN/RURAL OPTION = RURAL

BUILDING HEIGHT (M) = 4.8768

MIN HORIZ BLDG DIM (M) = 60.9600

MAX HORIZ BLDG DIM (M) = 121.9200
```

THE REGULATORY (DEFAULT) MIXING HEIGHT OPTION WAS SELECTED. THE REGULATORY (DEFAULT) ANEMOMETER HEIGHT OF 10.0 METERS WAS ENTERED.

BUOY. FLUX = $0.000 \text{ M}^{**}4/\text{S}^{**}3$; MOM. FLUX = $0.225 \text{ M}^{**}4/\text{S}^{**}2$.

*** FULL METEOROLOGY ***

*** SCREEN AUTOMATED DI STANCES ***

*** TERRAIN HEIGHT OF O. M ABOVE STACK BASE USED FOR FOLLOWING DISTANCES ***

1. 0.000 0 0.0 0.0 0.0 0.00 0.00 0.00 0.00 100. 6.162 6 1.5 1.5 10000.0 7.43 4.07 4.10 200. 6.328 6 1.0 1.0 10000.0 7.81 7.73 5.15	
300. 5.330 6 1.0 1.0 10000.0 7.81 11.23 6.60 400. 4.221 6 1.0 1.0 10000.0 7.81 14.64 7.97 500. 3.350 6 1.0 1.0 10000.0 7.81 17.97 9.28 600. 2.702 6 1.0 1.0 10000.0 7.81 21.24 10.54 700. 2.261 6 1.0 1.0 10000.0 7.81 21.24 10.54 800. 1.905 6 1.0 1.0 10000.0 7.81 27.63 12.40 900. 1.629 6 1.0 1.0 10000.0 7.81 30.78 13.39 1000. 1.424 6 1.0 1.0 10000.0 7.81 33.88 14.17 1100. 1.251 6 1.0 1.0 10000.0 7.81 36.96 15.03 1200. 1.111 6 1.0 1.0 10000.0 7.81 43.04 16.67 1400.	SS SS SS SS SS SS SS SS SS SS SS SS SS

```
BAE Final July results. OUT 1.0 1.0 10000.0 7.8
    2500.
                     0. 3972
                                                                                                                  7.81
                                                                                                                                 77. 95
                                                                                                                                                   24.42
                     0. 3760
                                             6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
6 1.0
    2600.
                                                                                                                                                   24.95
                                                                                                                                                                        SS
                                                   6
                                                                 1.0
                                                                                 1. 0 10000. 0
                                                                                                                  7. 81
                                                                                                                                  80.76
                     0. 3567
0. 3390
                                                   6
                                                                                                                  7.81
    2700.
                                                                                 1. 0 10000. 0
                                                                                                                                  83.57
                                                                                                                                                    25.47
                                                                                                                                                                        SS
    2800.
                                                                                 1. 0 10000. 0
                                                                                                                   7.81
                                                                                                                                  86.37
                                                                                                                                                    25.98
                                                                                                                                                                        SS
                     0. 3227
0. 3077
                                                                                 1. 0 10000. 0
                                                                                                                                                                        SS
                                                                                                                  7.81
                                                                                                                                  89.15
    2900.
                                                                                                                                                    26.48
                                                                                                                                  91.92
                                                                                                                                                    26. 98
                                                                                 1.0 10000.0
                                                                                                                  7.81
                                                                                                                                                                        SS
    3000.
    3500.
                     0. 2506
                                                                                1.0 10000.0
                                                                                                                  7.81
                                                                                                                                105.65
                                                                                                                                                   28.98
                                                                                                                                                                        SS
                                                                                1. 0 10000. 0
                     0.2097
                                                                                                                  7.81
                                                                                                                                119, 17
                                                                                                                                                   30.84
                                                                                                                                                                        SS
    4000.
    4500.
                     0. 1792
                                                                                1. 0 10000. 0
                                                                                                                  7.81
                                                                                                                                132.50
                                                                                                                                                   32.57
                     0. 1556
                                                                                1. 0 10000. 0
                                                                                                                  7.81
                                                                                                                                145.67
                                                                                                                                                                        SS
    5000.
                                                                                                                                                   34. 21
                                                                                                                                158.69
    5500.
                     0. 1369
                                                                                1. 0 10000. 0
                                                                                                                  7.81
                                                                                                                                                   35.76
                                                                                                                                                                        SS
    6000.
                     0. 1219
                                                                                1. 0 10000. 0
                                                                                                                  7.81
                                                                                                                                171. 58
                                                                                                                                                   37.23
                                                                                                                                                                        SS
    6500.
                     0.1094
                                                                                 1. 0 10000. 0
                                                                                                                  7.81
                                                                                                                                184.34
                                                                                                                                                    38.64
                                                                                                                                                                        SS
                                                                                 1. 0 10000. 0
                                                                                                                                196.99
                     0. 9908E-01
                                                                                                                                                   40.00
                                                                                                                                                                        SS
    7000.
                                                                                                                  7.81
                     0. 9062E-01
                                                                                1. 0 10000. 0
                                                                                                                  7.81
                                                                                                                                209. 54
                                                                                                                                                                        SS
    7500.
                                                                                                                                                   41. 16
                     0.8335E-01
    8000.
                                                                                1. 0 10000. 0
                                                                                                                  7.81
                                                                                                                                221.98
                                                                                                                                                   42.28
                                                                                                                                                                        SS
    8500.
                     0. 7706E-01
                                                                                1. 0 10000. 0
                                                                                                                  7.81
                                                                                                                                234.34
                                                                                                                                                   43.36
                                                                                                                                                                        SS
                     0. 7156E-01
                                                                                1. 0 10000. 0
                                                                                                                                                                        SS
    9000.
                                                                                                                  7.81
                                                                                                                                246.61
                                                                                                                                                   44.40
                     0. 6673E-01
                                                                                                                                                                        SS
    9500.
                                                                                1.0 10000.0
                                                                                                                  7.81
                                                                                                                                258.79
                                                                                                                                                   45.41
                     0. 6244E-01
                                                                                1. 0 10000. 0
                                                                                                                                                                        SS
  10000.
                                                                                                                  7.81
                                                                                                                                270.90
                                                                                                                                                   46.38
                     0. 3695E-01
                                                                                1. 0 10000. 0
1. 0 10000. 0
                                                                                                                                388.43
                                                                                                                                                                       SS
  15000.
                                                                                                                  7.81
                                                                                                                                                   54.88
  20000.
                     0. 2613E-01
                                                                                                                  7.81
                                                                                                                                500.95
                                                                                                                                                   60.29
                                                                                                                                                                        SS
                                                                                 1. 0 10000. 0
                                                                                                                                609.75
                                                                                                                                                                        SS
                     0. 1998E-01
                                                                                                                  7.81
                                                                                                                                                   64.86
  25000.
                     0. 1605E-01
                                                                               1. 0 10000. 0
                                                                                                                  7.81
                                                                                                                               715.59
                                                                                                                                                                        SS
  30000.
                                                                                                                                                   68.84
                                                                                 1. 0 10000. 0
  40000.
                     0. 1155E-01
                                                                                                                  7.81
                                                                                                                              920. 22
                                                                                                                                                   74.49
                                                                                                                                                                        SS
                     0.8949E-02
                                                                           1. 0 10000. 0
                                                                                                                  7.81 1117.42
                                                                                                                                                   79.19
  50000.
                                                                1. 0
MAXIMUM 1-HR CONCENTRATION AT OR BEYOND
                                                                                                 1. M:
                                                                              1. 0 10000. 0
                     6. 387
                                      6
                                                                 1.0
                                                                                                                  7. 81 6. 98
                                                                                                                                                4. 83
                                                                                                                                                                       SS
                     MEANS NO CALC MADE (CONC = 0.0)
  DWASH=
  DWASH=NO MEANS NO BUILDING DOWNWASH USED
  DWASH=HS MEANS HUBER-SNYDER DOWNWASH USED
  DWASH=SS MEANS SCHULMAN-SCIRE DOWNWASH USED
  DWASH=NA MEANS DOWNWASH NOT APPLICABLE, X<3*LB
        *** REGULATORY (Default) ***
PERFORMING CAVITY CALCULATIONS
*** CAVITY CALCULATION - 1 ***
                                                                                  *** CAVITY CALCULATION - 2 ***
   CAVITY CALCULATION - 1

CONC (UG/M**3) = 0.000

CRIT WS @10M (M/S) = 99.99

CRIT WS @ HS (M/S) = 99.99

DILUTION WS (M/S) = 99.99

CAVITY HT (M) = 4.88

CAVITY LENGTH (M) = 29.43
                                                                                    CAVITY CALCULATION -
CONC (UG/M**3) =
CRIT WS @10M (M/S) =
CRIT WS @ HS (M/S) =
DILUTION WS (M/S) =
CAVITY HT (M) =
CAVITY LENGTH (M) =
                                                                                                                                          0.000
                                                                                                                                          99.99
                                                                                                                                          99.99
                                                                                                                                          99.99
                                                                                                                                          4. 88
                                                                                                                                        25.86
    ALONGWIND DIM (M)
                                                       60. 96
                                                                                     ALONGWIND DIM (M)
                                            =
                                                                                                                                        121.92
CAVITY CONC NOT CALCULATED FOR CRIT WS > 20.0 M/S. CONC SET = 0.0
END OF CAVITY CALCULATIONS
           ********
           *** SUMMARY OF SCREEN MODEL RESULTS ***
```

BAE Final July results. OUT

CALCULATI ON	MAX CONC	DIST TO	TERRAIN
PROCEDURE	(UG/M**3)	MAX (M)	HT (M)
SIMPLE TERRAIN	6. 387	178.	0.



File Edit Windows Help



Output Text

Summary Auto-Distances Discrete Complex Cavity

Maximum Concentrations

Calculation Procedure	Distance To Max.	Maximum 1-Hr Conc	Maximum 3-Hr Conc	Maximum 8-Hr Conc	Maximum 24-Hr Conc	Maximum Ann Conc
	(m)	(μg/m³)	(μg/m³)	(µg/m³)	(μg/m³)	(μg/m³)
Simple Ter	178.00	6.387390	5.748651	4.471173	2.554956	0.510991

Note: Distance to Max is cavity length and Terrain Height is cavity height for cavity concentions. Scalars for 3-Hr, 8-Hr, 24-Hr and Annual periods can be changed (see File|Preferences...).

View Output File



ANALYTICAL REPORT

Lab Number: L1313216

Client: P. W. Grosser

630 Johnson Avenue

Suite 7

Bohemia, NY 11716

ATTN: John Eichler Phone: (631) 589-6353

Project Name: BAE-GREENLAWN

Project Number: BAE 1102 Report Date: 07/22/13

The original project report/data package is held by Alpha Analytical. This report/data package is paginated and should be reproduced only in its entirety. Alpha Analytical holds no responsibility for results and/or data that are not consistent with the original.

Certifications & Approvals: NY (11627), CT (PH-0141), NH (2206), NJ NELAP (MA015), RI (LAO00299), PA (68-02089), LA NELAP (03090), FL (E87814), TX (T104704419), WA (C954), DOD (L2217.01), USDA (Permit #P330-11-00109), US Army Corps of Engineers.

320 Forbes Boulevard, Mansfield, MA 02048-1806 508-822-9300 (Fax) 508-822-3288 800-624-9220 - www.alphalab.com



Project Name: BAE-GREENLAWN Lab Number: L1313216

Project Number: BAE 1102 Report Date: 07/22/13

Alpha Sample ID	Client ID	Sample Location	Collection Date/Time
L1313216-01	BLOWER 3A	5 CUBA HILL RD., GREENLAWN, NY	07/12/13 12:09
L1313216-02	BLOWER 3B	5 CUBA HILL RD., GREENLAWN, NY	07/12/13 12:01
L1313216-03	BLOWER 3C	5 CUBA HILL RD., GREENLAWN, NY	07/12/13 11:51



Project Name: BAE-GREENLAWN Lab Number: L1313216

Project Number: BAE 1102 Report Date: 07/22/13

Project Number: BAE 1102 Report Date: 07/22/13

Case Narrative

The samples were received in accordance with the Chain of Custody and no significant deviations were encountered during the preparation or analysis unless otherwise noted. Sample Receipt, Container Information, and the Chain of Custody are located at the back of the report.

Results contained within this report relate only to the samples submitted under this Alpha Lab Number and meet all of the requirements of NELAC, for all NELAC accredited parameters. The data presented in this report is organized by parameter (i.e. VOC, SVOC, etc.). Sample specific Quality Control data (i.e. Surrogate Spike Recovery) is reported at the end of the target analyte list for each individual sample, followed by the Laboratory Batch Quality Control at the end of each parameter. If a sample was re-analyzed or re-extracted due to a required quality control corrective action and if both sets of data are reported, the Laboratory ID of the re-analysis or re-extraction is designated with an "R" or "RE", respectively. When multiple Batch Quality Control elements are reported (e.g. more than one LCS), the associated samples for each element are noted in the grey shaded header line of each data table. Any Laboratory Batch, Sample Specific % recovery or RPD value that is outside the listed Acceptance Criteria is bolded in the report. Performance criteria for CAM and RCP methods allow for some LCS compound failures to occur and still be within method compliance. In these instances, the specific failures are not narrated but are noted in the associated QC table. This information is also incorporated in the Data Usability format for our Data Merger tool where it can be reviewed along with any associated usability implications. Soil/sediments, solids and tissues are reported on a dry weight basis unless otherwise noted. Definitions of all data qualifiers and acronyms used in this report are provided in the Glossary located at the back of the report.

In reference to questions H (CAM) or 4 (RCP) when "NO" is checked, the performance criteria for CAM and RCP methods allow for some quality control failures to occur and still be within method compliance. In these instances the specific failure is not narrated but noted in the associated QC table. The information is also incorporated in the Data Usability format of our Data Merger tool where it can be reviewed along with any associated usability implications.

Please see the associated ADEx data file for a comparison of laboratory reporting limits that were achieved with the regulatory Numerical Standards requested on the Chain of Custody.

HOLD POLICY

For samples submitted on hold, Alpha's policy is to hold samples free of charge for 30 days from the date the project is completed. After 30 days, we will dispose of all samples submitted including those put on hold unless you have contacted your Client Service Representative and made arrangements for Alpha to continue to hold the samples.

Please contact Client Services at 800-624-9220 with any questions.



Project Name:BAE-GREENLAWNLab Number:L1313216Project Number:BAE 1102Report Date:07/22/13

Case Narrative (continued)

Volatile Organics in Air

Canisters were released from the laboratory on July 12, 2013. The canister certification results are provided as an addendum.

Samples L1313216-01 through -03: Prior to sample analysis, the canisters were pressurized with UHP Nitrogen due to canister size. The pressurization resulted in a dilution of the samples. The reporting limits have been elevated accordingly.

Sample L1313216-01 has elevated detection limits due to the dilution required by the elevated concentrations of target compounds in the sample.

Sample L1313216-01 results for Propylene should be considered estimated due to co-elution with a non-target peak.

I, the undersigned, attest under the pains and penalties of perjury that, to the best of my knowledge and belief and based upon my personal inquiry of those responsible for providing the information contained in this analytical report, such information is accurate and complete. This certificate of analysis is not complete unless this page accompanies any and all pages of this report.

Authorized Signature:

Title: Technical Director/Representative Date: 07/22/13

Christopher J. Anderson

ALPHA

AIR



Project Number: BAE 1102

Lab Number:

Date Collected:

Date Received:

Field Prep:

L1313216

07/12/13 12:09

Not Specified

07/15/13

Report Date: 07/22/13

SAMPLE RESULTS

Lab ID: L1313216-01 D

Client ID: BLOWER 3A

Sample Location: 5 CUBA HILL RD., GREENLAWN, NY

Matrix: Soil_Vapor Anaytical Method: 48,TO-15 Analytical Date: 07/18/13 01:21

Analyst: MB

		ppbV			ug/m3			Dilution
Parameter	Results	RL	MDL	Results	RL	MDL	Qualifier	Factor
Volatile Organics in Air - Mans	sfield Lab							
Propylene	105	72.7		181	125			145.4
Dichlorodifluoromethane	ND	29.1		ND	144			145.4
Chloromethane	ND	29.1		ND	60.1			145.4
Freon-114	ND	29.1		ND	203			145.4
Vinyl chloride	ND	29.1		ND	74.4			145.4
1,3-Butadiene	ND	29.1		ND	64.4			145.4
Bromomethane	ND	29.1		ND	113			145.4
Chloroethane	ND	29.1		ND	76.8			145.4
Ethanol	ND	364		ND	686			145.4
Vinyl bromide	ND	29.1		ND	127			145.4
Acetone	ND	145		ND	344			145.4
Trichlorofluoromethane	ND	29.1		ND	164			145.4
Isopropanol	ND	72.7		ND	179			145.4
1,1-Dichloroethene	ND	29.1		ND	115			145.4
Methylene chloride	ND	145		ND	504			145.4
3-Chloropropene	ND	29.1		ND	91.1			145.4
Carbon disulfide	ND	29.1		ND	90.6			145.4
Freon-113	ND	29.1		ND	223			145.4
trans-1,2-Dichloroethene	ND	29.1		ND	115			145.4
1,1-Dichloroethane	ND	29.1		ND	118			145.4
Methyl tert butyl ether	ND	29.1		ND	105			145.4
Vinyl acetate	ND	29.1		ND	102			145.4
2-Butanone	ND	29.1		ND	85.8			145.4
cis-1,2-Dichloroethene	53.1	29.1		211	115			145.4



Project Number: BAE 1102 Lab Number:

L1313216

Report Date:

07/22/13

SAMPLE RESULTS

Lab ID: L1313216-01 D

Client ID: **BLOWER 3A**

Sample Location: 5 CUBA HILL RD., GREENLAWN, NY Date Collected: 07/12/13 12:09 Date Received:

07/15/13

Field Prep: Not Specified

·		ppbV ug/m3			•	Dilution		
Parameter	Results	RL	MDL	Results	RL	MDL	Qualifier	Factor
Volatile Organics in Air - Mansfi	eld Lab							
Ethyl Acetate	ND	72.7		ND	262			145.4
Chloroform	ND	29.1		ND	142			145.4
Tetrahydrofuran	ND	29.1		ND	85.8			145.4
1,2-Dichloroethane	ND	29.1		ND	118			145.4
n-Hexane	ND	29.1		ND	103			145.4
1,1,1-Trichloroethane	77.5	29.1		423	159			145.4
Benzene	ND	29.1		ND	93.0			145.4
Carbon tetrachloride	ND	29.1		ND	183			145.4
Cyclohexane	ND	29.1		ND	100			145.4
1,2-Dichloropropane	ND	29.1		ND	134			145.4
Bromodichloromethane	ND	29.1		ND	195			145.4
1,4-Dioxane	ND	29.1		ND	105			145.4
Trichloroethene	82.6	29.1		444	156			145.4
2,2,4-Trimethylpentane	ND	29.1		ND	136			145.4
Heptane	ND	29.1		ND	119			145.4
cis-1,3-Dichloropropene	ND	29.1		ND	132			145.4
4-Methyl-2-pentanone	ND	29.1		ND	119			145.4
trans-1,3-Dichloropropene	ND	29.1		ND	132			145.4
1,1,2-Trichloroethane	ND	29.1		ND	159			145.4
Toluene	ND	29.1		ND	110			145.4
2-Hexanone	ND	29.1		ND	119			145.4
Dibromochloromethane	ND	29.1		ND	248			145.4
1,2-Dibromoethane	ND	29.1		ND	224			145.4
Tetrachloroethene	9520	29.1		64600	197			145.4
Chlorobenzene	ND	29.1		ND	134			145.4
Ethylbenzene	ND	29.1		ND	126			145.4
p/m-Xylene	ND	58.2		ND	253			145.4
Bromoform	ND	29.1		ND	301			145.4



Project Number: BAE 1102 Lab Number:

L1313216

Report Date:

07/22/13

SAMPLE RESULTS

Lab ID: L1313216-01 D

BLOWER 3A

Client ID: Sample Location: 5 CUBA HILL RD., GREENLAWN, NY Date Collected:

07/12/13 12:09

Date Received:

07/15/13

Field Prep:

Not Specified

		ppbV			ug/m3			Dilution
Parameter	Results	RL MDL		Results RL		MDL	Qualifier	Factor
Volatile Organics in Air - Mansf	ield Lab							
Styrene	ND	29.1		ND	124			145.4
1,1,2,2-Tetrachloroethane	ND	29.1		ND	200			145.4
o-Xylene	ND	29.1		ND	126			145.4
4-Ethyltoluene	ND	29.1		ND	143			145.4
1,3,5-Trimethylbenzene	ND	29.1		ND	143			145.4
1,2,4-Trimethylbenzene	ND	29.1		ND	143			145.4
Benzyl chloride	ND	29.1		ND	151			145.4
1,3-Dichlorobenzene	ND	29.1		ND	175			145.4
1,4-Dichlorobenzene	ND	29.1		ND	175			145.4
1,2-Dichlorobenzene	ND	29.1		ND	175			145.4
1,2,4-Trichlorobenzene	ND	29.1		ND	216			145.4
Hexachlorobutadiene	ND	29.1		ND	310			145.4

Internal Standard	% Recovery	Qualifier	Acceptance Criteria
1,4-Difluorobenzene	110		60-140
Bromochloromethane	117		60-140
chlorobenzene-d5	113		60-140



Project Number: BAE 1102

Lab Number:

Date Collected:

Date Received:

Field Prep:

L1313216

07/12/13 12:01

Not Specified

07/15/13

Report Date: 07/22/13

SAMPLE RESULTS

Lab ID: L1313216-02 D

Client ID: BLOWER 3B

Sample Location: 5 CUBA HILL RD., GREENLAWN, NY

Matrix: Soil_Vapor Anaytical Method: 48,TO-15 Analytical Date: 07/18/13 02:02

Analyst: MB

Volatile Organics in Air - Mansfield Lab Propylene ND 1.11 ND 1.91 2.22 Dichlorodifluoromethane 1.33 0.445 ND 0.919 2.22 Chloromethane ND 0.445 ND 0.919 2.22 Freon-114 ND 0.445 ND 3.11 2.22 Vinyl chloride ND 0.445 ND 3.11 2.22 I,3-Butadiene ND 0.445 ND 0.984 2.22 Bromomethane ND 0.445 ND 1.73 2.22 Chloroethane ND 0.445 ND 1.17 2.22 Chloroethane ND 0.445 ND 1.05 2.22 Vinyl bromide ND 0.445 ND 1.05 2			ppbV			ug/m3			Dilution Factor
Propylene ND 1.11 ND 1.91 2.22 Dichlorodifluoromethane 1.33 0.445 6.58 2.20 2.22 Chloromethane ND 0.445 ND 0.919 2.22 Freon-114 ND 0.445 ND 3.11 2.22 Vinyl chloride ND 0.445 ND 1.14 2.22 1,3-Butadiene ND 0.445 ND 0.984 2.22 Bromomethane ND 0.445 ND 1.73 2.22 Chloroethane ND 0.445 ND 1.17 2.22 Ethanol ND 5.56 ND 1.05 2.22 Vinyl bromide ND 0.445 ND 1.95 2.22 Trichlorofluoromethane 8.05	Parameter	Results	RL	RL MDL		Results RL MDL		Qualifier	
Dichlorodiffluoromethane 1.33 0.445 6.58 2.20 2.22 Chloromethane ND 0.445 ND 0.919 2.22 Freon-114 ND 0.445 ND 3.11 2.22 Vinyl chloride ND 0.445 ND 1.14 2.22 1,3-Butadiene ND 0.445 ND 0.984 2.22 Bromomethane ND 0.445 ND 1.73 2.22 Chloroethane ND 0.445 ND 1.17 2.22 Chloroethane ND 0.445 ND 1.05 2.22 Uinyl bromide ND 0.445 ND 1.05 2.22 Vinyl bromide ND 0.445 ND 1.95 2.22 Trichlorofluoromethane 8.	Volatile Organics in Air - Man	sfield Lab							
Chloromethane	Propylene	ND	1.11		ND	1.91			2.224
Freon-114	Dichlorodifluoromethane	1.33	0.445		6.58	2.20			2.224
Vinyl chloride ND 0.445 ND 1.14 2.2 1,3-Butadiene ND 0.445 ND 0.984 2.2 Bromomethane ND 0.445 ND 1.73 2.2 Chloroethane ND 0.445 ND 1.17 2.2 Ethanol ND 5.56 ND 10.5 2.2 Vinyl bromide ND 0.445 ND 1.95 2.2 Acetone ND 2.22 ND 5.27 2.2 Acetone ND 2.22 ND 5.27 2.2 Acetone ND 2.22 ND 5.27 2.2 Trichlorofluoromethane 8.05 0.445 45.2 2.50 2.2 Isopropanol 1.40 1.11 <td>Chloromethane</td> <td>ND</td> <td>0.445</td> <td></td> <td>ND</td> <td>0.919</td> <td></td> <td></td> <td>2.224</td>	Chloromethane	ND	0.445		ND	0.919			2.224
1,3-Butadiene ND 0.445 ND 0.984 2.2 Bromomethane ND 0.445 ND 1.73 2.2 Chloroethane ND 0.445 ND 1.17 2.2 Ethanol ND 5.56 ND 10.5 2.2 Vinyl bromide ND 0.445 ND 1.95 2.2 Acetone ND 2.22 ND 5.27 2.2 Trichlorofluoromethane 8.05 0.445 ND 5.27 2.2 Isopropanol 1.40 1.11 3.44 2.73 2.2 In-1-Dichloroethene 21.3 0.445 84.5 1.76 2.2 Methylene chloride ND 2.22 ND 7.71 2.2 3-Chloropropene ND 0.445 ND 1.39 2.2 Trichlorofluoromethane 8.05 0.445 ND 1.39 2.2 In-1-Dichloroethene ND 0.445 ND 1.39 2.2 In-1-Dichloroethene ND 0.445 ND 1.39 2.2 In-1-Dichloroethene ND 0.445 ND 1.39 2.2 In-1-Dichloroethene 2.75 0.445 10.9 1.76 2.2 In-1-Dichloroethane 8.9 0.445 2.79 1.80 2.2 In-1-Dichloroethane 8.9 0.445 ND 1.60 2.2 In-Dichloroethane ND 0.445 ND 1.60 2.2 In-Dichloroethane ND 0.445 ND 1.60 2.2 In-Dichloroethane ND 0.445 ND 1.57 2.2 In-Dichloroethane ND 0.445 ND 1.57 2.2 In-Dichloroethane ND 0.445 ND 1.57 2.2 In-Dichloroethane ND 0.445 ND 1.57 2.2 In-Dichloroethane ND 0.445 ND 1.57 2.2 In-Dichloroethane ND 0.445 ND 1.57 2.2 In-Dichloroethane ND 0.445 ND 1.57 2.2 In-Dichloroethane ND 0.445 ND 1.57 2.2 In-Dichloroethane ND 0.445 ND 1.57 2.2 In-Dichloroethane ND 0.445 ND 1.57 2.2 In-Dichloroethane ND 0.445 ND 1.57 2.2 In-Dichloroethane ND 0.445 ND 1.57 2.2	Freon-114	ND	0.445		ND	3.11			2.224
Bromomethane	Vinyl chloride	ND	0.445		ND	1.14			2.224
Chloroethane	1,3-Butadiene	ND	0.445		ND	0.984			2.224
Ethanol ND 5.56 ND 10.5 2.2: Vinyl bromide ND 0.445 ND 1.95 2.2: Acetone ND 2.22 ND 5.27 2.2: Trichlorofluoromethane 8.05 0.445 45.2 2.50 2.2: Isopropanol 1.40 1.11 3.44 2.73 2.2: 1,1-Dichloroethene 21.3 0.445 84.5 1.76 2.2: Methylene chloride ND 2.22 ND 7.71 2.2: 3-Chloropropene ND 0.445 ND 1.39 2.2: Carbon disulfide ND 0.445 ND 1.39 2.2: Treon-113 0.620 0.445 ND 1.39 2.2: trans-1,2-Dichloroethene 2.75 0.445 10.9 1.76 2.2: Methyl tert butyl ether ND 0.445 ND 1.60 2.2: Methyl tert butyl ether ND 0.445 ND 1.60 2.2: Methyl tert butyl ether ND 0.445 ND 1.57 2.2: Methyl tert butyl ether ND 0.445 ND 1.57 2.2: Methyl tert butyl ether ND 0.445 ND 1.57 2.2: Methyl tert butyl ether ND 0.445 ND 1.57 2.2: Methyl tert butyl ether ND 0.445 ND 1.57 2.2:	Bromomethane	ND	0.445		ND	1.73			2.224
Vinyl bromide ND 0.445 ND 1.95 2.22 Acetone ND 2.22 ND 5.27 2.23 Trichlorofluoromethane 8.05 0.445 45.2 2.50 2.23 Isopropanol 1.40 1.11 3.44 2.73 2.23 Methylene chloridene 21.3 0.445 84.5 1.76 2.23 Methylene chloride ND 2.22 ND 7.71 2.23 3-Chloropropene ND 0.445 ND 1.39 2.23 Carbon disulfide ND 0.445 ND 1.39 2.23 Freon-113 0.620 0.445 ND 1.76 2.23 trans-1,2-Dichloroethane 2.75 0.445 10.9 1.76 2.23 Methyl tert	Chloroethane	ND	0.445		ND	1.17			2.224
Acetone ND 2.22 ND 5.27 2.21 Trichlorofluoromethane 8.05 0.445 45.2 2.50 2.21 Isopropanol 1.40 1.11 3.44 2.73 2.21 Isopropanol 2.1.3 0.445 84.5 1.76 2.21 Methylene chloride ND 2.22 ND 7.71 2.21 3-Chloropropene ND 0.445 ND 1.39 2.21 Carbon disulfide ND 0.445 ND 1.39 2.21 Trans-1,2-Dichloroethene 2.75 0.445 10.9 1.76 2.21 I,1-Dichloroethane 68.9 0.445 10.9 1.76 2.21 Methyl tert butyl ether ND 0.445 ND 1.60 2.21 Methyl tert butyl ether ND 0.445 ND 1.57 2.21 Methyl tert butyl ether ND 0.445 ND 1.57 2.21 Dichloroethane ND 0.445 ND 1.57 2.21 Dichloroethane ND 0.445 ND 1.57 2.21 Dichloroethane ND 0.445 ND 1.57 2.21 Dichloroethane ND 0.445 ND 1.57 2.21 Dichloroethane ND 0.445 ND 1.57 2.21 Dichloroethane ND 0.445 ND 1.57 2.21 Dichloroethane ND 0.445 ND 1.57 2.21 Dichloroethane ND 0.445 ND 1.57 2.21 Dichloroethane ND 0.445 ND 1.57 2.21 Dichloroethane ND 0.445 ND 1.57 2.21 Dichloroethane ND 0.445 ND 1.57 2.21 Dichloroethane ND 0.445 ND 1.57 2.21 Dichloroethane ND 0.445 ND 1.57 2.21 Dichloroethane ND 0.445 ND 1.57 2.21	Ethanol	ND	5.56		ND	10.5			2.224
Trichlorofluoromethane 8.05 0.445 45.2 2.50 2.21 Isopropanol 1.40 1.11 3.44 2.73 2.22 1,1-Dichloroethene 21.3 0.445 84.5 1.76 2.22 Methylene chloride ND 2.22 ND 7.71 2.22 3-Chloropropene ND 0.445 ND 1.39 2.22 Carbon disulfide ND 0.445 ND 1.39 2.22 Freon-113 0.620 0.445 ND 1.39 2.22 trans-1,2-Dichloroethene 2.75 0.445 4.75 3.41 2.22 1,1-Dichloroethane 68.9 0.445 10.9 1.76 2.22 Methyl tert butyl ether ND 0.445 ND 1.60 2.22	Vinyl bromide	ND	0.445		ND	1.95			2.224
Stock Strict St	Acetone	ND	2.22		ND	5.27			2.224
1,1-Dichloroethene 21.3 0.445 84.5 1.76 2.25 Methylene chloride ND 2.22 ND 7.71 2.25 3-Chloropropene ND 0.445 ND 1.39 2.25 Carbon disulfide ND 0.445 ND 1.39 2.25 Freon-113 0.620 0.445 ND 1.39 2.25 trans-1,2-Dichloroethene 2.75 0.445 10.9 1.76 2.25 1,1-Dichloroethane 68.9 0.445 279 1.80 2.25 Methyl tert butyl ether ND 0.445 ND 1.60 2.25 Wethyl tert butyl ether ND 0.445 ND 1.57 2.25 Vinyl acetate ND 0.445 ND 1.57 2.25 2-Butanone ND 0.445 ND 1.31 2.25	Trichlorofluoromethane	8.05	0.445		45.2	2.50			2.224
Methylene chloride ND 2.22 ND 7.71 2.23 3-Chloropropene ND 0.445 ND 1.39 2.23 Carbon disulfide ND 0.445 ND 1.39 2.23 Freon-113 0.620 0.445 4.75 3.41 2.23 trans-1,2-Dichloroethene 2.75 0.445 10.9 1.76 2.23 1,1-Dichloroethane 68.9 0.445 279 1.80 2.23 Methyl tert butyl ether ND 0.445 ND 1.57 2.23 Vinyl acetate ND 0.445 ND 1.57 2.23 2-Butanone ND 0.445 ND 1.31 2.23	Isopropanol	1.40	1.11		3.44	2.73			2.224
3-Chloropropene ND 0.445 ND 1.39 2.22 Carbon disulfide ND 0.445 ND 1.39 2.22 Freon-113 0.620 0.445 4.75 3.41 2.22 trans-1,2-Dichloroethene 2.75 0.445 10.9 1.76 2.22 1,1-Dichloroethane 68.9 0.445 279 1.80 2.22 Methyl tert butyl ether ND 0.445 ND 1.60 2.22 Vinyl acetate ND 0.445 ND 1.57 2.22 2-Butanone ND 0.445 ND 1.31 2.22	1,1-Dichloroethene	21.3	0.445		84.5	1.76			2.224
Carbon disulfide ND 0.445 ND 1.39 2.25 Freon-113 0.620 0.445 4.75 3.41 2.25 trans-1,2-Dichloroethene 2.75 0.445 10.9 1.76 2.25 1,1-Dichloroethane 68.9 0.445 279 1.80 2.25 Methyl tert butyl ether ND 0.445 ND 1.60 2.25 Vinyl acetate ND 0.445 ND 1.57 2.25 2-Butanone ND 0.445 ND 1.31 2.25	Methylene chloride	ND	2.22		ND	7.71			2.224
Freon-113	3-Chloropropene	ND	0.445		ND	1.39			2.224
trans-1,2-Dichloroethene 2.75 0.445 10.9 1.76 2.25 1,1-Dichloroethane 68.9 0.445 279 1.80 2.25 Methyl tert butyl ether ND 0.445 ND 1.60 2.25 Vinyl acetate ND 0.445 ND 1.57 2.25 2- 2- 2- 2- 2- 2- 2- 2- 2- 2- 2- 2- 2-	Carbon disulfide	ND	0.445		ND	1.39			2.224
1,1-Dichloroethane 68.9 0.445 279 1.80 2.23 Methyl tert butyl ether ND 0.445 ND 1.60 2.23 Vinyl acetate ND 0.445 ND 1.57 2.23 2-Butanone ND 0.445 ND 1.31 2.23	Freon-113	0.620	0.445		4.75	3.41			2.224
Methyl tert butyl ether ND 0.445 ND 1.60 2.23 Vinyl acetate ND 0.445 ND 1.57 2.23 2-Butanone ND 0.445 ND 1.31 2.23	trans-1,2-Dichloroethene	2.75	0.445		10.9	1.76			2.224
Vinyl acetate ND 0.445 ND 1.57 2.23 2-Butanone ND 0.445 ND 1.31 2.23	1,1-Dichloroethane	68.9	0.445		279	1.80			2.224
2-Butanone ND 0.445 ND 1.31 2.23	Methyl tert butyl ether	ND	0.445		ND	1.60			2.224
THE OUTTO THE TRUE TO THE PROPERTY OF THE PROP	Vinyl acetate	ND	0.445		ND	1.57			2.224
cis-1.2-Dichloroethene. 40.1 0.445 150 1.76 2.21	2-Butanone	ND	0.445		ND	1.31			2.224
40.1 0.443 135 1.70 2.22	cis-1,2-Dichloroethene	40.1	0.445		159	1.76			2.224



Project Number: BAE 1102

Lab Number:

L1313216

Report Date:

07/22/13

SAMPLE RESULTS

Lab ID: L1313216-02 D

Client ID: BLOWER 3B

Sample Location: 5 CUBA HILL RD., GREENLAWN, NY

Date Collected:
Date Received:

07/12/13 12:01 07/15/13

Field Prep:

Not Specified

Not	Spe	CITIE

	ppbV			ug/m3			Dilutio	
Parameter	Results	RL	MDL	Results	RL	MDL	Qualifier	Factor
Volatile Organics in Air - Mansfie	eld Lab							
Ethyl Acetate	ND	1.11		ND	4.00			2.224
Chloroform	ND	0.445		ND	2.17			2.224
Tetrahydrofuran	1.05	0.445		3.10	1.31			2.224
1,2-Dichloroethane	ND	0.445		ND	1.80			2.224
n-Hexane	ND	0.445		ND	1.57			2.224
1,1,1-Trichloroethane	14.3	0.445		78.0	2.43			2.224
Benzene	ND	0.445		ND	1.42			2.224
Carbon tetrachloride	ND	0.445		ND	2.80			2.224
Cyclohexane	ND	0.445		ND	1.53			2.224
1,2-Dichloropropane	ND	0.445		ND	2.06			2.224
Bromodichloromethane	ND	0.445		ND	2.98			2.224
1,4-Dioxane	ND	0.445		ND	1.60			2.224
Trichloroethene	ND	0.445		ND	2.39			2.224
2,2,4-Trimethylpentane	ND	0.445		ND	2.08			2.224
Heptane	ND	0.445		ND	1.82			2.224
cis-1,3-Dichloropropene	ND	0.445		ND	2.02			2.224
4-Methyl-2-pentanone	ND	0.445		ND	1.82			2.224
trans-1,3-Dichloropropene	ND	0.445		ND	2.02			2.224
1,1,2-Trichloroethane	ND	0.445		ND	2.43			2.224
Toluene	ND	0.445		ND	1.68			2.224
2-Hexanone	ND	0.445		ND	1.82			2.224
Dibromochloromethane	ND	0.445		ND	3.79			2.224
1,2-Dibromoethane	ND	0.445		ND	3.42			2.224
Tetrachloroethene	ND	0.445		ND	3.02			2.224
Chlorobenzene	ND	0.445		ND	2.05			2.224
Ethylbenzene	ND	0.445		ND	1.93			2.224
p/m-Xylene	ND	0.890		ND	3.87			2.224
Bromoform	ND	0.445		ND	4.60			2.224



Project Number: BAE 1102 Lab Number:

L1313216

Report Date:

07/22/13

SAMPLE RESULTS

Lab ID: L1313216-02 D

BLOWER 3B

Client ID: Sample Location: 5 CUBA HILL RD., GREENLAWN, NY Date Collected:

07/12/13 12:01

Date Received:

07/15/13

Field Prep:

Not Specified

		ppbV			ug/m3			Dilution
Parameter	Results	RL	MDL	Results	RL	MDL	Qualifier	Factor
Volatile Organics in Air - Mans	sfield Lab							
Styrene	ND	0.445		ND	1.89			2.224
1,1,2,2-Tetrachloroethane	ND	0.445		ND	3.06			2.224
o-Xylene	ND	0.445		ND	1.93			2.224
4-Ethyltoluene	ND	0.445		ND	2.19			2.224
1,3,5-Trimethylbenzene	ND	0.445		ND	2.19			2.224
1,2,4-Trimethylbenzene	ND	0.445		ND	2.19			2.224
Benzyl chloride	ND	0.445		ND	2.30			2.224
1,3-Dichlorobenzene	ND	0.445		ND	2.68			2.224
1,4-Dichlorobenzene	ND	0.445		ND	2.68			2.224
1,2-Dichlorobenzene	ND	0.445		ND	2.68			2.224
1,2,4-Trichlorobenzene	ND	0.445		ND	3.30			2.224
Hexachlorobutadiene	ND	0.445		ND	4.75			2.224

Internal Standard	% Recovery	Qualifier	Acceptance Criteria
1,4-Difluorobenzene	107		60-140
Bromochloromethane	114		60-140
chlorobenzene-d5	111		60-140



Project Number: BAE 1102

Lab Number:

L1313216

Report Date: 07/22/13

SAMPLE RESULTS

Lab ID: L1313216-03 D

Client ID: BLOWER 3C

Sample Location: 5 CUBA HILL RD., GREENLAWN, NY

Matrix: Soil_Vapor Anaytical Method: 48,TO-15 Analytical Date: 07/18/13 02:34

Analyst: MB

Date Collected:	07/12/13 11:51
Date Received:	07/15/13
Field Prep:	Not Specified

		ppbV			ug/m3		Dilution	
Parameter	Results	RL	MDL	Results	RL	MDL	Qualifier	Factor
Volatile Organics in Air - Mar	nsfield Lab							
Propylene	ND	1.12		ND	1.93			2.233
Dichlorodifluoromethane	1.31	0.447		6.48	2.21			2.233
Chloromethane	ND	0.447		ND	0.923			2.233
Freon-114	ND	0.447		ND	3.12			2.233
Vinyl chloride	ND	0.447		ND	1.14			2.233
1,3-Butadiene	ND	0.447		ND	0.989			2.233
Bromomethane	ND	0.447		ND	1.74			2.233
Chloroethane	ND	0.447		ND	1.18			2.233
Ethanol	ND	5.58		ND	10.5			2.233
Vinyl bromide	ND	0.447		ND	1.95			2.233
Acetone	2.34	2.23		5.56	5.30			2.233
Trichlorofluoromethane	0.480	0.447		2.70	2.51			2.233
Isopropanol	ND	1.12		ND	2.75			2.233
1,1-Dichloroethene	ND	0.447		ND	1.77			2.233
Methylene chloride	ND	2.23		ND	7.75			2.233
3-Chloropropene	ND	0.447		ND	1.40			2.233
Carbon disulfide	ND	0.447		ND	1.39			2.233
Freon-113	ND	0.447		ND	3.43			2.233
trans-1,2-Dichloroethene	ND	0.447		ND	1.77			2.233
1,1-Dichloroethane	ND	0.447		ND	1.81			2.233
Methyl tert butyl ether	ND	0.447		ND	1.61			2.233
Vinyl acetate	ND	0.447		ND	1.57			2.233
2-Butanone	ND	0.447		ND	1.32			2.233
cis-1,2-Dichloroethene	ND	0.447		ND	1.77			2.233



Project Number: BAE 1102

Lab Number:

L1313216

Report Date:

07/22/13

SAMPLE RESULTS

Lab ID: L1313216-03 D

Client ID: BLOWER 3C

Sample Location: 5 CUBA HILL RD., GREENLAWN, NY

Date Collected:

07/12/13 11:51

Date Received: Field Prep:

07/15/13

Not Specified

Campio Location: 0 COB/(THEE IND., OINEE	1	• •			. тор.		tot opoome
_		ppbV			ug/m3		o ""	Dilution Factor
Parameter	Results	RL	MDL	Results	RL	MDL	Qualifier	1 40101
Volatile Organics in Air - Mans	ifield Lab							
Ethyl Acetate	ND	1.12		ND	4.04			2.233
Chloroform	ND	0.447		ND	2.18			2.233
Tetrahydrofuran	ND	0.447		ND	1.32			2.233
1,2-Dichloroethane	ND	0.447		ND	1.81			2.233
n-Hexane	ND	0.447		ND	1.58			2.233
1,1,1-Trichloroethane	ND	0.447		ND	2.44			2.233
Benzene	ND	0.447		ND	1.43			2.233
Carbon tetrachloride	ND	0.447		ND	2.81			2.233
Cyclohexane	ND	0.447		ND	1.54			2.233
1,2-Dichloropropane	ND	0.447		ND	2.07			2.233
Bromodichloromethane	ND	0.447		ND	2.99			2.233
1,4-Dioxane	ND	0.447		ND	1.61			2.233
Trichloroethene	ND	0.447		ND	2.40			2.233
2,2,4-Trimethylpentane	ND	0.447		ND	2.09			2.233
Heptane	ND	0.447		ND	1.83			2.233
cis-1,3-Dichloropropene	ND	0.447		ND	2.03			2.233
4-Methyl-2-pentanone	ND	0.447		ND	1.83			2.233
trans-1,3-Dichloropropene	ND	0.447		ND	2.03			2.233
1,1,2-Trichloroethane	ND	0.447		ND	2.44			2.233
Toluene	ND	0.447		ND	1.68			2.233
2-Hexanone	ND	0.447		ND	1.83			2.233
Dibromochloromethane	ND	0.447		ND	3.81			2.233
1,2-Dibromoethane	ND	0.447		ND	3.44			2.233
Tetrachloroethene	ND	0.447		ND	3.03			2.233
Chlorobenzene	ND	0.447		ND	2.06			2.233
Ethylbenzene	ND	0.447		ND	1.94			2.233
p/m-Xylene	ND	0.893		ND	3.88			2.233
Bromoform	ND	0.447		ND	4.62			2.233



Project Number: BAE 1102

Lab Number:

L1313216

Report Date:

07/22/13

SAMPLE RESULTS

Lab ID: L1313216-03 D

Date Collected:

07/12/13 11:51

Client ID: BLOWER 3C

Date Received:

07/15/13

Sample Location: 5 CUBA HILL RD., GREENLAWN, NY

Field Prep:

Not Specified

		ppbV			ug/m3		Dilution	
Parameter	Results	RL	MDL	Results	RL	MDL	Qualifier	Factor
Volatile Organics in Air - Man	sfield Lab							
Styrene	ND	0.447		ND	1.90			2.233
1,1,2,2-Tetrachloroethane	ND	0.447		ND	3.07			2.233
o-Xylene	ND	0.447		ND	1.94			2.233
4-Ethyltoluene	ND	0.447		ND	2.20			2.233
1,3,5-Trimethylbenzene	ND	0.447		ND	2.20			2.233
1,2,4-Trimethylbenzene	ND	0.447		ND	2.20			2.233
Benzyl chloride	ND	0.447		ND	2.31			2.233
1,3-Dichlorobenzene	ND	0.447		ND	2.69			2.233
1,4-Dichlorobenzene	ND	0.447		ND	2.69			2.233
1,2-Dichlorobenzene	ND	0.447		ND	2.69			2.233
1,2,4-Trichlorobenzene	ND	0.447		ND	3.32			2.233
Hexachlorobutadiene	ND	0.447		ND	4.77			2.233

Internal Standard	% Recovery	Qualifier	Acceptance Criteria
1,4-Difluorobenzene	98		60-140
Bromochloromethane	108		60-140
chlorobenzene-d5	101		60-140



Project Name: BAE-GREENLAWN Lab Number: L1313216

Project Number: BAE 1102 Report Date: 07/22/13

Method Blank Analysis Batch Quality Control

Analytical Method: 48,TO-15 Analytical Date: 07/17/13 14:39

		ppbV			ug/m3			Dilution
Parameter	Results	RL	MDL	Results	RL	MDL	Qualifier	Factor
Volatile Organics in Air - Mansfiel	d Lab for samp	ole(s): 01	-03 Batch	: WG62236	60-4			
Propylene	ND	0.500		ND	0.861			1
Dichlorodifluoromethane	ND	0.200		ND	0.989			1
Chloromethane	ND	0.200		ND	0.413			1
Freon-114	ND	0.200		ND	1.40			1
Vinyl chloride	ND	0.200		ND	0.511			1
1,3-Butadiene	ND	0.200		ND	0.442			1
Bromomethane	ND	0.200		ND	0.777			1
Chloroethane	ND	0.200		ND	0.528			1
Ethanol	ND	2.50		ND	4.71			1
Vinyl bromide	ND	0.200		ND	0.874			1
Acetone	ND	1.00		ND	2.38			1
Trichlorofluoromethane	ND	0.200		ND	1.12			1
Isopropanol	ND	0.500		ND	1.23			1
1,1-Dichloroethene	ND	0.200		ND	0.793			1
Methylene chloride	ND	1.00		ND	3.47			1
3-Chloropropene	ND	0.200		ND	0.626			1
Carbon disulfide	ND	0.200		ND	0.623			1
Freon-113	ND	0.200		ND	1.53			1
trans-1,2-Dichloroethene	ND	0.200		ND	0.793			1
1,1-Dichloroethane	ND	0.200		ND	0.809			1
Methyl tert butyl ether	ND	0.200		ND	0.721			1
Vinyl acetate	ND	0.200		ND	0.704			1
2-Butanone	ND	0.200		ND	0.590			1
cis-1,2-Dichloroethene	ND	0.200		ND	0.793			1
Ethyl Acetate	ND	0.500		ND	1.80			1



Project Name: BAE-GREENLAWN Lab Number: L1313216

Project Number: BAE 1102 Report Date: 07/22/13

Method Blank Analysis Batch Quality Control

Analytical Method: 48,TO-15 Analytical Date: 07/17/13 14:39

		ppbV			ug/m3			Dilution
Parameter	Results	RL	MDL	Results	RL	MDL	Qualifier	Factor
Volatile Organics in Air - Mar	nsfield Lab for samp	le(s): 01-	03 Batch:	: WG62236	60-4			
Chloroform	ND	0.200		ND	0.977			1
Tetrahydrofuran	ND	0.200		ND	0.590			1
1,2-Dichloroethane	ND	0.200		ND	0.809			1
n-Hexane	ND	0.200		ND	0.705			1
1,1,1-Trichloroethane	ND	0.200		ND	1.09			1
Benzene	ND	0.200		ND	0.639			1
Carbon tetrachloride	ND	0.200		ND	1.26			1
Cyclohexane	ND	0.200		ND	0.688			1
1,2-Dichloropropane	ND	0.200		ND	0.924			1
Bromodichloromethane	ND	0.200		ND	1.34			1
1,4-Dioxane	ND	0.200		ND	0.721			1
Trichloroethene	ND	0.200		ND	1.07			1
2,2,4-Trimethylpentane	ND	0.200		ND	0.934			1
Heptane	ND	0.200		ND	0.820			1
cis-1,3-Dichloropropene	ND	0.200		ND	0.908			1
4-Methyl-2-pentanone	ND	0.200		ND	0.820			1
trans-1,3-Dichloropropene	ND	0.200		ND	0.908			1
1,1,2-Trichloroethane	ND	0.200		ND	1.09			1
Toluene	ND	0.200		ND	0.754			1
2-Hexanone	ND	0.200		ND	0.820			1
Dibromochloromethane	ND	0.200		ND	1.70			1
1,2-Dibromoethane	ND	0.200		ND	1.54			1
Tetrachloroethene	ND	0.200		ND	1.36			1
Chlorobenzene	ND	0.200		ND	0.921			1
Ethylbenzene	ND	0.200		ND	0.869			1



Project Name: BAE-GREENLAWN Lab Number: L1313216

Project Number: BAE 1102 Report Date: 07/22/13

Method Blank Analysis Batch Quality Control

Analytical Method: 48,TO-15 Analytical Date: 07/17/13 14:39

		ppbV			ug/m3			Dilution
Parameter	Results	RL	MDL	Results	RL	MDL	Qualifier	Factor
Volatile Organics in Air - Mans	field Lab for samp	le(s): 01-	03 Batcl	h: WG62236	0-4			
p/m-Xylene	ND	0.400		ND	1.74			1
Bromoform	ND	0.200		ND	2.07			1
Styrene	ND	0.200		ND	0.852			1
1,1,2,2-Tetrachloroethane	ND	0.200		ND	1.37			1
o-Xylene	ND	0.200		ND	0.869			1
4-Ethyltoluene	ND	0.200		ND	0.983			1
1,3,5-Trimethylbenzene	ND	0.200		ND	0.983			1
1,2,4-Trimethylbenzene	ND	0.200		ND	0.983			1
Benzyl chloride	ND	0.200		ND	1.04			1
1,3-Dichlorobenzene	ND	0.200		ND	1.20			1
1,4-Dichlorobenzene	ND	0.200		ND	1.20			1
1,2-Dichlorobenzene	ND	0.200		ND	1.20			1
1,2,4-Trichlorobenzene	ND	0.200		ND	1.48			1
Hexachlorobutadiene	ND	0.200		ND	2.13			1



Project Name: BAE-GREENLAWN

Project Number: BAE 1102

Lab Number: L1313216

ırameter	LCS %Recovery	Qual	LCSD %Recovery	Qual	%Recovery Limits	RPD	Qual	RPD Limits
platile Organics in Air - Mansfield Lab	Associated sample(s)	: 01-03	Batch: WG6223	60-3				
Chlorodifluoromethane	84		-		70-130	-		
Propylene	88		-		70-130	-		
Dichlorodifluoromethane	106		-		70-130	-		
Chloromethane	82		-		70-130	-		
1,2-Dichloro-1,1,2,2-tetrafluoroethane	97		-		70-130	-		
Methanol	79		-		70-130	-		
Vinyl chloride	86		-		70-130	-		
1,3-Butadiene	86		-		70-130	-		
Butane	77		-		70-130	-		
Bromomethane	92		-		70-130	-		
Chloroethane	82		-		70-130	-		
Ethyl Alcohol	84		-		70-130	-		
Dichlorofluoromethane	89		-		70-130	-		
Vinyl bromide	95		-		70-130	-		
Acrolein	71		-		70-130	-		
Acetone	108		-		70-130	-		
Acetonitrile	81		-		70-130	-		
Trichlorofluoromethane	123		-		70-130	-		
iso-Propyl Alcohol	96		-		70-130	-		
Acrylonitrile	79		-		70-130	-		
Pentane	78		-		70-130	-		



Project Name: BAE-GREENLAWN

Project Number: BAE 1102

Lab Number: L1313216

arameter	LCS %Recovery	Qual	LCSD %Recovery	Qual	%Recovery Limits	RPD	Qual	RPD Limits
/olatile Organics in Air - Mansfield Lab	Associated sample(s):	01-03	Batch: WG6223	60-3				
Ethyl ether	78		-		70-130	-		
1,1-Dichloroethene	101		-		70-130	-		
tert-Butyl Alcohol	90		-		70-130	-		
Methylene chloride	97		-		70-130	-		
3-Chloropropene	118		-		70-130	-		
Carbon disulfide	90		-		70-130	-		
1,1,2-Trichloro-1,2,2-Trifluoroethane	106		-		70-130	-		
trans-1,2-Dichloroethene	86		-		70-130	-		
1,1-Dichloroethane	95		-		70-130	-		
Methyl tert butyl ether	91		-		70-130	-		
Vinyl acetate	97		-		70-130	-		
2-Butanone	91		-		70-130	-		
cis-1,2-Dichloroethene	110		-		70-130	-		
Ethyl Acetate	86		-		70-130	-		
Chloroform	114		-		70-130	-		
Tetrahydrofuran	75		-		70-130	-		
2,2-Dichloropropane	100		-		70-130	-		
1,2-Dichloroethane	115		-		70-130	-		
n-Hexane	94		-		70-130	-		
Isopropyl Ether	88		-		70-130	-		
Ethyl-Tert-Butyl-Ether	94		-		70-130	-		



Project Name: BAE-GREENLAWN

Project Number: BAE 1102

Lab Number: L1313216

arameter	LCS %Recovery	Qual	LCSD %Recovery	Qual	%Recovery Limits	RPD	Qual	RPD Limits
/olatile Organics in Air - Mansfield Lab Assoc	ciated sample(s)): 01-03	Batch: WG6223	60-3				
1,1,1-Trichloroethane	116		-		70-130	-		
1,1-Dichloropropene	95		-		70-130	-		
Benzene	85		-		70-130	-		
Carbon tetrachloride	120		-		70-130	-		
Cyclohexane	80		-		70-130	-		
Tertiary-Amyl Methyl Ether	82		-		70-130	-		
Dibromomethane	98		-		70-130	-		
1,2-Dichloropropane	86		-		70-130	-		
Bromodichloromethane	105		-		70-130	-		
1,4-Dioxane	88		-		70-130	-		
Trichloroethene	101		-		70-130	-		
2,2,4-Trimethylpentane	86		-		70-130	-		
Methyl methacrylate	116		-		70-130	-		
Heptane	95		-		70-130	-		
cis-1,3-Dichloropropene	95		-		70-130	-		
4-Methyl-2-pentanone	88		-		70-130	-		
trans-1,3-Dichloropropene	87		-		70-130	-		
1,1,2-Trichloroethane	98		-		70-130	-		
Toluene	80		-		70-130	-		
1,3-Dichloropropane	78		-		70-130	-		
2-Hexanone	75		-		70-130	-		



Project Name: BAE-GREENLAWN

Project Number: BAE 1102

Lab Number: L1313216

Parameter	LCS %Recovery	Qual	LCSD %Recovery	Qual	%Recovery Limits	RPD	Qual	RPD Limits
/olatile Organics in Air - Mansfield Lab Association	ciated sample(s)): 01-03	Batch: WG6223	60-3				
Dibromochloromethane	94		-		70-130	-		
1,2-Dibromoethane	96		-		70-130	-		
Octane	70		-		70-130	-		
Tetrachloroethene	94		-		70-130	-		
1,1,1,2-Tetrachloroethane	92		-		70-130	-		
Chlorobenzene	91		-		70-130	-		
Ethylbenzene	86		-		70-130	-		
p/m-Xylene	90		-		70-130	-		
Bromoform	91		-		70-130	-		
Styrene	84		-		70-130	-		
1,1,2,2-Tetrachloroethane	89		-		70-130	-		
o-Xylene	93		-		70-130	-		
1,2,3-Trichloropropane	80		-		70-130	-		
Nonane (C9)	81		-		70-130	-		
Isopropylbenzene	88		-		70-130	-		
Bromobenzene	83		-		70-130	-		
o-Chlorotoluene	88		-		70-130	-		
n-Propylbenzene	86		-		70-130	-		
p-Chlorotoluene	88		-		70-130	-		
4-Ethyltoluene	83		-		70-130	-		
1,3,5-Trimethylbenzene	94		-		70-130	-		



Project Name: BAE-GREENLAWN

Project Number: BAE 1102

Lab Number: L1313216

arameter	LCS %Recovery	Qual	LCSD %Recovery	Qual	%Recovery Limits	RPD	Qual	RPD Limits
olatile Organics in Air - Mansfield Lab As	sociated sample(s)	: 01-03	Batch: WG6223	60-3				
tert-Butylbenzene	92		-		70-130	-		
1,2,4-Trimethylbenzene	99		-		70-130	-		
Decane (C10)	81		-		70-130	-		
Benzyl chloride	72		-		70-130	-		
1,3-Dichlorobenzene	96		-		70-130	-		
1,4-Dichlorobenzene	96		-		70-130	-		
sec-Butylbenzene	88		-		70-130	-		
p-Isopropyltoluene	87		-		70-130	-		
1,2-Dichlorobenzene	96		-		70-130	-		
n-Butylbenzene	93		-		70-130	-		
1,2-Dibromo-3-chloropropane	99		-		70-130	-		
Undecane	87		-		70-130	-		
1,2,4-Trichlorobenzene	101		-		70-130	-		
Naphthalene	94		-		70-130	-		
1,2,3-Trichlorobenzene	94		-		70-130	-		
Hexachlorobutadiene	101		-		70-130	-		



Project Name: BAE-GREENLAWN

Project Number: BAE 1102

Lab Number: L1313216 **Report Date:** 07/22/13

rameter	Native Sam	ple Duplicate Sampl	e Units	RPD	Qual	RPD Limits
latile Organics in Air - Mansfield Lab Ass	ociated sample(s): 01-03	QC Batch ID: WG622360-5	QC Sample:	L1313177-01	Client ID:	DUP Sample
Propylene	117	106	ppbV	10		25
Dichlorodifluoromethane	0.734	0.678	ppbV	8		25
Chloromethane	ND	ND	ppbV	NC		25
1,2-Dichloro-1,1,2,2-tetrafluoroethane	ND	ND	ppbV	NC		25
Vinyl chloride	ND	ND	ppbV	NC		25
1,3-Butadiene	12.7	12.3	ppbV	3		25
Bromomethane	ND	ND	ppbV	NC		25
Chloroethane	ND	ND	ppbV	NC		25
Ethyl Alcohol	13.9	14.3	ppbV	3		25
Vinyl bromide	ND	ND	ppbV	NC		25
Acetone	323	301	ppbV	7		25
Trichlorofluoromethane	ND	ND	ppbV	NC		25
iso-Propyl Alcohol	2.20	1.79	ppbV	21		25
1,1-Dichloroethene	ND	ND	ppbV	NC		25
Methylene chloride	ND	ND	ppbV	NC		25
3-Chloropropene	ND	ND	ppbV	NC		25
Carbon disulfide	1.42	1.43	ppbV	1		25
1,1,2-Trichloro-1,2,2-Trifluoroethane	ND	ND	ppbV	NC		25
trans-1,2-Dichloroethene	ND	ND	ppbV	NC		25



Project Name: BAE-GREENLAWN

Project Number: BAE 1102

Lab Number: L1313216

Parameter	Native Sam	ole Duplicate Sampl	e Units	RPD	RPD Limits
olatile Organics in Air - Mansfield Lab Asso	ciated sample(s): 01-03	QC Batch ID: WG622360-5	QC Sample:	L1313177-01	Client ID: DUP Sample
1,1-Dichloroethane	ND	ND	ppbV	NC	25
Methyl tert butyl ether	ND	ND	ppbV	NC	25
Vinyl acetate	ND	ND	ppbV	NC	25
2-Butanone	7.79	7.84	ppbV	1	25
cis-1,2-Dichloroethene	ND	ND	ppbV	NC	25
Ethyl Acetate	ND	ND	ppbV	NC	25
Chloroform	20.5	19.6	ppbV	4	25
Tetrahydrofuran	ND	ND	ppbV	NC	25
1,2-Dichloroethane	ND	ND	ppbV	NC	25
n-Hexane	19.9	20.0	ppbV	1	25
1,1,1-Trichloroethane	ND	ND	ppbV	NC	25
Benzene	8.02	8.18	ppbV	2	25
Carbon tetrachloride	ND	ND	ppbV	NC	25
Cyclohexane	3.84	3.81	ppbV	1	25
1,2-Dichloropropane	ND	ND	ppbV	NC	25
Bromodichloromethane	ND	ND	ppbV	NC	25
1,4-Dioxane	ND	ND	ppbV	NC	25
Trichloroethene	ND	ND	ppbV	NC	25
2,2,4-Trimethylpentane	ND	ND	ppbV	NC	25



Project Name: BAE-GREENLAWN

Project Number: BAE 1102

Lab Number: L1313216 **Report Date:** 07/22/13

arameter		Native Sample	Duplicate Sample	e Units	RPD	RPD Limits
olatile Organics in Air - N	Mansfield Lab Associated sar	mple(s): 01-03 QC	Batch ID: WG622360-5	QC Sample:	L1313177-01	Client ID: DUP Sample
Heptane		13.0	12.5	ppbV	4	25
cis-1,3-Dichloropropene		ND	ND	ppbV	NC	25
4-Methyl-2-pentanone		ND	ND	ppbV	NC	25
trans-1,3-Dichloropropene		ND	ND	ppbV	NC	25
1,1,2-Trichloroethane		ND	ND	ppbV	NC	25
Toluene		28.4	29.6	ppbV	4	25
2-Hexanone		ND	ND	ppbV	NC	25
Dibromochloromethane		ND	ND	ppbV	NC	25
1,2-Dibromoethane		ND	ND	ppbV	NC	25
Tetrachloroethene		ND	ND	ppbV	NC	25
Chlorobenzene		ND	ND	ppbV	NC	25
Ethylbenzene		9.20	9.50	ppbV	3	25
p/m-Xylene		34.9	35.6	ppbV	2	25
Bromoform		ND	ND	ppbV	NC	25
Styrene		0.533	0.544	ppbV	2	25
1,1,2,2-Tetrachloroethane		ND	ND	ppbV	NC	25
o-Xylene		12.3	12.6	ppbV	2	25
4-Ethyltoluene		4.20	4.38	ppbV	4	25
1,3,5-Trimethylbenzene		4.00	4.00	ppbV	0	25



Project Name: BAE-GREENLAWN

Project Number: BAE 1102

Lab Number:

L1313216

Report Date:

07/22/13

arameter	Native Sample	Duplicate Sample	Units	RPD	RPD Limits
olatile Organics in Air - Mansfield Lab Ass	sociated sample(s): 01-03 QC	Batch ID: WG622360-5	QC Sample: L	.1313177-01 C	Client ID: DUP Sample
1,2,4-Trimethylbenzene	15.0	15.1	ppbV	1	25
Benzyl chloride	ND	ND	ppbV	NC	25
1,3-Dichlorobenzene	ND	ND	ppbV	NC	25
1,4-Dichlorobenzene	ND	ND	ppbV	NC	25
1,2-Dichlorobenzene	ND	ND	ppbV	NC	25
1,2,4-Trichlorobenzene	ND	ND	ppbV	NC	25
Hexachlorobutadiene	ND	ND	ppbV	NC	25



BAE-GREENLAWN Lab Number: L1313216

Project Number: BAE 1102 Report Date: 07/22/13

Canister and Flow Controller Information

Samplenum	Client ID	Media ID	Media Type	Date Prepared	Bottle Order	Cleaning Batch ID	Can Leak Check	Initial Pressure (in. Hg)	Pressure on Receipt (in. Hg)	Flow Controler Leak Chk	Flow Out mL/min	Flow In mL/min	% RPD
L1313216-01	BLOWER 3A	776	1.0L Can	07/12/13	90641	L1312473-02	Pass	-29.3	-1.0	-	-	-	-
L1313216-02	BLOWER 3B	823	1.0L Can	07/12/13	90641	L1312473-02	Pass	-28.8	-1.1	-	-	-	-
L1313216-03	BLOWER 3C	721	1.0L Can	07/12/13	90641	L1312473-02	Pass	-29.3	-1.2	-	-	-	-



Project Name:

L1312473

Lab Number:

Project Name: BATCH CANISTER CERTIFICATION

Project Number: CANISTER QC BAT Report Date: 07/22/13

Air Canister Certification Results

Date Collected: Lab ID: L1312473-02 07/02/13 15:54

Client ID: CAN 841 SHELF 7 Date Received: 07/03/13

Field Prep: Sample Location: Not Specified

Matrix: Air Anaytical Method: 48,TO-15

Analytical Date: 07/05/13 17:25

Analyst: RY

		ppbV			ug/m3			Dilution
Parameter	Results	RL	MDL	Results	RL	MDL	Qualifier	Factor
Volatile Organics in Air - Mansfield Lab)							
Chlorodifluoromethane	ND	0.200		ND	0.707			1
Propylene	ND	0.500		ND	0.861			1
Propane	ND	0.200		ND	0.361			1
Dichlorodifluoromethane	ND	0.200		ND	0.989			1
Chloromethane	ND	0.200		ND	0.413			1
Freon-114	ND	0.200		ND	1.40			1
Methanol	ND	5.00		ND	6.55			1
Vinyl chloride	ND	0.200		ND	0.511			1
1,3-Butadiene	ND	0.200		ND	0.442			1
Butane	ND	0.200		ND	0.475			1
Bromomethane	ND	0.200		ND	0.777			1
Chloroethane	ND	0.200		ND	0.528			1
Ethanol	ND	2.50		ND	4.71			1
Dichlorofluoromethane	ND	0.200		ND	0.842			1
Vinyl bromide	ND	0.200		ND	0.874			1
Acrolein	ND	0.500		ND	1.15			1
Acetone	ND	1.00		ND	2.38			1
Acetonitrile	ND	0.200		ND	0.336			1
Trichlorofluoromethane	ND	0.200		ND	1.12			1
Isopropanol	ND	0.500		ND	1.23			1
Acrylonitrile	ND	0.200		ND	0.434			1
Pentane	ND	0.200		ND	0.590			1
Ethyl ether	ND	0.200		ND	0.606			1
1,1-Dichloroethene	ND	0.200		ND	0.793			1
Tertiary butyl Alcohol	ND	0.500		ND	1.52			1



L1312473

Lab Number:

Project Name: BATCH CANISTER CERTIFICATION

Project Number: CANISTER QC BAT **Report Date:** 07/22/13

Air Canister Certification Results

Lab ID: Date Collected: L1312473-02 07/02/13 15:54

Client ID: CAN 841 SHELF 7 Date Received: 07/03/13

Sample Location: Field Prep: Not Specified

	ppbV ug/m3					Dilution		
Parameter	Results	RL	MDL	Results	RL	MDL	Qualifier	Factor
Volatile Organics in Air - Mansfield	Lab							
Methylene chloride	ND	1.00		ND	3.47			1
3-Chloropropene	ND	0.200		ND	0.626			1
Carbon disulfide	ND	0.200		ND	0.623			1
Freon-113	ND	0.200		ND	1.53			1
rans-1,2-Dichloroethene	ND	0.200		ND	0.793			1
1,1-Dichloroethane	ND	0.200		ND	0.809			1
Methyl tert butyl ether	ND	0.200		ND	0.721			1
/inyl acetate	ND	0.200		ND	0.704			1
2-Butanone	ND	0.200		ND	0.590			1
cis-1,2-Dichloroethene	ND	0.200		ND	0.793			1
Ethyl Acetate	ND	0.500		ND	1.80			1
Chloroform	ND	0.200		ND	0.977			1
Tetrahydrofuran	ND	0.200		ND	0.590			1
2,2-Dichloropropane	ND	0.200		ND	0.924			1
1,2-Dichloroethane	ND	0.200		ND	0.809			1
n-Hexane	ND	0.200		ND	0.705			1
Diisopropyl ether	ND	0.200		ND	0.836			1
ert-Butyl Ethyl Ether	ND	0.200		ND	0.836			1
1,1,1-Trichloroethane	ND	0.200		ND	1.09			1
1,1-Dichloropropene	ND	0.200		ND	0.908			1
Benzene	ND	0.200		ND	0.639			1
Carbon tetrachloride	ND	0.200		ND	1.26			1
Cyclohexane	ND	0.200		ND	0.688			1
ert-Amyl Methyl Ether	ND	0.200		ND	0.836			1
Dibromomethane	ND	0.200		ND	1.42			1
,2-Dichloropropane	ND	0.200		ND	0.924			1
Bromodichloromethane	ND	0.200		ND	1.34			1
1,4-Dioxane	ND	0.200		ND	0.721			1



L1312473

Lab Number:

Project Name: BATCH CANISTER CERTIFICATION

Project Number: CANISTER QC BAT **Report Date:** 07/22/13

Air Canister Certification Results

Lab ID: Date Collected: L1312473-02 07/02/13 15:54

Client ID: CAN 841 SHELF 7 Date Received: 07/03/13

Sample Location: Field Prep: Not Specified

	ppbV ug/m3					Dilution		
Parameter	Results	RL	MDL	Results	RL	MDL	Qualifier	Factor
Volatile Organics in Air - Mansfie	eld Lab							
Trichloroethene	ND	0.200		ND	1.07			1
2,2,4-Trimethylpentane	ND	0.200		ND	0.934			1
Methyl Methacrylate	ND	0.500		ND	2.05			1
Heptane	ND	0.200		ND	0.820			1
cis-1,3-Dichloropropene	ND	0.200		ND	0.908			1
4-Methyl-2-pentanone	ND	0.200		ND	0.820			1
rans-1,3-Dichloropropene	ND	0.200		ND	0.908			1
1,1,2-Trichloroethane	ND	0.200		ND	1.09			1
Toluene	ND	0.200		ND	0.754			1
1,3-Dichloropropane	ND	0.200		ND	0.924			1
2-Hexanone	ND	0.200		ND	0.820			1
Dibromochloromethane	ND	0.200		ND	1.70			1
,2-Dibromoethane	ND	0.200		ND	1.54			1
Butyl acetate	ND	0.500		ND	2.38			1
Octane	ND	0.200		ND	0.934			1
Tetrachloroethene	ND	0.200		ND	1.36			1
1,1,1,2-Tetrachloroethane	ND	0.200		ND	1.37			1
Chlorobenzene	ND	0.200		ND	0.921			1
Ethylbenzene	ND	0.200		ND	0.869			1
o/m-Xylene	ND	0.400		ND	1.74			1
Bromoform	ND	0.200		ND	2.07			1
Styrene	ND	0.200		ND	0.852			1
1,1,2,2-Tetrachloroethane	ND	0.200		ND	1.37			1
o-Xylene	ND	0.200		ND	0.869			1
1,2,3-Trichloropropane	ND	0.200		ND	1.21			1
Nonane	ND	0.200		ND	1.05			1
sopropylbenzene	ND	0.200		ND	0.983			1
Bromobenzene	ND	0.200		ND	0.793			1



Project Name: BATCH CANISTER CERTIFICATION

Project Number: CANISTER QC BAT

Lab Number:

L1312473

Report Date: 07/22/13

Air Canister Certification Results

Lab ID: L1312473-02
Client ID: CAN 841 SHELF 7

Sample Location:

Date Collected:

07/02/13 15:54

Date Received:

07/03/13

Field Prep: Not Specified

		ppbV			ug/m3			Dilution
Parameter	Results	RL	MDL	Results	RL	MDL	Qualifier	Factor
Volatile Organics in Air - Mansfield	d Lab							
2-Chlorotoluene	ND	0.200		ND	1.04			1
n-Propylbenzene	ND	0.200		ND	0.983			1
4-Chlorotoluene	ND	0.200		ND	1.04			1
4-Ethyltoluene	ND	0.200		ND	0.983			1
1,3,5-Trimethylbenzene	ND	0.200		ND	0.983			1
tert-Butylbenzene	ND	0.200		ND	1.10			1
1,2,4-Trimethylbenzene	ND	0.200		ND	0.983			1
Decane	ND	0.200		ND	1.16			1
Benzyl chloride	ND	0.200		ND	1.04			1
1,3-Dichlorobenzene	ND	0.200		ND	1.20			1
1,4-Dichlorobenzene	ND	0.200		ND	1.20			1
sec-Butylbenzene	ND	0.200		ND	1.10			1
p-IsopropyItoluene	ND	0.200		ND	1.10			1
1,2-Dichlorobenzene	ND	0.200		ND	1.20			1
n-Butylbenzene	ND	0.200		ND	1.10			1
1,2-Dibromo-3-chloropropane	ND	0.200		ND	1.93			1
Undecane	ND	0.200		ND	1.28			1
Dodecane	ND	0.200		ND	1.39			1
1,2,4-Trichlorobenzene	ND	0.200		ND	1.48			1
Naphthalene	ND	0.200		ND	1.05			1
1,2,3-Trichlorobenzene	ND	0.200		ND	1.48			1
Hexachlorobutadiene	ND	0.200		ND	2.13			1

	Results	Qualifier	Units	RDL	Dilution Factor
Tentatively Identified Compounds					

No Tentatively Identified Compounds



Project Name: BATCH CANISTER CERTIFICATION Lab Number: L1312473

Project Number: CANISTER QC BAT Report Date: 07/22/13

Air Canister Certification Results

Lab ID: L1312473-02 Date Collected: 07/02/13 15:54

Client ID: CAN 841 SHELF 7 Date Received: 07/03/13

Sample Location: Field Prep: Not Specified

Parameter Results RL MDL Results RL MDL Qualifier Factor

Volatile Organics in Air - Mansfield Lab

Internal Standard	% Recovery	Qualifier	Acceptance Criteria
1,4-Difluorobenzene	72		60-140
Bromochloromethane	71		60-140
chlorobenzene-d5	83		60-140



L1312473

Lab Number:

Project Name: BATCH CANISTER CERTIFICATION

Project Number: CANISTER QC BAT Report Date: 07/22/13

Air Canister Certification Results

Lab ID: L1312473-02 Date Collected: 07/02/13 15:54

Client ID: CAN 841 SHELF 7 Date Received: 07/03/13

Sample Location: Field Prep: Not Specified

Matrix: Air

Analytical Method: 48,TO-15-SIM Analytical Date: 07/05/13 17:25

Analyst: RY

		ppbV			ug/m3			Dilution
Parameter	Results	RL	MDL	Results	RL	MDL	Qualifier	Factor
Volatile Organics in Air by SIM	- Mansfield Lab							
Dichlorodifluoromethane	ND	0.050		ND	0.247			1
Chloromethane	ND	0.500		ND	1.03			1
Freon-114	ND	0.050		ND	0.349			1
Vinyl chloride	ND	0.020		ND	0.051			1
1,3-Butadiene	ND	0.020		ND	0.044			1
Bromomethane	ND	0.020		ND	0.078			1
Chloroethane	ND	0.020		ND	0.053			1
Acetone	ND	2.00		ND	4.75			1
Trichlorofluoromethane	ND	0.050		ND	0.281			1
Acrylonitrile	ND	0.500		ND	1.09			1
1,1-Dichloroethene	ND	0.020		ND	0.079			1
Methylene chloride	ND	1.00		ND	3.47			1
Freon-113	ND	0.050		ND	0.383			1
Halothane	ND	0.050		ND	0.404			1
rans-1,2-Dichloroethene	ND	0.020		ND	0.079			1
1,1-Dichloroethane	ND	0.020		ND	0.081			1
Methyl tert butyl ether	ND	0.020		ND	0.072			1
2-Butanone	ND	0.500		ND	1.47			1
cis-1,2-Dichloroethene	ND	0.020		ND	0.079			1
Chloroform	ND	0.020		ND	0.098			1
1,2-Dichloroethane	ND	0.020		ND	0.081			1
1,1,1-Trichloroethane	ND	0.020		ND	0.109			1
Benzene	ND	0.100		ND	0.319			1
Carbon tetrachloride	ND	0.020		ND	0.126			1
1,2-Dichloropropane	ND	0.020		ND	0.092			1



L1312473

Lab Number:

Project Name: BATCH CANISTER CERTIFICATION

Project Number: CANISTER QC BAT Report Date: 07/22/13

Air Canister Certification Results

Lab ID: L1312473-02 Date Collected: 07/02/13 15:54

Client ID: CAN 841 SHELF 7 Date Received: 07/03/13

Sample Location: Field Prep: Not Specified

Campio 200alioni	ppbV			ug/m3			Hot Opcome	
								Dilution
Parameter	Results	RL	MDL	Results	RL	MDL	Qualifier Fac	Factor
Volatile Organics in Air by SIM - N	Mansfield Lab							
Bromodichloromethane	ND	0.020		ND	0.134			1
1,4-Dioxane	ND	0.100		ND	0.360			1
Trichloroethene	ND	0.020		ND	0.107			1
cis-1,3-Dichloropropene	ND	0.020		ND	0.091			1
4-Methyl-2-pentanone	ND	0.500		ND	2.05			1
trans-1,3-Dichloropropene	ND	0.020		ND	0.091			1
1,1,2-Trichloroethane	ND	0.020		ND	0.109			1
Toluene	ND	0.050		ND	0.188			1
Dibromochloromethane	ND	0.020		ND	0.170			1
1,2-Dibromoethane	ND	0.020		ND	0.154			1
Tetrachloroethene	ND	0.020		ND	0.136			1
1,1,1,2-Tetrachloroethane	ND	0.020		ND	0.137			1
Chlorobenzene	ND	0.020		ND	0.092			1
Ethylbenzene	ND	0.020		ND	0.087			1
p/m-Xylene	ND	0.040		ND	0.174			1
Bromoform	ND	0.020		ND	0.207			1
Styrene	ND	0.020		ND	0.085			1
1,1,2,2-Tetrachloroethane	ND	0.020		ND	0.137			1
o-Xylene	ND	0.020		ND	0.087			1
Isopropylbenzene	ND	0.500		ND	2.46			1
1,3,5-Trimethybenzene	ND	0.020		ND	0.098			1
1,2,4-Trimethylbenzene	ND	0.020		ND	0.098			1
1,3-Dichlorobenzene	ND	0.020		ND	0.120			1
1,4-Dichlorobenzene	ND	0.020		ND	0.120			1
sec-Butylbenzene	ND	0.500		ND	2.74			1
p-Isopropyltoluene	ND	0.500		ND	2.74			1
1,2-Dichlorobenzene	ND	0.020		ND	0.120			1
n-Butylbenzene	ND	0.500		ND	2.74			1



Project Name: BATCH CANISTER CERTIFICATION

Lab Number:

L1312473

Project Number: CANISTER QC BAT

Report Date: 07/22/13

Air Canister Certification Results

Lab ID: L1312473-02

Date Collected:

07/02/13 15:54

Client ID: CAN 841 SHELF 7

Date Received:

07/03/13

Sample Location: Fi

Field Prep:

Not Specified

	ppbV			ug/m3				Dilution
Parameter	Results	RL	MDL	Results	RL	MDL	Qualifier	Factor
Volatile Organics in Air by SIM - I	Mansfield Lab							
1,2,4-Trichlorobenzene	ND	0.050		ND	0.371			1
Naphthalene	ND	0.050		ND	0.262			1
1,2,3-Trichlorobenzene	ND	0.050		ND	0.371			1
Hexachlorobutadiene	ND	0.050		ND	0.533			1

Internal Standard	% Recovery	Qualifier	Acceptance Criteria		
1,4-difluorobenzene	75		60-140		
bromochloromethane	72		60-140		
chlorobenzene-d5	83		60-140		



Project Name: BAE-GREENLAWN Lab Number: L1313216

Project Number: BAE 1102 Report Date: 07/22/13

Sample Receipt and Container Information

Were project specific reporting limits specified?

Reagent H2O Preserved Vials Frozen on: NA

Cooler Information Custody Seal

Cooler

N/A Absent

Container Info	Temp					
Container ID	Container Type	Cooler	рΗ	deg C Pres	Seal	Analysis(*)
L1313216-01A	Canister - 1 Liter	N/A	N/A	Υ	Absent	TO15-LL(30)
L1313216-02A	Canister - 1 Liter	N/A	N/A	Υ	Absent	TO15-LL(30)
L1313216-03A	Canister - 1 Liter	N/A	N/A	Υ	Absent	TO15-LL(30)



Project Name: BAE-GREENLAWN Lab Number: L1313216

Project Number: BAE 1102 Report Date: 07/22/13

GLOSSARY

Acronyms

EDL - Estimated Detection Limit: This value represents the level to which target analyte concentrations are reported as estimated values, when those target analyte concentrations are quantified below the reporting limit (RL). The EDL includes any adjustments from dilutions, concentrations or moisture content, where applicable. The use of EDLs is specific to the analysis of PAHs using Solid-Phase Microextraction (SPME).

EPA - Environmental Protection Agency.

LCS - Laboratory Control Sample: A sample matrix, free from the analytes of interest, spiked with verified known amounts of analytes
or a material containing known and verified amounts of analytes.

LCSD - Laboratory Control Sample Duplicate: Refer to LCS.

LFB - Laboratory Fortified Blank: A sample matrix, free from the analytes of interest, spiked with verified known amounts of analytes or a material containing known and verified amounts of analytes.

MDL - Method Detection Limit: This value represents the level to which target analyte concentrations are reported as estimated values, when those target analyte concentrations are quantified below the reporting limit (RL). The MDL includes any adjustments from dilutions, concentrations or moisture content, where applicable.

MS - Matrix Spike Sample: A sample prepared by adding a known mass of target analyte to a specified amount of matrix sample for which an independent estimate of target analyte concentration is available.

MSD - Matrix Spike Sample Duplicate: Refer to MS.

NA - Not Applicable.

NC - Not Calculated: Term is utilized when one or more of the results utilized in the calculation are non-detect at the parameter's reporting unit.

NI - Not Ignitable.

RL - Reporting Limit: The value at which an instrument can accurately measure an analyte at a specific concentration. The RL includes any adjustments from dilutions, concentrations or moisture content, where applicable.

RPD - Relative Percent Difference: The results from matrix and/or matrix spike duplicates are primarily designed to assess the precision of analytical results in a given matrix and are expressed as relative percent difference (RPD). Values which are less than five times the reporting limit for any individual parameter are evaluated by utilizing the absolute difference between the values; although the RPD value will be provided in the report.

SRM - Standard Reference Material: A reference sample of a known or certified value that is of the same or similar matrix as the associated field samples.

Footnotes

 The reference for this analyte should be considered modified since this analyte is absent from the target analyte list of the original method.

Terms

Analytical Method: Both the document from which the method originates and the analytical reference method. (Example: EPA 8260B is shown as 1,8260B.) The codes for the reference method documents are provided in the References section of the Addendum.

Data Qualifiers

- A Spectra identified as "Aldol Condensation Product".
- The analyte was detected above the reporting limit in the associated method blank. Flag only applies to associated field samples that have detectable concentrations of the analyte at less than five times (5x) the concentration found in the blank. For MCP-related projects, flag only applies to associated field samples that have detectable concentrations of the analyte at less than ten times (10x) the concentration found in the blank. For DOD-related projects, flag only applies to associated field samples that have detectable concentrations of the analyte at less than ten times (10x) the concentration found in the blank AND the analyte was detected above one-half the reporting limit (or above the reporting limit for common lab contaminants) in the associated method blank. For NJ-Air-related projects, flag only applies to associated field samples that have detectable concentrations of the analyte above the reporting limit.
- Co-elution: The target analyte co-elutes with a known lab standard (i.e. surrogate, internal standards, etc.) for co-extracted analyses.
- Concentration of analyte was quantified from diluted analysis. Flag only applies to field samples that have detectable concentrations
 of the analyte.
- E Concentration of analyte exceeds the range of the calibration curve and/or linear range of the instrument.
- G The concentration may be biased high due to matrix interferences (i.e, co-elution) with non-target compound(s). The result should be considered estimated.
- H The analysis of pH was performed beyond the regulatory-required holding time of 15 minutes from the time of sample collection.
- I The RPD between the results for the two columns exceeds the method-specified criteria; however, the lower value has been reported

Report Format: Data Usability Report



Project Name:BAE-GREENLAWNLab Number:L1313216Project Number:BAE 1102Report Date:07/22/13

Data Qualifiers

due to obvious interference.

- M Reporting Limit (RL) exceeds the MCP CAM Reporting Limit for this analyte.
- NJ Presumptive evidence of compound. This represents an estimated concentration for Tentatively Identified Compounds (TICs), where the identification is based on a mass spectral library search.
- P The RPD between the results for the two columns exceeds the method-specified criteria.
- Q The quality control sample exceeds the associated acceptance criteria. For DOD-related projects, LCS and/or Continuing Calibration Standard exceedences are also qualified on all associated sample results. Note: This flag is not applicable for matrix spike recoveries when the sample concentration is greater than 4x the spike added or for batch duplicate RPD when the sample concentrations are less than 5x the RL. (Metals only.)
- **R** Analytical results are from sample re-analysis.
- **RE** Analytical results are from sample re-extraction.
- J Estimated value. This represents an estimated concentration for Tentatively Identified Compounds (TICs).
- ND Not detected at the reporting limit (RL) for the sample.

Report Format: Data Usability Report



Project Name:BAE-GREENLAWNLab Number:L1313216Project Number:BAE 1102Report Date:07/22/13

REFERENCES

Compendium of Methods for the Determination of Toxic Organic Compounds in Ambient Air. Second Edition. EPA/625/R-96/010b, January 1999.

LIMITATION OF LIABILITIES

Alpha Analytical performs services with reasonable care and diligence normal to the analytical testing laboratory industry. In the event of an error, the sole and exclusive responsibility of Alpha Analytical shall be to re-perform the work at it's own expense. In no event shall Alpha Analytical be held liable for any incidental, consequential or special damages, including but not limited to, damages in any way connected with the use of, interpretation of, information or analysis provided by Alpha Analytical.

We strongly urge our clients to comply with EPA protocol regarding sample volume, preservation, cooling, containers, sampling procedures, holding time and splitting of samples in the field.



Certificate/Approval Program Summary

Last revised August 3, 2012 - Mansfield Facility

The following list includes only those analytes/methods for which certification/approval is currently held. For a complete listing of analytes for the referenced methods, please contact your Alpha Customer Service Representative.

Connecticut Department of Public Health Certificate/Lab ID: PH-0141.

Wastewater/Non-Potable Water (Inorganic Parameters: pH, Turbidity, Conductivity, Alkalinity, Aluminum, Antimony, Arsenic, Barium, Beryllium, Boron, Cadmium, Calcium, Chromium, Cobalt, Copper, Iron, Lead, Magnesium, Manganese, Mercury, Molybdenum, Nickel, Potassium, Selenium, Silver, Sodium, Strontium, Thallium, Tin, Titanium, Vanadium, Zinc, Total Residue (Solids), Total Suspended Solids (non-filterable).

Organic Parameters: PCBs, Organochlorine Pesticides, Technical Chlordane, Toxaphene, Acid Extractables, Benzidines, Phthalate Esters, Nitrosamines, Nitroaromatics & Isophorone, PAHs, Haloethers, Chlorinated Hydrocarbons, Volatile Organics.)

Solid Waste/Soil (Inorganic Parameters: pH, Aluminum, Antimony, Arsenic, Barium, Beryllium, Cadmium, Calcium, Chromium, Hexavalent Chromium, Cobalt, Copper, Iron, Lead, Magnesium, Manganese, Mercury, Molybdenum, Nickel, Potassium, Selenium, Silver, Sodium, Thallium, Titanium, Vanadium, Zinc, Total Organic Carbon, Corrosivity, TCLP 1311, SPLP 1312. Organic Parameters: PCBs, Organochlorine Pesticides, Technical Chlordane, Toxaphene, Volatile Organics, Acid Extractables, Benzidines, Phthalates, Nitrosamines, Nitroaromatics & Cyclic Ketones, PAHs, Haloethers, Chlorinated Hydrocarbons.)

Florida Department of Health Certificate/Lab ID: E87814. NELAP Accredited.

Non-Potable Water (Inorganic Parameters: SM2320B, SM2540D, SM2540G.)

Solid & Chemical Materials (Inorganic Parameters: 6020, 7470, 7471, 9045. Organic Parameters: EPA 8260, 8270, 8082, 8081.)

Air & Emissions (EPA TO-15.)

Louisiana Department of Environmental Quality Certificate/Lab ID: 03090. NELAP Accredited.

Non-Potable Water (Inorganic Parameters: EPA 180.1, 245.7, 1631E, 3020A, 6020A, 7470A, 9040, 9050A, SM2320B, 2540D, 2540G, 4500H-B, Organic Parameters: EPA 3510C, 3580A, 3630C, 3640A, 3660B, 3665A, 5030B, 8015D, 3570, 8081B, 8082A, 8260B, 8270C, 8270D.)

Solid & Chemical Materials (Inorganic Parameters: EPA 1311, 3050B, 3051A, 3060A, 6020A, 7196A, 7470A, 7471B, 7474, 9040B, 9045C, 9060. Organic Parameters: EPA 3540C, 3570, 3580A, 3630C, 3640A, 3660, 3665A, 5035, 8015D, 8081B, 8082A, 8260B, 8270C, 8270D.)

Biological Tissue (Inorganic Parameters: EPA 6020A. Organic Parameters: EPA 3570, 3510C, 3610B, 3630C, 3640A, 8270C, 8270D.)

Air & Emissions (EPA TO-15.)

New Hampshire Department of Environmental Services Certificate/Lab ID: 2206. NELAP Accredited.

Non-Potable Water (<u>Inorganic Parameters</u>: EPA 180.1, 1631E, 6020A, 7470A, 9040B, 9050A, SM2540D, 2540G, 4500H+B, 2320B, 3020A, . <u>Organic Parameters</u>: EPA 3510C, 3630C, 3640A, 3660B, 8081B, 8082A, 8270C, 8270D, 8015D.)

Solid & Chemical Materials (Inorganic Parameters: SW-846 1311, 3050B, 3051A, 6020A, 7471B, 9040B, 9045C. Organic Parameters: SW-846 3540C, 3580A, 3630C, 3640A, 3660B, 3665A, 8270C, 8015D, 8082A, 8081B.)

New Jersey Department of Environmental Protection Certificate/Lab ID: MA015. NELAP Accredited.

Non-Potable Water (<u>Inorganic Parameters</u>: SW-846 1312, 3020A, SM2320B, SM2540D, 2540G, 4500H-B, EPA 180.1, 1631E, SW-846 7470A, 9040C, 6020A, 9050A. <u>Organic Parameters</u>: SW-846 3510C, 3580A, 3630C, 3640A, 3660B, 3665A, 8015D, 8081B, 8082A, 8270C, 8270D)

Solid & Chemical Materials (Inorganic Parameters: SW-846 1311, 1312, 3050B, 3051A, 6020A, 7471B, 7474, 9040B, 9040C, 9045C, 9045D, 9060. Organic Parameters: SW-846 3540C, 3570, 3580A, 3630C, 3640A, 3660B, 3665A, 8081B, 8082A, 8270C, 8270D, 8015D.)

Atmospheric Organic Parameters (EPA 3C, TO-15, TO-10A, TO-13A-SIM.)

Biological Tissue (Inorganic Parameters: SW-846 6020A. <u>Organic Parameters</u>: SW-846 8270C, 8270D, 3510C, 3570, 3610C, 3630C, 3640A)

New York Department of Health Certificate/Lab ID: 11627. NELAP Accredited.

Non-Potable Water (Inorganic Parameters: SM2320B, SM2540D, 6020A, 1631E, 7470A, 9050A, EPA 180.1, 3020A. Organic Parameters: EPA 8270C, 8270D, 8081B, 8082A, 3510C.)

Solid & Hazardous Waste (Inorganic Parameters: EPA 6020A, 7471B, 7474, 9040C, 9045D. Organic Parameters: EPA 8270C, 8270D, 8081B, 8082A, 1311, 3050B, 3580A, 3570, 3051A.)

Air & Emissions (EPA TO-15, TO-10A.)

Pennsylvania Certificate/Lab ID: 68-02089 NELAP Accredited

Non-Potable Water (Inorganic Parameters: 1312, 1631E, 180.1, 3020A, 6020A, 7470A, 9040B, 9050A, 2320B, 2540D, 2540G, SM4500H+-B. Organic Parameters: 3510C, 3580A, 3630C, 3640A, 3660B, 3665A, 8015D, 8081B, 8082A, 8270C, 8270D.)

Solid & Hazardous Waste (Inorganic Parameters: EPA 1311, 3051A, 6020A, 7471B, 7474 9040B, 9045C, 9060. Organic Parameters: EPA3050B, 3540C, 3570, 3580A, 3630C, 3640A, 3660B, 3665A, 8270C, 8270D, 8081B, 8015D, 8082A.)

Rhode Island Department of Health Certificate/Lab ID: LAO00299. NELAP Accredited via NJ-DEP.

Refer to NJ-DEP Certificate for Non-Potable Water.

Texas Commission of Environmental Quality Certificate/Lab ID: T104704419-08-TX. NELAP Accredited.

Solid & Chemical Materials (Inorganic Parameters: EPA 6020, 7470, 7471, 1311, 9040, 9045, 9060. Organic Parameters: EPA 8015, 8270, 8081, 8082.)

Air (Organic Parameters: EPA TO-15)

Virginia Division of Consolidated Laboratory Services Certificate/Lab ID:460194. NELAP Accredited.

Non-Potable Water (<u>Inorganic Parameters</u>: EPA 3020A, 6020A, 245.7, 9040B. <u>Organic Parameters</u>: EPA 3510C, 3640A, 3660B, 3665A, 8270C, 8270D, 8082A, 8081B, 8015D.)

Solid & Chemical Materials (Inorganic Parameters: EPA 6020A,7470A,7471B,9040B,9045C,3050B,3051, 9060. Organic Parameters: EPA 3540C, 3580A, 3630C, 3640A, 3660B, 3665A, 3570, 8270C, 8270D, 8081B, 8082A, 8015D.)

Washington State Department of Ecology <u>Certificate/Lab ID</u>: C954. *Non-Potable Water* (<u>Inorganic</u> Parameters: SM2540D, 180.1, 1631E.)

Solid & Chemical Materials (<u>Inorganic Parameters</u>: EPA 6020, 7470, 7471, 7474, 9045C, 9050A, 9060. <u>Organic Parameters</u>: EPA 8081, 8082, 8015, 8270.)

U.S. Army Corps of Engineers

Department of Defense, L-A-B Certificate/Lab ID: L2217.01.

Non-Potable Water (Inorganic Parameters: EPA 6020A, SM4500H-B. Organic Parameters: 3020A, 3510C, 8270C, 8270C, 8270C-ALK-PAH, 8270D-ALK-PAH, 8082A, 8081B, 8015D-SHC, 8015D.)

Solid & Hazardous Waste (Inorganic Parameters: EPA 1311, 3050B, 6020A, 7471A, 9045C, 9060, SM 2540G, ASTM D422-63. Organic Parameters: EPA 3580A, 3570, 3540C, 8270C, 8270D, 8270C-ALK-PAH, 8270D-ALK-PAH 8082A, 8081B, 8015D-SHC, 8015D.

Air & Emissions (EPA TO-15.)

Analytes Not Accredited by NELAP

Certification is not available by NELAP for the following analytes: **8270C:** Biphenyl. **TO-15:** Halothane, 2,4,4-Trimethyl-2-pentene, 2,4,4-Trimethyl-1-pentene, Thiophene, 2-Methylthiophene, 3-Methylthiophene, 2-Ethylthiophene, 1,2,3-Trimethylbenzene, Indan, Indene, 1,2,4,5-Tetramethylbenzene, Benzothiophene, 2-Methylnaphthalene, 1-Methylnaphthalene.