

TOWN OF HUNTINGTON

DEPARTMENT OF ENVIRONMENTAL WASTE MANAGEMENT

EAST NORTHPORT LANDFILL SITE INSPECTION REPORT

Date	Day of the Week	Report No.	Report Length		
4/18/05	S (M) T W T F S	2005-1	Page ___ of ___ Page(s)		
Report Personnel					
Signature(s)	Print Name(s)	TOHDEC or Company Name			
1. <i>[Signature]</i>	1. R. Koopman	1. TOHDEC ^{EWV}			
2.	2.	2.			
3.	3.	3.			
Equipment & Instrumentation Used					
1.	None	4.			
2.		5.			
3.		6.			
Atmospheric Conditions					
Readings Taken at Islip - MacArthur Airport					
Time	Weather Conditions	Temperature (F)	Barometric Pressure (in) & Direction	Relative Humidity (%)	Wind Speed (mph) & Direction
9:00	CLAR	56°	30.4	78%	SSW @ 5 mph
Site Inspection Results					
Landfill Components	Typical Problems	Locations and Types of Problems Noted in Field	Required Maintenance and Repairs		
Stormwater Drainage Pipes Structures, Manholes & Catch Basins	Obstructed or interrupted stormwater flow commonly caused by sediment in drainage pipes and structures, debris on drainage grates, uneven settlement or separation of drainage pipes and or structures. Long term problems often include pipe or structure cracks, loose mortar and brick work, broken or missing structure steps and deteriorated drainage frames, grates and manhole covers.	DRAINAGE COMPONENTS O.K. (checked some debris) FROM GRATES			

Gabions & Rip Rap Channels	Obstructed or interrupted stormwater flow is commonly caused by debris or vegetative growth in the gabion cages and rip rap channels. Broken gabion cages can result in gabion stone loss creating erosion and washout problems.	Gabions, Rip Rap all appears OK	N/A
Recharge Basins	Overflowing of the recharge basins or a decrease of the drainage capacity is often due to excessive vegetative growth and sediment on the basin surface. Scouring at drainage outlets can be caused by excessive stormwater flow.	Basins Dry - NO SIGN OF OVERFLOW - SOME veg. growth NO SCOURING	N/A

Exhibit 3 (Continued)

Site Inspection Results			
Landfill Components	Typical Problems	Locations and Types of Problems Noted in Field	Required Maintenance and Repairs
Vegetative Cover, Topsoil & Final Cover Materials	Bare, bald or dead grass areas often result from dry climate periods or droughts. Damage to the vegetative cover, topsoil and or final cover material may result from the following: soil erosion, washouts, stormwater run-on or run-off, rodent holes and unwanted vegetative growth such as trees, shrubs, and vines. Ponding areas and wet spots are often caused by uneven soil settlement or poor soil drainage.	NO EXTENSIVE bare or eroded AREAS NOTICED - SOME AREAS dry but will probably revive. Some UNWANTED wood growth.	REMOVE Large (72") woody saplings & bushes
Landfill Liner & Geosynthetic Materials	Severe erosion of the cover material could cause landfill liner and geosynthetic material deterioration from unwanted atmospheric exposure. Liner rips or tears due could occur as a result of uneven soil settlement below the liner. Excessive loads placed on the landfill area could result in liner punctures.	NO SIGNIFICANT erosion seen. NO Liner exposed OR UNEVEN settlement noticed	
Gas Blower Station	Structural damage to blower station house, blowers, lighting and or electrical power systems are often caused by storms, long term outdoor weather exposure and or vandalism. Note: The inspection, maintenance and repairs of the gas monitoring wells, collection wells and condensate traps are recorded on the Gas Monitoring Reports.	Blower station All OK. - Some LEAVES & debris	SWEEP OUT LEAVES - CLEAN UP CLEARLY. BRASS BLOWERS AS REQUIRED
Crushed Stone Roads	Stone loss can occur due to vehicular use, erosion, settlement. Excessive growth within roadway limits will result in obstructed or reduced roadway capacity.	SOME Stone loss on Road to top front end	- add stone on top rd.

<p>Bifuminous Pavements</p>	<p>Pavement cracks and deterioration are often caused by corrosive chemical spills or seasonal effects of freezing and thawing. Pavement settlement can result in ponding areas.</p>	<p>Some CRACKS in TARMAAC - NOT SIGNIFICANT ONE hole</p>	<p>- hole in tarmaac (in 6") should be filled. TARMAAC/ROADWAY should be sealed</p>
<p>Fences, Gates, Guide Rails, and Locks, & Warning Signs</p>	<p>Vandalism and on site tampering can be detected by checking for cut open fences, broken gates and locks, missing or graffiti covered warning signs. Damaged guide rail sections often occur from vehicular contact. In general, metal corrosion, rust, cracking, pitting, fatigue should be observed.</p>	<p>No signs of Vandalism noticed - gates/locks/fence all OK</p>	<p>—</p>
<p>Lobster Traps/ Fishing Gear</p>	<p>Traps placed in the wrong location may cause loss of vegetation and subsequent erosion of surface soils. Traps leaning against fence may damage fencing. Traps must not interfere with any Landfill equipment or access to areas</p>	<p>Lobster Traps remain in most areas w/ vegetation growing on them. NOT a problem</p>	<p>—</p>

Use the area below for additional comments

Landfill in general good condition - NO STRUCTURAL OR VISUAL OR SAFETY problems. Need to remove some woody growth on slopes