

330 Crossways Park Drive, Woodbury, New York 11797-2015 516-364-9890 • 718-460-3634 • Fax: 516-364-9045 www.dvirkaandbartilucci.com

May 26, 2011

Board of Directors

Henry J. Chlupsa, P.E. President & Chairman Steven A. Fangmann, P.E., BCEE Executive Vice President

Robert L. Raab, P.E. Vice President

Vice Presidents

Richard M. Walka Senior Vice President

Dennis F. Koehler, P.E. Senior Vice President

Joseph H. Marturano Senior Vice President

Garrett M. Byrnes, P.E. Vice President

Thomas P. Fox, P.G. Vice President

William D. Merklin, P.E. Vice President

Harvey P. Moutal, P.E., BCEE Vice President

Michael Neuberger, P.E. Vice President

Kenneth J. Pritchard, P.E.

Theodore S. Pytlar, Jr.

Vice President
Michael E. Urtnowski

Brian M. Veith, P.E. Vice President

Charles J. Wachsmuth, P.E. Vice President

Senior Associates

Steven M. Cabrera
Christopher M. Clement
Rob J. DeGiorgio, P.E., CPESC
Joseph A. Fioraliso, P.E.
Michael R. Hofgren
Richard W. Lenz, P.E.
Philip R. Sachs, P.E.

Daniel Shabat, P.E. Associates

Joseph F. Baader
Rudolph F. Cannavale
Ellen R. DeOrsay
Matthew R. DeVinney, P.E.
Frank DeVita
Christopher W. Francis
Christopher Koegel
Christopher M. LeHanka
James J. Magda
Olga Mubarak-Jaramillo
Roger W. Owens
Robbin A. Petrella
Edward J. Reilly
Jason R. Tonne

Mr. Payson Long
Division of Environmental Remediation
New York State Department of Environmental Conservation
625 Broadway, 12th Floor
Albany, NY 12233-7013

Re: Active Industrial Uniform Site (Site No. 1-52-125)

D&B Work Assignment No. D004446-01

Quarterly Report No. 24

D&B No. 2578

Dear Mr. Long:

Quarterly Report No. 24 presents a summary of the quarterly operation, maintenance, monitoring and sampling activities performed at the Active Industrial Uniform Site groundwater extraction and treatment system, located at 63 West Montauk Highway in the Village of Lindenhurst, Suffolk County, New York (see Attachment A, Figure 1), for the period beginning October 1, 2010 through December 31, 2010.

Operation, system maintenance, monitoring and sampling activities were conducted by a New York State Department of Environmental Conservation (NYSDEC) "call-out" contractor, Environmental Assessment and Remediations (EAR), under direct contract with the NYSDEC. Reporting, data management and assessment, and additional engineering/technical evaluation services were performed by Dvirka and Bartilucci Consulting Engineers (D&B).

Presented below is a summary of system operations and maintenance completed during the quarter, as well as the results and interpretation of the sample collection and analysis completed during this reporting period. All groundwater monitoring well sample data is discussed in the Groundwater Sampling Report No. 4. In addition, a Site Management Plan (SMP) for the Active Industrial Uniform Site is currently being drafted by D&B.

Groundwater Extraction and Treatment System Operation and Maintenance

During this reporting period, on-site extraction well RW-1 operated at an average pumping rate of approximately 112 gallons per minute (gpm). As stated in Quarterly Report No. 22, the NYSDEC requested the shutdown of off-site extraction well RW-2 on April 21, 2010 due to the presence of historically low concentrations of chlorinated volatile organic compounds (VOCs), along with continued decline in total VOC concentrations.

CONSULTING ENGINEERS

Mr. Payson Long
Division of Environmental Remediation
New York State Department of Environmental Conservation
May 26, 2011

Page 2

Since the treatment system is no longer receiving groundwater from extraction well RW-2, extraction well RW-1's flow rate was increased in April 2010 in order to maximize its radius of influence and improve the capture of chlorinated VOC-contaminated groundwater potentially migrating off-site. Based on a review of the data, the flow rate for RW-1 shows an overall decreasing trend since the extraction well flow rate was adjusted in April 2010, possibly due to iron plating on the well screen and/or slight pump wear over time. A normalized graph of the average flow rate for RW-1 since May 2009 is presented in Attachment B.

During this reporting period, approximately 13,325,000 gallons of treated groundwater was discharged to Little Neck Creek. Though not included on the as-built drawings for the site, the discharge water flows to a storm water basin adjacent to the creek and the overflow from this structure flows into the creek. Approximately 27.3 pounds of total VOCs were removed from the extracted groundwater during this reporting period and approximately 1,397 pounds of total VOCs have been removed since start-up of the system. The average total VOC removal efficiency for this quarter was approximately 98 percent. A summary of the extraction and treatment system performance results is provided in Attachment C.

The groundwater extraction system was operational for a total of approximately 1,986 hours and inoperative for a total of approximately 221 hours due to system alarm conditions and non-routine maintenance.

Alarm conditions responded to during this reporting period included the following:

- Transfer pump No. 2 fault resulting from an under-current condition (one event);
- Loss of power to the treatment system building, which caused the transfer pump VFDs to malfunction and need to be reset (one event); and
- High level alarm condition at air stripper No. 1 (two events).

Non-routine maintenance performed during this reporting period included the following:

- Backfill portions of the UST excavation area with clean fill and on-site cleanup of recycled concrete aggregate (RCA) on October 18, 2010;
- Replacement of leaking sample ports on October 26 and 28 and November 2, 2010;
- Assessment and repair of treatment system heaters and assessment of in-situ soil remediation enclosure for the soil excavated as part of the UST removal excavation on November 2, 2010;
- Assessment of outdoor lighting on December 2, 2010;
- Assessment of blocked effluent carbon sample port due to ice, and assessment of malfunctioning treatment system building heaters on December 22, 2010.

CONSULTING ENGINEERS

Mr. Payson Long
Division of Environmental Remediation
New York State Department of Environmental Conservation
May 26, 2011

Page 3

- Assessment of granulated activated carbon (GAC) vessels, which was discharged from the treatment system effluent stack on December 22, 2010.
- Pumping out of knock out drum condensate on December 22 and 23, 2010;
- Assessment and restart of treatment system building heaters on December 23, 2010;
- Shutdown of treatment system, and draining of system stripper towers, influent and effluent piping due to lack of heat within the treatment system building on December 23, 2010; and
- Removal of snow from the property on December 29, 2010.

EAR has reported that routine maintenance was not conducted during this reporting period due to the large amount of system downtime during this reporting period.

A copy of the Site Activities Logs, System Monitoring Logs and a System Operations and Downtime Log for this reporting period, which includes a summary of system maintenance events and alarm responses, as prepared by EAR, is provided in Attachment D.

As noted in the Quarter 22 report, the treatment system effluent piping was borescoped in order to diagnose a high pressure reading and associated alarm conditions in the piping. The high pressure is possibly due to a blockage in the effluent piping. However, as the treatment system is currently only receiving water from one extraction well, treatment system effluent flow rate and pressure have reduced such that system shutdowns related to the possible effluent piping restriction have not occurred. Based on this information, and at the current influent flow rate, further diagnosis of the treatment system effluent piping is no longer warranted.

Groundwater Extraction and Treatment System Monitoring (Aqueous Samples)

Monthly groundwater samples were collected from the combined influent sample tap (COMB-INF) and the treatment system discharge sample tap (COMB-EFF) on October 26 and November 30, 2010. All samples were analyzed for VOCs by United States Environmental Protection Agency (USEPA) Method 624. The samples collected from the combined influent sample tap were also analyzed for Target Analyte List (TAL) metals by USEPA Method 6010B and for pH by USEPA Method 9040B.

Monthly, quarterly and semiannual treatment system samples for the month of December were not collected during this reporting period due to the amount of system downtime during the month of December. As per the NYSDEC, routine sampling will resume once the treatment system is restarted.

All sample results are summarized in Attachment E.

Based on the analytical results of the influent groundwater sample results, COMB-INF total VOCs ranged from 233 ug/l to a maximum concentration of 283 ug/l detected in samples collected on October 26, 2010. During this reporting period, tetrachloroethene (PCE) was detected in exceedance

CONSULTING ENGINEERS

Mr. Payson Long
Division of Environmental Remediation
New York State Department of Environmental Conservation
May 26, 2011

Page 4

of its Class GA groundwater standard of 5.0 ug/l at concentrations ranging from 190 ug/l to 230 ug/l, with the maximum concentration detected in samples collected on October 26, 2010. Trichloroethene (TCE) was detected in excess of its Class GA groundwater standard of 5.0 ug/l at concentrations ranging from 42.0 ug/l to 49.0 ug/l, with the maximum concentration detected in samples collected on October 26, 2010. As noted in Quarterly Report No. 22, cis-1,2-dichlorethene (cis-1,2-DCE), was not analyzed during this reporting period as USEPA Method 624 does not report cis-1,2-DCE as part of its suite of compounds. D&B notified the NYSDEC that cis-1,2-DCE was not included as part of Method 624 upon review of the data and has recommended returning to Method 8260, in order to continue to monitor this site-specific contaminant of concern.

In addition, COMB-INF manganese was detected in excess of its Class GA groundwater standard of 300 ug/l at concentrations ranging from 974 ug/l to 986 ug/l, with the maximum concentration detected in the samples collected on November 30, 2010, while COMB-INF sodium was detected in exceedance of its Class GA groundwater standard of 20,000 ug/l at concentrations ranging from 22,300 ug/l to 23,100 ug/l, with the maximum concentration detected in samples collected on November 30, 2010. COMB-INF iron was detected in exceedance of its Class GA groundwater standard of 300 ug/l at a concentration of 1,360 ug/l on November 30, 2010.

The sample results for VOCs from the aqueous phase air stripper discharge have been compared to the NYSDEC site-specific effluent limits. Based on the aqueous phase effluent sample results, COMB-EFF VOCs were all detected below the NYSDEC site-specific effluent limits.

Groundwater Extraction and Treatment System Monitoring (Air Sampling)

Air samples were collected from the vapor phase carbon adsorption system influent (VPCV-INF), midfluent (VPCV-MID) and effluent (VPCV-EFF) sample taps on October 26 and November 30, 2010 and analyzed for VOCs utilizing USEPA Method TO-15. The results of the vapor phase carbon adsorption system samples are compared to the NYSDEC site-specific effluent limits. The vapor phase carbon adsorption system discharge sample results are provided in Attachment E.

VOC effluent discharge rates were below the NYSDEC site-specific effluent discharge rates, with the exception of 1,2-DCE and TCE. 1,2-DCE was discharged at a rate of 5.7 x 10⁻³ lbs/hr and 8.1 x 10⁻³ on October 26 and November 30, 2010, respectively, exceeding its site-specific effluent discharge rate of 3.0 x 10⁻³ lbs/hr, while TCE was discharged at a rate of 1.2 x 10⁻² lbs/hr on November 30, 2010, exceeding its site-specific effluent discharge rate of 6.0 x 10⁻³ lbs/hr. The NYSDEC was immediately notified of these exceedances upon review of the data. D&B will continue to closely monitor 1,2-DCE and TCE concentrations in the treatment system vapor samples and continue to notify the NYSDEC when exceedances of the site-specific effluent limits are noted. Also, as recommended in previous quarterly reports, a change-out of the GAC in the two on-site carbon vessels is warranted.

Data Validation

The data packages submitted by Test America have been reviewed for completeness and compliance with NYSDEC ASP Quality Assurance/Quality Control (QA/QC) requirements. Test America is a

CONSULTING ENGINEERS

Mr. Payson Long Division of Environmental Remediation New York State Department of Environmental Conservation May 26, 2011 Page 5

New York State Department of Health (NYSDOH) Environmental Laboratory Approval Program (ELAP)-certified laboratory. All sample results have been deemed valid and usable for environmental assessment purposes, except as noted below:

- For air samples collected on October 26, 2010, the laboratory used a one-point calibration for ethanol and ethanol was qualified as estimated (J/UJ) in all samples.
- For air samples collected on October 26, 2010, cis-1,2-DCE and PCE were detected above the linear range of the instrument calibration and were reanalyzed at a secondary dilution. The associated results are qualified with a "D."
- For air samples collected on November 30, 2010, cis-1,2-DCE, TCE, and PCE were detected above the linear range of the instrument calibration and were reanalyzed at a secondary dilution. The associated results are qualified with a "D."

Data Validation Checklists are presented in Attachment F.

Findings

Based on the results of performance monitoring conducted during this reporting period, D&B offers the following findings:

- The results of the system influent samples show that extraction well RW-1 is continuing to capture VOC-contaminated groundwater.
- The replacement analytical method approved for VOC analysis (USEPA Method 624) includes all site-specific contaminants of concern, with the exception of cis-1,2-DCE.
- Extraction well RW-1 was pumping at an average rate of 112 gpm during this reporting period, which is higher than the contract-required flow rate range of 80 gpm to 100 gpm, as specified in the Active Industrial Uniform Site Contract Documents. As detailed in Quarterly Report No. 22, extraction well RW-1 was adjusted to pump at a higher extraction rate after extraction well RW-2 was shut down on April 21, 2010, in order to increase its on-site radius of influence and ensure that all on-site VOCs are captured prior to migration off-site.
- The effluent pressure readings have been lower, as compared to previous quarters, due to only RW-1 pumping.
- Note that no new supply wells have been installed on the Active Industrial property and, based on a windshield inspection of the immediate area, no new schools or parks have been constructed in the vicinity of or downgradient from the Active Industrial property.
- The Class GA Groundwater Standards and Guidance Values and the NYSDEC site-specific effluent limits have not been modified since system start-up in December 2001.
 A new DER-10 document, dated May 2010, has been implemented since the March 1998 ROD was issued.

CONSULTING ENGINEERS

Mr. Payson Long Division of Environmental Remediation New York State Department of Environmental Conservation May 26, 2011

Page 6

The toxicity data, cleanup levels and remedial action objectives, as defined in the March 1997 Record of Decision, remain unchanged.

Recommendations

Based on the results of performance monitoring completed during this reporting period, D&B provides the following recommendations:

- Continue operation of the groundwater extraction and treatment system to minimize downgradient migration of site-related contaminants currently being captured by the system.
- Based on the exceedances noted in the effluent samples collected from the carbon vessels, it is warranted to replace the granular activated carbon contained in the carbon vessels.
- Due to the fact that the treatment system is currently only receiving water from extraction well RW-1, further diagnosis of the treatment system effluent piping is no longer warranted. However, if the influent flow rate, and therefore pressure, is increased in the future, it may be warranted to continue the borescope of the effluent piping.
- Change the VOC analytical method back to USEPA Method 8260 in order to monitor the concentrations of cis-1,2-DCE in site groundwater.

Please do not hesitate to contact me at (516) 364-9890, Ext. 3094, if you have any questions.

Very truly yours,

Stephen Tauss Project Manager

SET/PM(t)/j,lf Attachments

cc:

R. Walka (D&B)


P. Martorano (D&B)

F. DeVita (D&B)

♦2578\SET031011-PL_QR24.DOC(R06)

ATTACHMENT A

FIGURES



SOURCE: GOOGLE EARTH 2005




ACTIVE INDUSTRIAL UNIFORM SITE VILLAGE OF LINDENHURST, NEW YORK

SITE LOCATION MAP

FIGURE 1

ATTACHMENT B

NORMALIZED GRAPH OF AVERAGE FLOW RATE FOR RW-1



ATTACHMENT C

PERFORMANCE SUMMARY

ACTIVE INDUSTRIAL UNIFORM SITE NYSDEC SITE No. 1-52-125 EXTRACTION AND TREATMENT SYSTEM PERFORMANCE RESULTS - AQUEOUS

SAMPLE COLLECTION DATE	SYSTEM INFLUENT AVERAGE EXTRACTION RATE (gpm)	SYSTEM INFLUENT TOTAL VOC CONCENTRATION (ug/L)	SYSTEM EFFLUENT TOTAL VOC CONCENTRATION (ug/L)	TOTAL VOC REMOVAL EFFICIENCY (%)	ESTIMATED AVERAGE TOTAL VOC REMOVAL RATE (lb/hr)	ESTIMATED SYSTEM RUNTIME (hr)	CUMULATIVE TOTAL VOC REMOVAL (lbs)
7/20/2006	65.32 (RW-1) 0.00 (RW-2)	550	< 5.0	99.09%	1.80E-02	473 (RW-1) 0 (RW-2)	1.040.86
8/17/2006	63.60 (RW-1) 91.30 (RW-2)	258	< 5.0	98.06%	2.00E-02	719 (RW-1) 96 (RW-2)	1.055.23
9/19/2006	60.33 (RW-1) 90.31 (RW-2)	294	< 5.0	98.30%	2.22E-02	1016 (RW-1) 1016 (RW-2)	1,077.73 (2)
10/9/2006	59.18 (RW-1) 0.00 (RW-2)	666	< 5.0	99.25%	1.97E-02	209 (RW-1) 0 (RW-2)	1,081.85
11/1/2006	58.40 (RW-1) 0.00 (RW-2)	840	< 5.0	99.40%	2.45E-02	550 (RW-1) 0 (RW-2)	1.095.35
12/8/2006	56.70 (RW-1) 0.00 (RW-2)	474	< 5.0	98.95%	1.34E-02	1418 (RW-1) 0 (RW-2)	1,114.41 (2)
1/5/2007	54.22 (RW-1) 0.00 (RW-2)	405	< 5.0	98.77%	1.10E-02	85 (RW-1) 0 (RW-2)	1,115.35
2/26/2007	56.28 (RW-1) 0.00 (RW-2)	244	< 5.0	97.95%	6.87E-03	756 (RW-1) 0 (RW-2)	1,120.54
3/16/2007	52.37 (RW-1) 0.00 (RW-2)	281	< 5.0	98.22%	7.36E-03	505 (RW-1) 0 (RW-2)	1,124.26 (2)
6/15/2007	51.33 (RW-1) 0.00 (RW-2)	269 ⁽⁴⁾	< 5.0	98.14%	6.91E-03	213 (RW-1) 0 (RW-2)	1,125.73 (2)
7/12/2007	52.26 (RW-1) 0.00 (RW-2)	257	< 5.0	98.05%	6.72E-03	266 (RW-1) 0 (RW-2)	1,127.52
8/10/2007	52.47 (RW-1) 0.00 (RW-2)	251	< 5.0	98.01%	6.59E-03	692 (RW-1) 0 (RW-2)	1,132.08
9/12/2007	51.57 (RW-1) 0.00 (RW-2)	295	< 5.0	98.31%	7.61E-03	1232 (RW-1) 0 (RW-2)	1,141.46 ⁽²⁾
10/22/2007	50.10 (RW-1) 0.00 (RW-2)	293	< 5.0	97.98%	6.19E-03	504 (RW-1) 0 (RW-2)	1,141.48
11/13/2007	49.28 (RW-1) 0.00 (RW-2)	250	6.0	97.60%	6.16E-03	1019 (RW-1) 0 (RW-2)	1,150.85 ⁽²⁾
	49.28 (RW-1) 0.00 (RW-2)	207	< 5.0	97.50%	6.16E-03 4.42E-03	` ` ` ` ` ` ` ` ` ` ` ` ` ` `	
1/28/2008 2/22/2008	42.64 (RW-1) 0.00 (RW-2)	207	< 5.0 < 5.0	97.58%	4.42E-03 5.39E-03	650 (RW-1) 0 (RW-2) 473 (RW-1) 0 (RW-2)	1,153.72
	<u> </u>					` ' '	1,156.28
3/14/2008	43.71 (RW-1) 0.00 (RW-2)	231	< 5.0	97.83%	5.05E-03	923 (RW-1) 0 (RW-2)	1,160.94 (2)
4/21/2008	40.16 (RW-1) 0.00 (RW-2)	209	< 5.0	97.60%	4.19E-03	480 (RW-1) 0 (RW-2)	1,162.95
5/14/2008	38.81 (RW-1) 0.00 (RW-2)	153	< 5.0	96.72%	2.96E-03	552 (RW-1) 0 (RW-2)	1,164.58
6/19/2008	40.21 (RW-1) 0.00 (RW-2)	205	< 5.0	97.56%	4.12E-03	1136 (RW-1) 0 (RW-2)	1,169.26 ⁽²⁾
7/14/2008	39.96 (RW-1) 0.00 (RW-2)	308	< 5.0	98.38%	6.16E-03	317 (RW-1) 0 (RW-2)	1,171.21
8/6/2008	36.42 (RW-1) 0.00 (RW-2)	408	< 5.0	98.77%	7.43E-03	215 (RW-1) 0 (RW-2)	1,172.81
9/12/2008	33.56 (RW-1) 70.01 (RW-2)	277 (RW-1) 39.2 (RW-2)	< 5.0	95.36%	4.65E-03 (RW-1) 1.37E-03 (RW-2)	1,228 (RW-1) 838 (RW-2)	1,179.67 ⁽²⁾
10/22/2008	19.22 (RW-1) 82.51 (RW-2)	91.9	< 5.0	94.56%	4.68E-03	483 (RW-1) 483 (RW-2)	1,181.93
11/21/2008	24.64 (RW-1) 79.18 (RW-2)	97.6	< 5.0	94.88%	5.07E-03	718 (RW-1) 718 (RW-2)	1,185.57
12/16/2008	24.55 (RW-1) 79.22 (RW-2)	80.6	< 5.0	93.80%	4.18E-03	740 (RW-1) 740 (RW-2)	1,188.67 ⁽²⁾
1/13/2009	25.50 (RW-1) 78.57 (RW-2)	68.0	< 5.0	92.65%	3.54E-03	0.75 (RW-1) 0.75 (RW-2)	1,188.67
2/27/2009	29.98 (RW-1) 87.28 (RW-2)	81.0	< 5.0	93.83%	4.75E-03	157 (RW-1) 157 (RW-2)	1,189.42
4/1/2009	29.79 (RW-1) 86.99 (RW-2)	78.1	< 5.0	93.60%	4.56E-03	754 (RW-1) 754 (RW-2)	1,192.85 (2)
4/24/2009	29.38 (RW-1) 83.02 (RW-2)	89.1	< 5.0	94.39%	5.01E-03	527 (RW-1) 527 (RW-2)	1,195.50
5/14/2009	88.43 (RW-1) 82.80 (RW-2)	330 (RW-1) 15.0 (RW-2)	< 5.0	98.48%	1.46E-02 (RW-1) 6.21E-04 (RW-2)	305 (RW-1) 408 (RW-2)	1,200.20
7/1/2009	86.12 (RW-1) 84.37 (RW-2)	152.8	< 5.0	96.73%	6.58E-03	157 (RW-1) 157 (RW-2)	1,201.24
10/28/2009	90.59 (RW-1) 84.78 (RW-2)	109.6	7.7	92.97%	4.97E-03	621 (RW-1) 621 (RW-2)	1,204.32
11/17/2009	92.34 (RW-1) 84.78 (RW-2)	` ' ' '	< 5.0	98.44%	1.48E-02 (RW-1) 5.9E-04 (RW-2)	440 (RW-1) 27 (RW-2)	1,210.87
12/23/2009	88.69 (RW-1) 0.00 (RW-2)	525.3	< 5.0	99.05%	2.33E-02	865 (RW-1) 0 (RW-2)	1,231.02
3/1/2010	65.06 (RW-1) 66.18 (RW-2)		< 5.0	98.52%	1.10E-02 (RW-1) 4.3E-04 (RW-2)	721 (RW-1) 136 (RW-2)	1,239.02
3/25/2010	79.42 (RW-1) 79.42 (RW-2)	392.6 (RW-1) 13.0 (RW-2)	< 5.0	98.73%	1.56E-02 (RW-1) 5.2E-04 (RW-2)	638 (RW-1) 523 (RW-2)	1,249.24
4/29/2010	138.00 (RW-1) 66.42 (RW-2)	637.0 (RW-1) 13.0 (RW-2)	< 5.0	99.22%	4.40E-02 (RW-1) 4.3E-04 (RW-2)	464 (RW-1) 275 (RW-2)	1,269.74
5/27/2010	128.63 (RW-1) 0.00 (RW-2)	560.0	< 5.0	99.11%	3.60E-02	671 (RW-1) 0 (RW-2)	1,293.93
6/24/2010	124.45 (RW-1) 0.00 (RW-2)	510.6	< 5.0	99.02%	3.18E-02	822 (RW-1) 0 (RW-2)	1,320.06
7/28/2010	121.10 (RW-1) 0.00 (RW-2)	400.0	< 5.0	98.75%	2.42E-02	649 (RW-1) 0 (RW-2)	1,335.79
8/31/2010	117.77 (RW-1) 0.00 (RW-2)	367.6	< 5.0	98.64%	2.17E-02	815 (RW-1) 0 (RW-2)	1,353.45
9/27/2010	115.31 (RW-1) 0.00 (RW-2)	371.5	< 5.0	98.65%	2.14E-02	734 (RW-1) 0 (RW-2)	1,369.17
10/26/2010	112.29 (RW-1) 0.00 (RW-2)	283.3	< 5.0	98.24%	1.59E-02	613 (RW-1) 0 (RW-2)	1,378.92
11/30/2010	109.58 (RW-1) 0.00 (RW-2)	232.7	< 5.0	97.85%	1.28E-02	831 (RW-1) 0 (RW-2)	1,389.51
12/31/2010 ⁽⁵⁾	110.00 (RW-1) 0.00 (RW-2)	232.7	< 5.0	97.85%	1.28E-02	543 (RW-1) 0 (RW-2)	1,396.46

- NOTES:

 1. Total mass of VOC recovered through December 31, 2004 based on information contained in the Fourth Quarter 2004 Operation and Maintenance Report prepared by Blue Water Environmental Inc.

 2. Estimated through the end of the reporting period.

- 3. Performance results for the reporting period are shaded.
- COMB-INF result approximated as average of 3/16/07 and 7/12/07 results due to laboratory reporting error.
 No sampling event completed in December due to large amount of downtime. RW-1 flow rate and COMB-INF result assumed the same as the 11/30/2010 sampling event.

ABBREVIATIONS gpm: gallons per minute ug/L: micrograms per liter lb/hr: pounds per hour

ATTACHMENT D

SITE LOGS

PERSONNEL ON-SITE	DATE/TIME ON-SITE	TIME OFFSITE		REASON FOR SI	TE VIS	SIT (CHECK BOX BELOW)
KH 1045	10-4-14 1045	1230		Monitoring		Maintenance
				Sampling		Other (Provide Description)
			X	Alarm Response		
Description: Systendown to	ransfer pump #2	under govern Res	44	in 6 troterte	ď.	
Collected readour	Aron the soil pile	stoten.				
	*					
4.4.					~~~	
Retel	10/5/10 0830	1100		Monitoring		Maintenance
				Sampling	0	Other (Provide Description)
				Alarm Response		
Description:	7					
				ALCO CONTROL OF THE C		
Bruce C.	10/18/10 590)	1415		Monitoring		Maintenance
Bruce C.	10/18/10 .	114/5		Sampling	$\bot \!$	Other (Provide Description)
	/ /			Alarm Response		
Description: FU 1a	Exe. pir @	Seven (ME U	4/	CLEAN FR	U	+ RCA on SITE
CLEAR U	P					

PERSONNEL ON-SITE	DATE/TIME ON-SITE		TIME OFFSITE		REASON FOR SITE VISIT (CHECK BOX BELOW)				
K= 10/26/10	lolaslo	1015	1 S 1 S	N	Monitoring	K	Maintenance		
Соружий режим в на мания поличения на подобовить образований в поличений в настой обобностью образований образований обобностью образований образовани	man di sanggan dan sanggan dan sanggan	nakanish Ganasanis makinggipi kemunanan emerepenan		N/	Sampling		Other (Provide Description)		
THE CONTRACTOR OF THE PROPERTY OF THE CONTRACTOR			AND THE CONTROL OF TH		Alarm Response		Manuse passe asserbances and one each education of the climical and the contract of the contra		
escription: MONHAG	ste ch	eck + G	18 tom Soundin	g, R	epiace les	iking	SAMPLE POR.		
				****		-esf			
	NAME AND ADDRESS OF THE PROPERTY OF THE PROPER			enocomo de environ					
(9	10/28/10	1330	left of Sec	Q.	Monitoring	¥	Maintenance		
					Sampling		Other (Provide Description)		
NOTICAL CALCENSO DE LA CALCENSIA CALCENSIA DA LA FILLA DE LA CALCENSIA DE CALCENSIA DE LA CALCENSIA DE CALCEN	A CONTRACTOR OF THE PROPERTY O		SOLUTION CONTROL CONTR						
				Š	Alarm Response	ı			
Description: Replace	2 5 17-11/1	pe for	sthey were I			ale Sh	int oue eyetem.		
escription: Replace	2 3 HW	AE POP	5 that were			alē Sh	of ove eystem.		
						ale Sh	Maintenance		
	11-2-10	0800	sthat were 1		Monitoring	ale Sh	Maintenance		
					Monitoring Sampling	olë Sh			
< 					Monitoring	ole St	Maintenance		
escription:	11-2-10	0800	1345		Monitoring Sampling Alarm Response	<u> </u>	Maintenance Other (Provide Description)		
escription:	11-2-10	0800	1345		Monitoring Sampling Alarm Response	<u> </u>	Maintenance Other (Provide Description)		
escription:	11-2-10	0800	1345		Monitoring Sampling Alarm Response	<u> </u>	Maintenance Other (Provide Description)		
Scription:	11-2-10	0800			Monitoring Sampling Alarm Response	<u> </u>	Maintenance Other (Provide Description)		

PERSONNEL ON-SITE	DATE/TIME ON-SITE	TIME OFFSITE	REASON FOR SITE VISIT (CHECK BOX BE			SIT (CHECK BOX BELOW)
PL	11/5/10 /430			Monitoring		Maintenance
				Sampling		Other (Provide Description)
				Alarm Response		
Description:	f power, h	leset Uto		Restan	40	
KS	11/30/10@0815	godies Antistenen aven konstanten konstanti ja karen etti tilaheden vatta kopullarin konstanti seksistä esitä s	X	Monitoring		Maintenance
THE PROPERTY OF THE PROPERTY O	ante en en la colocular compositiva de la compositiva della compos	and the second s	K	Sampling		Other (Provide Description)
Vision Augusta Muhamban (Maria Calaban	AND THE RESIDENCE OF THE SECOND CONTRACT OF T	adanat kuudukun karanta areen areen ya muun ka hada hada ka ka ka ka da		Alarm Response		<u></u>
KS	12210@1345			Monitoring		Maintenance
	The second secon	AMERI SECULO SE	- Consideration	Sampling	ď	Other (Provide Description)
tema temahan dinangkahan salaban salaban salaban salaban berma dinangkahan permanangkahan permanangkah salaban			Rettormente	Alarm Response		The second secon
Description: Trake o	hotas of outdo	or lighting. To		s Outidon	rig	rting Switch on,

PERSONNEL ON-SITE	DATE/TIN	WE ON-SITE	TIME OFFSITE	REASON FOR SITE VISIT (CHECK BO)		
KMK	12/9/10	0900	1515	Monitoring	Maintenance	
<u> </u>	*	PPA SEEK SEEK DE SEE ALLES ON DE WOODE DE SEEK AND SEEK SEEK SEEK SEEK SEEK SEEK SEEK SEE		Sampling	Other (Provide Description)	
Description:				Alarm Response		
MW-(10	1-106,5	(5)				
KMK, JAB	12/10/11		1515	SAMPLING.	6wofmws.	
h	12-16-10	800	1600	Monitoring	Maintenance	
		THE RESIDENCE OF THE PROPERTY OF THE PERSON		Sampling	Other (Provide Description)	
escription:	With the Command and the Comma			X Alarm Response		
4] 647/E 1500	12/22/10	0800	<u>0960</u> 0930	Monitoring	Maintenance	
				Sampling		
			од на при		The first of the property of t	
escription: ೧೩ ಎ೯೧	fusci- his	Jek Maul	A Cochen San	A 1		
the resolution in	1 Block	23 5	efficit Car	Hance discha	TOUR FROM HOTZ TO	

	DATE/TIME ON-SITE	TIME OFFSITE	REASON FOR S	ITF VI	SIT (CHECK BOX BELOW)
Db	12 23 10 0915	LLOO	Monitoring		
FEILIGE BORRONNESS DE LA MONTE PER RESTORATION DE LA MONTE		and the second s			Maintenance
	and the second s		Sampling		Other (Provide Description)
rescription: Restart	theater, assess	KO DEGNO DO	Alarm Response		MANAGEMENT CONTRACTOR OF THE C
THATOENA A EX	efluent lines	, D(ain, syster	n -	rowers +
	· -				
B/DG	12/29/10 0800	Itoo			
			Monitoring		Maintenance
	- Committee Committee of the Committee Committ	CONTRACTOR	Sampling	X	Other (Provide Description)
escription: 6/00/1	removal.		Alarm Response		
				A CONTRACTOR OF THE PARTY OF TH	
S/KH	1540 0800	1500	Monitoring		Maintenance
5/KH	5/10 0800	1500	Monitoring Sampling	-	Maintenance
			Sampling	XC	Other (Provide Degaring)
			Sampling	XC	Other (Provide Degaring)
			Sampling	XC	Other (Provide Degaring)
	Shout proble from Carbon		Sampling	XC	Other (Provide Degaring)
			Sampling	XC	Other (Provide Degaring)

ACTIVE INDUSTRIAL UNIFORM SITE, NYSDEC SITE No. 1-52-125 SYSTEM MONITORING LOG

	en <mark>anne con l'entre anne anne en entre de l'entre de l</mark>	EM MONITORING LOG		
DATE	<u> 18131/10 KS</u>	9/27/10 KS	10/26/10 15	11/30/10 KS
TIME	OSIS	0845	1015	0815
RW-1				
Flow Rate (gpm)	177	115,31	112,29€ 1048	169.58
Total Flow (gal)	25966377681015	264154544 80910	268872320	274409984e0854
Depth to Water (feet)	3 1	13.12	13.15	13.4
Water Column Above Pump (feet)	entrover of ordering metabol entropies.	encollingua punc montañ		and the second s
Pump Pressure (psi)	17031	17	Most	I+ Fosi
RW-2				
Flow Rate (gpm)		"Viewpod was represented		
Total Flow (gal)				
Bicycle Pump Pressure Reading (psi)	мблифкосануунунган -	and the second s		
Water Column Above Pump (ft H₂O)(psi x 2.31)	K-MANAGANGANGANA M	Notes to the second deposition of the second d		
Pump Pressure (psi)	Aboten participates		199	
Air Stripping Tower (ST-1)		***************************************	-	
Stripper Inlet (Combined Influent) Pressure (psi)	13	3	12/100	13
Transfer Pump (P-1) Outlet Pressure (psi)	2- 2	22	22	27-
Sump Level (inches)	20	20	20	20
Discharge Speed (%)	146.6	46.3	45,8 %	45.6%
Air Stripping Tower (ST-2)	-			
Stripper Inlet Pressure (psi)	22	22	To Zon	22
Transfer Pump (P-2) Outlet Pressure (psi)	2-7-	21	19.5	
Sump Level (inches)	2-1	20	21	2
Discharge Speed (%)		0,0	57,0%,	56.4
Air Stripper Blower (B-1)	J g Agent			
Moisture Knockout Influent (ST-2 Effluent) Vacuum (inches H ₂ O)	Left from	3.5	4,5	4
Blower Influent Vacuum (inches H ₂ 0)	Metalogo.			
Blower Effluent Pressure (inches H ₂ O)	Te la	7, 20,	7.9	9.2
Blower Effluent Velocity (feet/minute)	3535	3355	3390	3600
Blower Effluent Temperature (°F)	83.5	76,8	76,7	73.3
Blower Effluent Flow Rate (ft³/minute)	290	157.5	1190	11270
Treated Water Discharge	1	8 / A ^A		
Flow Rate (gpm)	120.19	116,00	112,20	110.72
Total Flow (gal)	138712758481023	39171584020910	3964755848 1189	4020778240089

ACTIVE INDUSTRIAL UNIFORM SITE, NYSDEC SITE No. 1-52-125 SYSTEM MONITORING LOG

DATE	8 auto KS	9/22/10 KS	10/28/10 KS	11/30/10 KS
TIME	6815	0845	1015	08 15
Vapor Phase Carbon				
Lead vessel pressure (inchesH ₂ O)		6.5	1: 0	8,5
Lead vessel temperature (°F)	899	7a °	720	68°
Lag vessel pressure (inches H ₂ O)	and the second	3,5	3.5	4
Lag vessel temperature (°F)	80°	78-	710	650
Catridge Filter System				
Inlet Pressure (psi)				
Outlet Pressure (psi)				
Pressure Differential (psi)				
Process Sampling Performed		negamen etaks hidd dan oo'd heelt hid is an oo op oo mee hij dan door oo oo op op op dy sysjen oo mee op oo		
(Monthly) Combined Influent (VOCs, TAL Inorganics, pH)	@ 1041	@ 1022	C.1238	@ 1051
(Monthly) Combined Effluent (VOCs)	@ 1048	@ 1035	@ 1246	@ 1100
(Monthly) Influent Vapor (VOCs)	@ 1107	<u>e 1116</u>	@ <u>1331</u>	@ 1112
(Monthly) Mid-fluent Vapor (VOCs)	@ 1114	@ Han	@ 1342	@ 1124
(Monthly) Effluent Vapor (VOCs)	@ 1123	@ 1137	@ 1550	Q 1135
(Quarterly) Influent RW-1 (VOCs, TAL Inorganics, pH)		@ 1048		
(Quarterly) Influent RW-2 (VOCs, TAL Inorganics, pH)		Communication of the Communica		
(Quarterly) Mid-fluent (VOCs)		@ 1100		
(Quarterly) Effluent (TAL Inorgaincs)		@ 103S		
(Semi-Annual) Effluent (pH, COD, TSS TDS)				
(Semi-Annual) Effluent (Field Test - DO, Conductivity, turbidity, chlorine) COMMENTS				

8/31/10 System conning wormed on Archival + departure
9/27/10 System conning wormed on Archival + Departure.

ACTIVE INDUSTRIAL UNIFORM SITE, NYSDEC SITE NO. 1-52-125 SYSTEM OPERATIONS AND DOWNTIME SHEET

SHUT-OFF DATE/TIME	RESTART DATE/TIME	CAUSE	ACTIONS TAKEN	TOTALIZED DEADING
	1 1		ACTIONS TAKEN	TOTALIZER READING
4/12/10 1000	4/21/1010 1230	Video face	- Cut Effloew line tock forblack.	RW-1235168
4/29/10 1300	4/29/10 1320	KOD	Emphy	RW 1 237634048
	6/10/10 0900	HH/ASHI	Pumpdown /restart	RW 1 245434208
7/15/10 @ 915	745-10 1400		Paintina PVC PID96	Qh.(
7-16-10 @ 825	7,5-10 1320		1/	25/636528 RW1 2517716/6
10-4-10 @0940	10-4-10 @ 1/31	Tranter Left	Resoldand star 6 sts for	RW1 2G5272202
10/26/10 @ 1423	10-26-10 1545	Replace Ports		268896224
10/28/10 @ 1244	10/28/10 1400	f (E /		269199840
n/s/10 @ 1332	13/5/10 14.47	203809	Roset UFO's Trestante	1270469600
12-16-10 - 556	12-16-16 12/6	High level tener like	on level suikh	27/871800
12/23/10-09/10	12/23/10 0930	Highlerel AST	Erspand to SIARIN BECURETT	201-1277889568 202 1132338216
	·			

ATTACHMENT E

ANALYTICAL RESULTS

ACTIVE INDUSTRIAL UNIFORM SITE NYSDEC SITE No. 1-52-125

RESULTS OF SYSTEM COMBINED INFLUENT ANALYSIS - VOLATILE ORGANIC COMPOUNDS (VOCs)

SAMPLE ID	COMB INF	COMB INF	NYSDEC CLASS GA
SAMPLE TYPE	WATER	WATER	GROUNDWATER
DATE OF	10/26/2010	11/30/2010	STANDARDS AND
COLLECTED BY	D&B	D&B	GUIDANCE VALUES
UNITS	(ug/L)	(ug/L)	(ug/L)
VOCs	<u> </u>	, <u> </u>	1
Dichlorodifluoromethane	U	U	5 GV
Chloromethane	U	U	
Vinyl chloride	1.8 J	0.72 J	2 ST
Bromomethane	U	U	5 ST
Chloroethane	2.5 J	U	5 ST
Trichlorofluoromethane	U	U	5 ST
1,1-Dichloroethene	U	U	5 ST
Methylene Chloride	U	U	5 ST
trans-1,2-Dichloroethene	U	U	5 ST
1,1-Dichloroethane	U	U	5 ST
Chloroform	U	U	7 ST
1,2-Dichloroethane	U	U	0.6 ST
1,1,1-Trichloroethane	U	U	5 ST
Carbon tetrachloride	U	U	5 ST
Trichloroethene	49	42	5 ST
1,2-Dichloropropane	U	U	1 ST
Bromodichloromethane	U	U	5 ST
2-Chloroethyl vinyl ether	U	U	5 ST
cis-1,3-Dichloropropene	U	U	0.4 ST
trans-1,3-Dichloropropene	U	U	0.4 ST
1,1,2-Trichloroethane	U	U	1 ST
Dibromochloromethane	U	U	50 GV
Bromoform	U	U	50 GV
Tetrachloroethene	230	190	5 ST
Chlorobenzene	U	U	5 ST
1,1,2,2-Tetrachloroethane	U	U	5 ST
1,3-Dichlorobenzene	U	U	3 ST
1,4-Dichlorobenzene	U	U	3 ST
1,2-Dichlorobenzene	U	U	3 ST
Total VOCs	283.3	232.72	

NOTES:

Concentration exceeds NYSDEC Class GA Groundwater Standards or Guidance Values

ABBREVIATIONS:

QUALIFIERS:

ug/L = Micrograms per liter

--: Not established

ST: Standard Value

GV: Guidance Value

U: Compound analyzed for but not detected

J: Compound found at a concentration below CRDL, value estimated

B: Compound found in a blank as well as the sample

ACTIVE INDUSTRIAL UNIFORM SITE NYSDEC SITE No. 1-52-125

RESULTS OF SYSTEM COMBINED INFLUENT ANALYSIS - INORGANIC COMPOUNDS AND GENERAL CHEMISTRY

SAMPLE ID	COMB INF	COMB INF	
SAMPLE TYPE	WATER	WATER	
DATE OF COLLECTION	10/26/2010	11/30/2010	NYSDEC CLASS GA
COLLECTED BY	D&B	D&B	GROUNDWATER STANDARDS
UNITS	(ug/L)	(ug/L)	(ug/L)
INORGANIC COMPOUNDS			
Aluminum	U	11.4 J	
Antimony	U	U	3
Arsenic	U	U	25
Barium	16.2	16.3	1,000
Beryllium	U	U	
Cadmium	U	U	5
Calcium	20,200	21,200	
Chromium	U	U	
Cobalt	0.68 J	U	
Copper	26.2	3.1 J	200
Iron	181	1,360	300
Lead	U	U	25
Magnesium	3,280	3,370	
Manganese	974	986	300
Mercury	U	U	0.7
Nickel	U	U	100
Potassium	2,700	2,740	
Selenium	U	U	10
Silver	0.29 J	U	50
Sodium	22,200	23,100	20,000
Thallium	U	U	
Vanadium	U	U	
Zinc	227	U	
Iron and Manganese	1,155	2,346	500
GENERAL CHEMISTRY			
pH (S.U.)	6.31	6.11	6.5 - 8.5

NOTES:	<u></u>
	Concentration exceeds NYSDEC Class GA Groundwate
	Standards

ABBREVIATIONS:

ug/L: Micrograms per liter

--: Not established

S.U.: Standard units

QUALIFIERS:

U: Compound analyzed for but not detected.

J: Compound found at a concentration below CRDL, value estimated

ACTIVE INDUSTRIAL UNIFORM SITE NYSDEC SITE No. 1-52-125 RESULTS OF SYSTEM EFFLUENT ANALYSIS - VOLATILE ORGANIC COMPOUNDS (VOCs)

SAMPLE ID	COMB EFF	COMB EFF	
SAMPLE TYPE	WATER	WATER	NYSDEC
DATE OF	10/26/2010	11/30/2010	Site Specific
COLLECTED BY	D&B	D&B	Effluent Limitation
UNITS	(ug/L)	(ug/L)	
VOCs	` ,	, ,	(ug/L)
Dichlorodifluoromethane	U	U	NL NL
Chloromethane	U	U	NL
Vinyl Chloride	U	U	10
Bromomethane	U	U	NL
Chloroethane	U	U	NL
Trichlorofluoromethane	U	U	NL
1,1 Dichloroethene	U	U	NL
Methylene Chloride	U	U	NL
trans-1,2-Dichloroethene	U	U	10*
1,1 Dichloroethane	U	U	NL
Chloroform	U	U	NL
1,2 Dichloroethane	U	U	NL
1,1,1 Trichloroethane	U	U	5
Carbon Tetrachloride	U	U	NL
Trichloroethlyene	U	U	10
1,2 Dichloropropane	U	U	NL
Bromodichloromethane	U	U	NL
2-Chloroethyl Vinyl Ether	U	U	NL
c 1,3 Dichloropropene	U	U	NL
t 1,3 Dichloropropene	U	U	NL
1,1,2 Trichloroethane	U	U	NL
Dibromochloromethane	U	U	NL
Bromoform	U	U	NL
Tetrachloroethene	U	U	4
Chlorobenzene	U	U	NL
1,1,2,2 Tetrachloroethane	U	U	NL
1,3 Dichlorobenzene	U	U	NL
1,4 Dichlorobenzene	U	U	NL
1,2 Dichlorobenzene	U	U	NL
Total VOCs	0	0	

NOTES:

Concentration exceeds NYSDEC
Site Specific Effluent Limitation

ABBREVIATIONS

ug/L = Micrograms per liter NL - No limit specified

QUALIFIERS:

U: Compound analyzed for but not detected

J: Compound found at a concentration below CRDL, value estimated

^{* -} Effluent limitation for 1,2 Dichloroethene (Total)

^{** -} Effluent limit for xylene-o= 5 ug/l, xylene -m&p = 10 ug/l

ACTIVE INDUSTRIAL UNIFORM SITE

NYSDEC SITE No. 1-52-125 RESULTS OF ANALYSIS OF VAPOR PHASE CARBON VESSEL (VPCV) INFLUENT - VOLATILE ORGANIC COMPOUNDS (VOCs)

SAMPLE ID	VPCV-	INF	VPCV	-INF	
SAMPLE TYPE	AIR		AIF		
DATE OF COLLECTION	10/26/2		11/30/2010		NIVODEO D
BLOWER VELOCITY (FEET/MIN)	3,39		3,60		NYSDEC Permit
BLOWER FLOW RATE (FT ³ /MIN)	1,07		1,14		Equivalency Limit
, , ,	Concentration	Loading Rate	Concentration	Loading Rate	(lbs/hr)
UNITS	(ug/m³)	(lb/hr)	(ug/m³)	(lb/hr)	
VOCs					
t 1,3 Dichloropropene	U		U		
Freon 114	U		U		
Acetone	U		U		
Ethanol	34 J*	1.4E-04	U		
Ethyl Acetate	U		U		
Ethylbenzene	U		U		
Trichlorofluoromethane	U		U		
Heptane Hexachloro-,1,3-Butadiene	U		U U		
Hexane	U		U		
2-Hexanone	l ü		U		
Isopropyl Alcohol	Ü		Ü		
Methylene Chloride	Ü		Ü		
Benzene	Ü		Ü	1	
Benzyl Chloride	Ü		Ü		
Styrene	U		Ü	1	
1,1,2,2 Tetrachloroethane	U		U		
Tetrachloroethene	980 D	4.0E-03	3,400 D	1.5E-02	7.0E-03
Tetrahydrofuran	U		U		
Toluene	3.1	1.2E-05	U		
1,2,4 Trichlorobenzene	U		U		
1,1,1 Trichloroethane	U		U		1.0E-03
1,1,2 Trichloroethane	U	4.05.00	U	0.05.00	0.05.00
Trichloroethlyene	300	1.2E-03	470	2.0E-03	6.0E-03
1,2,4 Trimethylbenzene	U		U U		
1,3,5 Trimethylbenzene Vinyl Acetate	U		U		
Vinyl Chloride	7.4	3.0E-05	9.9	4.2E-05	1.4E-02
o-Xylene	7.4 U	3.0L-03	9.9 U	4.2L-03	1.0E-03
Methyl tert-butyl ether	Ü		Ü		1.02 00
1,2,2 Trifluoro-1,1,2 Tricloroethane	Ü		Ü		
m + p Xylene	U		Ü		1.0E-03
Bromodichloromethane	U		U		
1,2 Dibromoethane	U		U		
Methyl Ethyl Ketone	U		U		
4-Methyl-2-Pentanone	U		U		
Bromoform	U		U		
Bromomethane	U		U		
1,3 Butadiene	U		U	1	
4-Ethyltoluene	U		U	1	
Carbon Disulfide	U		U		
Carbon Tetrachloride	U		U	1	
Chlorobenzene	U		U U	1	
Dibromochloromethane Chloroethane	U		U		
Chloroform	U		U	1	
Chloromethane	U		U	1	
Propene	Ü		Ü	1	
Cyclohexane	Ü		Ü	1	
1,2 Dichlorobenzene	Ü		Ü	1	
1,3 Dichlorobenzene	U		U	1	
1,4 Dichlorobenzene	U		U	1	
Dichlorodifluoromethane	U		U		
1,1 Dichloroethane	U		U	1	
1,2 Dichloroethane	U		U	1	
1,1 Dichloroethene	U		U	1	
cis-1,2-Dichloroethene	650 D		1,300 D	1	
trans-1,2-Dichloroethene	4.5	2.05.00	6.6	F 05 00	2.05.00
1,2-Dichloroethene (total)	654.5	2.6E-03	1306.6	5.6E-03	3.0E-03
1,2 Dichloropropane	U		U	1	
c 1,3 Dichloropropene Total BTEX	U		U U	1	
Total VOCs	1,979	8.0E-03	5,187	2.2E-02	
10101 1003	1,313	0.0E-03	3,107	∠.∠E-U∠	

ABBREVIATIONS: ug/m³ - Micrograms per cubic meter

- QUALIFIERS:
 U: Compound analyzed for but not detected.
 J: Analyte detected at or below quantitation limits
- D: Result taken from reanalysis at a secondary dilution
- J*: Analyte qualified as estimated based on laboratory calibration

ACTIVE INDUSTRIAL UNIFORM SITE

NYSDEC SITE No. 1-52-125 RESULTS OF ANALYSIS OF VAPOR PHASE CARBON VESSEL (VPCV) MIDFLUENT - VOLATILE ORGANIC COMPOUNDS (VOCs)

SAMPLE ID	VPCV-I	MID	VPCV-	MID	
SAMPLE TYPE	AIR		AIR		1
DATE OF COLLECTION	10/26/2	010	11/30/2	2010	
BLOWER VELOCITY (FEET/MIN)	3,39		3,60		NYSDEC Permit Equivalency
BLOWER FLOW RATE (FT ³ /MIN)	1,07		1,14		Limit
,	Concentration	Emission Rate	Concentration	Emission Rate	(lbs/hr)
UNITS	(ug/m ³)	(lb/hr)	(ug/m³)	(lb/hr)	
VOCs	, ,	` ′		` ′	
t 1,3 Dichloropropene	U		U		
Freon 114	U		U		
Acetone	U		U		
Ethanol	57 J*	2.30E-04	U		
Ethyl Acetate	U		U		
Ethylbenzene	U		U		
Trichlorofluoromethane	U		U		
Heptane	U		U		
Hexachloro-,1,3-Butadiene	U		U		
Hexane	U		U		
2-Hexanone	U		U		
Isopropyl Alcohol	U		U		
Methylene Chloride	U		U		
Benzene	U		U		
Benzyl Chloride	Ü		Ü		
Styrene	U		U		
1,1,2,2 Tetrachloroethane	U		U		
Tetrachloroethene	320	1.29E-03	1,500	6.42E-03	7.0E-03
Tetrahydrofuran	33	1.33E-04	U		
Toluene	U		Ü		
1,2,4 Trichlorobenzene	Ü		U		
1,1,1 Trichloroethane	14	5.64E-05	Ü		1.0E-03
1,1,2 Trichloroethane	U		Ü		
Trichloroethlyene	1,700	6.85E-03	2,400 D	1.03E-02	6.0E-03
1,2,4 Trimethylbenzene	U		Ú		
1,3,5 Trimethylbenzene	Ü		Ü		
Vinyl Acetate	Ü		Ü		
Vinyl Chloride	16	6.45E-05	12	5.1E-05	1.4E-02
o-Xylene	U	002 00	 U	0.12 00	1.0E-03
Methyl tert-butyl ether	31 U	1.25E-04	33	1.4E-04	
1,2,2 Trifluoro-1,1,2 Tricloroethane	U	1.202 01	U		
m + p Xylene	Ü		Ü		1.0E-03
Bromodichloromethane	Ü		Ü		1.02 00
1,2 Dibromoethane	Ü		Ü		
Methyl Ethyl Ketone	Ü		Ü		
4-Methyl-2-Pentanone	Ü		Ü		
Bromoform	Ü		Ü		
Bromomethane	Ü		Ü		
1,3 Butadiene	Ü		Ü		
4-Ethyltoluene	Ü		Ü		
Carbon Disulfide	Ü		Ü		
Carbon Tetrachloride	Ü		Ü		
Chlorobenzene	Ü		Ü		
Dibromochloromethane	Ü		Ü		
Chloroethane	Ü		Ü		
Chloroform	Ü		Ü		
Chloromethane	Ü		Ü		
Propene	Ü		Ü		
Cyclohexane	Ü		Ü		
1,2 Dichlorobenzene	Ü		Ü		
1,3 Dichlorobenzene	U		U		
1,4 Dichlorobenzene	U		U		
Dichlorodifluoromethane	U		U		
1,1 Dichloroethane	U		U		
1,2 Dichloroethane	Ü		Ü		
1,1 Dichloroethene	Ü		Ü		
cis-1,2-Dichloroethene	2,500 D		1,400		
trans-1,2-Dichloroethene	12		8.5		
1,2-Dichloroethene (total)	2,512	1.0E-02	1,409	6.0E-03	3.0E-03
1,2 Dichloropropane	U		U		Ī
c 1,3 Dichloropropene	U		U		
Total BTEX	U		U	1	
Total VOCs	4,683	1.9E-02	5,354	2.3E-02	

ABBREVIATIONS:

ug/m³ - Micrograms per cubic meter

- U: Compound analyzed for but not detected.
- J: Analyte detected at or below quantitation limits
- D: Result taken from reanalysis at a secondary dilution
- $J^{\star}\!\!:$ Analyte qualified as estimated based on laboratory calibration

ACTIVE INDUSTRIAL UNIFORM SITE NYSDEC SITE No. 1-52-125 RESULTS OF ANALYSIS OF VAPOR PHASE CARBON VESSEL (VPCV) EFFLUENT - VOLATILE ORGANIC COMPOUNDS (VOCs)

SAMPLE ID	VPCV-	EFF	VPCV-	EFF	
SAMPLE TYPE	AIR		AIR		
DATE OF COLLECTION	10/26/2	010	11/30/2010		NIVODEO B
BLOWER VELOCITY (FEET/MIN)	3,39	0	3,600		NYSDEC Permit Equivalency Limit
BLOWER FLOW RATE (FT ³ /MIN)	1,07	5	1,14	2	(lbs/hr)
	Concentration	Emission Rate	Concentration	Emission Rate	(103/111)
UNITS	(ug/m ³)	(lb/hr)	(ug/m³)	(lb/hr)	
VOCs					
t 1,3 Dichloropropene	U		U		
Freon 114	U		U		
Acetone	U	0.45.04	U		
Ethanol	53 J*	2.1E-04	U		
Ethyl Acetate	U		U U		
Ethylbenzene Trichlorofluoromethane	U		U		
Heptane	U		U		
Hexachloro-,1,3-Butadiene	l Ü		U		
Hexane	Ü		Ü		
2-Hexanone	Ü		Ü		
Isopropyl Alcohol	26	1.0E-04	Ü		
Methylene Chloride	U		U		
Benzene	U		U		
Benzyl Chloride	U		U		
Styrene	U		U		
1,1,2,2 Tetrachloroethane	U		U		
Tetrachloroethene	17	6.9E-05	230	9.8E-04	7.0E-03
Tetrahydrofuran	12	4.8E-05	U		
Toluene	U		U		
1,2,4 Trichlorobenzene	U	7.05.05	U		4.05.00
1,1,1 Trichloroethane	18 U	7.3E-05	U U		1.0E-03
1,1,2 Trichloroethane Trichloroethlyene	700	2.8E-03	2,800	1.2E-02	6.0E-03
1,2,4 Trimethylbenzene	U	2.01-03	2,000 U	1.ZL-0Z	0.01-03
1,3,5 Trimethylbenzene	U		U		
Vinyl Acetate	Ü		U		
Vinyl Chloride	11	4.4E-05	14	6.0E-05	1.4E-02
o-Xylene	U	2 00	U.	0.02 00	1.0E-03
Methyl tert-butyl ether	25	1.0E-04	72	3.1E-04	
1,2,2 Trifluoro-1,1,2 Tricloroethane	U		U		
m + p Xylene	U		U		1.0E-03
Bromodichloromethane	U		U		
1,2 Dibromoethane	U		U		
Methyl Ethyl Ketone	U		U		
4-Methyl-2-Pentanone	U		U		
Bromoform	U		U		
Bromomethane	U		U		
1,3 Butadiene	U		U		
4-Ethyltoluene	U		U		
Carbon Disulfide Carbon Tetrachloride	U		U U		
Chlorobenzene	U		U		
Dibromochloromethane	U		U		
Chloroethane	U		U		
Chloroform	Ü		Ü		
Chloromethane	Ü		Ü		
Propene	Ü		Ü		
Cyclohexane	Ü		Ü		
1,2 Dichlorobenzene	U		U		
1,3 Dichlorobenzene	U		U		
1,4 Dichlorobenzene	U		U		
Dichlorodifluoromethane	U		U		
1,1 Dichloroethane	3.6	1.5E-05	U		
1,2 Dichloroethane	U		U		
1,1 Dichloroethene	1 400 D		U 1 000		
cis-1,2-Dichloroethene trans-1,2-Dichloroethene	1,400 D 11		1,900 U		
1,2-Dichloroethene (total)	1,411	5.7E-03	1,900	8.1E-03	3.0E-03
1,2 Dichloropropane	U	52 00	1,500 U	52 00	3.32 00
c 1,3 Dichloropropene	Ü		Ü		
Total BTEX	Ü		Ü		
Total VOCs	2,277	9.2E-03	5,016	2.1E-02	

ABBREVIATIONS: ug/m³ - Micrograms per cubic meter

- QUALIFIERS:
 U: Compound analyzed for but not detected.
 J: Analyte detected at or below quantitation limits
 D: Result taken from reanalysis at a secondary dilution
- J*: Analyte qualified as estimated based on laboratory calibration

ATTACHMENT F

DATA VALIDATION CHECKLISTS

Project Name:	Active Industrial aka Lindenhurs	t .		•
Project Number:	2578-04		-	
Sample Date(s):	October 26, 2010			
Matrix/Number of Samples:	Water/ 2(Combined and Effluent Trip Blank/ 0)		
Analyzing Laboratory:	TestAmerica Laboratories, Shelto	on, CT		
Analyses:	Volatile Organic Compounds (V Metals: by USEPA SW 846 meth method 7470A		JSEPA SW 84	16
Laboratory Report No:	220-13840	Date:11/19/2010		

ORGANIC ANALYSES

VOCS

	Reported		Performance Acceptable		Not
•	No	Yes	No	Yes	Required
1. Holding times		X		X	
2. Blanks					
A. Method blanks		X		X	
B. Trip blanks					X
C. Field blanks					X
3. Laboratory Control Sample (LCS) %R					X
4. Surrogate spike recoveries		X		X	
5. Field duplicates RPD					X

VOCs - volatile organic compounds %R - percent recovery %D - percent difference

%RSD - percent relative standard deviation

RRF - relative response factor RPD - relative percent difference

Comments:

Performance was acceptable.

INORGANIC ANALYSES

METALS

	Repo	orted	l .	mance ptable	Not
	No	Yes	No	Yes	Required
1. Holding times		X		X	
2. Blanks					
A. Method blanks		X		X	
B. Field blanks					X.
3 Laboratory control sample %R					X
4. Matrix Spike sample %R					X
5. Duplicate %RPD					X
6. Field duplicates RPD					X

%R - percent recovery

%D - percent difference

RPD - relative percent difference

<u>Comments</u>: Performance was acceptable.

		<u></u>	
L	ALIDATION PERFORMED BY & DATE:	Donna M. Brown 3/2/2011	
- 1 '	VALIDATION PERFORMED BY SIGNATURE:	10 - R-	-

Project Name:	Active Industrial			
Project Number:	2578-04			
Sample Date(s):	October 26, 2010			
Matrix/Number of Samples:	<u>Air/ 3</u>			
Analyzing Laboratory:	TestAmerica Laboratories, Knoxville, TN			
Analyses:	Volatile Organic Compounds (VOCs): TO15			
Laboratory Report No:	H0K020477	Date:11/09/2010		

ORGANIC ANALYSES VOCS

	Rep	orted		rmance eptable	Not
	No	Yes	No	Yes	Required
1. Holding times	-	X		X	
2. Method blanks		X		X	
3. Matrix spike (MS) %R					X
4. Matrix spike duplicate (MSD) %R					X
5. MS/MSD precision (RPD)					X
6. Laboratory Control Sample (LCS) %R		X		X	
7. Surrogate spike recoveries		X		X	
8. Field duplicates RPD					X

VOCs - volatile organic compounds %R - percent recovery

%D - percent difference

%RSD - percent relative standard deviation

RRF - relative response factor

RPD - relative percent difference

Comments:

Performance was acceptable with the following exception:

The laboratory used a one-point calibration for ethanol and ethanol was qualified as estimated (J/UJ) in all samples.

Sample results associated with compound that exhibited a concentration greater than the linear range of the instrument calibration are summarized in the following table.

Sample ID	Compound	Original Analysis (ppb(v/v)-ug/m3)	Diluted Analysis (ppb(v/v)-ug/m3)	Reported Analysis (ppb(v/v)-ug/m3)
INFLUENT	Tetrachloroethene	170-1200 E	140-980 D	140-980 D
INFLUENT	Cis-1,2-dichloroethene	180-700 E	160-650 D	160-650 D
EFFLUENT	Cis-1,2-dichloroethene	420-1700 E	350-1400 D	350-1400 D
MID-FLUENT	Cis-1,2-dichloroethene	- 410-1600 E	620-2500 D	620-2500 D

VALIDATION PERFORMED BY & DATE:	Donna M. Brown 3/2/2011
VALIDATION PERFORMED BY SIGNATURE:	D-2

Project Name:	Active Industrial aka Lindenhurst	
Project Number:	2578-04	
Sample Date(s):	November 30, 2010	
Matrix/Number of Samples:	Water/ 2(Combined and Effluent) Trip Blank/ 0	
Analyzing Laboratory:	TestAmerica Laboratories, Shelton, CT	
Analyses:	Volatile Organic Compounds (VOCs): UMetals: by USEPA SW 846 method 601 method 7470A	
Laboratory Report No:	220-14179	Date:12/17/2010

ORGANIC ANALYSES

VOCS

	Reported		Performance Acceptable		Not
	No	Yes	No	Yes	Required
1. Holding times		X		X	
2. Blanks					
A. Method blanks		X		X	
B. Trip blanks					X
C. Field blanks					X
3. Laboratory Control Sample (LCS) %R					X
4. Surrogate spike recoveries		X		X	
5. Field duplicates RPD					X

VOCs - volatile organic compounds %R - percent recovery

%D - percent difference %RSD - percent relative standard deviation

RRF - relative response factor RPD - relative percent difference

Comments:

Performance was acceptable.

INORGANIC ANALYSES

METALS

			Perfor	mance	
	Repo	orted	Acce	otable	Not
,	No	Yes	No	Yes	Required
1. Holding times		X		X	
2. Blanks					
A. Method blanks		X		X	
B. Field blanks					X
3 Laboratory control sample %R					X
4. Matrix Spike sample %R					X
5. Duplicate %RPD					X
6. Field duplicates RPD					X

%R - percent recovery

%D - percent difference

RPD - relative percent difference

Comments:

Performance was acceptable.

VALIDATION PERFORMED BY & DATE:	Donna M. Brown 3/2/2011
VALIDATION PERFORMED BY SIGNATURE:	10mR

Project Name:	Active Industrial			
Project Number:	2578-04			
Sample Date(s):	November 30, 2010			
Matrix/Number of Samples:	Air/3			
Analyzing Laboratory:	TestAmerica Laboratories, Knoxville, TN			
Analyses:	Volatile Organic Compounds (VOCs): TO15			
Laboratory Report No:	H0L030559	Date:12/14/2010		

ORGANIC ANALYSES VOCS

	Reported		Performance Acceptable		Not
	No	Yes	No	Yes	Required
1. Holding times		X		X	1 7 1
2. Method blanks		X		X	
3. Matrix spike (MS) %R		1111111			X
4. Matrix spike duplicate (MSD) %R					X
5. MS/MSD precision (RPD)					X
6. Laboratory Control Sample (LCS) %R		. X		X	
7. Surrogate spike recoveries		X		X	
8. Field duplicates RPD					X

VOCs - volatile organic compounds

RRF - relative response factor RPD - relative percent difference

%R - percent recovery

%D - percent difference %RSD - percent relative standard deviation

Comments:

Performance was acceptable with the following exception:

Sample results associated with compound that exhibited a concentration greater than the linear range of the instrument calibration are summarized in the following table.

Sample ID	Compound	Original Analysis (ppb(v/v)-ug/m3)	Diluted Analysis (ppb(v/v)-ug/m3)	Reported Analysis (ppb(v/v)-ug/m3)
INFLUENT	Tetrachloroethene	350-2400 E	500-3400 D	500-3400 D
INFLORM	Cis-1,2-dichloroethene	260-1000 E	320-1300 D	320-1300 D
MID FLUENT	Trichloroethene	490-2600 E	440-2400 D	440-2400 D

VALIDATION PERFORMED BY & DATE:	Donna M. Brown 3/2/2011
VALIDATION PERFORMED BY SIGNATURE:	ea-Ri