

NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION

Division of Environmental Remediation, Remedial Bureau C

625 Broadway, 12th Floor, Albany, NY 12233-7014

P: (518) 402-9662 | F: (518) 402-9679

www.dec.ny.gov

March 3, 2022

Richard Rienzo
Consolidated Edison Company of New York, Inc.
31-01 20th Avenue
Long Island City, NY 11105

Re: Remedial Design Work Plan
Former West 45th Street Gas Works
Site #231109

Dear Richard Rienzo:

The New York State Department of Environmental Conservation (Department) and the New York State Department of Health (NYSDOH) have reviewed the Remedial Design Work Plan (RDWP) for the Former West 45th Street Gas Works, Operable Unit 2 (the site) located at the intersection of West 45th Street and 12th Avenue in New York, New York, submitted by Parsons on behalf of Consolidated Edison Co. of New York, Inc., dated January 2022. The RDWP is hereby approved pending submission of a signed and stamped final version. Please provide a schedule for field work implementation including a 10-business day notification to the Department.

If you have any questions, please feel free to contact me at 518-402-2029 or email: greta.white@dec.ny.gov.

Sincerely,



Greta White, P.G.
Project Manager
Remedial Action Bureau C
Division of Environmental Remediation

EC: K. Kaiser, ConEd
D. MacNeal and J. Brown, NYSDEC
A. Perretta & S. McLaughlin, NYSDOH



Department of
Environmental
Conservation

REMEDIAL DESIGN WORK PLAN
FOR THE FORMER WEST 45TH STREET GAS
WORKS SITE – OPERABLE UNIT 2

Site #231109



CONSOLIDATED EDISON CO. OF NEW YORK, INC.
31-01 20th Avenue
Long Island City, NY 11105

Prepared by:




301 Plainfield Road, Suite 350
Syracuse, NY 13212

JANUARY 2022

Certification

"I certify that this Report was prepared in accordance with all applicable statutes and regulations and in substantial conformance with the DER Technical Guidance for Site Investigation and Remediation (DER10.)"



Engineer's Seal

PARSONS

3/7/22

Date

TABLE OF CONTENTS

	<u>Page</u>
1.0 INTRODUCTION	1-1
1.1 RDWP Organization.....	1-2
1.2 Site Background.....	1-2
1.2.1 Site History and Operation	1-2
1.3 Site topography, Soils, Geology and Hydrogeology	1-3
1.3.1 Topography.....	1-3
1.3.2 Soils	1-3
1.3.3 Geology	1-3
1.3.4 Hydrogeology.....	1-4
1.3.5 Groundwater Usage	1-4
1.3.6 Nature and Extent of Remaining Impacts	1-4
1.3.7 Exposure Assessment.....	1-5
1.4 Standards, Criteria, and Guidance	1-6
1.4.1 Remedial Goal.....	1-6
1.4.2 Remedial Action Objectives.....	1-6
1.5 Description of Selected Remedy.....	1-7
2.0 SUPPLEMENTAL PRE-DESIGN INVESTIGATION	2-1
2.1 Supplemental Soil Boring Field Program.....	2-1
2.1.1 NYSDOT Permitting and Site Access.....	2-1
2.1.2 Utility Clearance	2-1
2.1.3 Soil Boring Installation.....	2-2
2.1.4 Site Survey.....	2-2
2.1.5 Management of Investigation Derived Waste	2-2
2.2 Bench Scale Treatability Study.....	2-3
2.3 Subsurface Hydraulics Evaluation and Modeling	2-4
2.4 3D Rendering of Site Lithologies	2-4
2.5 Structural Evalauton of Sensitive Structures	2-5
3.0 REMEDIAL DESIGN	3-1
3.1 Remedial Design Task 1 – Removal of Overburden Soil	3-1
3.2 Remedial Design Task 2 – ISS Mix Design.....	3-1
3.3 Remedial Design Task 3 – ISS Methodology.....	3-1
3.4 Remedial design Task 4 – Site Restoration and Cover	3-2
4.0 PERMITS, ACCESS AGREEMENT, AND APPROVALS	4-1
4.1 Supplemental PDI Permits and Site Access Agreements.....	4-1
4.2 Remedial Action Permits and Approvals	4-1
5.0 REMEDIAL DESIGN DOCUMENTS AND SCHEDULE	5-1

REMEDIAL DESIGN WORK PLAN
FORMER WEST 45TH STREET GAS
WORKS SITE
OPERABLE UNIT 2

5.1	75% Pre-Final Remedial Design.....	5-1
5.2	Final (100%) Remedial Design.....	5-2
5.3	Remedial Design Schedule	5-2
6.0	POST-CONSTRUCTION ACTIVITIES	6-1
6.1	Final Engineering Report	6-1
6.2	Site Management Plan	6-2
	6.2.1 Institutional and Engineering Controls	6-2
	6.2.2 Monitoring Plan	6-2
7.0	REFERENCES.....	7-1

TABLES IN TEXT

Table 1.1 – RDWP Organization

Table 1.2 – Remedial Action Objectives

Table 5.1 – Preliminary Project Schedule

LIST OF FIGURES

Figure 1 – Site Location Map

Figure 2 – Operable Unit Map and Former MGP Structures

Figure 3 – Bedrock Elevations

Figure 4 – OU-2 Pre-Design Investigation Cross Section A-A'

Figure 5 – OU-2 Pre-Design Investigation Cross Section B-B'

Figure 6 – OU-2 Pre-Design Investigation Cross Section C-C'

Figure 7 – OU-2 Pre-Design Investigation Cross Section D-D'

Figure 8 – OU-2 Pre-Design Investigation 2012 Groundwater Elevations

Figure 9 – Alternative 2A – Estimated Remediation Area ISS to Bedrock

Figure 10 – West 45th St. ISS 3D Rendering

Figure 11 – Jet Grout Columns Area 1 & Area 3

Figure 12 – Jet Grout Columns Area 2

LIST OF APPENDICES

APPENDIX A – NEW YORK CITY PLANING COMMISSION ZONING MAP 8c

LIST OF ACRONYMS

3D	Three dimensional
AAR	Alternatives Analysis Report
bgs	Below ground surface
BTEX	Benzene, toluene, ethylbenzene, xylene
CAMP	Community Air Monitoring Plan
COC	Contaminate of concern
Con Edison	Consolidated Edison Company of New York, Inc.
CSCO	Commercial Use Soil Cleanup Objective
DER-10	NYSDEC Technical Guidance for Site Investigation and Remediation
DNAPL	Dense nonaqueous phase liquid
DOT	Department of Transportation
FER	Final Engineering Report
FSP	Field Sampling Plan
GSI	Geo-Solutions, Inc.
GWQS	Groundwater quality standards
HASP	Health and Safety Plan
ISS	<i>In situ</i> stabilization and solidification
LEAF	Leaching Environmental Assessment
MGP	Manufactured gas plant
MSL	Mean sea level
MW	Monitoring well
NAPL	Nonaqueous phase liquid
NYCRR	New York Codes Rules and Regulations
NYSDEC	New York State Department of Environmental Conservation
NYSDOH	New York State Department of Health
NYSDOT	New York State Department of Transportation
OU	Operable Unit
PAH	Polycyclic aromatic hydrocarbon
PCE	Tetrachloroethylene
PDI	Predesign investigation
PID	Photoionization detector
ppm	Parts per million
PRR	Periodic Review Report
QAPP	Quality Assurance Project Plan
RAO	Remedial action objective
RCRA	Resource Conservation and Recovery Act

LIST OF ACRONYMS - CONTINUED

RDWP	Remedial Design Work Plan
SC	Site characterization
SCG	Standards, Criteria, and Guidance Values
SCO	Soil Cleanup Objectives
Site	OU-2 of the Former West 45th Street Gas Works in New York City, New York
TCLP	Toxicity Characteristics Leaching Procedure
TDS	Total dissolved solids
TMV	Toxicity, mobility, or volume
TOGS	Technical and Operational Guidance Series
TP	Test pit
UCS	Unconfined compressive strength
USCO	Unrestricted Use Soil Cleanup Objective
USEPA	U.S. Environmental Protection Agency
VOC	Volatile organic compound

1.0 INTRODUCTION

On behalf of Consolidated Edison Company of New York, Inc. (Con Edison), this Remedial Design Work Plan (RDWP) for Operable Unit 2 (OU-2) of the Former West 45th Street Gas Works Site has been prepared for the New York State Department of Environmental Conservation (NYSDEC). The Former West 45th Street Gas Works is located in the borough of Manhattan in New York City, New York, in an area loosely bounded by 46th Street to the north, 11th Avenue to the east, 44th Street to the south, and 12th Street (aka Route 9A and the Henry Hudson Highway) to the west, as shown in [Figure 1](#). For characterization purposes, the Former West 45th Street Gas Works was divided into two distinct areas designated as Operable Unit 1 (OU-1) and OU-2, as shown in [Figure 2](#). This RDWP focuses only on the OU-2 portion of the Former West 45th Street Gas Works Site, which is herein referred to as the Site. The Site is located mid-block between 11th Avenue and 12th Avenue and is bounded by 46th Street to the north and 45th Street to the south.

The purpose of this RDWP is to define the tasks to take place as components of the remedial design process; including identification of pre-design testing; modeling; and other tasks necessary for the preparation and development of final plans and specifications necessary to implement the remedial alternative set forth in the Decision Document.

The final Alternatives Analysis Report (AAR) for the Site was submitted to the NYSDEC in November 2020 (Parsons). The NYSDEC-approved AAR included an evaluation of three remedial alternatives to address non-aqueous phase liquid (NAPL) or manufactured gas plant (MGP)-related impacts at the Site, comparing them to the nine evaluation criteria outlined in NYSDEC Technical Guidance for Site Investigation and Remediation (DER-10) and in accordance with New York Codes Rules and Regulations (NYCRR) 6 NYCRR 375-1.8(f). The three remedial alternatives evaluated in the final AAR included the following:

- Alternatives 1 and 1A – Excavation and off-site disposal and treatment of soils that exceed Commercial Use Soil Cleanup Objectives (CSCOs) and/or NAPL-impacted soils to a depth of 15 feet and in situ stabilization and solidification (ISS) for deeper NAPL-impacted soils,
- Alternatives 2 and 2A – ISS of soils that exceed CSCOs and/or NAPL-impacted soils to 15 feet and ISS of deeper NAPL-impacted soils, and
- Alternative 3 – Implementation of a Site Management Plan (SMP).

The NYSDEC selected Remedial Alternative 2A – ISS of soils exceeding CSCOs and/or NAPL-impacted soils to a depth of greater than 30 feet below ground surface (bgs). This remedial alternative consists of the following major components:

- Excavation and disposal of overburden Site soils to a depth of up to 5-feet bgs,
- ISS of soils that exceed CSCOs and/or NAPL-impacted soils to depths greater than 30 feet bgs, and
- Institutional and engineering controls for remaining Site contamination.

This RDWP has been prepared to outline the scope of pre-design tasks required to develop the remedial design for the Site.

1.1 RDWP ORGANIZATION

The RDWP is organized as follows:

Table 1.1 RDWP Organization

Section	Description
Section 1 - Introduction	Presents the organization of the RDWP, pertinent Site background information, a summary of potentially applicable standards, criteria, and guidance (SCGs) criteria, a site characterization summary, RAOs, and a description of the NYSDEC-selected remedy.
Section 2 – Pre-Design Investigation	Presents the scope and rationale for supplemental pre-design investigation (PDI) activities to be completed in support of the remedial design.
Section 3 – Remedial Design	Describes the remedial design activities to be completed in support of implementing the NYSDEC selected remedy.
Section 4 – Permits, Access Agreements and Approvals	Identifies the permits, access agreements, and approvals necessary to conduct the supplemental pre-design investigation activities and to implement the NYSDEC selected remedy.
Section 5 – Remedial Design Documents and Schedule	Identifies the remedial design documents to be prepared in support of the remedial action and presents the anticipated project schedule for implementing the supplemental pre-design investigation activities and preparing the remedial design.
Section 6 – Post-Remedial Construction Activities	Describes the documents to be prepared following the remedial construction.
Section 7 - References	Presents a list of documents used to support the preparation of this RDWP.

The current Field Sampling Plan (FSP), Quality Assurance Project Plan (QAPP) and Health and Safety Plan (HASP) with a Community Air Monitoring Plan (CAMP), will be updated before field activities begin.

1.2 SITE BACKGROUND

1.2.1 Site History and Operation

The Site was part of the former West 45th Street Gas Works (MGP) which was present on portions of the city blocks from 44th to 46th Street, between 11th Avenue and the Hudson River. Former MGP structures located on OU-2 included two gasholders and associated structures and a purifying house.

The plant operated from 1877 to the mid-1890s using the coal gas process prior to switching to a carbureted gas process. Although most of the buildings and structures associated with the MGP facility were removed in 1913, the large tar-sealed gasholder located at OU-2 was used until 1965. The height of the large gasholder appears to have increased from 90 feet in 1911 to 276 feet in 1930, expanding the holder's capacity from 2,000,000 cubic feet to 7,000,000 cubic feet before being decommissioned and demolished in the mid-1960s. The subsurface remnants of the gasholders are still believed to be present on the Site. Following demolition of the aboveground structures, Con Edison used the Site for heavy equipment storage and as a parking lot. In 1995, Con Edison constructed a natural gas refueling station on the northeast corner of OU-2 which has since been removed. In 2000, the New York State Department of Transportation (NYSDOT) acquired the Site from Con Edison. The existing zone for the Site based on the New York City Planning Commission Zoning Map 8c ([Appendix A](#)) is a manufacturing district.

The current Site is covered with concrete and asphalt pavement, having been developed as a parking lot with a pedestrian bridge over 12th Avenue (State Route 9A) leading to the adjacent Intrepid Sea, Air and Space Museum.

1.3 SITE TOPOGRAPHY, SOILS, GEOLOGY AND HYDROGEOLOGY

1.3.1 Topography

Surface topography ranges from approximately 10 to 20 feet above mean sea level (MSL) at the Site and tends to decrease slightly downward from north to south and from east to west.

1.3.2 Soils

Subsurface soils observed during Site Characterization (SC) and PDI field activities consist of fill material, to include silts, sand, gravels, large cobbles, and other debris (e.g., brick, ash, etc.). Subsurface structures are present at the Site, and include gas holder walls and foundations encountered during PDI field activities.

1.3.3 Geology

The bedrock underlying the Site is the Manhattan Formation, composed of gray to black mica schist that has been intensely folded and deformed by two major geologic episodes of mountain building during the Paleozoic Era, more than 200 million years ago. The depth of the bedrock surface in the mid to lower west Manhattan area varies from more than 150 feet bgs in the Chelsea section to near the surface in the Clinton area (AKRF 1994).

Soil borings were advanced during SC and PDI field encountered gneissic schist bedrock at significantly varying depths. [Figure 3](#) details bedrock elevations based on soil boring and test pit locations. Bedrock highs above 15 feet bgs. were observed in the northwestern, northeastern, and southwestern corners of the Site. A bedrock high is observed between 12.5 and 16 feet bgs in the center of the Site, directly below the interior portion of the former large gas holder. The bottom of the large gasholder appears to be a combination of concrete and bedrock. Bedrock depths encountered within the large gasholder appear to be deeper along the perimeter of the holder (between 35 and 45 feet bgs), forming a bedrock trough in a ring shape around the entire bedrock high. Cross sections that transverse the Site from east to west and from north to south are shown on [Figures 4](#) through [7](#).

1.3.4 Hydrogeology

Groundwater levels were collected at the Site in 2003, 2006, 2007, and 2012 via gauging events and tidal studies. Data from the 2003, 2006, and 2007 events were similar and indicate groundwater flow beneath the Site is to the west toward the Hudson River. Overall, groundwater maintains a general flow toward the west. A mounding effect observed within the footprint of the large gasholder increased between 2003 and 2012, and artesian conditions were encountered during PDI field activities in select wells in 2012. [Figure 8](#) is a groundwater elevation contour map based on the 2012 gauging event. A tidal study conducted during SC field activities in March 2006 determined Site monitoring wells are not subject to tidal influence.

1.3.5 Groundwater Usage

Groundwater at the Site is not used for potable purposes (nor is groundwater anywhere in New York City used for potable purposes).

1.3.6 Nature and Extent of Remaining Impacts

Manufactured gas-production byproducts, typically dense non-aqueous phase liquid (DNAPL) (i.e., coal tar), often account for the majority of the environmental impacts at former MGP sites. Principal components of coal tar are benzene, toluene, ethylbenzene, and xylene (BTEX) compounds, which are volatile organic compounds (VOCs), and polycyclic aromatic hydrocarbons (PAHs), which are semivolatile organic compounds (SVOCs). Because coal tar typically contains elevated levels of these compounds, soil samples and groundwater monitoring wells that contain visual evidence of coal tar are typically assumed to contain BTEX and PAHs at concentrations greater than applicable SCGs.

1.3.6.1 *Surface Soil*

Surface soils were characterized during SC and PDI field activities via soil boring advancement and test pit excavation. Soil samples collected during SC field activities were submitted for laboratory analysis of Target Compound List (TCL) VOCs, TCL SVOCs, Target Analyte List (TAL) metals, cyanide and Toxicity Characteristic Leaching Procedure (TCLP) lead. Soil samples collected during PDI field activities were submitted for laboratory analysis of TCL VOCs, TCL SVOCs, and cyanide. Soil sample results were compared to 6 NYCRR 375 Unrestricted Use Soil Cleanup Objective (USCO) and CSCOs.

Impacts to soil in exceedance of applicable criteria for BTEX compounds were detected at depths ranging from 7 to 35 feet bgs. Impacts to soil in exceedance of applicable criteria for PAHs were detected at depths ranging from 7 to 36 feet bgs.

Impacts to soil were generally found in exceedance of applicable criteria in locations where NAPL was observed in the subsurface, primarily along the perimeters of the former gasholders and in the vicinity of the former tar tank/skimmer pump structures, as described in further sections.

During PDI activities, soil samples were collected for waste characterization analysis to evaluate potential disposal options. Of all collected samples, one sample exhibited a TCLP benzene concentration exceeding the U.S. Environmental Protection Agency (USEPA) regulatory limit of 0.5 ppm for a hazardous waste.

1.3.6.2 *NAPL*

During SC and PDI activities, soil samples were visually characterized, and the presence of potential impacts (NAPL, sheen, odor, staining) was noted. NAPL was detected at depths ranging from 1 to 41

feet bgs, generally along the perimeter of the gasholders in the vicinity of the former tar tanks/skimmer pumps. NAPL detected within the former gasholders was limited to the outside edge of the structures. NAPL was not observed at locations near the center of the large gasholder. NAPL was detected during SC and PDI activities at or near the bedrock surface in the southern portion of the Site. Accumulations of DNAPL have been detected in groundwater monitoring wells located near the southwestern corner of the Site during groundwater gauging activities.

Two representative samples of NAPL were collected from SC soil boring locations and submitted to an analytical laboratory for forensic hydrocarbon fingerprint analysis. In general, the analytical results of fingerprint analysis indicate that the samples contained probable residue from a former MGP using the carbureted water gas process.

1.3.6.3 *Groundwater*

Three groundwater sampling events have been conducted at the Site. Groundwater samples collected during each event were submitted for laboratory analysis of TCL VOCs, TCL SVOCs, TAL metals, and cyanide.

During each groundwater sampling event, VOCs (primarily BTEX compounds) and PAHs were detected in select groundwater monitoring wells at concentrations exceeding their respective groundwater quality standards (GWQS). Concentrations of VOCs and PAHs in exceedance of applicable criteria were generally detected in the vicinity of the large gasholder. Additionally, minimum concentrations have consistently been detected in the most downgradient well. Metals have been detected in Site groundwater however are not attributed to MGP-related impacts.

1.3.6.4 *Soil Vapor*

During SC activities, soil gas samples were collected from three locations along the northern and eastern boundaries of the Site. Two soil gas samples (at 1 foot and 4 feet bgs) were collected from each location. All soil gas samples were submitted for laboratory analysis of VOCs using modified USEPA Method TO-15. Various VOCs, including BTEX, tetrachloroethylene (PCE) and trichloroethylene (TCE) were detected at concentrations greater than New York State Department of Health (NYSDOH) guidance.

1.3.7 Exposure Assessment

A qualitative exposure assessment was performed for the Site in accordance with Appendix 3B of NYSDEC DER 10 and was included in the AAR. The exposure assessment was based on the results of the investigation activities completed at the Site.

The Site is in a highly-urbanized area, which is zoned for manufacturing uses. The Site is currently developed as a parking lot that includes a pedestrian bridge over 12th Avenue (Route 9A/Henry Hudson Parkway) to the Intrepid Sea, Air and Space Museum. Currently, the Site is covered with concrete and asphalt pavement, and there is no exposed surface soil on the Site.

Under current conditions, a potential exposure to impacted materials at the Site is unlikely unless intrusive subsurface work is performed (e.g., repair of underground utilities) or if the Site were developed. The field investigations have revealed that surface soils consist of fill material and are covered with concrete or asphalt pavement. Therefore, current exposure to soils at the Site is limited. In addition, no free-phase product or DNAPL was observed in surface soil below that parking area during previous investigations. Proper engineering controls will be implemented during future intrusive remedial activities to minimize exposure at the Site.

Groundwater throughout the Site is impacted primarily with BTEX, PAHs, and NAPL. Potential exposure to impacted groundwater may occur if future construction activities are conducted at the Site. Groundwater at the Site currently is not used for potable purposes, and there reportedly are no plans for future use of potable or commercial/industrial groundwater at the Site or in the general vicinity of the Site. Site groundwater flows westward toward the Hudson River, approximately 0.1 mile from the Site boundary. Based on the analytical results for groundwater samples collected at the Site, groundwater concentrations did not exceed the Class GA standards in a monitoring well located upgradient of the Hudson River.

1.4 STANDARDS, CRITERIA, AND GUIDANCE

Title 6 of the NYCRR Part 375-6 Remedial Program Soil Cleanup Objectives (SCOs), effective December 14, 2006, was used in preparing remedial alternatives for the Site. Remedial actions conducted in New York State are required to attain chemical-, action-, and location-specific SCGs to the extent practicable as per DER-10 (NYSDEC 2010). The remedy evaluation portion of the AAR considered applicable SCGs.

1.4.1 Remedial Goal

The primary remedial goal for the areas of the Site affected by MGP-related impacts is to ensure that the MGP-related contamination does not present a threat to human health or the environment considering the manner in which the properties are used, and to develop and implement the necessary remedial actions to remediate the area to a level that is protective of human health and the environment for such uses.

1.4.2 Remedial Action Objectives

RAOs established for the Site represent media-specific goals that are protective of public health and the environment. They have been developed through consideration of the results of Site investigation activities and with reference to potential SCGs, as well as current and foreseeable future anticipated uses of the Site. The RAOs were presented in the Decision Document dated July 2021 and are outlined below.

Table 1.2 Remedial Action Objectives

Medium	Protection	RAO
Soil	Public Health	Prevent ingestion/direct contact with contaminated soil
		Prevent inhalation of or exposure from contaminants volatilizing from contaminants of concern (COCs) in soil
	Environmental	Prevent migration of COCs that would result in groundwater or surface water contamination
Groundwater	Public Health	Prevent ingestion of groundwater with contaminant levels exceeding drinking water standards
		Prevent contact with, or inhalation of volatiles, from contaminated groundwater
	Environmental	Restore the groundwater aquifer to pre-disposal/pre-release conditions, to the extent practicable

Medium	Protection	RAO
		Remove the source of groundwater or surface water contamination
Soil Vapor	Public Health	Mitigate impacts to public health resulting from existing, or the potential for, soil vapor intrusion into buildings at the Site

1.5 DESCRIPTION OF SELECTED REMEDY

The NYSDEC-selected remedy identified in the Decision Document issued by NYSDEC in July 2021 for OU2 of Site #231109 consists of the following major components:

- Excavation and disposal of overburden Site soils to a depth of up to 5 feet bgs,
- ISS of soils that exceed CSCOs and/or NAPL-impacted soils to depths greater than 30 feet bgs, and
- Institutional and engineering controls for remaining Site contamination.

Excavation of overburden soil to a depth of up to 5 feet bgs will be required prior to the implementation of the ISS field program to allow for bulking of the subsurface material. This excavated material will be transported off site for disposal. Backfill material meeting the requirements of 6 NYCRR Part 375-6.7(d) will be brought to the Site to provide protection of the ISS soils, complete backfilling, and establish the designed grades at the Site following the remediation activities.

ISS will be implemented on remaining source materials below a depth of 5 feet bgs. The treatment zone will extend from approximately 5 feet bgs to approximately 15 feet bgs in select areas of the Site, to approximately 30 feet bgs in other areas, and to bedrock in the areas depicted on [Figure 9](#).

The solidified ISS mass will be then covered with a cover system to prevent direct exposure to the solidified mass. In addition, the cover will allow for commercial use of the Site and to protect the ISS component of the Site remedy by providing sufficient thermal protection of the solidified mass from seasonal freeze/thaw cycles.

Following implementation of the Site remedy, a SMP consisting of a monitoring program, groundwater sampling, periodic inspections, and periodic review reports will be used to monitor the long-term effectiveness and performance of this remedy.

2.0 SUPPLEMENTAL PRE-DESIGN INVESTIGATION

The following supplemental PDI activities will be conducted to support the design of the NYSDEC selected remedy:

- Supplemental soil boring field program to collect soil samples to support a bench scale treatability study for the ISS component of the Site remedy,
- Bench scale treatability study,
- Subsurface hydraulics evaluation and modeling,
- A three-dimensional (3D) rendering of Site lithologies, and
- Structural evaluation of sensitive structures.

The results of the supplemental PDI activities will be included in the development of the remedial design for the Site remedy.

2.1 SUPPLEMENTAL SOIL BORING FIELD PROGRAM

Rotosonic drilling techniques will be implemented at the Site to advance soil borings to target depths and collect soil samples, NAPL, and groundwater that will be used for the bench scale treatability study. Additional borings may also be installed to provide additional information related to obstructions and the debris field present in the areas to be remediated. The supplemental soil boring field program will include the advancement of soil borings for the delineation of subsurface obstructions in locations determined via 3D model analysis, and the advancement of soil borings for the purpose of soil sampling to support the bench scale treatability study.

Perimeter air monitoring will be completed in accordance with the NYSDOH CAMP and the Site-specific HASP during intrusive activities. The following tasks will be conducted as components of this activity.

2.1.1 NYSDOT Permitting and Site Access

Drilling activities to be completed in support of the bench scale treatability study will be conducted within the NYSDOT owned parking lot at the Site. As such, a NYSDOT permit application will be completed to gain access to the parking lot and will include the following information:

- A description of field activities,
- An anticipated field schedule,
- Contact information for the Con Edison and Parsons team members,
- A drawing depicting the proposed drilling locations and work areas,
- Work Zone Traffic Control drawings, and
- A Certificate of Insurance.

The NYSDOT permit application and drawings will be signed and sealed by a Professional Engineer licensed in the State of New York. Permit close out will be done at the completion of field activities.

2.1.2 Utility Clearance

Prior to the start of intrusive work, a utility clearance program will be completed in accordance with Con Edison requirements.

2.1.3 Soil Boring Installation

Six soil borings will be advanced in locations near previous boring locations PDI-10, PDI-20, PDI-22, PDI-27, PDI-29 and MW-24 shown as SPDI-1 through SPDI-6 on [Figure 9](#). Soil boring locations were selected based on the results of previous geotechnical analysis generated during the PDI distinguishing six soil types based on the Unified Soil Classification System classification (SC-SM at PDI-10, SC at PDI-20, GP-GM at PDI-22, SM at PDI-27, GP at PDI-29, and CL at MW-24) and the presence of NAPL (PDI-20, PDI-22, PDI-27, PDI-29, and MW-24). Additional borings may also be installed to provide additional information related to obstructions and the debris field present in the areas to be remediated in locations based on analysis of the 3D model. All soil boring locations are subject to change based on accessibility, utility clearance, and conditions encountered during the Site inspection and field activities.

Soil borings will be advanced via rotosonic drilling to a depth of up to 37 feet bgs, depending on the boring location and depth to bedrock. Soil samples retrieved from each boring will be visually classified for soil type, grain size, texture, moisture content, and visible evidence of staining or impacts. Samples will be collected from each soil boring within the intervals where target soil types were distinguished during the previous geotechnical analysis, and submitted for analysis of the following:

- Moisture content,
- Sieve analysis and visual classification,
- Organic content,
- Soil pH,
- Soil density, and
- Water testing (pH, hardness, total dissolved solids [TDS])

Soil index testing results and remaining soil samples will be used for the bench scale treatability study, which is further discussed in [Section 2.4](#).

Additionally, soil samples will also be submitted for analysis of TCL VOCs, TCL SVOCs, Target Analyte List (TAL) metals, cyanide, TCLP VOCs, TCLP SVOCs, TCLP metals, polychlorinated biphenyls, Resource Conservation and Recovery Act (RCRA) Characteristics, TCLP Pesticides, and TCLP Herbicides at a NYSDOH accredited laboratory.

2.1.4 Site Survey

The soil boring locations will be surveyed by a Professional Surveyor licensed in the State of New York. Vertical control of elevations will be established to the nearest 0.01-foot and will be based on a U.S. Geological Survey datum and benchmarks established on the Site. Horizontal control will be based on New York State plane coordinate system with established and referenced control points. All survey elevations will be referenced to the North American Vertical Datum of 1988, and all horizontal locations of each point will be surveyed in the New York State Plan Coordinate System – Long Island Zone North American Datum of 1983.

2.1.5 Management of Investigation Derived Waste

Investigation-derived wastes generated during the field investigation will be containerized. Soils will be placed in 55-gallon Department of Transportation (DOT) approved drums and labeled appropriately. Plastic sheeting and personal protective equipment will be consolidated in DOT-approved drum(s).

Fluids will be placed in DOT-approved fluid drums with closed tops. The drums will be staged in a secure area prior to proper characterization and off-site disposal.

2.2 BENCH SCALE TREATABILITY STUDY

The goal of the bench-scale treatability study is to assess the treatability and effectiveness of mixing NAPL-impacted Site soils with various reagent design mixes to determine an effective reagent design mix(es) and dose requirements for achieving established performance criteria.

Based on previous geotechnical analysis completed at the Site, six discrete soil types have been identified in the subsurface. For the bench-scale testing, samples of each soil representing the six assumed lithologies at the Site will be collected within the anticipated ISS footprint during field activities and submitted for the treatability study as detailed below.

The treatability study will be performed in three steps:

- Step 1 – Soil Index Testing,
- Step 2 – Initial Mixture Development, and
- Step 3 – Final Mixture Development and Confirmation Testing.

During Step 1, prior to developing reagent mixtures, each of the six soil composite samples will be analyzed for:

- As received moisture content,
- Sieve analysis with visual classification,
- Loss on ignition (total organic content),
- Soil pH,
- Soil density (single point Proctor), and
- Water testing (pH, hardness, and TDS)

Based on the results of Step 1, reagent mixtures will be developed for testing during Step 2. Up to six selected soil reagent combinations will be applied to each of the six composite soil samples, for a total of 36 mixes. The following analysis will be performed on the mixes:

- Standard grout tests (e.g., pH and temperature; viscosity and density),
- Slump (visual or mini slump cone) and density,
- Early unconfined compressive strength (UCS) development monitoring using pocket penetrometer,
- UCS testing following 3- and 7-day curing periods, and
- Hydraulic conductivity testing following 7- and 14-day curing periods.

Additionally, Step 2 mixtures will be submitted for laboratory analysis of the following:

- Final leachate pH for Synthetic Precipitation Leaching Procedure (SPLP) analysis,
- TCL SPLP VOCs,
- TCL SPLP SVOCs, and
- TAL SPLP metals.

Based on the results of Step 2, 12 mixes, two from each composite soil type, will be selected for additional testing during Step 3. The following are components of Step 3 testing to finalize mixture development:

- USC testing following 14- and 28-day curing periods,
- Hydraulic conductivity testing after samples have cured for 28 days, and
- Slake immersion with no UCS.

Additionally, Step 3 mixtures will be submitted for laboratory analysis of the following:

- Final leachate pH for SPLP analysis,
- TCL VOCs via Leaching Environmental Assessment (LEAF) USEPA Method 1315,
- TCL SVOCs via LEAF USEPA Method 1315,
- TAL metals via LEAF USEPA Method 1315, and
- Conductivity, specific conductance, oxidation-reduction potential, and pH.

Laboratory analysis of materials and leachate will be performed in a step-wise process by utilizing SPLP analysis during Step 2 and LEAF analysis during Step 3. Analysis via LEAF Method 1315 involves submerging a complete sample of each final mixture in closed containers with zero headspace for a total period of 63 days, with the collection of leachate waters at nine specific intervals for laboratory analysis of VOCs, SVOCs, metals, conductivity, specific conductance, oxidation-reduction potential, and pH. This method allows for monitoring of leached concentrations and mass over time, as well as cumulative concentration and mass release over the duration of the analysis.

The scope of the ISS bench scale treatability study and the number of ISS design mixes may be modified during the soil sampling and treatability study preparation activities based on the characteristics of the composite soil samples and the early results of the hydraulic conductivity and/or unconfined compressive strength testing.

2.3 SUBSURFACE HYDRAULICS EVALUATION AND MODELING

The Site is hydraulically complicated in that spatial and temporal distribution of water levels are often at unexpected elevations. For example, several monitoring wells at the Site frequently became artesian during PDI activities. As shown on [Figure 8](#), which is the 2012 Groundwater Elevation Contour, groundwater levels in MW-5, PW-1, and MW-24 were all determined to be above ground surface, meaning that the groundwater flowed out of the top of the casing after the J plugs were removed for gauging. To better understand the anomalous nature of the subsurface hydraulic system, a study will be executed using existing Site data to determine if and to what degree these hydraulic anomalies may impact and/or should be accounted for in the remedial design.

In addition, since the ISS will significantly alter the subsurface hydraulics, a groundwater model will be developed to evaluate potential alterations in the groundwater flow directions and rates following remedial construction. This model will simulate the changes in the groundwater systems with the goal of identifying the potential for an unexpected rise in the water table and/or redirection of groundwater flow.

2.4 3D RENDERING OF SITE LITHOLOGIES

This task includes the development of a 3D visualization model of the relevant subsurface. The Site is complicated because the elevation of the top of bedrock and/or other subsurface obstructions are variable, including potential backfilling with large bedrock boulders. To complete the ISS, detailed depth assignments are needed to estimate spatial characteristics in a dense, point-by-point manner to accommodate the complicated Site features and design requirements. As such, the 3D model will be generated to identify bedrock elevations in relation to observed obstructions to help improve spatial

distribution of the total depth of each ISS column/grid location and provide more informed conceptualization and an improved visualization tool for the remedial design.

Figure 10 is a conceptual rendering and has been included for illustrative purposes. The conceptual rendering identifies the three excavation areas, the excavation zones, the soil mixing zones, and the jet grouting zones with the extrapolated bedrock contour of the Site shown underneath.

2.5 STRUCTURAL EVALAUTION OF SENSITIVE STRUCTURES

A visual evaluation of existing above-grade structures (e.g., multi-story building, pedestrian bridge) at the Site that would need to be monitored during the remedial construction activities will be completed as part of the supplemental PDI. This will include a records search at the New York City Department of Buildings to obtain available engineering drawings that may exist for these above-grade structures. Real time monitoring and surveying technologies that would be implemented during the remedial construction at the Site will be considered at part of this evaluation.

3.0 REMEDIAL DESIGN

This section describes the remedial design tasks to be completed to prepare the design for the selected Site remedy. Preparation of the remedial design will include the following general tasks:

- Remedial Design Task 1 – Removal of Overburden Soil
- Remedial Design Task 2 – ISS Mix Design
- Remedial Design Task 3 – ISS Methodology
- Remedial Design Task 4 – Site Restoration and Cover

A description of each task associated with the preparation of the remedial design is presented below. Note that additional supporting remediation tasks (e.g., Site preparation, maintaining the Site cover, waste management) will be developed as part of the remedial design. The remedial design will also present proposed locations for temporary remediation support structures (e.g., staging areas), requirements for soil erosion control and monitoring and mitigation procedures for dust, odor, and vapors. Green remediation principles and techniques also will be evaluated during the remedial design and implementation processes.

3.1 REMEDIAL DESIGN TASK 1 – REMOVAL OF OVERBURDEN SOIL

Excavation of overburden soil to a depth of up to five feet in select areas of the Site will be required prior to the implementation of the ISS activities to allow for bulking of the subsurface material and to remove and/or expose debris and other obstructions. The bulking factor is typically 25 to 30 percent and would more accurately be estimated during the bench-scale treatability study. The perimeter of the excavation areas will be sloped or shored as required. The excavated material will be sampled for waste characterization and transported for off-site disposal. ISS bulking materials will be managed within the 5-foot excavations and disposed off-site. The removal of overburden soil will also allow for subsurface utilities to be exposed, identified, and rerouted as required. Lastly, the removal of overburden soils to a depth of 5 feet will ensure the constructed ISS formation is below frost depths.

3.2 REMEDIAL DESIGN TASK 2 – ISS MIX DESIGN

ISS technology generally involves the mixing of contaminated soils with a binder reagent to create stabilized material that discourages groundwater flow through it, thus greatly reducing the potential for contaminants in Site soils from migrating off site. The results of the bench scale treatability study will be used during the remedial design to determine the ISS mix designs to achieve the RAOs established for the Site. The remedial design will include the proposed hydraulic conductivity and unconfined compressive strength for the ISS formation based on the results of the treatability study and other Site considerations. The goal is to establish two or more ISS mix designs that can achieve the required hydraulic conductivity and unconfined compressive strength determined during the remedial design.

3.3 REMEDIAL DESIGN TASK 3 – ISS METHODOLOGY

ISS will be implemented on remaining source materials below a depth of 5 feet. The treatment zone will extend from approximately 5 feet bgs to approximately 15 feet bgs. It is anticipated that the ISS within this depth interval will be conducted using “bucket mixing” methods. The excavators will also be used to remove subsurface obstructions within these depths. The actual ISS methodology will be

determined during the remedial design and confirmed by the selected remediation contractor implementing the Site remedy.

The ISS methodology below 15 feet bgs is anticipated to consist of jet grouting technology. This is primarily due to the presence of existing obstructions that were encountered during previous Site investigations. During the implementation of the supplemental soil boring field program, additional soil borings may be installed to confirm the presence of subsurface obstructions that were documented during previous Site investigations.

The diameters and spacing of the ISS columns will also be determined during the remedial design. The diameters and spacing of ISS jet grout columns may be decreased based on the presence of subsurface obstructions and potential shadowing effects created by the jet grouting around obstructions. A conceptual layout of the ISS jet grout columns is presented in [Figure 11](#) for designated Area 1 and Area 3 of the ISS formation and [Figure 12](#) for the designated Area 2 of the ISS formation. The actual diameters and spacing of the ISS columns will be confirmed by the selected remediation contractor implementing the Site remedy.

3.4 REMEDIAL DESIGN TASK 4 – SITE RESTORATION AND COVER

Imported backfill meeting the requirements of 6 NYCRR Part 375-6.7(d) will be brought to the Site to backfill the excavations to the subgrade design grades for the Site cover.

A Site cover will be required to allow for commercial use of the Site and to protect the ISS component of the remedy. In the ISS areas, the function of this cover will be to provide sufficient thermal protection of the solidified mass from seasonal freeze/thaw cycles and prevent contact with the ISS material. A Site cover currently exists in the form of asphalt pavement and will be maintained in areas where excavation and ISS are not performed to allow for commercial use of the Site. Any Site redevelopment will maintain the existing Site cover. The Site cover may include paved surface parking areas, sidewalks, or soil where the upper one foot of exposed surface soil meets the applicable SCOs for commercial use.

Where the soil cover is required over the ISS treatment area, it will consist of a minimum of four feet of soil meeting the SCOs for commercial use. For areas where solidified material underlies the cover, the solidified material itself will serve as the demarcation layer due to the nature of the material. The design requirements mandated by the NYSDOT for the restored parking lot will also be incorporated into the remedial design for the Site.

4.0 PERMITS, ACCESS AGREEMENT, AND APPROVALS

The remedial design will be developed to meet applicable SCGs, permits and approvals. In addition to NYSDEC approval of the remedial design, local permits and approvals will be necessary to implement the NYSDEC-selected remedy.

4.1 SUPPLEMENTAL PDI PERMITS AND SITE ACCESS AGREEMENTS

Drilling activities to be completed in support of the bench scale treatability study will be conducted within the NYSDOT-owned parking lot at the Site. As such, a permit application will be completed to gain access to the parking lot and will include the following information:

- A description of field activities,
- An anticipated field schedule,
- Contact information for the Con Edison and Parsons team members,
- A drawing depicting the proposed drilling locations and work areas,
- Work Zone Traffic Control drawings, and
- A Certificate of Insurance.

The drawings will be signed and sealed by a Professional Engineer licensed in the State of New York.

4.2 REMEDIAL ACTION PERMITS AND APPROVALS

Permits and approvals anticipated to complete the remedial construction activities may include (but are not limited to):

- Remediation General Permit for Stormwater Discharges from Construction Activities,
- NYSDOT Access Permit,
- Traffic Control Permits, and
- New York City Building Permits.

A final list of permits necessary to implement the remedy will be identified in the remedial design.

5.0 REMEDIAL DESIGN DOCUMENTS AND SCHEDULE

The scope of work for this task includes preparation of remedial design documents consistent with the requirements of NYSDEC DER-10. The following remedial design submittals will be prepared:

- 75% Pre-Final Remedial Design
- 100% Remedial Design
- Final 100% (Issued-for-Bid) Remedial Design

Specific technical design elements to be developed during the design process include:

- Detailed engineering design to provide quantities, locations, and construction details for the stabilization of soils
- Site restoration details

The general contents of each remedial design document are presented below.

5.1 75% PRE-FINAL REMEDIAL DESIGN

The 75% Pre-Final Remedial Design Report will generally include the following information:

- Narrative descriptions of remedial activities and responsibility assignments including an introductory section that provides a brief overview of the remedial design, Site background information, the design report objectives, and results of the supplemental PDI),
- A summary of the remedy with a basis of design that describes the proposed remedial design and presents information used to develop the design approach and construction components of the project, including design calculations, where appropriate, to support the basis of design,
- A description of Site controls for protecting the public health, safety, welfare, and environment and to maintain the effectiveness of the remedial action,
- Draft technical specifications,
- Draft design drawings, and
- Draft project control plans, including:
 - CAMP that describes the monitoring activities that will be conducted during the remedial activities,
 - A Waste/Soil Management Plan that describes the characterization, handling, treatment, and disposal requirements for various waste materials that will be generated,
 - Water Management Plan for handling of waters generated/collected during remedial activities,
 - Sampling and Analysis Plan that outlines requirements for characterization of soil and water generated,
 - Noise Monitoring Plan that describes monitoring requirements and acceptable noise levels during remedial activities, and
 - Odor, Vapor, and Dust Control Plan that presents methods to minimize potential impacts to the surrounding community.
- Construction quality assurance language that describes the materials and procedures necessary for proper construction, evaluation, and documentation during remedial activities, along with required transportation routes showing truck routes to minimize disturbances to the community,

- Conceptual Remedial Action Schedule that presents the anticipated schedule for implementation of the remedial activities, and

Project plans will be presented in brief reports that describe the general approach to the design of the component and any required design calculations.

5.2 FINAL (100%) REMEDIAL DESIGN

The Final (100%) Remedial Design Report will address comments provided by the NYSDEC on the 95% Remedial Design Report and will finalize all the design documents for final distribution to the NYSDEC. The Final (100%) Remedial Design Report will include final technical specifications and drawings, final project plans, and the final construction schedule.

5.3 REMEDIAL DESIGN SCHEDULE

The anticipated schedule for completing the supplemental PDI activities identified in this RDWP and a preliminary schedule for completion of the remedial design and construction of the selected remedy for the Site are presented in [Table 5.1](#) below.

Table 5.1 Preliminary Project Schedule

Task	Anticipated Time Frame
Obtain Access Agreements, Conduct Supplemental PDI Activities	2Q to 3Q 2022
Prepare 75% Pre-Final Design for NYSDEC	4Q 2022 to 2Q 2023
Submit 75% Pre-Final Design to NYSDEC	3Q 2023
Address NYSDEC comments on prefinal design; prepare final design	4Q 2023 to 1Q 2024
Submit Final (100%) Remedial Design Report to NYSDEC	2Q 2024

This anticipated schedule for conducting the supplemental PDI activities is dependent on Site access. Preparation of remedial design documents is dependent on receipt of NYSDEC comments on project submittals.

6.0 POST-CONSTRUCTION ACTIVITIES

Following remedial construction activities, the completed remedial programs for the Site will be documented in a certified Final Engineering Report (FER) using the guidance provided in Section 5.8 of DER-10. Future Site activities will be conducted in accordance with an SMP to be established for the Site coving the OU2 portion of the Former West 45th Street Gas Works Site discussed in this RDWP, and incorporating the information detailed in the Interim Site Management Plan submitted to the NYSDEC in May 2021 for the OU1 portion of the Former West 45th Street Gas Works Site. The anticipated components of the SMP and FER are presented below.

6.1 FINAL ENGINEERING REPORT

A FER will be prepared in accordance with DER-10 guidance to document implementation of the completed remedial program, and will consist of the following elements:

- A summary of relevant background information, including Site location/description and history,
- A summary of the final remedial activities, as constructed, including:
 - A description of any problems encountered during construction and their resolutions,
 - A description of changes to the design documents and why the changes were made,
 - Quantities and concentrations of constituents in media (e.g., soil and water) removed,
 - A listing of the waste streams, including quantity of materials treated/disposed and corresponding treatment/disposal locations,
 - The quantity of excavated material re-used as subsurface fill (if applicable),
 - Boundaries of the real property subject to the environmental easement or other institutional controls, and
 - A detailed description of site restoration activities.
- A list of the RAOs and remedial goals applied to the remedial activities,
- A description of source and quality of fill,
- A description of the community air monitoring and other remedial action compliance activities performed,
- Tables and figures containing laboratory analytical results,
- “As-built” drawings bearing the stamp and signature of a Professional Engineer licensed to practice in New York State and showing:
 - Surveyed excavation limits and ISS limits
 - Permanent survey markers for horizontal and vertical control for site management
- A description of the institutional controls employed at the site and a copy of the environmental easement, when available, and
- A certification statement with the signature and seal of a Professional Engineer licensed to practice in New York State.

The following supplemental information will also be provided with the FER:

- Fully executed manifests/certificates of disposal documenting the off-site transportation and treatment/disposal of waste materials generated as part of the remedial activities
- Copies of weekly field reports and air monitoring logs documenting results of air monitoring performed in accordance with the CAMP

- Results of all analyses, including laboratory analytical data reports and data validation reports
- Correspondence with the NYSDEC and others, as deemed relevant to the remedial activities

6.2 SITE MANAGEMENT PLAN

The SMP will be prepared consistent with the applicable requirements of DER-10 and in a format generally consistent with the NYSDEC's SMP template. As indicated in the Decision Document, the SMP will consist of the following:

- Institutional and Engineering Controls Plan – describes the use restrictions and engineering controls that will be established
- Monitoring Plan – used to assess the performance and effectiveness of the remedy. The SMP will include requirements for post-remedial action groundwater and NAPL monitoring, as well as Site inspection schedules and NYSDEC reporting requirements

6.2.1 Institutional and Engineering Controls

The Institutional and Engineering Controls Plan will identify use restrictions and engineering controls for the Site and detail the steps and media-specific requirements necessary to ensure that institutional and/or engineering controls remain in place and effective. This plan includes but is not limited to:

- An Excavation Plan which details the provisions for management of future excavations in areas of remaining contamination,
- Descriptions of the provisions of the environmental easement including any land use and groundwater use restrictions,
- A provision for evaluating the potential for soil vapor intrusion for any buildings developed on the Site and off-Site locations, including those that previously did not respond or refused sampling offers, and include provisions for implementing actions recommended to address exposures related to soil vapor intrusion,
- Provisions for the management and inspection of the identified engineering controls,
- Maintaining Site access controls and NYSDEC notification, and
- The steps necessary for the for the periodic reviews and certification of the institutional and/or engineering controls.

6.2.2 Monitoring Plan

The SMP also will require that Con Edison institute a long-term monitoring program to assess the performance and effectiveness of the remedy. The Monitoring Plan will, at a minimum, include details and requirements for the following:

- Periodic monitoring of groundwater,
- Periodic monitoring for vapor intrusion for any buildings developed in the area of Site management,
- Annual inspections of the institutional and engineering controls,
- A schedule for performance and effectiveness monitoring, and
- A schedule for submittal of Periodic Review Reports (PRRs) to the NYSDEC.

Consistent with DER-10 (Section 6.3), the PRRs will include certification of institutional and engineering controls until the NYSDEC notifies the property owner in writing that this certification is no longer needed. The PRR will contain certification that the institutional controls and engineering controls put in place are still in place and are either unchanged from the previous certification or are

REMEDIAL DESIGN WORK PLAN
FORMER WEST 45TH STREET GAS
WORKS SITE
OPERABLE UNIT 2

compliant with NYSDEC approved modifications and indicate that nothing has occurred that would impair the ability of the control to protect public health or the environment or constitute a violation or failure to comply with the SMP unless otherwise approved by the NYSDEC.

7.0 REFERENCES


AKRF, Inc. 1994. Route 9A Reconstruction Project – Environmental Impact Statement. May.


NYSDEC, 2010. *DER-10 Technical Guidance for Site Investigation and Remediation*. New York State Department of Environmental Conservation. May.

NYSDEC, 2016. *NYSDEC ISS QA/QC Guidance Document*. New York State Department of Environmental Conservation Letter. February 22.

Parsons, 2020. Revised Alternative Analysis Report for the former West 45th Street Gas Works Site Operable Unit No. 2. November.

FIGURES





LEGEND:

- CURRENT FEATURES
- HISTORICAL FEATURES (LOCATIONS ARE APPROXIMATE)
- EXISTING BUILDING
- CHAIN LINK FENCE
- LIMITS OF OU-1
- LIMITS OF OU-2
- BLOCK 1093 TAX BLOCK NUMBER
- 21 TAX LOT NUMBER FOR PARCELS WITHIN FORMER MGP
- TAX LOT BOUNDARIES
- APPROXIMATE EXTENT OF UPS PARKING GARAGE




FIGURE 2

CONSOLIDATED EDISON OF NEW YORK
FORMER WEST 45th STREET GAS WORKS – OU2
NEW YORK, NEW YORK


OPERABLE UNIT MAP AND
FORMER MGP STRUCTURES

PARSONS

200 COTTONTAIL LANE, SOMERSET, N.J. 08873, PHONE: 732-537-3500



WEST 46th STREET
(TRAFFIC FLOW →)



LEGEND:

- PROPERTY BOUNDARY
- APPROXIMATE LOCATION OF FORMER MGP STRUCTURES
- SOIL BORING LOCATION
- MONITORING WELL LOCATION
- ABANDONED MONITORING WELL
- ABANDONED PUMPING WELL
- EXISTING PUMPING WELL
- (-27.3')/-41.5' (BEDROCK ELEVATION)/DEPTH RELATIVE TO GROUND SURFACE (NAVD88)
- * NX CORE WAS NOT COLLECTED AT THIS LOCATION BECAUSE OF DRILLING ISSUES (e.g., ARTESIAN CONDITIONS, PRESENCE OF DEBRIS) OR PROXIMITY TO A LOCATION WHERE A NX CORE WAS TAKEN
- BEDROCK ELEVATION CONTOURS (DASHED WHERE INFERRED)
- CROSS SECTION LOCATION

NOTES:

- GROUND SURFACE ELEVATIONS RANGE FROM 10 FT TO 14.6 FT (NAVD88) ACROSS THE SITE.




FIGURE 3

CONSOLIDATED EDISON OF NEW YORK
FORMER WEST 45th STREET GAS WORKS - OU2
NEW YORK, NEW YORK

BEDROCK ELEVATIONS



200 COTTONTAIL LANE, SOMERSET, N.J. 08873, PHONE: 732-537-3500



CONCRETE

ASPHALT

BEDROCK

VISIBLE NAPL IN SOIL SAMPLE

VISIBLE NAPL IN WASH WATER

BRICK

? BEDROCK DEPTH ESTIMATED FROM FIELD OBSERVATIONS WITHOUT BEDROCK CORE

ESTIMATED POTENTIOMETRIC SURFACE ELEVATION

MONITORING WELL SCREEN INTERVAL

SOIL BORING

FORMER HOLDER WALL LOCATION (APPROX)



SCALE: 1"=20'
HORIZONTAL SCALE



SCALE: 1"=10'
VERTICAL SCALE

NOTES:

- ELEVATIONS ARE BASED ON NAVD88.
- NO HATCHING BELOW GROUND SURFACE INDICATES FILL MATERIALS, WHICH INCLUDE SAND, GRAVEL, COBBLES, WEATHERED GNEISSIC SCHIST, AND DEBRIS (BRICK, CONCRETE, WOOD, METAL).
- BEDROCK ELEVATIONS BASED ON BORING LOGS AND CONTOURS SHOWN ON FIGURE 3.
- GROUNDWATER ELEVATIONS BASED ON CONTOURS SHOWN ON FIGURE 8.


FIGURE 4

CONSOLIDATED EDISON OF NEW YORK
FORMER WEST 45th STREET GAS WORKS - OU2
NEW YORK, NEW YORK

OU-2 PRE-DESIGN INVESTIGATION
CROSS SECTION A-A'

PARSONS

200 COTTONTAIL LANE, SOMERSET, N.J. 08873, PHONE: 732-537-3500



CONCRETE

ASPHALT

BEDROCK

VISIBLE NAPL IN SOIL SAMPLE

VISIBLE NAPL IN WASH WATER

METAL

? BEDROCK DEPTH ESTIMATED FROM FIELD OBSERVATIONS WITHOUT BEDROCK CORE

ESTIMATED POTENTIOMETRIC SURFACE ELEVATION

MONITORING WELL SCREEN INTERVAL

SOIL BORING

FORMER HOLDER WALL LOCATION (APPROX)



SCALE: 1"=20'
HORIZONTAL SCALE



SCALE: 1"=10'
VERTICAL SCALE

NOTES:

- ELEVATIONS ARE BASED ON NAVD88.
- NO HATCHING BELOW GROUND SURFACE INDICATES FILL MATERIALS, WHICH INCLUDE SAND, GRAVEL, COBBLES, WEATHERED GNEISSIC SCHIST, AND DEBRIS (BRICK, CONCRETE, WOOD, METAL).
- BEDROCK ELEVATIONS BASED ON BORING LOGS AND CONTOURS SHOWN ON FIGURE 3.
- GROUNDWATER ELEVATIONS BASED ON CONTOURS SHOWN ON FIGURE 8.


FIGURE 5

CONSOLIDATED EDISON OF NEW YORK
FORMER WEST 45th STREET GAS WORKS - OU2
NEW YORK, NEW YORK

OU-2 PRE-DESIGN INVESTIGATION
CROSS SECTION B-B'

PARSONS

200 COTTONTAIL LANE, SOMERSET, N.J. 08873, PHONE: 732-537-3500



CONCRETE

ASPHALT

BEDROCK

VISIBLE NAPL IN SOIL SAMPLE

VISIBLE NAPL IN WASH WATER

BRICK

? BEDROCK DEPTH ESTIMATED FROM FIELD OBSERVATIONS WITHOUT BEDROCK CORE

ESTIMATED POTENTIOMETRIC SURFACE ELEVATION

MONITORING WELL SCREEN INTERVAL

SOIL BORING

FORMER HOLDER WALL LOCATION (APPROX)



SCALE: 1"=20'
HORIZONTAL SCALE



SCALE: 1"=10'
VERTICAL SCALE

NOTES:

- ELEVATIONS ARE BASED ON NAVD88.
- NO HATCHING BELOW GROUND SURFACE INDICATES FILL MATERIALS, WHICH INCLUDE SAND, GRAVEL, COBBLES, WEATHERED GNEISSIC SCHIST, AND DEBRIS (BRICK, CONCRETE, WOOD, METAL).
- BEDROCK ELEVATIONS BASED ON BORING LOGS AND CONTOURS SHOWN ON FIGURE 3.
- GROUNDWATER ELEVATIONS BASED ON CONTOURS SHOWN ON FIGURE 8.


FIGURE 6

CONSOLIDATED EDISON OF NEW YORK
FORMER WEST 45th STREET GAS WORKS - OU2
NEW YORK, NEW YORK


OU-2 PRE-DESIGN INVESTIGATION
CROSS SECTION C-C'

PARSONS

200 COTTONTAIL LANE, SOMERSET, N.J. 08873, PHONE: 732-537-3500



- CONCRETE
- ASPHALT
- BEDROCK
- VISIBLE NAPL IN SOIL SAMPLE
- VISIBLE NAPL IN WASH WATER
- BRICK
- BEDROCK DEPTH ESTIMATED FROM FIELD OBSERVATIONS WITHOUT BEDROCK CORE
- ESTIMATED POTENTIOMETRIC SURFACE ELEVATION
- MONITORING WELL SCREEN INTERVAL
- SOIL BORING
- FORMER HOLDER WALL LOCATION (APPROX)



NOTES:

- ELEVATIONS ARE BASED ON NAVD88.
- NO HATCHING BELOW GROUND SURFACE INDICATES FILL MATERIALS, WHICH INCLUDE SAND, GRAVEL, COBBLES, WEATHERED GNEISSIC SCHIST, AND DEBRIS (BRICK, CONCRETE, WOOD, METAL).
- BEDROCK ELEVATIONS BASED ON BORING LOGS AND CONTOURS SHOWN ON FIGURE 3.
- GROUNDWATER ELEVATIONS BASED ON CONTOURS SHOWN ON FIGURE 8.


FIGURE 7


CONSOLIDATED EDISON OF NEW YORK
FORMER WEST 45TH STREET GAS WORKS - OU2
NEW YORK, NEW YORK

OU-2 PRE-DESIGN INVESTIGATION
CROSS SECTION D-D'


PARSONS

200 COTTONTAIL LANE, SOMERSET, N.J. 08873, PHONE: 732-537-3500







Perspective from Due North facing South




Perspective from Due East facing West




Perspective from Due South facing North




Perspective from Due West facing East




3D Perspective Key




Excavation 0-5 ft. bgs.




In-Situ soil mixing 5-15 ft. bgs.



In-Situ jet grout columns 15-30 ft. bgs.



In-Situ jet grout columns 15 ft. bgs. to bedrock.



Bedrock

FIGURE 10


CONSOLIDATED EDISON OF NEW YORK
FORMER WEST 45th STREET GAS WORKS -OU2
NEW YORK, NEW YORK

West 45th St. ISS 3D Rendering


PARSONS

200 COTTONTAIL LANE, SOMERSET, M.J. 08873, PHONE: 732-537-3500

FILE NAME: P:\CONED\452727 - WEST 45TH OU-2 RDWP\CAD\452727-ISS-001.DWG
PLOT DATE: 11/18/2021 5:17 PM PLOTTED BY: RUSSO, JILL



AREA 1



AREA 3

LEGEND:

- — — — — ISS TO 15'
- — — — — ISS TO 30'
- — — — — ISS >30'
- — — — — BEDROCK CONTOURS (DASHED IF INFERRED)
- + ○ JET GROUT COLUMNS




FIGURE 11

CONSOLIDATED EDISON OF NEW YORK
FORMER WEST 45th STREET GAS WORKS - OU2
NEW YORK, NEW YORK


JET GROUT COLUMNS
AREA 1 & AREA 3

PARSONS
200 COTTONTAIL LANE, SOMERSET, N.J. 08873, PHONE: 732-537-3500

FILE NAME: P:\CONED\452727 - WEST 45TH OU-2 RDWP\CAD\452727-ISS-001.DWG
PLOT DATE: 11/16/2021 4:17 PM PLOTTED BY: RUSSO, JILL



APPENDIX A
NEW YORK CITY PLANING COMMISSION ZONING MAP 8C



CITY PLANNING COMMISSION
CITY OF NEW YORK
DIAGRAM SHOWING PROPOSED
ZONING CHANGE
ON SECTIONAL MAP
8c

BOROUGH OF
MANHATTAN

New York, Certification Date
JANUARY 03, 2011


S. Voyages, R.A. Director
Technical Review Division



NOTE:

- Indicates Zoning District Boundary.
- The area enclosed by the dotted line is proposed to be rezoned by changing from M1-5, M2-3 and M3-2 Districts to R8, R8A, R9 and M2-4 Districts, establishing within proposed R8A and R9 Districts a C2-5 District, and establishing a Special Clinton District.
- Indicates a C2-5 District.
- CL** Indicates a Special Clinton District.

Click blue box on map to view sketch map of proposed map change



ZONING MAP

THE NEW YORK CITY PLANNING COMMISSION

Major Zoning Classifications:

The number(s) and/or letter(s) that follows as R, C or M District designation indicates use, bulk and other controls as described in the text of the Zoning Resolution.

R - RESIDENTIAL DISTRICT

C - COMMERCIAL DISTRICT

M - MANUFACTURING DISTRICT

SPECIAL PURPOSE DISTRICT
The number(s) and/or letter(s) that follows as S District designation indicates use, bulk and other controls as described in the text of the Zoning Resolution.

AREA(S) REZONED

Effective Date(s) of Rezoning:

*03-03-2010 C. 100051 ZAM
12-21-2009 C. 090430 ZAM

Special Requirements:

For a list of lots subject to CEQR environmental requirements, see APPENDIX C.

For a list of lots subject to "D" restrictive declarations, see APPENDIX D.

For Inclusionary Housing designated areas on this map, see APPENDIX F.

CITY MAP CHANGE(S):

A 12-08-2009 C. 090096A) MM

ZONING MAP 8c

MAP KEY

5d	6b
8a	8c
8b	8d
9a	9b

© Copyright by City of New York

NOTE: Zoning information is shown on this map to subject. For the most up-to-date zoning information for the map, visit the Zoning section of the Department of City Planning website: www.nyc.gov/dcp/zoning, or contact the Zoning Information Center at (212) 312-3301.

NOTE: When no dimensions for zoning district boundaries appear on the zoning map, said dimensions are determined by the City Engineer's Office.

C1-1 C1-2 C1-3 C1-4 C1-5 C1-6 C1-7 C1-8 C1-9 C1-10 C1-11 C1-12 C1-13 C1-14 C1-15 C1-16 C1-17 C1-18 C1-19 C1-20 C1-21 C1-22 C1-23 C1-24 C1-25 C1-26 C1-27 C1-28 C1-29 C1-30 C1-31 C1-32 C1-33 C1-34 C1-35 C1-36 C1-37 C1-38 C1-39 C1-40 C1-41 C1-42 C1-43 C1-44 C1-45 C1-46 C1-47 C1-48 C1-49 C1-50 C1-51 C1-52 C1-53 C1-54 C1-55 C1-56 C1-57 C1-58 C1-59 C1-60 C1-61 C1-62 C1-63 C1-64 C1-65 C1-66 C1-67 C1-68 C1-69 C1-70 C1-71 C1-72 C1-73 C1-74 C1-75 C1-76 C1-77 C1-78 C1-79 C1-80 C1-81 C1-82 C1-83 C1-84 C1-85 C1-86 C1-87 C1-88 C1-89 C1-90 C1-91 C1-92 C1-93 C1-94 C1-95 C1-96 C1-97 C1-98 C1-99 C1-100 C1-101 C1-102 C1-103 C1-104 C1-105 C1-106 C1-107 C1-108 C1-109 C1-110 C1-111 C1-112 C1-113 C1-114 C1-115 C1-116 C1-117 C1-118 C1-119 C1-120 C1-121 C1-122 C1-123 C1-124 C1-125 C1-126 C1-127 C1-128 C1-129 C1-130 C1-131 C1-132 C1-133 C1-134 C1-135 C1-136 C1-137 C1-138 C1-139 C1-140 C1-141 C1-142 C1-143 C1-144 C1-145 C1-146 C1-147 C1-148 C1-149 C1-150 C1-151 C1-152 C1-153 C1-154 C1-155 C1-156 C1-157 C1-158 C1-159 C1-160 C1-161 C1-162 C1-163 C1-164 C1-165 C1-166 C1-167 C1-168 C1-169 C1-170 C1-171 C1-172 C1-173 C1-174 C1-175 C1-176 C1-177 C1-178 C1-179 C1-180 C1-181 C1-182 C1-183 C1-184 C1-185 C1-186 C1-187 C1-188 C1-189 C1-190 C1-191 C1-192 C1-193 C1-194 C1-195 C1-196 C1-197 C1-198 C1-199 C1-200 C1-201 C1-202 C1-203 C1-204 C1-205 C1-206 C1-207 C1-208 C1-209 C1-210 C1-211 C1-212 C1-213 C1-214 C1-215 C1-216 C1-217 C1-218 C1-219 C1-220 C1-221 C1-222 C1-223 C1-224 C1-225 C1-226 C1-227 C1-228 C1-229 C1-230 C1-231 C1-232 C1-233 C1-234 C1-235 C1-236 C1-237 C1-238 C1-239 C1-240 C1-241 C1-242 C1-243 C1-244 C1-245 C1-246 C1-247 C1-248 C1-249 C1-250 C1-251 C1-252 C1-253 C1-254 C1-255 C1-256 C1-257 C1-258 C1-259 C1-260 C1-261 C1-262 C1-263 C1-264 C1-265 C1-266 C1-267 C1-268 C1-269 C1-270 C1-271 C1-272 C1-273 C1-274 C1-275 C1-276 C1-277 C1-278 C1-279 C1-280 C1-281 C1-282 C1-283 C1-284 C1-285 C1-286 C1-287 C1-288 C1-289 C1-290 C1-291 C1-292 C1-293 C1-294 C1-295 C1-296 C1-297 C1-298 C1-299 C1-300 C1-301 C1-302 C1-303 C1-304 C1-305 C1-306 C1-307 C1-308 C1-309 C1-310 C1-311 C1-312 C1-313 C1-314 C1-315 C1-316 C1-317 C1-318 C1-319 C1-320 C1-321 C1-322 C1-323 C1-324 C1-325 C1-326 C1-327 C1-328 C1-329 C1-330 C1-331 C1-332 C1-333 C1-334 C1-335 C1-336 C1-337 C1-338 C1-339 C1-340 C1-341 C1-342 C1-343 C1-344 C1-345 C1-346 C1-347 C1-348 C1-349 C1-350 C1-351 C1-352 C1-353 C1-354 C1-355 C1-356 C1-357 C1-358 C1-359 C1-360 C1-361 C1-362 C1-363 C1-364 C1-365 C1-366 C1-367 C1-368 C1-369 C1-370 C1-371 C1-372 C1-373 C1-374 C1-375 C1-376 C1-377 C1-378 C1-379 C1-380 C1-381 C1-382 C1-383 C1-384 C1-385 C1-386 C1-387 C1-388 C1-389 C1-390 C1-391 C1-392 C1-393 C1-394 C1-395 C1-396 C1-397 C1-398 C1-399 C1-400 C1-401 C1-402 C1-403 C1-404 C1-405 C1-406 C1-407 C1-408 C1-409 C1-410 C1-411 C1-412 C1-413 C1-414 C1-415 C1-416 C1-417 C1-418 C1-419 C1-420 C1-421 C1-422 C1-423 C1-424 C1-425 C1-426 C1-427 C1-428 C1-429 C1-430 C1-431 C1-432 C1-433 C1-434 C1-435 C1-436 C1-437 C1-438 C1-439 C1-440 C1-441 C1-442 C1-443 C1-444 C1-445 C1-446 C1-447 C1-448 C1-449 C1-450 C1-451 C1-452 C1-453 C1-454 C1-455 C1-456 C1-457 C1-458 C1-459 C1-460 C1-461 C1-462 C1-463 C1-464 C1-465 C1-466 C1-467 C1-468 C1-469 C1-470 C1-471 C1-472 C1-473 C1-474 C1-475 C1-476 C1-477 C1-478 C1-479 C1-480 C1-481 C1-482 C1-483 C1-484 C1-485 C1-486 C1-487 C1-488 C1-489 C1-490 C1-491 C1-492 C1-493 C1-494 C1-495 C1-496 C1-497 C1-498 C1-499 C1-500 C1-501 C1-502 C1-503 C1-504 C1-505 C1-506 C1-507 C1-508 C1-509 C1-510 C1-511 C1-512 C1-513 C1-514 C1-515 C1-516 C1-517 C1-518 C1-519 C1-520 C1-521 C1-522 C1-523 C1-524 C1-525 C1-526 C1-527 C1-528 C1-529 C1-530 C1-531 C1-532 C1-533 C1-534 C1-535 C1-536 C1-537 C1-538 C1-539 C1-540 C1-541 C1-542 C1-543 C1-544 C1-545 C1-546 C1-547 C1-548 C1-549 C1-550 C1-551 C1-552 C1-553 C1-554 C1-555 C1-556 C1-557 C1-558 C1-559 C1-560 C1-561 C1-562 C1-563 C1-564 C1-565 C1-566 C1-567 C1-568 C1-569 C1-570 C1-571 C1-572 C1-573 C1-574 C1-575 C1-576 C1-577 C1-578 C1-579 C1-580 C1-581 C1-582 C1-583 C1-584 C1-585 C1-586 C1-587 C1-588 C1-589 C1-590 C1-591 C1-592 C1-593 C1-594 C1-595 C1-596 C1-597 C1-598 C1-599 C1-600 C1-601 C1-602 C1-603 C1-604 C1-605 C1-606 C1-607 C1-608 C1-609 C1-610 C1-611 C1-612 C1-613 C1-614 C1-615 C1-616 C1-617 C1-618 C1-619 C1-620 C1-621 C1-622 C1-623 C1-624 C1-625 C1-626 C1-627 C1-628 C1-629 C1-630 C1-631 C1-632 C1-633 C1-634 C1-635 C1-636 C1-637 C1-638 C1-639 C1-640 C1-641 C1-642 C1-643 C1-644 C1-645 C1-646 C1-647 C1-648 C1-649 C1-650 C1-651 C1-652 C1-653 C1-654 C1-655 C1-656 C1-657 C1-658 C1-659 C1-660 C1-661 C1-662 C1-663 C1-664 C1-665 C1-666 C1-667 C1-668 C1-669 C1-670 C1-671 C1-672 C1-673 C1-674 C1-675 C1-676 C1-677 C1-678 C1-679 C1-680 C1-681 C1-682 C1-683 C1-684 C1-685 C1-686 C1-687 C1-688 C1-689 C1-690 C1-691 C1-692 C1-693 C1-694 C1-695 C1-696 C1-697 C1-698 C1-699 C1-700 C1-701 C1-702 C1-703 C1-704 C1-705 C1-706 C1-707 C1-708 C1-709 C1-710 C1-711 C1-712 C1-713 C1-714 C1-715 C1-716 C1-717 C1-718 C1-719 C1-720 C1-721 C1-722 C1-723 C1-724 C1-725 C1-726 C1-727 C1-728 C1-729 C1-730 C1-731 C1-732 C1-733 C1-734 C1-735 C1-736 C1-737 C1-738 C1-739 C1-740 C1-741 C1-742 C1-743 C1-744 C1-745 C1-746 C1-747 C1-748 C1-749 C1-750 C1-751 C1-752 C1-753 C1-754 C1-755 C1-756 C1-757 C1-758 C1-759 C1-760 C1-761 C1-762 C1-763 C1-764 C1-765 C1-766 C1-767 C1-768 C1-769 C1-770 C1-771 C1-772 C1-773 C1-774 C1-775 C1-776 C1-777 C1-778 C1-779 C1-780 C1-781 C1-782 C1-783 C1-784 C1-785 C1-786 C1-787 C1-788 C1-789 C1-790 C1-791 C1-792 C1-793 C1-794 C1-795 C1-796 C1-797 C1-798 C1-799 C1-800 C1-801 C1-802 C1-803 C1-804 C1-805 C1-806 C1-807 C1-808 C1-809 C1-810 C1-811 C1-812 C1-813 C1-814 C1-815 C1-816 C1-817 C1-818 C1-819 C1-820 C1-821 C1-822 C1-823 C1-824 C1-825 C1-826 C1-827 C1-828 C1-829 C1-830 C1-831 C1-832 C1-833 C1-834 C1-835 C1-836 C1-837 C1-838 C1-839 C1-840 C1-841 C1-842 C1-843 C1-844 C1-845 C1-846 C1-847 C1-848 C1-849 C1-850 C1-851 C1-852 C1-853 C1-854 C1-855 C1-856 C1-857 C1-858 C1-859 C1-860 C1-861 C1-862 C1-863 C1-864 C1-865 C1-866 C1-867 C1-868 C1-869 C1-870 C1-871 C1-872 C1-873 C1-874 C1-875 C1-876 C1-877 C1-878 C1-879 C1-880 C1-881 C1-882 C1-883 C1-884 C1-885 C1-886 C1-887 C1-888 C1-889 C1-890 C1-891 C1-892 C1-893 C1-894 C1-895 C1-896 C1-897 C1-898 C1-899 C1-900 C1-901 C1-902 C1-903 C1-904 C1-905 C1-906 C1-907 C1-908 C1-909 C1-910 C1-911 C1-912 C1-913 C1-914 C1-915 C1-916 C1-917 C1-918 C1-919 C1-920 C1-921 C1-922 C1-923 C1-924 C1-925 C1-926 C1-927 C1-928 C1-929 C1-930 C1-931 C1-932 C1-933 C1-934 C1-935 C1-936 C1-937 C1-938 C1-939 C1-940 C1-941 C1-942 C1-943 C1-944 C1-945 C1-946 C1-947 C1-948 C1-949 C1-950 C1-951 C1-952 C1-953 C1-954 C1-955 C1-956 C1-957 C1-958 C1-959 C1-960 C1-961 C1-962 C1-963 C1-964 C1-965 C1-966 C1-967 C1-968 C1-969 C1-970 C1-971 C1-972 C1-973 C1-974 C1-975 C1-976 C1-977 C1-978 C1-979 C1-980 C1-981 C1-982 C1-983 C1-984 C1-985 C1-986 C1-987 C1-988 C1-989 C1-990 C1-991 C1-992 C1-993 C1-994 C1-995 C1-996 C1-997 C1-998 C1-999 C1-1000 C1-1001 C1-1002 C1-1003 C1-1004 C1-1005 C1-1006 C1-1007 C1-1008 C1-1009 C1-1010 C1-1011 C1-1012 C1-1013 C1-1014 C1-1015 C1-1016 C1-1017 C1-1018 C1-1019 C1-1020 C1-1021 C1-1022 C1-1023 C1-1024 C1-1025 C1-1026 C1-1027 C1-1028 C1-1029 C1-1030 C1-1031 C1-1032 C1-1033 C1-1034 C1-1035 C1-1036 C1-1037 C1-1038 C1-1039 C1-1040 C1-1041 C1-1042 C1-1043 C1-1044 C1-1045 C1-1046 C1-1047 C1-1048 C1-1049 C1-1050 C1-1051 C1-1052 C1-1053 C1-1054 C1-1055 C1-1056 C1-1057 C1-1058 C1-1059 C1-1060 C1-1061 C1-1062 C1-1063 C1-1064 C1-1065 C1-1066 C1-1067 C1-1068 C1-1069 C1-1070 C1-1071 C1-1072 C1-1073 C1-1074 C1-1075 C1-1076 C1-1077 C1-1078 C1-1079 C1-1080 C1-1081 C1-1082 C1-1083 C1-1084 C1-1085 C1-1086 C1-1087 C1-1088 C1-1089 C1-1090 C1-1091 C1-1092 C1-1093 C1-1094 C1-1095 C1-1096 C1-1097 C1-1098 C1-1099 C1-1100 C1-1101 C1-1102 C1-1103 C1-1104 C1-1105 C1-1106 C1-1107 C1-1108 C1-1109 C1-1110 C1-1111 C1-1112 C1-1113 C1-1114 C1-1115 C1-1116 C1-1117 C1-1118 C1-1119 C1-1120 C1-1121 C1-1122 C1-1123 C1-1124 C1-1125 C1-1126 C1-1127 C1-1128 C1-1129 C1-1130 C1-1131 C1-1132 C1-1133 C1-1134 C1-1135 C1-1136 C1-1137 C1-1138 C1-1139 C1-1140 C1-1141 C1-1142 C1-1143 C1-1144 C1-1145 C1-1146 C1-1147 C1-1148 C1-1149 C1-1150 C1-1151 C1-1152 C1-1153 C1-1154 C1-1155 C1-1156 C1-1157 C1-1158 C1-1159 C1-1160 C1-1161 C1-1162 C1-1163 C1-1164 C1-1165 C1-1166 C1-1167 C1-1168 C1-1169 C1-1170 C1-1171 C1-1172 C1-1173 C1-1174 C1-1175 C1-1176 C1-1177 C1-1178 C1-1179 C1-1180 C1-1181 C1-1182 C1-1183 C1-1184 C1-1185 C1-1186 C1-1187 C1-1188 C1-1189 C1-1190 C1-1191 C1-1192 C1-1193 C1-1194 C1-1195 C1-1196 C1-1197 C1-1198 C1-1199 C1-1200 C1-1201 C1-1202 C1-1203 C1-1204 C1-1205 C1-1206 C1-1207 C1-1208 C1-1209 C1-1210 C1-1211 C1-1212 C1-1213 C1-1214 C1-1215 C1-1216 C1-1217 C1-1218 C1-1219 C1-1220 C1-1221 C1-1222 C1-1223 C1-1224 C1-1225 C1-1226 C1-1227 C1-1228 C1-1229 C1-1230 C1-1231 C1-1232 C1-1233 C1-1234 C1-1235 C1-1236 C1-1237 C1-1238 C1-1239 C1-1240 C1-1241 C1-1242 C1-1243 C1-1244 C1-1245 C1-1246 C1-1247 C1-1248 C1-1249 C1-1250 C1-1251 C1-1252 C1-1253 C1-1254 C1-1255 C1-1256 C1-1257 C1-1258 C1-1259 C1-1260 C1-1261 C1-1262 C1-1263 C1-1264 C1-1265 C1-1266 C1-1267 C1-1268 C1-1269 C1-1270 C1-1271 C1-1272 C1-1273 C1-1274 C1-1275 C1-1276 C1-1277 C1-1278 C1-1279 C1-1280 C1-1281 C1-1282 C1-1283 C1-1284 C1-1285 C1-1286 C1-1287 C1-1288 C1-1289 C1-1290 C1-1291 C1-1292 C1-1293 C1-1294 C1-1295 C1-1296 C1-1297 C1-1298 C1-1299 C1-1300 C1-1301 C1-1302 C1-1303 C1-1304 C1-1305 C1-1306 C1-1307 C1-1308 C1-1309 C1-1310 C1-1311 C1-1312 C1-1313 C1-1314 C1-1315 C1-1316 C1-1317 C1-1318 C1-1319 C1-1320 C1-1321 C1-1322 C1-1323 C1-1324 C1-1325 C1-1326 C1-1327 C1-1328 C1-1329 C1-1330 C1-1331 C1-1332 C1-1333 C1-1334 C1-1335 C1-1336 C1-1337 C1-1338 C1-1339 C1-1340 C1-1341 C1-1342 C1-1343 C1-1344 C1-1345 C1-1346 C1-1347 C1-1348 C1-1349 C1-1350 C1-1351 C1-1352 C1-1353 C1-1354 C1-1355 C1-1356 C1-1357 C1-1358 C1-1359 C1-1360 C1-1361 C1-1362 C1-1363 C1-1364 C1-1365 C1-1366 C1-1367 C1-1368 C1-1369 C1-1370 C1-1371 C1-1372 C1-1373 C1-1374 C1-1375 C1-1376 C1-1377 C1-1378 C1-1379 C1-1380 C1-1381 C1-1382 C1-1383 C1-1384 C1-1385 C1-1386 C1-1387 C1-1388 C1-1389 C1-1390 C1-1391 C1-1392 C1-1393 C1-1394 C1-1395 C1-1396 C1-1397 C1-1398 C1-1399 C1-1400 C1-1401 C1-1402 C1-1403 C1-1404 C1-1405 C1-1406 C1-1407 C1-1408 C1-1409 C1-1410 C1-1411 C1-1412 C1-1413 C1-1414 C1-1415 C1-1416 C1-1417 C1-1418 C1-1419 C1-1420 C1-1421 C1-1422 C1-1423 C1-1424 C1-1425 C1-1426 C1-1427 C1-1428 C1-1429 C1-1430 C1-1431 C1-1432 C1-1433 C1-1434 C1-1435 C1-1436 C1-1437 C1-1438 C1-1439 C1-1440 C1-1441 C1-1442 C1-1443 C1-1444 C1-1445 C1-1446 C1-1447 C1-1448 C1-1449 C1-1450 C1-1451 C1-1452 C1-1453 C1-1454 C1-1455 C1-1456 C1-1457 C1-1458 C1-1459 C1-1460 C1-1461 C1-1462 C1-1463 C1-1464 C1-1465 C1-1466 C1-1467 C1-1468 C1-1469 C1-1470 C1-1471 C1-1472 C1-1473 C1-1474 C1-1475 C1-1476 C1-1477 C1-1478 C1-1479 C1-1480 C1-1481 C1-1482 C1-1483 C1-1484 C1-1485 C1-1486 C1-1487 C1-1488 C1-1489 C1-1490 C1-1491 C1-1492 C1-1493 C1-1494 C1-1495 C1-1496 C1-1497 C1-1498 C1-1499 C1-1500 C1-1501 C1-1502 C1-1503 C1-1504 C1-1505 C1-1506 C1-1507 C1-1508 C1-1509 C1-1510 C1-1511 C1-1512 C1-1513 C1-1514 C1-1515 C1-1516 C1-1517 C1-1518 C1-1519 C1-1520 C1-1521 C1-1522 C1-1523 C1-1524 C1-1525 C1-1526 C1-1527 C1-1528 C1-1529 C1-1530 C1-1531 C1-1532 C1-1533 C1-1534 C1-1535 C1-1536 C1-1537 C1-1538 C1-1539 C1-1540 C1-1541 C1-1542 C1-1543 C1-1544 C1-1545 C1-1546 C1-1547 C1-1548 C1-1549 C1-1550 C1-1551 C1-1552 C1-1553 C1-1554 C1-1555 C1-1556 C1-1557 C1-1558 C1-1559 C1-1560 C1-1561 C1-1562 C1-1563 C1-1564 C1-1565 C1-1566 C1-1567 C1-1568 C1-1569 C1-1570 C1-1571 C1-1572 C1-1573 C1-1574 C1-1575 C1-1576 C1-1577 C1-1578 C1-1579 C1-1580 C1-1581 C1-1582 C1-1583 C1-1584 C1-1585 C1-1586 C1-1587 C1-1588 C1-1589 C1-1590 C1-1591 C1-1592 C1-1593 C1-1594 C1-1595 C1-1596 C1-1597 C1-1598 C1-1599 C1-1600 C1-1601 C1-1602 C1-1603 C1-1604 C1-1605 C1-1606 C1-1607 C1-1608 C1-1609 C1-1610 C1-1611 C1-1612 C1-1613 C1-1614 C1-1615 C1-1616 C1-1617 C1-1618 C1-1619 C1-1620 C1-1621 C1-1622 C1-1623 C1-1624 C1-1625 C1-1626 C1-1627 C1-1628 C1-1629 C1-1630 C1-1631 C1-1632 C1-1633 C1-1634 C1-1635 C1-1636 C1-1637 C1-1638 C1-1639 C1-1640 C1-1641 C1-1642 C1-1643 C1-1644 C1-1645 C1-1646 C1-1647 C1-1648 C1-1649 C1-1650 C1-1651 C1-1652 C1-1653 C1-1654 C1-1655 C1-1656 C1-1657 C1-1658 C1-1659 C1-1660 C1-1661 C1-1662 C1-1663 C1-1664 C1-1665 C1-1666 C1-1667 C1-1668 C1-1669 C1-1670 C1-1671 C1-1672 C1-1673 C1-1674 C1-1675 C1-1676 C1-1677 C1-1678 C1-1679 C1-1680 C1-1681 C1-1682 C1-1683 C1-1684 C1-1685 C1-1686 C1-1687 C1-1688 C1-1689 C1-1690 C1-1691 C1-1692 C1-1693 C1-1694 C1-1695 C1-1696 C1-1697 C1-1698 C1-1699 C1-1700 C1-1701 C1-1702 C1-1703 C1-1704 C1-1705 C1-1706 C1-1707 C