

From: Davies, Wyn <Wyn.Davies@arcadis.com>
Sent: Wednesday, February 05, 2020 2:30 PM
To: Spellman, John (DEC)
Cc: Jackson, Darrel; O'Connor, Maryanne (DEC); Banach, Katie; Earp, Steve
Subject: AVNET - Former Channel Master Site, Ellenville, NY CEMR for Second Half 2019
Attachments: 020520.Avnet Channel Master Ellenville NY CEMR Second Half 2019.pdf

ATTENTION: This email came from an external source. Do not open attachments or click on links from unknown senders or unexpected emails.

John:

Per the requirements of Avnet/Channel Master's RCRA Corrective Action & Post Closure Consent Order executed on February 6, 2018, attached is the Chemical Effectiveness Monitoring Report (CEMR) for the second half of 2019 reporting period. We appreciate your willingness and desire to only provide electronic reporting of these regulatory reports.

Please let me know of any questions or concerns you may have regarding the report. As always, just call me on my mobile 610.360.4895

Wyn

Wyn V. Davies, CIH | Associate Vice President | Remediation Technical Expert wyn.davies@arcadis.com

Arcadis | Arcadis of New York Inc.

1717 Route 208 North Fair Lawn NJ | 07410 | USA

T. +1 201.398.4409 | M. +1 610.360.4895

Connect with us! www.arcadis.com | [LinkedIn](#) | [Twitter](#) | [Facebook](#) | [Connect App](#)



This email and any files transmitted with it are the property of Arcadis and its affiliates. All rights, including without limitation copyright, are reserved. This email contains information that may be confidential and may also be privileged. It is for the exclusive use of the intended recipient(s). If you are not an intended recipient, please note that any form of distribution, copying or use of this communication or the information in it is strictly prohibited and may be unlawful. If you have received this communication in error, please return it to the sender and then delete the email and destroy any copies of it. While reasonable precautions have been taken to ensure that no software or viruses are present in our emails, we cannot guarantee that this email or any attachment is virus free or has not been intercepted or changed. Any opinions or other information in this email that do not relate to the official business of Arcadis are neither given nor endorsed by it.

Mr. John Spellman, P.E.
Division of Environmental Remediation
New York State Dept. of Environmental Conservation
625 Broadway
Albany, NY 12233-7014

Arcadis U.S., Inc.
17-17 Route 208 North
Fair Lawn
New Jersey 07410
Tel 201 797 7400
Fax 201 797 4399
www.arcadis.com

Subject:
Avnet Inc. / Former Channel Master Site, Ellenville, NY
RCRA Corrective Action & Post Closure Consent Order
Index Number: CO 3-20170802-152
Site Number: 356025

Environment

Chemical Effectiveness Monitoring Report
Semi-Annual Report for Period July 1, 2019 to December 31, 2019

Date:
February 05, 2020

Dear Mr. Spellman:

Contact:
Wyn V. Davies, CIH

Enclosed is the semi-annual Chemical Effectiveness Monitoring Report (CEMR) for the former Channel Master site located in Ellenville, NY submitted on behalf of Avnet, Inc. This report covers the July 1, 2019 to December 31, 2019 reporting period and presents a summary of the ongoing 2019 corrective action activity results at the facility through the second half of 2019. The overall summary of the activities for 2019, as well as a statistical evaluation, of all wells will be performed and this annual report will be issued to the NYSDEC in 2Q2020.

Phone:
610.360.4895


Email:
wyn.davies@arcadis.com

If you have any comments or questions regarding the report, please call me at 610.360.4895.

Our ref:
00395052.0000

Sincerely,

Arcadis of NY, Inc.



Wyn V. Davies, CIH
Associate Vice President

Copies:
Darrel Jackson, Avnet Inc., (w/encl.)


AVNET Inc. – Former Channel Master Facility

CHEMICAL EFFECTIVENESS MONITORING REPORT

Second Half 2019

Report Period – July 1 to December 31, 2019


February 2020

A large, solid orange geometric shape, resembling a stylized triangle or a section of a larger triangle, is positioned in the bottom right corner of the page. It is composed of two overlapping triangles, creating a complex, angular form that extends from the bottom edge towards the top right corner.

**CHEMICAL
EFFECTIVENESS
MONITORING REPORT
AVNET/FORMER
CHANNEL MASTER
SITE, ELLENVILLE NY**

Second Half 2019

(July 01 to December 31, 2019)



Wyn V. Davies, CIH
Associate Vice President

Prepared for:
AVNET Inc.

Prepared by:
Arcadis of NY, Inc.
17-17 Route 208 North
Fair Lawn
New Jersey 07410
Tel 201 797 7400
Fax 201 797 4399

Our Ref.:
30001478 - 00395052.0000

Date:
February 5, 2020

This document is intended only for the use of the individual or entity for which it was prepared and may contain information that is privileged, confidential and exempt from disclosure under applicable law. Any dissemination, distribution or copying of this document is strictly prohibited.

CONTENTS

1	Site Background.....	2
2	Chemical Effectiveness Monitoring Plan - Progress Summary	2
3	Evaluation	4
3.1	Influence of Pumping on Groundwater Flow	4
3.2	Quantities of TCA Recovered and Associated Removal Rates	5
4	Determination of Water Quality Trend	5
4.1	Historical	5
4.2	Current Monitoring Data Results	7
5	Conclusions and Recommendations	7

TABLES

Table 2-1	1,1,1-TCA Concentrations and Removal in Recovery Well
Table 2-2	1,1,1-TCA Concentrations and Removal in BH-20
Table 2-3	Initial 1,1,1-TCA Concentrations
Table 2-4	1,1,1-TCA Concentration History

FIGURES

Figure 3-1A	Monitoring Well Locations Formerly Inside the Plant Building and Current Data
Figure 3-1	Water Table Elevation Contour Map – November 25, 2019
Figure 3-2	Iso-concentration Map for 1,1,1-Trichloroethane – November 25, 2019

1 SITE BACKGROUND

Channel Master owned and operated a manufacturing facility in Ellenville, New York until the facility was sold to Imperial Schrade in 1984. Channel Master, which was owned by Avnet Inc. at that time, relocated its operations out of state and agreed to retain responsibility for identified environmental conditions associated with its Channel Master Division at the Ellenville, NY site. In October 1997, Avnet sold its Channel Master Division and again retained its responsibilities associated with its former operations at the Ellenville site, including assuming the role of responsible party in the RCRA Corrective Action & Post Closure Consent Order executed on February 6, 2018.

During its period of operation, Channel Master treated its wastewater in a chemical treatment system within the plant building and in an outdoor surface impoundment (Lagoon) on Channel Master's property. The plant and the surface impoundment were decommissioned under the Resource Conservation and Recovery Act (RCRA) in accordance with Channel Master's approved Closure Plan. Groundwater beneath the building was found to be contaminated with several volatile organic compounds (VOCs), the primary of which was 1,1,1-trichloroethane (TCA), a solvent used in degreasing. A groundwater recovery and treatment system was installed and has been operating since January 1987 to remedy the groundwater contamination beneath the building pad.

In March 1991, the New York State Department of Environmental Conservation (NYSDEC) issued a 6NYCRR Part 373 Post-Closure Permit for the facility (NYSDEC # 3-5156-91/4-0) which was replaced by a RCRA Corrective Action & Post Closure Consent Order executed on February 6, 2018. The post-closure monitoring requirements for the former surface impoundment (lagoon area) and the monitoring and evaluation requirements for the groundwater treatment and recovery system (plant area) are addressed in the Consent Order. The corrective action was also covered by a HSWA permit (#NYDO42457788, issued by the United States Environmental Protection Agency [USEPA] in May 1991 which has been managed by NYSDEC and continues to be covered by the RCRA Corrective Action & Post Closure Consent Order executed on February 6, 2018.

2 CHEMICAL EFFECTIVENESS MONITORING PLAN - PROGRESS SUMMARY

Channel Master developed a Chemical Effectiveness Monitoring Plan (CEMR) to assess the effectiveness of the corrective action program and has been incorporated into the RCRA Corrective Action & Post Closure Consent Order executed on February 6, 2018. The purpose of the plan, as described in the permit, is to determine the rate of groundwater cleanup and verify that groundwater elevation gradients are being maintained toward the recovery well. To satisfy these objectives, the plan proposed use of water quality and water level data collected from the

recovery well and eight monitoring wells (BH-1, BH-2, BH-9, BH-11A, BH-11B, BH-16, BH-18, and BH-19) located formerly inside¹ the plant building (see Figure 3-1A).

Earlier evaluations of the effectiveness of the corrective action concluded that pumping the recovery well is effectively removing contaminants from the groundwater. However, during the period of time from 1989 to early 1992, monitoring well BH-19 had shown an increase in the concentration of TCA, which is used as the indicator parameter in this assessment. From 1993 to 1999, TCA concentrations in BH-19 generally followed a cyclical pattern before beginning a steady decrease in 1999. This monitoring well is located approximately ten feet from the recovery well and is screened deeper (41 to 51 feet below grade) than the others in the network, including the recovery well. To investigate the possibility of induced downward migration of contaminants, Channel Master proposed collecting analytical data from well BH-17 for at least one year. BH-17 is screened deeper than most wells at the site (from 22 to 32 feet below grade) and is located in the area of greatest groundwater contamination. As proposed in the evaluation report, groundwater from BH-17 is being analyzed instead of BH-1 (which was originally part of the monitoring network) for comparison to groundwater data obtained from the other deep wells and to determine the significance of the earlier increase detected at BH-19. Although deep well BH-13 was also sampled during both semiannual sampling rounds in 2000 and 2001 to provide additional data on the deeper groundwater under the plant (as requested by the NYSDEC in its letter to Avnet dated January 18, 2000), the NYSDEC discontinued the requirement to sample BH-13 in 2002, since no significant concentrations of TCA were detected there in the four sampling rounds.

In September 1991, Channel Master began pumping an additional recovery well (BH-20) inside the plant building. Screened to a depth of 24.5 feet, BH-20 was installed in July 1990 approximately 70 feet west (upgradient) of the existing recovery well. At the time, this was near the area of greatest groundwater contamination. Pumping of BH-20 ceased in April 2001 because of mechanical difficulties with the well screen and pump. Because of the historically low recovery obtained at this well (less than 5 pounds of TCA had been removed from BH-20 since December 1996) and the fact that the area of greatest contamination is now much closer to the main recovery well, this did not have a significantly adverse impact on the effectiveness of the groundwater treatment system. Nonetheless, BH-20 was rehabilitated during the annual maintenance of the recovery well and associated piping in July 2002, at which time the pumping of BH-20 recommenced. BH-20 was not included in the Chemical Effectiveness Monitoring Plan because it was not being operated at the time the plan was developed; however, the results of pumping this well are evaluated in this report.

In a letter dated January 18, 2000, Gary Casper of the NYSDEC directed Avnet to sample deep well BH-13 in April and October 2000 to further evaluate the conditions in the deep groundwater in the plant area. Neither sample contained contaminants exceeding NYSDEC groundwater quality standards. At the request of the NYSDEC, Avnet sampled BH-13 again in May and October 2001. As indicated in the semiannual groundwater monitoring report for the May 2001

¹ In April 2016, the former manufacturing building demolition was completed while maintaining the integrity of the building slab (the well structures are no longer “inside” the building). No substantial changes to the corrective action area or groundwater flow is anticipated.

sampling round, the groundwater elevation measured at BH-13 was more than 5 feet lower than the elevations measured at deep wells BH-11A, BH-17, and BH-19, indicating that BH-13 is to some degree hydraulically downgradient of the other deep wells. Therefore, because the groundwater sample from deep well BH-13 contained only 0.39 micrograms per liter ($\mu\text{g/l}$) of TCA (significantly less than the concentrations found in the other deep wells), it appears that TCA is not migrating laterally to a significant degree in the deep groundwater. Because TCA was not detected above its groundwater quality standard (GWQS) in BH-13 during any of the four sampling events in 2000 and 2001, the NYSDEC agreed to discontinue sampling BH-13 starting in 2002.

In the third and fourth quarters of 2015 and first quarter of 2016, the current site owner (AmTrust Realty) performed a demolition of the former Channel Master manufacturing buildings. The demolition activities removed all above ground structures and maintained the integrity of the building floor/pad to avoid potential issues of disrupting the groundwater flow patterns as well as the effectiveness of the groundwater recovery and treatment system. Arcadis monitored the progress of the demolition work to assure no disturbance of the well structures or the creation of infiltration pathways within the building pad occurred during the performance of the work. The relocation of the groundwater treatment system and the establishment of a new operational center on the building pad between the recovery well and BH-20 were performed in a manner that averted operational shutdowns beyond Post Closure requirements for the former Channel Master Site.

3 EVALUATION

3.1 Influence of Pumping on Groundwater Flow

Groundwater elevations were measured in the monitoring wells associated with the former plant building on November 25, 2019. These measurements were used to generate a groundwater contour map (see Figure 3-1) and to evaluate the current efficacy of the hydraulic control. Before pumping of the recovery well began in 1986, groundwater contours indicated flow generally toward the east. These contours were relatively parallel and straight. The current significant bending of the contour lines around the Recovery Well indicates that groundwater beneath the former plant building concrete slab is drawn toward the pumping well. The groundwater contours also support the impact of BH-20 on the groundwater flow to this intermittent groundwater recovery operation. Groundwater from the area surrounding the most highly contaminated groundwater shallow monitoring wells BH-11B and BH-16 also indicate flows toward the recovery well and BH-20 respectively. Therefore, the results of the current semi-annual groundwater elevation event support the goals of the CEMR in maintaining the efficacy of hydraulic control with the recovery wells. Additionally, there continues to be no groundwater flow disturbances/impacts related to the demolition of the building structure for the well structures installed beneath the former building floor slab through this semi-annual monitoring period.

3.2 Quantities of TCA Recovered and Associated Removal Rates

As discussed in the Chemical Effectiveness Monitoring Plan, 1,1,1-trichloroethane (TCA) has been detected in the monitored wells during every sampling event and consistently occurs at higher concentrations than other parameters. Therefore, TCA has been used in the semi-annual assessments (and found historically acceptable to the NYSDEC) as the indicator of contamination beneath the former plant building and the site. TCA concentrations in the recovery well have been monitored since 1986, prior to implementation of the corrective action program. TCA concentrations in BH 20 have been monitored since installation of that well in July 1990.

TCA concentration data on the recovery well are presented in Table 2-1, and the TCA concentration data for recovery well BH 20 are presented in Table 2-2.

To estimate the mass of TCA recovered from the recovery well and from BH 20, the concentration of TCA in the groundwater was multiplied by the volume of water pumped during the period between that sampling date and the preceding sampling date. The volume of groundwater pumped from the wells is recorded weekly. The following equation was used:

$$\text{Mass of TCA pumped (lb.)} = C \cdot V \cdot K$$

Where C = Concentration of TCA, in $\mu\text{g/l}$;

V = Volume of groundwater pumped, in gallons; and

K = Conversion factor: 8.34×10^{-9} (liters H_2O)(lb. TCA)/(gallons H_2O)(μg TCA)

Estimates of the mass of TCA recovered from each well since the start of pumping are presented in Table 2-1 and Table 2-2. The total amount of TCA removed by the Recovery Well and BH-20 through December 31, 2019 is approximately 866 pounds.

The removal rates are variable because of variability in both the concentrations and pumped volumes. The estimated average TCA removal rate from pumping the recovery well during the period covering July 1 to December 31, 2019 was approximately 0.0019 pounds per day (0.34 pounds total for the Second Half of year 2019). The estimated average TCA removal rate from BH 20 during the same period was approximately 0.00003 pounds per day (0.005 pounds total for the Second Half of year 2019).

4 DETERMINATION OF WATER QUALITY TREND

4.1 Historical

Avnet has evaluated groundwater data from the sampled monitoring wells as part of the corrective action program to assess the impact of TCA removal on groundwater quality beneath the plant's former building slab. Although the permit originally required the sampling of eight monitoring wells (BH-1, BH-2, BH-9, BH-11A, BH-11B, BH-16, BH-18, and BH-19), concentrations of TCA have been monitored in ten wells since 1986. Of the eight wells initially required to be sampled, six wells (BH-1, BH-2, BH-9, BH-11B, BH-16 and BH-18) are approximately 20 feet deep and monitor the shallow water table, while the other two wells (BH-

11A and BH-19) monitor deeper zones of the water bearing formation and are 38 and 51 feet deep, respectively. A third deep well, BH-17, is 32 feet deep and is also used to monitor the deeper zone. Prior to October 1991, this well was only sampled twice, in September 1985 and August 1986. The well is now being sampled instead of BH-1 to investigate the possibility of downward migration of contaminants as discussed in the previous section. In addition, the NYSDEC directed Avnet to sample deep well BH-13 in April and October 2000 and in May and October 2001 to provide additional information on the deeper groundwater under the site. The sampling of BH-13 was discontinued in 2002, as agreed to by the NYSDEC. The locations of these wells are shown on Figure 3-1A.

Water quality data collected before the start of the corrective action program were used to determine the average background concentration of TCA in the monitoring wells. Generally, two or three values are available from each well, as shown on Table 2-3. The concentrations measured at each well vary considerably, sometimes by as much as two orders of magnitude. Therefore, the estimates of background concentrations have a high degree of error associated with them.

In the case of several monitoring wells, samples collected shortly after installation (1985-1986, before the pumping and treating system began operating) contained the highest TCA concentrations recorded in those wells. This is particularly evident in the samples collected from BH 11A, BH-11B, BH-16, BH-18, and BH-17 (although one sample from BH-17 collected in 1998 contained the highest TCA concentration ever recorded for that well). The contaminants may have mobilized from the unsaturated soil during well installation; therefore, the concentrations detected may not represent what was present in the groundwater, and the calculated background concentrations may be overestimated.

Trends in water quality can be determined from historic data collected since the start of the corrective action program as presented in Table 2-4. Table 2-4 reveals a significant groundwater quality reduction trend of TCA in shallow wells decreasing in three orders of magnitude since pumping began [Especially evident in wells BH11B and BH-16].

Annual average TCA concentrations in deep well BH-19 have been generally decreasing since 1992, with the annual averages for the years 2002-2019 being the lowest ever. No sample from BH-19 has exceeded the NYSDEC GWQS for TCA (5.0 µg/l) since October 2000, and TCA has been detected in BH-19 above its laboratory reporting limit (generally 1.0 µg/l) only three times since April 2003. The annual average TCA concentration in deep well BH-17 peaked in 1998, and although the TCA concentration has tended to fluctuate somewhat since sampling of BH-17 began in 1991, TCA has been detected in BH-17 above its GWQS on only two occasions since October 2003. TCA concentrations in the other wells have been generally decreasing since 1987 as shown in Table 2-4.

The addition of one data point to the existing set of data is generally not sufficient to create a significant change in the linear regression analyses. Accordingly, the NYSDEC agreed that these analyses may now be performed on an annual basis and submitted with the Annual Report.

4.2 Current Monitoring Data Results

The results of the TCA monitoring for the Second Half of 2019 are presented in Table 2-4.

An iso-concentration map was constructed using the TCA concentrations in the five shallow groundwater samples collected in November 2019, as shown on Figure 3-2. Although the isopleths themselves should not be considered exact, the patterns on this map indicate that the area of highest contamination is near BH-11B (36 µg/l) and BH-16 (580 µg/l).

These results confirm that the recovery well is positioned near the area of greatest groundwater contamination and requires no modification to the goals of the Chemical Effectiveness Monitoring Plan.

5 CONCLUSIONS AND RECOMMENDATIONS

Water quality and water level data collected from the shallow wells located beneath the pad of the former plant building indicate that pumping the recovery well continues to remove contaminants from the groundwater. Groundwater quality in monitoring wells BH-11B, BH-16, and BH-18, historically three of the most contaminated shallow wells, has improved significantly as a result of the pumping. The concentration of 1,1,1-trichloroethane (TCA) in all three wells has decreased by several orders of magnitude since pumping began, although it appears that the reduction of the TCA concentration in groundwater has slowed in recent years. All samples collected from BH-11B and BH-16 (the two most contaminated wells) from October 2006 through December 2019 contained TCA at concentrations less than one part per million (ppm or mg/l), and in 24 of the 30 sampling rounds since April 2002, samples from these two wells have both contained TCA below one ppm. The TCA concentration in BH-18 has only slightly exceeded GWQS on two occasions since April 1999 – most recently in 2011.

A qualitative review of the most recent shallow groundwater contour map (Figure 3-1) and iso-concentration map (Figure 3-2) indicate that the contaminant plume appears to be effectively contained by the recovery well and BH-20 capture zones. This is supported by the fact that TCA has not been detected above its NYSDEC GWQS of 5.0 µg/l in the downgradient shallow well BH-9 since 1994, except for five samples, one in October 2005, one in November 2011, one in May 2013, one in November 2018, one in May 2019 and the current round in November 2019.

Avnet will continue to sample BH-17 (in lieu of shallow well BH-1) as well as BH-11A and BH-19 to monitor concentrations of volatile organic compounds (VOCs) in the deep groundwater, thereby addressing the concern with downward and/or deep lateral migration.

Therefore, the historical weight of evidence of facts continues to support the conclusion that the current corrective action program is effectively controlling the contaminant plume in the shallow groundwater and therefore should continue.

TABLES



TABLE 2-1

**1,1,1-TCA CONCENTRATIONS AND REMOVAL IN RECOVERY WELL
Former Channel Master Site
Chemical Effectiveness Monitoring**

SAMPLING DATE	TCA CONCENTRATION IN WATER (ug/l)	WATER PUMPED* (gallons)	TCA REMOVED (pounds)	TCA REMOVAL RATE (lbs/day)
3/18/1986	19	0		
12/3/1986	7500	0		
12/8/1986	3100	81000	2.1	0.419
1/14/1987	2300	180910	3.5	0.094
2/20/1987	920	941560	7.2	0.195
3/20/1987	630	873500	4.6	0.164
4/29/1987	860	1120240	8.0	0.201
5/27/1987	150	608350	0.76	0.027
6/11/1987	1100	295070	2.7	0.180
7/28/1987	710	966190	5.7	0.122
8/18/1987	520	569900	2.5	0.118
9/15/1987	670	732400	4.1	0.146
10/12/1987	1100	751920	6.9	0.255
11/19/1987	860	944670	6.8	0.178
1/20/1988	1900	1611970	26	0.412
2/17/1988	1300	227410	2.5	0.088
3/18/1988	2200	620380	11	0.379
4/7/1988	840	556180	3.9	0.195
5/18/1988	450	571190	2.1	0.052
6/7/1988	660	0	0.0	0.000
7/12/1988	620	0	0.0	0.000
8/30/1988	730	569960	3.5	0.071
9/30/1988	640	164950	0.88	0.028
10/27/1988	460	439310	1.7	0.062
11/30/1988	360	1225510	3.7	0.108
12/22/1988	750	462160	2.9	0.131
1/17/1989	470	446290	1.7	0.067
2/8/1989	670	475070	2.7	0.121
3/29/1989	330	1199950	3.3	0.067
5/2/1989	170	319080	0.45	0.013
5/22/1989	5.1	262740	0.011	0.001
6/30/1989	470	464420	1.8	0.047
7/6/1989	320	0	0.0	0.000
8/2/1989	370	363790	1.1	0.042
9/12/1989	260	1680180	3.6	0.089
10/4/1989	320	985570	2.6	0.120
10/25/1989	380	975570	3.1	0.147
12/13/1989	290	1739400	4.2	0.086
1/9/1990	480	431730	1.7	0.064
2/6/1990	1000	528180	4.4	0.157
3/3/1990	1100	426570	3.9	0.157
4/2/1990	640	923500	4.9	0.164
5/10/1990	460	1152430	4.4	0.116
6/4/1990	380	1419860	4.5	0.180
7/1/1990	290	0	0.0	0.000
8/7/1990	250	3049880	6.4	0.172

TABLE 2-1

**1,1,1-TCA CONCENTRATIONS AND REMOVAL IN RECOVERY WELL
Former Channel Master Site
Chemical Effectiveness Monitoring**

SAMPLING DATE	TCA CONCENTRATION IN WATER (ug/l)	WATER PUMPED* (gallons)	TCA REMOVED (pounds)	TCA REMOVAL RATE (lbs/day)
9/4/1990	220	1703420	3.1	0.112
10/8/1990	320	2054910	5.5	0.161
11/6/1990	250	1261917	2.6	0.091
12/10/1990	280	1791263	4.2	0.123
1/9/1991	640	503440	2.7	0.090
2/9/1991	330	1093430	3.0	0.097
3/6/1991	310	862420	2.2	0.089
4/20/1991	290	2432100	5.9	0.131
7/24/1991	270	2639010	5.9	0.063
10/15/1991	5000	3464990	144	1.741
12/21/1991	430	3211800	12	0.172
6/19/1992	890	7858630	58	0.322
12/7/1992	310	5733730	15	0.087
7/9/1993	195	4164728	6.8	0.032
12/6/1993	300	3789014	9.5	0.063
10/25/1994	970	8423700	68	0.211
3/28/1995	2000	4139800	69	0.448
7/12/1995	970	3354600	27	0.256
12/5/1995	200	4766100	7.9	0.054
6/11/1996	780	4398500	29	0.151
12/17/1996	1800	4297700	65	0.341
6/10/1997	160	3151400	4.2	0.024
12/16/1997	120	4643400	4.6	0.025
4/28/1998	360	4258800	13	0.096
12/10/1998	160	5930800	7.9	0.035
6/24/1999	66	3907100	2.2	0.011
12/28/1999	170	5397900	7.7	0.041
6/13/2000	340	4098800	11.6	0.069
12/29/2000	270	5491500	12.4	0.062
6/12/2001	170	5710200	8.1	0.049
12/26/2001	36	6573900	2.0	0.010
6/25/2002	36	4680800	1.4	0.0078
12/31/2002	26	5184000	1.1	0.0059
6/24/2003	40	5627400	1.9	0.011
12/30/2003	140	5525800	6.5	0.034
6/29/2004	130	6198100	6.7	0.037
12/28/2004	0	5540600	0.0	0.000
6/28/2005	32	5317700	1.4	0.0078
12/27/2005	0	4438700	0.0	0.000
6/28/2006	23	4667300	0.90	0.0049
12/27/2006	41	5061500	1.7	0.010
6/26/2007	16	5288400	0.71	0.0039
12/24/2007	15	5007800	0.63	0.0035
6/24/2008	19	4378500	0.69	0.0038
12/30/2008	39	3677500	1.20	0.0063
6/30/2009	13	3752500	0.41	0.0022

TABLE 2-1

**1,1,1-TCA CONCENTRATIONS AND REMOVAL IN RECOVERY WELL
Former Channel Master Site
Chemical Effectiveness Monitoring**

SAMPLING DATE	TCA CONCENTRATION IN WATER (ug/l)	WATER PUMPED* (gallons)	TCA REMOVED (pounds)	TCA REMOVAL RATE (lbs/day)
12/30/2009	16	4403800	0.59	0.0032
6/29/2010	12	3898500	0.39	0.0022
12/28/2010	19	4132300	0.65	0.0036
6/15/2011	11	4750000	0.44	0.0026
12/28/2011	9.4	4941900	0.39	0.0020
6/30/2012	14	4951000	0.58	0.0031
12/26/2012	22	5283500	0.97	0.0054
6/28/2013	16	5503000	0.73	0.0040
12/31/2013	66	5214300	2.87	0.0154
6/25/2014	22	4860400	0.89	0.0051
12/30/2014	18	4812400	0.72	0.0038
6/5/2015	14	4427300	0.52	0.0033
12/29/2015	18	5227600	0.78	0.0038
6/30/2016	19	3794107	0.60	0.0033
12/30/2016	26	4926193	1.07	0.0058
6/30/2017	23	4090300	0.78	0.0043
12/27/2017	14	3594000	0.42	0.0023
6/30/2018	13	4158500	0.45	0.0024
12/31/2018	14	5078800	0.59	0.0032
6/3/2019	14	4241800	0.50	0.0032
12/1/2019	15	2691900	0.34	0.0019
TOTALS		321,796,142	826.94	

Notes:

* Gallons pumped is measured from previous sampling date.

Updated 1/2020

TABLE 2-2

1,1,1-TCA CONCENTRATIONS AND REMOVAL IN BH-20
Former Channel Master Site
Chemical Effectiveness Monitoring

SAMPLING DATE	TCA CONCENTRATION IN WATER (ug/l)	WATER PUMPED* (gallons)	TCA REMOVED (pounds)	TCA REMOVAL RATE (lbs/day)
7/13/1990	4300	12,487	0.45	0.090
7/25/1990	270	0	0.00	0.000
10/17/1990	860	0	0.00	0.000
1/9/1991	2100	0	0.00	0.000
10/15/1991	2700	16,410	0.37	0.018
12/21/1991	4800	88,290	3.5	0.053
1/15/1992	2800	32,880	0.77	0.031
6/19/1992	4100	201,990	6.9	0.044
12/7/1992	1800	182,170	2.7	0.016
7/7/1993	740	330,450	2.0	0.010
12/6/1993	790	118,620	0.78	0.0051
10/25/1994	3000	324,410	8.1	0.025
3/28/1995	1700	124,490	1.8	0.011
7/12/1995	930	85,160	0.66	0.0062
12/5/1995	850	124,840	0.88	0.0061
6/11/1996	630	217,360	1.1	0.0060
12/17/1996	1400	192,540	2.2	0.012
6/10/1997	560	190,070	0.89	0.0051
12/16/1997	600	153,750	0.77	0.0041
4/28/1998	370	156,550	0.48	0.0036
12/10/1998	350	226,630	0.66	0.0029
6/24/1999	190	194,730	0.31	0.0016
12/28/1999	130	146,970	0.16	0.0009
6/13/2000	410	250,780	0.86	0.0051
12/29/2000	240	266,290	0.53	0.0027
12/31/2002	0	209,410	0.00	0.0000
6/24/2003	34	226,960	0.064	0.00037
12/30/2003	170	296,080	0.42	0.0022
6/29/2004	75	239,060	0.15	0.00082
12/28/2004	21	108,140	0.019	0.00010
6/28/2005	48	254,480	0.10	0.00056
12/27/2005	130	189,520	0.21	0.00113
6/28/2006	110	192,330	0.18	0.00096
12/27/2006	160	200,010	0.27	0.00147
6/26/2007	41	234,690	0.080	0.00044
12/24/2007	59	104,060	0.051	0.00028
6/24/2008	84	196,380	0.14	0.00075
12/30/2008	350	68,170	0.20	0.00105
6/30/2009	65	84,360	0.05	0.00025
12/30/2009	71	84,380	0.05	0.00027
6/29/2010	45	137,270	0.05	0.00028
12/28/2010	83	70,630	-1.80	-0.00991
6/15/2011	45	138,690	1.06	0.00626
12/28/2011	50	206,800	0.08	0.00043
6/30/2012	52	66,660	0.03	0.00015
12/26/2012	65	61,170	0.03	0.00019
6/28/2013	55	89,650	0.04	0.00022
12/31/2013	63	96,070	0.05	0.00027
6/25/2014	17	88,060	0.01	0.00007
12/30/2014	133	63,340	0.07	0.00037
6/5/2015	41	67,840	0.02	0.00013
12/29/2015	32	19,020	0.005	0.00003
6/30/2016	13	31,590	0.003	0.00002
12/30/2016	160	19,400	0.026	0.00014
6/30/2017	92	54,880	0.042	0.00023
12/27/2017	26	47,610	0.010	0.00006
6/30/2018	14	71,340	0.008	0.00005
12/31/2018	15	61,310	0.008	0.00004
6/3/2019	46	62,980	0.024	0.00016
12/1/2019	20	28,440	0.005	0.00003
TOTALS		7,808,647	38.80	

Notes:

* Gallons pumped is measured from previous sampling date.

Pumping of BH-20 ceased in April 2001 and was continued in July 2002.

Updated 1/2020

TABLE 2-3
INITIAL 1,1,1-TCA CONCENTRATIONS
Former Channel Master Site
Chemical Effectiveness Monitoring

Well No. Well Screen Interval (ft bgl)	BH-1 10-20	BH-2 10-20	BH-9 10-20	BH-11A 28-38	BH-11B 10-20	BH-16 10-20	BH-17 22-32	BH-18 10-20	BH-19 41-51
1985									
13-Jun	0.5 *	19.5	17.0						
17-Jul	2.0	17.0	4.0						
17-Sep				0.5 *	37,800	276,000	226	19,930	
17-Dec					13,300				
1986									
18-Mar				30.0					18.0
20-Jun		0.5 *	0.5 *						
16-Sep	9.3		38.0		140,000	900,000	0.8 *	9,200	0.8 *
03-Dec						170,000			
Sample average (1985-86)	3.9	12.3	14.9	15.3	63,700	448,667	113	14,565	9.4

NOTES: Blank space indicates well was not sampled
* indicates a value of one-half the detection limit for samples in which TCA was not detected
ft bgl = feet below grade level
All concentrations presented in units of ug/l.

TABLE 2-4

1,1,1-TCA CONCENTRATION HISTORY
Former Channel Master Site, Ellenville, NY
Chemical Effectiveness Monitoring Network

Well No. Well Screen Interval (ft bgl)	BH-1 10-20	BH-2 10-20	BH-9 10-20	BH-11A 28-38	BH-11B 10-20	BH-16 10-20	BH-17 22-32	BH-18 10-20	BH-19 41-51
Average Initial Concentration (data collected 1985-1986)	3.9	12.3	14.9	15.3	63,700	448,667	113	14,565	9.4
1987 20-Feb 29-Apr 27-May 18-Aug						304,000 90,000 100,000 470,000 170,000			9.4 14.0 93.0
average		94	30	0.15 *	55,000	258,500		1,600	39
1988 20-Jan 07-Apr 21-Jul 27-Oct		57 260 380 31	65 23 8.3 17	0.15 * 2.5 1.2 2.7	46,000 39,000 3,500 11,000	69,000 150,000 66,000 210,000		560 950 990 410	1.1 4.8 0.55 0.95
average		182	28	1.6	24,875	123,750		728	1.9
1989 17-Jan 01-May 05-Jul 25-Oct		38 17 200 79	7.4 1.2 180 16	1.9 1.2 0.33 11.0	17,000 12,000 22,000 20,000	370,000 48,000 26,000 110,000		1,300 120 660 330	2.5 0.4 130.0 92.0
average	4.1	84	68	3.6	17,750	138,500		603	56
1990 23-Jan 10-May 25-Jul 17-Oct	100 100 8.3 3.2	50 160 43 16	6.2 19 11 7.4	0.15 * 1.6 1.1 1.0	36,000 18,000 18,000 25,000	78,000 63,000 28,000 59,000		450 150 3,600 490	46 54 47 190
average	53	67	11	0.96	24,250	57,000		1,173	84
1991 09-Jan 24-Apr 24-Jul 15-Oct	10 3.2 4.4 41	58 54 32 41	7.0 11 9.7 4.8	1.4 3.4 0.48 4.8	13,000 6,100 28,000 19,000	12,000 16,000 12,000 19,000		700 310 160 12	130 170 70 190
average	5.9	46	8	2.5	16,525	14,750	11	296	140
1992 16-Jan 07-Apr 22-Jul 20-Oct		32 14 12 8.0	10 7.8 7.3 5.3	0.2 * 5.4 6.8 0.7	31,000 17,000 18,000 6,700	2,400 6,100 11,000 13,000	1.6 1.5 89 2.8	1,100 1,700 1,900 160	250 250 140 160
average		17	7.6	3.3	18,175	8,125	24	1,215	200
1993 26-Jan 07-Apr 06-Jul 02-Nov		9.0 14 0.25 *	300.0 6.8 0.25 *	5.7 2.0 0.25 * 0.25 *	14,000 180 11,800 13,000	4,200 5,500 3,270 12,000	0.75 0.80 18.4 160	2,300 4.1 13 150	68 14 21 93
average		7.8	102	2.1	9,745	6,243	45	617	49
1994 01-Feb 13-Apr 06-Jul 12-Oct		6.3 4.5 32 21	17 21 1.2 3.2	7.2 6.0 2.9 2.1	9,000 9,000 10,000 5,300	4,900 5,000 4,000 8,400	62 0.25 * 190 110	450 120 180 300	41 23 18 90
average		16	11	4.6	8,325	5,575	91	263	43
1995 10-Jan 11-Apr 12-Jul 25-Oct		7.7 25 12 17	3.6 1.9 3.8 2.6	0.25 * 2.5 0.25 * 4.6	5,800 5,600 5,400 2,900	2,300 1,500 7,900 13,000	2.7 6.4 120 39	620 120 3.5 19	37 13 35 140
average		15	3.0	1.9	4,925	6,175	42	191	56
1996 25-Jan 03-Apr 10-Jul 08-Oct		17 16 28 46	1.2 1.3 1.1 0.90	2.3 3.2 0.80 2.4	1,900 3,100 6,800 6,500	4,300 1,700 4,800 4,000	0.25 * 14 32 28	4.5 9.5 9.0 10	26 18 42 67
average		27	1.1	2.2	4,575	3,700	19	8.3	38
1997 14-Jan 29-May 22-Oct		12 12 19	1.8 2.5 1.4	0.25 * 0.32 1.7	7,500 6,800 690	1,200 1,100 4,910	75.0 3.4 260	110 10 2.9	49 5.1 76
average		14	1.9	0.76	4,997	2,403	113	41	43
1998 28-Apr 27-Oct		22 30	1.0 1.0	1.7 4.3	3,900 1,800	1,700 2,200	135.0 360.0	260 0.24	37 110
average		26	1.0	3.0	2,850	1,950	248	130	74
1999 08-Apr 20-Oct		3.7 26	2.0 1.7	1.4 4.9	3,000 6,300	360 2,300	22 180	130 2.5	64 38
average		15	1.9	3.2	4,650	1,330	101	66	51

TABLE 2-4

1,1,1-TCA CONCENTRATION HISTORY
Former Channel Master Site, Ellenville, NY
Chemical Effectiveness Monitoring Network

Well No. Well Screen Interval (ft bgl)	BH-1 10-20	BH-2 10-20	BH-9 10-20	BH-11A 28-38	BH-11B 10-20	BH-16 10-20	BH-17 22-32	BH-18 10-20	BH-19 41-51
2000 19-Apr 17-Oct		16 9.9	0.99 0.59	1.1 2.9	4,300 5,900	380 1,600	5.9 67	6.9 2.0	20 21
average		13	0.79	2.0	5,100	990	36	4.5	21
2001 31-May 29-Oct		8.1 2.3	1.3 0.79	12 9.6	4,200 1,600	840 960	62 79	1.6 1.4	4.1 0.17
average		5.2	1.0	11	2,900	900	71	1.5	2.1
2002 18-Apr 09-Oct		6.6 3.0	0.73 1.1	4.7 3.7	2,900 730	420 700	110 140	1.4 1.4	0.24 0.11 *
average		4.8	0.92	4.2	1,815	560	125	1.4	0.18
2003 29-May 23-Oct		9.8 23	1.3 0.7	4.3 3.3	3,000 900	210 120	120 75	1.3 1.3	0.37 0.13 *
average		16	1.0	3.8	1,950	165	98	1.3	0.25
2004 07-Apr 22-Oct		11 27	0.71 J 1.8	3.0 3.0	1,200 2,800	75 120	0.5 * 0.5 *	3.1 5.6	0.5 * 0.5 *
average		19	1.3	3.0	2,000	98	0.5	4.4	0.5
2005 29-Apr 21-Oct		3.1 4.0	0.94 18	3.4 3.6	300 240	170 390	0.5 * 0.5 *	2.6 2.0	0.5 * 0.5 *
average		3.6	9.5	3.5	270	280	0.5	2.3	0.5
2006 20-Apr 10-Oct		12 17	0.76 J 0.55	2.3 2.3	1,500 33	110 120	0.84 J 0.5 *	1.3 0.95 J	0.55 J 0.5 *
average		14.5	0.66	2.3	767	115	0.7	1.1	0.5
2007 21-Apr 30-Oct		4.4 9.5	0.94 J 1.7	2.0 0.5 *	140 530	160 120	0.5 * 77	4.2 0.78 J	0.5 * 0.5 *
average		7.0	1.32	1.3	335	140	38.8	2.5	0.5
2008 03-Apr 22-Oct		3.9 6.8	1.3 0.28 J	0.5 * 0.5 *	77 240	490 210	2.1 0.36 J	3.0 0.80 J	0.5 * 0.5 *
average		5.4	0.79	0.5	159	350	1.2	1.9	0.5
2009 10-Apr 23-Nov		6.0 9.0	2.3 1.1	0.5 * 0.12 *	160 240	430 220	5.2 1.8	3.2 0.93	0.53
average		7.5	1.7	0.31	200	325	3.5	2.1	0.53
2010 15-Jun 10-Nov			0.98 0.78	0.12 * 0.12 *	220 170	430 210	0.12 * 0.12 *	0.95 0.98	
average		16.0	0.9	0.12	195	320	0.12	1.0	0.12
2011 02-May 22-Nov		6.2 2.6	1.6 5.9	0.12 * 0.12 *	22 94 E	300 E 180 E	4.7 0.12 *	12 0.87	0.39 0.12 *
average		4.4	3.8	0.12	58	240	2.41	6.4	0.26
2012 01-May 25-Oct		3.5 8.3	4.3 5.2	0.12 * 0.12 *	110 E 61	250 E 280 E	4.7 0.12 *	3.5 1.6	0.12 * 0.12 *
average		5.9	4.8	0.12 *	86	265	2.41	2.6	0.12 *
2013 03-May 24-Oct		3.1 5.5	6.1 0.46	0.12 * 0.12 *	26 150 E	220 E 520 E	2.5 0.12 *	3.4 0.72	0.12 * 0.12 *
average		4.3	3.3	0.12 *	88	370	1.31	2.1	0.12 *
2014 07-May 28-Oct		1.2 5.1	0.2 0.26	0.12 * 0.12 *	38 160	320 E 59	2.9 0.35	4.80 0.55	0.12 * 0.12 *
average		3.2	0.23	0.12 *	99	190 E	1.63	2.68	0.12 *
2015 15-Apr 13-Nov		5.5 8.6	0.81 1.60	0.12 * 0.12	36 26	340 410	3.3 0.12 *	3.00 1.2	0.12 * 0.12 *
average		7.1	1.2	0.1 *	31.0	375.0	1.7 *	2.1	0.12 *

TABLE 2-4

1,1,1-TCA CONCENTRATION HISTORY
Former Channel Master Site, Ellenville, NY
Chemical Effectiveness Monitoring Network

Well No. Well Screen Interval (ft bgl)	BH-1 10-20	BH-2 10-20	BH-9 10-20	BH-11A 28-38	BH-11B 10-20	BH-16 10-20	BH-17 22-32	BH-18 10-20	BH-19 41-51
2016 20-May 04-Nov		2.7 12	1.70 0.39	0.12 * 0.12 *	71 180	410 450	0.36 0.12 *	0.47 0.44	0.12 * 0.29
average		7.4	1.05	0.12 *	126	430	0.24	0.46	0.21 *
2017 07-May 22-Nov		5.2 7.14	15.00 0.12 *	0.12 * 0.12 *	75 120	330 990	0.12 * 0.12 *	1.00 0.56 J	0.12 * 0.12 *
average		6.2	7.56	0.12 *	98	660	0.12	0.78	0.12 *
2018 19-May 20-Nov		2.9 3.4	0.80 J 9.60	0.12 * 0.12 *	80 18	130 640	0.12 * 0.12 *	0.68 J 0.72 J	0.12 * 0.12 *
average		3.2	5.20	0.12 *	49	385	0.12	0.70	0.12 *
2019 17-May 25-Nov		2.7 3.6	7.20 6.20	0.12 * 0.61 J	20 36	180 580	0.12 * 0.12 *	0.54 J 0.64 J	0.12 * 0.28 J
average		3.2	6.70	0.37 *	28	380	0.12 *	0.59	0.20 *
(Feb 1987- November 2019)	24	29	12	2	8,857	29,615	41	275	39

NOTES:

Blank spaces indicate well was not sampled

J - estimated value; detected below quantitation limit

* - indicates a value of one-half the detection limit for samples in which TCA was not detected

E- Result exceeded calibration range, secondary dilution required

ft bgl = feet below grade level


All concentrations presented in units of ug/l.

FIGURES



Legend


1,1,1-TCA - Trichloroethane
ug/l - Micrograms per liter



Document Path: G:\Project\0395052 Channel Master AVNET\GIS\ChannelMaster.mxd

Legend


Former Plant Area Water Table Contours (11/25/2019)



0 25 50 100 Feet

Elevations: feet MSL.

Document Path: G:\Project\0395052 Channel Master AV\NET\GIS\ChannelMaster.mxd



Arcadis U.S., Inc.

17-17 Route 208 North

Fair Lawn, New Jersey 07410

Tel 201 797 7400

Fax 201 797 4399

www.arcadis.com