

One General Motors Drive Syracuse, New York 13206 tel: 315 434-3200

fax: 315 463-5100

October 21, 2008

Mr. Steven P. Stucker, P.G. Lead Engineer National Grid 300 Erie Boulevard West Syracuse, New York 13202-4250

Subject:

Annual (2008) Groundwater Monitoring Report

Hudson (Water Street) Site, Hudson, New York

Dear Mr. Stucker:

CDM is pleased to submit this Annual (2008) *Groundwater Monitoring Report* for the Hudson (Water Street) Site, Hudson, New York. This report includes the requirements associated with the operation, maintenance, and monitoring of the Remedial Action Plan (RA) at Operable Unit (OU) 1 of the Hudson (Water Street) Former Manufactured Gas Plant (MGP) Site located in Hudson, New York. Please refer to the Operation, Maintenance, and Monitoring Plan (OM&M Plan), January 2007 and the CDM memorandum dated July 30, 2007 for quarterly well monitoring, annual sampling, quarterly site inspection requirements, and associated detailed site conditions and groundwater flow pattern documentation.

Background

The Hudson (Water Street) Former Manufactured Gas Plant Site located in Hudson, New York is comprised of approximately two acres of land and is owned by National Grid (refer to Attachment A for Figure 1 - Location Map and Figure 2 - Post Remediation Site Conditions). The remedial action plan in place at the site was substantially completed in December 2006 and the OM&M Plan was finalized in January 2007 to provide a method for monitoring its effectiveness.

The objective of the post-construction groundwater monitoring task within the OM&M plan is to characterize post-remedy groundwater flow patterns and assess the quality of shallow groundwater as it leaves the site. Groundwater samples are analyzed for the presence and/or extent of benzene, toluene, ethylbenzene and total xylenes (BTEX) and naphthalene.

Site Inspections and General Maintenance

The annual site inspection was conducted on September 16, 2008. In addition, site inspections were also performed on March 10, 2008 and June 10, 2008. Annual site inspections will continue

Mr. Steven P. Stucker, P.G. October 21, 2008 Page 2

for a five year period and will include inspection of the existing groundwater monitoring wells (MW-02, MW-03, MW-05, MW-06, MW-07, MW-08A, MW-09A, MW-10, MW-11, OW-2, OW-4), the three existing DNAPL monitoring wells (RW-1, RW-2, CW-01A), security fencing, and other site features. To date, there have been no public complaints or comments noted by National Grid. The site inspection reports are included in Attachment B.

The site in general, including the surface cover areas, erosion controls, steel sheet pile retaining wall and trees, shrubs and other planting materials are in good condition. In July 2008, riprap was installed along the Hudson River bank (near RW-1) due to minor settlement and erosion. National Grid's OM&M contractor will continue to note additional settlement and/or erosion.

DNAPL Monitoring and Collection

Quarterly DNAPL monitoring took place over the last year on the following dates; December 1, 2007, March 10, 2008, June 10, 2008 and September 16, 2008. No DNAPL was recovered from any of the wells during any of these events. However, during the December 1, 2007 monitoring at well CW-01A, a slight odor was noted. The DNAPL monitoring and collection reports are included in Attachment B.

As stated in the OM&M Plan, quarterly DNAPL monitoring was required for a period of at least one year for RW-1, RW-2, and CW-01A. If DNAPL was present, the depth to the DNAPL surface from the top of the well casing was to be measured and recorded. DNAPL would be collected and disposed of off-site as necessary. If DNAPL does not accumulate in any of the wells at a thickness more than 0.1 foot within the first year or the rate of DNAPL production for each well does not exceed two gallons per year, with the rate measured over the period of one year, the program will be completed.

After the initial one year monitoring period the DNAPL program was evaluated. Due to no recovery of DNAPL over the last four monitoring periods the DNAPL monitoring program will be terminated.

Site Monitoring Wells

The site monitoring wells include: MW-02, MW-03, MW-05, MW-06, MW-07, MW-08A, MW-09A, MW-10, MW-11, OW-2, OW-4, CW-01A, RW-1 and RW-2. Only monitoring wells MW-03, MW-05, MW-06 and MW-11 were sampled for site constituents. Well locations are shown on the Site Plan in Attachment A.

Well Gauging

All wells listed in the section above, as well as the level of the Hudson River, were gauged prior to groundwater sampling on June 10th. The water level elevation (feet above mean sea level (amsl) ranged from 1.77 feet amsl at MW-02, to 7.97 feet amsl at CW-01A. The wells were gauged again on September 19, 2008 during the site inspection. The water elevation ranged from 0.77 feet amsl at RW-1, to 8.02 feet amsl CW-01A. The groundwater direction continues appears to remain in a south/southeast direction as shown on previous groundwater contour

Mr. Steven P. Stucker, P.G. October 21, 2008 Page 3

figures. A summary of all static water level measurements collected at the site is included in Attachment B.

Groundwater Sampling

Groundwater samples were collected from monitoring wells MW-03, MW-05, MW-06 and MW-11. The wells were purged using a peristaltic pump. Field Measurements of pH, conductivity, turbidity, dissolved oxygen, temperature, total dissolved solids and oxidation-reduction potential were recorded using a Horiba water quality meter during sample collection. Samples were collected once field parameters had been stabilized. Well purging data is included in Attachment B.

Four aqueous samples and a field duplicate were processed for BTEX, and naphthalene by the USEPA SW486 method 8260B, with additional QC requirements of the NYSDEC ASP. A trip blank was also analyzed. The samples were sent to Test America (formerly Severn Trent Laboratories, Inc.) of Buffalo, New York in accordance with the NYSDEC Analytical Services Protocol. The chain-of-custody record is included in Attachment B.

After the initial five year monitoring period has been completed, the collected data will be evaluated to determine whether the program should be continued and/or if any modifications are necessary. According to the OM&M Plan, the program will be complete if it is demonstrated that chemicals of potential concern (COPC's) are not migrating offsite through the groundwater at concentrations higher than the New York State Ambient Water Quality Standards (NYSAWQS). The program may be discontinued if the concentrations of COPC's in samples collected are below the NYSAWQS for two consecutive years starting with the fourth year of the five year program. If the standards are not met at this time, the program will be continued until concentrations of COPC are below the standards for two consecutive years.

Groundwater Analytical Results

There was no BTEX or naphthalene detected in the samples from monitoring wells MW-03, MW-05 and MW-06. However, benzene, ethylbenzene and o-xylene were detected in MW-11. Both benzene and ethlybenzene were detected above the NYSAWQS in monitoring well MW-11. Summarized laboratory results are included in Attachment C.

Data Validation

The analytical data report provided by Test America was sent to Data Validation Services of North Creek, New York for third party data validation. The primary objective of the data validation was to identify any questionable or invalid laboratory processes or data. The data validation company generated the Data Usability Summary Report (DUSR) from review of the summary form information, with review of sample raw data and limited review of the associated QC raw data, as required for the DUSR validation package.

The review completed by Data Validation Services stated that the field sample analyte values/reporting limits are usable as reported. The data validation report (with qualified laboratory report forms) is included in Attachment D.

Mr. Steven P. Stucker, P.G. October 21, 2008 Page 4

Conclusions and Recommendations

The data collected from the June 2008 sampling event indicate that there are three contaminants of concern (benzene, ethylbenzene and o-xylene) at well MW-11 with benzene and ethylbenzene above the NYSAWQS. In addition, total xylenes and naphthalene detected at this well during August 2007 was not detected during the June 2008 event. Additionally, from the August 2007 to the June 2008 sampling event, benzene levels were reduced from 12 ug/L to 3.8 ug/L and ethylbenzene levels were reduced from 16 ug/L to 8 ug/L. MW-11 is located to the west of the brick warehouse, sampling and monitoring will continue at this location.

Since inception of the well monitoring, no DNAPL has been noted in any site well. Therefore, CDM recommends discontinuing the DNAPL quarterly monitoring at the site. The remaining groundwater monitoring program and maintenance activities, as described in the OM&M Plan dated January 2007 will be continued.

If you have any questions relating to these sampling events or our recommendations, please do not hesitate to contact me at 315-434-3256.

Very truly yours,

Matthew D. Millias, P.E.


Matthew D. Millias


Senior Project Manager

Camp Dresser & McKee

Cc: Tim Beaumont - CDM

Attachment A Site Maps







LEGEND:

PROPERTY TIME

MAJOR CONTOUR LINE

MINOR CONTOUR LINE

APPROXIMATE EDGE OF WATER

(VARIES WITH TIDE)

TOWN FENCE

RICH FENCE

RIPRAP

CRUSHED STONE

CONCRETE

ASPHALT/PAVEMENT

VEGETATED AREA

STAMPED CONCRETE

GRASSCRETE PAWNG

DECIDICUS TREE

GROUNDWATER WATER-LEVEL

MONITORING WELL

NW-12 MONITORING WELL

RW-1 Q MAPL COLLECTION/RECOVERY

WELL

TROSH BIN

HINO

LIANDHOLE

UNCOLLECTION MAPCLE

U

NOT

 SURVEY DATA WAS OBTAINED FROM SURVEYS BY C.T. MALE ASSOCIATES, DATED AUGUST 23, 2005 AND NOVEMBER 15, 2005, DRAWING FILES F-ASRUELLDWG AND W-ASBUILTIONG, RESPECTIVELY



NATIONAL GRID HUDSON (WATER STREET)

POST REMEDIATION SITE CONDITIONS

CDM

Figure 2

Attachment B Inspection and Monitoring Forms

Site Inspection Hudson-Water Street Operable Unit 1 Hudson, New York

Date:	3/10/2008	Time:	1045
Technician:	Beaumont	Weather:	Sunny 30's

Surface Cover Areas					
Excessive Settlement Observed	YES	NO	COMMENTS:		
Cracks or Potholes Observed	YES	NO			
Depressions and/or Rutting Observed	YES	NO			
Exposed subbase materials Observed	YES	NO			

Erosion Controls (Rip-Rap or Sod)				
Exposed or damaged Geotextile layer(s) Observed	YES	NO	COMMENTS:	
Excessive Settlement Observed	YES	NO		
Stressed Vegetation Observed	YES	NO		

Steel Sheetpile Retaining Wall				
Settlement of Wall	YES	NO	COMMENTS:	
Subsidence or Cracking of Soils Behind the Wall	YES	NO		
Cracking or Separation of Wall Joints	YES	NO		

Trees, Shrubs and other Planting Materials						
Strong Growth Observed	YES	NO	COMMENTS:			

Surface Water Quality						
Sheens Observed On:	Rip-Rap	NONE	MINOR	SIGNIFICANT	COMMENTS:	
	Sheetpile Wall	NONE	MINOR	SIGNIFICANT		
	Other Water Surfaces	NONE	MINOR	SIGNIFICANT		

General Comments:

There is a flat bed trailer staged in the corner of the fenced in area.

There is a lot of debris washed up on the lawn.

The gate to the warehouse needs repair. Looks to have been opened backwards and needs adjustment. It is secure.

There is some rip-rap erosion near RW-1.

Site Inspection Hudson-Water Street Operable Unit 1 Hudson, New York

Date:	6/10/2008	Time:	800
Technician:	Beaumont	Weather:	Sunny 80's

	Surface Cover Are	as		
Excessive Settlement Observed	YES	NO	COMMENTS:	·
Cracks or Potholes Observed	YES	NO		
Depressions and/or Rutting Observed	YES	NO		
Exposed subbase materials Observed	YES	NO		

Erosion Controls (Rip-Rap or Sod)				
Exposed or damaged Geotextile layer(s) Observed	YES	NO	COMMENTS:	
Excessive Settlement Observed	YES	NO		
Stressed Vegetation Observed	YES	NO		

Steel Sheetpile Retaining Wall				
Settlement of Wall	YES	NO	COMMENTS:	
Subsidence or Cracking of Soils Behind the Wall	YES	NO		
Cracking or Separation of Wall Joints	YES	NO		

Trees, Shrubs and other Planting Materials						
Strong Growth Observed YES NO COMMENTS:						

Surface Water Quality					
Sheens Observed On:	Rip-Rap	NONE	MINOR	SIGNIFICANT	COMMENTS:
	Sheetpile Wall	NONE	MINOR	SIGNIFICANT	
	Other Water Surfaces	NONE	MINOR	SIGNIFICANT	

General Comments:

There is some rip-rap erosion near RW-1.

Asplundh will be repairing the rip-rap area .

Site Inspection Hudson-Water Street Operable Unit 1 Hudson, New York

Date:	9/16/2008	Time:	1300
Technician:	Beaumont	Weather:	Sunny 70's

Surface Cover Areas									
Excessive Settlement Observed	YES	NO	COMMENTS:						
Cracks or Potholes Observed	YES	NO_							
Depressions and/or Rutting Observed	YES	NO							
Exposed subbase materials Observed	YES	NO							

Erosion Controls (Rip-Rap or Sod)										
Exposed or damaged Geotextile layer(s) Observed	YES	NO	COMMENTS:							
Excessive Settlement Observed	YES	NO	some rip rap settling along grassline.							
Stressed Vegetation Observed	YES	NO								

Steel Sheetpile Retaining Wall										
Settlement of Wall	YES	NO	COMMENTS:							
Subsidence or Cracking of Soils Behind the Wall	YES	NO								
Cracking or Separation of Wall Joints YES NO										

Trees, Shrubs and other Planting Materials									
Strong Growth Observed	YES	NO	COMMENTS:						

Surface Water Quality										
Sheens Observed On:	Rip-Rap	NONE	MINOR	SIGNIFICANT	COMMENTS:					
	Sheetpile Wall	NONE	MINOR	SIGNIFICANT						
	Other Water Surfaces	NONE	MINOR	SIGNIFICANT						

General Comments:

Asplundh repaired the rip-rap area near RW-1.

National Grid Water Street-Operable Unit 1 Hudson, New York

Well ID.	Sample?	Well Size	Well Material	Stickup- Flush	DTP	DTW	DTP	DTB	Sump ?	Comments
MW-02	No	2"	PVC	Flush		4.78_		20.50	No	
MW-03	No	2"	PVC_	Flush		2.06		25.50	No	
MW-05	No	2"	PVC	Stickup		5.58		28.10	No	
MW-06	No	2"	PVC	Stickup	_	6.03		26.10	Yes	
MW-07	No	2"	PVC	Stickup		2.85		24.55	Yes	
MW-08A	No	2"	PVC	Flush		2.84		25.85	No	
MW-09A	No	2"	PVC	Stickup		5.54		25.07	Yes_	
MW-10	No	2"	PVC	Flush		0.75		28.70	Yes	
MW-11	No_	2"	PVC_	Flush		0.86	···· <u>-</u>	8.10	Yes	
OW-2	No	2"	P <u>V</u> C	Stickup		5.72		27.55	Yes	
OW-4	No	2"	PVC	Stickup		5.35		28.05	Yes	
Hudson River	No					5.80				Chiseled square adjacent to the 8th railing post on top of the sheetpile wall.
CW-01A	No	4"	Steel	Flush		0.78		30.90	Yes	
RW-1	No_	4"	PVC	Flush		4.10		26.50	Yes	
RW-2	No	4"	PVC	Flush		5.10		22.35	Yes	

March 10, 2008

Niagara Mohawk, a National Grid Company Water Street Hudson, New York

Well ID.	Sample?	Well Size	Well Material	Stickup- Flush	DTP	DTW	DTP	DTB	Sump ?	Comments
MW-02		2"	PVC	Flush		4.33		20.50	No	
MW-03		2"	PVC	Flush		2.26		25.50	No	
MW-05		2"	PVC	Stickup		5.69		28.10	No	
MW-06		2"	PVC	Stickup		5.55		26.10	Yes	
MW-07		2"	PVC	Stickup		5.10		24.55	Yes	
MW-08A		2"	PVC	Flush		3.56		25.85	No	
MW-09A		2"	PVC	Stickup		5.45		25.07	Yes	
MW-10		2"	PVC	Flush		2.27		28.70	Yes	
MW-11	_	2"	PVC	Flush		2.75		8.10	Yes	
OW-2		2"	PVC	Stickup		5.82		27.55	Yes	
OW-4		2"	PVC	Stickup		5.45		28.05	Yes	
Hudson River						2.90				Chiseled square adjacent to the 8th railing post on top of the sheetpile wall.
CW-01A		4"	Steel	Flush		1.70		30.90	Yes	slight odor
RW-1		4"	PVC	Flush		2.82		26.50	Yes	
RW-2		4"	PVC	Flush		2.56		22.35	Yes	

Purge water is stored in labeled 5-gallon drums within the fenced area.

June 10 2008

National Grid Water Street-Operable Unit 1 Hudson, New York

	Well ID.	Sample?	Well Size	Well Material	Stickup- Flush	DTP	ртw	DTP	ртв	Sump ?	Comments
	MW-02	No	2"	PVC	Flush		4.40	_	20.50	No	
	MW-03	No	2 ⁿ	PVC	Flush		1.96		25.50	No	
	MW-05	No	2"	PVC	Stickup		5.09		28.10	No	
	MW-06	No	2"	PVC	Stickup		5.27		26.10	Yes	
	MW-07	No	2"	PVC	Stickup		4.53		24.55	Yes	
		No	2"	PVC	Flush		3.42		25.85	No	
	MW-09A	No	2*	PVC	Stickup		5.23		25.07	Yes	
	MW-10	No	2"	PVC	Flush		1.75		28.70	Yes	
	MW-11	No	2"	PVC	Flush		2.35		8.10	Yes	
. [OW-2	No	2"	PVC	Stickup	_	5.20		27.55	Yes	
	OW-4	No	2"	PVC	Stickup		4.96		28.05	Yes	
. [Hudson River	No		-		_	3.72			-	Chiseled square adjacent to the 8th railing post on top of the sheetpile wall.
	CW-01A	No	4"	Steel	Flush		1.65	_	30.90	Yes	slight odor
	RW-1	No	4"	PVC	Flush		4.32		26.50	Yes	
Į	RW-2	No	4"	PVC	Flush		4.18		22.35	Yes	

September 16, 2008

Quarterly DNAPL Monitoring Event (December 1, 2007)

		<u>' </u>					
Well Id.	DTP	DTW	DTP	DTB	Thickness	Amount Recovered	Comments
CW-01A		2.00		30.90	0	0	Slight odor
RW-1_		4.92		26.50	0	0	
RW-2		5.50		22.35	00	0	

Quarterly DNAPL Monitoring Event (March 10, 2008)

	addition of the state of the st												
Well Id.	DTP	DTW	DTP	DTB	Thickness	Amount Recovered	Comments						
CW-01A		0.78		30.90	0	0							
RW-1		4.10		26.50	0	0							
RW-2		5.10		22.35		0							

Quarterly DNAPL Monitoring Event (June 10, 2008)

addition by DNAP E Monitoring Event (dulie 10, 2000)											
Well Id.	DTP	DTW	DTP	DTB	Thickness	Amount Recovered	Comments				
CW-01A		1.70		30.90	0	0					
RW-1		2.82		26.50	0	0					
RW-2		2.56		22.35	0	0					

Quarterly DNAPL Monitoring Event (September 16, 2008)

addition blant a monitoring Event (coptember 10, 2000)									
Well Id.	DTP	DTW	DTP	DTB	Thickness	Amount Recovered	Comments		
CW-01A		1.65		30.90	0	0			
RW-1		4.32		26.50	0	0			
RW-2		4.18		22.35	0	00			

National Grid Water Street, Hudson, New York

Sampling Pe	rsonnel: Tir	n Beaumont			Date:	6/10/08		
Job Number:	36380.64152				Weather:	Sunay	<u>81°</u>	
Well Id.	MW-03				Time In:	950 '	Time Out:	1030
Well In	ormation	<u> </u>						🗀
			TOC	Other	Well Type		—	itick-Up
Depth to Wa		(feet)	2.26		Well Lock		Yes	No
Depth to Pro		(feet)			_	Point Marked:	Yes	No
Depth to Bot		(feet)	25.50		Well Mate		SSOU	
Length of Wa		(feet)	23.24		Well Dian		2" XOth	er:
Volume of W		(gal)	3.72		Comment	is:		
Three Well V	olumes:	(gal)	11.16					
Purging I	nformation	•					Oppusation F	·
D				N			Conversion F	
Purging Meth		Baile			os Pump	gal/ft.	1" ID 2" ID	4" ID 6"
Tubing/Baile		Teflo	k		ethylene	of	0.04 0.16	0.66 1.4
Sampling Me		Baile		Grundfo	os Pump	water		
Average Pun		(ml/min)	250			1 galle	on=3.7 <u>85L=</u> 3785m	L=133/cu. re
Duration of P		(min)	30	ر	v . 🗀 N			
Total Volume	Removed:	(gal)		id well go dry?	Yes No	الكما		
Horiba U-22	Water Quality	Meter Used?	Yes	No 🗌				
Time	DTW	pН	Conductivity	Turbidity	DO	Temp	TDS	ORP
	(feet)		(mS/cm)	(NTU)	(mg/L)	(°C)	(g/L)	(mV)
155	3.60	7.11	1.30	103.0	1.93	1602	(88)	-153
1000	6.50	7,28	1,24	५५८	105	15.70	.8	-164
1005	9.00	7.37	1,23	45.0	0	15.78	182	-165
1010	10.05	7.35	1.22	40-1	0	15.80	. 8	-165
1015	11.02	7.34	1.22	30.7	0	15.85	.8	-164
1020	12.00	7.32	1.22	31.2	0	15.86	٢,	-163
1025	13.02	7.33	1.22	31.8	0	15.88	.8	-161
						<u> </u>		
				_				
	_							
		L	<u></u>			<u> </u>	L	
Sampling In	formation:							
Sampling In	formation:							
	formation: 46 Method 8260	VOC's	BTEX Includir	ng Naphthalene		3 - 40 mL vials	Yes	No□
		VOC's	BTEX Includii	ng Naphthalene		3 - 40 mL vials	Yes	⊠ No □
	46 Method 8260				l s			_
USEPA SW-8 Sample ID:	46 Method 8260 Mい・03-0	⊌08 Di	uplicate?	Yes No X	s	hipped: Drop-of	f Syracus <u>e Se</u> rvic	e Center
USEPA SW-8 Sample ID: Sample Time:	46 Method 8260 MW・03・0	⊌08 Di	uplicate?		S S	hipped: Drop-of F	f Syracuse Servic	e Center UPS
USEPA SW-8 Sample ID:	46 Method 8260 MW・03・0	⊌08 Di	uplicate?	Yes No X	s	hipped: Drop-of	f Syracuse Servic red-Ex Test Am	e Center X UPS erica
SEPA SW-8 sample ID: ample Time:	46 Method 8260 MW・03・0	⊌08 Di	uplicate? S/MSD?	Yes No X	s	hipped: Drop-of F	f Syracuse Servic	e Center X UPS erica

Sampling Per	rsonnel: Tim	Beaumont			Date:	6/10/08	?	
Job Number:	36380.64152				Weather:	Sunay	80°	
Well Id.	MW-05				Time In:	900	Time Out:	945
Well Inf	formation		TOC	Other	Well Type	e: Flus	hmount S	Stick-Up
Depth to Wat	er:	(feet)	5.69		Well Lock	ced:	Yes	No
Depth to Prod	duct:	(feet)			Measuring	Point Marked:	Yes 🔀	No
Depth to Bott	om:	(feet)	28.10		Well Mate	erial: PVC		ner:
Length of Wa		(feet)	22.41		Well Dian	neter: 1"	2" ∑ Ot#	her:
Volume of W	ater in Well:	(gal)	3.59		Commen	ts:		
Three Well V	olumes:	(gal)	10.17					
Duning I	-fotion							
Purging II	nformation					<u> </u>	Conversion F	actors
Purging Meth		Baile	Peristaltic	Grundfo	os Pump	gal/ft.	1" ID 2" ID	
Tubing/Bailer		Teflor	—		ethylene	gavit.	 	
Sampling Me		Baile		· · · · · · · · · · · · · · · · · · ·	os Pump	water	0.04 0.16	0.66 1.47
Average Purr		(ml/min)	250	Z Granon	33 · ap		on=3.785L=3785n	
Duration of P		(min)	30				<u> </u>	,, <u>,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,</u>
Total Volume				d well go dry?	Yes			
					1631			
Horiba U-22	Water Quality I	Meter Used?	Yes	N₀ _				
Time a	DTM		Conductivity	المالية المالية	500	Taman	TDC	000
Time	DTW	pН	Conductivity	Turbidity	DO	Temp	TDS	ORP
	(feet)		(mS/cm)	(NTU)	(mg/L)	(°C)	(g/L)	(mV)
905	(feet) 7.22	7.14	(mS/cm)	(NTU) 54./	(mg/L) /.05	(°C)	(g/L) , 50	(mV) -184
905	(feet) 7.22 7.96	7.14	(mS/cm) ,571 ,764	(NTU) 54./ 48./	(mg/L) /.05 /33	(°C) /360 /3.70	(g/L) , 50	(mV) -184 -192
905 910 115	(feet) 7.22 7.96 8.75	7.14 7.23 7.37	(mS/cm) , 57 f , 76 f , 77 6	(NTU) 54./ 48./ 10.8	(mg/L) /.07 / 33 . ! !	(°C) /360 /3.70 (3.52	(g/L) , 50 , 49 , 48	(mV) -194 -192 -194
905 910 115 920	(feet) 7.22 7.96 8.75 /0.92	7.14 7.23 7.37 7.26	(mS/cm) ,571 ,764 ,746 ,740	(NTU) 54.1 48.1 10.8 3.4	(mg/L) /.07 /.33 .11	(°C) /360 /3.70 /3.52 /1.53	(g/L) , 50 , 49 , 48	(mV) -184 -192 -194 -188
905 910 115 920 925	(feet) 7.22 7.96 8.75 /0.92 /2.25	7.14 7.23 7.37 7.26 7.32	(mS/cm) , 57 r , 76 y , 746 , 740 , 73 y	(NTU) 54.1 48.1 10.8 3.4 4.2	(mg/L) /.07 /.33 .11 0	(°C) /360 /3.70 /3.52 /1.53 /3.57	(g/L) , 50 , 49 , 48 , 47	(mV) -184 -192 -194 -186
905 910 115 920 925 930	(feet) 7.22 7.96 8.75 /0.92 /2.25 /3.60	7.14 7.23 7.37 7.26 7.32 7.36	(mS/cm) ,571 ,764 ,746 ,740 ,734	(NTU) 54./ 48./ 10.8 3.4 4.2	(mg/L) /.07 /.33 .11 0 0	(°C) /360 /3.70 (3.52 /1.53 /3.57 /3.52	(g/L) , yo , yo , yo , yo , yo , yo , yo	(mV) -184 -192 -194 -188
905 910 115 920 925	(feet) 7.22 7.96 8.75 /0.92 /2.25	7.14 7.23 7.37 7.26 7.32	(mS/cm) , 57 r , 76 y , 746 , 740 , 73 y	(NTU) 54.1 48.1 10.8 3.4 4.2	(mg/L) /.07 /.33 .11 0	(°C) /360 /3.70 /3.52 /1.53 /3.57	(g/L) , 50 , 49 , 48 , 47	(mV) -184 -192 -194 -186
905 910 115 920 925 930	(feet) 7.22 7.96 8.75 /0.92 /2.25 /3.60	7.14 7.23 7.37 7.26 7.32 7.36	(mS/cm) ,571 ,764 ,746 ,740 ,734	(NTU) 54./ 48./ 10.8 3.4 4.2	(mg/L) /.07 /.33 .11 0 0	(°C) /360 /3.70 (3.52 /1.53 /3.57 /3.52	(g/L) , yo , yo , yo , yo , yo , yo , yo	(mV) -184 -192 -194 -186
905 910 115 920 925 930	(feet) 7.22 7.96 8.75 /0.92 /2.25 /3.60	7.14 7.23 7.37 7.26 7.32 7.36	(mS/cm) ,571 ,764 ,746 ,740 ,734	(NTU) 54./ 48./ 10.8 3.4 4.2	(mg/L) /.07 /.33 .11 0 0	(°C) /360 /3.70 (3.52 /1.53 /3.57 /3.52	(g/L) , yo , yo , yo , yo , yo , yo , yo	(mV) -184 -192 -194 -186
905 910 115 920 925 930	(feet) 7.22 7.96 8.75 /0.92 /2.25 /3.60	7.14 7.23 7.37 7.26 7.32 7.36	(mS/cm) ,571 ,764 ,746 ,740 ,734	(NTU) 54./ 48./ 10.8 3.4 4.2	(mg/L) /.07 /.33 .11 0 0	(°C) /360 /3.70 (3.52 /1.53 /3.57 /3.52	(g/L) , yo , yo , yo , yo , yo , yo , yo	(mV) -184 -192 -194 -186
905 910 115 920 925 930	(feet) 7.22 7.96 8.75 /0.92 /2.25 /3.60	7.14 7.23 7.37 7.26 7.32 7.36	(mS/cm) ,571 ,764 ,746 ,740 ,734	(NTU) 54./ 48./ 10.8 3.4 4.2	(mg/L) /.07 /.33 .11 0 0	(°C) /360 /3.70 (3.52 /1.53 /3.57 /3.52	(g/L) , yo , yo , yo , yo , yo , yo , yo	(mV) -184 -192 -194 -186
905 910 115 920 925 930	(feet) 7.22 7.96 8.75 /0.92 /2.25 /3.60	7.14 7.23 7.37 7.26 7.32 7.36	(mS/cm) ,571 ,764 ,746 ,740 ,734	(NTU) 54./ 48./ 10.8 3.4 4.2	(mg/L) /.07 /.33 .11 0 0	(°C) /360 /3.70 (3.52 /1.53 /3.57 /3.52	(g/L) , yo , yo , yo , yo , yo , yo , yo	(mV) -184 -192 -194 -186
905 910 115 920 925 930 735	(feet) 7.22 7.96 8.75 /0.92 /2.25 /3.60 /Y.02	7.14 7.23 7.37 7.26 7.32 7.36	(mS/cm) ,571 ,764 ,746 ,740 ,734	(NTU) 54./ 48./ 10.8 3.4 4.2	(mg/L) /.07 /.33 .11 0 0	(°C) /360 /3.70 (3.52 /1.53 /3.57 /3.52	(g/L) , yo , yo , yo , yo , yo , yo , yo	(mV) -184 -192 -194 -186
905 910 115 920 925 930	(feet) 7.22 7.96 8.75 /0.92 /2.25 /3.60 /Y.02	7.14 7.23 7.37 7.26 7.32 7.36	(mS/cm) ,571 ,764 ,746 ,740 ,734	(NTU) 54./ 48./ 10.8 3.4 4.2	(mg/L) /.07 /.33 .11 0 0	(°C) /360 /3.70 (3.52 /1.53 /3.57 /3.52	(g/L) , yo , yo , yo , yo , yo , yo , yo	(mV) -184 -192 -194 -186
905 910 115 920 925 930 735	(feet) 7.22 7.96 8.75 /0.92 /2.25 /3.60 /Y.02	7.14 7.23 7.37 7.26 7.32 7.36 7.35	(mS/cm) ,57 r ,76 r ,776 ,779 ,737 ,737	(NTU) 54./ 48./ 10.8 3.9 4.2 3.8 3.2	(mg/L) /.05 /.33 .11 0 0 0	(°C) /360 /3.70 (3.52 /3.53 /3.51 /3.52 /3.53	(g/L) , 50 , 49 , 48 , 47 , 47 , 47	(mV) -184 -192 -194 -186 -186 -187
905 910 115 920 925 930 735	(feet) 7.22 7.96 8.75 /0.92 /2.25 /3.60 /Y.02	7.14 7.23 7.37 7.26 7.32 7.36 7.35	(mS/cm) ,57 r ,76 r ,776 ,779 ,737 ,737	(NTU) 54./ 48./ 10.8 3.4 4.2	(mg/L) /.05 /.33 .11 0 0 0	(°C) /360 /3.70 (3.52 /1.53 /3.57 /3.52	(g/L) , 50 , 49 , 48 , 47 , 47 , 47	(mV) -184 -192 -194 -186
905 910 115 920 925 930 735 Sampling In:	(feet) 7.22 7.96 8.75 /0.92 /2.25 /3.60 /Y.02 formation:	7.14 7.23 7.37 7.26 7.32 7.36 7.35	(mS/cm) , 57 r , 76 y , 776 , 779 , 739 , 731 , 737	(NTU) 59./ 48./ 70.8 3.9 4.2 3.1 3.2-	(mg/L) /. 0 \(\) / 3 \(\) . 11 0 0 0 0	(°C) /3.60 /3.70 /3.52 /3.57 /3.52 /3.53 6 - 40 mL vials	(g/L) , yo , yo , yo , yo , yo , yo , yo	(mV) -184 -194 -194 -186 -184 -182
905 900 115 920 920 930 735 Sampling In: USEPA SW-84 Sample ID:	(feet) 7.22 7.96 8.75 /0.92 /2.25 /3.60 /Y.02 formation: 46 Method 8260	7.14 7.23 7.37 7.26 7.32 7.36 7.35	(mS/cm) , 57 r , 76 f , 776 , 7790 , 739 , 731 , 737 , 737 BTEX Includir	(NTU) 5Y./ 48./ 70.¥ 3.9 4.2 3.8 3.2- mg Naphthalene Yes No	(mg/L) /.05 /.33 .11 0 0 0 0 FD-0608 S	(°C) /3.60 /3.70 /3.52 /3.57 /3.52 /3.53 6 - 40 mL vials	(g/L) , Yo	(mV) -184 -192 -194 -186 -186 -187 -182
905 910 115 920 925 930 735 Sampling In:	(feet) 7.22 7.96 8.75 /0.92 /2.25 /3.60 /Y.02 formation:	7.14 7.23 7.37 7.26 7.32 7.36 7.35	(mS/cm) , 57 r , 76 f , 776 , 7790 , 739 , 731 , 737 , 737 BTEX Includir	(NTU) 59./ 48./ 70.8 3.9 4.2 3.1 3.2-	(mg/L) /.05 /.33 .11 0 0 0 0 FD-0608 S	(°C) /3.60 /3.70 /3.52 /3.57 /3.52 /3.53 6 - 40 mL vials	(g/L) , yo , yo , yo , yo , yo , yo , yo	(mV) -184 -194 -194 -186 -184 -182
905 900 115 920 920 930 735 Sampling In: USEPA SW-84 Sample ID:	(feet) 7.22 7.96 8.75 /0.92 /2.25 /3.60 /Y.02 formation: 46 Method 8260 MW-05-066 935	7.14 7.23 7.37 7.26 7.32 7.36 7.35 VOC's	(mS/cm) , 57 r , 76 f , 776 , 7790 , 739 , 731 , 731 , 737 , 737 BTEX Includir uplicate? S/MSD?	(NTU) 5Y./ 48./ 70.¥ 3.9 4.2 3.8 3.2- mg Naphthalene Yes No	(mg/L) /.05 /.33 .11 0 0 0 0 FD-0608 S	(°C) /3.60 /3.70 /3.52 /3.57 /3.52 /3.53 6 - 40 mL vials	(g/L) , Yo	(mV) -184 -192 -194 -186 -186 -187 -182 SENO CE Center UPS
905 9/0 115 920 925 930 735 Sampling In USEPA SW-8- Sample ID: Sample Time:	(feet) 7.22 7.96 8.75 /0.92 /2.25 /3.60 /Y.02 formation: 46 Method 8260 MW-05-066 935	7.14 7.23 7.37 7.26 7.32 7.36 7.35	(mS/cm) , 57 r , 76 f , 776 , 7790 , 739 , 731 , 731 , 737 , 737 BTEX Includir uplicate? S/MSD?	(NTU) 5Y./ 48./ 70.¥ 3.9 4.2 3.8 3.2- mg Naphthalene Yes No	(mg/L) /.05 /.33 .11 0 0 0 0 FD-0608 S	(°C) /3.60 /3.70 /3.52 /3.57 /3.52 /3.53 6 - 40 mL vials	(g/L) , yo , yg	(mV) -189 -192 -199 -198 -186 -189 -182 s No ce Center UPS merica

National Grid Water Street, Hudson, New York 6/10/08 Date: Sampling Personnel: Tim Beaumont Sonny 79 • Weather: Job Number: 36380.64152 822 Time Out: 205 Time In: Well Id. MW-06 Well Information Stick-Up Well Type: Flushmount TOC Other Depth to Water: (feet) 5.55 Well Locked: Yesl) No Measuring Point Marked: Yes 2 Depth to Product: (feet) 26.10 PVC X SS Depth to Bottom: (feet) Well Material: Other: Other: 2" 20.55 Well Diameter: Length of Water Column: (feet) Volume of Water in Well: 3.29 Comments: (gal) Three Well Volumes: 9.87 (gal) **Purging Information Conversion Factors Purging Method:** 1" ID | 2" ID | 4" ID | 6" ID Bailer Peristaltic X **Grundfos Pump** gal/ft. Tubing/Bailer Material: Stainless St. Polyethylene Teflon of Sampling Method: Bailer X Peristaltic Grundfos Pump water | 0.04 | 0.16 | 0.66 | 1.47 Average Pumping Rate: 250 7 150 🛞 (ml/min) 1 gallon=3.785L=3785mL=1337cu. feet **Duration of Pumping:** (min) 30 Yes No 🗶 Did well go dry? Total Volume Removed: (gal) 42.0 Yes No Horiba U-22 Water Quality Meter Used? pН Conductivity Time DTW Turbidity DO Temp TDS ORP (feet) (mS/cm) (NTU) (mg/L) (°C) (g/L) (mV) 815 91 6.55 1.04 120 13.61 6.15 -112 820 1.70 6.25 1.03 74.2 -105 130 13.61 725 9.80 4.22 59.1 13.68 1.01 ./6 <u>- /n8</u> 10.20 6.18 199 14.02 \$30 **5**7.3 114 -107 **6.2** \ 835 11.62 , 97 . [8 14,20 -105 50.1 6 12.50 840 4.28 96 22 14,32 50. B -/08 6.30 13.22 .96 19 14.31 242 50.2 -//0 Sampling Information: Yes No USEPA SW-846 Method 8260 VOC's BTEX Including Naphthalene 9 - 40 mL vials Sample ID: MW-6-0608 Duplicate? Yes No 2 Shipped: Drop-off Syracuse Service Center Sample Time: 242 MS/MSD? Yes No Fed-Ex **UPS** Comments/Notes: Laboratory: Test America Amherst, New York

no opor no sheen

Sampling Personnel: Tim	Beaumont			Date: 4/10/08						
Job Number: 36380.64152				Weather:	Sunny	820				
Well ld. MW-11				Time In:	1035	Time Out:	1130			
Well Information	-		011	144-U.T.			NS-1-11-			
Depth to Water:	/fact)	70C	Other	Well Type Well Lock		hmount Yes	Stick-Up No			
Depth to Product:	(feet)				Point Marked:	Yes	No			
Depth to Bottom:	(feet)	8.10		Well Mate		-	ner:			
Length of Water Column:	(feet)	5.35		Well Dian		2" \ Ott				
Volume of Water in Well:	(gal)	, 26		Comment	-					
Three Well Volumes:	(gal)	2.58								
Purging Information						Conversion F	actors			
Purging Method:	Baile	r Peristaltic	Grundfo	s Pumn	gal/ft.	1" ID 2" ID				
Tubing/Bailer Material:	Teffor	F-1	_	ethylene	gai/it.	1 15 2 15	1 10 10 12			
Sampling Method:	Baile		Grundfo		water	0.04 0.16	0.66 1.47			
Average Pumping Rate:	(ml/min)	300				on=3.785L=3785n	·			
Duration of Pumping:	(min)	30			ga					
Total Volume Removed:	(gai) -		d well go dry?	Yes No						
Horiba U-22 Water Quality M			No D			_				
Time DTW	рН	Conductivity	Turbidity	DO	Temp	TDS	ORP			
(feet)		(mS/cm)	(NTU)	(mg/L)	(°C)	(g/L)	(mV)			
1040 5.80	7.14	1.32	127.0	1.21	1691	.8	-113			
1045 2.80	7.09	1.13	74.2	પા	14.74	.7	-125			
1050 2.80	7.15	1.00	50.6		16.86	6	- 140			
1057 2.80	<u> 7.19</u>	198	24.2	0	16.92	.6	-/63			
المصعدان	7.07	07		_						
1100 2.80		.98	15.1	0	16.95	.6	-171			
100 2.80	7.09	.97	12.2	0	16.96	.6	-171			
					/6.95 /6.96 /896		-171			
1105 2.80	7,09	.97	12.2	0	16.96	. 6	-171			
1105 2.80	7,09	.97	12.2	0	16.96	. 6	-171			
1105 2.80	7,09	.97	12.2	0	16.96	. 6	-171			
1105 2.80	7,09	.97	12.2	0	16.96	. 6	-171			
1105 2.80	7,09	.97	12.2	0	16.96	. 6	-171			
107 2.80	7,09	.97	12.2	0	16.96	. 6	-171			
1105 2.80	7,09	.97	12.2	0	16.96	. 6	-171			
107 2.80	7,09	,97	12.2	0	16.96	, 6 f	-171			
Sampling Information:	7.10 7.10 VOC's	BTEX Including	12. 2	0	3 - 40 mL vials	Yes	-171 -180 -185			

Chain of Custody Record



TAL-4142 (0907)						1-11							L.,					11/4			1,41						
Client		Project	Mana	ager	1	199	1	U	111	16	5							Dai	e//	101	107	7			of Custody I	lumber 79	
Address / Briss Mohrs Price		Teleph			Stor January	ea Coo	The second second	x Nu	mber	T	4	163	3 5	-/0	00			Lat	Nun	nber				Page	, //	_ of	1
City State Zip	Code 32-06	Site Co			UNIO	at	Lat	Con	_								Ana	alysis e spa	(At	tach s ne	list i	1)					
Project Name and Location (State)	· 1.4.	Carrier	Wayt	bill No	umber		UV.	5	DC C	1	elv	Ten		FX3	Park				1		1				Special	Instructio	ons/
Contract/Purchase Order/Quole No					latrix	1			Con	taine	ers	&		0 B6	tha l											ns of Red	
Sample I.D. No. and Description (Containers for each sample may be combined on one line)	Date	Time	Aur	Aqueous	Sed	io No	Unpres	HZSON	HNO3	HCI	NaOH	ZnAc/	NaOn I	200	Aroh					1							
HW63-0608	6/10/08	1025		X						3				X													
Flu 05-0608		935		X						3				X													
MENTER BOWD DO WILL		845		X						9				X					1								
MW-11-0408		1110		X						3				X												7	
File Duo8	4	-		X						3				X													
Tru Plank	5/19/08	_		X						1				X											, William	N. I	
	20.11.04										920						-			1							
	NV .											T							1							7211	
				1															1	7						-	
					1													+		1			H				
						+	-												1		+					H-D-	
				-	1 2	1			- 199.0	-//-		-						+	+	+	+						
Possible Hazard Identification			IS	amole	e Disp	osal	_					_	1		_				_	1	1			1			
	Poison B	☐ Unknown	1		1 37	o Cliei	11	of a	Dispo	sal E	By L	ab		Arch	nive I	For _		_ N	lonth:	s 10			e asse I mont		f samples are	retained	
Turn Around Time Required	THE !			7.77		all In	T is						pecify						- 9						18 10 15		
24 Hours 48 Hours 7 Days 14 Da	ays 21 Day	ys Ou	her	5	277)		_			Co	W	1	13														
I Relinquished By		Date	107		Time	15		1. F	Recei	ved i	By	Ta.	and a	134	in the				No.					Dal	e /	Time	
2 Relinquished By		Date			Time			2 F	Recei	ved i	Ву		*	N. S.										Dal	e	Time	
3 Relinquished By		Date			Time			3 F	Recei	ved i	Ву													Dal	е	Time	
Comments										X = 3	200									-					Rith		

Hudson (Water Street) Static Water Level Measurements

	Top of Inner		Depth to Water (feet)											Vater Level	Elevation	(feet amsl)							
M/cil (D	(feet arnst)	6/11/2007	6/20/2007	6/26/2007	7/24/2007	8/14/2007	6/19/2007	9/13/2007	12/1/2007	3/10/2008	6/10/2008	9/16/2008	6/11/2007	6/20/2007	6/26/2007	7/24/2007	8/14/2007	8/19/2007	9/13/2007	12/1/2007	3/10/2008	6/10/2008	9/16/2008
WW 02	6 IU	4.37	4 15	5 15	431	4 14	4 33	4 38	4.87	4 78	4.33	4.40	1 73	1 95	0 95	1 79	1 96	1 77	1 72	1 23	1 32	1 77	1 70
MW uJ	8.97	231	2.25	3 69	2 10	1 87	2 01	2.37	2.38	2 06	2 26	1.96	6 66	6.72	5 28	6.87	7 10	6.96	6 60	6 59	691	671	7 ט
MW u5	12.57	5 90	5 60	6 87	5 75	5 55	5 70	5 67	5 45	5 58	5 69	5.09	6 67	6 97	5 70	6 82	7 02	6 87	6 90	7 12	6 99	6 88	7 48
M W-UG	11 83	5 55	5 20	5 52	5 49	5 37	5 54	5 60	5 68	6.03	5 55	5.27	6 29	6 64	6 32	6 35	6 47	6.30	6 24	616	581	6 29	6 57
MW-07	8 94	טו כ	4 85	5 08	5 40	5 38	5 55	5.29	4.18	2 85	5.10	4.53	3 84	4 09	3.86	3.54	3 56	3.39	3 65	4 76	6 09	3 84	441
ABO WIA	داز با	3.47	× 90	3 85	3 74	3 62	3.84	3.75	3 48	2 84	3.56	3.42	2.89	3 46	251	2 62	2 74	2 52	261	2 88	3 52	2 80	2 94
Net Ast	810	5 48	5.25	5 56	5 29	5 15	5 15	5 27	5 55	5 54	5 45	5 23	2.92	3 15	2 84	3 11	3 25	3 25	3 13	2 85	2 86	2 95	3 17
AIW IU	207	1.70	16)	2 17	1 12	2 20	2 38	1 52	2 10	0 75	2 27	1 75	6 99	7 08	6 52	7 57	6.49	631	7 17	6 59	7 94	6 42	6 94
IVIVV 11	957	2 150	∠81	3 12	2 94	3 36	3 53	2 77	2.42	0.86	2.75	2 35	6 77	6.76	6.45	6 63	621	6 04	6 80	7 15	871	6 82	7 22
UW-2	17.192	5 89	5 72	6 34	5 8 5	5 70	5 83	5 57	5 60	5 72	5 82	5 20	6 93	7 10	5 88	6 97	7 12	6.99	7 25	7 22	7 10	7 00	7 62
OM-4	12 60	5 52	5 33	6 00	5 48	5 34	5 50	5.42	5.28	5 35	5 45	4.96	7.14	7.33	6 66	7.18	7 32	7 16	7 24	7 38	7 31	7 21	7 70
Hod Jon Hiver	5.49	4 45	نا د	4 75	4 80	6 15	4 00	5 50	6 03	5 80	2 90	3.72	0 84	2 19	0.54	0 49	-0 86	1 29	-0 21	-0 74	-051	2 39	1 57
CWDIA	96/	2 12	IVd	ı√a	iva	ı√a	r/a	1 65	2 00	0.78	1.70	1.65	7 55	ıva	n/a	ıva	ı∀a	n∕a	8 02	7 67	8 89	7 97	8 05
HW I	יי פט	J 60	ı√a	ı√a	IVa	n/a	ıva	4 04	4 92	4 10	2 82	4 32	1 49	ıνa	n/a	ıva	ıva	iVa	1 05	0 17	0 99	2 27	0 77
HW-2	1 7/0	4 00	IVa	ıva	ıva	ινa	iVa	4 11	5 50	5 10	2.56	4 18	0 96	ıva	ıva	ıva	ιVa	n/a	0.85	-0 54	-0 14	2 40	D 78

District

Estimated elevation, well payed over during surveying but discovered presently and can be monitored

atrial Above Wear Sea Level

Attachment C Laboratory Data Summary

National Grid Hudson (Water Street)

Hudson, New York

Analytical Data Summary

Compound	NYSAWQS	Jı	une 2008 E	vent (ug/l	Ĺ)
Compound	(ug/L)	MW-03	MW-05	MW-06	MW-11
Benzene	1	ND	ND	ND	3.8
Toluene	5	ND	ND	ND	ND
Ethylbenzene	5	ND	ND	ND	8
o-Xylene	-	ND	ND	ND	2.4
m/p-Xylenes	_	ND	ND	ND	ND
Xylene (total)	5	ND	ND	ND	ND
Naphthalene	10	ND	ND	ND	ND

ND - Not Detected

NYSAWQS - New York State Aqueous Water Quality Standards

Bolded numbers exceed the NYSAWQS

National Grid Hudson (Water Street) Hudson, New York

Analytical Data Summary

Compound	August 2007 Event (ug/L)									
Compound	MW-03	MW-05	MW-06	MW-07	MW-11					
Benzene	ND	ND	ND	ND	12					
Toluene	ND	ND	ND	ND	ND					
Ethylbenzene	ND	ND	ND	ND	16					
o-Xylene	ND	ND	ND	ND	6.8					
m/p-Xylenes	ND	ND	ND	ND	ND					
Xylene (total)	ND	ND	ND	ND	7.5					
Naphthalene	ND	ND	ND	ND	5.1					

Attachment D Data Validation Report

Data Validation Services

120 Cobble Creek Road P.O. Box 208 North Creek, NY 12853

> Phone 518-251-4429 Facsimile 518-251-4428

September 10, 2008

Matthew Millias CDM One General Motors Dr. Suite 2 Syracuse, NY 13206

RE: Data Usability Summary Report for NMPC-Hudson-Water St site TAL-Buffalo Job No. A08-6791

Dear Mr. Millias:

Review has been completed for the data package generated by TestAmerica Laboratories, Inc. that pertains to samples collected 6/10/08 at the NMPC Hudson Water St. site. Four aqueous samples and a field duplicate were processed for BTEX, and naphthalene by the USEPA SW846 method 8260B, with additional QC requirements of the NYSDEC ASP. A trip blank was also analyzed.

The data packages submitted contain full deliverables for validation, but this usability report is generated from review of the summary form information, with review of sample raw data, and limited review of associated QC raw data. Full validation has not been performed. However, the reported summary forms have been reviewed for application of validation qualifiers, using guidance from the NMPC generic QAPP, USEPA Region 2 validation SOPs, the USEPA National Functional Guidelines for Data Review, and professional judgment, as affects the usability of the data. The following items were reviewed:

- * Laboratory Narrative Discussion
- * Custody Documentation
- * Holding Times
- Surrogate and Internal Standard Recoveries
- * Matrix Spike Recoveries/Duplicate Correlations
- * Field Duplicate Correlations
- * Preparation/Calibration Blanks
- * Control Spike/Laboratory Control Samples
- * CalibrationStandard Responses
- * Instrumental Tunes
- * Instrument IDLs
- * Sample Quantitation and Identification

The items listed above which show deficiencies are discussed within the text of this narrative. All of the other items were determined to be acceptable for the DUSR level review.

In summary, field sample analyte values/reporting limits are usable as reported, with the exception that results for one compound in the samples are considered estimated in quantitative value.

Copies of the laboratory case narratives and the sample identification summary forms are attached to this text, and should be reviewed in conjunction with this report. Also included with this narrative are laboratory sample results forms with the validation qualifiers applied in red.

BTEX by EPA 8260B/NYSDEC ASP

Holding times were met and instrumental tunes are within acceptance ranges. Surrogate and internal standard recoveries are within required limits. Blanks show no contamination.

The matrix spikes of MW-06-0608 show acceptable accuracy and precision values. Blind field duplicate correlations of MW-05-0608 were also with within guidance limits.

Calibrations standards show acceptable responses, with the exception of that for naphthalene in the continuing calibration verification standard (35%D). The results for that compound (all are non-detection) are qualified as estimated ("UJ"), and may have a low bias.

Reporting limits for m,p-xylene and total xylene could be lowered to 1 ug/L.

Data Completeness

Although required of the laboratory deliverables, raw data are not identified with the client ID.

Please do not hesitate to contact me if you have comments or questions regarding this report.

Very truly yours,

Judy Harry

•	
•	
•	VALIDATION QUALIFIER DEFINITIONS
-	
•	
•	
a	
-	
•	
•	

DATA QUALIFIER DEFINITIONS

The following definitions provide brief explanations of the national qualifiers assigned to results in the data review process. If the Regions choose to use additional qualifiers, a complete explanation of those qualifiers should accompany the data review.

- U The analyte was analyzed for, but was not detected above the reported sample quantitation limit.
- J The analyte was positively identified; the associated numerical value is the approximate concentration of the analyte in the sample.
- N The analysis indicates the present of an analyte for which there is presumptive evidence to make a "tentative identification."
- NJ The analysis indicates the presence of an analyte that has been "tentatively identified" and the associated numerical value represents its approximate concentration.
- UJ The analyte was not detected above the reported sample quantitation limit.

 However, the reported quantitation limit is approximate and may or may not represent the actual limit of quantitation necessary to accurately and precisely measure the analyte in the sample.
- R The sample results are rejected due to serious deficiencies in the ability to analyze the sample and meet quality control criteria. The presence or absence of the analyte cannot be verified.

CLIENT and LABORATORY SAMPLE IDS and CASE NARRATIVES

NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION

SAMPLE IDENTIFICATION AND ANALYTICAL REQUEST SUMMARY

LAB NAME: TESTAMERICA LABORATORIES, INC.

CUSTOMER SAMPLE ID	LABORATORY SAMPLE ID	ANALYTICAL REQUIREMENTS							
		VOA GC/MS	BNA GC/MS	VOA GC	PEST PCB	METALS	TCLP HERB	WATER QUALITY	
FD-0608	A8679105	SW8463		-	-	-	-		
MW-03-0608	A8679101	SW8463	ı		-	•	ı	•	
MW-05-0608	A8679102	SW8463	•			-	-	_	
MW-06-0608	A8679103	SW8463	•	-	_	-	-		
MW-11-0608	A8679104	SW8463	-	-	•	•		•	

NYSDEC-1

SAMPLE SUMMARY

			SAMPI	ED	RECEIV	ED CE
LAB SAMPLE ID	CLIENT SAMPLE ID	MATRIX	DATE	TIME	DATE	TIME
A8679105	FD-0608	WATER	06/10/2008	00:00	06/12/2008	09:15
A8679101	MW-03-0608	WATER	06/10/2008	10:25	06/12/2008	09:15
A8679102	MW-05-0608	WATER	06/10/2008	09:35	06/12/2008	09:15
A8679103	MW-06-0608	WATER	06/10/2008	08:45	06/12/2008	09:15
A8679103MS	MW-06-0608	WATER	06/10/2008	08:45	06/12/2008	09:15
A8679103SD	MW-06-0608	WATER	06/10/2008	08:45	06/12/2008	09:15
A8679104	MW-11-0608	WATER	06/10/2008	11:10	06/12/2008	09:15
A8679106	Trip Blank	WATER	06/10/2008	00:00	06/12/2008	09:15

The results presented in this report relate only to the analytical testing and condition of the sample at receipt. This report pertains to only those samples actually tested. All pages of this report are integral parts of the analytical data. Therefore, this report should be reproduced only in its entirety.

SDG NARRATIVE

Job#: A08-6791

Project#: NY7A9595

Site Name: Niagara Mohawk O & M

General Comments

The enclosed data may or may not have been reported utilizing data qualifiers (Q) as defined on the Data Comment Page.

Soil, sediment and sludge sample results are reported on "dry weight" basis unless otherwise noted in this data package.

According to 40CFR Part 136.3, pH, Chlorine Residual, Dissolved Oxygen, Sulfite, and Temperature analyses are to be performed immediately after aqueous sample collection. When these parameters are not indicated as field (e.g. pH-Field), they were not analyzed immediately, but as soon as possible after laboratory receipt.

Sample dilutions were performed as indicated on the attached Dilution Log. The rationale for dilution is specified by the 3-digit code and definition.

Sample Receipt Comments

A08-6791

Sample Cooler(s) were received at the following temperature(s); 6@2.0 °C All samples were received in good condition.

GC/MS Volatile Data

For method 8260, all samples were preserved to a pH less than 2.

The results presented in this report relate only to the analytical testing and condition of the sample at receipt. This report pertains to only those samples actually tested. All pages of this report are integral parts of the analytical data. Therefore, this report should be reproduced only in its entirety.

"I certify that this data package is in compliance with the terms and conditions of the contract, both technically and for completeness, for other than the conditions detailed above. Release of the data contained in this Sample Data package and in the electronic data deliverables has been authorized by the Iaboratory Manager or his/her designee, as verified by the following signature."

Jason R. Kacalski Project Manager

Date

The results presented in this report relate only to the analytical testing and condition of the sample at receipt. This report pertains to only those samples actually tested. All pages of this report are integral parts of the analytical data. Therefore, this report should be reproduced only in its entirety.

QUALIFIED SAMPLE REPORT FORMS

CAMP DRESSER AND MCKEE NIAGARA MOHAWK O & M METHOD 8260 - BIEX + NAPHIHALENE ANALYSIS DATA SHEET

Lab Nam	ne: <u>TestAmerica Laboratories Inc.</u> Contrac	FD-0608
	le: <u>RECNY</u> Case No.: SAS No	
Matrix:	(soil/water) <u>WATER</u>	Lab Sample ID: <u>A8679105</u>
Sample	wt/vol: <u>5.00</u> (g/mL) <u>ML</u>	Lab File ID: <u>S5078.RR</u>
Level:	(low/med) <u>LOW</u>	Date Samp/Recv: 06/10/2008 06/12/2008
% Moist	ure: not dec Heated Purge: N	Date Analyzed: 06/22/2008
GC Colu	mn: <u>ZB-624</u> ID: <u>0.18</u> (mm)	Dilution Factor:1.00
Soil Ex	tract Volume: (uL)	Soil Aliquot Volume: (uL)
	CAS NO. COMPOUND	CONCENTRATION UNITS: (ug/L or ug/Kg) <u>UG/L</u> Q
	71-43-2Benzene 108-88-3Toluene 100-41-4Ethylbenzene 95-47-6	1.0 U 1.0 U

CAMP DRESSER AND MCKEE NIAGARA MOHAWK O & M METHOD 8260 - BTEX + NAPHTHALENE ANALYSIS DATA SHEET

Lab Name: TestAmerica Laboratories Inc. Contract:		MW-03-0	608 ———	
Lab Code: RECNY Case No.: SAS No.:				
Matrix: (soil/water) WATER Lab Sa	mple ID:	<u>A8679101</u>	_	
Sample wt/vol: 5.00 (g/mL) ML Lab Fi	le ID:	S5072.RR		
Level: (low/med) <u>LOW</u> Date S	amp/Recv:	06/10/20	08 <u>06/1</u>	2/2008
% Moisture: not dec Heated Purge: N Date A	nalyzed:	06/22/20	<u>80</u>	
GC Column: <u>ZB-624</u> ID: <u>0.18</u> (mm) Dilution	on Factor:	1.00		
Soil Extract Volume: (uL) Soil A	liquot Vol	ume:	(u	L)
CAS NO. COMPOUND (ug/L or t		UG/L	Q	
71-43-2Benzene 108-88-3Toluene 100-41-4Ethylbenzene 95-47-6		1.0 1.0 1.0 1.0 2.0 3.0	U U U U U	

CAMP DRESSER AND MCKEE NIAGARA MOHAWK O & M METHOD 8260 - BTEX + NAPHTHALENE ANALYSIS DATA SHEET

Tab Name Test America I show towice Tree Continuet.	MW- 05-	-0608	
Lab Name: TestAmerica Laboratories Inc. Contract:		= 	
Lab Code: RECNY Case No.: SAS No.: SDG	No.:		
Matrix: (soil/water) WATER Lab Sample	E ID: <u>A867910</u>)2	
Sample wt/vol: 5.00 (g/mL) ML Lab File I	D: <u>\$5073.R</u>	R	
Level: (low/med) LOW Date Samp/	Recv: <u>06/10/2</u>	008 06/12	2/2008
% Moisture: not dec Heated Purge: N Date Analy	zed: <u>06/22/2</u>	8008	
GC Column: ZB-624 ID: 0.18 (mm) Dilution F	actor:1.0	<u>10</u>	
Soil Extract Volume: (uL) Soil Aliqu	ot Volume:	(u	L)
CONCENTRATION CAS NO. COMPOUND (ug/L or ug/K		Q	
71-43-2Benzene	1.0	ט	
108-88-3Toluene	1.0 1.0	ט	
100-41-4Ethylbenzene 95-47-6o-Xylene	1.0	ן ט	
m/p-Xylenes	2.0	σ	
1330-20-7Total Xylenes	3.0	ַ ע	
91-20-3Naphthalene	1.0	JU UT	

CAMP DRESSER AND MCKEE NIAGARA MOHAWK O & M METHOD 8260 - BTEX + NAPHTHALENE ANALYSIS DATA SHEET'

	Lab Name: TestAmerica Laboratories Inc. Contract:		MW-06-0608	3
•	Lab Code: RECNY Case No.: SAS No.:			
	Matrix: (soil/water) <u>WATER</u>	Lab Sample ID:	A8679103	
	Sample wt/vol:	Lab File ID:	S5074.RR	
	Level: (low/med) <u>LOW</u>	Date Samp/Recv:	06/10/2008	06/12/2008
ł	% Moisture: not dec Heated Purge: N	Date Analyzed:	06/22/2008	
	GC Column: <u>ZB-624</u> ID: <u>0.18</u> (mm)	Dilution Factor:	1.00	
	Soil Extract Volume: (uL)	Soil Aliquot Vol	ume:	(uL)
		CENTRATION UNITS: g/L or ug/Kg) _		Q
	71-43-2Benzene 108-88-3Toluene 100-41-4Ethylbenzene 95-47-6	1	1.0 U 1.0 U 1.0 U 1.0 U 2.0 U 3.0 U 1.0 U	ut

CAMP DRESSER AND MCKEE NIAGARA MOHAWK O & M METHOD 8260 - BTEX + NAPHTHALENE ANALYSIS DATA SHEET

Lab Name: TestAmerica Laboratories Inc. Contract:		MW-11-0608	
Lab Code: RECNY Case No.: SAS No.:		<u> </u>	
Matrix: (soil/water) <u>WATER</u>	Lab Sample ID:	A8679104	
Sample wt/vol:	Lab File ID:	S5077.RR	
Level: (low/med) <u>LOW</u>	Date Samp/Recv:	06/10/2008 06/1	2/2008
% Moisture: not dec Heated Purge: N	Date Analyzed:	06/22/2008	
GC Column: <u>ZB-624</u> ID: <u>0.18</u> (mm)	Dilution Factor	:1.00	
Soil Extract Volume: (uL)	Soil Aliquot Vo	lume: (u	L)
	NCENTRATION UNITS ug/L or ug/Kg)	_	
71-43-2Benzene 108-88-3Toluene 100-41-4Ethylbenzene 95-47-6		3.8 1.0 8.0 2.4 2.0 U	
91-20-3Narhthalene		1.0	

CAMP DRESSER AND MCKEE NIAGARA MOHAWK O & M METHOD 8260 - BTEX + NAPHTHALENE ANALYSIS DATA SHEET

Lab Name: <u>TestAmerica Lab</u> oratories	Inc. Contract:		Trip	stank	
Lab Code: RECNY Case No.:					
Matrix: (soil/water) WATER		Lab Sample ID:	<u>A867910</u>	06	
Sample wt/vol: $\underline{5.00}$ (g/mL)	<u>ML</u>	Lab File ID:	S5079.R	R	
Level: (low/med) <u>LOW</u>		Date Samp/Recv:	06/10/2	008 <u>06/1</u>	2/2008
% Moisture: not dec Heated	l Purge: <u>N</u>	Date Analyzed:	06/22/2	8008	
GC Column: <u>ZB-624</u> ID: <u>0.18</u> (m	rm)	Dilution Factor	:1.0	00	
Soil Extract Volume: (uL)		Soil Aliquot Vo	olume:	(u	L)
CAS NO. COMPOUND		INCENTRATION UNITS (ug/L or ug/Kg)	_	Q	
71-43-2Benzene 108-88-3Toluene 100-41-4Ethylbenzene 95-47-6	es		1.0 1.0 1.0 2.0 3.0	n (172) n n n	