


2002 Annual Report


Colesville Landfill,
Broome County, New York
NYSDEC Site 704010





Infrastructure, buildings, environment, communications



ARCADIS



Kenneth Zegel
Staff Engineer

David E. Stern
Project Hydrogeologist

Steven M. Feldman
Project Director

2002 Annual Report

Colesville Landfill,
Broome County, New York
NYSDEC Site 704010

Prepared for:
Broome County Division of Solid Waste
Management

Prepared by:
ARCADIS G&M, Inc.
88 Duryea Road
Melville
New York 11747
Tel 631 249 7600
Fax 631 249 7610

Our Ref.:
NY000949.00014.00004

Date:
15 May 2003

This document is intended only for the use of the individual or entity for which it was prepared and may contain information that is privileged, confidential, and exempt from disclosure under applicable law. Any dissemination, distribution, or copying of this document is strictly prohibited.

1. Introduction	1
2. Summary of Groundwater Remediation Activities	1
3. Summary of Monitoring Program	2
3.1 Environmental Effectiveness Monitoring	2
3.2 Groundwater Remediation System Performance Monitoring	3
4. Methodology	4
4.1 Water-Level Measurements	4
4.2 Groundwater Sampling	5
4.3 Spring Water and Surface Water Sampling	5
4.4 Remedial System Performance Monitoring	5
4.4.1 PT System Performance Monitoring	5
4.4.2 ARI System Performance Monitoring	6
5. Groundwater Flow	6
6. Water Quality	6
6.1 Baseline Groundwater Sampling Event	7
6.1.1 Volatile Organic Compounds	7
6.1.2 Indicators of Reducing Conditions	8
6.1.3 Evidence of Biodegradation	8
6.2 Groundwater Monitoring (Quarter Number 1)	9
6.2.1 Volatile Organic Compounds	9
6.2.2 Indicators of Reducing Conditions	9
6.2.3 Evidence of Biodegradation	10
6.3 Spring Water Monitoring	10
6.4 Surface Water Monitoring	10

7.	Groundwater Remediation System Performance	11
7.1	PT System	11
7.1.1	Summary of Operation, Maintenance, and Monitoring	11
7.1.2	Results of Performance Sampling	11
7.2	ARI System	12
7.2.1	Summary of Operation, Maintenance, and Monitoring	12
7.2.2	Results of Performance Sampling	13
8.	Conclusions	14
9.	Recommendations	16
10.	Project Schedule	16
11.	References	17

Tables

- 1 Water-Level Measurements Collected on, July 22 and December 9, 2002, Colesville Landfill, Broome County, New York.
- 2 Concentrations of Volatile Organic Compounds Detected in Groundwater Samples, Baseline and Quarter Number 1 Sampling Rounds, Colesville Landfill, Broome County, New York.
- 3 Concentrations of Selected Metals, General Chemistry and Field Parameters, and Dissolved Gases Detected in Groundwater Samples, Baseline and Quarter Number 1 Sampling Rounds, Colesville Landfill, Broome County, New York.
- 4 Concentrations of Volatile Organic Compounds and Selected Metals Detected in Aqueous Samples Collected from the PT System, Quarter Number 1, Colesville Landfill, Broome County, New York.
- 5 Concentrations of Volatile Organic Compounds Detected in Spring Samples, Baseline and Quarter Number 1 Sampling Rounds, Colesville Landfill, Broome County, New York.
- 6 Concentrations of Selected General Chemistry and Field Parameters Detected in Spring Samples, Baseline and Quarter Number 1 Sampling Rounds, Colesville Landfill, Broome County, New York.

- 7 Concentrations of Volatile Organic Compounds Detected in Surface Water, Baseline Sampling Event, Colesville Landfill, Broome County, New York.
- 8 Concentrations of Selected General Chemistry and Field Parameters Detected in Surface Water, Baseline Sampling Event, Colesville Landfill, Broome County, New York.
- 9 Pump-and-Treat System Quarter Number 1 Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.
- 10 Pump-and-Treat System Mass Removal Rate of Volatile Organic Compounds, Groundwater Remediation System, Colesville Landfill, Broome County, New York.
- 11 Concentrations of Volatile Organic Compounds Detected in Air Stripper Effluent, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Figures

- 1 Water-Level Elevations and Groundwater Flow Direction, July 22, 2002, Colesville Landfill, Broome County, New York.
- 2 Water-Level Elevations and Groundwater Flow Direction, December 9, 2002, Colesville Landfill, Broome County, New York.
- 3 Concentrations of Volatile Organic Compounds in Groundwater, July 2002, Colesville Landfill, Broome County, New York.
- 4 Concentrations of Biogeochemical Indicators in Groundwater and Surface Water, July to December 2002, Colesville Landfill, Broome County, New York.

Appendices

- A Groundwater Remediation System Startup Summary Report, Colesville Landfill, Broome County, New York.
- B Water-Level Measurement and Groundwater Sampling Logs.
- C NYSDEC DAR-1 Air Modeling Data.
- D Automated Reagent Injection System Operating Parameters.

1. Introduction

This 2002 Annual Monitoring Report (Report) was prepared on behalf of Broome County Division of Solid Waste Management for the Colesville Landfill, located in Broome County, New York (site) to evaluate and document long-term monitoring (LTM) activities at the site. Remediation and monitoring activities are being conducted pursuant to the Record of Decision (ROD) and Explanation of Significant Difference (ESD) that were executed in March 1991 and September 2000, respectively. LTM activities (which include environmental effectiveness and remediation system performance monitoring) were performed in accordance with the LTM Plan (ARCADIS G&M, Inc. 2002), which was approved by the United States Environmental Protection Agency (USEPA) and New York State Department of Environmental Conservation (NYSDEC). The LTM Plan provides a detailed description of the LTM program, methodology, and rationale. Where applicable these elements are either summarized or incorporated by reference herein. The LTM discussed in this report includes the baseline event (July 2002) and Quarter Number 1 (September to December 2002). The operation, maintenance, and monitoring (OM&M) performed for the Groundwater Remediation System from September to December 2002 is also discussed in this report.

This report discusses groundwater flow and water quality (groundwater, spring water, and surface water) conditions observed during the Quarter Number 1 and compares the current data to the baseline round, as applicable. In addition, this report describes the OM&M associated with the Groundwater Remediation System through December 2002. Following the detailed data analysis and discussion is a summary of findings, conclusions, and recommendations. The conclusions and recommendations made in this report will continue to be re-evaluated in future reports as additional data become available. Also provided is the LTM and Groundwater Remediation System OM&M schedule for the forthcoming quarter.

2. Summary of Groundwater Remediation Activities

This section provides a chronology of remedial system construction and startup and summarizes the components and function of the Groundwater Remediation System.

The chronology of Groundwater Remediation System construction and startup is as follows: Injection well and monitoring well drilling was conducted between September 11, 2000 and November 3, 2000. Groundwater Remediation System construction was conducted between May 13, 2002 and October 4, 2002. The

Groundwater Remediation System full system startup was completed on September 8, 2002. The final system inspection was conducted on October 4, 2002. All construction activities associated with the Groundwater Remediation System were conducted in accordance with the NYSDEC approved Groundwater Remediation System Technical Design Drawings and Technical Specifications, and as described in the July 2000 report (ARCADIS G&M, Inc. 2000).

The Groundwater Remediation System consists of two components: 1) A groundwater recovery system (i.e., pump and treat [PT] system); and, 2) An automated reagent injection (ARI) system. The PT system consists of wells that pump groundwater at a total rate of approximately 1 gallon per minute (gpm). The wells supply extracted groundwater to the treatment building where it is treated by air stripping and filtration. The treated effluent is then either utilized as part of the ARI process or is discharged to the existing drainage swale that discharges to the North Stream (Figure 1). The ARI system utilizes a molasses and treated groundwater water mixture that is sequentially injected via a line of 17 injection wells (designated as IW-1 through IW-15, PW-6, and GMMW-1). Depending on the results of the effectiveness and performance monitoring conducted (see Sections 6 and 7 of this report, respectively), the amount, location, and frequency of reagent injections varies. The Groundwater Remediation System Engineering Report (ARCADIS G&M, Inc. 2000) provides a complete description of the design criteria and system components of the Groundwater Remediation System. A summary of the methodology and results for system startup of the Groundwater Remediation System is provided in Appendix A of this report.

3. Summary of Monitoring Program

The following sections summarize the environmental effectiveness monitoring and remedial system performance monitoring activities conducted at and near the time of the baseline-sampling event and during Quarter Number 1.

3.1 Environmental Effectiveness Monitoring

The environmental effectiveness monitoring performed includes collection and analysis of water samples collected from monitoring wells, springs, and surface water. The complete list of sampling locations includes 16 monitoring wells, four spring locations, and a single surface water sampling point. Baseline round measurements and laboratory analytical parameters were as follows:

- Water-level (hydraulic) measurements were collected from 16 monitoring wells.

- Groundwater samples collected from 14 monitoring wells were analyzed for volatile organic compounds (VOCs), selected metals, the complete list of general chemistry and field parameters, and dissolved gases.
- Four spring water samples were analyzed for VOCs and selected general chemistry and field parameters.
- A single surface water sample was analyzed for VOCs and selected general chemistry and field parameters.

Quarter Number 1 measurements and laboratory analytical parameters were as follows:

- Water-level (hydraulic) measurements were collected from 16 monitoring wells.
- Five groundwater samples (quarterly list of wells) were collected and analyzed for VOCs, selected metals, general chemistry and field parameters, and dissolved gases.
- Four spring water samples were collected and analyzed for VOCs and field parameters.
- A single surface water sample was collected and analyzed for VOCs.

Section 5 (Groundwater Flow) discusses the hydraulic measurements and groundwater flow conditions during the baseline event and Quarter Number 1. Section 6 of this report discusses the results of the baseline event and evaluates Quarter Number 1 Water Quality Monitoring. Field sampling logs and chain of custody records are provided in Appendix B of this report.

3.2 Groundwater Remediation System Performance Monitoring

Groundwater Remediation System performance monitoring is conducted on a quarterly basis to monitor system performance of the PT and ARI systems. PT system performance monitoring includes OM&M of PT system equipment, the collection of six groundwater samples and one vapor sample, and recording system operating parameters. ARI system performance monitoring includes O&M of ARI system equipment, recording downhole field parameters in select groundwater monitoring wells and injection wells, collecting and analyzing select injection wells for total organic carbon (TOC), and reporting system operating parameters. In addition to the

PT and ARI system performance monitoring tasks listed above, select groundwater analytical data collected as part of the environmental effectiveness monitoring is reviewed on a quarterly basis to assess the overall effectiveness of the Groundwater Remediation System. Baseline (as indicated below) and Quarter Number 1 measurements and laboratory analytical parameters were as follows:

- Six groundwater samples were collected and analyzed for VOCs and total iron for PT system performance monitoring.
- One vapor sample was collected and analyzed for VOCs for PT system performance monitoring.
- Four groundwater samples were collected and analyzed for TOC (three samples collected to establish baseline conditions, one sample collected during the Quarter Number 1 sampling round) to monitor ARI system performance.
- Downhole field parameters were recorded on November 20, 2002 to monitor ARI system performance.
- PT system operating parameters were recorded during the quarterly site visit.
- ARI system operating parameters were recorded during each injection event.

As discussed previously, the Groundwater Remediation System startup methodology and results have been provided in Appendix A, and will not be discussed further in this report.

4. Methodology

The following sections summarize hydraulic measurement methodology, sample collection and analyses methods and procedures, and the remedial system performance monitoring methodology. Details are further provided in the LTM Plan.

4.1 Water-Level Measurements

The depth to groundwater in monitoring wells was measured as follows: the depth to groundwater in each well was measured to the nearest one-hundredth of a foot with an electronic water-level indicator probe from the surveyed measuring point.

4.2 Groundwater Sampling

Monitoring wells (baseline: GMMW-2, GMMW-5, GMMW-6, PW-3, PW-4, PW-5, PW-7, PW-13, W-5, W-6, W-7, W-13, W-14S, W-17S, W-18S, and W-20S) (Q1: GMMW-2, GMMW-5, GMMW-6, PW-4, and W-5) were purged using a variable speed, 2-inch diameter submersible pump following USEPA Micropurge/low-flow protocols. Field parameters including pH, specific conductance, DO, oxidation/reduction potential (ORP), turbidity, and temperature were monitored in a flow-through cell. Following stabilization of field parameters, the purge rate was then reduced to approximately 100 ml/min and the groundwater sample was collected directly from the pump discharge (USEPA 1998).

4.3 Spring Water and Surface Water Sampling

Spring water samples were collected as grab samples directly from Springs SP-2, SP-3, SP-4, and SP-5 (Figure 1). During sampling, pH, temperature, and specific conductivity were tested.

The surface water sample was collected as a grab sample directly from the North Stream (approximately midstream) at Location F-6 (Figure 1). During sampling, pH, temperature, dissolved oxygen, and specific conductivity were tested.

4.4 Remedial System Performance Monitoring

The following sections describe the Groundwater Remediation System performance monitoring (PT and ARI Systems) conducted between August and December 2002.

4.4.1 PT System Performance Monitoring

Groundwater samples were collected as grab samples directly from Production Wells GMPW-3, GMPW-4, and GMPW-5, the combined influent water to the low profile air stripper, the combined effluent from the low profile air stripper prior to entering the cartridge filters, and the combined effluent after the cartridge filters. An effluent air sample was collected as a grab sample directly from the designated point located on the low profile air stripper stack.

4.4.2 ARI System Performance Monitoring

Groundwater samples were collected as grab samples utilizing a hand bailer from Injection Wells IW-3, IW-8, and IW-13 for TOC analysis. Prior to sampling, the pH of the purge water from each injection well was tested. In addition to injection wells, field parameters were recorded from select monitoring wells using a YSI 600XL multi-parameter, down hole, water quality monitor to provide an early indication of the establishment of the IRZ as part of initial evaluation of ARI system performance. During each monitoring event, the YSI multi-probe was placed at the midpoint of each screen interval for the collection of the field measurements. Field parameters were recorded upon stabilization (stabilization assessed based on field judgment) of the various readings.

5. Groundwater Flow

Depth to groundwater measurements were made on July 24, 2002 and December 9, 2002. Water-level elevations data are provided in Table 1. Water-level elevations and the groundwater flow direction in July 2002 and December 2002 are illustrated on Figures 1 and 2, respectively. Based on the hydraulic data collected during these rounds, groundwater flow conditions at the site remain consistent with previous rounds in that groundwater moving within the glacial outwash aquifer beneath the landfill is part of a shallow groundwater subsystem that discharges into nearby surface water bodies. The direction of groundwater flow at the landfill western perimeter (project area) is toward the west and southwest. Further east the groundwater flows directly toward the south/southwest.

6. Water Quality

The following sections describe the results obtained from the July 2002 baseline event, discuss the water quality results obtained from Quarter Number 1 round and, as needed, compares the current data to baseline conditions and background conditions. The analytical results obtained from groundwater, surface water, and spring water sampling events are provided in Tables 2 through 7. Where applicable, the results of performance monitoring of the groundwater remedial systems (PT and ARI systems) are similarly tabulated and are summarized in the sections below. Section 7 of this report provides a complete description and evaluation of performance monitoring conducted during this period.

6.1 Baseline Groundwater Sampling Event

Activities performed during the baseline groundwater sampling event included sampling of 14 monitoring wells. The results and discussion of the findings of the baseline groundwater sampling event are provided in the following sections.

6.1.1 Volatile Organic Compounds

Individual and total VOC concentrations in groundwater samples collected in July 2002 are provided in Table 2. The baseline total VOC (TVOC) concentrations are shown on Figure 3. The areal extent of TVOC plume concentrations is generally consistent with the total VOC plume distribution that was defined in 1996 (Geraghty & Miller, Inc. 1997). Total VOC concentrations greater than 50 micrograms per liter ($\mu\text{g/L}$) extend approximately from the landfills western perimeter, near Wells PW-7 and W-6 to Well W-18, approximately 1,400 ft downgradient of the landfill western perimeter. Well GMMW-6 (installed in Year 2001) exhibited the highest concentration of total VOCs (2,067 $\mu\text{g/L}$) and is located approximately 200 ft downgradient of the ARI system injection wells.

Wells GMMW-2, GMMW-5, GMMW-6, PW-3, PW-4, and W-5 exhibited total VOC concentrations more than an order of magnitude greater than wells located further downgradient, with the predominant VOC concentrations ranging as follows: trichloroethene (TCE) (3.9 to 120 $\mu\text{g/L}$), 1,1-dichloroethane (1,1-DCA) (53 to 550 $\mu\text{g/L}$), 1,1,1-trichloroethane (1,1,1-TCA) (6.7 to 88 $\mu\text{g/L}$), chlorobenzene (<1 to 62 $\mu\text{g/L}$), chloroethane (8.9 to 170 $\mu\text{g/L}$), cis-1, 2-dichloroethene (1,2-DCE) (38 to 960 $\mu\text{g/L}$), and vinyl chloride (VC) (1.7 to 160 $\mu\text{g/L}$). Upgradient wells (PW-7, PW-13, and W-13) and wells further to the south and east (PW-5, W-6, W-7, W-14S, W-16S, W-17S, W-18, and W-20S) exhibited low or non-detectable concentrations of VOCs, with predominant individual VOC concentrations ranging from <1 $\mu\text{g/L}$ to the following maximum values: TCE (19 $\mu\text{g/L}$), 1,1-DCA (23 $\mu\text{g/L}$), 1,1,1-TCA (12 $\mu\text{g/L}$), chlorobenzene (27 $\mu\text{g/L}$), chloroethane (11 $\mu\text{g/L}$), and 1,2-DCE (9.8 $\mu\text{g/L}$). VC was detected in a single well (PW-7 at 1.9 $\mu\text{g/L}$). VOC concentrations decrease to below the limits of detection prior to discharging to the Susquehanna River, as exhibited by results from Well W-20S.

Concentrations of the various daughter compounds (i.e., 1,1-DCA, 1,2-DCE, chloroethane, and VC) comprise an average total of 76 percent of the total VOCs detected in project area Wells GMMW-2, GMMW-5, GMMW-6, PW-3, PW-4, and W-5.

6.1.2 Indicators of Reducing Conditions

The presence of soluble (ferrous) iron (Fe) and manganese (Mn), the formation of methane, negative oxidation reduction potential (ORP) values, and decreased concentration of dissolved oxygen (DO), sulfate, and nitrate (Table 3) in groundwater provide strong evidence of reducing conditions within the contaminated aquifer segment downgradient of the site, resulting in geochemical conditions that are amenable to enhancing the biodegradation of VOCs. Based on the groundwater data collected in July 2002, the occurrence of geochemical indicators is as follows:

- Wells GMMW-5, GMMW-6, and W-5 exhibited elevated concentrations of dissolved iron and, to a somewhat lesser extent, elevated concentrations of dissolved manganese, relative to background concentrations.
- Wells GMMW-5, GMMW-6, and W-5 exhibited neutral to negative ORP values.
- Wells GMMW-2, GMMW-5, GMMW-6, and W-5 exhibited elevated concentrations of methane.
- Wells within the reducing segment of the aquifer (GMMW-2, GMMW-5, and GMMW-6) exhibited depleted DO values.
- Wells GMMW-2, GMMW-5, GMMW-6, and W-5 exhibited depleted concentrations of nitrate. In a biologically active (reducing) environment, nitrate would be the first electron acceptor to be depleted after oxygen is consumed. This provides a good indication that reducing conditions are occurring within the contaminated segment of aquifer.

The occurrence of geochemical indicators in the monitoring well network is shown on Figure 4. Data collected from Wells GMMW-5, GMMW-6, and W-5, which are located closest to the site, provide the strongest evidence of reducing conditions in the aquifer. The data indicate that the geochemical conditions in the shallow aquifer immediately downgradient of the site are amenable to biodegradation of VOCs.

6.1.3 Evidence of Biodegradation

Increased concentrations of biodegradation end products (Table 3) in monitoring wells provide strong evidence of the occurrence of bioactivity and biodegradation of VOCs within the plume. The occurrence of the biodegradation end products in the

performance monitoring well network is shown on Figure 4. Wells GMMW-2, GMMW-5, GMMW-6, PW-3, and W-5 exhibited increased concentrations of ethane and ethene. Wells GMMW-5 and W-5, which are located closest to the landfill western perimeter, exhibit the highest levels of ethene and ethane concentrations, which indicates that biodegradation processes are acting to degrade VOCs in the segment of aquifer immediately downgradient of the landfill western perimeter. Well PW-3 located near the distal end of the elevated VOC levels within the plume, also exhibited elevated ethane and ethene concentrations.

6.2 Groundwater Monitoring (Quarter Number 1)

Activities performed during the groundwater sampling event performed in December 2002 (Quarter Number 1) included sampling of 14 monitoring wells. The results and discussion of the findings of the baseline groundwater sampling event are provided in the following sections.

6.2.1 Volatile Organic Compounds

The results of sampling PT system Extraction Wells GMPW-3, GMPW-4, and GMPW-5 (Table 4) provide additional evidence that VOC concentrations downgradient of the landfill western perimeter are consistent with prior rounds of data and with the currently defined extent of the VOC plume, with total VOC concentrations as follows: GMPW-3 (162 µg/L) GMPW-4 (193 µg/L) and GMPW-5 (<1.0 µg/L). A complete evaluation of performance monitoring conducted on the PT system is provided in Section 7.1.2 of this report.

Individual and total VOC concentrations in groundwater samples collected in December 2002 are provided in Table 2. In comparison to baseline conditions, Wells GMMW-5, GMMW-6, and PW-4, exhibiting somewhat higher TVOC concentrations (primarily due to increased concentrations of 1,2-DCE, 1,1-DCA, and VC), while Well W-5 exhibited a decrease in TVOC concentration this round. Additional evaluation of VOC concentrations in groundwater relative to Groundwater Remediation System Performance is provided in Section 7.2.2 of this report.

6.2.2 Indicators of Reducing Conditions

Table 3 provides the results of biogeochemical monitoring conducted in Quarter Number 1. Based on the groundwater data collected in December 2002, geochemical conditions at the project area have been modified from that observed in the baseline

round in that wells that are located closest to the landfill western perimeter exhibit early indications of the establishment of the IRZ (i.e., increased TOC concentrations in Wells GMMW-5 and W-5 and overall stronger anerobic and reducing conditions). A comparison of key field parameter readings collected from injection wells monitored between July and December 2002 (interim period) indicate that the ARI system is performing as designed. Further detail on ARI system performance monitoring is provided in Section 7.2.2 of this report.

6.2.3 Evidence of Biodegradation

Table 3 provides the results of biodegradation end product concentrations in monitoring wells and illustrates the continued occurrence of bioactivity and biodegradation of VOCs within the plume. Overall results indicate stable to increasing concentrations of biodegradation end products, particularly carbon dioxide, ethane, and ethene in Wells GMMW-5 and W-5 compared to the baseline round. These wells are located closest to the ARI injection wells and would be expected to be the first wells to exhibit increases in biodegradation end products. Additional details on the results of biogeochemical monitoring as evidence of Groundwater Remediation System performance and effectiveness are discussed in Section 7.2.2 of this report.

6.3 Spring Water Monitoring

Spring water quality analytical results for the baseline and Quarter Number 1 sampling events are summarized in Table 5 and 6. As shown in Table 5, the individual VOCs detected vary from location to location, but generally consist of 1,1-DCA, chlorobenzene, chloroethane, cis-1,2-DCE, VC, and BTEX compounds (benzene, toluene, ethyl benzene, and total xylenes). The results of spring sampling indicated generally lower values at Locations SP-2 and SP-3 in comparison to prior rounds of data collected from 1995 through 2000 (ARCADIS G&M, Inc. 2003). Spring SP-4 total VOC concentrations in July and December 2002 were as follows (541.4 µg/L and 909.5 µg/L, respectively). The results obtained from Spring SP-5 in July and December 2002 were as follows (155.2 µg/L and 113.5 µg/L, respectively). Field parameters collected from spring samples in July and December 2002 are provided in Table 6.

6.4 Surface Water Monitoring

The results of analysis of the downstream surface water sample collected during the baseline round indicated no detectable levels of VOCs (Table 7), which is consistent

with prior rounds of data (Geraghty & Miller, Inc. 1997). Field parameter readings obtained at the time of sampling are provided in Table 8.

7. Groundwater Remediation System Performance

The following section describes the results of the Groundwater Remediation System performance monitoring conducted during Quarter Number 1.

7.1 PT System

The following section describes the results of the PT system performance monitoring conducted during Quarter Number 1.

7.1.1 Summary of Operation, Maintenance, and Monitoring

During the first quarter of system operation, the PT system operated continuously with only minor system shutdowns for routine operation and maintenance. PT system OM&M was conducted on December 9 and 10, 2002 and included operation and maintenance of system equipment, the collection of system performance samples (water and vapor), and recording system operating parameters. Table 9 provides a summary of the recorded system operating parameters. As shown on Table 9, the total influent groundwater recovery rate was approximately 1-gallon per minute (gpm), with individual recovery rates of 0.57-gpm, 0.19-gpm, and 0.34-gpm for recovery wells GMPW-3, GMPW-4, and GMPW-5, respectively. A total of 138,092 gallons of groundwater was recovered during the reporting period and a total of 143,450 gallons of groundwater has been recovered since the beginning of system startup. The low profile air stripper blower discharge pressure was 8.5-inches of water column (i.w.c.), and the low profile air stripper blower flowrate was 26 standard cubic feet per minute (scfm). The low profile air stripper blower flowrate was substantially lower than its recommended operating flowrate (150-acfm) due to the accumulation of iron oxide and bacterial floc on the low profile air stripper trays. The low profile air stripper was immediately cleaned and returned to its normal operating condition. It should also be noted that although the low profile air stripper flowrate was reduced, it did not adversely affect the performance of the PT system as described below.

7.1.2 Results of Performance Sampling

PT system performance sampling was conducted on December 9 and 10 of 2002. On December 9, 2002 six groundwater samples were collected and on December 10, 2002

one vapor sample was collected. Groundwater samples collected included individual recovery well samples (GMPW-3, GMPW-4, and GMPW-5), total influent, total effluent (from low profile air stripper) before the cartridge filters, and total effluent after the cartridge filters. In addition, one vapor sample was collected from the effluent stack of the low profile air stripper.

Table 4 provides a summary of the PT system performance sampling groundwater analytical results. Table 11 provides a summary of the PT system performance sampling vapor analytical results. According to the New York State Department of Environmental Conservation (NYSDEC) Technical and Operational Guidance Series (TOGS) 1.2.1, one of the purposes of the Model Technology Best Professional Judgment (BPJ) limits is to provide guidance to NYSDEC staff responsible for writing requirements equivalent to SPDES permits for discharges from remediation sites. As such, these values have been selected as the effluent design criteria for the PT system. As shown on Table 4, all groundwater COCs were effectively treated to below their respective BPJ limits via the low profile air stripper and cartridge filters. Based on the total groundwater recovered during the reporting period and total influent groundwater concentration, approximately 0.21 pounds (lbs) of mass were removed from the subsurface during the quarterly reporting period, as shown in Table 10. A total of approximately 0.22 lbs of VOCs have been removed from the subsurface since system startup.

As shown on Table 11, effluent vapor concentrations for all COCs were below their respective detection limits. To be conservative, a NYSDEC DAR-1 air model was calculated using the individual vapor analytical detection limits of COCs detected in the influent groundwater. All COCs were below their respective short-term guidance concentrations (SGCs) and annual guidance concentrations (AGCs). Appendix C contains the NYSDEC DAR-1 AGC screening simulation based on the hand calculations provided in the NYSDEC DAR-1 AGC/SGC Tables dated July 12, 2000.

7.2 ARI System

The following section describes the results of the ARI system performance monitoring conducted during Quarter Number 1.

7.2.1 Summary of Operation, Maintenance, and Monitoring

During the first quarter of ARI system operation, the ARI system operated continuously, with only minor system shutdowns for routine operation and

maintenance activities. ARI system OM&M was conducted on a weekly basis (via remote telemetry) during the first quarter and included operation and maintenance of system equipment and recording system operating parameters during each automated injection event. On November 19, 2002, two 615-gallon polyprocessing tanks were installed as a replacement for the existing molasses totes. The installation of the tanks allows for molasses deliveries to be completed with fewer complications. Following startup the molasses concentration and frequency of injection were altered. The concentration of molasses in solutions was adjusted from an initial concentration of 27% to 14% molasses by volume and the frequency of injections was increased to weekly instead of bi-weekly. During Quarter Number 1, nine automated injections were conducted. Each automated injection event consisted of injecting 37-gallons of approximately 14-percent molasses solution to each of the 17 injection wells on a weekly basis. Based on the number of injection events, quantity of molasses solution delivered to each injection well, and molasses solution percentage, approximately 5,661-gallons of molasses solution was delivered to the subsurface during Quarter Number 1. Appendix D provides a summary of the recorded system operating parameters for each of the injection events for this period.

7.2.2 Results of Performance Sampling

ARI system performance sampling was conducted on November 20 and December 10 of 2002 to monitor the performance of the ARI system. As discussed previously, ARI system performance sampling consisted of collecting groundwater samples from Injection Wells IW-3, IW-8, and IW-13 for TOC analysis, and recording groundwater field parameters from select monitoring wells using a YSI 600XL multi-parameter, down hole, water quality monitor. Based on the anticipated hydrogeologic conditions at the site, it was calculated that Monitoring Wells W-5, GMMW-5, and GMMW-6 could have been affected by the ARI system during the reporting period. As such, these wells were selected for interim performance sampling. In addition to performance sampling conducted explicitly for ARI system monitoring, the Quarter Number 1 analytical results of Monitoring Wells W-5, GMMW-5, and GMMW-6 sampled under the environmental effectiveness monitoring program were utilized to determine the effectiveness of the ARI system.

As discussed previously, Tables 2 and 3 summarize the results of VOCs, and inorganic and field parameters, respectively, for the baseline, interim, and first quarterly sampling events. A comparison of the baseline to the interim and first quarterly groundwater monitoring results indicates that the ARI system is performing as designed. Specifically, analytical results and field parameters indicate that

geochemical conditions in the current area of ARI system influence exhibit a lack of DO, negative ORP, increase in TOC, and an increase in chlorinated VOC (CVOC) degradation products (i.e., ethene and ethane).

- As shown in Table 3, DO concentrations in monitoring wells GMMW-5 and W-5 decreased from 3.24 milligrams per liter (mg/L) to 1.36 mg/L and from 6.67 mg/L to 1.40 mg/L, respectively, during the first quarter of operation.
- TOC concentrations in monitoring wells GMMW-5 and W-5 increased from 8.25 mg/L to 56.5 mg/L and from 4.33 to 39.6 mg/L, respectively.
- TOC concentrations in injection wells IW-3 and IW-13 increased from 2.67 mg/L to 1,140 mg/L and from 3.60 to 495 mg/L, respectively.
- CVOC degradation products also increased significantly during the first quarter of operation, as mentioned above.
- Ethene concentrations in monitoring wells GMMW-5 and W-5 increased from 1,000 nanograms per liter (ng/L) to 1,400 ng/L and from 13,000 ng/L to 28,000 ng/L, respectively.
- Ethane concentrations in monitoring wells GMMW-5 and W-5 increased from 56 ng/L to 150 ng/L and from 35,000 ng/L to 53,000 ng/L, respectively.

Total VOC concentrations within the ARI influence area did not change substantially during the first quarter of operation. However, this result is anticipated due to the competing reactions which involve contaminant biodegradation, formation of daughter products, and desorption of adsorbed VOC mass during the initial operation of the IRZ. This can result in VOC concentrations increasing or remaining constant during the short- to mid-term. However, it is anticipated that VOC concentrations will drop significantly over the long-term (i.e., following the desorption period).

8. Conclusions

Based on the data obtained from the baseline, interim OM&M of the Groundwater Remediation System, and Quarter Number 1, ARCADIS concludes the following:

- The groundwater flow direction in the project area (i.e., adjacent to the landfill western perimeter) and site-wide in the July and December 2002 rounds was

consistent with previous rounds. The groundwater flow direction in the project area is toward the southwest from the western perimeter of the landfill. The groundwater flow direction in areas further to the east of the project area is toward the south/southwest.

- The July 2002 baseline results indicate that the extent of the groundwater TVOC plume has remained stable since 1997, with the area of highest TVOC concentrations located in the project area. Wells located upgradient or substantial distances downgradient of the project area continue to exhibit low or non-detectable concentrations of VOCs. The December 2002 TVOC analytical results in wells located close to the ARI injection well line were essentially the same as the July 2002 round. This is likely due to competing reactions which involve contaminant biodegradation, formation of daughter products, and desorption of adsorbed VOC mass during the initial operation of the IRZ.
- Biogeochemical conditions observed in July 2002 and December 2002 are as follows:
 - The July 2002 data indicate conditions amenable to biodegradation of VOCs. Elevated concentrations of biodegradation end products provide additional evidence that biodegradation of VOCs is occurring within the project area.
 - The December 2002 biogeochemical data indicate similar geochemical conditions downgradient and stable to increasing levels of biodegradation end products in key wells closest to the ARI system injection wells.
- The Groundwater Remediation System operated continuously during the reporting period with only minor system shutdowns for operation and maintenance activities.
- The PT system is operating as designed and is treating recovered groundwater to below BPJ limits prior to discharge.
- The ARI system is operating as designed and has established an anaerobic IRZ within the vicinity of the injection wells.
- Groundwater within the current ARI influence area exhibited increased levels of CVOC degradation products.

9. Recommendations

No recommendations for changes to the groundwater monitoring program are made at this time.

10. Project Schedule

Groundwater environmental effectiveness monitoring is scheduled to be conducted in Year 2003 on the quarterly schedule set forth in the LTM Plan. Performance monitoring of the Groundwater Remediation System will also be performed consistent with the LTM Plan. Changes to the monitoring plan for Year 2003 would be considered based on field conditions or the need to refine data collection needs in support monitoring system performance and effectiveness.

11. References

- ARCADIS G&M, Inc. 2003. Spring Remedy Comparative Analysis and Preferred Remedy Conceptual Design, Colesville Landfill, Broome County, New York. March 3, 2003.
- ARCADIS G&M, Inc. 2002. Long-Term Monitoring Plan, Colesville Landfill, Broome County, New York, NYSDEC Site 704010. June 28, 2002.
- ARCADIS Geraghty & Miller, Inc. 2000. Groundwater Remediation System Engineering Report, Broome County and GAF Corporation. July 27, 2000.
- Geraghty & Miller, Inc. 1997. First Quarter 1996 Sampling Report, Colesville Landfill, Broome County, New York. January 1997.
- U.S. Environmental Protection Agency (USEPA). 1998. Groundwater Sampling Procedure, Low Stress (Low-Flow) Purging and Sampling, USEPA Region II. March 1998.

ARCADIS

Table 1. Water-Level Measurements Collected on July 22 and December 9, 2002, Colesville Landfill, Broome County, New York.

Well	MP Elevation (feet above msl)	July 21, 2002 Depth to Water (feet below MP)	July 21, 2002 Water-Level Elevation (feet above msl)	December 9, 2002 Depth to Water (feet below MP)	December 9, 2002 Water-Level Elevation (feet above msl)	MP Description
GMMW-2	1030.95	33.61	997.34	38.11	992.84	Inner casing
GMMW-5	1043.66	48.81	994.85	49.26	994.40	Inner casing
GMMW-6	1033.56	39.94	993.62	40.18	993.38	Inner casing
PW-3	988.92	NA	NA	NA	NA	Inner casing
PW-4	1001.75	17.77	983.98	18.81	982.94	Inner casing
PW-5	986.12	1.27	984.85	52.51	Artesian	Inner casing
W-5	1051.41	52.17	999.24	NA	NA	Inner casing
W-6	1050.38	50.57	999.81	51.54	998.84	Inner casing
PW-7	1042.47	39.45	1003.02	NA	NA	Inner casing
W-7	1049.12	43.48	1005.64	44.61	1004.51	Inner casing
PW-10	1049.29	39.07	1010.22	40.31	1008.98	Inner casing
PW-13	1072.41	62.17	1010.24	63.20	1009.21	Inner casing
W-13	1053.43	47.50	1005.93	48.26	1005.17	Inner casing
W-14S	957.68	9.45	948.23	NA	NA	Inner casing
W-16S	990.33	32.10	958.23	9.30	981.03	Outer casing
W-17S	959.13	10.69	948.44	11.47	947.66	Inner casing
W-18	973.56	11.83	961.73	11.38	962.18	Inner casing
W-20S	952.88	10.11	942.77	8.72	944.16	Inner casing

msl mean sea level
MP Measuring Point
NA Not Accessible

ARCADIS

Table 2. Concentrations of Volatile Organic Compounds Detected in Groundwater Samples, Baseline and Quarter Number 1 Sampling Rounds, Colesville Landfill, Broome County, New York.^{1,2}

Constituents (units in ug/L)	Sample ID: GMMW-2	GMMW-5	GMMW-6	GMMW-6	PW-3	PW-4	PW-4	PW-5	PW-7	PW-10	PW-13	W-5
	Date: 07/25/02	07/25/02	12/10/2002	07/25/02	07/25/02	07/25/02	12/10/2002	07/25/02	07/23/02	12/10/2002	07/23/02	07/25/02
1,1,1-Trichloroethane	88 J	7.2 J	<1	6.7 J	<10	31 J	69 J	62	<1.0 J	<1	1.5	8.5 J
1,1,2-Trichloroethane	<1.0 J	<1.0 J	<1	4.8 J	<10	<1.0 J	<1.0 J	<1	<1.0 J	<1	<1.0	<1.0 J
1,1-Dichloroethane	93 J	86 J	120	550 J	670	53 J	62 J	73	<1.0 J	4.8	1.3	160 J
1,1-Dichloroethene	4.2 J	1.5 J	<1	8.3 J	<10	<1.0 J	2.8 J	7.2	<1.0 J	<1	<1.0	1.2 J
1,2,4-Trimethylbenzene	<1.0 J	<1.0 J	<1	<1.0 J	<10	<1.0 J	<1.0 J	<1	<1.0 J	<1	<1.0	1.3 J
1,2-Dichlorobenzene	<1.0 J	<1.0 J	<1	<1.0 J	<10	<1.0 J	<1.0 J	<1	<1.0 J	<1	<1.0	<1.0 J
1,2-Dichloroethane	<1.0 J	<1.0 J	1.1	5.6 J	<10	1.1 J	<1.0 J	<1	<1.0 J	<1	<1.0	1.3 J
1,2-Dichloropropane	<1.0 J	<1.0 J	<1	2.3 J	<10	<1.0 J	<1.0 J	<1	<1.0 J	<1	<1.0	<1.0 J
Benzene	6.9 J	<1.0 J	<1	7.4 J	<10	<1.0 J	<1.0 J	1.8	<1.0 J	1.9	<1.0	2.2 J
Chlorobenzene	48 J	5.8 J	9	62 J	54	<1.0 J	<1.0 J	<1	<1.0 J	4.0	4.0	15 J
Chloroethane	27 J	13 J	22	170 J	190	8.9 J	17 J	20	<1.0 J	<1	<1.0	70 J
Chloroform	<1.0 J	<1.0 J	<1	4.5 J	<10	1.8 J	2.7 J	<1	<1.0 J	<1	<1.0	<1.0 J
Chloromethane	<1.0 J	<1.0 J	<1	<1.0 J	<10	<1.0 J	<1.0 J	<1	<1.0 J	<1	<1.0	<1.0 J
cis-1,2-Dichloroethene	200 J	100 J	160	960 J	1100	38 J	72 J	130	<1.0 J	4.7	1.6	53 J
Dichlorodifluoromethane	<1.0 J	<1.0 J	<1	10 J	<10	1.8 J	3.9 J	<1	<1.0 J	<1	<1.0	<1.0 J
Ethylbenzene	<1.0 J	<1.0 J	<1	<1.0 J	<10	<1.0 J	<1.0 J	<1	<1.0 J	<1	<1.0	1.4 J
m,p-Xylene	<2.0 J	<2.0 J	<2	<2.0 J	<20	<2.0 J	<2.0 J	<2	<2.0 J	<2	<2.0	4.2 J
Methylene chloride	2.7 J	2.2 J	2.1	22 J	<10	1.8 J	5.4 J	4.9	<1.0 J	<1	<1.0	3.0 J
Naphthalene	<1.0 J	<1.0 J	<1	<1.0 J	<10	<1.0 J	<1.0 J	<1	<1.0 J	<1	4.4	<1.0 J
o-Xylene	<1.0 J	<1.0 J	<1	1.3 J	<10	<1.0 J	<1.0 J	<1	<1.0 J	<1	<1.0	2.2 J
Tetrachloroethene	1.0 J	<1.0 J	<1	2.2 J	<10	3.1 J	<1.0 J	<1	<1.0 J	<1	<1.0	<1.0 J
Toluene	<1.0 J	1.1 J	2.4	<1.0 J	<10	<1.0 J	<1.0 J	<1	<1.0 J	<1	<1.0	6.3 J
trans-1,2-Dichloroethene	<1.0 J	<1.0 J	<1	3.5 J	<10	<1.0 J	<1.0 J	<1	<1.0 J	<1	<1.0	1.0 J
Trichloroethene	120 J	3.9 J	2.8	86 J	64	19 J	38 J	82	<1.0 J	<1	5.3	6.0 J
Vinyl chloride	29 J	12 J	15	160 J	250	1.7 J	5.4 J	6.5	<1.0 J	<1	<1.0	91 J
Total VOCs	619.8	232.7	334.4	2,066.6	2328	161.2	278.2	387.4	0	55.4	18.1	427.6

See footnotes on last page.

ARCADIS

Table 2. Concentrations of Volatile Organic Compounds Detected in Groundwater Samples, Baseline and Quarter Number 1 Sampling Rounds, Colesville Landfill, Broome County, New York.^{1,2}

Constituents (units in ug/L)	Sample ID: Date: 12/10/2002	W-5	W-6	W-7	W-13	W-14S	W-16S	W-17S	W-18S	W-20S
			07/25/02	07/24/02	07/25/02	07/24/02	07/24/02	07/24/02	07/23/02	07/23/02
1,1,1-Trichloroethane	6.6	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	12 J	<1.0 J
1,1,2-Trichloroethane	<1	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J
1,1-Dichloroethane	180	23 J	10 J	<1.0 J	<1.0 J	<1.0 J	17 J	3.5 J	15 J	<1.0 J
1,1-Dichloroethene	<1	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J
1,2,4-Trimethylbenzene	<1	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J
1,2-Dichlorobenzene	<1	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J
1,2-Dichloroethane	<1	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J
1,2-Dichloropropane	<1	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J
Benzene	2.2	3.9 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	4.8 J	<1.0 J	<1.0 J	<1.0 J
Chlorobenzene	16	5.5 J	13 J	<1.0 J	<1.0 J	<1.0 J	27 J	<1.0 J	<1.0 J	<1.0 J
Chloroethane	82	5.2 J	7.3 J	<1.0 J	2.2 J	<1.0 J	11 J	<1.0 J	<1.0 J	<1.0 J
Chloroform	<1	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	1.0 J	<1.0 J
Chloromethane	<1	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J
cis-1,2-Dichloroethene	8.2	2.8 J	2.1 J	<1.0 J	<1.0 J	<1.0 J	2.4 J	1.2 J	9.8 J	<1.0 J
Dichlorodifluoromethane	<1	4.1 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J
Ethylbenzene	<1	1.9 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J
m,p-Xylene	0.8J	<2.0 J	<2.0 J	<2.0 J	<2.0 J	<2.0 J	<2.0 J	<2.0 J	<2.0 J	<2.0 J
Methylene chloride	3.7	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J
Naphthalene	<1	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J
o-Xylene	<1	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J
Tetrachloroethene	<1	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J
Toluene	3.8	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J
trans-1,2-Dichloroethene	<1	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J
Trichloroethene	3.8	3.3 J	1.6 J	<1.0 J	<1.0 J	<1.0 J	2.0 J	2.5 J	19 J	<1.0 J
Vinyl chloride	36	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J	<1.0 J
Total VOCs	343.1	49.7	34	2.2	0	64.2	7.2	56.8	0	0

See footnotes on last page.

ARCADIS

Table 2. Concentrations of Volatile Organic Compounds Detected in Groundwater Samples, Baseline and Quarter Number 1 Sampling Rounds, Colesville Landfill, Broome County, New York.^{1,2}

Notes:

1. Baseline sampling conducted during the week of July 22, 2002.
2. Groundwater Remediation system startup was completed on September 8, 2002.

Bold Constituent detected above MDL.

J Estimated value
MDL Method detection limit
VOCs Volatile Organic Compounds
ug/L Micrograms per liter

ARCADIS

Table 3. Concentrations of Selected Metals, General Chemistry and Field Parameters, and Dissolved Gases Detected in Groundwater Samples, Baseline and Quarter Number 1 Sampling Rounds, Colesville Landfill, Broome County, New York.^{1,2}

Parameters	Sample ID:	GMMW-2	GMMW-2	GMMW-5	GMMW-5	GMMW-5	GMMW-5	GMMW-6	GMMW-6	GMPW-1	IW-3 ³	IW-3 ³	IW-8 ³
	Date:	7/25/2002	12/10/2002	7/24/2002	11/20/2002	12/10/2002	12/10/2002	7/25/2002	12/10/2002	11/20/2002	8/30/2002	12/9/2002	8/30/2002
<u>UNITS</u>													
<u>METALS</u>													
Iron		0.0579	0.0539	15.7	13.1	1.67	1.8	1.90	2.03	2.67	1,140	5.16	
Iron, Dissolved		0.0579	0.0539	15.7	13.1	1.67	1.8	1.90	2.03	2.67	1,140	5.16	
Manganese		0.0139	0.0234	2.07	2.04	1.90	2.03	2.04	2.03	2.04	2.03	2.03	
Manganese, Dissolved		0.0139	0.0234	2.07	2.04	1.90	2.03	2.04	2.03	2.04	2.03	2.03	
<u>GENERAL CHEMISTRY</u>													
Alkalinity, Total (As CaCO ₃)		7.00	1.00	8.60	8.7	4.20	1.2	4.20	1.2	4.20	1.2	4.20	
Chloride		<0.2	0.12 J	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2	
Nitrogen, Nitrate (As N)		<0.01	<0.01	0.0410	0.084	<0.01	0.036	<0.01	0.036	<0.01	0.036	<0.01	
Nitrogen, Nitrite		1.81	9.48	8.25	56.5	<0.5	26.5	<0.5	26.5	<0.5	26.5	<0.5	
Total Organic Carbon		<2.0	3.43	6.16	12.1	<2.0	<2.0	<2.0	<2.0	<2.0	<2.0	<2.0	
Sulfate		0.248	—	—	—	0.149	—	—	—	—	—	—	
Sulfide (field)		—	—	—	—	—	—	—	—	—	—	—	
<u>FIELD PARAMETERS</u>													
pH	Standard units	6.34	6.63	6.22	6.76	6.58	6.10	6.79	7.46	7.80	4.85	6.55	
Specific Conductance	mmhos/cm	0.427	0.331	0.383	0.352	0.242	0.875	1.01	0.316	—	0.82	—	
Turbidity	NTU	46.1	40	63.7	—	28.7	150	550	—	—	—	—	
Dissolved Oxygen	mg/L	1.32	2.33	3.24	1.07	1.36	1.40	1.66	1.00	—	2.25	—	
Temperature	deg C	13.7	11.9	14.0	9.7	10.5	15.6	10.4	9.6	—	9.5	—	
ORP	mV	122	64	-106	-215.5	-74	11	-30	-210.3	—	-435	—	
<u>DISSOLVED GASES</u>													
Carbon dioxide	mg/L	130	110	51	—	62	140	140	—	—	—	—	
Carbon monoxide	mg/L	<0.40	<0.40	<0.40	—	<0.40	<0.40	<0.40	—	—	—	—	
Ethane	ng/L	590	480	56	—	150	720	1,100	—	—	—	—	
Ethene	ng/L	4,300	2,300	1,000	—	1,400	29,000	35,000	—	—	—	—	
Methane	ug/L	670	660	530	—	180	580	720	—	—	—	—	
Nitrogen	mg/L	14	16	17	—	15	13	16	—	—	—	—	
Oxygen	mg/L	2.8	5.4	2.7	—	1.6	2.8	5.6	—	—	—	—	

See footnotes on last page.

ARCADIS

Table 3. Concentrations of Selected Metals, General Chemistry and Field Parameters, and Dissolved Gases Detected in Groundwater Samples, Baseline and Quarter Number 1 Sampling Rounds, Colesville Landfill, Broome County, New York, 12

Parameters	Sample ID:	IW-13 ³	IW-13 ³	PW-2	PW-3	PW-4	PW-4	PW-5	PW-7	PW-10	PW-11	PW-13
	Date:	8/30/2002	12/10/2002	11/20/2002	07/25/02	07/25/02	12/10/2002	07/25/02	7/23/2002	12/10/2002	11/20/2002	7/23/2002
METALS												
Iron		-	-	-	-	-	-	-	-	-	-	-
Iron, Dissolved		-	-	-	-	-	-	-	-	-	-	-
Manganese		-	-	-	-	-	-	-	-	-	-	-
Manganese, Dissolved		-	-	-	-	-	-	-	-	-	-	-
GENERAL CHEMISTRY												
Alkalinity, Total (As CaCO ₃)		-	-	-	-	-	-	-	-	-	-	-
Chloride		-	-	-	-	-	-	-	-	-	-	-
Nitrogen, Nitrate (As N)		-	-	-	-	-	-	-	-	-	-	-
Nitrogen, Nitrite		-	-	-	-	-	-	-	-	-	-	-
Total Organic Carbon		3.60	495	-	1.55	1.49	8.97	1.90	-	5.31	-	-
Sulfate		-	-	-	-	8.52	11.2	-	-	20.5	-	-
Sulfide (field)		-	-	-	0.051	0.025	-	0.244	0.065	-	-	0.005
FIELD PARAMETERS												
pH		6.48	6.12	8.06	6.33	5.89	6.09	8.15	6.18	6.47	6.83	5.81
Specific Conductance		-	0.646	0.186	0.472	0.361	0.358	0.248	0.219	0.248	0.636	0.172
Turbidity		-	-	-	37.8	0.6	8.0	231	122	58	-	27
Dissolved Oxygen		-	4.10	0.71	7.20	3.50	1.54	0.35	2.30	1.27	0.88	0.40
Temperature		-	10.0	10.5	12.9	15.6	13.5	10.8	14.5	9.1	9.6	20.8
ORP		-	-399.8	-81.2	292	201	137	105	19	-38	0.636	121
DISSOLVED GASES												
Carbon dioxide		-	-	-	140	260	340	0.96	-	140	-	-
Carbon monoxide		-	-	-	<0.40	<0.40	<0.40	<0.40	-	<0.40	-	-
Ethane		-	-	-	1,100	79	79	<5.0	-	<5.0	-	-
Ethene		-	-	-	12,000	480	300	310	-	<5.0	-	-
Methane		-	-	-	37	33	18	1.8	-	0.98	-	-
Nitrogen		-	-	-	12	12	14	17	-	18	-	-
Oxygen		-	-	-	6.2	3.9	4.7	2.7	-	2.7	-	-

See footnotes on last page.

ARCADIS

Table 3. Concentrations of Selected Metals, General Chemistry and Field Parameters, and Dissolved Gases Detected in Groundwater Samples, Baseline and Quarter Number 1 Sampling Rounds, Colesville Landfill, Broome County, New York.^{1,2}

Parameters	Sample ID:	W-5	W-5	W-5	W-6	W-7	W-13	W-14S	W-16S	W-17S	W-18	W-20S
	Date:	7/24/2002	11/20/2002	12/10/2002	7/24/2002	07/24/02	7/23/2002	07/24/02	07/24/02	07/24/02	07/23/02	07/23/02
<u>UNITS</u>												
<u>METALS</u>												
Iron		--	--	--	--	--	--	--	--	--	--	--
Iron, Dissolved		29.8	--	49.5	--	--	--	<0.035	--	--	--	--
Manganese		--	--	--	--	--	--	--	--	--	--	--
Manganese, Dissolved		1.49	--	1.31	--	--	--	<0.005	--	--	--	--
<u>GENERAL CHEMISTRY</u>												
Alkalinity, Total (As CaCO ₃)		--	--	--	--	--	--	--	--	--	--	--
Chloride		4.40	--	1.8	--	--	--	2.10	--	--	--	--
Nitrogen, Nitrate (As N)		<0.2	--	<0.2	--	--	--	0.361	--	--	--	--
Nitrogen, Nitrite		0.0370	--	0.068	--	--	--	<0.01	--	--	--	--
Total Organic Carbon		4.33	--	39.6	2.03	1.54	--	1.29	2.04	--	2.15	--
Sulfate		5.34	--	8.16	--	--	--	11.0	--	--	--	--
Sulfide (field)		--	--	--	0.625	0.027	--	0.02	0.0014	<0.005	0.021	0.006
<u>FIELD PARAMETERS</u>												
pH	Standard units	6.56	6.78	6.67	5.97	6.19	6.51	5.46	6.03	6.42	6.13	5.36
Specific Conductance	mmhos/cm	0.765	0.716	0.624	0.47	0.538	1.470	0.06	0.208	0.335	0.382	0.107
Turbidity	NTU	180	--	90.8	55	49.9	55.7	43.1	5.1	27.9	47.2	16
Dissolved Oxygen	mg/L	6.67	0.87	1.40	0.20	0.96	3.56	6.54	1.80	3.47	4.90	3.80
Temperature	deg C	14.2	9.7	4.9	17.7	15.5	18.4	9.2	15.4	12.9	14.9	18.8
ORP	mV	-103	-123.7	-73	-42	-55	-85	265	199	213	169	299
<u>DISSOLVED GASES</u>												
Carbon dioxide	mg/L	110	--	190	--	--	--	--	170	--	--	--
Carbon monoxide	mg/L	<0.40	--	<0.40	--	--	--	--	<0.40	--	--	--
Ethane	ng/L	35,000	--	53,000	--	--	--	--	510	--	--	--
Ethene	ng/L	13,000	--	28,000	--	--	--	--	360	--	--	--
Methane	ug/L	1,400	--	1,200	--	--	--	--	1,800	--	--	--
Nitrogen	mg/L	13	--	14	--	--	--	--	9.5	--	--	--
Oxygen	mg/L	1.2	--	1.2	--	--	--	--	2.8	--	--	--

See footnotes on last page.

ARCADIS

Table 3. Concentrations of Selected Metals, General Chemistry and Field Parameters, and Dissolved Gases Detected in Groundwater Samples, Baseline and Quarter Number 1 Sampling Rounds, Colesville Landfill, Broome County, New York.^{1,2}

Notes:

1. Baseline sampling conducted during the week of July 22, 2002.
2. Groundwater Remediation System startup completed on September 8, 2002.
3. Injection wells were sampled in accordance with the schedule set forth in Table 3 of the Long-Term Monitoring Plan (ARCADIS 2002).

J	Estimated value
mg/L	milligrams per liter
mmhos/cm	millimhos per centimeter
NTU	Nephelometric Turbidity Units
deg C	degrees Celsius
mV	millivolts
ng/L	nanograms per liter
--	Not analyzed
ug/L	Micrograms per liter
IW	Injection Well

ARCADIS

Table 4. Concentrations of Volatile Organic Compounds and Selected Metals Detected in Aqueous Samples Collected from the PT System, Quarter Number 1, Colesville Landfill, Broome County, New York.

Constituents	Model Technology BPJ Limits ^{1,2} (ug/L)	Sample ID: Date:	GMPW-3 12/9/2002	GMPW-4 12/9/2002	GMPW-5 12/9/2002	INFLUENT 12/9/2002	EFFLUENT-BC 12/9/2002	EFFLUENT-AC 12/9/2002
VOCs (units in ug/L)								
1,1,1-Trichloroethane	10-20		46	41	<1	46	<1	<1
1,1,2-Trichloroethane	10		<1	<1	<1	<1	<1	<1
1,1-Dichloroethane	10		33	36	<1	30	<1	<1
1,1-Dichloroethene	10		4.7	6.8	<1	8.3	<1	<1
1,2,4-Trimethylbenzene	--		<1	<1	<1	<1	<1	<1
1,2-Dichlorobenzene	--		<1	<1	<1	<1	<1	<1
1,2-Dichloroethane	10-30		<1	<1	<1	<1	<1	<1
1,2-Dichloropropane	--		<1	<1	<1	<1	<1	<1
Benzene	5		5	5.6	<1	4.8	<1	<1
Chlorobenzene	--		<1	<1	<1	<1	<1	<1
Chloroethane	--		<1	8.8	<1	15	<1	<1
Chloroform	--		<1	<1	<1	<1	<1	<1
Chloromethane	10		<1	<1	<1	<1	<1	<1
cis-1,2-Dichloroethene	10		28	35	<1	25	1.9	2.1
Dichlorodifluoromethane	--		<1	<1	<1	1.4	<1	<1
Ethyl Benzene	5		<1	<1	<1	<1	<1	<1
m+p-Xylenes	5		<2	<2	<2	<2	<1	<1
Methylene Chloride	10-50		11	11	<1	8.8	<1	<1
o-Xylene	5		<1	<1	<1	<1	<1	<1
Tetrachloroethene	10		<1	<1	<1	<1	<1	<1
Toluene	5		<1	<1	<1	<1	<1	<1
trans-1,2-Dichloroethene	10-50		<1	<1	<1	<1	<1	<1
Trichloroethene	10		30	42	<1	31	1.4	<1
Vinyl Chloride	10-50		5.1	7.3	<1	6.9	<1	<1
Total VOCs			162.8	193.5	<1	177.2	3.3	2.1
Model Technology BPJ Limits^{3,4} (mg/L)								
Metals (units in mg/L)								
Total Iron	1.2 / 0.61		3.61	1.03	0.572	6.35	0.81	0.188

ARCADIS

Table 4. Concentrations of Volatile Organic Compounds and Selected Metals Detected in Aqueous Samples Collected from the PT System, Quarter Number 1, Colesville Landfill, Broome County, New York.

Notes:

1. Model Technology Best Professional Judgement (BPJ) Limits recommended for Air Stripping with appropriate pretreatment from Attachment C of TOGS 1.2.1.
2. When a range is listed for the BPJ limit, a variation in available references was found. Recommended daily maximum limits should be in this range.
3. Model Technology BPJ Limits recommended for Lime, Settle and Filter treatment.
4. The recommended daily maximum permit limit is 1.2 mg/L and the recommended daily average permit limit is 0.61 mg/L.
5. Production wells were sampled in accordance with the schedule set forth in Table 3 of the Long-Term Monitoring Plan (ARCADIS 2002).

--	No BPJ limit listed.
J	Estimated value.
ug/L	Micrograms per liter.
mg/L	Milligrams per liter.
VOCs	Volatile Organic Compounds.
AC	After Cartridge Filter.
BC	Before Cartridge Filter.
PT	Pump and Treat.
MDL	Method Detection Limit.

ARCADIS

Table 5. Concentrations of Volatile Organic Compounds Detected in Spring Samples, Baseline and Quarter Number 1 Sampling Rounds, Colesville Landfill, Broome County, New York.^{1,2}

Parameters (units in ug/L)	Sample ID: Date:	SP-2 07/25/02	SP-2 12/9/2002	SP-3 07/25/02	SP-3 12/9/2002	SP-4 07/25/02	SP-4 12/9/2002	SP-5 07/25/02	SP-5 12/9/2002	SP-5 (MARSH ³) 08/22/02	SP-5 (CULVERT) 08/29/02
1,1,1-Trichloroethane		<1.0 J	<1	2.9 J	<1	9.2 J	<1	<1.0 J	<1	<1.0 J	<1.0 J
1,1,2-Trichloroethane		<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	<1.0 J	<1.0 J
1,1-Dichloroethane		36 J	12	46 J	23	200 J	240	45 J	31	<1.0 J	<1.0 J
1,1-Dichloroethene		<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	<1.0 J	<1.0 J
1,2,4-Trimethylbenzene		<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	<1.0 J	<1.0 J
1,2-Dichlorobenzene		<1.0 J	<1	<1.0 J	<1	1.1 J	<1	<1.0 J	<1	<1.0 J	<1.0 J
1,2-Dichloroethane		<1.0 J	<1	<1.0 J	<1	2.6 J	4.3	<1.0 J	<1	<1.0 J	<1.0 J
1,2-Dichloropropane		<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	<1.0 J	<1.0 J
Benzene		<1.0 J	<1	<1.0 J	<1	2.7 J	2	5.5 J	3.9	<1.0 J	<1.0 J
Chlorobenzene		9.9 J	<1	7.9 J	<1	18 J	14	81 J	52	<1.0 J	<1.0 J
Chloroethane		<1.0 J	<1	8.3 J	<1	<1.0 J	30	17 J	23	<1.0 J	<1.0 J
Chloroform		<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	<1.0 J	<1.0 J
Chloromethane		<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	2.1 J	<1.0 J
cis-1,2-Dichloroethene		1.5 J	1.3	2.3 J	1.3	73 J	400	1.4 J	<1	<1.0 J	<1.0 J
Dichlorodifluoromethane		<1.0 J	<1	<1.0 J	<1	3.2 J	<1	<1.0 J	<1	<1.0 J	<1.0 J
Ethylbenzene		2.2 J	<1	<1.0 J	<1	<1.0 J	<1	2.8 J	<1	5.6 J	<1.0 J
m,p-Xylene		<2.0 J	<2	<2.0 J	<2	<2.0 J	<2	<2.0 J	<2	28 J	<2.0 J
Methylene chloride		<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	1.1 J	<1	<1.0 J	<1.0 J
Naphthalene		<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	<1.0 J	<1.0 J
o-Xylene		<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	12 J	<1.0 J
Tetrachloroethene		<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	<1.0 J	<1.0 J
Toluene		<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	<1.0 J	<1	210 J	<1.0 J
trans-1,2-Dichloroethene		<1.0 J	<1	<1.0 J	<1	1.6 J	8.2	<1.0 J	<1	<1.0 J	<1.0 J
Trichloroethene		2.7 J	1.8	3.1 J	2.3	<1.0 J	21	1.4 J	<1	<1.0 J	<1.0 J
Vinyl chloride		<1.0 J	<1	<1.0 J	<1	230 J	190	<1.0 J	<1	<1.0 J	<1.0 J
Total VOCs		52.3	15.1	70.5	26.6	541.4	909.5	155.2	113.5	257.7	0

Notes:

J Estimated value.

VOCs Volatile Organic Compounds

ug/L Micrograms per liter.

1. Baseline sampling conducted during the week of July 22, 2002.
2. Groundwater Remediation system brought permanently on-line on September 8, 2002.
3. Sample collected in marsh area between SP-5 and East Windsor Road.

ARCADIS

Table 6. Concentrations of Selected General Chemistry and Field Parameters Detected in Spring Samples, Baseline and Quarter Number 1 Sampling Rounds, Colesville Landfill Broome County, New York.^{1,2}

Parameters	Sample ID:	SP-2	SP-2	SP-3	SP-3	SP-4	SP-4	SP-4	SP-5	SP-5	SP-5	SP-5	
	Date:	7/25/2002	12/9/2002	7/25/2002	12/9/2002	7/25/2002	7/25/2002	12/9/2002	2/17/2003	7/25/2002	11/20/2002	12/9/2002	2/17/2003
<u>UNITS</u>													
<u>GENERAL CHEMISTRY</u>													
Sulfide (field) ³		0.033	--	0.2	--	0.145	--	--	0.035	--	--	--	--
<u>FIELD PARAMETERS</u>													
pH		6.53	6.38	7.17	6.37	6.78	6.5	6.63	5.79	6.75	6.06	6.48	
Specific Conductance		0.249	0.27	0.282	0.198	0.848	0.586	0.753	-0.54	0.584	0.572	0.653	
Turbidity		181	0	395	0.7	203	125	--	60	--	487	--	
Dissolved Oxygen		8.96	3.89	9.36	8.57	9.26	5.80	1.32	3.00	1.34	4.90	1.76	
Temperature		17.17	4.4	16.92	3.3	19.69	1.8	4.7	15.1	9.51	3.6	4.6	
ORP		-24	35	-51	116	-125	17	-49.9	-29	-92.2	51	-19.6	

Notes:

1. Baseline sampling conducted during the week of July 22, 2002.
2. Groundwater Remediation System start-up was completed on September 8, 2002.
3. Sulfide analysis was performed on site on the date the samples were collected.

-- Not analyzed.
 mg/L milligrams per liter
 μmhos/cm micromhos per centimeter
 NTU Nephelometric Turbidity Units
 deg C degrees Celsius
 mV millivolts
 ORP Oxidation-Reduction Potential

ARCADIS

Table 7. Concentrations of Volatile Organic Compounds Detected in Surface Water, Baseline Sampling Event, Colesville Landfill, Broome County, New York.¹

Parameters (units in ug/L)	Sample ID: F-6 Date: 07/25/02
1,1,1-Trichloroethane	<1.0 J
1,1,2-Trichloroethane	<1.0 J
1,1-Dichloroethane	<1.0 J
1,1-Dichloroethene	<1.0 J
1,2,4-Trimethylbenzene	<1.0 J
1,2-Dichlorobenzene	<1.0 J
1,2-Dichloroethane	<1.0 J
1,2-Dichloropropane	<1.0 J
Benzene	<1.0 J
Chlorobenzene	<1.0 J
Chloroethane	<1.0 J
Chloroform	<1.0 J
Chloromethane	<1.0 J
cis-1,2-Dichloroethene	<1.0 J
Dichlorodifluoromethane	<1.0 J
Ethylbenzene	<1.0 J
m,p-Xylene	<2.0 J
Methylene chloride	<1.0 J
Naphthalene	<1.0 J
o-Xylene	<1.0 J
Tetrachloroethene	<1.0 J
Toluene	<1.0 J
trans-1,2-Dichloroethene	<1.0 J
Trichloroethene	<1.0 J
Vinyl chloride	<1.0 J
Total VOCs	0

Note:

1. Baseline sampling conducted during the week of July 22, 2002.

J Estimated value.

VOCs Volatile Organic Compounds

ug/L Micrograms per liter.

ARCADIS

Table 8. Concentrations of Selected General Chemistry and Field Parameters Detected in Surface Water, Baseline Sampling Event, Colesville Landfill, Broome County, New York.

Parameters	Sample ID: F-6	Date: 7/25/2002
<u>UNITS</u>		
<u>GENERAL CHEMISTRY</u>		
Sulfide (field) ³	mg/L	0.001
<u>FIELD PARAMETERS</u>		
pH	pH units	7.12
Specific Conductance	millimhos/cm	0.182
Turbidity	NTU	0.8
Dissolved Oxygen	mg/L	10.01
Temperature	deg C	14.9
ORP	mV	271

Notes:

1. Baseline sampling conducted during the week of July 22, 2002.
2. Groundwater Remediation System start-up was completed on September 8, 2002.
3. Sulfide analysis was performed on site on the date the samples were collected.

-- Not analyzed.
 mg/L milligrams per liter
 µmhos/cm micromhos per centimeter
 NTU Nephelometric Turbidity Units
 deg C degrees Celsius
 mV millivolts
 ORP Oxidation-Reduction Potential

ARCADIS

Table 9. Pump-and-Treat System Quarter Number 1 Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Date	Time Recorded	Air Stripper Measurements			Flow Measurements				
		Blower Discharge Pressure PI-301 (i.w.c.)	Blower Effluent Flowrate (acfm)	Total Effluent Totalizer FQI-401 (gallons)	Water Bypass Totalizer FQI-402 (gallons)	GMPW-3 Totalizer FQI-101 (gallons)	GMPW-4 Totalizer FQI-102 (gallons)	GMPW-5 Totalizer FQI-103 (gallons)	
9/10/2002	6:20 PM	8.1	147.8	5,357.9	2,858.9	2,837.5	1,269.8	1,949.6	
12/10/2002	7:30 PM	8.5	26.2	143,450.0	134,330.0	77,386.0	26,167.6	46,057.5	
		Average Daily Flowrate (gpm) =			1.05	1.00	0.57	0.34	
Total Groundwater Recovered During Reporting Period (gallons) =					138,092	131,471	74,549	44,108	

See Notes on Last Page of Table

Notes:

gpm Gallons per minute.
i.w.c. Inches of water column
acfm Actual cubic feet per minute

ARCADIS

Table 10. Pump-and-Treat System Mass Removal Rate of Volatile Organic Compounds, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Date Sampled	Total VOC Influent Concentration (ug/L)	Well Totalizer Reading (gallons)	Total Groundwater Recovered ¹ Between Sampling Intervals (gal)	Influent Concentration ² Geometric Mean (ug/L)	Total Mass ³ Removed (lbs)
9/8/2002	121.1	2,319.0	2319	121.1	0.0023
9/10/2002	203.4	5,357.9	3039	156.9	0.0040
12/10/2002	177.2	143,450.0	138092	189.8	0.2188
Total Mass Removed (lbs) =					0.2251

ug/L Micrograms per liter.

gal Gallons.

lbs Pounds.

VOC Volatile organic compound.

1. Total Groundwater Recovered Between Sampling Intervals = Well Totalizer Reading for current sampling event - Well Totalizer Reading for prior sampling event
2. Influent Concentration Geometric Mean = (Influent Concentration for prior sampling event x Influent Concentration for current sampling event) (1/2)
3. Total Mass Removed = (Total Groundwater Recovered Between Sampling Intervals) x Influent Concentration Geometric Mean x 3.7854 L/gallon x (1 lb / 453,592,370 ug)

ARCADIS

Table 11. Concentrations of Volatile Organic Compounds Detected in Air Stripper Effluent, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Compounds	CAS Numbers	Sample ID: Date Sampled:	Stripper Effluent 12/10/2002 ppb
Vinyl Chloride	75-01-4		ND
Chloroethane(Ethyl Chloride)	75-00-3		ND
1,1-Dichloroethene(Vinylidene Chloride)	75-35-4		ND
Methylene Chloride(Dichloromethane)	75-09-2		19
1,1-Dichloroethane	75-34-3		50
cis-1,2 - Dichloroethylene	156-59-2		48
Chloroform	67-66-3		ND
1,1,1-Trichloroethane(Methyl Chloroform)	71-55-6		53
Benzene	71-43-2		ND
Trichloroethene	79-01-6		36
Toluene	108-88-3		ND
Ethyl benzene	100-41-4		ND
m,p-Xylene	108-38-3/106-42-3		ND
o-Xylene	95-47-6		ND
1,2,4-Trimethylbenzene	95-63-6		ND
2-Propanol (Isopropyl alcohol)	67-63-0		ND
Dichlorodifluoromethane(Freon 12)	75-71-8		ND

ppb: parts per billion

ND: Denotes analyte not detected at or above its laboratory quantification limit.

Notes/Assumptions:

1. Samples collected by ARCADIS personnel on the dates shown and submitted to Air Toxics Laboratories LTD for volatile organic compound (VOC) analyses using a modified USEPA Method TO 14A/15.

ARCADIS

Appendix A

Groundwater Remediation System
Startup Summary Report, Colesville
Landfill, Broome County, New
York.


ARCADIS


Appendix A

Groundwater Remediation System Startup Summary Report


Colesville Landfill, Broome County, New York
NYSDEC Site 704010

ARCADIS


Kenneth Zegel
Staff Engineer


Steven M. Feldman
Project Manager

ARCADIS Engineers & Architects of New York, P.C.


Christina Tuohy, P.E.
Vice President

Appendix A
Groundwater Remediation
System Startup Summary
Report

Colesville Landfill, Broome
County, New York
NYSDEC Site 704010

Prepared for:
Broome County Division of Solid Waste
Management

Prepared by:
ARCADIS G&M, Inc.
88 Duryea Road
Melville
New York 11747
Tel 631 249 7600
Fax 631 249 7610

Our Ref.:
NY000949.0014.0004

Date:
15 May 2003

*This document is intended only for the use
of the individual or entity for which it was
prepared and may contain information that
is privileged, confidential, and exempt from
disclosure under applicable law. Any
dissemination, distribution, or copying of
this document is strictly prohibited.*

Disclosure Statement	A-1
1. Introduction	A-2
2. Pre-Startup Injection Well Monitoring	A-2
3. Groundwater Pump-and-Treat System Startup	A-2
3.1 PT System Mechanical Testing	A-2
3.2 PT System Startup Performance Testing	A-3
4. Automated Reagent Injection System Startup	A-4
4.1 System Mechanical Testing and Startup	A-5
4.2 System Startup Performance Testing	A-5
5. Conclusions	A-6

Tables

A-1	Pump-and-Treat System Startup Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.
A-2	Concentrations of Compounds Detected in Groundwater Samples Collected During System Startup, Groundwater Remediation System, Colesville Landfill, Broome County, New York.
A-3	Concentrations of Volatile Organic Compounds Detected in Air Stripper Effluent, Groundwater Remediation System, Colesville Landfill, Broome County, New York.
A-4	Initial Automated Reagent Injection System Input Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.
A-5	Initial Automated Reagent Injection System Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Figures

A-1	Site Location Map, Colesville Landfill, Broome County, New York.
A-2	Site Plan, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

- A-3 Piping and Instrumentation Diagram, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Attachment

- A-1 NYSDEC DAR-1 Results

ARCADIS

Groundwater Remediation System Startup Summary

Colesville Landfill, Broome
County, NYSDEC Site
704010

Disclosure Statement

The laws of New York State require that the corporations which render engineering services in New York be owned by individuals licensed to practice engineering in the State. ARCADIS cannot meet that requirement. Therefore, all engineering services rendered to Broome County in New York are being performed by ARCADIS Engineers and Architects of New York, P.C., a New York Professional corporation qualified to render professional engineering in New York. There is no surcharge or extra expense associated with the rendering of professional services by ARCADIS Engineers and Architects of New York, P.C.

ARCADIS is performing all those services that do not constitute professional engineering, and is providing administrative and personnel support to ARCADIS Engineers and Architects of New York, P.C. All matters relating to the administration of the contract with Broome County are being performed by ARCADIS pursuant to its Amended and Restated Services Agreement with ARCADIS Engineers and Architects of New York, P.C.

1. Introduction

ARCADIS was retained by Broome County to design and construct a groundwater remediation system at the Colesville Landfill in Broome County, New York (site). The site location is shown on Figure A-1. The Groundwater Remediation System is comprised of a groundwater pump-and-treat (PT) system combined with an automated reagent injection (ARI) system for in-situ enhanced reductive dechlorination (ERD). The groundwater remediation system design was approved on August 24, 2000 by the New York State Department of Environmental Conservation (NYSDEC). This Groundwater Remediation System Startup Summary Report documents the system startup conducted from August 27, 2002 to September 12, 2002. System startup was conducted in accordance with the Groundwater Remediation System Startup and Performance Analysis Plan which was submitted to the NYSDEC on June 28, 2002.

2. Pre-Startup Injection Well Monitoring

Prior to system startup, groundwater samples were collected from Injection Wells IW-3, IW-8, and IW-13 on August 30, 2002 for field testing of pH and laboratory analysis of total organic carbon (TOC). TOC samples were analyzed using USEPA Method 415.1. TOC and pH results from the three injection wells were used to establish baseline (pre-injection) groundwater conditions along the injection perimeter. Baseline TOC and pH results are provided in Table A-3 of the 2002 Annual Report, the locations of all injection wells are shown on Figure A-2.

3. Groundwater Pump-and-Treat System Startup

The following section describes the startup procedures and system performance monitoring for the PT system.

3.1 PT System Mechanical Testing

Mechanical testing of the PT system was conducted from August 27, 2002 to September 7, 2002. Mechanical testing of the PT system consisted of testing each system component to ensure that it performed in conformance with the Design Drawings and manufacturers specifications. Individual components tested included the pneumatic recovery pumps in recovery wells GMPW-3, GMPW-4 and GMPW-5, air compressor AC-200, low profile air stripper AS-100, blower B-300, transfer pump TP-400, and all associated piping and appurtenances. In addition to testing individual components, the PT system was temporarily operated as a whole to ensure smooth

operation and to test PT system alarms, interlocks, and controls. During the mechanical testing, all system components, alarms, interlocks, and controls operated in conformance with their respective design criteria and manufacturers specifications. The PT system was permanently brought on-line on September 8, 2002.

3.2 PT System Startup Performance Testing

System startup performance testing was conducted from September 8, 2002 to September 12, 2002. System startup performance testing consisted of recording system operating parameters on a daily basis and collecting system performance samples on September 8, 2002 and September 10, 2002.

Table A-1 summarizes the significant PT system operating parameters recorded during startup. System operating parameters were recorded on an hourly basis during the first day of startup and were recorded twice per day thereafter. As shown in Table A-1, individual recovery well average daily flowrates ranged from 0.55 to 0.59 gallons per minute (gpm) for Well GMPW-3, from 0.20 to 0.22 gpm for Well GMPW-4, and from the 0.35 to 0.39 gpm for Well GMPW-5. The total effluent daily average flow-rate ranged from 1.01 to 1.05 gpm. During the PT system performance monitoring, water level measurements were collected from the individual recovery wells; however, the water level fell below the top of each respective pneumatic recovery pump and the water level measuring device was unable to take an accurate reading. Based on water level measurements within the recovery wells, calculated daily average flowrates, and the maximum flowrate capable of each pneumatic pump, groundwater is being extracted from the recovery wells at a rate equal to or greater than the rate of recovery. Low profile air stripper system operating parameters were consistent with the design criteria and the manufacturer's specifications. The low profile air stripper blower B-300 effluent flow-rate ranged from 142.2 to 426.3 standard cubic feet per minute (scfm), while the discharge pressure ranged from 6.0 to 8.2 inches of water column (i.w.c.). The effluent flowrate of 426.3-scfm and discharge pressure of 6.0 i.w.c. were recorded immediately following system startup and do not represent normal operating conditions.

Table A-2 summarizes the PT system performance sampling results. PT system performance samples were collected on September 8, 2002 and September 10, 2002. The collection of PT samples included:

- Individual recovery well samples for Wells GMPW-3, GMPW-4, and GMPW-5.

ARCADIS

Groundwater Remediation System Startup Summary

Colesville Landfill, Broome
County, NYSDEC Site
704010

- Total influent to low profile air stripper AS-100.
- Total effluent from AS-100 prior to entering bag filters BF-400/401; and,
- Total effluent from low profile air stripper AS-100 immediately following bag filters BF-400/401.

All groundwater samples were analyzed for volatile organic compounds (VOCs) using USEPA Method 8260 and total iron following USEPA Method 6010. According to the New York State Department of Environmental Conservation (NYSDEC) Technical and Operational Guidance Series (TOGS) 1.2.1, one of the purposes of the Model Technology Best Professional Judgment (BPJ) limits is to provide guidance to NYSDEC staff responsible for writing requirements equivalent to SPDES permits for discharges from remediation sites. As such, these values have been selected as the effluent design criteria for the PT system. As shown in Table A-2, all groundwater COCs were effectively treated to below their respective BPJ limits via the low profile air stripper and cartridge filters.

As indicated in Table A-2, the majority of the VOC analytical results are denoted as estimated values because of an oversight by the groundwater analytical laboratory. These samples were analyzed outside of the recommended 14-day USEPA holding times. ARCADIS has discussed the exceeded holding times with the analytical laboratory on several occasions who has ensured us that the oversight will not occur again.

In addition to groundwater samples, an effluent vapor samples were collected from the discharge stack of low profile air stripper AS-100 on September 8 and September 10, 2002. All vapor samples were analyzed using a modified (direct-inject) USEPA Method TO-14/15. Vapor analytical results are provided in Table A-3. A NYSDEC Air Guide DAR-1 model was performed utilizing the effluent vapor analytical data. Based on the DAR-1 analysis, all COCs in vapor are well below their respective short-term guidance concentrations (SGCs) and annual guidance concentrations (AGCs). A printout of the DAR-1 results has been provided in Attachment A-1.

4. Automated Reagent Injection System Startup

The following section describes the startup procedures and system performance monitoring for the ARI system.

4.1 System Mechanical Testing and Startup

Mechanical testing of the ARI system was conducted from August 27, 2002 to September 7, 2002. Mechanical testing of the ARI system consisted of testing each system component to ensure that it performed in conformance with the Design Drawings and manufacturer's specifications. Individual components tested included molasses pump MP-700, transfer pumps TP-600 and TP-900, molasses mixer MM-800, and all associated piping and appurtenances. In addition to testing individual components, the automated reagent injection system was temporarily operated as a whole to ensure smooth operation and to test PT system alarms, interlocks, and controls. This consisted of performing manual mixing and injection sequences (20-gallons of molasses solution to each injection well) on September 7, 2002. During the mechanical testing, all system components, alarms, interlocks, and controls operated in conformance with their respective design criteria and manufacturer's specifications. However, it was determined that an electrically actuated ball valve (designated as SV-26, see Figure A-3) was required to control the input of raw molasses during a molasses reagent mixing event. In addition, it was determined that low-flow alarms were required for both the raw molasses-feed line and the molasses solution injection line. The raw molasses feed line low-flow alarm will serve as the indicator that the raw molasses totes are empty. The molasses solution injection line low-flow alarm will serve as a backup to pressure switch high PSH-902 and will assist in shutting the ARI system down in the event of an injection well fouling, pipe break, or pump failure. The ARI system was permanently brought on-line on September 8, 2002.

4.2 System Startup Performance Testing

ARI system startup performance testing was conducted on September 8, 2002. System performance testing consisted of visually observing system operation and recording system operating parameters during the first day of system operation. Prior to initiating the initial ARI sequence, system input parameters were defined to set the molasses solution strength, molasses solution injection volume to each well, rinse water injection volume to each well, and injection frequency. These parameters were defined based on field and analytical data collected from the ERD Pilot Test (ARCADIS Geraghty & Miller 1998). Table A-4 summarizes the initial ARI system input parameters. During the first day of operation, minor system control problems were encountered; therefore, the initial automated mixing and injection sequence was conducted at two intervals during the day in order to test and correct the deficiencies.

Table A-5 summarizes the significant system operating parameters recorded during the first day of automated operation and during the manual injection performed on September 7, 2002. As discussed above, the initial automated injection was conducted over two intervals to correct system control deficiencies; therefore, these injection parameters do not reflect the actual ARI input parameters (Table A-4). Following the third injection interval, all operational deficiencies were corrected. Molasses solution injections thereafter will be conducted in accordance with the input parameters listed in Table A-4 unless otherwise specified in subsequent quarterly monitoring reports.

5. Conclusions

Based on the results of the system mechanical testing and system startup performance testing, the Groundwater Remediation System is performing as designed. The PT system is achieving the maximum possible groundwater recovery rate and is effectively treating impacted groundwater to below BPJ Limits. In addition, low profile air stripper AS-100 air emissions are well below the NYSDEC DAR-1 regulatory standards. Following minor ARI system control problems encountered during the first day of system operation, the ARI system was fully operational and has performed in conformance with its design criteria. Long-term PT system and ARI system monitoring and reporting will be conducted in accordance with the Long-Term Monitoring Plan submitted to the NYSDEC on June 28, 2002.

ARCADIS

Table A-1. Pump-and-Treat System Startup Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Date	Time Recorded	Air Stripper Measurements			Flow Measurements				
		Blower Discharge Pressure	Blower Effluent Flowrate	Total Effluent Totalizer	Water Bypass Totalizer	GMPW-3 Totalizer	GMPW-4 Totalizer	GMPW-5 Totalizer	
		PI-301 (i.w.c.)	(scfm)	FQI-401 (gallons)	FQI-402 (gallons)	FQI-101 (gallons)	FQI-102 (gallons)	FQI-103 (gallons)	
9/8/2002	8:45 AM	6.0	426.3	1,778.5	14.2	846.2	554.8	691.0	
	10:30 AM	8.0	181.7	1,881.1	42.5	891.5	577.5	738.2	
	11:30 AM	8.0	175.8	1,944.1	42.5	923.8	589.1	758.5	
	12:30 PM	8.2	158.0	2,000.8	40.3	962.8	603.4	782.5	
	1:30 PM	8.2	163.6	2,070.7	42.5	996.5	616.2	804.3	
	2:30 PM	8.2	166.5	2,133.5	42.5	1,027.5	627.8	824.6	
	3:30 PM	8.2	179.4	2,176.0	42.5	1,061.3	640.3	845.9	
9/9/2002	4:30 PM	8.2	157.7	2,249.3	42.5	1,094.9	652.7	867.1	
	5:30 PM	8.2	166.3	2,319.0	42.5	1,137.5	668.0	894.8	
	Average Daily Flowrate (gpm) =				1.03	0.05	0.22	0.39	
	8:30 AM	8.2	149.4	3,255.2	771.1	1,651.1	852.3	1,216.5	
	4:15 PM	8.2	143.3	3,724.9	1,237.2	1,918.2	947.6	1,381.0	
	Average Daily Flowrate (gpm) =				1.01	0.57	0.21	0.35	
	7:40 AM	8.2	154.0	4,695.5	2,200.9	2,461.8	1,138.0	1,717.0	
9/10/2002	6:20 PM	8.1	147.8	5,357.9	2,858.9	2,837.5	1,269.8	1,949.6	
	Average Daily Flowrate (gpm) =				1.04	0.59	0.21	0.36	
	7:40 AM	8.1	142.2	6,202.2	3,698.1	3,298.0	1,432.3	2,238.0	
	5:15 PM	8.2	147.1	6,800.4	4,292.8	3,628.5	1,550.3	2,447.9	
	Average Daily Flowrate (gpm) =				1.04	0.57	0.21	0.37	
	7:40 AM	8.2	154.9	7,698.6	5,186.1	4,118.4	1,725.6	2,760.3	
	4:20 PM	8.2	160.6	8,244.5	5,739.3	4,413.1	1,831.0	2,948.9	
9/12/2002	Average Daily Flowrate (gpm) =				1.05	0.57	0.20	0.36	

See Notes on Last Page of Table

ARCADIS

Table A-1. Pump-and-Treat System Startup Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Page 2 of 2

Notes:

gpm	Gallons per minute.
i.w.c.	Inches of water column
acfm	Actual cubic feet per minute

ARCADIS

Table A-2. Concentrations of Compounds Detected in Groundwater Samples Collected During System Startup, Colesville Landfill Groundwater Remediation System, Broome County, New York.

Constituents	Model Technology BPJ Limits ^{1,2} (ug/L)	Sample ID: Date:	GMPW-3* 9/8/2002	GMPW-3* 9/10/2002	GMPW-4* 9/8/2002	GMPW-4* 9/10/2002
VOCs (units in ug/L)						
Chloromethane	10	<	1.0	J	1.0	J
Vinyl Chloride	10-50		12	J	18	J
Chloroethane	-		13	J	22	J
1,1-Dichloroethene	10		3.6	J	6.3	J
Methylene Chloride	10-50		22	J	31	J
trans-1,2-Dichloroethene	10-50	<	1.0	J	1.0	J
1,1-Dichloroethane	10		60	J	84	J
cis-1,2-Dichloroethene	10		48	J	92	J
Chloroform	-		1.3	J	1.0	J
1,1,1-Trichloroethane	10-20		110	J	140	J
Benzene	5		11	J	13	J
1,2-Dichloroethane	10-30	<	1.0	J	1.1	J
Trichloroethene	10		67	J	100	J
Ethyl Benzene	5	<	1.0	J	4.4	J
m+p-Xylenes	5		2.8	J	15	J
o-Xylene	5	<	1.0	J	4.8	J
1,2,4-Trimethylbenzene	-	<	1.0	J	1.1	J
Dichlorodifluoromethane	-		3.0	J	3.8	J
Total VOCs			350.70	338.00	536.50	504.20
Metals (units in mg/L)						
Model Technology Sample ID: GMPW-3* GMPW-4* GMPW-4*						
BPJ Limits ^{3,4} Date: 9/8/2002 9/10/2002 9/10/2002						
Total Iron	1.2 / 0.61		1.66	0.653	1.69	0.584
See Notes on Last Page.						

ARCADIS

Table A-2. Concentrations of Compounds Detected in Groundwater Samples Collected During System Startup, Colesville Landfill Groundwater Remediation System, Broome County, New York.

Constituents	Model Technology BPJ Limits ¹ (ug/L)	Sample ID: Date:	GMPW-5* 9/8/2002	GMPW-5* 9/10/2002	Influent 9/8/2002	Influent* 9/10/2002
VOCs (units in ug/L)						
Chloromethane	10	<	1.0	J	2.1	J
Vinyl Chloride	10-50	<	1.0	J	3.4	J
Chloroethane	--	<	1.0	J	3.9	J
1,1-Dichloroethene	10	<	1.0	J	1.4	J
Methylene Chloride	10-50	<	1.5	J	7.6	J
trans-1,2-Dichloroethene	10-50	<	1.0	J	1.0	J
1,1-Dichloroethane	10	<	2.6	J	17	J
cis-1,2-Dichloroethene	10	<	2.6	J	17	J
Chloroform	--	<	1.0	J	1.0	J
1,1,1-Trichloroethane	10-20	<	4	J	32	J
Benzene	5	<	1.0	J	3	J
1,2-Dichloroethane	10-30	<	1.0	J	1.0	J
Trichloroethene	10	<	3.1	J	24	J
Ethyl Benzene	5	<	1.0	J	1.0	J
m+p-Xylenes	5	<	8.6	J	7.6	J
o-Xylene	5	<	2.4	J	2.1	J
1,2,4-Trimethylbenzene	--	<	1.0	J	1.0	J
Dichlorodifluoromethane	--	<	1.0	J	1.0	J
Total VOCs			25.10	25.40	121.10	203.40
Metals (units in mg/L)						
Model Technology BPJ Limits ^{3,4} (mg/L)	Sample ID: Date:	GMPW-5* 9/8/2002	GMPW-5* 9/10/2002	Influent 9/8/2002	Influent* 9/10/2002	
Total Iron	1.2 / 0.61	0.407	1.27	0.590	0.386	
See Notes on Last Page.						

ARCADIS

Table A-2. Concentrations of Compounds Detected in Groundwater Samples Collected During System Startup, Colesville Landfill Groundwater Remediation System, Broome County, New York.

Constituents	Model Technology BPJ Limits ¹ (ug/L)	Sample ID: Date:	Effluent-BC 9/8/2002	Effluent-BC 9/10/2002	Effluent-AC 9/8/2002	Effluent-AC* 9/10/2002
VOCs (units in ug/L)						
Chloromethane	10		-	-	1.8	< 1.0 J
Vinyl Chloride	10-50		-	-	< 1.0	< 1.0 J
Chloroethane	-		-	-	< 1.0	< 1.0 J
1,1-Dichloroethene	10		-	-	< 1.0	< 1.0 J
Methylene Chloride	10-50		-	-	< 1.0	< 1.0 J
trans-1,2-Dichloroethene	10-50		-	-	< 1.0	< 1.0 J
1,1-Dichloroethane	10		-	-	< 1.0	< 1.0 J
cis-1,2-Dichloroethene	10		-	-	< 1.0	< 1.0 J
Chloroform	-		-	-	< 1.0	< 1.0 J
1,1,1-Trichloroethane	10-20		-	-	< 1.0	< 1.0 J
Benzene	5		-	-	< 1.0	< 1.0 J
1,2-Dichloroethane	10-30		-	-	< 1.0	< 1.0 J
Trichloroethene	10		-	-	< 1.0	< 1.0 J
Ethyl Benzene	5		-	-	< 1.0	< 1.0 J
m+p-Xylenes	5		-	-	< 2.0	< 2.0 J
o-Xylene	5		-	-	< 1.0	< 1.0 J
1,2,4-Trimethylbenzene	-		-	-	< 1.0	< 1.0 J
Dichlorodifluoromethane	-		-	-	< 1.0	< 1.0 J
Total VOCs			0.00	0.00	1.8	0.00
Metals (units in mg/L)						
Model Technology BPJ Limits ^{3,4} (mg/L)	Sample ID: Date:	Effluent-BC 9/8/2002	Effluent-BC 9/10/2002	Effluent-AC 9/8/2002	Effluent-AC* 9/10/2002	
Total Iron	1.2 / 0.61	1.47	0.505	< 0.035	< 0.035	

See Notes on Last Page.

ARCADIS

Table A-2. Concentrations of Compounds Detected in Groundwater Samples Collected During System Startup, Colesville Landfill Groundwater Remediation System, Broome County, New York.

Notes:

1. Model Technology BPJ Limits recommended for Air Stripping with appropriate pretreatment from Attachment C of TOGS 1.2.1.
2. When a range is listed for the BPJ limit, a variation in available references was found. Recommended daily maximum limits should be in this range.
3. Model Technology BPJ Limits recommended for Lime, Settle and Filter treatment.
4. The recommended daily max permit limit is 1.2 mg/L and the recommended daily average permit limit is 0.61 mg/L.
5. Groundwater Remediation System startup completed on September 8, 2002.
6. Production wells were sampled in accordance with the schedule set forth in Table 3 of the Long-Term Monitoring Plan (ARCADIS 2002).

J	Estimated value.
ug/L	Micrograms per liter.
mg/L	Milligrams per liter.
Bold	Constituent detected above method detection limit.
VOCs	Volatile Organic Compounds
*	Indicates sample exceeded the recommended USEPA holding time for VOCs.
AC	After Cartridge Filter
BC	Before Cartridge Filter

ARCADIS

Table A-3. Concentrations of Volatile Organic Compounds Detected in Air Stripper Effluent, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Compounds	CAS Numbers	Sample ID: Date Sampled:	Effluent_ Day 1	Effluent_ Day 3
			9/8/2002 ppb	9/10/2002 ppb
Vinyl Chloride	75-01-4		ND	ND
Chloroethane(Ethyl Chloride)	75-00-3		ND	ND
1,1-Dichloroethene(Vinylidene Chloride)	75-35-4		ND	ND
Methylene Chloride(Dichloromethane)	75-09-2		ND	12
1,1-Dichloroethane	75-34-3		ND	ND
cis-1,2 - Dichloroethylene	156-59-2		ND	ND
Chloroform	67-66-3		ND	ND
1,1,1-Trichloroethane(Methyl Chloroform)	71-55-6		ND	ND
Benzene	71-43-2		ND	ND
Trichloroethene	79-01-6		ND	ND
Toluene	108-88-3		7.4	5.6
Ethyl benzene	100-41-4		ND	ND
m,p-Xylene	108-38-3/106-42-3		ND	ND
o-Xylene	95-47-6		ND	ND
1,2,4-Trimethylbenzene	95-63-6		ND	ND
2-Propanol (Isopropyl alcohol)	67-63-0		18	10
Dichlorodifluoromethane(Freon 12)	75-71-8		ND	ND

ppb: parts per billion

ND: Denotes analyte not detected at or above it's laboratory quantification limit.

Notes/Assumptions:

1. Samples collected by ARCADIS personnel on the dates shown and submitted to Air Toxics Laboratories LTD.
for volatile organic compound (VOC) analyses using a modified USEPA Method TO 14A/15.
2. Compounds listed were detected in influent groundwater and/or air stripper effluent during startup.

ARCADIS

Table A-4. Initial Automated Reagent Injection System Input Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Molasses to Water Ratio (%) =	27	Programmed Mixing Time (min.) ¹ =	30
Injection Frequency (per week) =	2	PSL-701 Setpoint (i.w.c.) =	NA
PSH-902 Setpoint (psi) =	39	PSN-901 Setpoint (psi) =	20
FAL-701 Setpoint (gpm) =	0.33	FAL-901 Setpoint (gpm) =	1

Injection Well ID	Molasses Solution Injection Quantity (gal.)	Rinse ² Quantity (gal.)	Raw Molasses Per Well (gal.)
PW-6	37	5	10
IW-3	37	5	10
IW-1	37	4	10
IW-2	37	3	10
GMMW-1	37	3	10
IW-4	37	4	10
IW-5	37	5	10
IW-6	37	7	10
IW-7	37	8	10
IW-8	37	9	10
IW-9	37	11	10
IW-10	37	12	10
IW-11	37	13	10
IW-12	37	15	10
IW-13	37	16	10
IW-14	37	18	10
IW-15	37	19	10

Notes:

- gal. Gallons
min. Minutes
i.w.c. Inches of water column.
psi Pounds per square inch.
gpm Gallons per minute.
NA Not applicable.
FAL Flow alarm low.
PSH Pressure switch high.
PSL Pressure switch low.
PSN Pressure switch normal.
1. Programmed mixing time is calculated from the expiration time of the molasses injection countdown timer to the startup of transfer pump TP-900 during an injection sequence or from the end of transfer pump TP-600 operation to the restart of an injection during a mixing sequence.
 2. Rinse quantity is approximately 1-pipeline volume for each injection well.

Table A-5. Initial Automated Reagent Injection System Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Initial Injection - Injection Number 1a ⁴					
Injection Date = 9/7/2002					
Molasses to Water Ratio (%) =		27		Programmed Mixing Time (min.) ¹ =	
				30	
Injection Well ID	Molasses Solution Injection Quantity (gal.)	Rinse ² Quantity (gal.)	Raw Molasses Per Well (gal.)	Max. Injection Flowrate (gpm)	Max. Injection Pressure (psi)
PW-6	20	5	5.40	14.7	31
IW-3	20	5	5.40	16.7	34
IW-1	20	4	5.40	15.5	35
IW-2 ³	18	3	4.86	16.3	33
GMMW-1	20	3	5.40	12.8	36
IW-4	20	4	5.40	15.6	36
IW-5	20	5	5.40	17.1	34
IW-6	20	7	5.40	15.1	34
IW-7	20	8	5.40	13.5	36
IW-8	20	9	5.40	15.8	34
IW-9	20	11	5.40	16.1	33
IW-10	20	12	5.40	16	33
IW-11	20	13	5.40	15.8	34
IW-12	20	15	5.40	15.8	34
IW-13	20	16	5.40	15.9	33
IW-14	20	18	5.40	10.9	36
IW-15	20	19	5.40	12.8	34
Totals (gal.) =	338	157	91.26	NA	NA

Notes:

- gal. Gallons
min. Minutes
psi Pounds per square inch.
gpm Gallons per minute.
NA Not applicable.
1. Programmed mixing time is calculated from the expiration time of the molasses injection countdown timer to the startup of transfer pump TP-900 during an injection sequence or from the end of transfer pump TP-600 operation to the restart of an injection during a mixing sequence.
 2. Rinse quantity is approximately 1-pipeline volume for each injection well.
 3. A reduced quantity of molasses solution injected into well IW-2 because of an unsecured wellhead.
 4. Initial injection performed on September 7, 2002 was conducted manually to test system equipment.

ARCADIS

Table A-5. Initial Automated Reagent Injection System Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Initial Injection - Injection Number 1b

Injection Date = 9/8/2002

Molasses to Water Ratio (%) = 27 Programmed Mixing Time (min.)¹ = 30

Injection Well ID	Molasses Solution Injection Quantity (gal.)	Rinse ² Quantity (gal.)	Raw Molasses Per Well (gal.)	Max. Injection Flowrate (gpm)	Max. Injection Pressure (psi)
PW-6	5	5	1.35	NM	NM
IW-3	5	5	1.35	NM	NM
IW-1	5	4	1.35	NM	NM
IW-2	5	3	1.35	NM	NM
GMMW-1	5	3	1.35	NM	NM
IW-4	5	4	1.35	NM	NM
IW-5	5	5	1.35	NM	NM
IW-6	5	7	1.35	NM	NM
IW-7	5	8	1.35	NM	NM
IW-8	5	9	1.35	NM	NM
IW-9	5	11	1.35	NM	NM
IW-10	5	12	1.35	NM	NM
IW-11	5	13	1.35	NM	NM
IW-12	5	15	1.35	NM	NM
IW-13	5	16	1.35	NM	NM
IW-14	5	18	1.35	NM	NM
IW-15	5	19	1.35	NM	NM
Totals (gal.) =	85	157	22.95	NA	NA

Notes:

gal. Gallons
min. Minutes
psi Pounds per square inch.
gpm Gallons per minute.
NM Not measured.
NA Not applicable.

1. Programmed mixing time is calculated from the expiration time of the molasses injection countdown timer to the startup of transfer pump TP-900 during an injection sequence or from the end of transfer pump TP-600 operation to the restart of an injection during a mixing sequence.
2. Rinse quantity is approximately 1-pipeline volume for each injection well.

ARCADIS

Table A-5. Initial Automated Reagent Injection System Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Initial Injection - Injection Number 1c

Injection Date = 9/8/2002

Molasses to Water Ratio (%) = 27

Programmed Mixing Time (min.)¹ = 30

Injection Well ID	Molasses Solution Injection Quantity (gal.)	Rinse ² Quantity (gal.)	Raw Molasses Per Well (gal.)	Max. Injection Flowrate (gpm)	Max. Injection Pressure (psi)
PW-6	12	5	3.24	15.8	34
IW-3	12	5	3.24	15.9	33
IW-1	12	4	3.24	15	35
IW-2	12	3	3.24	15.5	33
GMMW-1	12	3	3.24	15.5	33
IW-4	12	4	3.24	13	35
IW-5	12	5	3.24	14.4	35
IW-6	12	7	3.24	14.6	35
IW-7	12	8	3.24	12.8	35
IW-8	12	9	3.24	11.7	37
IW-9	12	11	3.24	11.6	37
IW-10	12	12	3.24	12.6	36
IW-11	12	13	3.24	13.5	36
IW-12	12	15	3.24	13.5	35
IW-13	12	16	3.24	11	37
IW-14	12	18	3.24	7.6	38
IW-15	12	19	3.24	10.3	37

Totals (gal.) = 204 157 55.08 NA NA

Notes:

gal. Gallons
min. Minutes
psi Pounds per square inch.
gpm Gallons per minute.
NA Not applicable.

1. Programmed mixing time is calculated from the expiration time of the molasses injection countdown timer to the startup of transfer pump TP-900 during an injection sequence or from the end of transfer pump TP-600 operation to the restart of an injection during a mixing sequence.
2. Rinse quantity is approximately 1-pipeline volume for each injection well.

ARCADIS

Attachment A-1

NYSDEC DAR-1 Results

Table A1-1. NYSDC DAR-1 Air Modeling Data, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Parameters for 9/8/2002 Sampling Event

Discharge Temperature	T	524.67	°R
Ambient Temperature	Ta	529.67	°R
Stack Diameter	D	6	in
Stack Radius	R	0.25	ft
Stack Area	A	0.20	ft ²
Exit Velocity	V	14.03	fps
Exit Flow	Q	165	acfm
Exit Flow	Q	166	scfm
Stack Height	h _s	17	ft
Building Height	h _b	13.25	ft
Ratio of Heights	h _s /h _b	1.28	
Plume rise credit? h _s /h _b > 1.5?	(if no, h _e =h _s)	(If Yes, h _e = h _s + 1.1 (F _m) ^{1/3})	
Momentum Flux	F _m = Ta/T * V ² * R ²	n/a	ft ⁴ /s ²
Effective Stack Height	h _e	17.00	ft
Reduction Factor? 2.5 > h _s /h _b > 1.5?		No, do not reduce impact	
Actual Annual Impact	C _a	RF*6*Q _s /h _e ^{2.25}	
Mass Flow	Q _a	S lbs emitted for last 12 months	

fps: feet per second

acfm: actual cubic feet per minute

ug/m³: micrograms per cubic meter

lb/yr: pounds per year

lb/hr: pounds per hour

ppb: parts per billion

Notes/Assumptions:

1. The stack discharge temperature is 65°F based on recorded parameters.
2. The ambient temperature is approximately 70°F, the average temperature during start-up.
3. Calculations assume that the system will run with the maximum allowable concentrations between quarterly readings.
4. AGC refers to the Annual Guideline Concentration as determined using the hand calculations in the DAR-1 AGC/SGC Tables dated July 12, 2000.
5. To be conservative the lower detection limit was used for compounds that were below the limit of detection, but are found in the influent groundwater of the Groundwater Remediation System.

ARCADIS

Table A1-1. NYSDEC DAR-1 Air Modeling Data, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Calculation of AGC based on 9/8/2002 Sampling Event									
Compounds	CAS Numbers	Maximum Limit on (AGC ¹) C _a	Maximum Mass Flow Q _a lb/yr	Lab Data 9/8/02 ppb	Detection Limit Used ⁵	Actual Emissions C _a ug/m ³	Actual Mass Flow per Hour lb/hr	Actual Mass Flow per Year lb/yr	Percent of Annual %
Vinyl Chloride	75-01-4	0.02	1.96	5	*	12.99	8.09E-06	0.07047	3.60
Chloroethane(Ethyl Chloride)	75-00-3	10,000	978,044.97	5	*	13.41	8.35E-06	0.07275	0.00
1,1-Dichloroethene(Vinylidene Chloride)	75-35-4	0.02	1.96	5	*	20.15	1.26E-05	0.10932	5.59
Methylene Chloride(Dichloromethane)	75-09-2	2.10	205.39	5	*	17.66	1.10E-05	0.09578	0.05
1,1-Dichloroethane	75-34-3	20	1,956.09	5	*	20.57	1.28E-05	0.11159	0.01
cis-1,2 - Dichloroethylene	156-59-2	1,900	185,828.54	5	*	20.15	1.26E-05	0.10932	0.00
Chloroform	67-66-3	0.04	4.21	5	*	24.82	1.55E-05	0.13462	3.20
1,1,1-Trichloroethane(Methyl Chloroform)	71-55-6	1,000	97,804.50	5	*	27.73	1.73E-05	0.15044	0.00
Benzene	71-43-2	0.13	12.71	5	*	16.24	1.01E-05	0.08807	0.69
Trichloroethene	79-01-6	0.45	44.01	5	*	27.31	1.70E-05	0.14816	0.34
Toluene	108-88-3	400	39,121.80	7.4	*	28.34	1.77E-05	0.15375	0.00
Ethyl benzene	100-41-4	1,000	97,804.50	5	*	22.07	1.37E-05	0.11970	0.00
m,p-Xylene	108-38-3/106-42-3	700	68,463.15	5	*	21.65	1.35E-05	0.11742	0.00
o-Xylene	95-47-6	700	68,463.15	5	*	22.07	1.37E-05	0.11970	0.00
1,2,4-Trimethylbenzene	95-63-6	290	28,363.30	5	*	24.98	1.56E-05	0.13552	0.00
2-Propanol (Isopropyl alcohol)	67-63-0	7,000	684,631.48	18	*	44.97	2.80E-05	0.24396	0.00
Dichlorodifluoromethane(Freon 12)	75-71-8	12,000	1,173,653.96	5	*	12.49	7.78E-06	0.06777	0.00

fps: feet per second
 acfm: actual cubic feet per minute
 ug/m³: micrograms per cubic meter
 lb/yr: pounds per year
 lb/hr: pounds per hour
 ppb: parts per billion

Notes/Assumptions:

1. The stack discharge temperature is 65°F based on recorded parameters.
2. The ambient temperature is approximately 70°F, the average temperature during start-up.
3. Calculations assume that the system will run with the maximum allowable concentrations between quarterly readings.
4. AGC refers to the Annual Guideline Concentration as determined using the hand calculations in the DAR-1 AGC/SGC Tables dated July 12, 2000.
5. To be conservative the lower detection limit was used for compounds that were below the limit of detection, but are found in the influent groundwater of the Groundwater Remediation System.

ARCADIS

Table A1-1. NYSDEC DAR-1 Air Modeling Data, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Parameters for 9/10/2002 Sampling Event

Discharge Temperature	T	524.67	°R
Ambient Temperature	Ta	529.67	°R
Stack Diameter	D	6	in
Stack Radius	R	0.25	ft
Stack Area	A	0.20	ft ²
Exit Velocity	V	12.5	fps
Exit Flow	Q	147	acfm
Exit Flow	Q	148	scfm
Stack Height	h _s	17	ft
Building Height	h _b	13.25	ft
Ratio of Heights	h _s /h _b	1.28	
Plume rise credit? h _s /h _b > 1.5?	(If no, h _e =h _s)	(If Yes, h _e = h _s + 1.1 (F _m) ^{1/3})	
Momentum Flux	F _m = Ta/T * V ² * R ²	n/a	ft ⁴ /s ²
Effective Stack Height	h _e	17.00	ft
Reduction Factor? 2.5 > h _s /h _b > 1.5?		No, do not reduce impact	
Actual Annual Impact	C _a	RF*6*Q _a /h _e ^{2.25}	ug/m ³
Mass Flow	Q _a	S lbs emitted for last 12 months	

fps: feet per second
 acfm: actual cubic feet per minute
 ug/m³: micrograms per cubic meter
 lb/yr: pounds per year
 lb/hr: pounds per hour
 ppb: parts per billion

Notes/Assumptions:

1. The stack discharge temperature is 65°F based on recorded parameters.
2. The ambient temperature is approximately 70°F, the average temperature during start-up.
3. Calculations assume that the system will run with the maximum allowable concentrations between quarterly readings.
4. AGC refers to the Annual Guideline Concentration as determined using the hand calculations in the DAR-1 AGC/SGC Tables dated July 12, 2000.
5. To be conservative the lower detection limit was used for compounds that were below the limit of detection, but are found in the influent groundwater of the Groundwater Remediation System.

ARCADIS

Table A1-1. NYSDEC DAR-1 Air Modeling Data, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Calculation of AGC based on 9/10/2002 Sampling Event

Compounds	CAS Numbers	Maximum Limit on C _a (AGC ⁴) ug/m ³	Maximum Mass Flow Q _a lb/yr	Lab Data 9/10/02 ppb	Detection Limit Used ⁵	Actual Emissions C _a ug/m ³	Actual Mass Flow per Hour lb/hr	Actual Mass Flow per Year lb/yr	Percent of AGC %
Vinyl Chloride	75-01-4	0.02	1.96	5	*	12.99	7.21E-06	0.06277	3.21
Chloroethane(Ethyl Chloride)	75-00-3	10,000	978,044.97	5	*	13.41	7.44E-06	0.06480	0.00
1,1-Dichloroethene(Vinylidene Chloride)	75-35-4	0.02	1.96	5	*	20.15	1.12E-05	0.09737	4.98
Methylene Chloride(Dichloromethane)	75-09-2	2.10	205.39	12	*	42.37	2.35E-05	0.20474	0.10
1,1-Dichloroethane	75-34-3	20	1,956.09	5	*	20.57	1.14E-05	0.09940	0.01
cis-1,2 - Dichloroethylene	156-59-2	1,900	185,828.54	5	*	20.15	1.12E-05	0.09737	0.00
Chloroform	67-66-3	0.04	4.21	5	*	24.82	1.38E-05	0.11991	2.85
1,1,1-Trichloroethane(Methyl Chloroform)	71-55-6	1,000	97,804.50	5	*	27.73	1.54E-05	0.13400	0.00
Benzene	71-43-2	0.13	12.71	5	*	16.24	9.01E-06	0.07845	0.62
Trichloroethene	79-01-6	0.45	44.01	5	*	27.31	1.52E-05	0.13197	0.30
Toluene	108-88-3	400	39,121.80	5.6	*	21.45	1.19E-05	0.10364	0.00
Ethyl benzene	100-41-4	1,000	97,804.50	5	*	22.07	1.22E-05	0.10662	0.00
m,p-Xylene	108-38-3/106-42-3	700	68,463.15	5	*	21.65	1.20E-05	0.10459	0.00
o-Xylene	95-47-6	700	68,463.15	5	*	22.07	1.22E-05	0.10662	0.00
1,2,4-Trimethylbenzene	95-63-6	290	28,363.30	5	*	24.98	1.39E-05	0.12071	0.00
2-Propanol (Isopropyl alcohol)	67-63-0	7,000	684,631.48	5	*	12.49	6.93E-06	0.06036	0.00
Dichlorodifluoromethane(Freon 12)	75-71-8	12,000	1,173,653.96	5	*	12.49	6.93E-06	0.06036	0.00

fps: feet per second
acfm: actual cubic feet per minute
ug/m³: micrograms per cubic meter
lb/yr: pounds per year
lb/hr: pounds per hour
ppb: parts per billion

Notes/Assumptions:

1. The stack discharge temperature is 65°F based on recorded parameters.
2. The ambient temperature is approximately 70°F, the average temperature during start-up.
3. Calculations assume that the system will run with the maximum allowable concentrations between quarterly readings.
4. AGC refers to the Annual Guideline Concentration as determined using the hand calculations in the DAR-1 AGC/SGC Tables dated July 12, 2000.
5. To be conservative the lower detection limit was used for compounds that were below the limit of detection, but are found in the influent groundwater of the Groundwater Remediation System.

ARCADIS

Table A1-2: NYSDDEC Dar-1 Air Modeling Data, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Calculation of the Short-Term Guideline Concentration (SGC) for Sampling Event on 9/8/2002

Compounds	CAS Numbers	Maximum Limit (SGC)	Analytical Concentration	Detection Limit Used	Actual Emissions C_a	Mass/hour	Potential Impact (Step III.A.3 in DAR-1)	Short Term Impact (Step III.A.5 in DAR-1)	Percent of the SGC
		($\mu\text{g}/\text{m}^3$)	(ppb)		($\mu\text{g}/\text{m}^3$)	(lb/hr)	($\mu\text{g}/\text{m}^3$)	($\mu\text{g}/\text{m}^3$)	(%)
Vinyl Chloride	75-01-4	180,000	5	*	12.99	8.08E-06	0.0014	0.08973	5.0E-05
Chloroethane(Ethyl Chloride)	75-00-3	--	5	*	13.41	8.34E-06	0.0014	0.09263	NA
1,1-Dichloroethene(Vinylidene Chloride)	75-35-4	--	5	*	20.15	1.25E-05	0.0021	0.13920	NA
Methylene Chloride(Dichloromethane)	75-09-2	14,000	5	*	17.66	1.10E-05	0.0019	0.12195	8.7E-04
1,1-Dichloroethane	75-34-3	--	5	*	20.57	1.28E-05	0.0022	0.14210	NA
cis-1,2 - Dichloroethylene	156-59-2	--	5	*	20.15	1.25E-05	0.0021	0.13920	NA
Chloroform	67-66-3	150	5	*	24.82	1.54E-05	0.0026	0.17141	1.1E-01
1,1,1-Trichloroethane(Methyl Chloroform)	71-55-6	68,000	5	*	27.73	1.72E-05	0.0029	0.19156	2.8E-04
Benzene	71-43-2	1,300	5	*	16.24	1.01E-05	0.0017	0.11215	8.6E-03
Trichloroethene	79-01-6	54,000	5	*	27.31	1.70E-05	0.0029	0.18866	3.5E-04
Toluene	108-88-3	37,000	7.4	*	28.34	1.76E-05	0.0030	0.19577	5.3E-04
Ethyl benzene	100-41-4	54,000	5	*	22.07	1.37E-05	0.0023	0.15242	2.8E-04
m,p-Xylene	108-38-3/106-42-3	4,300	5	*	21.65	1.35E-05	0.0023	0.14952	3.5E-03
o-Xylene	95-47-6	4,300	5	*	22.07	1.37E-05	0.0023	0.15242	3.5E-03
1,2,4-Trimethylbenzene	95-63-6	--	5	*	24.98	1.55E-05	0.0027	0.17256	NA
2-Propanol (Isopropyl alcohol)	67-63-0	120,000	18	*	44.97	2.80E-05	0.0048	0.31064	2.6E-04
Dichlorofluoromethane(Freon 12)	75-71-8	--	5	*	25.13	1.56E-05	0.0027	0.17358	NA

$\mu\text{g}/\text{m}^3$: Micrograms per cubic meter

ppb: parts per billion

*: Analyte concentration below detection limit, detection limit was used in calculations

lb/hr: pounds per hour

--: No SGC listed for compound

Notes:

- DAR-1 refers to DAR-1 AGC/SGC Tables dated 12 July 2000
- SGC refers to the Short-Term Guideline Concentration as determined using the hand calculations in the DAR-1 AGC/SGC Tables dated July 12, 2000.
- To be conservative the lower detection limit was used for compounds that were below the limit of detection, but are found in the influent groundwater of the Groundwater Remediation System.

ARCADIS

Table A1-2: NYSDEC Dar-1 Air Modeling Data, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Calculation of the Short-Term Guideline Concentration (SGC) for Sampling Event on 9/10/2002

Compounds	CAS Numbers	Maximum Limit (SGC)	Analytical Concentration	Detection Limit Used	Actual Emissions C_a	Mass/hour	Potential Impact (Step III, A.3 in DAR-1)	Short Term Impact (Step III, A.5 in DAR-1)	Percent of the SGC
		($\mu\text{g}/\text{m}^3$)	(ppb)		($\mu\text{g}/\text{m}^3$)	(lb/hr)	($\mu\text{g}/\text{m}^3$)	($\mu\text{g}/\text{m}^3$)	(%)
Vinyl Chloride	75-01-4	180,000	5	*	12.99	7.20E-06	0.0012	0.08000	4.4E-05
Chloroethane(Ethyl Chloride)	75-00-3	--	5	*	13.41	7.43E-06	0.0013	0.08259	NA
1,1-Dichloroethene(Vinylidene Chloride)	75-35-4	--	5	*	20.15	1.12E-05	0.0019	0.12410	NA
Methylene Chloride(Dichloromethane)	75-09-2	14,000	12		42.37	2.35E-05	0.0040	0.26095	1.9E-03
1,1-Dichloroethane	75-34-3	--	5	*	20.57	1.14E-05	0.0019	0.12669	NA
cis-1,2 - Dichloroethylene	156-59-2	--	5	*	20.15	1.12E-05	0.0019	0.12410	NA
Chloroform	67-66-3	150	5	*	24.82	1.38E-05	0.0024	0.15283	1.0E-01
1,1,1-Trichloroethane(Methyl Chloroform)	71-55-6	68,000	5	*	27.73	1.54E-05	0.0026	0.17079	2.5E-04
Benzene	71-43-2	1,300	5	*	16.24	9.00E-06	0.0015	0.09999	7.7E-03
Trichloroethene	79-01-6	54,000	5	*	27.31	1.51E-05	0.0026	0.16820	3.1E-04
Toluene	108-88-3	37,000	5.6		21.45	1.19E-05	0.0020	0.13208	3.6E-04
Ethyl benzene	100-41-4	54,000	5	*	22.07	1.22E-05	0.0021	0.13589	2.5E-04
m,p-Xylene	108-38-3/106-42-3	4,300	5	*	21.65	1.20E-05	0.0021	0.13331	3.1E-03
o-Xylene	95-47-6	4,300	5	*	22.07	1.22E-05	0.0021	0.13589	3.2E-03
1,2,4-Trimethylbenzene	95-63-6	--	5		24.98	1.38E-05	0.0024	0.15385	NA
2-Propanol (Isopropyl alcohol)	67-63-0	120,000	10		24.98	1.39E-05	0.0024	0.15386	1.3E-04
Dichlorofluoromethane(Freon 12)	75-71-8	--	5	*	25.13	1.56E-05	0.0027	0.17358	NA

$\mu\text{g}/\text{m}^3$: Micrograms per cubic meter

ppb: parts per billion


*: Analyte concentration below detection limit, detection limit was used in calculations

lb/hr: pounds per hour

--: No SGC listed for compound

Notes:

- DAR-1 refers to DAR-1 AGC/SGC Tables dated 12 July 2000
- SGC refers to the Short-Term Guideline Concentration as determined using the hand calculations in the DAR-1 AGC/SGC Tables dated July 12, 2000.
- To be conservative the lower detection limit was used for compounds that were below the limit of detection, but are found in the influent groundwater of the Groundwater Remediation System.



SOURCE: U.S.G.S. QUADRANGLES, 7.5 MINUTE SERIES, AFTON, N.Y. , REVISED 1957.

copyright © 20 01

NO.	DATE	REVISION DESCRIPTION	BY
			CKD

ARCADIS G&M



88 Duryea Road
Mehville, NY 11747
Tel: (631) 246-7600 Fax: (631) 246-7610

DRAWN
KZ

DATE
12/19/02

SITE LOCATION MAP

COLESVILLE LANDFILL
BROOME COUNTY, NEW YORK

PROJECT MANAGER
KZ

LEAD DESIGN PROF.
CT

PROJECT NUMBER


NY00949.014

DEPARTMENT MANAGER
NV

CHECKED
KZ

DRAWING NUMBER

A-1



SITE PLAN

SCALE: 1"=50'-0"

NO.	DATE	REVISION DESCRIPTION	BY	CHKD
-----	------	----------------------	----	------

DRAWING CONFIDENTIAL: THIS DRAWING AND ALL INFORMATION CONTAINED THEREON IS, AND SHALL REMAIN THE PROPERTY OF ARCADIS GERAGHTY & MILLER AS AN INSTRUMENT OF PROFESSIONAL SERVICE. THIS INFORMATION SHALL NOT BE USED IN WHOLE OR IN PART WITHOUT THE FULL KNOWLEDGE AND PRIOR WRITTEN CONSENT OF ARCADIS GERAGHTY & MILLER.

COLESVILLE LANDFILL
BROOME COUNTY, NEW YORK

SITE PLAN



85 Deyou Road
Babylon, New York 11747
Tel: 631/269-7000 Fax: 631/269-7010

PROJECT MANAGER S. FELDMAN	DEPARTMENT MANAGER N. VALKENBURG
LEAD DESIGN PROFESSIONAL C. TUOHY	CHECKED K. ZIEGLER
DRAWN LMC	DATE 5/11/03
PROJECT NUMBER NY000949	DRAWING NUMBER A-2

ARCADIS

Appendix B

**Water-Level Measurement and
Groundwater Sampling Logs.**

REP-1 + MS/MSD

Page 1 of 1
Date 7/25/02

Casing Diameter (inches) 2

Well Materials	 PVC
	 ST. Steel

Pump Intake: 2' off Sanded Bottom

Volumes Purged Pump Screen is then
3' off
Sounded Bottle

Sampled By: SN ILL

By: SN JCL
Recorded: SN

[illegible]

Groundwater Sampling Form

Page 1 of 1

Project/No. NY 000949.0014.00004 Well GMMW-5

Date 7/24/02

Screen Setting	Measuring Point Description
53-63	—

Casing Diameter (inches) **2**

Static Water Level 48.92 Measured Width

Well Materials ✓ PVC
ST. Steel

Total depth 68 Pump On: 13⁵⁵

Pump Intake: 1' off bottom

Purge Method: _____ Pump Off: _____

Volumes Purged 1

Centrifugal _____ Sample Time: _____

Sampled By: SH/CL/GW

Submersible _____
Other _____ Bailer Type: _____

[illegible]

ARCADIS GERAGHTY & MILLER
Low-Flow Groundwater Sampling Log

Project Number: M900949. P14 Task: Y Well ID: GMMW-6
Date: 7-25-02 Sampled By: GW/SH/cl
Sampling Time: 11.30-12.45 Recorded By: cl
Weather: 85° F Coded Replicate No.: —

WELL INFORMATION

Casing Material: PVC Purge Method: low flow MDT Flo
Casing Diameter: 2" Purge Rate: 500 ml/min
Total Depth: sanded: 55.9' Total Volume Purged:
Depth to Water: 39.98 Pump Intake Depth: 10' screen 50'
Water Column: - Pump on: 11.42 Off: 12.30
Gallons/Foot: - Parameters Sampled: see below
Gallons in Well: -

FIELD PARAMETER MEASUREMENTS

[illegible]

Well Secure: _____
Color: VERY LIGHT BROWN
SLIGHT ODOUR

Purge Water Disposal: OTG
Turbidity(qualitative): med turbid

Groundwater Sampling Form

Page 1 of 1

Project/No. NY00949.0014.6000 Well FW-3

Date 2-23-02

Screen Setting	Measuring Point Description
4-7-29-7	PVC

Casing Diameter (inches) 2"

Static Water Level 12.31 Measured Width

Well Materials PVC
ST. Steel

Total depth 30.2 seconds Rump On: 1842
129.7

Pump Intake: Z' off battery

Purge Method Pump Off:

Volumes Purged 1

Centrifugal _____ Sample Time: _____

Submersible ☒ ~~_____~~
Other ☒ ~~_____~~ Bailer Type: 1

Sampled By: SH/GW/CL

[illegible]

ARCADIS GERAGHTY & MILLER

Groundwater Sampling Form

Page 1 of 1

Project/No. NY010949.0014.0000Y

Well PW-4

Date 1/25/07

Screen Setting	Measuring Point Description
14.7-29.7	

Casing
Diameter (inches) **Z**

Static	17 (57)	Measured Width
--------	---------	----------------

Well Materials ✓ PVC
ST. Steel

Water Level 18.73

Total depth 29.7 Pump On:

Pump Intake: 3' off bottom

Volumes Purged

Purge Method

Pump Off:

Centrifugal

Sample Time:

Submersible

Other

Bailer Type:

Sampled

By:

[illegible]

Groundwater Sampling Form

Page 1 of 1

Project/No. NY 000949.000/4.0004 Well PW-5

Date 1/25/02

Screen Setting	Measuring Point Description
4.7-29.7	1

Casing Diameter (inches) 2

Static Water Level	1.02	Measured Width	
-----------------------	------	----------------	--

Well Materials  PVC
ST. Steel

Total depth 29.7 Pump On: 13

Pump Intake: 5' off Bottom

Purge Method Pump Off: 14⁰⁰

Volumes Purged 1

Centrifugal _____
Submersible ☒ Sample Time: 19:2

Sampled By: SW/CL

Other _____ Bailer Type: _____

SH/CL
Recorded: SH

Time	Minutes Elapsed	Rate (gpm) (ML)	DTW	Gallons Purged	pH	Cond. umhos ms/cm	TURB (NTUs)	Redox (mV)	Diss. O ₂ (mg/L)	TEMP. (C) (F)	REMARKS 3)
1342		580	1.64		7.79	244	620	164	7.09	11.95	
1347		580	1.77		8.06	249	401	144	.45	10.91	
1352		400	1.71		8.12	249	438	129	.40	10.66	
1357		400	1.74		8.14	249	398	124	.37	10.55	
1402		400	1.73		8.15	249	309	117	.37	10.28	
1407		400	1.75		8.14	248	266	111	.34	10.96	
1412		400			8.15	248	231	105	.35	10.76	
Sulfide: .244											

Groundwater Sampling Form

Page 1 of 1

Well PW-7

Date 7/23/62

Casing
Diameter (inches) **2**

Well Materials  PVC

ST. Steel

Pump Intake: 5' off bottom

Volumes Purged

Sampled

By:

Other

Bailer Type:

[illegible]

ARCADIS GERAGHTY & MILLER
Low-Flow Groundwater Sampling Log

Project Number: MA00949 P14 Task: 4 Well ID: PW13
 Date: 7-23-02 Sampled By: GW/SU/CL
 Sampling Time: 08:10 Recorded By: CL
 Weather: 85 WAGY Coded Replicate No.:

WELL INFORMATION

Casing Material: 2" PVC Purge Method: Low Flow Red Flo
Casing Diameter: 2" Purge Rate: 500 mL/min
Total Depth: 78.5 Total Volume Purged: —
Depth to Water: 62.17 Pump Intake Depth: screen 43.5-78.5
Water Column: — Pump on: 08.45 Off: 09.50
Gallons/Foot: — Parameters Sampled: see below
Gallons in Well: —

FIELD PARAMETER MEASUREMENTS

[illegible]

Well Secure: _____ ✓
Color: ~~CLAY~~, NONE
NO ODOR

Purge Water Disposal: GROUND
Turbidity(qualitative): clear

ARCADIS GERAGHTY & MILLER

Groundwater Sampling Form

Page 1 of 1

Project/No. NY000999.0014.00004 Well SP-2

Date 7/25/02

Screen Setting	Measuring Point Description
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	23
24	24
25	25
26	26
27	27
28	28
29	29
30	30
31	31
32	32
33	33
34	34
35	35
36	36
37	37
38	38
39	39
40	40
41	41
42	42
43	43
44	44
45	45
46	46
47	47
48	48
49	49
50	50
51	51
52	52
53	53
54	54
55	55
56	56
57	57
58	58
59	59
60	60
61	61
62	62
63	63
64	64
65	65
66	66
67	67
68	68
69	69
70	70
71	71
72	72
73	73
74	74
75	75
76	76
77	77
78	78
79	79
80	80
81	81
82	82
83	83
84	84
85	85
86	86
87	87
88	88
89	89
90	90
91	91
92	92
93	93
94	94
95	95
96	96
97	97
98	98
99	99
100	100

Casing
Diameter (inches)

Static Water Level	_____	Measured Width	_____
-----------------------	-------	----------------	-------

Well Materials	— PVC
	— ST. Steel

Total depth 1 Pump On: 1

Pump

Purge Method	Pump Off:	—
--------------	-----------	---

Volumes Purged _____

Centrifugal _____ Sample Time: _____

Submersible _____
Other _____ Bailer Type: _____

Sampled By: BL

[illegible]

ARCADIS GERAGHTY & MILLER
Low-Flow Groundwater Sampling Log

Project Number: 14000949-0014 Task: 00004 Well ID: SP-3
Date: 7-25-02 Sampled By: _____
Sampling Time: _____ Recorded By: _____
Weather: _____ Coded Replicate No.: _____

WELL INFORMATION

Casing Material: _____ Purge Method: _____
Casing Diameter: _____ Purge Rate: _____
Total Depth: _____ Total Volume Purged: _____
Depth to Water: _____ Pump Intake Depth _____
Water Column: _____ Pump on: _____ Off: _____
Gallons/Foot: _____ Parameters Sampled: _____
Gallons in Well: _____

FIELD PARAMETER MEASUREMENTS

[illegible]

Well Secure: _____
Color: _____

Purge Water Disposal: _____
Turbidity(qualitative): _____

Groundwater Sampling Form

Page of

Other _____ Bailer Type: _____ By: _____

[illegible]

ARCADIS GERAGHTY & MILLER
Low-Flow Groundwater Sampling Log

Project Number: N4000949.004 Task: 00004 Well ID: SP-5
Date: 7-25-07 Sampled By: _____
Sampling Time: _____ Recorded By: _____
Weather: _____ Coded Replicate No.: _____

WELL INFORMATION

Casing Material: _____ Purge Method: _____
Casing Diameter: _____ Purge Rate: _____
Total Depth: _____ Total Volume Purged: _____
Depth to Water: _____ Pump Intake Depth _____
Water Column: _____ Pump on: _____ Off: _____
Gallons/Foot: _____ Parameters Sampled: _____
Gallons in Well: _____

FIELD PARAMETER MEASUREMENTS

[illegible]

Well Secure: _____
Color: _____

Purge Water Disposal: _____

Turbidity(qualitative): _____

ARCADIS GERAGHTY & MILLER

Groundwater Sampling Form

Page 1 of 1

Project/No. NY 000949-0014.00009 Well W-5

Date 1/29/02

Screen Setting	Measuring Point Description
44-59	

Casing
Diameter (inches) 2"

Static Water Level 57.94 Measured Width _____

Well Materials ✓ PVC
ST. Steel

Total depth 61.5 Pump On: 12⁴⁵

Pump Intake: 1' off bottom

Purge Method Pump Off:

Volumes Purged 1

Centrifugal _____ Sample Time: _____

Sampled By: **SH**

Submersible Other **Bailer Type:**[illegible]

ARCADIS GERAGHTY & MILLER
Low-Flow Groundwater Sampling Log

Low-Flow Groundwater Sampling Log

Project Number: <u>M000949114</u>	Task: <u>4</u>	Well ID: <u>W-6</u>
Date: <u>7-24-02</u>	Sampled By: <u>GW/SH/CL</u>	
Sampling Time: <u>16:00 - 1:00 pm</u>	Recorded By: <u>SH</u>	
Weather: <u>85° F</u>	Coded Replicate No.: <u>—</u>	

WELL INFORMATION

Casing Material: PVC Purge Method: Low-Flow Redi Flo
Casing Diameter: 2" Purge Rate: see below
Total Depth: 59.5 Total Volume Purged: —
Depth to Water: 50.57 Pump Intake Depth (15' screen)
Water Column: — Pump on: 5:30 pm Off: —
Gallons/Foot: — Parameters Sampled: see below
Gallons in Well: —

FIELD PARAMETER MEASUREMENTS

[illegible]

Well Secure: ☒
Color: GRAY

Purge Water Disposal: Ground
Turbidity(qualitative): None

ARCADIS GERAGHTY & MILLER
Low-Flow Groundwater Sampling Log

Project Number: M000949 P14 Task: 4 Well ID: W-7
 Date: 7-24-02 Sampled By: GW/SH/CL
 Sampling Time: 16:00 - Recorded By: CL
 Weather: 85° PC Coded Replicate No.: _____

WELL INFORMATION

Casing Material: PVC Purge Method: Low Flow - Redi Flow
Casing Diameter: 2" Purge Rate: _____
Total Depth: 51.5 Total Volume Purged: —
Depth to Water: 43.48 Pump Intake Depth: (15' screen)
Water Column: — Pump on: _____ Off: _____
Gallons/Foot: — Parameters Sampled: See below
Gallons in Well: —

FIELD PARAMETER MEASUREMENTS

[illegible]

Well Secure: Needs Lock Purge Water Disposal: Land Surface
Color: Reddish - Brown Sediment Turbidity(qualitative): Some
Water - clear

ARCADIS GERAGHTY & MILLER
Groundwater Sampling Form

Page 1 of 1
7/23/02

Project/No. N4000949-0014.00003 Well W-13

Screen Setting	Measuring Point Description	

Static Water Level **46.32** Measured Width

Total depth 50 Pump On: 1

Actual: approx - 55'

Purge Method _____ Pump Off: _____

Centrifugal _____ Sample Time: _____

Submersible

Other _____ Bailer Type: _____

Date 7/23/07

Casing Diameter (inches) 2

Well Materials	☒ PVC
	☐ ST Steel

Pump 11 - ET R 11

Intake: 6 off 10-10-10

Volumes Purged 1

Sampled
By: SH/6W

By: SH/6W
Receives: SN

Time	Minutes Elapsed	Rate (gpm) (ML)	DTW	Gallons Purged	pH	Cond. umhos ms/cm	TURB (NTUs)	Redox (mV)	Diss. O2 (mg/L)	TEMP. (C) (F)	REMARKS 3)
950		100	-		6.57	147 1776	55.7	-75	3.56	18.77	
Water Level Fell below Pump Screen on three Separate Attempts											
W-13 will be bailed dry - let Recover - and a Sample will be taken with a bailer by CL											
(2) @ Time of Sample 6.64 147 43.7 -75 8.37 16.35 1710											

ARCADIS GERAGHTY & MILLER
Groundwater Sampling Form

Page 1 of 1

Project/No. N4000949.0014.00004 Well W-145

Date 7/24/02

Screen Setting	Measuring Point Description
4 1/2' - 19 1/2'	—

Casing Diameter (inches) 2.0"

Static	Measured Width
24.1	24.1

Well Materials ☒ PVC

Total depth 21' Pump On: 8³⁰

Pump

Purge Method Pump Off: 9"

Volumes Purged 1

Centrifugal _____ Sample Time: 90s

Submersible 8

Sampled 20/1/84

Other ☒ Bailer Type: —

By: 6W/SA

[illegible]

ARCADIS GERAGHTY & MILLER
Low-Flow Groundwater Sampling Log

Project Number: M000944.0014 Task: 4 Well ID: W-105
Date: 7-24-02 Sampled By: GW/SH/CL
Sampling Time: 11.00 - 12.45 Recorded By: CL
Weather: 80° sunny Coded Replicate No.: —

WELL INFORMATION

Casing Material: CAN'T see Purge Method: LOW FLOW REPI FLO
Casing Diameter: 11 Purge Rate: 500 ml
Total Depth: 23' Total Volume Purged: —
Depth to Water: — Pump Intake Depth: 18'
Water Column: — Pump on: 11.33 Off: 12.20
Gallons/Foot: — Parameters Sampled: see below
Gallons in Well: —

FIELD PARAMETER MEASUREMENTS

[illegible]

Well Secure: ✓
Color: none
no odor

Purge Water Disposal: OK
Turbidity(qualitative): Clear

Groundwater Sampling Form

Page 1 of 1

Project/No. NYC00949.0014.00004 Well 41-175

Date 7/24/62

Screen Setting	Measuring Point Description
5-26	—

Casing Diameter (inches) 7"

Static	Measured Width	—
--------	----------------	---

Well Materials PVC

Water Level 10.52

ST. Steel

Total depth 20' Pump On: 11:00

Pump 1

Purge Method Pump Off: 11⁴⁵

Volumes Purged 1

Centrifugal _____ Sample Time: 11:37

Submersible _____
Other _____ Bailer Type: _____

Sampled By: CV/SH

Time	Minutes Elapsed	Rate (gpm) (ML)	DTW	Gallons Purged	pH	Cond. umhos ms/cm	TURB (NTUs)	Redox (mV)	Diss. O2 (mg/L)	TEMP. (C) (F)	REMARKS 3)
11:05		500	10.82		6.38	334	75.2	238	4.64	12.79	
11:10		↓	10.83		6.40	335	39.0	222	3.92	12.80	
11:15		↓	—		6.41	335	22.2	216	3.64	13.07	
11:20		↓	10.83		6.42	335	28.6	213	3.55	12.90	
11:25		—	—		6.42	335	28.2	213	3.57	12.97	
11:30			10.83		6.41	336	22.3	213	3.61	12.49	
11:36			10.83		6.42	335	27.9	213	3.47	12.85	
Sulfide: <.005 (under Range)											

ARCADIS GERAGHTY & MILLER
Low-Flow Groundwater Sampling Log

Project Number: M000919 P14 Task: 9 Well ID: 00 103
Date: 7-23-02 Sampled By: GLH/SH/CL
Sampling Time: 15.10-16.30 Recorded By: CL
Weather: 80° RAIN Coded Replicate No.: —

WELL INFORMATION

Casing Material: PVC Purge Method: Low Flow Redi Flow
Casing Diameter: 2" Purge Rate: ---
Total Depth: 23' Total Volume Purged: ---
Depth to Water: 11.83 Pump Intake Depth: 17' (15' screen)
Water Column: --- Pump on: 15.33 Off: 16.20
Gallons/Foot: --- Parameters Sampled: see below
Gallons in Well: ---

FIELD PARAMETER MEASUREMENTS

[illegible]

Well Secure: ☒ None
Color: no odor

Purge Water Disposal: By hand
Turbidity(qualitative): Clear

ARCADIS GERAGHTY & MILLER
Low-Flow Groundwater Sampling Log

Project Number: M020949 P14 Task: 4 Well ID: N-205
 Date: 7-23-02 Sampled By: GW/CL
 Sampling Time: 11.45-14.40 Recorded By: CL
 Weather: 80° RAIN, LIGHTNING Coded Replicate No.: —

WELL INFORMATION

Casing Material: PC Purge Method: LOW FLOW Red FLO
 Casing Diameter: 2" Purge Rate: 200 mL
 Total Depth: 22' Total Volume Purged: —
 Depth to Water: 10.10 (TOL) Pump Intake Depth: 5' from bottom screen: 122'
 Water Column: — Pump on: 12.05 to 12.45 off: 14.20 to 14.30
 Gallons/Foot: — Parameters Sampled: see below
 Gallons in Well: —

FIELD PARAMETER MEASUREMENTS

Time	Rate ml./min	Gallons Purged	Turbidity (NTUs)	REDOX (mV)	pH (SI Units)	Conductivity (µmhos/cm)	Temp (°C)	Depth to Water	Diss. Oxygen	Comments
12.05	300	—	—	258	5.62	110.3	14.5	—	4.9	
12.10	11	—	—	262	5.61	110.3	15.1	12.5	4.4	
12.15	400	—	—	270	5.59	109.5	18.6	12.5	4.4	
12.20	300	—	—	276	5.61	109.2	19.7	—	4.6	
12.25	200 350	—	—	276	5.57	108.1	19.8	12.6	4.6	
12.30	200	—	—	275	5.55	107.9	19.7	12.53	4.0	
12.35	11	—	15	269	5.52	107.9	19.6	—	3.8	
12.40	11	—	—	272	—	—	—	12.48	—	
PUMP STOPPED WORKING										
FIXED PUMP @ 1330 & PUT PUMP BACK IN WELL TO ATTEMPT PURGE										
14.00	500	—	55	294	5.50	108.9	15.5	13.64	4.3	
14.05	500	—	50	295	5.47	108.4	16.9	13.70	4.7	
14.10	11	—	—	295	5.45	107.2	17.7	13.75	4.7	
14.15	450	—	—	298	5.42	107.1	18.1	13.60	4.4	
14.20	11	—	27	298	5.40	107.1	18.6	13.56	4.2	
14.25	11	—	16	299	5.36	107.0	18.8	13.56	3.8	
SLIDE: 0.006 mg/L										

Well Secure: ☒

Purge Water Disposal: GROUND

Color: clear

Turbidity (qualitative): clear

NO ODP



CHAIN-OF-CUSTODY RECORD

Project Number/Name NY 000949.0014.00004

Project Location COLESDALE NY.

Laboratory BUCK LABS

Project Manager STEVE FELDMAN

Sampler(s)/Affiliation G.W. SH, C.L.

ANALYSIS / METHOD / SIZE	
40ml VIAL	(HCL)
125ml PAPER	(HCL)
250ml PAPER	(HCL)
500ml PAPER	(HCL)
CI, NO ₂ , NO ₃ , SO ₄	(HCL)

Sample ID/Location	Matrix	Date/Time Sampled	Lab ID	Remarks	Total
PW-13	L	7-23-02			2
PW-7		7-23-02			2
W-185		7-23-02			3
W-205		7-23-02			2
TB-7-23-02		7-23-02			2
W-145		7-24-02			2
W-175		7-24-02			2
W-165		7-24-02			2
TB-7-24-02		7-24-02			2
W-7		7-24-02			3
Total No. of Bottles/Containers					29

Sample Matrix: L = Liquid; S = Solid; A = Air

Relinquished by: D. Hume Organization: ARCADIS Date: 7/24/02 Time: 6:00

Received by: _____ Organization: _____ Date: _____ Time: _____

Relinquished by: _____ Organization: _____ Date: _____ Time: _____

Received by: _____ Organization: _____ Date: _____ Time: _____

Special Instructions/Remarks: REMARK TO DAVE EXPD 1-631-391-5284

Delivery Method: ☐ In Person

☒ Common Carrier FEDEX

☐ Lab Courier

☐ Other

Sampling of injection wells
performed by Matt Bokus
from ARCADIS (Albany office)

8/30/01

MSB

Chesille LF

IW-13

DTW: 57.82'

DTB: 79.40'

Well Vol: 4.316 gal

Vol. #	Field pH
1	6.71
2	6.52
3	6.48

1005- Collect sample. Water light brown, silty.

IW-8

DTW: 51.14'

DTB: 71.59'

Well Vol: ~4.09 gal

Vol. #	Field pH
1	7.05
2	6.61
3	6.55

1055- Collect sample. light brown very silty

IW-3

DTW: 47.21'

DTB: 64.59' (Drip tube in well)

Well Vol: 3.47 gal

Vol	Field pH
1	7.78
2	7.66
3	7.80

1135- Collect sample. light brown not as silty.

Static Water Level _____ Measured With _____ Date/Time 1-22-02

Recovery	☐	End of Test	
----------	--------------------------	-------------	--

Distance From Well
Measured To Pumping
Well# _____

Discharge
Rate _____

Orifice _____

[illegible]

Static Water Level _____ Measured With _____ Date/Time 12-9-02

Recovery ☐ End of Test _____

Distance From Well Measured To Pumping Well	Discharge Rate	Orifice
100	100	100
200	200	200
300	300	300
400	400	400
500	500	500
600	600	600
700	700	700
800	800	800
900	900	900
1000	1000	1000

Date & Time	Well Or t (mins)	Held (ft)	Wet (ft)	Depth to Water (ft)	s (ft)	Dew. 1) Corr. (ft)	Art. 2) s' (ft)	Q (gpm)	Mand-meter (in)	Remarks 3)
	GMMW-2			38.11						
	GMMW-3			49.26						
	GMMW-6			40.18						
	W-5			52.51						
	PW-4			18.81						
	W-13			48.26						
	PW-13			63.20						
	PW-5			-						ARTESIAN
	W-6			51.54						
	W-7			44.61						
	W-18			11.38						
	PW-3			-						NO PVC WELL
	W-16S			9.30						
	W-17S			11.47						
	W-20S			8.72						
	W-14S			-						
	PW-10			40.31						

Water Sampling Log

Project Colesville Landfill Project No. NY000949.001477 Page 1 of 1
 Site Location Broome County, NY Date 8-22-02
 Site/Well No. SP-5 (culvert) Replicate No. _____ Code No. _____
 Weather Immediately following 1-hour rainstorm Sampling Time: Begin 7:35pm End 7:40pm

Evacuation Data

Measuring Point _____
 MP Elevation (ft) _____
 Land Surface Elevation (ft) _____
 Sounded Well Depth (ft bmp) _____
 Depth to Water (ft bmp) _____
 Water-Level Elevation (ft) _____
 Water Column in Well (ft) _____
 Casing Diameter/Type _____
 Gallons in Well _____
 Gallons Pumped/Bailed Prior to Sampling Grab Sample
 Sample Pump Intake Setting (ft bmp) _____
 Purge Time begin _____ end _____
 Pumping Rate (gpm) _____
 Evacuation Method NA

Field Parameters

Color _____
 Odor _____
 Appearance _____
 pH (s.u.) _____
 Conductivity (mS/cm) _____
 (µmhos/cm) _____
 Turbidity (NTU) _____
 Temperature (°C) _____
 Dissolved Oxygen (mg/L) _____
 Salinity (%) _____
 Sampling Method Grab
 Remarks No flow of water
not enough rain

Constituents Sampled

Container Description

Number

Preservative

See COC _____

Sampling Personnel

J. Hime

Well Casing Volumes

Gal./Ft. 1-¼" = 0.06 2" = 0.16 3" = 0.37 4" = 0.65
 1-½" = 0.09 2-½" = 0.26 3-½" = 0.50 6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units
gpm	Gallons per minute	N/A	Not Applicable	umhos/cm	Micromhos per centimeter
mg/L	Miligrams per liter	NR	Not Recorded	VOC	Volatile Organic Compounds



ANALYSIS / METHOD / SIZE
3000 7000 12000 15000 18000 20000

Sample Matrix:	L = Liquid;	S = Solid;	A = Air
			Total No. of Bottles/ Containers
			3

Relinquished by: <u>[Signature]</u>	Organization: <u>ARCADIS</u>	Date: <u>8/23/02</u>	Time: <u>2:23 PM</u>	Seal Intact? <u>Yes</u>
Received by: <u>[Signature]</u>	Organization: <u>Rock Labs</u>	Date: <u>8/23/02</u>	Time: <u>2:33 PM</u>	Seal Intact? <u>Yes</u>
Relinquished by: _____	Organization: _____	Date: <u>1/1</u>	Time: _____	Seal Intact? _____
Received by: _____	Organization: _____	Date: <u>1/1</u>	Time: _____	Seal Intact? _____
Special Instructions/Remarks: <u>Please direct questions to Steve Tellman @ (631) 311-2244</u>				

Delivery Method: ☐ In Person ☐ Common Carrier ☒ Lab Courier ☐ Other

SPECIFY _____

SPECIFY _____

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0014 T7 Page 1 of 1
 Site Location Broome County, NY Date 8-29-02
 Site/Well No. SP-5 (culvert) Replicate No. _____ Code No. _____
 Weather Raining Sampling Time: Begin 9:15 End 9:25

Evacuation Data

Measuring Point _____
 MP Elevation (ft) _____
 Land Surface Elevation (ft) _____
 Sounded Well Depth (ft bmp) _____
 Depth to Water (ft bmp) _____
 Water-Level Elevation (ft) _____
 Water Column in Well (ft) _____
 Casing Diameter/Type _____
 Gallons in Well _____
 Gallons Pumped/Bailed
 Prior to Sampling Grab Sample
 Sample Pump Intake
 Setting (ft bmp) _____
 Purge Time begin _____ end _____
 Pumping Rate (gpm) _____
 Evacuation Method n/a

Field Parameters

Color _____
 Odor _____
 Appearance _____
 pH (s.u.) _____
 Conductivity (mS/cm) _____
 (µmhos/cm) _____
 Turbidity (NTU) _____
 Temperature (°C) _____
 Dissolved Oxygen (mg/L) _____
 Salinity (%) _____
 Sampling Method Grab
 Remarks _____

Constituents Sampled	Container Description	Number	Preservative
<u>SEE LOC</u>	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Sampling Personnel

J. Hime

Well Casing Volumes

Gal./Ft.	1-¼" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-½" = 0.09	2-½" = 0.26	3-½" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units
gpm	Gallons per minute	N/A	Not Applicable	µmhos/cm	Micromhos per centimeter
mg/L	Miligrams per liter	NR	Not Recorded	VOC	Volatile Organic Compounds



Project Number/Name NY 000948 0014.00005

Project Location COLLESVILLE LANDFILL

Laboratory B.L.L.B.s

Project Manager STEVE FLEMMING

Sampler(s)/Affiliation *Area 1's*

[illegible]

Relinquished by: <u>Shawn Bell</u>	Organization: <u>Armed:</u>	Date <u>8/30/02</u>	Time <u>1140</u>	Seal Intact?
Received by: <u>Nilean Hamster</u>	Organization: <u>Buck Labs</u>	Date <u>8/30/02</u>	Time <u>1:10</u>	Yes No <u>N/A</u>
Relinquished by: _____	Organization: _____	Date <u>1/1</u>	Time _____	Seal Intact?
Received by: _____	Organization: _____	Date <u>1/1</u>	Time _____	Yes No N/A

Special Instructions/Remarks:

Delivery Method: ☒ In Person ☐ Common Carrier ☐ Lab Courier ☐ Other SPECIFY _____



CHAIN-OF-CUSTODY RECORD

Laboratory Task Order No./P.O. No.:

Page

of-

Project Number/Name:

Colesville Landfill

Project Location _____

Broome County, NY

Laboratory_____

Environmental

Project Manager

S. Feldman

Sampler(s)/Affiliation

J. Hime

[illegible]

Sample ID/Location	Matrix	Date/Time Sampled	Lab ID																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
--------------------	--------	-------------------	--------	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

Sample Matrix: L = Liquid; S = Solid; A = Air

Relinquished by:

2021.11.11

15 SEPTEMBER 2006

Organization:

ARCADIS

Date 8/20/2019

Time 02

6:00 am

Seal Intact?

Relinquished by:

1

Organization:

Date / /

Time _____

Seal Intact?

Special Instructions/Remarks:

Delivery Method:

☒ In Person☐ Common Carrier☐ Lab Courier☐ Other:

SPECIFY

SPECIFY

AG 05-12401

Groundwater Sampling Form

Project/No.	Well	GMMW-5	Date	12/10/02
-------------	------	--------	------	----------

Static Water Level	48.78	Measured Width		Well Materials	PVC
					ST. Steel

Purge Method _____ Pump Off: _____ Volumes Purged _____ 4 gal

Centrifugal _____ **Sample Time:** 8:30
Submersible X
Other _____
Bailer Type: _____
Sampled By: _____ DD/TM

[illegible]

Groundwater Sampling Form

Page 1 of 1

Project/No.	Well	GMMW-5	Date	12/10/02
-------------	------	--------	------	----------

Screen Setting	Measuring Point Description	Casing Diameter (inches)
-------------------	--------------------------------	-----------------------------

Static Water Level	48.78	Measured Width		Well Materials	PVC
					ST. Steel

Total depth _____ Pump On: 7:44 _____ Pump Intake: _____

Purge Method _____ Pump Off: _____ Volumes Purged 4 gal

Centrifugal _____ Sample Time: 8:30
Submersible X _____ Sampled _____

Other _____ Bailer Type: _____ By: _____ DD/TM

[illegible]

Groundwater Sampling Form

Project/No. _____ Well W-5 Date 12/10/02

Static Water Level	52.52	Measured Width		Well Materials	PVC
					ST. Steel

Total depth _____ Pump On: 9:07 _____ Pump

Purge Method Pump Off: _____ Volumes Purged 4 gal

Centrifugal _____ Sample Time: 9:45

Submersible ☒ X ☐ Sampled

Other _____ Bailer Type: _____ By: _____ DD/TM

[illegible]

Page 1 of 1

[illegible]

Groundwater Sampling Form

Project/No.	Well	GMMW-6	Date	12/10/02
-------------	------	--------	------	----------

Static Water Level	40.63	Measured Width		Well Materials	PVC
					ST. Steel

Purge Method Pump Off: Volumes Purged 4 gal

Centrifugal _____ **Sample Time:** 10:35
Submersible__X
Other _____ Bailer Type: _____ Sampled By: _____ DD/TM

[illegible]

Groundwater Sampling Form

Project/No.	Well	PW-4	Date	12/10/02
-------------	------	------	------	----------

Static Water Level	18.78	Measured Width		Well Materials	PVC
					ST. Steel

Total depth _____ Pump On: 12:25 Pump

Purge Method Pump Off: Volumes Purged 4 gal

Centrifugal _____ Sample Time: 13:00

Submersible X Sampled

Other _____ Bailer Type: _____ By: _____ DD/TM

[illegible]

ARCADIS

Groundwater Sampling Form

Page 1 of 1

Project/No. _____ Well PW-10 Date 12/10/02

Screen Setting		Measuring Point Description
Casing Diameter (inches)		

Static Water Level	40.30	Measured Width		Well Materials	PVC
					ST. Steel

Total depth _____ Pump On: 15:40 Pump Intake: _____

Purge Method Pump Off: _____ Volumes Purged ____ 4 gal

Centrifugal _____ **Sample Time:** 16:20
Submersible X Sampled

Other _____ Bailer Type: _____ By: _____ DD/TM _____

[illegible]



Infrastructure, buildings, environment, communications

ARCADIS G&M, Inc.
441 New Karer Road
Suite 4
Albany
New York 12205
Tel 518 452 7826
Fax 518 452 4398

TELEFAX

To: KEN ZEGEL

Copies:

ENVIRONMENTAL

Fax: (516) 249-7610

Total pages:

Date: 1/10/03

Subject: COLESVILLE LANDFILL
FIELD LOGS - DEC. 9-10, 2002

ARCADIS Project No.: 7

NY000949.0015

From: DD

Phone Number:
x 13

If you do not receive all pages, please call to let us know as soon as possible.

THIS MESSAGE IS INTENDED ONLY FOR THE USE OF THE INDIVIDUAL OR ENTITY TO WHICH IT IS ADDRESSED AND MAY CONTAIN INFORMATION THAT IS PRIVILEGED, CONFIDENTIAL, AND EXEMPT FROM DISCLOSURE UNDER APPLICABLE LAW. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution, or copying of this communication is strictly prohibited. If you have received this communication in error, please notify us immediately by telephone and return the original message to us at the above address via the U.S. postal service.

Part of a bigger picture

12/9/02

$$w_H/2m$$

915 - Pick up sample bottles from Dick Lads

945-00/TM ARRIVE ON SITE MESS w/ JASON

Go over Stores Layout

H₂O levels

Summary: 2, 3, 11

49	76	W-18: 11.38
----	----	-------------

GW-11-6	40.18	AW-3: NO PVC well?
---------	-------	--------------------

N-5: 5281 1825:9 W-10: 9130

pw-4:	18.81	6-175: 11.47
-------	-------	--------------

W-15: 4A.26	W-205: 872
-------------	------------

QW-13: 63.70

W-5: ARTEGIDA

4515 : 9-4

Page 10: 40.31

1954-52.5 - Orange County, W. Oregon

Drop Pump. Pump cut = 5/75 - Blue H₂O w/

Fluor To Recharge, And Sample

44: 707

Rs. 4.90

Ans. 1572

15

Temp: 9.5

Tvno: 487

3 June 1967

A-7 (1405)

12/9/02

COLUMBIA

1420. Pull IN-3 PIPE
Grain Sample w/ 2" Gauge From
Middle of Screened Interval
Sample IN-3 @ 1445

Time pH Cond DO Temp ORP
0 4.78 .872 2.32 9.59 -393.9
5 4.81 .867 2.12 9.63 -428.8
10 4.85 .844 2.23 9.59 -433.4
15 4.88 .831 2.26 9.55 -435.8
20 4.95 .820 2.25 9.52 -435.0

1515 Time Field Readings C.O. Sample F-6
Surface Water

pH Cond Temp DO Temp ORP
6.45 .110 0 13.53 0.3 12.1

1440 Sample Seals SF-3

pH Cond Temp DO Temp ORP
6.37 .198 0.7 8.59 3.3 11.6

12/9/02

COLUMBIA

1615 - Sample SF-2 w/ DUC-1
pH Cond Temp DO Temp ORP
6.38 .170 0 3.99 4.4 35

1620 - Sample SF-4
pH Cond Temp DO Temp ORP
6.50 .2586 125 5.80 1.8 17

1700 Closes Treatment System No Sample

1740 Closes Effluent And Sample w/ Sample
Container

1800 Re-DO Closures Reopened

* Arrived To Sample Seals 5 But Also Felt
UP - Will Try All Tomorrow

1840 Depart Site

12/10/02

CALDWELL

WEATHER: SUN 100°

700 W/IN/TM ARRIVE ON SITE

TRY OUT RMP - MIND: MARKS

CALDWELL 41-22 w/ APPROX SOUTHWEST = 0.12

SWIMMING

DTW: 48170 INITIAL FLOW: 600

START: 7414

pH	COND	TEMP	DE	TEMP	COND	TIME	DTW	FLOW
6.48	272	76.8	2.23	8.5	34	0	533.2	442
6.63	291	39.2	1.74	5.8	-57	5	54.82	300
6.66	284	34.0	1.54	4.5	-63	10	54.97	300
6.64	272	34.9	1.31	4.9	-68	15	54.99	300
6.60	248	32.4	1.21	8.5	-67	20	55.52	300
6.62	258	34.4	1.37	7.5	-71	25	55.90	370
6.58	242	28.7	1.34	10.5	-74	30	56.59	300

830 - Collect Sands w/ HYDRO; 40 LBS
STRESS DOLLS

12/10/02

CALDWELL

4-6 DTW 52.62 INITIAL FLOW 300

START: 907

PH	COND	TEMP	DE	TEMP	COND	TIME	DTW	FLOW
6.53	577	73	2.80	7.4	-37	0	55.34	300
6.63	607	76.7	1.87	5.8	-62	5	54.65	200
6.64	600	78.1	1.41	4.5	-68	10	54.70	150
6.67	624	70.8	1.40	4.7	-73	15	54.81	150

700 OF RMP IS AT 57.08 & 2.2' OF 40 - FLOW
IS STAYING - WITH SANDS - APPROX THIS WERE
RECORDED - NO STAY FLOW RMP 7:23 DTW 54.84

945 - SANDS - 40 & CLEAN, 17.5 GPH w/ 10/12
OBSERV. DTW AT 945 WAS 53.01

12/10/02

CHARGE

General-6 DTM: 40.63 STREET TIME: 100

INTER FAN 600

off Comp Time to Time and Time One Fan

6.74	1.02	>999	2.78	7.8	-10	0	43.47	400
6.74	1.04	>999	1.58	8.2	-20	5	44.30	400
6.77	1.01	>999	1.43	7.7	-28	10	44.66	300
6.78	1.05	>999	1.45	7.4	-27	15	44.55	300
6.78	1.01	728	1.48	8.8	-29	20	44.57	300
6.78	1.02	890	1.55	8.8	-30	25	44.63	300
6.77	1.00	560	1.61	10.0	-30	30	44.69	300
6.74	1.01	550	1.66	10.4	-30	35	44.69	300

SAMPLE @ 1005 UNDER N TOWER, BARNUM

SURE, w/ no noise

DUP-1 CONFIRMED

12/10/02

CHARGE

General-2 DTM: 38.11 INTER FAN: 600

STREET 105

off Comp Time to Time and Time One Fan

7.23	3.51	503	4.09	9.2	31	0	40.94	600
6.72	3.38	430	4.82	9.7	25	5	41.53	520
6.61	3.28	2.63	4.61	11.2	27	10	41.57	500
6.63	3.26	196	3.07	11.8	36	15	41.59	500
6.62	3.28	111	2.24	11.5	41	20	41.57	500
6.64	3.3	70.9	2.37	11.9	52	25	41.55	500
6.64	3.35	52.9	2.57	11.8	58	30	41.53	450
6.63	3.37	46.8	2.32	11.8	63	35	41.49	450
6.63	3.37	40.0	2.33	11.9	64	40	41.48	450

F0.4 CALIBRATED @ 4800

F4-1200C

SAMPLE GROUND @ 1115 H2O CLAMP - 517 GARY

w/ NO NOISE

12/10/02

CLEVELAND

1200 PW-13 1000 TONG POWER AND SENSORS

FOR TDC AT 2" BRIDGE - GONG SAMPLE

YSL - CEMENT

Time Temp GWP DO pH

1355 9.97 6.57 4.3 -499.4 6.10

1400 9.99 6.58 4.3 -424.0 6.11

1405 9.99 6.57 4.3 -405.4 6.11

1411 9.97 6.50 4.1 -410.1 6.11

1418 9.99 6.46 4.1 -399.8 6.12

PW-4 Internal Flow: 400 Time: 1225

Flow: 18.78

pH Cond Temp DO Temp GWP Time

6.26 312 173 6.39 10.2 160 19.17 400

6.09 312 80.6 4.92 11.4 157 19.38 400

6.07 314 25.5 3.24 12.3 154 19.59 400

6.10 332 13.0 2.40 13.0 149 19.74 400

6.10 353 12.1 1.75 13.1 146 19.80 400

6.10 359 10.2 1.57 13.3 140 19.82 400

6.07 358 8.0 1.54 13.5 137 19.82 400

Sample @ 1000 - H₂O SENSITIVE YOUNG OF SET OUTSIDE

0.001

12/10/02

CLEVELAND

1200 PW-13 1000 TONG POWER AND SENSORS

FOR TDC AT 2" BRIDGE - GONG SAMPLE

YSL - CEMENT

1200 PW-13 1000 TONG POWER AND SENSORS

FOR TDC AT 2" BRIDGE - GONG SAMPLE

1200 PW-13 1000 TONG POWER AND SENSORS

FOR TDC AT 2" BRIDGE - GONG SAMPLE

1200 PW-13 1000 TONG POWER AND SENSORS

FOR TDC AT 2" BRIDGE - GONG SAMPLE

pH Cond Temp DO Temp GWP Time

6.59 260 799 3.43 8.3 2 40.51 500

6.50 258 797 1.51 8.7 -17 40.32 500

6.48 257 799 1.32 8.7 -27 40.32 500

6.47 256 797 1.28 8.9 -32 40.32 500

6.47 257 799 1.29 9.1 -37 40.32 500

6.47 248 58 -1.27 9.1 -38 40.32 500

Sample @ 1620 - H₂O SET YOUNG OF SET OUTSIDE

Was RED AT START OF PUSING

12/10/62

Continued

1745 WENT NW 8 NEW TOWN - BARNES WING
INSPECTING, THEN BACKEN BAY - REMAINS IN
BONE FRAME ON GROUND - 10' ANGLE
ON RIVER IN WING

1800. SAW "COURTESY" FLY STATION 55

DOWN IN FLYING STREET

NEW COURTESY / 1000 CUE


1900 DO BARNES - NW 8 NEW TOWN

1900 MOVING FOR INTERCOM SYSTEM

GO OVER STATION 4/54

2015 IN DEPT. SINE

TH



Memorandum

To: Ken Zegel

Cc: Steve Feldman

From: Jason Hime

Subject: Downhole probe/YSI parameters recorded 11/20/2002 at the Colesville Landfill

On November 20, 2002, between the hours of 3:30pm and 5:30pm, six groundwater locations were sampled at the Colesville Landfill ERD site in Harpursville, NY. The sampling locations were as follows: GMMW-5, GMPW-1, PW-11, W-5, PW-2 and SP-5. The instruments used to record parameters at these locations were the M-scope, downhole probe and the YSI owned by the ARCADIS Melville office. The weather during sampling was clear and the temperature was between 45 and 55 degrees Fahrenheit. Parameters recorded were: Depth to Water, Temperature, pH, Conductivity, REDOX and Dissolved Oxygen. The YSI was allowed to stabilize a minimum of 10 minutes after the downhole probe reached the sampling depth. The field sampler was Jason Hime of the ARCADIS Melville office. One note that must be mentioned is that during calibration the Oxidation Reduction Potential was calibrated at 200 mV at 55 degrees Fahrenheit. The calibration solution was rated as 200 to 275 mV at 77 degrees Fahrenheit.

ARCADIS G&M, Inc.

Low-Flow Groundwater Sampling Log

Project Number: NY 949.14 Task: 6 Well ID: GMMW-5
Date: 11/20/02 Sampled By: JH
Sampling Time: 3:30 pm Recorded By: JH
Weather: 55° sunny Coded Replicate No.: _____

Instrument Identification
Water Quality Meter(s): YSI Serial #: _____

Purging Information			
Casing Material:	PVC	Purge Method:	N/A
Casing Diameter:	2"	Screen Interval (ft bmp):	Top 53' Bottom 63'
Sounded Depth (ft bmp):	68'	Pump Intake Depth (ft bmp):	58'
Depth to Water (ft bmp):	49.5'	Purge time	Start: Finish:

Field Parameter Measurements Taken During Purging

[illegible]

Sample Condition	Color:	Odor:	Appearance:
Sample Collection			
Parameter:	Container:	No.	Preservative:

PID Reading

Comments

Calibrated ORP to 200mV at 55°F
stabilized for 15 minutes

Low-Flow Groundwater Sampling Log

Purging Information		Purge Method: <u>1/2"</u>	
Casing Material:	<u>Step 1</u>	Screen Interval (ft bmp):	Top <u>4' 5'</u> Bottom <u>2' 11'</u>
Casing Diameter:	<u>4"</u>	Pump Intake Depth (ft bmp):	<u>10' from bottom</u>
Sounded Depth (ft bmp):	<u>—</u>	Purge time	Start: <u>—</u> Finish: <u>—</u>
Depth to Water (ft bmp):	<u>48.12'</u>		

[illegible]

PID Reading	
Comments	Let stabilize for 15 minutes

ARCADIS G&M, Inc.

Low-Flow Groundwater Sampling Log

Project Number:

Date:

Sampling Time:

Weather:

Task:

Sampled By:

Recorded By:

Coded Replicate No.:

Well ID:

Instrument Identification

Water Quality Meter(s):

Serial #:

Purging Information

Casing Material:

Casing Diameter:

Sounded Depth (ft bmp):

Depth to Water (ft bmp):

Purge Method:

Screen Interval (ft bmp): Top

~~Pump Intake~~ Depth (ft bmp):

Purge time

Start:

Bottom

Finish:

Field Parameter Measurements Taken During Purging

[illegible]

Sample Condition

Sample Collection

Parameter:

Color:

Odor:

Appearance:

Container:

No.

Preservative:

PID Reading

Comments

stabilized 10 minutes

Low-Flow Groundwater Sampling Log

Purging Information			
Casing Material:	2"	Purge Method:	N/A
Casing Diameter:	PVC	Screen Interval (ft bmp):	Top 44 Bottom 59
Sounded Depth (ft bmp):	36.8'	Pump Intake Depth (ft bmp):	44 5' off bottom
Depth to Water (ft bmp):	52.7	Purge time	Start: Finish:

[illegible]

PID Reading	
Comments	Let stabilize for 10 minutes

ARCADIS G&M, Inc.

Low-Flow Groundwater Sampling Log

Project Number: NY 949.14 Task: G Well ID: PLW-2
Date: 11/29/02 Sampled By: JH
Sampling Time: 5:00 pm Recorded By: JH
Weather: 45° clear Coded Replicate No.: _____

Instrument Identification
Water Quality Meter(s): YSI Serial #: _____

Purging Information		Purge Method:	<u>n/a</u>	
Casing Material:	<u>2"</u>	Screen Interval (ft bmp):	Top <u>5</u>	Bottom <u>20</u>
Casing Diameter:	<u>PVC</u>	Pump Intake Depth (ft bmp):	<u>10' off bottom</u>	
Sounded Depth (ft bmp):	<u>20.63'</u>	Purge time	Start:	Finish:
Depth to Water (ft bmp):	<u>6.6'</u>			

Field Parameter Measurements Taken During Purging

[illegible]

Sample Condition	Color:	Odor:	Appearance:
Sample Collection			
Parameter:	Container:	No.	Preservative:

PID Reading

Comments

Stabilized for 5 minutes
Height of stick-up above bnd surface was 33"

ARCADIS G&M, Inc.

Low-Flow Groundwater Sampling Log

Project Number: NY 949, 14 Task: 6 Well ID: SP-5
Date: 11/20/02 Sampled By: JH
Sampling Time: 5:10 Recorded By: JH
Weather: 45° clear Coded Replicate No.: _____

Instrument Identification
Water Quality Meter(s): YSI

Purging Information		Purge Method: <u>n/a</u>	
Casing Material:	<u>Na</u>	Screen Interval (ft bmp):	Top <u>Na</u> Bottom <u>Na</u>
Casing Diameter:	<u>1</u>	Pump Intake Depth (ft bmp):	<u>~10" below surface</u>
Sounded Depth (ft bmp):		Purge time	Start: Finish:
Depth to Water (ft bmp):	<u>1</u>		

Field Parameter Measurements Taken During Purging

[illegible]

Sample Condition	Color:	Odor:	Appearance:
Sample Collection			
Parameter:	Container:	No.	Preservative:

PID Reading

Comments

oil coating, orange color let stabilize for 10 minutes

ARCADIS

Appendix C

New York State Department of
Environmental Conservation DAR-1
Air Modeling Data

ARCADIS

Table C-1. NYSDEC DAR-1 Air Modeling Data, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Parameters for 12/10/2002 Sampling Event

Discharge Temperature	T	513.67	°R
Ambient Temperature	Ta	494.67	°R
Stack Diameter	D	6	in
Stack Radius	R	0.25	ft
Stack Area	A	0.20	ft ²
Exit Velocity	V	2.17	fps
Exit Flow	Q	26	acfm
Exit Flow	Q	26	scfm
Stack Height	h _s	17	ft
Building Height	h _b	13.25	ft
Ratio of Heights	h _s /h _b	1.28	
Plume rise credit? h _s /h _b > 1.5?	(If no, h _e =h _s)	(If Yes, h _e = h _s + 1.1 (F _m) ^{1/3})	
Momentum Flux	F _m = TaT * V2 * R2	n/a	ft ³ /s ²
Effective Stack Height	h _e	17.00	ft
Reduction Factor? 2.5 > h _s /h _b > 1.5?	No, do not reduce impact		
Actual Annual Impact	C _a	RF*6*Q _s /h _e ^{2.25}	ug/m ³
Mass Flow	Q _a	S lbs emitted for last 12 months	

fps: feet per second
 acfm: actual cubic feet per minute
 ug/m³: micrograms per cubic meter
 lb/yr: pounds per year
 lb/hr: pounds per hour
 ppb: parts per billion

Notes/Assumptions:

1. The stack temperature is 54°F based on recorded parameters.
2. The ambient temperature is approximately 35°F, the average temperature during sampling.
3. Calculations assume that the system will run with the maximum allowable concentrations between quarterly readings.
4. AGC refers to the Annual Guideline Concentration as determined using the hand calculations in the DAR-1 AGC/SGC Tables dated July 12, 2000.
5. To be conservative the lower detection limit was used for compounds that were below the limit of detection, but are found in the influent groundwater of the Groundwater Remediation System.

ARCADIS

Table C-1. NYSDEC DAR-1 Air Modeling Data, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Calculation of AGC based on 12/10/2002 Sampling Event

Compounds	CAS Numbers	Maximum Limit on C _a (AGC ⁴) ug/m ³	Maximum Mass Flow Q _a lb/yr	Lab Data 12/10/02 ppb	Detection Limit Used ⁵	Actual Emissions C _a ug/m ³	Actual Mass Flow per Hour lb/hr	Actual Mass Flow per Year lb/yr	Percent of AGC %
Vinyl Chloride	75-01-4	0.02	1.96	12	*	31.18	3.06E-06	0.02612	1.34
Chloroethane(Ethyl Chloride)	75-00-3	10,000	978,044.97	12	*	32.19	3.16E-06	0.02696	0.00
1,1-Dichloroethene(Vinylidene Chloride)	75-35-4	0.02	1.96	12	*	48.36	4.75E-06	0.04051	2.07
Methylene Chloride(Dichloromethane)	75-09-2	2.10	205.39	19		67.09	6.59E-06	0.05620	0.03
1,1-Dichloroethane	75-34-3	20	1,956.09	50		205.72	2.02E-05	0.17232	0.01
cis-1,2 - Dichloroethylene	156-59-2	1,900	185,828.54	48		193.46	1.90E-05	0.16205	0.00
Chloroform	67-66-3	0.04	4.21	12	*	59.56	5.85E-06	0.04989	1.19
1,1,1-Trichloroethane(Methyl Chloroform)	71-55-6	1,000	97,804.50	53		293.96	2.89E-05	0.24624	0.00
Benzene	71-43-2	0.13	12.71	12	*	38.97	3.83E-06	0.03264	0.26
Trichloroethene	79-01-6	0.45	44.01	36		196.55	1.93E-05	0.16473	0.37
Toluene	108-88-3	400	39,121.80	12	*	45.96	4.51E-06	0.03850	0.00
Ethyl benzene	100-41-4	1,000	97,804.50	12	*	52.96	5.20E-06	0.04436	0.00
m,p-Xylene	108-38-3/106-42-3	700	68,463.15	12	*	51.95	5.10E-06	0.04352	0.00
o-Xylene	95-47-6	700	68,463.15	12	*	52.96	5.20E-06	0.04436	0.00
1,2,4-Trimethylbenzene	95-63-6	290	28,363.30	12	*	59.96	5.89E-06	0.05022	0.00
2-Propanol (Isopropyl alcohol)	67-63-1	7,000	684,631.48	12	*	29.98	2.95E-06	0.02511	0.00
Dichlorodifluoromethane(Freon 12)	75-71-8	12,000	1,173,653.96	12	*	29.98	2.87E-06	0.00213	0.00

fps: feet per second

acfm: actual cubic feet per minute

ug/m³: micrograms per cubic meter

lb/yr: pounds per year

lb/hr: pounds per hour

ppb: parts per billion

Notes/Assumptions:

1. The stack temperature is 54°F based on recorded parameters.
2. The ambient temperature is approximately 35°F, the average temperature during sampling.
3. Calculations assume that the system will run with the maximum allowable concentrations between quarterly readings.
4. AGC refers to the Annual Guideline Concentration as determined using the hand calculations in the DAR-1 AGC/SGC Tables dated July 12, 2000.
5. To be conservative the lower detection limit was used for compounds that were below the limit of detection, but are found in the influent groundwater of the Groundwater Remediation System.

ARCADIS

Table C-2: NYSDEC Dar-1 Air Modeling Data, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Calculation of the Short-Term Guideline Concentration (SGC) for Sampling Event on 12/10/2002

Compounds	CAS Numbers	Maximum Limit (SGC)	Analytical Concentration	Detection Limit Used	Actual Emissions C_a	Mass/hour	Potential Impact (Step III.A.3 in DAR-1)	Maximum Impact (Step III.A.5 in DAR-1)	Short Term Impact (Step III.A.5 in DAR-1)	Percent of the SGC
		($\mu\text{g}/\text{m}^3$)	(ppb)		($\mu\text{g}/\text{m}^3$)	(lb/hr)	($\mu\text{g}/\text{m}^3$)	($\mu\text{g}/\text{m}^3$)	($\mu\text{g}/\text{m}^3$)	(%)
Vinyl Chloride	75-01-4	180,000	12	*	31.18	1.94E-05	0.0033	0.21536	0.21536	1.2E-04
Chloroethane(Ethyl Chloride)	75-00-3	—	12	*	32.19	2.00E-05	0.0034	0.22232	0.22232	NA
1,1-Dichloroethene(Vinylidene Chloride)	75-35-4	—	12	*	48.36	3.01E-05	0.0051	0.33407	0.33407	NA
Methylene Chloride(Dichloromethane)	75-09-2	14,000	19		67.09	4.17E-05	0.0071	0.46342	0.46342	3.3E-03
1,1-Dichloroethane	75-34-3	—	50		205.72	1.28E-04	0.0219	1.42096	1.42096	NA
cis-1,2 - Dichloroethylene	156-59-2	—	48		193.46	1.20E-04	0.0206	1.33628	1.33628	NA
Chloroform	67-66-3	150	12	*	59.56	3.70E-05	0.0063	0.41139	0.41139	2.7E-01
1,1,1-Trichloroethane(Methyl Chloroform)	71-55-6	68,000	53		293.96	1.83E-04	0.0312	2.03050	2.03050	3.0E-03
Benzene	71-43-2	1,300	12	*	38.97	2.42E-05	0.0041	0.26915	0.26915	2.1E-02
Trichloroethene	79-01-6	54,000	36		196.65	1.22E-04	0.0209	1.35833	1.35833	2.5E-03
Toluene	108-88-3	37,000	12	*	45.96	2.86E-05	0.0049	0.31746	0.31746	8.6E-04
Ethyl benzene	100-41-4	54,000	12	*	52.96	3.29E-05	0.0056	0.36580	0.36580	6.8E-04
m,p-Xylene	108-38-3/106-42-3	4,300	12	*	51.95	3.23E-05	0.0055	0.35884	0.35884	8.3E-03
o-Xylene	95-47-6	4,300	12	*	52.96	3.29E-05	0.0056	0.36580	0.36580	8.5E-03
1,2,4-Trimethylbenzene	95-63-6	—	12	*	59.96	3.73E-05	0.0064	0.41415	0.41415	NA
2-Propanol (Isopropyl alcohol)	67-63-0	120,000	12	*	29.98	1.86E-05	0.0032	0.20709	0.20709	1.7E-04
Dichlorofluoromethane(Freon 12)	75-71-8	—	12	*	60.31	3.75E-05	0.0064	0.41660	0.41660	NA

$\mu\text{g}/\text{m}^3$: Micrograms per cubic meter

ppb: parts per billion

*: Analyte concentration below detection limit, detection limit was used in calculations

lb/hr: pounds per hour

—: No SGC listed for compound

Notes:

1. DAR-1 refers to DAR-1 AGC/SGC Tables dated 12 July 2000.
2. SGC refers to the Short-Term Guideline Concentration as determined using the hand calculations in the DAR-1 AGC/SGC Tables dated July 12, 2000.
3. To be conservative the lower detection limit was used for compounds that were below the limit of detection, but are found in the influent groundwater of the Groundwater Remediation System.

ARCADIS

Appendix D

Automated Reagent Injection System Operating Parameters

ARCADIS

Table D-1. Automated Reagent Injection System Summary Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Summary of Automated Reagent Injections

Date	Total Quantity of Molasses Solution Injected (gal.)	Total Quantity of Molasses Injected (gal.)	Total Quantity of Rinse Water Injected (gal.)
9/19/2002	629	103	157
9/26/2002	629	103	157
10/4/2002	629	103	157
10/11/2002	629	87	157
10/18/2002	629	87	157
10/25/2002	629	87	157
11/21/2002	629	91	157
12/2/2002	629	87	157
12/10/2002	629	87	157

Quarter Totals
(gal.) = 5,661 837 1,413

Totals Since
Startup (gal.) = 6,288 1,006 1,884

Notes:
gal. Gallons

Table D-2. Automated Reagent Injection System Quarter Number 1 Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Injection Number 2					
Injection Date = 9/19/2002					
Molasses to Water Ratio (%) =		16.4		Programmed Mixing Time (min.) ¹ =	
				30	
Injection Well ID	Molasses Solution Injection Quantity (gal.)	Rinse ² Quantity (gal.)	Raw Molasses Per Well (gal.)	Min. Injection Flowrate (gpm)	Max. Injection Pressure (psi)
PW-6	37	5	6.07	16.8	31
IW-3	37	5	6.07	13.1	34
IW-1	37	4	6.07	11.2	32
IW-2	37	3	6.07	11.2	35
GMMW-1	37	3	6.07	9.1	36
IW-4	37	4	6.07	9.4	36
IW-5	37	5	6.07	13	33
IW-6	37	7	6.07	11.2	35
IW-7	37	8	6.07	10.1	36
IW-8	37	9	6.07	12	34
IW-9	37	11	6.07	13.5	32
IW-10	37	12	6.07	8.5	35
IW-11	37	13	6.07	13.5	30
IW-12	37	15	6.07	12.8	33
IW-13	37	16	6.07	11.8	33
IW-14	37	18	6.07	8.3	36
IW-15	37	19	6.07	10.6	35
Totals (gal.) =	629	157	103.16	NA	NA

Notes:

- gal. Gallons
min. Minutes
i.w.c. Inches of water column.
psi Pounds per square inch.
gpm Gallons per minute.
NA Not applicable.
NM Not measured.
1. Programmed mixing time is calculated from the expiration time of the molasses injection countdown timer to the startup of transfer pump TP-900 during an injection sequence or from the end of transfer pump TP-600 operation to the restart of an injection during a mixing sequence.
 2. Rinse quantity is approximately 1-pipeline volume for each injection well.
 3. On 10/11/2002 the volume in the mixing tank was adjusted in the program to accommodate a level switch that was prematurely being triggered due to convection caused by the mixing of solution.
 4. On 11/21/2002 the remainder of molasses in the 275-gallon totes was pumped into the mixing tank before the new molasses tanks were installed causing an elevated molasses concentration in solution on this date.

Table D-2. Automated Reagent Injection System Quarter Number 1 Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Injection Number 3

Injection Date = 9/26/2002

Molasses to Water Ratio (%) = 16.4

Programmed Mixing Time (min.)¹ = 30

Injection Well ID	Molasses Solution Injection Quantity (gal.)	Rinse ³ Quantity (gal.)	Raw Molasses Per Well (gal.)	Min. Injection Flowrate (gpm)	Max. Injection Pressure (psi)
PW-6	37	5	6.07	NM	NM
IW-3	37	5	6.07	NM	NM
IW-1	37	4	6.07	NM	NM
IW-2	37	3	6.07	NM	NM
GMMW-1	37	3	6.07	NM	NM
IW-4	37	4	6.07	NM	NM
IW-5	37	5	6.07	NM	NM
IW-6	37	7	6.07	NM	NM
IW-7	37	8	6.07	NM	NM
IW-8	37	9	6.07	NM	NM
IW-9	37	11	6.07	NM	NM
IW-10	37	12	6.07	NM	NM
IW-11	37	13	6.07	NM	NM
IW-12	37	15	6.07	NM	NM
IW-13	37	16	6.07	NM	NM
IW-14	37	18	6.07	NM	NM
IW-15	37	19	6.07	NM	NM
Totals (gal.) =	629	157	103.16	NA	NA

Notes:

gal. Gallons
min. Minutes
i.w.c. Inches of water column.
psi Pounds per square inch.
gpm Gallons per minute.
NA Not applicable.
NM Not measured.

1. Programmed mixing time is calculated from the expiration time of the molasses injection countdown timer to the startup of transfer pump TP-900 during an injection sequence or from the end of transfer pump TP-600 operation to the restart of an injection during a mixing sequence.
2. Rinse quantity is approximately 1-pipeline volume for each injection well.
3. On 10/11/2002 the volume in the mixing tank was adjusted in the program to accommodate a level switch that was prematurely being triggered due to convection caused by the mixing of solution.
4. On 11/21/2002 the remainder of molasses in the 275-gallon totes was pumped into the mixing tank before the new molasses tanks were installed causing an elevated molasses concentration in solution on this date.

Table D-2. Automated Reagent Injection System Quarter Number 1 Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Injection Number 4					
Injection Date = 10/4/2002					
Molasses to Water Ratio (%) =		16.4		Programmed Mixing Time (min.) ¹ =	
				30	
Injection Well ID	Molasses Solution Injection Quantity (gal.)	Rinse ⁴ Quantity (gal.)	Raw Molasses Per Well (gal.)	Min. Injection Flowrate (gpm)	Max. Injection Pressure (psi)
PW-6	37	5	6.07	16.7	31
IW-3	37	5	6.07	15.4	33
IW-1	37	4	6.07	12	32
IW-2	37	3	6.07	16.5	32
GMMW-1	37	3	6.07	13	34
IW-4	37	4	6.07	NM	NM
IW-5	37	5	6.07	15.1	30
IW-6	37	7	6.07	13.8	31
IW-7	37	8	6.07	9.95	34
IW-8	37	9	6.07	NM	NM
IW-9	37	11	6.07	NM	NM
IW-10	37	12	6.07	NM	NM
IW-11	37	13	6.07	13.6	33
IW-12	37	15	6.07	14.9	32
IW-13	37	16	6.07	14.3	33
IW-14	37	18	6.07	10.4	35
IW-15	37	19	6.07	8.9	35
Totals (gal.) =	629	157	103.16	NA	NA

Notes:

gal. Gallons
min. Minutes
i.w.c. Inches of water column.
psi Pounds per square inch.
gpm Gallons per minute.
NA Not applicable.
NM Not measured.

1. Programmed mixing time is calculated from the expiration time of the molasses injection countdown timer to the startup of transfer pump TP-900 during an injection sequence or from the end of transfer pump TP-600 operation to the restart of an injection during a mixing sequence.
2. Rinse quantity is approximately 1-pipeline volume for each injection well.
3. On 10/11/2002 the volume in the mixing tank was adjusted in the program to accommodate a level switch that was prematurely being triggered due to convection caused by the mixing of solution.
4. On 11/21/2002 the remainder of molasses in the 275-gallon totes was pumped into the mixing tank before the new molasses tanks were installed causing an elevated molasses concentration in solution on this date.

Table D-2. Automated Reagent Injection System Quarter Number 1 Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Injection Number 5

Injection Date = 10/11/2002

Molasses to Water Ratio (%) = 13.9

Programmed Mixing Time (min.)¹ = 30

Injection Well ID	Molasses Solution Injection Quantity (gal.)	Rinse ⁵ Quantity (gal.)	Raw Molasses Per Well (gal.)	Min. Injection Flowrate (gpm)	Max. Injection Pressure (psi)
PW-6	37	5	5.14	NM	NM
IW-3	37	5	5.14	NM	NM
IW-1	37	4	5.14	NM	NM
IW-2	37	3	5.14	NM	NM
GMMW-1	37	3	5.14	NM	NM
IW-4	37	4	5.14	NM	NM
IW-5	37	5	5.14	NM	NM
IW-6	37	7	5.14	NM	NM
IW-7	37	8	5.14	NM	NM
IW-8	37	9	5.14	NM	NM
IW-9	37	11	5.14	NM	NM
IW-10	37	12	5.14	NM	NM
IW-11	37	13	5.14	NM	NM
IW-12	37	15	5.14	NM	NM
IW-13	37	16	5.14	NM	NM
IW-14	37	18	5.14	NM	NM
IW-15	37	19	5.14	NM	NM
Totals (gal.) =	629	157	87.43	NA	NA

Notes:

gal. Gallons
min. Minutes
i.w.c. Inches of water column.
psi Pounds per square inch.
gpm Gallons per minute.
NA Not applicable.
NM Not measured.

1. Programmed mixing time is calculated from the expiration time of the molasses injection countdown timer to the startup of transfer pump TP-900 during an injection sequence or from the end of transfer pump TP-600 operation to the restart of an injection during a mixing sequence.
2. Rinse quantity is approximately 1-pipeline volume for each injection well.
3. On 10/11/2002 the volume in the mixing tank was adjusted in the program to accommodate a level switch that was prematurely being triggered due to convection caused by the mixing of solution.
4. On 11/21/2002 the remainder of molasses in the 275-gallon totes was pumped into the mixing tank before the new molasses tanks were installed causing an elevated molasses concentration in solution on this date.

Table D-2. Automated Reagent Injection System Quarter Number 1 Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Injection Number 6					
Injection Date = 10/18/2002					
Molasses to Water Ratio (%) = 13.9 Programmed Mixing Time (min.) ¹ = 30					
Injection Well ID	Molasses Solution Injection Quantity (gal.)	Rinse ⁶ Quantity (gal.)	Raw Molasses Per Well (gal.)	Min. Injection Flowrate (gpm)	Max. Injection Pressure (psi)
PW-6	37	5	5.14	NM	NM
IW-3	37	5	5.14	NM	NM
IW-1	37	4	5.14	NM	NM
IW-2	37	3	5.14	NM	NM
GMMW-1	37	3	5.14	NM	NM
IW-4	37	4	5.14	NM	NM
IW-5	37	5	5.14	NM	NM
IW-6	37	7	5.14	NM	NM
IW-7	37	8	5.14	NM	NM
IW-8	37	9	5.14	NM	NM
IW-9	37	11	5.14	NM	NM
IW-10	37	12	5.14	NM	NM
IW-11	37	13	5.14	NM	NM
IW-12	37	15	5.14	NM	NM
IW-13	37	16	5.14	NM	NM
IW-14	37	18	5.14	NM	NM
IW-15	37	19	5.14	NM	NM
Totals (gal.) =	629	157	87.43	NA	NA

Notes:

gal. Gallons
min. Minutes
i.w.c. Inches of water column.
psi Pounds per square inch.
gpm Gallons per minute.
NA Not applicable.
NM Not measured.

1. Programmed mixing time is calculated from the expiration time of the molasses injection countdown timer to the startup of transfer pump TP-900 during an injection sequence or from the end of transfer pump TP-600 operation to the restart of an injection during a mixing sequence.
2. Rinse quantity is approximately 1-pipeline volume for each injection well.
3. On 10/11/2002 the volume in the mixing tank was adjusted in the program to accommodate a level switch that was prematurely being triggered due to convection caused by the mixing of solution.
4. On 11/21/2002 the remainder of molasses in the 275-gallon totes was pumped into the mixing tank before the new molasses tanks were installed causing an elevated molasses concentration in solution on this date.

Table D-2. Automated Reagent Injection System Quarter Number 1 Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Injection Number 7

Injection Date = 10/25/2002

Molasses to Water Ratio (%) = 13.9

Programmed Mixing Time (min.)¹ = 30

Injection Well ID	Molasses Solution Injection Quantity (gal.)	Rinse ⁷ Quantity (gal.)	Raw Molasses Per Well (gal.)	Min. Injection Flowrate (gpm)	Max. Injection Pressure (psi)
PW-6	37	5	5.14	NM	NM
IW-3	37	5	5.14	NM	NM
IW-1	37	4	5.14	NM	NM
IW-2	37	3	5.14	NM	NM
GMMW-1	37	3	5.14	NM	NM
IW-4	37	4	5.14	NM	NM
IW-5	37	5	5.14	NM	NM
IW-6	37	7	5.14	NM	NM
IW-7	37	8	5.14	NM	NM
IW-8	37	9	5.14	NM	NM
IW-9	37	11	5.14	NM	NM
IW-10	37	12	5.14	NM	NM
IW-11	37	13	5.14	NM	NM
IW-12	37	15	5.14	NM	NM
IW-13	37	16	5.14	NM	NM
IW-14	37	18	5.14	NM	NM
IW-15	37	19	5.14	NM	NM
Totals (gal.) =	629	157	87.43	NA	NA

Notes:

gal. Gallons
min. Minutes
i.w.c. Inches of water column.
psi Pounds per square inch.
gpm Gallons per minute.
NA Not applicable.
NM Not measured.

1. Programmed mixing time is calculated from the expiration time of the molasses injection countdown timer to the startup of transfer pump TP-900 during an injection sequence or from the end of transfer pump TP-600 operation to the restart of an injection during a mixing sequence.
2. Rinse quantity is approximately 1-pipeline volume for each injection well.
3. On 10/11/2002 the volume in the mixing tank was adjusted in the program to accommodate a level switch that was prematurely being triggered due to convection caused by the mixing of solution.
4. On 11/21/2002 the remainder of molasses in the 275-gallon totes was pumped into the mixing tank before the new molasses tanks were installed causing an elevated molasses concentration in solution on this date.

ARCADIS

Table D-2. Automated Reagent Injection System Quarter Number 1 Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Injection Number 8

Injection Date = 11/21/2002

Molasses to Water Ratio (%) = 14.5

Programmed Mixing Time (min.)¹ = 30

Injection Well ID	Molasses Solution Injection Quantity (gal.)	Rinse ² Quantity (gal.)	Raw Molasses Per Well (gal.)	Min. Injection Flowrate (gpm)	Max. Injection Pressure (psi)
PW-6	37	5	5.37	15	15.3
IW-3	37	5	5.37	14.8	15
IW-1	37	4	5.37	11	27
IW-2	37	3	5.37	8.53	28
GMMW-1	37	3	5.37	11.7	24
IW-4	37	4	5.37	15.2	14
IW-5	37	5	5.37	15.3	15
IW-6	37	7	5.37	13.6	1
IW-7	37	8	5.37	12	25
IW-8	37	9	5.37	15	21
IW-9	37	11	5.37	13.5	14
IW-10	37	12	5.37	13.4	22
IW-11	37	13	5.37	13.6	26
IW-12	37	15	5.37	13.6	25
IW-13	37	16	5.37	12.7	21
IW-14	37	18	5.37	8.4	28
IW-15	37	19	5.37	10.2	27
Totals (gal.) =	629	157	91.21	NA	NA

Notes:

gal. Gallons
min. Minutes
i.w.c. Inches of water column.
psi Pounds per square inch.
gpm Gallons per minute.
NA Not applicable.
NM Not measured.

1. Programmed mixing time is calculated from the expiration time of the molasses injection countdown timer to the startup of transfer pump TP-900 during an injection sequence or from the end of transfer pump TP-600 operation to the restart of an injection during a mixing sequence.
2. Rinse quantity is approximately 1-pipeline volume for each injection well.
3. On 10/11/2002 the volume in the mixing tank was adjusted in the program to accommodate a level switch that was prematurely being triggered due to convection caused by the mixing of solution.
4. On 11/21/2002 the remainder of molasses in the 275-gallon totes was pumped into the mixing tank before the new molasses tanks were installed causing an elevated molasses concentration in solution on this date.

Table D-2. Automated Reagent Injection System Quarter Number 1 Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Injection Number 9					
Injection Date = 12/2/2002					
Molasses to Water Ratio (%) =		13.9		Programmed Mixing Time (min.) ¹ =	
				30	
Injection Well ID	Molasses Solution Injection Quantity (gal.)	Rinse ⁹ Quantity (gal.)	Raw Molasses Per Well (gal.)	Min. Injection Flowrate (gpm)	Max. Injection Pressure (psi)
PW-6	37	5	5.14	16	31
IW-3	37	5	5.14	NM	NM
IW-1	37	4	5.14	12	34
IW-2	37	3	5.14	14	34
GMMW-1	37	3	5.14	14	34
IW-4	37	4	5.14	14	33
IW-5	37	5	5.14	14	34
IW-6	37	7	5.14	11	35
IW-7	37	8	5.14	10	33
IW-8	37	9	5.14	11	33
IW-9	37	11	5.14	13	32
IW-10	37	12	5.14	9	34
IW-11	37	13	5.14	15	31
IW-12	37	15	5.14	14	32
IW-13	37	16	5.14	13	32
IW-14	37	18	5.14	11	34
IW-15	37	19	5.14	8	35
Totals (gal.) =	629	157	87.43	NA	NA

Notes:

gal.	Gallons
min.	Minutes
i.w.c.	Inches of water column.
psi	Pounds per square inch.
gpm	Gallons per minute.
NA	Not applicable.
NM	Not measured.

1. Programmed mixing time is calculated from the expiration time of the molasses injection countdown timer to the startup of transfer pump TP-900 during an injection sequence or from the end of transfer pump TP-600 operation to the restart of an injection during a mixing sequence.
2. Rinse quantity is approximately 1-pipeline volume for each injection well.
3. On 10/11/2002 the volume in the mixing tank was adjusted in the program to accommodate a level switch that was prematurely being triggered due to convection caused by the mixing of solution.
4. On 11/21/2002 the remainder of molasses in the 275-gallon totes was pumped into the mixing tank before the new molasses tanks were installed causing an elevated molasses concentration in solution on this date.

Table D-2. Automated Reagent Injection System Quarter Number 1 Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Injection Number 10

Injection Date = 12/10/2002

Molasses to Water Ratio (%) = 13.8

Programmed Mixing Time (min.)¹ = 30

Injection Well ID	Molasses Solution Injection Quantity (gal.)	Rinse ¹⁰ Quantity (gal.)	Raw Molasses Per Well (gal.)	Min. Injection Flowrate (gpm)	Max. Injection Pressure (psi)
PW-6	37	5	5.11	15.5	17
IW-3	37	5	5.11	15.3	17
IW-1	37	4	5.11	16	22
IW-2	37	3	5.11	11.5	27
GMMW-1	37	3	5.11	15.3	22
IW-4	37	4	5.11	17	14
IW-5	37	5	5.11	16.8	17
IW-6	37	7	5.11	14.1	21
IW-7	37	8	5.11	10.2	29
IW-8	37	9	5.11	14.8	23
IW-9	37	11	5.11	13.4	23
IW-10	37	12	5.11	14.6	24
IW-11	37	13	5.11	15.3	21
IW-12	37	15	5.11	14.5	20
IW-13	37	16	5.11	12.6	20
IW-14	37	18	5.11	9.9	25
IW-15	37	19	5.11	10.6	26.5

Totals (gal.) =	629	157	86.80	NA	NA
-----------------	-----	-----	-------	----	----

Notes:

gal. Gallons
min. Minutes
i.w.c. Inches of water column.
psi Pounds per square inch.
gpm Gallons per minute.
NA Not applicable.
NM Not measured.

1. Programmed mixing time is calculated from the expiration time of the molasses injection countdown timer to the startup of transfer pump TP-900 during an injection sequence or from the end of transfer pump TP-600 operation to the restart of an injection during a mixing sequence.
2. Rinse quantity is approximately 1-pipeline volume for each injection well.
3. On 10/11/2002 the volume in the mixing tank was adjusted in the program to accommodate a level switch that was prematurely being triggered due to convection caused by the mixing of solution.
4. On 11/21/2002 the remainder of molasses in the 275-gallon totes was pumped into the mixing tank before the new molasses tanks were installed causing an elevated molasses concentration in solution on this date.