

ARCADIS of New York, Inc.  
Two Huntington Quadrangle  
Suite 1S10  
Melville  
New York 11747  
Tel 631 249 7600  
Fax 631 249 7610  
[www.arcadis-us.com](http://www.arcadis-us.com)

Mr. George Jacob  
United States Environmental Protection Agency – Region 2  
290 Broadway, 20th Floor  
New York, New York 10007-1866

Subject:  
Operational Year 4 Quarter Number 3 Monitoring Report,  
Colesville Landfill, Broome County, New York. (Site No. 704010).

ENVIRONMENT

Dear Mr. Jacob:

On behalf of Broome County, ARCADIS is providing the Operational Year 4 Quarter Number 3 Monitoring Report for the Colesville Landfill, Broome County, New York.

Please feel free to contact me if you have any questions or comments.

Sincerely,

ARCADIS of New York, Inc.

Steven M. Feldman  
Project Manager

Date:  
January 30, 2007

Contact:  
Steven M. Feldman

Phone:  
(631) 391-5244

Email:  
[sfeldman@arcadis-us.com](mailto:sfeldman@arcadis-us.com)

Our ref:  
NY000949.0019.00004

Copies:  
Payson Long, NYSDEC  
David Donoghue, Broome County  
Julia Guastella, NYSDOH  
File


Imagine the result


**Broome County**  
**Division of Solid Waste Management**

**Operational Year 4**  
**Quarter Number 3**  
**Monitoring Report**

January 30, 2007

ARCADIS

  
Kenneth Zegok, P.E.  
Senior Engineer

  
Steven M. Feldman  
Project Director

  
Christina Berardi Tuohy, P.E.  
Vice President

**Operational Year 4  
Quarter Number 3  
Monitoring Report**

Colesville Landfill,  
Broome County, New York  
NYSDEC Site 704010

Prepared for:  
Broome County Division of Solid Waste  
Management

Prepared by:  
ARCADIS of New York, Inc.  
Two Huntington Quadrangle  
Suite 1S10  
Melville  
New York 11747  
Tel 631.249.7600  
Fax 631.249.7610

Our Ref.:  
NY000949.0019.00004

Date:  
January 30, 2007

*This document is intended only for the use  
of the individual or entity for which it was  
prepared and may contain information that  
is privileged, confidential and exempt from  
disclosure under applicable law. Any  
dissemination, distribution or copying of  
this document is strictly prohibited.*

<b>1. Introduction</b>	<b>1</b>
<b>2. Methodology</b>	<b>1</b>
2.1 Environmental Effectiveness Monitoring	2
2.2 Groundwater Remediation System Performance Monitoring	2
2.3 Spring Water Remediation System Performance Monitoring	3
<b>3. Groundwater Flow</b>	<b>3</b>
<b>4. Groundwater Quality</b>	<b>3</b>
4.1 Volatile Organic Compounds	3
4.2 Indicators of Reducing Conditions	4
4.3 Evidence of Biodegradation	4
<b>5. Spring Water Quality</b>	<b>4</b>
<b>6. Surface Water Quality</b>	<b>5</b>
<b>7. Groundwater Remediation System Performance</b>	<b>5</b>
7.1 PT System	5
7.1.1 Summary of Operation, Maintenance, and Monitoring	5
7.1.2 Results of Performance Sampling	6
7.2 ARI System	7
7.2.1 Summary of Operation, Maintenance, and Monitoring	7
7.2.2 Results of Performance Sampling	7
<b>8. Spring Water Remediation System Performance</b>	<b>8</b>
<b>9. Conclusions</b>	<b>8</b>
<b>10. Recommendations</b>	<b>9</b>
<b>11. Project Schedule</b>	<b>10</b>

**12. References****11****Tables**

Table 1	Concentrations of Volatile Organic Compounds Detected in Groundwater, Spring Water, and Surface Water, Operational Year 4, Quarter Number 3, Colesville Landfill, Broome County, New York.
Table 2	Concentrations of Selected Metals, General Chemistry, Field Parameters, and Dissolved Gases Detected in Groundwater, Operational Year 4, Quarter Number 3 Sampling Round, Colesville Landfill, Broome County, New York.
Table 3	PT System Operating Parameters, Operational Year 4, Quarter Number 3, Groundwater Remediation System, Colesville Landfill, Broome County, New York.
Table 4	Concentrations of Volatile Organic Compounds and Selected Metals Detected in Aqueous Samples Collected from the PT System, Operational Year 4, Quarter Number 3, Colesville Landfill, Broome County, New York.
Table 5	PT System Mass Removal Rate of Volatile Organic Compounds, Operational Year 4, Quarter Number 3, Groundwater Remediation System, Colesville Landfill, Broome County, New York.
Table 6	Concentrations of Volatile Organic Compounds Detected in Air Stripper Effluent, Operational Year 4, Quarter Number 3, Groundwater Remediation System, Colesville Landfill, Broome County, New York.
Table 7	Concentrations of Volatile Organic Compounds Detected in Aqueous Samples Collected from the SP-5 Remediation System, Operational Year 4, Quarter Number 3, Colesville Landfill, Broome County, New York.
Table 8	Spring Water Remediation System Mass Removal Rate of Volatile Organic Compounds, Operational Year 4, Quarter Number 3, Colesville Landfill, Broome County, New York.

**Figures**

Figure 1	Long-Term Effectiveness Monitoring Locations, Colesville Landfill, Broome County, New York.
----------	---

**Appendices**

- A Groundwater Sampling Logs
- B New York State Department of Environmental Conservation DAR-1 Air Modeling Data
- C Automated Reagent Injection System Operating Parameters

## 1. Introduction

This Monitoring Report (Report) was prepared on behalf of the Broome County Division of Solid Waste Management for the Colesville Landfill, located in Broome County, New York (site) to evaluate and document long-term monitoring (LTM) activities at the site. Remediation and monitoring activities are being conducted pursuant to the Record of Decision (ROD) and Explanation of Significant Difference (ESD) that were issued in March 1991 and September 2000, respectively. LTM activities (which include environmental effectiveness and remediation system performance monitoring) were performed in accordance with the LTM Plan (ARCADIS G&M, Inc. 2002), LTM Plan Addendum for Spring Water Remediation Systems (ARCADIS 2003), and Interim Remedial Action Report (ARCADIS 2004), which were approved by the United States Environmental Protection Agency (USEPA) and New York State Department of Environmental Conservation (NYSDEC). These documents provide a detailed description of the LTM program, methodology, and rationale. Where applicable these elements are either summarized or incorporated by reference herein.

This report describes the results of the July 2006 groundwater quality monitoring event conducted during Operational Year 4, Quarter Number 3. A description of the operation, maintenance, and monitoring (OM&M) associated with the Groundwater Remediation System from April 2006 through July 2006 has also been included. In addition, this report describes SP-5 Spring Water Remediation System OM&M activities conducted during this quarter. Following the detailed data analysis and discussion is a summary of findings, conclusions, and recommendations.

During the current reporting period, damage occurred at the former SP-4 spring area and at production well GMPW-5 as a result of flooding of the North Stream. Further discussion of the flood damage is provided herein when applicable to the LTM program and/or OM&M of the Groundwater Remediation System. Repair of the damaged components will be discussed in future Monitoring Reports.

## 2. Methodology

The following section provides a summary of the environmental effectiveness and remedial system performance monitoring methodology for Operational Year 4, Quarter Number 3. A site plan, which shows the location of environmental effectiveness monitoring, is provided on Figure 1.

## 2.1 Environmental Effectiveness Monitoring

The environmental effectiveness monitoring performed during Operational Year 4, Quarter Number 3 included the following:

- Groundwater samples were collected from five monitoring wells (Year 4, Q3 list of wells) during the week of July 24, 2006 and were selectively analyzed for volatile organic compounds (VOCs) and select inorganic parameters. Field parameters were also recorded at these monitoring locations.
- Samples (VOCs only) were collected at the SP-4 and F-6 surface water locations on July 28, 2006.

In accordance with the Proposed Modifications to the Long-Term Monitoring Program (ARCADIS 2005), groundwater samples were collected from monitoring wells utilizing passive diffusive bag (PDB) samplers.

## 2.2 Groundwater Remediation System Performance Monitoring

Groundwater Remediation System performance monitoring activities during Operational Year 4, Quarter Number 3 were as follows:

- Pump-and-treat (PT) system production well influent and effluent samples were collected during the OM&M quarterly site visit completed during the week of July 24, 2006. The samples were selectively analyzed for VOCs and total iron.
- One vapor sample from the PT system air stripper effluent was collected during the OM&M quarterly site visit completed during the week of July 24, 2006. The sample was analyzed for VOCs.
- PT system operating parameters were recorded during the quarterly OM&M site visit.
- Total Organic Carbon (TOC) samples were collected from select injection wells during the week of July 24, 2006.
- Automated reagent injection (ARI) system operating parameters were recorded during each injection event.



PT system groundwater samples were collected as grab samples directly from the individual recovery pipelines connected to production wells GMPW-3 and GMPW-4, the combined influent water to the low profile air stripper, and the combined effluent after the cartridge filters. A grab sample could not be collected from production well GMPW-5 due to well damage caused by flooding of the North Stream. The effluent air sample was collected as a grab sample directly from the designated point located on the low profile air stripper stack.

## 2.3 Spring Water Remediation System Performance Monitoring

SP-5 Spring Water Remediation System OM&M was conducted on July 28, 2006 in accordance with the LTM Plan Addendum for Spring Water Remediation Systems (ARCADIS 2003) and consisted of the collection of influent and effluent spring water samples for analysis of VOCs. Discharge flow rate and depth to water in the treatment unit were also recorded. The influent sample was collected after removing three well volumes from the influent monitoring well, which is located within the SP-5 treatment unit and screened below the liquid phase granular activated carbon (LPGAC) zone. The treatment system effluent sample was collected as a grab sample from the discharge pipe prior to entering the riprap-lined outlet. All spring water samples were analyzed for VOCs using USEPA Method 8260.

## 3. Groundwater Flow

A synoptic round of water level measurements will be completed during Quarters 2 and 4 for evaluation of groundwater flow conditions.

## 4. Groundwater Quality

The following sections describe the analytical results for groundwater samples collected during the July 2006 monitoring round (Operational Year 4, Quarter Number 3). Groundwater analytical results are provided in Tables 1 and 2. Where applicable, the previous round of analytical results for the respective sampling location has been provided in the same table for comparative purposes.

### 4.1 Volatile Organic Compounds

As shown in Table 1, total VOC (TVOC) concentrations in all monitoring wells sampled during the reporting period were generally stable to decreasing. Specifically, monitoring well GMMW-5, which is located closest to the IRZ, remained stable at 299.0

micrograms per liter (ug/L) during the current reporting period. Similarly, TVOC concentrations in mid-plume monitoring wells PW-4, W-5 and GMMW-2 remained stable at 60.2 ug/L, 193.3 ug/L, and 337.8 ug/L, respectively. TVOC concentrations in mid-plume monitoring well GMMW-6 decreased significantly to 551.1 ug/L.

PT system analytical VOC results are provided in Table 4. During the current reporting period, TVOC concentration at production wells GMPW-3 and GMPW-4 were consistent with prior rounds of data. Specifically, TVOC concentrations in production wells GMPW-3 and GMPW-4 were 284.0 ug/L and 362.5 ug/L, respectively. A complete evaluation of performance monitoring conducted on the PT system is provided in Section 7.1.2 of this report.

## 4.2 Indicators of Reducing Conditions

Groundwater analytical results for biogeochemical parameters and field parameters were collected in accordance with the LTM plan and are provided in Table 2. In summary, field and laboratory groundwater data for Wells GMMW-5 and GMMW-6 indicate that strongly reducing conditions are being maintained within the IRZ. This is evidenced by the presence of reduced forms of alternate electron acceptors (i.e., methane). Further details of the ARI system performance monitoring are provided in Section 7.2.2 of this report.

## 4.3 Evidence of Biodegradation

Table 2 provides the results of biodegradation end product concentrations in monitoring wells and indicates the continued occurrence of bioactivity and biodegradation of VOCs within the IRZ. Specifically, the concentration of ethene within monitoring wells GMMW-5 and GMMW-6 continue to be elevated when compared to baseline conditions. Ethene results for monitoring well GMMW-6 remained elevated during Operational Year 4, Quarter Number 3 and continue to indicate that the IRZ has extended to the vicinity of this well. Additional details on the results of biogeochemical monitoring as evidence of Groundwater Remediation System performance and effectiveness are discussed in Section 7.2.2 of this report.

## 5. Spring Water Quality

Spring water samples from the SP-2 and SP-3 spring water locations were not collected during the current reporting period due to unsafe conditions caused by

flooding of the North Stream. Further details are provided in Section 10, Recommendations.

Analytical results for the former SP-4 spring location are provided in Section 6 below. Analytical results for the SP-5 Spring Water Remediation System are discussed in Section 8 of this report.

## 6. Surface Water Quality

Surface water quality analytical results for the Operational Year 4, Quarter Number 3 monitoring round are summarized in Table 1. As shown in Table 1, surface water quality at the F-6 and SP-4 sampling locations remains consistent with prior rounds of analytical data. Specifically, TVOC concentrations at the F-6 and SP-4 sampling locations were 4.1 ug/L and 6.6 ug/L, respectively. This data indicate that surface water quality is not being adversely impacted despite the damage caused to the side-slopes of the landfill and the former SP-4 spring area.

## 7. Groundwater Remediation System Performance

The following section describes the results of the Groundwater Remediation System performance monitoring conducted during Operational Year 4, Quarter Number 3.

### 7.1 PT System

The following section describes the results of the PT system performance monitoring conducted during Operational Year 4, Quarter Number 3.

#### 7.1.1 Summary of Operation, Maintenance, and Monitoring

The PT system operated continuously during Operational Year 4, Quarter Number 3. PT system OM&M was conducted during the week of July 24, 2006 and included operation and maintenance of system equipment, the collection of system performance samples (water and vapor), and recording system operating parameters. Table 3 provides a summary of the recorded system operating parameters. As shown in Table 3, the total influent groundwater recovery rate was approximately 0.25-gallons per minute (gpm), with individual recovery rates of 0.03-gpm, 0.21-gpm, and 0.03-gpm for production wells GMPW-3, GMPW-4, and GMPW-5, respectively. The average recovery rate during Operational Year 4, Quarter Number 3 at production wells GMPW-3 and GMPW-5 were well below system startup conditions. ARCADIS

continued to troubleshoot the cause of the decreased flow rate at GMPW-3 and believes it is a result of a mechanical malfunction as opposed to a well problem. As referenced previously, production well GMPW-5 was damaged as a result of flooding of the North Stream. Accordingly, this well did not operate during most of the current reporting period. Production well GMPW-4 operated in a manner consistent with its previous operation. A total of 43,205 gallons of groundwater were recovered during the reporting period and a total of 1,117,090 gallons of groundwater have been recovered since system startup. The low profile air stripper operated at design specifications with the blower discharge pressure of 8.6-inches of water column (i.w.c.) and a low profile air stripper blower flowrate of 325 standard cubic feet per minute (scfm).

## 7.1.2 Results of Performance Sampling

PT system performance sampling for Operational Year 4, Quarter Number 3 was conducted on July 27 and 28, 2006. As discussed previously, four groundwater samples and one vapor sample were collected. Groundwater samples included collection of individual production well samples (GMPW-3 and GMPW-4), total influent, and total effluent after the cartridge filters. The vapor sample was collected from the effluent stack of the low profile air stripper.

Table 4 provides a summary of the PT system performance groundwater sampling analytical results. As shown in Table 4, all groundwater VOCs were treated to below their respective Best Professional Judgment (BPJ) limits via the low profile air stripper. The total iron concentration after the cartridge filter was below the respective recommended daily average BPJ limit. Based on the total groundwater recovered during the reporting period and total influent groundwater concentration, an estimated 0.11 pounds (lbs) of VOC mass were removed from the subsurface during the quarterly reporting period, as shown in Table 5. A total of approximately 2.00 lbs of VOCs have been removed from the subsurface since system startup.

Table 6 provides a summary of the PT system performance vapor sampling analytical results. As shown in Table 6, VOCs were not detected above their respective detection limits. To be conservative, a NYSDEC DAR-1 air model was calculated using the actual analytical data for detected constituents or the detection limit of all constituents, which were not detected but have historically been detected in the influent groundwater. All COCs were below their respective short-term guidance concentrations (SGCs) and annual guidance concentrations (AGCs). Appendix B contains the NYSDEC DAR-1 AGC screening simulation based on the hand

calculations provided in the NYSDEC DAR-1 AGC/SGC tables dated December 22, 2003.

## 7.2 ARI System

The following section describes the results of the ARI system performance monitoring conducted during Operational Year 4, Quarter Number 3.

### 7.2.1 Summary of Operation, Maintenance, and Monitoring

ARI system OM&M was conducted during the Operational Year 4, Quarter Number 3 OM&M site visit during the week of July 24, 2006 and included operation and maintenance of system equipment. A reagent injection was not conducted during the current reporting period. Nonetheless, sufficient organic carbon was maintained within the subsurface to maintain the anaerobic IRZ (as described below).

### 7.2.2 Results of Performance Sampling

ARI system performance sampling was conducted on July 28, 2006. As discussed previously, this event consisted of obtaining TOC samples at three injection wells. In addition, analytical results from select monitoring wells under the environmental effectiveness monitoring program were utilized to determine the effectiveness of the ARI system. A summary of key observations is as follows:

- The TOC concentration at monitoring well GMMW-5 (24.1 mg/L), GMMW-6 (38.6 mg/L) and injection wells IW-3 (430 mg/L), IW-8 (274 mg/L), and IW-13 (40.5 mg/L) indicate that sufficient organic carbon is being delivered to the subsurface to maintain the IRZ.
- The methane concentration in monitoring well GMMW-5 remained significantly elevated at 23,000 micrograms per liter (ug/L), providing evidence that strongly reducing conditions (methanogenic) are being maintained within the IRZ.
- Similarly, the methane concentration in monitoring well GMMW-6 remained elevated at 3,900 ug/L.
- The ethene concentration in monitoring well GMMW-5 remained elevated at 36,000 nanograms per liter (ng/L). The ethane concentration in monitoring

well GMMW-5 increased to 11,000 (ng/L). The data continue to indicate that complete reductive dechlorination is occurring within the IRZ; and,

- The ethene concentration in monitoring well GMMW-6 remained elevated at 110,000 ng/L.

As referenced previously, TVOC concentrations remained stable at monitoring well GMMW-5 and TVOC concentrations in mid-plume monitoring well GMMW-6 decreased significantly to 551.1 ug/L.

## 8. Spring Water Remediation System Performance

SP-5 Spring Water Remediation System OM&M was conducted on July 28, 2006 in accordance with the LTM Plan Addendum for Spring Water Remediation Systems (ARCADIS 2003). SP-5 remediation system analytical results are provided in Table 7. As shown in Table 7, all effluent COCs were treated to at or below their respective BPJ limits via the LPGAC. Influent TVOC analytical data (79.6 ug/L) remained consistent with historical analytical data. Table 8 contains the SP-5 Spring Water Remediation System field parameters recorded during Operational Year 4, Quarter Number 3. As shown in Table 8, the SP-5 remedial system treated approximately 178,823 gallons of spring water during the operating period. An estimated 0.13 lbs of VOCs was removed by the SP-5 remedial system during the same period. An estimated 1,034,177 gallons of spring water have been treated and an estimated 0.76 lbs of VOC mass have been recovered since system startup.

## 9. Conclusions

Based on the data obtained from the Operational Year 4, Quarter Number 3 monitoring, ARCADIS concludes the following:

- The revised injection methodology continues to maintain the anaerobic IRZ and is completely degrading contaminant mass. This is evidenced by the observation of methanogenic conditions and significant increase in reductive dechlorination end-products (i.e., ethene).
- The Groundwater Remediation System operated continuously during the current reporting period. Similar to recent operation, the recovery rate in production well GMPW-3 remained below historical levels. In addition, production well GMPW-5

did not operate for the majority of the current reporting period due to damage caused by flooding of the North Stream.

- The PT system is operating as designed and is treating recovered groundwater VOCs and total iron to below BPJ limits prior to discharge.
- The ARI system is operating as designed and has established an anaerobic IRZ in the vicinity of and downgradient of the injection wells.
- The SP-5 Spring Water Remediation System is operating as designed and is treating recovered spring water VOCs to below BPJ limits prior to discharge.
- Surface water data indicate that surface water quality is not being adversely impacted despite the damage caused to the side-slopes of the landfill and the former SP-4 spring area.

## 10. Recommendations

The following recommendations are made for Operational Year 4, Quarter Number 3 activities:

- Once conditions are made safe for entry, inspect the SP-2 and SP-3 spring locations to identify their current condition as a result of the flood damage.
- Continue to operate the ARI system following the modified injection methodology utilized during the current reporting period.
- Continue to evaluate and troubleshoot performance of production well GMPW-3 to determine the cause of decreased performance. Consider replacing the pump.
- Locate production well GMPW-5 and determine the appropriate repair for the well.
- Inspect the former SP-4 spring location and determine the appropriate maintenance for this area.

## 11. Project Schedule

Groundwater environmental effectiveness monitoring is scheduled to be conducted for Operational Year 4 on the quarterly schedule set forth in the Proposed Modifications to Long-Term Monitoring Program (ARCADIS 2005). System OM&M of the Groundwater Remediation System will continue to be performed on a quarterly basis consistent with the LTM Plan. Evaluation of the flood damage to remedial components is currently underway. The damaged components will be repaired as soon as feasible. Repair status of the damaged remedial components will be documented in future Monitoring Reports and through interim correspondence with the NYSDEC and USEPA.



# ARCADIS

## Operational Year 4 Quarter Number 3 Monitoring Report

Colesville Landfill  
Broome County, New York  
NYSDEC Site 704010

### 12. References

ARCADIS G&M, Inc. 2002. Long-Term Monitoring Plan, Colesville Landfill, Broome County, New York, NYSDEC Site 704010. June 28, 2002.

ARCADIS G&M, Inc. 2003. Long-Term Monitoring Plan Addendum for Spring Water Remediation Systems, Colesville Landfill, Broome County, New York , NYSDEC Site 704010. November 3, 2003.

ARCADIS G&M, Inc. 2004. Interim Remedial Action Report, Colesville Landfill, Broome County, New York, NYSDEC Site 704010. September 22, 2004.

ARCADIS G&M, Inc. 2005 Proposed Modifications to Long-Term Monitoring Program, Broome County, New York, NYSDEC Site 704010. June 28, 2005.

ARCADIS G&M, Inc. 2006 Operational Year 3 Annual Monitoring Report, Broome County, New York, NYSDEC Site 704010. March 2, 2006.

# ARCADIS

Table 1. Concentrations of Volatile Organic Compounds Detected in Groundwater, Operational Year 4, Quarter Number 3, Colesville Landfill, Broome County, New York.

Constituents (units in ug/L)	Sample ID: Date:	GMMW-02 3/30/2006	GMMW-02 7/27/2006	GMMW-05 3/30/2006	GMMW-05 7/27/2006	GMMW-06 3/30/2006	GMMW-06 7/27/2006	GMMW-06* 7/27/2006
1,1,1-Trichloroethane		24	19	<1.0	<1.0	8.2	6	5.6
1,1,2-Trichloroethane		<1.0	<1.0	<1.0	<1.0	<1.0	<5.0	<5.0
1,1-Dichloroethane		110	83	62	3.5	440	250	250
1,1-Dichloroethene		2.0	1.3	<1.1	<1.0	<1.0	<5.0	<5.0
1,2-Dichloroethane		<1.0	<1.0	<1.0	3.5	<1.0	<5.0	<5.0
1,2-Dichloropropane		<1.0	<1.0	<1.1	<1.0	<1.0	<5.0	<5.0
Benzene		2.8	2.9	1.4	2.5	5.9	7.1	7
Chlorobenzene		37	32	17	22	36	33	34
Chloroethane		34	24	160	230	190	150	150
Chloroform		<1.0	<1.0	<1.1	<1.0	<1.0	<5.0	<5.0
cis-1,2-Dichloroethene		140	100	38	16	200	64	60
Dichlorodifluoromethane		<1.0	<1.0	<1.0	<1.0	<1.0	<5.0	<5.0
Ethylbenzene		<1.0	<1.0	<1.0	<1.0	<1.0	<5.0	<5.0
Methylene chloride		1.4	1.6 U	2.4	2.8 U	11	12	12
Methyl tert-butyl ether		<1.0	<1.0	<1.0	<1.0	<1.0	<5.0	<5.0
Naphthalene		<1.0	<1.0	<1.0	<1.0	<1.0	<5.0	<5.0
o-Xylene		<1.0	<1.0	1.8	3.2	<1.0	<5.0	<5.0
Tetrachloroethene		<1.0	<1.0	<1.1	<1.0	<1.0	<5.0	<5.0
Toluene		<1.0	<1.0	2.8	4.8	<1.0	<5.0	<5.0
trans-1,2-Dichloroethene		<1.0	<1.0	<1.1	<1.0	<1.0	<5.0	<5.0
Trichloroethene		67	60	<1.1	<1.0	9	<1.0	<1.0
Vinyl chloride		17	14	12	11	87	29	28
<b>Total VOCs</b>		<b>435.2</b>	<b>336.2</b>	<b>297.4</b>	<b>297</b>	<b>987.1</b>	<b>551.1</b>	<b>546.6</b>

(1) Surfacewater sample

**Bold Constituent detected above MDL.**

VOCs Volatile Organic Compounds.

ug/L Micrograms per liter.

\* Field replicate.

J Estimated value.

MDL Method detection limit.

NA Not analyzed.

U Data Qualified as Non-Detect.

# ARCADIS

Table 1. Concentrations of Volatile Organic Compounds Detected in Groundwater, Operational Year 4, Quarter Number 3, Colesville Landfill, Broome County, New York.

Constituents (units in ug/L)	Sample ID: Date:	PW-04 3/30/2006	PW-04 7/27/2006	W-05 3/30/2006	W-05 7/27/2006	SP-4 <sup>(1)</sup> 3/31/06	SP-4 <sup>(1)</sup> 7/28/2006	F-6 <sup>(1)</sup> 12/23/2005
1,1,1-Trichloroethane		18	12	<1.0	<1.0	<1.0	<1.0	<1.0
1,1,2-Trichloroethane		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
1,1-Dichloroethane		17	13	94	81	3.5	4.9	1.7
1,1-Dichloroethene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
1,2-Dichloroethane		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
1,2-Dichloropropane		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Benzene		<1.0	<1.0	5.2	4.6	<1.0	<1.0	<1.0
Chlorobenzene		<1.0	<1.0	20	18	<1.0	<1.0	<1.0
Chloroethane		7.2	2.5	95	79	<1.0	<1.0	<1.0
Chloroform		1.4	1.5	<1.0	<1.0	<1.0	<1.0	<1.0
cis-1,2-Dichloroethene		13	15	3.2	1.7	<1.0	1.7	<1.0
Dichlorodifluoromethane		2.1	ND	2.3	<1.0	<1.0	<1.0	<1.0
Ethylbenzene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Methylene chloride		<1.0	1.2 U	2.5	3.1 U	<1.0	<1.0	<1.0
Methyl tert-butyl ether		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Naphthalene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
o-Xylene		<1.0	<1.0	<1.0	1.1	<1.0	<1.0	<1.0
Tetrachloroethene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Toluene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
trans-1,2-Dichloroethene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Trichloroethene		17	15	2.8	1.7	<1.0	<1.0	<1.0
Vinyl chloride		1.5	<1.0	6.2	3.1	<1.0	<1.0	<1.0
<b>Total VOCs</b>		<b>77.2</b>	<b>59.0</b>	<b>231.2</b>	<b>190.2</b>	<b>3.5</b>	<b>6.6</b>	<b>1.7</b>

(1) Surfacewater sample

**Bold Constituent detected above MDL.**

VOCs Volatile Organic Compounds.

ug/L Micrograms per liter.

\* Field replicate.

J Estimated value.

MDL Method detection limit.

NA Not analyzed.

U Data Qualified as Non-Detect.

# ARCADIS

Table 1. Concentrations of Volatile Organic Compounds Detected in Groundwater, Operational Year 4, Quarter Number 3, Colesville Landfill, Broome County, New York.

Constituents (units in ug/L)	Sample ID: Date:	F-6 <sup>(1)</sup> 7/28/2006	TBV072706 7/27/2006	TBV072806 7/28/2006	FBV072806 7/28/2006
1,1,1-Trichloroethane		<1.0	<1.0	<1.0	<1.0
1,1,2-Trichloroethane		<1.0	<1.0	<1.0	<1.0
1,1-Dichloroethane		<b>3.0</b>	<1.0	<1.0	<1.0
1,1-Dichloroethene		<1.0	<1.0	<1.0	<1.0
1,2-Dichloroethane		<1.0	<1.0	<1.0	<1.0
1,2-Dichloropropane		<1.0	<1.0	<1.0	<1.0
Benzene		<1.0	<1.0	<1.0	<1.0
Chlorobenzene		<1.0	<1.0	<1.0	<1.0
Chloroethane		<1.0	<1.0	<1.0	<1.0
Chloroform		<1.0	<1.0	<1.0	<1.0
cis-1,2-Dichloroethene		<b>1.1</b>	<1.0	<1.0	<1.0
Dichlorodifluoromethane		<1.0	<1.0	<1.0	<1.0
Ethylbenzene		<1.0	<1.0	<1.0	<1.0
Methylene chloride		<1.0	<1.0	<b>1.1</b>	<b>1.1</b>
Methyl tert-butyl ether		<1.0	<1.0	<1.0	<1.0
Naphthalene		<1.0	<1.0	<1.0	<1.0
o-Xylene		<1.0	<1.0	<1.0	<1.0
Tetrachloroethene		<1.0	<1.0	<1.0	<1.0
Toluene		<1.0	<1.0	<1.0	<1.0
trans-1,2-Dichloroethene		<1.0	<1.0	<1.0	<1.0
Trichloroethene		<1.0	<1.0	<1.0	<1.0
Vinyl chloride		<1.0	<1.0	<1.0	<1.0
<b>Total VOCs</b>		<b>4.1</b>	<b>0.0</b>	<b>1.1</b>	<b>1.1</b>

(1) Surfacewater sample

## **Bold Constituent detected above MDL.**

VOCs Volatile Organic Compounds.

ug/L Micrograms per liter.

\* Field replicate.

J Estimated value.

MDL Method detection limit.

NA Not analyzed.

U Data Qualified as Non-Detect.

# ARCADIS

Table 2. Concentrations of Selected Metals, General Chemistry, Field Parameters, and Dissolved Gases Detected in Groundwater, Operational Year 4, Quarter Number 3, Colesville Landfill, Broome County, New York.

Parameters	Sample ID: Date:	GMMW-02 3/30/06	GMMW-02 7/27/06	GMMW-05 3/30/06	GMMW-05 7/27/06
<u>UNITS</u>					
<u>METALS</u>					
Iron, Dissolved	mg/L	--	--	--	--
Manganese, Dissolved	mg/L	--	--	--	--
<u>GENERAL CHEMISTRY</u>					
Bromide	mg/L	--	--	--	--
Chloride	mg/L	--	--	--	--
Nitrogen, Nitrate (As N)	mg/L	--	--	--	--
Nitrogen, Nitrite	mg/L	--	--	--	--
Total Organic Carbon	mg/L	4.6	ND	37.6	24.1
Sulfate	mg/L	--	--	--	--
Sulfide (field)	mg/L	--	--	--	--
Iron (field)	mg/L	--	--	--	--
<u>FIELD PARAMETERS</u>					
pH	Standard units	6.4	6.54	6.07	6.6
Specific Conductance	mmhos/cm	0.704	0.1245	0.687	1.039
Turbidity	NTU	--	--	--	--
Dissolved Oxygen	mg/L	--	--	--	--
Temperature	deg C	13.1	18.6	10.4	18.8
ORP	mV	--	--	--	--
<u>DISSOLVED GASES</u>					
Carbon dioxide	mg/L	220	180	170	200
Carbon monoxide	mg/L	<1.0	<1	<1.0	<1
Ethane	ng/L	550	550	1400	11000
Ethene	ng/L	2900	3600	50000	36000
Methane	ug/L	1500	1600	18000	23000
Nitrogen	mg/L	23	14	13	4.1
Oxygen	mg/L	3.7	1.3	2.6	0.99

**Bold Constituent detected above MDL.**

mg/L	Milligrams per liter.
mmhos/cm	Millimhos per centimeter.
NTU	Nephelometric Turbidity Units.
deg C	Degrees Celsius.
mV	Millivolts.
ng/L	Nanograms per liter.
--	Not analyzed or collected.
ug/L	Micrograms per liter.
IW	Injection well.
ORP	Oxidation-reduction potential.
J	Qualifier assigned to analytical data indicating result is estimated.

Table 2. Concentrations of Selected Metals, General Chemistry, Field Parameters, and Dissolved Gases Detected in Groundwater, Operational Year 4, Quarter Number 3, Colesville Landfill, Broome County, New York.

Parameters	Sample ID: Date:	GMMW-06 3/30/06	GMMW-06 7/27/06	PW-4 3/30/06	PW-04 7/27/06
<u>UNITS</u>					
<u>METALS</u>					
Iron, Dissolved	mg/L	--	--	--	--
Manganese, Dissolved	mg/L	--	--	--	--
<u>GENERAL CHEMISTRY</u>					
Bromide	mg/L	--	--	--	--
Chloride	mg/L	--	--	--	--
Nitrogen, Nitrate (As N)	mg/L	--	--	--	--
Nitrogen, Nitrite	mg/L	--	--	--	--
Total Organic Carbon	mg/L	<b>19.8</b>	<b>38.6</b>	<b>3.98</b>	ND
Sulfate	mg/L	--	--	--	--
Sulfide (field)	mg/L	--	--	--	--
Iron (field)	mg/L	--	--	--	--
<u>FIELD PARAMETERS</u>					
pH	Standard units	<b>6.59</b>	<b>6.66</b>	<b>6.02</b>	<b>5.73</b>
Specific Conductance	mmhos/cm	<b>1.139</b>	<b>1.225</b>	<b>0.647</b>	<b>0.591</b>
Turbidity	NTU	--	--	--	--
Dissolved Oxygen	mg/L	--	--	--	--
Temperature	deg C	<b>11.1</b>	<b>16.3</b>	<b>10</b>	<b>17.7</b>
ORP	mV	--	--	--	--
<u>DISSOLVED GASES</u>					
Carbon dioxide	mg/L	<b>210</b>	<b>200</b>	<b>220</b>	<b>190</b>
Carbon monoxide	mg/L	<1.0	<1	<1.0	<1
Ethane	ng/L	<b>1500</b>	<b>2300</b>	<b>70</b>	<25
Ethene	ng/L	<b>110000</b>	<b>110000</b>	<b>310</b>	<b>160</b>
Methane	ug/L	<b>2400</b>	<b>3900</b>	<b>31</b>	<b>10</b>
Nitrogen	mg/L	<b>20</b>	<b>14</b>	<b>14</b>	<b>15</b>
Oxygen	mg/L	<b>2.9</b>	<b>1.6</b>	<b>2.8</b>	<b>4.2</b>

**Bold Constituent detected above MDL.**

mg/L	Milligrams per liter.
mmhos/cm	Millimhos per centimeter.
NTU	Nephelometric Turbidity Units.
deg C	Degrees Celsius.
mV	Millivolts.
ng/L	Nanograms per liter.
--	Not analyzed or collected.
ug/L	Micrograms per liter.
IW	Injection well.
ORP	Oxidation-reduction potential.
J	Qualifier assigned to analytical data indicating result is estimated.

# ARCADIS

Table 2. Concentrations of Selected Metals, General Chemistry, Field Parameters, and Dissolved Gases Detected in Groundwater, Operational Year 4, Quarter Number 3, Colesville Landfill, Broome County, New York.

Parameters	Sample ID: Date:	W-05 3/30/06	W-05 7/27/06	IW-03 3/30/06	IW-03 7/28/06
	<u>UNITS</u>				
<u>METALS</u>					
Iron, Dissolved	mg/L	--	--	--	--
Manganese, Dissolved	mg/L	--	--	--	--
<u>GENERAL CHEMISTRY</u>					
Bromide	mg/L	--	--	--	--
Chloride	mg/L	--	--	--	--
Nitrogen, Nitrate (As N)	mg/L	--	--	--	--
Nitrogen, Nitrite	mg/L	--	--	--	--
Total Organic Carbon	mg/L	<b>6.79</b>	<b>3.87</b>	<b>630</b>	<b>430</b>
Sulfate	mg/L	--	--	--	--
Sulfide (field)	mg/L	--	--	--	--
Iron (field)	mg/L	--	--	--	--
<u>FIELD PARAMETERS</u>					
pH	Standard units	<b>6.77</b>	<b>6.52</b>	--	<b>5.32</b>
Specific Conductance	mmhos/cm	<b>0.946</b>	<b>0.417</b>	--	--
Turbidity	NTU	--	--	--	--
Dissolved Oxygen	mg/L	--	--	--	--
Temperature	deg C	<b>12.5</b>	<b>17.7</b>	--	--
ORP	mV	--	--	--	--
<u>DISSOLVED GASES</u>					
Carbon dioxide	mg/L	<b>210</b>	190	--	--
Carbon monoxide	mg/L	<b>&lt;1.0</b>	<1	--	--
Ethane	ng/L	<b>16000</b>	<b>18000</b>	--	--
Ethene	ng/L	<b>8100</b>	<b>9500</b>	--	--
Methane	ug/L	<b>1500</b>	<b>2000</b>	--	--
Nitrogen	mg/L	<b>15</b>	<b>16</b>	--	--
Oxygen	mg/L	<b>1.8</b>	<b>1.5</b>	--	--

**Bold Constituent detected above MDL.**

mg/L	Milligrams per liter.
mmhos/cm	Millimhos per centimeter.
NTU	Nephelometric Turbidity Units.
deg C	Degrees Celsius.
mV	Millivolts.
ng/L	Nanograms per liter.
--	Not analyzed or collected.
ug/L	Micrograms per liter.
IW	Injection well.
ORP	Oxidation-reduction potential.
J	Qualifier assigned to analytical data indicating result is estimated.

Table 2. Concentrations of Selected Metals, General Chemistry, Field Parameters, and Dissolved Gases Detected in Groundwater, Operational Year 4, Quarter Number 3, Colesville Landfill, Broome County, New York.

Parameters	Sample ID: Date:	IW-08 3/30/06	IW-08 7/28/06	IW-13 3/30/06	IW-13 7/28/06
<u>UNITS</u>					
<u>METALS</u>					
Iron, Dissolved	mg/L	--	--	--	--
Manganese, Dissolved	mg/L	--	--	--	--
<u>GENERAL CHEMISTRY</u>					
Bromide	mg/L	--	--	--	--
Chloride	mg/L	--	--	--	--
Nitrogen, Nitrate (As N)	mg/L	--	--	--	--
Nitrogen, Nitrite	mg/L	--	--	--	--
Total Organic Carbon	mg/L	<b>2000</b>	<b>274</b>	<b>80.7</b>	<b>40.5</b>
Sulfate	mg/L	--	--	--	--
Sulfide (field)	mg/L	--	--	--	--
Iron (field)	mg/L	--	--	--	--
<u>FIELD PARAMETERS</u>					
pH	Standard units	--	<b>4.68</b>	--	<b>6.26</b>
Specific Conductance	mmhos/cm	--	--	--	--
Turbidity	NTU	--	--	--	--
Dissolved Oxygen	mg/L	--	--	--	--
Temperature	deg C	--	--	--	--
ORP	mV	--	--	--	--
<u>DISSOLVED GASES</u>					
Carbon dioxide	mg/L	--	--	--	--
Carbon monoxide	mg/L	--	--	--	--
Ethane	ng/L	--	--	--	--
Ethene	ng/L	--	--	--	--
Methane	ug/L	--	--	--	--
Nitrogen	mg/L	--	--	--	--
Oxygen	mg/L	--	--	--	--

**Bold Constituent detected above MDL.**

mg/L	Milligrams per liter.
mmhos/cm	Millimhos per centimeter.
NTU	Nephelometric Turbidity Units.
deg C	Degrees Celsius.
mV	Millivolts.
ng/L	Nanograms per liter.
--	Not analyzed or collected.
ug/L	Micrograms per liter.
IW	Injection well.
ORP	Oxidation-reduction potential.
J	Qualifier assigned to analytical data indicating result is estimated.



# ARCADIS

Table 3. PT System Operating Parameters, Operational Year 4, Quarter Number 3, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Date	Time Recorded	Air Stripper Measurements		Flow Measurements				
		Blower Discharge	Blower Effluent	Total	Water Bypass	GMPW-3	GMPW-4	GMPW-5**
		Pressure	Flowrate	Effluent Totalizer	Totalizer	Totalizer	Totalizer	Totalizer
		PI-301 (i.w.c.)	(scfm)	FQI-401 (gallons)	FQI-402 (gallons)	FQI-101 (gallons)	FQI-102 (gallons)	FQI-103 (gallons)
3/31/2006	5:30 PM	8.9	263	1,073,885.4	949,698.8	366,582.0	30,641.3	379,936.8
7/28/2006	1:10 PM	8.6	325	1,117,090.0	981,809.0	371,630.7	67,327.1	384,879.0
Average Daily Flowrate (gpm) =				0.25	0.19	0.03	0.21	0.03
Total Groundwater Recovered During Reporting Period (gallons) =				43,205	32,110	5,049	36,686	4,942

NM Not measured.  
gpm Gallons per minute.  
i.w.c. Inches of water column.  
scfm Standard cubic feet per minute.

## Notes:

- GMPW-4 totalizing flow meter malfunctioned and was replaced on 12/23/2005.
- GMPW-5 shutdown during reporting period due to damage caused by local flooding.

# ARCADIS

Table 4. Concentrations of Volatile Organic Compounds and Selected Metals Detected in Aqueous Samples Collected from the PT System, Operational Year 4, Quarter Number 3, Colesville Landfill, Broome County, New York<sup>5,6</sup>.

Constituents	Model Technology BPJ Limits <sup>1,2</sup> (ug/L)	Sample ID: GMPW-3 INF Date: 7/27/2006	GMPW-4 INF 7/27/2006	COMBINED INF 7/28/2006	EFFLUENT AC II 7/28/2006
1,1,1-Trichloroethane	10-20	37	33	38	<1.0
1,1,2-Trichloroethane	10	<1.0	<1.0	<1.0	<1.0
1,1-Dichloroethane	10	57	81	65	<1.0
1,1-Dichloroethene	10	2.8	2.6	2.7	<1.0
1,2-Dichloroethane	10-30	<1.0	<1.0	<1.0	<1.0
1,2-Dichloropropane	NA	<1.0	<1.0	<1.0	<1.0
Benzene	5	4.7	4.6	4.8	<1.0
Chlorobenzene	NA	<1.0	6	1.3	<1.0
Chloroethane	NA	20	34	22	<1.0
Chloroform	NA	<1.0	<1.0	<1.0	<1.0
cis-1,2-Dichloroethene	10	83	84	85	<1.0
Dichlorodifluoromethane	NA	1.9	2.2	1.9	<1.0
Ethylbenzene	5	<1.0	<1.0	<1.0	<1.0
Methylene Chloride	10-50	3.6 U	4.1 U	3.8 U	<1.0
Methyl tert-butyl ether	50	<1.0	<1.0	<1.0	<1.0
Naphthalene	10	<1.0	<1.0	<1.0	<1.0
o-Xylene	5	<1.0	<1.0	<1.0	<1.0
Tetrachloroethene	10	<1.0	<1.0	<1.0	<1.0
Toluene	5	<1.0	<1.0	<1.0	<1.0
trans-1,2-Dichloroethene	10-50	<1.0	<1.0	<1.0	<1.0
Trichloroethene	10	63	80	68	<1.0
Vinyl Chloride	10-50	11	31	15	<1.0
<b>Total VOCs</b>		<b>280.4</b>	<b>358.4</b>	<b>303.7</b>	<b>0</b>
	Model Technology BPJ Limits <sup>3,4</sup> (mg/L)				
<b>Metals (units in mg/L)</b>					
Total Iron	1.2 / 0.61	0.364	3.63	4.9	0.558

See Notes on Last Page.

## ARCADIS

Table 4. Concentrations of Volatile Organic Compounds and Selected Metals Detected in Aqueous Samples Collected from the PT System, Operational Year 4, Quarter Number 3, Colesville Landfill, Broome County, New York<sup>a,b</sup>.

---

**Notes:**

1. Model Technology Best Professional Judgment (BPJ) Limits recommended for Air Stripping with appropriate pretreatment from Attachment C of TOGS 1.2.1.
2. When a range is listed for the BPJ limit, a variation in available references was found. Recommended daily maximum limits should be in this range.
3. Model Technology BPJ Limits recommended for Lime, Settle and Filter treatment.
4. The recommended daily maximum permit limit is 1.2 mg/L and the recommended daily average permit limit is 0.61 mg/L.
5. Production wells were sampled in accordance with the schedule set forth in Table 3 of the Long-Term Monitoring Plan (ARCADIS 2002).
6. Bold values indicate compound detected above method detection limit.

NA	No BPJ limit listed.
J	Estimated Value.
ug/L	Micrograms Per Liter.
mg/L	Milligrams Per Liter.
VOCs	Volatile Organic Compounds.
AC	After Cartridge Filter.
PT	Pump and Treat.
--	Not Analyzed or Collected.
<	Analyte Below Detection Limit.
U	Data Qualified as Non-Detect.

# ARCADIS

Table 5. PT System Mass Removal Rate of Volatile Organic Compounds, Operational Year 4, Quarter Number 3, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Date Sampled	Total VOC Influent Concentration (ug/L)	Total Effluent Totalizer FQI-401 (gallons)	Total Groundwater Recovered <sup>1</sup> Between Sampling Intervals (gal)	Influent Concentration <sup>2</sup> Geometric Mean (ug/L)	Total Estimated Mass <sup>3</sup> Removed (lbs)
3/30/2006	299.8	1,073,885.4	NA	NA	NA
7/28/2006	307.5	1,117,090.0	43,204.6	304	0.11
Total Estimated Mass Removed During Operational Year 4, Quarter Number 3 (lbs) =					0.11
Total Estimated Mass Removed Since System Startup (lbs) =					2.00

## Notes:

NA Not applicable.  
 ug/L Micrograms per liter.  
 gal Gallons.  
 lbs Pounds.  
 VOC Volatile organic compound.

1. Total Groundwater Recovered Between Sampling Intervals = Well Totalizer Reading for current sampling event - Well Totalizer Reading for prior sampling event.
2. Influent Concentration Geometric Mean = (Influent Concentration for prior sampling event x Influent Concentration for current sampling event) ^ (1/2).
3. Total Mass Removed = (Total Groundwater Recovered Between Sampling Intervals) x Influent Concentration Geometric Mean x 3.7854 L/gallon x (1 lb / 453,592,370 ug).

# ARCADIS

Table 6. Concentrations of Volatile Organic Compounds Detected in Air Stripper Effluent, Operational Year 4, Quarter Number 3, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Compounds	CAS Numbers	Sample ID: Date Sampled:	Effluent 7/28/2006 ppbv
Vinyl Chloride	75-01-4		<7.2
Chloroethane(Ethyl Chloride)	75-00-3		<7.2
1,1-Dichloroethene(Vinylidene Chloride)	75-35-4		<7.2
Methylene Chloride(Dichloromethane)	75-09-2		<7.2
1,1-Dichloroethane	75-34-3		<7.2
cis-1,2-Dichloroethylene	156-59-2		<7.2
Chloroform	67-66-3		<7.2
1,1,1-Trichloroethane(Methyl Chloroform)	71-55-6		<7.2
Benzene	71-43-2		<7.2
Trichloroethene	79-01-6		<7.2
Toluene	108-88-3		<7.2
Ethyl benzene	100-41-4		<7.2
m,p-Xylene	108-38-3/106-42-3		<7.2
o-Xylene	95-47-6		<7.2
1,2,4-Trimethylbenzene	95-63-6		<7.2
2-Propanol (Isopropyl alcohol)	67-63-0		<7.2
Dichlorodifluoromethane(Freon 12)	75-71-8		<7.2

**Bold Constituent detected above MDL.**

ppbv: parts per billion by volume

## Notes/Assumptions:

1. Samples collected by ARCADIS personnel on the dates shown and submitted to Air Toxics Laboratories LTD. for volatile organic compound (VOC) analyses using a modified USEPA Method TO-14A.

# ARCADIS

Table 7. Concentrations of Volatile Organic Compounds Detected in Aqueous Samples Collected from the SP-5 Spring Water Remediation System, Operational Year 4, Quarter Number 3, Colesville Landfill, Broome County, New York.

Constituents	Model Technology BPJ Limits <sup>1,2</sup> (ug/L)	Sample ID: SP-5 INF. Date: 7/28/2006	SP-5 EFF. 7/28/2006
<b><u>VOCs (units in ug/L)</u></b>			
1,1,1-Trichloroethane	10	<1.0	<1.0
1,1-Dichloroethane	10	<b>32</b>	<b>5.4</b>
1,2-Dichloroethane	10-100	<1.0	<1.0
Benzene	5	<b>3</b>	<1.0
Chlorobenzene	10-25	<b>31</b>	<b>1.4</b>
Chloroethane	10	<b>9.8</b>	<b>10</b>
cis-1,2-Dichloroethene	10	<b>1.8</b>	<1.0
Dichlorodifluoromethane	NA	<1.0	<1.0
Ethylbenzene	5	<1.0	<1.0
Toluene	5	<1.0	<1.0
trans-1,2-Dichloroethene	10-100	<1.0	<1.0
Trichloroethene	10	<b>2</b>	<1.0
Vinyl Chloride	10	<1.0	<1.0
<b>Total VOCs</b>		<b>79.6</b>	<b>16.8</b>

**Bold Constituent detected above MDL.**

ug/L	Micrograms per liter.
VOCs	Volatile organic compounds.
<	Analyte below detection limit.
INF.	Influent.
EFF.	Effluent.
NA	No BPJ limit listed.

**Notes:**

1. Model Technology Best Professional Judgment (BPJ) Limits recommended for carbon adsorption with appropriate pretreatment from Attachment C of TOGS 1.2.1.
2. When a range is listed for the BPJ limit, a variation in available references was found. Recommended daily maximum limits should be in this range.

# ARCADIS

Table 8. Spring Water Remediation System Mass Removal Rate of Volatile Organic Compounds, Operational Year 4, Quarter Number 3, Colesville Landfill, Broome County, New York.

Date Sampled	Total VOC Influent Concentration (ug/L)	Effluent Flowrate (gpm)	Depth to Water (feet btc)	Total Groundwater Treated <sup>1</sup> Between Sampling Intervals (gal)	Influent Concentration <sup>2</sup> Geometric Mean (ug/L)	Total Estimated Mass <sup>3</sup> Removed (lbs)
3/31/2006	91.5	0.99	0	NA	NA	NA
7/28/2006	79.6	1.1	0	178,823	85.3	0.13

Total Estimated Mass Removed During Current Quarter (lbs) = 0.13

Total Estimated Mass Removed Since System Startup (lbs) = 0.76

Total Effluent Treated Since System Startup (gallons) = 1,034,177

## Notes:

NA Not applicable.  
 NR Not recorded.  
 ug/L Micrograms per liter.  
 gpm Gallons per minute.  
 btc Below top of casing.  
 gal Gallons.  
 lbs Pounds.  
 VOC Volatile organic compound.

1. Total Spring Water Treated Between Sampling Intervals = Effluent Flowrate x 1440 min/day x days between sampling events.
2. Influent Concentration Geometric Mean = (Influent Concentration for prior sampling event x Influent Concentration for current sampling event)<sup>1/2</sup>.
3. Total Mass Removed = (Total Groundwater Treated Between Sampling Intervals) x Influent Concentration Geometric Mean x 3.7854 L/gallon x (1 lb / 453,592,370 ug).

ARCADIS

**Appendix A**

Groundwater Sampling Logs



AK/00949-0019.00030

**Well**

SP8- INF

**Date**

7-28-06

### Measuring Point Description

**Casing  
Diameter (inches)**

**Measured Width**

Well Materials	PVC
	ST. Steel

**Total depth.**

**Pump On:**

**Pump Intake:**

### Purge Method

**Pump Off:**

**Volumes Purged\_**

## Centrifugal

**Sample Time:**

**Sampled By:**

### Submersible

### Other

**Bailer Type:**

dm-LT

[illegible]

## Groundwater Sampling Form

Page of

**Well**

SP5-EPF

Date \_\_\_\_\_

5-28-X

### Measuring Point Description

**Casing  
Diameter (inches)**

**Measured Width**

Well Materials PVC

PVC

**ST. Steel**

**Total depth** \_\_\_\_\_ **Pump On:** \_\_\_\_\_

## Pump

**Intake:**

<b>Purge Method</b>	<b>. Pump Off:</b>
---------------------	--------------------

### Volumes Purged.

**Centrifugal** \_\_\_\_\_ **Sample Time:** \_\_\_\_\_

**Sample Time:**

### ■ Submersible

Other ☒ (Bailer) Type:

**Sampled**

**By:**

$$d m - i \kappa I$$
[illegible]

Project/No. X/400299.0049.0003A

**Well**

EXPLORE  
VAPOR

Date \_\_\_\_\_

7-28-00

## Screen Setting

### Measuring Point Description

**Casing  
Diameter (inches)**

### Static Water Level

**Measured Width**

Well Materials	PVC
	ST. Steel

**Total depth**

**Pump On:**

**Pump Intake:**

### Purge Method

**. Pump Off:**

### Volumes Purged

## Centrifugal

**Sample Time:**

**Sampled By:**

**Submersible**  
**Other**

**Bailer Type:**

[illegible]

## Groundwater Sampling Form

Page of

Well *EXPWent*

Date 7-28-06

**Casing  
Diameter (inches)**

Well Materials	PVC
	ST. Steel

**Pump Intake:**

### Volumes Purged.

Sampled By: PM-KT

Submersible \_\_\_\_\_  
Other Sample Box Bailer Type:

[illegible]

Date 7-28-06

**Casing  
Diameter (inches)**

Well Materials	PVC
	ST. Steel

**Pump Intake:**

### Volumes Purged

**Sampled By:**

DM-R.S.

lowflo.xls.xls  
10/20/98

## Groundwater Sampling Form

Page \_\_\_\_\_ of \_\_\_\_\_

**Well**

50-4

**Date**

7-28-06

**Sampled By:**

$$\Delta m - KI.$$
[illegible]

Project No. W-2009-019. Dxs 3A

**Well**

P-6

Date \_\_\_\_\_

## Screen Setting

### Measuring Point Description

**Casing  
Diameter (inches)**

### Static Water Level

**Measured Width**

## Well Materials

**PVC**

## ST. Steel

**Total depth**

**Pump On:**

## Pump

**Intake:**

### Purge Method

**Pump Off:**

## Volumes Purged.

## Centrifugal

**Sample Time:**

## Submersible

**Bailer Type:**

Sampled  
By:

1)  $m - KI$

lowflo.xls.xls  
10/20/98

## Groundwater Sampling Form

Page of

110044. 0019-0031

**Well**

PW 13

Date \_\_\_\_\_

7-28-04

### Measuring Point Description

**Casing  
Diameter (inches)**

**Measured Width**

Well Materials	PVC
	ST. Steel

**Total depth**

**Pump On:**

**Pump Intake:**

### Purge Method

**Pump Off:**

### Volumes Purged

## Centrifugal

**Sample Time:**

0840

## Submersible

**Bailer Type:**

**Sampled By:**

**Other**

[illegible]

Color - Light  
Slight odor



Project/No. NY 00944-0029-0003A Well

Well *Iw8*

Date \_\_\_\_\_

Screen Setting	Measuring Point Description
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	23
24	24
25	25
26	26
27	27
28	28
29	29
30	30
31	31
32	32
33	33
34	34
35	35
36	36
37	37
38	38
39	39
40	40
41	41
42	42
43	43
44	44
45	45
46	46
47	47
48	48
49	49
50	50
51	51
52	52
53	53
54	54
55	55
56	56
57	57
58	58
59	59
60	60
61	61
62	62
63	63
64	64
65	65
66	66
67	67
68	68
69	69
70	70
71	71
72	72
73	73
74	74
75	75
76	76
77	77
78	78
79	79
80	80
81	81
82	82
83	83
84	84
85	85
86	86
87	87
88	88
89	89
90	90
91	91
92	92
93	93
94	94
95	95
96	96
97	97
98	98
99	99
100	100

Casing Diameter (inches) 4"

Static Water Level	Measured Width
10.0	10.0
10.5	10.5
11.0	11.0
11.5	11.5
12.0	12.0
12.5	12.5
13.0	13.0
13.5	13.5
14.0	14.0
14.5	14.5
15.0	15.0
15.5	15.5
16.0	16.0
16.5	16.5
17.0	17.0
17.5	17.5
18.0	18.0
18.5	18.5
19.0	19.0
19.5	19.5
20.0	20.0
20.5	20.5
21.0	21.0
21.5	21.5
22.0	22.0
22.5	22.5
23.0	23.0
23.5	23.5
24.0	24.0
24.5	24.5
25.0	25.0
25.5	25.5
26.0	26.0
26.5	26.5
27.0	27.0
27.5	27.5
28.0	28.0
28.5	28.5
29.0	29.0
29.5	29.5
30.0	30.0
30.5	30.5
31.0	31.0
31.5	31.5
32.0	32.0
32.5	32.5
33.0	33.0
33.5	33.5
34.0	34.0
34.5	34.5
35.0	35.0
35.5	35.5
36.0	36.0
36.5	36.5
37.0	37.0
37.5	37.5
38.0	38.0
38.5	38.5
39.0	39.0
39.5	39.5
40.0	40.0
40.5	40.5
41.0	41.0
41.5	41.5
42.0	42.0
42.5	42.5
43.0	43.0
43.5	43.5
44.0	44.0
44.5	44.5
45.0	45.0
45.5	45.5
46.0	46.0
46.5	46.5
47.0	47.0
47.5	47.5
48.0	48.0
48.5	48.5
49.0	49.0
49.5	49.5
50.0	50.0
50.5	50.5
51.0	51.0
51.5	51.5
52.0	52.0
52.5	52.5
53.0	53.0
53.5	53.5
54.0	54.0
54.5	54.5
55.0	55.0
55.5	55.5
56.0	56.0
56.5	56.5
57.0	57.0
57.5	57.5
58.0	58.0
58.5	58.5
59.0	59.0
59.5	59.5
60.0	60.0
60.5	60.5
61.0	61.0
61.5	61.5
62.0	62.0
62.5	62.5
63.0	63.0
63.5	63.5
64.0	64.0
64.5	64.5
65.0	65.0
65.5	65.5
66.0	66.0
66.5	66.5
67.0	67.0
67.5	67.5
68.0	68.0
68.5	68.5
69.0	69.0
69.5	69.5
70.0	70.0
70.5	70.5
71.0	71.0
71.5	71.5
72.0	72.0
72.5	72.5
73.0	73.0
73.5	73.5
74.0	74.0
74.5	74.5
75.0	75.0
75.5	75.5
76.0	76.0
76.5	76.5
77.0	77.0
77.5	77.5
78.0	78.0
78.5	78.5
79.0	79.0
79.5	79.5
80.0	80.0
80.5	80.5
81.0	81.0
81.5	81.5
82.0	82.0
82.5	82.5
83.0	83.0
83.5	83.5
84.0	84.0
84.5	84.5

Well Materials ✓ PVC  
ST. Steel

**Total depth** \_\_\_\_\_ **Pump On:** \_\_\_\_\_

**Pump Intake:**

Purge Method Pump Off:

**Volumes Purged** \_\_\_\_\_

**Centrifugal** \_\_\_\_\_ **Sample Time:** \_\_\_\_\_

0825

Submersible \_\_\_\_\_  
Other \_\_\_\_\_

Sampled By: *DW*

[illegible]

## Groundwater Sampling Form

**Project No.**

NY 100 949-0012003A

**Well**

ZW-3

**Date**

7-28-00

## Casing

Diameter (inches)

4

**Measured Width**

## Well Materials

**PVC**

**ST. Steel**

**Pump On:**

## Pump

**Intake:**

**Pump Off:**

**Volumes Purged\_**

**Sample Time:**

0814

## Submersible.

**Bailer Type:**

**Sampled**

**By:**

Δm

lowflo.xls.xls  
10/20/98

COLON AMBER  
SFALON 0702

**Well**

Билеу 4

Date 7-27-06

**Casing  
Diameter (inches)**

Well Materials	PVC
	ST. Steel

**Pump  
Intake:**

**Volumes Purged** \_\_\_\_\_

Sampled By: DM-KJ

Submersible \_\_\_\_\_  
Other ☒ S.P. Bailer Type: \_\_\_\_\_

[illegible]

Project/No. M000909.0019.0003A Well 6MPW 9

Date 7-27-06

Screen Setting	Measuring Point Description
----------------	-----------------------------

**Casing  
Diameter (inches)**

Static Water Level \_\_\_\_\_ Measured Width \_\_\_\_\_

Well Materials	PVC
	ST. Steel

Total depth \_\_\_\_\_ Pump On: \_\_\_\_\_

**Pump Intake:**

Purge Method Pump Off: \_\_\_\_\_

**Volumes Purged** \_\_\_\_\_

Centrifugal \_\_\_\_\_ Sample Time: 1515

Sampled By: DM. K. J.

Submersible \_\_\_\_\_  
Other                      Bailer Type: \_\_\_\_\_

[illegible]

## Groundwater Sampling Form

Page 1 of 1

Project/No. N/4000949.0019.GD3A Well Gmmw-6

Date 7/27/06

Screen Setting	Measuring Point Description
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	23
24	24
25	25
26	26
27	27
28	28
29	29
30	30
31	31
32	32
33	33
34	34
35	35
36	36
37	37
38	38
39	39
40	40
41	41
42	42
43	43
44	44
45	45
46	46
47	47
48	48
49	49
50	50
51	51
52	52
53	53
54	54
55	55
56	56
57	57
58	58
59	59
60	60
61	61
62	62
63	63
64	64
65	65
66	66
67	67
68	68
69	69
70	70
71	71
72	72
73	73
74	74
75	75
76	76
77	77
78	78
79	79
80	80
81	81
82	82
83	83
84	84
85	85
86	86
87	87
88	88
89	89
90	90
91	91
92	92
93	93
94	94
95	95
96	96
97	97
98	98
99	99
100	100

**Casing  
Diameter (inches)**

Static Water Level	Measured Width
-----------------------	----------------

Well Materials	PVC
	ST. Steel

**Total depth** \_\_\_\_\_ **Pump On:** \_\_\_\_\_

**Pump  
Intake:**

### Purge Method

**Pump Off:**

### Volumes Purged

### Centrifugal

**Sample Time:**

**Sampled**

## Submersible

**Other**

**Bailer Type:**

**By:**

[illegible]

Lowfla.xls.xls  
10/20/98

VOC's - Clear  
TOC Clear

Odor - ~~None~~ Slight  
Very

Voc's, LASEE,  
+ Toc's

Project/No. NY000949-0019-000319

**Well**

GMMW-2

**Date**

7-27-08

## Screen Setting

### Measuring Point Description

**Casing  
Diameter (inches)**

### Static Water Level

**Measured Width**

## Well Materials

PVC

## ST. Steel

**Total depth**

**Pump On:**

## Pump

**Intake:**

### Purge Method

**. Pump Off:**

### Volumes Purged

### Centrifugal

**Sample Time:**

14145

**Submersible.**

**Other**

**Bailer Type:**

**Sampled**

**By:**

[illegible]

Voc's / toc Clear

no oak

Удѣл, межи гоним, ерне, + удѣл

**Well**

W-5

**Date**

7-27-04

### Measuring Point Description

## Casing

Diameter (inches)

**Measured Width**

## Well Materials

**PVC**

**ST. Steel**

**Total depth**

**Pump On:**

**Pump**

**Intake:**

### Purge Method

**. Pump Off:**

### Volumes Purged.

### Centrifugal

**Sample Time:**

15:25

### Submersible

**Bailer Type:**

**Sampled**

**By:**

[illegible]

Project/No.

NY 000649-0029-0003A

**Well**

PW-4

**Date**

7-27-00

### Measuring Point Description

**Casing  
Diameter (inches)**

### Static Water Level

**Measured Width**

## Well Materials

**PVC**

## ST. Steel

**Total depth**

**Pump On:**

**Pump**

**Intake:**

### Purge Method

**. Pump Off:**

### Volumes Purged.

## Centrifugal

**Sample Time:**

15:05

**Submersible.**

**Other**

**Bailer Type:**

**Sampled  
By:**

KJ

[illegible]

clear

Odor none

восз<sup>1</sup>с, мегнаве, еопале, етние & др



Project/No. NY000949.0019.0503A Well Gmmw5

Date 7/27/06

## Screen Setting

### Measuring Point Description

**Casing**  
**Diameter (inches)**

**Static  
Water Level**

**Measured Width**

Well Materials	PVC
	ST. Steel

**Total depth**

**Pump On:**

### Pump

**Intake:**

### Purge Method

**Pump Off:**

### Volumes Purged

### Centrifugal

**Sample Time:**

13:58

### Submersible

**Bailer Type:**

**Sampled**

**By:**

[illegible]

VOC'S - clear

Toe gold

odor none

VOC's, GASES, & SOLIDS

ARCADIS

## Appendix B

New York State Department of  
Environmental Conservation DAR-1  
Air Modeling Data

# ARCADIS

Table B-1. NYSDEC DAR-1 Air Modeling Data, Operational Year 4, Quarter Number 3, Colesville Landfill, Broome County, New York.

Page 1 of 3

## Parameters for 7/28/2006 Sampling Event

Discharge Temperature	T	527	°R
Ambient Temperature	Ta	541	°R
Stack Diameter	D	6	in
Stack Radius	R	0.25	ft
Stack Area	A	0.20	ft <sup>2</sup>
Exit Velocity	V	27.6	fps
Exit Flow	Q	325	acfm
Exit Flow	Q	325	scfm
Stack Height	h <sub>s</sub>	17	ft
Building Height	h <sub>b</sub>	13.25	ft
Ratio of Heights	h <sub>s</sub> /h <sub>b</sub>	1.28	
Plume rise credit? h <sub>s</sub> /h <sub>b</sub> > 1.5?	(If no, h <sub>e</sub> =h <sub>s</sub> )	(If Yes, h <sub>e</sub> = h <sub>s</sub> + 1.1 (F <sub>m</sub> ) <sup>1/3</sup> )	
Momentum Flux	F <sub>m</sub> = Ta/T * V <sup>2</sup> * R <sup>2</sup>	n/a	ft <sup>4</sup> /s <sup>2</sup>
Effective Stack Height	h <sub>e</sub>	17.0	ft
Reduction Factor? 2.5 > h <sub>s</sub> /h <sub>b</sub> > 1.5?		No, do not reduce impact	
Actual Annual Impact	C <sub>a</sub>	RF*6*Q <sub>a</sub> /h <sub>e</sub> <sup>2.25</sup>	
Mass Flow	Q <sub>a</sub>	S lbs emitted for last 12 months	

fps: feet per second

acfm: actual cubic feet per minute

ug/m<sup>3</sup>: micrograms per cubic meter

lb/yr: pounds per year

lb/hr: pounds per hour

ppb: parts per billion

## Notes/Assumptions:

1. The stack discharge temperature is 67°F based on recorded parameters.
2. The ambient temperature is approximately 81°F based on recorded conditions.
3. Calculations assume that the system will run with the maximum allowable concentrations between quarterly readings.
4. AGC refers to the Annual Guideline Concentration as determined using the hand calculations in the DAR-1 AGC/SGC Tables dated December 22, 2003.
5. To be conservative the lower detection limit was used for compounds that were below the limit of detection, but are found in the influent groundwater of the Groundwater Remediation System.

# ARCADIS

Table B-2. NYSDEC DAR-1 Air Modeling Data, Operational Year 4, Quarter Number 3, Colesville Landfill, Broome County, New York.

Page 2 of 3

Calculation of the Short-Term Guideline Concentration (SGC) for Sampling Event on 7/28/2006

Compounds	CAS Numbers	Maximum Limit (SGC) (ug/m <sup>3</sup> )	Analytical Concentration (ppb)	Detection Limit Used	Actual Emissions C <sub>a</sub> (ug/m <sup>3</sup> )	Mass/hour (lb/hr)	Maximum Potential Impact (Step III.A.3 in DAR-1) (ug/m <sup>3</sup> )	Short Term Impact (Step III.A.5 in DAR-1) (ug/m <sup>3</sup> )	Percent of the SGC (%)
Vinyl Chloride	75-01-4	180,000	7.2	*	18.71	2.63E-05	0.0045	0.29191	1.6E-04
Chloroethane(Ethyl Chloride)	75-00-3	--	7.2	*	19.31	2.71E-05	0.0046	0.30134	NA
1,1-Dichloroethene(Vinylidene Chloride)	75-35-4	--	7.2	*	29.02	4.08E-05	0.0070	0.45280	NA
Methylene Chloride(Dichloromethane)	75-09-2	14,000	7.2	*	25.42	3.57E-05	0.0061	0.39671	2.8E-03
1,1-Dichloroethane	75-34-3	--	7.2	*	29.62	4.16E-05	0.0071	0.46224	NA
cis-1,2 - Dichloroethylene	156-59-2	--	7.2	*	29.02	4.08E-05	0.0070	0.45280	NA
1,1,1-Trichloroethane(Methyl Chloroform)	71-55-6	68,000	7.2	*	39.93	5.61E-05	0.0096	0.62314	9.2E-04
Trichloroethene	79-01-6	54,000	7.2	*	39.33	5.52E-05	0.0094	0.61370	1.1E-03
Dichlorofluoromethane(Freon 12)	75-71-8	--	7.2	*	36.19	5.08E-05	0.0087	0.56466	NA

ug/m<sup>3</sup>: Micrograms per cubic meter

ppb: parts per billion

\*: Analyte concentration below detection limit, detection limit was used in calculations

lb/hr: pounds per hour

--: No SGC listed for compound

NA: Not applicable

**Notes:**

1. DAR-1 refers to DAR-1 AGC/SGC Tables dated December 22, 2003.
2. SGC refers to the Short-Term Guideline Concentration as determined using the hand calculations in the DAR-1 AGC/SGC Tables dated December 22, 2003.
3. To be conservative the lower detection limit was used for compounds that were below the limit of detection, but are found in the influent groundwater of the Groundwater Remediation System.

# ARCADIS

Table B-3. NYSDEC DAR-1 Air Modeling Data, Operational Year 4, Quarter Number 3, Colesville Landfill, Broome County, New York.

Page 3 of 3

## Calculation of AGC based on 7/28/2006 Sampling Event

Compounds	CAS Numbers	Maximum Limit on C <sub>a</sub> (AGC <sup>4</sup> ) ug/m <sup>3</sup>	Maximum Mass Flow Q <sub>a</sub> lb/yr	Lab Data ppb	Detection Limit Used <sup>5</sup>	Actual Emissions C <sub>a</sub> ug/m <sup>3</sup>	Actual Mass Flow per Hour lb/hr	Actual Mass Flow per Year lb/yr	Percent of Annual %
Vinyl Chloride	75-01-4	0.11	10.76	7.2	*	18.71	2.28E-05	0.19935	1.85
Chloroethane(Ethyl Chloride)	75-00-3	10,000	978,044.97	7.2	*	19.31	2.35E-05	0.20579	0.00
1,1-Dichloroethene(Vinylidene Chloride)	75-35-4	70	6,846.31	7.2	*	29.02	3.54E-05	0.30922	0.00
Methylene Chloride(Dichloromethane)	75-09-2	2.1	205.39	7.2	*	25.42	3.10E-05	0.27092	0.13
1,1-Dichloroethane	75-34-3	0.63	61.62	7.2	*	29.62	3.61E-05	0.31567	0.51
cis-1,2-Dichloroethylene	156-59-2	1,900	185,828.54	7.2	*	29.02	3.54E-05	0.30922	0.00
1,1,1-Trichloroethane(Methyl Chloroform)	71-55-6	1,000	97,804.50	7.2	*	39.93	4.87E-05	0.42555	0.00
Trichloroethene	79-01-6	0.5	48.90	7.2	*	39.33	4.79E-05	0.41910	0.86
Dichlorodifluoromethane(Freon 12)	75-71-8	12,000	1,173,653.96	7.2	*	17.99	2.19E-05	0.19169	0.00

fps: feet per second

acfm: actual cubic feet per minute

ug/m<sup>3</sup>: micrograms per cubic meter

lb/yr: pounds per year

lb/hr: pounds per hour

ppb: parts per billion

## Notes/Assumptions:

1. The stack discharge temperature is 67°F based on recorded parameters.
2. The ambient temperature is approximately 81°F based on recorded conditions.
3. Calculations assume that the system will run with the maximum allowable concentrations between quarterly readings.
4. AGC refers to the Annual Guideline Concentration as determined using the hand calculations in the DAR-1 AGC/SGC Tables dated December 22, 2003.
5. To be conservative the lower detection limit was used for compounds that were below the limit of detection, but are found in the influent groundwater of the Groundwater Remediation System.

ARCADIS

## Appendix C

Automated Reagent Injection System  
Operating Parameters

## ARCADIS

Table C-1. Automated Reagent Injection System Summary of Operational Year 4, Quarter Number 3 Injection Quantities,  
Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Page 1 of 1

### NO INJECTIONS COMPLETED DURING REPORTING PERIOD