



Infrastructure, environment, facilities

Mr. George Jacob
United States Environmental Protection Agency – Region 2
290 Broadway, 20th Floor
New York, New York 10007-1866

Subject:
Operational Year 5 Annual Monitoring Report,
Colesville Landfill, Broome County, New York. (Site No. 704010).

Dear Mr. Jacob:

On behalf of Broome County, ARCADIS is providing the Operational Year 5 Annual Monitoring Report for the Colesville Landfill, Broome County, New York.

Please feel free to contact me if you have any questions or comments.

Sincerely,

ARCADIS

Steven M. Feldman
Project Manager

Copies:

Payson Long, NYSDEC
David Donoghue, Broome County
Julia Guastella, NYSDOH
File

ARCADIS
Two Huntington Quadrangle
Suite 1S10
Melville
New York 11747
Tel 631 249 7600
Fax 631 249 7610
www.arcadis-us.com

ENVIRONMENT


Date:
June 12, 2008

Contact:
Steven M. Feldman

Phone:
(631) 391-5244

Email:
sfeldman@arcadis-us.com

Our ref:
NY000949.0020.00004




Imagine the result

G:\PROJECT\BROOME\NY00949.020\Reports\Yr5Q4 Report_covlet.doc



Infrastructure, environment, facilities

Imagine the result




**Broome County Division of Solid
Waste Management**

**Operational Year 5
Annual Monitoring Report**


Colesville Landfill, Broome County, New York
NYSDEC Site 704010

June 12, 2008


ARCADIS



Kenneth Zegel, P.E.
Senior Engineer



Steven M. Feldman
Project Director



Christina Berardi Tuohy, P.E.
Vice President
License Number 078743-1, New York

**Operational Year 5
Annual Monitoring Report**
Colesville Landfill,
Broome County, New York
NYSDEC Site 704010

Prepared for:
Broome County Division of Solid Waste
Management

Prepared by:
ARCADIS of New York, Inc.
Two Huntington Quadrangle
Suite 1S10
Melville
New York 11747
Tel 631.249.7600
Fax 631.249.7610

Our Ref.:
NY000949.0021.00004

Date:
June 12, 2008

*This document is intended only for the use
of the individual or entity for which it was
prepared and may contain information that
is privileged, confidential and exempt from
disclosure under applicable law. Any
dissemination, distribution or copying of
this document is strictly prohibited.*

1. Introduction	1
2. Methodology	1
2.1 Environmental Effectiveness Monitoring	2
2.2 Groundwater Remediation System Performance Monitoring	2
2.3 Spring Water Remediation System Performance Monitoring	3
3. Groundwater Flow	3
4. Groundwater Quality	4
4.1 Volatile Organic Compounds	4
4.2 Indicators of Reducing Conditions	5
4.3 Evidence of Biodegradation	5
5. Spring Water Quality	6
6. Surface Water Quality	6
7. Status of Flood Related Damages	6
8. Groundwater Remediation System Performance	6
8.1 PT System	6
8.1.1 Summary of Operation, Maintenance, and Monitoring	7
8.1.2 Results of Performance Sampling	7
8.2 ARI System	9
8.2.1 Summary of Operation, Maintenance, and Monitoring	9
8.2.2 Results of Performance Sampling	9
9. Spring Water Remediation System Performance	11
10. Conclusions	11
11. Recommendations	12

12. Project Schedule	12
13. References	13

Tables

Table 1	Water-Level Measurements Collected During Operational Year 5, Colesville Landfill, Broome County, New York.
Table 2	Concentrations of Volatile Organic Compounds Detected in Groundwater, Operational Year 5, Colesville Landfill, Broome County, New York.
Table 3	Concentrations of General Chemistry, Field Parameters, and Dissolved Gases Detected in Groundwater, Operational Year 5, Colesville Landfill, Broome County, New York.
Table 4	Concentrations of Volatile Organic Compounds and Selected Metals Detected in Aqueous Samples Collected from the PT System, Operational Year 5, Colesville Landfill, Broome County, New York.
Table 5	Concentrations of Volatile Organic Compounds Detected in Surface Water, Operational Year 5, Colesville Landfill, Broome County, New York.
Table 6	PT System Operating Parameters, Operational Year 5, Quarter Number 4 and Annual Summary, Groundwater Remediation System, Colesville Landfill, Broome County, New York.
Table 7	PT System Mass Removal Rate of Volatile Organic Compounds, Operational Year 5, Quarter Number 4 and Annual Summary, Groundwater Remediation System, Colesville Landfill, Broome County, New York.
Table 8	Concentrations of Volatile Organic Compounds Detected in Air Stripper Effluent, Operational Year 5, Quarter Number 4 and Annual Summary, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Figures

Figure 1	Site Plan Showing Water- Level Elevations on September 19, 2007.
Figure 2	As-Built Survey of the Former SP-4 Spring Area.
Figure 3	As-Built Survey of the SP-5 Spring Area.

Appendices

- A Groundwater Sampling Logs
- B New York State Department of Environmental Conservation DAR-1 Air Modeling Data
- C Automated Reagent Injection System Operating Parameters
- D Degradation Trend Figures

1. Introduction

This Operational Year 5, Quarter Number 4 Annual Monitoring Report (Report) was prepared on behalf of the Broome County Division of Solid Waste Management for the Colesville Landfill, located in Broome County, New York (site) to evaluate and document long-term monitoring (LTM) activities at the site. Remediation and monitoring activities are being conducted pursuant to the Record of Decision (ROD) and Explanation of Significant Difference (ESD) that were issued in March 1991 and September 2000, respectively. LTM activities (which include environmental effectiveness and remediation system performance monitoring) were performed in accordance with the LTM Plan (ARCADIS G&M, Inc. 2002), LTM Plan Addendum for Spring Water Remediation Systems (ARCADIS 2003), and Interim Remedial Action Report (ARCADIS 2004), which were approved by the United States Environmental Protection Agency (USEPA) and New York State Department of Environmental Conservation (NYSDEC). These documents provide a detailed description of the LTM program, methodology, and rationale. Where applicable these elements are either summarized or incorporated by reference herein.

This report provides the data collected from the September 2007 water-level measurement round and the groundwater quality monitoring event conducted during Operational Year 5, Quarter Number 4 (annual monitoring event). A description of the operation, maintenance, and monitoring (OM&M) associated with the Groundwater Remediation System during Operational Year 5, Quarter Number 4 has also been provided. Included in the analysis of the results is a summary and discussion of all data collected during Operational Year 5 (September 2006 through September 2007). Following the detailed data analysis and discussion is a summary of findings, conclusions, and recommendations.

As referenced in previous monitoring reports (ARCADIS 2007), damage occurred at the former SP-4 spring area and at recovery well GMPW-5 as a result of flooding of the North Stream. Further discussion of the repair of the flood damage is provided herein when applicable to the LTM program and/or OM&M of the Groundwater Remediation System.

2. Methodology

The following section provides a summary of the environmental effectiveness and remedial system performance monitoring methodology for Operational Year 5, Quarter

Number 4. A site plan, which shows the location of environmental effectiveness monitoring, is provided on Figure 1.

2.1 Environmental Effectiveness Monitoring

The environmental effectiveness monitoring performed during Operational Year 5, Quarter Number 4, included the following:

- Water-level (hydraulic) measurements were collected from 25 monitoring wells on September 19, 2007.
- Groundwater samples were collected from 17 monitoring wells (Year 5, Q4 list of wells) during the week of September 18, 2007 and were selectively analyzed for volatile organic compounds (VOCs), dissolved gases, and total organic carbon (TOC). Field parameters were also recorded at these monitoring locations.
- Samples (VOCs only) were collected at the SP-4 and F-6 surface water locations on September 20, 2007.

In accordance with the Proposed Modifications to the Long-Term Monitoring (LTM) Program (ARCADIS 2005), groundwater samples were collected from monitoring wells utilizing passive diffusive bag (PDB) samplers.

The depth to groundwater in monitoring wells was measured using methods consistent with those described in the LTM Program.

2.2 Groundwater Remediation System Performance Monitoring

Groundwater Remediation System performance monitoring activities during Operational Year 5, Quarter Number 4 were as follows:

- Pump-and-treat (PT) system recovery well influent and effluent samples were collected on September 19 and 20, 2007. The samples were selectively analyzed for VOCs and total iron.
- One vapor sample from the PT system air stripper effluent was collected on September 27, 2007. The sample was analyzed for VOCs.

- PT system operating parameters were recorded during the quarterly OM&M site visit.
- TOC samples were collected from select injection wells during the week of September 18, 2007.
- Automated reagent injection (ARI) system operating parameters were recorded during each injection event.
- A TOC sample was collected from alternate electron donor monitoring well TW-1 on September 18, 2007.

PT system groundwater samples were collected as grab samples directly from the individual recovery pipelines connected to recovery wells GMPW-3, GMPW-4, GMPW-5, the combined influent water to the low profile air stripper, and the combined effluent after the cartridge filters. The effluent air sample was collected as a grab sample directly from the designated point located on the low profile air stripper stack.

2.3 Spring Water Remediation System Performance Monitoring

SP-5 Spring Water Remediation System performance monitoring could not be conducted during the current reporting period due to a lack of flow at the SP-5 spring area. It is believed that the lack of flow is a direct result of an overall lower seasonal groundwater elevation at the site. Further discussion is provided in Section 9.0 of this report.

3. Groundwater Flow

Water-level measurements were made from existing wells on September 19, 2007. Water-level elevation data for Operational Year 5, Quarter Number 4 is provided in Table 1. A summary of water-level elevation data for Operational Year 5 is included in this table. Water-level elevations and the groundwater flow direction for the September 2007 monitoring event are shown on Figure 1. As shown on Figure 1, the groundwater flow direction in the project area (i.e., adjacent to the landfill western perimeter) and site-wide in the Operational Year 5, Quarter Number 4 round was consistent with previous rounds. The groundwater flow direction in the project area is toward the southwest from the western perimeter of the landfill. The groundwater flow direction in areas further to the east of the project area is toward the south/southwest.

Water-level elevation data for Operational Year 5 was similar to prior rounds of data. Seasonal fluctuations are observed during each operating quarter; however, the data generally indicate groundwater flow directions consistent with that observed during the Operational Year 4, Quarter Number 4 monitoring event.

4. Groundwater Quality

The following sections describe the analytical results for groundwater samples collected during the September 2007 monitoring round (Operational Year 5, Quarter Number 4). A discussion of analytical results for all data collected during Operational Year 5 is also provided. Groundwater analytical data for Operational Year 5, Quarter Number 4 is provided in Tables 2 and 3. A summary of all analytical data collected during Operational Year 5 is also provided on the referenced tables.

4.1 Volatile Organic Compounds

A comparison of Operational Year 5, Quarter Number 4 groundwater analytical results with previous analytical data indicate that the dissolved phase plume continues to be stable and that the anaerobic in-situ reactive zone (IRZ) is completely degrading contaminant mass. Specifically, total VOC (TVOC) concentrations for plume boundary, landfill interior, and landfill perimeter monitoring wells were stable to decreasing. TVOC concentrations for mid-plume monitoring wells generally decreased. Specific observations are provided below.

Plume boundary, landfill interior, and landfill perimeter monitoring data indicate that the dissolved phase plume is stable to decreasing in size. Total VOC (TVOC) concentrations for plume boundary monitoring wells W-17S and W-18 remained stable at 0.0 micrograms per liter (ug/L) and 75.2 ug/L, respectively. Offsite monitoring well W-20S remained stable at 0.0 ug/L. Landfill perimeter monitoring wells W-6, W-7, and W-13 slightly increased or remained stable at 65.0 ug/L, 11.5 ug/L, and 0.0 ug/L, respectively. Landfill perimeter monitoring well PW-7 significantly decreased from 532.5 ug/L in September 2006 to 190.8 ug/L. Landfill interior monitoring well PW-13 generally remained stable at 31.5 ug/L. Landfill interior monitoring well GMMW-7 increased from 258.8 ug/L in September 2006 to 370.8 ug/L in September 2007.

In general, TVOC concentrations in mid-plume monitoring wells located furthest from the IRZ were stable during the current reporting period. Specifically, mid-plume monitoring wells W-16S and PW-4 remained stable at 54.0 ug/L and 67.4 ug/L, respectively. TVOC concentrations in mid-plume monitoring well PW-3 increased from

86.1 ug/L in September 2006 to 163.4 ug/L in September 2007. TVOC concentrations in mid-plume monitoring wells located closest to the IRZ (GMMW-5, GMMW-6, W-5 and GMMW-2) were generally stable during September 2007 at 85.5 ug/L, 403.3 ug/L, 211.1 ug/L and 316.5 ug/L, respectively; mid-plume monitoring well PW-5 remained stable at 0.0 ug/L.

A comparative analysis of groundwater analytical data for VOCs during Operational Year 5 continues to corroborate historical data and indicate that the dissolved phase plume is stable to decreasing. The overall stable plume provides continued evidence that ongoing natural attenuation processes are effectively controlling the further migration of the plume. Data also indicate that the IRZ is completely degrading mass as observed by a continuing decreasing trend of VOCs in monitoring wells GMMW-5, GMMW-6, W-5 and to a lesser extent GMMW-2.

PT system VOC analytical results are provided in Table 4. During the current reporting period, TVOC concentration at recovery wells GMPW-3 and GMPW-4 were stable when compared to prior data. Specifically, TVOC concentrations in recovery wells GMPW-3, GMPW-4, and GMPW-5 were 179.8 ug/L, 245.2 ug/L, and 16.9 ug/L, respectively. A complete evaluation of performance monitoring conducted on the PT system is provided in Section 8.1.2 of this report.

4.2 Indicators of Reducing Conditions

Groundwater analytical results for biogeochemical parameters and field parameters were collected in accordance with the LTM plan and are provided in Table 3. In summary, field and laboratory groundwater data for Wells GMMW-5 and GMMW-6 indicate that strongly reducing conditions are being maintained within the IRZ. This is evidenced by the presence of reduced forms of alternate electron acceptors (i.e., methane). Further details of the ARI system performance monitoring are provided in Section 8.2.2 of this report.

4.3 Evidence of Biodegradation

Table 3 provides the results of biodegradation end product concentrations in monitoring wells and indicates the continued occurrence of bioactivity and biodegradation of VOCs within the IRZ. Specifically, the concentration of ethane and/or ethene within monitoring wells GMMW-5 and GMMW-6 continue to be elevated when compared to baseline conditions. GMMW-5 is located closest to the ARI injection wells and would be expected to be the first well to exhibit increases in

biodegradation end products. Ethene results for monitoring well GMMW-6 remained elevated during Operational Year 5, Quarter Number 4 and continue to indicate that the IRZ has extended to the vicinity of this well. Additional details on the results of biogeochemical monitoring as evidence of Groundwater Remediation System performance and effectiveness are discussed in Section 8.2.2 of this report.

5. Spring Water Quality

Spring water locations SP-2 and SP-3 were observed during the OM&M site visit on September 20, 2007. Spring water samples were not collected due to lack of flow at SP-2, and only a minimal puddle of stagnant water in a low-lying area at SP-3.

6. Surface Water Quality

Table 5 presents the analytical results for surface water sampling location F-6 and SP-4 during Operational Year 5. As shown in Table 5, surface water quality remained stable during the reporting period. Similarly, surface water quality remained stable during Operational Year 5 with VOC concentrations either not detected or slightly above the limits of detection. The data continue to indicate that surface water is not being adversely impacted by the dissolved phase groundwater plume or the former SP-4 spring water location.

7. Status of Flood Related Damages

As referenced in the Operational Year 5, Quarter Number 3, monitoring report, maintenance of the former SP-4 spring area was completed. Accordingly, ARCADIS completed an as-built survey of the Former SP-4 spring area improvement. The as-built survey of the SP-4 area provided in Figure 2.

8. Groundwater Remediation System Performance

The following section describes the results of the Groundwater Remediation System performance monitoring conducted during Operational Year 5, Quarter Number 4. A brief summary of system performance during Operational Year 5 is also provided.

8.1 PT System

The following section describes the results of the PT system performance monitoring conducted during Operational Year 5, Quarter Number 4.

8.1.1 Summary of Operation, Maintenance, and Monitoring

During Operational Year 5, Quarter Number 4, the PT system operated continuously with the exception of brief system shutdowns as a result of minor system alarms and routine OM&M activities.

PT system OM&M for Operational Year 5, Quarter Number 4 was conducted during the week of September 18, 2007 and included operation and maintenance of system equipment, the collection of system performance samples (water and vapor), and recording system operating parameters. Table 6 provides a summary of the recorded system operating parameters for the current operating period. As shown in Table 6, the total effluent groundwater recovery rate for Operational Year 5, Quarter Number 4 was approximately 0.30-gallon per minute (gpm), with individual recovery rates of 0.06-gpm, 0.17-gpm, and 0.03-gpm in GMPW-3, GMPW-4, and GMPW-5, respectively. The average recovery rates in recovery wells GMPW-3 and GMPW-5 were below system startup data. The average individual recovery well rate during Operational Year 5, Quarter Number 4 in recovery well GMPW-4 was consistent with system start up data.

A total of 40,444 gallons of groundwater was recovered during Operational Year 5, Quarter Number 4, and a total of 1,324,522 gallons of groundwater has been recovered since system startup. The low profile air stripper operated in accordance with the design specifications had a blower flow rate of 208 standard cubic feet per minute (scfm).

The overall system pumping rate during Operational Year 5 was higher when compared to previous operation (e.g. Operational Year 4) due to replacement of the recovery well pump in GMPW-3. Similar to the current reporting period, the PT system operated continuously during Operational Year 5 with minor system shutdown for system maintenance. As shown in Table 6, the total effluent groundwater recovery rate for Operational Year 5 was approximately 0.53-gpm, with individual recovery rates of 0.27-gpm, 0.20-gpm, and 0.07-gpm for recovery wells GMPW-3, GMPW-4, and GMPW-5, respectively. A total of 272,187 gallons of groundwater was recovered during Operational Year 5.

8.1.2 Results of Performance Sampling

PT system performance sampling for Operational Year 5, Quarter Number 4 was conducted on September 20, 2007. As discussed previously, five groundwater

samples and one vapor sample were collected. Groundwater samples included collection of individual recovery well samples (GMPW-3, GMPW-4, and GMPW-5), total influent, and total effluent after the cartridge filters. The vapor sample was collected from the effluent stack of the low profile air stripper.

Table 4 provides a summary of the PT system performance groundwater sampling analytical results. As shown in Table 4, all groundwater VOCs were treated to below their respective Best Professional Judgment (BPJ) limits via the low profile air stripper. Total iron concentration after the cartridge filter was 1.94 mg/L for the fourth quarter sampling event, which is above the BPJ recommended daily average limit of 0.61 mg/L and recommended daily limit of 1.2 mg/L. The cartridge filters were replaced shortly after the quarterly sampling event. Based on the total groundwater recovered during the reporting period and total influent groundwater concentration, an estimated 0.05 pounds (lbs) of VOC mass were removed from the subsurface during the quarterly reporting period, as shown in Table 7. A total of approximately 2.59 lbs of VOCs have been removed from the subsurface since system startup. A total of approximately 0.56 lbs of mass were recovered during Operational Year 5.

Table 8 provides a summary of the PT system performance sampling vapor analytical results for the Operational Year 5, Quarter Number 4 monitoring event as well as a summary of all data for Operational Year 4. As shown in Table 8, VOCs were not detected above their respective detection limits during the current reporting period. To be conservative, NYSDEC DAR-1 air model calculations were performed using the actual analytical data for detected constituents and the detection limit of all constituents that were not detected but have historically been detected in the influent groundwater. All COCs were below their respective short-term guidance concentrations (SGCs) and annual guidance concentrations (AGCs). Appendix B contains the NYSDEC DAR-1 AGC screening simulation based on the hand calculations provided in the NYSDEC DAR-1 AGC/SGC tables dated December 22, 2003.

As shown in Table 4, the PT system operated effectively during Operational Year 5 and treated influent VOCs to below their respective BPJ limits during each operational period. As shown in Table 7, a total of approximately 0.56 lbs of VOC mass were recovered during Operational Year 5. An annual summary of NYSDEC DAR-1 screening simulations has been provided in Table B-2 of Appendix B, all COCs were below their respective SGCs and AGCs during each operating period of Operational Year 5.

8.2 ARI System

The following section describes the results of the ARI system performance monitoring conducted during Operational Year 5, Quarter Number 4. A brief summary of ARI system performance for Operational Year 5 has also been provided.

8.2.1 Summary of Operation, Maintenance, and Monitoring

ARI system OM&M was conducted during the Operational Year 5, Quarter Number 4 OM&M site visit during the week of September 18, 2007 and included operation and maintenance of system equipment and the collection of samples for analysis of TOC from injection wells IW-2, IW-3, IW-8, and IW-13. In addition, a TOC sample was collected from monitoring well TW-1 to evaluate the long-term performance of the alternate electron donor in providing TOC to the subsurface.

One reagent injection was conducted during Operational Year 5, Quarter Number 4. The injection was initiated on June 20, 2007 and was completed on July 12, 2007. As described in the Hydraulic Injection Test and Alternate Electron Donor Pilot Test Letter Work Plan (ARCADIS 2006), an alternate electron donor (e.g., emulsified edible oil [EOS]) was injected into existing injection well IW-8 during the week of December 18, 2006. Accordingly, IW-8 was not included in the current reagent injection to allow for long-term groundwater monitoring of the alternate electron donor.

Based on the number of injection events, quantity of molasses solution delivered to each injection well, and molasses solution percentage, approximately 13,705-gallons of molasses solution were delivered to the subsurface during Operational Year 5, Quarter Number 4. A total of 130,931-gallons of molasses solution have been injected since system startup. Appendix C provides a summary of the recorded system operating parameters for each of the injection events for Operational Year 5, Quarter Number 4.

8.2.2 Results of Performance Sampling

ARI system performance sampling was conducted on September 18, 2007 and included the collection of TOC samples from injection wells IW-2, IW-3, IW-8, and IW-13. In addition to performance sampling conducted explicitly for ARI system monitoring, analytical results from select wells sampled under the environmental effectiveness monitoring program were also utilized to determine the effectiveness of the ARI system.

As discussed previously, Tables 2 and 3 summarize the results of VOCs, and biogeochemical and field parameters, respectively, for the ARI system performance monitoring and environmental effectiveness Operational Year 5, Quarter Number 4 sampling event. Analytical results and field parameters indicate that geochemical conditions in the current area of ARI system influence exhibit sufficient TOC within injection wells, elevated chlorinated VOC (CVOC) degradation products (i.e., ethene and ethane), and elevated reduced forms of alternate electron acceptors (i.e., methane). Operational Year 5, Quarter Number 4 analytical data provide strong evidence that VOCs are being completely degraded within the IRZ along the downgradient flow path.

Key observations for Operational Year 5, Quarter Number 4, are as follows:

- The TOC concentration at monitoring well GMMW-5 (84 mg/L) and injection wells IW-3 (230 mg/L), IW-8 (1,600 mg/L), and IW-13 (34 mg/L) indicated that sufficient organic carbon is being delivered to the subsurface to maintain the IRZ.
- The TOC in monitoring well TW-1 was 120 mg/L. The data indicate that the alternate electron donor EOS continues to provide sufficient organic carbon to the subsurface following the one time injection in injection well IW-8.
- The methane concentration in monitoring wells GMMW-5 and GMMW-6 remained elevated at 24,000 ug/L and 1,700 ug/L, respectively. These data provide evidence that strongly reducing conditions (methanogenic) are being maintained within the IRZ.
- The ethene concentration in monitoring well GMMW-6 remained elevated at 73,000 ng/L. The concentration in monitoring well GMMW-6 remained an order of magnitude above baseline conditions during the operational year.
- The ethane concentration remained elevated in monitoring wells GMMW-5 and GMMW-6 at 14,000 and 5,200 ng/L, respectively.
- TVOC concentrations remained stable but significantly lower than baseline conditions in monitoring wells GMMW-5 and GMMW-6.

Figures D-1, D-2, D-3, and D-4 (see Appendix D) presents a summary of groundwater data for PCE and PCE related daughter compounds in monitoring wells GMMW-05,

GMMW-06, GMMW-02, and W-05 since the baseline monitoring event conducted in July 2002. As shown on Figures D-1 through D-4, the decline in contaminant mass (primarily 1,2-DCE) corresponds to a significant increase in methane and degradation end product (ethene/ethane). This trend is typical for successful IRZs.

9. Spring Water Remediation System Performance

In an effort to address the additional springs that were noted during the 5-year review inspection, SP-5 modifications were implemented during April and July, 2007. The riprap and filter fabric were removed and replaced, the spring water infiltration area was expanded and the ground elevation was raised, and an additional ring was added to the SP-5 manhole. An as built of the modified SP-5 Spring area is provided on Figure 3.

SP-5 Spring Water Remediation System OM&M could not be conducted during Operational Year 5, Quarter Number 4 due to a lack of water-flow from the system effluent discharge pipe. It is believed that the lack of flow is a direct result of the overall lower ground water table elevation observed at the site during the September 2007 water-level gauging event.

10. Conclusions

Based on the data obtained from the Operational Year 5, Quarter Number 4 monitoring and overall system performance during Operational Year 5, ARCADIS concluded the following:

- The groundwater flow direction in the project area (i.e., adjacent to the landfill western perimeter) and site-wide in the September 2007 round was consistent with previous rounds. The groundwater flow direction in the project area is toward the southwest from the western perimeter of the landfill. The groundwater flow direction in areas further to the east of the project area is toward the south/southwest.
- The anaerobic IRZ established downgradient of the injection transect is successfully reducing the concentration of site-related VOCs through enhanced reductive dechlorination. TVOC analytical results in monitoring wells GMMW-5 and GMMW-6 continued to decrease significantly during the operational year while the concentration of methane and ethane/ethane remained elevated.

- Site-wide groundwater analytical data for VOCs is consistent with site historical data and indicate that the dissolved phase plume is stable. This observation provides continued evidence that ongoing natural attenuation processes are effectively controlling the further migration of the plume in areas beyond the present-day influence of the IRZ.
- The PT system is operating as designed and is treating recovered groundwater VOCs to below BPJ limits prior to discharge.
- Sufficient organic carbon was delivered to the subsurface to maintain the IRZ as evidenced through the analytical data.
- Surface water quality continues to be consistent with historical data indicating that impacted groundwater and/or flood related damages are not causing an adverse impact to surface water along the North Stream.

11. Recommendations

The following recommendations are made for Operational Year 6, Quarter Number 1 activities:

- Continue to inspect the former spring locations and the side slopes of the north stream.
- Continue to operate the ARI system without injection well IW-8. Obtain and evaluate data related to the ongoing alternate electron donor pilot program.
- Continue to evaluate the performance of recovery well GMPW-5 to determine the cause of the decrease in groundwater recovery.

12. Project Schedule

Groundwater environmental effectiveness monitoring is scheduled to be conducted for Operational Year 5 on the quarterly schedule set forth in the Proposed Modifications to Long-Term Monitoring Program (ARCADIS 2005). System OM&M of the Groundwater Remediation System will continue to be performed on a quarterly basis consistent with the LTM Plan. Maintenance of the SP-5 spring water remediation system will be completed. 13.

ARCADIS

Operational Year 5 Annual Monitoring Report

Colesville Landfill
Broome County, New York
NYSDEC Site 704010

13. References

ARCADIS G&M, Inc. 2002. Long-Term Monitoring Plan, Colesville Landfill, Broome County, New York, NYSDEC Site 704010. June 28, 2002.

ARCADIS G&M, Inc. 2003. Long-Term Monitoring Plan Addendum for Spring Water Remediation Systems, Colesville Landfill, Broome County, New York, NYSDEC Site 704010. November 3, 2003.

ARCADIS G&M, Inc. 2004. Interim Remedial Action Report, Colesville Landfill, Broome County, New York, NYSDEC Site 704010. September 22, 2004.

ARCADIS G&M, Inc. 2005 Proposed Modifications to Long-Term Monitoring Program, Broome County, New York, NYSDEC Site 704010. June 28, 2005.

ARCADIS G&M, Inc. 2006 Operational Year 3 Annual Monitoring Report, Broome County, New York, NYSDEC Site 704010. March 2, 2006.

ARCADIS G&M, Inc. 2006. Hydraulic Injection Test and Alternate Electron Donor Pilot Test, Colesville Landfill, Broome County, New York (Site No. 704010). November 30, 2006.

ARCADIS of New York, Inc. 2007. Operational Year 5, Quarter Number 1 Monitoring Report, Colesville Landfill, Broome County, New York (Site No. 704010). July 26, 2007

ARCADIS

Table 1. Water-Level Measurements Collected During Operational Year 5, Colesville Landfill, Broome County, New York.

Well Identification	MP Elevation (feet above msl)	3/26/2007 Depth to Water (feet below MP)	3/26/2007 Water-Table Elevation (feet above msl)	9/19/2007 Depth to Water (feet below MP)	9/19/2007 Water-Table Elevation (feet above msl)	MP Description
GMMW-2	1030.95	35.50	995.45	36.32	994.63	Inner casing
GMMW-3	1028.02	33.33	994.69	34.30	993.72	Inner casing
GMMW-4	1042.9	45.75	997.15	46.19	996.71	Inner casing
GMMW-5	1043.66	48.20	995.46	49.04	994.62	Inner casing
GMMW-6	1033.56	37.65	995.91	38.59	994.97	Inner casing
GMMW-7	1045.43	46.93	998.50	47.63	997.80	Inner casing
PW-1	976.23	NM	--	15.13	961.10	Inner casing
PW-2	975.28	NM	--	6.93	968.35	Inner casing
PW-3	988.92	9.45	979.47	13.67	975.25	Inner casing
PW-4	1001.75	16.02	985.73	18.14	983.61	Inner casing
PW-5	986.12	0	986.12	0.60	985.52	Inner casing
W-5	1051.41	51.00	1000.41	51.60	999.81	Inner casing
W-6	1050.38	48.24	1002.14	49.95	1000.43	Inner casing
PW-7	1042.47	38.99	1003.48	39.72	1002.75	Inner casing
PW-8	1049.73	NM	--	39.75	1009.98	Inner casing
W-7	1049.12	40.74	1008.38	43.20	1005.92	Inner casing
PW-10	1049.29	36.42	1012.87	39.00	1010.29	Inner casing
PW-11	1052.37	51.29	1001.08	52.15	1000.22	Inner casing
PW-13	1072.41	60.16	1012.25	61.45	1010.96	Inner casing
W-13	1053.43	45.61	1007.82	47.65	1005.78	Inner casing
W-14S	957.68	NM	--	10.35	947.33	Inner casing
W-16S	990.33	NM	--	9.76	980.57	Outer casing
W-17S	959.13	8.04	951.09	11.81	947.32	Inner casing
W-18	973.56	9.45	964.11	11.68	961.88	Inner casing
W-20S	952.88	7.05	945.83	11.54	941.34	Inner casing

msl Mean sea level.
 MP Measuring point.
 NM Not measured.
 -- Water Level not Recorded

ARCADIS

Table 2. Concentrations of Volatile Organic Compounds Detected in Groundwater, Operational Year 5, Colesville Landfill, Broome County, New York.

Constituents (units in ug/L)	Sample ID: Date:	GMMW-02 12/8/2006	GMMW-02 3/26/2007	GMMW-02 6/19/2007	GMMW-02 9/18/2007	GMMW-05 12/7/2006	GMMW-5 3/26/2007	GMMW-05 6/19/2007	GMMW-05 9/18/2007	GMMW-06 12/7/2006	GMMW-06 3/26/2007
1,1,1-Trichloroethane		14	12	9.6	9.2	<5.0	<1.0	<1.0	<1.0	3.7	5.2
1,1,2-Trichloroethane		<1.0	<1.0	<1.0	<1.0	<5.0	<1.0	<1.0	<1.0	1.2	1.4
1,1-Dichloroethane		76	78	79	91	23	32	<1.0	16	200	170
1,1-Dichloroethene		1.3	1.3	1.3	<1.0	<5.0	<1.0	<1.0	<1.0	<1.0	<1.0
1,2-Dichloroethane		<1.0	<1.0	<1.0	<1.1	<5.0	2.1	<1.0	1	1.9	<1.0
1,2-Dichloropropane		<1.0	<1.0	<1.0	<1.0	<5.0	<1.0	<1.0	<1.0	1.2	1.2
Benzene		2.7	2.5	2.4	1.3	<5.0	1.6	<1.0	<1.0	9.8	7.7
Chlorobenzene		32	32	31	31	21	26	<1.0	20	46	38
Chloroethane		23	24	29	26	150	120	<1.0	41	190	180
Chloroform		<1.0	<1.0	<1.0	<1.0	<5.0	<1.0	<1.0	<1.0	<1.0	1.3
dis-1,2-Dichloroethene		110	110	98	100	<5.0	2.7	<1.0	1.7	30	54
Dichlorodifluoromethane		<1.0	<1.0	<1.0	<1.0	<5.0	<1.0	<1.0	<1.0	5.1	5.1
Ethylbenzene		<1.0	<1.0	<1.0	<1.0	<5.0	<1.0	<1.0	<1.0	2.4	1.6
Methylene chloride		<1.0	<1.0	1.3	<1.0	<5.0	1.7	<1.0	<1.0	7.6	6.1
Methyl tert-butyl ether		<1.0	<1.0	<1.0	<1.0	<5.0	<1.0	<1.0	<1.0	<1.0	<1.0
Naphthalene		<1.0	<1.0	<1.0	<1.0	<5.0	<1.0	<1.0	<1.0	<1.0	<1.0
o-Xylene		<1.0	<1.0	<1.0	<2.0	<5.0	3	<1.0	2.5	3.1	1.4
Tetrachloroethene		<1.0	<1.0	<1.0	<1.0	<5.0	<1.0	<1.0	<1.0	<1.0	<1.0
Toluene		<1.0	<1.0	<1.0	<1.0	<5.0	5.3	<1.0	3.3	3.3	2
trans-1,2-Dichloroethene		<1.0	<1.0	<1.0	<1.0	<5.0	<1.0	<1.0	<1.0	1.9	1.5
Trichloroethene		52	49	43	40	<5.0	<1.0	<1.0	<1.0	2	8.5
Vinyl chloride		13	15	18	18	<5.0	1.8	<1.0	<1.0	21	31
p-Xylene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Carbon Tetrachloride		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Total VOCs		324.0	323.8	312.6	316.5	194.0	196.2	0.0	85.5	530.2	516.0

Bold Constituent detected above MDL.

VOCs Volatile Organic Compounds.

ug/L Micrograms per liter.

* Field replicate.

J Estimated value.

MDL Method detection limit.

NA Not analyzed.

ARCADIS

Table 2. Concentrations of Volatile Organic Compounds Detected in Groundwater, Operational Year 5, Colesville Landfill, Broome County, New York.

Constituents (units in ug/L)	Sample ID: Date:	GMMW-06 6/19/2007	GMMW-06 9/19/2007	GMMW-07 9/19/07	PW-03 9/19/07	PW-04 12/7/2006	PW-04 3/26/2007	PW-04 6/19/2007	PW-04 9/19/2007	PW-05 9/19/2007	PW-07 9/19/07
1,1,1-Trichloroethane	6.1	7.2	6.5	17	13	10	9.8	10	<1.0	<1.0	4.5
1,1,2-Trichloroethane	1.6	1.1	1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
1,1-Dichloroethane	180	150	110	47	8.8	9.3	10	11	<1.0	<1.0	92
1,1-Dichloroethene	<1.0	<1.0	1.4	1.2	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
1,2-Dichloroethane	<1.0	1.1	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
1,2-Dichloropropane	1.3	1.1	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Benzene	7.2	7.8	1.2	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Chlorobenzene	33	37	12	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	11
Chloroethane	150	120	34	7.1	3.8	3	4.6	3.8	<1.0	<1.0	40
Chloroform	1.1	<1.0	<1.0	1.1	1.2	1.0	1.0	1.0	<1.0	<1.0	<1.0
cis-1,2-Dichloroethene	45	36	130	50	14	9.2	11	12	<1.0	<1.0	20
Dichlorodifluoromethane	4.6	5.5	1.1	1.4	1.7	1.5	2.5	1.5	<1.0	<1.0	<1.0
Ethylbenzene	1.7	2.8	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Methylene chloride	4.9	5	1.6	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Methyl tert-butyl ether	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Naphthalene	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
o-Xylene	1.7	2.7	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Tetrachloroethene	<1.0	<1.0	<1.0	3.4	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Toluene	1.9	2.5	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
trans-1,2-Dichloroethene	1.4	1.8	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Trichloroethene	9.6	4.5	37	32	24	24	21	22	<1.0	<1.0	9.3
Vinyl chloride	29	17	35	3.2	<1.0	<1.0	1.1	<1.0	<1.0	<1.0	14
p-Xylene	<1.0	3.6	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Carbon Tetrachloride	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	1.8	<1.0	<1.0	<1.0
Total VOCs	480.1	403.1	370.8	163.4	66.5	58.0	61.0	61.3	0.0	190.8	

Bold Constituent detected above MDL.

VOCs Volatile Organic Compounds.

ug/L Micrograms per liter.

* Field replicate.

J Estimated value.

MDL Method detection limit.

NA Not analyzed.

ARCADIS

Table 2. Concentrations of Volatile Organic Compounds Detected in Groundwater, Operational Year 5, Colesville Landfill, Broome County, New York.

Constituents (units in ug/L)	Sample ID: Date:	PW-13 9/19/07	W-05 12/8/2006	W-05 3/26/2007	W-05 6/19/2007	W-05 9/19/2007	W-06 9/18/2007	W-07 9/19/07	W-13 9/19/2007	W-16S 9/19/07	W-17S 9/19/2007	W-18 9/19/2007
1,1,1-Trichloroethane		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	18
1,1,2-Trichloroethane		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
1,1-Dichloroethane		6.9	79	66	67	66	21	3.1	<1.0	17	<1.0	17
1,1-Dichloroethene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
1,2-Dichloroethane		1.6	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
1,2-Dichloropropane		<1.0	<1.0	<1.0	1.2	<1.0	1.2	<1.0	<1.0	<1.0	<1.0	<1.0
Benzene		<1.0	6.8	5.8	6.4	6.2	3.9	<1.0	<1.0	2.2	<1.0	<1.0
Chlorobenzene		14	16	13	13	11	14	2.6	<1.0	24	<1.0	<1.0
Chloroethane		3.1	120	120	150	120	8.2	4.4	<1.0	5.6	<1.0	2.2
Chloroform		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
cis-1,2-Dichloroethene		1.9	2.7	2.8	2.4	2.4	6.0	<1.0	<1.0	1.6	<1.0	16
Dichlorodifluoromethane		<1.0	<1.0	<1.0	<1.0	<1.0	3.8	<1.0	<1.0	1.2	<1.0	<1.0
Ethylbenzene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Methylene chloride		<1.0	3	2.8	3.5	3.2	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Methyl tert-butyl ether		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Naphthalene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
o-Xylene		<1.0	<1.0	<1.0	2.6	2.3	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Tetrachloroethene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Toluene		<1.0	1.1	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
trans-1,2-Dichloroethene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Trichloroethene		2.5	1.5	1.7	<1.0	<1.0	6.9	1.4	<1.0	2.4	<1.0	22
Vinyl chloride		1.5	<1.0	1.4	1.2	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
p-Xylene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Carbon Tetrachloride		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Total VOCs		31.5	230.1	215.2	247.3	211.1	65.0	11.5	0.0	54.0	0.0	75.2

Bold Constituent detected above MDL.

VOCs Volatile Organic Compounds.

ug/L Micrograms per liter.

* Field replicate.

J Estimated value.

MDL Method detection limit.

NA Not analyzed.

ARCADIS

Table 2. Concentrations of Volatile Organic Compounds Detected in Groundwater, Operational Year 5, Colesville Landfill, Broome County, New York.

Constituents (units in ug/L)	Sample ID: Date:	W-20S 9/19/07	FBV122105 9/19/2007
1,1,1-Trichloroethane		<1.0	<1.0
1,1,2-Trichloroethane		<1.0	<1.0
1,1-Dichloroethane		<1.0	<1.0
1,1-Dichloroethene		<1.0	<1.0
1,2-Dichloroethane		<1.0	<1.0
1,2-Dichloropropane		<1.0	<1.0
Benzene		<1.0	<1.0
Chlorobenzene		<1.0	<1.0
Chloroethane		<1.0	<1.0
Chloroform		<1.0	<1.0
cis-1,2-Dichloroethene		<1.0	<1.0
Dichlorodifluoromethane		<1.0	<1.0
Ethylbenzene		<1.0	<1.0
Methylene chloride		<1.0	<1.0
Methyl tert-butyl ether		<1.0	<1.0
Naphthalene		<1.0	<1.0
o-Xylene		<1.0	<1.0
Tetrachloroethene		<1.0	<1.0
Toluene		<1.0	<1.0
trans-1,2-Dichloroethene		<1.0	<1.0
Trichloroethene		<1.0	<1.0
Vinyl chloride		<1.0	<1.0
p-Xylene		<1.0	<1.0
Carbon Tetrachloride		<1.0	<1.0
Total VOCs		0.0	0.0

Bold Constituent detected above MDL.

VOCs	Volatile Organic Compounds.
ug/L	Micrograms per liter.
*	Field replicate.
J	Estimated value.
MDL	Method detection limit.
NA	Not analyzed.

ARCADIS

Table 3. Concentrations of General Chemistry, Field Parameters, and Dissolved Gases Detected in Groundwater, Operational Year 5, Colesville Landfill, Broome County, New York.

Parameters	Sample ID: Date:	GMMW-02 12/8/06	GMMW-02 3/26/07	GMMW-02 6/19/07	GMMW-02 9/19/07	GMMW-04 6/18/07	GMMW-04 9/19/07
GENERAL CHEMISTRY							
Total Organic Carbon	mg/L	4.38	<2.00	<2.00	8.8	7.6	6.9
FIELD PARAMETERS							
pH	Standard units	5.89	6.56	6.29	6.48	6.57	6.76
Specific Conductance	mmhos/cm	0.628	0.442	0.558	0.746	0.553	0.621
Turbidity	NTU	--	4.9	--	9.7	--	13.2
Dissolved Oxygen	mg/L	--	--	2.74	12.3	3.5	5.05
Temperature	deg C	7.1	10.4	13.23	11.1	12.78	11.4
ORP	mV	--	--	79	15	-70	-96
DISSOLVED GASES							
Carbon dioxide	mg/L	--	--	<5.00	--	--	--
Carbon monoxide	mg/L	--	--	<1.00	--	--	--
Ethane	ng/L	740	830	800	670	--	--
Ethene	ng/L	5,300	5,300	6,400	7,500	--	--
Methane	ug/L	2,900	4,000	4,100	3,900	--	--
Nitrogen	mg/L	--	--	21	--	--	--
Oxygen	mg/L	--	--	2.7	--	--	--

Bold **Constituent detected above MDL.**
 mg/L Milligrams per liter.
 mmhos/cm Millimhos per centimeter.
 NTU Nephelometric Turbidity Units.
 deg C Degrees Celsius.
 mV Millivolts.
 ng/L Nanograms per liter.
 -- Not analyzed or collected.
 ug/L Micrograms per liter.
 IW Injection well.
 ORP Oxidation-reduction potential.
 J Qualifier assigned to analytical data indicating result is estimated.

ARCADIS

Table 3. Concentrations of General Chemistry, Field Parameters, and Dissolved Gases Detected in Groundwater, Operational Year 5, Colesville Landfill, Broome County, New York.

Parameters	Sample ID: Date:	GMMW-05 12/7/06	GMMW-05 3/26/07	GMMW-05 6/19/07	GMMW-05 9/19/07	GMMW-06 12/7/06	GMMW-06 3/26/07
GENERAL CHEMISTRY							
Total Organic Carbon	mg/L	28	96.4	130	84	246	4.55
FIELD PARAMETERS							
pH	Standard units	7.2	6.56	6.40	6.41	6.9	6.61
Specific Conductance	mmhos/cm	0.713	0.754	0.843	1.9	0.814	0.821
Turbidity	NTU	--	13.3	--	33.8	--	8.1
Dissolved Oxygen	mg/L	--	--	3.9	13.39	--	--
Temperature	deg C	6.1	10.5	14.95	12.7	9.4	10.3
ORP	mV	--	--	-71	-94	--	--
DISSOLVED GASES							
Carbon dioxide	mg/L	--	--	<5.00	--	--	--
Carbon monoxide	mg/L	--	--	<1.00	--	--	--
Ethane	ng/L	86,000	20,000	13,000	14,000	6,700	4,800
Ethene	ng/L	15,000	6,200	1,500	370	120,000	100,000
Methane	ug/L	17,000	29,000	25,000	24,000	7,800	1,800
Nitrogen	mg/L	--	--	4.4	--	--	--
Oxygen	mg/L	--	--	1.5	--	--	--

Bold	Constituent detected above MDL.
mg/L	Milligrams per liter.
mmhos/cm	Millimhos per centimeter.
NTU	Nephelometric Turbidity Units.
deg C	Degrees Celsius.
mV	Millivolts.
ng/L	Nanograms per liter.
--	Not analyzed or collected.
ug/L	Micrograms per liter.
IW	Injection well.
ORP	Oxidation-reduction potential.
J	Qualifier assigned to analytical data indicating result is estimated.

Table 3. Concentrations of General Chemistry, Field Parameters, and Dissolved Gases Detected in Groundwater, Operational Year 5, Colesville Landfill, Broome County, New York.

Parameters	Sample ID: Date:	GMMW-06 6/19/07	GMMW-06 9/18/07	GMMW-07 9/19/07	PW-03 9/19/07	PW-04 12/7/06	PW-04 3/26/07
GENERAL CHEMISTRY							
Total Organic Carbon	mg/L	2.4	--	5.6	--	3.59	<2.00
FIELD PARAMETERS							
pH	Standard units	6.38	6.47	6.69	6.39	5.38	5.56
Specific Conductance	mmhos/cm	0.88	0.799	0.29	0.621	0.961	1.82
Turbidity	NTU	--	16.3	30.1	455	--	126
Dissolved Oxygen	mg/L	4.45	13.01	4.7	7.8	--	--
Temperature	deg C	14.07	11.2	10.6	13.7	8.6	9.9
ORP	mV	-6	-63	-7	36	--	--
DISSOLVED GASES							
Carbon dioxide	mg/L	<5.00	--	--	--	--	--
Carbon monoxide	mg/L	<1.00	--	--	--	--	--
Ethane	ng/L	3,800	5,200	710	--	52	62
Ethene	ng/L	85,000	73,000	5,400	--	290	150
Methane	ug/L	1,700	1,700	1,100	--	12	12
Nitrogen	mg/L	20	--	--	--	--	--
Oxygen	mg/L	1.9	--	--	--	--	--

Bold Constituent detected above MDL.
 mg/L Milligrams per liter.
 mmhos/cm Millimhos per centimeter.
 NTU Nephelometric Turbidity Units.
 deg C Degrees Celsius.
 mV Millivolts.
 ng/L Nanograms per liter.
 -- Not analyzed or collected.
 ug/L Micrograms per liter.
 IW Injection well.
 ORP Oxidation-reduction potential.
 J Qualifier assigned to analytical data indicating result is estimated.

ARCADIS

Table 3. Concentrations of General Chemistry, Field Parameters, and Dissolved Gases Detected in Groundwater, Operational Year 5, Colesville Landfill, Broome County, New York.

Parameters	Sample ID: Date:	PW-04 6/19/07	PW-04 9/18/07	PW-05 9/19/07	PW-07 9/19/07	PW-13 9/19/07	W-05 12/8/06
GENERAL CHEMISTRY							
Total Organic Carbon	mg/L	<2.00	8.0	6.0	--	--	--
FIELD PARAMETERS							
pH	Standard units	5.41	5.69	7.73	6.21	5.93	6.19
Specific Conductance	mmhos/cm	1.65	1.28	0.297	0.285	0.26	1.059
Turbidity	NTU	--	35.1	16.7	371	44	--
Dissolved Oxygen	mg/L	4.5	8.95	6.12	2.52	2.65	--
Temperature	deg C	13.27	12.6	16.9	9.7	10.1	7.2
ORP	mV	160	131	103	-25	22	--
DISSOLVED GASES							
Carbon dioxide	mg/L	<5.00	--	--	--	--	--
Carbon monoxide	mg/L	<1.00	--	--	--	--	--
Ethane	ng/L	58	<25	<25	--	--	18,000
Ethene	ng/L	74	<25	<25	--	--	4,600
Methane	ug/L	17	0.940	1.2	--	--	2,000
Nitrogen	mg/L	19	--	--	--	--	--
Oxygen	mg/L	4	--	--	--	--	--

Bold	Constituent detected above MDL.
mg/L	Milligrams per liter.
mmhos/cm	Millimhos per centimeter.
NTU	Nephelometric Turbidity Units.
deg C	Degrees Celsius.
mV	Millivolts.
ng/L	Nanograms per liter.
--	Not analyzed or collected.
ug/L	Micrograms per liter.
IW	Injection well.
ORP	Oxidation-reduction potential.
J	Qualifier assigned to analytical data indicating result is estimated.

ARCADIS

Table 3. Concentrations of General Chemistry, Field Parameters, and Dissolved Gases Detected in Groundwater, Operational Year 5, Colesville Landfill, Broome County, New York.

Parameters	Sample ID: Date:	W-05 3/26/07	W-05 6/19/07	W-05 9/19/07	W-06 9/19/07	W-07 9/19/07	W-13 9/19/07
GENERAL CHEMISTRY							
Total Organic Carbon	mg/L	7.61	9.51	13	--	--	--
FIELD PARAMETERS							
pH	Standard units	6.46	6.31	6.17	6.09	6.11	6.07
Specific Conductance	mmhos/cm	0.829	0.95	0.945	0.5	0.438	0.826
Turbidity	NTU	41	--	950	7.4	49.4	13.1
Dissolved Oxygen	mg/L	--	2.5	11.91	2.46	3.64	4.15
Temperature	deg C	10.6	15.66	12.4	10.8	10.6	11.3
ORP	mV	--	-36	-84	-32	21	-1
DISSOLVED GASES							
Carbon dioxide	mg/L	--	<5.00	--	--	--	--
Carbon monoxide	mg/L	--	<1.00	--	--	--	--
Ethane	ng/L	20,000	22,000	20,000	--	--	--
Ethene	ng/L	4,400	3,600	2,300	--	--	--
Methane	ug/L	2,300	2,400	3,000	--	--	--
Nitrogen	mg/L	--	21	--	--	--	--
Oxygen	mg/L	--	2.4	--	--	--	--

Bold	Constituent detected above MDL.
mg/L	Milligrams per liter.
mmhos/cm	Millimhos per centimeter.
NTU	Nephelometric Turbidity Units.
deg C	Degrees Celsius.
mV	Millivolts.
ng/L	Nanograms per liter.
--	Not analyzed or collected.
ug/L	Micrograms per liter.
IW	Injection well.
ORP	Oxidation-reduction potential.
J	Qualifier assigned to analytical data indicating result is estimated.

ARCADIS

Table 3. Concentrations of General Chemistry, Field Parameters, and Dissolved Gases Detected in Groundwater, Operational Year 5, Colesville Landfill, Broome County, New York.

Parameters	Sample ID: Date:	W-14S 9/19/07	W-16S 9/19/07	W-17S 9/19/07	W-18 9/19/07	W-20S 9/19/07	IW-2 6/19/07
GENERAL CHEMISTRY							
Total Organic Carbon	mg/L	--	--	--	--	--	26.3
FIELD PARAMETERS							
pH	Standard units	5.57	6.32	6.33	6.2	5.92	5.33
Specific Conductance	mmhos/cm	0.075	0.424	0.224	0.434	0.096	0.182
Turbidity	NTU	>999	155.2	72.7	240	20	--
Dissolved Oxygen	mg/L	7.45	3	4.81	7.41	7.01	2.72
Temperature	deg C	15	15	13.6	15.7	14.2	13.25
ORP	mV	171	102	133	144	132	92
DISSOLVED GASES							
Carbon dioxide	mg/L	--	--	--	--	--	--
Carbon monoxide	mg/L	--	--	--	--	--	--
Ethane	ng/L	--	--	--	--	--	--
Ethene	ng/L	--	--	--	--	--	--
Methane	ug/L	--	--	--	--	--	--
Nitrogen	mg/L	--	--	--	--	--	--
Oxygen	mg/L	--	--	--	--	--	--

Bold **Constituent detected above MDL.**
 mg/L Milligrams per liter.
 mmhos/cm Millimhos per centimeter.
 NTU Nephelometric Turbidity Units.
 deg C Degrees Celsius.
 mV Millivolts.
 ng/L Nanograms per liter.
 -- Not analyzed or collected.
 ug/L Micrograms per liter.
 IW Injection well.
 ORP Oxidation-reduction potential.
 J Qualifier assigned to analytical data indicating result is estimated.

ARCADIS

Table 3. Concentrations of General Chemistry, Field Parameters, and Dissolved Gases Detected in Groundwater, Operational Year 5, Colesville Landfill, Broome County, New York.

Parameters	Sample ID: Date:	IW-2 9/18/07	IW-03 12/8/06	IW-03 3/27/07	IW-03 6/18/07	IW-03 9/19/07	IW-08 12/8/06
GENERAL CHEMISTRY							
Total Organic Carbon	mg/L	240	3780	32.5	227	230	5,890
FIELD PARAMETERS							
pH	Standard units	5.71	4.06	5.64	5.27	5.5	3.51
Specific Conductance	mmhos/cm	1.08	1.81	0.376	0.634	0.802	2.19
Turbidity	NTU	177	--	--	--	170	--
Dissolved Oxygen	mg/L	14.02	--	--	2.9	3.21	--
Temperature	deg C	11.6	9.3	--	12.59	11.5	6.60
ORP	mV	-37	--	--	68	7	--
DISSOLVED GASES							
Carbon dioxide	mg/L	--	--	--	--	--	--
Carbon monoxide	mg/L	--	--	--	--	--	--
Ethane	ng/L	--	--	--	--	--	--
Ethene	ng/L	--	--	--	--	--	--
Methane	ug/L	--	--	--	--	--	--
Nitrogen	mg/L	--	--	--	--	--	--
Oxygen	mg/L	--	--	--	--	--	--

Bold Constituent detected above MDL.
 mg/L Milligrams per liter.
 mmhos/cm Millimhos per centimeter.
 NTU Nephelometric Turbidity Units.
 deg C Degrees Celsius.
 mV Millivolts.
 ng/L Nanograms per liter.
 -- Not analyzed or collected.
 ug/L Micrograms per liter.
 IW Injection well.
 ORP Oxidation-reduction potential.
 J Qualifier assigned to analytical data indicating result is estimated.

ARCADIS

Table 3. Concentrations of General Chemistry, Field Parameters, and Dissolved Gases Detected in Groundwater, Operational Year 5, Colesville Landfill, Broome County, New York.

Parameters	Sample ID: Date:	IW-08 3/18/07	IW-08 6/19/07	IW-08 9/19/07	IW-09 3/27/07	IW-13 12/8/06
GENERAL CHEMISTRY						
Total Organic Carbon	mg/L	1.59	1,370	1,600	426	22
FIELD PARAMETERS						
pH	Standard units	4.42	4.42	4.4	3.51	5.89
Specific Conductance	mmhos/cm	1.176	1.176	1.64	2.19	0.722
Turbidity	NTU	--	--	770	--	--
Dissolved Oxygen	mg/L	3.35	3.35	2.63	--	--
Temperature	deg C	13.94	13.94	11.20	6.60	6.20
ORP	mV	105	3.35	82	--	--
DISSOLVED GASES						
Carbon dioxide	mg/L	--	--	--	--	--
Carbon monoxide	mg/L	--	--	--	--	--
Ethane	ng/L	--	--	--	--	--
Ethene	ng/L	--	--	--	--	--
Methane	ug/L	--	--	--	--	--
Nitrogen	mg/L	--	--	--	--	--
Oxygen	mg/L	--	--	--	--	--

Bold	Constituent detected above MDL.
mg/L	Milligrams per liter.
mmhos/cm	Millimhos per centimeter.
NTU	Nephelometric Turbidity Units.
deg C	Degrees Celsius.
mV	Millivolts.
ng/L	Nanograms per liter.
--	Not analyzed or collected.
ug/L	Micrograms per liter.
IW	Injection well.
ORP	Oxidation-reduction potential.
J	Qualifier assigned to analytical data indicating result is estimated.

ARCADIS

Table 3. Concentrations of General Chemistry, Field Parameters, and Dissolved Gases Detected in Groundwater, Operational Year 5, Colesville Landfill, Broome County, New York.

Parameters	Sample ID: Date:	IW-13 3/27/07	IW-13 6/18/07	IW-13 9/19/07	TW-1 6/18/07	TW-1 9/19/07
GENERAL CHEMISTRY						
Total Organic Carbon	mg/L	13	17.2	34	169	120
FIELD PARAMETERS						
pH	Standard units	5.87	5.78	5.98	6.17	6.33
Specific Conductance	mmhos/cm	0.473	0.436	0.51	1.016	1.21
Turbidity	NTU	86	--	273	--	440
Dissolved Oxygen	mg/L	--	3.06	3.21	3.75	2.74
Temperature	deg C	--	14.27	13.00	15.67	11.10
ORP	mV	--	-2	-26	-67	-98
DISSOLVED GASES						
Carbon dioxide	mg/L	--	--	--	--	--
Carbon monoxide	mg/L	--	--	--	--	--
Ethane	ng/L	--	--	--	--	--
Ethene	ng/L	--	--	--	--	--
Methane	ug/L	--	--	--	--	--
Nitrogen	mg/L	--	--	--	--	--
Oxygen	mg/L	--	--	--	--	--

Bold **Constituent detected above MDL.**
 mg/L Milligrams per liter.
 mmhos/cm Millimhos per centimeter.
 NTU Nephelometric Turbidity Units.
 deg C Degrees Celsius.
 mV Millivolts.
 ng/L Nanograms per liter.
 -- Not analyzed or collected.
 ug/L Micrograms per liter.
 IW Injection well.
 ORP Oxidation-reduction potential.
 J Qualifier assigned to analytical data indicating result is estimated.

ARCADIS

Table 4. Concentrations of Volatile Organic Compounds and Selected Metals Detected in Aqueous Samples Collected from the PT System, Operational Year 5, Colesville Landfill, Broome County, New York. 5,6

Constituents	Model Technology BPJ Limits ^{1,2} (ug/L)	Sample ID: Date:	GMPW-3 12/17/2006	GMPW-3 3/9/2007	GMPW-3 6/19/2007	GMPW-3 9/20/2007	GMPW-4 12/17/2006	GMPW-4 3/9/2007	GMPW-4 6/19/2007	GMPW-4 9/19/2007
1,1,1-Trichloroethane	10-20		32	31	20	23	27	31	19	23
1,1,2-Trichloroethane	10		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
1,1-Dichloroethane	10		56	53	44	45	82	84	78	67
1,1-Dichloroethene	10		2.7	2.5	2.2	1.6	2.5	2.6	2.2	1.7
1,2-Dichloroethane	10-30		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
1,2-Dichloropropane	NA		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Benzene	5		4.5	4.5	3.3	<1.0	4.6	4.8	3.9	2.2
Chlorobenzene	NA		2.7	<1.0	<1.0	<1.0	5.8	9.6	7.1	4.9
Chloroethane	NA		20	14	20	14	34	32	42	28
Chloroform	NA		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
cis-1,2-Dichloroethene	10		84	84	61	53	77	92	68	54
Dichlorodifluoromethane	NA		<1.0	<1.0	1.7	1.8	<1.0	1.5	2.4	2
Ethylbenzene	5		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Methylene Chloride	10-50		2.8	2.1	2.4	1.9	2.9	2.4	2.6	1.5
Methyl tert-butyl ether	50		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Naphthalene	10		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
o-Xylene	5		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Tetrachloroethene	10		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Toluene	5		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
trans-1,2-Dichloroethene	10-50		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Trichloroethene	10		67	73	48	40	68	110	64	56
Vinyl Chloride	10-50		9.7	7.8	11	<1.0	38	25	37	9.8
Total VOCs			281.4	271.9	213.6	180.3	341.8	394.9	326.2	250.1

Metals (units in mg/L)	Model Technology BPJ Limits ^{3,4} (mg/L)
Total Iron	1.2 / 0.61
	0.27
	1.17
	1.23
	16.7
	6.7
	0.775
	0.607
	8.98

See Notes on Last Page.

Operational Year 5. Colesville Landfill, Broome County, New York. 5,6

Metals (units in mg/L)	(mg/L)				
Total Iron	1.2 / 0.61	0.575	2.44	0.541	2.93
				1.52	0.294
					0.719
					10.8

See Notes on Last Page.

ARCADIS

Table 4. Concentrations of Volatile Organic Compounds and Selected Metals Detected in Aqueous Samples Collected from the PT System, Operational Year 5, Colesville Landfill, Broome County, New York. 5,6

Constituents	Model Technology BPJ Limits ^{1,2} (ug/L)	Sample ID: 12/17/2006 Date:	EFFLUENT AC II 3/9/2007	EFFLUENT AC II 6/19/2007	EFFLUENT AC II 9/20/2007
1,1,1-Trichloroethane	10-20		<1.0	<1.0	<1.0
1,1,2-Trichloroethane	10		<1.0	<1.0	<1.0
1,1-Dichloroethane	10		<1.0	<1.0	<1.0
1,4-Dichloroethane	10		<1.0	<1.0	<1.0
1,2-Dichloroethane	10-30		<1.0	<1.0	<1.0
1,2-Dichloropropane	NA		<1.0	<1.0	<1.0
Benzene	5		<1.0	<1.0	<1.0
Chlorobenzene	NA		<1.0	<1.0	<1.0
Chloroethane	NA		<1.0	<1.0	<1.0
Chloroform	NA		<1.0	<1.0	<1.0
cis-1,2-Dichloroethane	10		<1.0	<1.0	<1.0
Dichlorodifluoromethane	NA		<1.0	<1.0	<1.0
Ethylbenzene	5		3.5	<1.0	<1.0
Methylene Chloride	10-50		<1.0	<1.0	<1.0
Methyl tert-butyl ether	50		<1.0	<1.0	<1.0
Naphthalene	10		<1.0	<1.0	<1.0
o-Xylene	5		2.9	<1.0	<1.0
Tetrachloroethene	10		<1.0	<1.0	<1.0
Toluene	5		<1.0	<1.0	<1.0
trans-1,2-Dichloroethene	10-50		<1.0	<1.0	<1.0
Trichloroethene	10		<1.0	<1.0	<1.0
Vinyl Chloride	10-50		<1.0	<1.0	<1.0
Total VOCs			6.4	0.0	0.0
Model Technology BPJ Limits^{3,4} (mg/L)					
Metals (units in mg/L)					
Total Iron	1.2 / 0.61		0.442	1.57	1.94

See Notes on Last Page.

ARCADIS

Table 4. Concentrations of Volatile Organic Compounds and Selected Metals Detected in Aqueous Samples Collected from the PT System, Operational Year 5, Colesville Landfill, Broome County, New York. 5,6

Notes:

1. Model Technology Best Professional Judgment (BPJ) Limits recommended for Air Stripping with appropriate pretreatment from Attachment C of TOGS 1.2.1.
2. When a range is listed for the BPJ limit, a variation in available references was found. Recommended daily maximum limits should be in this range.
3. Model Technology BPJ Limits recommended for Lime, Settle and Filter treatment.
4. The recommended daily maximum permit limit is 1.2 mg/L and the recommended daily average permit limit is 0.61 mg/L.
5. Production wells were sampled in accordance with the schedule set forth in Table 3 of the Long-Term Monitoring Plan (ARCADIS 2002).
6. Bold values indicate compound detected above method detection limit.

NA	No BPJ limit listed.
J	Estimated Value.
ug/L	Micrograms Per Liter.
mg/L	Milligrams Per Liter.
VOCs	Volatile Organic Compounds.
AC	After Cartridge Filter.
PT	Pump and Treat.
--	Not Analyzed or Collected.

ARCADIS

Table 5. Concentrations of Volatile Organic Compounds Detected in Surface Water, Operational Year 5, Colesville Landfill, Broome County, New York.

Constituents (units in ug/L)	Sample ID: Date:	F-6 12/13/2006	F-6 3/27/2007	F-6 6/19/2007	SP-4 12/13/2006	SP-4 3/27/2007	SP-4 6/19/07	SP-4 9/20/07
1,1,1-Trichloroethane		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
1,1,2-Trichloroethane		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
1,1-Dichloroethane		<1.0	<1.0	1.2	<1.0	<1.0	2.4	3.8
1,1-Dichloroethene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
1,2-Dichloroethane		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
1,2-Dichloropropane		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Benzene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Chlorobenzene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Chloroethane		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.1
Chloroform		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
cis-1,2-Dichloroethene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	1.1
Dichlorodifluoromethane		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Ethylbenzene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Methylene chloride		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Methyl tert-butyl ether		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Naphthalene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
o-Xylene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Tetrachloroethene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Toluene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
trans-1,2-Dichloroethene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Trichloroethene		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Vinyl chloride		<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Total VOCs		0.0	0.0	1.2	0.0	0.0	2.4	4.9

Bold Constituent detected above MDL.
VOCs Volatile Organic Compounds.
ug/L Micrograms per liter.

ARCADIS

Table 6. PT System Operating Parameters, Operational Year 5, Quarter Number 4 and Annual Summary, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Date	Time Recorded	Air Stripper Measurements		Flow Measurements				GMPW-5 Totalizer FQI-103 (gallons)
		Blower Discharge Pressure PI-301 (i.w.c.)	Blower Effluent Flowrate (scfm)	Effluent Totalizer FQI-401 (gallons)	Water Bypass ² Totalizer FQI-402 (gallons)	GMPW-3 Totalizer FQI-101 (gallons)	GMPW-4 Totalizer FQI-102 (gallons)	
12/17/2006	10:00 AM	NM	349.0	1,175,830.0	1,023,400.0	379,055.0	108,500.0	399,822.0
3/27/2007	3:00 PM	8.9	NM	NM	NM	437,782.2	118,370.7	408,216.7
6/18/2007	12:00 PM	8.9	313.4	108,248.2	NM	506,371.0	159,041.5	415,950.3
9/20/2007	2:00 PM	8.5	208.4	148,692.6	NM	515,116.9	181,497.3	420,576.2
Average Daily Flowrate During Reporting Period (gpm) =								
				0.30	NA	0.06	0.17	0.03
Total Groundwater Recovered During Reporting Period (gallons) =								
				40,444	NA	8,746	22,456	4,626
Average Daily Flowrate During Operational Year 5 (gpm) =								
				0.53	NA	0.27	0.20	0.07
Total Groundwater Recovered During Operational Year 5 (gallons) =								
				1,324,522	NA	140,972	103,710	35,716
NA	Not applicable							
NM	Not measured.							
gpm	Gallons per minute.							
i.w.c.	Inches of water column.							
scfm	Standard cubic feet per minute.							

Notes:

1. Total effluent totalizer replaced on 12/23/2005.
2. Water bypass totalizer damaged as a result of freezing in February, 2007.

ARCADIS

Table 7. PT System Mass Removal Rate of Volatile Organic Compounds, Operational Year 5, Quarter Number 4 and Annual Summary, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Date Sampled	Influent Concentration (ug/L)	Total VOC (ug/L)	Total Effluent Totalizer FQI-401 (gallons)	Total Groundwater Recovered ¹ Between Sampling Intervals (gal)	Influent Concentration ² Geometric Mean (ug/L)	Total Estimated Mass ³ Removed (lbs)
6/18/2007		232.3	NA	NA	NA	NA
9/20/2007		93.3	148,692.6	40,444.6	147.2	0.05
Total Estimated Mass Removed During Operational Year 5, Quarter Number 4 (lbs) =						
0.05						

Notes:

NA Not applicable.
 ug/L Micrograms per liter.
 gal Gallons.
 lbs Pounds.
 VOC Volatile organic compound.

Total Estimated Mass Removed During Operational Year 5 (lbs) =
 0.56

Total Estimated Mass Removed Since System Startup (lbs) =
 2.59

1. Total Groundwater Recovered Between Sampling Intervals = Well Totalizer Reading for current sampling event - Well Totalizer Reading for prior sampling event.
2. Influent Concentration Geometric Mean = (Influent Concentration for prior sampling event x Influent Concentration for current sampling event) ^ (1/2).
3. Total Mass Removed = (Total Groundwater Recovered Between Sampling Intervals) x Influent Concentration Geometric Mean x 3.7854 L/gallon x (1 lb / 453,592,370 ug).

ARCADIS

Table 8. Concentrations of Volatile Organic Compounds Detected in Air Stripper Effluent, Operational Year 5, Quarter Number 4 and Annual Summary, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Compounds	CAS Numbers	Sample ID: Date Sampled:	Effluent 12/17/2006 ppbv	Effluent 3/9/2007 ppbv	Effluent 6/19/2007 ppbv	Effluent 9/27/2007 ppbv
Vinyl Chloride	75-01-4		<7.2	<7.2	<7.0	<7.3
Chloroethane(Ethyl Chloride)	75-00-3		<7.2	<7.2	<7.0	<7.3
1,1-Dichloroethene(Vinylidene Chloride)	75-35-4		<7.2	<7.2	<7.0	<7.3
Methylene Chloride(Dichloromethane)	75-09-2		<7.2	<7.2	<7.0	<7.3
1,1-Dichloroethane	75-34-3		<7.2	<7.2	<7.0	<7.3
cis-1,2-Dichloroethylene	156-59-2		<7.2	<7.2	<7.0	<7.3
Chloroform	67-66-3		<7.2	<7.2	<7.0	<7.3
1,1,1-Trichloroethane(Methyl Chloroform)	71-55-6		<7.2	<7.2	<7.0	<7.3
Benzene	71-43-2		<7.2	<7.2	<7.0	<7.3
Trichloroethene	79-01-6		<7.2	<7.2	<7.0	<7.3
Toluene	108-88-3		<7.2	<7.2	<7.0	<7.3
Ethyl benzene	100-41-4		<7.2	<7.2	<7.0	<7.3
m,p-Xylene	108-38-3/106-42-3		<7.2	56	<7.0	<7.3
o-Xylene	95-47-6		<7.2	<7.2	<7.0	<7.3
1,2,4-Trimethylbenzene	95-63-6		<7.2	<7.2	<7.0	<7.3
2-Propanol (Isopropyl alcohol)	67-63-0		<7.2	<7.2	<7.0	<7.3
Dichlorodifluoromethane(Freon 12)	75-71-8		<7.2	<7.2	<7.0	<7.3

Bold Constituent detected above MDL.

ppbv: parts per billion by volume

Notes/Assumptions:

1. Samples collected by ARCADIS personnel on the dates shown and submitted to Air Toxics Laboratories LTD.
for volatile organic compound (VOC) analyses using a modified USEPA Method TO-14A.

ENGINEERING DESIGN:
ALL PROFESSIONAL ENGINEERING SERVICES DEPICTED
ON THIS DRAWING HAVE BEEN PERFORMED FOR
ARCADIS BY ARCADIS ENGINEERS & ARCHITECTS OF
NEW YORK, P. C., A PROFESSIONAL CORPORATION,
QUALIFIED TO PERFORM SUCH SERVICES IN THE STATE
OF NEW YORK.

2	05/08	AS BOLT	JH	KZ
1	8/19/04	AS BOLT	JH	KZ

KEYPLAN



88 Durjoya Road
Melville, NY 11747
Tel: 631-249-7600 Fax: 631-249-7610
www.orcode-us.com

PROJECT TITLE

COLESVILLE LANDFILL
BROOME COUNTY, NEW YORK

SP-4 SPRNG AREA AS-BUILT
SITE PLAN

PROJECT MANAGER S. FELDMAN	DEPARTMENT MANAGER N. VALKENBURG
-------------------------------	-------------------------------------

LEAD DESIGN PROF.
C. TUOHY

CHECKED
K. ZEGEL

NY000949.0017


2



SP-4 SPRING AREA SITE PLAN

NOTE:

1. BASE MAP TAKEN FROM "TOPOGRAPHIC SITE SURVEY, COLESVILLE LANDFILL." BY RONALD SCHIESS, PLS, NY LIC NO. 049554, SOUTHERN TIER SURVEYING, LLP, DATED DECEMBER 14, 1999, REVISED AUGUST 2004, DECEMBER 2007 AND APRIL 2008.



LEGEND:


— 1000 —
EXISTING GRADE
LINE

— · — LIMITS OF NORTH
STREAM CHANNEL



RIPRAP ZONE

EXISTING PIEZOMETER



SP-5 SPRING AREA SITE PLAN

LEGEND

- TREATED WATER DISCHARGE LINE
- 980 EXISTING GRADE LINE
- RIPRAP AREA
- ASPHALT
- PW 2 EXISTING MONITORING WELL

NOTE:

1. BASE MAP TAKEN FROM "TOPOGRAPHIC SITE SURVEY, COLESVILLE LANDFILL." BY RONALD SCHIESS, PLS, NY LIC NO. 049554, SOUTHERN TIER SURVEYING, LLP, DATED DECEMBER 14, 1999, REVISED AUGUST 2004, DECEMBER 2007 AND APRIL 2008.

ENGINEERING DESIGN:
ALL PROFESSIONAL ENGINEERING SERVICES DEPICTED ON THIS DRAWING HAVE BEEN PERFORMED FOR ARCADIS BY ARCADIS ENGINEERS & ARCHITECTS OF NEW YORK, P.C. A PROFESSIONAL CORPORATION QUALIFIED TO PERFORM SUCH SERVICES IN THE STATE OF NEW YORK.



ARCADIS

Appendix A

Groundwater Sampling Logs

Date: 9/15/07

G:\PROJECTS\Coltsville\Coltsville for Kids\Singing\September 2006\DTW Form_0606.xls - Sheet1

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/18/07
 Site/Well No. Gmmw-5 Replicate No. REP V180907 Code No. ---
 Weather Sun 75° Sampling Time: Begin 1300 End 1306

Evacuation Data

Measuring Point Top of PUC
 MP Elevation (ft) ---
 Land Surface Elevation (ft) ---
 Sounded Well Depth (ft bmp) ---
 Depth to Water (ft bmp) 49.04
 Water-Level Elevation (ft) ---
 Water Column in Well (ft) ---
 Casing Diameter/Type 2"
 Gallons in Well ---
 Gallons Pumped/Bailed
 Prior to Sampling ---
 Sample Pump Intake
 Setting (ft bmp) ---
 Purge Time begin --- end ---
 Pumping Rate (gpm) ---
 Evacuation Method 2" Disposable poly bailer

Field Parameters

Color 4 Brown tint
 Odor med
 Appearance small pieces
 pH (s.u.) 6.41
 Conductivity (mS/cm) 19.0
 (µmhos/cm) ---
 Turbidity (NTU) 33.8
 Temperature (°C) 12.7
 Dissolved Oxygen (mg/L) 12.8 13.39
 ORP -94
 Sampling Method Bailer 1 PDB
 Remarks PDB - wicks / microseeps
Redeployed new PDB

Constituents Sampled	Container Description	Number	Preservative	
8021 VOLATILES	40 ML VOA VIALS	3	HCL	<u>Out</u> X 2
<u>Methane, Ethane, Ethene</u>		2		X
<u>TOC</u>		1		X 2
<u>Bromide</u>		1		

Sampling Personnel DD/AM KA/FGM

Well Casing Volumes

Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Millisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/18/07
 Site/Well No. W-5 Replicate No. — Code No. —
 Weather SW 75 Sampling Time: Begin — End 1340

Evacuation Data

Measuring Point Top of PVC
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) 51.60
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed Prior to Sampling —
 Sample Pump Intake Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer

Field Parameters

Color Clear
 Odor Slight
 Appearance Cloudy
 pH (s.u.) 6.17
 Conductivity (mS/cm) 0.945
 (µmhos/cm) —
 Turbidity (NTU) 950
 Temperature (°C) 12.40
 Dissolved Oxygen (mg/L) 11.91
 ORP -84
 Sampling Method Bailer / PDB

Remarks PDB - VOC'S Microsips
PDB played a PDB

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	3	HCL
Microsips		2	
TOC		1	
Bromide		1	
Sampling Personnel	DDTM KA / Fran		

Well Casing Volumes
 Gal./Ft. 1-1/4" = 0.06 2" = 0.16 3" = 0.37 4" = 0.65
 1-1/2" = 0.09 2-1/2" = 0.26 3-1/2" = 0.50 6" = 1.47

bmp below measuring point ml milliliter NTU Nephelometric Turbidity Units
 °C Degrees Celsius mS/cm Millisiemens per centimeter PVC Polyvinyl chloride
 ft feet msl mean sea-level s.u. Standard units

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/18/07
 Site/Well No. TW-1 Replicate No. — Code No. —
 Weather SW & 75° Sampling Time: Begin — End 1400

Evacuation Data

Measuring Point TOP OF PVC
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) 41 51.39
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed Prior to Sampling —
 Sample Pump Intake Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer

Field Parameters

Color lt Brown
 Odor med
 Appearance cloudy
 pH (s.u.) 6.33
 Conductivity (mS/cm) 1.21
 (µmhos/cm) —
 Turbidity (NTU) 440.
 Temperature (°C) 11.1
 Dissolved Oxygen (mg/L) 2.74
 ORP -98
 Sampling Method Bailer / PDB
 Remarks Redeployed PDB

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	3	HCL
TOC	—	1	—
Bromide	—	1	—
—	—	—	—
—	—	—	—

Sampling Personnel DD/TM

Well Casing Volumes				
Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/18/07
 Site/Well No. GMMW-6 Replicate No. MS/MSD Code No. —
 Weather SW 75° Sampling Time: Begin — End 1440

Evacuation Data

Measuring Point Top of PVC
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) 38.59
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed Prior to Sampling —
 Sample Pump Intake Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer

Field Parameters

Color Clear
 Odor Slight
 Appearance Clear
 pH (s.u.) 6.47
 Conductivity (mS/cm) 0.799
 (µmhos/cm) —
 Turbidity (NTU) 16.3
 Temperature (°C) 11.2
 Dissolved Oxygen (mg/L) 13.01
 ORP -63
 Sampling Method Bailer / PDB

Remarks PDB - VOCs - Micro-PS
Redeployed PDB

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	3	HCL
Methane Ethane Ethene		2	
TOC		1	

x 3 (mS/m)

Sampling Personnel DD/TM

Well Casing Volumes				
Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp below measuring point ml milliliter NTU Nephelometric Turbidity Units
 °C Degrees Celsius mS/cm Milisiemens per centimeter PVC Polyvinyl chloride
 ft feet msl mean sea-level s.u. Standard units

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 7/18/07
 Site/Well No. GMMW-2 Replicate No. — Code No. —
 Weather SW 75° Sampling Time: Begin — End 1500

Evacuation Data

Measuring Point Top of PVC
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) 36.32
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed Prior to Sampling —
 Sample Pump Intake Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer

Field Parameters

Color Clear
 Odor —
 Appearance —
 pH (s.u.) 6.48
 Conductivity (mS/cm) 0.746
 (µmhos/cm) —
 Turbidity (NTU) 9.7
 Temperature (°C) 11.1
 Dissolved Oxygen (mg/L) 12.30
 ORP 15
 Sampling Method Bailer / PDB
 Remarks PDB - VOCs
Redeployed PDB

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	3	HCL
<u>Ethane Ethene Methane</u>		2	<u>Na₂PO₄</u>
<u>TOC</u>		1	<u>H₂SO₄</u>

Sampling Personnel DB/TM KA/Fran

Well Casing Volumes				
Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp below measuring point ml milliliter NTU Nephelometric Turbidity Units
 °C Degrees Celsius mS/cm Milisiemens per centimeter PVC Polyvinyl chloride
 ft feet msl mean sea-level s.u. Standard units

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/18/07
 Site/Well No. PW-4 Replicate No. — Code No. —
 Weather SW 75° Sampling Time: Begin — End 1520

Evacuation Data

Measuring Point Top of PVC
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) 18.14
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed Prior to Sampling —
 Sample Pump Intake Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer

Field Parameters

Color clear
 Odor none
 Appearance little sediment
 pH (s.u.) 5.69
 Conductivity (mS/cm) 1.28
 (µmhos/cm) —
 Turbidity (NTU) 35.1
 Temperature (°C) 12.6
 Dissolved Oxygen (mg/L) 8.95
 ORP 131
 Sampling Method Bailer / PDB - VOC's
 Remarks Redeployed PDB microseeps

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	3	HCL
Methane Ethane Ethox		2	Na3PO4
TOC		1	H2SO4

Sampling Personnel DB/AM KA / Fran

Well Casing Volumes

Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 7/19/07
 Site/Well No. PW-13 Replicate No. — Code No. —
 Weather Foggy 55° Sampling Time: Begin — End 850

Evacuation Data

Measuring Point Top of PVC
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) 61.45
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed
 Prior to Sampling —
 Sample Pump Intake
 Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer / PDB

Field Parameters

Color Clear
 Odor Slight
 Appearance orange Iron pieces
 pH (s.u.) 5.93
 Conductivity
 (mS/cm) 0.260
 (umhos/cm) —
 Turbidity (NTU) 44.0
 Temperature (°C) 10.1
 Dissolved Oxygen (mg/L) 2.65
 ORP 22
 Sampling Method Bailer - PDB
 Remarks PDB covered in orange

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	3	HCL

Sampling Personnel DD/TM KAI Fegan

Well Casing Volumes

Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units
gpm	Gallons per minute	N/A	Not Applicable	umhos/cm	Micromhos per centimeter
mg/L	Miligrams per liter	NR	Not Recorded	VOC	Volatile Organic Compounds

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/19/07
 Site/Well No. PW-7 Replicate No. Code No.
 Weather Foggy 55° Sampling Time: Begin End 0925

Evacuation Data

Measuring Point Top of PVC
 MP Elevation (ft)
 Land Surface Elevation (ft)
 Sounded Well Depth (ft bmp)
 Depth to Water (ft bmp)
 Water-Level Elevation (ft)
 Water Column in Well (ft) 39.72
 Casing Diameter/Type 2"
 Gallons in Well
 Gallons Pumped/Bailed Prior to Sampling
 Sample Pump Intake Setting (ft bmp)
 Purge Time begin end
 Pumping Rate (gpm)
 Evacuation Method 2" Disposable poly bailer PDB

Field Parameters

Color Orange/Brown
 Odor None
 Appearance Thin/Orange mass
 pH (s.u.) 6.21
 Conductivity (mS/cm) 0.285
 (µmhos/cm)
 Turbidity (NTU) 371.0
 Temperature (°C) 9.7
 Dissolved Oxygen (mg/L) 2.52
 ORP -25
 Sampling Method Bailer / PDB
 Remarks PDB covered in Orange

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	3	HCL

Sampling Personnel DD/AM KA / Fern

Well Casing Volumes

Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp below measuring point ml milliliter NTU Nephelometric Turbidity Units
 °C Degrees Celsius mS/cm Milisiemens per centimeter PVC Polyvinyl chloride
 ft feet msl mean sea-level s.u. Standard units

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/19/07
 Site/Well No. GMMW-7 Replicate No. — Code No. —
 Weather Foggy 55° Sampling Time: Begin — End 0945

Evacuation Data

Measuring Point Top of PVC
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) 47.63
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed Prior to Sampling —
 Sample Pump Intake Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer PDB

Field Parameters

Color Clear
 Odor Slight
 Appearance Clear
 pH (s.u.) 6.69
 Conductivity (mS/cm) 0.290
 (µmhos/cm) —
 Turbidity (NTU) 36.30.1
 Temperature (°C) 10.6
 Dissolved Oxygen (mg/L) 4.70
 ORP -7.0
 Sampling Method Bailer / PDB
 Remarks —

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	3	HCL
Methane Ethane Ethene		2	
TOC		1	

Sampling Personnel DDTM KA/Fran

Well Casing Volumes
 Gal./Ft. 1-1/4" = 0.06 2" = 0.16 3" = 0.37 4" = 0.65
 1-1/2" = 0.09 2-1/2" = 0.26 3-1/2" = 0.50 6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/19/07
 Site/Well No. W-7 Replicate No. — Code No. —
 Weather Foggy / SW 55° Sampling Time: Begin — End 10:00

Evacuation Data

Measuring Point Top of PVC
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) 43.20
 Water-Level Elevation (ft) 43.20 -
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed Prior to Sampling —
 Sample Pump Intake Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer PDB

Field Parameters

Color Clear
 Odor None
 Appearance Clear
 pH (s.u.) 6.11
 Conductivity (mS/cm) 0.438
 (µmhos/cm) —
 Turbidity (NTU) 49.4
 Temperature (°C) 10.6
 Dissolved Oxygen (mg/L) KN Waters 3.64
 ORP 21.0
 Sampling Method Bailer / PDB
 Remarks —

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	<u>3</u>	HCL

Sampling Personnel DD/AM KA/Fran

Well Casing Volumes

Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/19/07
 Site/Well No. LS-6 Replicate No. --- Code No. ---
 Weather Sun 60° Sampling Time: Begin --- End 1020

Evacuation Data

Measuring Point Top of PVC
 MP Elevation (ft) ---
 Land Surface Elevation (ft) ---
 Sounded Well Depth (ft bmp) ---
 Depth to Water (ft bmp) 49.95
 Water-Level Elevation (ft) ---
 Water Column in Well (ft) ---
 Casing Diameter/Type 2"
 Gallons in Well ---
 Gallons Pumped/Bailed Prior to Sampling ---
 Sample Pump Intake Setting (ft bmp) ---
 Purge Time begin --- end ---
 Pumping Rate (gpm) ---
 Evacuation Method 2" Disposable poly bailer / PDB

Field Parameters

Color Clear
 Odor None
 Appearance Clear
 pH (s.u.) 6.09
 Conductivity (mS/cm) 0.500
 (µmhos/cm) ---
 Turbidity (NTU) 7.4
 Temperature (°C) 10.8
 Dissolved Oxygen (mg/L) 2.46
 ORP -32
 Sampling Method Bailer / PDB
 Remarks ---

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	<u>3</u>	<u>HCL</u>

Sampling Personnel DD/TM

Well Casing Volumes

Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/19/07
 Site/Well No. PW-3 Replicate No. — Code No. —
 Weather Sun 65° Sampling Time: Begin — End 1030

Evacuation Data

Measuring Point Top of PVC
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) 13.67
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed Prior to Sampling —
 Sample Pump Intake Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer PDB

Field Parameters

Color Lt Brown
 Odor None
 Appearance cloudy
 pH (s.u.) 6.39
 Conductivity (mS/cm) 0.621
 (µmhos/cm) —
 Turbidity (NTU) 455.0
 Temperature (°C) 13.7
 Dissolved Oxygen (mg/L) 7.80
 ORP 36
 Sampling Method Bailer PDB
 Remarks —

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	3	HCL

Sampling Personnel DD/TM KA / Fran

Well Casing Volumes				
Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/17/07
 Site/Well No. GMMW-4 Replicate No. — Code No. —
 Weather Sun 70° Sampling Time: Begin — End 11:00

Evacuation Data

Measuring Point Top of Pic
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) 46.19
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed Prior to Sampling —
 Sample Pump Intake Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer

Field Parameters

Color Clear
 Odor Slight
 Appearance Clear
 pH (s.u.) 6.76
 Conductivity (mS/cm) 0.621
 (µmhos/cm) —
 Turbidity (NTU) 13.2
 Temperature (°C) 11.4
 Dissolved Oxygen (mg/L) 5.05
 ORP -96
 Sampling Method Bailer
 Remarks —

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	0	HCl
TOC		1	H ₂ SO ₄
Bromide		1	

Sampling Personnel DD/TM KA/FRW

Well Casing Volumes
 Gal./Ft. 1-1/4" = 0.06 2" = 0.16 3" = 0.37 4" = 0.65
 1-1/2" = 0.09 2-1/2" = 0.26 3-1/2" = 0.50 6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units

ARCADIS

Water Sampling Log

Project	Colesville Landfill	Project No.	NY000949.0020	Page	1	of	1
Site Location	Harpursville, NY			Date	9/19/07		
Site/Well No.	W-145	Replicate No.	—	Code No.			
Weather	Sun 75	Sampling Time:	Begin	End	1240		

Evacuation Data

Measuring Point	Top of Pie
MP Elevation (ft)	
Land Surface Elevation (ft)	
Sounded Well Depth (ft bmp)	
Depth to Water (ft bmp)	10.35
Water-Level Elevation (ft)	
Water Column in Well (ft)	
Casing Diameter/Type	2"
Gallons in Well	
Gallons Pumped/Bailed Prior to Sampling	
Sample Pump Intake Setting (ft bmp)	
Purge Time	begin _____ end _____
Pumping Rate (gpm)	
Evacuation Method	2" Disposable poly bailer

Field Parameters

Color	Brown
Odor	None
Appearance	Brown
pH (s.u.)	5.57
Conductivity (mS/cm)	0.075
(µmhos/cm)	
Turbidity (NTU)	> 999
Temperature (°C)	15.0
Dissolved Oxygen (mg/L)	7.45
ORP	171
Sampling Method	Bailer
Remarks	1PDB

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	3	HCL
Sampling Personnel	DD/TM		

Well Casing Volumes

Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Millisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units
gpm	Gallons per minute	N/A	Not Applicable	umhos/cm	Micromhos per centimeter
mg/L	Miligrams per liter	NR	Not Recorded	VOC	Volatile Organic Compounds

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/19/07
 Site/Well No. W-205 Replicate No. — Code No. —
 Weather Sw 70° Sampling Time: Begin — End 1217

Evacuation Data

Measuring Point Top of
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) 11.54
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed Prior to Sampling —
 Sample Pump Intake Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer PDB

Field Parameters

Color Clear
 Odor None
 Appearance tiny black pieces
 pH (s.u.) 6.08 5.92
 Conductivity (mS/cm) 0.096
 (umhos/cm) —
 Turbidity (NTU) 200
 Temperature (°C) 14.2
 Dissolved Oxygen (mg/L) 7.01
 ORP 132
 Sampling Method Bailer / PDB
 Remarks —

Constituents Sampled	Container Description	Number	Preservative
<u>8021 VOLATILES</u>	<u>40 ML VOA VIALS</u>	<u>3</u>	<u>HCL</u>

Sampling Personnel BB/TM KA / Fm

Well Casing Volumes

Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units
gpm	Gallons per minute	N/A	Not Applicable	umhos/cm	Micromhos per centimeter
mg/L	Miligrams per liter	NR	Not Recorded	VOC	Volatile Organic Compounds

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpurville, NY Date 9/19/07
 Site/Well No. W-175 Replicate No. Code No.
 Weather SW 70° Sampling Time: Begin End 1300

Evacuation Data

Measuring Point TOP OF PVC
 MP Elevation (ft)
 Land Surface Elevation (ft)
 Sounded Well Depth (ft bmp)
 Depth to Water (ft bmp) 11.81
 Water-Level Elevation (ft)
 Water Column in Well (ft)
 Casing Diameter/Type 2"
 Gallons in Well
 Gallons Pumped/Bailed Prior to Sampling
 Sample Pump Intake Setting (ft bmp)
 Purge Time begin end
 Pumping Rate (gpm)
 Evacuation Method 2" Disposable poly bailer

Field Parameters

Color Clear to Cloudy
 Odor none
 Appearance det. organics
 pH (s.u.) 6.33
 Conductivity (mS/cm) 0.224
 (µmhos/cm)
 Turbidity (NTU) 72.7
 Temperature (°C) 13.6
 Dissolved Oxygen (mg/L) 4.81
 ORP 133
 Sampling Method Bailer
 Remarks POB

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	3	HCL

Sampling Personnel DD/TM KA / Fm

Well Casing Volumes				
Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units
gpm	Gallons per minute	N/A	Not Applicable	umhos/cm	Micromhos per centimeter
mg/L	Miligrams per liter	NR	Not Recorded	VOC	Volatile Organic Compounds

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/19/07
 Site/Well No. W-13 Replicate No. — Code No. —
 Weather Foggy 550 Sampling Time: Begin — End 9:10

Evacuation Data

Measuring Point Top of PVC
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) 47.65
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed Prior to Sampling —
 Sample Pump Intake Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer PDB

Field Parameters

Color Clear
 Odor Slight
 Appearance Clear
 pH (s.u.) 6.07
 Conductivity (mS/cm) 0.826
 (µmhos/cm) —
 Turbidity (NTU) 13.1
 Temperature (°C) 11.3
 Dissolved Oxygen (mg/L) 4.15
 ORP -1
 Sampling Method Bailer PDB

Remarks 2" bailer gets stuck about 7' down well. Use 1" Bailer.

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	<u>3</u>	HCL

Sampling Personnel DDT/M KAIFCW

Well Casing Volumes

Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/19/07
 Site/Well No. W-163 Replicate No. — Code No. —
 Weather Sun 75° Sampling Time: Begin — End 1322

Evacuation Data

Measuring Point Top of casing
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) 9.76
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed Prior to Sampling —
 Sample Pump Intake Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer / PDB

Field Parameters

Color Cloudy white
 Odor Slight
 Appearance tiny silt + tiny white bugs
 pH (s.u.) 6.32
 Conductivity (mS/cm) 0.424
 (µmhos/cm) —
 Turbidity (NTU) 155.2
 Temperature (°C) 15.0
 Dissolved Oxygen (mg/L) 3.00
 ORP 102
 Sampling Method Bailer / PDB
 Remarks —

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	3	HCL

Sampling Personnel DD/TM KA / Fran

Well Casing Volumes

Gal./Ft. 1-¼" = 0.06 2" = 0.16 3" = 0.37 4" = 0.65
 1-½" = 0.09 2-½" = 0.26 3-½" = 0.50 6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units
gpm	Gallons per minute	N/A	Not Applicable	umhos/cm	Micromhos per centimeter
mg/L	Miligrams per liter	NR	Not Recorded	VOC	Volatile Organic Compounds

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/19/07
 Site/Well No. PW-5 Replicate No. — Code No. —
 Weather Sun Sampling Time: Begin — End 1405

Evacuation Data

Measuring Point Top of Perc.
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) 0.6
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed Prior to Sampling —
 Sample Pump Intake Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer 1 POB

Field Parameters

Color Clear
 Odor None
 Appearance Slight cloudiness
 pH (s.u.) 7.73
 Conductivity (mS/cm) 0.297
 (µmhos/cm) —
 Turbidity (NTU) 16.7
 Temperature (°C) 16.9
 Dissolved Oxygen (mg/L) 6.12
 ORP 103
 Sampling Method Bailer 1 POB

Remarks —

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	3	HCL
TOC	—	1	H ₂ SO ₄
Methane Ethane Ethanol	—	2	—
—	—	—	—
—	—	—	—

Sampling Personnel DD/TM

Well Casing Volumes

Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/19/07
 Site/Well No. IW-2 Replicate No. — Code No. —
 Weather Sw 180° Sampling Time: Begin — End 1500

Evacuation Data

Measuring Point —
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) —
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed Prior to Sampling —
 Sample Pump Intake Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer

Field Parameters

Color Brown
 Odor Strong
 Appearance Brown
 pH (s.u.) 5.71
 Conductivity (mS/cm) 1.08
 (µmhos/cm) —
 Turbidity (NTU) 177.0
 Temperature (°C) 11.6
 Dissolved Oxygen (mg/L) 14.02
 ORP -37
 Sampling Method Bailer
 Remarks —

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	0	HCL
TOC	—	1	H2SO4
Bromide	—	1	—

Sampling Personnel DD/TM KAL

Well Casing Volumes

Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units
gpm	Gallons per minute	N/A	Not Applicable	umhos/cm	Micromhos per centimeter
mg/L	Miligrams per liter	NR	Not Recorded	VOC	Volatile Organic Compounds

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/19/07
 Site/Well No. IW-3 Replicate No. --- Code No. ---
 Weather Sw 75 Sampling Time: Begin --- End 1520

Evacuation Data

Measuring Point ---
 MP Elevation (ft) ---
 Land Surface Elevation (ft) ---
 Sounded Well Depth (ft bmp) ---
 Depth to Water (ft bmp) ---
 Water-Level Elevation (ft) ---
 Water Column in Well (ft) ---
 Casing Diameter/Type 2"
 Gallons in Well ---
 Gallons Pumped/Bailed Prior to Sampling ---
 Sample Pump Intake Setting (ft bmp) ---
 Purge Time begin --- end ---
 Pumping Rate (gpm) ---
 Evacuation Method 2" Disposable poly bailer

Field Parameters

Color Brown
 Odor Strong
 Appearance Brown
 pH (s.u.) 5.50
 Conductivity (mS/cm) 0.802
 (µmhos/cm) ---
 Turbidity (NTU) 170.0
 Temperature (°C) 11.5
 Dissolved Oxygen (mg/L) 3.21
 ORP 7.0
 Sampling Method Bailer
 Remarks ---

Constituents Sampled	Container Description	Number	Preservative
8024 VOLATILES	40 ML VOA VIALS	0	HCL
TOC		1	H2SO4

Sampling Personnel DD/AM KA

Well Casing Volumes
 Gal./Ft. 1-1/4" = 0.06 2" = 0.16 3" = 0.37 4" = 0.65
 1-1/2" = 0.09 2-1/2" = 0.26 3-1/2" = 0.50 6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/19/07
 Site/Well No. IW-13 Replicate No. — Code No. —
 Weather SW 70° Sampling Time: Begin — End 1600

Evacuation Data

Measuring Point —
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) —
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed
 Prior to Sampling —
 Sample Pump Intake
 Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer

Field Parameters

Color Cloudy Lt Brown / gray
 Odor St Med - to strong
 Appearance cloudy
 pH (s.u.) 5.98
 Conductivity (mS/cm) 0.510
 (µmhos/cm) —
 Turbidity (NTU) 273.0
 Temperature (°C) 13.0
 Dissolved Oxygen (mg/L) 3.21
 ORP -26
 Sampling Method Bailer
 Remarks Very little water
Bailer was hitting the
Bottom

Constituents Sampled	Container Description	Number	Preservative
<u>8021 VOLATILES</u>	<u>40 ML VOA VIALS</u>	<u>—</u>	<u>HCL</u>
<u>TOC</u>	<u>—</u>	<u>1</u>	<u>H2SO4</u>
<u>—</u>	<u>—</u>	<u>—</u>	<u>—</u>
<u>—</u>	<u>—</u>	<u>—</u>	<u>—</u>
<u>—</u>	<u>—</u>	<u>—</u>	<u>—</u>

Sampling Personnel DD/M KA

Well Casing Volumes

Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp below measuring point ml milliliter NTU Nephelometric Turbidity Units
 °C Degrees Celsius mS/cm Milisiemens per centimeter PVC Polyvinyl chloride
 ft feet msl mean sea-level s.u. Standard units

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/29/07
 Site/Well No. IW-8 Replicate No. — Code No. —
 Weather SW 70° Sampling Time: Begin — End 0244

Evacuation Data

Measuring Point —
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) —
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed Prior to Sampling —
 Sample Pump Intake Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer

Field Parameters

Color Brown
 Odor Strong
 Appearance Brown
 pH (s.u.) 4.40
 Conductivity (mS/cm) 1.64
 (µmhos/cm) —
 Turbidity (NTU) 770.0
 Temperature (°C) 11.2
 Dissolved Oxygen (mg/L) 2.63
 ORP 82
 Sampling Method Bailer

Remarks pulled 1st Bailer
Well ran dry after that
will let recharge overnight
Bailer seems to get stuck on something

Constituents Sampled	Container Description	Number	Preservative
8921-VOLATILES	40 ML VOA VIALS	0	HCl
TOC		1	H ₂ SO ₄
Bromide		1	

get heavy
comes up
empty.

Bailer
was with
the bottom

Sampling Personnel DD/TM

Well Casing Volumes

Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Millisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/20/07
 Site/Well No. Gm PW-5 Replicate No. — Code No. —
 Weather Sun 75 Sampling Time: Begin — End 11:30

Evacuation Data

Measuring Point _____
 MP Elevation (ft) _____
 Land Surface Elevation (ft) _____
 Sounded Well Depth (ft bmp) _____
 Depth to Water (ft bmp) _____
 Water-Level Elevation (ft) _____
 Water Column in Well (ft) _____
 Casing Diameter/Type 2" _____
 Gallons in Well _____
 Gallons Pumped/Bailed
 Prior to Sampling _____
 Sample Pump Intake
 Setting (ft bmp) _____
 Purge Time begin _____ end _____
 Pumping Rate (gpm) _____
 Evacuation Method 2" Disposable poly bailer System

Field Parameters

Color _____
 Odor _____
 Appearance _____
 pH (s.u.) 6.92
 Conductivity
 (mS/cm) _____
 (µmhos/cm) _____
 Turbidity (NTU) _____
 Temperature (°C) _____
 Dissolved Oxygen (mg/L) _____
 ORP _____
 Sampling Method Bailer System
 Remarks _____

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	3	HCL
Total IRON		1	HNO3

Sampling Personnel DD/TM DM/KA/Buch

Well Casing Volumes

Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Millisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units
gpm	Gallons per minute	N/A	Not Applicable	umhos/cm	Micromhos per centimeter
mg/L	Miligrams per liter	NR	Not Recorded	VOC	Volatile Organic Compounds

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpurville, NY Date 9/20/07
 Site/Well No. Gmpw-4 Replicate No. — Code No. —
 Weather SW 75 Sampling Time: Begin — End 1140

Evacuation Data

Measuring Point —
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) —
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed Prior to Sampling —
 Sample Pump Intake Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer System

Field Parameters

Color —
 Odor —
 Appearance —
 pH (s.u.) 6.04
 Conductivity (mS/cm) —
 (µmhos/cm) —
 Turbidity (NTU) —
 Temperature (°C) —
 Dissolved Oxygen (mg/L) —
 ORP —
 Sampling Method Bailer System
 Remarks —

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	3	HCL
Total Iron		1	HNO3

Sampling Personnel DD/TM DM / Bruce / KA

Well Casing Volumes

Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units
gpm	Gallons per minute	N/A	Not Applicable	umhos/cm	Micromhos per centimeter
mg/L	Miligrams per liter	NR	Not Recorded	VOC	Volatile Organic Compounds

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/20/07
 Site/Well No. GMPW-3 Replicate No. — Code No. 9/20/07
 Weather SW 75° Sampling Time: Begin — End 11:35

Evacuation Data

Measuring Point —
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) —
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed Prior to Sampling —
 Sample Pump Intake Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer System

Field Parameters

Color —
 Odor —
 Appearance —
 pH (s.u.) 5.82
 Conductivity (mS/cm) —
 (µmhos/cm) —
 Turbidity (NTU) —
 Temperature (°C) —
 Dissolved Oxygen (mg/L) —
 ORP —
 Sampling Method Bailer System
 Remarks —

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	3	HCL
Total IRON		1	HNO3

Sampling Personnel DD/ML Dm/Bruce/KA

Well Casing Volumes

Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units
gpm	Gallons per minute	N/A	Not Applicable	umhos/cm	Micromhos per centimeter
mg/L	Miligrams per liter	NR	Not Recorded	VOC	Volatile Organic Compounds

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/20/07
 Site/Well No. COMBINED INFILTRANT Replicate No. — Code No. —
 Weather SWN 75 Sampling Time: Begin — End 1145

Evacuation Data

Measuring Point —
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) —
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed Prior to Sampling —
 Sample Pump Intake Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer System

Field Parameters

Color —
 Odor —
 Appearance —
 pH (s.u.) —
 Conductivity (mS/cm) —
 (µmhos/cm) —
 Turbidity (NTU) —
 Temperature (°C) —
 Dissolved Oxygen (mg/L) —
 ORP —
 Sampling Method Bailer System
 Remarks —

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	3	HCL
Total Iron		1	HNO3

Sampling Personnel DDM KALDM / Grace

Well Casing Volumes
 Gal./Ft. 1-1/4" = 0.06 2" = 0.16 3" = 0.37 4" = 0.65
 1-1/2" = 0.09 2-1/2" = 0.26 3-1/2" = 0.50 6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units
gpm	Gallons per minute	N/A	Not Applicable	umhos/cm	Micromhos per centimeter
mg/L	Miligrams per liter	NR	Not Recorded	VOC	Volatile Organic Compounds

Water Sampling Log

Evacuation Data

Measuring Point _____

MP Elevation (ft) _____

Land Surface Elevation (ft) _____

Sounded Well Depth (ft bmp) _____

Depth to Water (ft bmp) _____

Water-Level Elevation (ft)

Water Column in Well (ft) _____

Casing Diameter/Type 2"

Gallons in Well _____

Gallons Pumped/Bailed
Prior to SamplingSample Pump Intake
Setting (ft bmp) _____

Purge Time begin end

Pumping Rate (gpm) _____

Evacuation Method	2" Disposable poly bailer
-------------------	---------------------------

Color _____

Odor _____

Appearance

pH (s.u.) _____

Conductivity
(mS/cm)

(μmhos/cm)

Turbidity (NTU) _____

Temperature (°C)

Dissolved Oxygen (mg/L)

ORP _____

Sampling Method	Bailer
-----------------	--------

Remarks _____

Sampling Personnel BD/TM Bruce / DM / KA

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Millisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units
gpm	Gallons per minute	N/A	Not Applicable	umhos/cm	Micromhos per centimeter
mg/L	Miligrams per liter	NR	Not Recorded	VOC	Volatile Organic Compounds

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/20/07
 Site/Well No. SP-4 Replicate No. — Code No. —
 Weather Sun 80 Sampling Time: Begin — End 1410

Evacuation Data

Measuring Point _____
 MP Elevation (ft) _____
 Land Surface Elevation (ft) _____
 Sounded Well Depth (ft bmp) _____
 Depth to Water (ft bmp) _____
 Water-Level Elevation (ft) _____
 Water Column in Well (ft) _____
 Casing Diameter/Type 2" _____
 Gallons in Well _____
 Gallons Pumped/Bailed
 Prior to Sampling _____
 Sample Pump Intake
 Setting (ft bmp) _____
 Purge Time begin _____ end _____
 Pumping Rate (gpm) _____
 Evacuation Method 2" Disposable poly-bailer Direct

Field Parameters

Color Clear
 Odor None
 Appearance Clear
 pH (s.u.) 7.12
 Conductivity (mS/cm) 0.210
 (µmhos/cm) _____
 Turbidity (NTU) 1.9
 Temperature (°C) 15.7
 Dissolved Oxygen (mg/L) 10.89
 ORP 51
 Sampling Method Bailer Direct grab
 Remarks _____

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	<u>3</u>	HCL

Sampling Personnel RD/TM KA/OM/BL

Well Casing Volumes

Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Milisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units
gpm	Gallons per minute	N/A	Not Applicable	µmhos/cm	Micromhos per centimeter
mg/L	Miligrams per liter	NR	Not Recorded	VOC	Volatile Organic Compounds

ARCADIS

Water Sampling Log

Project Colesville Landfill Project No. NY000949.0020 Page 1 of 1
 Site Location Harpursville, NY Date 9/20/07
 Site/Well No. SP-5 Replicate No. — Code No. —
 Weather SW 70 Sampling Time: Begin — End —

Evacuation Data

Measuring Point —
 MP Elevation (ft) —
 Land Surface Elevation (ft) —
 Sounded Well Depth (ft bmp) —
 Depth to Water (ft bmp) —
 Water-Level Elevation (ft) —
 Water Column in Well (ft) —
 Casing Diameter/Type 2"
 Gallons in Well —
 Gallons Pumped/Bailed Prior to Sampling —
 Sample Pump Intake Setting (ft bmp) —
 Purge Time begin — end —
 Pumping Rate (gpm) —
 Evacuation Method 2" Disposable poly bailer

Field Parameters

Color —
 Odor —
 Appearance —
 pH (s.u.) —
 Conductivity (mS/cm) —
 (umhos/cm) —
 Turbidity (NTU) —
 Temperature (°C) —
 Dissolved Oxygen (mg/L) —
 ORP —
 Sampling Method *Bailer

Remarks Did Not Sample

Constituents Sampled	Container Description	Number	Preservative
8021 VOLATILES	40 ML VOA VIALS	<u>0</u>	HCL

Sampling Personnel BD/TM KA/DM/BL

Well Casing Volumes

Gal./Ft.	1-1/4" = 0.06	2" = 0.16	3" = 0.37	4" = 0.65
	1-1/2" = 0.09	2-1/2" = 0.26	3-1/2" = 0.50	6" = 1.47

bmp	below measuring point	ml	milliliter	NTU	Nephelometric Turbidity Units
°C	Degrees Celsius	mS/cm	Millisiemens per centimeter	PVC	Polyvinyl chloride
ft	feet	msl	mean sea-level	s.u.	Standard units
gpm	Gallons per minute	N/A	Not Applicable	umhos/cm	Micromhos per centimeter
mg/L	Miligrams per liter	NR	Not Recorded	VOC	Volatile Organic Compounds

ARCADIS

Appendix B

New York State Department of
Environmental Conservation DAR-1
Air Modeling Data

ARCADIS

Table B-1. NYSDEC DAR-1 Air Modeling Data, Operational Year 5, Quarter Number 4, Colesville Landfill, Broome County, New York.

Parameters for 9/20/2007 Sampling Event					
Discharge Temperature	T	515	°R		
Ambient Temperature	Ta	539	°R		
Stack Diameter	D	6	in		
Stack Radius	R	0.25	ft		
Stack Area	A	0.20	ft ²		
Exit Velocity	V	17.3	fps		
Exit Flow	Q	203	acfm		
Exit Flow	Q	208	scfm		
Stack Height	h _s	17	ft		
Building Height	h _b	13.25	ft		
Ratio of Heights	h _s /h _b	1.28			
Plume rise credit? h _s /h _b > 1.5?	(If no, h _e =h _s)	(If Yes, h _e = h _s + 1.1 (F _m) ^{1/3})			
Momentum Flux	F _m = Ta/T * V ² * R ²	n/a	ft ⁴ /s ²		
Effective Stack Height	h _e	17.0	ft		
Reduction Factor? 2.5 > h _s /h _b > 1.5?		No, do not reduce impact			
Actual Annual Impact	C _a	RF*6*Q _g /h _e ^{2.25}			
Mass Flow	Q _a	S lbs emitted for last 12 months			

fps: feet per second
 acfm: actual cubic feet per minute
 ug/m³: micrograms per cubic meter
 lb/yr: pounds per year
 lb/hr: pounds per hour
 ppb: parts per billion

Notes/Assumptions:

1. The stack discharge temperature is 55°F based on recorded parameters.
2. The ambient temperature is approximately 79°F based on recorded conditions.
3. Calculations assume that the system will run with the maximum allowable concentrations between quarterly readings.
4. AGC refers to the Annual Guideline Concentration as determined using the hand calculations in the DAR-1 AGC/SGC Tables dated December 22, 2003.
5. To be conservative the lower detection limit was used for compounds that were below the limit of detection, but are found in the influent groundwater of the Groundwater Remediation System.

ARCADIS

Table B-2. NYSDEC DAR-1 Air Modeling Data, Operational Year 5, Quarter Number 4, Colesville Landfill, Broome County, New York.

Calculation of AGC based on 9/20/2007 Sampling Event

Compounds	CAS Numbers	Maximum Limit on C _a (AGC ⁴) ug/m ³	Maximum Mass Flow Q _a lb/yr	Lab Data ppb	Detection Limit Used ⁵	Actual Emissions C _a ug/m ³	Actual Mass Flow per Hour lb/hr	Actual Mass Flow per Year lb/yr	Percent of Annual %
Vinyl Chloride	75-01-4	0.11	10.76	7.3	*	18.97	1.48E-05	0.12647	1.18
Chloroethane(Ethyl Chloride)	75-00-3	10,000	978,044.97	7.3	*	19.58	1.53E-05	0.13056	0.00
1,1-Dichloroethene(Vinylidene Chloride)	75-35-4	70	6,846.31	7.3	*	29.42	2.30E-05	0.19619	0.00
Methylene Chloride(Dichloromethane)	75-09-2	2.1	205.39	7.3	*	25.78	2.01E-05	0.17188	0.08
1,1-Dichloroethane	75-34-3	0.63	61.62	7.3	*	30.03	2.34E-05	0.20027	0.33
cis-1,2-Dichloroethylene	156-59-2	1,900	185,828.54	7.3	*	29.42	2.30E-05	0.19619	0.00
1,1,1-Trichloroethane(Methyl Chloroform)	71-55-6	1,000	97,804.50	7.3	*	40.49	3.16E-05	0.26999	0.00
Trichloroethene	79-01-6	0.5	48.90	7.3	*	39.88	3.11E-05	0.26590	0.54
m,p-Xylene	108-38-3/106-42-3	700	68,463.15	7.3	*	31.60	2.47E-05	0.21074	0.00
Dichlorodifluoromethane(Freon 12)	75-71-8	12,000	1,173,653.96	7.3	*	18.24	1.42E-05	0.12162	0.00

fps: feet per second

acfm: actual cubic feet per minute

ug/m³: micrograms per cubic meter

lb/yr: pounds per year

lb/hr: pounds per hour

ppb: parts per billion

Notes/Assumptions:

1. The stack discharge temperature is 55°F based on recorded parameters.
2. The ambient temperature is approximately 79°F based on recorded conditions.
3. Calculations assume that the system will run with the maximum allowable concentrations between quarterly readings.
4. AGC refers to the Annual Guideline Concentration as determined using the hand calculations in the DAR-1 AGC/SGC Tables dated December 22, 2003.
5. To be conservative the lower detection limit was used for compounds that were below the limit of detection, but are found in the influent groundwater of the Groundwater Remediation System.

ARCADIS

Appendix C

Automated Reagent Injection System
Operating Parameters

ARCADIS

Table C-1. Automated Reagent Injection System Summary of Operational Year 5, Quarter Number 4 Injection Quantities, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Summary of Automated Reagent Injections

Date	Total Quantity of Molasses Solution Injected (gal.)	Total Quantity of Molasses Injected (gal.)	Total Quantity of Rinse Water Injected (gal.)
7/12/2008	13,705	157	137
Quarter Totals (gal.) =	13,705	157	137
Totals For Operational Year 5 (gal.) =	27,411	305	285
Totals Since Startup (gal.) =	130,931	8,586	7,966

Notes:

gal. Gallons

ARCADIS

Table C-2. Automated Reagent Injection System, Operational Year 5, Quarter Number 4 Operating Parameters, Groundwater Remediation System, Colesville Landfill, Broome County, New York.

Injection Number 55					
Injection Start Date =		6/20/2007			
Injection Completion Date =		7/12/2008			
Molasses to Water Ratio (%) =		1.0		Programmed Mixing Time (min.) ¹ =	
				60	
Injection Well ID	Molasses Solution Injection Quantity (gal.)	Rinse ² Quantity (gal.)	Raw Molasses Per Well (gal.)	Min. Injection ³ Flowrate (gpm)	Max. Injection Pressure (psi)
PW-6	530	5	5.3	NM	28
IW-3	530	5	5.3	NM	28
IW-1	210	4	2.1	NM	29
IW-2	210	3	2.1	NM	28
GMMW-1	140	3	1.4	NM	7
IW-4	989	4	9.9	NM	29
IW-5	989	5	9.9	NM	29
IW-6	989	7	9.9	NM	30
IW-7	989	8	9.9	NM	29
IW-8 ⁴	0	9	0.0	NM	0
IW-9	1,230	11	12.3	NM	32
IW-10	1,230	12	12.3	NM	29
IW-11	1,230	13	12.3	NM	29
IW-12	1,230	15	12.3	NM	29
IW-13	1,230	16	12.3	NM	30
IW-14	989	18	9.9	NM	29
IW-15	989	19	9.9	NM	39
Totals (gal.) =					
	13,705	157	137.1	NA	NA

Notes:

- gal. Gallons.
- min. Minutes.
- i.w.c. Inches of water column.
- psi Pounds per square inch.
- gpm Gallons per minute.
- NA Not applicable.
- NM Not measured.
- 1. Programmed mixing time is calculated from the expiration time of the molasses injection countdown timer to the startup of transfer pump TP-900 during an injection sequence or from the end of transfer pump TP-600 operation to the restart of an injection during a mixing sequence.
- 2. Rinse quantity is approximately 1-pipeline volume for each injection well.
- 3. Parameter not measured due to SCADA system malfunction.
- 4. Injection not conducted into IW-8 for ongoing Alternate Electron Donor Pilot test evaluation.

ARCADIS

Appendix D

Degradation Trend Figures

Figure D-1. Concentrations of PCE Daughter Products Versus Time in GMMW-5




Figure D-2. Concentrations of PCE Daughter Products Versus Time in GMMW-6




Figure D-3. Concentrations of PCE Daughter Products Versus Time in GMMW-02

