# ABBREVIATED
# 2012 LONG-TERM MONITORING REPORT
# FOR
# AIR FORCE PLANT 59
# JOHNSON CITY, NEW YORK

**Contract Number FA8903-10-D-8596**
**Task Order: 0061**

**Project Number:**
**ACHQ20125001**
**CDRL A005**

**Prepared for**

**Air Force Center for Engineering and the Environment**

**Prepared by**

**HydroGeoLogic, Inc.**

**October 2012**

HGL
HydroGeoLogic, Inc

# ABBREVIATED
# 2012 LONG-TERM MONITORING REPORT
# FOR
# AIR FORCE PLANT 59
# JOHNSON CITY, NEW YORK

**Contract Number FA8903-10-D-8596**
**Task Order: 0061**

**Project Number:**
**ACHQ20125001**
**CDRL A005**

**Prepared for**

**Air Force Center for Engineering and the Environment**
**772D Enterprise Sourcing Squadron**
**2261 Hughes Avenue**
**Suite 163**
**Lackland AFB, TX 78236**

**Prepared by**

**HydroGeoLogic, Inc.**
**313 Ushers Road**
**Ballston Lake, NY 12019**

**October 2012**

*This page intentionally left blank.*

# TABLE OF CONTENTS



# LIST OF FIGURES



# LIST OF TABLES



# LIST OF ATTACHMENTS

# LIST OF ACRONYMS AND ABBREVIATIONS

| | |
|---|---|
| AFCEE | Air Force Center for Engineering and the Environment |
| AFP 59 | Air Force Plant 59 |
| Alpha | Alpha Analytical Laboratory |
| *cis*-1,2-DCE | *cis*-1,2-dichloroethene |
| COPC | chemicals of potential concern |
| 1,1-DCA | 1,1-dichloroethane |
| FSP | Field Sampling Plan |
| HGL | HydroGeoLogic, Inc. |
| LTM | long-term monitoring |
| µg/L | micrograms per liter |
| MCL | maximum contaminant level |
| ND | non-detect |
| ng/L | nanograms per liter |
| NYSDEC | New York State Department of Environmental Conservation |
| PCE | tetrachloroethene |
| 1,1,1-TCA | 1,1,-trichloroethane |
| TCE | trichloroethene |
| *trans*-1,2-DCE | *trans*-1,2-dichloroethene |
| USEPA | U.S. Environmental Protection Agency |
| VOC | volatile organic compound |

# ABBREVIATED
# 2012 LONG-TERM MONITORING REPORT
# FOR
# AIR FORCE PLANT 59
# JOHNSON CITY, NEW YORK

## 1.0 INTRODUCTION

In 2012, Hydrogeologic, Inc. (HGL) completed the long-term monitoring (LTM) activities at Air Force Plant 59 (AFP 59) in Johnson City, New York (Figure 1). The Air Force Center for Engineering and the Environment (AFCEE) contracted HGL to complete the LTM activities.

The objectives of this abbreviated monitoring report are to summarize:

- The purpose, collection procedures, and results of the LTM activities; and
- The conclusions and recommendations based on the results of the LTM activities.

## 2.0 LONG-TERM MONITORING ACTIVITIES

### 2.1 PURPOSE OF THE LONG-TERM MONITORING ACTIVITIES

Based on the conclusions presented in the *Final Remedial Investigation Report* (Earth Tech, 1996) and recommendations made by the New York State Department of Environmental Conservation (NYSDEC), it was determined that volatile organic compounds (VOC) represent the only chemicals of potential concern (COPC) in groundwater at AFP 59. The LTM objectives for this project were to sample and evaluate VOC levels in groundwater that are above current maximum contaminant level (MCL) standards.

Groundwater samples were collected using the procedures found in the AFP 59 *Draft Field Sampling Plan (FSP) Addendum* (HGL, 2012a) to AECOM's 2009 Final FSP (AECOM, 2009). Samples were collected and analyzed at Alpha Analytical Laboratory (ALPHA) in Westborough, MA for VOCs (U.S. Environmental Protection Agency [USEPA] Method 8260B) and 1,4-dioxane (USEPA Method 8260SIM). The LTM included sampling the following monitoring wells: SW1, DW1, SW3, DW3, SW4, SW7, JC3, BM-121, URS-2D, URS-2D, URS-3D, and URS-5S. A minor deviation occurred from the original FSP. Well URS-9S could not be located; therefore, after discussion with AFCEE, it was decided to sample BM-121 in its place. Monitoring wells SW1 and DW1 represent upgradient (background) wells, and monitoring wells SW3 and DW3 represent downgradient wells. Monitoring wells JC3 (municipal well), BM-121, URS-2D, URS-2D, URS-3D, and URS-5S are off-site wells, located west and south of the site.

## 2.2 PROCEDURES USED FOR THE LONG-TERM MONITORING ACTIVITIES

Sampling activities followed protocols presented in the *Final Work Plan Base Long-Term Monitoring at AFP 59* (HGL, 2012c) and the *Final Field Sampling Plan Addendum* (HGL, 2012b). HGL collected groundwater samples from six on-site AFP 59 monitoring wells (SW1, DW1, SW3, DW3, SW4, and SW7); five off-site monitoring wells (BM-121, URS-2D, URS-2D, URS-3D, and URS-5S), and one municipal well (JC3) in July and August 2012. All of the sampled groundwater monitoring wells were analyzed for VOCS by USEPA Method SW8260B and 1,4-dioxane using USEPA Method SW8260SIM.

All the wells were sampled using micropurge methodology, which is a low flow-rate monitoring well purging and sampling method that induces laminar (non-turbulent) flow in the immediate vicinity of the sampling pump intake, thus drawing groundwater directly from the sampled aquifer horizontally through the monitoring well screen and into the sampling device. Purging of the monitoring wells was performed to evacuate water that had been stagnant in the monitoring wells, therefore obtaining a sample that is representative of the aquifer. The temperature, pH, specific conductivity and turbidity were also measured and recorded on the monitoring well sampling forms during purging. The field forms and calibration forms are appended as Attachment 1.

## 2.3 ANALYTICAL RESULTS FROM THE LONG-TERM MONITORING ACTIVITIES

The following paragraphs discuss the VOCs that were detected in the groundwater samples, including those samples collected from both on-site and off-site monitoring wells. The analytical results for groundwater samples collected from monitoring wells installed in the shallow and deep zones of the aquifer are discussed below. The VOCs detected in groundwater samples are illustrated on Figure 2. The analytical results for all groundwater samples collected during the July/August 2012 sampling event are summarized in Table 1.

### 2.3.1 Shallow Zone of the Aquifer

VOCs were detected in the groundwater samples collected from on-site monitoring wells SW1, SW3, SW4, and SW7, and off-site monitoring wells URS-2S, URS-9S and BM-121 (Refer to Figure 2). Chlorinated hydrocarbons were the only detected VOCs in the samples collected from the shallow zone of the aquifer. VOCs were not detected in the groundwater sample collected from on-site monitoring well SW1 or off-site BM-121, with the exception of a 1,4-dioxane detection of 254 nanograms per liter (ng/L).

The following maximum concentrations were detected in the groundwater samples collected from on-site monitoring well SW3 during the July/August 2012 event: trichloroethene (TCE) at 0.51 micrograms per liter (µg/L) and *cis*-1,2-dichloroethene (*cis*-1,2-DCE) at 0.28 J µg/L. The following maximum concentrations were detected in the groundwater samples collected from on-site monitoring well SW4 during the July/August 2012 event: 1,1,1- trichloroethane (1,1,1-TCA) at 0.66 µg/L; 1,1-dichloroethane (1,1-DCA) at 0.64 J µg/L; 1,1-dichloroethene (1,1-DCE) was non-detect; *cis*-1,2-DCE at 2.3 µg/L; tetrachloroethene (PCE) at 0.27 J µg/L;

*trans*-1,2-DCE was non-detect; and TCE at 11 µg/L. The following maximum concentrations were detected in the groundwater sample collected from on-site monitoring well SW7 during July/August 2012 event: 1,1,1-TCA at 2.0 µg/L; 1,1-DCA at 6.5 µg/L; PCE at 0.82 µg/L; *cis*-1,2-DCE at 44 µg/L; *trans*-1,2-DCE at 0.21 J µg/L; vinyl chloride at 1.2 M µg/L; and TCE at 9.9 µg/L. The following maximum concentrations were detected in the groundwater sample collected from off-site monitoring well URS-2S during the July/August 2012 event: 1,1-DCA at 1.6 µg/L; 1,1,1-TCA at 3.3 µg/L; TCE at 4.4 µg/L; and *cis*-1,2-DCE at 1.9 µg/L. The following maximum concentrations were detected in the groundwater sample collected from off-site monitoring well URS-5S during the July/August 2012 event: 1,1,1-TCA at 0.52 µg/L; and TCE at 0.82 µg/L.

Exceedances occurred above the New York State Groundwater Quality Standard of 5 µg/L for 1,1-DCA, *cis*-1,2-DCE, and TCE at well SW7. An exceedance also occurred at well SW4 for TCE. These results are highlighted on Figure 2.

During the July/August 2012 sampling effort, 1,4-dioxane was sampled in the four on-site and two off-site shallow monitoring wells. 1,4-dioxane was detected in monitoring wells SW4, BMI-121, URS-2S, and URS-5S at concentrations of 1,030 ng/L; 254 ng/L; 12,100 µg/L; and 9,560 µg/L, respectively. 1,4-dioxane was not detected in monitoring wells SW1 or SW3.

### 2.3.2 Deep Zone of the Aquifer

VOCs were detected in the groundwater samples collected from on-site monitoring wells DW1 and DW3 and the off-site monitoring well URS-2D and URS-3D (Refer to Figure 2). Chlorinated hydrocarbons were the only VOCs detected in the samples collected from the deep zone of the aquifer. VOCs were not detected in the groundwater sample collected from monitoring well DW1. The only VOC detected in monitoring well DW3 was *cis*-1,2-DCE at 56 µg/L and 1,1-DCA at 0.32 J µg/L. The following maximum concentrations were detected in the groundwater sample collected from the off-site monitoring well URS-2D: 1,1-DCA at 0.27 J µg/L; *cis*-1,2-DCE at 71µg/L; and vinyl chloride at 0.22 J µg/L. Additionally, the maximum concentrations were detected in the groundwater sample collected from the off-site monitoring well URS-3D: 1,1-DCA at 0.24 J µg/L; 1,1,1-TCA at 0.87 µg/L ; TCE at 4.4 µg/L and *cis*-1,2-DCE at 1.9 µg/L. *Cis*-1,2-DCE exceeded the New York State Groundwater Quality Standard of 5 µg/L in on-site well DW3 and off-site well URS-2D. Also, 1,4-dioxane was sampled in both the on-site and off-site deep monitoring wells. 1,4-dioxane was only detected in monitoring wells DW3 at 11,200 ng/L, URS-2D at 28,800 ng/L, and URS-3D at 9,560 ng/L.

## 2.4 TREND ANALYSIS

Table 2 presents concentrations of the most commonly detected chlorinated hydrocarbons in groundwater at AFP 59 over time. Only monitoring wells that were sampled as part of the groundwater monitoring program are included in the table.

In the groundwater samples collected from the shallow monitoring wells during the August 2012 sampling event, concentrations of the chlorinated hydrocarbons in monitoring well SW3 remained relatively constant (TCE) or decreased to non-detect (ND) concentrations (TCA and 1,1-DCA) when compared to the previous sampling event in November 2008. Concentrations of *cis*-1,2-DCE increased from the November 2008 sampling event, however the concentration detected in August 2012 was well below the NYS Groundwater Effluent Limitations, Class GA of 5 µg/L.

The concentrations of the chlorinated hydrocarbons in monitoring well SW4 remained relatively constant, with only moderate variation in TCE concentrations when compared to the November 2008 sampling event. TCE concentrations decreased from 12.7 µg/L in November 2008 to 11 µg/L in August 2012. The concentrations of 1,1-DCE (1 µg/L to ND); *cis*-1,2-DCE (3.38 µg/L to 2.0 µg/L); and 1,1-DCA (0.825 J µg/L to 0.64 J µg/L) each decreased during the August 2012 sampling event. The concentration of TCA slightly increased in the August sampling event (0.513 J to 0.66 J µg/L) as compared to the November 2008 sampling event.

Concentrations of TCA in monitoring well SW7 increased slightly from 1.88 µg/L in November 2008 to 2.0 µg/L in August 2012. TCE decreased slightly from 3.1 µg/L in October 2005 to 2.94 µg/L in June 2008, more than doubled to 8.15 µg/L in November 2008, while continually increasing to 9.9 µg/L in August 2012. 1,1-DCA has also continued to increase from 1.4 µg/L to 1.59 µg/L in June 2008, more than tripled to 5.04 µg/L in November 2008, and climbed to 6.5 µg/L in the August 2012 sampling event. Fluctuations have occurred with *cis*-1,2-DCE at well SW7. *Cis*-1,2-DCE decreased from 12 µg/L in October 2005 to 6.34 µg/L in June 2008, then increased to 35.3 M µg/L in November 2008, and continued to increase to 44 µg/L in August 2012. *Trans*-1,2-DCE increased from ND in October 2005 and June 2008 to 0.302 J µg/L in November 2008, and then declined to 0.21 J µg/L in August 2012.

In the groundwater sample collected from deep monitoring well DW3 during the August 2012 sampling event, the concentrations of chlorinated hydrocarbons remained at ND with the exception of *cis*-1,2-DCE and 1,1-DCA. The *cis*-1,2-DCE trend for DW3 has increased from 3 µg/L in October 2005 to 73.1 µg/L in June 2008, and has slowly decreased to 67.3 µg/L in November 2008 to 56 µg/L in August 2012. Additionally, 1,1-DCA detected at concentrations of 0.41 J µg/L during the November 2008 sampling event and continued to decrease to 0.32 J µg/L in August 2012. VOCs were not detected in the groundwater sample collected from deep monitoring well DW1 and shallow monitoring well SW1. These results are consistent with previous sampling events.

# 3.0 CONCLUSIONS AND RECOMMENDATIONS

Although VOC concentrations in the shallow monitoring wells have generally decreased since October 2005, concentrations of TCE and 1,1-DCA continued to exceed the New York State Groundwater Quality Standard of 5 µg/L in well SW7. Additionally, the concentrations of *cis*-1,2-DCE, 1,3,5-trimethylbenzene, and 1,2,4- trimethylbenzene exceeded the New York State

Groundwater Quality Standard of 5 µg/L during the August sampling event in monitoring well SW4. It should be noted that both the 1,3,5-trimethylbenzene, and 1,2,4- trimethylbenzene exceedances have not been typical for this well. Last, groundwater concentrations detected in off-site shallow monitoring well URS-2S and URS-5S did not exceed the New York State Groundwater Quality Standard of 5 µg/L for chlorinated compounds.

In the deep monitoring wells, *cis*-1,2-DCE was the only contaminant that had concentrations exceeding the New York State Groundwater Quality Standard of 5 µg/L. Monitoring well DW3, located on the AFP 59 boundary downgradient of the suspected source, and monitoring well URS-2D, located at a downgradient, off-site location, exceeded the New York State Groundwater Quality Standard for *cis*-1,2-DCE in this groundwater sampling events.

Based on the results of the LTM activities, groundwater exceeding the New York State Groundwater Quality Standards is migrating off of AFP 59 property in the deep monitoring wells. Additional groundwater monitoring is recommended to monitor the migration of contaminants off-site.

# 4.0 REFERENCES

AECOM, 2009a. *Final Field Sampling Plan for the Vapor Intrusion Investigation, Monitoring Well Abandonment, Groundwater Monitoring, and Fire Suppression Reservoir Investigation at Air Force Plant 59, Johnson City, New York*. August.

HydroGeoLogic, Inc. (HGL), 2012a. *Draft Field Sampling Plan Addendum, Basewide Long-Term Monitoring at Air Force Plant 59, Johnson City, New York*. May.

HGL, 2012b. *Final Field Sampling Plan Addendum, Basewide Long-Term Monitoring at Air Force Plant 59, Johnson City, New York*. June.

HGL, 2012c. *Final Work Plan, Basewide Long-Term Monitoring at Air Force Plant 59, Johnson City, New York*. June.

*This page intentionally left blank.*

# FIGURES




\\GST-srv-01\HGLGIS\AFP_59_MSIW\LTM_2012\(01)site_loc.mxd
10/24/2012 PD
Source: HGL, ESRI, ArcGIS Online Bing Maps Aerial

Legend

- Major Road
- Highway
- City Limit
- Surface Water Course

**Figure 1**
**Site Location**
**AFP 59**

# Figure 2
# Groundwater Sampling Results
# July and August 2012
# On-site and Off-site Monitoring Wells


| Well BM-121 | Concentration (µg/L) |
|---|---|
| Analyte | Aug-12 |
| All VOCs | ND |
| 1, 4- Dioxane | 0.254 |

| Well URS-5S | Concentration (µg/L) |
|---|---|
| Analyte | Aug-12 |
| 1,1,1-Trichloroethane | 0.52 |
| Trichloroethene | 0.82 |
| 1, 4- Dioxane | 0.532 |

| Well DW1 | Concentration (µg/L) | | |
|---|---|---|---|
| Analyte | Jun-08 | Nov-08 | Jul-12 |
| All Analytes | All VOCs ND | NS | All VOCs ND |

| Well SW1 | Concentration (µg/L) | | |
|---|---|---|---|
| Analyte | Jun-08 | Nov-08 | Jul-12 |
| All Analytes | All VOCs ND | NS | All VOCs ND |

| URS-2D | Concentration (µg/L) | | |
|---|---|---|---|
| Analyte | Jun-08 | Nov-08 | Aug-12 |
| 1,1-Dichloroethane | 0.239 J | NS | 0.27 J |
| cis-1,2-Dichloroethene | **71.9** | NS | **71** |
| Vinyl Chloride | 0.354 J | NS | 0.22 J |

| Well SW7 | Concentration (µg/L) | | |
|---|---|---|---|
| Analyte | Jun-08 | Nov-08 | Aug-12 |
| 1,1,1-Trichloroethane | 2.5 | 1.88 | 2 |
| 1,1-Dichloroethane | 1.59 | **5.04** | **6.5** |
| cis-1,2-Dichloroethene | **6.34** | **35.3 M** | **44** |
| Tetrachloroethene | 0.843 J | 0.59 J | 0.82 |
| trans-1,2-Dichloroethene | ND | 0.302 J | 0.21 J |
| Trichloroethene | 2.94 | **8.15** | **9.9** |
| Vinyl Chloride | ND | 1.21 M | 1.2 |
| 1, 4- Dioxane | 4.66 | NS | 6 |

| Well SW3 | Concentration (µg/L) | | |
|---|---|---|---|
| Analyte | Jun-08 | Nov-08 | Jul-12 |
| 1,1,1-Trichloroethane | 0.661 J | 0.345 J | ND |
| 1,1-Dichloroethane | 0.403 J | ND | ND |
| cis-1,2-Dichloroethene | 1.45 | ND | ND |
| Trichloroethene | 1.31 | 0.759 J | 0.51 |
| 1, 4- Dioxane | ND | NS | 0.28 J |

| URS-2S | Concentration (µg/L) | | |
|---|---|---|---|
| Analyte | Jun-08 | Nov-08 | Aug-12 |
| 1,1,1-Trichloroethane | 2.25 | NS | 3.3 |
| 1,1-Dichloroethane | 0.585 J | NS | 1.6 |
| cis-1,2-Dichloroethene | 0.996 J | NS | 1.9 |
| Trichloroethene | 2.22 | NS | 4.4 |

| Well URS-3D | Concentration (µg/L) |
|---|---|
| Analyte | Aug-12 |
| 1,1,1-Trichloroethane | 0.87 |
| 1,1-Dichloroethane | 0.24 J |
| cis-1,2-Dichloroethene | 1.2 |
| Trichloroethene | 1.7 |
| 1, 4- Dioxane | 9.56 |

| Well DW3 | Concentration (µg/L) | | |
|---|---|---|---|
| Analyte | Jun-08 | Nov-08 | Jul-12 |
| 1,1-Dichloroethene | ND | 0.41 J | 0.32 J |
| cis-1,2-Dichloroethene | **73.1** | **67.3** | **56** |
| trans-1,2-Dichloroethene | ND | 1.18 | ND |
| 1, 4- Dioxane | 14.3 | NS | 11.2 |

| Well SW4 | Concentration (µg/L) | | |
|---|---|---|---|
| Analyte | Jun-08 | Nov-08 | Aug-12 |
| 1,1,1-Trichloroethane | 2.98 | 0.513 J | 0.66 |
| 1,1-Dichloroethane | 1.51 | 0.825 J | 0.64 J |
| 1,1-Dichloroethene | 0.751 J | ND | ND |
| cis-1,2-Dichloroethene | 4.35 | 2.38 | 2.3 |
| Tetrachloroethene | 0.965 J | 0.305 J | 0.27 J |
| trans-1,2-Dichloroethene | ND | 0.364 J | ND |
| Trichloroethene | **17.8** | **12.7** | **11** |
| 1, 4- Dioxane | 8.18 | NS | 1.03 |

| Well JC3 | Concentration (µg/L) |
|---|---|
| Analyte | Aug-12 |
| 1,1,1-Trichloroethane | 0.56 |
| cis-1,2-Dichloroethene | 0.26 J |
| Trichloroethene | 0.92 |
| 1, 4- Dioxane | 0.898 |

## Legend

- AFP 59 Monitoring Well
- Off-site Monitoring Well
- URS-9S — Monitoring Well Identification
- Road
- Surface Water Course

Notes:
**35.3 M** =Shaded values indicate a New York State (NYS) groundwater effluent Class GA exceedance.
J=The analyte was positively detected, but the quantitaion is an estimation.
M=Matrix Effect. The analyte concentration was estimated due to matrix effect and therefore estimated.
ND=Analyte not detected above laboratory method detection limits.
NS=Monitoring well "Not Sampled" during event.
VOC=volatile organic compound

*\\Gst-srv-01\hglgis\AFP_59_MSIW\LTM_2012\(02)samp_result.mxd*
*10/24/2012 PD*
*Source: HGL, ESRI, AECOM, ArcGIS Online Bing Maps Aerial*

HydroGeoLogic, Inc

# TABLES

# Table 1
# Summary of Detected VOCs
# July and August 2012

| Method | Analyte | NYS GW Effluent Limitations Class GA | Units | 59DW1WG1 8/1/2012 L1213897-01 | 59DW3WG1 8/1/2012 L1213897-02 | 59JC3WG1 8/2/2012 L1213897-03 | 59SW1WG1 8/1/2012 L1213897-04 | 59SW3WG1 8/2/2012 L1213897-05 | 59BM121WG1 8/2/2012 L1213897-06 | 59SW7WG1 8/2/2012 L1213897-07 | 59URS2DWG1 7/31/2012 L1213897-08 | 59URS2SWG1 7/31/2012 L1213897-09 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **VOLATILES by Method 8260B** | Methylene chloride | 5 | µg/L | <5 | <5 | <5 | <5 | <5 | <5 | <5 | <5 | <5 |
| | 1,1-Dichloroethane | 5 | µg/L | <0.75 | **0.32 J** | <0.75 | <0.75 | <0.75 | <0.75 | **6.5** | **0.27 J** | **1.6** |
| | Chloroform | 7 | µg/L | <0.75 | <0.75 | <0.75 | <0.75 | <0.75 | <0.75 | <0.75 | <0.75 | <0.75 |
| | Tetrachloroethene | 5 | µg/L | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | **0.82** | <0.5 | <0.5 |
| | 1,1,1-Trichloroethane | 5 | µg/L | <0.5 | <0.5 | **0.56** | <0.5 | <0.5 | <0.5 | **2.0** | <0.5 | **3.3** |
| | 1,1-Dichloropropene | 5 | µg/L | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 |
| | 1,1,2,2-Tetrachloroethane | 5 | µg/L | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 |
| | Toluene | 5 | µg/L | <0.75 | <0.75 | <0.75 | <0.75 | <0.75 | <0.75 | <0.75 | <0.75 | <0.75 |
| | Vinyl chloride | 2 | µg/L | <1 | <1 | <1 | <1 | <1 | <1 | **1.2** | **0.22 J** | <1 |
| | 1,1-Dichloroethene | 5 | µg/L | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | **0.65** | <0.5 | <0.5 |
| | trans-1,2-Dichloroethene | 5 | µg/L | <0.75 | <0.75 | <0.75 | <0.75 | <0.75 | <0.75 | **0.21 J** | <0.75 | <0.75 |
| | Trichloroethene | 5 | µg/L | <0.5 | <0.5 | **0.92** | <0.5 | **0.51** | <0.5 | **9.9** | <0.5 | **4.4** |
| | o-Xylene | 5 | µg/L | <1 | <1 | <1 | <1 | <1 | <1 | <1 | <1 | <1 |
| | cis-1,2-Dichloroethene | 5 | µg/L | <0.5 | **56** | **0.26 J** | <0.5 | **0.28J** | <0.5 | **44** | **71** | **1.9** |
| | Acetone | NS | µg/L | <5 | <5 | <5 | <5 | <5 | <5 | <5 | <5 | <5 |
| | Bromochloromethane | 5 | µg/L | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 |
| | n-Butylbenzene | 5 | µg/L | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 |
| | sec-Butylbenzene | 5 | µg/L | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 |
| | p-Isopropyltoluene | 5 | µg/L | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 |
| | Naphthalene | 10 | µg/L | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 |
| | n-Propylbenzene | 5 | µg/L | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 |
| | 1,3,5-Trimethylbenzene | 5 | µg/L | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 |
| | 1,2,4-Trimethylbenzene | 5 | µg/L | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 | <2.5 |
| **SEMI-VOLATILES by Method 8270C-SIM** | 1,4-Dioxane | NS | ng/l | <153 | **11,200** | **898** | <153 | <152 | **254** | **6,000** | **28,800** | **12,100** |
| **FIELD PARAMETERS** | Temperature, Initial | NS | ° Celsius | 14.12 | 16.73 | 15.2 | 15.44 | 15.72 | 14.82 | 17.61 | 16.70 | 15.44 |
| | Temperature, Final | | ° Celsius | 14.41 | 15.18 | 15.2 | 14.58 | 14.83 | 14.83 | 16.68 | 15.78 | 15.03 |
| | pH | | Std units | 6.92 | 7.01 | 6.94 | 6.98 | 7.04 | 7.63 | 6.79 | 7.03 | 6.44 |
| | Specific Conductance | | µS/cm | 1,553 | 1,321 | 1,492 | 1,501 | 984 | 658 | 1,427 | 1,230 | 1,185 |
| | ORP | | mV | 145.3 | -34.8 | 138.4 | 119.9 | 60.8 | -155.8 | 93.2 | -70.8 | 5.1 |
| | Dissolved Oxygen | | mg/L | 2.35 | 0.44 | 4.2 | 0.76 | 1.4 | 0.16 | 0.39 | 0.58 | 0.53 |
| | Turbidity | | NTU | 19 | 80 | 0.12 | 5 | 0.75 | 13.5 | 11.7 | 100 | 24 |

**Notes:**

NS - Not Applicable

NS - No Standard

<2.5 - Non-Detect

**6.5** - NYS GW Effluent; Class GA exceedances

Bolded numbers are detections

# Table 1
# Summary of Detected VOCs
# July and August 2012

| Method | Analyte | NYS GW Effluent Limitations Class GA | Units | 59URS3DWG1 7/31/2012 L1213897-10 | 59URS5SWG1 8/2/2012 L1213897-11 | 59EB080112 8/2/2012 Equipment Blank L1213897-12 | 59EB080112 8/2/2012 Equipment Blank (Diluted 5X) L1213897-12 | 59TB073112 7/31/2012 Trip Blank L1213897-13 | 59DUP01WG1 8/2/2012 Duplicate: 59SW7WG1 L1213897-14 | 59DUP02WG1 8/2/2012 Duplicate: 59BM121WG1 L1213897-15 | 59AB080112 8/2/2012 Ambient Blank L1213897-16 | 59SW4WG1 8/29/2012 L1215563-01 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **VOLATILES by Method 8260B** | Methylene chloride | 5 | µg/L | <5 | <5 | **220 E** | **240** | <5 | <5 | <5 | **250** | <5 |
| | 1,1-Dichloroethane | 5 | µg/L | **0.24 J** | <0.75 | <0.75 | | <0.75 | **6.7** | <0.75 | <3 | **0.64 J** |
| | Chloroform | 7 | µg/L | <0.75 | <0.75 | **43** | | <0.75 | <0.75 | <0.75 | **46** | <0.75 |
| | Tetrachloroethene | 5 | µg/L | <0.5 | <0.5 | <0.5 | | <0.5 | **0.81** | <0.5 | <2 | **0.27 J** |
| | 1,1,1-Trichloroethane | 5 | µg/L | **0.87** | **0.52** | <0.5 | | <0.5 | **2.0** | <0.5 | <2 | **0.66** |
| | 1,1-Dichloropropene | 5 | µg/L | <2.5 | <2.5 | <2.5 | | <2.5 | <2.5 | <2.5 | <10 | <2.5 |
| | 1,1,2,2-Tetrachloroethane | 5 | µg/L | <0.5 | <0.5 | <0.5 | | <0.5 | <0.5 | <0.5 | <2 | <0.5 |
| | Toluene | 5 | µg/L | <0.75 | <0.75 | **0.38 J** | | <0.75 | <0.75 | <0.75 | <3 | <0.75 |
| | Vinyl chloride | 2 | µg/L | <1 | <1 | <1 | | <1 | **1.3** | <1 | <4 | <1 |
| | 1,1-Dichloroethene | 5 | µg/L | <0.5 | <0.5 | <0.5 | | <0.5 | **0.69** | <0.5 | <2 | <0.5 |
| | trans-1,2-Dichloroethene | 5 | µg/L | <0.75 | <0.75 | <0.75 | | <0.75 | <0.75 | <0.75 | <3 | <0.75 |
| | Trichloroethene | 5 | µg/L | **1.7** | **0.82** | <0.5 | | <0.5 | **10** | <0.5 | <2 | **11** |
| | o-Xylene | 5 | µg/L | <1 | <1 | <1 | NA | <1 | <1 | <1 | <4 | **0.34J** |
| | cis-1,2-Dichloroethene | 5 | µg/L | **1.2** | <0.5 | <0.5 | | <0.5 | **45** | <0.5 | <2 | **2.3** |
| | Acetone | NS | µg/L | <5 | <5 | **2.6 J** | | <5 | <5 | <5 | <20 | <5 |
| | Bromochloromethane | 5 | µg/L | <2.5 | <2.5 | **0.80 J** | | <2.5 | <2.5 | <2.5 | <10 | <2.5 |
| | n-Butylbenzene | 5 | µg/L | <0.5 | <0.5 | <0.5 | | <0.5 | <0.5 | <0.5 | <2 | 2.3 |
| | sec-Butylbenzene | 5 | µg/L | <0.5 | <0.5 | <0.5 | | <0.5 | <0.5 | <0.5 | <2 | **0.64** |
| | p-Isopropyltoluene | 5 | µg/L | <0.5 | <0.5 | <0.5 | | <0.5 | <0.5 | <0.5 | <2 | **1.2** |
| | Naphthalene | 10 | µg/L | <2.5 | <2.5 | <2.5 | | <2.5 | <2.5 | <2.5 | <10 | **2.9** |
| | n-Propylbenzene | 5 | µg/L | <0.5 | <0.5 | <0.5 | | <0.5 | <0.5 | <0.5 | <2 | **0.31 J** |
| | 1,3,5-Trimethylbenzene | 5 | µg/L | <2.5 | <2.5 | <2.5 | | <2.5 | <2.5 | <2.5 | <10 | **5.3** |
| | 1,2,4-Trimethylbenzene | 5 | µg/L | <2.5 | <2.5 | <2.5 | | <2.5 | <2.5 | <2.5 | <10 | **5.1** |
| **SEMI-VOLATILES by Method 8270C-SIM** | 1,4-Dioxane | NS | ng/l | **9,560** | **532** | <152 | NA | NA | **6,120** | **298** | NA | **1,030** |
| **FIELD PARAMETERS** | Temperature, Initial | NS | ° Celsius | 15.68 | 13.43 | NA | NA | NA | NA | NA | NA | 16.77 |
| | Temperature, Final | | ° Celsius | 17.15 | 13.16 | | | | | | | 16.43 |
| | pH | | Std units | 6.94 | 6.99 | | | | | | | 7.11 |
| | Specific Conductance | | µS/cm | 1,295 | 1,423 | | | | | | | 1,481 |
| | ORP | | mV | 82.7 | 117.2 | | | | | | | 111.3 |
| | Dissolved Oxygen | | mg/L | 2.62 | 1.29 | | | | | | | 2.98 |
| | Turbidity | | NTU | out of range | 24.3 | | | | | | | 11 |

**Notes:**

NS - Not Applicable

NS - No Standard

<2.5 - Non-Detect

**6.5** - NYS GW Effluent; Class GA exceedances

Bolded numbers are detections

**Table 2**
**Trend Analysis of VOCs in Groundwater**

| Well ID | Date Sampled | Concentrations of Analyte in Groundwater µg/L | | | | | | |
|---|---|---|---|---|---|---|---|---|
| | | TCA | TCE | VC | 1,1-DCE | *trans* - 1,2 DCE | 1,1-DCA | *cis* - 1,2 DCE |
| SW1 | Sep-86 | – | – | – | – | – | – | – |
| | Jan-92 | 0.5 | – | – | – | – | – | – |
| | Dec-94 | – | – | – | – | – | – | – |
| | Nov-99 | – | – | – | – | – | – | – |
| | May-00 | – | – | – | – | – | – | – |
| | Nov-00 | – | – | – | – | – | – | – |
| | May-01 | – | – | – | – | – | – | – |
| | Nov-01 | 0.11 J | – | – | – | – | – | – |
| | May-02 | – | – | – | – | – | – | – |
| | Nov-02 | – | – | – | – | – | – | – |
| | May-03 | – | – | – | – | – | – | – |
| | Nov-03 | – | – | – | – | – | – | – |
| | Jun-04 | – | – | – | – | – | – | – |
| | Nov-04 | – | – | – | – | – | – | – |
| | Oct-05 | – | – | – | – | – | – | – |
| | Jun-08 | – | – | – | – | – | – | – |
| | Aug-12 | – | – | – | – | – | – | – |
| DW1 | Jan-92 | 0.6 | – | – | – | – | – | – |
| | Dec-94 | – | – | – | – | – | – | 1.8 |
| | Nov-99 | – | – | – | – | – | – | – |
| | May-00 | – | – | – | – | – | – | – |
| | Nov-00 | – | – | – | – | – | – | – |
| | May-01 | – | – | – | – | – | – | – |
| | Nov-01 | – | – | – | – | – | – | – |
| | May-02 | – | – | – | – | – | – | – |
| | Nov-02 | – | – | – | – | – | – | – |
| | May-03 | – | – | – | – | – | – | – |
| | Nov-03 | – | – | – | – | – | – | – |
| | Jun-04 | – | – | – | – | – | – | – |
| | Nov-04 | – | – | – | – | – | – | – |
| | Oct-05 | – | – | – | – | – | – | – |
| | Jun-08 | – | – | – | – | – | – | – |
| | Aug-12 | – | – | – | – | – | – | – |
| SW3 | Sep-86 | – | **6** | – | – | – | – | – |
| | Jan-92 | **12** | **9** | – | – | – | **5** | – |
| | Dec-94 | 0.5 | 1.8 | – | – | – | – | – |
| | Dec-95 | 0.86 | 2.8 | – | – | – | – | 0.44 |
| | Jul-97 | – | 1 | – | – | – | – | – |
| | Nov-98 | 0.22 | 0.81 | – | – | – | – | 0.1 |
| | Apr-99 | 0.51 | 0.71 | – | – | – | – | 0.17 |
| | Nov-99 | 0.29 | 0.9 | – | – | – | – | 0.39 |
| | May-00 | 0.69 | 1 | – | – | – | 0.55 | 1.29 |
| | Nov-00 | 0.43 | 0.9 | – | – | – | – | 0.22 |
| | May-01 | 0.46 | 0.8 | – | – | – | 0.32 | 1.29 |
| | Nov-01 | 0.32 J | 0.5 J | – | – | – | – | – |
| | May-02 | 0.42 J | 0.8 J | – | – | – | 0.46 J | – |
| | May-03 | 0.584 J | 0.893 J | – | – | – | 0.302 J | 1.37 J |
| | Nov-03 | 0.398 J | 0.856 J | – | – | – | – | 0.511 J |

**Table 2**
**Trend Analysis of VOCs in Groundwater (continued)**

| Well ID | Date Sampled | Concentrations of Analyte in Groundwater µg/L | | | | | | |
|---|---|---|---|---|---|---|---|---|
| | | TCA | TCE | VC | 1,1-DCE | *trans* - 1,2 DCE | 1,1-DCA | *cis* - 1,2 DCE |
| SW3 cont. | Jun-04 | 0.9 J | 0.94 J | – | – | – | 0.95 J | 3.7 |
| | Nov-04 | 0.52 J | 1 | 0.26 J | – | – | 0.38 J | 1.5 |
| | Oct-05 | 0.47 J | 0.86 J | – | – | – | – | 0.55 J |
| | Jun-08 | 0.661 J | 1.31 | – | – | – | 0.403 J | 1.45 |
| | Nov-08 | 0.345 J | 0.759 J | – | – | – | – | – |
| | Aug-12 | – | 0.51 | – | – | – | – | 0.28 J |
| DW3 | Jan-92 | 0.3 | – | – | – | – | 0.3 | – |
| | Dec-94 | – | – | 0.28 | – | – | 0.26 | **36** |
| | Dec-95 | – | – | – | – | – | – | **5.2** |
| | Apr-97 | – | – | – | – | – | – | **41** |
| | Jul-97 | – | – | – | – | – | – | **49** |
| | Nov-98 | – | – | – | – | – | 0.34 | **66** |
| | Apr-99 | – | – | 0.28 | 0.11 | – | 0.35 | **67** |
| | Nov-99 | – | – | – | – | – | – | – |
| | May-00 | – | – | – | – | 0.25 | 0.16 | **24.98** |
| | Nov-00 | – | – | – | – | – | – | **16.85** |
| | May-01 | – | – | – | – | – | – | **13.29** |
| | Nov-01 | – | – | – | – | – | – | **13.58** |
| | May-02 | – | – | – | – | – | 0.1 J | **21.08** |
| | May-03 | – | – | – | – | – | – | – |
| | Nov-03 | – | – | – | – | – | – | 1.18 J |
| | Jun-04 | – | – | – | – | – | – | 1.3 |
| | Nov-04 | – | – | – | – | – | – | 2.1 |
| | Oct-05 | – | – | – | – | – | – | 3 |
| | Jun-08 | – | – | – | – | – | – | **73.1** |
| | Nov-08 | – | – | – | – | – | 0.41 J | **67.3** |
| | Aug-12 | | | | | | 0.32 J | **56** |
| SW4 | Jan-92 | 2 | **97** | – | 0.3 | – | 0.6 | – |
| | Dec-94 | **20** | **370** | – | 2.1 | | **8.5** | **19** |
| | Dec-95 | **34** | **1200** | – | 4.9 | 2.1 | **6.9** | **34** |
| | Apr-97 | – | – | – | – | – | **7.1** | **71** |
| | Jul-97 | **23** | **290** | – | – | – | – | **15** |
| | Nov-98 | **8** | **46** | 0.42 | 0.82 | – | **9** | **10** |
| | Apr-99 | 1.9 | **9.53** | – | – | – | 0.87 | 1.85 |
| | Nov-99 | 2.13 | **9.5** | – | 0.18 | – | **7.7** | **7.15** |
| | May-00 | 2.88 | **8** | 0.11 | 0.21 | 0.49 | 1.67 | 4.3 |
| | Nov-00 | 1.14 | **15.2** | 1.49 | 0.29 | – | **15.25** | **11.18** |
| | May-01 | 3.35 | **34** | – | 0.36 | 0.38 | 1.3 | 3.19 |
| | Nov-01 | 0.88 | **5.7** | 0.43 J | 0.12 J | – | **7.18** | **5.27** |
| | May-02 | 2.54 | **21.63** | – | 0.34 J | – | 0.79 J | 2.07 |
| | May-03 | 3.05 J | **9.09 J** | – | – | – | 1.44 J | 3.36 J |
| | Nov-03 | 2.03 | 4.63 | – | – | – | 0.93 | 1.93 |
| | Jun-04 | 2.8 | **41** | – | 0.57 J | 0.11 | 1.3 | 3.3 |
| | Nov-04 | 3.1 | **56** | – | 0.88 J | 0.19 J | 1.4 | 4.1 |

**Table 2**
**Trend Analysis of VOCs in Groundwater (continued)**

| Well ID | Date Sampled | Concentrations of Analyte in Groundwater µg/L | | | | | | |
|---|---|---|---|---|---|---|---|---|
| | | TCA | TCE | VC | 1,1-DCE | *trans* - 1,2 DCE | 1,1-DCA | *cis* - 1,2 DCE |
| SW4 cont. | Oct-05 | 2.2 | **43** | – | 1 | | 1.7 | **6.3** |
| | Jun-08 | 2.98 | **17.8** | – | 0.751 J | 0.364 J | 1.51 | 4.35 |
| | Nov-08 | 0.513 J | **12.7** | – | – | – | 0.825 J | 3.38 |
| | Aug-12 | 0.66 | **11** | – | – | – | 0.64 J | 2.3 |
| SW7 | Dec-94 | 4.6 | **56** | 6.2 | 1 | 0.3 | **33** | **150** |
| | Dec-95 | 2.2 | **43** | 6.8 | 0.8 | | **20** | **130** |
| | Jul-97 | – | **17.8** | – | – | – | – | 2 |
| | Nov-98 | 2.5 | **12.7** | 3.4 | 0.65 | 0.28 | **12** | **82** |
| | Apr-99 | 1.23 | **15** | – | – | – | 1.46 | **5.25** |
| | Nov-99 | 1.01 | **7.9** | – | 0.19 | – | 3.38 | **18.8** |
| | May-00 | 0.67 | 4 | – | – | 0.12 | 0.71 | 2.43 |
| | Nov-00 | 0.91 | **11** | 0.52 | 0.15 | – | 3.48 | **16.06** |
| | May-01 | 1.18 | 3.95 | – | – | – | 0.47 | 1.46 |
| | Nov-01 | 0.8 J | **5.7** | 0.85 J | 0.19 J | 0.13 J | 3.02 | **25.89** |
| | May-02 | 0.87 J | 1.5 | – | – | – | 0.47 J | 2.79 |
| | May-03 | 1.5 J | 3.8 | – | – | – | 0.409 J | 1.43 J |
| | Nov-03 | 0.674 J | 1.9 | – | – | – | 0.509 | 2.76 |
| | Jun-04 | 1 | 1 | – | – | – | 0.3 J | 1.1 |
| | Nov-04 | 1.5 | 2.1 | 0.47 J | 0.25 J | – | 1.5 J | **10 J** |
| | Oct-05 | 0.73 J | 3.1 | – | – | – | 1.4 | **12** |
| | Jun-08 | 2.5 | 2.94 | – | – | – | 1.59 | **6.34** |
| | Nov-08 | 1.88 | **8.15** | 1.21 M | – | 0.302 J | **5.04** | **35.3 M** |
| | Aug-12 | 2 | **9.9** | 1.2 | 0.65 | 0.21 J | **6.5** | **44** |

**Notes:**

**ND**: Analyte not detected above laboratory method detection limits

**NS**: Monitoring well "Not Sampled" during event

**J**: The analyte was positively detected, but the quantitaion is an estimation

**M**: Matrix Effect. The analyte concentration was estimated due to matrix effect and therefore estimated

Bolded numbers are detections

*This page intentionally left blank.*

# ATTACHMENT 1

# FIELD FORMS

HydroGeoLogic, Inc
Exceeding Expectations

# AFP59 2012 LTM Event
## Daily Instrument and Calibration Log

**Circle One:**
**Spring/Fall**

**Date:**

| Standard Value / Standard Lot Number | pH4 | pH7 | pH10 | SC 1000 | ORP 100 mv | 100% Sat. | |
|---|---|---|---|---|---|---|---|
| | 4.00 2/6 2011 ~~2010169~~ MS | 7.00 2110040 ~~2104466~~ MS | 10.01 2102011 ~~2101326~~ MS | 1413 9319 ~~9084~~ MS | 240.0 3899 ~~2855~~ MS | | |
| Instrument Serial # 05B1766AA | pH4 | pH7 | pH10 | SC 1000 | ORP | D.O. | |
| 7/31/12 Pre Calibration | 3.80 | 7.09 | 10.06 | 1331 | 227.2 | 97.7% | 8.70 mg/L |
| Calibrated | 4.00 | 7.00 | 10.01 | 1413 | 240.0 | 100.5% | 8.95 mg/L |
| End of Day Drift | 3.93 | 7.04 | 10.01 | 1416 | 236.1 | 103.7% | 8.73 mg/L |
| Instrument Serial # 06M1025 A11 | pH4 | pH7 | pH10 | SC 1000 | ORP | D.O. | |
| Pre Calibration | 3.83 | 7.14 | 10.00 | MS ~~1331~~ 1313 | 224.1 | 107.3% | 9.52 mg/L |
| Calibrated | 4.00 | 7.00 | 10.00 | ~~1413~~ 1413 | 240.0 | 100.8% | 8.92 mg/L |
| End of Day Drift | 3.97 | 6.99 | 9.99 | 1414 | 236.4 | 101.6% | 8.59 mg/L |
| Instrument Serial # 06M1025 A11 | pH4 | pH7 | pH10 | SC 1000 | ORP | D.O. | |
| 8/1/12 Pre Calibration | 3.96 | 7.01 | 10.03 | 1.411 | 241.6 | 114.0% | 10.05 |
| Calibrated | 4.00 | 7.00 | 10.00 | 1.413 | 240.0 | 99.9% | 8.88 |
| End of Day Drift | 4.10 | 7.08 | ~~9.89~~ 10.04 | 1.411 | 235.7 | 102.4% | 8.51 mg/L |
| Instrument Serial # 05B1766AA | pH4 | pH7 | pH10 | SC 1000 | ORP | D.O. | |
| Pre Calibration | 3.98 | 6.99 | 10.03 | 1418 | 241.5 | 105.8% | 9.31 mg/L |
| Calibrated | 4.00 | 7.00 | 10.00 | 1413 | 240.0 | 99.9% | 8.79 mg/L |
| End of Day Drift | ~~4.03~~ 3.98 | 6.99 | 10.07 | 1413 | 240.5 | 99.9% | 8.69 |
| Instrument Serial # | pH4 | pH7 | pH10 | SC 1000 | ORP | D.O. | |
| Pre Calibration | | | | | | | |
| Calibrated | | | | | | | |
| End of Day Drift | | | | | | | |

HGL HydroGeoLogic, Inc Exceeding Expectations

# AFP59 2012 LTM Event
## Daily Instrument and Calibration Log

**Circle One: Spring/Fall**

**Date:** 8/2/12

| Standard Value / Standard Lot Number | pH4 | pH7 | pH10 | SC 1000 | ORP 100 mv | 100% Sat. |
|---|---|---|---|---|---|---|
| | 2102d1 | 2110040 | 2102071 | 9319 | 3899 | |
| **Instrument Serial # 05B1766AA** | **pH4** | **pH7** | **pH10** | **SC 1000** | **ORP** | **D.O.** |
| | 3.99 | | | | | |
| Pre Calibration | ~~4.05~~ | 6.99 | 10.02 | 1411 | 240.7 | 99.9 |
| Calibrated | 4.00 | ~~7.00~~ | 10.00 | 1413 | 240.0 | ~~89~~ 100 |
| End of Day Drift | 3.99 | 6.99 | 10.04 | 1412 | 240.2 | 99.8 |
| **Instrument Serial # 06M1025AII** | **pH4** | **pH7** | **pH10** | **SC 1000** | **ORP** | **D.O.** |
| | ~~3.98~~ MS | | ~~10.02~~ MS | MS | MS | MS |
| Pre Calibration | ~~4.08~~ | 6.98 | ~~9.98~~ | 1.417 | 237.3 | |
| Calibrated | 4.00 | 7.00 | 10.00 | 1.413 | 240.0 | |
| End of Day Drift | | | | | | |
| **Instrument Serial #** | **pH4** | **pH7** | **pH10** | **SC 1000** | **ORP** | **D.O.** |
| Pre Calibration | | | | | | |
| Calibrated | | | | | | |
| End of Day Drift | | | | | | |
| **Instrument Serial #** | **pH4** | **pH7** | **pH10** | **SC 1000** | **ORP** | **D.O.** |
| Pre Calibration | | | | | | |
| Calibrated | | | | | | |
| End of Day Drift | | | | | | |
| **Instrument Serial #** | **pH4** | **pH7** | **pH10** | **SC 1000** | **ORP** | **D.O.** |
| Pre Calibration | | | | | | |
| Calibrated | | | | | | |
| End of Day Drift | | | | | | |

8.91 mg/L
8.92 mg/L
8.91

← NOT USED 8/2/12

# GROUNDWATER FIELD SAMPLING DATA SHEET

| | |
|---|---|
| Well No.: URS-3D | Location: AFP59 |
| Sampler(s): G. Riker | Project Name: AFP59 2012 GWS |
| Well Depth: 90.85 SOLINST | Project #: AF7061 Date: 07.31.12 Time: 11:20 |
| DTW (ft): 39.35 DTP Top (ft): | Courier: ___FedEx ___UPS X Hand ___Other |
| MP Ht. Above/Below Ground Surface: | Sampling Method : BP |
| Condition of Bottom of Well: GOOD | Type of Pump: Bladder Pump |
| Screen Interval FTOC(ft): (65.33 - 95.33) | Weather (sun/clear, overcast/rain, wind direction, ambient temperature): |
| Well Diameter (in): 2" SS | CLOUDY; HUMID |
| Placement of Pump Inlet (ft): ~~85.05~~ 83.0 | |

## Field Parameters

| Time | Depth to Water (ft) | Flow Rate (L/m) | Total Volume (L) | pH | Temp. (C) | Cond. (umhos/cm) | ORP (mv) | DO (mg/L) | Turb. (NTU) E-2 | Type, Size, and Amount of Sediment Discharged |
|---|---|---|---|---|---|---|---|---|---|---|
| 12:05 | 39.29 | .1 | .50 | 6.83 | 15.68 | 1.279 | 76.5 | 2.61 | OUT OF RANGE | RD/BRN; TURBID |
| 12:10 | 39.29 | .1 | 1.5 | 6.91 | 15.74 | 1.278 | 75.8 | 2.66 | OUT OF RANGE | RD/BRN; TURBID |
| 12:20 | 39.29 | .1 | 2.0 | 6.90 | 15.81 | 1.273 | 78.9 | 2.69 | " | |
| 12:25 | 39.29 | .1 | 2.5 | 6.91 | 15.99 | 1.272 | 81.2 | 2.71 | " | |
| 12:30 | 39.29 | .1 | 3.0 | 6.93 | 16.17 | 1.270 | 82.1 | 2.67 | " | |
| 12:35 | 39.30 | .1 | 3.5 | 6.92 | 16.32 | 1.269 | 84.6 | 2.83 | " | |
| 12:40 | 39.30 | .1 | 4.0 | 6.94 | 16.45 | 1.275 | 83.9 | 2.81 | " | |
| 12:45 | 39.29 | .1 | 4.5 | 6.96 | 16.85 | 1.287 | 82.0 | 2.73 | " | |
| 12:50 | 39.29 | .1 | 5.0 | 6.95 | 17.08 | 1.292 | 82.0 | 2.63 | " | |
| 12:55 | 39.30 | .1 | 5.5 | 6.95 | 17.12 | 1.294 | 82.5 | 2.61 | " | |
| 13:00 | 39.30 | .1 | 6.0 | 6.94 | 17.15 | 1.295 | 82.7 | 2.62 | " | |
| | SAMPLED 13:01 | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |

## Observations

Color: Clear Other (describe): VERY TURBID REDDISH BRN/SILTY SETTLES

Odor: (None) Low Medium High Very Strong H2S Fuel-like

Notes: PUMP QED BLADDER S/N 19095

SOLINST 100' S/N 1028

LAMOTTE S/N 01906

YSI S/N 11507

Signed/Sampler(s): [signature]

## WELL INSPECTION AND GROUNDWATER LEVEL MEASUREMENT SHEET

WELL NUMBER: URS-3D

PROJECT NAME: AFP59

DATE/TIME: 07.31.12

CITY/STATE: Johnson City, NY

INSPECTED BY: G. RIKER
M. JACKSON

Water Level Indicator Serial No.: 1028

VENT WELL

MONITORING WELL INSTRUMENT READING (VOCs): 0 ppm

WELL INSPECTION/GROUNDWATER LEVEL MEASUREMENT

| | |
|---|---|
| WELL DEPTH (FEET FROM TOP OF PVC) | ~~39.35~~ 90.85 |
| WATER LEVEL DEPTH (FEET FROM TOP OF PVC) | 39.35 |
| PVC WELL STICK-UP (FEET, ABOVE GRADE) | 1.9' |
| PROTECTIVE CASING STICK-UP (FEET, AGS) | 2.0' |
| WELL DIAMETER (INCHES) | 2 |
| WELL CONSTRUCTION (PVC, STEEL, ETC.) | S/S |

| | | | |
|---|---|---|---|
| LOCKED UPON ARRIVAL? | ~~YES~~ | (NO) | WAS CUT LOCK ON ARRIVAL |
| LOCK REPLACED? | YES | (NO) | |
| OBSTRUCTIONS? | YES | (NO) | |
| DAMAGE TO WELL PAD/STICKUP/CASING, ETC? | YES | (NO) | (If YES, detail in comments below) |
| WELL RELABELED? | YES | (NO) | |
| WELL PHOTOGRAPHED? | YES | NO | |

GENERAL CONDITION/COMMENTS/RECOMMENDATIONS:

VERY SILTY DURING SAMPLING/PURGE @ 83' PUMP INTAKE

# FIELD SAMPLING REPORT

| | | | |
|---|---|---|---|
| LOCATION: | AFP59 | PROJECT NAME: | AFP59 2012 GWS |
| SITE: | AFP59 | PROJECT NO: | AF7061 |

## SAMPLE INFORMATION

SAMPLE ID: 59URS3DWG1 DATE: 7-31-12 TIME: 1301

MATRIX TYPE: WG

SAMPLING METHOD: BP

LOT CONTROL #: ___ ___ ___ ___

(Ambient Blank # - Equipment Blank # - Trip Blank # - Cooler #)

CHAIN-OF-CUSTODY #: _____

SAMPLE BEG. DEPTH (FT):

SAMPLE END DEPTH (FT):

GRAB (X) COMPOSITE ( )

ENTER SAMPLE NUMBERS FOR QC SAMPLES/ BLANKS ASSOCIATED WITH THIS SAMPLE:

MATRIX SPIKE (MS): —

MATRIX SPIKE DUP (SD): —

FIELD DUP (FD): —

AMBIENT BLANK (AB): —

EQUIPMENT BLANK (EB): —

TRIP BLANK (TB): 59TB073112

| CONTAINER SIZE/TYPE | # | PRESERVATIVE/ PREPARATION | ANALYTICAL METHOD | ANALYSIS |
|---|---|---|---|---|
| 1L Amber | 2 | Cool to 4C | 8270C | 1,4 Dioxane |
| 40 mL VOA | 3 | Cool to 4C HCl ph<2 | SW8260B | VOCs |

## NOTABLE OBSERVATIONS

| PID READINGS | SAMPLE CHARACTERISTICS | MISCELLANEOUS |
|---|---|---|
| 1st 0.0 | COLOR: | |
| 2nd | ODOR: | |
| | OTHER: | |

pH 6.94 Temperature 17.15 (C) Dissolved Oxygen 2.62 (mg/L) Specific Conductivity 1.295 (umhos/cm)

Iron — (mg/L) Oxidation/Reduction Potential 82.7 (mv) Turbidity out of Range (NTU)

## GENERAL INFORMATION

WEATHER: SUN/CLEAR _____ OVERCAST/RAIN _____ WIND DIRECTION _____ AMBIENT TEMPERATURE _____

SHIPMENT VIA: FEDEX _____ HAND DELIVER ___x___ COURIER _____ OTHER _____

SHIPPED TO: ~~Accutest Laboratories of Northeast - Marlboro, MA~~ Alpha Analytical

COMMENTS:

SAMPLER: George Riker OBSERVER: Mike Jackson

**MATRIX TYPE CODES**

| | |
|---|---|
| DC=DRILL CUTTINGS | SL=SLUDGE |
| WG=GROUND WATER | SO=SOIL |
| LH=HAZARDOUS LIQUID WASTE | GS=SOIL GAS |
| SH=HAZRDOUS SOLID WASTE | WS=SURFACE WATER |
| SE=SEDIMENT | SW=SWAB/WIPE |

**SAMPLING METHOD CODES**

| | |
|---|---|
| B=BAILER | G=GRAB |
| BP=BLADDER PUMP | HA=HAND AUGER |
| PP=PERISTALIC PUMP | H=HOLLOW STEM AUGER |
| CS=COMPOSITE SAMPLE | HP=HYDRO PUNCH |
| C=CONTINUOUS FLIGHT AUGER | SS=SPLIT SPOON |
| DT=DRIVEN TUBE | SP=SUBMERSIBLE PUMP |

*This page intentionally left blank.*

# GROUNDWATER FIELD SAMPLING DATA SHEET

| | |
|---|---|
| Well No.: URS-2D | Location: AFP59 |
| Sampler(s): G RIKER | Project Name: AFP59 2012 GWS |
| Well Depth: 90.20 | Project #: AF7061 Date: 07.31.12 Time: 14:40 |
| DTW (ft): 33.11 DTP Top (ft): | Courier: ___FedEx ___UPS X Hand ___Other |
| MP Ht. Above/Below Ground Surface: | Sampling Method : BP |
| Condition of Bottom of Well: SOFT | Type of Pump: Bladder Pump |
| Screen Interval FTOC(ft): (65 - 90) | Weather (sun/clear, overcast/rain, wind direction, ambient temperature): PTLY. SUNNY; HUMID; LOW 80'S |
| Well Diameter (in): 2 | |
| Placement of Pump Inlet (ft): 83 | |

## Field Parameters

| Time | Depth to Water (ft) | Flow Rate (L/m) | Total Volume (L) | pH | Temp. (C) | Cond. (umhos/cm) | ORP (mv) | DO (mg/L) | Turb. (NTU) | Type, Size, and Amount of Sediment Discharged |
|---|---|---|---|---|---|---|---|---|---|---|
| 15:18 | 33.18 | .150 | ∅ | 6.82 | 16.70 | 1.205 | -19.6 | 2.58 | 210 | FINE SUSPENDED SOLIDS |
| 15:25 | 33.14 | .150 | 1.05 | 6.76 | 16.23 | 1.237 | -41.6 | 0.82 | 270 | |
| 15:30 | 33.15 | .150 | 1.80 | 6.83 | 16.32 | 1.245 | -52.1 | 0.64 | 180 | |
| 15:35 | 33.17 | .150 | 2.55 | 6.92 | 16.20 | 1.241 | -61.5 | 0.53 | 200 | |
| 15:40 | 33.15 | .150 | 3.30 | 6.96 | 16.14 | 1.240 | -64.8 | 0.55 | 180 | |
| 15:45 | 33.15 | .150 | 4.05 | 6.94 | 15.88 | 1.232 | -64.9 | 0.60 | 220 | |
| 15:50 | 33.18 | .150 | 4.80 | 6.97 | 15.96 | 1.234 | -67.3 | 0.60 | 160 | |
| 15:55 | 33.15 | .150 | 5.55 | 6.99 | 15.86 | 1.231 | -68.6 | 0.59 | 160 | |
| 16:00 | 33.15 | .150 | 6.30 | 6.97 | 15.78 | 1.228 | -69.0 | 0.59 | 150 | |
| 16:05 | 33.15 | .150 | 7.05 | 6.99 | 15.74 | 1.227 | -70.8 | 0.59 | 140 | |
| 16:10 | 33.15 | .150 | 7.80 | 7.01 | 15.76 | 1.227 | -71.2 | 0.60 | 110 | |
| 16:15 | 33.16 | .150 | 8.55 | 7.03 | 15.78 | 1.230 | -70.8 | 0.58 | 100 | |
| *SAMPLE @ 16:17 (2ND SAMPLE @ 17:10) MS/MSD | | | | | | | | | | |
| | | DTW: 33.15' @ 17:10 | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |

## Observations

Color: Clear Other (describe): SLIGHTLY TURBID; REDDISH BRN. SUSPENDED FINES

Odor: (None) Low Medium High Very Strong H2S Fuel-like

Notes: PUMP: # PUMP 10298

SOLINST 100': S/N 47088

QED MP-10 · 2541

YSI · S/N 11507

QED WATERMARD COMP: S/N 050985

Signed/Sampler(s):

## WELL INSPECTION AND GROUNDWATER LEVEL MEASUREMENT SHEET

WELL NUMBER: URS-2D

PROJECT NAME: AFP59

DATE/TIME: 7/31/12 1620

CITY/STATE: Johnson City, NY

INSPECTED BY: George Riker

Water Level Indicator Serial No.: Solinst 47088

VENT WELL

MONITORING WELL INSTRUMENT READING (VOCs): 0.0 ppm

WELL INSPECTION/GROUNDWATER LEVEL MEASUREMENT

WELL DEPTH (FEET FROM TOP OF PVC) 90.20

WATER LEVEL DEPTH (FEET FROM TOP OF PVC) 33.11

PVC WELL STICK-UP (FEET, ABOVE GRADE) —

PROTECTIVE CASING STICK-UP (FEET, AGS) FLUSH MOUNT

WELL DIAMETER (INCHES) 2

WELL CONSTRUCTION (PVC, STEEL, ETC.) STAINLESS STEEL

| | | | |
|---|---|---|---|
| LOCKED UPON ARRIVAL? | (YES) | NO | |
| LOCK REPLACED? | YES | (NO) | |
| OBSTRUCTIONS? | YES | (NO) | |
| DAMAGE TO WELL PAD/STICKUP/CASING, ETC? | YES | (NO) | (If YES, detail in comments below) |
| WELL RELABELED? | YES | (NO) | |
| WELL PHOTOGRAPHED? | (YES) | NO | |

GENERAL CONDITION/COMMENTS/RECOMMENDATIONS: FLUSH MOUNT. LOCATED IN Backyard of Corner HOME. 5' from URS-25

# FIELD SAMPLING REPORT

| | | | |
|---|---|---|---|
| LOCATION: | AFP59 | PROJECT NAME: | AFP59 2012 GWS. |
| SITE: | AFP59 | PROJECT NO: | AF7061 |

## SAMPLE INFORMATION

SAMPLE ID: 59URS2DWG1 DATE: 7-31-12 TIME: 1617

MATRIX TYPE: WG

SAMPLING METHOD: BP

LOT CONTROL #: ___ ___ ___ ___

(Ambient Blank # - Equipment Blank # - Trip Blank # - Cooler #)

CHAIN-OF-CUSTODY #: _____

SAMPLE BEG. DEPTH (FT): —

SAMPLE END DEPTH (FT): —

GRAB ~~X~~ COMPOSITE ( )

ENTER SAMPLE NUMBERS FOR QC SAMPLES/ BLANKS ASSOCIATED WITH THIS SAMPLE:

MATRIX SPIKE (MS): 59URS2DWG1-MS

MATRIX SPIKE DUP (SD): 59URS2DWG1-MSD

FIELD DUP (FD): —

AMBIENT BLANK (AB): —

EQUIPMENT BLANK (EB): —

TRIP BLANK (TB): 59TB073112

| CONTAINER SIZE/TYPE | # | PRESERVATIVE/ PREPARATION | ANALYTICAL METHOD | ANALYSIS |
|---|---|---|---|---|
| 1L Amber | 2 | Cool to 4C | 8270C | 1,4 Dioxane |
| 40 mL VOA | 3 | Cool to 4C HCl ph<2 | SW8260B | VOCs |

## NOTABLE OBSERVATIONS

| PID READINGS | SAMPLE CHARACTERISTICS | MISCELLANEOUS |
|---|---|---|
| 1st 0.0 | COLOR: | |
| 2nd | ODOR: | |
| | OTHER: | |

pH 7.03 Temperature 15.78 (C) Dissolved Oxygen 0.58 (mg/L) Specific Conductivity 1,230 (umhos/cm)

Iron — (mg/L) Oxidation/Reduction Potential -70.8 (mv) Turbidity 100 (NTU)

## GENERAL INFORMATION

WEATHER: SUN/CLEAR X OVERCAST/RAIN _____ WIND DIRECTION _____ AMBIENT TEMPERATURE 80°

SHIPMENT VIA: FEDEX _____ HAND DELIVER ___x___ COURIER _____ OTHER _____

SHIPPED TO: ~~Accutest Laboratories of Northeast Marlboro, MA~~ Alpha Analytical Albany, NY

COMMENTS:

SAMPLER: George Ritter OBSERVER: Mike Jackson

| MATRIX TYPE CODES | | SAMPLING METHOD CODES | |
|---|---|---|---|
| DC=DRILL CUTTINGS | SL=SLUDGE | B=BAILER | G=GRAB |
| WG=GROUND WATER | SO=SOIL | BP=BLADDER PUMP | HA=HAND AUGER |
| LH=HAZARDOUS LIQUID WASTE | GS=SOIL GAS | PP=PERISTALIC PUMP | H=HOLLOW STEM AUGER |
| SH=HAZRDOUS SOLID WASTE | WS=SURFACE WATER | CS=COMPOSITE SAMPLE | HP=HYDRO PUNCH |
| SE=SEDIMENT | SW=SWAB/WIPE | C=CONTINUOUS FLIGHT AUGER | SS=SPLIT SPOON |
| | | DT=DRIVEN TUBE | SP=SUBMERSIBLE PUMP |

*This page intentionally left blank.*

# GROUNDWATER FIELD SAMPLING DATA SHEET

| | |
|---|---|
| Well No.: URS-2S | Location: AFP59 |
| Sampler(s): MIKE JACKSON | Project Name: AFP59 2012 GWS |
| Well Depth: 58.60 | Project #: AF7061 Date: 7/31/12 Time: 1720 |
| DTW (ft): 34.35 DTP Top (ft): | Courier: ___FedEx ___UPS X Hand ___Other |
| MP Ht. Above/Below Ground Surface: | Sampling Method : BP |
| Condition of Bottom of Well: | Type of Pump: Bladder Pump |
| Screen Interval FTOC(ft): (35.45 - 60.45) | Weather (sun/clear, overcast/rain, wind direction, ambient temperature): |
| Well Diameter (in): 2 | Partly Cloudy, Humid, 80° |
| Placement of Pump Inlet (ft): 53.45 | |

**Field Parameters**

| Time | Depth to Water (ft) | Flow Rate (L/m) | Total Volume (L) | pH (+/-0.1) | Temp (C) (+/-3%) | Cond. ~~(umhos/cm)~~ mS/cm (+/-10) | ORP (mv) (+/-10) | DO (mg/L) | Turb. (NTU) | Type, Size, and Amount of Sediment Discharged |
|---|---|---|---|---|---|---|---|---|---|---|
| 1740 | 33.52 | 0.18 | 0.5 | 6.37 | 15.44 | 1.186 | 10.3 | 0.77 | 120 | |
| 1745 | 33.52 | 0.18 | 1.4 | 6.45 | 15.29 | 1.191 | 1.9 | 0.76 | 80 | |
| 1750 | 33.52 | 0.18 | 2.3 | 6.44 | 15.17 | 1.187 | 5.2 | 0.77 | 50 | |
| 1755 | 33.52 | 0.18 | 3.2 | 6.45 | 15.11 | 1.184 | 3.1 | 0.69 | 39 | |
| 1800 | 33.52 | 0.18 | 4.1 | 6.43 | 15.10 | 1.182 | 5.6 | 0.68 | 30 | |
| 1805 | 33.52 | 0.18 | 5.0 | 6.44 | 15.08 | 1.182 | 7.7 | 0.59 | 25 | |
| 1810 | 33.52 | 0.18 | 5.9 | 6.44 | 15.03 | 1.185 | 5.1 | 0.53 | 24 | |
| 1812 | Collect | | Ground | Water | | Samples | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |

## Observations

Color: (Clear) Other (describe):

Odor: (None) Low Medium High Very Strong H2S Fuel-like

Notes: #18731

33.27 DTW Post pump Install YSI 556 (06M025AH)

Canotec 2020 (SN# 2523-1501) Final DTW = 33.41

well with 3020 compressor #2040

Solinst WLI model 101 (#17088)

Signed/Sampler(s):

## WELL INSPECTION AND GROUNDWATER LEVEL MEASUREMENT SHEET

WELL NUMBER: URS-2S

PROJECT NAME: AFP59

DATE/TIME: 7/31/12 1815

CITY/STATE: Johnson City, NY

INSPECTED BY: MDJ

Water Level Indicator Serial No.: Solonst #47088

VENT WELL

MONITORING WELL INSTRUMENT READING (VOCs): 0.6 ppm

WELL INSPECTION/GROUNDWATER LEVEL MEASUREMENT

WELL DEPTH (FEET FROM TOP OF PVC) 58.60

WATER LEVEL DEPTH (FEET FROM TOP OF PVC) 34.35

PVC WELL STICK-UP (FEET, ABOVE GRADE) -

PROTECTIVE CASING STICK-UP (FEET, AGS) -

WELL DIAMETER (INCHES) 2

WELL CONSTRUCTION (PVC, STEEL, ETC.) Stainless STEEL

| | | | |
|---|---|---|---|
| LOCKED UPON ARRIVAL? | (YES) | NO | |
| LOCK REPLACED? | YES | (NO) | |
| OBSTRUCTIONS? | YES | (NO) | |
| DAMAGE TO WELL PAD/STICKUP/CASING, ETC? | YES | (NO) | (If YES, detail in comments below) |
| WELL RELABELED? | YES | (NO) | |
| WELL PHOTOGRAPHED? | (YES) | NO | |

GENERAL CONDITION/COMMENTS/RECOMMENDATIONS:

Backyard of House on Corel. Flush mount
5' from URS-2D

# FIELD SAMPLING REPORT

| | | | |
|---|---|---|---|
| LOCATION: | AFP59 | PROJECT NAME: | AFP59 2012 GWS |
| SITE: | AFP59 | PROJECT NO: | AF7061 |

## SAMPLE INFORMATION

SAMPLE ID: 59URS2SGW1

DATE: 7-31-12 TIME: 1815

MATRIX TYPE: WG

SAMPLING METHOD: BP

LOT CONTROL #: ___ ___ ___ ___

(Ambient Blank # - Equipment Blank # - Trip Blank # - Cooler #)

CHAIN-OF-CUSTODY #: _____

SAMPLE BEG. DEPTH (FT): —

SAMPLE END DEPTH (FT): —

GRAB (X) COMPOSITE ( )

ENTER SAMPLE NUMBERS FOR QC SAMPLES/ BLANKS ASSOCIATED WITH THIS SAMPLE:

MATRIX SPIKE (MS): —

MATRIX SPIKE DUP (SD): —

FIELD DUP (FD): —

AMBIENT BLANK (AB): —

EQUIPMENT BLANK (EB): —

TRIP BLANK (TB): 59TB073112

| CONTAINER SIZE/TYPE | # | PRESERVATIVE/ PREPARATION | ANALYTICAL METHOD | ANALYSIS |
|---|---|---|---|---|
| 1L Amber | 2 | Cool to 4C | 8270C | 1,4 Dioxane |
| 40 mL VOA | 3 | Cool to 4C HCl ph<2 | SW8260B | VOCs |

## NOTABLE OBSERVATIONS

| PID READINGS | SAMPLE CHARACTERISTICS | MISCELLANEOUS |
|---|---|---|
| 1st 0.0 | COLOR: | |
| 2nd | ODOR: | |
| | OTHER: | |

pH ~~6.96~~ 6.94 Temperature 15.03 (C) Dissolved Oxygen 0.53 (mg/L) Specific Conductivity 1.185 ~~(umhos/cm)~~ mS/cm

Iron — (mg/L) Oxidation/Reduction Potential 51 (mv) Turbidity 24 (NTU)

## GENERAL INFORMATION

WEATHER: SUN/CLEAR X OVERCAST/RAIN _____ WIND DIRECTION _____ AMBIENT TEMPERATURE 80°F

SHIPMENT VIA: FEDEX _____ HAND DELIVER ___x___ COURIER _____ OTHER _____

SHIPPED TO: ~~Accutest Laboratories of Northeast - Marlboro, MA~~ Alpha Analytical Albany, NY

COMMENTS:

SAMPLER: MIKE JACKSON OBSERVER: George Riker

| MATRIX TYPE CODES | | SAMPLING METHOD CODES | |
|---|---|---|---|
| DC=DRILL CUTTINGS | SL=SLUDGE | B=BAILER | G=GRAB |
| WG=GROUND WATER | SO=SOIL | BP=BLADDER PUMP | HA=HAND AUGER |
| LH=HAZARDOUS LIQUID WASTE | GS=SOIL GAS | PP=PERISTALIC PUMP | H=HOLLOW STEM AUGER |
| SH=HAZRDOUS SOLID WASTE | WS=SURFACE WATER | CS=COMPOSITE SAMPLE | HP=HYDRO PUNCH |
| SE=SEDIMENT | SW=SWAB/WIPE | C=CONTINUOUS FLIGHT AUGER | SS=SPLIT SPOON |
| | | DT=DRIVEN TUBE | SP=SUBMERSIBLE PUMP |

*This page intentionally left blank.*

# GROUNDWATER FIELD SAMPLING DATA SHEET

| | |
|---|---|
| Well No.: DW-1 | Location: AFP59 |
| Sampler(s): G. Riker | Project Name: AFP59 2012 GWS |
| Well Depth: 59.4 | Project #: AF7061 Date: 08.01.12 Time: 08:30 |
| DTW (ft): 18.16 DTP Top (ft): | Courier: ___FedEx ___UPS X Hand ___Other |
| MP Ht. Above/Below Ground Surface: | Sampling Method : BP |
| Condition of Bottom of Well: Hard | Type of Pump: Bladder Pump |
| Screen Interval FTOC(ft): (52 - 626421) | Weather (sun/clear, overcast/rain, wind direction, ambient temperature): |
| Well Diameter (in): ~~2~~ 4" PVC | PREDOM. CLOUDY |
| Placement of Pump Inlet (ft): 54 | UPPER 70's |
| | MOSTLY CALM |

## Field Parameters

| Time | Depth to Water (ft) | Flow Rate (L/m) | Total Volume (L) | pH | Temp (C) | Cond. (umhos/cm) | ORP (mv) | DO (mg/L) | Turb. (NTU) | Type, Size, and Amount of Sediment Discharged |
|---|---|---|---|---|---|---|---|---|---|---|
| 08:55 | 18.16 | .2 | Ø | 6.29 | 14.12 | 1.094 | 277.7 | 5.09 | | FAIRLY CLEAR ! |
| 09:00 | 18.19 | .2 | 1.0 | 6.26 | 14.09 | 1.321 | 274.2 | 3.22 | 38 | |
| 09:05 | 18.19 | .2 | 2.0 | 6.40 | 14.06 | 1.424 | 255.4 | 2.81 | 37 | |
| 09:10 | 18.19 | .2 | 3.0 | 6.53 | 14.02 | 1.481 | 241.0 | 2.62 | 37 | |
| 09:15 | 18.19 | .2 | 4.0 | 6.67 | 14.37 | 1.508 | 227.1 | 2.62 | 37 | |
| 09:20 | 18.19 | .2 | 5.0 | 6.77 | 14.35 | 1.529 | 203.9 | 2.63 | 30 | |
| 09:25 | 18.19 | .2 | 6.0 | 6.79 | 14.31 | 1.540 | 189.6 | 2.43 | 23 | |
| MP-10 CONTROLLER FAILED ! | | | | | | | | | | |
| RESTART MP-10 - 2541 | | | | | | | | | | |
| 09:43 | 18.19 | | | | | | | | | |
| 09:45 | 18.19 | .25 | 6.5 | 6.91 | 14.32 | 1.553 | 160.6 | 2.43 | | |
| 09:50 | 18.19 | .2 | 7.5 | 6.90 | 14.55 | 1.556 | 159.7 | 2.34 | ~~22~~ | |
| 09:55 | 18.19 | .2 | 8.5 | 6.91 | 14.40 | 1.551 | 156.1 | 2.36 | 26 | |
| 10:00 | 18.18 | .2 | 9.5 | 6.93 | 14.33 | 1.549 | 152.6 | 2.35 ~~2.33~~ | 22 | |
| 10:05 | 18.18 | .2 | 10.5 | 6.91 | 14.40 | 1.552 | 147.9 | 2.33 | 20 | |
| 10:10 | 18.18 | .2 | 11.5 | 6.92 | 14.41 | 1.553 | 145.3 | 2.35 | 19 | |

SAMPLED 10:13 - 10:27
DTW: 18.18

## Observations

| |
|---|
| Color: (Clear) Other (describe): |
| Odor: (None) Low Medium High Very Strong H2S Fuel-like |
| Notes: PUMP: S/N 19095 |
| LaMOTTE # - 01906 |
| YSI # 11507 |
| QUED WIZARD # 2006 / MP-10 - 1909 |
| SOLINST 100' : # 1028 |
| Signed/Sampler(s): |

## WELL INSPECTION AND GROUNDWATER LEVEL MEASUREMENT SHEET

WELL NUMBER: DW-1 PROJECT NAME: AFP59

DATE/TIME: 8/1/12 1030 CITY/STATE: Johnson City, NY

INSPECTED BY: George Riker Water Level Indicator Serial No.: Solinst 1028

VENT WELL

MONITORING WELL INSTRUMENT READING (VOCs): 0.0 ppm

WELL INSPECTION/GROUNDWATER LEVEL MEASUREMENT

| | |
|---|---|
| WELL DEPTH (FEET FROM TOP OF PVC) | 59.4 |
| WATER LEVEL DEPTH (FEET FROM TOP OF PVC) | 18.16 |
| PVC WELL STICK-UP (FEET, ABOVE GRADE) | 3.62 |
| PROTECTIVE CASING STICK-UP (FEET, AGS) | 3.83 |
| WELL DIAMETER (INCHES) | 4 |
| WELL CONSTRUCTION (PVC, STEEL, ETC.) | PVC |

| | | | |
|---|---|---|---|
| LOCKED UPON ARRIVAL? | (YES) | NO | (Lock on expandable cap) |
| LOCK REPLACED? | YES | (NO) | |
| OBSTRUCTIONS? | YES | (NO) | |
| DAMAGE TO WELL PAD/STICKUP/CASING, ETC? | YES | (NO) | (If YES, detail in comments below) |
| WELL RELABELED? | YES | (NO) | |
| WELL PHOTOGRAPHED? | (YES) | NO | |

GENERAL CONDITION/COMMENTS/RECOMMENDATIONS:

# FIELD SAMPLING REPORT

| | | | |
|---|---|---|---|
| LOCATION: | AFP59 | PROJECT NAME: | AFP59 2012 GWS |
| SITE: | AFP59 | PROJECT NO: | AF7061 |

## SAMPLE INFORMATION

SAMPLE ID: 59DW1WG1

DATE: 8-1-12 TIME: 1013

MATRIX TYPE: WG

SAMPLING METHOD: BP

LOT CONTROL #: ___ ___ ___ ___

(Ambient Blank # - Equipment Blank # - Trip Blank # - Cooler #)

CHAIN-OF-CUSTODY #: _____

SAMPLE BEG. DEPTH (FT): —

SAMPLE END DEPTH (FT): —

GRAB (X) COMPOSITE ( )

ENTER SAMPLE NUMBERS FOR QC SAMPLES/ BLANKS ASSOCIATED WITH THIS SAMPLE:

MATRIX SPIKE (MS): —

MATRIX SPIKE DUP (SD): —

FIELD DUP (FD): —

AMBIENT BLANK (AB): —

EQUIPMENT BLANK (EB): —

TRIP BLANK (TB): 59TB073112

| CONTAINER SIZE/TYPE | # | PRESERVATIVE/ PREPARATION | ANALYTICAL METHOD | ANALYSIS |
|---|---|---|---|---|
| 1L Amber | 2 | Cool to 4C | 8270C | 1,4 Dioxane |
| 40 mL VOA | 3 | Cool to 4C HCl ph<2 | SW8260B | VOCs |

## NOTABLE OBSERVATIONS

| PID READINGS | SAMPLE CHARACTERISTICS | MISCELLANEOUS |
|---|---|---|
| 1st 0.0 | COLOR: | |
| 2nd | ODOR: | |
| | OTHER: | |

pH 6.92 Temperature 14.41 (C) Dissolved Oxygen 2.35 (mg/L) Specific Conductivity 1,553 (umhos/cm)

Iron — (mg/L) Oxidation/Reduction Potential 145.3 (mv) Turbidity 19 (NTU)

## GENERAL INFORMATION

WEATHER: SUN/CLEAR ~~CLEAR~~ OVERCAST RAIN _____ WIND DIRECTION _____ AMBIENT TEMPERATURE 70's

SHIPMENT VIA: FEDEX _____ HAND DELIVER x COURIER _____ OTHER _____

SHIPPED TO: ~~Accutest Laboratories of Northeast - Marlboro, MA~~ Alpha Analytical Albany, NY

COMMENTS:

SAMPLER: George Riker OBSERVER: MIKE JACKSON

**MATRIX TYPE CODES**

| | |
|---|---|
| DC=DRILL CUTTINGS | SL=SLUDGE |
| WG=GROUND WATER | SO=SOIL |
| LH=HAZARDOUS LIQUID WASTE | GS=SOIL GAS |
| SH=HAZRDOUS SOLID WASTE | WS=SURFACE WATER |
| SE=SEDIMENT | SW=SWAB/WIPE |

**SAMPLING METHOD CODES**

| | |
|---|---|
| B=BAILER | G=GRAB |
| BP=BLADDER PUMP | HA=HAND AUGER |
| PP=PERISTALIC PUMP | H=HOLLOW STEM AUGER |
| CS=COMPOSITE SAMPLE | HP=HYDRO PUNCH |
| C=CONTINUOUS FLIGHT AUGER | SS=SPLIT SPOON |
| DT=DRIVEN TUBE | SP=SUBMERSIBLE PUMP |

*This page intentionally left blank.*

# GROUNDWATER FIELD SAMPLING DATA SHEET

| | |
|---|---|
| Well No.: SW-1 | Location: AFP59 |
| Sampler(s): G. RIKER | Project Name: AFP59 2012 GWS |
| Well Depth: 28.35 | Project #: AF7061 Date: 08.01.12 Time: 10:30 |
| DTW (ft): 18.13 DTP Top (ft): | Courier: ___FedEx ___UPS X Hand ___Other |
| MP Ht. Above/Below Ground Surface: | Sampling Method : BP |
| Condition of Bottom of Well: HARD | Type of Pump: Bladder Pump |
| Screen Interval FTOC(ft): (15.74 - 25.74285 | Weather (sun/clear, overcast/rain, wind direction, ambient temperature): |
| Well Diameter (in): ~~8~~ 2" PVC | OVERCAST; MOSTLY CALM; UPPER 70'S |
| Placement of Pump Inlet (ft): 23.5 | |

## Field Parameters

| Time | Depth to Water (ft) | Flow Rate (L/m) | Total Volume (L) | pH | Temp (C) | Cond. (umhos/cm) | ORP (mv) | DO (mg/L) | Turb. (NTU) | Type, Size, and Amount of Sediment Discharged |
|---|---|---|---|---|---|---|---|---|---|---|
| 10:50 | 18.14 | | Ø | 6.96 | 15.44 | 1.496 | 174.8 | 2.99 | | CLEAR |
| 10:55 | 18.18 | .225 | 1.13 | 6.94 | 14.57 | 1.490 | 169.5 | 1.18 | 13 | |
| 11:00 | 18.16 | .225 | 2.25 | 6.96 | 14.77 | 1.498 | 156.4 | 0.85 | 12 | |
| 11:05 | 18.16 | .2 | 3.25 | 6.98 | 14.59 | 1.496 | 148.8 | 0.94 | 11 | |
| 11:10 | 18.16 | .2 | 4.25 | 6.97 | 14.59 | 1.496 | 144.3 | 0.80 | 9.6 | |
| 11:15 | 18.17 | .2 | 5.25 | 6.98 | 14.53 | 1.495 | 136.5 | 0.83 | 7.5 | |
| 11:20 | 18.16 | .2 | 6.25 | 6.97 | 14.56 | 1.498 | 130.9 | 0.75 | 6.7 | |
| 11:25 | 18.17 | .2 | 7.25 | 6.99 | 14.54 | 1.498 | 126.1 | 0.80 | 5.8 | |
| 11:30 | 18.17 | .2 | 8.25 | 6.98 | 14.58 | 1.501 | 119.9 | 0.76 | 5.0 | |
| SAMPLED 11:33 - 11:46 | | | | | | | | | | |
| DTW: 18:16 | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |

## Observations

| |
|---|
| Color: (Clear) Other (describe): |
| Odor: (None) Low Medium High Very Strong H2S Fuel-like |
| Notes: PUMP #18731 (PINE) |
| LaMOTTE # 01906 |
| YSI # 11507 |
| OAKTON/HEAD #2006 / MP-10-2541 |
| SOLINST 100' # 1028 |
| Signed/Sampler(s): |

## WELL INSPECTION AND GROUNDWATER LEVEL MEASUREMENT SHEET

WELL NUMBER: SW-1 PROJECT NAME: AFP59

DATE/TIME: 8/1/12 1150 CITY/STATE: Johnson City, NY

INSPECTED BY: George Riker Water Level Indicator Serial No.: SOLONST #1028

VENT WELL

MONITORING WELL INSTRUMENT READING (VOCs): 0.0 ppm

WELL INSPECTION/GROUNDWATER LEVEL MEASUREMENT

| | |
|---|---|
| WELL DEPTH (FEET FROM TOP OF PVC) | 28.35 |
| WATER LEVEL DEPTH (FEET FROM TOP OF PVC) | 18.13 |
| PVC WELL STICK-UP (FEET, ABOVE GRADE) | 3.45 |
| PROTECTIVE CASING STICK-UP (FEET, AGS) | 3.85 |
| WELL DIAMETER (INCHES) | 2 |
| WELL CONSTRUCTION (PVC, STEEL, ETC.) | PVC |

| | | | |
|---|---|---|---|
| LOCKED UPON ARRIVAL? | (YES) | NO | (expandable CAP) |
| LOCK REPLACED? | YES | (NO) | |
| OBSTRUCTIONS? | YES | (NO) | |
| DAMAGE TO WELL PAD/STICKUP/CASING, ETC? | YES | (NO) | (If YES, detail in comments below) |
| WELL RELABELED? | YES | (NO) | |
| WELL PHOTOGRAPHED? | (YES) | NO | |

GENERAL CONDITION/COMMENTS/RECOMMENDATIONS: CUT OFF ~~Ad~~ lock on stickup

# FIELD SAMPLING REPORT

| | | | |
|---|---|---|---|
| LOCATION: | AFP59 | PROJECT NAME: | AFP59 2012 GWS |
| SITE: | AFP59 | PROJECT NO: | AF7061 |

## SAMPLE INFORMATION

SAMPLE ID: 59SW1WG1

DATE: 8-1-12 TIME: MS 1150 1133

MATRIX TYPE: WG

SAMPLING METHOD: BP

LOT CONTROL #: ___ ___ ___ ___

(Ambient Blank # - Equipment Blank # - Trip Blank # - Cooler #)

CHAIN-OF-CUSTODY #: _____

SAMPLE BEG. DEPTH (FT): —

SAMPLE END DEPTH (FT): —

GRAB (X) COMPOSITE ( )

ENTER SAMPLE NUMBERS FOR QC SAMPLES/ BLANKS ASSOCIATED WITH THIS SAMPLE:

MATRIX SPIKE (MS): —

MATRIX SPIKE DUP (SD): —

FIELD DUP (FD): —

AMBIENT BLANK (AB): —

EQUIPMENT BLANK (EB): —

TRIP BLANK (TB): SGTB073112

| CONTAINER SIZE/TYPE | # | PRESERVATIVE/ PREPARATION | ANALYTICAL METHOD | ANALYSIS |
|---|---|---|---|---|
| 1L Amber | 2 | Cool to 4C | 8270C | 1,4 Dioxane |
| 40 mL VOA | 3 | Cool to 4C HCl ph<2 | SW8260B | VOCs |

## NOTABLE OBSERVATIONS

| PID READINGS | SAMPLE CHARACTERISTICS | MISCELLANEOUS |
|---|---|---|
| 1st 0.0 | COLOR: | |
| 2nd | ODOR: | |
| | OTHER: | |

pH 6.98 Temperature 14.58 (C) Dissolved Oxygen 0.76 (mg/L) Specific Conductivity 1.501 (umhos/cm)

Iron — (mg/L) Oxidation/Reduction Potential 119.9 (mv) Turbidity 5.0 (NTU)

## GENERAL INFORMATION

WEATHER: SUN/CLEAR _____ OVERCAST/RAIN _____ WIND DIRECTION _____ AMBIENT TEMPERATURE upper 70's

SHIPMENT VIA: FEDEX _____ HAND DELIVER ___x___ COURIER _____ OTHER _____

SHIPPED TO: ~~Accutest Laboratories of Northeast Marlboro, MA~~ Alpha Analytical Albany, NY

COMMENTS:

SAMPLER: George Aiken OBSERVER: Mike Jackson

**MATRIX TYPE CODES**

| | |
|---|---|
| DC=DRILL CUTTINGS | SL=SLUDGE |
| WG=GROUND WATER | SO=SOIL |
| LH=HAZARDOUS LIQUID WASTE | GS=SOIL GAS |
| SH=HAZRDOUS SOLID WASTE | WS=SURFACE WATER |
| SE=SEDIMENT | SW=SWAB/WIPE |

**SAMPLING METHOD CODES**

| | |
|---|---|
| B=BAILER | G=GRAB |
| BP=BLADDER PUMP | HA=HAND AUGER |
| PP=PERISTALIC PUMP | H=HOLLOW STEM AUGER |
| CS=COMPOSITE SAMPLE | HP=HYDRO PUNCH |
| C=CONTINUOUS FLIGHT AUGER | SS=SPLIT SPOON |
| DT=DRIVEN TUBE | SP=SUBMERSIBLE PUMP |

*This page intentionally left blank.*

# GROUNDWATER FIELD SAMPLING DATA SHEET

| | |
|---|---|
| Well No.: DW-3 | Location: AFP59 |
| Sampler(s): G. Rikel Ludwig Van Beethoven | Project Name: AFP59 2012 GWS |
| Well Depth: 85 | Project #: AF7061 Date: 08.01.12 Time: 13:30 |
| DTW (ft): 17.14 DTP Top (ft): | Courier: ___FedEx ___UPS X Hand ___Other |
| MP Ht. Above/Below Ground Surface: | Sampling Method : BP |
| Condition of Bottom of Well: soft | Type of Pump: Bladder Pump |
| Screen Interval FTOC(ft): (67.58 - 87.58867) | Weather (sun/clear, overcast/rain, wind direction, ambient temperature): |
| Well Diameter (in): ~~6~~ 4 | OVERCAST; HUMID; PERIODIC BREEZES |
| Placement of Pump Inlet (ft): 79 | |

## Field Parameters

| Time | Depth to Water (ft) | Flow Rate (L/m) | Total Volume (L) | pH | Temp. (C) | Cond. (umhos/cm) | ORP (mv) | DO (mg/L) | Turb. (NTU) | Type, Size, and Amount of Sediment Discharged |
|---|---|---|---|---|---|---|---|---|---|---|
| 13:45 | 17.16 | .2 | ∅ | 8.11 | 16.73 | 1.503 | 121.0 | 3.48 | 210 | CASING SIDE IS DIRTY!! |
| 13:50 | 17.16 | .2 | 1.0 | 6.63 | 15.52 | 1.360 | -11.1 | 0.69 | 140 | |
| 13:55 | 17.15 | .2 | 2.0 | 6.64 | 15.34 | 1.333 | -17.8 | 0.59 | 190 | |
| 14:00 | 17.16 | .2 | 3.0 | 6.73 | 15.28 | 1.328 | -26.4 | 0.55 | 180 | |
| 14:05 | 17.16 | .2 | 4.0 | 6.81 | 15.44 | 1.332 | -32.4 | 0.59 | 200 | |
| 14:10 | 17.15 | .2 | 5.0 | 6.88 | 15.35 | 1.333 | -32.5 | 0.56 | 190 | |
| 14:15 | 17.16 | .2 | 6.0 | 6.91 | 15.30 | 1.332 | -38.5 | 0.60 | 180 | |
| 14:20 | 17.15 | .2 | 7.0 | 6.94 | 15.48 | 1.335 | -33.8 | 0.52 | 160 | |
| 14:25 | 17.15 | .2 | 8.0 | 6.96 | 15.44 | 1.332 | -38.5 | 0.56 | 150 | |
| 14:30 | 17.15 | .2 | 9.0 | 6.96 | 15.24 | 1.326 | -43.2 | 0.52 | 110 | |
| 14:35 | 17.15 | .2 | 10.0 | 6.98 | 15.45 | 1.332 | -43.2 | 0.48 | 100 | |
| 14:40 | 17.15 | .2 | 11.0 | 7.01 | 15.45 | 1.328 | -45.7 | 0.51 | 85 | |
| 14:45 | 17.16 | .2 | 12.0 | 7.02 | 15.15 | 1.322 | -41.0 | 0.45 | 65 | |
| 14:50 | 17.16 | .2 | 13.0 | 7.01 | 15.13 | 1.318 | -36.0 | 0.40 | 80 | |
| 14:55 | 17.15 | .2 | 14.0 | 7.01 | 15.12 | 1.319 | -36.9 | 0.40 | 85 | |
| 15:00 | 17:15 | .2 | 15.0 | 7.01 | 15.18 | 1.321 | -34.8 | 0.44 | 80 | |

SAMPLED: 15:02 - 15:12
DTW: 17.15'

## Observations

Color: Clear Other (describe):

Odor: (None) Low Medium High Very Strong H2S Fuel-like 3.1 PPM PID

Notes: Pump#10298

Solinst 100' - #1028

LaMotte: S/N 01906

YSI: #11507

QED WIZARD #2006 / MP-10 - 2541

Signed/Sampler(s):

## WELL INSPECTION AND GROUNDWATER LEVEL MEASUREMENT SHEET

WELL NUMBER: DW-3 PROJECT NAME: AFP59

DATE/TIME: 8-1-12 1515 CITY/STATE: Johnson City, NY

INSPECTED BY: George Riker Water Level Indicator Serial No.: SOLINST #1028

VENT WELL

MONITORING WELL INSTRUMENT READING (VOCs): 0.4 ppm

WELL INSPECTION/GROUNDWATER LEVEL MEASUREMENT

| | |
|---|---|
| WELL DEPTH (FEET FROM TOP OF PVC) | 85 |
| WATER LEVEL DEPTH (FEET FROM TOP OF PVC) | 17.14 |
| PVC WELL STICK-UP (FEET, ABOVE GRADE) | — (FLUSH MOUNT) |
| PROTECTIVE CASING STICK-UP (FEET, AGS) | — (FLUSH MOUNT) |
| WELL DIAMETER (INCHES) | 4 |
| WELL CONSTRUCTION (PVC, STEEL, ETC.) | PVC |

| | | | |
|---|---|---|---|
| LOCKED UPON ARRIVAL? | YES | (NO) | |
| LOCK REPLACED? | YES | (NO) | |
| OBSTRUCTIONS? | YES | (NO) | |
| DAMAGE TO WELL PAD/STICKUP/CASING, ETC? | YES | (NO) | (If YES, detail in comments below) |
| WELL RELABELED? | YES | (NO) | |
| WELL PHOTOGRAPHED? | (YES) | NO | |

GENERAL CONDITION/COMMENTS/RECOMMENDATIONS:

# FIELD SAMPLING REPORT

| | | | |
|---|---|---|---|
| LOCATION: | AFP59 | PROJECT NAME: | AFP59 2012 GWS |
| SITE: | AFP59 | PROJECT NO: | AF7061 |

## SAMPLE INFORMATION

SAMPLE ID: 59DW3WG1 DATE: 8-1-12 TIME: 1502

MATRIX TYPE: WG

SAMPLING METHOD: BP

LOT CONTROL #: ___ ___ ___ ___

(Ambient Blank # - Equipment Blank # - Trip Blank # - Cooler #)

CHAIN-OF-CUSTODY #: _____

SAMPLE BEG. DEPTH (FT): —

SAMPLE END DEPTH (FT): —

GRAB (X) COMPOSITE ( )

ENTER SAMPLE NUMBERS FOR QC SAMPLES/ BLANKS ASSOCIATED WITH THIS SAMPLE:

MATRIX SPIKE (MS): —

MATRIX SPIKE DUP (SD): —

FIELD DUP (FD): —

AMBIENT BLANK (AB): —

EQUIPMENT BLANK (EB): —

TRIP BLANK (TB): 59TB073112

| CONTAINER SIZE/TYPE | # | PRESERVATIVE/ PREPARATION | ANALYTICAL METHOD | ANALYSIS |
|---|---|---|---|---|
| 40 mL VOA | 3 | Cool to 4C HCl ph<2 | SW8260B | VOCs |
| 1L Amber | 2 | Cool to 4C | 8270C | 1,4 Dioxane |

## NOTABLE OBSERVATIONS

| PID READINGS | SAMPLE CHARACTERISTICS | MISCELLANEOUS |
|---|---|---|
| 1st 0.4 | COLOR: | |
| 2nd | ODOR: | |
| | OTHER: | |

pH 7.01 Temperature 15.18 (C) Dissolved Oxygen 0.44 (mg/L) Specific Conductivity 1.321 (umhos/cm)

Iron → (mg/L) Oxidation/Reduction Potential -34.8 (mv) Turbidity 80 (NTU)

## GENERAL INFORMATION

WEATHER: SUN/CLEAR _____ (OVERCAST) RAIN _____ WIND DIRECTION _____ AMBIENT TEMPERATURE 80s

SHIPMENT VIA: FEDEX _____ HAND DELIVER ___x___ COURIER _____ OTHER _____

SHIPPED TO: ~~Accutest Laboratories of Northeast - Marlboro, MA~~ Alpha Analytical Albany, NY

COMMENTS:

SAMPLER: George Riker OBSERVER: MIKE Jackson

**MATRIX TYPE CODES**

| | |
|---|---|
| DC=DRILL CUTTINGS | SL=SLUDGE |
| WG=GROUND WATER | SO=SOIL |
| LH=HAZARDOUS LIQUID WASTE | GS=SOIL GAS |
| SH=HAZRDOUS SOLID WASTE | WS=SURFACE WATER |
| SE=SEDIMENT | SW=SWAB/WIPE |

**SAMPLING METHOD CODES**

| | |
|---|---|
| B=BAILER | G=GRAB |
| BP=BLADDER PUMP | HA=HAND AUGER |
| PP=PERISTALIC PUMP | H=HOLLOW STEM AUGER |
| CS=COMPOSITE SAMPLE | HP=HYDRO PUNCH |
| C=CONTINUOUS FLIGHT AUGER | SS=SPLIT SPOON |
| DT=DRIVEN TUBE | SP=SUBMERSIBLE PUMP |

*This page intentionally left blank.*

# GROUNDWATER FIELD SAMPLING DATA SHEET

| | |
|---|---|
| Well No.: SW-3 | Location: AFP59 |
| Sampler(s): G. Rikke | Project Name: AFP59 2012 GWS |
| Well Depth: ~~20~~ 29.63 | Project #: AF7061 Date: 08.01.12 Time: 15:30 |
| DTW (ft): 20' DTP Top (ft): | Courier: ___FedEx ___UPS X Hand ___Other |
| MP Ht. Above/Below Ground Surface: | Sampling Method : BP |
| Condition of Bottom of Well: HARD | Type of Pump: Bladder Pump |
| Screen Interval FTOC(ft): ~~17.68~~ 18.68 - 28.68295 | Weather (sun/clear, overcast/rain, wind direction, ambient temperature): |
| Well Diameter (in): ~~8~~ 2" | PTLY. SUNNY HUMID VERY LT. BREEZE |
| Placement of Pump Inlet (ft): 24.5 | |

## Field Parameters

| Time | Depth to Water (ft) | Flow Rate (L/m) | Total Volume (L) | pH | Temp. (C) | Cond. (umhos/cm) | ORP (mv) | DO (mg/L) | Turb. (NTU) | Type, Size, and Amount of Sediment Discharged |
|---|---|---|---|---|---|---|---|---|---|---|
| 15:40 | 20.00 | .225 | ∅ | 7.06 | 15.72 | 0.996 | 106.7 | 2.55 | | CLEAR |
| 15:45 | 20.00 | .225 | 1.13 | 6.95 | 15.81 | 1.002 | 98.4 | 1.80 ~~98.4~~ % | 14 | |
| 15:50 | 20.01 | .225 | 2.25 | 7.01 | 15.71 | 1.004 | 88.9 | 1.56 | 1.5 | |
| 15:55 | 20.01 | .225 | 3.38 | 7.03 | 15.18 | 0.996 | 79.4 | 1.52 | 0.95 | |
| 16:00 | 20.01 | .225 | 4.5 | 6.99 | 14.96 | 0.987 | 77.8 | 1.42 | 0.85 | |
| 16:05 | 20.02 | .225 | 5.63 | 7.02 | 14.97 | 0.987 | 74.0 | 1.43 | 0.85 | |
| 16:10 | 20.02 | .225 | 6.75 | 7.04 | 14.87 | 0.985 | 66.5 | 1.47 | 0.75 | |
| 16:15 | 20.02 | .225 | 7.88 | 7.04 | 14.81 | 0.984 | 63.9 | 1.40 | 0.80 | |
| 16:20 | 20.02 | .225 | 9.0 | 7.04 | 14.83 | 0.984 | 60.8 | 1.40 | 0.75 | |
| SAMPLED | | 16:22 - 16:34 | | | | | | | | |
| DTW - 20.02' | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |

## Observations

Color: (Clear) Other (describe):

Odor: (None) Low Medium High Very Strong H2S Fuel-like 0.4 ppm PID

Notes: PUMP # 18731

SOLINST 100': # 1028

LaMOTTE S/N 01906

YSI # 11507

GED WIZARD CONTROLLER #2006 / MP-10-2541

Signed/Sampler(s): [signature]

## WELL INSPECTION AND GROUNDWATER LEVEL MEASUREMENT SHEET

WELL NUMBER: SW-3 PROJECT NAME: AFP59

DATE/TIME: 8/1/12 1640 CITY/STATE: Johnson City, NY

INSPECTED BY: George Riker Water Level Indicator Serial No.: SOLINST #1028

VENT WELL

MONITORING WELL INSTRUMENT READING (VOCs): 3.1 ppm

WELL INSPECTION/GROUNDWATER LEVEL MEASUREMENT

| | |
|---|---|
| WELL DEPTH (FEET FROM TOP OF PVC) | 29.63 |
| WATER LEVEL DEPTH (FEET FROM TOP OF PVC) | 20.00 |
| PVC WELL STICK-UP (FEET, ABOVE GRADE) | 2.10 |
| PROTECTIVE CASING STICK-UP (FEET, AGS) | 2.34 |
| WELL DIAMETER (INCHES) | 2 |
| WELL CONSTRUCTION (PVC, STEEL, ETC.) | PVC |

| | | | |
|---|---|---|---|
| LOCKED UPON ARRIVAL? | (YES) | NO | (expandable cap) |
| LOCK REPLACED? | YES | (NO) | |
| OBSTRUCTIONS? | YES | (NO) | |
| DAMAGE TO WELL PAD/STICKUP/CASING, ETC? | YES | (NO) | (If YES, detail in comments below) |
| WELL RELABELED? | YES | (NO) | |
| WELL PHOTOGRAPHED? | (YES) | NO | |

GENERAL CONDITION/COMMENTS/RECOMMENDATIONS:

No lock on protective casing cap.

# FIELD SAMPLING REPORT

| | | | |
|---|---|---|---|
| LOCATION: | AFP59 | PROJECT NAME: | AFP59 2012 GWS |
| SITE: | AFP59 | PROJECT NO: | AF7061 |

## SAMPLE INFORMATION

SAMPLE ID: 59SW3WG1 DATE: 8-1-12 TIME: 1622

MATRIX TYPE: WG

SAMPLING METHOD: BP

LOT CONTROL #: ___ ___ ___ ___

(Ambient Blank # - Equipment Blank # - Trip Blank # - Cooler #)

CHAIN-OF-CUSTODY #: _____

SAMPLE BEG. DEPTH (FT): —

SAMPLE END DEPTH (FT): —

GRAB (X) COMPOSITE ( )

ENTER SAMPLE NUMBERS FOR QC SAMPLES/ BLANKS ASSOCIATED WITH THIS SAMPLE:

MATRIX SPIKE (MS): —

MATRIX SPIKE DUP (SD): —

FIELD DUP (FD): —

AMBIENT BLANK (AB): —

EQUIPMENT BLANK (EB): —

TRIP BLANK (TB): 59TB073112

| CONTAINER SIZE/TYPE | # | PRESERVATIVE/ PREPARATION | ANALYTICAL METHOD | ANALYSIS |
|---|---|---|---|---|
| 1L Amber | 2 | Cool to 4C | 8270C | 1,4 Dioxane |
| 40 mL VOA | 3 | Cool to 4C HCl ph<2 | SW8260B | VOCs |

## NOTABLE OBSERVATIONS

| PID READINGS | SAMPLE CHARACTERISTICS | MISCELLANEOUS |
|---|---|---|
| 1st 3.1 | COLOR: | |
| 2nd | ODOR: | |
| | OTHER: | |

pH 7.04 Temperature 14.83 (C) Dissolved Oxygen 4.40 (mg/L) Specific Conductivity 0.984 (umhos/cm)
Iron — (mg/L) Oxidation/Reduction Potential 60.8 (mv) Turbidity 0.75 (NTU)

## GENERAL INFORMATION

WEATHER: (PARTLY SUNNY) CLEAR _____ OVERCAST/RAIN _____ WIND DIRECTION _____ AMBIENT TEMPERATURE 80S

SHIPMENT VIA: FEDEX _____ HAND DELIVER ___x___ COURIER _____ OTHER _____

SHIPPED TO: ~~Accutest Laboratories of Northeast Marlboro, MA~~ Alpha Analytical Albany, NY

COMMENTS:

SAMPLER: George Riker OBSERVER: MIKE JACKSON

**MATRIX TYPE CODES**

| | |
|---|---|
| DC=DRILL CUTTINGS | SL=SLUDGE |
| WG=GROUND WATER | SO=SOIL |
| LH=HAZARDOUS LIQUID WASTE | GS=SOIL GAS |
| SH=HAZRDOUS SOLID WASTE | WS=SURFACE WATER |
| SE=SEDIMENT | SW=SWAB/WIPE |

**SAMPLING METHOD CODES**

| | |
|---|---|
| B=BAILER | G=GRAB |
| BP=BLADDER PUMP | HA=HAND AUGER |
| PP=PERISTALIC PUMP | H=HOLLOW STEM AUGER |
| CS=COMPOSITE SAMPLE | HP=HYDRO PUNCH |
| C=CONTINUOUS FLIGHT AUGER | SS=SPLIT SPOON |
| DT=DRIVEN TUBE | SP=SUBMERSIBLE PUMP |

*This page intentionally left blank.*

# GROUNDWATER FIELD SAMPLING DATA SHEET

| | |
|---|---|
| Well No.: URS-5S | Location: AFP59 |
| Sampler(s): MIKE JACKSON | Project Name: AFP59 2012 GWS |
| Well Depth: 68 | Project #: AF7061 Date: 8-1-12 Time: 1100 |
| DTW (ft): 24.15 DTP Top (ft): | Courier: ____FedEx ____UPS ____Hand ____Other |
| MP Ht. Above/Below Ground Surface: | Sampling Method : BP |
| Condition of Bottom of Well: | Type of Pump: Bladder Pump |
| Screen Interval FTOC(ft): ( - ) | Weather (sun/clear, overcast/rain, wind direction, ambient temperature): |
| Well Diameter (in): 2" (SS) | OVERCAST, HUMID, 78° |
| Placement of Pump Inlet (ft): ~~58.6~~ 59' | |

+/-0.1 +/-0.5 +/-3% +/-10 +/-10

**Field Parameters**

| Time | Depth to Water (ft) | Flow Rate (L/m) | Total Volume (L) | pH | Temp. (C) | Cond. (umhos/cm) | ORP (mv) | DO (mg/L) | Turb. (NTU) | Type, Size, and Amount of Sediment Discharged |
|---|---|---|---|---|---|---|---|---|---|---|
| 1113 | 24.15 | 0.25 | 0.5 | 6.68 | 13.43 | 1427 | 188.4 | 1.58 | 18 | |
| 1118 | 24.15 | 0.25 | ~~1.750~~ | 6.84 | 13.36 | 1428 | 171.6 | 1.47 | 83 | |
| 1123 | 24.15 | 0.25 | ~~0.750~~ | 6.97 | 13.34 | 1427 | 157.6 | 1.23 | 73.3 | |
| 1128 | 24.15 | 0.25 | ~~0.875~~ | 6.96 | 13.27 | 1425 | 149.5 | 1.32 | 41.1 | |
| 1133 | 24.15 | 0.25 | ~~1.00~~ | 6.98 | 13.24 | 1423 | 1425 | 1.37 | 38.8 | |
| 1139 | 24.15 | 0.25 | ~~1.25~~ | 6.99 | 13.18 | 1424 | 136.9 | 1.20 | 40.2 | |
| 1143 | 24.15 | 0.25 | ~~1.50~~ | 6.99 | 13.16 | 1425 | 130.3 | 1.14 | 38.1 | |
| 1148 | 24.15 | 0.25 | 8.25 | 6.99 | 13.14 | 1423 | 125.5 | 1.11 | 28.1 | |
| 1153 | 24.15 | 0.25 | 9.00 | 6.99 | 13.14 | 1423 | 122.1 | 1.08 | 26.8 | |
| 1158 | 24.15 | 0.25 | 10.25 | 6.99 | 1316 | 1423 | 117.2 | 1.29 | 24.3 | |
| 1200 | COLLECT | | SAMPLES (59URS5SW6.1) | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |

POINT VOLUME
2.00
3.25
4.50
5.75
7.00
8.25
9.50

## Observations

| |
|---|
| Color: (Clear) Other (describe): |
| Odor: (None) Low Medium High Very Strong H2S Fuel-like |
| Notes: Pump # 10298 |
| PUMP BOTTOM ~~GOES~~ CANNOT GET BELOW 60.6' TOC (INTAKE ABOVE BOTTOM) |
| ~~Intake placed at~~ ~~58.6~~ 59' YSI 556 (#05B17AA) |
| DTW ~~after~~ PUMP INSTALL = ~~24~~.15 MP10 (#04322) |
| LAMOTTE 2020we (1869-0413) SOLINST model 101 (#47088) |
| Signed/Sampler(s): |

## WELL INSPECTION AND GROUNDWATER LEVEL MEASUREMENT SHEET

| | | | |
|---|---|---|---|
| WELL NUMBER: | URS-5S | PROJECT NAME: | AFP59 |
| DATE/TIME: | 8-1-12 | CITY/STATE: | Johnson City, NY |
| INSPECTED BY: | MIKE JACKSON | Water Level Indicator Serial No.: | SOLINST 101 (#47088) |

VENT WELL

MONITORING WELL INSTRUMENT READING (VOCs): 0.0 ppm

WELL INSPECTION/GROUNDWATER LEVEL MEASUREMENT

| | |
|---|---|
| WELL DEPTH (FEET FROM TOP OF PVC) | 68' |
| WATER LEVEL DEPTH (FEET FROM TOP OF PVC) | 24.15 |
| PVC WELL STICK-UP (FEET, ABOVE GRADE) | — |
| PROTECTIVE CASING STICK-UP (FEET, AGS) | — |
| WELL DIAMETER (INCHES) | 2 |
| WELL CONSTRUCTION (PVC, STEEL, ETC.) | STAINLESS STEEL |

| | | | |
|---|---|---|---|
| LOCKED UPON ARRIVAL? | (YES) | NO | |
| LOCK REPLACED? | YES | (NO) | |
| OBSTRUCTIONS? | YES | (NO) | (Slight obstruction to pump at 60.6' TOC) |
| DAMAGE TO WELL PAD/STICKUP/CASING, ETC? | YES | (NO) | (If YES, detail in comments below) |
| WELL RELABELED? | YES | (NO) | |
| WELL PHOTOGRAPHED? | (YES) | NO | |

GENERAL CONDITION/COMMENTS/RECOMMENDATIONS: FLUSH MOUNT 1.0

TOC 1.05 Below Ground Surface.
TOC 1.10 Below 2nd down manhole cover.
Original Manhole cover 0.7 feet Below Grade.
Residential owner Body indicated Major
Owner possibly did not compact Area properly

# FIELD SAMPLING REPORT

| | | | |
|---|---|---|---|
| LOCATION: | AFP59 | PROJECT NAME: | AFP59 2012 GWS |
| SITE: | AFP59 | PROJECT NO: | AF7061 |

## SAMPLE INFORMATION

SAMPLE ID: 59URS5SWG1 DATE: 8-1-12 TIME: 1200

MATRIX TYPE: WG

SAMPLING METHOD: BP

LOT CONTROL #: ___ ___ ___ ___

(Ambient Blank # - Equipment Blank # - Trip Blank # - Cooler #)

CHAIN-OF-CUSTODY #: _____

SAMPLE BEG. DEPTH (FT): —

SAMPLE END DEPTH (FT): —

GRAB X COMPOSITE ( )

ENTER SAMPLE NUMBERS FOR QC SAMPLES/ BLANKS ASSOCIATED WITH THIS SAMPLE:

MATRIX SPIKE (MS): —

MATRIX SPIKE DUP (SD): —

FIELD DUP (FD): —

AMBIENT BLANK (AB): —

EQUIPMENT BLANK (EB): —

TRIP BLANK (TB): 59TB073112

| CONTAINER SIZE/TYPE | # | PRESERVATIVE/ PREPARATION | ANALYTICAL METHOD | ANALYSIS |
|---|---|---|---|---|
| 40 mL VOA | 3 | Cool to 4C HCl ph<2 | SW8260B | VOCs 8260B |
| 1L Amber | 2 | Cool to 4C | 8270C | 1,4 Dioxane |

## NOTABLE OBSERVATIONS

| PID READINGS | SAMPLE CHARACTERISTICS | MISCELLANEOUS |
|---|---|---|
| 1st 0.0 | COLOR: | |
| 2nd | ODOR: | |
| | OTHER: | |

pH 6.99 Temperature 13.16 (C) Dissolved Oxygen 1.29 (mg/L) Specific Conductivity 1423 (umhos/cm)
Iron — (mg/L) Oxidation/Reduction Potential 117.2 (mv) Turbidity 24.3 (NTU)

## GENERAL INFORMATION

WEATHER: SUN/CLEAR _____ OVERCAST/RAIN _____ WIND DIRECTION _____ AMBIENT TEMPERATURE 78°F

SHIPMENT VIA: FEDEX _____ HAND DELIVER ___x___ COURIER _____ OTHER _____

SHIPPED TO: ~~Accutest Laboratories of Northeast - Marlboro, MA~~ Alpha Analytical Albany NY

COMMENTS:

SAMPLER: MIKE JACKSON OBSERVER: —

| MATRIX TYPE CODES | | SAMPLING METHOD CODES | |
|---|---|---|---|
| DC=DRILL CUTTINGS | SL=SLUDGE | B=BAILER | G=GRAB |
| WG=GROUND WATER | SO=SOIL | BP=BLADDER PUMP | HA=HAND AUGER |
| LH=HAZARDOUS LIQUID WASTE | GS=SOIL GAS | PP=PERISTALIC PUMP | H=HOLLOW STEM AUGER |
| SH=HAZRDOUS SOLID WASTE | WS=SURFACE WATER | CS=COMPOSITE SAMPLE | HP=HYDRO PUNCH |
| SE=SEDIMENT | SW=SWAB/WIPE | C=CONTINUOUS FLIGHT AUGER | SS=SPLIT SPOON |
| | | DT=DRIVEN TUBE | SP=SUBMERSIBLE PUMP |

*This page intentionally left blank.*

# GROUNDWATER FIELD SAMPLING DATA SHEET

| | |
|---|---|
| Well No.: SW-7 | Location: AFP59 |
| Sampler(s): MIKE JACKSON | Project Name: AFP59 2012 GWS |
| Well Depth: 28.62 | Project #: AF7061 Date: 8-1-12 Time: 1530 |
| DTW (ft): 20.28 DTP Top (ft): | Courier: ___FedEx ___UPS X Hand ___Other |
| MP Ht. Above/Below Ground Surface: | Sampling Method : BP |
| Condition of Bottom of Well: | Type of Pump: Bladder Pump |
| Screen Interval FTOC(ft): ~~23~~ 15.85 ( - 28.85) | Weather (sun/clear, overcast/rain, wind direction, ambient temperature): |
| Well Diameter (in): ~~8~~ | Partly cloudy, Humid, 90° |
| Placement of Pump Inlet (ft): 24.5 | |

**Field Parameters** +/-0.1 +/-0.15 +/-3% +/-10 +/-10

| Time | Depth to Water (ft) | Flow Rate (L/m) | Total Volume (L) | pH | Temp. (C) | Cond. (umhos/cm) | ORP (mv) | DO (mg/L) | Turb. (NTU) | Type, Size, and Amount of Sediment Discharged |
|---|---|---|---|---|---|---|---|---|---|---|
| 1553 | 20.28 | 0.2 | 0.25 | 6.74 | 17.61 | 1434 | 129.1 | 0.90 | 35.5 | |
| 1558 | 20.28 | 0.2 | 1.25 | 6.54 | 16.82 | 1435 | 120.8 | 0.63 | 30.5 | |
| 1603 | 20.28 | 0.2 | 2.25 | 6.58 | 16.82 | 1431 | 114.2 | 0.54 | 26.3 | |
| 1608 | 20.28 | 0.2 | 3.25 | 6.74 | 16.78 | 1430 | 101.3 | ~~0.47~~ | 22.1 | 0.53 DO |
| 1613 | 20.28 | 0.2 | 4.25 | 6.74 | 16.66 | 1429 | 99.2 | 0.50 | 18.4 | |
| 1618 | 20.28 | 0.2 | 5.25 | 6.75 | 16.69 | 1428 | 96.5 | 0.41 | 15.2 | |
| 1623 | 20.28 | 0.2 | 6.25 | 6.79 | 16.68 | 1427 | 93.2 | 0.39 | 11.7 | |
| 1625 | collect | | samples | | 595W7W61 | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |

## Observations

Color: (Clear) Other (describe):

Odor: (None) Low Medium High Very Strong H2S Fuel-like

Notes: Pump #19095 (QED 1.75-inch Sample Pro).
Collect Duplicate (590DUP01WG1) Sample Time: 0901
YSI 556 MPS (05B1766AA) ~~QED~~ MP10 (04322)
(Anotec 2220 we (1860-0412)
Solinst 101 WLI (47088)

Signed/Sampler(s): Michael D. Jackson

## WELL INSPECTION AND GROUNDWATER LEVEL MEASUREMENT SHEET

WELL NUMBER: SW-7 PROJECT NAME: AFP59

DATE/TIME: 8-1-12 1645 CITY/STATE: Johnson City, NY

INSPECTED BY: MIKE JACKSON Water Level Indicator Serial No.: SOLINST 47088

VENT WELL

MONITORING WELL INSTRUMENT READING (VOCs): 0.0 ppm

WELL INSPECTION/GROUNDWATER LEVEL MEASUREMENT

| | |
|---|---|
| WELL DEPTH (FEET FROM TOP OF PVC) | 28.62 |
| WATER LEVEL DEPTH (FEET FROM TOP OF PVC) | 20.28 |
| PVC WELL STICK-UP (FEET, ABOVE GRADE) | 2.35 |
| PROTECTIVE CASING STICK-UP (FEET, AGS) | 2.65 |
| WELL DIAMETER (INCHES) | 2 |
| WELL CONSTRUCTION (PVC, STEEL, ETC.) | PVC |

| | | | |
|---|---|---|---|
| LOCKED UPON ARRIVAL? | (YES) | NO | (Expandable cap) |
| LOCK REPLACED? | YES | (NO) | |
| OBSTRUCTIONS? | YES | (NO) | |
| DAMAGE TO WELL PAD/STICKUP/CASING, ETC? | YES | (NO) | (If YES, detail in comments below) |
| WELL RELABELED? | YES | (NO) | |
| WELL PHOTOGRAPHED? | (YES) | NO | |

GENERAL CONDITION/COMMENTS/RECOMMENDATIONS:

NO LOCK ON STEEL PROTECTIVE CASING CAP.

# FIELD SAMPLING REPORT

| | | | |
|---|---|---|---|
| LOCATION: | AFP59 | PROJECT NAME: | AFP59 2012 GWS |
| SITE: | AFP59 | PROJECT NO: | AF7061 |

## SAMPLE INFORMATION

SAMPLE ID: 59SW7WG1 DATE: 8-1-12 TIME: 1625

MATRIX TYPE: WG

SAMPLING METHOD: BP

LOT CONTROL #: ___ ___ ___ ___

(Ambient Blank # - Equipment Blank # - Trip Blank # - Cooler #)

CHAIN-OF-CUSTODY #: _____

SAMPLE BEG. DEPTH (FT): —

SAMPLE END DEPTH (FT): —

GRAB (X) COMPOSITE ( )

ENTER SAMPLE NUMBERS FOR QC SAMPLES/ BLANKS ASSOCIATED WITH THIS SAMPLE:

MATRIX SPIKE (MS): —

MATRIX SPIKE DUP (SD): —

FIELD DUP (FD): 59DUP01WG1

AMBIENT BLANK (AB): 59AB080112

EQUIPMENT BLANK (EB): 59EB080112

TRIP BLANK (TB): 59TB073112

| CONTAINER SIZE/TYPE | # | PRESERVATIVE/ PREPARATION | ANALYTICAL METHOD | ANALYSIS |
|---|---|---|---|---|
| 40 mL VOA | 3 | Cool to 4C HCl ph<2 | SW8260B | VOCs |
| 1L Amber | 2 | Cool to 4C | 8270C | 1,4 Dioxane |

## NOTABLE OBSERVATIONS

| PID READINGS | SAMPLE CHARACTERISTICS | MISCELLANEOUS |
|---|---|---|
| 1st 0.0 | COLOR: | |
| 2nd | ODOR: | |
| | OTHER: | |

pH _____ Temperature _____(C) Dissolved Oxygen _____(mg/L) Specific Conductivity _____(umhos/cm)
Iron _____(mg/L) Oxidation/Reduction Potential _____(mv) Turbidity_____ (NTU)

## GENERAL INFORMATION

WEATHER: SUN/CLEAR _____ PARTLY CLOUDY OVERCAST/RAIN _____ WIND DIRECTION _____ AMBIENT TEMPERATURE 90°F

SHIPMENT VIA: FEDEX _____ HAND DELIVER ___x___ COURIER _____ OTHER _____

SHIPPED TO: ~~Accutest Laboratories of Northeast - Marlboro, MA~~ Alpha Analytical Albany, NY

COMMENTS:

SAMPLER: MIKE JACKSON OBSERVER: George Riker

| MATRIX TYPE CODES | | SAMPLING METHOD CODES | |
|---|---|---|---|
| DC=DRILL CUTTINGS | SL=SLUDGE | B=BAILER | G=GRAB |
| WG=GROUND WATER | SO=SOIL | BP=BLADDER PUMP | HA=HAND AUGER |
| LH=HAZARDOUS LIQUID WASTE | GS=SOIL GAS | PP=PERISTALIC PUMP | H=HOLLOW STEM AUGER |
| SH=HAZRDOUS SOLID WASTE | WS=SURFACE WATER | CS=COMPOSITE SAMPLE | HP=HYDRO PUNCH |
| SE=SEDIMENT | SW=SWAB/WIPE | C=CONTINUOUS FLIGHT AUGER | SS=SPLIT SPOON |
| | | DT=DRIVEN TUBE | SP=SUBMERSIBLE PUMP |

*This page intentionally left blank.*

# GROUNDWATER FIELD SAMPLING DATA SHEET

| | | |
|---|---|---|
| Well Name.: BM-121 | Project Name: AFP59 | LOCID: |
| Sampler(s): MIKE JACKSON | Project No.: AF7061 | |
| Well Depth: 56.04 (Max Sect.) | Date: 08.02.12 | Time: 08:00 |
| DTW (ft TOC): 27.51 | Screen Interval: N/A | |
| Well Diameter (in): 6" STEEL | Placement of Pump (ft TOC): 51 | |
| Type of Pump: QED 1.75-inch Sample Pro | Cloudy, Humid, 82° | |

## Field Parameters

L/min L +/-0.1 +/-0.5 +/-3% +/-10 +/-10

| Time | Depth to Water (ft) | Flow Rate ~~(gpm)~~ | Total Volume ~~(gal)~~ | pH | Temp (C) | Cond. ~~(umhos/cm)~~ mS/cm | ORP | D.O. (mg/L) | Turb. (N.T.U.) | Description |
|---|---|---|---|---|---|---|---|---|---|---|
| 0908 | 27.61 | 0.2 | 0.2 | 7.07 | 14.82 | 615 | -5.8 | 1.67 | 14.4 | |
| 0913 | 27.61 | 0.2 | 1.2 | 6.96 | 14.60 | 617 | -118.2 | 0.42 | 13.3 | |
| 0918 | 27.61 | 0.2 | 2.2 | 7.14 | 14.56 | 618 | -124.7 | 0.27 | 12.8 | |
| 0923 | 27.61 | 0.2 | 3.2 | 7.42 | 14.53 | 619 | -142.8 | 0.20 | 12.2 | |
| 0928 | 27.61 | 0.2 | 4.2 | 7.58 | 14.61 | 622 | -143.1 | 0.14 | 12.9 | |
| MS 0933 | 27.61 | 0.2 | 5.2 | 7.66 | 14.75 | 627 | -155.8 | 0.13 | 13.1 | |
| 0938 0944 | 27.61 | 0.2 | 6.2 | 7.68 | 14.75 | 632 | -156.2 | 0.12 | 12.5 | |
| 0943 | 27.61 | 0.2 | 7.2 | 7.66 | 14.73 | 639 | -133.8 | 0.07 | 13.4 | |
| 0948 | 27.61 | 0.2 | 8.2 | 7.66 | 14.76 | 642 | -148.2 | 0.08 | 13.5 | |
| 0953 | 27.61 | 0.2 | 9.2 | 7.65 | 14.82 | 650 | -152.1 | 0.06 | 13.7 | |
| 0958 | 27.61 | 0.2 | 10.2 | 7.63 | 14.83 | 658 | -153.8 | 0.16 | 13.5 | |
| 1000 | COLLECT | | SAMPLES | (59BM1WG1) | + DUPLICATE | (59DUP02WG1) | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |

## Observations

Notes: DTW = 27.40 w/Pump Installed.

YSI 556 MPS (#05B766AA) Solinst WLI model 101 (#50148)

Cannotte 2020 We (#1860-042) QED ~~300~~ MP 3020 (2049) (Pine # 05098)

QED MP-10 (#14974) @ 59DUP02WG1 Time = 0901

Signed/Sampler(s): Mike D. Jr

## WELL INSPECTION AND GROUNDWATER LEVEL MEASUREMENT SHEET

WELL NUMBER: ~~JC~~ MS BM-121

PROJECT NAME: AFP59

DATE/TIME: ~~JC~~ 8/2/12 1010

CITY/STATE: Johnson City, NY

INSPECTED BY: MIKE JACKSON

Water Level Indicator Serial No.: SOLOIST 50148

VENT WELL

MONITORING WELL INSTRUMENT READING (VOCs): 0.0 ppm

WELL INSPECTION/GROUNDWATER LEVEL MEASUREMENT

| | |
|---|---|
| WELL DEPTH (FEET FROM TOP OF PVC) | 56.04 |
| WATER LEVEL DEPTH (FEET FROM TOP OF PVC) | 27.51 |
| PVC WELL STICK-UP (FEET, ABOVE GRADE) | 3.15 |
| PROTECTIVE CASING STICK-UP (FEET, AGS) | NO PROTECTIVE CASING |
| WELL DIAMETER (INCHES) | 6 |
| WELL CONSTRUCTION (PVC, STEEL, ETC.) | STEEL |

STEEL

| | | |
|---|---|---|
| LOCKED UPON ARRIVAL? | YES | (NO) |
| LOCK REPLACED? | YES | (NO) |
| OBSTRUCTIONS? | YES | (NO) |
| DAMAGE TO WELL PAD/STICKUP/CASING, ETC? | YES | (NO) (If YES, detail in comments below) |
| WELL RELABELED? | YES | (NO) |
| WELL PHOTOGRAPHED? | (YES) | NO |

GENERAL CONDITION/COMMENTS/RECOMMENDATIONS:

STEEL CASING STICKUP WELL NOW
MUFFLER SHOP IN GRASSY AREA
BETWEEN SIDE WALK AND ROAD.

# FIELD SAMPLING REPORT

| | | | |
|---|---|---|---|
| LOCATION: | AFP59 | PROJECT NAME: | AFP59 2012 GWS |
| SITE: | AFP59 | PROJECT NO: | AF7061 |

## SAMPLE INFORMATION

SAMPLE ID: ~~59DW1WG1~~ ~~B~~ 59BM121WG1 DATE: 8-2-2012 TIME: 1000

MATRIX TYPE: WG

SAMPLING METHOD: BP

LOT CONTROL #: ___ ___ ___ ___

(Ambient Blank # - Equipment Blank # - Trip Blank # - Cooler #)

CHAIN-OF-CUSTODY #: _____

SAMPLE BEG. DEPTH (FT): —

SAMPLE END DEPTH (FT): —

GRAB ~~X~~ COMPOSITE ( )

ENTER SAMPLE NUMBERS FOR QC SAMPLES/ BLANKS ASSOCIATED WITH THIS SAMPLE:

MATRIX SPIKE (MS): —

MATRIX SPIKE DUP (SD): —

FIELD DUP (FD): —

AMBIENT BLANK (AB): —

EQUIPMENT BLANK (EB): —

TRIP BLANK (TB): 59TB073112

| CONTAINER SIZE/TYPE | # | PRESERVATIVE/ PREPARATION | ANALYTICAL METHOD | ANALYSIS |
|---|---|---|---|---|
| 1L Amber | 2 | Cool to 4C | 8270C | 1,4 Dioxane |
| 40 mL VOA | 3 | Cool to 4C HCl ph<2 | SW8260B | VOCs |

## NOTABLE OBSERVATIONS

| PID READINGS | SAMPLE CHARACTERISTICS | MISCELLANEOUS |
|---|---|---|
| 1st 0.0 | COLOR: | |
| 2nd | ODOR: | |
| | OTHER: | |

pH 7.63 Temperature 14.83 (C) Dissolved Oxygen 0.16 (mg/L) Specific Conductivity 658 ~~(umhos/cm)~~ mS/cm

Iron — (mg/L) Oxidation/Reduction Potential -155.8 (mv) Turbidity 13.5 (NTU)

## GENERAL INFORMATION

WEATHER: SUN/CLEAR ___ cloudy OVERCAST/RAIN ~~x~~ WIND DIRECTION calm AMBIENT TEMPERATURE 82 °F

SHIPMENT VIA: FEDEX ___ HAND DELIVER x COURIER ___ OTHER ___

SHIPPED TO: ~~Accutest Laboratories of Northeast - Marlboro, MA~~ Alpha Analytical Albany, NY

COMMENTS:

SAMPLER: MIKE JACKSON OBSERVER: —

| MATRIX TYPE CODES | | SAMPLING METHOD CODES | |
|---|---|---|---|
| DC=DRILL CUTTINGS | SL=SLUDGE | B=BAILER | G=GRAB |
| WG=GROUND WATER | SO=SOIL | BP=BLADDER PUMP | HA=HAND AUGER |
| LH=HAZARDOUS LIQUID WASTE | GS=SOIL GAS | PP=PERISTALIC PUMP | H=HOLLOW STEM AUGER |
| SH=HAZRDOUS SOLID WASTE | WS=SURFACE WATER | CS=COMPOSITE SAMPLE | HP=HYDRO PUNCH |
| SE=SEDIMENT | SW=SWAB/WIPE | C=CONTINUOUS FLIGHT AUGER | SS=SPLIT SPOON |
| | | DT=DRIVEN TUBE | SP=SUBMERSIBLE PUMP |

*This page intentionally left blank.*

HGL
HydroGeoLogic, Inc.

# GROUNDWATER FIELD SAMPLING DATA SHEET

| | | | |
|---|---|---|---|
| Well Name.: JC3 | | Project Name: | LOCID: |
| Sampler(s): MIKE Jackson | | Project No.: AF7061 | |
| Well Depth: N/A | | Date: 8-2-12 | Time: 1130 |
| DTW (ft TOC): N/A | | Screen Interval: N/A | |
| Well Diameter (in): N/A | | Placement of Pump (ft TOC): N/A | |
| Type of Pump: N/A | | | |

## Field Parameters

| Time | Depth to Water (ft) | Flow Rate (gpm) | Total Volume (gal) | pH | Temp. (C) | Cond. (umhos/cm) | ORP | D.O. (mg/L) | Turb. (N.T.U.) | Description |
|---|---|---|---|---|---|---|---|---|---|---|
| 1146 | | | | 6.94 | 15.2 | 1492 | 138.4 | 4.21 | 0.12 | 5 minute |
| 1145 | collect | | samples | | C | 59 JC3 (W61) | | | | purge |
| | | | | | | VOCs 8260B + | | 1,4-Dioxane | | 8270C |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |

1145

## Observations

Notes: Purge from well #3 (JC3)
1145 1140 start purge.

Signed/Sampler(s): MLE D.J.

# FIELD SAMPLING REPORT

| | | | |
|---|---|---|---|
| LOCATION: | AFP59 | PROJECT NAME: | AFP59 2012 GWS |
| SITE: | AFP59 | PROJECT NO: | AF7048 |

## SAMPLE INFORMATION

| | |
|---|---|
| SAMPLE ID: 59JC1WG1 | DATE: 8-2-12 TIME: 1175 |
| MATRIX TYPE: WG | ENTER SAMPLE NUMBERS FOR QC SAMPLES/ BLANKS ASSOCIATED WITH THIS SAMPLE: |
| SAMPLING METHOD: G | MATRIX SPIKE (MS): — |
| LOT CONTROL #: ___ ___ ___ ___ | MATRIX SPIKE DUP (SD): — |
| (Ambient Blank # - Equipment Blank # - Trip Blank # - Cooler #) | FIELD DUP (FD): — |
| CHAIN-OF-CUSTODY #: _____ | AMBIENT BLANK (AB): — |
| SAMPLE BEG. DEPTH (FT): — | EQUIPMENT BLANK (EB): — |
| SAMPLE END DEPTH (FT): — | TRIP BLANK (TB): 59TB073112 |
| GRAB (X) COMPOSITE ( ) | |

| CONTAINER SIZE/TYPE | # | PRESERVATIVE/ PREPARATION | ANALYTICAL METHOD | ANALYSIS |
|---|---|---|---|---|
| 40 mL VOA | 3 | Cool to 4C HCl ph<2 | SW8260B | VOCs |
| 1L Amber | 2 | Cool to 4C | 8270C | 1,4 Dioxane |

## NOTABLE OBSERVATIONS

| PID READINGS | SAMPLE CHARACTERISTICS | MISCELLANEOUS |
|---|---|---|
| 1st | COLOR: | |
| 2nd | ODOR: | |
| | OTHER: | |

pH 6.94 Temperature 15.2 (C) Dissolved Oxygen 4.21 (mg/L) Specific Conductivity 1492 (umhos/cm)
Iron — (mg/L) Oxidation/Reduction Potential 138.4 (mv) Turbidity 0.12 (NTU)

## GENERAL INFORMATION

WEATHER: SUN/CLEAR _____ OVERCAST/RAIN _____ WIND DIRECTION _____ AMBIENT TEMPERATURE Inside Building 80°

SHIPMENT VIA: FEDEX _____ HAND DELIVER ___x___ COURIER _____ OTHER _____

SHIPPED TO: ~~Accutest Laboratories of Northeast - Marlboro, MA~~ Alpha Analytical Laboratory, NJ

COMMENTS:

SAMPLER: MIKE JACKSON OBSERVER: —

| MATRIX TYPE CODES | | SAMPLING METHOD CODES | |
|---|---|---|---|
| DC=DRILL CUTTINGS | SL=SLUDGE | B=BAILER | G=GRAB |
| WG=GROUND WATER | SO=SOIL | BP=BLADDER PUMP | HA=HAND AUGER |
| LH=HAZARDOUS LIQUID WASTE | GS=SOIL GAS | PP=PERISTALIC PUMP | H=HOLLOW STEM AUGER |
| SH=HAZRDOUS SOLID WASTE | WS=SURFACE WATER | CS=COMPOSITE SAMPLE | HP=HYDRO PUNCH |
| SE=SEDIMENT | SW=SWAB/WIPE | C=CONTINUOUS FLIGHT AUGER | SS=SPLIT SPOON |
| | | DT=DRIVEN TUBE | SP=SUBMERSIBLE PUMP |

HydroGeoLogic, Inc

# STATIC GROUNDWATER ELEVATION LOG

**Project Name:** AFP59 2012 Groundwater Sampling Event

**Project No.:** AF7061

**Water Level Indicator ID#:** Water Level Indicator (Solinst model 101 # 47088) **PID Meter ID#:** MiniRAE 2000

| Well Identification | Date | Time | Static Depth to Water (from TOC) | Depth to Product (from TOC) | PID Reading | Comments |
|---|---|---|---|---|---|---|
| ~~DW-1~~ DW-3 | 7/31/12 | 1633 | 18.21 | | 0.4 | |
| ~~SW-1~~ SW-3 | 7/31/12 | 1637 | 18.19 | | ~~0.0~~ 3.1 | |
| SW-4 | 7/31/12 | | NOT FOUND | | | |
| SW-7 | 7/31/12 | 1645 | 20.36 | | 0.0 | |
| 2" ~~SW-3~~ SW-1 | | 1652 | 20.06 | | 0.0 | |
| 4" ~~DW-3~~ DW-1 | | 1654 | 17.21 | | 0.0 | |
| URS-2D | | 1440 | 33.11 | | 0.0 | |
| URS-2S | | 1715 | 34.35 | | 0.0 | |
| URS-3D | | 1120 | 39.35 | | 0.0 | |
| URS-5S | | | 24.18 | | 0.0 | |
| URS-9S | | | NOT FOUND | | | |
| BM-121 | 8/2/12 | 0805 | 27.15 | | 0.0 | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

*This page intentionally left blank.*

# CHAIN OF CUSTODY

PAGE 2 OF 2

ALPHA ANALYTICAL

Westborough, MA TEL: 508-898-9220 FAX: 508-898-9193
Mansfield, MA TEL: 508-822-9300 FAX: 508-822-3288

Date Rec'd in Lab:

ALPHA Job #:

## Client Information

Client: HGL
Address: 313 Ushers Road
Ballston Lake, NY 12019
Phone: (518) 877-0390
Fax: (518) 877-0414
Email: pdacyk@hgl.com

☐ These samples have been Previously analyzed by Alpha

## Project Information

Project Name: AFP 2012 Groundwater Sampling
Project Location: AFP59 Johnson City, NY
Project #: AF7061
Project Manager: Pete Dacyk
ALPHA Quote #:

## Turn-Around Time

☒ Standard ☐ Rush (ONLY IF PRE-APPROVED)

Due Date: Time:

## Report Information

☐ FAX ☐ EMAIL
☒ ADEx ☐ Add'l Deliverables

## Data Deliverables

## Billing Information

☒ Same as Client info PO #:

## Regulatory Requirements/Report Limits

State/Fed Program: Per Contract
Criteria: Per Contract

## MCP PRESUMPTIVE CERTAINTY-CT REASONABLE CONFIDENCE PROTOCOLS

☐ Yes ☐ No Are MCP Analytical Methods Required?
☐ Yes ☐ No Are CT RCP (Reasonable Confidence Protocols) Required?

Other Project Specific Requirements/Comments/Detection Limits:

SEE QAPP provided to Alpha by HGL

## ANALYSIS

SAMPLE HANDLING
*Filtration*
☐ Done
☒ Not Needed
☐ Lab to do
*Preservation*
☐ Lab to do
*(Please specify below)*

| ALPHA Lab ID (Lab Use Only) | Sample ID | Collection Date | Collection Time | Sample Matrix | Sampler's Initials | VOCs 8260B | 1,4 Dioxane (8270C) | Sample Specific Comments | TOTAL # BOTTLES |
|---|---|---|---|---|---|---|---|---|---|
| | 59URS2SWG1 a | 7-31-12 | 1812 | GW | MDJ | ☒ | ☒ | | 8 |
| | 59URS3DWG1 a' | 7-31-12 | 1301 | GW | GR | ☒ | ☒ | | 8 |
| | 59URS5SWG1 a | 8-1-12 | 1200 | GW | MDJ | ☒ | ☒ | | 8 |
| | ~~59URS6SWG1~~ MJ | | | GW | | ☒ | ☒ | MJ | 8 |
| | 59EB080112 e | 8-1-12 | 1815 | GW | MDJ | ☒ | ☒ | | 8 |
| | 59TB073112 a' | 7-31-12 | 0800 | GW | | ☒ | [redacted] | VOCs only | 8 |
| | 59DUP01WG1 | 8-1-12 | 0901 | GW | MDJ | ☒ | ☒ | | 2 |
| | 59DUP02WG1 a | 8-2-12 | 0901 | GW | MDJ | ☒ | ☒ | | 8 |
| | 59ABO 80112 a | 8-1-12 | 1615 | GW | MDJ | ☒ | ☐ | | 8 |
| | | | | | | ☐ | ☐ | | 8 |

| | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Container Type | V | A | - | - | - | - | - | - | - | - | - | - |
| Preservative | B | A | - | - | - | - | - | - | - | - | - | - |

**PLEASE ANSWER QUESTIONS ABOVE!**

**IS YOUR PROJECT MA MCP *or* CT RCP?**

FORM NO: 01-01(I) (rev. 30-JUL-07)

| Relinquished By: | Date/Time | Received By: | Date/Time |
|---|---|---|---|
| [illegible] HGL | 8-2-12 1752 | [illegible] | 8-2-12 1752 |

Please print clearly, legibly and completely. Samples can not be logged in and turnaround time clock will not start until any ambiguities are resolved. All samples submitted are subject to Alpha's Payment Terms.

# CHAIN OF CUSTODY

PAGE 1 OF 2

ALPHA ANALYTICAL

Westborough, MA TEL: 508-898-9220 FAX: 508-898-9193
Mansfield, MA TEL: 508-822-9300 FAX: 508-822-3288

Date Rec'd in Lab:

ALPHA Job #:

## Client Information

Client: HGL
Address: 313 Ushers Road
Ballston Lake, NY 12019
Phone: (518) 877-0390
Fax: (518) 877-0414
Email: pdacyk@hgl.com

☐ These samples have been Previously analyzed by Alpha

## Project Information

Project Name: AFP 2012 Groundwater Sampling
Project Location: AFP59 Johnson City, NY
Project #: AF7061
Project Manager: Pete Dacyk
ALPHA Quote #:

## Turn-Around Time

☒ Standard ☐ Rush (ONLY IF PRE-APPROVED)

Due Date: Time:

## Report Information Data Deliverables

☐ FAX ☐ EMAIL
☒ ADEx ☐ Add'l Deliverables

## Billing Information

☒ Same as Client info PO #:

## Regulatory Requirements/Report Limits

| State/Fed Program | Criteria |
|---|---|
| Per Contract | Per Contract |

## MCP PRESUMPTIVE CERTAINTY-CT REASONABLE CONFIDENCE PROTOCOLS

☐ Yes ☐ No Are MCP Analytical Methods Required?
☐ Yes ☐ No Are CT RCP (Reasonable Confidence Protocols) Required?

Other Project Specific Requirements/Comments/Detection Limits:

SEE QAPP provided to Alpha by HGL

## ANALYSIS

SAMPLE HANDLING
*Filtration*
☐ Done
☒ Not Needed
☐ Lab to do
*Preservation*
☐ Lab to do
*(Please specify below)*

| ALPHA Lab ID (Lab Use Only) | Sample ID | Collection Date | Collection Time | Sample Matrix | Sampler's Initials | VOCs 8260B | 1,4 Dioxane (8270C) | Sample Specific Comments | TOTAL # BOTTLES |
|---|---|---|---|---|---|---|---|---|---|
| | 59DW1WG1 | 8-1-12 | 1013 | GW | GR | ☒ | ☒ | | 8 |
| | 59DW3WG1 | 8-1-12 | 1502 | GW | GR | ☒ | ☒ | | 8 |
| | ~~59JC1WG1~~ MS 59JC3WG1 | 8-2-12 | 1145 | GW | MS | ☒ | ☒ | | 8 |
| | 59SW1WG1 | 8-1-12 | 1133 | GW | GR | ☒ | ☒ | | 8 |
| | 59SW3WG1 | ↓ | 1622 | GW | GR | ☒ | ☒ | | 8 |
| | ~~59SWWG1~~ MS 59BM121WG1 | 8-2-12 | 1000 | GW | MS | ☒ | ☒ | ← HOLD Analysis - HGL will call | 8 |
| | 59SW7WG1 | 8-1-12 | 1625 | GW | MS | ☒ | ☒ | | 8 |
| | 59URS2DWG1 | 7-31-12 | 1617 | GW | GR | ☒ | ☒ | | 8 |
| | 59URS2DWG1-MS | | | GW | | ☒ | ☒ | MS of 59URS2DWG1 | 8 |
| | 9URS2DWG1-MSD | ↓ | ↓ | GW | ↓ | ☒ | ☒ | MSDof 59URS2DWG1 | 8 |

| | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Container Type | V | A | - | - | - | - | - | - | - | - | - | - |
| Preservative | B | A | - | - | - | - | - | - | - | - | - | - |

**PLEASE ANSWER QUESTIONS ABOVE!**

**IS YOUR PROJECT MA MCP *or* CT RCP?**

| Relinquished By: | Date/Time | Received By: | Date/Time |
|---|---|---|---|
| [signature] | 8-2-12 1752 | [signature] | 8-2-12 1752 |

Please print clearly, legibly and completely. Samples can not be logged in and turnaround time clock will not start until any ambiguities are resolved. All samples submitted are subject to Alpha's Payment Terms.

FORM NO: 01-01(I) (rev. 30-JUL-07)

# CHAIN OF CUSTODY

PAGE 1 OF 1

ALPHA ANALYTICAL

Westborough, MA TEL: 508-898-9220 FAX: 508-898-9193
Mansfield, MA TEL: 508-822-9300 FAX: 508-822-3288

Date Rec'd in Lab:

ALPHA Job #:

## Client Information

Client: HGL
Address: 313 Ushers Road
Ballston Lake, NY 12019
Phone: (518) 877-0390
Fax: (518) 877-0414
Email: pdacyk@hgl.com

☐ These samples have been Previously analyzed by Alpha

## Project Information

Project Name: AFP 2012 Groundwater Sampling
Project Location: AFP59 Johnson City, NY
Project #: AF7061
Project Manager: Pete Dacyk
ALPHA Quote #:

## Turn-Around Time

☒ Standard ☐ Rush (ONLY IF PRE-APPROVED)

Due Date: Time:

## Report Information Data Deliverables

☐ FAX ☐ EMAIL
☒ ADEx ☐ Add'l Deliverables

## Billing Information

☒ Same as Client info PO #:

## Regulatory Requirements/Report Limits

| State/Fed Program | Criteria |
|---|---|
| Per Contract | Per Contract |

## MCP PRESUMPTIVE CERTAINTY-CT REASONABLE CONFIDENCE PROTOCOLS

☐ Yes ☐ No Are MCP Analytical Methods Required?
☐ Yes ☐ No Are CT RCP (Reasonable Confidence Protocols) Required?

Other Project Specific Requirements/Comments/Detection Limits:

EXPECTED HIGH CONCENTRATIONS in 59SW4WG1 Sample. SCREEN FIRST.

SEE QAPP provided to Alpha by HGL

## ANALYSIS

SAMPLE HANDLING
*Filtration*
☐ Done
☒ Not Needed
☐ Lab to do
*Preservation*
☐ Lab to do
*(Please specify below)*

| ALPHA Lab ID (Lab Use Only) | Sample ID | Collection Date | Collection Time | Sample Matrix | Sampler's Initials | VOCs 8260B | 1,4 Dioxane (8270C) | | | | | | | | | | | Sample Specific Comments | TOTAL # BOTTLES |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 59SW4WG1 | 8-29-12 | 1533 | GW | MDJ | ☒ | ☒ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | | 8 |
| | 59EB082912 | ↓ | 1650 | GW | MDJ | ☒ | ☒ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | | 8 |
| | 59TB082912 | ↓ | ~~1300~~ MT | GW | MDJ | ☒ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | | 8 |
| | | | | | | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | | 8 |
| | | | | | | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | | 8 |
| | | | | | | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | | 8 |
| | | | | | | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | | 2 |
| | | | | | | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | | 8 |
| | | | | | | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | | 8 |
| | | | | | | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | ☐ | | 8 |

| Container Type | V | A | - | - | - | - | - | - | - | - | - | - |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Preservative | B | A | - | - | - | - | - | - | - | - | - | - |

PLEASE ANSWER QUESTIONS ABOVE!

IS YOUR PROJECT MA MCP or CT RCP?

| Relinquished By: | Date/Time | Received By: | Date/Time |
|---|---|---|---|
| [illegible] HGL | 8/30/12 1345 | Kyle Cunningham | 8/30/12 1345 |

Please print clearly, legibly and completely. Samples can not be logged in and turnaround time clock will not start until any ambiguities are resolved. All samples submitted are subject to Alpha's Payment Terms.

FORM NO: 01-01(I) (rev. 30-JUL-07)

*This page intentionally left blank.*