Bi-Annual Sampling Report For Treatment Systems

November 2001 - March 2002

# Gladding Cordage Corporation Multi-Site Wells

Work Assignment Number D003821-27

Prepared for: Superfund Standby Program New York State Department of Environmental Conservation 625 Broadway, 12<sup>th</sup> Floor Albany, New York 12233-7013

Prepared by: Earth Tech, Inc. 40 British American Boulevard Latham, New York 12110

April 2002

### TABLE OF CONTENTS

| Chapt                    | er er  | Page   |
|--------------------------|--|--------|
| 1.0                      | INTRODUCTION  1.1 SITE DESCRIPTION  1.2 TREATMENT SYSTEMS  1.2.1 South Otselic Fish Hatchery (GLADD)   | 1<br>1 |
| 2.0                      | SAMPLING   | 2<br>2 |
| 3.0                      | SYSTEM MAINTENANCE AND MODIFICATIONS   | 3      |
| 4.0                      | CONCLUSIONS  | 4      |
| Table                    | LIST OF TABLES   |        |
| 2-1<br>2-2<br>2-3<br>2-4 | Resident and System Information Historical Raw Water Analytical Summary Current Round Analytical Summary Volatile Organic Compounds Included in EPA Method 524.2 |        |

#### 1.0 INTRODUCTION

In accordance with the monitoring plan for the granular activated carbon (GAC) groundwater treatment system associated with the Gladding Cordage Corporation (Gladding) site, the third round of semi-annual water sampling was performed on February 25, 2002. The results of laboratory analyses for this sampling event are summarized in this report, as are subsequent actions taken in response to the analysis. Routine system maintenance and/or required modifications are also discussed. This report covers activities that occurred during the period November 2001 through March 2002.

#### 1.1 SITE DESCRIPTION

The Gladding site (Site Code #7-09-009) is located in the hamlet of South Otselic, Town of Ostelic, Chenago County, New York. The site occupies about 7.5 acres near the center of the hamlet. The site is bound to the east by the Otselic River, to the south by Gladding Street, to the west by Ridge Road and to the north by undeveloped agricultural lands. Past disposal practices of 1,1,1- trichloroethane (1,1,1-TCA) at the Gladding site led to volatile organic compound (VOC) contamination of soil and groundwater, and closure of two municipal water supply wells located approximately 250 ft. south of the site. In 1990, the town of Otselic was awarded a Housing and Urban Development (HUD) grant to install a new municipal water supply well upgradient of the Gladding site.

A pump and treat system was constructed by the NYSDEC in 1996 to contain and remediate contaminated groundwater at the site. Groundwater from a domestic well at the NYSDEC South Otselic Fish Hatchery is being treated with a GAC system, maintained by Earth Tech under this Work Assignment. The groundwater at the fish hatchery presumably had been impacted by the disposal practices at the Gladding site.

#### 1.2 TREATMENT SYSTEMS

#### 1.2.1 South Otselic Fish Hatchery (GLADD)

The South Otselic Fish Hatchery well is located approximately one-mile southwest of the Gladding site. The NYSDEC began monitoring/maintaining this well in 1991.

The New York State Department of Health (NYSDOH) recommends potable water treatment with two tanks connected in series for organics removal from drinking water. This configuration provides a primary and secondary GAC unit and allows for monitoring water quality between these units. The South Otselic Fish Hatchery system consists of two activated carbon vessels for the removal of VOCs, and a Trojan model 708 ultraviolet (UV) disinfection unit. This system does not have a particle filter or a flow meter.

#### 2.0 SAMPLING

#### 2.1 SAMPLE LOCATIONS

Table 2-1 presents project information including location and well ID. Sampling points include raw, intermediate and effluent (final) ports. Final samples were collected from a sink in a nearby room.

#### 2.2 SAMPLING PROTOCOL

Standard protocol is to allow a sampling tap to run for at least 15 minutes prior to sampling to insure that representative water is in the system. After purging, samples are collected in the following order: effluent, intermediate, and finally raw water in order to minimize the possibility of cross-contamination. Volatile organics samples are placed in 40-milliliter (ml) vials and capped and then checked to insure that no air bubbles are trapped in the vial. Care is taken during collection to minimize agitation and to immediately place sample containers on ice to prevent volatilization.

Bacteria sampling of the final (treated) water is conducted after volatile sampling. Sampling protocol requires decontamination of the water tap by heating with an open flame for one minute prior to sampling.

Bi-annual samples are submitted for volatile analysis by the EPA Method 524.2 and total coliform analysis. The Division of Environmental Remediation Laboratory of Rensselaer, N.Y. provided analytical services for volatile organic analysis. Coliform analysis services are provided by Smith Environmental Laboratory of Hyde Park, New York, an M/WBE enterprise.

#### 2.3 SAMPLING AND FLOW READINGS

All standard sampling procedures were followed except taps were not run for 15 minutes prior to sampling since water is regularly drawn through the systems and representative groundwater is already within the systems.

A flow meter was not installed as part of the DEC's requirements for the treatment system; therefore flow volume data are not available.

#### 2.4 ANALYTICAL RESULTS

The laboratory data sheets for volatile analyses are distributed electronically by the laboratory to Earth Tech and NYSDEC, and are not included in this report. Historical raw water analytical data are summarized on Table 2-2. VOC analytical results for raw, intermediate, and final water samples for this round (only) are summarized on Table 2-3. The coliform test result was negative, and is not tabulated. A copy of the total coliform analysis is included with this report.

Carbon changeout will typically occur if an intermediate or final water sample VOC concentration equals or exceeds 1  $\mu$ g/l. No breakthrough of site-related VOCs was reported, and carbon changeouts were therefore not required at the hatchery.

The February 25, 2002 sampling results reported 4.0 ppb of 1,1,1-TCA in the raw water. The intermediate and final water samples were non-detect.

#### 3.0 SYSTEM MAINTENANCE AND MODIFICATIONS

Initial site inspections by Earth Tech were conducted in February 2001. The well location was inspected to assess GAC system conditions, foresee any potential maintenance problems, and to choose a suitable plan of action for system maintenance/modifications.

In November 2001, the existing UV disinfection unit was replaced with a Trojan model 708 unit because replacement parts were no longer available for the older unit. During the sampling event in February 2002, the UV sleeve was cleaned.

On March 29, 2002, Earth Tech responded to a call about a leak on the UV light. The leak was fixed.

### 4.0 CONCLUSIONS

The GAC water treatment system at the South Otselic Fish Hatchery is operating satisfactorily.

The next sampling round is scheduled for August 2002.



Table 2-1 Gladding Site, South Otselic, N.Y. Resident and System Information

| Location  | Owner/Contact  | Phone #        | Well ID | System Location           |
|---|--|----------------|---------|---------------------------|
| South Otselic Fish Hatchery<br>PO Box 170 NYS Route 26<br>South Otselic, NY 13155 | Patrick Emerson, Hatchery Manager<br>Tom Kielbasinski, Assistant Manager | (315) 653-7727 | GLADD   | Side room off of kitchen. |

# Table 2-2 Gladding Site Historical Raw Water Analytical Summary

Data up to and including June 2000 was provided by the NYSDEC

| Location              | Well ID | 19-Feb-91 | 28-Jun-91 | 11-Mar-92 | 25-Mar-92 | 17-Sep-92 | 16-Mar-94 | 10-Nov-94 | 5-Apr-95 | 24-Oct-95 | 4-Jun-97 |
|-----------------------|---------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|----------|-----------|----------|
|                       |         |           |           |           |           |           |           |           |          |           |          |
| Gladding              | GLADD   |           |           |           |           |           |           |           |          |           |          |
| 1,1,1-Trichloroethane |         | ND        | ND        | 8.0       | 9.4       | 19.0      | 9.0       | ND        | 6.0      | 9.0       | 8.0      |

 $<sup>^{\</sup>star}$  indicates duplicate sample result.

Concentrations in ug/l (ppb).

NS indicates no sample taken

ND indicates below detection limit

Results are shown only for detected analytes

J = estimated value

## Table 2-2 Gladding Site Historical Raw Water Analytical Summary

Data up to and including June 2000 was provided by the NYSDEC

| Location              | Well ID | 20-Nov-98 | 10-May-99 | 30-Nov-99 | 12-Jun-00 | 6-Feb-01 | 29-Aug-01 | 25-Feb-02 |  |
|-----------------------|---------|-----------|-----------|-----------|-----------|----------|-----------|-----------|--|
| <b>2</b> 1 111        | 01.455  |           |           |           |           |          |           |           |  |
| Gladding              | GLADD   |           |           |           |           |          |           |           |  |
| 1,1,1-Trichloroethane |         | 6.0       | 5.8       | 8.0       | 6.0       | ND       | ND        | 4.0       |  |

<sup>\*</sup> indicates duplicate sample result.

Concentrations in ug/l (ppb).

NS indicates no sample taken

ND indicates below detection limit

Results are shown only for detected analytes

J = estimated value

TABLE 2-3 Current Round Analytical Summary-EPA Method 524.2 Sampling Date : 2/25/02

| Compound  | GLADD - R                      | GLADD - I | GLADD - F |  |  |
|---|--------------------------------|-----------|-----------|--|--|
| 1,1,1-Trichloroethane   | 4.0 ND ND                      |           |           |  |  |
| J = estimated   | ND= non detect                 |           |           |  |  |
| E= estimated above calibration range.   | All concentrations are in ug/L |           |           |  |  |
| R= raw water sample   | D= diluted sample              |           |           |  |  |
| I= intermediate water sample  | * = duplicate sample           |           |           |  |  |
| F= final water sample   |                                |           |           |  |  |
| Only detected analytes are shown in this table.                                       |                                |           |           |  |  |
| Refer to Table 2-4 for a comprehensive list of analytes included in EPA Method 524.2. |                                |           |           |  |  |

WITHOUT CORPORATE PER 100 MIL PER 100 MIL PER 100 ML COLONY FORMING UNITS PER 1 ML CIAN(S) REPORT NOT VALID 9996 LAB DIRECTOR PHONE # LAB NO. B-TYPE OF FACILITY: **₹** RECEIVED AT LAB BY: 2126102 12 SAMPLE BOTTLE: □ OTHER: ★DRINKING
 MEET SATISFACTORY SANITARY QUALITY FOR SWIMMING
 □ WASTEWATER EFFLUENT ☐ OTHER: □ OTHER: EXAMINED THESE RESULTS INDICATE THAT THE WATER SAMPLE  $\square$  DID NOT <u>×</u> ☐ WASTE WATER; 12/10-1415 OTHER U21 4+10 ADDRESS: PPM ☐ FREE RESIDUAL ) **※**TOTAL RESIDUAL WHEN THE SAMPLE WAS COLLECTED. FOR INFORMATION CONCERNING UNSATISFACTORY SAMPLES PLEASE CALL: SMITH LABORATORY AT (845) 229-6536 91200 ☐ SURFACE WATER; AMERICAN FECAL COLIFORM COUNT FECAL STREP. COUNT N.V. TOTAL COLIFORM. VANVES NO NO Absert □ HETEROTROPHIC PLATE COUNT SOURCE: X DRINKING WATER; TREATMENT: 🗌 CHLORINATED ( 10:2% BRITISH PTE. 9 □ MFT □ MPN CZPA LATHAM FORWARD REPORT STRÉET ADDRESS SMITH LABORATORY 2015212 SAMPLING POINT: COLLECTED BY: □ MPN FACILITY NAME: 4 SCENIC DRIVE DELIVERED BY: HYDE PARK, N DATE SAMPLED 0/7 以E. COLI NAME □ MFT ☐ MFT

N.Y.S. APPROVED LAB. NO.

**BACTERIOLOGICAL EXAMINATION OF WATER** 

CUSTOMERS COPY

10924