PROGRESS REPORT NO. 7
REMEDIAL INVESTIGATION AND FEASIBILITY STUDY
VALEO FORMER GM – DELCO CHASSIS FACILITY
1555 LYELL AVENUE, ROCHESTER, NEW YORK
Site No. 8-28-099, EPA ID No. NYD002215226

by

Haley & Aldrich of New York
Rochester, New York

for

General Motors Corporation
Detroit, Michigan

File No. 70436-242
July 2004

HALEY&
ALDRICH

Haley & Aldrich of New York
200 Town Centre Dr.
Suite 2
Rochester, NY 14623-4264

Tel: 585.359.9000
Fax: 585.359.4650
HaleyAldrich.com

HALEY&
ALDRICH

27 July 2004
File No. 70436-242

New York State Department of
Environmental Conservation
Division of Environmental Remediation
Region 8
6274 East Avon-Lima Road
Avon, New York 14414-9519

Attention: Regional Hazardous Waste Remediation Engineer

Subject: Remedial Investigation Quarterly Progress Report No. 7
Site No. 8-28-099, EPA ID No. NYD002215226
Valeo Former GM – Delco Chassis Facility
1555 Lyell Avenue
Rochester, New York

OFFICES

Boston
Massachusetts

Cleveland
Ohio

Dayton
Ohio

Detroit
Michigan

Hartford
Connecticut

Kansas City
Kansas

Los Angeles
California

Manchester
New Hampshire

Parsippany
New Jersey

Portland
Maine

San Diego
California

Santa Barbara
California

Tucson
Arizona

Washington
District of Columbia

Gentlemen:

Please find enclosed two copies of Remedial Investigation Progress Report No. 7 for NYSDEC Registry Site No. 8-28-099, the Valeo Former GM – Delco Chassis Facility located at 1555 Lyell Avenue in the City of Rochester, Monroe County, New York. The Valeo Former GM – Delco Chassis Facility is hereinafter referred to as the "site." The site location is shown on Figure 1 of this report.

This report is submitted on behalf of General Motors Corporation (GM). It has been prepared in accordance with the terms of an Order On Consent between NYSDEC and GM ("RI/FS Order," Index # B8-0543-98-08) and our letter to the Department dated 10 May 2004.

This report covers the period from January through July 2004. Activities performed during the reporting period included the following supplemental remedial investigations specified in Work Plan Amendment No. 2 (presented in RI/FS Progress Report No. 2):

- additional soil and groundwater sampling to determine the extent of contamination detected in soil at the Melonite process wastewater sump; and
- test borings to determine the extent of contamination in overburden groundwater in and around the area of soil contamination at location TP-15-1 in AOR #7 (the presumed source of groundwater contamination detected at bedrock monitoring well MW-307-1).

Please feel free to contact us if you have any questions about the enclosed report.

Sincerely yours,
HALEY & ALDRICH OF NEW YORK

Jeffrey E. Loney
Vice President

Thomas D. Wells
Senior Environmental Geologist

c:
General Motors Corporation – M. Dedyne
Valeo – J. Kolanek
NYSDEC Environmental Enforcement Division, Buffalo – G. Bailey, Senior Attorney
NYSDEC Environmental Remediation Div., Albany - E. Belmore, Chief Western Section
MCDOH - R. Elliott
NYSDOH – M. Forcucci
Environ - CY Jeng

G:\Projects\70436\242\Qtly_Reports\No. 7\Qtly Rpt #7.doc

TABLE OF CONTENTS

LIST OF TABLES

LIST OF FIGURES

I. INTRODUCTION

This report is the seventh progress report covering remedial investigation (RI) activities performed at the Valeo Former GM – Delco Chassis Facility site. This report covers the period from February 2004 through July 2004.

This report has been prepared in accordance with the terms of an Order On Consent between the New York State Department of Environmental Conservation (NYSDEC) and the General Motors Corporation (GM) for a remedial investigation and feasibility study of the site ("RI/FS Order", Index # B8-0543-98-08). The site is listed as Site # 8-28-099 on the New York State Registry of Inactive Hazardous Waste Disposal Sites, and it is identified under state and federal programs regulating management of hazardous waste by U.S. Environmental Protection Agency (EPA) identification number NYD002215226.

The site is located at 1555 Lyell Avenue in the City of Rochester, Monroe County, New York. The site location is shown on Figure 1, and a site plan showing sampling locations and site features is presented on Figure 2.

II. RI/FS ACTIVITIES COMPLETED

Investigative activities performed during the reporting period included the supplemental remedial investigations specified in Work Plan Amendment No. 2 (presented in RI/FS Progress Report No. 2):

- soil and groundwater sampling to determine the extent of contamination of soil at the Melonite process wastewater sump in Building A;
- test borings and temporary well installations to determine the extent of contamination in overburden groundwater in and around the area of soil contamination at location TP-15-1 in AOR #7;
- laboratory analysis of soil and groundwater samples collected during the reporting period;
- validation of laboratory analysis results; and
- a site walkover by project team members for the purposes of ecological and human-health risk assessment reconnaissance.

Drilling services were performed by Nothnagle Drilling of Scottsville, New York. Laboratory analysis was performed by STL Laboratories of Buffalo, New York. The risk assessment walkover was conducted by Environ personnel in conjunction with a project-update meeting held at the site on 6 May 2004. The meeting was conducted with representatives of NYSDEC, the state and county health departments, GM, Valeo, Environ, and Haley & Aldrich to summarize the progress and findings of the RI activities completed to date.

Melonite Process Wastewater Sump Area

The supplemental investigations at the Melonite Sump focused on contamination by various metals detected in soil adjacent to the sump at previous test boring B-501. Previous sample analysis results for B-501, which are summarized on Table 1, indicated that the soil horizon at the top of bedrock (from 4 to 5.4 feet) contained copper, lead, zinc, and other metals at concentrations that indicated a possible past release of wastewater from the sump.

Two test borings were therefore drilled at locations 20 feet east (B-527) and west (B-528) of the sump. Soil sampling was performed at both locations on 9 April 2004, and bedrock drilling was performed at B-527 for the purpose of installing an overburden-bedrock interface monitoring well (MW-527). The well was developed after installation, and groundwater sampling using low-flow purging and sampling methods was performed on 28 April 2004. Soil samples from both borings and a groundwater sample from MW-527 were submitted to STL for analysis of previously-detected metal contaminants by US EPA SW 846 methods.

Test boring and well locations are shown on Figure 2. Test boring logs, a monitoring well installation report, and groundwater sampling records are presented in Appendix A. Soil and groundwater sample analysis results are presented in Table 1.

TP-15-1 Area in AOR #7

Soil contamination at the location of previous test pit TP-15-1 is the apparent source of groundwater contamination detected during the RI at downgradient bedrock monitoring well MW-307-1. Benzene, toluene, ethyl benzene, and xylene (BTEX) are present in a subsurface layer of contaminated soil at the TP-15-1 location, and these contaminants have been detected in RI samples from MW-307-1 at concentrations of up to 0.1 milligrams per liter (mg/L; equal to parts per million, ppm).

Previous soil sampling had delineated the lateral and vertical extent of contaminated soil and the nature of the soil profile in this area. To determine if and to what extent contaminated groundwater is present in the overburden in this area, soil sampling was performed at five locations in the immediate vicinity of the TP-15-1 location to assess the degree of groundwater saturation in soil. Borings were advanced to the apparent top of bedrock and continuous soil sampling was performed using direct push sampling methods at each boring. Visual observations of soil conditions did not indicate that groundwater or saturated soil were present in overburden at any of the locations.

In two of the borings, temporary PVC monitoring wells were installed to the top of rock. One temporary well (TW-1) was installed in the approximate center of the contaminated soil layer at TP-15-1, and the second (TW-2) was installed beyond the western extent of the contaminated soil layer approximately halfway between the center location and downgradient well MW-307-1. Temporary well locations are shown on Figure 2.

After installation, the temporary wells were checked on several occasions in April, May, and July 2004 for the presence of groundwater. Groundwater was not observed in either well.

The spring and early summer period during which the two temporary wells have been monitored for groundwater has been one of unseasonably wet weather. On the basis of the results of the soil sampling and temporary well installations, we therefore conclude that groundwater is not present in the overburden in the immediate vicinity of the TP-15-1 soil contamination and that the water table occurs below the top of bedrock in this area of the site.

III. UPCOMING RI/FS ACTIVITIES

No field activities are planned for the upcoming reporting period of June and July 2004. RI data evaluation and risk assessment activities will continue during the period.

IV. CITIZEN PARTICIPATION ACTIVITIES

The Citizen Participation Plan for the Valeo Former Delco Chassis site was updated to reflect changes in project personnel. The updated page is presented in Appendix B. No Citizen Participation activities are planned for the next reporting period.

REFERENCES

RI/FS Work Plan, Valeo Former GM - Delco Chassis Facility Site, 1555 Lyell Avenue, Rochester, New York, Registry Site #8-28-099. Haley & Aldrich of New York, December 2000.

Amendment No. 1 to the RI/FS Work Plan, Valeo Former GM-Delco Chassis Facility, Rochester, New York, Registry Site #8-28-099. Haley & Aldrich of New York, April 2002.

Citizen Participation Plan for the Valeo/Former GM - Delco Chassis Facility Inactive Hazardous Waste Disposal Site, Rochester, New York, Registry Site # 8-28-099. Haley & Aldrich of New York, July 2002.

Report for the Preliminary Site Assessment at the Abandoned Chemical Sales Facility Site, Rochester, New York, Site Number: 8-28-105. Ecology and Environment Engineering, P.C., March 2002.

Remedial Investigation Quarterly Progress Report No. 1, Site No. 8-28-099, EPA ID No. NYD002215226, Valeo Former GM – Delco Chassis Facility, 1555 Lyell Avenue, Rochester, New York. Haley & Aldrich of New York, December 2002.

Remedial Investigation Quarterly Progress Report No. 2, Site No. 8-28-099, EPA ID No. NYD002215226, Valeo Former GM – Delco Chassis Facility, 1555 Lyell Avenue, Rochester, New York. Haley & Aldrich of New York, February 2003.

Remedial Investigation Quarterly Progress Report No. 3, Site No. 8-28-099, EPA ID No. NYD002215226, Valeo Former GM – Delco Chassis Facility, 1555 Lyell Avenue, Rochester, New York. Haley & Aldrich of New York, May 2003.

Remedial Investigation Quarterly Progress Report No. 4, Site No. 8-28-099, EPA ID No. NYD002215226, Valeo Former GM – Delco Chassis Facility, 1555 Lyell Avenue, Rochester, New York. Haley & Aldrich of New York, August 2003.

Remedial Investigation Quarterly Progress Report No. 5, Site No. 8-28-099, EPA ID No. NYD002215226, Valeo Former GM – Delco Chassis Facility, 1555 Lyell Avenue, Rochester, New York. Haley & Aldrich of New York, November 2003.

Remedial Investigation Quarterly Progress Report No. 6, Site No. 8-28-099, EPA ID No. NYD002215226, Valeo Former GM – Delco Chassis Facility, 1555 Lyell Avenue, Rochester, New York. Haley & Aldrich of New York, February 2004.

TABLE 1
SUMMARY OF APRIL 2004 SAMPLE ANALYSIS RESULTS
VALEO FORMER GM-DELCO CHASSIS FACILITY SITE
ROCHESTER, NEW YORK

Draft, Privileged & Confidential -- Prepared at the request of GM Legal Counsel

AREA OF REVIEW	Melonite Process Wastewater Sump		
SAMPLE ID NUMBER	0886-042804-0941	0886-040904-1020	0886-040904-1015
SAMPLE DATE	4/28/04	4/9/04	4/9/04
SAMPLE LOCATION	MW-527	B-527	B-528
SAMPLE MATRIX	Groundwater	Soil	Soil
SAMPLE DEPTH	--	4.0 - 6.0 ft	6.0 - 8.0 ft.
Concentration Units	mg/L (ppm)	mg/KG (ppm)	mg/KG (ppm)
Antimony	ND < 0.020	ND < 17.3	ND < 16.5
Arsenic	0.0041	2.4	2.7
Beryllium	ND < 0.020	0.5	0.28
Cadmium	ND < 0.001	ND < 0.23	ND < 0.22
Chromium	ND < 0.004	13.6	7.9
Copper	ND < 0.010	17.1	12
Lead	ND < 0.006	9.9	4.4
Mercury	ND < 0.0002	ND < 0.024	ND < 0.022
Nickel	ND < 0.010	18.8	7.9
Selenium	ND < 0.015	ND < 4.6	ND < 4.4
Silver	ND < 0.003	ND < 0.58	ND < 0.55
Thallium	ND < 0.020	ND < 6.9	ND < 6.6
Zinc	ND < 0.020	59.2	22.7

Previously-reported sample data for the Melonite Process Wastewater Sump				
SAMPLE LOCATION	B-501			
SAMPLE DATE	6/30/2002			
SAMPLE MATRIX	Soil			
SAMPLE DEPTH	1.0 - 1.8 ft.	1.8 - 2.6 ft.	2.6 - 4.0 ft.	4.0 - 5.4 ft.
Concentration Units	mg/KG (ppm)	mg/KG (ppm)	mg/KG (ppm)	mg/KG (ppm)
Antimony	0.34J	0.58J	0.74J	70.5J
Arsenic	2.8	3	4.1	215
Beryllium	0.27J	0.14J	0.32J	5.7
Cadmium	0.21J	0.07J	0.17J	9.8
Chromium	7.5J	7.9J	10.4J	260J
Copper	9.2	6.4	8.3	739
Lead	8.8	8.4	36	1080
Mercury	0.015J	0.013J	0.093	ND < 0.005
Nickel	8.3J	3.9J	6.3J	93.6J
Selenium	ND < 0.52	0.67	ND < 0.58	205
Silver	0.2J	ND < 0.08	ND < 0.08	14.4
Thallium	0.59J	1J	ND < 0.51	228
Zinc	21.5J	9.6J	54.2J	3630J
Cyanide (total)	ND < 10	ND < 10	ND < 10	ND < 10

NOTES:
ND - Indicates that the analyte was analyzed and not detected above the quantitation limit shown.
J - Indicates a value greater than or equal to the instrument detection limit,
but less than the quantitation limit.



QUADRANGLE LOCATION: ROCHESTER WEST, N.Y.

HALEY & ALDRICH

VALEO/FORMER GM – DELCO CHASSIS FACILITY
ROCHESTER, NEW YORK
SITE NO. 8-28-099

SITE LOCATION

SCALE: 1" = 2000'

DECEMBER 2002

70436-242

FIGURE 1

APPENDIX A

Field Records

HALEY & ALDRICH

TEST BORING REPORT

Boring No. B-527

Project RI-FS-Valeo Former GM-Delco Chassis Facility Site Rochester, New York
Client REALM
Contractor Nothnagle Drilling, Inc.

File No. 70436-252
Sheet No. 1 of 2
Start
Finish
Driller Jeff
H&A Rep. D. Krause
Elevation 535 +/-
Datum RCD
Location

	Casing	Sampler	Barrel	Drilling Equipment and Procedures
Type				Rig Make & Model:
Inside Diameter (in.)				Bit Type:
Hammer Weight (lb.)			-	Drill Mud:
Hammer Fall (in.)			-	Casing:
				Hoist/Hammer:

Depth (ft.)	SPT[1]	Sample No. & Rec. (in.)	Sample Depth (ft.)	Well Diagram	Elev./Depth (ft.)	USCS Symbol	Visual-Manual Identification and Description (Density/consistency, color, GROUP NAME, max. particle size[2], structure, odor, moisture, optional descriptions, geologic interpretation)		Gravel % Coarse	Gravel % Fine	Sand % Coarse	Sand % Medium	Sand % Fine	% Fines	Field Test Dilatancy	Field Test Toughness	Field Test Plasticity	Field Test Strength
0				NO WELL INSTALLED			Concrete											
	3 2	S1 10	0.8 2.0		0.8		Stiff to soft, brown to black SAND with silt, moist, petroleum odor, mps 10mm	PID = 0.1 ppm				70	5	25				
	4 3 2	S2 18	2.0 4.0				Stiff to soft, brown to black SAND with silt, moist, petroleum odor, mps 10mm	PID = 0.5 ppm										
5	3 2 3	S3 16	4.0 6.0				Stiff to soft, brown to black SAND with silt, moist, petroleum odor, mps 10mm (sample 0886-040904-1020 B-527:4 to 6 ft.)											
	100 4 6	S4 Cobble No Recovery	6.0 8.0				No recovery											
					8.0		Refusal at 8.0 ft. See Core Boring Report Note: HSA Refusal at 8.0 ft.											
10																		
15																		
20																		

Water Level Data

Date	Time	Elapsed Time (hr.)	Depth (ft.) to: Bottom of Casing	Bottom of Hole	Water

Sample Identification

O Open End Rod
T Thin Wall Tube
U Undisturbed Sample
S Split Spoon
G Geoprobe

Well Diagram

Riser Pipe
Screen
Filter Sand
Cuttings
Grout
Concrete
Bentonite Seal

Summary

Overburden (lin. ft.) 8.0
Rock Cored (lin. ft.) 7.0
Samples 4S

Boring No. B-527

Field Tests: Dilatancy: R-Rapid, S-Slow, N-None
Toughness: L-Low, M-Medium, H-High
Plasticity: N-Nonplastic, L-Low, M-Medium, H-High
Dry Strength: N-None, L-Low, M-Medium, H-High, V-Very High

[1]SPT = Sampler blows per 6 in. [2]Maximum particle size (mm) is determined by direct observation within the limitations of sampler size (in millimeters).

Note: Soil identification based on visual-manual methods of the USCS as practiced by Haley & Aldrich, Inc.

USCS_TB3APID USCSLIB4.GLB USCSTC3A.GDT G:\PROJECTS\70436\252\70436-252TBC.GPJ Jun 18, 04

HALEY & ALDRICH

CORE BORING REPORT

Boring No. B-527
File No. 70436-252
Sheet No. 2 of 2

Depth (ft)	Drilling Rate Min./ft	Run No.	Depth (ft)	Recovery/RQD in.	Recovery/RQD %	Weathering	Elev./ Depth (ft)	Visual Description and Remarks
								SEE TEST BORING REPORT FOR OVERBURDEN DETAILS
								Began coring at 8.0 ft.
		C1	8.0 13.0	60 38	100 53	Fresh Slight	**8.0**	Hard, fresh to slightly weathered, fine-grained, light gray DOLOSTONE, low angle to horizontal beds, closely spaced beds, weathered fracture surfaces **-PENFIELD DOLOSTONE-**
10								
		C2	13.0 15.0	23 9	98 38	Fresh		Hard, fresh to slightly weathered, fine-grained, light gray DOLOSTONE, low angle to horizontal beds, closely spaced beds, weathered fracture surfaces with zones of pits and mineral deposition in voids and fractures at 14.2 ft. to 14.5 ft. **-PENFIELD DOLOSTONE-**
15							**15.0**	Notes: Approximately 100 to 150 gallons of water lost during drilling.
20								

OBSERVATION WELL INSTALLATION REPORT

HALEY & ALDRICH

Well No.	Boring No.
MW-527	B-527

PROJECT	RI/FS-Valeo Former GM-Delco Chassis Facility Site	H&A FILE NO.	70436-252
LOCATION	Rochester, New York	PROJECT MGR.	T. Wells
CLIENT	REALM	FIELD REP.	D. Krause
CONTRACTOR	Nothnagle Drilling, Inc.	DATE INSTALLED	4/9/2004
DRILLER	Kevin	WATER LEVEL	

Ground El.	+/-535 ft	Location	12 ft. South and 24 ft. East of Column F-7
El. Datum	RCD		☐ Guard Pipe ☑ Roadway Box

SOIL/ROCK CONDITIONS	BOREHOLE BACKFILL
CONCRETE 0.8	CEMENT 1.5
FILL 8	BENTONITE 2.5
BEDROCK PENFIELD DOLOSTONE 15	QUARTZ SAND 15

(Bottom of Exploration)

(Numbers refer to depth from ground surface in feet)



(Not to Scale)

Type of protective cover/lock	
Height/Depth of top of guard pipe/roadway box above/below ground surface	0.0 ft
Height/Depth of top of riser pipe above/below ground surface	-0.3 ft
Type of protective casing:	None
Length	-- ft
Inside Diameter	-- in
Depth of bottom of guard pipe/roadway box	1.1 ft

Type of Seals	Top of Seal (ft)	Thickness (ft)
Concrete	0.0	1.5
Bentonite Seal	1.5	1.0
Quartz Sand	2.5	12.5

Type of riser pipe:	PVC
Inside diameter of riser pipe	2.0 in
Type of backfill around riser	Bentonite Pellets
Diameter of borehole	2.5 in
Depth to top of well screen	4.9 ft
Type of screen	Slotted
Screen gauge or size of openings	0.0 in
Diameter of screen	2.0 in
Type of backfill around screen	Quartz Sand
Depth of bottom of well screen	14.85 ft
Bottom of Silt trap	15.0 ft
Depth of bottom of borehole	15.0 ft

Riser Pay Length (L1)	+	Length of screen (L2)	+	Length of silt trap (L3)	=	Pay length
4.55 ft		10 ft		0.15 ft		14.7 ft

COMMENTS:

Form # 3010

HALEY & ALDRICH

TEST BORING REPORT

Boring No. B-528

Project RI-FS-Valeo Former GM-Delco Chassis Facility Site Rochester, New York
Client REALM
Contractor Nothnagle Drilling, Inc.

File No. 70436-252
Sheet No. 1 of 1
Start
Finish
Driller Jeff
H&A Rep. D. Krause
Elevation 535 +/-
Datum RCD
Location

	Casing	Sampler	Barrel	Drilling Equipment and Procedures
Type				Rig Make & Model:
Inside Diameter (in.)				Bit Type:
Hammer Weight (lb.)				Drill Mud:
Hammer Fall (in.)			-	Casing:
			-	Hoist/Hammer:

Depth (ft.)	SPT[1]	Sample No. & Rec. (in.)	Sample Depth (ft.)	Well Diagram	Elev./Depth (ft.)	USCS Symbol	Visual-Manual Identification and Description (Density/consistency, color, GROUP NAME, max. particle size[2], structure, odor, moisture, optional descriptions, geologic interpretation)	Gravel % Coarse	Gravel % Fine	Sand % Coarse	Sand % Medium	Sand % Fine	% Fines	Field Test Dilatancy	Field Test Toughness	Field Test Plasticity	Field Test Strength
0							Concrete										
					1.1		Very stiff, brown sandy SILT with gravel, mps 0.75 in., no odor, slightly moist Very stiff, brown sandy SILT with gravel, mps 0.75 in., no odor, slightly moist										
							Dense, light to dark gray, poorly-graded SAND with gravel, mps 0.75 in.										
5					4.9		Stiff, tan to black sandy SILT with gravel, mps 0.75 ft. to 50 in., vary slight petroleum odor										
		S1	6.5 8.5	NO WELL INSTALLED													
					8.5		Refusal at 8.5 ft. (sample 0886-040904-1015 B-528:6.5 to 8.5 ft.)										
10																	

Water Level Data					
Date	Time	Elapsed Time (hr.)	Depth (ft.) to: Bottom of Casing	Bottom of Hole	Water

Sample Identification	
O	Open End Rod
T	Thin Wall Tube
U	Undisturbed Sample
S	Split Spoon
G	Geoprobe

Well Diagram	
	Riser Pipe
	Screen
	Filter Sand
	Cuttings
	Grout
	Concrete
	Bentonite Seal

Summary	
Overburden (lin. ft.)	8.5
Rock Cored (lin. ft.)	--
Samples	1S

Boring No. B-528

Field Tests: Dilatancy: R-Rapid, S-Slow, N-None
Toughness: L-Low, M-Medium, H-High
Plasticity: N-Nonplastic, L-Low, M-Medium, H-High
Dry Strength: N-None, L-Low, M-Medium, H-High, V-Very High

[1]SPT = Sampler blows per 6 in. [2]Maximum particle size (mm) is determined by direct observation within the limitations of sampler size (in millimeters).

Note: Soil identification based on visual-manual methods of the USCS as practiced by Haley & Aldrich, Inc.

USCS_TB3APID USCSLIB4.GLB USCSTC3A.GDT G:\PROJECTS\70436\252\70436-252TBC.GPJ Jun 18, 04

HALEY & ALDRICH

LOW FLOW/MNA FIELD SAMPLING FORM

Page of

PROJECT	RI/FS Valeo Former GM-Delco Chassis Facility	H&A FILE NO.	70436-242
LOCATION	Rochester, New York	PROJECT MGR.	T. Wells
CLIENT	REALM	FIELD REP	D. Krause
CONTRACTOR		DATE	04/28/04

Sampling Data:

Well ID: MW-527 Well Depth: ft Initial Depth To Water: ft Purging Device: low flow, comp. gas

Start time: Depth To Top Of Screen: ft Depth Of Pump Intake: ft Tubing Present In Well: ☐ Yes ☑ No

Finish Time: Depth To Bottom Of Screen ft Tubing Type: HDPE

Elapsed Time (24 hour)	Depth To Water From Casing (ft)	Pump Setting (ml/min) or (gal/min)	Purge Rate (ml/min) or (gal/min)	Cumulative Purge Vol. (liters) or (gal)	Temp-erature (°F) or (°C)	pH	Conduct-ivity (us/cm)	Dissolved Oxygen (mg/L)	Turbidity (NTU)	ORP/eH (mv)	Iron (mg/L)	Alkalinity (mg/L)	CO2 (mg/L)	Comments
920					23.02	7.4	1.77	1.02	120.0	87				
923					23.15	7.43	1.78	0.51	83.6	50				
926					23.18	7.42	1.77	0.34	65.0	32				
929					23.2	7.41	1.77	0.26	51.6	17				
932					23.21	7.41	1.76	0.22	43.0	8				
935					23.22	7.41	1.75	0.19	37.9	-2				
938					23.22	7.41	1.75	0.12	30.1	-9				
941	Sample	#0886-042804-0941									**0.2**	**360.0**	**520.0**	
		GW- PP Metals												
	NOTES:	MW-505 Two semi-permanent piezometers back by canal, B-532,B-533, were sounded and were both dry												
		DTB: 9.16												
		DTW: 9.02												

Form 3010

APPENDIX B

Updated page for the Citizen Participation Plan

7. List of Project Contacts for the Valeo/Former GM - Delco Chassis Facility Site

For additional information about the program to investigate the Valeo/Former GM- Delco Chassis Facility site, we encourage you to contact any of the following people:

New York State Department of Environmental Conservation:

Todd M. Caffoe, P.E., Project Manager (585) 226-5350
Citizen Participation Specialist (585) 226-5326
NYSDEC
6274 East Avon-Lima Road
Avon, NY 14414-9519

*You can also call **toll-free** 1-800-342-9296. Calls are recorded 24 hours a day. Leave your name, number and a brief message and someone will get back to you shortly.*

New York State Department of Health:

Matthew Forcucci, Technical Lead
NYSDOH
584 Delaware Avenue
Buffalo, NY 14202

Monroe County Health Department:

Joseph Albert (585) 274-6904
Monroe County Health Department
111 Westfall Road
PO Box 92832
Rochester, NY 14692

GM:

Mollie West (313) 665-3160
Mail Code 482-C29-B24
Media Relations
General Motors
300 Renaissance Center
Detroit, MI 48265-3000

Valeo:

James Kolanek (248) 340-3723
Environmental Safety & Health
Valeo Wiper Systems & Electric Motors
3000 University Drive
Auburn Hills, MI 48326-2356