

February 12, 2010

Mr. David Szymanski New York State Department of Environmental Conservation 270 Michigan Ave. Buffalo, NY 14203

Re: 2009 Periodic Review Report

Pfohl Brothers Landfill, Town of Cheektowaga, New York

Site 915043

Dear Mr. Walia:

Enclosed is the 2009 Periodic Review Report for the Pfohl Brothers Landfill in Cheektowaga, New York. URS has prepared this report on the behalf of the Town of Cheektowaga in accordance with your correspondence to Mr. William Pugh, Town of Cheektowaga Engineer, received January 4, 2010.

If you have any questions on this report, please feel free to contact me.

Sincerely,

URS CORPORATION

Jon Sundquist, Ph.D.

Project Manager

Enclosures

cc: William Pugh, P.E. – Town of Cheektowaga (w/attachments)

File 11172700 (C-1)

PERIODIC REVIEW REPORT 2009 PFOHL BROTHERS LANDFILL CHEEKTOWAGA, NY

Submitted to:

NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION 270 MICHIGAN AVENUE BUFFALO, NEW YORK 14203

Prepared by:

URS CORPORATION
77 GOODELL STREET
BUFFALO, NEW YORK 14203

Prepared for:

TOWN OF CHEEKTOWAGA
ENGINEERING DEPARTMENT
275 ALEXANDER AVE
CHEEKTOWAGA, NEW YORK 14211

FEBRUARY 2010

TABLE OF CONTENTS

1.0	Introduction	. 1
1.1	Background	. 1
1.2	Effectiveness of Remedial Program	. 1
1.3	Compliance	. 1
1.4	Recommendations	. 2
2.0	Site Overview	. 2
2.1	Site Description	. 2
2.2	Chronology	. 2
3.0	Remedy Performance, Effectiveness and Protectiveness	. 2
3.1	Groundwater Monitoring	. 3
3.2	Surface Water/Sediment Sampling	. 3
3.3	Effluent Monitoring	. 3
3.4	Hydraulic Monitoring	. 4
3.5	Wetlands Monitoring	. 4
3.6	General Physical and Mechanical Maintenance	. 4
4.0	IC/EC Plan Compliance	. 4
4.1	Institutional Controls	. 5
4.2	Engineering Controls	. 5
5.0	Operation & Maintenance and Monitoring Plan Compliance	. 5
6.0	Conclusions and Recommendations	. 5

FIGURES

Figure 2-1 Site Plan

ATTACHMENTS

Attachment A January 2009 – June 2009 Semi Annual Report
Attachment B July 2009 – December 2009 Semi Annual Report

Attachment C IC/EC Certification

1.0 INTRODUCTION

1.1 Background

This Pfohl Brothers Landfill Site (No. 915043) is a 130 acre landfill located on the north and south sides of Aero Drive in the Town of Cheektowaga, Erie County. The site is located in a commercial area just west of Transit Road. The landfill was operated between 1940 and 1969 receiving household and industrial wastes. The industrial waste materials included paints, waste solvents, thinners, pine tar pitch, cellulose, rubber, scrap metal and phenolic tars. A Remedial Investigation and Feasibility Study was completed in 1991. The data showed that on-site soils, groundwater, seeps, and sediments were contaminated with Volatile and Semi-Volatile Organic Compounds, and metals at various concentrations. The data did not show any significant off-site impact. A Record of Decision (ROD) was issued in 1992 requiring the landfill to be consolidated and closed. A second ROD was issued in 1994 which removed the northern portion of the site (located immediately south of Interstate 90) from the site description. The ROD also stated that there will be no action in regard to off-site groundwater. The final remedial design for the site was completed in 2000. The remedial construction consisted of waste consolidation; capping of landfills on either side of Aero Drive; providing leachate collection around these areas; restoring wetlands; and fencing the landfill. Work commenced in 2001 and was completed in 2002. The consolidated landfill was reduced to 94 acres. Deed restrictions have been filed by the Potentially Responsible Parties (PRPs). The Operation, Maintenance and Monitoring (OM&M) Plan was approved in March 2006 and is being implemented by the Town of Cheektowaga.

1.2 Effectiveness of Remedial Program

During 2009, the capping and remedial action remedy continued to successfully prevent exposure of buried waste to human health or environmental receptors. Effectiveness has been demonstrated through maintenance of the landfill cap, effective hydraulic control of groundwater beneath the cap, and regular semiannual groundwater sampling.

1.3 Compliance

The management of the site is in compliance with the OM&M Plan. Institutional controls in the form of deed restrictions remain in place.

1.4 Recommendations

No changes to the operation, maintenance, and monitoring of the site are recommended.

2.0 SITE OVERVIEW

2.1 <u>Site Description</u>

The boundaries of the site are shown on Figure 2-1. The site is located immediately southwest of the intersection of Interstate 90 and Transit Road in the Town of Cheektowaga. The site is bisected by the east/west Aero Drive. Each of the two portions of the landfill are covered with a cap comprising a gas venting layer, a low permeability synthetic membrane, and a barrier protection fill layer. Surrounding the entire site is a groundwater/leachate collection system consisting of a collection trench that drains into six wetwells. Leachate and groundwater collected in the wetwells is pumped via submersible pumps in the wetwells to a fifteen-inch sanitary sewer line on the south side of Aero Drive. This sanitary sewer, installed as part of the remedy, connects to the existing fifteen-inch sanitary sewer on Rein Road south of Aero Drive. The collected groundwater/leachate discharges to the sanitary sewer under a permit from the Buffalo Sewer Authority (BSA).

2.2 Chronology

The principal elements of the remedy were consolidation of waste materials, construction of a landfill cap and construction of a perimeter leachate collection system. Construction of the remedy was completed in 2002.

OM&M commenced in 2002 upon completion of construction. These efforts are performed in accordance with the OM&M plan issued as draft in 2002 and approved as final in 2006. Based upon the results of the first three years of surface water, sediment and monitoring results, the surface water/sediment sampling was discontinued in 2008, and the list of parameters evaluated during groundwater sampling was reduced in 2006 (limiting the list of VOC and SVOC parameters and metals) and 2007 (discontinuing dioxin and radionuclide analyses).

3.0 REMEDY PERFORMANCE, EFFECTIVENESS AND PROTECTIVENESS

The principal elements of the OM&M are:

▶ Groundwater Monitoring

- ▶ Surface Water/Sediment Sampling
- ► Effluent Monitoring
- ▶ Hydraulic Monitoring
- Wetlands Monitoring
- General physical and mechanical maintenance.

The Town of Cheektowaga submits OM&M reports to NYSDEC twice per year reporting on the performance, effectiveness, and protectiveness of each of these elements. The two reports covering the calendar year of 2009 are attached to this Periodic Review Report. A summary of the findings of performance, effectiveness, and protectiveness for 2009 is presented in the sections below.

3.1 **Groundwater Monitoring**

As the OM&M contractor for the Town of Cheektowaga, URS Corporation (URS) has performed twelve rounds of semi-annual groundwater sampling. Sampling was conducted in May and November 2009. Results of this sampling continue to show no impacts to groundwater from the landfill. In brief, no VOCs or SVOCs were detected, and metals detected are at concentrations similar to previous sampling events and are attributable to naturally occurring or offsite (e.g. road salting operations) sources. The attached semi-annual reports present the data from this sampling in tables, graphs, and charts.

3.2 Surface Water/Sediment Sampling

Surface water and sediment sampling was discontinued in 2008 after three years of sampling showed that no site-related contaminants were present in these media. This sampling was eliminated in accordance with the approved OM&M plan and as approved by NYSDEC.

3.3 Effluent Monitoring

URS performed effluent monitoring on a quarterly basis during 2009. The results of the sampling are reported in the attached semiannual report. The parameter values in the effluent have always been well below the discharge criteria for all quarterly sampling events conducted since the start of the OM&M.

3.4 **Hydraulic Monitoring**

URS performed hydraulic monitoring on a quarterly basis during 2009. Hydraulic monitoring is performed through measuring the water elevation in each of the six wetwells and in nine manholes associated with the perimeter collection system, and comparing each of these elevations with the groundwater elevations in paired monitoring wells adjacent to each wetwell or manhole. Hydraulic control is demonstrated by an hydraulic gradient from the monitoring wells to the collection system. The hydraulic gradient has been towards the groundwater collection system for every quarterly measurement taken.

3.5 Wetlands Monitoring

The monitoring of wetlands mitigation has not gone as originally planned in the OM&M manual. Initially, the wetlands species planted for mitigation faired poorly due to trampling from geese and deer. Fences were erected in 2004 to keep this wildlife out. Some wetland vegetation was also lost during landfill cap mowing in 2005 when the mowing contractor mowed a greater area than had been specified. The wetland vegetation species were replanted in 2005. However, in the time since construction ended in 2002, the *Phragmites sp.* vegetation that is quite abundant in this area has spread and established itself throughout the areas formerly disturbed during construction. *Phragmites sp.* does not provide robust food source for wildlife, but does act to stabilize soil in the interface zone between the landfill and the existing pond and wetland.

3.6 General Physical and Mechanical Maintenance

The Town of Cheektowaga performs the necessary general physical and mechanical maintenance as needed. Example maintenance items are routine maintenance and replacement of pumps and instrumentation used for groundwater/leachate collection, annual cap mowing, snow plowing, etc. A summary of the general maintenance activities performed during 2009 is provided in the attached semiannual reports.

4.0 IC/EC PLAN COMPLIANCE

There is no formal Institutional Control/Engineering Control (IC/EC) plan for this site. However, there are institutional and engineering controls in place and they are functioning as intended. These are discussed below.

4.1 <u>Institutional Controls</u>

Institutional controls (ICs) consist of restrictions on land use for the various parcels that comprise this site. The parcels subject and their restrictions are listed on the attached Site Management Periodic Review Report Notice Institutional and Engineering Controls Certification Form. The restrictions address building use, groundwater use, and land use. Compliance with these ICs is evaluated by observation to see if any infringing activities are occurring on these parcels. These ICs remain in effect, as certified in Attachment C.

Engineering Controls


Engineering controls (ECs) consist of the landfill cap, fencing and access control, collection of the groundwater/leachate, and vapor mitigation. Compliance with these ECs is evaluated at a minimum through inspection of these elements during each semiannual monitoring event. In most cases, inspection is more frequent. For example collection of the groundwater/leachate is monitored continuously by Town of Cheektowaga personnel and effluent compliance reports are submitted quarterly. These ECs remain in effect, as certified in Attachment C.

5.0 OPERATION & MAINTENANCE AND MONITORING PLAN COMPLIANCE

The components of the OM&M Plan are discussed above in Section 3.0. Summaries of OM&M activities performed during 2009 are provided in the attached semiannual reports. The OM&M activities show that the landfill and its groundwater/leachate collection system are operating as intended, and receive repairs and maintenance as needed in a timely fashion. Sampling of the groundwater in monitoring wells and the effluent generated by the groundwater/leachate collection system show that no landfill contamination is migrating to these media, and therefore the wastes remain effectively contained. No changes to the OM&M for this site are recommended.

6.0 CONCLUSIONS AND RECOMMENDATIONS

The remedy at the Pfohl Brothers Site Landfill is operating as designed and remains protective of human health and the environment. No changes to the OM&M for this site are recommended.






Site Boundary

URS

300 Feet

FIGURE 2-1



ATTACHMENT A

January 2009 – June 2009 Semi Annual Report

SEMI ANNUAL REPORT OPERATION AND MAINTENANCE JANUARY 2009 TO JUNE 2009 PFOHL BROTHERS LANDFILL CHEEKTOWAGA, NY

Submitted to:

NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION 270 MICHIGAN AVENUE BUFFALO, NEW YORK 14203

Prepared by:

URS CORPORATION
77 GOODELL STREET
BUFFALO, NEW YORK 14203

Prepared for:

TOWN OF CHEEKTOWAGA
ENGINEERING DEPARTMENT
275 ALEXANDER AVE
CHEEKTOWAGA, NEW YORK 14211

AUGUST 2009



August 14, 2009

Mr. Jaspal Singh Walia, P.E. New York State Department of Environmental Conservation 270 Michigan Ave. Buffalo, NY 14203

Re: Semi-Annual Report

Pfohl Brothers Landfill, Town of Cheektowaga, New York

Dear Mr. Walia:

Enclosed are two copies of the eleventh Semi-Annual Report for the Pfohl Brothers Landfill in Cheektowaga, New York. A copy has also been sent to Ms. Pamela Tames, P.E. of the United States Environmental Protection Agency. Also enclosed are Data Usability Summary Reports for laboratory analyses associated with the sampling events. PDF copies of the reports are also enclosed.

If you have any questions on this report, please feel free to contact me.

Sincerely,

URS CORPORATION

Jon Sundquist, Ph.D.

Project Manager

Enclosures

cc: Pamela Tames, P.E. - USEPA (w/attachments)

William Pugh, P.E. – Town of Cheektowaga (w/attachments)

File 11172700 (C-1)

TABLE OF CONTENTS

			Page No.			
1.0	INTRO	ODUCTION	1-1			
	1.1	Background	1-1			
	1.2	Operation and Maintenance Activities				
2.0	GENE	ERAL MAINTENANCE ACTIVITIES	2-1			
3.0	MONI	TORING ACTIVITIES	3-1			
	3.1	Groundwater Hydraulic Monitoring	3-1			
	3.2	Groundwater Quality Monitoring	3-1			
	3.3	Groundwater Discharge Monitoring	3-3			
	3.4	Monitoring Well Inspections	3-4			
4.0	SUMM	MARY AND RECOMMENDATIONS	4-1			
		TABLES				
Table 3	3-1	Groundwater Sample Results				
Table 3	3-2	Approved Revision Of Table 3.2 From The O&M Plan				
		FIGURES				
Figure	1-1	Site Location Map				
Figure	3-1	Monitoring Locations				
		APPENDICES				
Appen	dix A	Example Daily Inspection Sheets				
Appen	dix B	Monthly Flow Summaries (January 2009 – June 2009)				
Appen	dix C	Hydraulic Monitoring Tables				
Appen	dix D	Groundwater Purge and Sample Collection Logs				
Appendix E		E Historical Analytical Results				
Appendix F		BSA Permit No. 05-12-CH016				
Appendix G		Discharge Report Summary Tables				
Appendix H		H Monitoring Well Inspection Logs				

1.0 INTRODUCTION

1.1 Background

The Pfohl Brothers Landfill is located on Aero Drive in the Town of Cheektowaga, New York (Figure 1-1). The site is listed as site No. 9-15-043 on the New York State Department of Environmental Conservation's (NYSDEC's) Registry of Inactive Hazardous Waste Disposal Sites. A Consent Order between NYSDEC and potentially responsible parties (PRPs) for closure of the site was signed in 2001 and remedial construction commenced in 2001. The remedy included consolidation of waste material, capping of the waste disposal and consolidation areas, and encircling the landfill areas with a groundwater collection system to prevent off-site migration. The remedial action was completed in 2002.

Responsibility for implementing the remedy was divided between a "steering committee" of industrial PRPs and the Town of Cheektowaga. The steering committee responsibilities lay generally with the capital construction activities of the remedy including waste consolidation, cap and drainage system installation, etc. The Town of Cheektowaga, which was named as a PRP for disposal of municipal waste at the Pfohl Brothers Landfill when it was operating, is performing the operation and maintenance (O&M) activities at the landfill, pursuant to a settlement agreement between the Town and the steering committee.

1.2 Operation and Maintenance Activities

While construction of the remedy was substantially complete by late 2002, the final O&M manual was not approved by the NYSDEC until March 10, 2006. However, the Town of Cheektowaga and its consultant (URS Corporation) assumed most of the operational responsibilities since 2002. This includes a variety of general maintenance activities as outlined in Section 2 and sampling and other monitoring activities outlined in Section 3.

Beginning in 2004, the Town and URS assumed all of the O&M activities described in the O&M plan. This report is the eleventh semi-annual report as called for by Section 3.6 of the O&M plan.

2.0 GENERAL MAINTENANCE ACTIVITIES

Since completion of construction activities in 2002, personnel from the Town of Cheektowaga Engineering Department have performed general activities to ensure the physical operation of the landfill as intended by the design. The various O&M activities performed by the Town from January 2009 through June 2009 include the following actions.

- The amount of groundwater discharged through the collection system was recorded on a daily basis. The flow rate displayed by each wet well pump at the time of daily inspection and the total cumulative volume of flow was recorded for each wet well on daily inspection sheets. Examples of the daily inspection sheet are attached in Appendix A.
- Total cumulative effluent flow rates and volumes were summarized on a monthly basis starting in February 2003. The monthly totals for the period of January 2009 through June 2009, including graphs showing daily total discharge (gallons) as a function of calendar day, are presented in Appendix B.
- The wet well pumps were shutdown during wet weather flow conditions throughout the year to reduce hydraulic loading to the sewer. Such actions were only taken upon request of the Buffalo Sewer Authority during heavy storm events in order to reduce the hydraulic load on the BSA treatment system during such events. Shutdown events are recorded and included with the monthly flow data as previously requested by NYSDEC.
- Plowed snow to access the Control Building when necessary.
- Activated remote pump station shutdown during wet weather flow conditions as necessary. Shutdown events are recorded and included with the monthly flow data as previously requested by NYSDEC.
- Cleaned/replaced check valves as necessary at all wet wells.

- Prepared bid specifications for mowing landfill cap and awarded new contract for calendar years 2009, 2010, and 2011 (March 2009),
- Purchased and installed replacement flow transmitter in WW-3 (March 2009),
- Engaged wildlife trapper to control woodchuck activity (May 2009),
- Made repairs to discharge hose WW-4 (February 2009),
- Installed post mounted signs to identify all wetwells and manholes (May 2009)

3.0 MONITORING ACTIVITIES

The Town of Cheektowaga retained URS Corporation to perform monitoring activities as outlined in Section 3.1 of the O&M plan. During the period of January 2004 through the present, URS performed groundwater hydraulic monitoring (Section 3.1.1.2 of the O&M plan) and effluent monitoring (Section 3.1.4 of the O&M plan) on a quarterly basis. URS also performed the eleventh semi-annual groundwater quality monitoring event (Section 3.1.1.3 of the O&M plan). A summary of the monitoring activities is presented in the following subsections. Hydraulic and groundwater sampling locations are shown on Figure 3-1.

3.1 Groundwater Hydraulic Monitoring

Groundwater and surface water elevations were monitored on a quarterly basis at all locations listed in Table 3.1 of the O&M Plan. The hydraulic monitoring data tables showing groundwater elevations are presented in Appendix C. Table 1 of this appendix lists the measured elevations. Table 2 provides a comparison of the measured levels in the wells and corresponding manholes/wet wells.

The data presented in Appendix C indicate that groundwater levels outside the collection system were higher than the levels measured in the corresponding wet well or manhole for each measurement date. These data verify that collection system is operating as designed.

3.2 Groundwater Quality Monitoring

The eleventh semi-annual round of groundwater sampling was conducted between May 4, 2009 and May 7, 2009. All wells listed in Table 3.2 of the O&M plan were purged and sampled using dedicated/disposable equipment. Figure 3-1 shows the well locations. Low flow sampling techniques were used on most wells. Three wells, GW-4S, GW-7S, and GW-7D, were purged dry before a sample could be collected. These wells were sampled after their water levels recovered. Purge logs and sampling summary sheets are provided in Appendix D. Measurements of pH, specific conductivity, temperature, dissolved oxygen, oxidation reduction potential, and

turbidity taken during purging are provided in Appendix D. The samples were packed with ice in coolers and transported under chain-of-custody (CoC) control to Test America Laboratories of Amherst, New York.

Groundwater samples were analyzed for the parameters listed in Table 3.2 of the O&M plan as revised in accordance with Table 3-6 in the Semi Annual Report date September 2007 (January through June 2007) and as approved by the December 6, 2006 and November 29, 2007 correspondence from the NYSDEC authorizing a reduction in the parameters list (this table is included in this report as Table 3-2). Table 3-1 of this report presents the groundwater sample results compared with NYSDEC Ambient Water Quality Standards and Guidance Values and Groundwater Effluent Limitations Class GA water quality standards.

No VOCs were detected at concentrations above the Class GA water quality standards at any location. One SVOC, bis(2-ethylhexyl)phthalate, was detected at a concentration slightly exceeding its Class GA water quality standard in the upgradient well GW-07D.

Among the metals, iron, magnesium, manganese, and sodium routinely exceed Class GA standards in most site wells. The concentration of iron, magnesium, manganese, and sodium in most site wells was similar to the concentrations found during previous sampling events. Lead exceeded its groundwater standard in upgradient well GW-07D. Nickel was detected at a concentration exceeding its groundwater standard in wells GW-03S and GW-07S.

Sodium concentrations were generally higher in bedrock wells (GW-1D, GW-3D, GW-8D and GW-26D) and shallow wells adjacent to roads (GW-1S and GW-30S). No significant changes in metals concentrations were observed when compared to previous sampling event analytical results. The higher sodium concentrations in the bedrock wells may be attributed to the local bedrock composition and the elevated concentration in the shallow wells may be the result of seasonal road de-icing activities.

Appendix E, Figures E-1 through E-19 presents a trend analysis of groundwater parameters that routinely exceed Class GA groundwater standards. A review of the trend analysis indicated that no significant changes or trends in concentrations of any of the parameters

except as described below. Figure E-2 for GW-01S, indicates a consistent drop in sodium concentration over the last four sampling events. Figure E-4 for GW-03S indicates an upward trend for manganese over recent sampling events. Figure E-5 for GW-04D, indicates a slight drop in magnesium concentration which had been increasing over several sampling events. Figure E-7 provides a trend analysis for upgradient monitoring well GW-7D for chromium, iron, lead, and sodium. The metals concentrations at this upgradient well had been slowly increasing over several monitoring events but concentrations were drastically lower during the last two events. Figure E-13 for GW-29S, indicates a drop in iron concentration after concentrations had been slowly increasing over the three previous events.

The groundwater analytical data package was prepared by Test America in accordance with NYSDEC Category A deliverable requirements. It was reviewed for compliance with analytical method requirements and the following guidelines: USEPA *Contract Laboratory Program (CLP) National Functional Guidelines for Organic Data Review*, EPA-540-R-99-008, October 1999; USEPA *CLP National Functional Guidelines for Inorganic Data Review*, EPA-540-R-01-008, July 2002; and USEPA *Region II Data Validation SOP for SW-846 Method 8290, PCDDs and PCDFs by High Resolution Gas Chromatography/High-Resolution Mass Spectrometry (HRGC/HRMS)*, SOP No. HW-19, Revision 1, October 1994. Qualifications applied to the data include "J/UJ" (estimated concentration/estimated quantitation limit), "J+" (estimated concentration with possible high bias), "J-" (estimated concentration with possible low bias), and "U" (not detected).

A Data Usability Summary Report (DUSR) was prepared following the guidelines provided in NYSDEC Division of Environmental Remediation *Guidance for the Development of Data Usability Summary Reports*, dated June 1999. The DUSR dated June 2009 is submitted separately from this report.

3.3 Groundwater Discharge Monitoring

URS completed two quarterly sampling events (March 2009 and June 2009) of the groundwater collection system discharge since the previous semi-annual report. The sampling

was performed in accordance with the requirements of Discharge Permit No. 05-12-CH016 between the Buffalo Sewer Authority and the Town of Cheektowaga. A copy of Permit No. 05-12-CH016 is included as Appendix F.

During the sampling events in March 2009 and June 2009, each regulated parameter was below the limits set by the permit. Copies of the data summary tables that were included with the monitoring reports are included as Appendix G.

3.4 Monitoring Well Inspections

During the May 2009 groundwater sampling event, a well inspection was performed. All wells appeared to be in good condition with the exception of previously existing damage to the riser on GW-07D, and new damage to the risers at GW-01S and GW-01D. It appears that the weep holes in the protective casing at GW-01S and GW-01D corroded shut allowing water to accumulate in the annular space between the riser and protective casing and freeze during the winter thus indenting the stainless steel risers. Sampling could still be conducted, however the stainless steel bailer present in GW-01S could not be removed. The weep holes were redrilled during the June quarterly effluent sampling event to prevent further damage. The locks at GW-01S, GW-01D, and GW-07S required lubrication and were functioning properly afterwards. The monitoring well inspection logs may be found in Appendix H.

4.0 SUMMARY AND RECOMMENDATIONS

General Maintenance: The Town will continue to maintain mechanical equipment at the landfill on an as-needed basis and operate the groundwater collection and discharge system as designed. The Town will also continue regular inspections, mow the cap once per year, and plow access to the control building during winter months as necessary.

Groundwater Hydraulic Monitoring: Hydraulic monitoring has been performed on a quarterly basis in conjunction with the discharge monitoring. Water level measurement data demonstrates that the hydraulic gradient is from outside the landfill towards the collection trench. Continued quarterly monitoring is recommended.

Groundwater Quality Monitoring: Groundwater sample results indicate that only low levels of organic compounds and metals are present. Similar concentrations of most parameters were found during previous sampling events. The twelfth round of groundwater sampling will be conducted in November 2009. Low flow sampling techniques will continue to be used on wells that historically have been purged to dryness. A review of the purge logs (Appendix D) has indicated that four wells (GW-4S, GW-7S, GW-7D, and GW-31S) can still be purged to dryness even using low flow sampling techniques.

Groundwater Discharge Monitoring: Groundwater discharges remain within permit limits. Continued quarterly monitoring is recommended.

Surface Water and Sediment Sampling: URS asked that the NYSDEC consider the discontinuation of surface water and sediment sampling at the site in the January to June 2008 Semiannual Report. No future surface water or sediment sampling is planned.

Wetland Inspection Summary: An inspection of the wetlands during the May 2009 event indicated that most of the replanted wetland stock has flourished and the wetland areas are returning to their natural state.

TABLES

Location ID			GW-01D	GW-01S	GW-03D	GW-03S	GW-04D
Sample ID	GW-1D	GW-1S	GW-3D	GW-3S	GW-4D		
Matrix			Groundwater	Groundwater	Groundwater	Groundwater	Groundwater
Depth Interval (f	t)		-	-	-	-	-
Date Sampled			05/07/09	05/07/09	05/05/09	05/05/09	05/07/09
Parameter	Units	*					
Volatile Organic Compounds							
1,2-Dichloroethene (total)	UG/L	-			0.97 J		
Acetone	UG/L	-					
Vinyl chloride	UG/L	-			0.81 J		
Semivolatile Organic Compounds							
bis(2-Ethylhexyl)phthalate	UG/L	0.6					
Metals							
Arsenic	MG/L	0.15					
Barium	MG/L	-	0.0611	0.154	0.0864	0.154	0.0543
Cadmium	MG/L	1	0.0003 J	0.0007 J		0.0004 J	
Chromium	MG/L	193	0.0028 J	0.0033 J	0.0012 J	0.0275	
Copper	MG/L	24.3		0.0016 J		0.0028 J	
Iron	MG/L	0.3	0.536	11.9	2.13	0.951	0.166
Lead	MG/L	13.1					
Magnesium	MG/L	-	30.8	13.8	19.0	78.2	58.8
Manganese	MG/L	-	0.0216	0.757	0.990	0.521	0.0201
Nickel	MG/L	140		0.0017 J	0.0054 J	0.366	
Sodium	MG/L	-	86.6	163	206	41.0	57.4
Zinc	MG/L	223	0.0103	0.0158	0.0061 J	0.0200	0.0135

Flags assigned during chemistry validation are shown.

Concentration Exceeds

^{*-} NYSDEC TOGS (1.1.1), Ambient Water Quality Standards and Guidance Values and Groundwater Effluent Limitations. June 1998 (includes 4/2000 Addendum). Class B. * - Criteria based on sum of the aroclors.

Location ID			GW-04S	GW-07D	GW-07S	GW-08D	GW-08D
Sample ID	GW-4S	GW-7D	GW-7S	FD-050509	GW-8D		
Matrix			Groundwater	Groundwater	Groundwater	Groundwater	Groundwater
Depth Interval (f	t)		-	-	-	-	-
Date Sampled			05/07/09	05/05/09	05/05/09	05/05/09	05/05/09
Parameter	Units	*				Field Duplicate (1-1)	
Volatile Organic Compounds							
1,2-Dichloroethene (total)	UG/L	-					
Acetone	UG/L	-		7.4			
Vinyl chloride	UG/L	-					
Semivolatile Organic Compounds							
bis(2-Ethylhexyl)phthalate	UG/L	0.6		$\boxed{ 14}$			
Metals							
Arsenic	MG/L	0.15	0.0051 J			0.0046 J	0.0057 J
Barium	MG/L	-	0.115	0.0450	0.205	0.0657	0.0659
Cadmium	MG/L	-	0.0004 J	0.0009 J			
Chromium	MG/L	193	0.0204	0.0356		0.0031 J	0.0028 J
Copper	MG/L	24.3	0.0057 J	0.0112			
Iron	MG/L	0.3	4.61	4.04	0.171	2.61	2.60
Lead	MG/L	13.1		0.117			
Magnesium	MG/L	-	25.6	23.3	30.2	15.3	15.3
Manganese	MG/L	-	0.286	0.0560	0.0805	0.510	0.509
Nickel	MG/L	140	0.0160	0.0248	0.111	0.0026 J	0.0030 J
Sodium	MG/L	-	29.9	75.3	56.2	157	158
Zinc	MG/L	223	0.0477	0.0297	0.0079 J	0.0151	0.0154

Flags assigned during chemistry validation are shown.

Concentration Exceeds

^{*-} NYSDEC TOGS (1.1.1), Ambient Water Quality Standards and Guidance Values and Groundwater Effluent Limitations. June 1998 (includes 4/2000 Addendum). Class B. * - Criteria based on sum of the aroclors.

Location ID	Location ID			GW-26D	GW-28S	GW-29S	GW-30S
Sample ID			GW-8S(R)	GW-26D	GW-28S	GW-29S	GW-30S
Matrix			Groundwater	Groundwater	Groundwater	Groundwater	Groundwater
Depth Interval (fi	t)		-	-	-	-	-
Date Sampled			05/05/09	05/07/09	05/06/09	05/06/09	05/06/09
Parameter	Units	*					
Volatile Organic Compounds							
1,2-Dichloroethene (total)	UG/L	-		2.0 J			
Acetone	UG/L	ı	1.8 J				
Vinyl chloride	UG/L	ı	0.91 J	1.8			
Semivolatile Organic Compounds							
bis(2-Ethylhexyl)phthalate	UG/L	0.6					
Metals							
Arsenic	MG/L	0.15	0.0079 J			0.0212	
Barium	MG/L	1	0.506	0.127	0.0563	0.288	0.416
Cadmium	MG/L	-					
Chromium	MG/L	193	0.0009 J	0.0027 J			
Copper	MG/L	24.3					
Iron	MG/L	0.3	20.9	7.02	0.407	15.1	17.1
Lead	MG/L	13.1					
Magnesium	MG/L	-	48.6	19.7	36.9	77.8	51.3
Manganese	MG/L	-	0.982	1.07	1.04	0.727	2.57
Nickel	MG/L	140	0.0021 J	0.0020 J	0.0028 J		
Sodium	MG/L	-	238	222	30.0	13.9	728
Zinc	MG/L	223	0.0050 J	0.0037 J	0.0049 J	0.0184	

Flags assigned during chemistry validation are shown.

Concentration Exceeds

^{*-} NYSDEC TOGS (1.1.1), Ambient Water Quality Standards and Guidance Values and Groundwater Effluent Limitations. June 1998 (includes 4/2000 Addendum). Class B. * - Criteria based on sum of the aroclors.

Location ID			GW-31S	GW-32S	GW-33S	GW-34S	GW-35S
Sample ID	GW-31S	GW-32S	GW-33S	GW-34S	GW-35S		
Matrix			Groundwater	Groundwater	Groundwater	Groundwater	Groundwater
Depth Interval (f	t)		-	-	-	-	-
Date Sampled			05/06/09	05/06/09	05/06/09	05/04/09	05/07/09
Parameter	Units	*					
Volatile Organic Compounds							
1,2-Dichloroethene (total)	UG/L	-					
Acetone	UG/L	-					
Vinyl chloride	UG/L	-					
Semivolatile Organic Compounds							
bis(2-Ethylhexyl)phthalate	UG/L	0.6					
Metals							
Arsenic	MG/L	0.15					
Barium	MG/L	ı	0.0386	0.0557	0.0156	0.137	0.0523
Cadmium	MG/L	-					
Chromium	MG/L	193					0.0009 J
Copper	MG/L	24.3					
Iron	MG/L	0.3	0.443	0.063		0.202	0.019 J
Lead	MG/L	13.1					
Magnesium	MG/L	-	28.9	41.2	37.2	46.8	23.8
Manganese	MG/L	-	0.800	0.561	0.190	0.475	0.403
Nickel	MG/L	140	0.0025 J	0.0015 J	0.0044 J	0.0048 J	0.0018 J
Sodium	MG/L	-	5.7	4.1	5.4	35.9	2.7
Zinc	MG/L	223	0.0059 J	0.0261	0.0124	0.0044 J	0.0217

Flags assigned during chemistry validation are shown.

Concentration Exceeds

^{*-} NYSDEC TOGS (1.1.1), Ambient Water Quality Standards and Guidance Values and Groundwater Effluent Limitations. June 1998 (includes 4/2000 Addendum). Class B. * - Criteria based on sum of the aroclors.

FIGURES

URS



12/15/2005

APPENDIX A EXAMPLE DAILY INSPECTION SHEETS

Pfohl Brothers Landfill Site

Date Time 2 · 6 · 0 ? Weather conditions Read by: SUNTY 30 B. PU4 IH Level of Water from bottom (ft.) Flow gallons / minute Flow Totals gallons Pump Run Time Hrs. WW-3 5.2 0 20.8,38.8 / 295 WW-1 3.9 0 41,496 30 WW-1 3.9 0 588,770 //// // // // // // // // // // // // /	•	gsheet		Town of Cheektowa	
From bottom (ft.) gallons / minute gallons Hrs.		1:50			COLD 30
WW-3 5.2 0 208 388 /295					Pump Run Time Hrs.
WW-2 4.6 0 41,496 30 WW-1 3.9 0 588,770 1/71 WW-6 6.5 57.0 3,5/2,522 2318 WW-4 7.0 0 470,980 3337 WW-5 7.1 0 3,089,491 //57 Flow Totalizer at Meter chamber 8,255,964 Heat Trace Outside temp T = 30 Current A = 2.3 Set point SP = 40 Surge Suppressor events Motor Control Center Volts 480 volts Which WW was running? Amps 5 amps 10,20,30,40,50,60 60 Filter Checked Changed Changed Comments and/or Current Conditions J. NICHY ASO AT SITE TO TROUBLESHOOT WW 4. Hose Connection ABSE OF PUMP NEEDS PUMP NEEDS PUMP NEEDS PUMP HA.	WW-3	• •		1	I
WW-1 3.9 0 588,770 1/71 WW-6 6.5 57.0 3,5/2,522 23/8 WW-4 7.0 0 470,980 3331 WW-5 7.1 0 3,089,491 1/57 Flow Totalizer at Meter chamber B, 255,964 Heat Trace Outside temp T = 30 Outside temp T		_	D	/	
WW-6 6.5 57.0 3,5/2,522 2318 WW-4 7.0 0 470,980 3331 WW-5 7.1 0 3,089,491 1/57 Flow Totalizer at Meter chamber 8,255,964 Heat Trace Outside temp T = 30 Current A = 2.3 Set point SP = 40 Surge Suppressor events 1/68 Motor Control Center Volts Which WW was running? Amps 5 amps 1 2 3 4 5 6 € Filter Checked Changed Comments and/or Current Conditions J. NICHY ASO AT SITE TO TROUBLESHOOT WW 4. Hose Connector and Ar Base of Pump Needs REPAIR . WILL REVISIT SITE NEXT WEXT WEXES REPAIR . WILL REVISIT SITE NEXT WEXT WEXES REPAIR . POWER TURNED OFF TO PUMP # 4.				- 1	1171
WW-4		6.5			2318
Flow Totalizer at Meter chamber B, 255, 964		7.0			3331
Flow Totalizer at Meter chamber Heat Trace Outside temp T = 30 Current A = 2.3 Set point SP = 40 Set point SP = 40 Set point SP = 40 Motor Control Center Volts Amps 5 amps 1 2 3 4 5 6 X Filter Checked Changed Comments and/or Current Conditions J. NICHY ASO AT SITE TO TROUBLESHOOT WW 4. HOSE CONNECTION AT BASE OF PUMP NEEDS REPAIR. POWER TURNED OFF TO PUMP # 4.	WW-5	7.1	0	3,089,491	1157
Surge Suppressor events Set point SP = 40	Flow Tot		r	8,255,964	_
Volts 480 volts Which WW was running? Amps 5 amps 1 2 3 4 5 6 X Filter Checked Changed Comments and/or Current Conditions J. NICHY ASO AT SITE TO TROUBLESHOOT WW 4. HOSE CONNECTION AT BASE OF PUMP NEEDS RUAIR. WILL REVISIT SITE NEXT WEEK TO REPAIR. POWER TURNED OFF TO PUMP # 4.	Surge Su		168		
Comments and/or Current Conditions J. NICHY ALSO AT SITE TO TROUBLESHOOT WW 4. HOSE CONNECTION AT BASE OF PUMP NEEDS REPAIR. WILL REVISIT SITE NEXT WEEK TO REPAIR. POWER TURNED OF TO PUMP # 4.	Motor Co	Volts 480	_		j ?
J. NICHY ALSO AT SITE TO TROUBLESHOOT WW 4. HOSE CONNECTION AT BASE OF PUMP NEEDS REPAIR. WILL REVISIT SITE NEXT WEEK TO REPAIR. POWER TURNED OFF TO PUMP # 4.			-	*	
	Filter		Changed □		
	Comment	Checked	ons		
	Comment	Checked	ons		ww4,
	Comment	Checked	ons		ww4.
SIGNIFICANT DRIFTED SNOW COVER ON SITE.	Comment	Checked	ons		WW4, NEEDS WEEK TO
	Comment	Checked	ons		WW 4. NEEDS WEEK 70 PUMP # 4.
	Comment J. Ho. Rev	Checkedy standor Current Condition NICHY ASO SE CONNECTO PAIR. WILL PAIR. POWER	ONS AT SITE TO OND AT B REVISIT: TURNED	TROUBLESHOOT ASE OF PUMP SITE NEXT OFF TO F	
	Comment J. Ho. Rev	Checkedy standor Current Condition NICHY ASO SE CONNECTO PAIR. WILL PAIR. POWER	ONS AT SITE TO OND AT B REVISIT: TURNED	TROUBLESHOOT ASE OF PUMP SITE NEXT OFF TO F	

Pfohl Brothers Landfill Site

Daily Lo	gsheet		Town of Cheektowaga					
Date Time	3-27-09 1:00		Weather conditions Read by:	SUNNY 55° B. PUGH				
	Level of Water from bottom (ft.)	Flow gallons / minute	Flow Totals gallons	Pump Run Time Hrs.				
WW-3	4.1	35.5	284,005	1337				
WW-2	4.7	0	40 745	30 1390				
WW-1	4.1	1.0 2	1,147,272	2459				
WW-6	6.8	48,2	3,985,096	3379				
WW-4	7.1	6	541, 976	1574				
WW-5		6						
Flow Tota	alizer at Meter chambe	r 						
Heat Trac	Outside temp T = 55 Current A = 0		Set point SP = 40					
Surge Su	ppressor events	203	_					
Motor Cor	ntrol Center Volts 486 Amps 7	volts amps	Which WW was runnin	ng?				
Filter	Checked	Changed □						
Comment	s and/or Current Condition	ons						
* u	in 3 & mm	6 - LEVE	e ALARM (99) RESET				
-14-	AND PUM	PS BOTH	CAME ON	- OK FOR NOW				
AND PUMPS BOTH CAME ON -OK FOR NOW ** KEEP EYE ON WWZ - FLOW TOTAL THIS VISIT LESS THAN PRIOR VISIT - NEG. FLOW ALARM RESET								
LESS	THAN PRIOR V	BIT - NEG.	FLOW ALARI	y reser				
	canes au							
*	CLOCK NEC	DS TO E	ge moves	FORWARD				
	I HOUR O	N COMPUT	tn Process	DISPLAY				

APPENDIX B

MONTHLY FLOW SUMMARIES JANUARY 2009 – JUNE 2009

THE TOWN OF CHEEKTOWAGA



Main Pump Station 171 Central Boulevard Cheektowaga, NY 14225 Phone: 716-896-1777 Fax: 716-896-6437

February 7, 2009

Mr. William R. Pugh, P.E. Town Engineer Town of Cheektowaga

Re: Pfohl Bros. Flow Data

Dear Mr. Pugh,

Enclosed for your review, please find a copy of the **January 2009** Direct Discharge Flow Data Report, prepared by Jon W. Nichy.

There were no instances of inhibiting pumping operation, during this period. Should you have any other questions or comments regarding this submittal, please contact this office @ 896-1777.

Yours truly,

Town of Cheektowaga

løn W. Nichy

Superintendent

Main Pump Station

Direct Discharge Flow Data

40/04/0000	ſ	6755366			
12/31/2008 January-09	Time; 11:58pm unless otherwise stated	Totalizer Reading (Gallons)	64,538 Daily Total Discharge (Gallons)	6,755,391	Notes
1		6812926	57,560	6,812,951	
2		6868979	56,053	6,869,004	
3		6923737	54,758	6,923,762	
4		6976166	52,429	6,976,191	
5		7038272	62,106	7,038,297	
6		7164863	126,591	7,164,888	
7		7190956	26,093	7,190,981	
8		7238847	47,892	7,238,873	
9		7350287	111,440	7,350,313	
10		7417174	66,888	7,417,201	
11		7433800	16,626	7,433,827	
12		7451806	18,006	7,451,833	
13		7484257	32,451	7,484,284	
14		7543346	59,090	7,543,374	
15		7592796	49,450	7,592,824	
16		7609879	17,083	7,609,907	
17		7635814	25,935	7,635,842	
18		7648882	13,069	7,648,911	
19		7668564	19,682	7,668,593	
20		7758789	90,226	7,758,819	
21		7775754	16,965	7,775,784	
22		7794722	18,968	7,794,752	
23		7822681	27,959	7,822,711	
24		7825342	2,662	7,825,373	
25		7849238	23,896	7,849,269	
26		7866142	16,904	7,866,173	
27		7937676	71,535	7,937,708	
28		8008592	70,916	8,008,624	
29		8014598	6,007	8,014,631	
30		8014598	3 0	8,014,631	
31		8061906			
		1,306,540	1,306,548	1,306,548	

30 31 19 20 15 16 17 18 Pfohl Bros. January 2009 10 11 12 Daily Total Discharge (Gallons)

THE TOWN OF **CHEEKTOWAGA**



Main Pump Station

171 Central Boulevard Cheektowaga, NY 14225 Phone: 716-896-1777

Fax: 716-896-6437

March 6, 2009

Mr. William R. Pugh, P.E. Town Engineer Town of Cheektowaga

Re: Pfohl Bros. Flow Data

Dear Mr. Pugh,

Enclosed for your review, please find a copy of the February 2009 Direct Discharge Flow Data Report, prepared by Jon W. Nichy.

A monthly log sheet indicating inhibiting and enabling of pumping operation at

the site is included with this package.

Should you have any other questions or comments regarding this submittal, please contact this office @ 896-1777.

Yours truly,

Town of Cheektowaga

Jon W. Nichy

Superintendent


Main Pump Station

RECEIVED

MAR 1 0 2009

ENGINEERING DEPT Direct Discharge Flow Data

1/31/2009		8061906	47,308	8,061,939	
February-09	Time; 11:58pm unless otherwise stated	Totalizer Reading (Gallons)	Daily Total Discharge (Gallons)		Notes
1		8063154	1,249	8,063,188	
2		8093747	30,593	8,093,781	
3		8105566	11,820	8,105,601	
4		8160494	54,928	8,160,529	
5		8244018	83,525	8,244,054	
6		8265577	21,559	8,265,613	
7		8265577	0	8,265,613	
8		8301294	35,717	8,301,330	
9		8351039	49,746	8,351,076	
10		8415614	64,575	8,415,651	
11		8415614	0	8,415,651	
12		8415614	0	8,415,651	
13		8491851	76,237	8,491,888	
14		8618571	126,720	8,618,608	
15		8745291	126,720	8,745,328	
16		8867706	122,415	8,867,743	
17		8927103	59,397	8,927,140	
18		8944643	17,540	8,944,680	
19		8971168	26,525	8,971,205	
20		9029334	58,166	9,029,371	
21		9096229	66,895	9,096,266	
22		9122375	26,146	9,122,412	
23		9139164	16,789	9,139,201	
24		9158014	18,850	9,158,051	
25		9177684	19,670	9,177,721	
26		9244972	67,288	9,245,009	
27		9325156	80,184	9,325,193	
28		9419879	94,722	9,419,915	
29					
30					
31				40000	
		1,357,973	1,357,976	1,357,976	ני




PFOHL BROTHERS LANDFILL SITE CHEEKTOWAGA, NEW YORK

Auto Dialer System Log

			,
DATE	PUMP Inhibit -08 (Off)	TIME Enable -07 (On)	COMMENTS
1 /			
2/4/09	1201 pm	1202 pm	,
7/2/00	1/20		
2/1/07	428 pm	211	
2/8/09		911 am	
2/10/09	3:10 pm		
2/13/09	/	853am	
1			
	•		
2/27/29	853am	hullan	
7-1/51	U S Sugar	W-1-11pm	
		, , , , , , , , , , , , , , , , , , ,	
			·
1,			

THE TOWN OF CHEEKTOWAGA



Main Pump Station 171 Central Boulevard Cheektowaga, NY 14225

Phone: 716-896-1777 Fax: 716-896-6437

April 9, 2009

Mr. William R. Pugh, P.E. Town Engineer Town of Cheektowaga

Re:

Pfohl Bros. Flow Data

Dear Mr. Pugh,

Enclosed for your review, please find a copy of the **March 2009** Direct Discharge Flow Data Report, prepared by Jon W. Nichy.

A monthly log sheet indicating inhibiting and enabling of pumping operation at the site is included with this package.

Should you have any other questions or comments regarding this submittal, please contact this office @ 896-1777.

Yours truly,

Town of Cheektowaga

Jon W. Nichy

Superintendent

Main Pump Station

RECEIVED

APR 13 2009

ENGINEERING DEPT Direct Discharge Flow Data

	9,419,915		0440870		
	9,419,915	94,722	9419879	Time;	2/2//09
Notes		Daily Total Discharge (Gallons)	Totalizer Reading (Gallons)	March-09 11:58pm unless otherwise stated	
	9,434,896	14,981	9434859		1
	9,473,841	38,945	9473804		2
	9,485,227	11,386	9485190		3
	9,513,172	27,945	9513135		4
	9,555,179	42,007	9555142		5
	9,605,653	50,474	9605616		6
	9,618,086	12,433	9618049		7
	9,625,197	7,111	9625160		8
	9,663,896	38,699	9663859		9
	9,782,231	118,335	9782194		10
	9,833,175	50,944	9833138		11
2	9,940,307	107,132	9940270		12
	10,006,760	66,453	10006723		13
	10,059,925	53,165	10059888		14
	10,091,899	31,974	10091862		15
	10,091,899	0	10091862		16
	10,137,439	45,540	10137402		17
	10,137,439	0	10137402		18
	10,165,394	27,955	10165357		19
	10,278,099	112,705	10278062		20
	10,365,496	87,397	10365459		21
	10,376,082	10,586	10376045		22
	10,395,956	19,874	10395919		23
	10,459,899	63,943	10459862		24
	10,472,429	12,530	10472392		25
	10,477,703	5,274	10477666		26
	10,519,869	42,166	10519832		27
	10,557,604	37,735	10557567		28
	10,565,272	7,668	10565235		29
	10,581,211		10581174		30
	10,595,216 1,137,689		10595179 1,175,30 0		31

36.5

1012

12 13 14 15 16 17 18 Days Pfohl Bros. March 2009 Daily Total Discharge (Gallons)

基,-


M.

PFOHL BROTHERS LANDFILL SITE CHEEKTOWAGA, NEW YORK

Auto Dialer System Log

			* *
DATE	PUMP Inhibit -08 (Off)	TIME Enable -07 (On)	COMMENTS
3/7/09	1803pm		
3/8/09		0842	
		00,2	
3/8/09	23:00 pm		HEAVY RAIN
3/9/09		18,00 pm	CLEAN
			CCEAR
3/10/09	22/3 PM		RAIN
3/11/09		0959	1CP1710
3/11/09		7.17	Pare Failure
1	,		tore for love
3/29/09	1046	1425	
1			
CALL THE REAL PROPERTY.		Park Harry Company	RAIN
			1804770
			(8)+1)10

THE TOWN OF **CHEEKTOWAGA**



Main Pump Station 171 Central Boulevard Cheektowaga, NY 14225

Phone: 716-896-1777 Fax: 716-896-6437

May 2, 2009

Mr. William R. Pugh, P.E. Town Engineer Town of Cheektowaga

Re:

Pfohl Bros. Flow Data

Dear Mr. Pugh,

Enclosed for your review, please find a copy of the **April 2009** Direct Discharge Flow Data Report, prepared by Jon W. Nichy.

A monthly log sheet indicating inhibiting and enabling of pumping operation at

the site is included with this package.

Should you have any other questions or comments regarding this submittal, please contact this office @ 896-1777.

Yours truly,

Town of Cheektowaga

Jon W. Nichy

Superintendent Main Pump Station

RECEIVED

MAY 4 - 2009


ENGINEERING DEPT Direct Discharge Flow Data

				-	
	10,595,216	14,005	10595179	3/31//09	
Notes		Daily Total Discharge (Gallons)	Totalizer Reading (Gallons)	Time; 11:58pm unless otherwise stated	April-09
	10,613,853	18,637	10613816		1
	10,654,239	40,386	10654202		2
	10,719,324	65,085	10719287		3
	10,753,980	34,656	10753943		4
	10,777,002	23,022	10753943		5
	10,902,900	125,898	10879841		6
	10,931,737	28,837	10908678		* 7
	10,960,779	29,042	10937720		8
	10,977,241	16,462	10954182		9
	11,033,889	56,648	11010830		10
	11,106,659	72,770	11083600		11
	11,156,110	49,451	11133051		12
	11,192,498	36,388	11169439		13
	11,205,678	13,180	11182619		14
	11,227,139	21,461	11204080		15
	11,289,282	62,143	11289245		16
	11,332,565	43,283	11332528		17
	11,332,565	0	11332528		18
	11,340,198	7,633	11340161		19
	11,366,081	25,883	11366044		20
	11,384,857	18,776	~ 11384820		21
	11,414,995	30,138	11414958		22
	11,478,313	63,318	11478276		23
	11,568,852	90,539	11568815		24
	11,617,266	48,414	11617229		25
	11,649,896	32,630	11649859		26
	11,657,563	7,667	11657526		27
	11,660,466	2,903	11660429		28
	11,699,010	38,544	11698973		29
	11,699,010	0	11698973		30
					31
Ŀ	1,103,794	1,103,794	1,103,794		


PFOHL BROTHERS LANDFILL SITE CHEEKTOWAGA, NEW YORK

Auto Dialer System Log

DATE	PUMP Inhibit -08 (Off)	Enable -07 (On)	COMMENTS
4/1/09	1045 am	139 pm	
4/3/09	550 pm		,
4/4/09		127pm	
4/20/09	9:30 AM		RAIN
4/21/09		440 pm	LT. RHIN
			21. 11.110
			2
		12	
-			V
1.			



THE TOWN OF **CHEEKTOWAGA**



Main Pump Station 171 Central Boulevard

Cheektowaga, NY 14225 Phone: 716-896-1777 Fax: 716-896-6437

June 9, 2009

Mr. William R. Pugh, P.E. Town Engineer Town of Cheektowaga

Re: Pfohl Bros. Flow Data

Dear Mr. Pugh,

Enclosed for your review, please find a copy of the May 2009 Direct Discharge Flow Data Report, prepared by Jon W. Nichy.

A monthly log sheet indicating inhibiting and enabling of pumping operation at the site is included with this package.


Should you have any other questions or comments regarding this submittal, please contact this office @ 896-1777.

Yours truly,

Town of Cheektowaga

Jón W. Nichy / Superintendent

Main Pump Station



Direct Discharge Flow Data


		19011011				
	11,699,010	0	11698973	4/30//09		
Notes		Daily Total Discharge (Gallons)	Totalizer Reading (Gallons)	Time; 11:58pm unless otherwise stated		
	11,786,825	87,815	11786788		1	
	11,806,851	20,026	11806814		2	
	11,842,996	36,145	11842959		3	
	11,845,063	2,067	11845026		4	
	11,874,070	29,007	11874033		5	
	11,881,066	6,996	11881029		6	
	11,902,875	21,809	11902838		7	
	11,916,943	14,068	11935227		8	
	11,935,264	18,321	11935227		9	
	12,021,458	86,194	12021421		10	
	12,077,904	56,446	12077867		11	
	12,088,869	10,965	12088832		12	
	12,115,501	26,632	12115464		13	
	12,122,082	6,581	12122045		14	
	12,142,227	20,145	12142190		15	
	12,154,501	12,274	12154464		16	
	12,177,228	22,727	12177191		17	
	12,177,228	0	12177191		18	
	12,206,389	29,161	12206352		19	
	12,211,272	4,883	12211235		20	
	12,230,361	19,089	12230324		21	
	12,242,882	12,521	12242845		22	
	12,248,713	5,831	12248676		23	
	12,274,747	26,034	12274710		24	
	12,349,520	74,773	12349483		25	
	12,421,993	72,473	12421956		26	
	12,422,115	122	12422078		27	
	12,451,837	29,722	12451800		28	
	12,451,837	0	12451800		29	
	12,479,293	27,456	12479256		30	
	12,483,263		12483226		31	
	784,253	784,253	784,253			

PFOHL BROTHERS LANDFILL SITE CHEEKTOWAGA, NEW YORK

Auto Dialer System Log

PATE	PUMP Inhibit -08 (Off)	TIME Enable -07 (On)	COMMENTS
5/1/09	//30 pm	8:34ar	Rain
	6		
5/27/09 5/28/09	10:30 рм	8:53am	RAIN
4		7	

THE TOWN OF **CHEEKTOWAGA**



Main Pump Station 171 Central Boulevard Cheektowaga, NY 14225

Phone: 716-896-1777 Fax: 716-896-6437

July 10, 2009

Mr. William R. Pugh, P.E. Town Engineer Town of Cheektowaga

Re: Pfohl Bros. Flow Data

Dear Mr. Pugh,

Enclosed for your review, please find a copy of the **June 2009** Direct Discharge Flow Data Report, prepared by Jon W. Nichy.

A monthly log sheet indicating inhibiting and enabling of pumping operation at the site is included with this package.

Should you have any other questions or comments regarding this submittal, please contact this office @ 896-1777.

Yours truly,

Town of Cheektowaga

Jon W. Nichy/ Superintendent

Main Pump Station

RECEIVED

JUL 13 2009

ENGINEERING DEPT

15 16 17 Days Pfohl Bros. June 2009 12 13 14 ω Daily Total Discharge (Gallons)

Direct Discharge Flow Data

,	,		J		
5/31//09		12483226	3,970	12,483,263	
June-09	Time; 11:58pm unless otherwise stated	Totalizer Reading (Gallons)	Daily Total Discharge (Gallons)		Notes
1		12509360	26,134	12,509,397	
2		12512150	2,790	12,512,187	
3		12530662	18,512	12,530,699	
4		12535134	4,472	12,535,171	
5		12559764	24,630	12,559,801	
6		12559764	0	12,559,801	
7		12591586	31,822	12,591,623	
8		12653055	61,469	12,653,092	
9		12701608	48,553	12,701,645	
10		12736214	34,606	12,736,251	
11		12736214	0	12,736,251	
12		12757593	21,379	12,757,630	
13		12800465	42,872	12,800,502	
14		12800465	0	12,800,502	
15		12814769	14,304	12,814,806	
16		12830654	15,885	12,830,691	
17		12862486	31,832	12,862,523	
18		12862486	0	12,862,523	
19		12898213	35,727	12,898,250	
20		12922351	24,138	12,922,388	
21		12922351	0	12,922,388	
22		12938883	16,532	12,938,920	
23		13017267	78,384	13,017,304	
24		13033358	16,091	13,033,395	
25		13035929	2,571	13,035,966	
26		13081164	45,235	13,081,201	
27		1312166	40,501	13,121,702	
28		1313157	9,909	13,131,611	
29		1313157	4 0	13,131,611	
30		1316191	9 30,345	13,161,956	
31					
		678,69	3 678,693	678,693	J

PFOHL BROTHERS LANDFILL SITE CHEEKTOWAGA, NEW YORK

Auto Dialer System Log

DATE	PUMP Inhibit -08 (Off)	TIME Enable -07 (On)	COMMENTS
6/18/09			No Flow Heavy Rennis
6/20/09	1126	0938	
6/25/09	1458	0637	
6/28/09 6/30/09	2240	10.33	
	-		

APPENDIX C HYDRAULIC MONITORING TABLES

Location ID / Type	Northing	Easting	Ground Elevation (ft)	Casing Elevation (ft)	Meas.point (Riser)Elev.(ft)	Geol. Zone	Specific Gravity	Date / Time	Depth to Water (ft)	Water Elev. (ft)	Product Thick. (ft)	Corrected Water Elev. (ft)	Remark
GW-03S	1073812.622	1114605.762	692.61	NM	693.80	S	1						
MNW								3/19/2009 0000	2.43	691.37	0.00	691.37	
MNW								5/4/2009 0000	2.5	691.30	0.00	691.30	
MNW								6/22/2009 0000	4.92	688.88	0.00	688.88	
GW-04S	1072284.456	1114685.127	690.76	NM	692.72	S	1						
MNW	,							3/19/2009 0000	4.05	688.67	0.00	688.67	
MNW								5/4/2009 0000	4.3	688.42	0.00	688.42	
MNW								6/22/2009 0000	5.47	687.25	0.00	687.25	
GW-07S	1071238.157	1117666.265	697.47	NM	699.51	S	1						
MNW								3/19/2009 0000	4.28	695.23	0.00	695.23	
MNW								5/4/2009 0000	5.02	694.49	0.00	694.49	
MNW								6/22/2009 0000	5.98	693.53	0.00	693.53	
GW-08SR	1073714.172	1116786.343	695.08	NM	697.50	S	1						
MNW	,							3/19/2009 0000	5.38	692.12	0.00	692.12	
MNW								5/4/2009 0000	5.37	692.13	0.00	692.13	
MNW								6/22/2009 0000	5.42	692.08	0.00	692.08	
GW-28S	1073129.479	1117648.927	698.60	NM	700.95	S	1						
MNW								3/19/2009 0000	8.97	691.98	0.00	691.98	
MNW								5/4/2009 0000	9.58	691.37	0.00	691.37	
MNW								6/22/2009 0000	10.74	690.21	0.00	690.21	
GW-29S	1072552.638	1117761.993	697.50	NM	699.63	S	1						
MNW								3/19/2009 0000	8.12	691.51	0.00	691.51	
MNW								5/4/2009 0000	9.07	690.56	0.00	690.56	
MNW								6/22/2009 0000	10.21	689.42	0.00	689.42	

NM - No Measurement

The value noted in the column labeled Specific Gravity is an assumed value for free product, if found.

Type:

MH Manhole Monitoring Point MNW Monitoring Well

Location ID / Type	Northing	Easting	Ground Elevation (ft)	Casing Elevation (ft)	Meas.point (Riser)Elev.(ft)	Geol. Zone	Specific Gravity	Date / Time	Depth to Water (ft)	Water Elev. (ft)	Product Thick. (ft)	Corrected Water Elev. (ft)	Remark
GW-30S	1072096.109	1117743.563	693.67	NM	696.58	S	1						
MNW								3/19/2009 0000	8.36	688.22	0.00	688.22	
MNW								5/4/2009 0000	8.34	688.24	0.00	688.24	
MNW								6/22/2009 0000	8.47	688.11	0.00	688.11	
GW-31S	1071786.280	1117191.441	695.84	NM	698.62	S	1						
MNW								3/19/2009 0000	2.60	696.02	0.00	696.02	
MNW								5/4/2009 0000	3.33	695.29	0.00	695.29	
MNW								6/22/2009 0000	5.76	692.86	0.00	692.86	
GW-32S	1071613.793	1116364.200	696.19	NM	698.37	S	1						
MNW								3/19/2009 0000	2.80	695.57	0.00	695.57	
MNW								5/4/2009 0000	3.57	694.80	0.00	694.80	
MNW								6/22/2009 0000	5.13	693.24	0.00	693.24	
GW-33S	1072165.625	1115561.866	695.94	NM	698.24	S	1						
MNW								3/19/2009 0000	4.21	694.03	0.00	694.03	
MNW								5/4/2009 0000	4.88	693.36	0.00	693.36	
MNW								6/22/2009 0000	6.55	691.69	0.00	691.69	
GW-34S	1072979.205	1114730.200	692.51	NM	694.77	S	1						
MNW								3/19/2009 0000	2.74	692.03	0.00	692.03	
MNW								5/4/2009 0000	2.92	691.85	0.00	691.85	
MNW								6/22/2009 0000	3.62	691.15	0.00	691.15	
GW-35S	1071701.925	1115985.585	696.19	NM	697.39	S	1						
MNW								3/19/2009 0000	2.96	694.43	0.00	694.43	
MNW								5/4/2009 0000	3.67	693.72	0.00	693.72	
MNW								6/22/2009 0000	5.36	692.03	0.00	692.03	

NM - No Measurement

The value noted in the column labeled Specific Gravity is an assumed value for free product, if found.

Type:

MH Manhole Monitoring Point MNW Monitoring Well

Location I Type	ID /	Northing	Easting	Ground Elevation (ft)	Casing Elevation (ft)	Meas.point (Riser)Elev.(ft)	Geol. Zone	Specific Gravity	Date / Time	Depth to Water (ft)	Water Elev. (ft)	Product Thick. (ft)	Corrected Water Elev. (ft)	Remark
MH-01		1073806.665	1114810.501	698.62	NM	698.62	NA	1						
	МН								3/19/2009 0000	9.72	688.90	0.00	688.90	
	МН								5/4/2009 0000	10.31	688.31	0.00	688.31	
	МН								6/22/2009 0000	9.82	688.80	0.00	688.80	
MH-03		1073736.789	1115259.334	699.40	NM	699.40	NA	1						
	МН								3/19/2009 0000	10.60	688.80	0.00	688.80	
	МН								5/4/2009 0000	11.18	688.22	0.00	688.22	
	МН								6/22/2009 0000	10.70	688.70	0.00	688.70	
MH-07		1073838.229	1116243.757	696.82	NM	696.82	NA	1						
	МН								3/19/2009 0000	8.79	688.03	0.00	688.03	
	МН								5/4/2009 0000	9.39	687.43	0.00	687.43	
	МН								6/22/2009 0000	8.9	687.92	0.00	687.92	
MH-10		1073540.729	1117381.524	703.01	NM	703.01	NA	1						
	МН								3/19/2009 0000	14.48	688.53	0.00	688.53	
	МН								5/4/2009 0000	14.46	688.55	0.00	688.55	
	МН								6/22/2009 0000	14.43	688.58	0.00	688.58	
MH-15		1072531.567	1117761.125	699.02	NM	699.02	NA	1						
	МН								3/19/2009 0000	14.53	684.49	0.00	684.49	
	МН								5/4/2009 0000	14.67	684.35	0.00	684.35	
	МН								6/22/2009 0000	14.68	684.34	0.00	684.34	
MH-16		1072133.714	1117748.238	698.57	NM	698.57	NA	1						
	МН								3/19/2009 0000	14.21	684.36	0.00	684.36	
	МН								5/4/2009 0000	14.46	684.11	0.00	684.11	
	МН								6/22/2009 0000	14.41	684.16	0.00	684.16	

NM - No Measurement

The value noted in the column labeled Specific Gravity is an assumed value for free product, if found.

Type:

MH Manhole Monitoring Point MNW Monitoring Well

Location ID / Type	Northing	Easting	Ground Elevation (ft)	Casing Elevation (ft)	Meas.point (Riser)Elev.(ft)	Geol. Zone	Specific Gravity	Date / Time	Depth to Water (ft)	Water Elev. (ft)	Product Thick. (ft)	Corrected Water Elev. (ft)	Remark
MH-17	1071813.137	1117180.019	702.16	NM	702.16	NA	1						
MI	4							3/19/2009 0000	17.83	684.33	0.00	684.33	
MI	1							5/4/2009 0000	18.12	684.04	0.00	684.04	
MI	-							6/22/2009 0000	18.05	684.11	0.00	684.11	
MH-20	1071756.395	1115997.024	706.20	NM	706.20	NA	1						
MI	4							3/19/2009 0000	19.72	686.48	0.00	686.48	
MI	1							5/4/2009 0000	19.72	686.48	0.00	686.48	
MI	1							6/22/2009 0000	19.72	686.48	0.00	686.48	
MH-22	1072158.023	1115589.309	698.05	NM	698.05	NA	1						
MI	4							3/19/2009 0000	9.00	689.05	0.00	689.05	
MI	1							5/4/2009 0000	8.97	689.08	0.00	689.08	
MI	1							6/22/2009 0000	8.98	689.07	0.00	689.07	
MH-25	1072483.928	1114820.313	698.17	NM	698.17	NA	1						
MI	+							3/19/2009 0000	9.35	688.82	0.00	688.82	
MI	1							5/4/2009 0000	9.90	688.27	0.00	688.27	
MI	1							6/22/2009 0000	9.40	688.77	0.00	688.77	
SG-01	1073882.887	1114813.101	NM	NM	690.00	NA	1						
SC	à							3/19/2009 0000	-1.20	691.20	0.00	691.20	
SC	3							5/4/2009 0000	-1.0	691.00	0.00	691.00	
SC	à							6/22/2009 0000	NM	-	NM	-	DRY
SG-02	1073738.27	1116805.85	NM	NM	690.00	NA	1						
SC	à							3/19/2009 0000	-2.18	692.18	0.00	692.18	
SC	3							5/4/2009 0000	-3.2	693.20	0.00	693.20	
SC	à							6/22/2009 0000	-3.1	693.10	0.00	693.10	

NM - No Measurement

The value noted in the column labeled Specific Gravity is an assumed value for free product, if found.

Type:

MH Manhole Monitoring Point

MNW Monitoring Well SG Staff Gauge

Location ID Type	/ Northing	Easting	Ground Elevation (ft)	Casing Elevation (ft)	Meas.point (Riser)Elev.(ft)	Geol. Zone	Specific Gravity	Date / Time	Depth to Water (ft)	Water Elev. (ft)	Product Thick. (ft)	Corrected Water Elev. (ft)	Remark
WW-01	1073676.903	1115710.476	NM	NM	684.02	NA	1						
N	Н							3/19/2009 0000	-4.7	688.72	0.00	688.72	
N	Н							5/4/2009 0000	-4.0	688.02	0.00	688.02	
N	Н							6/22/2009 0000	-4.5	688.52	0.00	688.52	
WW-02	1073684.724	1116792.311	NM	NM	684.18	NA	1						
N	Н							3/19/2009 0000	-4.7	688.88	0.00	688.88	
N	Н							5/4/2009 0000	-4.6	688.78	0.00	688.78	
N	Н							6/22/2009 0000	-4.7	688.88	0.00	688.88	
WW-03	1073140.339	1117618.499	NM	NM	683.80	NA	1						
N	Н							3/19/2009 0000	-5.5	689.30	0.00	689.30	
N	Н							5/4/2009 0000	-5.6	689.40	0.00	689.40	
N	Н							6/22/2009 0000	-5.6	689.40	0.00	689.40	
WW-04	1072057.563	1117610.508	NM	NM	676.62	NA	1						
l N	Н							3/19/2009 0000	-7.3	683.92	0.00	683.92	
N	Н							5/4/2009 0000	-7.0	683.62	0.00	683.62	
N	Н							6/22/2009 0000	-7.1	683.72	0.00	683.72	
WW-05	1071661.368	1116370.876	NM	NM	676.14	NA	1						
N	н							3/19/2009 0000	-8.0	684.14	0.00	684.14	
N	Н							5/4/2009 0000	-7.5	683.64	0.00	683.64	
N	Н							6/22/2009 0000	-7.8	683.94	0.00	683.94	
WW-06	1072988.420	1114811.518	NM	NM	681.89	NA	1						
N	Н							3/19/2009 0000	NM	-	0.00	-	PLC Error
N	Н							5/4/2009 0000	-6.8	688.69	0.00	688.69	
N	Н							6/22/2009 0000	-7.2	689.09	0.00	689.09	

NM - No Measurement

The value noted in the column labeled Specific Gravity is an assumed value for free product, if found.

Type:

MH Manhole Monitoring Point MNW Monitoring Well

TABLE 2 PFOHL BROTHERS LANDFILL SITE **OVERBURDEN HYDRAULIC GRADIENT**

WELL PAIR:	WW-1	*	Level	WW-2	GW-8SR	Level	SG-02	Level
	Water Level	Water Level	Difference	Water Level	Water Level	Difference	Water Level	Difference
DATE	(ft amsl)	(ft amsl)	(ft)	(ft amsl)	(ft amsl)	(ft)	(ft amsl)	(ft)
3/19/2009	688.72			688.88	692.12	3.24	692.18	3.30
5/4/2009	688.02			688.78	692.13	3.35	693.20	4.42
6/22/2009	688.52			688.88	692.08	3.20	693.10	4.22

WELL PAIR:	WW-3	GW-28S	Level	WW-4	*	Level
	Water Level	Water Level	Difference	Water Level	Water Level	Difference
DATE	(ft amsl)	(ft amsl)	(ft)	(ft amsl)	(ft amsl)	(ft)
3/19/2009	689.30	691.98	2.68	683.92		
5/4/2009	689.40	691.37	1.97	683.62		
6/22/2009	689.40	690.21	0.81	683.72		

WELL PAIR:	WW-5	GW-32S	Level	WW-6	GW-34S	Level
	Water Level	Water Level	Difference	Water Level	Water Level	Difference
DATE	(ft amsl)	(ft amsl)	(ft)	(ft amsl)	(ft amsl)	(ft)
3/19/2009	684.14	695.57	11.43	**	692.03	NA
5/4/2009	683.64	694.80	11.16	688.69	691.85	3.16
6/22/2009	683.94	693.24	9.30	689.09	691.15	2.06

WELL PAIR:	MH-1	SG-1	Level	MH-15	GW-29S	Level
	Water Level	Water Level	Difference	Water Level	Water Level	Difference
DATE	(ft amsl)	(ft amsl)	(ft)	(ft amsl)	(ft amsl)	(ft)
3/19/2009	688.90	691.20	2.30	684.49	691.51	7.02
5/4/2009	688.31	691.00	2.69	684.35	690.56	6.21
6/22/2009	688.80	DRY		684.34	689.42	5.08

WELL PAIR:	MH-16	GW-30S	Level	MH-17	GW-31S	Level
	Water Level	Water Level	Difference	Water Level	Water Level	Difference
DATE	(ft amsl)	(ft amsl)	(ft)	(ft amsl)	(ft amsl)	(ft)
3/19/2009	684.36	688.22	3.86	684.33	696.02	11.69
5/4/2009	684.11	688.24	4.13	684.04	695.29	11.25
6/22/2009	684.16	688.11	3.95	684.11	692.86	8.75

WELL PAIR:	MH-20	GW-35S	Level	MH-22	GW-33S	Level
	Water Level	Water Level	Difference	Water Level	Water Level	Difference
DATE	(ft amsl)	(ft amsl)	(ft)	(ft amsl)	(ft amsl)	(ft)
3/19/2009	686.48	694.43	7.95	686.48	694.03	7.55
5/4/2009	686.48	693.72	7.24	689.08	693.36	4.28
6/22/2009	686.48	692.03	5.55	689.07	691.69	2.62

Notes:

^{* =} No corresponding monitoring well. ** = PLC Level gauge malfunctioning

APPENDIX D

GROUNDWATER PURGE AND SAMPLE COLLECTION LOGS

Project:		11175616.00000)	Site:	Pfohl	Brothers	_ Well I.D.: _	GW-1S
Date:	5/7/2009	Sampling	Personnel:	Rob Mu	ırphy, Tim II	fkovich	_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		_Tubing Type:	LDPE/	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	3.80'	Depth to Well Bottom:	14.94'	Well Diameter:	2"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	6.9	_	Estimated Purge Volume (liters):	6.9
Sample ID:		GW-1S		Sample Time:	9	:48	QA/QC:	None
	er Information:		lged inwards,			steel bailer fro	m within well, sar	mpled around it.

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
9:03			w through cell d		, ,	. ,	250	3.80
9:12	6.79	9.38	1.136	4.31	442	-81.0	130	4.41
9:17	6.78	9.19	1.131	1.36	335	-75.5	130	4.45
9:22	6.78	9.17	1.116	1.32	226	-71.5	130	4.46
9:27	6.80	9.04	1.091	1.00	142	-63.0	130	4.47
9:32	6.79	8.98	1.086	0.92	113	-65.3	130	4.48
9:37	6.78	9.02	1.086	0.84	95	-68.6	130	4.43
9:42	6.77	9.06	1.089	0.82	84	-68.9	130	4.41
9:45	6.76	9.06	1.095	0.78	77	-71.6	130	4.40
9:48	6.75	9.10	1.100	0.75	72	-73.1	130	4.39
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Project:		11175616.00000)	Site:	Pfohl	Brothers	_ Well I.D.: _	GW-1D
Date:	5/7/2009	Sampling	Personnel:	Rob Mu	urphy, Tim It	fkovich	_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		_Tubing Type:_	LDPE/	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	2.93'	Depth to Well Bottom:	39.63'	Well Diameter:	4"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	90.6	_	Estimated Purge Volume (liters):	66.2
Sample ID:		GW-1D		Sample Time:	11	1:25	QA/QC:	None
	e Parameters: er Information:	VOCs, SVOCs, Sulfur odor	and TAL Meta	als				

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
10:15	7.13	9.78	0.997	2.52	44	-165.7	945	2.93
10:25	7.15	9.60	1.002	0.30	16	-185.0	945	2.98
10:30	7.14	9.53	1.003	0.17	17	-189.1	945	2.98
10:35	7.14	9.41	1.002	0.15	6	-192.8	945	2.98
10:45	7.13	9.31	1.000	0.10	5	-207.7	945	2.98
10:55	7.13	9.34	0.998	0.06	6	-220.7	945	2.98
11:05	7.12	9.32	0.998	0.04	5	-234.5	945	2.98
11:15	7.12	9.37	0.994	0.03	6	-242.6	945	2.98
11:20	7.11	9.33	0.994	0.03	5	-245.7	945	2.98
11:25	7.11	9.40	0.993	0.03	6	-246.4	945	2.98
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Information: WATER VOLUMES--0.75 inch diameter well = 87 ml/ft; 1 inch diameter well = 154 ml/ft; 2 inch diameter well = 617 ml/ft; 4 inch diameter well = 2470 ml/ft ($vq_{N}^{1} = \pi r^{2}h$)

Project:		11175616.00000		Site:	Pfohl	Brothers	_ Well I.D.: _	GW-3S
Date:	5/5/2009	Sampling	Personnel:	Rob Mu	urphy, Tim If	kovich	_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		_Tubing Type:	LDPE/	'Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	2.56'	Depth to Well Bottom:	13.24'	Well Diameter:	2"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	6.6	-	Estimated Purge Volume (liters):	7.4
Sample ID:		GW-3S		Sample Time:	9	:47	QA/QC:	None
	e Parameters: er Information:	VOCs, SVOCs, a	and TAL Meta	als				

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
9:02	7.02	9.57	1.155	4.36	162	-65.8	240	4.07
9:07	6.78	8.81	1.137	1.54	120	-55.2	185	4.64
9:12	6.76	8.79	1.133	1.22	73	-50.3	150	4.97
9:17	6.77	8.77	1.128	0.96	50	-38.4	150	5.37
9:22	6.79	8.78	1.127	1.09	29	-30.8	150	5.59
9:27	6.77	8.88	1.124	0.84	13	-21.8	150	5.91
9:32	6.76	9.23	1.117	0.62	12	-13.2	150	6.18
9:37	6.76	9.06	1.118	0.62	10	-12.1	150	6.31
9:42	6.75	8.90	1.116	0.59	8	-10.5	150	6.52
9:47	6.78	8.87	1.115	0.67	9	-6.2	150	6.65
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Information: WATER VOLUMES--0.75 inch diameter well = 87 ml/ft; 1 inch diameter well = 154 ml/ft; 2 inch diameter well = 617 ml/ft; 4 inch diameter well = 2470 ml/ft ($vq_{N}^{1} = \pi r^{2}h$)

Project:		11175616.00000		Site: _	Pfohl	Brothers	_ Well I.D.: _	GW-3D
Date:	5/5/2009	Sampling	Personnel:	Rob Mu	urphy, Tim I	fkovich	_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		Tubing Type:_	LDPE,	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	1.91'	Depth to Well Bottom:	35.69'	Well Diameter:	4"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	83.4	_	Estimated Purge Volume (liters):	85.0
Sample ID:		GW-3D		Sample Time:	1	1:58	QA/QC:	MS/MSD
•	e Parameters: er Information:	VOCs, SVOCs,	and TAL Meta	als				

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
10:18	6.94	10.26	1.390	4.65	9	-23.7	850	1.91
10:23	6.61	9.24	1.410	0.65	100	-47.3	850	1.91
10:33	6.54	9.21	1.432	0.24	20	-63.8	850	1.91
10:43	6.49	9.20	1.428	0.14	6	-68.8	850	1.91
10:53	6.47	9.26	1.422	0.12	4	-80.3	850	1.91
11:03	6.47	9.34	1.421	0.11	5	-77.3	850	1.91
11:13	6.43	9.42	1.424	0.11	6	-76.5	850	1.91
11:18	6.25	9.55	1.420	0.12	3	-60.2	850	1.91
11:28	6.17	9.66	1.426	0.11	3	-74.5	850	1.91
11:38	6.15	9.70	1.422	0.10	2	-73.6	850	1.91
11:48	6.19	9.74	1.424	0.10	2	-77.3	850	1.91
11:53	6.18	9.74	1.422	0.11	2	-76.4	850	1.91
11:58	6.18	9.77	1.420	0.10	2	-76.6	850	1.91
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Information: WATER VOLUMES--0.75 inch diameter well = 87 ml/ft; 1 inch diameter well = 154 ml/ft; 2 inch diameter well = 617 ml/ft; 4 inch diameter well = 2470 ml/ft ($vq_{M}^{1} = \pi r^{2}h$)

Project:		11175616.00000)	Site:	Pfohl Brothers		_ Well I.D.: _	GW-4S
Date:		Sampling	Personnel:	connel: Rob Murphy, Tim Ifkovich		fkovich	_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		_Tubing Type:_	LDPE/	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	4.41'	Depth to Well Bottom:	16.25'	Well Diameter:	2"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	7.3	_	Estimated Purge Volume (liters):	28.7
Sample ID:		GW-4S		Sample Time:	14	4:25	QA/QC:	None
	e Parameters: er Information:	VOCs, SVOCs,			es (<75ml/r	min). Pumped	dry and sampled	d after recovery.

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
12:05	7.68	8.44	0.466	2.56	57	-161.1	820	4.41
12:10	7.66	7.93	0.459	0.62	31	-180.4	820	10.80
12:15	7.71	8.33	0.457	0.72	73	-167.8	820	13.14
12:20	7.72	8.32	0.462	1.14	44	-154.3	820	14.48
12:25	7.62	8.10	0.457	0.53	5	-145.2	820	14.93
12:30	7.60	8.14	0.451	0.36	4	-143.2	820	15.52
12:35	7.66	8.27	0.449	0.31	4	-148.6	820	16.05
12:40	7.70	8.38	0.446	0.30	4	-154.9	820	16.20
								DRY
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Information: WATER VOLUMES--0.75 inch diameter well = 87 ml/ft; 1 inch diameter well = 154 ml/ft; 2 inch diameter well = 617 ml/ft; 4 inch diameter well = 2470 ml/ft ($vq_{ij} = \pi r^2 h$)

Project:		11175616.0000)	Site:	Pfohl	Brothers	_ Well I.D.: _	GW-4D	
Date:	5/7/2009	Sampling	Personnel:	Rob Mu	urphy, Tim I	fkovich	_ Company:_	URS Corporation	
Purging/ Sampling Device:		Geopump 2		Tubing Type:	LDPE	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint	
Measuring Point:	Below Top of Riser	Initial Depth to Water:	12.46'	Depth to Well Bottom:	45.57'	Well Diameter:	4"	Screen Length:	
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	81.8	-	Estimated Purge Volume (liters):	8.4	
Sample ID:		GW-4D		Sample Time:	1;	3:59	QA/QC:	None	
	e Parameters: er Information:	VOCs, SVOCs,	and TAL Meta	als					
									_

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
12:59	7.36	10.70	1.179	4.04	3	-167.4	150	12.74
13:04	7.29	10.75	1.182	2.00	3	-173.3	200	12.97
13:09	7.27	10.68	1.184	1.43	2	-169.7	200	13.12
13:14	7.26	10.66	1.184	0.96	2	-176.6	200	12.32
13:19	7.24	11.02	1.184	0.71	2	-182.5	115	13.37
13:29	7.22	11.20	1.190	0.50	2	-169.5	115	13.43
13:39	7.20	11.05	1.191	0.32	1	-177.9	115	13.50
13:49	7.19	11.70	1.196	0.22	1	-184.5	115	13.50
13:54	7.18	11.39	1.190	0.20	1	-192.0	115	13.50
13:59	7.19	11.65	1.191	0.20	1	-187.7	115	13.50
Tolerance:	0.1		3%	10%	10%	+ or - 10		

WELL PURGING LOG

URS Corporation

SITE NAME:	Pfohl Brothers Landfill		WELL NO.:	G	W-7S
PROJECT NO.:	11175616.00000				
STAFF:	Rob Murphy, Tim Ifkovich				
DATE(S):	5/4/09, 5/5/09				
				WELL ID.	VOL. (GAL/FT)
1. TOTAL CASING	G AND SCREEN LENGTH (FT.)	=	35.04	1"	0.040
2. WATER LEVEL	BELOW TOP OF CASING (FT.)	=	5.02	2"	0.17
3. NUMBER OF F	EET STANDING WATER (#1 - #2)	=	30.02	3"	0.38
4. VOLUME OF W	VATER/FOOT OF CASING (GAL.)	=	0.17	4"	0.66
5. VOLUME OF W	VATER IN CASING (GAL.)(#3 x #4)	=	5.1	5"	1.04
6. VOLUME OF W	VATER TO REMOVE (GAL.)(#5 x 3)	=		6"	1.50
7. VOLUME OF W	WATER ACTUALLY REMOVED (GAL.)	=	7.5	8"	2.60
			V=0	.0408 x (CASING	DIAMETER [INCHES]) ²

				ACCUM	MULATED '	VOLUME F	PURGED (GALLONS)		
PARAMETERS	Initial	2	4	6	7					
рН	8.00	7.96	7.96	7.95	7.91					
SPEC. COND. (mS/cm)	0.397	0.378	0.384	0.388	0.391					
DO (mg/l)	8.81	11.02	8.72	9.95	7.14					
TEMPERATURE (°C)	11.21	9.35	10.19	10.81	11.61					
TURBIDITY (NTU)	139	39	27	135	116					
ORP (millivolts)	-3.1	4.6	15.5	7.3	1.9					
TIME	14:05	14:12	14:20	14:27	14:35					

COMMENTS: 14:05 - Begin handbailing well.

14:40 - Well dry after removing 7.5 gallons

5/5/2009 16:05 - return to well, depth to water = 5.26 feet.

16:40 - Collect sample.

WELL PURGING LOG

URS Corporation

SITE NAME:	Pfohl Brothers Landfill		WELL NO.:	G	W-7D
PROJECT NO.:	11175616.00000				
STAFF:	Rob Murphy, Tim Ifkovich				
DATE(S):	5/4/09, 5/5/09				
1 TOTAL CASING	G AND SCREEN LENGTH (FT.)	=	60.30	WELL ID. 1"	VOL. (GAL/FT) 0.040
	` '			•	
2. WATER LEVEL	BELOW TOP OF CASING (FT.)	=	41.95	2"	0.17
3. NUMBER OF F	EET STANDING WATER (#1 - #2)	=	18.35	3"	0.38
4. VOLUME OF W	ATER/FOOT OF CASING (GAL.)	=	0.66	4"	0.66
5. VOLUME OF W	ATER IN CASING (GAL.)(#3 x #4)	=	12.1	5"	1.04
6. VOLUME OF W	ATER TO REMOVE (GAL.)(#5 x 3)	=		6"	1.50
7. VOLUME OF W	ATER ACTUALLY REMOVED (GAL.)	=	12.0	8"	2.60
			V=	0.0408 x (CASING	DIAMETER [INCHES]) ²

				ACCUM	MULATED '	VOLUME F	PURGED (GALLONS)		
PARAMETERS	Initial	3	6	9	12					
рН	8.48	8.23	7.81	7.82	7.90					
SPEC. COND. (mS/cm)	0.644	0.727	0.483	0.474	0.480					
DO (mg/)	3.19	7.17	7.45	7.54	9.41					
TEMPERATURE (°C)	13.83	12.67	12.66	11.98	11.98					
TURBIDITY (NTU)	4	3	15	39	45					
ORP (millivolts)	-195.4	-194.8	-63.2	-53.8	-48.1					
TIME	12:45	12:51	13:40	13:49	13:56					

COMMENTS: 13:00 - Difficulty with whale pump, try another vehicle/battery and had same result of low flow.

13:30 - Begin handbailing the well to dryness.

5/5/2009 16:05 - return to well, depth to water = 59.19 feet.

16:10 - Collect sample, only enough volume to fill 3 voa vials, 1 metals container and 1-1 liter Amber container.

	11175616.00000		Site:	Pfohl E	Brothers	_ Well I.D.: _	GW-8SR
5/5/2009	Sampling Pe	rsonnel:	Rob Mu	ırphy, Tim If	kovich	_ Company:_	URS Corporation
	Geopump 2		Tubing Type:	LDPE/	Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Below Top of Riser		5.38'	Depth to Well Bottom:	13.03'	Well Diameter:	2"	Screen Length:
Stainles	ss Steel		Volume in 1 Well Casing (liters):	4.7	-	Estimated Purge Volume (liters):	7.8
	GW-8SR		Sample Time:	13	:50	QA/QC:	None
e Parameters: er Information:	VOCs, SVOCs, and	TAL Meta	ls				
	5/5/2009 Below Top of Riser Stainles	Geopump 2 Below Top of Initial Depth Riser to Water: Stainless Steel GW-8SR e Parameters: VOCs, SVOCs, and	Geopump 2 Below Top of Initial Depth Riser to Water: 5.38' Stainless Steel GW-8SR e Parameters: VOCs, SVOCs, and TAL Meta	Geopump 2 Below Top of Initial Depth Riser to Water: 5.38' Stainless Steel GW-8SR Tubing Type: Depth to Well Bottom: Volume in 1 Well Casing (liters): Sample Time:	Geopump 2 Tubing Type: LDPE/ Below Top of Initial Depth Depth to Well Bottom: 13.03' Volume in 1 Well Casing (liters): 4.7 GW-8SR Sample Time: 13 e Parameters: VOCs, SVOCs, and TAL Metals	Sampling Personnel: Rob Murphy, Tim Ifkovich Geopump 2 Tubing Type: LDPE/Silicone Below Top of Initial Depth Depth to Well Bottom: 13.03' Diameter: Volume in 1 Well Casing (liters): 4.7 GW-8SR Sample Time: 13:50 Parameters: VOCs, SVOCs, and TAL Metals	Sampling Personnel: Rob Murphy, Tim Ifkovich Company: Sampling Personnel: Rob Murphy, Tim Ifkovich Company:

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
13:00	6.32	11.66	2.114	1.57	644	-65.2	200	5.38
13:05	6.18	11.94	2.092	0.34	510	-56.6	150	6.91
13:15	6.14	12.15	2.089	0.20	316	-50.5	150	7.03
13:25	6.09	11.65	2.100	0.16	145	-42.2	150	7.09
13:30	6.08	11.48	2.099	0.14	94	-40.7	150	7.09
13:35	6.08	11.39	2.096	0.14	63	-41.0	150	7.09
13:40	6.08	11.72	2.081	0.13	47	-38.6	150	7.09
13:45	6.08	11.91	2.090	0.14	33	-29.8	150	7.09
13:50	6.08	12.03	2.079	0.13	21	-36.5	150	7.09
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Project:		11175616.00000)	Site:	Pfohl	Brothers	_ Well I.D.:	GW-8D
Date:	5/5/2009	Sampling	Personnel:	Rob M	urphy, Tim If	kovich	_ Company:	URS Corporation
Purging/ Sampling Device:	_	Geopump 2		Tubing Type:	LDPE/	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	5.88'	Depth to Well Bottom:	36.60'	Well Diameter:	4"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	75.9	-	Estimated Purge Volume (liters):	65.0
Sample ID:		GW-8D		Sample Time:	15	5:35	_ QA/QC:	Duplicate (FD-050509)
	e Parameters: er Information:	VOCs, SVOCs,	and TAL Meta	als				

PURGE PARAMETERS

TIME	pН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
14:30	6.95	11.05	1.213	1.63	258	-86.2	1000	5.88
14:40	6.66	10.55	1.154	0.24	15	-82.2	1000	5.87
14:50	6.60	10.37	1.148	0.17	6	-76.0	1000	5.86
15:00	6.57	10.40	1.146	0.13	6	-72.0	1000	5.86
15:05	6.57	10.33	1.147	0.12	4	-70.5	1000	5.86
15:10	6.57	10.33	1.146	0.12	4	-70.3	1000	5.86
15:15	6.58	10.22	1.146	0.11	2	-69.2	1000	5.86
15:20	6.57	10.32	1.146	0.11	3	-67.9	1000	5.86
15:25	6.54	10.37	1.145	0.10	2	-66.2	1000	5.86
15:30	6.54	10.36	1.147	0.10	3	-65.8	1000	5.86
15:35	6.54	10.36	1.145	0.10	2	-64.9	1000	5.86
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Project:		11175616.00000)	Site: _	Pfohl	Brothers	_ Well I.D.: _	GW-26D
Date:	5/7/2009	Sampling	Personnel:	Rob Mu	urphy, Tim I	fkovich	_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		Tubing Type:_	LDPE,	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	6.69'	Depth to Well Bottom:	40.71'	Well Diameter:	4"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	84.0	-	Estimated Purge Volume (liters):	42.8
Sample ID:		GW-26D		Sample Time:	15	5:50	QA/QC:	None
	e Parameters: er Information:	VOCs, SVOCs,			in purge wa	ater.		

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
15:05	6.94	11.89	1.568	4.76	452	-100.6	950	6.69
15:10	6.57	11.29	1.560	1.63	292	-126.3	950	6.70
15:15	6.54	11.28	1.560	0.49	23	-135.1	950	6.70
15:20	6.53	11.31	1.560	0.19	111	-142.0	950	6.70
15:25	6.53	11.27	1.560	0.14	146	-144.7	950	6.70
15:30	6.54	11.27	1.561	0.11	77	-146.9	950	6.70
15:35	6.53	11.55	1.560	0.10	56	-146.5	950	6.70
15:40	6.53	11.46	1.564	0.08	27	-149.8	950	6.70
15:45	6.52	11.52	1.562	0.08	25	-149.6	950	6.70
15:50	6.50	11.51	1.563	0.07	24	-148.9	950	6.70
Tolerance:	0.1		3%	10%	10%	+ or - 10		

	11175616.00000		Site:	Pfohl I	Brothers	_ Well I.D.: _	GW-28S
5/6/2009	Sampling F	Personnel:	Rob Mu	urphy, Tim If	kovich	_ Company:_	URS Corporation
	Geopump 2		Tubing Type:_	LDPE/	Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Below Top of Riser	Initial Depth to Water:	9.65'	Depth to Well Bottom:	15.55'	Well Diameter:	2"	Screen Length:
Stainles	ss Steel		Volume in 1 Well Casing (liters):	3.6	-	Estimated Purge Volume (liters):	6.3
	GW-28S		Sample Time:	9:	:30	QA/QC:	None
e Parameters: er Information:	VOCs, SVOCs, a	nd TAL Meta	als				
	5/6/2009 Below Top of Riser Stainles	Geopump 2 Below Top of Initial Depth Riser to Water: Stainless Steel GW-28S e Parameters: VOCs, SVOCs, and	Geopump 2 Below Top of Initial Depth Riser to Water: 9.65' Stainless Steel GW-28S e Parameters: VOCs, SVOCs, and TAL Meta	Geopump 2 Below Top of Initial Depth Riser to Water: 9.65' Stainless Steel GW-28S Tubing Type: Popth to Well Bottom: Volume in 1 Well Casing (liters): Sample Time:	Geopump 2 Tubing Type: LDPE/ Below Top of Initial Depth Depth to Well Bottom: 15.55' Volume in 1 Well Casing (liters): 3.6 GW-28S GW-28S GW-28S GW-28S GW-28S GROWN Murphy, Tim If Rob Murphy, Tim If Page 14 Sample Time: 9 Page Parameters: VOCs, SVOCs, and TAL Metals	Sampling Personnel: Rob Murphy, Tim Ifkovich Geopump 2 Tubing Type: LDPE/Silicone Below Top of Initial Depth Depth to Well Bottom: 15.55' Diameter: Volume in 1 Well Casing (liters): 3.6 GW-28S Sample Time: 9:30 Parameters: VOCs, SVOCs, and TAL Metals	Sampling Personnel: Rob Murphy, Tim Ifkovich Company: Sampling Personnel: Rob Murphy, Tim Ifkovich Company:

PURGE PARAMETERS

TIME	pН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
8:55	6.90	8.80	0.704	2.20	200	-33.2	240	9.65
9:00	6.85	8.94	0.704	1.01	120	-29.4	170	10.87
9:05	6.90	9.19	0.698	N/A	47	-15.9	170	10.95
9:10	6.84	9.11	0.695	1.59	29	-12.7	170	10.98
9:15	6.84	9.05	0.697	1.25	21	-9.6	170	11.03
9:20	6.84	9.07	0.700	1.07	14	-7.2	170	11.07
9:25	6.84	9.12	0.707	1.03	10	-5.1	170	11.08
9:30	6.84	9.16	0.710	0.95	8	-4.1	170	11.10
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Project:		11175616.00000)	Site:	Pfohl	Brothers	_ Well I.D.: _	GW-29S
Date:	5/6/2009	Sampling	Personnel:	Rob Mu	urphy, Tim It	fkovich	_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		Tubing Type:_	LDPE/	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	9.11'	Depth to Well Bottom:	19.98'	Well Diameter:	2"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	6.7	-	Estimated Purge Volume (liters):	7.2
Sample ID:		GW-29S		Sample Time:	1(0:47	QA/QC:	None
		VOCs, SVOCs, Water red brown						

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
10:07	6.88	10.67	1.044	5.34	950	-63.7	245	9.11
10:12	6.74	10.59	1.008	1.08	455	-59.9	170	11.36
10:17	6.70	10.66	1.019	1.28	286	-60.0	170	11.52
10:22	6.62	10.59	1.049	0.94	158	-61.5	170	11.64
10:27	6.58	10.73	1.066	0.62	95	-61.8	170	11.70
10:32	6.54	10.80	1.097	0.55	54	-63.1	170	11.76
10:37	6.53	10.92	1.112	0.51	40	-62.1	170	11.74
10:42	6.52	11.08	1.123	0.51	35	-60.6	170	11.70
10:47	6.51	11.37	1.128	0.49	30	-57.1	170	11.60
Tolerance:	0.1		3%	10%	10%	+ or - 10		

	11175616.00000		Site:	Pfohl E	Brothers	_ Well I.D.: _	GW-30S	
5/6/2009	Sampling Pers	sonnel:	Rob Mu	rphy, Tim If	kovich	_ Company:_	URS Corporation	
	Geopump 2	Tubi	ng Type:	LDPE/	Silicone	Pump/Tubing Inlet Location:	Screen midpoint	
Below Top of Riser	•		•	17.95'	Well Diameter:	2"	Screen Length:	
Stainles	ss Steel	Wel	l Casing	5.9	-	Estimated Purge Volume (liters):	10.8	
	GW-30S		•	12	::05	QA/QC:	None	
	VOCs, SVOCs, and T	AL Metals						_
	5/6/2009 Below Top of Riser Stainles	Geopump 2 Below Top of Initial Depth Riser to Water: 8.3 Stainless Steel GW-30S e Parameters: VOCs, SVOCs, and T	Geopump 2 Tubin Below Top of Initial Depth Riser to Water: 8.35' Well Stainless Steel (li GW-30S T	Geopump 2 Below Top of Initial Depth Riser to Water: Stainless Steel GW-30S Sample Tubing Type: Depth to Well Bottom: Volume in 1 Well Casing (liters): Sample Time:	Geopump 2 Tubing Type: LDPE/ Below Top of Initial Depth Depth to Well Bottom: 17.95' Volume in 1 Well Casing (liters): 5.9 GW-30S Sample Time: 12 Parameters: VOCs, SVOCs, and TAL Metals	Sampling Personnel: Rob Murphy, Tim Ifkovich Geopump 2 Tubing Type: LDPE/Silicone Below Top of Initial Depth Depth to Well Bottom: 17.95' Diameter: Volume in 1 Well Casing (liters): 5.9 Sample Time: 12:05 Parameters: VOCs, SVOCs, and TAL Metals	Sampling Personnel: Rob Murphy, Tim Ifkovich Company: Sampling Personnel: Rob Murphy, Tim Ifkovich Company:	Sampling Personnel: Rob Murphy, Tim Ifkovich Company: URS Corporation Sometimes of the company of the compan

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
11:35	6.48	11.06	4.093	1.49	162	-60.3	360	8.35
11:40	6.26	10.17	4.160	0.50	53	-56.4	360	8.40
11:45	6.21	9.68	4.180	0.32	23	-60.2	360	8.40
11:50	6.22	9.59	4.205	0.21	13	-68.5	360	8.40
11:55	6.20	9.54	4.234	0.15	12	-67.6	360	8.40
12:00	6.19	9.34	4.252	0.14	5	-72.4	360	8.40
12:05	6.17	9.42	4.259	0.13	4	-75.1	360	8.40
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Project:		11175616.00000)	Site:	Pfohl	Brothers	Well I.D.:	GW-31S
Date:	5/6/2009	Sampling	Personnel:	Rob Mu	ırphy, Tim II	fkovich	_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		_Tubing Type:	LDPE/	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	5.61'	Depth to Well Bottom:	9.57'	Well Diameter:	2"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	2.4	_	Estimated Purge Volume (liters):	9.1
Sample ID:		GW-31S		Sample Time:	13	3:36	QA/QC:	None
	e Parameters: er Information:	VOCs, SVOCs,	and TAL Meta	als				

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
12:30	7.08	12.48	0.710	3.62	652	-7.3	195	5.61
12:35	6.75	11.15	0.655	0.91	449	5.6	195	6.32
12:40	6.70	11.18	0.613	0.98	141	7.8	195	7.18
12:45	6.68	11.25	0.573	2.31	116	10.4	145	7.73
12:50	6.67	11.25	0.575	2.82	96	13.0	145	8.09
12:55	6.65	11.54	0.570	3.04	36	14.2	115	8.26
13:00	6.64	11.37	0.588	3.16	29	15.1	115	8.39
13:05	6.61	11.49	0.607	2.82	31	14.5	115	8.48
13:10	6.59	11.39	0.623	2.67	35	13.2	115	8.56
13:15	6.62	11.53	0.641	2.57	23	10.1	115	8.62
13:20	6.60	11.21	0.652	2.26	16	8.7	115	8.67
13:25	6.60	11.40	0.661	2.06	15	7.3	115	8.75
13:30	6.61	11.32	0.664	1.86	12	4.4	115	8.82
13:33	6.61	11.15	0.669	1.79	11	2.4	115	8.86
13:36	6.62	10.99	0.671	1.67	10	1.8	115	8.90
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Project:		11175616.00000)	Site:	Pfohl	Brothers	Well I.D.:	GW-32S
Date:	5/6/2009	Sampling	Personnel:	Rob Mu	ırphy, Tim II	fkovich	_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		_Tubing Type:	LDPE/	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	3.79'	Depth to Well Bottom:	9.92'	Well Diameter:	2"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	3.8	_	Estimated Purge Volume (liters):	6.0
Sample ID:		GW-32S		Sample Time:	14	4:55	QA/QC:	None
	e Parameters: er Information:	VOCs, SVOCs,	and TAL Meta	als				

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
14:20	7.06	11.58	0.670	2.26	294	-5.3	170	3.79
14:30	6.82	10.61	0.594	0.83	53	14.2	170	4.32
14:40	6.82	10.54	0.593	0.62	10	18.6	170	4.33
14:45	6.83	10.50	0.593	0.58	3	18.5	170	4.34
14:50	6.85	10.48	0.594	0.54	2	18.7	170	4.34
14:55	6.84	10.29	0.598	0.52	2	19.2	170	4.34
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Project:		11175616.00000		Site:	Pfohl	Brothers	_ Well I.D.: _	GW-33S
Date:	5/6/2009	Sampling	Personnel:	Rob Mu	rphy, Tim I	fkovich	_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		_Tubing Type:	LDPE/	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	5.22'	Depth to Well Bottom:	8.20'	Well Diameter:	2"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	1.8	-	Estimated Purge Volume (liters):	4.1
Sample ID:		GW-33S		Sample Time:	15	5:55	QA/QC:	None
	e Parameters: er Information:	VOCs, SVOCs, a	and TAL Meta	als				

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
15:25	6.67	11.91	0.920	1.64	9	18.4	190	5.22
15:30	6.57	11.79	0.800	0.98	7	24.2	145	6.30
15:35	6.60	11.97	0.731	0.95	3	23.9	120	6.41
15:40	6.61	11.60	0.720	1.22	3	23.9	120	6.51
15:45	6.58	11.40	0.717	1.27	2	25.3	120	6.59
15:50	6.57	11.79	0.721	1.22	2	25.1	120	6.62
15:55	6.65	12.45	0.701	1.20	2	26.1	120	6.64
Tolerance:	0.1		3%	10%	10%	+ or - 10		

	11175616.00000	Site:	Pfohl	Brothers	_ Well I.D.: _	GW-34S
5/4/2009	Sampling Personr	nel: Rob Mu	Rob Murphy, Tim Ifkovich		_ Company:_	URS Corporation
	Geopump 2	Tubing Type:	LDPE/	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Below Top of Riser	Initial Depth to Water: 2.92'	Depth to Well Bottom:	10.00'	Well Diameter:	2"	Screen Length:
Stainles	ss Steel	Volume in 1 Well Casing (liters):	4.4	-	Estimated Purge Volume (liters):	16.5
	GW-34S	Sample Time:	16	6:33	QA/QC:	None
Sample Parameters: VOCs, SVOCs, and TAL Met Other Information:		Metals				
	5/4/2009 Below Top of Riser Stainles	Geopump 2 Below Top of Initial Depth Riser to Water: 2.92' Stainless Steel GW-34S e Parameters: VOCs, SVOCs, and TAL N	Geopump 2 Below Top of Initial Depth Riser to Water: 2.92' Stainless Steel GW-34S Sample Tubing Type: Volume in 1 Well Casing (liters): Sample Time:	Geopump 2 Tubing Type: LDPE Below Top of Initial Depth Depth to Water: 2.92' Well Bottom: 10.00' Volume in 1 Well Casing (liters): 4.4 GW-34S Sample Time: 16 Parameters: VOCs, SVOCs, and TAL Metals	Geopump 2 Tubing Type: LDPE/Silicone Below Top of Initial Depth Depth to Well Bottom: 10.00' Diameter: Volume in 1 Well Casing (liters): 4.4 GW-34S GW-34S Sample Time: 16:33 Rob Murphy, Tim Ifkovich Riser LDPE/Silicone Well Depth to Well Casing (liters): 4.4	Sampling Personnel: Rob Murphy, Tim Ifkovich Company: Sampling Personnel: Rob Murphy, Tim Ifkovich Company:

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
15:32	6.50	7.85	1.314	9.08	26	3.3	500	4.48
15:37	6.38	8.87	1.337	6.81	21	8.7	300	4.60
15:42	6.38	8.36	1.200	5.09	5	8.0	300	4.72
15:47	6.38	8.45	1.150	4.50	1	12.7	240	4.51
15:52	6.37	8.41	1.147	4.11	1	12.9	240	4.48
15:57	6.34	8.42	1.142	3.27	1	17.5	240	4.48
16:02	6.34	8.42	1.112	2.69	1	14.4	240	4.52
16:07	6.33	8.40	1.078	2.28	1	14.5	240	4.55
16:12	6.34	8.30	1.059	2.02	1	15.2	240	4.56
16:17	6.35	8.47	1.032	1.65	1	15.6	240	4.57
16:22	6.35	8.42	1.025	1.36	1	14.6	240	4.61
16:27	6.35	8.43	1.022	1.06	1	9.6	240	4.62
16:30	6.35	8.34	1.025	0.98	1	6.1	240	4.65
16:33	6.35	8.36	1.023	0.96	1	5.4	240	4.66
Tolerance:	0.1		3%	10%	10%	+ or - 10		

	11175616.00000		Site:	Pfohl	Brothers	_ Well I.D.: _	GW-35S
5/7/2009	Sampling Pers	sonnel:	Rob Murphy, Tim Ifkovich		_ Company:_	URS Corporation	
	Geopump 2	Tu	ıbing Type:	LDPE/	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Below Top of Riser	•		•	7.45'	Well Diameter:	2"	Screen Length:
Stainles	ss Steel			2.4	-	Estimated Purge Volume (liters):	9.2
	GW-35S		Sample Time:	16	5:36	QA/QC:	None
	VOCs, SVOCs, and T	AL Metals					
	5/7/2009 Below Top of Riser Stainles	Geopump 2 Below Top of Initial Depth Riser to Water: 3.9 Stainless Steel GW-35S e Parameters: VOCs, SVOCs, and T	5/7/2009 Sampling Personnel: Geopump 2 Tu Below Top of Initial Depth Riser to Water: 3.52' Work Widtle Wid	Geopump 2 Below Top of Initial Depth Riser to Water: 3.52' Stainless Steel GW-35S Sample Tubing Type: Depth to Well Bottom: Volume in 1 Well Casing (liters): Sample Time:	Geopump 2 Tubing Type: LDPE/ Below Top of Initial Depth Depth to Water: 3.52' Well Bottom: 7.45' Volume in 1 Well Casing (liters): 2.4 GW-35S GW-35S Sample Time: 16	Geopump 2 Tubing Type: LDPE/Silicone Below Top of Initial Depth Depth Niser to Water: 3.52' Well Bottom: 7.45' Diameter: Volume in 1 Well Casing (liters): 2.4 GW-35S GW-35S Sample Time: 16:36 Parameters: VOCs, SVOCs, and TAL Metals	Sampling Personnel: Rob Murphy, Tim Ifkovich Company: Sampling Personnel: Rob Murphy, Tim Ifkovich Company:

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
16:00	7.05	12.93	0.578	2.31	6	-60.7	290	3.52
16:05	7.06	12.58	0.489	1.31	5	-50.5	250	4.41
16:10	7.02	12.80	0.466	1.35	2	-48.5	250	4.39
16:15	7.00	12.85	0.466	0.93	3	-50.8	250	4.40
16:20	7.00	12.17	0.471	0.63	1	-53.5	250	4.43
16:25	7.03	12.13	0.474	0.50	1	-60.1	250	4.43
16:30	7.04	12.21	0.475	0.44	1	-62.9	250	4.43
16:33	7.04	12.27	0.475	0.40	1	-66.7	250	4.43
16:36	7.04	12.31	0.476	0.38	1	-70.6	250	4.43
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Project Name: Pfohl Brothers Project Number: 11175616.00000

Sampling Crew Members: R. Murphy, T. Ifkovich Supervisor: J. Sundquist

Date of Sampling: May 4, 2009

Sample I.D. Number	Well Number	Well Volume (liters)	Volume Purged (liters)	Sample Time	Sample Description	Analysis Required	Chain-of- Custody Number
GW-34S	GW-34S	4.4	16.5	16:33	Groundwater	VOCs/SVOCs/ Metals	Not Applicable

Additional Comments: All wells were purged using low flow methods until parameter stabilization.

Project Name: Pfohl Brothers Project Number: 11175616.00000

Sampling Crew Members: R. Murphy, T. Ifkovich Supervisor: J. Sundquist

Date of Sampling: May 5, 2009

Sample I.D. Number	Well Number	Well Volume (liters)	Volume Purged (liters)	Sample Time	Sample Description	Analysis Required	Chain-of- Custody Number
GW-3S	GW-3S	6.6	7.4	9:47	Groundwater		Not Applicable
GW-3D	GW-3D	83.4	85	11:58	Groundwater		Not Applicable
GW-3D MS	GW-3D	83.4	85	11:58	Matrix Spike	VOCs/SVOCs/	Not Applicable
GW-3D MSD	GW-3D	83.4	85	11:58	Matrix Spike Duplicate	Metals	Not Applicable
GW-8SR	GW-8SR	4.7	7.8	13:50	Groundwater		Not Applicable
GW-8D	GW-8D	75.9	65	15:35	Groundwater		Not Applicable
FD-050509	GW-8D	75.9	65	15:35	Blind Duplicate		Not Applicable

Additional Comments: All wells were purged using low flow methods until parameter stabilization.

Project Name: Pfohl Brothers Project Number: 11175616.00000

Sampling Crew Members: R. Murphy, T. Ifkovich Supervisor: J. Sundquist

Date of Sampling: May 5, 2009 (continued)

Sample I.D Number	. Well Number	Well Volume (liters)	Volume Purged (liters)	Sample Time	Sample Description	Analysis Required	Chain-of- Custody Number
GW-7D	GW-7D	45.8	45.4	16:10	Groundwater	VOCs/SVOCs/ Metals	Not Applicable
GW-7S	GW-7S	19.3	28.4	16:40	Groundwater	Wetals	Not Applicable
TB-050509)				Trip Blank	VOCs	Not Applicable

Additional Comments: All wells were purged using low flow methods until parameter stabilization.

Project Name: Pfohl Brothers Project Number: 11175616.00000

Sampling Crew Members: R. Murphy, T. Ifkovich Supervisor: J. Sundquist

Date of Sampling: May 6, 2009

Sample I.D. Number	Well Number	Well Volume (liters)	Volume Purged (liters)	Sample Time	Sample Description	Analysis Required	Chain-of- Custody Number
GW-28S	GW-28S	3.6	6.3	9:30	Groundwater	VOCs/SVOCs/ Metals	Not Applicable
GW-29S	GW-29S	6.7	7.2	10:47	Groundwater		Not Applicable
GW-30S	GW-30S	5.9	10.8	12:05	Groundwater		Not Applicable
GW-31S	GW-31S	2.4	9.1	13:36	Groundwater		Not Applicable
GW-32S	GW-32S	3.8	6	14:55	Groundwater		Not Applicable
GW-33S	GW-33S	1.8	4.1	15:55	Groundwater		Not Applicable
TB-050609					Trip Blank	VOCs	Not Applicable

Additional Comments: All wells were purged using low flow methods until parameter stabilization.

Project Name: Pfohl Brothers Project Number: 11175616.00000

Sampling Crew Members: R. Murphy, T. Ifkovich Supervisor: J. Sundquist

Date of Sampling: May 7, 2009

Sample I.D. Number	Well Number	Well Volume (liters)	Volume Purged (liters)	Sample Time	Sample Description	Analysis Required	Chain-of- Custody Number	
GW-1S	GW-1S	6.9	6.9	9:48	Groundwater	VOCs/SVOCs/ Metals	Not Applicable	
GW-1D	GW-1D	90.6	66.2	11:25	Groundwater		Not Applicable	
GW-4D	GW-4D	81.8	8.4	13:59	Groundwater		Not Applicable	
GW-4S	GW-4S	7.3	28.7	14:25	Groundwater		Not Applicable	
GW-26D	GW-26D	84	42.8	15:50	Groundwater		Not Applicable	
GW-35S	GW-35S	2.4	9.2	16:36	Groundwater		Not Applicable	
TB-050709					Trip Blank	VOCs	Not Applicable	

Additional Comments: All wells were purged using low flow methods until parameter stabilization.

APPENDIX E HISTORICAL ANALYTICAL RESULTS

FIGURE E-1
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-1D




FIGURE E-2
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-1S




FIGURE E-3
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-3D




FIGURE E-4
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-3S




FIGURE E-5
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-4D




FIGURE E-6
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-4S




FIGURE E-7
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-7D




FIGURE E-8
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-7S




FIGURE E-9
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-8D




FIGURE E-10
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-8SR




FIGURE E-11
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-26D




FIGURE E-12
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-28S




FIGURE E-13
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-29S




FIGURE E-14
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-30S




FIGURE E-15
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-31S




FIGURE E-16
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-32S




FIGURE E-17
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-33S




FIGURE E-18
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-34S





FIGURE E-19
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-35S



APPENDIX F BSA PERMIT NO. 05-12-CH016

AUTHORIZATION TO DISCHARGE UNDER THE BUFFALO POLLUTANT DISCHARGE ELIMINATION SYSTEM

PERMIT NO. 05-12-CH016 USEPA Category 40 CFR Part 403

In accordance with the provisions of the Federal Water Pollution Control Act, as amended, and the Sewer Regulations of the Buffalo Sewer Authority, authorization is hereby granted to:

THE TOWN OF CHEEKTOWAGA

to discharge wastewater from a facility located at:

PFOHL BROTHERS LANDFILL REMEDIATION SITE 1000 AERO DRIVE

CHEEKTOWAGA, NEW YORK 14225

The wastewater permitted herein shall be discharged to the Town of Cheektowaga sewer system, which is connected to the Buffalo Municipal Sewer System and Treatment facilities, and which wastewater will be treated at the Buffalo Sewer Authority's Treatment Plant.

Issuance of this permit is based upon a permit application filed on **November 3, 2005** analytical data. This permit is granted in accordance with discharge limitations, monitoring requirements and other conditions set forth in Parts I and II hereof.

Effective this 1st day of April, 2006

To Expire the 31st day of March, 2009

General Manager

Signed this 30th day of March, 2006

Permit No. 05-12-CH016 Part I Page 2 of 5

PART I: SPECIFIC CONDITIONS

A. DISCHARGE LIMITATIONS & MONITORING REQUIREMENTS

During the period beginning the effective date of this Permit and lasting until the expiration date, discharge from the permitted facility outfall (see attached map) shall be limited and monitored **quarterly** by the permittee as specified below.

Sample		Discharge Limitations ⁽¹⁾	Samp	ling Requirements
Point	Parameter	Daily Max	Period	Type
001	pН	5.0 – 12.0 S.U.	1 day	Composite ²
	Total Cadmium	1.17 lbs.	1 day	Composite ²
	Total Chromium	1.17 lbs.	1 day	Composite ²
	Total Copper	3.74 lbs.	1 day	Composite ²
	Total Lead	1.17 lbs.	1 day	Composite ²
	Total Nickel	3.27 lbs.	1 day	Composite ²
	Total Zinc	5.84 lbs.	1 day	Composite ²
	Total Barium	2.34 lbs.	1 day	Composite ²
	Total Suspended Solids ⁵	250 mg/l	1 day	Composite ²
	Total Flow	140,100 gallons ⁶	1 day	Discharge meter reading

Footnotes are explained on page 5.

PART I: SPECIFIC CONDITIONS

A. DISCHARGE LIMITATIONS & MONITORING REQUIREMENTS

During the period beginning the effective date of this Permit and lasting until the expiration date, discharge from the permitted facility outfall (see attached map) shall be limited and monitored **once** by the permittee as specified below.

Sample		Discharge Limitations ⁽¹⁾	Sampling Requirements		
Point	Parameter	Daily Max	Period	Type	
001	Total Mercury	0.001 lbs.	1 day	Composite ²	
	USEPA Test				
	Method 608 ⁴	To be monitored	1 day	Grab ³	
	USEPA Test			,	
	Method 624 ⁴	To be monitored	1 day	Grab ³	
	USEPA Test			_	
	Method 625 ⁴	To be monitored	1 day	Grab ³	

Footnotes are explained on page 5.

Permit No. 05-12-CH016 Part I Page 4 of 5

PART I: SPECIFIC CONDITIONS

B. DISCHARGE MONITORING REPORTING REQUIREMENTS


During the period beginning the effective date of this permit and lasting until the expiration date, discharge monitoring results shall be summarized and reported quarterly by the permittee on the days specified below:

Sample		Reporting Requirements						
Point 001	Parameter All except USEPA Test Methods 608, 624, 625 & T Mercury	Initial Report June 30, 2006	Subsequent Reports Every March 31 st , June 30 th , September 30 th and December 31 st					
	USEPA Test Methods 608, 624 and 625 & T Mercury	March 31, 2008						

PART I: SPECIFIC CONDITIONS

C. SPECIAL REQUIREMENTS

- 1. Mass limits based on an average discharge of 140,100 gpd.
- 2. Composite samples may be time proportioned.
- 3. Four grab samples must be collected at equally spaced intervals throughout the sample day. The four (4) grab samples must be composited by a NYSDOH certified laboratory prior to analysis.
- 4. The permittee must report any compound whose concentration is equal to or greater than 0.01 mg/L. The permittee is not authorized to discharge any of the parameters evaluated by these test procedures which may cause or contribute to a violation of water quality standards or harm the sewerage system. Any parameter detected may, at the discretion of the BSA, be specifically limited and incorporated in this permit.
- 5. Surchargeable over 250 mg/L.
- 6. Flow is an action level only. If the permittee consistently exceeds this level, the BSA must be notified so that this permit can be modified.



APPENDIX G DISCHARGE REPORT SUMMARY TABLES

SAMPLING FIELD SHEET

URS

Client Name:	Pfohl Br	others Landin			
Address:	Aero Dri	ive, Cheektow	/aga, NY		
Contact:	Bill Pugl	h, P.E.		Phone:	716-897-7288
Installation:					
Sample Point:	SP-001				
Sample Locati	ion:	Meter Chamb	er - ball valve on	6" HDPE	E forcemain
Date:	3/19/	09 Crew:	R. Murphy, R	. Piurek,	T. Ifkovich
Weather:	45° F, cl	lear			
Sampling Devi	rice:	NA			
Time of Installa	lation:	11:25	Type of	Sample:	Composite
Sample Interva	al:	NA	Sample	Volume:	NA
	10 606 201				,144 gals), WW-03 (208,888 gals),
Date: Weather: Time of Collec	3/20/0 35° F, cl	s), WW-05 (4,		/W-06 (3	,850,787 gals) & MH-25 (10,137,402 gals).
Date: Weather: Time of Collec	3/20/0 35° F, cl	s), WW-05 (4,	,029,357 gals), W	/W-06 (3	,850,787 gals) & MH-25 (10,137,402 gals).
Date: Weather: Time of Collec Field Measure	3/20/ 35° F, cl ction:	s), WW-05 (4,	,029,357 gals), W	. Piurek,	,850,787 gals) & MH-25 (10,137,402 gals). T. Ifkovich
Date: Weather: Time of Collec Field Measure	3/20/ 35° F, cl ction: ements:	s), WW-05 (4,	R. Murphy, R	. Piurek, Buffer 7-	7 Buffer 4- 4 Buffer 10- 10
Date: Weather: Time of Collec Field Measure	3/20/ 35° F, cl etion: ements: :30/RJM me/initial)	s), WW-05 (4, 09 Crew: lear 11:25	R. Murphy, R PH Calibration: pH Measurement	. Piurek, Buffer 7-	7 Buffer 4- 4 Buffer 10- 10
Date: Weather: Time of Collection Field Measure 11: (tir	3/20/ 35° F, cl ction: ements: :30/RJM me/initial)	s), WW-05 (4, 09 Crew: lear 11:25	R. Murphy, R PH Calibration: pH Measurement Temperature:	. Piurek, Buffer 7-	7 Buffer 4- 4 Buffer 10- 10 7.3
Date: Weather: Time of Collector Field Measure 11: (tir Identification: Physical Obse	3/20/ 35° F, cl etion: ements: 30/RJM me/initial) EFF-032	s), WW-05 (4,	R. Murphy, R PH Calibration: pH Measurement Temperature:	. Piurek, Buffer 7-	7 Buffer 4- 4 Buffer 10- 10
Date: Weather: Time of Collect Field Measure 11: (tir Identification: Physical Obset Laboratory:	3/20/ 35° F, cl ction: ements: :30/RJM me/initial) EFF-032 ervations:	s), WW-05 (4,	R. Murphy, R R. Murphy, R pH Calibration: pH Measurement Temperature:	W-06 (3	7 Buffer 4- 4 Buffer 10- 10 7.3
Date: Weather: Time of Collect Field Measure 11: (tir Identification: Physical Obset Laboratory: Comments:	3/20/ 35° F, cl ction: ements: :30/RJM me/initial) EFF-032 ervations: TestAmer Wells WV	s), WW-05 (4, 709 Crew: lear 11:25	PH Calibration: pH Measurement Temperature:	W-06 (3 . Piurek,	7 Buffer 4- 4 Buffer 10- 10 7.3
Date: Weather: Time of Collect Field Measure 11: (tir Identification: Physical Obset Laboratory: Comments: PLC displa	3/20/ 35° F, cl ction: ements: :30/RJM me/initial) EFF-032 ervations:	s), WW-05 (4, 09 Crew: lear 11:25 2009 rica, Buffalo, No. 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,	R. Murphy, R R. Murphy, R pH Calibration: pH Measurement Temperature:	. Piurek, Buffer 7-	7 Buffer 4- 4 Buffer 10- 10 7.3 10.3°C

TABLE 1

PFOHL BROTHERS LANDFILL - EFFLUENT MONITORING ANALYTICAL RESULTS, TOTAL FLOW, AND MASS LOADINGS MARCH 2009

Sample ID	EFF-032009							
Matrix Effluent Water								
Date Sampled	3/20/2009							
Parameter	Result	Mass Loading	Discharge Limitation	Violations				
	(mg/L)	(lbs/day)	(lbs/day)	(Y/N)				
Total Barium	0.32	0.15	2.34	No				
Total Cadmuim	ND ⁽¹⁾	NA ⁽²⁾	1.17	No				
Total Chromium	0.00096	0.0005	1.17	No				
Total Copper	0.0025	0.001	3.74	No				
Total Lead	ND	NA	1.17	No				
Total Nickel	0.0047	0.002	3.27	No				
Total Zinc	0.013	0.006	5.84	No				
Total Suspended Solids	7.2	NA	250 ⁽³⁾	No				
pH ⁽⁴⁾	7.3	NA	5.0 - 12.0	No				
Total Flow ⁽⁵⁾		56,374	140,000	No				

Notes:

- (1) ND = Not Detected
- (2) NA = Not Applicable
- (3) Discharge Limitation in units of mg/L
- (4) pH measurement and Discharge Limitation in Standard Units
- (5) Total Flow reported in gallons, sample was collected over a 24 hour period

$$\text{Calculation:} \quad \left(\frac{x \text{ mg}}{L}\right) \!\! \left(\frac{y \text{ gal}}{\text{day}}\right) \!\! \left(\frac{1 \text{ lb}}{453,\!600 \text{ mg}}\right) \!\! \left(\frac{3.785 \, L}{\text{gal}}\right) = \frac{x \times y}{119,\!841} \cdot \frac{\text{lb}}{\text{day}}$$

SAMPLING FIELD SHEET

URS

Client Name: Pfoh	l Brothers Landfill			
Address: Aero	Drive, Cheektow	aga, NY		
Contact: Bill P	ugh, P.E.		Phone:	716-897-7288
Installation:				
Sample Point: SP-0	01			
Sample Location:	Meter Chamb	er - ball valve on	6" HDPE	forcemain
Date:6/	22/09 Crew:	R. Murphy, R.	Piurek,	T. Ifkovich
Weather: 77° F	-, partly cloudy			
Sampling Device:	NA			
Time of Installation:	14:25	Type of	Sample:	Composite
Sample Interval:	NA	Sample	Volume:	NA
				,004 gals), WW-03 (297,176 gals),
Date: 6/ Weather: 84° F Time of Collection:	gals), WW-05 (5, 23/09 Crew: -, clear 14:35	440,913 gals), W	,	728,854 gals) & MH-25 (12,922,351 gals).
Date: 6/ Weather: 84° F	23/09 Crew: -, clear	, ,,	Piurek,	728,854 gals) & MH-25 (12,922,351 gals).
Date: 6/ Weather: 84° F Time of Collection: Field Measurements:	23/09 Crew: -, clear	R. Murphy, R.	Piurek,	728,854 gals) & MH-25 (12,922,351 gals). T. Ifkovich
Date: 6/ Weather: 84° F Time of Collection: Field Measurements: 14:40/RJN	23/09 Crew: -, clear	R. Murphy, R.	Piurek,	7 _ Buffer 4 4 _ Buffer 10 10 _
Date: 6/ Weather: 84° F Time of Collection: Field Measurements: 14:40/RJN (time/initial)	23/09 Crew: -, clear	R. Murphy, R. pH Calibration: pH Measurement:	Piurek,	728,854 gals) & MH-25 (12,922,351 gals). T. Ifkovich 7 Buffer 4- 4 Buffer 10- 10 6.7
Date: 6/ Weather: 84° F Time of Collection: Field Measurements: 14:40/RJN (time/initial)	23/09 Crew:	R. Murphy, R. pH Calibration: pH Measurement: Temperature:	Piurek,	7 Buffer 4- 4 Buffer 10- 10 6.7
Date: 6/ Weather: 84° F Time of Collection: Field Measurements: 14:40/RJN (time/initial)	23/09 Crew:	R. Murphy, R. pH Calibration: pH Measurement: Temperature:	Piurek,	7 Buffer 4- 4 Buffer 10- 10 6.7
Date: 6/ Weather: 84° F Time of Collection: Field Measurements: 14:40/RJN (time/initial) Identification: EFF- Physical Observations Laboratory: TestAl	23/09 Crew:	R. Murphy, R. pH Calibration: pH Measurement: Temperature:	Piurek,	7 Buffer 4- 4 Buffer 10- 10 6.7 16.6°C
Date: 6/ Weather: 84° F Time of Collection: Field Measurements: 14:40/RJN (time/initial) Identification: EFF- Physical Observations Laboratory: TestAl Comments: Wells	23/09 Crew:	R. Murphy, R. pH Calibration: pH Measurement: Temperature:	Piurek, Buffer 7-	7 Buffer 4- 4 Buffer 10- 10 6.7
Date: 6/ Weather: 84° F Time of Collection: Field Measurements: 14:40/RJM (time/initial) Identification: EFF- Physical Observations Laboratory: TestAl Comments: Wells PLC display volun	23/09 Crew: -, clear 14:35 // -062309 :	R. Murphy, R. pH Calibration: pH Measurement: Temperature: NY 5 were pumping a 197,032 gals), W	Buffer 7-	7 Buffer 4- 4 Buffer 10- 10 6.7 16.6°C

TABLE 1

PFOHL BROTHERS LANDFILL - EFFLUENT MONITORING ANALYTICAL RESULTS, TOTAL FLOW, AND MASS LOADINGS JUNE 2009

Sample ID	EFF-062309							
Matrix	Effluent Water							
Date Sampled	6/23/2009							
Parameter	Result	Mass Loading	Discharge Limitation	Violations				
	(mg/L)	(lbs/day)	(lbs/day)	(Y/N)				
Total Barium	0.433	0.19	2.34	No				
Total Cadmuim	ND ⁽¹⁾	NA ⁽²⁾	1.17	No				
Total Chromium	0.0004	0.0002	1.17	No				
Total Copper	0.0022	0.001	3.74	No				
Total Lead	0.0012	0.001	1.17	No				
Total Nickel	0.006	0.003	3.27	No				
Total Zinc	0.0115	0.005	5.84	No				
Total Suspended Solids	28.8	NA	250 ⁽³⁾	No				
pH ⁽⁴⁾	6.7	NA	5.0 - 12.0	No				
Total Flow ⁽⁵⁾		53,593	140,000	No				

Notes:

- (1) ND = Not Detected
- (2) NA = Not Applicable
- (3) Discharge Limitation in units of mg/L
- (4) pH measurement and Discharge Limitation in Standard Units
- (5) Total Flow reported in gallons, sample was collected over a 24 hour period

$$\text{Calculation:} \quad \left(\frac{x \text{ mg}}{L}\right) \!\! \left(\frac{y \text{ gal}}{\text{day}}\right) \!\! \left(\frac{1 \text{ lb}}{453,\!600 \text{ mg}}\right) \!\! \left(\frac{3.785 \, L}{\text{gal}}\right) = \frac{x \times y}{119,\!841} \cdot \frac{\text{lb}}{\text{day}}$$

APPENDIX H MONITORING WELL INSPECTION LOGS

WELL INSPECTION SUMMARY

Project Name: Pfohl Brothers Landfill Project Number: 11175616.00000

Inspection Crew Members: R. Murphy, T. Ifkovich Supervisor: J. Sundquist

Date(s) of Inspection: May 4-7, 2009

Other Comments	Well Depth (ft. BTOC)	Water Level (ft. BTOC)	Riser	Protective Casing	Surface Seal	Lock	Well I.D. Number
Lubricated lock	14.94	3.80	Bulged	OK	OK	ОК	GW-1S
Lubricated lock	39.63	2.93	Bulged	OK	OK	ОК	GW-1D
	13.24	2.56	OK	OK	OK	ОК	GW-3S
	35.69	1.91	OK	OK	OK	OK	GW-3D
Lubricated lock	16.25	4.41	OK	OK	OK	OK	GW-4S
	45.57	12.46	OK	OK	OK	ОК	GW-4D
	35.04	5.02	OK	OK	ОК	OK	GW-7S
	60.30	41.95	Damaged	OK	OK	OK	GW-7D

Additional Comments: The weep holes in the protective casing appear to have corroded shut, allowing water to freeze within the

annular space, bulging the riser pipe this past winter.

WELL INSPECTION SUMMARY

Project Name: Pfohl Brothers Landfill Project Number: 11175616.00000

Inspection Crew Members: R. Murphy, T. Ifkovich Supervisor: J. Sundquist

Date(s) of Inspection: May 4-7, 2009

Well I.D. Number	Lock	Surface Seal	Protective Casing	Riser	Water Level (ft. BTOC)	Well Depth (ft. BTOC)	Other Comments
GW-8SR	OK	OK	OK	OK	5.38	13.03	
GW-8D	ОК	OK	OK	OK	5.88	36.60	
GW-26D	ОК	OK	OK	OK	6.69	40.71	
GW-28S	ОК	OK	OK	OK	9.65	15.55	
GW-29S	OK	OK	OK	OK	9.11	19.98	
GW-30S	OK	OK	OK	OK	8.35	17.95	
GW-31S	OK	OK	OK	OK	5.61	9.57	
GW-32S	ОК	ОК	OK	OK	3.79	9.92	

Additional Comments:

WELL INSPECTION SUMMARY

Project Name: Pfohl Brothers Landfill Project Number: 11175616.00000

Inspection Crew Members: R. Murphy, T. Ifkovich Supervisor: J. Sundquist

Date(s) of Inspection: May 4-7, 2009

Well I.D. Number	Lock	Surface Seal	Protective Casing	Riser	Water Level (ft. BTOC)	Well Depth (ft. BTOC)	Other Comments
GW-33S	OK	OK	OK	OK	5.22	8.20	
GW-34S	OK	OK	OK	OK	2.92	10.00	
GW-35S	OK	OK	OK	OK	3.52	7.45	

Additional Comments:

ATTACHMENT B

July 2009 – December 2009 Semi Annual Report



February 12, 2010

Mr. Jaspal Singh Walia, P.E. New York State Department of Environmental Conservation 270 Michigan Ave. Buffalo, NY 14203

Re: **Semi-Annual Report**

Pfohl Brothers Landfill, Town of Cheektowaga, New York

Dear Mr. Walia:

Enclosed are two copies of the tenth Semi-Annual Report for the Pfohl Brothers Landfill in Cheektowaga, New York. A copy has also been sent to Ms. Pamela Tames, P.E. of the United States Environmental Protection Agency. Also enclosed are Data Usability Summary Reports for laboratory analyses associated with the sampling events. PDF copies of the reports are also enclosed.

If you have any questions on this report, please feel free to contact me.

Sincerely,

URS CORPORATION

Jon Sundquist, Ph.D.

Project Manager

Enclosures

cc: Pamela Tames, P.E. - USEPA (w/attachments)

William Pugh, P.E. – Town of Cheektowaga (w/attachments)

File 11172700 (C-1)

SEMI ANNUAL REPORT OPERATION AND MAINTENANCE JULY 2009 TO DECEMBER 2009 PFOHL BROTHERS LANDFILL CHEEKTOWAGA, NY

Submitted to:

NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION 270 MICHIGAN AVENUE BUFFALO, NEW YORK 14203

Prepared by:

URS CORPORATION
77 GOODELL STREET
BUFFALO, NEW YORK 14203

Prepared for:

TOWN OF CHEEKTOWAGA
ENGINEERING DEPARTMENT
275 ALEXANDER AVE
CHEEKTOWAGA, NEW YORK 14211

FEBRUARY 2010

TABLE OF CONTENTS

]	Page No.			
1.0	INTRO	ODUCTION	1-1			
	1.1	Background	1-1			
	1.2	Operation and Maintenance Activities				
2.0	GENE	ERAL MAINTENANCE ACTIVITIES	2-1			
3.0	MONI	TORING ACTIVITIES	3-1			
	3.1	Groundwater Hydraulic Monitoring	3-1			
	3.2	Groundwater Quality Monitoring	3-1			
	3.3	Groundwater Discharge Monitoring	3-4			
	3.4	Monitoring Well Inspections	3-4			
4.0	SUMM	MARY AND RECOMMENDATIONS	4-1			
		TABLES				
Table 3	3-1	Groundwater Sample Results				
Table 3	3-2	Approved Revision Of Table 3.2 From The O&M Plan				
		FIGURES				
Figure	1-1	Site Location Map				
Figure	3-1	Monitoring Locations				
		APPENDICES				
Appen	dix A	Example Daily Inspection Sheets				
Appen	dix B	Monthly Flow Summaries (July 2009 – December 2009)				
Appen	dix C	Hydraulic Monitoring Tables				
Appen	dix D	Groundwater Purge and Sample Collection Logs				
Appen	dix E	Historical Analytical Results				
Appen	dix F	BSA Permit No. 05-12-CH016				
Appen	dix G	Discharge Report Summary Tables				
Appen	dix H	Monitoring Well Inspection Logs				

1.0 INTRODUCTION

1.1 Background

The Pfohl Brothers Landfill is located on Aero Drive in the Town of Cheektowaga, New York (Figure 1-1). The site is listed as site No. 9-15-043 on the New York State Department of Environmental Conservation's (NYSDEC's) Registry of Inactive Hazardous Waste Disposal Sites. A Consent Order between NYSDEC and potentially responsible parties (PRPs) for closure of the site was signed in 2001 and remedial construction commenced in 2001. The remedy included consolidation of waste material, capping of the waste disposal and consolidation areas, and encircling the landfill areas with a groundwater collection system to prevent off-site migration. The remedial action was completed in 2002.

Responsibility for implementing the remedy was divided between a "steering committee" of industrial PRPs and the Town of Cheektowaga. The steering committee responsibilities lay generally with the capital construction activities of the remedy including waste consolidation, cap and drainage system installation, etc. The Town of Cheektowaga, which was named as a PRP for disposal of municipal waste at the Pfohl Brothers Landfill when it was operating, is performing the operation and maintenance (O&M) activities at the landfill, pursuant to a settlement agreement between the Town and the steering committee.

1.2 Operation and Maintenance Activities

While construction of the remedy was substantially complete by late 2002, the final O&M manual was not approved by the NYSDEC until March 10, 2006. However, the Town of Cheektowaga and its consultant (URS Corporation) assumed most of the operational responsibilities since 2002. This includes a variety of general maintenance activities as outlined in Section 2 and sampling and other monitoring activities outlined in Section 3.

Beginning in 2004, the Town and URS assumed all of the O&M activities described in the O&M plan. This report is the twelfth semi-annual report as called for by Section 3.6 of the O&M plan.

2.0 GENERAL MAINTENANCE ACTIVITIES

Since completion of construction activities in 2002, personnel from the Town of Cheektowaga Engineering Department have performed general activities to ensure the physical operation of the landfill as intended by the design. The various O&M activities performed by the Town from July 2009 through December 2009 include the following actions.

- The amount of groundwater discharged through the collection system was recorded on a daily basis. The flow rate displayed by each wet well pump at the time of daily inspection and the total cumulative volume of flow was recorded for each wet well on daily inspection sheets. Examples of the daily inspection sheet are attached in Appendix A.
- Total cumulative effluent flow rates and volumes were summarized on a monthly basis starting in February 2003. The monthly totals for the period of July 2009 through December 2009, including graphs showing daily total discharge (gallons) as a function of calendar day, are presented in Appendix B.
- The wet well pumps were shutdown during wet weather flow conditions throughout the year to reduce hydraulic loading to the sewer. Such actions were only taken upon request of the Buffalo Sewer Authority during heavy storm events in order to reduce the hydraulic load on the BSA treatment system during such events. Shutdown events are recorded and included with the monthly flow data as previously requested by NYSDEC.
- Plowed snow to access the Control Building when necessary.
- Cleaned/replaced check valves as necessary at all wet wells.
- NYSEG crews made repairs to overhead conducter lines and re-crimped all
 connections on the customer side of the distribution pole to resolve incoming power
 fluctuations (August 2009).
- The battery for the Control Building intrusion alarm was replaced (August 2009).

- Niagara Grass performed a complete mowing of the entire landfill acreage the week of August 31st to September 4th, 2009.
- Wildlife trapper engaged on an as-needed basis to control ground burrowing animals, and as of September 2009 over 17 woodchucks were reported being trapped.
- Replaced WW-5 pump discharge hose on November 14, 2009.
- Great Lakes Building Systems completed replacement of the failed Control Building security panel (December 2009).

3.0 MONITORING ACTIVITIES

The Town of Cheektowaga retained URS Corporation to perform monitoring activities as outlined in Section 3.1 of the O&M plan. During the period of January 2004 through the present, URS performed groundwater hydraulic monitoring (Section 3.1.1.2 of the O&M plan) and effluent monitoring (Section 3.1.4 of the O&M plan) on a quarterly basis. URS also performed the twelfth semi-annual groundwater quality monitoring event (Section 3.1.1.3 of the O&M plan). A summary of the monitoring activities is presented in the following subsections. Hydraulic and groundwater sampling locations are shown on Figure 3-1.

3.1 Groundwater Hydraulic Monitoring

Groundwater and surface water elevations were monitored on a quarterly basis at all locations listed in Table 3.1 of the O&M Plan. The hydraulic monitoring data tables showing groundwater elevations are presented in Appendix C. Table 1 of this appendix lists the measured elevations. Table 2 provides a comparison of the measured levels in the wells and corresponding manholes/wet wells.

The data presented in Appendix C indicate that groundwater levels outside the collection system were higher than the levels measured in the corresponding wet well or manhole for each measurement date, with the exception of the WW-6/GW-34S pairing on September 24, 2009 where the outside monitoring point was slightly lower on that date. These data verify that collection system is operating as designed.

3.2 **Groundwater Quality Monitoring**

The twelfth semi-annual round of groundwater sampling was conducted between November 10, 2009 and November 13, 2009. All wells listed in Table 3.2 of the O&M plan were purged and sampled using dedicated/disposable equipment. Figure 3-1 shows the well locations. Low flow sampling techniques were used on most wells. Three wells, GW-4S, GW-7S, and GW-7D, were purged dry before a sample could be collected. These wells were sampled after their

water levels recovered. Purge logs and sampling summary sheets are provided in Appendix D. Measurements of pH, specific conductivity, temperature, dissolved oxygen, oxidation reduction potential, and turbidity taken during purging are provided in Appendix D. The samples were packed with ice in coolers and transported under chain-of-custody (CoC) control to Test America Laboratories of Amherst, New York.

Groundwater samples were analyzed for the parameters listed in Table 3.2 of the O&M plan as revised in accordance with Table 3-6 in the Semi Annual Report dated September 2007 (January through June 2007) and as approved by the December 6, 2006 and November 29, 2007 correspondence from the NYSDEC authorizing a reduction in the parameters list (this table is included in this report as Table 3-2). Table 3-1 of this report presents the groundwater sample results compared with NYSDEC Ambient Water Quality Standards and Guidance Values and Groundwater Effluent Limitations Class GA water quality standards.

No VOCs or SVOCs were detected at concentrations above the Class GA water quality standards at any location.

Among the metals, iron, magnesium, manganese, and sodium routinely exceed Class GA standards in most site wells. The concentration of iron, magnesium, manganese, and sodium in most site wells was similar to the concentrations found during previous sampling events. Aresenic was detected at a concentration exceeding its groundwater standard in well GW-29S. Chromium was detected at concentrations exceeding groundwater standards in both GW-03S and GW-07D. Lead exceeded its groundwater standard in upgradient well GW-07D. Nickel was detected at a concentration exceeding its groundwater standard in well GW-03S.

Sodium concentrations were generally higher in bedrock wells (GW-1D, GW-3D, GW-8D and GW-26D) and shallow wells adjacent to roads (GW-1S and GW-30S) sodium was also elevated in GW-08SR. No significant changes in metals concentrations were observed when compared to previous sampling event analytical results. The higher sodium concentrations in the bedrock wells may be attributed to the local bedrock composition and the elevated concentration in the shallow wells may be the result of seasonal road de-icing activities.

Appendix E, Figures E-1 through E-19 presents a trend analysis of groundwater parameters that routinely exceed Class GA groundwater standards. A review of the trend analysis indicated that no significant changes or trends in concentrations of any of the parameters exceeding groundwater standards have occurred over the twelve semi-annual sampling events except as described below. Figure E-2 for GW-01S, indicates a consistent drop in sodium concentration over the last five sampling events. Figure E-4 for GW-03S indicates an upward trend for nickel since monitoring began, in addition chromium has exceeded its groundwater standard at GW-03S for 3 of the last 5 sampling events. Figure E-5 for GW-04D, indicates a slight increasing trend for magnesium. Figure E-10 for GW-08SR shows an upward trend in sodium concentration over recent events. Figure E-12 for GW-28S, indicates decreasing trend for sodium since monitoring began. Figure E-13 for GW-29S, indicates a slight increasing trend in iron concentration since monitoring began and arsenic has been detected at concentrations exceeding its groundwater standard for 4 of the last 5 sampling events.

The groundwater analytical data package was prepared by Test America in accordance with NYSDEC Category A deliverable requirements. It was reviewed for compliance with analytical method requirements and the following guidelines: USEPA Contract Laboratory Program (CLP) National Functional Guidelines for Organic Data Review, EPA-540-R-99-008, October 1999; USEPA CLP National Functional Guidelines for Inorganic Data Review, EPA-540-R-01-008, July 2002; and USEPA Region II Data Validation SOP for SW-846 Method 8290, PCDDs and PCDFs by High Resolution Gas Chromatography/High-Resolution Mass Spectrometry (HRGC/HRMS), SOP No. HW-19, Revision 1, October 1994. Qualifications applied to the data include "J/UJ" (estimated concentration/estimated quantitation limit), "J+" (estimated concentration with possible high bias), "J-" (estimated concentration with possible low bias), and "U" (not detected).

A Data Usability Summary Report (DUSR) was prepared following the guidelines provided in NYSDEC Division of Environmental Remediation *Guidance for the Development of Data Usability Summary Reports*, dated June 1999. The DUSR dated December 2009 is submitted separately from this report.

3.3 Groundwater Discharge Monitoring

URS completed two quarterly sampling events (September 2009 and December 2009) of the groundwater collection system discharge since the previous semi-annual report. The sampling was performed in accordance with the requirements of Discharge Permit No. 05-12-CH016 between the Buffalo Sewer Authority and the Town of Cheektowaga. A copy of Permit No. 05-12-CH016 is included as Appendix F.

During the sampling events in September 2009 and December 2009, each regulated parameter was below the limits set by the permit. Copies of the data summary tables that were included with the monitoring reports are included as Appendix G.

3.4 <u>Monitoring Well Inspections</u>

During the November 2009 groundwater sampling event, a well inspection was performed. All wells appeared to be in good condition with the exception of previously existing damage to the risers on GW-07D, GW-01S, and GW-01D. The monitoring well inspection logs may be found in Appendix H.

4.0 SUMMARY AND RECOMMENDATIONS

General Maintenance: The Town will continue to maintain mechanical equipment at the landfill on an as-needed basis and operate the groundwater collection and discharge system as designed. The Town will also continue regular inspections, mow the cap once per year, and plow access to the control building during winter months as necessary.

Groundwater Hydraulic Monitoring: Hydraulic monitoring has been performed on a quarterly basis in conjunction with the discharge monitoring. Water level measurement data demonstrates that the hydraulic gradient is from outside the landfill towards the collection trench. Continued quarterly monitoring is recommended.

Groundwater Quality Monitoring: Groundwater sample results indicate that only low levels of organic compounds and metals are present. Similar concentrations of most parameters were found during previous sampling events. The thirteenth round of groundwater sampling will be conducted in May 2009. Low flow sampling techniques will continue to be used on wells that historically have been purged to dryness. A review of the purge logs (Appendix D) has indicated that four wells (GW-4S, GW-7S, GW-7D, and GW-31S) can still be purged to dryness even using low flow sampling techniques.

Groundwater Discharge Monitoring: Groundwater discharges remain within permit limits. Continued quarterly monitoring is recommended.

Surface Water and Sediment Sampling: URS asked that the NYSDEC consider the discontinuation of surface water and sediment sampling at the site in the January to June 2008 Semiannual Report. No future surface water or sediment sampling is planned.

Wetland Inspection Summary: An inspection of the wetlands during the May 2009 event indicated that most of the replanted wetland stock has flourished and the wetland areas are returning to their natural state.

TABLES

TABLE 3-1 GROUNDWATER SAMPLE ANALYTICAL RESULTS PFOHL BROTHERS LANDFILL SITE NOVEMBER 2009

Location ID	_		GW-01D	GW-01S	GW-03D	GW-03S	GW-04D
Sample ID			GW-1D	GW-1S	GW-3D	GW-3S	GW-4D
Matrix			Groundwater	Groundwater	Groundwater	Groundwater	Groundwater
Depth Interval (f	t)		-	-	-	-	-
Date Sampled			11/12/09	11/12/09	11/11/09	11/11/09	11/12/09
Parameter	Units	*					
Volatile Organic Compounds							
1,2-Dichloroethene (total)	UG/L	5			1.1 J		
Acetone	UG/L	50					
Vinyl chloride	UG/L	2			0.65 J		
Semivolatile Organic Compounds							
1,3-Dichlorobenzene	UG/L	3			1.4 J		
1,4-Dichlorobenzene	UG/L	3			2.2 J		
bis(2-Ethylhexyl)phthalate	UG/L	5					
Phenol	UG/L	1					0.43 J
Arsenic	MG/L	0.025					
Barium	MG/L	1	0.0670	0.163	0.0867	0.157	0.0722
Cadmium	MG/L	0.005		0.0003 J		0.0003 J	
Chromium	MG/L	0.05	0.0052	0.0014 J	0.0017 J	0.248	
Copper	MG/L	0.2				0.0075 J	
Iron	MG/L	0.3	0.415	9.02	2.48	2.40	0.063
Lead	MG/L	0.025					
Magnesium	MG/L	35	33.5	14.3	18.7	75.4	71.0
Manganese	MG/L	0.3	0.0190	0.735	0.888	0.227	0.0188
Nickel	MG/L	0.1	0.0027 J		0.0062 J	0.677	
Sodium	MG/L	20	87.8	149	181	38.3	73.2
Zinc	MG/L	2	0.0584	0.0027 J		0.0129	0.0015 J

^{*-} NYSDEC TOGS (1.1.1), Ambient Water Quality Standards and Guidance Values and Groundwater Effluent Limitations. June 1998 (includes 4/2000 Addendum). Class GA. * - PCB Criteria based on sum of the aroclors.

Flags assigned during	chemistry validation are shown
	Concentration Exceeds

TABLE 3-1 GROUNDWATER SAMPLE ANALYTICAL RESULTS PFOHL BROTHERS LANDFILL SITE NOVEMBER 2009

Location ID Sample ID Matrix Depth Interval (ft) Date Sampled		GW-04S GW-4S Groundwater - 11/12/09	GW-07D GW-7D Groundwater - 11/11/09	GW-07S GW-7S Groundwater - 11/11/09	GW-08D DUPLICATE Groundwater - 11/11/09	GW-08D GW-8D Groundwater - 11/11/09								
							Parameter	Units	*				Field Duplicate (1-1)	
							Volatile Organic Compounds							
							1,2-Dichloroethene (total)	UG/L	5				1.2 J	1.2 J
							Acetone	UG/L	50		2.7 J			
Vinyl chloride	UG/L	2				1.3	1.3							
Semivolatile Organic Compounds														
1,3-Dichlorobenzene	UG/L	3												
1,4-Dichlorobenzene	UG/L	3												
bis(2-Ethylhexyl)phthalate	UG/L	5		3.0 J										
Phenol	UG/L	1												
Arsenic	MG/L	0.025				0.0067 J	0.0065 J							
Barium	MG/L	1	0.0992	0.0497	0.204	0.114	0.110							
Cadmium	MG/L	0.005		0.0012										
Chromium	MG/L	0.05		0.128	0.0066	0.0166	0.0205							
Copper	MG/L	0.2		0.0196										
Iron	MG/L	0.3	0.356	4.84	0.256	3.85	3.69							
Lead	MG/L	0.025		0.132										
Magnesium	MG/L	35	24.1	25.3	29.4	20.1	19.4							
Manganese	MG/L	0.3	0.284	0.0704	0.0625	0.651	0.629							
Nickel	MG/L	0.1	0.0054 J	0.0636	0.0497	0.0087 J	0.0086 J							
Sodium	MG/L	20	28.7	81.9	55.5	238	230							
Zinc	MG/L	2	0.0027 J	0.0261	0.0042 J	0.0262	0.0246							

^{*-} NYSDEC TOGS (1.1.1), Ambient Water Quality Standards and Guidance Values and Groundwater Effluent Limitations. June 1998 (includes 4/2000 Addendum). Class GA. * - PCB Criteria based on sum of the aroclors.

Flags assigned during	chemistry validation are shown
	Concentration Exceeds

TABLE 3-1 GROUNDWATER SAMPLE ANALYTICAL RESULTS PFOHL BROTHERS LANDFILL SITE NOVEMBER 2009

Location ID Sample ID Matrix Depth Interval (ft) Date Sampled		GW-08SR	GW-26D	GW-28S	GW-29S	GW-30S								
		GW-8SR	GW-26D	GW-28S	GW-29	GW-30S								
		Groundwater - 11/11/09	Groundwater - 11/12/09	Groundwater - 11/11/09	Groundwater - 11/13/09	Groundwater - 11/13/09								
							Parameter	Units	*					
							Volatile Organic Compounds							
1,2-Dichloroethene (total)	UG/L	5		2.0 J										
Acetone	UG/L	50												
Vinyl chloride	UG/L	2	1.0	1.6										
Semivolatile Organic Compounds														
1,3-Dichlorobenzene	UG/L	3												
1,4-Dichlorobenzene	UG/L	3												
bis(2-Ethylhexyl)phthalate	UG/L	5												
Phenol	UG/L	1				0.59 J								
Arsenic	MG/L	0.025	0.0086 J			0.0406								
Barium	MG/L	1	0.535	0.128	0.0762	0.334	0.402							
Cadmium	MG/L	0.005				0.0003 J	0.0003 J							
Chromium	MG/L	0.05	0.0020 J			0.0038 J								
Copper	MG/L	0.2	0.0013 J			0.0023 J								
Iron	MG/L	0.3	22.7	5.62	0.283	17.2	13.8							
Lead	MG/L	0.025												
Magnesium	MG/L	35	49.2	20.7	33.9	81.4	43.3							
Manganese	MG/L	0.3	1.10	1.01	1.05	0.804	2.24							
Nickel	MG/L	0.1	0.0046 J	0.0030 J	0.0035 J	0.0017 J								
Sodium	MG/L	20	287	254	27.4	15.0	629							
Zinc	MG/L	2	0.0039 J	0.0052 J	0.0033 J	0.0032 J	0.0015 J							

^{*-} NYSDEC TOGS (1.1.1), Ambient Water Quality Standards and Guidance Values and Groundwater Effluent Limitations. June 1998 (includes 4/2000 Addendum). Class GA. * - PCB Criteria based on sum of the aroclors.

Flags assigned during	chemistry validation are shown
	Concentration Exceeds

TABLE 3-1 GROUNDWATER SAMPLE ANALYTICAL RESULTS PFOHL BROTHERS LANDFILL SITE NOVEMBER 2009

Location ID			GW-31S	GW-32S	GW-33S	GW-34S	GW-35S
Sample ID			GW-31S	GW-32S	GW-33S	GW-34S	GW-35S
Matrix			Groundwater	Groundwater	Groundwater	Groundwater	Groundwater
Depth Interval (ft)			-	-	-	-	-
Date Sampled			11/13/09	11/13/09	11/11/09	11/10/09	11/12/09
Parameter	Units	*					
Volatile Organic Compounds							
1,2-Dichloroethene (total)	UG/L	5					
Acetone	UG/L	50					
Vinyl chloride	UG/L	2					
Semivolatile Organic Compounds							
1,3-Dichlorobenzene	UG/L	3					
1,4-Dichlorobenzene	UG/L	3					
bis(2-Ethylhexyl)phthalate	UG/L	5					
Phenol	UG/L	1					
Arsenic	MG/L	0.025					
Barium	MG/L	1	0.0675	0.0682	0.0378	0.175	0.0666
Cadmium	MG/L	0.005	0.0004 J	0.0003 J			
Chromium	MG/L	0.05	0.0034 J	0.0015 J	0.0012 J		
Copper	MG/L	0.2	0.0021 J	0.0016 J		0.0016 J	
Iron	MG/L	0.3	0.264	0.097		0.046 J	0.044 J
Lead	MG/L	0.025					
Magnesium	MG/L	35	31.7	44.6	43.0	59.9	28.8
Manganese	MG/L	0.3	0.981	0.274	0.0431	0.155	0.396
Nickel	MG/L	0.1	0.0051 J	0.0023 J	0.0024 J	0.0061 J	0.0024 J
Sodium	MG/L	20	6.7	7.1	5.3	36.5	3.4
Zinc	MG/L	2	0.0068 J	0.0045 J	0.0027 J	0.0035 J	0.0033 J

^{*-} NYSDEC TOGS (1.1.1), Ambient Water Quality Standards and Guidance Values and Groundwater Effluent Limitations. June 1998 (includes 4/2000 Addendum). Class GA. * - PCB Criteria based on sum of the aroclors.

Flags assigned during	chemistry validation are shown
	Concentration Exceeds

TABLE 3-2

APPROVED REVISION OF TABLE 3.2 FROM THE O&M PLAN

GROUNDWATER SAMPLING SUMMARY OPERATION AND MAINTENANCE PLAN PFOHL BROTHERS LANDFILL SITE, CHEEKTOWAGA, NEW YORK

LOCATIONS

GW-1D/1S

GW-3D/3S

GW-4D/4S

GW-7D/7S

GW-8D/8S(R)

GW-26D/35S

GW-28S

GW-29S

GW-30S

GW-31S

GW-32S

GW-33S

GW-34S

FREQUENCY

semi-annually for overburden and bedrock groundwater

PARAMETERS

Field pН

> conductivity temperature turbidity

VOCs Acetone

Benzene

1,2-Dichloroethene (total) 1,1,2-Trichloroethane

Vinyl chloride

SVOCs Phenol

> 1,3-Dichlorobenzene 1,4-Dichlorobenzene bis(2-Ethylhexyl)phthalate

TABLE 3-2 (continued)

APPROVED REVISION OF TABLE 3.2 FROM THE O&M PLAN

GROUNDWATER SAMPLING SUMMARY OPERATION AND MAINTENANCE PLAN PFOHL BROTHERS LANDFILL SITE, CHEEKTOWAGA, NEW YORK

PARAMETERS (cont'd)

Metals Antimony

Arsenic Barium Cadmium Chromium Copper Iron Lead

Magnesium Manganese Mercury Nickel Silver Sodium Zinc

FIGURES

URS



12/15/2005 12/15/2005

APPENDIX A EXAMPLE DAILY INSPECTION SHEETS

Pfohl Brothers Landfill Site

Daily Logs				•
√ate Time	7/27/09	-	Weather conditions Read by:	BILL PUGH
	Level of Water from bottom (ft.)	Flow gallons / minute	Flow Totals gallons	Pump Run Time Hrs.
WW-3	5.5	0	10	1343
WW-2	4.7	0	-1692	3ව
WW-1	4.2	0	140,039	1640
WW-6	6.8	0	225,212	2472
ww-4	6.5	15.2	43,544	3495
ww-5	5.6	27.8	373,553	2309
-	zer at Meter chamber		182,402	
_	Outside temp T = 76 Current A = 0		Set point SP = 40°	
rge Suppr	Current A = 0 essor events	volts	Which WW was running	?
rge Suppr Motor Contro	essor events oi Center	volts		?
rge Suppr Motor Contro	essor events ol Center Volts 480	= '	Which WW was running	?
rge Suppr Motor Contro - - Filter	essor events col Center Volts 480 Amps /5	amps Changed	Which WW was running	?
rge Suppr Motor Contro Filter Comments a	essor events col Center Volts 480 Amps /5 Checked © und/or Current Condition	amps Changed	Which WW was running 1□ 2□ 3□ 4□ 5☑ 6□	
Filter Comments a	essor events cl Center Volts 480 Amps /5 Checked and/or Current Condition W 2 - NEG	amps Changed □ S Frow. — I	Which WW was running 102030405060 RAN PUMP CIGAR BAU	2 ON CHECK VALVE
Filter Comments a MAA PLE	essor events cli Center Volts 480 Amps /5 Checked und/or Current Condition V 2 - NEG SET ALL AL	amps Changed The second of t	Mhich WW was running 102030405060 RAN PUMP CLEAR BAU OMING VOL	2 ON CHECK VALVE TAGE
Filter Comments a MAA ILE	essor events col Center 480 Amps /5 Checked and/or Current Condition W Z - NEG SET ALL AL	amps Changed The second of	Which WW was running 102030405060 RAN PUMP CUEAR BAU OMING VOL	2 ON CHECK VALVE TAGE
Filter Comments a MAA ILE	essor events col Center 480 Amps /5 Checked and/or Current Condition W Z - NEG SET ALL AL	amps Changed The second of	Which WW was running 102030405060 RAN PUMP CUEAR BAU OMING VOL	2 ON CHECK VALVE TAGE
Filter Comments a MAA ILE	essor events col Center 480 Amps /5 Checked and/or Current Condition W Z - NEG SET ALL AL	amps Changed The second of	Mhich WW was running 102030405060 RAN PUMP CLEAR BAU OMING VOL	2 ON CHECK VALVE TAGE

Pfohl Brothers Landfill Site

Daily L	ogsheet	•	Town of Cheektowa	aga 💮
) vate	10/23/09	• .	Weather conditions	BILL PUGH
Time	2:10		Read by:	BILL PUGH
	Level of Water from bottom (ft.)	Flow gallons / minute	Flow Totals gallons	Pump Run Time Hrs.
WW-3	5.5	0	34	1343
WW-2	4.6	0	14090	57
WW-1	3.9	0	499, 497 1, 244, 208 204, 834	1825
WW-6	6.0	0	1,244,208	3022
WW-4	7.0	0	204,834	3630
WW-5	6.3	39.4	1,672,684	2881
Flow Tota	alizer at Meter chamber		3,661,124	
Heat Trac	Outside temp T = 46 Current A = 0		Set point SP = 4-6	
rge Sup	pressor events	414,308		
Motor Con	trol Center Volts 480	volts	Which WW was running?	
e e	Amps 5	amps	10 20 30 40 5 60	:
Filter	Checked []	Changed □		
Comments	and/or Current Conditions			
			SEASON - LOW	•
	· · · · · · · · · · · · · · · · · · ·			
·				
		-		
				· · · · · · · · · · · · · · · · · · ·


Daily Log		oni Brotners L	.andiiii Site Town of Cheektowa	ga
yate Time	10/30/09	-		BILL PUGH
	Level of Water from bottom (ft.)	Flow gallons / minute	Flow Totals gallons	Pump Run Time Hrs.
WW-3	5.5	0	14,025	57
WW-2	4.7	0	499,497	1825
WW-1	4.1	62.9	1, 429, 807	3071
WW-6	7.0	0	204,834	3630
WW-4	7.7	0	1,828,961	2949
WW-5	lizer at Meter chamber		4,002,377	
irge Supt	Outside temp T = 65 Current A = 0 pressor events	414,309	Set point SP = 40	
Motor Conf	trol Center Volts 480 Amps 5	_volts _amps	Which WW was running?	
Filter	Checked []	Changed □		
	and/or Current Condition		ig, Frow n	JW 2
			· · · · · · · · · · · · · · · · · · ·	

=;

APPENDIX B

MONTHLY FLOW SUMMARIES JULY 2009 – DECEMBER 2009

THE TOWN OF CHEEKTOWAGA



Main Pump Station 171 Central Boulevard Cheektowaga, NY 14225 Phone: 716-896-1777

Fax: 716-896-6437

August 7, 2009

Mr. William R. Pugh, P.E. Town Engineer Town of Cheektowaga

Re: Pfohl Bros. Flow Data

Dear Mr. Pugh,

Enclosed for your review, please find a copy of the July 2009 Direct Discharge Flow Data Report, prepared by Jon W. Nichy.

Please note that the Discharge Totalizers were reset on July 1, 2009.

A monthly log sheet indicating inhibiting and enabling of pumping operation at the site is included with this package.

Should you have any other questions or comments regarding this submittal, please contact this office @ 896-1777.

Yours truly,

Town of Cheektowaga

Jon W. Nichy

Superintendent Main Pump Station

RECEIVED

AUG 1 0 2009

ENGINEERING DEPT Direct Discharge Flow Data

6/30/2009		13161919	30,345	13,161,956	
July-09	Time; 11:58pm unless otherwise stated	Totalizer Reading (Gallons)	Daily Total Discharge (Gallons)		Notes
1		0	0	0	· · · ·
2		14733	14,733		
3		28408	13,675	28,408	
4		28408	. 0	28,408	
. 5		42820	14,412	42,820	
6		160138	117,318	160,138	
7		278606	118,468	278,606	,
8		278606	0	278,606	
9		326089	47,483	_ 326,089	
10		333617	7,528	333,617	
11		363392	29,775	363,392	
12		363392	0	363,392	
13		394644	31,252	394,644	
14		394644	0	394,644	
15		444029	. 49,386	444,030	
16		462758	18,729	462,759	
17		480808	18,050	480,809	
18		480808	0	480,809	
19		485954	5,146	485,955	
20		534455	48,502	534,457	
21		534455	. 0	534,457	
22	·	534455	0	534,457	
23		536424	1,969	536,426	
24		676001	139,577	676,003	
25		731266	55,265	731,268	
26		745355	14,088	745,356	
27		799099	53,745	799,101	
28		812460	13,360	812,461	
29		848711	36,252	848,713	
30		871476	22,765	871,478	
31		898917	27,441	898,919	

10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 Days 6 |0 20000 -160000 ₇ Daily Total Discharge (Gallons) 140000 40000 120000 -


Pfohl Bros. July 2009

PFOHL BROTHERS LANDFILL SITE CHEEKTOWAGA, NEW YORK

Auto Dialer System Log

			- L
DATE	PUMP Inhibit -08 (Off)	TIME Enable -07 (On)	COMMENTS
7/2/09	0613	1710	
7/3/09	0204		
7/5/09		1746	
7/6/69	0722	1052	
7/10/09	1507		
7/19/09		1745	
7/21/09	1908		
7/23/09		2259	
7/25/09	1757		
7/26/69	•	1813	*

THE TOWN OF CHEEKTOWAGA



Main Pump Station 171 Central Boulevard Cheektowaga, NY 14225 Phone: 716-896-1777

Fax: 716-896-6437

September 9, 2009

Mr. William R. Pugh, P.E. Town Engineer Town of Cheektowaga

Re: Pfohl Bros. Flow Data

Dear Mr. Pugh,

Enclosed for your review, please find a copy of the August 2009 Direct Discharge Flow Data Report, prepared by Jon W. Nichy.

A monthly log sheet indicating inhibiting and enabling of pumping operation at

the site is included with this package.

Should you have any other questions or comments regarding this submittal, please contact this office @ 896-1777.

Yours truly,

Town of Cheektowaga

Jon W. Nichy Superintendent Main Pump Station

RECEIVED

SEP - 9 2009

ENGINEERING DEPT Direct Discharge Flow Data

7/31/200	7/31/2009		27,441	898,919		
August-09	Time; 11:58pm unless otherwise stated	Totalizer Reading (Gallons)	Daily Total Discharge (Gallons)	f	Notes	
1		0	0	898,919		
2		898917	0			
3	·	948797	49,880			
4		1011969	63,172			
5		1011969	0	1,011,971		
6		1011969	. 0	1,011,971		
7		1042279	30,310			
8		1079779	37,500			
9	_	1094130	14,351	1,094,132		
10		1094939	809	1,094,941		
11		1168086	73,147	1,168,088		
12		1346091	178,005	1,346,093		
13	·	1359543	13,452	1,359,545	•	
14		1367712	8,169	1,367,714		
15		1398621	30,910	1,398,624		
16		1426303	27,682	1,426,306		
17		1434096	7,793	1,434,099		
18		1470147	36,051	1,470,150		
19		1492325	22,178	1,492,328		
20		1499898	7,574	1,499,902		
21		1528953	29,055	1,528,957		
22		1572811	43,858	1,572,815		
23		1572811	0	1,572,815		
24		1572811	0	1,572,815		
25		1589670	16,859	1,589,674		
26		1615551	25,881	1,615,555		
27		1615551	0	1,615,555		
28		1664976	49,425	1,664,980	· · · · · · · · · · · · · · · · · · ·	
29		1701641	36,665	1,701,645		
30		1768169	66,529	1,768,174		
31		1818391	50,222	1,818,396		
	Ĺ	919,477	919,477	919,477		

26 27 28 29 30 31 24 25 23 22 21 10 11 12 13 14 15 16 17 18 19 20 Days თ ω 0 200000 ₁ 20000 80000 - 00009 40000 160000 140000 120000 100000 180000 Daily Total Discharge (Gallons)

Pfohl Bros. August 2009

PFOHL BROTHERS LANDFILL SITE CHEEKTOWAGA, NEW YORK

Auto Dialer System Log

			*
DATE	PUMP Inhibit -08 (Off)	TIME Enable -07 (On)	COMMENTS
8/4/09	11:31 pm	1157 cd	RAIN
8/9/09	2:00 prg	1422 ON	RMIN
8/23/09 8/23/09 8/20/09	4:21 pm	11:49PM	RMINI
8/29/09	0907	1207 6N	
		4	

THE TOWN OF CHEEKTOWAGA



Main Pump Station 171 Central Boulevard Cheektowaga, NY 14225 Phone: 716-896-1777 Fax: 716-896-6437

October 6, 2009

Mr. William R. Pugh, P.E. Town Engineer Town of Cheektowaga

Re: Pfohl Bros. Flow Data

Dear Mr. Pugh,

Enclosed for your review, please find a copy of the **September 2009** Direct Discharge Flow Data Report, prepared by Jon W. Nichy.

A monthly log sheet indicating inhibiting and enabling of pumping operation at

the site is included with this package.

Should you have any other questions or comments regarding this submittal, please contact this office @ 896-1777.

Yours truly,

Town of Cheektowaga

Jon W. Nichy

Superintendent Main Pump Station

RECEIVED

OCT = 6 700g

ENGINEERING DEPT Direct Discharge Flow Data

8/31/2009		1818391	50,222	1,818,396	
September-09	Time; 11:58pm unless otherwise stated	Totalizer Reading (Gallons)	Daily Total Discharge (Gallons)		Notes
1	·	1828075	9,684	1,828,080	
2		1860286	32,211	1,860,291	
3		1860286	0	1,860,291	
4		1885331	25,045		
. 5	,	1901723	16,393	1,901,729	
6		1901723	0	1,901,729	
7		1941024	39,301	1,941,030	
8		1941024	0	1,941,030	
9		1942991	1,967	1,942,997	
10		1983467	40,476	1,983,473	
11		1983467	. 0	1,983,473	
12		. 1992416	8,949	1,992,422	
13		. 2112869	120,452	2,112,874	
14		2143360	30,492	2,143,366	
15		2158914	15,554	2,158,920	
16		2183263	24,349	2,183,269	•
17		2200724	17,461	2,200,730	
. 18		2207659	6,935	2,207,665	
19		2207659	0	2,207,665	
20		2240330	32,671	2,240,336	
21		2248842	. 8,512	2,248,848	
22		2248915	73	2,248,921	
23		2278328	29,414	2,278,335	
24		2291773	13,445	2,291,780	
25		2291947	174	2,291,954	
26		2324886	32,939	2,324,893	
27		2423090	98,204	2,423,097	
28		2461107	38,017	2,461,114	
29		2516973	55,866	2,516,980	
30		2666369	149,397	2,666,377	
31					
		847,978	847,981	847,981	


29 30 31 28 15 16 17 18 19 20 21 22 23 24 25 26 27 Days Pfohl Bros. September 2009 10 11 12 13 14 Daily Total Discharge (Gallons) 160000 140000 40000 20000 120000 -

PFOHL BROTHERS LANDFILL SITE CHEEKTOWAGA, NEW YORK

Auto Dialer System Log

			· k
DATE	PUMP Inhibit -08 (Off)	TIME Enable -07 (On)	COMMENTS
9/21	6:21 PM	12:04 pm	14/n/ C(C747)
9/28	950 AM	242pm	RAIN
		,	

THE TOWN OF CHEEKTOWAGA



Main Pump Station 171 Central Boulevard Cheektowaga, NY 14225 Phone: 716-896-1777 Fax: 716-896-6437

November 4, 2009

Mr. William R. Pugh, P.E. Town Engineer Town of Cheektowaga

Re: Pfohl Bros. Flow Data

Dear Mr. Pugh,

Enclosed for your review, please find a copy of the October 2009 Direct Discharge Flow Data Report, prepared by Jon W. Nichy.

A monthly log sheet indicating inhibiting and enabling of pumping operation at

the site is included with this package.

Should you have any other questions or comments regarding this submittal, please contact this office @ 896-1777.

Yours truly,

Town of Cheektowaga

Jon W. Nichy

Superintendent

Main Pump Station


PFOHL BROTHERS LANDFILL SITE CHEEKTOWAGA, NEW YORK

Auto Dialer System Log


DATE	PUMP Inhibit -08 (Off)	TIME Enable -07 (On)	COMMENTS
10/2/09	254pm		
10/3/09	7	100400	
10/6/09		12:28AM	CLEAN
10/11/10			
10/6/09	11:17 Pm		RAIN
10/08/09			
70,00,707		1120pm	CLEAN
10/23/09	. 7:20 pm		
10/25/09	7.20 pg	7:00	RHIN
7-720/01		3:08 Am	CLEAN
1/9/09	1022pm		
Tolilag	- Coppin	3:37pm	
11101		20 Am	
10/31/09	0519am		
16/3/109		158 sm	
. /		7	
	·		
1,			
		<u> </u>	

Direct Discharge Flow Data

9/30/2009		2666369	149,397	2,666,377	
October-09	Time; 11:58pm unless otherwise stated	Totalizer Reading (Gallons)	Daily Total Discharge (Gallons)		Notes
1		2728073	61,704	2,728,081	
2		2728073	0	2,728,081	
3		2751751	23,678	2,751,759	
4		2768840	17,089	2,768,848	
. 5		2768840	. 0	2,768,848	
. 6 .	·	2947071	178,230	2,947,078	
7		2947071	0	2,947,078	
8		2950773	3,703	2,950,781	
9		3127483	176,710	3,127,491	
10		3127483	0	3,127,491	
11		3190014	62,531	3,190,022	
12		3352880	162,866	3,352,888	
13		3371977	19,097	3,371,985	
14		3392110	20,134	3,392,119	***
15		3401041	8,931	3,401,050	
16		3437135	36,095	3,437,145	
17		3437135	0	3,437,145	
18		3479529	42,394	3,479,539	
19		3499170	19,641	3,499,180	
20		3504083	4,913	3,504,093	
21	,	3534009	29,926	3,534,019	
. 22		3621791	87,782	3,621,801	
23		3673313	51,522	3,673,323	
24		3673313	0	3,673,323	
25		3726102	52,789	3,726,112	
26		3825574	99,472	3,825,584	
27		3873401	47,828	3,873,412	
28		3888088	14,687	3,888,099	
29		3930927	42,839	3,930,938	
30		4037247	106,320	4,037,258	
31		4109567 1,443,198	72,320	4,109,578	



THE TOWN OF CHEEKTOWAGA



Main Pump Station 171 Central Boulevard Cheektowaga, NY 14225

Phone: 716-896-1777 Fax: 716-896-6437

December 3, 2009

Mr. William R. Pugh, P.E. Town Engineer Town of Cheektowaga

Re: Pfohl Bros. Flow Data

Dear Mr. Pugh,

Enclosed for your review, please find a copy of the **November 2009** Direct Discharge Flow Data Report, prepared by Jon W. Nichy.

A monthly log sheet indicating inhibiting and enabling of pumping operation at

the site is included with this package.

Should you have any other questions or comments regarding this submittal, please contact this office @ 896-1777.

Yours trally,

Town of Cheektowaga

Jon W. Nichy

Superintendent

Main Pump Station

Direct Discharge Flow Data

10/31/2009		4109567	72,320	4,109,578	
November-09	Time; 11:58pm unless otherwise stated	Totalizer Reading (Gallons)	Daily Total Discharge (Gallons)		Notes
:		4180876	71,309	4,180,887	
2		4187972	7,097	4,187,984	
3		4220767	32,795	4,220,779	
4		4236098	15,332	4,236,111	
5		4283102	47,004	4,283,115	
6		4368893	85,791	4,368,906	
7		4448470	79,577	4,448,483	
8	1	4448470	0	4,448,483	
9		4478122	29,653	4,478,136	
10		4493027	14,905	4,493,041	
11		4511345	18,318	4,511,359	
12		4511946	601	4,511,960	
13		4553822	41,876	4,553,836	
14		4558371	4,550	4,558,386	
15		4662757	104,386	4,662,772	
16		4709273	46,516	4,709,288	
17		4720965	11,692	4,720,980	
18		4720965	0	4,720,980	
19		4736071	15,106	4,736,086	
20		4811205	75,134	4,811,220	
21		4942054	130,849	4,942,069	
22		4999163	57,109	4,999,178	
23		5033105	33,942	5,033,120	
24		5048078	14,974	5,048,094	
25		5054292	6,214	5,054,308	
26		5151250	96,958	5,151,266	
27		5209846	58,596	5,209,862	
28		5291643	81,797	5,291,659	
29		5375302	83,659	5,375,318	
30		5375302	0	5,375,318	
31					
		1,265,735	1,265,740	1,265,740	


28 29 19 20 15 16 17 18 Pfohl Bros. November 2009 13 14 10 11 12 O

PFOHL BROTHERS LANDFILL SITE CHEEKTOWAGA, NEW YORK

Auto Dialer System Log

DATE	PUMP Inhibit -08 (Off)	TIME Enable -07 (On)	COMMENTS
	İ	,	,
74-129/19			
11/11/1	7,00 PM		RAIN
11/2			
1114109	0949	1106	
7 / / / /		7700	,
		·	
16/10/1	- 101-		
//////////	0815		
11/20/06		BC124	
1110101		(1-10)	
	٠.,		
, ,			
11/26/10	1277		7
11/4/109	1337		
11/2/109		08.59	
11/27/20	Mul		
11/11/01	-/9/4		
1128109		1720	the second secon
1/00/00	A states	<u>-</u>	
11119109	2149	İ	
7 7 11	7		
<u>-</u>	<u>.</u>		
			*
•			
			· · · · · ·
			v
			*.

THE TOWN OF CHEEKTOWAGA



Main Pump Station 171 Central Boulevard Cheektowaga, NY 14225 Phone: 716-896-1777 Fax: 716-896-6437

January 2, 2010

Mr. William R. Pugh, P.E. Town Engineer Town of Cheektowaga

Re: Pfohl Bros. Flow Data

Dear Mr. Pugh,

Enclosed for your review, please find a copy of the **December 2009** Direct Discharge Flow Data Report, prepared by Jon W. Nichy.

A monthly log sheet indicating inhibiting and enabling of pumping operation at

the site is included with this package.

Should you have any other questions or comments regarding this submittal, please contact this office @ 896-1777.

Yours truly,

Town of Cheektowaga

Jon W. Nichy

Superintendent

Main Pump Station

RECEIVED

JAN 0 4 2010

ENGINEERING DEPT Direct Discharge Flow Data

11/30/2009		5375302	0	5,820,342	
December-09	Time; 11:58pm unless otherwise stated	Totalizer Reading (Gallons)	Daily Total Discharge (Gallons)		Notes
.1		5375302	0	5,820,342	
2		5409145	33,844	5,854,186	
3		5464131	54,986	5,909,172	
4	,	5624062	159,931	6,069,103	
5		5784969	160,907	6,230,010	
6		5878986	94,018	6,324,028	
7		5926620	47,634	6,371,662	
8		5935314	8,694	6,380,356	
9		5937258	1,944	6,382,300	· · · · · · · · · · · · · · · · · · ·
10		5937258	0	6,382,300	
11		6017005	79,747	6,462,047	
12		6188140	171,135	6,633,182	
13		6276427	88,287	6,721,469	
14		6276427	. 0	6,721,469	
15		6305602	29,176	6,750,645	
16		6473006	167,404	6,918,049	
17		6609581	136,575	7,054,624	
18		6636899	27,318	7,081,942	
19	:	6675503	38,604	7,120,546	
20		6690257	14,754	7,135,300	
21		6707221	16,964	7,152,264	
22		6719566	12,346	7,164,610	
23	•	6737278	17,712	7,182,322	
24		6737278	0	7,182,322	
25		6737278	0	7,182,322	
26		6737278	0	7,182,322	
27		6814557	77,279	7,259,601	
28		6977669	163,112	7,422,713	
29		7073909	96,240	7,518,953	-
30		7086062	12,153	7,531,106	
31		7108085 1,732,783	22,023 1,7 32,78 7	7,553,129 1,732,78 7	

3 တ္ထ 29 28 27 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 Days Pfohl Bros. December 2009 10 Ŋ +0 180000 ₇ 40000 -20000 -100000 80000 140000 120000 -160000 00009 Daily Total Discharge (Gallons)

PFOHL BROTHERS LANDFILL SITE CHEEKTOWAGA, NEW YORK

Auto Dialer System Log

		····	
DATE	PUMP Inhibit -08 (Off)	TIME Enable -07 (On)	COMMENTS
12/2/09	6:45 BM		HEAVY RAIN
13/-/-			
143/09		2:11	
15/12/00			
12/13/09	1130 AM		RAIN
<u> </u>			
1.5/1.8	e.,		
12/15/09		6130 PM	
	•		
12/24/19	0800		
17-9/07	0800		farin-Melt
			Main-1 (et
12/21/09	080	> 0800	
14001	-010	. 1	
١,			**
• •			
		1,	

APPENDIX C HYDRAULIC MONITORING TABLES

Location ID / Type	Northing	Easting	Ground Elevation (ft)	Casing Elevation (ft)	Meas.point (Riser)Elev.(ft)	Geol. Zone	Specific Gravity	Date / Time	Depth to Water (ft)	Water Elev. (ft)	Product Thick. (ft)	Corrected Water Elev. (ft)	Remark
GW-03S	1073812.622	1114605.762	692.61	NM	693.80	S	1						
MNW								9/24/2009 0000	6.24	687.56	0.00	687.56	
MNW								11/10/2009 0000	2.57	691.23	0.00	691.23	
MNW								12/21/2009 0000	2.45	691.35	0.00	691.35	
GW-04S	1072284.456	1114685.127	690.76	NM	692.72	S	1						
MNW								9/24/2009 0000	6.21	686.51	0.00	686.51	
MNW								11/10/2009 0000	4.41	688.31	0.00	688.31	
MNW								12/21/2009 0000	4.46	688.26	0.00	688.26	
GW-07S	1071238.157	1117666.265	697.47	NM	699.51	S	1						
MNW								9/24/2009 0000	6.99	692.52	0.00	692.52	
MNW								11/10/2009 0000	4.73	694.78	0.00	694.78	
MNW								12/21/2009 0000	4.37	695.14	0.00	695.14	
GW-08SR	1073714.172	1116786.343	695.08	NM	697.50	S	1						
MNW								9/24/2009 0000	7.30	690.20	0.00	690.20	
MNW								11/10/2009 0000	5.40	692.10	0.00	692.10	
MNW								12/21/2009 0000	5.40	692.10	0.00	692.10	
GW-28S	1073129.479	1117648.927	698.60	NM	700.95	S	1						
MNW								9/24/2009 0000	10.73	690.22	0.00	690.22	
MNW								11/10/2009 0000	9.05	691.90	0.00	691.90	
MNW								12/21/2009 0000	8.77	692.18	0.00	692.18	
GW-29S	1072552.638	1117761.993	697.50	NM	699.63	S	1						_
MNW								9/24/2009 0000	10.14	689.49	0.00	689.49	
MNW								11/10/2009 0000	7.90	691.73	0.00	691.73	
MNW								12/21/2009 0000	7.91	691.72	0.00	691.72	

NM - No Measurement

The value noted in the column labeled Specific Gravity is an assumed value for free product, if found.

Type:

MH Manhole Monitoring Point MNW Monitoring Well

SG Staff Gauge

Location ID / Type	Northing	Easting	Ground Elevation (ft)	Casing Elevation (ft)	Meas.point (Riser)Elev.(ft)	Geol. Zone	Specific Gravity	Date / Time	Depth to Water (ft)	Water Elev. (ft)	Product Thick. (ft)	Corrected Water Elev. (ft)	Remark
GW-30S	1072096.109	1117743.563	693.67	NM	696.58	S	1						
MNW								9/24/2009 0000	8.38	688.20	0.00	688.20	
MNW								11/10/2009 0000	8.10	688.48	0.00	688.48	
MNW								12/21/2009 0000	8.02	688.56	0.00	688.56	
GW-31S	1071786.280	1117191.441	695.84	NM	698.62	S	1						
MNW								9/24/2009 0000	8.65	689.97	0.00	689.97	
MNW								11/10/2009 0000	2.73	695.89	0.00	695.89	
MNW								12/21/2009 0000	NM	-	NM	-	Well Frozen
GW-32S	1071613.793	1116364.200	696.19	NM	698.37	S	1						
MNW								9/24/2009 0000	6.03	692.34	0.00	692.34	
MNW								11/10/2009 0000	3.16	695.21	0.00	695.21	
MNW								12/21/2009 0000	2.98	695.39	0.00	695.39	
GW-33S	1072165.625	1115561.866	695.94	NM	698.24	S	1						
MNW								9/24/2009 0000	7.52	690.72	0.00	690.72	
MNW								11/10/2009 0000	4.40	693.84	0.00	693.84	
MNW								12/21/2009 0000	4.95	693.29	0.00	693.29	
GW-34S	1072979.205	1114730.200	692.51	NM	694.77	S	1						
MNW								9/24/2009 0000	5.88	688.89	0.00	688.89	
MNW								11/10/2009 0000	2.75	692.02	0.00	692.02	
MNW								12/21/2009 0000	2.89	691.88	0.00	691.88	
GW-35S	1071701.925	1115985.585	696.19	NM	697.39	S	1						
MNW								9/24/2009 0000	6.05	691.34	0.00	691.34	
MNW								11/10/2009 0000	3.22	694.17	0.00	694.17	
MNW								12/21/2009 0000	2.96	694.43	0.00	694.43	

NM - No Measurement

The value noted in the column labeled Specific Gravity is an assumed value for free product, if found.

Type:

MH Manhole Monitoring Point MNW Monitoring Well

SG Staff Gauge

Location ID / Type	Northing	Easting	Ground Elevation (ft)	Casing Elevation (ft)	Meas.point (Riser)Elev.(ft)	Geol. Zone	Specific Gravity	Date / Time	Depth to Water (ft)	Water Elev. (ft)	Product Thick. (ft)	Corrected Water Elev. (ft)	Remark
MH-01	1073806.665	1114810.501	698.62	NM	698.62	NA	1						
MH								9/24/2009 0000	9.87	688.75	0.00	688.75	
MH								11/10/2009 0000	10.25	688.37	0.00	688.37	
MH								12/21/2009 0000	10.43	688.19	0.00	688.19	
MH-03	1073736.789	1115259.334	699.40	NM	699.40	NA	1						
МН								9/24/2009 0000	10.73	688.67	0.00	688.67	
MH								11/10/2009 0000	11.12	688.28	0.00	688.28	
MH								12/21/2009 0000	11.23	688.17	0.00	688.17	
MH-07	1073838.229	1116243.757	696.82	NM	696.82	NA	1						
MH								9/24/2009 0000	8.96	687.86	0.00	687.86	
MH								11/10/2009 0000	9.32	687.50	0.00	687.50	
MH								12/21/2009 0000	9.42	687.40	0.00	687.40	
MH-10	1073540.729	1117381.524	703.01	NM	703.01	NA	1						
MH								9/24/2009 0000	14.48	688.53	0.00	688.53	
MH								11/10/2009 0000	14.49	688.52	0.00	688.52	
MH								12/21/2009 0000	14.52	688.49	0.00	688.49	
MH-15	1072531.567	1117761.125	699.02	NM	699.02	NA	1						
MH								9/24/2009 0000	14.89	684.13	0.00	684.13	
MH								11/10/2009 0000	14.82	684.20	0.00	684.20	
MH								12/21/2009 0000	14.92	684.10	0.00	684.10	
MH-16	1072133.714	1117748.238	698.57	NM	698.57	NA	1						
МН								9/24/2009 0000	14.49	684.08	0.00	684.08	
MH								11/10/2009 0000	14.51	684.06	0.00	684.06	
MH								12/21/2009 0000	14.52	684.05	0.00	684.05	

NM - No Measurement

The value noted in the column labeled Specific Gravity is an assumed value for free product, if found.

Type:

MH Manhole Monitoring Point MNW Monitoring Well

SG Staff Gauge

Location ID Type	/ Northing	Easting	Ground Elevation (ft)	Casing Elevation (ft)	Meas.point (Riser)Elev.(ft)	Geol. Zone	Specific Gravity	Date / Time	Depth to Water (ft)	Water Elev. (ft)	Product Thick. (ft)	Corrected Water Elev. (ft)	Remark
MH-17	1071813.137	1117180.019	702.16	NM	702.16	NA	1						
M	н							9/24/2009 0000	18.11	684.05	0.00	684.05	
M	Н							11/10/2009 0000	18.12	684.04	0.00	684.04	
M	Н							12/21/2009 0000	18.15	684.01	0.00	684.01	
MH-20	1071756.395	1115997.024	706.20	NM	706.20	NA	1						
M	н							9/24/2009 0000	19.75	686.45	0.00	686.45	
M	Н							11/10/2009 0000	19.74	686.46	0.00	686.46	
M	Н							12/21/2009 0000	19.77	686.43	0.00	686.43	
MH-22	1072158.023	1115589.309	698.05	NM	698.05	NA	1						
M	н							9/24/2009 0000	9.00	689.05	0.00	689.05	
M	Н							11/10/2009 0000	8.97	689.08	0.00	689.08	
M	Н							12/21/2009 0000	8.99	689.06	0.00	689.06	
MH-25	1072483.928	1114820.313	698.17	NM	698.17	NA	1						
M	н							9/24/2009 0000	9.45	688.72	0.00	688.72	
M	Н							11/10/2009 0000	9.84	688.33	0.00	688.33	
M	Н							12/21/2009 0000	10.04	688.13	0.00	688.13	
SG-01	1073882.887	1114813.101	NM	NM	690.00	NA	1						
S	G							9/24/2009 0000	NM	-	NM	-	Dry
S	G							11/10/2009 0000	-1.10	691.10	0.00	691.10	
S	G							12/21/2009 0000	-1.18	691.18	0.00	691.18	
SG-02	1073738.27	1116805.85	NM	NM	690.00	NA	1	_					
S	G							9/24/2009 0000	NM	-	NM	-	Dry
S	G							11/10/2009 0000	-3.16	693.16	0.00	693.16	
S	G							12/21/2009 0000	-3.10	693.10	0.00	693.10	

NM - No Measurement

The value noted in the column labeled Specific Gravity is an assumed value for free product, if found.

Type:

MH Manhole Monitoring Point MNW Monitoring Well

MNW Monitoring Well SG Staff Gauge

Location ID Type	Northing	Easting	Ground Elevation (ft)	Casing Elevation (ft)	Meas.point (Riser)Elev.(ft)	Geol. Zone	Specific Gravity	Date / Time	Depth to Water (ft)	Water Elev. (ft)	Product Thick. (ft)	Corrected Water Elev. (ft)	Remark
WW-01	1073676.903	1115710.476	NM	NM	684.02	NA	1						
MI	4							9/24/2009 0000	-4.5	688.52	0.00	688.52	
MI	1							11/10/2009 0000	-4.1	688.12	0.00	688.12	
MI	1							12/21/2009 0000	-4.0	688.02	0.00	688.02	
WW-02	1073684.724	1116792.311	NM	NM	684.18	NA	1						
М	4							9/24/2009 0000	-4.6	688.78	0.00	688.78	
MI	4							11/10/2009 0000	-4.7	688.88	0.00	688.88	
MI	1							12/21/2009 0000	-4.6	688.78	0.00	688.78	
WW-03	1073140.339	1117618.499	NM	NM	683.80	NA	1						
М	4							9/24/2009 0000	-5.4	689.20	0.00	689.20	
MI	1							11/10/2009 0000	-5.5	689.30	0.00	689.30	
MI	4							12/21/2009 0000	-5.6	689.40	0.00	689.40	
WW-04	1072057.563	1117610.508	NM	NM	676.62	NA	1						
М	4							9/24/2009 0000	-7.0	683.62	0.00	683.62	
MI	1							11/10/2009 0000	-7.0	683.62	0.00	683.62	
MI	+							12/21/2009 0000	-6.9	683.52	0.00	683.52	
WW-05	1071661.368	1116370.876	NM	NM	676.14	NA	1						
М	4							9/24/2009 0000	-6.7	682.84	0.00	682.84	
MI	1							11/10/2009 0000	-7.1	683.24	0.00	683.24	
MI	+							12/21/2009 0000	-5.6	681.74	0.00	681.74	
WW-06	1072988.420	1114811.518	NM	NM	681.89	NA	1						
М	4							9/24/2009 0000	-7.3	689.19	0.00	689.19	
MI	1							11/10/2009 0000	-6.9	688.79	0.00	688.79	
MI	+							12/21/2009 0000	-6.8	688.69	0.00	688.69	

NM - No Measurement

The value noted in the column labeled Specific Gravity is an assumed value for free product, if found.

Type:

MH Manhole Monitoring Point

MNW Monitoring Well SG Staff Gauge

APPENDIX D

GROUNDWATER PURGE AND SAMPLE COLLECTION LOGS

Project:	11175616.00000			Site: _	Pfohl	Brothers	_ Well I.D.: _	GW-1S
Date:	11/12/2009	Sampling	Personnel:	Rob Mu	urphy, Tim I	fkovich	_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		_Tubing Type:_	LDPE,	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	3.97'	Depth to Well Bottom:	14.94'	Well Diameter:	2"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	6.8	_	Estimated Purge Volume (liters):	6.9
Sample ID:		GW-1S		Sample Time:	1	1:48	_ QA/QC: _	None
		VOCs, SVOCs, Riser pipe is bu			e stainless	steel bailer fro	m within well, saı	mpled around it.

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
10:58	Start pumping	g, bypassed flo	w through cell d	ue to abundan	t orange parti	culates	180	3.97
11:03							150	4.30
11:08	*	*	+	+	+	+	150	4.45
11:13	7.38	12.03	1.070	4.98	190	-116.0	150	4.55
11:18	6.95	11.97	1.070	4.10	65	-109.3	150	4.60
11:23	6.71	11.88	1.099	3.95	55	-99.7	150	4.61
11:33	6.49	11.90	1.110	3.91	45	-92.9	150	4.61
11:38	6.45	11.93	1.115	3.87	45	-87.9	150	4.61
11:43	6.52	11.85	1.119	3.80	34	-83.8	150	4.61
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Project:		11175616.00000)	Site:	Pfohl	Brothers	_ Well I.D.: _	GW-1D
Date:	11/12/2009	Sampling	Personnel:	Rob Mu	urphy, Tim If	fkovich	_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		Tubing Type:_	LDPE/	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	2.83'	Depth to Well Bottom:	39.65'	Well Diameter:	4"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	90.9	_	Estimated Purge Volume (liters):	45.0
Sample ID:		GW-1D		Sample Time:	13	3:00	QA/QC:	None
	e Parameters: er Information:	VOCs, SVOCs, Sulfur odor	and TAL Meta	als				

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
12:10	7.25	11.09	1.063	4.79	20	-204.6	900	2.83
12:20	7.17	10.95	1.068	2.26	8.9	-250.8	900	2.88
12:30	7.06	11.07	1.065	2.35	5.1	-263.9	900	2.89
12:35	7.02	11.09	1.064	2.24	4.2	-270.8	900	2.89
12:40	6.92	11.15	1.061	2.30	4.5	-282.7	900	2.89
12:45	6.84	11.17	1.073	2.28	5.4	-289.0	900	2.89
12:50	6.82	11.15	1.070	2.29	4.2	-292.0	900	2.89
12:55	6.18	11.13	1.067	2.29	2.7	-295.7	900	2.89
13:00	6.80	11.21	1.069	2.21	2.3	-297.2	900	2.89
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Project:	11175616.00000			Site:	Pfohl	Brothers	Well I.D.:	GW-3S
Date:	11/11/2009	Sampling	Personnel:	Rob Mu	urphy, Tim It	fkovich	_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		_Tubing Type:	LDPE/	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	2.39'	Depth to Well Bottom:	13.25'	Well Diameter:	2"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	6.7	_	Estimated Purge Volume (liters):	6.0
Sample ID:		GW-3S		Sample Time:	8	:23	QA/QC:	None
	e Parameters: er Information:	VOCs, SVOCs,	and TAL Meta	als				

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
7:43	7.69	8.93	1.157	7.66	120	12.8	220	2.39
7:48	7.62	9.54	1.148	5.63	55	24.9	140	4.61
7:53	7.58	9.64	1.145	6.02	40	32.2	140	4.85
7:58	7.55	9.68	1.144	6.03	38	33.1	140	5.04
8:03	7.52	9.85	1.142	6.33	26	34.8	140	5.36
8:08	7.51	9.95	1.142	6.16	26	39.3	140	5.64
8:13	7.50	10.10	1.141	5.91	24	36.7	140	5.84
8:18	7.47	10.23	1.143	5.65	24	28.3	140	6.11
8:23	7.46	10.30	1.143	5.56	23	28.9	140	6.30
Tolerance:	0.1		3%	10%	10%	+ or - 10		

	11175616.00000		Site:	Pfohl I	Brothers	_ Well I.D.: _	GW-3D
11/11/2009	Sampling I	Personnel:	Rob Mu	urphy, Tim If	kovich	_ Company:_	URS Corporation
	Geopump 2		_Tubing Type:	LDPE/	Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Below Top of Riser	Initial Depth to Water:	2.02'	Depth to Well Bottom:	35.65'	Well Diameter:	4"	Screen Length:
Stainles	ss Steel		Volume in 1 Well Casing (liters):	83.1	-	Estimated Purge Volume (liters):	53.4
	GW-3D		Sample Time:	9	:45	QA/QC:	MS/MSD
e Parameters: er Information:	VOCs, SVOCs, a	nd TAL Meta	als				
	Below Top of Riser Stainles	Geopump 2 Below Top of Initial Depth Riser to Water: Stainless Steel GW-3D e Parameters: VOCs, SVOCs, a	Geopump 2 Below Top of Initial Depth Riser to Water: 2.02' Stainless Steel GW-3D e Parameters: VOCs, SVOCs, and TAL Meta	Geopump 2 Below Top of Initial Depth Riser to Water: 2.02' Stainless Steel GW-3D Sample Tubing Type: Volume in 1 Well Casing (liters): Sample Time:	Geopump 2 Tubing Type: LDPE/ Below Top of Initial Depth Depth to Water: 2.02' Well Bottom: 35.65' Volume in 1 Well Casing (liters): 83.1 GW-3D Sample Time: 9 e Parameters: VOCs, SVOCs, and TAL Metals	Sampling Personnel: Rob Murphy, Tim Ifkovich	Sampling Personnel: Rob Murphy, Tim Ifkovich Company:

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
8:45	7.44	11.36	1.408	5.30	3	-44.8	890	2.02
8:50	7.44	11.41	1.397	4.40	0	-51.9	890	2.04
9:00	7.37	11.44	1.398	4.24	0	-60.3	890	2.04
9:10	7.35	11.46	1.391	4.18	0	-64.4	890	2.04
9:20	7.34	11.48	1.391	4.30	0	-67.3	890	2.04
9:30	7.32	11.47	1.391	4.17	0	-69.3	890	2.04
9:35	7.32	11.49	1.390	4.17	0	-69.8	890	2.04
9:40	7.31	11.51	1.390	4.06	0	-70.8	890	2.04
9:45	7.30	11.50	1.390	4.01	0	-71.6	890	2.04
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Project:		11175616.00000)	Site: _	Pfohl	Brothers	_ Well I.D.: _	GW-4S
Date:	11/12/2009	Sampling	Personnel:	Rob Murphy, Tim Ifkovich			_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		_Tubing Type:	LDPE/	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	4.43'	Depth to Well Bottom:	16.23'	Well Diameter:	2"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	7.3	_	Estimated Purge Volume (liters):	26.1
Sample ID:		GW-4S		Sample Time:	1(0:25	QA/QC:	None
Sampl		VOCs, SVOCs,			es (<75ml/r	nin). Pumped	dry and sampled	d after recovery.

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
7:46	8.82	10.83	0.460	5.45	60	-147.8	900	4.43
7:51	9.41	10.86	0.431	2.59	21	-95.4	900	10.11
7:56	9.46	10.76	0.436	2.42	4	-97.5	900	13.02
8:01	8.91	11.14	0.474	1.64	20	-144.2	900	14.85
8:06	8.50	11.20	0.490	1.03	0	-124.0	900	15.45
8:11	8.36	11.21	0.473	0.88	2	-137.8	900	16.04
8:15	8.32	11.06	0.462	2.59	2	-156.7	900	DRY
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Project:		11175616.0000)	Site:	Pfohl	Brothers	_ Well I.D.: _	GW-4D
Date:	11/12/2009	Sampling	Personnel:	Rob Mu	urphy, Tim II	fkovich	_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		_Tubing Type:_	LDPE/	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	13.01'	Depth to Well Bottom:	45.57'	Well Diameter:	4"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	80.4	_	Estimated Purge Volume (liters):	13.7
Sample ID:		GW-4D		Sample Time:	1():01	QA/QC:	None
	er Information:	VOCs, SVOCs,		pump kept shut	ting off at lo	wer rate.		

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
8:22	7.91	9.43	1.241	4.70	330	-114.1	310	13.01
8:27	Cleaned out f	low-through ce	ell .				120	
8:31	7.87	8.74	1.273	5.22	31	-135.2	120	13.61
8:41	7.82	8.81	1.270	2.76	14	-157.4	120	13.76
8:51	7.78	8.62	1.293	2.23	11	-209.4	120	13.89
9:01	7.79	7.94	1.304	2.33	11	-245.7	105	13.87
9:11	7.70	8.42	1.329	2.41	11	-276.0	140	13.94
9:21	7.67	9.34	1.327	2.51	10	-290.6	140	14.07
9:26	7.63	9.36	1.340	2.55	10	-303.4	140	14.11
9:31	7.58	9.22	1.352	2.64	10	-310.8	140	14.17
9:36	7.60	9.28	1.362	2.60	10	-313.2	140	14.08
9:41	7.52	9.50	1.377	2.83	10	-307.2	140	14.17
9:46	7.45	9.71	1.385	2.93	10	-313.5	140	14.25
9:51	7.34	9.94	1.376	2.88	10	-316.3	140	14.33
9:56	7.32	9.91	1.385	2.91	10	-315.1	140	14.40
10:01	7.31	9.99	1.387	2.92	10	-314.7	140	14.44
Tolerance:	0.1		3%	10%	10%	+ or - 10		

WELL PURGING LOG

URS Corporation

SITE NAME:	Pfohl Brothers Landfill		WELL NO.:	G	W-7S
PROJECT NO.:	11175616.00000				
STAFF:	Rob Murphy, Tim Ifkovich				
DATE(S):	11/10/09, 11/11/09				
				WELL ID.	VOL. (GAL/FT)
1. TOTAL CASING	G AND SCREEN LENGTH (FT.)	=	35.08	1"	0.040
2. WATER LEVEL	BELOW TOP OF CASING (FT.)	=	4.73	2"	0.17
3. NUMBER OF F	EET STANDING WATER (#1 - #2)	=	30.35	3"	0.38
4. VOLUME OF W	VATER/FOOT OF CASING (GAL.)	=	0.17	4"	0.66
5. VOLUME OF W	VATER IN CASING (GAL.)(#3 x #4)	=	5.2	5"	1.04
6. VOLUME OF W	VATER TO REMOVE (GAL.)(#5 x 3)	=		6"	1.50
7. VOLUME OF W	VATER ACTUALLY REMOVED (GAL.)	=	7.5	8"	2.60
			V=(0.0408 x (CASING	DIAMETER [INCHES]) ²

				ACCU	/ULATED	VOLUME F	PURGED (GALLONS)		
PARAMETERS	Initial	2	4	6	7					
рН	7.98	8.02	8.02	8.06	8.03					
SPEC. COND. (mS/cm)	0.576	0.576	0.576	0.574	0.570					
DO (mg/l)	8.42	9.32	10.90	10.83	9.22					
TEMPERATURE (°C)	11.73	11.79	11.17	11.10	11.04					
TURBIDITY (NTU)	58	~50	~50	~70	~180					
ORP (millivolts)	93.1	123.3	126.2	144.4	165.2					
TIME										

COMMENTS: - Begin handbailing well. Batteries died in turbidity meter.

10:45 - Well dry after removing 7.5 gallons

11/11/2009 14:07 - return to well, depth to water = 4.97 feet.

14:15 - Collect sample.

WELL PURGING LOG

URS Corporation

SITE NAME:	Pfohl Brothers Landfill		WELL NO.:	G	W-7D
PROJECT NO.:	11175616.00000				
STAFF:	Rob Murphy, Tim Ifkovich				
DATE(S):	11/10/09, 11/11/09				
				WELL ID.	VOL. (GAL/FT)
1. TOTAL CASING	G AND SCREEN LENGTH (FT.)	=	60.28	1"	0.040
2. WATER LEVEL	BELOW TOP OF CASING (FT.)	=	42.79	2"	0.17
3. NUMBER OF F	EET STANDING WATER (#1 - #2)	=	17.49	3"	0.38
4. VOLUME OF W	VATER/FOOT OF CASING (GAL.)	=	0.66	4"	0.66
5. VOLUME OF W	VATER IN CASING (GAL.)(#3 x #4)	=	11.5	5"	1.04
6. VOLUME OF W	VATER TO REMOVE (GAL.)(#5 x 3)	=		6"	1.50
7. VOLUME OF W	VATER ACTUALLY REMOVED (GAL.)	=	12.0	8"	2.60
			V=0	.0408 x (CASING	DIAMETER [INCHES]) ²

				ACCU	MULATED	VOLUME F	PURGED (GALLONS)		
PARAMETERS	Initial	3	6	9	12					
рН	8.01	7.91	8.00	8.12	8.22					
SPEC. COND. (mS/cm)	0.678	0.690	0.713	0.740	0.752					
DO (mg/)	8.28	10.35	8.71	7.56	8.09					
TEMPERATURE (°C)	11.09	11.09	11.14	11.16	11.22					
TURBIDITY (NTU)	<10	<10	~20	~40	~50					
ORP (millivolts)	-67.1	-80.3	-79.2	-83.2	-63.5					
TIME										

COMMENTS:

11:33 - Handbailed the well to dryness.

11/11/2009

14:18 - return to well, depth to water = 59.05 feet.

14:25 - Collect sample, only enough volume to fill 3 voa vials, 1 metals container and 1-1 liter Amber container.

Project:		11175616.00000)	Site:	Pfohl I	Brothers	_ Well I.D.: _	GW-8SR	
Date:	11/11/2010	Sampling	Personnel:	Rob Murphy, Tim Ifkovich		_ Company:_	URS Corporation		
Purging/ Sampling Device:		Geopump 2		Tubing Type:_	LDPE/	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint	
Measuring Point:	Below Top of Riser	Initial Depth to Water:	5.42'	Depth to Well Bottom:	13.03'	Well Diameter:	2"	Screen Length:	
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	4.7	-	Estimated Purge Volume (liters):	8.8	
Sample ID:		GW-8SR		Sample Time:	11	1:16	QA/QC:	None	
	e Parameters: er Information:	VOCs, SVOCs,	and TAL Meta	als					_
									_

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
10:26	7.18	10.84	2.229	7.85	230	-48.1	220	5.42
10:31	6.97	10.99	2.333	6.14	225	-57.2	170	6.76
10:36	6.87	11.07	2.335	6.60	220	-59.4	170	7.03
10:41	6.80	11.30	2.339	7.00	150	-55.3	170	7.17
10:46	6.66	11.51	2.346	7.26	105	-49.4	170	7.25
10:51	6.59	11.43	2.370	7.41	70	-46.3	170	7.30
10:56	6.55	11.52	2.379	7.40	55	-41.7	170	7.32
11:01	6.47	11.67	2.384	7.45	45	-39.1	170	7.36
11:06	6.39	11.67	2.393	7.55	35	-38.3	170	7.37
11:11	6.32	11.68	2.399	7.60	30	-37.6	170	7.39
11:16	6.30	11.81	2.405	7.64	30	-38.4	170	7.41
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Project:		11175616.00000)	Site:	Pfohl	Brothers	_ Well I.D.:	GW-8D
Date:	11/11/2009	Sampling	Personnel:	Rob Murphy, Tim Ifkovich		_ Company:	URS Corporation	
Purging/ Sampling Device:		Geopump 2		_Tubing Type:_	LDPE.	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	5.98'	Depth to Well Bottom:	36.58'	Well Diameter:	4"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	75.6	_	Estimated Purge Volume (liters):	50.6
Sample ID:		GW-8D		Sample Time:	1:	2:32	QA/QC:	Duplicate (ID=Duplicate)
	e Parameters: er Information:	VOCs, SVOCs,	and TAL Meta	als				

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
11:37	6.39	11.31	2.004	7.21	230	-31.8	920	5.98
11:47	6.16	11.26	2.072	6.03	4	-38.7	920	5.98
11:57	6.06	11.30	1.977	5.80	2	-40.4	920	5.98
12:07	6.02	11.41	1.701	4.96	0	-25.5	920	5.98
12:12	6.07	11.34	1.694	4.86	0	-23.8	920	5.98
12:17	6.25	11.36	1.688	4.61	0	-24.1	920	5.98
12:22	6.32	11.41	1.687	4.62	0	-24.1	920	5.98
12:27	6.33	11.43	1.685	4.57	0	-23.9	920	5.98
12:32	6.41	11.51	1.679	4.52	0	-24.3	920	5.98
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Project:		11175616.00000)	Site: _	Pfohl	Brothers	_ Well I.D.: _	GW-26D
Date:	11/12/2009	Sampling	Personnel:	Rob Mu	urphy, Tim I	fkovich	_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		Tubing Type:_	LDPE	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	6.85'	Depth to Well Bottom:	40.75'	Well Diameter:	4"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	83.7	-	Estimated Purge Volume (liters):	47.9
Sample ID:		GW-26D		Sample Time:	14	4:34	QA/QC:	None
	e Parameters: er Information:	VOCs, SVOCs, Occasional puls		als ned particulates	in purge wa	ater.		

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
13:39	7.30	11.96	1.636	8.80	40	-83.3	870	6.85
13:44	6.70	11.59	1.707	4.02	1	-91.2	870	6.87
13:54	6.28	11.54	1.708	4.22	0	-86.9	870	6.85
14:04	6.09	11.57	1.709	4.22	0	-82.2	870	6.86
14:09	6.06	11.55	1.711	4.09	0	-81.0	870	6.86
14:14	6.00	11.53	1.710	4.12	0	-78.8	870	6.86
14:19	6.03	11.54	1.712	4.25	0	-78.5	870	6.86
14:24	6.11	11.50	1.705	4.30	0	-79.4	870	6.86
14:29	6.14	11.49	1.707	4.34	0	-79.9	870	6.86
14:34	6.18	11.51	1.706	4.35	0	-80.7	870	6.86
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Project:	11175616.00000			Site:	Pfohl I	Brothers	_ Well I.D.: _	GW-28S
Date:	11/11/2009	Sampling I	Personnel:	Rob Mu	urphy, Tim If	kovich	_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		_Tubing Type:	LDPE/	Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	9.07'	Depth to Well Bottom:	15.55'	Well Diameter:	2"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	4.0	-	Estimated Purge Volume (liters):	6.6
Sample ID:		GW-28S		Sample Time:	13	3:32	QA/QC:	None
	e Parameters: er Information:	VOCs, SVOCs, a	and TAL Meta	als				

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
12:57	7.40	12.81	0.753	3.47	17	-27.7	235	9.07
13:02	7.08	12.74	0.726	2.37	11	-13.2	180	10.04
13:07	7.02	12.72	0.716	2.27	8	0.9	180	10.23
13:12	6.99	12.75	0.713	2.23	7	11.5	180	10.33
13:17	6.91	12.67	0.715	2.15	5	30.2	180	10.40
13:22	6.87	12.85	0.722	2.10	5	35.6	180	10.41
13:27	6.81	12.82	0.729	2.15	5	38.6	180	10.43
13:32	6.81	12.76	0.732	2.14	5	40.7	180	10.44
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Project:		11175616.00000)	Site:	Pfohl	Brothers	_ Well I.D.: _	GW-29S
Date:	11/13/2009	Sampling	Personnel:	Rob Mu	urphy, Tim If	fkovich	_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		Tubing Type:_	LDPE/	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	8.20'	Depth to Well Bottom:	20.00'	Well Diameter:	2"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	7.3	_	Estimated Purge Volume (liters):	10.0
Sample ID:		GW-29S		Sample Time:	11	1:59	QA/QC:	None
		VOCs, SVOCs, Water red brown						

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
11:00	7.26	13.07	1.279	5.28	950	-69.4	170	8.20
11:05	6.97	13.22	1.271	4.66	550	-66.7	170	10.14
11:10	6.89	12.75	1.246	4.49	400	-62.6	170	10.32
11:15	6.89	12.69	1.226	4.48	310	-61.2	170	10.44
11:20	6.88	12.64	1.216	4.47	230	-59.2	170	10.57
11:25	6.86	12.73	1.207	4.34	170	-63.0	170	10.67
11:30	6.78	12.85	1.224	4.20	110	-65.7	170	10.76
11:35	6.75	12.93	1.229	4.15	100	-66.0	170	10.79
11:40	6.73	12.99	1.233	4.09	90	-66.2	170	10.83
11:45	6.71	13.01	1.240	4.00	70	-66.5	170	10.86
11:50	6.72	12.90	1.245	3.91	60	-62.4	170	10.89
11:53	6.75	12.86	1.246	3.88	50	-60.0	170	10.91
11:56	6.76	12.88	1.247	3.83	50	-57.8	170	10.92
11:59	6.78	12.85	1.250	3.80	45	-55.7	170	10.93
Tolerance:	0.1		3%	10%	10%	+ or - 10		

	11175616.00000		Site:	Pfohl I	Brothers	_ Well I.D.: _	GW-30S
11/13/2009	Sampling	Personnel:	Rob Mu	ırphy, Tim If	kovich	_ Company:_	URS Corporation
	Geopump 2		_Tubing Type:	LDPE/	Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Below Top of Riser	Initial Depth to Water:	8.13'	Depth to Well Bottom:	17.95'	Well Diameter:	2"	Screen Length:
Stainles	ss Steel		Volume in 1 Well Casing (liters):	6.1	-	Estimated Purge Volume (liters):	14.4
	GW-30S		Sample Time:	10):37	QA/QC:	None
	VOCs, SVOCs, a	and TAL Meta	als				
	Below Top of Riser	Geopump 2 Below Top of Initial Depth Riser to Water: Stainless Steel GW-30S e Parameters: VOCs, SVOCs, a	Geopump 2 Below Top of Initial Depth Riser to Water: 8.13' Stainless Steel GW-30S e Parameters: VOCs, SVOCs, and TAL Meta	Geopump 2 Below Top of Initial Depth Riser to Water: 8.13' Volume in 1 Well Casing (liters): GW-30S Sample Time: Parameters: VOCs, SVOCs, and TAL Metals	Geopump 2 Tubing Type: LDPE/ Below Top of Initial Depth Depth to Water: 8.13' Well Bottom: 17.95' Volume in 1 Well Casing (liters): 6.1 GW-30S GW-30S Sample Time: 100 Sample Time: 100 Parameters: VOCs, SVOCs, and TAL Metals	Sampling Personnel: Rob Murphy, Tim Ifkovich	Sampling Personnel: Rob Murphy, Tim Ifkovich Company:

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
10:07	7.39	12.42	3.962	11.98	65	-38.3	480	8.13
10:17	6.98	12.84	3.628	6.65	15	-77.0	480	8.20
10:27	6.93	12.97	3.641	7.22	6	-84.6	480	8.20
10:32	6.91	13.06	3.651	7.47	3	-85.1	480	8.20
10:37	6.90	13.10	3.655	7.59	3	-84.0	480	8.20
Tolerance:	0.1		3%	10%	10%	+ or - 10		

11175616.00000			Site:	Pfohl I	Brothers	_ Well I.D.: _	GW-31S
11/13/2009	Sampling F	Personnel:	Rob Mu	rphy, Tim If	kovich	_ Company:_	URS Corporation
	Geopump 2		_Tubing Type:	LDPE/	Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Below Top of Riser	Initial Depth to Water:	2.88'	Depth to Well Bottom:	9.58'	Well Diameter:	2"	Screen Length:
Stainles	ss Steel		Volume in 1 Well Casing (liters):	4.1	-	Estimated Purge Volume (liters):	3.6
	GW-31S		Sample Time:	9	:30	QA/QC:	None
e Parameters: er Information:	VOCs, SVOCs, a	nd TAL Meta	als				
	Below Top of Riser Stainles	Geopump 2 Below Top of Initial Depth Riser to Water: Stainless Steel GW-31S e Parameters: VOCs, SVOCs, a	Geopump 2 Below Top of Initial Depth Riser to Water: 2.88' Stainless Steel GW-31S e Parameters: VOCs, SVOCs, and TAL Meta	Geopump 2 Below Top of Initial Depth Riser to Water: 2.88' Stainless Steel GW-31S Sample Tubing Type: Depth to Well Bottom: Volume in 1 Well Casing (liters): Sample Time:	Geopump 2 Tubing Type: LDPE/ Below Top of Initial Depth Depth to Water: 2.88' Well Bottom: 9.58' Volume in 1 Well Casing (liters): 4.1 GW-31S GW-31S Sample Time: 9 e Parameters: VOCs, SVOCs, and TAL Metals	Sampling Personnel: Rob Murphy, Tim Ifkovich	Sampling Personnel: Rob Murphy, Tim Ifkovich Company:

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
8:55	7.67	8.85	0.713	6.89	13	90.7	125	2.88
9:00	7.60	8.96	0.715	2.50	9.0	95.0	100	4.36
9:05	7.54	9.06	0.716	2.14	8.0	98.8	100	4.71
9:10	7.52	9.20	0.717	2.06	8.0	100.2	100	5.01
9:15	7.50	9.40	0.718	1.99	9.2	103.7	100	5.28
9:20	7.44	9.40	0.721	1.97	7.7	103.2	100	5.52
9:25	7.42	9.63	0.722	1.92	7.5	97.4	100	5.72
9:30	7.41	9.70	0.724	1.92	7.7	93.5	100	5.92
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Project:		11175616.00000)	Site:	Pfohl	Brothers	Well I.D.:	GW-32S
Date:	11/13/2009	Sampling	Personnel:	Rob Mu	rphy, Tim If	fkovich	_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		Tubing Type:	LDPE/	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	3.28'	Depth to Well Bottom:	9.94'	Well Diameter:	2"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	4.1	-	Estimated Purge Volume (liters):	6.1
Sample ID:		GW-32S		Sample Time:	8	:23	QA/QC:	None
	e Parameters: er Information:	VOCs, SVOCs,	and TAL Meta	als				

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
7:48	7.63	8.95	0.732	8.61	45	51.3	230	3.28
7:58	7.72	9.10	0.721	4.54	12	63.1	150	3.70
8:03	7.72	9.07	0.718	4.05	8	65.2	150	3.71
8:08	7.72	9.08	0.710	3.43	5	67.1	150	3.73
8:13	7.72	9.13	0.705	3.11	5	68.9	150	3.74
8:18	7.73	9.23	0.701	3.02	4	67.8	150	3.75
8:23	7.72	9.45	0.698	2.87	4	66.7	150	3.76
Tolerance:	0.1		3%	10%	10%	+ or - 10		

	11175616.00000		Site:	Pfohl	Brothers	_ Well I.D.: _	GW-33S
11/11/2009	Sampling P	ersonnel:	Rob Mu	rphy, Tim If	kovich	_ Company:_	URS Corporation
	Geopump 2		Tubing Type:	LDPE/	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Below Top of Riser	Initial Depth to Water:	4.55'	Depth to Well Bottom:	8.20'	Well Diameter:	2"	Screen Length:
Stainles	ss Steel		Volume in 1 Well Casing (liters):	2.3	-	Estimated Purge Volume (liters):	5.1
	GW-33S		Sample Time:	15	5:38	QA/QC:	None
	VOCs, SVOCs, ar	nd TAL Meta	als				
	Below Top of Riser	Geopump 2 Below Top of Initial Depth Riser to Water: Stainless Steel GW-33S e Parameters: VOCs, SVOCs, an	Geopump 2 Below Top of Initial Depth Riser to Water: 4.55' Stainless Steel GW-33S e Parameters: VOCs, SVOCs, and TAL Meta	Geopump 2 Below Top of Initial Depth Riser to Water: 4.55' Volume in 1 Well Casing (liters): GW-33S Sample Time: Parameters: VOCs, SVOCs, and TAL Metals	Geopump 2 Tubing Type: LDPE/ Below Top of Initial Depth Depth to Well Bottom: 8.20' Volume in 1 Well Casing (liters): 2.3 GW-33S Sample Time: 15 Parameters: VOCs, SVOCs, and TAL Metals	Geopump 2 Tubing Type: LDPE/Silicone Below Top of Initial Depth Niser to Water: 4.55' Stainless Steel GW-33S Sample Time: 15:38 Rob Murphy, Tim Ifkovich Rob Murphy, Tim Ifkovich Rob Murphy, Tim Ifkovich Rob Murphy, Tim Ifkovich Well Stainless Steel Sample Time: 15:38	Sampling Personnel: Rob Murphy, Tim Ifkovich Company:

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
14:58	7.62	11.44	0.820	5.45	2.6	64.1	210	4.55
15:03	7.49	11.48	0.814	4.76	1.6	76.8	120	5.70
15:08	7.41	11.55	0.821	4.52	1.4	88.1	120	5.88
15:13	7.33	11.60	0.832	4.23	1.3	97.6	120	6.05
15:18	7.30	11.33	0.842	3.70	0	105.1	110	6.11
15:23	7.28	11.43	0.850	3.56	0	107.9	110	6.16
15:28	7.28	11.45	0.854	3.29	0	107.4	110	6.21
15:33	7.27	11.36	0.857	3.12	0	104.1	110	6.23
15:38	7.27	11.24	0.861	3.02	0	104.3	110	6.25
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Project:		11175616.00000)	Site:	Pfohl	Brothers	Well I.D.:	GW-34S
Date:	11/10/2009	/2009 Sampling Personne		Rob Mu	Rob Murphy, Tim Ifkovich		_ Company:_	URS Corporation
Purging/ Sampling Device:		Geopump 2		Tubing Type:	LDPE/	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Measuring Point:	Below Top of Riser	Initial Depth to Water:	2.78'	Depth to Well Bottom:	10.00'	Well Diameter:	2"	Screen Length:
Casing Type:	Stainles	ss Steel		Volume in 1 Well Casing (liters):	4.5	_	Estimated Purge Volume (liters):	12.4
Sample ID:		GW-34S		Sample Time:	16	6:20	QA/QC:	None
	e Parameters: er Information:	VOCs, SVOCs,	and TAL Meta	als				

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
15:25	7.58	11.11	1.464	9.90	11	93.3	375	2.78
15:30	6.98	10.32	1.461	4.76	10	125.2	210	4.00
15:35	6.81	10.09	1.458	5.55	10	143.7	210	4.20
15:40	7.11	10.90	1.450	5.88	6.8	133.5	210	4.31
15:45	6.89	10.08	1.445	6.01	6.5	136.6	210	4.41
15:50	6.84	10.00	1.429	6.09	3.8	134.3	210	4.51
15:55	6.84	9.89	1.405	6.24	2.9	130.0	210	4.56
16:00	6.86	9.83	1.377	6.21	2.0	123.3	210	4.58
16:05	6.87	9.72	1.319	5.76	1.4	112.0	210	4.58
16:10	6.88	9.64	1.294	5.34	0.7	101.3	210	4.58
16:15	6.89	9.61	1.277	5.20	0.5	97.2	210	4.58
16:20	6.90	9.61	1.263	5.19	0.4	96.6	210	4.58
Tolerance:	0.1		3%	10%	10%	+ or - 10		

	11175616.00000	Site:	Pfohl	Brothers	_ Well I.D.: _	GW-35S
11/12/2009	Sampling Perso	onnel: Rob Mu	urphy, Tim I	fkovich	_ Company:_	URS Corporation
	Geopump 2	Tubing Type:	LDPE	/Silicone	Pump/Tubing Inlet Location:	Screen midpoint
Below Top of Riser	•	Depth to Well Bottom:	7.45'	Well Diameter:	2"	Screen Length:
Stainles	ss Steel	Volume in 1 Well Casing (liters):	2.5	_	Estimated Purge Volume (liters):	7.4
	GW-35S	Sample Time:	1	5:15	QA/QC:	None
e Parameters: er Information:	VOCs, SVOCs, and TA	L Metals				
	Below Top of Riser Stainles	Geopump 2 Below Top of Initial Depth Riser to Water: 3.32 Stainless Steel GW-35S e Parameters: VOCs, SVOCs, and TA	Geopump 2 Below Top of Initial Depth Riser to Water: 3.32' Volume in 1 Well Casing (liters): GW-35S GW-35S Parameters: VOCs, SVOCs, and TAL Metals	Geopump 2 Tubing Type: LDPE Below Top of Initial Depth Depth to Water: 3.32' Well Bottom: 7.45' Volume in 1 Well Casing (liters): 2.5 Sample GW-35S GW-35S GW-35S GW-35S GW-35S GW-35S Sample Time: 1	Sampling Personnel: Rob Murphy, Tim Ifkovich	Sampling Personnel: Rob Murphy, Tim Ifkovich Company:

PURGE PARAMETERS

TIME	рН	TEMP (°C)	COND. (mS/cm)	DISS. O ₂ (mg/l)	TURB. (NTU)	Eh (mV)	FLOW RATE (ml/min.)	DEPTH TO WATER (btor)
14:45	6.67	12.23	0.754	5.19	15	-3.2	245	3.32
14:50	6.56	11.90	0.607	3.17	3	1.2	245	4.11
14:55	6.58	11.67	0.583	2.65	2	2.2	245	4.12
15:00	6.58	11.46	0.580	2.20	1	-1.5	245	4.12
15:05	6.60	11.49	0.574	1.99	1	-2.7	245	4.12
15:10	6.61	11.26	0.572	1.96	1	4.3	245	4.12
15:15	6.63	11.11	0.577	1.86	1	7.0	245	4.12
Tolerance:	0.1		3%	10%	10%	+ or - 10		

Project Name: Project Number: 11175616.00000

Sampling Crew Members: R. Murphy, T. Ifkovich Supervisor: J. Sundquist

Date of Sampling: <u>November 10, 2009</u>

Sample I.D. Number	Well Number	Well Volume (liters)	Volume Purged (liters)	Sample Time	Sample Description	Analysis Required	Chain-of- Custody Number
GW-34S	GW-34S	4.5	12.4	16:20	Groundwater	VOCs/SVOCs/ Metals	Not Applicable

Additional Comments: All wells were purged using low flow methods until parameter stabilization.

Project Name: Pfohl Brothers Project Number: 11175616.00000

Sampling Crew Members: R. Murphy, T. Ifkovich Supervisor: J. Sundquist

Date of Sampling: <u>November 11, 2009</u>

Sample I.D. Number	Well Number	Well Volume (liters)	Volume Purged (liters)	Sample Time	Sample Description	Analysis Required	Chain-of- Custody Number
GW-3S	GW-3S	6.7	6	8:23	Groundwater		Not Applicable
GW-3D	GW-3D	83.1	53.4	9:45	Groundwater		Not Applicable
GW-3D MS	GW-3D	83.1	53.4	9:45	Matrix Spike	VOCs/SVOCs/	Not Applicable
GW-3D MSD	GW-3D	83.1	53.4	9:45	Matrix Spike Duplicate	Metals	Not Applicable
GW-8SR	GW-8SR	4.7	8.8	11:16	Groundwater		Not Applicable
GW-8D	GW-8D	75.6	50.6	12:32	Groundwater		Not Applicable
DUPLICATE	GW-8D	75.6	50.6	12:32	Blind Duplicate		Not Applicable

Additional Comments: All wells were purged using low flow methods until parameter stabilization.

Project Name: Project Number: 11175616.00000

Sampling Crew Members: R. Murphy, T. Ifkovich Supervisor: J. Sundquist

Date of Sampling: <u>November 11, 2009 (continued)</u>

Sample I.D. Number	Well Number	Well Volume (liters)	Volume Purged (liters)	Sample Time	Sample Description	Analysis Required	Chain-of- Custody Number
GW-28S	GW-28S	4.0	6.6	13:32	Groundwater		Not Applicable
GW-7S	GW-7S	19.7	28.4	14:15	Groundwater	VOCs/SVOCs/ Metals	Not Applicable
GW-7D	GW-7D	43.5	45.4	14:25	Groundwater	iviciais	Not Applicable
GW-33S	GW-33S	2.3	5.1	15:38	Groundwater		Not Applicable
TB-111109					Trip Blank	VOCs	Not Applicable

Additional Comments: All wells were purged using low flow methods until parameter stabilization.

Project Name: Project Number: 11175616.00000

Sampling Crew Members: R. Murphy, T. Ifkovich Supervisor: J. Sundquist

Date of Sampling: <u>November 12, 2009</u>

Sample I.D. Number	Well Number	Well Volume (liters)	Volume Purged (liters)	Sample Time	Sample Description	Analysis Required	Chain-of- Custody Number
GW-4D	GW-4D	80.4	13.7	10:01	Groundwater	VOCs/SVOCs/ Metals	Not Applicable
GW-4S	GW-4S	7.3	26.1	10:25	Groundwater		Not Applicable
GW-1S	GW-1S	6.8	6.9	11:48	Groundwater		Not Applicable
GW-1D	GW-1D	90.9	45.0	13:00	Groundwater		Not Applicable
GW-26D	GW-26D	83.7	47.9	14:34	Groundwater		Not Applicable
GW-35S	GW-35S	2.5	7.4	15:15	Groundwater		Not Applicable
TB-111209					Trip Blank	VOCs	Not Applicable

Additional Comments: All wells were purged using low flow methods until parameter stabilization.

Project Name: Pfohl Brothers Project Number: 11175616.00000

Sampling Crew Members: R. Murphy, T. Ifkovich Supervisor: J. Sundquist

Date of Sampling: November 13, 2009

Sample I.D. Number	Well Number	Well Volume (liters)	Volume Purged (liters)	Sample Time	Sample Description	Analysis Required	Chain-of- Custody Number
GW-32S	GW-32S	4.1	6.1	8:23	Groundwater	VOCs/SVOCs/ Metals	Not Applicable
GW-31S	GW-31S	4.1	3.6	9:30	Groundwater		Not Applicable
GW-30S	GW-30S	6.1	14.4	10:37	Groundwater		Not Applicable
GW-29S	GW-29S	7.3	10.0	11:59	Groundwater		Not Applicable
TB-111309					Trip Blank	VOCs	Not Applicable

Additional Comments: All wells were purged using low flow methods until parameter stabilization.

APPENDIX E HISTORICAL ANALYTICAL RESULTS

FIGURE E-1
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-1D




FIGURE E-2
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-1S




FIGURE E-3
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-3D




FIGURE E-4
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-3S




FIGURE E-4
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-3S




FIGURE E-5
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-4D




FIGURE E-6
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-4S




FIGURE E-7
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-7D




FIGURE E-8
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-7S




FIGURE E-9
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-8D




FIGURE E-10 TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS IN MONITORING WELL GW-8SR




FIGURE E-11
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-26D




FIGURE E-12
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-28S




FIGURE E-13
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-29S




FIGURE E-13
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-29S




FIGURE E-14
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-30S




FIGURE E-15
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-31S




FIGURE E-16
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-32S




FIGURE E-17
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-33S




FIGURE E-18
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-34S





FIGURE E-19
TRENDS OF PARAMETERS ROUTINELY EXCEEDING GROUNDWATER STANDARDS
IN MONITORING WELL GW-35S



APPENDIX F BSA PERMIT NO. 05-12-CH016

AUTHORIZATION TO DISCHARGE UNDER THE BUFFALO POLLUTANT DISCHARGE ELIMINATION SYSTEM

PERMIT NO. 05-12-CH016 USEPA Category 40 CFR Part 403

In accordance with the provisions of the Federal Water Pollution Control Act, as amended, and the Sewer Regulations of the Buffalo Sewer Authority, authorization is hereby granted to:

THE TOWN OF CHEEKTOWAGA

to discharge wastewater from a facility located at:

PFOHL BROTHERS LANDFILL REMEDIATION SITE 1000 AERO DRIVE

CHEEKTOWAGA, NEW YORK 14225

The wastewater permitted herein shall be discharged to the Town of Cheektowaga sewer system, which is connected to the Buffalo Municipal Sewer System and Treatment facilities, and which wastewater will be treated at the Buffalo Sewer Authority's Treatment Plant.

Issuance of this permit is based upon a permit application filed on **November 3, 2005** analytical data. This permit is granted in accordance with discharge limitations, monitoring requirements and other conditions set forth in Parts I and II hereof.

Effective this 1st day of April, 2006

To Expire the 31st day of March, 2009

General Manager

Signed this 30-4 day of March, 2006

PART I: SPECIFIC CONDITIONS

A. DISCHARGE LIMITATIONS & MONITORING REQUIREMENTS

During the period beginning the effective date of this Permit and lasting until the expiration date, discharge from the permitted facility outfall (see attached map) shall be limited and monitored quarterly by the permittee as specified below.

Sample		Discharge Limitations ⁽¹⁾	Sampling Requirements			
Point	Parameter	Daily Max	Period	Туре		
001	pН	5.0 – 12.0 S.U.	1 day	Composite ²		
	Total Cadmium	1.17 lbs.	1 day	Composite ²		
	Total Chromium	1.17 lbs.	1 day	Composite ²		
	Total Copper	3.74 lbs.	1 day	Composite ²		
	Total Lead	1.17 lbs.	1 day	Composite ²		
	Total Nickel	3.27 lbs.	1 day	Composite ²		
	Total Zinc	5.84 lbs.	1 day	Composite ²		
	Total Barium	2.34 lbs.	1 day	Composite ²		
	Total Suspended Solids ⁵	250 mg/l	1 day	Composite ²		
	Total Flow	140,100 gallons ⁶	1 day	Discharge meter reading		

Footnotes are explained on page 5.

Permit No. 05-12-CH016 Part I Page 3 of 5

PART I: SPECIFIC CONDITIONS

A. DISCHARGE LIMITATIONS & MONITORING REQUIREMENTS

During the period beginning the effective date of this Permit and lasting until the expiration date, discharge from the permitted facility outfall (see attached map) shall be limited and monitored **once** by the permittee as specified below.

Sample		Discharge Limitations ⁽¹⁾	Sampli	ing Requirements
Point	Parameter	Daily Max	Period	Type
001	Total Mercury	0.001 lbs.	1 day	Composite ²
	USEPA Test			- 13
	Method 608 ⁴	To be monitored	1 day	Grab ³
	USEPA Test			3
	Method 624 ⁴	To be monitored	1 day	Grab ³
	USEPA Test			~ · 3
	Method 625 ⁴	To be monitored	1 day	Grab ³

Footnotes are explained on page 5.

Permit No. 05-12-CH016 Part I Page 4 of 5

PART I: SPECIFIC CONDITIONS

B. DISCHARGE MONITORING REPORTING REQUIREMENTS


During the period beginning the effective date of this permit and lasting until the expiration date, discharge monitoring results shall be summarized and reported quarterly by the permittee on the days specified below:

Sample		Reporting Requirements					
Point 001	Parameter All except USEPA Test Methods 608, 624, 625 & T Mercury	Initial Report June 30, 2006	Subsequent Reports Every March 31 st , June 30 th , September 30 th and December 31 st				
	USEPA Test Methods 608, 624 and 625 & T Mercury	March 31, 2008					

PART I: SPECIFIC CONDITIONS

C. SPECIAL REQUIREMENTS

- 1. Mass limits based on an average discharge of 140,100 gpd.
- 2. Composite samples may be time proportioned.
- 3. Four grab samples must be collected at equally spaced intervals throughout the sample day. The four (4) grab samples must be composited by a NYSDOH certified laboratory prior to analysis.
- 4. The permittee must report any compound whose concentration is equal to or greater than 0.01 mg/L. The permittee is not authorized to discharge any of the parameters evaluated by these test procedures which may cause or contribute to a violation of water quality standards or harm the sewerage system. Any parameter detected may, at the discretion of the BSA, be specifically limited and incorporated in this permit.
- 5. Surchargeable over 250 mg/L.
- 6. Flow is an action level only. If the permittee consistently exceeds this level, the BSA must be notified so that this permit can be modified.



APPENDIX G DISCHARGE REPORT SUMMARY TABLES

SAMPLING FIELD SHEET

URS

Client Name: Pfohl	Brothers Landfill	l		
Address: Aero	Drive, Cheektow	aga, NY		
Contact: Bill P	ugh, P.E.		Phone:	716-897-7288
Installation:				
Sample Point: SP-0	01			
Sample Location:	Meter Chamb	er - ball valve on	6" HDPE	E forcemain
Date: 09/	/24/09 Crew:	R. Murphy, S.	McCabe	e, T. Ifkovich
Weather: 70° F	, cloudy			
Sampling Device:	NA			
Time of Installation:	8:00	Type of S	Sample:	Composite
Sample Interval:	NA	Sample \	Volume:	NA
Date: 9/2	25/09 Crew: , partly cloudy 8:00	R. Murphy, S.	,	81,544 gals) & MH-25 (2,291,676 gals).
Field Measurements:				
8:00/RJM (time/initial)		pH Calibration:	Buffer 7-	7 Buffer 4- 4 Buffer 10- 10
		pH Measurement:		6.8
		Temperature:		15.4°C
Identification: EFF-	092509			
Physical Observations				
Laboratory: TestAr	merica, Buffalo, N	ΙΥ		
		at the time of sa		kup. '93 gals), WW-03 (34 gals),
				93 gais), vvv-03 (34 gais), 81,544 gais) & MH-25 (2,291,947 gais).
Reviewed By:		(Supervisor)		Date:

TABLE 1

PFOHL BROTHERS LANDFILL - EFFLUENT MONITORING ANALYTICAL RESULTS, TOTAL FLOW, AND MASS LOADINGS SEPTEMBER 2009

Sample ID	EFF-092509						
Matrix	Effluent Water						
Date Sampled		Ç	9/25/2009				
Parameter	Result	Mass Loading	Discharge Limitation	Violations			
	(mg/L)	(lbs/day)	(lbs/day)	(Y/N)			
Total Barium	0.306	0.001	2.34	No			
Total Cadmuim	ND ⁽¹⁾	NA ⁽²⁾	1.17	No			
Total Chromium	ND	NA	1.17	No			
Total Copper	ND	NA	3.74	No			
Total Lead	ND	NA	1.17	No			
Total Nickel	0.0077	0.00002	3.27	No			
Total Zinc	0.0056	0.00001	5.84	No			
Total Suspended Solids	8.8	NA	250 ⁽³⁾	No			
рН ⁽⁴⁾	6.8	NA	5.0 - 12.0	No			
Total Flow ⁽⁵⁾		271	140,000	No			

Notes:

- (1) ND = Not Detected
- (2) NA = Not Applicable
- (3) Discharge Limitation in units of mg/L
- (4) pH measurement and Discharge Limitation in Standard Units
- (5) Total Flow reported in gallons, sample was collected over a 24 hour period

$$\text{Calculation:} \quad \left(\frac{x \text{ mg}}{L}\right) \!\! \left(\frac{y \text{ gal}}{\text{day}}\right) \!\! \left(\frac{1 \text{ lb}}{453,\!600 \text{ mg}}\right) \!\! \left(\frac{3.785 \, L}{\text{gal}}\right) = \frac{x \times y}{119,\!841} \cdot \frac{\text{lb}}{\text{day}}$$

SAMPLING FIELD SHEET

URS

Client Name: Pfohl	Brothers Landfill			
Address: Aero	Drive, Cheektow	aga, NY		
Contact: Bill P	ugh, P.E.		Phone:	716-897-7288
<u>Installation</u> :				
Sample Point: SP-00	01			
Sample Location:	Meter Chamb	er - ball valve on 6	6" HDPE	Ē forcemain
Date: 12/	21/09 Crew:	R. Murphy, R. I	Piurek,	T. Ifkovich
Weather: 30° F	, partly cloudy			
Sampling Device:	NA			
Time of Installation:	10:55	Type of Sa	ample:	Composite
Sample Interval:	NA	Sample V	olume:	NA
Date: 12/ Weather: 23° F Time of Collection:	22/09 Crew: , clear 11:05	R. Murphy, R. I	`	,788,676 gals) & MH-25 (6,703,435 gals). T. Ifkovich
Date: 12/ Weather: 23° F Time of Collection:	22/09 Crew: , clear 11:05	R. Murphy, R. I	Piurek,	
Date: 12/ Weather: 23° F Time of Collection: Field Measurements:	22/09 Crew: , clear 11:05	R. Murphy, R. I	Piurek,	T. Ifkovich
Date: 12/ Weather: 23° F Time of Collection: Field Measurements: 11:10/RJM	22/09 Crew: , clear 11:05	R. Murphy, R. I	Piurek,	T. Ifkovich 7 Buffer 4- 4 Buffer 10- 10
Date: 12/ Weather: 23° F Time of Collection: Field Measurements: 11:10/RJM (time/initial)	22/09 Crew: , clear 11:05	R. Murphy, R. I	Piurek,	T. Ifkovich 7 Buffer 4- 4 Buffer 10- 10 7.4
Date: 12/ Weather: 23° F Time of Collection: Field Measurements: 11:10/RJM (time/initial)	22/09 Crew: , clear 11:05	R. Murphy, R. I	Piurek,	7 Buffer 4- 4 Buffer 10- 10 7.4 7.8°C
Date: 12/ Weather: 23° F Time of Collection: Field Measurements: 11:10/RJM (time/initial) Identification: EFF- Physical Observations: Laboratory: TestAr Comments: No well PLC display volum	22/09 Crew: , clear 11:05 122209 nerica, Buffalo, Notes: WW-01 (73)	R. Murphy, R. I	Piurek, Buffer 7-	T. Ifkovich 7 Buffer 4- 4 Buffer 10- 10 7.4 7.8°C Skup. 792 gals), WW-03 (34 gals),
Date: 12/ Weather: 23° F Time of Collection: Field Measurements: 11:10/RJM (time/initial) Identification: EFF- Physical Observations: Laboratory: TestAr Comments: No well PLC display volum	22/09 Crew: , clear 11:05 122209 nerica, Buffalo, Notes: WW-01 (73)	R. Murphy, R. I	Piurek, Buffer 7-	7 Buffer 4- 4 Buffer 10- 10 7.4 7.8°C

TABLE 1

PFOHL BROTHERS LANDFILL - EFFLUENT MONITORING ANALYTICAL RESULTS, TOTAL FLOW, AND MASS LOADINGS DECEMBER 2009

Sample ID	EFF-122209						
Matrix	Effluent Water						
Date Sampled		1	2/22/2009				
Parameter	Result	Mass Loading	Discharge Limitation	Violations			
	(mg/L)	(lbs/day)	(lbs/day)	(Y/N)			
Total Barium	0.238	0.026	2.34	No			
Total Cadmuim	0.0003	0.00003	1.17	No			
Total Chromium	0.0026	0.00028	1.17	No			
Total Copper	0.0021	0.00023	3.74	No			
Total Lead	ND ⁽¹⁾	NA ⁽²⁾	1.17	No			
Total Nickel	0.007	0.00076	3.27	No			
Total Zinc	0.0123	0.00133	5.84	No			
Total Suspended Solids	ND	NA	250 ⁽³⁾	No			
pH ⁽⁴⁾	7.4	NA	5.0 - 12.0	No			
Total Flow ⁽⁵⁾		12,933	140,000	No			

Notes:

- (1) ND = Not Detected
- (2) NA = Not Applicable
- (3) Discharge Limitation in units of mg/L
- (4) pH measurement and Discharge Limitation in Standard Units
- (5) Total Flow reported in gallons, sample was collected over a 24 hour period

$$\text{Calculation:} \quad \left(\frac{x \text{ mg}}{L}\right) \!\! \left(\frac{y \text{ gal}}{\text{day}}\right) \!\! \left(\frac{1 \text{ lb}}{453,\!600 \text{ mg}}\right) \!\! \left(\frac{3.785 \, L}{\text{gal}}\right) = \frac{x \times y}{119,\!841} \cdot \frac{\text{lb}}{\text{day}}$$

APPENDIX H MONITORING WELL INSPECTION LOGS

WELL INSPECTION SUMMARY

Project Name: <u>Pfohl Brothers Landfill</u> Project Number: <u>11175616.00000</u>

Inspection Crew Members: R. Murphy, T. Ifkovich Supervisor: J. Sundquist

Date(s) of Inspection: November 10-13, 2009

Well I.D. Number	Lock	Surface Seal	Protective Casing	Riser	Water Level (ft. BTOC)	Well Depth (ft. BTOC)	Other Comments
GW-1S	ОК	ОК	OK	Bulged	3.97	14.94	
GW-1D	ОК	OK	OK	Bulged	2.83	39.65	
GW-3S	ОК	OK	OK	OK	2.39	13.25	
GW-3D	ОК	OK	OK	OK	2.02	35.65	
GW-4S	ОК	OK	OK	OK	4.43	16.23	
GW-4D	ОК	OK	OK	OK	13.01	45.57	
GW-7S	OK	OK	OK	OK	4.73	35.08	
GW-7D	ОК	OK	ОК	Damaged	42.79	60.28	

Additional Comments:			

WELL INSPECTION SUMMARY

Project Name: <u>Pfohl Brothers Landfill</u> Project Number: <u>11175616.00000</u>

Inspection Crew Members: R. Murphy, T. Ifkovich Supervisor: J. Sundquist

Date(s) of Inspection: November 10-13, 2009

Well I.D. Number	Lock	Surface Seal	Protective Casing	Riser	Water Level (ft. BTOC)	Well Depth (ft. BTOC)	Other Comments
GW-8SR	ОК	OK	OK	OK	5.42	13.03	
GW-8D	ОК	OK	OK	OK	5.98	36.58	
GW-26D	ОК	OK	OK	OK	6.85	40.75	
GW-28S	ОК	OK	OK	OK	9.07	15.55	
GW-29S	ОК	OK	OK	OK	8.20	20.00	
GW-30S	ОК	OK	OK	OK	8.13	17.95	
GW-31S	OK	OK	OK	OK	2.88	9.58	
GW-32S	OK	OK	OK	OK	3.28	9.94	

Additional Comments:		

WELL INSPECTION SUMMARY

Project Name: <u>Pfohl Brothers Landfill</u> Project Number: <u>11175616.00000</u>

Inspection Crew Members: R. Murphy, T. Ifkovich Supervisor: J. Sundquist

Date(s) of Inspection: November 10-13, 2009

Well I.D. Number	Lock	Surface Seal	Protective Casing	Riser	Water Level (ft. BTOC)	Well Depth (ft. BTOC)	Other Comments
GW-33S	ОК	ОК	OK	OK	4.55	8.20	
GW-34S	ОК	OK	OK	OK	2.78	10.00	
GW-35S	ОК	OK	OK	OK	3.32	7.45	

Additional Comments:		
	-	

ATTACHMENT C IC/EC CERTIFICATION



Enclosure 1 NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION Site Management Periodic Review Report Notice Institutional and Engineering Controls Certification Form



	ita Na	Site Details 915043	Box 1	V
3	ite No.	913043	•	
S	ite Name	Pfohl Brothers Landfill	•	
- C	ity/Town:	ss: Aero Drive and Transit Road Zip Code: 14221 Cheektowaga		:
Al Si	ite Acreag	Jse(s) (if applicable, does not address local zoning): ge: 94.0		
U	wner: ivit	ultiple Owners		
Re	eporting P	Period: February 12, 2009 to February 12, 2010		•
	•		<u> </u>	
	:	Varification of Cita Dataile	•	Box 2
		Verification of Site Details	YES	NO
1.	Is the in	nformation in Box 1 correct?	×	
	If NO, a	are changes handwritten above or included on a separate sheet?		•.
2.	Has sor tax map	me or all of the site property been sold, subdivided, merged, or undergone a part amendment during this Reporting Period?		· 🗶
	If YES, submitte	is documentation or evidence that documentation has been previously ed included with this certification?	Ġ	
3.	Have ar for or at	ny federal, state, and/or local permits (e.g., building, discharge) been issued the property during this Reporting Period?		X
		is documentation (or evidence that documentation has been previously ed) included with this certification?		
4.	If use of restriction	f the site is restricted, is the current use of the site consistent with those ons?	×	
	If NO, is	an explanation included with this certification?		
· 5.	For non-	-significant-threat Brownfield Cleanup Program Sites subject to ECL 27-1415.7(new information revealed that assumptions made in the Qualitative Exposure	c),	NA
	Assessn	nent regarding offsite contamination are no longer valid?		
	If YES, i	s the new information or evidence that new information has been previously dincluded with this Certification?	. 🗆	
6.	are the a	significant-threat Brownfield Cleanup Program Sites subject to ECL 27-1415.7(dessumptions in the Qualitative Exposure Assessment still valid (must be every five years)?	c),	□ N/A
	if NO, an	e changes in the assessment included with this certification?		

SITE NO. 915043

Description of Institutional Controls

Description of Institutional Co	ntrols
Par <u>cel</u>	Institutional Control
S B L Image: 82.03-4-9.11	
	Building Use Restriction
	Ground Water Use Restriction
•	Landuse Restriction
S B L Image: 82.03-4-9.2	
	Building Use Restriction
	Ground Water Use Restriction
	Landuse Restriction
S_B_L Image: 82.03-4-10	<u></u>
	Building Use Restriction
	Ground Water Use Restriction
1	Landuse Restriction
S_B_L Image: 82.03-4-5	Duttitus I be Destriction
	Building Use Restriction
	Ground Water Use Restriction Landuse Restriction
	Landuse Restriction
S_B_L Image: 81.04-1-27	Building Use Restriction
	Ground Water Use Restriction
	Landuse Restriction
2 2 4 2 4 2 2 4	Landuse Restriction
S_B_L Image: 81.04-1-28.1	Building Use Restriction
	Ground Water Use Restriction
	Landuse Restriction
0. 7. 1. 1	
S_B_L Image: 81.04-2-9.1	Building Use Restriction
	Ground Water Use Restriction
	Landuse Restriction
O. D. I. Images, 94 04 2 10 1	
S_B_L Image: 81.04-2-10.1	Building Use Restriction
	Ground Water Use Restriction
	Landuse Restriction
S_B_L Image: 81.04-2-11	
3_B_E mage. • 11• . 1 · 1	Building Use Restriction
	Ground Water Use Restriction
	Landuse Restriction
S_B_L Image: 82.03-4-11	
<u></u>	Building Use Restriction
	Ground Water Use Restriction
	Landuse Restriction
S_B_L Image: 82.03-4-6	
	Building Use Restriction
	Ground Water Use Restriction
	Landuse Restriction
S_B_L Image: 82.03-4-8	
	Building Use Restriction
	Ground Water Use Restriction
	Landuse Restriction
S_B_L Image: 82.03-4-9.12	B W. H. B. H. B.
	Building Use Restriction
	Ground Water Use Restriction
	Landuse Restriction
S_B_L Image: 81.04-1-26	Building Line Bootriction
	Building Use Restriction Ground Water Use Restriction
	Landuse Restriction
	Landuse Mesulcuon

Surface Water Use Restriction

Description of Engineering Controls

	Description of Enginee	ering Controls
	Parcel	Engineering Control
	S B L Image: 82.03-4-9.11	<u> </u>
	5_b_L illiage. 62.03-4-9.11	Cover System
		Fencing/Access Control
	,	Leachate Collection
	• • • •	Vapor Mitigation
ĺ	S_B_L Image: 82.03-4-9.2	
	 	Cover System
ı	·	Fencing/Access Control
ı	• .	Leachate Collection
ı	0. D. I. I	Vapor Mitigation ,
	S_B_L Image: 82.03-4-10	Cover System
		Cover System Fencing/Access Control
		Leachate Collection
		Vapor Mitigation
ļ	S B_L Image: 82.03-4-5	o apor magazioni
I		Cover System
ŀ	•	Fencing/Access Control
I		Leachate Collection
١		Vapor Mitigation
l	S_B_L Image: 81.04-1-27	Carram Creatains
١	•	Cover System Fencing/Access Control
I		Leachate Collection
		Vapor Mitigation
l	S B L image: 81.04-1-28.1	· upor maganon
l		Cover System
l		Fencing/Access Control
l		Leachate Collection
l		Vapor Mitigation
l	S_B_L Image: 81.04-2-9.1	0
l	•	Cover System Fencing/Access Control
l		Leachate Collection
l		Vapor Mitigation
ĺ	S B L Image: 81.04-2-10.1	Tapol III.igadon
	0_0_1ags. 0 1	Cover System
l		Fencing/Access Control
١	•	Leachate Collection
		Vapor Mitigation
	S_B_L Image: 81.04-2-11	Ô
		Cover System
		Fencing/Access Control Leachate Collection
		Vapor Mitigation
	S_B_L Image: 82.03-4-11	vapor magadon
	O_B_L IIIAgo. OLIOO-4-11	Cover System
	•	Fencing/Access Control
		Leachate Collection
		Vapor Mitigation
	0.0 1.1	

S_B_L Image: **82.03-4-8**

S_B_L Image: 82.03-4-6

Cover System Fencing/Access Control Leachate Collection Vapor Mitigation

Cover System
Fencing/Access Control
Leachate Collection
Vapor Mitigation

Parcel

S B L Image: 82.03-4-9.12

Engineering Control

Cover System

Fencing/Access Control Leachate Collection Vapor Mitigation

S B L Image: 81.04-1-26

Cover System

Fencing/Access Control Leachate Collection Vapor Mitigation

Attach documentation if IC/ECs cannot be certified or why IC/ECs are no longer applicable. (See instructions)

Control Description for Site No. 915043

Parcel: 81.04-1-26

In accordance with the Declaration of Covenants and Restrictions filed with the Erie County Clerk's Office on 4/25/03 and included as Appendix P in the Remedial Action Construction Report, Vol. II, the following Controls are in place:

A. Entire Site: i) Groundwater use prohibition, ii) Surface water use prohibition.

B. Capped Area: i) Fencing, ii) No Excavation, iii) Planting trees/shrubs prohibited.

C. Cleared Portion within the Perimeter Barrier System: i) Only Commercial/Industrial Development is allowed. Construction restrictions.

Parcel: 81.04-1-27

In accordance with the Declaration of Covenants and Restrictions filed with the Erie County Clerk's Office on 4/25/03 and included as Appendix P in the Remedial Action Construction Report, Vol. II, the following Controls are in place:

A. Entire Site: i) Groundwater use prohibition, ii) Surface water use prohibition.

B. Capped Area: i) Fencing, ii) No Excavation, iii) Planting trees/shrubs prohibited.

C. Cleared Portion within the Perimeter Barrier System: i) Only Commercial/Industrial Development is allowed. Construction restrictions.

Parcel: 81.04-1-28.1

In accordance with the Declaration of Covenants and Restrictions filed with the Erie County Clerk's Office on 4/25/03 and included as Appendix P in the Remedial Action Construction Report, Vol. II, the following Controls are in place:

A. Entire Site: i) Groundwater use prohibition, ii) Surface water use prohibition.

B. Capped Area: i) Fencing, ii) No Excavation, iii) Planting trees/shrubs prohibited.

C. Cleared Portion within the Perimeter Barrier System: i) Only Commercial/Industrial Development is allowed. Construction restrictions.

Parcel: 81.04-2-10.1

In accordance with the Declaration of Covenants and Restrictions filed with the Erie County Clerk's Office on 4/25/03 and included as Appendix P in the Remedial Action Construction Report, Vol. II, the following Controls are in place:

A. Entire Site: i) Groundwater use prohibition, ii) Surface water use prohibition.

B. Capped Area: i) Fencing, ii) No Excavation, iii) Planting trees/shrubs prohibited.

C. Cleared Portion within the Perimeter Barrier System: i) Only Commercial/Industrial Development is allowed. Construction restrictions.

Parcel: 81.04-2-11

In accordance with the Declaration of Covenants and Restrictions filed with the Erie County Clerk's Office on 4/25/03 and included as Appendix P in the Remedial Action Construction Report, Vol. II, the following Controls are in place:

A. Entire Site: i) Groundwater use prohibition, ii) Surface water use prohibition.

B. Capped Area: i) Fencing, ii) No Excavation, iii) Planting trees/shrubs prohibited.

C. Cleared Portion within the Perimeter Barrier System: i) Only Commercial/Industrial Development is allowed. Construction restrictions.

Control Description for Site No. 915043

Parcel: 81.04-2-9.1

In accordance with the Declaration of Covenants and Restrictions filed with the Erie County Clerk's Office on 4/25/03 and included as Appendix P in the Remedial Action Construction Report, Vol. II, the following Controls are in place:

A. Entire Site: i) Groundwater use prohibition, ii) Surface water use prohibition.

B. Capped Area: i) Fencing, ii) No Excavation, iii) Planting trees/shrubs prohibited.

C. Cleared Portion within the Perimeter Barrier System: i) Only Commercial/Industrial Development is allowed. Construction restrictions.

Parcel: 82.03-4-10

In accordance with the Declaration of Covenants and Restrictions filed with the Erie County Clerk's Office on 4/25/03 and included as Appendix P in the Remedial Action Construction Report, Vol. II, the following Controls are in place:

A. Entire Site: i) Groundwater use prohibition, ii) Surface water use prohibition.

B. Capped Area: i) Fencing, ii) No Excavation, iii) Planting trees/shrubs prohibited.

C. Cleared Portion within the Perimeter Barrier System: i) Only Commercial/Industrial Development is allowed. Construction restrictions.

Parcel: 82.03-4-11

In accordance with the Declaration of Covenants and Restrictions filed with the Erie County Clerk's Office on 4/25/03 and included as Appendix P in the Remedial Action Construction Report, Vol. II, the following Controls are in place:

A. Entire Site: i) Groundwater use prohibition, ii) Surface water use prohibition.

B. Capped Area: i) Fencing, ii) No Excavation, iii) Planting trees/shrubs prohibited.

C. Cleared Portion within the Perimeter Barrier System: i) Only Commercial/Industrial Development is allowed. Construction restrictions.

Parcel: 82.03-4-5

In accordance with the Declaration of Covenants and Restrictions filed with the Erie County Clerk's Office on 4/25/03 and included as Appendix P in the Remedial Action Construction Report, Vol. II, the following Controls are in place:

A. Entire Site: i) Groundwater use prohibition, ii) Surface water use prohibition.

B. Capped Area: i) Fencing, ii) No Excavation, iii) Planting trees/shrubs prohibited.

C. Cleared Portion within the Perimeter Barrier System: i) Only Commercial/Industrial Development is allowed. Construction restrictions.

Parcel: 82.03-4-6

In accordance with the Declaration of Covenants and Restrictions filed with the Erie County Clerk's Office on 4/25/03 and included as Appendix P in the Remedial Action Construction Report, Vol. II, the following Controls are in place:

A. Entire Site: i) Groundwater use prohibition, ii) Surface water use prohibition.

B. Capped Area: i) Fencing, ii) No Excavation, iii) Planting trees/shrubs prohibited.

C. Cleared Portion within the Perimeter Barrier System: i) Only Commercial/Industrial Development is allowed. Construction restrictions.

Parcel: 82.03-4-8

In accordance with the Declaration of Covenants and Restrictions filed with the Erie County Clerk's Office on 4/25/03 and included as Appendix P in the Remedial Action Construction Report, Vol. II, the following Controls are in place:

A. Entire Site: i) Groundwater use prohibition, ii) Surface water use prohibition.

B. Capped Area: i) Fencing, ii) No Excavation, iii) Planting trees/shrubs prohibited.

C. Cleared Portion within the Perimeter Barrier System: i) Only Commercial/Industrial Development is allowed. Construction restrictions.

Parcel: 82.03-4-9.11

In accordance with the Declaration of Covenants and Restrictions filed with the Erie County Clerk's Office on 4/25/03 and included as Appendix P in the Remedial Action Construction Report, Vol. II, the following Controls are in place:

A. Entire Site: i) Groundwater use prohibition, ii) Surface water use prohibition.

B. Capped Area: i) Fencing, ii) No Excavation, iii) Planting trees/shrubs prohibited.

C. Cleared Portion within the Perimeter Barrier System: i) Only Commercial/Industrial Development is allowed. Construction restrictions.

Control Description for Site No. 915043

Parcel: 82.03-4-9.12

In accordance with the Declaration of Covenants and Restrictions filed with the Erie County Clerk's Office on 4/25/03 and included as Appendix P in the Remedial Action Construction Report, Vol. II, the following Controls are in place:

A. Entire Site: i) Groundwater use prohibition, ii) Surface water use prohibition.

B. Capped Area: i) Fencing, ii) No Excavation, iii) Planting trees/shrubs prohibited.

C. Cleared Portion within the Perimeter Barrier System: i) Only Commercial/Industrial Development is allowed. Construction restrictions.

Parcel: 82.03-4-9.2

In accordance with the Declaration of Covenants and Restrictions filed with the Erie County Clerk's Office on 4/25/03 and included as Appendix P in the Remedial Action Construction Report, Vol. II, the following Controls are in place:

A. Entire Site: i) Groundwater use prohibition, ii) Surface water use prohibition.

B. Capped Area: i) Fencing, ii) No Excavation, iii) Planting trees/shrubs prohibited.

C. Cleared Portion within the Perimeter Barrier System: i) Only Commercial/Industrial Development is allowed. Construction restrictions.

Periodic Review Report (PRR) Certification Statements

1.	I certify by checking "YES" below	v that:			:	,	
	 a) the Periodic Review repreviewed by, the party making 	ort and all attachments ng the certification;	were prepared un	der the direct	ion of, an	d	
	 b) to the best of my knowle are in accordance with the re 	edge and belief, the wo	k and conclusions remedial program	described in and general	y accepte	2 a	
	: •				YES	NO	
2.	If this site has an IC/EC Plan (or or Engineering control listed in B following statements are true:	equivalent as required oxes 3 and/or 4, I certi	in the Decision Do y by checking "YE	ocument), for S" below that	each Inst all of the	itutional	
a) Cor	the Institutional Control and/or E trol was put in-place, or was last	ngineering Control(s) e approved by the Depar	employed at this sit tment;	te is unchang	ed since	he date th	at the
	nothing has occurred that would environment;	impair the ability of su	ch Control, to prote	ect public hea	lth and		
c) eva	access to the site will continue to luate the continued maintenance	be provided to the De of this Control;	partment, to evalu	ate the remed	dy, includi	ng access	s to
	nothing has occurred that would trol; and	constitute a violation o	r failure to comply	with the Site	Managen	nent Plan	for this
e) and	if a financial assurance mechani sufficient for its intended purpose	sm is required by the o	versight document ument.	for the site, t	he mecha	anism rem	ains vali
					YES	NO	
				.*			
3.	If this site has an Operation and	Maintenance (O&M) Pl	an (or equivalent a	s required in	the Decis	ion Docur	nent);
	I certify by checking "YES" below Decision Document) are being m		quirements (or equ	uivalent as re	quired in	the	• .
				A .	×		
١.	If this site has a Monitoring Plan						
	I certify by checking "YES" below in the Decision Document) is being the property of the contract of the contr	that the requirements and met.	of the Monitoring F	Plan (or equiv	alent as r YES	equired NO	
				•	×		•
	· · · · · · · · · · · · · · · · · · ·			·			

IC CERTIFICATIONS SITE NO. 915043

Box 6

SITE OFM MANAGER

SITE-OWNER OR DESIGNATED REPRESENTATIVE SIGNATURE

I certify that all information and statements in Boxes 2 and/or 3 are true. I understand that a false statement made herein is punishable as a Class "A" misdemeanor, pursuant to Section 210.45 of the Penal

Town of CHEEKTOWAGA ENGINEERING DEPT

275 ALEXANDER AVE.

print name

Town of CHEEKTOWAGA ENGINEERING DEPT

275 ALEXANDER AVE.

print business address am certifying as 5 TE 0 m MANAGEN (Owner or Remedial Party)

for the Site named in the Site Details Section of this form.

W-R. M Signature of Owner or Remedial Party Rendering Certification

SITE Of M MANAGEN 2/8/10 Date

IC/EC CERTIFICATIONS

Box 7

QUALIFIED ENVIRONMENTAL PROFESSIONAL (QEP) SIGNATURE

I certify that all information in Boxes 4 and 5 are true. I understand that a false statement made herein is punishable as a Class "A" misdemeanor, pursuant to Section 210.45 of the Penal Law.

TOWN OF CHECK TOWAGA ENGINEERING DEPT.

275 ALEXANDER AVE.

print name

TOWN OF CHECK TOWAGA ENGINEERING DEPT.

275 ALEXANDER AVE.

print business address

SITE OF M PROVIDER/MANAGEN

(Owner or Remedial Party) for the Site named in the Site Details Section of this form.



2/8/10

Signature of Qualified Environmental Professional, for the Owner or Remedial Party, Rendering Certification

Stamp (if Required)

SITE Of M PROVIDER/MANAGER