The electronic version of this file/report should have the file name:

Type of document.Spill Number.Year-Month.File Year-Year or Report name.pdf

report. hw915053 1997 -03-01. IRM MONITURING. pdf
AND MAINTENANCE REPORT

Project Site numbers will be proceeded by the following:

Municip**a**l Brownfields - b

Superfund - hw

Spills - sp


ERP - e

VCP - v

BCP - c

non-releasable - put .nf.pdf

Example: letter.sp9875693.1998-01.Filespillfile.nf.pdf



IRM MONITORING AND
MAINTENANCE REPORT
ANNUAL REPORT 1997
STRIPPIT, INC.
AKRON, NEW YORK
NYSDEC SITE NUMBER 9-15-053

Prepared by:

Day Environmental, Inc.

2144 Brighton-Henrietta Town Line Road

Rochester, New York 14623

Prepared for:

Strippit, Inc.

A Unit of IDEX Corporation 12975 Clarence Center Road Akron, New York 14001

Date:

March, 1997

## TABLE OF CONTENTS

1.0	INTR	ODUCTION	1
2.0	GROU	JNDWATER SAMPLING PROCEDURES	1
3.0	GROU	JNDWATER ELEVATIONS	2
4.0	ANAL	YTICAL LABORATORY RESULTS	3
5.0	SITE	INSPECTION REPORT FEBRUARY 6, 1997 SAMPLE ROUND	4
6.0	DISC	USSION	4
Figure		Locus Plan	
Figure		Site Plan	
Figure	e 3 e 4	Groundwater Contour Map: April 11, 1995 / May 8, 1996 Groundwater Contour Map: October 16, 1995 / October 29, 1996	
Apper	ndix <b>A</b>	February 6, 1997 Sample Round: ACTS Testing Labs, Inc. Report and Chair of-Custody Documentation	n-
Apper	ndix <b>B</b>	February 6, 1997 Sample Round: Monitoring Well Sample Logs	
Apper	ndix <b>C</b>	Summary of Detected Parameters, Mean Concentrations and Standar Deviations	rd
Apper	ndix <b>D</b>	Site Inspection Report	

### 1.0 INTRODUCTION

Strippit, Inc., a Unit of IDEX Corporation (Strippit), has implemented an Interim Remedial Measure (IRM) approved by the New York State Department of Environmental Conservation (NYSDEC) at a former disposal area (Site) located south of their facility at 12975 Clarence Center Road in Akron, New York (see Locus Plan, Figure 1). As outlined in the NYSDEC's March 1995 Record of Decision (ROD), post-closure monitoring and maintenance is required at the Site to evaluate the effectiveness of the IRM. Specific post-closure monitoring and maintenance requirements are presented in a document prepared by Day Engineering, P.C. titled Post-Closure Monitoring and Maintenance Plan; Interim Remedial Measure; Strippit, inc.; Akron, New York dated February 1995.

This annual report summarizes the results of the eight quarterly sample rounds completed at the Site between April 11, 1995, and February 6, 1997 and includes a statistical evaluation of data collected during these rounds to compare downgradient concentrations to upgradient concentrations. This report also includes a discussion of groundwater flow conditions, the results of the February 6, 1996 inspection of the Site and a discussion of the long-term groundwater monitoring completed to date.

#### 2.0 GROUNDWATER SAMPLING PROCEDURES

A site plan, showing the location of the monitoring wells at the Site is included as Figure 2. Groundwater sampling initially included the measurement of static water levels in each of the wells (designated GW-1 through GW-5). Following these measurements, water was purged from each well using a dedicated bailer. Typically the wells were purged until a volume of water equal to approximately three well casings was removed or until the wells were dry. The wells were then allowed to recover so that "fresh" water was retained for testing.

Groundwater samples were collected for testing using a dedicated bailer which is permanently stored above the water within each well casing. Each of the samples collected for subsequent testing was given a unique field sample code. A typical code is shown below.

02067-GW-1

Where:

02067 = sample date GW-1 = sample location The analytical laboratory also assigned lab numbers to each of the samples to track the samples throughout the testing process (refer to the analytical laboratory report for the February 6, 1997 sample round included in Appendix A).

The initial groundwater samples collected from each well were typically tested in the field for the following parameters using the equipment listed below.

- pH: Cole-Parmer Model 05985-80 Digi-Sensit pH Meter
- Specific conductance and temperature: Cole-Parmer Model 1481-5 Conductivity/Temperature Meter
- Turbidity: LaMotte Model 2008 Turbidity Meter

Following the field testing, samples were collected for analytical testing. These laboratory samples were placed in pre-cleaned containers provided by the analytical laboratory. The analytical laboratory added necessary preservatives to the containers before they were delivered to the Site.

The containers for volatile organic compound (VOC) testing were filled first. The remaining sample containers were filled by placing approximately equal amounts of sample from the bailer into each sample container until the container was filled. When the containers were filled they were placed in a plastic cooler containing ice and stored in a locked field vehicle until they were picked up by the analytical laboratory for testing. Chain-of-custody documentation was maintained throughout the sample collection process. Copies of the executed chain-of-custody forms for the February 6, 1997 sample round are included with the test results in Appendix A.

Copies of the monitoring well sample logs for the February 6, 1997 sample round are included in Appendix B (documentation for previous rounds was submitted in earlier quarterly reports). These logs summarize in-situ measurements, groundwater depths, purging information and other relative data.

#### 3.0 GROUNDWATER ELEVATIONS AND FLOW PATTERNS

During each sample round, the depth to groundwater was measured from a monitoring point elevation established on the top of each well casing using an electronic tape water level indicator. The groundwater depths and elevations measured during each of the sample rounds are included in the table in Appendix C.

Groundwater contour maps for the April 11, 1995 sample round (i.e., seasonally high groundwater elevations) and the October 16, 1995 sample round (i.e., seasonally low groundwater elevations) are included as Figures 3 and 4, respectively. These maps also

include groundwater contours for comparable sample rounds conducted in 1996 (e.g., the April 11, 1995 map also includes data collected during the May 8, 1996 sample round and the October 16, 1995 map also includes the data collected during the October 29, 1996 sample round). As indicated by the contour maps, monitoring wells GW-2 and GW-5 are located in apparent upgradient positions and the remaining wells (GW-1, GW-3 and GW-4) are located in downgradient positions relative to the IRM fill area and wells GW-2 and GW-5. As depicted on Figures 3 and 4, the direction of groundwater flow is generally to the north (i.e., towards GW-4) and the northwest (i.e., towards GW-1 and GW-3). While the groundwater elevations are higher in all wells during 1996, compared to 1995, the groundwater flow directions are generally comparable.

### 4.0 ANALYTICAL LABORATORY RESULTS

During the February 6, 1997 sample round, groundwater samples were collected from each of the five monitoring wells (i.e., GW-1 through GW-5). A duplicate sample, designated "DUP", was collected from monitoring well GW-4. A trip blank, designated "TRIP", was prepared by the analytical laboratory and handled/transported similarly to the other test samples. All samples were analyzed by ACTS Testing Labs, Inc. (ACTS) of Buffalo, New York for the following parameters.

- TCL Volatile Organic Compounds via USEPA Method 8240
- Total phenols via applicable procedures listed in "Standard Methods for the Examination of Water and Wastewater," 18th Edition
- Total and Soluble Barium, Cyanide, Iron, Magnesium and Manganese via applicable procedures listed in "Standard Methods for the Examination of Water and Wastewater," 18th Edition.

Each sample was analyzed for the complete list of parameters presented above, except the trip blank which was only analyzed for TCL VOCs. ACTS filtered a portion of unpreserved sample from each test location using a 2-micron filter to create the "soluble" sample for testing. A copy of ACTS report for samples collected on February 6, 1996 is included in Appendix A.

Field and analytical test parameters measured above applicable detection limits reported by the analytical laboratory during any of the quarterly sample rounds and applicable mean and standard deviation values for these parameters are summarized in the tables presented in Appendix C. Groundwater elevations measured during each sample round are also included on these tables.

### 5.0 SITE INSPECTION REPORT FEBRUARY 6, 1997 SAMPLE ROUND

A copy of the site inspection report completed during the February 6, 1997 sample round is included in Appendix D. Copies of photographs, showing the condition of the Site at the time of the inspection are also included in Appendix D.

#### 6.0 DISCUSSION

When groundwater elevations measured in the monitoring wells at the Site for comparable sample rounds are reviewed [e.g., comparing the first (spring) sample round of 1995 to the first sample round of 1996], it is evident that the groundwater level elevations were higher in all wells during 1996 events than they are in comparable 1995 events. These groundwater levels ranged from between about 1.6 feet higher (GW-1 during the first annual sample rounds) to 4.7 feet higher (GW-5 during the third sample rounds). It is also evident that the increases are higher during the second and third sample rounds (i.e., summer and fall, respectively) averaging about 3.8 feet than during the first and fourth sample rounds (i.e., spring and winter, respectively) averaging about 2.2 feet.

Despite the variation in groundwater elevations, the pattern of groundwater flow remained similar when 1995 and 1996 data are compared (i.e., flow towards the north-northwest, refer to Figures 3 and 4).

A review of the mean concentrations for the detected parameters indicates that the majority of the inorganic compounds detected were measured at concentrations below Class GA standards established in 6 NYCRR Parts 700-705 for potable groundwater supplies. Mean values exceeding these standards include total iron in all wells and soluble iron in wells GW-1, GW-3, GW-4 and GW-5. The mean concentration for total magnesium exceed Class GA standards in wells GW-1, GW-3 and GW-4. Only the mean concentrations of soluble magnesium in wells GW-1 and GW-4 exceed Class GA standards. The mean concentration of methylene chloride in each well exceeded the Class GA standards. However, methylene chloride was typically detected in blank samples and, as such, the presence of elevated concentrations of methylene chloride may not be representative of site conditions. No mean concentration for other volatile organic compounds or semi-volatile organic compounds exceed the Class GA standards. The mean pH values measured in the upgradient wells (GW-2 and GW-5) are elevated (i.e., they exceed 8.5 standard units). However, elevated pH values were not measured in downgradient wells, although well GW-1 had a mean pH concentration of 8.45.

To assess groundwater quality variations at the Site, the mean concentrations for parameters detected in upgradient wells (i.e., GW-2 and GW-5) were initially compared to the mean concentrations of detected compounds in downgradient wells (i.e., GW-1, GW-3 and GW-4). To complete this evaluation, the upgradient wells were grouped to establish a single "background" concentration for each of the detected parameters and this background value was compared to the mean concentrations in each of the downgradient wells. This comparison indicates that the mean concentration in the downgradient wells for the following parameters exceed the background concentration:

- Specific conductance in wells GW-1 and GW-4
- total and soluble magnesium in wells GW-1, GW-3 and GW-4;
- total manganese in well GW-3;
- soluble manganese in wells GW-1, GW-3, and GW-4;
- total phenols GW-3;
- carbon disulfide in well GW-3;
- 2-butanene in well GW-3;
- chloroform in well GW-3;
- methylene chloride in wells GW-3;

The mean concentration of the other detected compounds in the downgradient wells is less than or comparable to background concentrations.

To evaluate if the apparent increase in the above downgradient wells is statistically significant, a Student's T-test at the 0.05 level of significance was completed. Generally, this test included the comparison of the background concentration calculated for wells GW-2 and GW-5 to the mean concentrations for the above parameters/wells utilizing the following:

$$t = \frac{X_1 - X_2}{s (1/n)^{1/2}}$$

Where the background concentration  $(X_1)$  is compared to the mean concentration in downgradient wells  $(X_2)$  and s is the standard deviation and n is the number of samples from the downgradient sample set. If t is greater than a published critical value of t (based on the degrees of freedom, n - 1 and  $\alpha = 0.05$ ), the increase in the downgradient wells is considered to be statistically significant.

The results of the t-tests indicate that only the increases in the downgradient mean concentration of total and soluble magnesium in wells GW-1, GW-3 and GW-4, and the mean concentration of total manganese in GW-3 are statistically significant. All of the other compounds evaluated during the t-testing were determined not to be statistically significant.


Based upon the above evaluation, magnesium (and potentially manganese in well GW-4) appears to have caused a degradation of groundwater quality in positions downgradient of the Site. A comparison of the data collected in 1996 to the data collected in 1995 indicates that only the total and soluble magnesium concentrations measured in samples from GW-1 exhibited a statistical increase during the 1996 monitoring rounds. The total and soluble magnesium concentrations measured in samples from GW-3 and GW-4 and the total and soluble concentrations measured in samples from GW-3 either decreased or exhibited a statistically insignificant increase in 1996 compared to 1995.

Monitoring of the IRM closure, during the February 6, 1997 sample round, indicates that the cap system is in relatively good condition. While some of the cap was covered with snow, no significant areas of degradation were observed.

In addition, the monitoring wells and the gas well are in relatively good condition and their surface seals appeared to be adequate.

The next scheduled monitoring round is on or about May 6, 1997. Based upon the results of the work completed to date, it is recommended that quarterly monitoring continue for at least one more year and that water samples continue to be tested for the current parameter list. Following the review of the upcoming years sample results, consideration should be given to reducing the sampling frequency to bi-annually and to reducing the required parameter list.

FIGURE 1
LOCUS PLAN



PROJECT NO. 09385-96

FIGURE 1

SHEET 1 OF 1

PROJECT TITLE
STRIPPIT, INC.
AKRON, NEW YORK

GROUNDWATER MONITORING
DRAWING TITLE
LOCUS PLAN

DAY ENVIRONMENTAL, INC.

ENVIRONMENTAL CONSULTANTS ROCHESTER, NEW YORK DATE 3/19/97


DRAWN BY

SCALE

1" = 2000


FIGURE 2

SITE PLAN




## FIGURE 3

GROUNDWATER CONTOUR MAP: APRIL 11, 1995 / MAY 8, 1996



## FIGURE 4

GROUNDWATER CONTOUR MAP: OCTOBER 16, 1995 / OCTOBER 29, 1996



## APPENDIX A

ACTS TESTING LABS, INC REPORT & CHAIN-OF-CUSTODY DOCUMENTATION FEBRUARY 6, 1997 SAMPLE ROUND



## ACTS TESTING LABS, INC.

3916 Broadway Buffalo, NY 14227-1104 Tei (716) 684-3300 Fax (716) 684-3303

FEB 2 6 1997

Technical Report #6B-00974E

Project Name: Strippit: Long Term Monitoring

Porject # 09385-96

February 21, 1997 Page 1 of 5 ELAP ID# 10247

Mr. Ray Kampff DAY ENVIRONMENTAL, INC. 2144 Brighton-Henrietta Townline Rd Rochester, NY 14623-2700

### SUBJECT:

Analyses of seven (7) water samples received on February 6, 1997.

#### **RESULTS:**

See Pages Two through Five.

#### EXPERIMENTAL:

The analyses were determined according to "Standard Methods for the Examination of Water and Wastewater," 18th Edition.

"Test Methods for Evaluating Solid Waste: Physical/Chemical Methods," SW-846, 3rd Edition, September 1994.

ACTS TESTING LABS, INC

Charles E. Hartke

Manager, Chemistry Laboratory

ACTS TESTING LABS, INC.

Elizabeth R. Hausler, Supervisor Gas Chromatography Laboratory

ACTS TESTING LABS, INC.

Lisa M. Clerici, Supervisor Wet Chemistry Laboratory

cme

This report is intended for your exclusive use. Any copying or replication of this report to or for any other person or eristy, or use of our name or trademark, is permitted only with our written permission. Our report is kim samples identified herein. The results set forth in this report are not necessarily indicative or representative of the statistical questry or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof. You shall have thirty days from receipt of this report to request additional testing of the samples or to constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents



February 21, 1997 Technical Report #7B-00974E Page 2 of 5

<b>RESULT</b>	<u>S</u>
---------------	----------

KEGGETO.			
	ACTS #7B-00974E	ACTS #7B-00975E	ACTS #7B-00976E
	<u>02067-GW-3</u>	02067-GW-4	02067-GW-1
pН	7.63	8.08	8.55
Barium, Sol <b>ub</b> le	0.066	0.049	0.033
Barium, Tot <b>al</b>	0.083	0.083	0.041
Iron, Solubl <b>e</b>	0.12	0.22	0.04
Iron, Total	2.37	4.52	1.00
Magnesium, Soluble	<b>29</b> .7	40.2	63.0
Magnesium, Total	<b>32</b> .9	50.9	65.6
Manganese, Soluble	0.148	0.026	0.015
Manganese, Total	· 0.148	0.104	0.041
Phenois	< 0.005	0.018	< 0.005
Conductivity	342	792	870
	ACTS #7B-00977E	ACTS #7B-00978E	ACTS #7B-00979E
	<u>02067-GW-2</u>	02067-GW-5	02067-DUP
pH	11.31	10.90	8.33
Barium, Sol <b>ub</b> le	0.115	0.056	0.050
Barium, Tot <b>al</b>	0.127	0.114	0.059
Iron, Soluble	0.34	0.64	0.23
Iron, Total	0.41	8.67	1.22
Magnesium, Soluble	0.089	5.42	39.1
Magnesium, Total	0.342	18.6	41.4
Manganese, Soluble	800.0	0.016	0.035
Manganese, Total	0.009	0.218	0.047
Phenois	0.005	0.005	0.006
Conductivity Conductivity	244	286	694

Results, except pH and Conductivity, are reported as mitligrams per liter (mg/L).



February 21, 1997 Technical Report #7B-00974E Page 3 of 5

	ACTS #7B-00974E	ACTS #78-00975E	ACTS #7B-00976E
TCL VOLATI <b>LE</b> S	02067-GW-3	02067-GW-4	02067-GW-1
Dichlorodiflu <b>oromet</b> hane	< 1.0 (< 1.0)*	< 1.0	< 1.0
Chlorometha <b>ne</b>	< 1.0 (< 1.0)*	< 1.0	< 1.0
Vinyl Chlorid <b>e</b>	< 1.0 (< 1.0)*	< 1.0	< 1.0
Bromometha <b>ne</b>	< 1.0 (< 1.0)*	< 1.0	< 1.0
Chloroethane	< 1.0 (< 1.0)*	< 1.0	< 1.0
1,1-Dichloroethene	< 0.5 (< 0.5)*	< 0.5	< 0.5
Acetone	< 5.0 (< 5.0)*	5.0	< 5.0
Carbon Disu <b>lfid</b> e	< 0.5 (< 0.5)*	< 0.5	< 0.5
Methylene C <b>hlo</b> ride	< 5.0 (< 5.0)*	< 5.0	< 5.0
trans-1,2-Dichloroethene	< 0.5 (< 0.5)*	< 0.5	< 0.5
1,1-Dichloroe <b>th</b> a <b>ne</b>	< 0.5 (< 0.5)*	< 0.5	< 0.5
Chloroform	< 0.5 (< 0.5)*	< 0.5	< 0.5
1,2-Dichloroethane	< 0.5 (< 0.5)*	< 0.5	< 0.5
2-Butanone	< 2.0 (< 2.0)*	< 2.0	< 2.0
1,1,1-Trichlo <b>ro</b> eth <b>a</b> ne	< 0.5 (< 0.5)*	< 0.5	< 0.5
Carbon Tetrachloride	< 0.5 (< 0.5)*	< 0.5	< 0.5
Benzene	< 0.5 (< 0.5)*	< 0.5	< 0.5
Trichloroethe <b>ne</b>	< 0.5 (< 0.5)*	< 0.5	< 0.5
1,2-Dichloro <b>pro</b> pane	< 0.5 (< 0.5)*	< 0.5	< 0.5
Bromodichloromethane	< 0.5 (< 0.5)*	< 0.5	< 0.5
cis-1,3-Dichloropropene	< 0.5 (< 0.5)*	< 0.5	< 0.5
4-Methyl-2-p <b>en</b> tanone	< 0.5 (< 0.5)*	< 0.5	< 0.5
2-Hexanone	< 2.0 (< 2.0)*	< 2.0	< 2.0
Toluene	< 0.5 (< 0.5)*	< 0.5	< 0.5
trans-1,3-Dic <b>hl</b> or <b>op</b> ropene	< 0.5 (< 0.5)*	< 0.5	< 0.5
1,1,2-Trichlor <b>o</b> ethane	< 0.5 (< 0.5)*	< 0.5	< 0.5
Tetrachloroe <b>thene</b>	< 0.5 (< 0.5)*	< 0.5	< 0.5
Dibromochloromethane	< 0.5 (< 0.5)*	< 0.5	< 0.5
1,2-Dibromo <b>eth</b> ane	< 0.5 (< 0.5)*	< 0.5	< 0.5
Chlorobenze <b>ne</b>	< 0.5 (< 0.5)*	< 0.5	< 0.5
Ethylbenzen <b>e</b>	< 0.5 (< 0.5)*	< 0.5	< 0.5
M,P-Xylenes	< 1.0 (< 1.0)*	< 1.0	< 1.0
O-Xylene	< 0.5 (< 0.5)*	< 0.5	< 0.5
Styrene	< 0.5 (< 0.5)*	< 0.5	< 0.5
Bromoform	< 1.0 (< 1.0)*	< 1.0	< 1.0
1,1,2,2-Tetra <b>ch</b> loroethane	< 0.5 (< 0.5)*	< 0.5	< 0.5
1,2-Dibromo-3-chloropropane	< 1.0 (< 1.0)*	< 1.0	< 1.0

Results are reported as micrograms per liter (ug/L). \*=Duplicate results



February 21, 1997 Technical Report #7B-00974E Page 4 of 5

	ACTS #7B-00977E	ACTS #7B-00978E	ACTS #7B-00979E
TCL VOLATILES	02067-GW-2	02067-GW-5	02067-DUP
Dichlorodiflu <b>or</b> omethane	< 1.0	< 1.0	< 1.0
Chlorometha <b>n</b> e	< 1.0	< 1.0	< 1.0
Vinyl Chloride	< 1.0	< 1.0	< 1.0
Bromometha <b>n</b> e	< 1.0	< 1.0	< 1.0
Chloroethan <b>e</b>	< 1.0	< 1.0	< 1.0
1,1-Dichloro <b>et</b> he <b>ne</b>	< 0.5	< 0.5	< 1.0
Acetone	19.0	< 5.0	< 5.0
Carbon Disu <b>lfi</b> de	< 0.5	< 0.5	< 0.5
Methylene Chloride	< 5.0	< 5.0	< 5.0
trans-1,2-Dichloroethene	< 0.5	< 0.5	< 0.5
1,1-Dichloro <b>et</b> hane	0.6	< 0.5	< 0.5
Chloroform	· < 0.5	< 0.5	< 0.5
1,2-Dichloro <b>et</b> hane	< 0.5	< 0.5	< 0.5
2-Butanone	< 2.0	< 2.0	< 2.0
1,1,1-Trichlo <b>ro</b> et <b>ha</b> ne	< 0.5	< 0.5	< 0.5
Carbon Tetr <b>ac</b> hloride	< 0.5	< 0.5	< 0.5
Benzene	< 0.5	< 0.5	< 0.5
Trichloroeth <b>en</b> e	< 0.5	< 0.5	< 0.5
1,2-Dichloro <b>pr</b> op <b>an</b> e	< 0.5	< 0.5	< 0.5
Bromodichlo <b>ro</b> methane	< 0.5	< 0.5	< 0.5
cis-1,3-Dichl <b>or</b> opropene	< 0.5	< 0.5	< 0.5
4-Methyl-2-p <b>en</b> ta <b>no</b> ne	< 0.5	< 0.5	< 0.5
2-Hexanone	< 2.0	< 2.0	< 2.0
Toluene	0.6	< 0.5	< 0.5
trans-1,3-Dic <b>hl</b> or <b>op</b> ropene	< 0.5	< 0.5	< 0.5
1,1,2-Trichlo <b>ro</b> et <b>ha</b> ne	< 0.5	< 0.5	< 0.5
Tetrachloroe <b>th</b> ene	< 0.5	< 0.5	< 0.5
Dibromochlo <b>ro</b> m <b>et</b> hane	< 0.5	< 0.5	< 0.5
1,2-Dibromo <b>et</b> ha <b>ne</b>	< 0.5	< 0.5	< 0.5
Chlorobenze <b>n</b> e	< 0.5	< 0.5	< 0.5
Ethylbenzen <b>e</b>	< 0.5	< 0.5	< 0.5
M,P-Xylenes	< 1.0	< 1.0	< 1.0
O-Xylene	< 0.5	< 0.5	< 0.5
Styrene	< 0.5	< 0.5	< 0.5
Bromoform	<b>&lt; 1</b> .0	< 1.0	< 1.0
1,1,2,2-Tetrachloroethane	< 0.5	< 0.5	< 0.5
1,2-Dibromo-3-chloropropane	< 1.0	< 1.0	< 1.0

Results are reported as micrograms per liter (ug/L).



February 21, 1997 Technical Report #7B-00974E Page 5 of 5

	ACTS #7B-00980E
TCL VOLATILES	TRIP BLANK
Dichlorodiflu <b>or</b> omethane	< 1.0
Chloromethane	< 1.0
Vinyl Chloride	< 1.0
Bromomethane	< 1.0
Chloroethan <b>e</b>	< 1.0
1,1-Dichloro <b>et</b> he <del>ne</del>	< 1.0
Acetone	< 5.0
Carbon Disu <b>lfi</b> de	< 0.5
Methylene Chloride	25.0
trans-1,2-Dichloroethene	< 0.5
1,1-Dichloro <b>et</b> ha <b>ne</b>	< 0.5
Chloroform	- < <b>0</b> .5
1,2-Dichloro <b>et</b> hane	< 0.5
2-Butanone	< 2.0
1,1,1-Trichlo <b>ro</b> et <b>ha</b> ne	< 0.5
Carbon Tetr <b>ac</b> hlo <b>ri</b> de	< 0.5
Benzene	< 0.5
Trichloroeth <b>en</b> e	< 0.5
1,2-Dichloro <b>pr</b> op <b>a</b> ne	< 0.5
Bromodichlo <b>ro</b> methane	< 0.5
cis-1,3-Dichl <b>or</b> opropene	< 0.5
4-Methyl-2-pentanone	< 0.5
2-Hexanone	< 2.0
Toluene	< 0.5
trans-1,3-Di <b>ch</b> lor <b>op</b> ropene	< 0.5
1,1,2-Trichlo <b>ro</b> et <b>ha</b> ne	< 0.5
Tetrachloroe <b>th</b> ene	< 0.5
Dibromochlo <b>ro</b> m <b>et</b> hane	< 0.5
1,2-Dibromo <b>et</b> ha <b>n</b> e	< 0.5
Chlorobenze <b>n</b> e	< 0.5
Ethylbenzen <b>e</b>	< 0.5
M,P-Xylenes	< 1.0
O-Xylene	< 0.5
Styrene	< 0.5
Bromoform	< 1.0
1,1,2,2-Tetrachloroethane	< 0.5
1,2-Dibromo-3-chloropropane	< 1.0

Results are reported as micrograms per liter (ug/L).

INTERNAL CHAIN-OF-CUST**ODY RECORDS**PROJECT NUMBER 09385-96
TECHNICAL REPORT NUMBER 7B-00974E
STRIPPIT LONG TERM MONITORING

1		Notebook No		
ECT		Continued Fro	m Page -	<del></del>
ما	Time	Sample 10	Int	Received by
. 97	906	7800972E	Brut	Buguthan
3 (	930	713-007656 713-009006-713-009056,713-009066-713-009066	OR	Part as
		73-009086, 73-00904E 75-00406, 73-004536, 73-00954E,		
		73.00958E, 73.00959E, 73.00964E, 713-00984E	1	1
	10 n	7800941M, 7800843M, 7800943M	LMO	( Duntes
	1045	76006525, 76008905, 7600891E, 4800678 F 7600891E	JUS	1. Sobocorphy
	,50	7B-00 889E, 7B-00890, 7B-00891	KO	Kon Present
	135	the first of the f	LKN	Contracte
	}· • ·	7301015m	inc	L.C.ERICE
	2:30	78-00965E		B HIND
	7	7800 0150		
7-97	520	7800933E, 7800964E, 7800990E, 7801009E, 7801033E,	105	1. Sobocinsh
7/	3	7801034E 780105/E 7801052E	1	ka-1
	y 55		K.O	450 (M. H.)
	910	7B-00 994E, 7B-00 995	JOS	
	7	7800851E, 7800853E, 7800965E, 7800953E, 7800954E,	1	L
	1015	7801035E, 7801036E, 7801037E, 7801036E	BUH	B ZLOS
	10,	760036 4 760037 2500 0097 4 760037 1760037 1960037 1960037 1960037 1960037 15000037 15000037 15000037 15000037 15000037 15000037 15000037 15000037 15000037 15000037 15000037 15000037 15000037 15000037 150000037 15000037 15000037 15000037 15000037 15000037 15000037 150000037 150000037 150000037 150000037 150000037 150000037 150000037 150000037 1500000037 1500000037 15000000000000000000000000000000000000		
	10 35	713-004166, 73-009176, 713-009306, 713-009316, 713-009446	Ou	Photof Red
= -	10	7/3-008956	1	
	1,00	7801016E, 7801039E; 7801040E, 7801041E, 7601043E,	105	1. Solvensh
		7801043E	1	1 / 2/
	1115	7B-00925E, 7B-01011	K-C	3 Jaur Byly.
	35	78-01060M	LUC	) L. Dustin
	150	Bolowan	Sa	Florit Ben
	50	1301001E, 7301005E, 7301003E	fet	Stateoli
	215	76-00888 715-00928 78-00926 78-00975	DA	10.Um
	-9	78-009296,78-009206,76000197600006,78-010036	1 +	
	215	7B. 009586 7B. 009546, 7B. 009646, 73-009876, 7B-00966	G Coth	MITTING
		7/3-009896, 7/3-009846		10 4-1
	1400	700 106 m	JAG.	> Hen A Sex
-97	710	78-01073H, 78-01073H. 78-01074H, 7601075H, 7601075	1/40	faun Dest
<u>→</u> ····(; /	940	7801079m, 7821050 m, 7621057m	744	3 touth by
	945	7801054E 7801055E 7801069E 7801070E, 7001071E	103	J. Sobocinan
	1010	70-01082M, 7A-01083M 70-01084M. 78-010157M	unu	11- Butu
			Co	ontinued on Page
	,	Read and Understood By		
_				

:CT		Continued			
s with by Initial	Comments				Initial
	Phow Sent to Life Science	es		که ب	BIMH
	755		2-7-47	1030	Cal
			1	7	
<u> </u>					
				10'	uno
diends en	Rogic Ford Mills		2-7-97	1,50	JOS
	3050 Metals		2-7-92	200	KU
	semi-Volat			135	40
Edwards ou	Lega		2-7-47	-/	
	meas -		7007	405	BM
	NHJU	_	27-97	7	13' 0-
				:36	0.5
	Metals			10 30	205
			<i>L</i>		<u> </u>
	625		2-10-97		K.0
	COO		2-10-97	130	JOS
			1		
	Pherols				
	O+6 (Deplated)		2-10-47	1130	Other
			1-1-		
	Phos		2-10-97	200	JAS
	<b> </b>		V	1	
	625		2-10-91	1130	KU.
	602110		2-10-97	1/31	L14/)
diands com	Zoc,10		240-97		LAND,
			2 1077	220	ITU
	(a)/62 Viels	of 3 diglet d	20-17	360	DAV
	7		4	<u> </u>	14
	7.05		2-10-47	3000	(372)
	1		1 1	1-1-	14
Vando Cr	1000		2-10-17	400	1 ATT-0
wards ca	Loga		2-11-97		(40)
durando Ca	736		2-11-97		1 Lav
	Metals		2-11-97	1/30	7
Edwards cu	Lognin		2-11-9	10 10	490
curino co	+ ~ · · · · · · · · · · · · · · · · · ·		Cor	ntinued on Pa	ge
	Read and	Understood By			
		Signed			Date
Signed	Date				

4		Notebook No Continued From	
ROJECT			Ivit Received lan
I te	Time	Dangle 13	
-1-97	10 45 -	DOMATION	Per fillela brote
	1,00	7801078E 7801078 /801078 / 7801079	JOS J. Sobocinoln.
		780026 E, 7801027E, 7801028E, 7801029E	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	1"	7/3-CCP446 7/3-OCF45E, 713-00/01015 713-010736.	well the
		73-01050E, 73-010536, 73-01061E, 73-010621-	+ + + //
	المحادث	78-01065E 7B-01066E, TB-01067E, 73-00950E	The Country
	7 7	78-100007 7B0 1054E 7B0 1055E	for total from
	210	180 108mm, Briosen, 3-0108m 780109cm 780109mm	Ap Lange &
	7	7801092m 7801093m	1 4
		seniorum resporta resportan resportan	
	245	7800984E, 780087E 7800986, 7800989E 7800370E	JOS J. Sobocina
	1	7801033E 7801050E, 7801054E, 7801054E	100
11	410	3-01101m, 7Ballom, 7Ballo3m, 7Balloum	Jas Joint
	7	BUILDSM 7BOILDON	4
~ 12 17	8:55	78-01030E, 78-01031E, 78-01032E	Lac CCEPTES
	945	7801107M	THE TOTAL STATE OF THE PARTY OF
	945	7B-009646, 7B-009326, 7B-009376, 7B-0047346	To Chif Jove
	1	713-008356 713-008366	
	1000	7801098E, 780109E, 7801100E, 7800774E, 780095E	JOS / Solocusch
	1000	76001848 78009538 78009946, 1800912E,	JAD J. Solversk
		7801039 7801040E 7801041E 7801043E 1801043E	
	11:30	7801112M 7801113M 7801114M 7801111111	Mi L Doctor
	1200	760090 78 7891 760 889, 76099 1, 760915, 7609 25	BMH Buy sto
1	1230	7B01012 78:039,7B1040,7B1041,7B1042,7B1043,7B0763	
	1235	780,061,780,065 780,058 .780,110	0-0-1/2
	1250	78-01171x, 78-01113111	347 der 1.
	105.	78-00927E7B-CORDIE7B-CO922E, 730197676 OILLE	Str. Carry
	330	780126M	SUN
	325	7B-0097467B-009755,7B-0097657B-00977E,	Our De Crun
	<u> </u>	7B-00978E, 7B-00979E, 7B-00980E	CT 101+10
	330	713 -010616, 713-01063E, 713-011206, 713-011296,	1 (2)
	L	713-011306, 713-011316, 713-011336	
	1_1		105 / Salarcanos
	2-137	780116E, 7801130E, 7801133E	IMPO TO A
	<b>Browner</b>	7001134M, 78-01135M 78-01136M	Continued on Page
	1		1 1. 1
-		Read and Understood By	

Date

CT			Continued	From Page		. 1
ą	wheel beg	Initial	Comments	Date		Initial
T	3		$< \omega$	1-11-97	11,0	MY
	<u>-: .                                   </u>		Metals (3050)	2-11-97	1230	JOS
			7 (50)		<i>Y</i>	
				2-11-47	200	etal
	,	<del></del>	7>			
	I			1/1/22		7-1
		<del>-</del>	9270 A TUI EXPERTION	3/11/27	730	626
			Δ	27/1=1	210	EAG
<u>40</u>	sands	cu	Log iù	241-87		1
	4	<i>-</i>	<u> </u>	V		V
	1	4			O (2)	105
			PhOS / 78009STE, 7000SEE.	2-11-27	5	JOS
			Depleted + > 7800985E, 78009706)	<u> </u>	ايـا	
*	ands	Che	Lan	2-11-97	410	SAB
	7	4	*		<u> </u>	<u> </u>
			TCCP	<u> </u>		00
	evarde	nu	20910	2-12-18	445	448
_5=74	معدد من رس		O+6 (deplected)	2-12-47	10 >0	aw
	<del></del>	-	1 (25)	1 2		1
₩.	-i <del>ii</del>		Metals	2-12-24	1130	105
			COO	2-12:74	200	105
					<b> </b>	<u> </u>
نسنو	10000		Kelgin	3127	1 30	UD
F	Jac. Co	1		2 -12-97	1230	BMH
-			TKN	2-17-97	1275	BMH
	ا الشاريطين السياسطين العالم			2-12-57	100	BMH
			NH3N	2-1297	1257	PAB
<b>B</b> .			(es/vo) vials lofd deplec	1	230	DAU
500	<u> </u>		- 120	212-1	373	7193
	Jando	Ca.	Logich 12 to 12 do do to	27277	400	DAV:
			gayo wals lota depleted		4	4
	<u> </u>		BOD /73-011004 deplated)	2-12.9	500	CAL
			130D (73-011206 deplated)		1	2
				-		
			M 1 6 51 04 11.15	2-13-9	7 1030	JOS
		_   _	Metals, Flanh pt-11166	2-13-9	7 gur	cro
4	Links	Cu-	7030		ntinued on Pa	
			Read and Understood By			
_		ned	Date Signed			Date
	Dig	,				

CHAIN-OF-CUSTODY RECORDS
PROJECT NUMBER 09385-96
TECHNICAL REPORT NUMBER 7B-00974E
STRIPPIT LONG TERM MONITORING



## **CHAIN OF CUSTODY RECORD**

(Instructions on Reverse)

Company Name:	Address:	¢ş:	<b></b>			
Day Environmental	10 m		Remarks:	ast al		
Report Recipient:				i.		
Ray Kampff Phone #	8 to 5 to	(1) (1)	Sam	plas for	- pH	92/
	Project Name:	LongTorm				
292-1090	Strpp	tong Trom	Speci	fic long	uc tanc	
292-0425	Droige X	85-96	invida	lition to	Daga	13/1/
Samplers: (Signature)	3.070	00-76	7		1-4100000	5715 FRA
Samplers, (agrature)			Preservation	1/2 / Sal	\$	·
SAMPLE TYPE	3		引 [3]表	Test Re	quested/Analys	is'th
	2 5 5 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		ers ers		ا ت	14.1 1-mg
				3 360	1 2	'A
DATE TIME OO MATRIX	ACTS#	SAMPLE ID	CODITAT	3/2/2/ 5	1 6 7	) No. 10
8 8	(for Lab use only)	· ·		126 36 126		
		$\mathbb{R}_{q}$	(5 ) =	5000000000	6	20
	7		#	K 128 150	1 1	
2/6/96 1150 X GW	37 CPO0-81	02067-GW-3	5	<u>X X X -</u>	X	9
1220 X	7800975E	02067 -GW-4		XXX	X	เหล
1308 X	1 1	02067 - GW-1	5 / .	XXX	X	
5 1330 X X		02067-GW-2	4 8	XXX	XEX	<u>ب</u>
V 1355 X V		02067-GW-5		XXX	X	N
		and the second of the second o	<del>                                     </del>	13 3	· <del>   </del>	<u> </u>
V	7800979E	02067 - DUP		$\Delta \mid X \mid X$	XX	
					-	<u>つ</u>
	7B-10980E	Trip Blank	2	× :	ا ب	, <b>4</b> h
	24.			<u> </u>	· ***	>> ••••
3	•	15 15 15 15 15 15 15 15 15 15 15 15 15 1	·			
Relinquished By (Signature)	Date/Time: 2/6/971	Received By: (Signature)	F پ	Relinquished By Signatu	(Sec)	<b>4</b> 1
( famet	4619711	KNAT WILL		LABOUNN)	3/ 5	20.10.7
Date/Time: Received at Laboratory By: (Signature)	gnature)	ACTS Testing Labs	i, Inc.	cy "- y six		¥ 8
3:00 pm	, jt	Attn: Sample Custo	•	Quote #:	<del>4</del> <del>2</del> 1	51 W
3:00 pm / Chady Edu	toda		o, NY 14227 🛚 🗸	PO #:		
Jan Cary		ph: 716-684-3300 fax: 71			· · · · · · · · · · · · · · · · · · ·	Si isi isi

Distribution: White - Report

Yellow - Laboratory

Pink - Client/Field Technician

SAMPLE RECEIPT CHECKLIST PROJECT NUMBER 09385-96 STRIPPIT LONG TERM MONITORING



## CHEMISTRY LABORATORY SAMPLE RECEIPT CHECKLIST

Client	:	Date:
Conta	act:	Phone:
Addre	PSS:	Fax:
Ched	ked B <b>y</b> :	
Samp	ole Gr <b>ou</b> p <b>N</b> umber: 78-00974E, 78-009	15E, 7600976E, 7800977E, 780097
1.	Air Bill Sticker/No. always absent unless otherw	rise noted. 7800975E7 7800980E
2.	Shipping container condition intact unless other	wise noted.
3.	Sample custody seals absent unless otherwise	noted.
4.	Sa <b>m</b> ple Labels	Present/Absent
5.	Chain of Custody Records	Present/Absent
6.	Sample Condition	Intact/Broken/Leaking
7.	Does information on the Chain of Custody correspond with Sample Labels	Xes/No
8.	Does information on the Chain of Custody correspond with Login Sheet	<b>Y</b> es/No
9.	Sample properly preserved	Yes/No
	Sulfite NaOH + Zinc Acetate  Metals with HNO <sub>3</sub> Metals with Optima HNO <sub>3</sub> Cyanide with NaOH + Ascorbic Acid  COD with H <sub>2</sub> SO <sub>4</sub>	Phenols with $H_2SO_4$ Oil & Grease with $H_2SO_4$ TPO <sub>4</sub> with $H_2SO_4$ Ammonia, TKN with $H_2SO_4$
10.	Irre <b>g</b> ula <b>rit</b> y	Sample Number:  Discrepancy:  Sample Number:
11.	Da <b>te</b> Contacted:	Discrepancy:
12.	Corrective Action Taken:	
	- 1/ Del 781	<del>\( \)</del>

## APPENDIX B

MONITORING WELL SAMPLE LOGS JANUARY 22, 1996 SAMPLE ROUND

## DAY ENGINEERING MONITORING WELL SAMPLING LOG

Gw-1

SECTION 1										
SITE LOCATION: 5 + rippit Inc. Akron, N.Y. JOB #: 09385-96										
PROJECT NAME: IRM Past-Clasure Maniforing DATE: 2/6/97										
SAMPLE C	SAMPLE COLLECTOR(S): R. Kampff									
WEATHER CONDITIONS: OverCast 20°F										
SECTION 2 - PURGE INFORMATION										
DEPTH OF WELL [FT]: 58.5 (MEASURED FROM TOP OF CASING - T.O.C.)										
STATIC WATER LEVEL (SWL) [FT]: 39.3 (MEASURED FROM T.O.C.)										
DEPTH OF WATER COLUMN [FT]: 19.2 (DEPTH OF WELL - SWL)										
CALCULATED VOL. OF HO PER WELL CASING [GAL]: 3./										
CALCULATIONS: <u>CASING DIA.(FI)</u> <u>WELL CONSTANTYGAL/FI)</u> <u>CALCULATIONS</u>										
2" (0.1667) 0.1632 VOL OF H <sub>2</sub> 0 IN CASING = DEPTH OF WATER COLUMN 4" (0.3333) 0.6528 <u>x Well Constant</u> 6" (0.5000) 1.4688										
CALCULATED PURGE VOLUME [GAL]: (3-5 TIMES CASING VOLUME - SPECIFY)										
ACTUAL VOLUME PURGED [GAL]: 8 9 0 1/005 (DRY)										
PURGE METHOD: Bailer PURGE START: 1030 END: 1059										
SECTION 3 - SAMPLE IDENTIFICATION										
SAMPLE ID #	TIME	SAMPL METHO		ANALYTICAL SCAN(S)		SAMPLE APPEARANCE				
02067-	1305	Bai	ler	see Coc						
SECTION 4 - SAMPLE DATA										
SWL (FT)	TEMP (°C)	рН	CONDUCTIVIT (uMHOS/CM)	•	TURBIDITY (NTU)	VISUA	C.	PID/FID READING		
53.3					30=	Cloudy				
					· - <del></del>			PARTICIPATION		

# DAY ENGINEERING MONITORING WELL SAMPLING LOG

GW-2

SITE LOCATION: Stripp; Troc. Akron, N.V. JOB \$: 09385-96 PROJECT NAME: IRM Post-Closure Monitoring Date: 2/6/97  SAMPLE COLLECTOR(S): R. Kompff WEATHER CONDITIONS: Over as the condition of the	SECTION 1										
FROJECT NAME: IRM Past-Claure Monitoring Date: 2/6/97  SAMPLE COLLECTOR(8): R. Kampth  WEATHER CONDITIONS: Our Cast 20°F  SECTION 2 - PURGE INFORMATION  DEPTH OF WELL [FT]: 78.6 (MEASURED FROM TOP OF CASING - T.O.C.)  STATIC WATER LEVEL(SWL) [FT]: 49.4 (MEASURED FROM T.O.C.)  DEPTH OF WATER COLUMN [FT]: 29.2 (DEPTH OF WELL - SWL)  CALCULATIONS: CASING DIAGFD WELL CONSTANTIGAL FD  2 (0.1667) 0.162 (0.162) (OLOTH 19 IN CASING - DEPTH OF WATER COLUMN 14 (0.1333) 0.652 (0.1628) (OLOTH 19 IN CASING - DEPTH OF WATER COLUMN 14 (0.1333) 0.652 (0.1628) (OLOTH 19 IN CASING - DEPTH OF WATER COLUMN 14 (0.1333) 0.652 (0.1628) (OLOTH 19 IN CASING - DEPTH OF WATER COLUMN 14 (0.1333) 0.652 (0.1628) (OLOTH 19 IN CASING - DEPTH OF WATER COLUMN 15 (0.1628) (OLOTH 19 IN CASING - DEPTH OF WATER COLUMN 16 (0.16328) (OLOTH 19 IN CASING - DEPTH OF WATER COLUMN 17 (0.16328) (OLOTH 19 IN CASING - DEPTH OF WATER COLUMN 18 (0.16328) (OLOTH 19 IN CASING - DEPTH OF WATER COLUMN	SITE LOCATION: Strippit, Inc. Akron, N.Y. JOB \$: 09385-96										
SECTION 2 - PURGE INFORMATION  DEPTH OF WELL [FT]: 78.6 (MEASURED FROM TOP OF CASING - T.O.C.)  STATIC WATER LEVEL(SWL) [FT]: 49.4 (MEASURED FROM T.O.C.)  DEPTH OF WATER COLUMN [FT]: 29.2 (DEPTH OF WELL - SWL)  CALCULATED VOL. OF BLO PER WELL CASING [GAL]: 4.8  CALCULATIONS: CASING DIAGFT WELL CONSTANTIGAL/FD 20.1637 (0.1637) (0.1632 VOL OF H.O. IN CASING - DEPTH OF WATER COLUMN 2 WELL CONSTANT  4' (0.333) 0.6528 (0.1632 VOL OF H.O. IN CASING - DEPTH OF WATER COLUMN 2 WELL CONSTANT  CALCULATED PURGE VOLUME [GAL]: (3.5 TIMES CASING VOLUME - SPECIFY)  ACTUAL VOLUME PURGED [GAL]: 690/005 (dry)  PURGE METHOD: 80/00 PURGE START: 0840 END: 0907  SECTION 3 - SAMPLE IDENTIFICATION  SAMPLE TIME SAMPLING METHOD ANALYTICAL SCAN(S) SAMPLE APPEARANCE  C2067- 10.20	PROJECT NAME: IRM Post-Closure Monitoring DATE: 2/6/97										
DEPTH OF WELL [FT]: 78.6 (MEASURED FROM TOP OF CASING -T.O.C.)  STATIC WATER LEVEL (SWL) [FT]: 49.4 (MEASURED FROM T.O.C.)  DEPTH OF WATER COLUMN [FT]: 29.2 (DEPTH OF WELL -SWL)  CALCULATED VOL. OF H <sub>2</sub> O PER WELL CASING [GAL]: 4.8  CALCULATIONS: CASING DIAGFT) WELL CONSTANTIGAL/FD (CALCULATIONS)  1.01632 (O.0572) 0.1632 (O.0572) VOL OF H <sub>2</sub> O IN CASING - DEPTH OF WATER COLUMN x WELL CONSTANT  CALCULATED PURGE VOLUME [GAL]: (3-5 TIMES CASING VOLUME - SPECIFY)  ACTUAL VOLUME PURGED [GAL]: 6 90/005 (d/g)  PURGE METHOD: 89/00 END: 09.07  SECTION 3 - SAMPLE IDENTIFICATION  SAMPLE TIME SAMPLING ANALYTICAL SCAN(S) SAMPLE APPEARANCE  C2C67- 10.70 METHOD											
DEPTH OF WELL [FT]: 78.6 (MEASURED FROM TOP OF CASING -T.O.C.)  STATIC WATER LEVEL (SWL) [FT]: 49.4 (MEASURED FROM T.O.C.)  DEPTH OF WATER COLUMN [FT]: 29.2 (DEPTH OF WELL - SWL)  CALCULATED VOL. OF H_O PER WELL CASING [GAL]: 4.8  CASING PLAYER WELL CONSTANTIGAL/FD (CALCULATIONS)  2' (0.1667)											
STATIC WATER LEVEL (SWL) [FT]: 49.4 (MEASURED FROM T.O.C.)  DEPTH OF WATER COLUMN [FT]: 29.2 (DEPTH OF WELL SWL)  CALCULATED VOL. OF H <sub>2</sub> O PER WELL CASING [GAL]: 4.8  CALCULATIONS:  CASING DIAGET WELL CONSTANTIGAL/FD CALCULATIONS  2º (0.1637) 0.1632 VOL OF H <sub>2</sub> O IN CASING - DEPTH OF WATER COLUMN 1.4 (0.3333) 0.6522 (0.5000) 1.4688  CALCULATED PURGE VOLUME [GAL]: (3-5 TIMES CASING VOLUME - SPECIFY)  ACTUAL VOLUME PURGED [GAL]: 690/lons (dry)  PURGE METHOD: 890/lon PURGE START: 0840 END: 0907  SAMPLE TIME SAMPLING METHOD ANALYTICAL SCAN(S) SAMPLE ID # METHOD SAMPLE APPEARANCE	SECTION 2 - PURGE INFORMATION										
DEPTH OF WATER COLUMN [FT]: 29.2 (DEPTH OF WELL - SWL)  CALCULATED VOL. OF H <sub>2</sub> O PER WELL CASING [GAL]: 4.8  CASING DIA (FT) WELL CONSTANTIGAL (FT) CALCULATIONS  2' (0.1637) 0.1632 VOL OF H <sub>2</sub> O IN CASING - DEPTH OF WATER COLUMN X WELL CONSTANT  6' (0.5000) 1.4638  CALCULATED PURGE VOLUME [GAL]: (3.5 TIMES CASING VOLUME - SPECIFY)  ACTUAL VOLUME PURGED [GAL]: 690/ons (dry)  PURGE METHOD: 89/or PURGE START: 0840 END: 0907  BECTION 3 - BAMPLE IDENTIFICATION  SAMPLE TIME SAMPLING METHOD ANALYTICAL SCAN(S) SAMPLE APPEARANCE	DEPTH OF WELL [FT]: 78.6 (MEASURED FROM TOP OF CASING -T.O.C.)										
CALCULATED VOL. OF HO PER WELL CASING [GAL]:	STATIC WATER LEVEL (SWL) [FT]: 49.4 (MEASURED FROM T.O.C.)										
CALCULATIONS:  CASING DIA(FT) WELL CONSTANTIGAL/FT)  2' (0.1667) 0.1632 VOL OF H 2 IN CASING - DEPTH OF WATER COLUMN 4' (0.3333) 0.6528 6' (0.5000) 1.4688  CALCULATED PURGE VOLUME [GAL]: (3-5 TIMES CASING VOLUME - SPECIFY)  ACTUAL VOLUME PURGED [GAL]: 6 90/015 (dry)  PURGE METHOD: 89/01 PURGE START: 08/0 END: 09/07  BECTION 3 - BAMPLE IDENTIFICATION  SAMPLE TIME SAMPLING ANALYTICAL SCAN(S) SAMPLE ID # METHOD  O2067- 10.200 METHOD	202										
ACTUAL VOLUME PURGED [GAL]: 6 gollons (dry)  PURGE METHOD: 8 gr/p PURGE START: 08 90 END: 09 07  BECTION 3 - BAMPLE IDENTIFICATION  SAMPLE TIME SAMPLING ANALYTICAL SCAN(S) SAMPLE APPEARANCE  02067- 1020 February Confidence of the confidence of th	CALCULATED VOL. OF H <sub>2</sub> O PER WELL CASING [GAL]: 4.8  CALCULATIONS:  CASING DIA.(FT) WELL CONSTANTIGAL/FT) CALCULATIONS  2° (0.1667) 0.1632 VOL OF H <sub>2</sub> O IN CASING = DEPTH OF WATER COLUMN  4° (0.3333) 0.6528  6° (0.5000) 1.4688										
PURGE METHOD: BQ: O PURGE START: 0840 END: 0907  BECTION 3 - BAMPLE IDENTIFICATION  SAMPLE TIME SAMPLING ANALYTICAL SCAN(S) SAMPLE APPEARANCE  02067- 1030 START: 0840 END: 0907											
SAMPLE TIME SAMPLING ANALYTICAL SCAN(S) SAMPLE APPEARANCE											
ID # METHOD APPEARANCE	SECTION 3 - SAMPLE IDENTIFICATION										
02067- GWZ 1330 Bailer See COC		ANALYTICAL SCAN(S)		-							
	02067- GWZ 1330 Bailer	See Co									
SECTION 4 - SAMPLE DATA											
SWL TEMP PH CONDUCTIVITY TURBIDITY VISUAL PID/FID (FT) (UMHOS/CM) (NTU) READING	SWL TEMP PH CONDUCTIVION (uMHOS/CM	,	VISUA	,							
69.8 74.0 Cloudy	69.8	74.0	Cloudy	74210EH;S117							

## DAY ENGINEERING MONITORING WELL SAMPLING LOG

Gw-3

SECTION 1											
SITE LOCATION: 5 trippit Inc. Akron, N.V. JOB #:	09385-96										
PROJECT NAME: IRM Post-Closure Monitoring DATE	2/6/97										
SAMPLE COLLECTOR(S): R. Kampff											
WEATHER CONDITIONS: Overcast 20°F											
SECTION 2 - PURGE INFORMATION											
DEPTH OF WELL [FT]: 5/.7 (MEASURED FROM TOP OF CASING - T.O.C.)											
STATIC WATER LEVEL(SWL) [FT]: 32.3 (MEASURED FROM	M T.O.C )										
DEPTH OF WATER COLUMN [FT]: 19.4 (DEPTH OF WELL	- SWL)										
CALCULATED VOL. OF H <sub>2</sub> O PER WELL CASING [GAL]: 3.2  CALCULATIONS:  CASING DIA.(FI) WELL CONSTANT(GAL/FI) CALCULATIONS  2' (0.1667) 0.1632 VOL OF H <sub>2</sub> O IN CASING = DEPTH OF WATER COLD  4' (0.3333) 0.6528	ANT NG VOLUME - SPECIFY)										
SECTION 3 - SAMPLE IDENTIFICATION											
ID # METHOD	SAMPLE APPEARANCE										
02067- GW3 1150 Bailor See COC											
SECTION 4 - SAMPLE DATA											
SWL TEMP PH CONDUCTIVITY TURBIDITY VISUAL (FT) (°C) (uMHOS/CM) (NTU)	PID/FID READING										
32.9 47.4 Clear	FILEWALSAN										

### DAY ENGINEERING MONITORING WELL SAMPLING LOG

GW-4/DUP

SECTION 1											
SITE LOCATION: Strippit, Inc. / Akron, Now York JOB \$: 09385-96											
PROJECT NAME: IRM POST-Clasure Monitoring DATE: 2/6/97											
SAMPLE COLLECTOR(S): R. Kompff											
WEATHER CONDITIONS: OURCAST 20°F											
SECTION 2 - PURGE INFORMATION											
DEPTH OF WELL [FT]: 5/.8 (MEASURED FROM TOP OF CASING - T.O.C.)											
STATIC WATER LEVEL(SWL) [FT]: 36./ (MEASURED FROM T.O.C)											
DEPTH OF WATER COLUMN [FT]: 15.7 (DEPTH OF WELL-SWL)											
CALCULATED VOL. OF H <sub>2</sub> O PER WELL CASING [GAL]: 2.6  CALCULATIONS: CASING DIA.(FI) WELL CONSTANTIGAL/FI) CALCULATIONS  2" (0.1667) 0.1632 VOL OF H <sub>2</sub> IN CASING = DEPTH OF WATER COLUMN 4" (0.3333) 0.6528 × WELL CONSTANT 6" (0.5000) 1.4688											
CALCULATED PURGE VOLUME [GAL]: (3-5 TIMES CASING VOLUME - SPECIFY)											
ACTUAL VOLUME PURGED [GAL]: 8 9 9/10 n S											
purge method: Railer purge start: 0944 end: 1010											
SECTION 3 - SAMPLE IDENTIFICATION											
SAMPLE TIME SAMPLING ANALYTICAL SCAN(S) SAMPLE APPEARANCE											
02067-BUT 1220 891/PT SEE COC Slight Sheen											
SECTION 4 - SAMPLE DATA											
SWL TEMP (°C) PH CONDUCTIVITY TURBIDITY VISUAL PID/FID READING											
37.2 115.6 Cloudy											

## day engineering monitoring well sampling log Gw-5

SECTION 1											
SITE LOCATION: Strippit, Inc. JAKron, New York JO	B #: 09385-96										
PROJECT NAME: IRM POST-Closure Monitoring DA	TE: 2/6/97										
SAMPLE COLLECTOR(S): R. Kampff											
WEATHER CONDITIONS: OUPCOST 20°F											
SECTION 2 - PURGE INFORMATION											
DEPTH OF WELL [FT]: 74.7 (MEASURED FROM TOP OF CASING - T.O.C.)											
STATIC WATER LEVEL(SWL) [FT]: 650.25 (MEASURE)	ji										
DEPTH OF WATER COLUMN [FT]: 24.45 (DEPTH OF	WELL - SWL)										
CALCULATED VOL. OF H <sub>2</sub> O PER WELL CASING [GAL]:  CALCULATIONS:  CASING DIA.(FI) WELL CONSTANT/GAL/FI) CALCULATIONS  2° (0.1667) 0.1632 VOL OF H <sub>2</sub> O IN CASING = DEPTH OF WATER COLUMN  4° (0.3333) 0.6528  x WELL CONSTANT  6° (0.5000) 1.4688											
CALCULATED PURGE VOLUME [GAL]: (3-5 TIME)  ACTUAL VOLUME PURGED [GAL]: 5.2 9 allons (DRY)  PURGE METHOD: 8 9 / 6 PURGE START: 9	S CASING VOLUME - SPECIFY)										
Token Biari.	ERU. 07 /										
SECTION 3 - SAMPLE IDENTIFICATION											
SAMPLE TIME SAMPLING ANALYTICAL SCAN(S) ID # METHOD	SAMPLE APPEARANCE										
02067- GWS 1355 Bailer See COC											
SECTION 4 - SAMPLE DATA											
SWL TEMP PH CONDUCTIVITY TURBIDITY VIST (FT) (°C) (umhos/cm) (NTU)	UAL PID/FID READING										
65.95 clordy >	FILESHELLSHM										

## DAY ENGINEERING MONITORING WELL SAMPLING LOG

		BECTION	1									
SITE LOCATION:					JOB :	<b>#</b> :						
PROJECT NAME:					DATE	:						
SAMPLE COLLECTOR	(s):			<del></del>								
WEATHER CONDITION	:											
	SECTION 2 - PURGE INFORMATION											
DEPTH OF WELL [F	r]:			(\%	EASURED FROM	TOP OF	CASING - T.O.C.)					
STATIC WATER LEV.	EL (SWL)	[FT]:			(MEASURED FR	ом т.о.с	)					
DEPTH OF WATER C	OLUMN (	[FT]:		<del></del>	(DEPTH OF WEI	L - SWL)						
CALCULATED VOL.  CALCULATIONS:  CASING DIA.(FI) WELL CO  2" (0.1667) 0.10  4" (0.3333) 0.6  6" (0.5000) 1.4  CALCULATED PURGE  ACTUAL VOLUME PU  PURGE METHOD:	NSTANTIG 632 528 688 VOLUMI RGED [6	AL/FT CALCUI VOL O  GAL]:	ATIC PH2	ONS O IN CASING = DEPI	TH OF WATER CO x WELL CONS (3 - 5 TIMES CA	ILUMN STANT SING VOI						
	SEC	TION 3 - 8A	MP	LE IDENTIFI	CATION							
SAMPLE TIME ID #	SAMPL METHO	ING D	AN	NALYTICAL SO	CAN(S)	SAMPI APPE	LE ARANCE					
		SECTION 4	_	SAMPLE DAT	A							
SWL TEMP (°C)	рН	CONDUCTIVI (uMHOS/CM		TURBIDITY (NTU)	VISUA	L.	PID/FID READING					
							177221057FC1015					

#### APPENDIX C

SUMMARY OF DETECTED PARAMETERS, MEAN CONCENTRATIONS AND STANDARD DEVIATIONS

## STRIPPIT, INC. INTERIM REMEDIAL MEASURE POST-CLOSURE MONITORING

Monitoring Well: <u>GW-1</u>

Page 1 of 2

						SAMPLE RO	UND				
TEST PARAMETER	UNITS	4/11/95	7/12/95	10/16/95	1/22/96	5/8/96	8/6/96	10/29/96	2/6/97	Mean	Standard Deviation
pН	Standard	7.35	8.76	8.63	9.07	8.87	8.04	8.31	8.55	8.45	0.56
specific conductance	uMHOS/cm	1,400	1,170	751	889	1,297	. 862	1,179	870	1,052	223
turbidity	NTU	85.8	200+	46.6	-	101.6	83.8	135.2	-	-	-
barium, soluble	mg/L	0.058	0.059	0.06	0.12	0.054	0.03	0.042 /0.038	0.033	0.055	0.025
barium, total	mg/L	0.079	0.123	0.07	0.13	0.054	0.04	0.055 / 0.060	0.041	0.072	0.031
iron, soluble	mg/L	LT 0.03	0.36	0.13	8.24	0.15	LT 0.03	1.07 / 1.06	0.04	1.23	2.51
iron, total	mg/L	1.46	6.82	2.53	8.34	0.15	0.17	2.83 / 3.09	1.00	2.93	2.7
magnesium, soluble	mg/L	50.8	44.6	47.5	66.8	62.9	68.6	58.1 / 56.6	63.0	57.6	8.04
magnesium, total	mg/L	54.0	52.0	56.8	68.8	62.9	71.2	65.1 / <b>6</b> 4.5	65.6	62.3	6.2
manganese, soluble	mg/L	LT 0.005	0.026	0.01	0.23	0.039	0.021	0.042 / 0.038	0.015	0.047	0.066
manganese, total	mg/L	0.038	0.171	0.08	0.24	0.039	0.024	0.080 / 0.091	0.041	0.089	0.068
total phenols	mg/l	-		•	•	LT 0.005	LT 0.005	LT 0.005	LT 0.005	0.005	0
dichlorodifluoromethane	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 1.0	LT 1.0	LT 1.0	LT 1.0	0.75	0.25
chloromethane	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 1.0	LT 1.0	LT 1.0	LT 1.0	0.75	0.25
vinyl chloride	ug/L	LT 0.5	LT 0.5*	LT 0.5	LT 0.5	LT 1.0	LT 1.0	LT 1.0	LT 1.0	0.75	0.25
acetone	ug/L	26*	5.0	34.0 B	6.0	71.0 B	LT 5.0B	LT 5.0B	LT 5.0	19.6	22.2
carbon disulfide	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0
trans-1,2-dichloroethene	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0
1.1-dichloroethane	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0
chloroform	ug/L	LT 0.5	LT 0.5	1.5 B	LT 0.5	LT 0.5	1.0 B	LT 0.5	LT 0.5	0.7	0.3
2-butanone	ug/L	LT 1.0	2*	LT 0.5	0.5	LT 1.0	LT 1.0	LT 1.0	LT 2.0	1.1	0.5

						SAMPLE RO	UND				
TEST PARAMETER	UNITS	4/11/95	7/12/95	10/16/95	1/22/96	5/8/96	8/6/96	10/29/96	2/6/97	Меап	Standard Deviation
1,1,1-trichloroethane	ug/L	LT 0.5	LT 0.5	0.9 B	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.55	0.13
carbon tetrachloride	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0
benzene	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0
trichloroethene	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0
toluene	ug/L	LT 0.5	LT 0.5	LT 0.5	0.6	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.51	0.03
tetrachloroethene	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0
methylene chloride	ug/L	11 B	LT 5.0	21.0 B	LT 5.0	35.0 B	14.0 B	LT 5.0B	LT 5.0	12.6	10
m,p-xylenes	ug/l	LT 1.0	LT 1.0	LT 1.0	LT 1.0	LT 1.0	LT 1.0	LT 1.0	LT 1.0	1.0	0
o-xylenes	ug/l	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0
phenol	ug/l	LT 1.0	LT 1.0	LT 1.0	LT 1.0	-		•	•	•	
groundwater elevation	feet	713.43	711.04	710.09	712.82	715.76	714.71	714.29	715.02	-	

LT = Less than detection limit shown.

B = Compound also detected in blank (see laboratory report).

\* = Estimated value, see lab report.

- = Not tested.

The following compouds were detected in blank samples at the concentrations shown.

4/11/95 Sample Round: Methylene chloride 2.8 ug/l.

7/12/95 Sample Round: Acetone 5.0 ug/l, methylene chloride 5.2 ug/l, chloroform 1.0 ug/l, 2-butanone 3.0 ug/l.

10/16/95 Sample Round: Acetone 20 ug/l, methylene chloride 14 ug/l, chloroform 1.3 ug/l, 1,1-trichloroethane 0.9 ug/l, 2-butanone 2.0 ug/l.

1/22/96 Sample Round: Acetone 10 ug/l

5/8/96 Sample Round: Acetone 82.0 ug/l, methylene chloride 46.0 ug/l; chloroform 2.0 ug/l. Acetone 6.0 ug/l, methylene chloride 11.0 ug/l, chloroform 1.0 ug/l.

10/29/96 Sample Round: Acetone 12.0 ug/l, methylene chloride 6.0 ug/l.

## STRIPPIT, INC. INTERIM REMEDIAL MEASURE POST-CLOSURE MONITORING

Monitoring Well: <u>GW-2</u>

Page 1 of 2

					SAMP	LE ROUND					
TEST PARAMETER	UNITS	4/11/95	7/12/95	10/16/95	1/22/96	5/8/96	8/6/96	10/29/96	2/6/97	Mean	Standard Deviation
рН	Standard	7.23	11.58	11.71	12.23	11.55	11.33	11.29	11.31	11.03	1.46
specific conductance	uMHOS/cm	1,870	1,170	695	771	1,239	1,050	827	244	983	446
turbidity	NTU	200+	16.5	11.9	_	11.6	6.91	3.92	74.0	-	-
barium, soluble	mg/L	0.199	0.20	0.18	0.15	0.116	0.129	0.112 / 0.117	0.115	0.146	0.035
barium, total	mg/L	0.210	0.211	0.21	0.18	0.118	0.130	0.145 / 0.132	0.127	0.162	0.037
iron, soluble	mg/L	LT 0.03	0.15	0.007	0.43	0.09	LT 0.03	0.082 / 0.117	0.34	0.13	0.14
iron, total	mg/L	0.25	0.49	1.44	1.26	0.09	0.18	0.256 / 0.264	0.41	0.52	0.46
magnesium, soluble	mg/L	LT 0.05	0.14	0.23	1.01	0.47	0.95	0.90 / 0. <b>92</b>	0.089	0.53	0.39
magnesium, total	mg/L	1.03	0.36	0.91	1.36	0.47	2.51	2.95 / 2.64	0.342	1.4	0.98
manganese, soluble	mg/L	LT 0.005	0.053	LT 0.005	0.03	LT 0.005	LT 0.005	LT 0.005 / LT 0.005	0.008	0.013	0.016
manganese, total	mg/L	0.006	0.150	0.02	0.04	LT 0.005	LT 0.005	0.029 / 0.027	0.009	0.032	0.043
total phenols	mg/l	-	-	-	-	LT 0.05	0.020	0.008	0.005	0.0095	0.006
dichlorodifluoromethane	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 1.0	LT 1.0	LT 1.0	LT 1.0	0.75	0.25
chloromethane	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 1.0	LT 1.0	LT 1.0	LT 1.0	0.75	0.25
vinyl chloride	ug/L	LT 0.5	LT 0.5*	LT 0.5	LT 0.5	LT 1.0	LT 1.0	LT 1.0	LT 1.0	0.75	0.25
acetone	ug/L	31*	33	63.0 B	24.0	100 B	21.0 B	47.0 B	19.0	42.2	25.8
carbon disulfide	ug/L	LT 0.5	LT 0.5*	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0
trans-1,2-dichloroethene	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0
1,1-dichloroethane	ug/L	0.6*	LT 0.5	0.7	LT 0.5	0.5	LT 0.5	0.7	0.6	0.57	0.08
chtoroform	ug/L	LT 0.5	LT 0.5	2.0	0.6	LT 0.5	0.8 B	LT 0.5	LT 0.5	0.7	0.5

					SAMP	LE ROUND					
TEST PARAMETER	UNITS	4/11/95	7/12/95	10/16/95	1/22/96	5/8/96	8/6/96	10/29/96	2/6/97	Mean	Standard <b>Deviation</b>
2-butanone	ug/L	3.0*	6.0*	<b>LT</b> 0.5	2.0	4.0	LT 1.0	<b>LT</b> 1.0	LT 2.0	2.4	1.7
1,1,1-trichloroethane	ug/L	LT 0.5	LT 0.7	0.6 B	LT 0.5	LT 0.5	0.6	LT 0.5	LT 0.5	0.55	0.07
carbon tetrachloride	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0
benzene	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	. 0.6	LT 0.5	LT 0.5	0.51	0.03
trichloroethene	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0
toluene	ug/L	0.7*	LT 0.5	0.9	0.6	0.8	1.0	0.9	0.6	0.75	0.17
tetrachloroethene	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0
methylene chloride	ug/f,	11 B	LT 5.0	23.0	10.0	38.0 B	LT 5.0 B	LT 5.0 B	LT 5.0B	11.9	10.8
m,p-xylenes	ug/l	LT 1.0	LT 1.0	LT 1.0	1.0	LT 1.0	LT 1.0	LT 1.0	LT 1.0	1.0	0
o-xylenes	ug/l	LT 0.5	LT 0.5	LT 0.5	0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0
phenol	ug/l	LT 1.0	5.6	2.0	3.0	_	-	-	•	<b>-</b>	-
groundwater elevation	feet	719.90	717.08	715.62	718.59	721.58	720.24	719.96	721.22	•	_

LT = Less than detection limit shown.

B = Compound also detected in blank (see laboratory report).

\* Estimated value, see lab report.

- = Not tested

The following compouds were detected in blank samples at the concentrations shown.

4/11/95 Sample Round: Methylene chloride 2,8 ug/l.

7/12/95 Sample Round: Acetone 5.0 ug/l, methylene chloride 5.2 ug/l, chloroform 1.0 ug/l, 2-butanone 3.0 ug/l.

10/16/95 Sample Round: Acetone 20 ug/l, methylene chloride 14 ug/l, chloroform 1.3 ug/l, 1,1-trichloroethane 0.9 ug/l, 2-butanone 2.0 ug/l.

1/22/96 Sample Round: Acetone 10 ug/l

5/8/96 Sample Round: Acetone 82.0 ug/l, methylene chloride 46.0 ug/l; chloroform 2.0 ug/l. Acetone 6.0 ug/l, methylene chloride 11.0 ug/l, chloroform 1.0 ug/l.

10/29/96 Sample Round: Acetone 12.0 ug/l, methylene chloride 6.0 ug/l.

## STRIPPIT, INC. INTERIM REMEDIAL MEASURE POST CLOSURE MONITORING

Monitoring Well: <u>GW-3</u>

Page 1 of 3

						SAMPLE R	OUND				
TEST PARAMETER	UNITS	4/11/95	7/12/95	10/16/95	1/22/96	5/8/96	8/6/96	10/29/97	2/6/97	Mean	Standard Deviation
рН	Standard	6.82	8.01	8.01	<b>8.44</b> 8.39	8.42	7.85	7.53	7.63	7.89	0.49
specific conductance	uMHOS/cm	2,010	568	502	475	614	623	585	342	761	538
turbidity	NTU	26.0	26.8	191	-	70.7	5.12	150.3	47.4		-
barium, soluble	mg/L	0.056	0.003 0.061	<b>0.04</b> 0.06	0. <del>09</del> 0.08	0.072 0.078	0.065	0.067 0.080	0.066	0.063	0.021
barium, total	mg/L	0.065	0.094 0.252	<b>0.17</b> 0.16	0.09 0.09	0.078 0.078	0.086	<b>0.076</b> 0.080	0.083	0.108	0.052
iron, soluble	mg/L	LT 0.03	0.11 0.09	0.09 0.10	3.33 2.71	1.59 2.46	0.05	1.47 2.00	0.12	1.09	1.17
iron, total	mg/L	1.56	3.45 9.97	15.5 11.6	4.35 3.83	6.00 2.46	1.30	2.11 1.89	2.37	5.11	4.3
magnesium, soluble	mg/L	27.7	30.3 28.4	31.5 27.8	33.7 30.2	28.8 32.5	27.9	27.5 29.4	29.7	29.6	1.9
magnesium, total	mg/L	28.3	37.4 100	83.1 62.0	34.5 30.4	29.4 32.5	32.7	3.09 30.8	32.9	43.5	22.3
manganese, soluble	mg/L	0.078	0.141 0.134	0.02 0.13	0.20 0.13	0.119 0.144	0.124	0.104 0.121	0.148	0.123	0.043
manganese, total	mg/L	0.120	0.251 0.660	0.77 0. <b>5</b> 5	0.22 0.20	0.140 0.144	0.141	0.129 0.127	0.148	0.277	0.217
total phenois	mg/I					LT 0.005 LT 0.005	0.14	LT 0.005 LT 0.005	LT 0.005	0.027	0.05
dichlorodifluoromethane	ug/L	2.4*	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 1.0 LT 1.0	LT 1.0	LT 1.0 LT 1.0	LT 1.0	0.9	0.5

						SAMPLE RO	DUND			•	•
TEST PARAMETER	UNITS	4/11/95	7/12/95	10/16/95	1/22/96	5/8/96	8/6/96	10/29/97	2/6/97	Mean	Standard Deviation
chloromethane	ug/I.	1.5*	LT 0.5 LT <b>0.5</b>	LT 0.5 <b>LT 0</b> .5	LT 0.5 <b>L</b> T 0. <b>5</b>	LT 1.0 <b>LT 1</b> .0	LT 1.0	LT 1.0 LT <b>1.0</b>	LT 1.0	0.8	0.3
vinyl chloride	ug/L	2.3*	LT 0.5* LT 0.5*	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 1.0 LT 1.0	LT 1.0	LT 1.0 LT 1.0	LT 1.0	0.09	0.5
acetone	ug/L	16*	11.0 10.0	20.0 B 17.0 B	LT 5.0 B 6.0 B	100 B 80.0 B	LT 5.0 B	LT 5.0 B LT 5.0 B	LT 5.0	20.1	26.3
carbon disulfide	ug/L	1.8*	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	3.0	LT 0.5 LT 0.5	LT 0.5	0.8	0.7
trans-1,2-dichloroethene	ug/L	0.8*	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5	LT 0.5 LT 0.5	LT 0.5	0.52	0.08
1,1-dichloroethane	ug/L	0.8*	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5	LT 0.5 LT 0.5	LT 0.5	0.52	0.08
chloroform	ug/L	0.7*	LT 1.0 2.0	1.0 B 2.0	LT 0.5 LT 0.5	LT 0.5 B 0.9 B	3.0 B	LT 0.5 LT 0.5	LT 0.5	1.1	0.8
2-butanone	ug/L	LT 1.0	3.0* 12.0	LT 0.5 1.0	LT 0.5 0.6	LT 0.5 LT 1.0	LT 1.0	LT 1.0 LT 1.0	LT 2.0	1.9	3.0
1,1,1-trichloroethane	ug/L	1.8*	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5	LT 0.5 LT 0.5	LT 0.5	0.6	0.35
carbon tetrachloride	ug/L	1.7*	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5	LT 0.5 LT 0.5	LT 0.5	0.6	0.33
benzene	ug/L	0.5*	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5	LT 0.5 LT 0.5	LT 0.5	0.5	θ
trichloroethene	ug/L	0.8*	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5	LT 0.5 LT 0.5	LT 0.5	0.52	0.08
toluene	ug/L	0.7*	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5	LT 0.5 LT 0.5	LT 0.5	0.52	0.08
tetrachloroethene	ug/L	0.9*	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5	LT 0.5 LT 0.5	LT 0.5	0.52	0.008
methylene chloride	ug/L	6.3 B	LT 5.0 LT 5.0	23.0 B 8.0 B	5.0 6.0	47.0 B 28.0 B	10.0 B	LT 5.0 B LT 5.0 B	LT 5.0 B	12.2	12.4

Page 3 of 3

		SAMPLE ROUND											
TEST PARAMETER	UNITS	4/11/95	7/12/95	10/16/95	1/22/96	5/8/96	8/6/96	10/29/97	2/6/97	Mean	Standard Deviation		
m,p-xylenes	ug/l	LT 1.0	3.0 LT <b>1.0</b>	LT 1.0 <b>LT 1</b> .0	LT 1.0 LT 1.0	LT 1.0 <b>LT 1</b> .0	LT 1.0	LT 1.0 LT <b>1.0</b>	LT 1.0	2	2.8		
o-xylenes	ug/l	LT 0.5	1.0 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5 LT 0.5	LT 0.5	LT 0.5 LT 0.5	LT 0.5	0.54	0.14		
phenol	ug/l	LT 1.0	LT 1.0 LT 1.0	LT 1.0 LT 1.0	LT 1.0 LT 1.0	-	-	-	-	-	-		
groundwater elevation	feet	709.53	707.19	705.56	708.26	711.25	710.47	709.65	710.29	-	-		

Notes:

LT = Less than detection limit shown.

B = Compound also detected in blank (see below).

\* = Estimated value, see lab report.

The following compounds were detected in blank samples at the concentrations shown.

4/11/95 Sample Round: Methylene chloride 2.8 ug/l

7/12/95 Sample Round: Acetone 5.0 ug/L, methylene chloride 5.2 ug/L, chloroform 1.0 ug/L, 2-butanone 3.0 ug/L.

10/16/95 Sample Round: Acetone 20 ug/L, methylene chloride 14 ug/L, chloroform 1.3 ug/L, 1,1,-trichloroethane 0.9 ug/L, 2-butanone 2.0 ug/L.

1/22/96 Sample Round: Acetone 10 ug/L.

5/8/96 Sample Round: Acetone 82.0 ug/l, methylene chloride 46.0 ug/l; chloroform 2.0 ug/l. 8/6/96 Sample Round: Acetone 6.0 ug/l, methylene chloride 11.0 ug/l, chloroform 1.0 ug/l.

10/29/96 Sample Round: Acetone 12.0 ug/l, methylene chloride 6.0 ug/l.

## STRIPPIT, INC. INTERIM REMEDIAL MEASURE POST CLOSURE MONITORING

Monitoring Well: <u>GW-4</u>

Page 1 of 3

						SAMPLE RO	UND				
TEST PARAMETER	UNITS	4/11/95	7/12/95	10/16/95	1/22/96	5/8/96	8/6/96	10/29/96	<b>2/</b> 6/97	Mean	Standard Deviation
рН	Standard	7.06	8.31	8.34	9.07	8.03	8.01	7.47	8.08 8.33	7.97	0.59
specific conductance	uMHOS/cm	1,990	935	628	626	1,118	1,141	1,094	792 694	1,030	426
turbidity	NTU	200+	200+	106.7	-	42.7	105.4	46.7	115.6	_	-
barium, soluble	mg/L	0.038 0.052	0.058	0.07	0.11	0.044	0.043 0.039	0.05	0.049 0.050	0.055	0.019
barium, total	mg/I.	0.101 <b>0.175</b>	0.099	0.12	0.13	0.044	0.046 0.042	0.054	0.083 0.059	0.087	0.041
iron, soluble	mg/L	LT 0.03 LT 0.03	1.00	0.37	8.32	1.0	0.03 0.03	1.94	0.22 0.23	1.2	2.32
iron, total	mg/L	7.93 16.1	6.72	11.9	9.85	1.0	0.42 0.43	2.14	4.52 1.22	6.1	5.1
magnesium, soluble	mg/L	53.1 47.0	36.7	30.2	47.9	39.7	39.5 3 <b>5.5</b>	44.3	40.2 39.1	41.2	6.1
magnesium, total	mg/L	68.5 87.3	48.3	66.0	49.4	39.7	40.1 37.6	49.1	50.9 41.4	52.6	14.6
manganese, soluble	mg/L	LT 0.005 LT 0.005	0.029	0.15	0.20	0.022	0.016 0.015	0.062	0.026 0.035	0.05	0.061
manganese, total	mg/L	0.21 0.43	0.162	0.32	0.24	0.022	0.025 0.018	0.086	0.104 0.047	0.151	0.13
total phenois	mg/l					LT 0.005	LT 0.005 LT 0.005	LT 0.005	0.018 0.006	0.007	0.005
dichlorodifluoromethane	ug/i.	LT 0.5 LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 1.0	LT 1.0 LT 1.0	LT 1.0	LT 1.0 LT 1.0	0.75	0.25

			SAMPLE ROUND												
TEST PARAMETER	UNITS	4/11/95	7/12/95	10/16/95	1/22/96	5/8/96	8/6/96	10/29/96	2/6/97	Mean	Standard Deviation				
chloromethane	ug/L	LT 0.5 L <b>T 0.5</b>	LT 0.5	LT 0.5	LT 0.5	LT 1.0	LT 1.0 LT <b>1.0</b>	LT 1.0	LT 1.0 LT <b>1.0</b>	0.75	0.25				
vinyl chloride	ug/L	LT 0.5 LT 0.5	LT 0.5*	LT 0.5	LT 0.5	LT 1.0	LT 1.0 LT 1.0	LT 1.0	LT 1.0 LT 1.0	0.75	0.25				
acetone	ug/L	13* 11*	LT 5.0	29.0 B	14.0	38.0 B	LT 5.0 LT 5.0	LT 5.0 B	5.0 LT 5.0	12.3	10.7				
carbon disulfide	ug/L	LT 0.5 LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5 LT 0.5	LT 0.5	LT 0.5 LT 0.5	0.5	0				
trans-1,2-dichloroethene	ug/L	LT 0.5 LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5 LT 0.5	LT 0.5	LT 0.5 LT 0.5	0.5	0				
1,1-dichloroethane	ug/L	LT 0.5 LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5 LT 0.5	LT 0.5	LT 0.5 LT 0.5	0.5	0				
chloroform	ug/L	LT 0.5 LT 0.5	1.6	1.0 B	0.8	LT 0.5	LT 0.5 B 0.6 B	LT 0.5	LT 0.5 LT 0.5	0.7	0.3				
2-butanone	ug/L	LT 1.0 LT 1.0	LT 1.0	LT 0.5	1.0	LT 1.0	LT 1.0 LT 1.0	LT 1.0	LT 2.0 LT 2.0	1.1	0.4				
1,1,1-trichloroethane	ug/L	LT 0.5 LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5 LT 0.5	LT 0.5	LT 0.5 LT 0.5	0.5	0				
carbon tetrachloride	ug/L	LT 0.5 LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5 LT 0.5	LT 0.5	LT 0.5 LT 0.5	0.5	0				
benzene	ug/L	LT 0.5 LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5 LT 0.5	LT 0.5	LT 0.5 LT 0.5	0.5	θ				
trichloroethene	ug/L	LT 0.5 LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5 LT 0.5	LT 0.5	LT 0.5 LT 0.5	0.5	0				
toluene	ug/L	LT 0.5 LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5 LT 0.5	LT 0.5	LT 0.5 LT 0.5	0.5	0				
tetrachloroethene	ug/L	LT 0.5 LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5 LT 0.5	LT 0.5	LT 0.5 LT 0.5	0.5	0				
methylene chloride	ug/L	2.7 B 2.5 B	LT 5.0	18.0 B	10	36.0 B	7.0 B LT 5.0 B	LT 5.0 B	LT 5.0 B LT 5.0 B	9.2	9.4				

	UNITS		SAMPLE ROUND											
TEST PARAMETER		4/11/95	7/12/95	10/16/95	1/22/96	5/8/96	8/6/96	10/29/96	2/6/97	Mean	Standard Deviation			
m,p-xylenes	ug/l	LT 1.0 LT 1.0	2.0	LT 1.0	LT 1.0	LT 1.0	LT 1.0 LT <b>1.0</b>	LT 1.0	LT 1.0 LT 1.0	1.1	0.3			
o-xylenes	ug/l	LT 0.5 LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5 LT 0.5	LT 0.5	LT 0.5 LT 0.5	0.5	0			
phenol	ug/l	LT 1.0 LT 1.0	LT 1.0	LT 1.0	LT 1.0	-	-	-	-	-	-			
groundwater elevation	feet	715.06	712.56	711.13	713.69	716.70	715.75	715.36	716.14	-	-			

LT = Less than detection limit shown.

B = Compound also detected in blank (see below).

\* = Estimated value, see lab report.

The following compounds were detected in blank samples at the concentrations shown.

4/11/95 Sample Round: Methylene chloride 2.8 ug/l

7/12/95 Sample Round: Acetone 5.0 ug/L, methylene chloride 5.2 ug/L, chloroform 1.0 ug/L, 2-butanone 3.0 ug/L.

10/16/95 Sample Round: Acetone 20 ug/L, methylene chloride 14 ug/L, chloroform 1.3 ug/L, 1,1,-trichloroethane 0.9 ug/L, 2-butanone 2.0 ug/L.

1/22/96 Sample Round: Acetone 10 ug/L.

5/8/96 Sample Round: Acetone 82.0 ug/l, methylene chloride 46.0 ug/l; chloroform 2.0 ug/l. Acetone 6.0 ug/l, methylene chloride 11.0 ug/l, chloroform 1.0 ug/l.

10/29/96 Sample Round: Acetone 12.0 ug/l, methylene chloride 6.0 ug/l.

STRIPPIT, INC.
INTERIM REMEDIAL MEASURE
POST CLOSURE MONITORING

Monitoring Well: <u>GW-5</u>

Page 1 of 2

		SAMPLE ROUND										
TEST PARAMETER	UNITS	4/11/95	7/12/95	10/16/95	1/22/96	5/8/96	8/6/96	10/29/96	2/6/97	Mean	Standard Deviation	
pH	Standard	6.99	10.88	10.97	11.54	10.93	10.87	10.39	10.90	10.43*	1.33	
specific conductance	uMHOS/cm	2,090	735	506	641	831	816	737	286	830	505	
turbidity	NTU	200+	167.8	113.2	<del>-</del>	162.6	181	37.8	49.5	-	-	
barium, soluble	mg/L	0.078	0.484	0.06	0.18	0.05	0.051	0.049	0.056	0.126	0.141	
barium, total	mg/L	0.172	0.600	0.18	0.23	0.053	0.055	0.090	0.114	0.187	0.167	
iron, soluble	mg/L	LT 0.03	0.09	0.34	24.8	0,48	LT 0.03	0.99	0.64	3.42	8.14	
iron, total	mg/L	23.0	1.73	24.7	34.3	0.51	0.28	1.33	8.67	11.82	12.64	
magnesium, soluble	mg/L	16.5	4.32	3.68	33.5	2.40	1.33	1.96	5.42	8.64	10.43	
magnesium, total	mg/L	32.2	9.71	32.8	<b>42</b> .5	2.53	2.49	3.05	18.6	17.98	14.97	
manganese, soluble	mg/L	LT 0.005	LT 0.005	0.01	0.57	0.011	LT 0.005	0.014	0.016	0.079	0.185	
manganese, total	mg/L	0.485	0.038	0.62	0.76	0.011	0.008	0.03	0.218	0.271	0.287	
total phenois	mg/ł	•	-	-	•	LT 0.005	LT 0.005	LT 0.005	0.005	0.005	0	
dichlorodifluoromethane	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 1.0	LT 1.0	LT 1.0	LT 1.0	0.75	0.25	
chloromethane	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 1.0	LT 1.0	LT 1.0	LT 1.0	0.75	0.25	
vinyl chloride	ug/L	LT 0.5	LT 0.5*	LT 0.5	LT 0.5	LT 1.0	LT 1.0	LT 1.0	LT 1.0	0.75	0.25	
acetone	ug/L	33*	29	43.0 B	8.0	57.0 B	7.0 B	9.0 B	LT 5.0	23.9	18.3	
carbon disulfide	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0	
trans-1,2-dichloroethene	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0	
1,1-dichloroethane	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0	
chioroform	ug/L	LT 0.5	LT 1.0	1.0 B	LT 0.5	LT 0.5	2.0 B	LT 0.5	LT 0.5	0.8	0.5	

			SAMPLE ROUND											
TEST PARAMETER	UNITS	4/11/95	7/12/95	10/16/95	1/22/96	5/8/96	8/6/96	10/29/96	2/6/97	Mean	Standard <b>Deviation</b>			
2-butanone	ug/L	LT 1.0	LT 1.0	<b>1.0</b> B	<b>LT</b> 0.5	LT 1.0	LT 1.0	LT 1.0	LT 2.0	1.1	0.4			
1,1,1-trichloroethane	ug/L	LT 0.5	LT 0.5	1.5 B	0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.6	0.3			
carbon tetrachloride	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0			
benzene	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0			
trichloroethene	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0			
toluene	ug/L	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0			
tetrachloroethene	ug/L	LT 0.5	LT 0.5	0.6	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.51	0.03			
methylene chloride	ug/L	2.4 B	LT 5.0	24.0 B	12.0	23.0 B	10.0 B	LT 5.0 B	LT 5.0 B	10.8	7.9			
m,p-xylenes	ug/l	LT 1.0	LT 1.0	LT 1.0	LT 1.0	LT 1.0	LT 1.0	LT 1.0	LT 1.0	1.0	0			
o-xylenes	ug/l	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	LT 0.5	0.5	0			
phenol	ug/l	LT 1.0	LT 1.4	LT 1.4	LT 1.0	•	•	•	•	•	•			
groundwater elevation	feet	719.54	<b>7</b> 16. <b>7</b> 2	715.29	718.53	721.37	719.99	719.94	721.01	•	•			

LT = Less than detection limit shown.

B = Compound also detected in blank (see below).

\* = Estimated value, see lab report.

The following compounds were detected in blank samples at the concentrations shown.

4/11/95 Sample Round: Methylene chloride 2.8 ug/l

7/12/95 Sample Round: Acetone 5.0 ug/L, methylene chloride 5.2 ug/L, chloroform 1.0 ug/L, 2-butanone 3.0 ug/L.

10/16/95 Sample Round: Acetone 20 ug/L, methylene chloride 14 ug/L, chloroform 1.3 ug/L, 1,1,-trichloroethane 0.9 ug/L, 2-butanone 2.0 ug/L.

1/22/96 Sample Round: Acetone 10 ug/L.

5/8/96 Sample Round: Acetone 82.0 ug/l, methylene chloride 46.0 ug/l; chloroform 2.0 ug/l. Acetone 6.0 ug/l, methylene chloride 11.0 ug/l, chloroform 1.0 ug/l.

10/29/96 Sample Round: Acetone 12.0 ug/l, methylene chloride 6.0 ug/l.


#### APPENDIX D

SITE INSPECTION REPORT JANUARY 22, 1996 SAMPLE ROUND

# LONG-TERM QUARTERLY MONITORING REPORT INTERIM REMEDIAL MEASURE STRIPPIT, INC. AKRON, NEW YORK

Date of Inspection: February 6, 1997
Inspected By: Raymond L. Kampff
Summary of Observation:  General Condition of Cover:3-6+ inches of snow cover at time of inspection,  no areas of concern noted.
Evidence of Erosion, sloughing or other degradation: Yes X No  Explain:
Evidence of cracking: Yes X No  Explain (include measurements and site sketch): snow cover obscured a complete
view of cap
Evidence of water seepage:  Yes  No
Explain:
Evidence of Settlement: Yes No  Explain:
Condition of monitoring wells and gas wells: No problems noted, surface seals appeared to be intact, all locks were replaced during this sample round.

Condition of Vegetative Cover: N/A	+
Condition of drainage ways (discuss amount of water/sediments present, vegetative grow unusual staining, blockage, etc.)No problems observed.	th,
Additional Comments:	
Action Item(s) Required: Cleaned of drainage and settling basin in spring recommended.	
Action Item(s) completed since last inspection: N/A	
Signatures: Jaymond Jampaf	




View looking north at top of cap.



View looking north at eastern side of cap; well casing for GW-2 in foreground and GW-5 in background.



View looking south towards monitoring well GW-1 at western slope of cap.



View looking south at northern cap; gas well condenser in foreground.