

2015 ANNUAL MONITORING / INSPECTION **REPORT**

SNPE-VDM Creek Bank Corrective Actions

VanDeMark Chemical Inc. - Lockport, New York

Order on Consent: R9-20080205-5

Submitted To: SNPE, Inc.

103 Carnegie Center, Suite 300 Princeton, New Jersey 08540

VanDeMark Chemical Inc. One North Transit Rd. Lockport, New York 14094

New York State Department of Environmental Conservation

270 Michigan Ave. Buffalo, New York 14203

Submitted By: Golder Associates Inc.

2430 N. Forest Road, Suite 100 Getzville, NY 14068 USA

Distribution:

2 copies -New York State Department of Environmental Conservation

1 copy – SNPE, Inc.

1 copy -Golder Associates Inc.

April 2016 Project No. 093-89168





Table of Contents

1.0	IN	TRODUCTION	2
2.0	SE	MI-ANNUAL MONITORING AND INSPECTIONS	4
2.1	ı	Passive DNAPL Collection Trench	4
2	.1.1	May 2015 Inspection	4
2	.1.2	November 2015 Inspection	4
2.2	(Creek Bank Area	4
2	.2.1	May 2015 Inspection	4
2	.2.2	November 2015 Inspection	5
2.3	(Collection Trench Overflow Filter Sump Structure	5
2	.3.1	May 2015 Inspection	
2	.3.2	November 2015 Inspection	6
3.0	SE	MI-ANNUAL GROUNDWATER MONITORING	7
3.1	I	Introduction	7
3.2	(Creek Bank Piezometers	7
3	.2.1	Piezometer Development	7
3	.2.2	Piezometer Sampling & Analytical Results	7
3.3	ı	Plant Monitoring Well Sampling & Analytical Results	8
3.4	ı	Filter Sump Structure Sampling & Analytical Results	9
4.0	MA	AINTENANCE AND CLEAN-OUT ACTIVITIES	. 11
5.0	RE	FERENCES	. 12

1

List of Tables

Table 3-1	2015 Groundwater and Vault Monitoring Results
Table 3-2	Historic Groundwater and Vault Monitoring Results

List of Figures

Figure 1-2 OMP Site Plan- VDM Plant and Creek Bank Area

Figure 3-1 Creek Bank Area Site Plan

Appendices

Appendix A Operations and Monitoring Summary Inspection Forms

Appendix B Sample Collection Field Logs



2

1.0 INTRODUCTION

Golder Associates Inc. (Golder) under contract to SNPE Inc. (SNPE) and in close cooperation with VanDeMark Chemical Inc. (VDM), the Site owner, has prepared this annual monitoring and inspection summary report for 2015, in support of the Operations and Maintenance Plan (OMP) that was prepared for the VDM Lockport facility by Golder (Golder, April 2013). This summary report describes the activities that were undertaken during 2015 to maintain and monitor the effectiveness of the remedial system that was implemented at the VDM site along a portion of VDM's property adjacent to the north bank of Eighteen Mile Creek Bank (hereafter referred to as the "Creek Bank Area") and associated groundwater/DNAPL impacts at VDM's manufacturing facility in Lockport, New York. The VDM facility is located in the north central sector of the City of Lockport city limits, as shown on Figure 1-1.

The purpose of the constructed remedial system was twofold: create a barrier to restrict and contain the migration of dense non-aqueous phase liquid (DNAPL) consisting of coal tar residuals that have been exiting the fractured bedrock formation at, or near, the toe of the Creek Bank area slope; and promote the collection of the DNAPL in a defined permeable trench for subsequent mechanical removal, if required. This annual monitoring/inspection report documents the extent to which these objectives are being met based on the following primary activities that were conducted throughout the 2015 monitoring period:

- Three visual inspections for presence of DNAPL in the passive upgradient permeable collection trench installed along the grout cutoff wall alignment;
- Three visual inspections for presence of DNAPL along the Eighteen Mile Creek bank areas where coal tar residuals have previously been observed;
- Semi-annual groundwater sampling of the four piezometers installed upgradient and downgradient of the grout cutoff wall;
- Semi-annual sampling of the water discharge from the collection trench Filter Sump overflow chamber;
- Semi-annual groundwater sampling of two representative monitoring wells located within the VDM Plant at the top of the Niagara Escarpment;
- Visual inspection of the Filter Sump media (i.e., filter sand and activated carbon) and sump chamber;
- Visual inspection of the passive collection trench for the presence of DNAPL residuals;
- Visual inspection of the collection trench permeable stone media and DNAPL observation sumps.

Figure 1-2 shows the locations of the areas both within the active VDM facility and to the south along the Eighteen Mile Creek Bank Area (Creek Bank Area) that were monitored as part of this annual report.





The following sections present details on the frequency and methodologies employed for the inspections, monitoring and maintenance activities described above. The documentation and reporting associated with these activities are also described and provided.

3

2.0 SEMI-ANNUAL MONITORING AND INSPECTIONS

On March 18, 2015, the NYSDEC approved the petition dated March 5, 2015 from SNPE to reduce annual inspections from quarterly to semi-annually to coincide with the semi-annual groundwater sampling events. This schedule was implemented for the 2015 O & M reporting period.

4

2.1 Passive DNAPL Collection Trench

Visual inspections were performed on the DNAPL collection trench by Golder personnel in May, and November 2015. Based on the visual inspections performed by Golder personnel, the following observations were recorded and summarized on written inspection reports, included in this report as Appendix A.

2.1.1 May 2015 Inspection

DNAPL accumulation was not observed during the May 2015 inspection period within the DNAPL observation sumps located within the DNAPL collection trench based on visual inspection and use of a wooden probe stick inserted to bottom of four, 4-inch diameter PVC DNAPL observation sumps (OS-1, OS-2, OS-3 and OS-4). Groundwater was encountered in OS-1 and OS-3, while OS-2 and OS-4 were dry. Snow covered ground conditions limited the visual inspection of some sheltered slope areas. The down-gradient slope was generally obscured by snow cover, while the up-gradient slope was only partially covered.

2.1.2 November 2015 Inspection

DNAPL accumulation was not observed during the November 2015 inspection period within the DNAPL observation sumps located within the DNAPL collection trench based on visual inspection and use of a stick to probe the bottom of four, 4-inch diameter PVC DNAPL observation sumps (OS-1, OS-2, OS-3 and OS-4). Groundwater was encountered in OS-1 and OS-3, while OS-2 and OS-4 were dry. Large amounts of dead foliage inhibited the visual inspection of both the up and down-gradient slopes.

2.2 **Creek Bank Area**

Visual inspections were performed along approximately 300 feet of the Creek Bank Area down gradient of the DNAPL collection trench in May and November, 2015. Based on the visual inspections performed by Golder personnel, the following observations were recorded and summarized on written inspection reports, included in this report as Appendix A.

2.2.1 May 2015 Inspection

DNAPL accumulation was observed by the NYSDEC and Golder representatives along a 15-20 long section of the creek bank south of PZ-1 on the down gradient side of the collection trench during the May 2015 inspection. The small outcroppings of solidified DNAPL were discovered intermingled within portions of a partially exposed large stone formation assumed to be a part of a former buried mill race structure



adjacent to the creek bank. The large rock structure was not removed during the construction of the collection trench as it was critical to the structural support of the creek bank in that area. It was agreed that all exposed DNAPL seeps observed during the May inspection would be removed by Golder during the November 2015 inspection visit. During the May inspection no other signs of DNAPL were observed along the up-gradient slope and toe area of the creek bank north of the DNAPL collection trench, as well as the down-gradient portion adjacent to the creek.

2.2.2 November 2015 Inspection

During the November 2015 inspection the exposed DNAPL residuals noted during the May 2015 inspection were removed by Golder personnel with hand tools and placed in 5 gallon containers. A total of 3 containers were filled (approximately 15 gallons by volume) of DNAPL residuals were removed and transferred to a poly lined 55 gallon steel drum supplied by VanDeMark. The material was removed from a 15-20 long section of the creek bank south of the buried stone structure which is also south of the PZ-1 location. No additional DNAPL accumulations were observed during the November 2015 inspection period along the up-gradient slope and toe area of the creek bank north of the DNAPL collection trench, although remaining foliage at the time of inspection may have limited full observation of possible small outbreaks. New DNAPL accumulations were not observed along the down-gradient portion adjacent to the Creek.

2.3 Collection Trench Overflow Filter Sump Structure

Inspections of the collection trench drainage/filtration system including the Filter Sump and gravel filled sump drain were performed during the May and November, 2015 inspection periods. Visual observations included noting the general condition of the drainage sump filter media and any evidence of excessive solids accumulation, presence of DNAPL residuals or filter media washout. Based on the visual inspections performed by Golder personnel, the following observations were recorded and summarized on written inspection reports, included in this report as Appendix A.

2.3.1 May 2015 Inspection

During the May 2015 inspection period, DNAPL or other signs of contamination were not present on the surface of accumulated water or filter media in the filter sump. There was no erosion or disturbance of the drainage sump filter media, with only negligible sediment present on the top of the sand media. The overflow section (filtered water discharge chamber) of the sump structure was clear and free of any sediment or solids. Water was observed to be freely overflowing to the discharge pipe.

The gravel filled sump drainage area adjacent to the filter sump was observed to be in good condition with no evidence of surficial water overflow, silting or DNAPL.



2.3.2 November 2015 Inspection

During the November 2015 inspection period, DNAPL or other signs of contamination were not present on the surface of accumulated water or filter media in the filter sump. There was no erosion or disturbance of the drainage sump filter media, with only a small amount sediment present on the top of the sand media. The overflow section (filtered water discharge chamber) of the sump structure was clear and free of any sediment or solids. Water was observed to be freely overflowing to the discharge pipe.

6

The gravel filled sump drainage area adjacent to the filter sump was observed to be in good condition with no evidence of surficial water overflow, silting or DNAPL.



3.0 SEMI-ANNUAL GROUNDWATER MONITORING

3.1 Introduction

A total of four (4) piezometers located in the Creek Bank Area were installed in 2012 and two (2) bedrock monitoring wells located at the top of the escarpment within the VDM plant site and installed in 1999 and 2006 were monitored to establish a groundwater quality baseline data set at the site as described below. A table summarizing the piezometer, monitoring well and DNAPL Observation Sump installation information (Table 3-1) was provided in the Operations & Maintenance Plan (OMP) report previously submitted by Golder (Golder, April 2013).

7

3.2 Creek Bank Piezometers

Piezometer development and semi-annual groundwater sampling was performed on the four (4) piezometers (PZ-1, PZ-2, PZ-3 and PZ-4) installed as part of the Creek Bank Corrective Measures in 2012 (refer to Figure 3-1) as described below.

3.2.1 Piezometer Development

The 2-inch diameter piezometers were purged prior to both the May and November 2015 sampling events. Purging methods implored by Golder personnel involved the use of dedicated polyethylene bailers to remove standing water and sediment trapped in well screens to insure representative samples of groundwater at each location. Purging of piezometers continued until extraction of three well volumes was complete and field measurements for turbidity, pH, specific conductivity and temperature stabilized.

Well purging data, including the duration of the development process, methods employed, and the volume of water removed, are included on the Sample Collection Field Logs provided in Appendix B. Water purged from the piezometers during the development process was collected by Golder personnel in appropriate containers and discharged into VDM's process sewer manhole.

3.2.2 Piezometer Sampling & Analytical Results

Following development, groundwater samples were collected from each of the piezometers to assess the general groundwater quality up gradient and down gradient of the grout wall and bedrock cutoff system. Pre-sampling activities included determining the piezometer's water elevation, a piezometer-maintenance check, and non-aqueous phase liquid (NAPL) determination. All piezometers were measured, however piezometer PZ-1 was found to be dry during sampling activities and no measurements could be obtained. After completion of these pre-sampling activities, the piezometers were purged of three well volumes (or until dry). A sample of the third well volume was measured for the following field parameters: pH, temperature, and specific conductivity.



Groundwater samples were then collected for chemical analysis using dedicated polyethylene bailers. The groundwater samples were shipped via courier under proper chain of custody procedures to TestAmerica Laboratories, Inc. (TestAmerica) in Buffalo, New York, a New York State Department of Health Environmental Laboratory Accreditation Program (ELAP) certified laboratory, within 24 hours of collection. Water purged from the piezometers during the sampling activities was collected in appropriate containers by Golder personnel and discharged into VDM's process sewer manhole. At the conclusion of each semi-annual sampling event, the physical condition of the piezometers and protective casings/locks was also noted and any recommended repairs or maintenance required (if necessary) was documented on the sample collection field logs provided in Appendix B.

All piezometer groundwater samples collected were analyzed for TCL Volatile Organic Compounds (VOCs) in accordance with USEPA Method 8260B and TCL Semi-volatile Organic Compounds (SVOCs) in accordance with USEPA Method 8270C and the analytical results are presented in Table 3-1. This is the third year of Site monitoring following the completion of the Corrective Measures, therefore the 2015 sample results are also presented in Table 3-2 comparing this year's analytical results to the 2013 and 2014 groundwater sampling events analytical results.

The results of the piezometer sampling and analyses identified one SVOC, phenol, in PZ-3, in both sampling events as exceeding the NYSDEC Part 703 groundwater quality standards (GWQS). The detection of phenol in this piezometer is consistent with previous sampling event findings. No other compounds were detected above the GWQS in the piezometers. Golder will assess the piezometer groundwater data for trends and evaluate the effectiveness of the Corrective Measures as additional analytical data is collected during future annual monitoring events.

3.3 Plant Monitoring Well Sampling & Analytical Results

Semi-annual groundwater sampling was performed on only one (1) existing monitoring well, MW-7D, located within the operational portion of the VDM facility at the top of the escarpment, to assess the general groundwater quality at these up gradient locations on the top of the escarpment. Monitoring Well MW-7D was installed in 2006 by Benchmark as part of voluntary site investigations associated with the sale of the facility. During the June 2014 sampling event MW-3D, installed in 1999 by Dames and Moore and located within the operational portion of the VDM facility, was noted as being damaged by plant snow removal activities the previous winter/spring, therefore no samples were obtained from MW-3D during the 2014 and 2015 sampling events and a replacement well was not identified for sampling. Location of the wells is presented on Figure 1-2.

Pre-sampling activities included measuring the well's water elevation, a well-maintenance check, and non-aqueous phase liquid (NAPL) determination. After completion of these pre-sampling activities, the wells were purged of three well volumes (or until dry). A sample of the third well volume was measured for



the following field parameters: pH, temperature, and specific conductivity. Groundwater samples were then collected for chemical analysis using dedicated polyethylene bailers. The groundwater samples were shipped via courier under proper chain of custody procedures to Test America within 24 hours of collection. Water purged from the wells during the sampling activities was collected in appropriate containers by Golder personnel and discharged into VDM's process sewer manhole.

All monitoring well groundwater samples collected were analyzed for TCL Volatile Organic Compounds (VOCs) in accordance with USEPA Method 8260B and TCL Semi-volatile Organic Compounds (SVOCs) in accordance with USEPA Method 8270C and the analytical results are presented in Table 3-1. This is the third year of Site monitoring following the completion of the Corrective Measures and 2015 sample results are also presented in Table 3-2 to compare 2015 analytical results to the results from the 2013 and 2014 groundwater sampling events analytical results.

The results of the monitoring well sampling and analyses identified six VOCs in the spring and fall 2015 monitoring events as exceeding the NYSDEC Part 703 GWQS. One SVOC, acenaphthene was detected in monitoring well MW-7D during the May 2015 sampling event above the GWQS.

VOCs detected in MW-7D within the operational portion of the VDM facility were not detected in down-gradient piezometers. Golder will continue to assess Plant monitoring well groundwater data for trends and evaluate potential impacts of the up-gradient groundwater on the Corrective Measures as additional analytical data is collected from future annual monitoring events.


At the conclusion of each semi-annual sampling event, the physical condition of the monitoring wells and protective casings or covers was noted and any recommended repairs or maintenance required (if necessary) was documented on the sample collection field logs provided in Appendix B.

3.4 Filter Sump Structure Sampling & Analytical Results

Semi-annual sampling was performed on the collection trench drainage/filtration system overflow chamber (Filter Sump) as part of the annual site inspection activities performed by Golder personnel in 2014. One aqueous sample was collected from the overflow chamber of the Filter Sump to assess the general performance of the grout wall and bedrock cutoff system. Pre-sampling activities included inspection of the vault filter media, a vault-maintenance check, and non-aqueous phase liquid (NAPL) determination.

After completion of these pre-sampling activities, a sample of the Filter Sump effluent water was measured for the following field parameters: pH, temperature, and specific conductivity. Aqueous samples were then collected for chemical analysis by direct fill methods. The aqueous samples were shipped via courier under proper chain of custody procedures to TestAmerica within 24 hours of collection.





One VOC, chloroform was detected in the Filter Sump sample during the November 2015 effluent sampling. One SVOC was detected bis(2-ethlhexyl)phthalate above the GWQS in the May sampling event as exceeding the NYSDEC Part 703 groundwater quality standards (GWQS). Bis(2-ethlhexyl)phthalate is a common laboratory contaminant and was not detected in the 2013 or 2014 sample results, therefore they are considered to be an anomalous result in this sample. No other compounds were detected above the GWQS.

At the conclusion of each semi-annual sampling event, the physical condition of the collection vault was noted and any recommended repairs or maintenance required (if necessary) was documented on the sample collection field logs provided in Appendix B.





4.0 MAINTENANCE AND CLEAN-OUT ACTIVITIES

As described in Section 2.0 above, the inspections conducted in 2015 did not find evidence of DNAPL impacts to the DNAPL Collection Trench or Filter Sump, therefore maintenance or clean-out activities were not necessary or performed on these components of the Creek Bank Area remedial system. Repairs to the piezometers and monitoring wells were not required since no damage was observed to the protective casings, locks or the monitoring well or piezometer risers.

Approximately 15 gallons of solidified DNAPL residuals was removed from the creek bank south of PZ-1 as described in Section 2.2. The collected material was transferred into a poly lined 55 gallon steel drum for characterization and disposal by VDM. Some routine trimming of tree branches and debris clearing was performed by VDM along the access road down to the bottom of the Creek Bank Area to maintain good access to the monitoring piezometers and Filter Sump.





5.0 REFERENCES

1.) Golder Associates Inc., SNPE-VanDeMark Corrective Actions, Operation & Maintenance Plan, prepared for SNPE Inc., April 2013.



SNPE-VANDEMARK SITE 2015 GROUNDWATER AND VAULT MONITORING RESULTS LOCKPORT, NY

			•									T	
Lab ID	NYSDEC Part 703	480-80722-4	480-90488-4	480-80722-5	480-90488-5	480-80722-1	480-90488-1	480-80722-2	480-90488-2	480-80722-3	480-90488-3	480-80722-6	130617007-007
Sample Date	Groundwater	5/20/2015	11/4/2015	5/20/2015	11/4/2015	5/20/2015	11/4/2015	5/20/2015	11/4/2015	5/20/2015	11/4/2015	5/20/2015	11/4/2015
Sample ID	Quality Standards	Vault Effluent	Vault Effluent	MW-7D	MW-7D	PZ-2	PZ-2	PZ-3	PZ-3	PZ-4	PZ-4	Dup (Vault)	Dup (Vault)
Units	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L
Volatile Organics by GC/MS (US EPA	olatile Organics by GC/MS (US EPA Method 8260B)												
1,1,1-Trichloroethane	5	-	-	52	59	-	-	-	-	-		-	-
1,1-Dichloroethane	5	-	-	180	210	-	-	-	-	-	-	-	-
1,1-Dichloroethene	5	-	-	54	60	-	-	-	-	-	-	-	-
1,2-Dichloroethane	0.6	-	-	3.6 J	4.2 J	-	-	-	-	-	-	-	-
2-Butanone	NV	-	-	-	-	-	-	-	-	-	-	-	-
Acetone	NV	-	-	-	-	-	-	9.1 ^J	4.9	-	-	-	-
Carbon disulfide	60	-	-	-	-	-	-	-	3	-	-	-	-
Carbon tetrachloride	5	-	-	-	-	-	-	-	-	-	-	-	-
Chloroethane	5	-	-	68	110	-	-	-	-	-	-	-	-
Chloroform	7	2.4	11	-	-	1.6	0.54 ^J	-	-	-	-	2.6	11
cis-1,2-Dichloroethene	5	-	-	-	-	-	-	-	-	-		-	-
Ethylbenzene	5	-	-	-	-	-	-	-	-	-	-	-	-
Trichloroethene	5	-	-	-	-	-	-	-	-	-	-	-	-
Vinyl chloride	2	-	-	13	15	-	-	-	-	-	-	-	-
Semivolatile Organics by GC/MS (US	EPA Method 82700	C)											
Biphenyl	5	-	-	3.3 J	-	-	-	-	-	-	-	-	-
2,4-Dimethylphenol	5	-	-	-	-	-	0.56 J	-	-	-	-	-	-
2-Methylnaphthalene	NV	-	-	-	-	-	-	1.9 J	2 J	-	-	-	-
2-Nitroaniline	5	-	-	-	-	-	-	-	-	-	-	-	-
4-Methylphenol	5	-	-	-	-	-	-	1.5 J	1.4 J	-	-	-	-
4-Methylphenol & 3-Methlyphenol	5	-	-	-	-	-	-	-	-	-	-	-	-
Acenaphthene	20	-	-	42 J	-	3.5 J	5	4.2 J	3.7 J	-	-	-	-
Acenaphthylene	NV	-	-	0.54 J	-	-	-	-	-	-	-	-	-
Anthracene	NV	-	-	0.84 ^J	-	0.75 ^J	-	0.32 J	0.38 ^J	-	-	-	-
Benzaldehyde	NV	-	-	-	-	-	0.26 J	-	-	-	-	-	-
Benzo(a)anthracene	NV	-	-	-	-	-	-	-	-	-	-	-	-
Benzo(a)pyrene	ND	-	-	-	-	-	-	-	-	-	-	-	-
Benzo(b)fluoranthene	NV	-	-	-	-	-	-	-	-	-	-	-	-
Bis(2-ethylhexyl)phthalate	5	7.9	3.2 J	-	-	-	1.8 J	-	2.7 J	-	1.7 J	-	-
Butyl benzyl phthalate	5	-	0.47 JB	0.48 J	-	-	0.47 JB	-	0.48 ^{JB}	-	0.61 ^{JB}	-	0.48 ^{JB}
Caprolactam	NV	-	-	-	2200	-	140 DL	- ,	280	-	110	-	-
Carbazole	NV	-	-	5.2	-	0.88	1.2	0.62 J	0.48 J	-	-	-	-
Chrysene	NV	-	-	-	-	0.42 J	0.33 J	-	-	-	-	-	-
Dibenzofuran	NV	-	-	32	-	- JB	0.51 ^J	-	-	-	-	- ID	-
Di-n-butyl phthalate	50	-	-	-	-	0.40	- 4 4 J	-	-	-	-	0.3 ^{JB}	-
Fluoranthene	NV	-	-	1.2 J	-	0.96 J	1.4	-		-	-	-	-
Fluorene	NV	-	-	22	-	1.5	2.2 J	1.1	0.76	-	-	-	-
Isophorone	NV	-	-	-	-	-	-	-	-	-	-	-	-
N-Nitrosodi-n-propylamine	NV	-	-	- 1.4 JB	-	- JB	- 4.4 J	- B	-	-	-	-	-
Naphthalene	10	-	-	1.4	-	2.4	1.4	/	6.6	-	-	-	-
Nitrobenzene	0.4	-	-	-	-	-	-	- 10	- 	-	-	-	-
Phenanthrene	50	-	-	6.2	-	3.1 ^J	6.1	1.6 J	1.5 J	-	-	-	-
Phenol	1* NV	-	-	0.47 J	-	- 1.7 J	- 2 J	50	73 J	-	-	-	-
Pyrene	NV	-	-	U.4/ -	-	1.7	2 -	-	U.46 "	-	-	-	-

Kev: Vault Effluent Sample Results

Plant Monitoring Well Sample Results

Piezometer Sample Results

Footnotes:

- Compound not detected above the Analytical Method Detection Limit

BOLD = Value exceed the groundwater quality standards.

* = The sum of all phenols

NV = No GW Quality Standard

- = Analyte detected at a level less that Reporting Limit and greater than or equal to the Method Detection Limit.
- $^{\rm B}$ = Analyte detected in the method blank.

SNPE-VANDEMARK SITE HISTORIC GROUNDWATER AND VAULT MONITORING RESULTS LOCKPORT, NY

							_	_																										
Lab ID	NYSDEC Part 703	130617007-001	130930005-006B	480-62067-2	480-71961-4	480-80722-4	480-90488-4	130617007-003	130930005-001B	-	130617007-002	130930005-002B	480-62067-1	480-71961-5	480-80722-5	480-90488-5	130617007-004	130930005-003B	480-62067-6	480-71961-1	480-80722-1	480-90488-1	130617007-005	130930005-004B	480-62067-3	480-71961-2	480-80722-2	480-90488-2	130617007-006	130930005-005B	480-62067-5	480-62067-3	480-80722-3	480-90488-3
Sample Date	Groundwater	6/13/2013	9/26/2013	6/17/2014	11/25/2014		11/4/2015	6/13/2013	9/26/2013		6/13/2013	9/26/2013	6/17/2014	11/25/2014	5/20/2015	11/4/2015	6/13/2013	9/26/2013	6/17/2014	11/25/2014	5/20/2015	11/4/2015	6/13/2013	9/26/2013	6/17/2014	11/25/2014	5/20/2015	11/4/2015	6/13/2013	9/26/2013	6/17/2014	11/25/2014	5/20/2015	11/4/2015
Sample ID	Quality Standards	Vault Effluent	Vault Effluent	Vault Effluent	Vault Effluent	Vault Effluent	Vault Effluent	MW-3D		MW-3D+	MW-7D±	MW-7D	MW-7D	MW-7D	MW-7D	MW-7D	PZ-2	PZ-2	PZ-2	PZ-2	PZ-2	PZ-2	PZ-3	PZ-3	PZ-3	PZ-3	PZ-3	PZ-3	PZ-4	PZ-4	PZ-4	PZ-4	PZ-4	PZ-4
Units	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L	ug/L
Volatile Organics by GC/MS (US EPA	Method 8260B)																																	
1,1,1-Trichloroethane	5	-	-	-	-	-	-	11	13		19	71	97	140	52	59	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	- '	-	-
1,1-Dichloroethane	5	-	-	-	-	-	-	87	120		79	260	-	350	180	210	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-
1,1-Dichloroethene	5	-		-	-	-	-	27	38		21	70	77	110	54	60	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			-
1,2-Dichloroethane	0.6	-	•	-	•	-	-	17	23		2 J	-	4.8	6.6	3.6 J	4.2 J	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			-
2-Butanone	NV	-	-	-	-	-	-	-	-		-	-	-	-	-	-	-	35	-	-	-	-	-	-	-	-	-	-	-	-	-			
Acetone	NV	1.8 ^{J, B}	-	-	-	-	-	-	-		-	-	-	-	-	-	-	12	-	-	-	-	-	8.6 J	16 "	6 ¹	9.1 ^J	4.9 J	8.3 ^{J. B}	-	-		-	-
Carbon disulfide	60	-		-	-	-	-	-	-		-	-		-	-	-	-	-	-	-	-	-	-	-	0.61 J	-	-	3	-	-	-			-
Carbon tetrachloride	5	-		-	-	-	-	-	-			-	0.53	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			-
Chloroethane	5		-	-	-	-	-	-	-		20	58	73	100	68	110	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			-
Chloroform	7	4.2 J		3.7	9.6	2.4	11		-		-	-	0.8	-	-	-	12	14	3.2	0.6 J	1.6	0.54	-	-	-	-	-	-	-	-	-	-	_	
cis-1,2-Dichloroethene	5	-	-	-	-	-	-	l -	-		-	-	0.98 J	-	-	-	· ·	-	-	-	-	-	H -	-	-	-	-	-	-	-	-			
Ethylbenzene	5		-	-	•	-	-	· ·	-		2.9 J	-	2	-	-	-		-	-	-	-	-	· ·	-	-	-	-	-	-	-	-			
Trichloroethene Vinvl chloride	5	-	-	-	-:-	-	-	17	26		5.3 J	23	1.1	19	13	15	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-
	_	-	-	-	-	-	-	1/	26		5.3	23	21	19	13	15	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Semivolatile Organics by GC/MS (US	EPA Method 8270	C)				1								1	1			T				,		1	,	,		1						
Biphenyl	5	-	-	-	-	-	-	-	-		-	-	-	5	3.3	-	-	-	-	0.1 J	-	-	-	-	-	-	-	-	-	-	-			-
2,4-Dimethylphenol	5	-	-	-	-	-	-	-	-		-	-	-	0.48 J	-	-	-	-	-	0.9 J	-	0.56 J	-	-	-	-	-	-	-	-	-		-	-
2-Methylnaphthalene	NV	-	-	-	-	-	-	-	-		-	1.1 J	-	-	-	-	-	-	-	-	-	-	-	-	0.79 J	1.3 J	1.9 J	2 J	-	-	-	'	-	-
2-Nitroaniline	5		-	-	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	1.1 J	-	-	-		-	-	-	-
4-Methylphenol	5	-	-	-	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	2.6 J	-	1.2 J	1.5 J	1.4 J	-	-	-	-	-	-
4-Methylphenol & 3-Methlyphenol	5	-	-	-	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	5.9 J	-	-	-	-	-
Acenaphthene	20	-	-	-	-	-	-	2.5 J	2.9 J		27	28	12	39	42 DL	-	-	1.4 J	0.88 J	4.1 J	3.5 J	5	-	3.7 J	1.6 J	2.7 J	4.2 J	3.7 J	-	-	-	-	-	-
Acenaphthylene	NV	-	-	-	-	-	-	-	-		1.2 J	-	-	0.56 J	0.54 J	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		-	-
Anthracene	NV	-	-	-	-	-	-	-	-		-	-	0.22 J	1 J	0.84 J	-	-	-	0.23 J	1.2 J	0.75 J	-	1.1 J	- 1	-	-	0.32 J	0.38 J	-	-	-		-	-
Benzaldehyde	NV	-		-	0.86 ^{JB*}	-	-	-	-		-	-	-	0.84 ^{JB*}	-	-	-	-	-	0.87 ^{JB}	-	0.26 J	-	-	-	1.5 JB*	-	-	-	-	-	0.89 JB*	-	-
Benzo(a)anthracene	NV	-	-	-	-	-	-	-	-		-	-	-	-	-	-	-	2.0	0.38 J	0.53	-	-	1.3	_ 3	-	-	-	-	-	-	-		-	-
Benzo(a)pyrene	ND	-	-	-	-	-	-	-	-		-	-	-	-	-	-	-	1.6 J	-	0.5 J	-	-	1 ^J	- J	-	-	-	-	-	-	-		-	-
Benzo(b)fluoranthene	NV	-	-	-	-	-	-	-	-		-	-	-	0.28 J	-	-	-	-	-	0.43	-	-		-	-	-	-		-	-				
Bis(2-ethylhexyl)phthalate	5	-		-	3.1 J	7.9	3.2 JB	-	-		-	2.5 J	6.7 J	3.5 J		-	1.5 J	1.1 J	-	3.4 J	-	1.8 J	1.2		-	6.3	-	2.7 J	-	-	15 ³	3.1 ^J		1.7 J 0.61 JB
Butyl benzyl phthalate	5 NV	-	-	-	<u> </u>	-	0.47 ^{JB}	<u> </u>	-		-	-	-	-	0.48	2200	-	-	-	-	-	0.47 JB 140 DL	<u> </u>	<u> </u>	-	-	-	0.48 ^{JB}	-	-	-			110
Caprolactam Carbazole	NV NV	-	-	-		-	-	<u> </u>	1.2 J		2.3 J	5.1	2.2	10		2200	<u> </u>	+ -	-	1.1 J*	0.88 J	1.2 J	+ -	-	-	1 -	0.62 J	0.48 J	-	-	-			110
Chrysene	NV NV				-:-	-		1:	1.2		2.3	5.1	2.2	10	5.2		1.1 J	2.2 J	0.42 J	0.59 J	0.88	0.33 J	1.4 J	_ J			0.62	0.48				-		
Dibenzofuran	NV NV						-	+ :	1.2		16	18	6.5 J		32		1.1	2.2	0.42	0.59	0.42	0.51	1.44	+ -			-	-		-		-		-
Di-n-butyl phthalate	50	12 J.B				-	-	2 J.B	1.2		1.5 J. B	2.5 J	0.0	27	32				-	-	0.48 JB	0.01	1				_	-			-	0.31 J		
Fluoranthene	NV	1.2		-			-		1.47		-	1.5	0.34 J	1.3	1.2 J	-	1.1	2.6 J	0.47	1.7	0.48	1.4 J	1.6 J	- 1	-		-	-		-	-	0.01		-
Fluorene	NV	-	-	-	-	-	-		_		8.9	9.7	4.3	18	22	-	-	-	0.32	1.9 J	1.5	2.2		-	0.34 J	0.64 J	1.1 J	0.76 J	-	-	_	-		_
Isophorone	NV	-				-	-	-	-		-	-	-	10		-	-	-	-	-	-	-		-	-	-	-	-	-		-	-		
N-Nitrosodi-n-propylamine	NV	-		-		-	-	-	-		-	-	-	-	-	-	-	-	-	4.1 JB	-	-		-	-	-	-	-	-		-	4.2 JB	-	
Naphthalene	10	-	-	-	-	-	-	-	-		8.2	9.8	2.5	8	1.4 JB	-	-	1.5 J	0.54 J	1.3 J	2.4 JB	1.4 J	-	3.4 J	2.5	4.4 J	7 ^B	6.6	4.3 J	-	-		-	
Nitrobenzene	0.4	-	-	-	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	0.49 J	-		-		-	-	-	-
Phenanthrene	50	-	-	-	-	-	-	-	-		1.8 J	4.2 J	1.1 J	7.5	6.2	-	1.2 J	3.3 J	1 J	5.4	3.1 J	6.1	3.3 J	2.4 J	0.52 J	1.4 J	1.6 J	1.5 J	-		-	-	-	-
Phenol	1*	-		-		-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	1	130	38	53	50	73 J	260	1.4 J	-	0.61 J	-	
Pyrene	NV			-		-	-	-	-		-	1.1 J	-	0.74 J	0.47 J		1.9 J	4.4 J	0.74 J	2.9 J	1.7 J	2 J	2.8 J	-	-	-	-	0.46 J		-	-		-	_

Key:
Vault Effluent Sample Results
Plant Monitoring Well Sample Results
Piezometer Sample Results

- Footnotes:

 Compound not detected above the Analytical Method Detection Limit

 BOLD

 Value exceed the groundwater quality standards.

 This well was damaged and unable to be sampled.

 In 2013 this sample was incorrectly labeled as MW-2D on chain of custody and laboratory report

 The sum of all phenols

 NV = No GW Quality Standard

Qualifications:


J = Analyte detected at a level less that Reporting Limit and greater than or equal to the Method Detection Limit. Concentrations in this range are estimated.

B = Analyte detected in the method blank.


GOLDER ASSOCIATES Tables 3-1 and 3-2 - 2015 Groundwater and Vault Results Summary.xlsx/Table 3-2 (2015)

page 2 of 2







1.) BASE MAP TAKEN FROM U.S.G.S. 7.5 MINUTE QUADRANGLE OF LOCKPORT, NEW YORK DATED 1980.



NJ Authorization #24GA28029100	SCALE	AS SHOWN	TITLE
Golder Golder	DATE	02/04/11	
Associates	DESIGN	AML	SITE LOCATION MAP
Buffalo, New York	CADD	GLS	
FILE No. 09389168A011	CHECK		I
PROJECT No. 093-89168 REV. 0	REVIEW		SNPE - VANDEMARK CHEMICAL FIGURE 1-1





APPENDIX A

OPERATIONS AND MONITORING SUMMARY INSPECTION FORMS

OPERATIONS & MONITORING SUMMARY

SHEET 1 OF 2

PROJECT NUMB	ER: 093-89168	PROJECT TITLE:	Creek Bank Corrective Measures -Site No. 932149	
OWNER:	SNPE - VanDeMark Chemic			
LOCATION: _	Lockport, New York	SUB CONTRACTOR(S):		
	DATE: 5/2	0/15		
WEATHED.	TEMPERATURE:	LOW: 60 @	ні с н <u>6б</u> @	
WEATHER: CLOUD COVER	fangul.	PRECIPITATION	HIGH & @ WIND W/A	
GOLDER PER	SONNEL ON SITE:			
		TONATHAN TAY	Kon	
SUMMARY O	F FIELD INSPECTION	OBSERVATIONS:		
	/		W/ MIKE HONTON OF NYSTEC	
0 EFF	ENKAT VALLET	: wager was	OBSERVED TO BE CLEAR &	
1		AULUADIO DISTERNIL	wind obstitute.	
OR	TOP OF FIL	THE SAND MEDIL	MINOR SEDIMENT ACCUMULATION	
ON	TOP OF 3A	NO BED.		
(2) obs	enoped son	1ps;	. NO SHEEN ON TWAPE DEJECTED (PROSED	7
05-	1: WATER PI	resent (4200)		
05-	2: Dry - NO	DNAPL PRESENT	NO SHELD OR TWAPE DEFECTED (PROSE	0)
05-	-3: water pla	LIENT (8)		
05-	4: DAY -NO	DNAPL PRESENT	ELOPE : TOE ANEA (N. OF DNAPL COLLEGED	
(3) 0B	SENJATIONS ENCH): NO NE	w DNAPE ACOM	SCOPE , TOE AREA (N. OF DWAR COLLEY TO CLATIONS OFFICENT TO CALEK ! SEVERAL	
(A) 03	ERVATIONS OF	LOWN GRADIEN 3	cope Application	
SMA	L ONAPE OUTBI	CANES OBSERVED	SOUTH OF PZ-1 ON STEEP BANK	- 1
GOLDER AC	TIVITIES AND TEST R	ESULTS: SECTION THE	SOUTH OF PZ-1 ON STEEP BANK OUGHT TO BE SOUTH FACE OF BURIED ST E, DEPOSITS FOUND IN A 15:- 20 LONG	anes.
- If W.	AS HENERD WY.	DOIS INSIEGRON !	NAPL DEPOSITS WOULD BE PEOPLE SAMPLING EVENT.	
			,	
]
VA	Golder		SUBMITTED BY	
A	ssociates		- Javan 1. I vova	

GOLDER FORM: R4-0699 (JANUARY 2005)

FIELD MONITORING SUMMARY

PROJECT NUMBER: 093-89/68 OWNER: SNPE-Var Dy My 2 LOCATION: Lockport, New York SUB CONTRACTOR(S): SHEET 1 OF 2 PROJECT TITLE: Creek Park Corrective Measures CONTRACTOR: SUB CONTRACTOR(S):
WEATHER: PRECIPITATION: TEMPERATURE: ~73°F WIND: //s/d
GOLDER PERSONNEL ON SITE: Patrick T. Martin, Jonathan Taylor SUMMARY OF FIELD OBSERVATIONS / INSPECTIONS PERFORMED:
The inspection was coordinated my DEC personal, However no representative was pressent during the inspection.
O Inspected Effluent Wantt - water is clear & appears to be overflowing to outfall of No restriction. No evidence of DNAPL or Sheen on water
Surface or top of Sand media. Minimal Sadiment accumulation nated on top of Sand filter Surface.
05-1 -> water present to ~3.5. No DNAPL, sheen, or ador observed. OS-2 -> Dry. No DNAPL observed
OS-3 -> Water proset 8-10". No PNAPL, sheen, or odor observal.
3 Observation of ingendient Slope (North of DNAPL trench) -No new DNAPL accumulations observed (Itany lat debris)

GOLDER ACTIVITIES AND TEST RESULTS:

Dobservation of Downstron Dowgradient Slop (South of PNAP trench)

- Scen of DNAPL obsered in earlier inspection of NYSDEC was

removed from rock structure located approximately 15' cost of PZ-1.

Approximity three (3) 5 galler brekets were removed from the creek bank and streed in a 55 galler dram on Site for disposal. A larger Seems of DNAPL was Easted within the stone structure. The scen could only be particly removed due to Stability of creek bank.

Supported BY:

Golder

APPENDIX B PIEZOMETER DEVELOPMENT AND SAMPLE COLLECTION FORMS



AP20CT	ales		5	
GAI PROJECT NAME	Vantenark Change	GAI PROJECT NO.	093-89168	
SAMPLE ID.	MW-70	SOURCE CODES: RIV	ER OR STREAM, WELL,	SOIL, OTHER (CIRCLE ONE)
S management	PURGIN	G INFORMATION (IF A	PPLICABLE)	
PURGE DATE (mm/dd. CASING VOL.(Gal.) PURGING DEVICE (SE	_3.0_	GAL, PURGED (Gal.)	9.0	ELAPSED HRS. CC.15
FUNGING DEVICE (SE	EE BELOW) Boile	PURGING DEVICE MA	ATERIAL POLY	DEDICATED (V N)
	SAMP	LE COLLECTION INFO	PRMATION	
SAMPLING DATE (mm SAMPLING DEVICE (S SAMPLING DEVICE M	SEE BELOW) Bailer	DEDICATED (Y) N)		MATRIX FILTERED (Y /66
(A) AIR-LIFT PUMP (B) BLAD	DER PUMP (C) PERISTALTIC PUMP (D) SCOOP/	SHOVEL (E) BAILER (F) OTHER (SPI	ECIFY)	
	WELL	INFORMATION (IF API	PLICABLE)	
REFERENCE POINT REF. PT. ELEV.(FT. M DEPTH TO WATER (F GW. ELEV.(FT. MSL.)	REF. PT.) ~3	LAND ELEVATION (F WELL DEPTH (FT.) STICKUP (FT.) WELL DIAMETER (IN	~ 49 N/A	
w.	FIELD ME	EASURMENTS (FOUR I	REPLICATES)	Final Sample
pH (STD)				
SPEC. COND.((uS)		5.4	
TEMPERATUR	RE (C)		14,100	
OTHER (SPEC	CIFY)	/		
5	C	COMMENTS/CALCULA	TIONS	
WEATHER CONDITIO	ONS			
SAMPLE APPEARANG	CE			
	- Buc	clar to water No	adors Slight	L turbid
1" DIA. CASING CON 2" DIA. CASING CON	TAINS .041 Gal./Ft.	A CONTRACTOR OF THE CONTRACTOR		
4" DIA, CASING CON		···		
- 27	5-95			
PLEASE INCLUIDE SAMPLE	BOTTLE SIZE, BOTTLE COLOR, BOTTLE MATER	RIAL PRESERVATIVES AND ANALYT	ICAL METHODS ON LABORATOR	Y CUSTODY FORMS
			METHODO ON ENDONATOR	
				,



ASSOCI	alles			
GAI PROJECT NAME	Vondemark Chan	GAI PROJECT NO.	093-89168	
SAMPLE ID.	PZ-2	SOURCE CODES: RIV	ER OR STREAM, WELL, SOIL, OTHER (CIRCLE (ONE)
	PURGING	G INFORMATION (IF A	PPLICABLE)	
PURGE DATE (mm/dd/ CASING VOL.(Gal.) PURGING DEVICE (SE	0.15	TIME (24 HR CLOCK) GAL. PURGED (Gal.) PURGING DEVICE MA	0.5	U.LO
N - CO	V	LE COLLECTION INFO		
SAMPLING DATE (mm SAMPLING DEVICE (S SAMPLING DEVICE M	SEE BELOW) Bailor	- A PROPERTY OF THE PARTY OF TH	MATRIX FILTERED (Y MATRIX FILTERED (Y MATRIX FILTERED (Y MATRIX FILTERED (Y MATRIX	_
E237		INFORMATION (IF API		
REFERENCE POINT REF. PT. ELEV.(FT. M DEPTH TO WATER (R GW. ELEV.(FT. MSL.)	REF. PT.)	LAND ELEVATION (FT.) WELL DEPTH (FT.) STICKUP (FT.) WELL DIAMETER (INC		-4
	FIELD ME Initial Purge	ASURMENTS (FOUR I	REPLICATES) Initial Sample Final Sample	
pH (STD)			LANS .	7-
SPEC. COND.(i	us)		1.27	1
			16.2°	
OTHER (SPEC				
		OMMENTS/CAN OUT AT	FIGNS	_
	C	OMMENTS/CALCULAT	TIONS	
WEATHER CONDITIO	ONS			
SAMPLE APPEARANCE	CE Brown Ruto	der Turkid		
1" DIA. CASING CONT	TAINS .041 Gal./Ft.			
2" DIA. CASING CONT 4" DIA. CASING CONT				
	river vigo (Matheligo Spillabiliti) ikis			
DI FACE INCLUDE CAMPLE	BOTTLE SIZE BOTTLE COLAD BOTTLE MATER	IAI DOCCEDNATINGS AND ANALYS	ICAL METHODS ON LABORATORY CUSTODY FORMS.	
LEAGE INCLUDE SAMPLE	DOTTER SIZE, BUTTER CONOR, BUTTER MATER	IAL, FREDERVALIVES AND ANALY I	NETHOUS ON LABORATORY CUSTODY FURMS.	
SAMPLER SIGNATUR	RE fartly eagh		DATE 5/20/15	_



GAI PROJECT NAME	1 1 1 21 . 1	CAL DEGLECT NO	884	
GAI PROJECT NAME	e Munk Chemical	GAI PROJECT NO.	093-89168	_
SAMPLE ID. PZ	-4	SOURCE CODES: RIVER	OR STREAM WEL	, SOIL, OTHER (CIRCLE ONE)
	PURGING 1	NFORMATION (IF APP	LICABLE)	
PURGE DATE (mm/dd/yy) CASING VOL.(Gal.)	5,20,15	TIME (24 HR CLOCK) GAL. PURGED (Gal.)	09:30	ELAPSED HRS. CO:15
PURGING DEVICE (SEE BELOW)	Botton	PURGING DEVICE MATE	RIAL Poly	DEDICATED (V) N)
	SAMPLE	COLLECTION INFORM	TATION	
SAMPLING DATE (mm/dd/yy) SAMPLING DEVICE (SEE BELOW) SAMPLING DEVICE MATERIAL	5,20,15 bailor Poly	TIME (24 HR CLOCK) DEDICATED (1) N) SAMPLE TYPE - QHAB /	COMPOSITE (CIRC	MATRIX W
(A) AIR-LIFT PUMP (B) BLADDER PUMP (C) P.	ERISTALTIC PUMP (D) SCOOP/SHO	OVEL (E) BAILER (F) OTHER (SPECIF	n	
	WELL IN	FORMATION (IF APPLI	CABLE)	
REFERENCE POINT REF. PT. ELEV.(FT. MSL) DEPTH TO WATER (REF. PT.) GW. ELEV.(FT. MSL.)	Tor	LAND ELEVATION (FT./M WELL DEPTH (FT.) STICKUP (FT.) WELL DIAMETER (INCHE	~10	
	FIELD MEA	SURMENTS (FOUR RE	PLICATES) Initial Sample	Final Sample
ρH (STD)				
SPEC. COND.(uS)		_/	6.02	
TEMPERATURE (C)	/		129°C	<u> </u>
OTHER (SPECIFY)	/	/		/
5 T T T T T T T T T T T T T T T T T T T	CO	MMENTS/CALCULATIO	NS	
WEATHER CONDITIONS				
SAMPLE APPEARANCE				
				E.
1" DIA. CASING CONTAINS .041 G 2" DIA. CASING CONTAINS .163 G			- -	
4" DIA. CASING CONTAINS .652 G	al./Ft.			
A			<u> </u>	
PLEASE INCLUDE SAMPLE BOTTLE SIZE, BO	OTTLE COLOR, BOTTLE MATERIAL	, PRESERVATIVES AND ANALYTICAL	METHODS ON LABORAT	ORY CUSTODY FORMS.
	1111			
SAMPLER SIGNATURE	the second			DATE 5/20/15
	Gold	der Associates		10013



UPPOCTUTE	
GAI PROJECT NAME Vandemak Chunial	GAI PROJECT NO. 093-89168
SAMPLE ID. P2-3	SOURCE CODES: RIVER OR STREAM WELL, SOIL, OTHER (CIRCLE ONE)
PURGIN	IG INFORMATION (IF APPLICABLE)
PURGE DATE (mm/dd/yy) CASING VOL.(Gal.) PURGING DEVICE (SEE BELOW) Daile V	TIME (24 HR CLOCK) GAL. PURGED (Gal.) PURGING DEVICE MATERIAL ON BAL. DEDICATED CON.)
SAMF	PLE COLLECTION INFORMATION
SAMPLING DATE (mm/dd/yy) SAMPLING DEVICE (SEE BELOW) SAMPLING DEVICE MATERIAL (A) AIR-LIFT PUMP (B) BLADDER PUMP (C) PERISTALTIC PUMP (D) SCOOP	DEDICATED (Y /N) SAMPLE TYPE GRAB / COMPOSITE (CIRCLE ONE)
	INFORMATION (IF APPLICABLE)
REFERENCE POINT REF. PT. ELEV.(FT. MSL.) DEPTH TO WATER (REF. PT.) GW. ELEV.(FT. MSL.)	LAND ELEVATION (FT./MSL) WELL DEPTH (FT.) STICKUP (FT.) WELL DIAMETER (INCHES)
	EASURMENTS (FOUR REPLICATES)
PH (STD) SPEC. COND.(uS) TEMPERATURE (C) OTHER (SPECIFY)	Final Purge Initial Sample Final Sample 3.3 1/1,9 °C
	COMMENTS/CALCULATIONS
WEATHER CONDITIONS	
SAMPLE APPEARANCE	
1" DIA. CASING CONTAINS .041 Gal./Ft. 2" DIA. CASING CONTAINS .163 Gal./Ft. 4" DIA. CASING CONTAINS .652 Gal./Ft.	
PLEASE INCLUDE SAMPLE BOTTLE SIZE, BOTTLE COLOR, BOTTLE MATE	RIAL, PRESERVATIVES AND ANALYTICAL METHODS ON LABORATORY CUSTODY FORMS.



GAI PROJECT NAME VandeMark Chinical	GAI PROJECT NO			
SAMPLEID. Vault Effluet	SOURCE CODES: RIVER OR STREAM, WELL, SOIL, OTHER ICIRCLE ON	Ξ)		
PURGING INFORMATION (IF APPLICABLE)				
PURGE DATE (mm/dd/yy) 5 / 2 0 / 75 CASING VOL.(Gal.) PURGING DEVICE (SEE BELOW)	TIME (24 HR CLOCK) ELAPSED HRS GAL. PURGED (Gal.) PURGING DEVICE MATERIAL DEDICATED (Y / N)			
SAMPLE	COLLECTION INFORMATION			
SAMPLING DATE (mm/dd/yy) SAMPLING DEVICE (SEE BELOW) SAMPLING DEVICE MATERIAL	TIME (24 HR CLOCK) MATRIX DEDICATED-(Y / N) FILTERED (Y / N) SAMPLE TYPE - GRAP / COMPOSITE (CIRCLE ONE)			
(A) AIR-LIFT PUMP (B) BLADDER PUMP (C) PERISTALTIC PUMP (D) SCOOPISHOV	FORMATION (IF APPLICABLE)			
REFERENCE POINT	LAND ELEVATION (ET AICL)	_		
REF. PT. ELEV.(FT. MSL)	LAND ELEVATION (ET./MSL) WELL DEPTH (FT.)			
DEPTH TO WATER (REF. PT.)	STICKUP (FT.)			
GW. ELEV.(FT. MSL.)	WELL DIAMETER (INCHES)			
FIELD MEASURMENTS (FOUR REPLICATES) Initial Purge Final Purge Initial Sample Final Sample				
pH (STD)				
SPEC. COND.(uS)				
TEMPERATURE (C)				
OTHER (SPECIFY)				
COMMENTS/CALCULATIONS				
WEATHER CONDITIONS				
SAMPLE APPEARANCE				
1" DIA. CASING CONTAINS .041 Gal./Ft. 2" DIA. CASING CONTAINS .163 Gal./Ft.	of Disp taken from Vault	-11		
4" DIA. CASING CONTAINS .652 Gal./Ft.				
PLEASE INCLUDE SAMPLE BOTTLE SIZE, BOTTLE COLOR, BOTTLE MATERIAL,	PRESERVATIVES AND ANALYTICAL METHODS ON LABORATORY CUSTODY FORMS.			
SAMPLER SIGNATURE Gold	er Associates DATE 5/20/15	_		



	0+W	GAI PROJECT NO.	093-89168	
SAMPLE ID.	<u>+ </u>	SOURCE CODES: RIVER OR	STREAM, WELL, SOIL, OTHER (CIRCLE ONE)	
PURGING INFORMATION (IF APPLICABLE)				
PURGE DATE (mm/dd/yy)/	11.4115	TIME (24 HR CLOCK)	ELAPSED HRS.	
CASING VOL.(Gal.)		GAL, PURGED (Gal.)	The second of th	
PURGING DEVICE (SEE BELOW)		PURGING DEVICE MATERIAL	DEDICATED (Y / N)	
	SAMPLE	COLLECTION INFORMAT	ION	
SAMPLING DATE (mm/dd/yy)	11,4,15	TIME (04 LIB CLOCK)	15:00 MATRIX 40	
	2	TIME (24 HR CLOCK)	1/10	
SAMPLING DEVICE (SEE BELOW)	+50.10V	DEDICATED (N)	FILTERED (Y /db)	
SAMPLING DEVICE MATERIAL	Poly	SAMPLE TYPE - GRAB/CON	IPOSITE (CIRCLE ONE)	
(A) AIR-LIFT PUMP (B) BLADDER PUMP (C) PERIST	ALTIC PUMP (D) SCOOP/SHOV	EL (E) BAILER (F) OTHER (SPECIFY)		
	WELL INF	ORMATION (IF APPLICA	BLE)	
REFERENCE POINT		LAND ELEVATION (FT./MSL)		
REF. PT. ELEV.(FT. MSL)		WELL DEPTH (FT.)		
DEPTH TO WATER (REF. PT.)		STICKUP (FT.)		
GW. ELEV.(FT. MSL.)		WELL DIAMETER (INCHES)	A STATE OF THE STA	
FIELD MEASURMENTS (FOUR REPLICATES) Initial Purge Initial Sample Final Sample				
	Initial Purge	Final Purge Init		
pH (STD)	Initial Purge	Final Purge Init	tial Sample Final Sample 7. 4 7. 41	
	Initial Purge			
SPEC. COND.(uS)	Initial Purge		7.4 7.41 577 2538	
	Initial Purge		7.4 577 2538 12.1° /2.2°	
SPEC. COND.(uS)	Initial Purge		7.4 7.41 577 2538	
SPEC. COND.(uS) TEMPERATURE (C)			7.4 577 2538 12.1° /2.2°	
SPEC. COND.(uS) TEMPERATURE (C)			7.4 577 2538 12.1° /2.2°	
SPEC. COND.(uS) TEMPERATURE (C) OTHER (SPECIFY)	COM	IMENTS/CALCULATIONS	7.4 577 2538 12.1° /2.2°	
SPEC. COND.(uS) TEMPERATURE (C) OTHER (SPECIFY) WEATHER CONDITIONS SAMPLE APPEARANCE	Clan - No Oc	IMENTS/CALCULATIONS	7.4 577 2538 12.1° /2.2°	
SPEC. COND.(uS) TEMPERATURE (C) OTHER (SPECIFY) WEATHER CONDITIONS SAMPLE APPEARANCE 1* DIA. CASING CONTAINS .041 Gal./F	Claw - No 0	IMENTS/CALCULATIONS	7.4 577 2538 12.1° /2.2°	
SPEC. COND.(uS) TEMPERATURE (C) OTHER (SPECIFY) WEATHER CONDITIONS SAMPLE APPEARANCE 1' DIA. CASING CONTAINS .041 Gal./F 2' DIA. CASING CONTAINS .163 Gal./F	Claw - No 0	IMENTS/CALCULATIONS	7.4 577 2538 12.1° /2.2°	
SPEC. COND.(uS) TEMPERATURE (C) OTHER (SPECIFY) WEATHER CONDITIONS SAMPLE APPEARANCE 1* DIA. CASING CONTAINS .041 Gal./F	Clow - No 03 1. 1.	IMENTS/CALCULATIONS	7.4 577 2538 12.1° /2.2°	
SPEC. COND.(uS) TEMPERATURE (C) OTHER (SPECIFY) WEATHER CONDITIONS SAMPLE APPEARANCE 1' DIA. CASING CONTAINS .041 Gal./F 2' DIA. CASING CONTAINS .163 Gal./F	Clow - No 03 1. 1.	IMENTS/CALCULATIONS	7.4 577 2538 12.1° /2.2°	
SPEC. COND.(uS) TEMPERATURE (C) OTHER (SPECIFY) WEATHER CONDITIONS SAMPLE APPEARANCE 1' DIA. CASING CONTAINS .041 Gal./F 2' DIA. CASING CONTAINS .163 Gal./F	Clow - No 03 1. 1.	IMENTS/CALCULATIONS	7.4 577 2538 12.1° /2.2°	
SPEC. COND.(uS) TEMPERATURE (C) OTHER (SPECIFY) WEATHER CONDITIONS SAMPLE APPEARANCE 1' DIA. CASING CONTAINS .041 Gal./F 2' DIA. CASING CONTAINS .163 Gal./F	Con - No 0.	IMENTS/CALCULATIONS Jov Collected	7.4 577 2538 12.1° /2.2° 85 102	
SPEC. COND.(uS) TEMPERATURE (C) OTHER (SPECIFY) WEATHER CONDITIONS SAMPLE APPEARANCE 1" DIA. CASING CONTAINS .041 Gal./F 2" DIA. CASING CONTAINS .163 Gal./F 4" DIA. CASING CONTAINS .652 Gal./F	Con - No 0.	IMENTS/CALCULATIONS Jov Collected	7.4 577 2538 12.1° /2.2° 85 102	



GAI PROJECT NAME VDA	N-0+M	GAI PROJECT NO.	093-89168	
SAMPLE ID. PZ-	1-0+1	SOURCE CODES: RIV	ER OR STREAM, WELL	, SOIL, OTHER (CIRCLE ONE)
-		INFORMATION (IF A	PPLICABLE)	
PURGE DATE (mm/dd/yy) CASING VOL.(Gal.) PURGING DEVICE (SEE BELOW)	11,4,15	TIME (24 HR CLOCK) GAL, PURGED (Gal.) PURGING DEVICE MA	ATERIAL	ELAPSED HRS. ::: DEDICATED (Y / N)
	SAMPLE	COLLECTION INFO	RMATION	
SAMPLING DATE (mm/dd/yy) SAMPLING DEVICE (SEE BELOW) SAMPLING DEVICE MATERIAL		TIME (24 HR CLOCK) DEDICATED-(Y / N) SAMPLE TYPE - GRA	AB / COMPOSITE (CIRCL	MATRIX FILTERED (Y / N) E ONE)
(A) ATR-LIFT PUMP (B) BLADDER PUMP (C) PI	ERISTALTIC PUMP (D) SCOOP/SH	OVEL (E) BAILER (F) OTHER (SP	EC(FY)	
364	WELL IN	IFORMATION (IF AP	PLICABLE)	
REFERENCE POINT REF. PT. ELEV.(FT. MSL) DEPTH TO WATER (REF. PT.) GW. ELEV.(FT. MSL.)		LAND ELEVATION (F WELL DEPTH (FT.) STICKUP (FT.) WELL DIAMETER (IN	~3	<i>71,</i> 67
	FIELD MEA	SURMENTS (FOUR	REPLICATES) Initial Sample	Final Sample
pH (STD) SPEC. COND.(uS) TEMPERATURE (C) OTHER (SPECIFY)				
COMMENTS/CALCULATIONS				
WEATHER CONDITIONS			E	
SAMPLE APPEARANCE				
1" DIA. CASING CONTAINS .041 G 2" DIA. CASING CONTAINS .163 G 4" DIA. CASING CONTAINS .652 G	al./Ft.			
PLEASE INCLUDE SAMPLE BOTTLE SIZE, BU	OTTLE COLOR, BOTTLE MATERIA	L, PRESERVATIVES AND ANALYT	FICAL METHODS ON LABORATO	DATE /// //



1 MODULE	ics		
GAI PROJECT NAME	NDM OFW	GAI PROJECT NO.	093-89168
SAMPLE ID.	P7-2	SOURCE CODES: RIV	/ER OR STREAM WELL, SOIL, OTHER (CIRCLE ONE)
	PURGING	INFORMATION (IF AI	PPLICABLE)
PURGE DATE (mm/dd/y CASING VOL.(Gal.) PURGING DEVICE (SEE	~6.15	TIME (24 HR CLOCK) GAL, PURGED (Gal.) PURGING DEVICE MA	-Derts No
	SAMPL	E COLLECTION INFO	DRMATION
SAMPLING DATE (mm/c SAMPLING DEVICE (SE SAMPLING DEVICE MA	EBELOW) Bailer	TIME (24 HR CLOCK) DEDICATED-(ON) SAMPLE TYPE - GRA	15:70 MATRIX FILTERED (Y 10) AB) COMPOSITE (CIRCLE ONE)
(A) AIR-LIFT PUMP (B) BLADDE	R PUMP (C) PERISTALTIC PUMP (D) SCOOPISH	IOVEL (E) BAILER (F) OTHER (SPE	ECIFY)
	WELL II	NFORMATION (IF APP	PLICABLE)
REFERENCE POINT REF. PT. ELEV.(FT. MS DEPTH TO WATER (RE GW. ELEV.(FT. MSL.)	1	LAND ELEVATION (FT WELL DEPTH (FT.) STICKUP (FT.) WELL DIAMETER (INC	-10.54
	FIELD MEA	ASURMENTS (FOUR I	REPLICATES) Initial Sample Final Sample
pH (STD)	6.80	6.80	
SPEC. COND.(us	s) 1256	1072	1104
TEMPERATURE	(C) 14.(13.9	
OTHER (SPECIF	-3Z	-27	-28
	co	MMENTS/CALCULA	TIONS
WEATHER CONDITION	IS		
SAMPLE APPEARANC	Yellow Slies	Hy clardy - M	6 990
1" DIA. CASING CONTA	AINS .041 Gal./Ft. \$2 3, 6	2/0.041)= 0.1	148 ×3 = 6.44
2" DIA. CASING CONTA			
4 BIA. CASING CONTA	111/3 .032 Gal./Ft.		-
PLEASE INCLUDE SAMPLE B	OTTLE SIZE, BOTTLE COLOR, BOTTLE MATERIA	AL, PRESERVATIVES AND ANALYT	TICAL METHODS ON LABORATORY CUSTODY FORMS.
	//////		.//
SAMPLER SIGNATURE		Ider Associates	DATE 11/4/15



- Indoorded		_		• • • • • • • • • • • • • • • • • • • •
GAI PROJECT NAME	M O+M	GAI PROJECT NO.	093-89168_	_
SAMPLE ID. 12-	-3	SOURCE CODES: RI	VER OR STREAM, WELI	L, SOIL, OTHER (CIRCLE ONE)
	PURGING	INFORMATION (IF A	APPLICABLE)	
PURGE DATE (mm/dd/yy) CASING VOL.(Gal.) PURGING DEVICE (SEE BELOW)	11 4115 -0.15 Bala	TIME (24 HR CLOCK) GAL. PURGED (Gal.) PURGING DEVICE M	10.5	ELAPSED HRS. : 102 DEDICATED (1) N)
	SAMPL	E COLLECTION INFO	ORMATION	
SAMPLING DATE (mm/dd/yy) SAMPLING DEVICE (SEE BELOW) SAMPLING DEVICE MATERIAL	11, 4, 15 Bailor Poly		AB/ COMPOSITE (CIRCI	MATRIX FILTERED (Y 100) LE ONE)
(A) AIR-LIFT PUMP (B) BLADDER PUMP (C) PE	RISTALTIC PUMP (D) SCOOPISH	HOVEL (E) BAILER (F) OTHER (SP	PECIFY)	
	WELL	NFORMATION (IF AP	PLICABLE)	
REFERENCE POINT REF. PT. ELEV.(FT. MSL.) DEPTH TO WATER (REF. PT.) GW. ELEV.(FT. MSL.)	5.43	LAND ELEVATION (F WELL DEPTH (FT.) STICKUP (FT.) WELL DIAMETER (IN	251	72
	FIELD MEA	ASURMENTS (FOUR	•	
pH (STD) SPEC. COND.(uS) TEMPERATURE (C) OTHER (SPECIFY)	12.5 4303 15.0 -192	Final Purge 1162 2017 15.0 -296	Initial Sample	Final Sample
COMMENTS/CALCULATIONS				
WEATHER CONDITIONS				
SAMPLE APPEARANCE	Slightly Clan	1-1 No Sodor		
1° DIA. CASING CONTAINS .041 Ga	1./Ft. 3,69 (.	041)= 0.15 x	3= 0.45	
2" DIA. CASING CONTAINS .163 Ga 4" DIA. CASING CONTAINS .652 Gal				
PLEASE INCLUDE SAMPLE BOTTLE SIZE, BOT	TLE COLOR, BOTTLE MATERIAL	DOESEDUATIVES AND ANALYT	TO ALL RETURNS ON LABOR TO	
	1/	/ AND ENTANTES AND ANALY!	TOAL METHODS ON LABORATO	DAY CUSTODY FORMS.
SAMPLER SIGNATURE	the Brash	_		DATE 1/4/15
Golder Associates				



Ansociates				
GAI PROJECT NAME VDM - O+N	GAI PROJECT NO			
SAMPLE ID. PZ-4	SOURCE CODES: RIVER OR STREAM, WELL, SOIL, OTHER (CIRCLE ONE)			
PURGINO	G INFORMATION (IF APPLICABLE)			
PURGE DATE (mm/dd/yy) CASING VOL.(Gal.) PURGING DEVICE (SEE BELOW) CASING VOL.(Gal.) CASING VOL.(Gal.)	TIME (24 HR CLOCK) 14:30 ELAPSED HRS. :08 GAL. PURGED (Gal.) PURGING DEVICE MATERIAL Paly DEDICATED (F) N)			
SAMP	LE COLLECTION INFORMATION			
SAMPLING DATE (mm/dd/yy) SAMPLING DEVICE (SEE BELOW) SAMPLING DEVICE MATERIAL Poly	TIME (24 HR CLOCK) DEDICATED (7 / N) SAMPLE TYPE - GRAB / COMPOSITE (CIRCLE ONE)			
(A) AIR-LIFT PUMP (B) BLADDER PUMP (C) PERISTALTIC PUMP (D) SCOOP!	SHOVEL (E) BAILER (F) OTHER (SPECIFY)			
WELL	INFORMATION (IF APPLICABLE)			
REFERENCE POINT REF. PT. ELEV.(FT. MSL) DEPTH TO WATER (REF. PT.) GW. ELEV.(FT. MSL.)	LAND ELEVATION (FT./MSL) WELL DEPTH (FT.) STICKUP (FT.) WELL DIAMETER (INCHES)			
FIELD ME Initial Purge	EASURMENTS (FOUR REPLICATES) Final Purge Initial Sample Final Sample			
pH (STD) 7.72	7.03 / 7.06			
SPEC. COND.(us) 6(18	6529			
127	13.6			
OTHER (SPECIFY)	-92 -92			
COMMENTS/CALCULATIONS				
WEATHER CONDITIONS				
SAMPLE APPEARANCE Sishell Cloud-1	-Noodor			
1° DIA. CASING CONTAINS .041 Gal./Ft. 5-25	(0.041) = 0.21 ×/3 = 0.645			
2" DIA. CASING CONTAINS .163 Gal./Ft.				
4* DIA. CASING CONTAINS .652 Gal./Ft.				
PLEASE INCLUDE SAMPLE BOTTLE SIZE, BOTTLE COLOR, BOTTLE MATER	RIAL, PRESERVATIVES AND ANALYTICAL METHODS ON LABORATORY CUSTODY FORMS.			
711 1				
SAMPLER SIGNATURE	DATE 1/4/15			



GAI PROJECT NAME	NOW-0+1/	GAI PROJECT NO.	093-89168	
SAMPLE ID.	NW-70	SOURCE CODES: RIVER	OR STREAM, WELL, SOIL, OTHER (CIRCLE ONE)	
PURGING INFORMATION (IF APPLICABLE)				
PURGE DATE (mm/dd/yy) CASING VOL.(Gal.) PURGING DEVICE (SEE BE		TIME (24 HR CLOCK) GAL. PURGED (Gal.) PURGING DEVICE MATE	7	
	SAMPLE	COLLECTION INFORI	MATION	
SAMPLING DATE (mm/dd/y) SAMPLING DEVICE (SEE BI SAMPLING DEVICE MATER	ELOW) Pallor	TIME (24 HR CLOCK) DEDICATEDO N) SAMPLE TYPE - GRAP	FILTERED (Y/N) COMPOSITE (CIRCLE ONE)	
(A) AIR-LIFT PUMP (B) BLADDER PU	IMP (C) PERISTALTIC PUMP (D) SCOOPISHO	OVEL (E) BAILER (F) OTHER (SPECIF	(Y)	
	WELLIN	FORMATION (IF APPL	ICABLE)	
REFERENCE POINT REF. PT. ELEV.(FT. MSL) DEPTH TO WATER (REF. P GW. ELEV.(FT. MSL.)	т.)	LAND ELEVATION (FT // WELL DEPTH (FT.) STICKUP (FT.) WELL DIAMETER (INCH	46- 49.62	
	FIELD MEA	SURMENTS (FOUR RE	PLICATES) Initial Sample Final Sample	
pH (STD)	6.85	6.93	705	
SPEC. COND.(uS)	3412	4963	3031	
TEMPERATURE (C)	15,4°C	15,3°c	/	
OTHER (SPECIFY)	orp _54_	28	/	
	со	MMENTS/CALCULATION	ONS	
WEATHER CONDITIONS		20		
SAMPLE APPEARANCE	5/11/11/11	+ Sixt - No	21 -	
12 DIA CACINIC CONTAINS	2130 19 1000	(+ ips:)====	3.0//	
1° DIA. CASING CONTAINS 2" DIA. CASING CONTAINS	1-811	Mar (163)	= 3.04 × 3 = 9	
4" DIA. CASING CONTAINS	6 .652 Gal./Ft.			
	MS/	150 Collected		
PLEASE INCLUDE SAMPLE BOTTL	E SIZE, BOTTLE COLOR, BOTTLE MATERIA	L, PRESERVATIVES AND ANALYTICA	L METHODS ON LABORATORY CUSTODY FORMS.	
SAMPLER SIGNATURE			DATE	

Golder Associates

At Golder Associates we strive to be the most respected global group of companies specializing in ground engineering and environmental services. Employee owned since our formation in 1960, we have created a unique culture with pride in ownership, resulting in long-term organizational stability. Golder professionals take the time to build an understanding of client needs and of the specific environments in which they operate. We continue to expand our technical capabilities and have experienced steady growth with employees now operating from offices located throughout Africa, Asia, Australasia, Europe, North America and South America.

Africa + 27 11 254 4800
Asia + 852 2562 3658
Australasia + 61 3 8862 3500
Europe + 356 21 42 30 20
North America + 1 800 275 3281
South America + 55 21 3095 9500

solutions@golder.com www.golder.com

Golder Associates Inc. 2430 N. Forest Road, Suite 100 Getzville, NY 14068 USA

Tel: (716) 204-5880 Fax: (716) 204-5878

