

February 15, 2006

Mr. James Maggio Maggio Data Printing, Ltd. 1735 Express Drive North Hauppauge, N.Y. 11788

Re: Limited Phase II Subsurface Investigation

1735 Express Drive North Hauppauge, N.Y. 11788 Hillmann Job #: N6-1589

Dear Mr. Maggio:

As requested, Hillmann Environmental Group L.L.C. (Hillmann) has completed a limited Phase II subsurface investigation and Ground Penetrating Radar (GPR) survey at 1735 Express Drive North, Hauppauge, NY. Field activities occurred on January 12, 2006, January 31, 2006 and February 1, 2006. The purpose of this investigation was to determine if the presence of a former Underground Storage Tank, (UST), septic leach field and/or prior site activities may have resulted in environmental contamination on the property.

### **Background**

Hillmann performed a Phase I Environmental Site Assessment (ESA) for the site on January 10, 2006. The ESA identified a 2,000-gallon UST on the property that was reportedly cleaned, filled and closed in place on July 30, 1992. No soil or groundwater analytical results were on record with the applicable regulatory agencies. The ESA identifies AFTA Chemical Corporation as a previous tenant on the property. AFTA was issued violation notices from the Suffolk County Department of Health (DOH) and New York State Department of Environmental Conversation (NYSDEC) on August 11, 1980 and September 8, 1981 regarding the discharge of industrial wastes to the groundwater without a valid state permit and not possessing proper certificates for holding tanks and storage areas. AFTA stored and utilized "cleaning products including organic solvents." An internal memo from the Suffolk County Office of Pollution Control sent to the DOH dated October 14, 1997 was reviewed in the ESA. The memo details the past dumping of chemicals on the site including "anhydrous ethyl alcohol, 'carsi wash', press wash, varnelene, alcohol, motor oil, transmission fluids, camera solutions, 'tint' and hydraulic fluid." It is possible some of the historic dumping of chemicals on site could have been through the septic system, which may have impacted the septic leach field.

### Scope of Work

Hillmann conducted a geophysical survey with ground penetrating radar (GPR) on the property to determine the location of the 2,000-gallon underground storage tank (UST) that is present at the

site. GPR is applied by transmitting signals into the subsurface. Subsurface structures and other forms of interference deflect the signals. The GPR survey is non-invasive. Data is collected in the form of anomalies that represent the subsurface interference. These anomalies are likely to identify the shape of a subsurface structure, however, interfering factors may limit the accuracy and cause inconclusive results. Such interfering factors include conglomerated soil media (e.g., rocks, bricks, construction debris, etc.), soil moisture, re-bar in foundation, and vibration caused by nearby construction activities. The depth of penetration in ideal conditions is 8-12 feet BGS.

Hillmann advanced subsurface borings in selected areas of the subject site using direct push boring equipment (a/k/a Geoprobe®) on January 12, 2006 and February 1, 2006. The Geoprobe® unit consists of a vehicle-mounted hydraulic ram that forces a four foot long barrel shaped probe into the ground with a pneumatic hammer. The probes collected continuous 4-foot sections of earth within acetate liners to be examined for contamination and extract soil samples for laboratory analysis. Four borings, B1(a) through B4(a) were advanced to a depth of 16 feet below ground surface (bgs) each in the vicinity of the septic leach field on January 12, 2006. A temporary well point was installed in B3(a) to facilitate collection of a groundwater sample. Six borings, B1 through B6, were advanced on February 1, 2006. B1 and B6 were advanced to 20 feet bgs with a temporary well installed in B1 to facilitate collection of groundwater samples. B2 through B5 were advanced to 16 feet bgs.

All soil and groundwater samples were analyzed for Volatile Organic Compounds, (VOC's), Base Neutral (BN) compounds, Priority Pollutant Metals (PP Metals) and PCB's at an accredited laboratory and compared to applicable New York state standards.

### **Field Investigations**

The GPR survey identified the location of the abandoned in place 2,000-gallon UST on the southeast side of the building. Borings B1 and B2 were advanced in the vicinity of the UST with groundwater collected from B1. Borings B1(a) through B4(a) were advanced in the vicinity of the grass septic leach field in the front of the building. Groundwater was collected from B3(a). Borings B3 and B4 were advanced in the back of the building and Borings B5 and B6 were advanced in the driveway on the east side of the site. A temporary well was installed in B4, however, no water was able to be recovered. Samples from borings advanced within the leach field were collected at 8-10 feet bgs. B1 and B6 were sampled at 19-20 bgs and B2 – B5 were sampled at approximately 16 feet bgs.

A site plan and boring logs are included in the appendices of this report.

# Results Soil Sample Analytical Results

Sample #	B1	B2	В3	B4	B5	В6	Standards
Compounds							
Antimony	<2.0	<2.1	<2.0	<2.0	<2.1	<2.1	N/A
Arsenic	<2.0	2.3	2.5	<2.0	<2.1	2.4	7.5
Beryllium	<0.51	<0.52	<0.50	<0.49	<0.51	<0.52	0.16
Cadmium	<0.51	<0.52	<0.50	<0.49	<0.51	<0.52	1
Chromium	6.2	7.9	7.5	5	15.1	8.3	10

Copper	8.2	7.7	6.3	6.3	9.8	6.1	25
Lead	9.6	4.1	3.4	3.6	3	2.9	N/A
Mercury	<0.032	<0.032	<0.033	<0.033	<0.031	<0.033	0.1
Nickel	6.9	6.4	6.4	4.9	6.9	6.1	13
Selenium	<2.0	<2.1	<2.0	<2.0	<2.1	<2.1	2
Silver	<1.0	<1.0	<1.0	<0.99	<1.0	<1.0	N/A
Thallium	<1.0	<1.0	<1.0	<0.99	<1.0	<1.0	N/A
Zinc	31.5	13.8	14.9	9.8	15.8	13.6	20
Acenaphthene	ND	ND	ND	0.0497 J	ND	0.0479	50
Anthracene	ND	ND	ND	0.0717	ND	0.104	50
Benzo(a)anthracene	0.0147 J	0.177	ND	0.185	0.0286 J	0.375	.224
Benzo(a)pyrene	ND	0.167	ND	0.177	0.0262 J	0.375	0.061
Benzo(b)fluoranthene	ND	0.227	ND	0.203	0.0401 J	0.45	1.1
Benzo(g,h,i)perylene	ND	0.0531 J	ND	0.0633 J	ND	0.14	50
Benzo(k)fluoranthene	ND	0.0732	ND	0.14	ND	0.442	1.1
bis(2-Ethylhexyl)phthalate	ND	0.0354 J	ND	ND	ND	ND	50
Carbazole	ND	0.0509 J	ND	0.0591 J	ND	0.126	N/A
Dibenzo(a,h)anthracene	ND	ND	ND	ND	ND	0.0517 J	0.014
Dibenzofuran	ND	ND	ND	0.055 J	ND	0.022 J	6.2
Chrysene	0.0232 J	ND	ND	0.243	0.0368 J	0.434	0.4
Fluoranthene	0.0397 J	0.532	ND	0.636	0.108	1.1	50
Fluorene	ND	0.0285 J	ND	0.0889	ND	0.0554 J	50
Indeno(1,2,3-cd)pyrene	ND	0.0697 J	ND	0.0719	ND	0.131	3.2
Phenanthrene	0.0235 J	0.339	ND	0.583	0.0495 J	0.669	50
Pyrene	0.0378 J	0.424	ND	0.512	0.105	1.01	50
Tetrachloroethene	ND	0.00084 J	ND	ND	ND	ND	1.4

Sample #	B1(a)	B2(a)	B3(a)	B4(a)	Standards
Compounds					
Antimony	<2.1	<2.1	<2.2	<2.2	N/A
Arsenic	<2.1	<2.1	2.6	<2.2	7.5
Beryllium	<0.52	<0.54	<0.55	<0.55	0.16
Cadmium	<0.52	<0.54	<0.55	<0.55	1
Chromium	5.9	9.7	9.4	13.3	10
Copper	5	8.4	9.7	8.9	25
Lead	3.2	4.3	4.1	5.1	N/A
Mercury	<0.034	<0.035	<0.035	<0.035	0.1
Nickel	<4.2	8.8	11.4	8.3	13
Selenium	<2.1	<2.1	<2.2	<2.2	2
Silver	<1.0	<1.1	<1.1	<1.1	N/A
Thallium	<1.0	<1.1	<1.1	<1.1	N/A
Zinc	9.1	21.8	22.3	21.7	20
Carbon disulfide	ND	ND	ND	0.00096 J	2.7

### Groundwater Sample Analytical Results

Sample #	B3(a)	B1-GW	Standards
Date Sampled	1/12/2006	2/1/2006	
Compounds			
Antimony	<50	<30	6
Arsenic	310	224	50
Beryllium	34.1	35.8	N/A
Cadmium	<40	<20	10
Chromium	1770	924	50
Copper	1200	1000	1,000
Lead	606	547	50
Mercury	<0.80	0.99	1.4
Nickel	1390	913	100
Selenium	<50	<50	10
Silver	<100	<50	50
Thallium	<100	<50	8
Zinc	2610	4050	5,000
1,4 Dichlorobenzene	18.1 J	ND	3
Chlorobenzene	0.44 J	ND	5
1,1 Dichloroethane	0.54 J	ND	5
cis-1,2-Dichloroethene	5.1	ND	N/A
Ethylbenzene	0.29 J	ND	N/A
Toluene	0.85 J	ND	N/A
Vinyl chloride	15.1	ND	2
Xylene (total)	0.63 J	ND	5

### Notes:

ND = Not Detected

NA = Not Applicable

J = Estimated Value

Bold Print = Value Exceeded Standard

Only those compounds detected are present

Soil Parameters Reported in Parts Per Million (PPM)

Groundwater Parameters Reported in Parts Per Billion (PPB)

### **Conclusions and Recommendations**

Beryllium and Selenium concentrations were detected slightly above current TAGM 4046 standards in all four of the borings advanced in the leach field. Zinc was above standards in three of the four borings, B2(a) – B4(a), advanced in the leach field. Beryllium and Selenium were detected slightly above standards in the majority of the remaining borings advanced around the perimeter of the property. Zinc was also slightly above standards in B1.

Groundwater collected from Boring B1 also contained elevated levels of metals above TAGM standards. However, the laboratory results state "elevated sample detection limit due to difficult sample matrix". Therefore the compounds detected above standards could be attributed to laboratory error.

Slightly elevated levels of PAH compounds were detected in Boring B6; which was advanced in the parking area very near the Long Island Expressway service road. The slightly elevated levels of PAH compounds may be attributed to runoff from the heavy use highway in close proximity to the site.

Based on the above information, the slightly elevated levels of Beryllium, Selenium and Zinc may be attributed to "normal background levels" for this site. Groundwater analysis from B3(a) in the leach field indicated elevated levels of metals and two VOC compounds (1,4 Dichlorobenzene and Vinyl Chloride) above standards which may be attributed to the past storage and/or use of chemicals on the site. The past release of chemicals on site was noted by the NYSDEC and DOH in 1980 and 1981, and by the Suffolk County Office of Pollution Control and DOH in 1997.

Based on the above information, Hillmann did not find any evidence that the abandoned UST on site has impacted the soil or groundwater. Hillmann recommends filing a Freedom Of Information Act (FOIA) request to the DOH and NYSDEC to ascertain the specifics of the chemical releases on the site and the follow up responses of the regulatory agencies. Additional borings may be recommended pending the results of the FOIA request.

Should you have any questions or require additional information, please do not hesitate to contact me.

Project Manager / Geologist

Sincerely,


HILLMANN ENVIRONMENTAL GROUP, L.L.C.

hus Husehmen

Christopher Hirschmann Environmental Scientist

Attachments

### SITE DIAGRAM



Expressway Drive North

# SUMMARY OF ANALYTICAL RESULTS

N6-1589 Summary of Soil Analytical Data from Second Sampling Event (Feb. 1, 2006) Maggio Data Printing, Ltd. 1735 Expressway Drive North, Hauppauge, New York 11788

Sample #	B1	B2	B3	B4	B5	B6	Standards
Compounds							
Antimony	<2.0	<2.1	<2.0	<2.0	<2.1	<2.1	N/A
Arsenic	<2.0	2.3	2.5	<2.0	<2.1	2.4	7.5
Beryllium	<0.51	<0.52	<0.50	<0.49	<0.51	<0.52	0.16
Cadmium	<0.51	<0.52	<0.50	< 0.49	<0.51	<0.52	1
Chromium	6.2	7.9	7.5	5	15.1	8.3	10
Copper	8.2	7.7	6.3	6.3	9.8	6.1	25
Lead	9.6	4.1	3.4	3.6	3	2.9	N/A
Mercury	<0.032	<0.032	<0.033	< 0.033	<0.031	< 0.033	0.1
Nickel	6.9	6.4	6.4	4.9	6.9	6.1	13
Selenium	<2.0	<2.1	<2.0	<2.0	<2.1	<2.1	2
Silver	<1.0	<1.0	<1.0	< 0.99	<1.0	<1.0	N/A
Thallium	<1.0	<1.0	<1.0	< 0.99	<1.0	<1.0	N/A
Zinc	31.5	13.8	14.9	9.8	15.8	13.6	20
Acenaphthene	ND	ND	ND	0.0497 J	ND	0.0479	50
Anthracene	ND	ND	ND	0.0717	ND	0.104	50
Benzo(a)anthracene	0.0147 J	0.177	ND	0.185	0.0286 J	0.375	.224
Benzo(a)pyrene	ND	0.167	ND	0.177	0.0262 J	0.375	0.061
Benzo(b)fluoranthene	ND	0.227	ND	0.203	0.0401 J	0.45	1.1
Benzo(g,h,i)perylene	ND	0.0531 J	ND	0.0633 J	ND	0.14	50
Benzo(k)fluoranthene	ND	0.0732	ND	0.14	ND	0.442	1,1
bis(2-Ethylhexyl)phthalate	ND	0.0354 J	ND	ND	ND	ND	50
Carbazole	ND	0.0509 J	ND	0.0591 J	ND	0.126	N/A
Dibenzo(a,h)anthracene	ND	ND	ND	ND	ND	0.0517 J	0.014
Dibenzofuran	ND	ND	ND	0.055 J	ND	0.022 J	6.2
Chrysene	0.0232 J	ND	ND	0.243	0.0368 J	0.434	0.4
Fluoranthene	0.0397 J	0.532	ND	0.636	0.108	1.1	50
Fluorene	ND	0.0285 J	ND	0.0889	ND	0.0554 J	50
Indeno(1,2,3-cd)pyrene	ND	0.0697 J	ND	0.0719	ND	0.131	3.2
Phenanthrene	0.0235 J	0.339	ND	0.583	0.0495 J	0.669	50
Pyrene	0.0378 J	0.424	ND	0.512	0.105	1.01	50
Tetrachloroethene	ND	0.00084 J	ND	ND	ND	ND	1.4

### Notes:

ND = Not Detected
NA = Not Applicable
J = Estimated Value
Bold Print = value ex

Bold Print = value exceeded standard
Only those compounds detected are presented
All parameters in ppm (mg/kg)
Standards from NYS TAGM 4046

N6-1589 Summary of Soil Analytical Data from First Sampling Event (Jan 12, 2006)

## Maggio Data Printing, Ltd. 1735 Expressway Drive North, Hauppauge, New York 11788

Sample #	B1(a)	B2(a)	B3(a)	B4(a)	Standards
Compounds					
Antimony	<2.1	<2.1	<2.2	<2.2	N/A
Arsenic	<2.1	<2.1	2.6	<2.2	7.5
Beryllium	<0.52	<0.54	<0.55	<0.55	0.16
Cadmium	<0.52	<0.54	<0.55	<0.55	1
Chromium	5.9	9.7	9.4	13.3	10
Copper	5	8.4	9.7	8.9	25
Lead	3.2	4.3	4.1	5.1	N/A
Mercury	< 0.034	< 0.035	< 0.035	< 0.035	0.1
Nickel	<4.2	8.8	11.4	8.3	13
Selenium	<2.1	<2.1	<2.2	<2.2	2
Silver	<1.0	<1.1	<1.1	<1.1	N/A
Thallium	<1.0	<1.1	<1.1	<1.1	N/A
Zinc	9.1	21.8	22.3	21.7	20
Carbon disulfide	ND	ND	ND	0.00096 J	2.7

### Notes:

ND = Not Detected

NA = Not Applicable

J = Estimated Value

**Bold Print = value exceeded standard** 

Only those compounds detected are presented

All parameters in ppm (mg/kg)

N6-1589 Summary of Groundwater Analytical Data Maggio Data Printing, Ltd. 1735 Expressway Drive North, Hauppauge, New York 11788

Sample #	B3(a)	B1-GW	Standards
Date Sampled	1/12/2006	2/1/2006	
Compounds			
Antimony	<50	<30	6
Arsenic	310	224	50
Beryllium	34.1	35.8	N/A
Cadmium	<40	<20	10
Chromium	1770	924	50
Copper	1200	1000	1,000
Lead	606	547	50
Mercury	<0.80	0.99	1.4
Nickel	1390	913	100
Selenium	<50	<50	10
Silver	<100	<50	50
Thallium	<100	<50	8
Zinc	2610	4050	5,000
1,4 Dichlorobenzene	18.1 J	ND	3
Chlorobenzene	0.44 J	ND	5
1,1 Dichloroethane	0.54 J	ND	5
cis-1,2-Dichloroethene	5.1	ND	N/A
Ethylbenzene	0.29 J	ND	N/A
Toluene	0.85 J	ND	N/A
Vinyl chloride	15.1	ND	2
Xylene (total)	0.63 J	ND	5

### Notes:

ND = Not Detected
NA = Not Applicable
J = Estimated Value
Bold Print = value exceeded standard
Only those compounds detected are presented
All parameters in ppm (mg/kg)
Standards from NYS TAGM 4046



# HILLMANN ENVIRONMENTAL GROUP, L.L.C. RECORD OF SUBSURFACE EXPLORATION

TEST NO:	B1(a)	_(TP = TEST PIT, B = BORING, A = AUGUR PROBE)
CLIENT:	Maggio Data Printing, Ltd.	DATE START:1/12/2006
PROJECT:	Limited Subsurface Investigation	DATE COMPLET 1/12/2006
LOCATION:	1735 Expressway Drive North	DRILLING METHOD: Geoprobe
	Hauppauge, NY	RIG TYPE:
HILLMANN	PROJECT NO: N6-1589	TEST METHOD: Boring
DRILLER:	Team Drilling	SURFACE ELEVATION:
HILLMANN	REP: Chris Hirschmann	TERMINATION DEPTH: 16ft.

GROUNDW	ATER DATA		
DEPTH	ELEV.		TIME
(FT.) BGS	(FT.) MSL		
N/A	N/A	D-	
		C-	
PRODUCT-			
GW-			
D=DURING DRILLII	VG. C-COMPLETION		

DEPTH	T	SAMPL	Ē				<del>,</del>	
	DEPTH	NO.	REC.	BLOW/6"	N	DESCRIPTION	PID READING	DEPTH
(FEET)	(FEET)		INCH				(PPM)	(FEET)
0	· J					12-Organic Soil		0
	1		1				0	i i
				Ì			"	
			İ					
		1				12-Sandy Clay	-	
		1				*Wet @ 4ft.		
_							Ì	_1
								_ [
	1			1				
	1			]				
	1							
						18-Tan Sand	0	
5					į		ĺ	5
								Ĭ
	1			1		6-Sandy Clay		-
	1			1		O-Garray Glay	0	-
_	1			1				-
••	İ							
-						6-Tan Sand	0	_
_						* Sample Collected		
•-	1					18-Tan/Grayish Sand	0	-
_	1					16-TarvGrayIsh Sand	0	
	1							
0								10 —
						18-Tan Clayey Sand w/Black	0	
								1
								-
				<del>  </del>				1
		1				12-Gray Wet Clay	0	
	]							-1
-								]
	1					12-Red/Tan Sand (Drier)	o	~ [
5	İ					The state of the s	'	
	1							15
-						24-Dense, Dark Gray Clay w/Silver Specks	0	1
-								_
								_
_								- [
								-
_								- 1
	]			1				-
	1							[
0	1			[				
								20 — 2
_				j i				
	1							

TEST NO: B2(a)	_(TP = TEST PIT, B = BORING, A = AUGUR PROBE)
CLIENT: Maggio Data Printing, Ltd.	DATE START: 1/12/2006
PROJECT: Limited Subsurface Investigation	DATE COMPLET 1/12/2006
LOCATION: 1735 Expressway Drive North	DRILLING METHOD: Geoprobe
Hauppauge, NY	RIG TYPE:
HILLMANN PROJECT NO: N6-1589	TEST METHOD: Boring
DRILLER: Team Drilling	SURFACE ELEVATION:
HILLMANN REP: Chris Hirschmann	TERMINATION DEPTH: 16ft

GROUNDW	ATER DATA		
DEPTH	ELEV.	TIM	1E
(FT.) BGS	(FT.) MSL	1	
N/A	N/A	D-	
		C-	
PRODUCT-		Π'	
GW-		7	
D=DURING DRILLI	NG, C=COMPLETION		

DEPTH		SAMPL	F					
	DEPTH	NO.	REC.	BLOW/6"	N	DESCRIPTION	PID READING	DEPTH
(FEET)	(FEET)	ļ	INCH	<u> </u>	ļ		(PPM)	(FEET)
0		l	1	İ		6-Organic Matter	0	0 —
			i					• -
_		ł			l			
				ł	i			
	l			1	Ī			
	1	Į						
_								
		-		1		12-Clayey,Sand Damp	_	
_				]	ĺ	12-Olayey, Sand Damp	0	
				1				
								- 4
5						36- Dark Tan Clay w/White Sand & Rocks		
						So- Dark Tan Ciay w/writte Sand & Hocks	0	5
		]						- [
						*Sampled	0	
								_ [
-								- [
1								
		1						
				ļ				8
-				ł		48-Sandy Clay (Brown), Damp in Places	0	_
						w/White Small Rocks	0	
							٠	~
ا ـــ ه								-
								10
-								1
-								
1								1
						48-Clayey Sand (Tan)	0	-1
-								
								_
								ļ
[								~
5						:		- [
							[	15 —
-								
								1
-								
_ [							ļ	ľ
_ [				l				-
- 1								-1
								_ 1
-				<b>i</b>				· · ·
								[
l l								
0 -						<u> </u>		<u>20</u> — 20
-								-
					J			1
_					- 1			-
						· · · · · · · · · · · · · · · · · · ·		

TEST NO: B3(a)	TP = TEST PIT, B = BORING, A = AUGUR PROBE)	GROU
CLIENT: Maggio Data Printing, Ltd.	DATE START: 1/12/2006	DEPT
PROJECT: Limited Subsurface Investigation	DATE COMPLET 1/12/2006	(FT.) B
LOCATION: 1735 Expressway Drive North	DRILLING METHOD: Geoprobe	N/A
Hauppauge, NY	RIG TYPE:	1.00
HILLMANN PROJECT NO: N6-1589	TEST METHOD: Boring	PRODUCT-
DRILLER: Team Drilling	SURFACE ELEVATION:	GW-
HILLMANN REP: Chris Hirschmann	TERMINATION DEPTH: 16ft.	D-DI IBING I

GROUNDW	ATER DATA	
DEPTH	ELEV.	TIME
(FT.) BGS	(FT.) MSL	
N/A	N/A	D-
		C-
PRODUCT-		
GW-		
D=DURING DRILLI	NG. C=COMPLETION	

DEPTH		SAMPL	.E				T No.	
(FEET)	DEPTH (FEET)	NO.	REC.	BLOW/6"	N	DESCRIPTION	PID READING	DEPTH
0	, <u>, , , , , , , , , , , , , , , , , , </u>	<u> </u>	INCH	<del> </del>	<del></del>		(PPM)	(FEET)
	Ī					6-Organic Soil	0	0 —
					1			
						6-Tan, Damp Clayey Sand	0	
			Í		l			<u>.</u> .
				1			ĺ	_
					1			
~				1	1			1
					ĺ			-
								-
- [		, and		ļ —		12-Sandy Clay - Wet		<del> </del>
5 —		' l				12 dandy diay - Wet	0	-
								5
_ [		ŀ						-
				1				
						12-Dry, Yellow, Coarse Grain Sand	0	-
-								_
								i –
-								_
- 1						6-Dry, Yellow, Coarse Grain Sand	0	
-							-	
-		ł				12-Very Dark, Clayey Sand (Smells Like Sewer)	0	
0 —				1		*Sampled	Ü	40
						·		10
	}	ĺ				12-Clayey Sand w/Black Streaks		
		,				an elayoy sana melani sircans		· -
}	1	- 1						-
[				!				
		1				40 V		
[	ľ	ľ		1 1		18-Very Wet	0	
					ĺ			
		- 1						-
, _	ľ	ľ			- 1	36-Dark Brown, Sandy Clay w/White Rocks	0	
								15 —
		1						
- 1-								
-[					ļ	*Temp Well Instalted		
		1						
- [	İ	ŀ	i					
	1	- 1						
								-
	- 1							
, _	1	1						
								20
_					1		İ	
[]		- 1					1	-
				L				

TEST NO:	B4(a)	(TP = TEST PIT, B = BORING, A = AUGUR PROBE)
CLIENT:	Maggio Data Printing, Ltd.	DATE START: 1/12/2006
PROJECT:	Limited Subsurface Investigation	DATE COMPLET 1/12/2006
LOCATION:	1735 Expressway Drive North	DRILLING METHOD: Geoprobe
	Hauppauge, NY	RIG TYPE:
HILLMANN F	PROJECT NO: N6-1589	TEST METHOD: Boring
DRILLER:	Team Drilling	SURFACE ELEVATION:
HILLMANN F	REP: Chris Hirschmann	TERMINATION DEPTH: 16ft.

GROUNDW	ATER DATA	
DEPTH	ELEV.	TIME
(FT.) BGS	(FT.) MSL	
N/A	N/A	D-
		C-
PRODUCT-		
GW-		
D-DURING DRILLI	NG C-COMPLETION	

DEPTH	Γ	SAMPL	.E				Pile	DE0-::
(FEET)	DEPTH (FEET)	NO.	REC.	BLOW/6"	N	DESCRIPTION	PID READING	DEPTH
0	,, <u>, , , , , , , , , , , , , , , , , ,</u>		inch.			6-Organic Soil	(PPM)	(FEET)
		ļ				lo-Organic Son	0	• -
			İ					-
						10 Paddish (Top Page 6)		- [
					i	16-Reddish/Tan Damp Clay, Sandy	0	
-								
-							İ	-
Ι	ĺ							
i -	ļ							
_	İ							- [
-	<u> </u>	-		ļ	<b></b>			4
-		l			ł	30-Clayey Sand, Damp, Coarse Grain w/White Fine Rocks	0	[
5 —		l				(End is Dark/Faint Sewer Smell)		5
-								
-								_
-								
-				ļ				
		<u> </u>						- 8
						10-Clayey Sand, Damp, Coarse Grain w/White Fine Rocks	0	
						(End is Dark/Faint Sewer Smell)	, and the second	
						*Sampled	0	
0							"	10 —
_						8-Clayey Sand, Damp, Coarse Grain w/White Fine Rocks & Dark	0	10 —
						Black Streaks (Sewer Smell)	"	
				j :		16-Clayey Sand, Damp, Coarse Grain w/White Fine Rocks & Dark	0	-
_						Black Streaks (Mild Sewer Smell)	"	-   - 1:
_						Stack Circans (Wild Cower Strick)	-	1:
			1			26 Clause Cand Dame Coassa Cusin walklish Files Fire to 2 P. I		[
						36-Clayey Sand, Damp, Coarse Grain w/White Fine Rocks & Dark	0	
						Black Streaks (Mild Smell)		-
5								
•								15
						V.		
_								1
_	]							-
-								
-							1	
								-
							]	]
0								20 20
								_
				L.				_ [
					_	······································	·	

TEST NO: B1	(TP = TEST PIT, B = Bo	ORING, A = AUGUR PROBE)	
CLIENT: Maggio Data Printing, Ltd.	DATE START:	2/1/2006	<u> </u>
PROJECT: Limited Subsurface Investigation	DATE COMPLETE:	2/1/2006	
LOCATION: 1735 Expressway Drive North	_ DRILLING METHOD:	Direct Push	N/
Hauppauge, NY	RIG TYPE:	Geoprobe	,,,,
HILLMANN PROJECT NO: N6-1589	TEST METHOD:		PR
DRILLER: Team Drilling	SURFACE ELEVATION	DN:	GV
HILLMANN REP: Chris Hirschmann	TERMINATION DEPT	H- 10ft	197

GROUNDWA	ATER DATA		
DEPTH	ELEV.	T	TIME
(FT.) BGS	(FT.) MSL		
N/A	N/A	D-	
		C-	
PRODUCT-		$\neg$	
GW-			
D=DURING DRILLIN	NG, C=COMPLETION		

DEPTH	Т	SAMPL	E			E-Solina Britzina		
(FEET)	DEPTH (FEET)	NO.	REC.	BLOW/6"	N	DESCRIPTION	PID READING	DEPTH
	(FEE1)	+	INCH	+	<del> </del>		(PPM)	(FEET)
1	1		24	ı		6 in Asphalt		0
	İ	1					i	
-						18 in Clayey Sand w/ Black Streaks	0	
-	ļ	1		1			"	
	i							- 1
			1	ļ				- 1
	Į.	1						
	1	ĺ			}			- 1
_		]	ŀ				}	1 -1
ł		]				•	1	
				ļ				_ 4
-				1	ł	**4ft Encountered Refusal - Moved Boring 1ft. Away	0	
5				ł			ľ	1
		Í .	24			24 in Clayey Sand w/ Black Streaks	_	5
_			·	1	f	2-4 III. Ciayoy Garid W Black Streaks	0	
		1						-
-	i			l .				l i
-			!					]
				1			1	
-								_  8
-	!	İ i	36			36 in Clayey Sand w/ Black Streaks	0	——
		l i		1		Suggest of the sugges	"	-
								-
0 —	1	i l						-
i i				1		** Tan Sand, Wet @ 10ft.	ĺ	10
-								
-								]
1								[
-								1 1
			36			36 in Tan sand		12
_		1				oo iii. Tan sand		1 -1
								[ ]
- [		i		l f				- [
-								~
5 —								15 —
				l i			•	_ [
- [	_			l i				i I
_ [			36			36 in Tan sand		16
_						ov iii. Tan sang		- [
_ 1								
1		l						]
		[		1			i	
~								
- [						**TEMP. WELL INSTALLED @ 19ft.		_
								···
0		ŀ						-
`				<del></del>				20 20
					i			
	l	- 1						
								_ [

TEST NO: B2	TP = TEST PIT, B = BORING, A = AUGUR PROBE)	Г
CLIENT: Maggio Data Printing, Ltd.	DATE START: 2/1/2006	Г
PROJECT: Limited Subsurface Investigation	DATE COMPLET 2/1/2006	
LOCATION: 1735 Expressway Drive North	DRILLING METHOD: Direct Push	N
Hauppauge, NY	RIG TYPE: Geoprobe	
HILLMANN PROJECT NO: N6-1589	TEST METHOD:	P
DRILLER: Team Drilling	SURFACE ELEVATION:	G
HILLMANN REP: Chris Hirschmann	TERMINATION DEPTH: 16ft.	n

GROUNDW	ATER DATA		
DEPTH	ELEV.		TIME
(FT.) BGS	(FT.) MSL		
N/A	N/A	D-	•
		C-	
PRODUCT-			
GW-		7	
D=DURING DRILLI	NG, C=COMPLETION		

DEPTH		SAMPL	E				PID	DEPTH
(FEET)	DEPTH (FEET)	NO.	REC. INCH	BLOW/6"	N	DESCRIPTION	READING	1
0	(1,551)		12	<del>-</del>		Cir. Through Applica	(PPM)	(FEET)
			\ '°			6 in Through Asphalt		0
		]	ļ					
			•					
						6 in Clayey Sand w/ Black Streaks		-
						o III Clayey Sand W/ Black Streaks		
	1							
] _								-
								- [
			36	1		6 in Cave-in		4
5								5 _
-								, –
-								
						30 in Clayey Sand w/ Black Streaks & White Rocks		
]								_ [
-			L	1				- 8
- ]			36			36 in Tan Sand		
-				1 1				_
-								
0								10
l l								_
								[
				i i				- 1
-								12
-			18			18 in Tan Sand w/ White Rocks		
-								
								-
								- ]
-								- [
5 —				1				15
-								
-				_		** SAMPLED @ 16ft.		- 16
- [								-
-								-
-								-
-								[
-								-
-								
-								
0 -				<del>  </del>				20 — 20
-							İ	
-								
}								

# HILLMANN ENVIRONMENTAL GROUP, L.L.C. RECORD OF SUBSURFACE EXPLORATION

TEST NO:	B3	TP = TEST PIT, B = BC	DRING, A = AUGUR PROBE)	GROUNDWATI	ER DATA	
	Maggio Data Printing, Ltd.	DATE START:	2/1/2006	DEPTH	ELEV.	TIME
	Limited Subsurface Investigation	DATE COMPLETE:	2/1/2006	(FT.) BGS	(FT.) MSL	THAT
LOCATION:		DRILLING METHOD:	Direct Push	N/A	N/A	D-
	Hauppauge, NY	RIG TYPE:	Geoprobe			C-
	PROJECT NO: N6-1589	TEST METHOD:		PRODUCT-	<del></del>	
DRILLER:		SURFACE ELEVATION	N:	GW-	<del></del>	
HILLMANN	REP: Chris Hirschmann	TERMINATION DEPT	H: 16ft.	D=DURING DRILLING	, C=COMPLETION	

DEPTH	<del></del>	0	<u></u>			D=DURING DRILLIN		
VETIN	DEPTH	SAMPL NO.	REC.	BLOW/6"	N	DESCRIPTION	PID	DEPTH
(FEET)	(FEET)		INCH	DEG 1170	"	DESCRIPTION	READING (PPM)	I
0			36			6 in Through Asphalt	(PPM)	(FEET)
						- In ough replicat		0
		l						
_								
	1	1				30 in Tan Sand w/ Black Streaks		- 1
	İ							
	<b>l</b> .		1					_
				i				
1								!
- 1								_ [
			36			6 in Cave-in		
5								
								5
							1	
							İ	-
_ [				İ		30 in Tan Sand w/ Black Streaks		
- 1								1
[							,	
-								- 8
-			36			3 in - Cave-in		
		- 1						
								ļ l
0								
						20 in Ton Conductific block story		10
						33 in Tan Sand with black streaks		
1								í I
-								-
								1
-			36			36 in Tan Sand w/ White Rocks		
- [		- 1						
								<u></u> }
[			ļ					-
5		ŀ		i				-
_							1	15
					•	W CANDIED & 40%	İ	
ŀ			-			** SAMPLED @ 16ft.		1
-		J					1	
- [	ļ	ŀ					1	
-	ł		,				1	<u></u>
-	-			1				_ [
-	i	]		1				
- 1	l	- 1		ŀ			1	
- 1	ŀ						ļ	-
۰ ا				-				
` <u>.</u>								20 2
	ŀ		1	- 1	ł			
-		- 1						
1	1	- 1					ı	

TEST NO: B4	_(TP = TEST PIT, B = BORING, A = AUGUR PROBE)
CLIENT: Maggio Data Printing, Ltd.	DATE START: 2/1/2006
PROJECT: Limited Subsurface Investigation	DATE COMPLET 2/1/2006
LOCATION: 1735 Expressway Drive North	DRILLING METHOD: Direct Push
Hauppauge, NY	RIG TYPE: Geoprobe
HILLMANN PROJECT NO: N6-1589	TEST METHOD:
DRILLER: Team Drilling	SURFACE ELEVATION:
HILLMANN REP: Chris Hirschmann	TERMINATION DEPTH: 20ft.

GROUNDW	ATER DATA	
DEPTH	ELEV.	TIME
(FT.) BGS	(FT.) MSL	-
N/A	N/A	D-
		C-
PRODUCT-		
GW-		
D=DURING DRILLI	NG, C=COMPLETION	

DEPTH SAMPLE						PID	DEDTH		
(FEET)	DEPTH (FEET)	NO.	REC.	BLOW/6"	N	DESCRIPTION	READING	DEPTH	
0	(PEEI)	<del> </del>	INCH	┥───	<del></del>		(PPM)	(FEET)	
	ŀ		12	]		2 in Through Asphalt	0	0 —	
				}	1				
-	ļ					†	İ		
		1							
		İ		1		10 in Tan Sand w/ White Rocks & Black Streaks			
_					i		1		
		-						[	
-								[	
- ]			10			10 in Tan Sand w/ White Rocks & Black Streaks	<del></del>	<del>                                     </del>	
5 —				1		The same of the sa			
					ĺ			5 ]	
_ [				]				-	
i	1							i I	
							ì	- 1	
- 1								-	
_								l – I	
				ļ					
-			24			24 in Light Tan Sand			
		1							
1	•							[ <u> </u>	
0		1						10	
				1				'0 -	
								-	
- 1									
_				]				-	
			36	1		26 in Light Ton Conduct Direct Others			
_		- 1	00			36 in Light Tan Sand w/ Black Streaks			
		İ					Ì		
- 1									
-									
		1					İ		
5 —		ı						15 —	
-  -						** SAMPLED @ 16ft.		1	
-				1 1	j				
-		- 1	48			48 in Tan Sand		1	
-1		İ						_ [	
								_	
		- 1						- [	
[									
1	1					ATTEMP WELL WOTALLED C. CO.			
0	}					** TEMP. WELL INSTALLED @ 20ft.			
~ <del></del> -⊦				<del>                                     </del>		- No Water Recovery		202	
- ]	ļ								
-	l								
	i						1		

TEST NO: B5	(TP = TEST PIT, B = BORING, A = AUGUR PROBE)
CLIENT: Maggio Data Printing, Ltd.	DATE START: 2/1/2006
PROJECT: Limited Subsurface Investigation	DATE COMPLET 2/1/2006
LOCATION: 1735 Expressway Drive North	DRILLING METHOD: Direct Push
Hauppauge, NY	RIG TYPE: Geoprobe
HILLMANN PROJECT NO: N6-1589	TEST METHOD:
DRILLER: Team Drilling	SURFACE ELEVATION:
HILLMANN REP: Chris Hirschmann	TERMINATION DEPTH: 16ft

GROUNDW	ATER DATA	
DEPTH	ELEV.	TIME
(FT.) BGS	(FT.) MSL	
N/A	N/A	D-
		C-
PRODUCT-		
GW-		
D=DURING DRILLII	NG, C=COMPLETION	

DEPTH		SAMPL	F			T **		
(FEET)	DEPTH	NO.	REC.	BLOW/6"	N	DESCRIPTION	PID READING	DEPTH
	(FEET)	<del></del>	INCH		<del> </del>		(PPM)	(FEET)
0 -			36			6 in Through Asphalt		0 —
[		1						
			ľ	l				
								<u></u>
					1	30 in Light Tan Sand w/ Some Dark Streaks		
				i				
-				1				_
								-
}					l			
[				ł				
[	·····		40	<del> </del>	-	20 in Light Tay Conduct Course But Course		
5			40			20 in Light Tan Sand w/ Some Dark Streaks		-
·					1			5 —
				l				
-								
-						20 in Moist, Dense Sand w/ White Rocks		-
-					ł			
					ľ			_
- [								_
			40			40 in Moist, Dense Sand w/ Small White Rocks		
					1			
						·		_
0								-
_				İ				10 —
_ [								-
					•			
F				_	<del> </del>			
-			40			40 in Moist, Dense Sand w/ Large White Rocks (present from 13'-16')		
		i						
								-
		- 1						
5 —		Ì						15
-		ľ		ŀ				_
- [						** SAMPLED @ 16ft.		
-								
		- 1						_
_ <u> </u>		1		·				-
		1					ŀ	
								-
-		[						
-								
° - -							<u> </u>	20
		i						-
-	1	ŀ						
	1	ĺ		l i				

TEST NO:	B6	(TP = TEST PIT, B =	BORING, A = AUGUR PROBE)
CLIENT:	Maggio Data Printing, Ltd.	DATE START:	2/1/2006
PROJECT:	Limited Subsurface Investigation	DATE COMPLET	2/1/2006
LOCATION:	1735 Expressway Drive North	DRILLING METHO	D: Direct Push
	Hauppauge, NY	RIG TYPE:	Geoprobe
HILLMANN	PROJECT NO: N6-1589	TEST METHOD:	
DRILLER:	Team Drilling	SURFACE ELEVA	TION:
HILLMANN	REP: Chris Hirschmann	TERMINATION DE	PTH: 20 ft.

GROUNDW	ATER DATA	
DEPTH	ELEV.	TIME
(FT.) BGS	(FT.) MSL	
N/A	N/A	D-
		C-
PRODUCT-		
GW-		
D=DURING DRILLII	NG. C=COMPLETION	

DEDTH	DEPTH SAMPLE					E-50 ING BIRELING, C-50WIFE HON			
PEFIN	DEPTH	NO.	REC.	BLOW/6"	N	DESCRIPTION	PID	DEPTH	
(FEET)	(FEET)		INCH			DESCRIPTION	READING (PPM)	(FEET)	
0			24			4 in Through Asphalt	VE CHILL	0 —	
	ł							" -	
	1								
	İ								
								J	
				]		20 in Moist, Tan Clay w/ Black Organic Soil			
								_	
-	1								
	1								
	ľ								
-								4	
			40			20 in Moist, Tan Clay w/ Black Organic Soil		<sup>#</sup>	
5						Side in only in black Organic doi:			
								5	
						20 in Tan Sandy Clay			
-								_ [	
-								_	
-								- 8	
-			40			30 in Tan Sandy Clay	-		
_									
0 _						10 in - Orange/Tan Clay w/ White Bastis & Stastis Ottobalis		<u>.</u>	
						10 in Orange/Tan Clay w/ White Rocks & Black Streaks		10 —	
"									
-				[ ]				-	
								-	
		_		<del>                                     </del>				12	
-			36			2 in Cave-in			
-				j					
-						14 in Tan/Orange Clayey Sand		[	
5 —						2 in White Rocks			
]						Z III YYIIILO FIOGRS		15	
"									
-				<del>  </del>		18 in Green/Tan Clayey Sand		16	
-			40			40 in Tan Fine Grain Sand			
-									
-								_	
] -								_	
-								_ ]	
_								-	
		l							
0 _		l				AT CANIDI ED @ 204		-	
"				-		** SAMPLED @ 20ft.		20 — 20	
"						<b> </b>			
"							]		
	i								