DAILY FIELD REPORT 039		WEATHER	Snow		Rain		Overca	ast	х	Partly Cloudy		Sunny	х
Prepared By: LANG	TEMP.	< 32		32-50		50-70			70-85	Х	>85	х	
BCP Project No: C224304						Date : August 30, 2021							
Project Name:	45 Commercial Street	15 Commercial Street					ne:	6:30 am to 4:00 pm					
Consultant: Langan Engineering, Environmental, Surveying, Landscape Architecture and Geology, D.P.C. (Langan)				_	_	Field F ⁄lota D		or	nnel:				
Foundation Contr Soil Broker: Clean	lager: Monadnock Construct actor: StructureTech New ` Earth LLC (CE) : Trans City Water & Sewer	York, Inc. (S	STNY)										

Work Activities Performed:

- STNY excavated the following areas in waste characterization grid COMP F (0-5) to about 2 feet below grade surface (bgs)(from original site grade) in preparation for plumbing piping installations. Excavated material consisted of previously installed New York State Department of Environmental Conservation (NYSDEC)-approved 0.75-inch virgin stone from Tilcon Mt. Hope Quarry and was stockpiled adjacent to the excavations in waste characterization grid COMP F.
 - o An about 40-foot-long by 2-foot-wide area.
 - o An about 20-foot-long by 2-foot-wide area.
 - o An about 12-foot-long by 2-foot-wide area.
- STNY excavated the following areas of the site. Excavated material consisted of non-native soil and did not exhibit signs of chemical- or petroleum-like contamination.
 - An about 23-foot-long by 15-foot-wide area to about 6 feet bgs (about 8 feet below original site grade) in waste characterization grids COMP B (0-5) and COMP I (5-10) for the foundation mat. Excavated material was added to Soil Stockpile 1.
 - An about 15-foot-long by 14-foot-wide area to about 6 feet bgs (about 8 feet below original site grade) in waste characterization grids COMP C (0-5) and COMP I (5-10) for the foundation mat. Excavated material was added to Soil Stockpile 1 or live loaded onto trucks for off site disposal to the Clean Earth of Bethlehem (CEPA) facility located in Bethlehem, Pennsylvania.
 - An about 37-foot-long by 8-foot-wide area to 3 foot bgs (about 5 feet below original site grade) in waste characterization grid COMP B (0-5) and COMP A (0-5) in preparation for grade beam installation. Excavated material was added to Soil Stockpile 1.
 - An about 16-foot-long by 10-foot-wide area to 7 foot bgs (about 8 feet below original site grade) in waste characterization grid COMP A (0-5) in preparation for pile cap installation. Excavated material was added to Soil Stockpile 1.
 - An about 25-foot-long by 7-foot-wide area to 1 foot bgs (from original site grade) in waste characterization grid COMP K (0-2) to allow for vehicle travel. Excavated material was added to Soil Stockpile 1 or live loaded onto trucks for off-site disposal to the CEPA facility located in Bethlehem, Pennsylvania.
- STNY backfilled an about 120-foot-long by 2.5-foot-wide area around the foundation mat in waste characterization grids COMP A, COMP B, and COMP C from about 8 feet bgs (from original site grade) to about 4 feet bgs with NYSDEC-approved 0.75-inch virgin stone from Tilcon Mt. Hope Quarry to raise the site grade.

Material Tracking:

- The following soil/fill was exported from the site:
 - o 12 loads of non-native soil were transported to the Clean Earth of Bethlehem (CEPA) facility located in Bethlehem, Pennsylvania.
- The following materials were imported to the site:
 - o STNY imported 4 loads of 0.75-inch virgin stone from Tilcon Mt. Hope Quarry.

Samples Collected:

- Langan collected three documentation samples, one at 2 feet bgs and two at 8 feet bgs in waste characterization grids COMP C, COMP B and COMP A, and three quality assurance/quality control (QA/QC) samples. The soil samples were submitted to Alpha Analytical Laboratories, Inc. for analysis of Part 375 volatile organic compounds (VOC), Part 375 semi-volatile organic compounds (SVOC) including 1,4-dioxane, polychlorinated biphenyls (PCB), pesticides/herbicides, target analyte list (TAL) metals including hexavalent and trivalent chromium, and per- and polyfluoroalkyl substances (PFAS).
 - o EP10_2
 - o EP16_8
 - o EP22_8
 - o EPDUP01_083021 (duplicate of EP10_2)
 - o EP16_8_MS01 (matrix spike)
 - o EP16_8_MSD01 (matrix spike duplicate)

Page 2 of 7 File Name: 2021-08-30 Daily Field Report_039


Air Monitoring

Particulate Monit	oring (µg/	m³)	Organic Vapor Monitoring (ppm)						
Daily background	35.2		Daily background	0.0					
Averaging Period	Upwind	Downwind	Averaging Period	Upwind	Downwind				
Daily Time Weighted Average	37.9	32.6	Daily Time Weighted Average	0.0	0.0				
Maximum 15-min Average	59.7	32.9	Maximum 15-min Average	0.0	0.0				
Minimum 1-min Instant Reading	27.0	30.0	Minimum 1-min Instant Reading	0.0	0.1				
Maximum 1-min Instant Reading	159.3	36.0	Maximum 1-min Instant Reading	0.1	0.0				


μg/m³-micrograms per cubic meter.

ppm= parts per million.

Data was not collected until 15:29 at the downwind station due to lack of power on site. Restoration of power is planned for the following week. No particulate or organic vapor exceedances at the downwind station were encountered. The daily Community Air Monitoring Program (CAMP) monitoring results are also presented in the following charts:



- STNY will continue to excavate for the remedial excavation and for pile cap installations.
- STNY will continue to backfill with 0.75-inch stone from Tilcon Mt. Hope Quarry.
- STNY will continue production pile driving.
- STNY will continue to export stockpiled soil to Clean Earth of Bethlehem, located in Bethlehem Pennsylvania.
- STNY will continue to pour concrete for pile caps/grade beams.






Photo 1:

View of STNY excavating in waste characterization grid COMP A (0-5) for a pile cap (facing east).



Photo 2:

View STNY backfilling with of 0.75-inch virgin stone around the foundation mat in waste characterization grids COMP C and COMP B (facing north).



View of STNY excavating for plumbing in waste characterization grid COMP F (facing north).




Photo 4:

View of STNY loading a truck with soil for off-site disposal to CEPA (facing north).



DAILY FIELD REPORT 040		WEATHER	Snow		Rain		Overca	ast	х	Partly Cloudy		Sunny	х
Prepared By: LANGAN		TEMP.	< 32		32-50		50-70			70-85	х	>85	х
BCP Project No:	C224304					Dat	te:	August 31, 2021					
Project Name:	45 Commercial Street	ommercial Street					Time: 6:45 am to 4:00 pm						
•	n Engineering, Environmen cture and Geology, D.P.C. (I	•	ng,		Langan Field Personnel: Yaskira Mota Diaz								
Construction Manager: Monadnock Construction Inc. (MC) Foundation Contractor: StructureTech New York, Inc. (STNY) Soil Broker: Clean Earth, Inc. (CE)					Shrir	iidhi	Shetty	y					
Utility Contractor: Trans City Water & Sewer (Trans City)													

Work Activities Performed:

- STNY used a Junttan 25H Pile Driving Rig to drive the following production piles in waste characterization grid COMP J South. All piles have been completed.
 - o Pile #3 was driven to about 68 feet below grade surface (bgs) (elevation [el¹] --57.3±).
 - o Pile #Hoist-E was driven to about 47 feet bgs (el –34.7±).
 - o Pile #Hoist-W was driven to about 47 feet bgs (el –34.5±).
 - o Pile #Hoist-S was driven to about 49 feet bgs (el –36.5±).
 - \circ Pile #M5 was driven to about 54 feet bgs (el $-41.8\pm$).
 - \circ Pile #M8 was driven to about 49 feet bgs (el $-36.5\pm$).
 - \circ Pile #M6 was driven to about 50 feet bgs (el $-38\pm$).
 - \circ Pile #M7 was driven to about 46 feet bgs (el $-34.4\pm$).
- STNY excavated the following areas of the site. Excavated material consisted of non-native soil and did not exhibit signs of chemical- or petroleum-like contamination.
 - O An about 15-foot-long by 12-foot-wide area to 3 foot bgs (about 5 feet below original site grade) in waste characterization grid COMP B (0-5) in preparation for pile cap installation. Excavated material was stockpiled in waste characterization grid COMP B (0-5) or live loaded onto trucks for off site disposal to the CEPA facility located in Bethlehem, Pennsylvania.
 - O An about 15-foot-long by 13-foot-wide area to 3 foot bgs (about 5 feet below original site grade) in waste characterization grid COMP B (0-5) in preparation for pile cap installation. Excavated material was stockpiled in waste characterization grid COMP B (0-5) or live loaded onto trucks for off site disposal to the CEPA facility located in Bethlehem, Pennsylvania.
 - O An about 13-foot-long by 13-foot-wide area to 3 foot bgs (about 5 feet below original site grade) in waste characterization grid COMP B (0-5) in preparation for pile cap installation. Excavated material was stockpiled in waste characterization grid COMP B (0-5) or live loaded onto trucks for off site disposal to the CEPA facility located in Bethlehem, Pennsylvania.
 - o An about 27-foot-long by 5-foot-wide area to 3 foot bgs (about 5 feet below original site grade) in waste characterization grid COMP F (0-5) in preparation for electrical utility piping installation. Excavated material was stockpiled on the boundary between waste characterization grids COMP F and COMP D.
- STNY backfilled the following areas with New York State Department of Environmental Conservation (NYSDEC)-approved 0.75-inch virgin stone from Tilcon Mt. Hope Quarry to raise the site grade.
 - o An about 12-foot-long by 11-foot-wide area in waste characterization grid COMP C from about 2 feet bgs (from original site grade) to original site grade.
 - An about 25-foot-long by 22-foot-wide area in waste characterization grid COMP C and COMP
 J North from about 2 feet bgs (from original site grade) to about 1 foot bgs.

- An about 105-foot-long by 2-foot-wide area in waste characterization grids COMP B, COMP C, and COMP D from a maximum depth of about 8 feet bgs (from original site grade) to original site grade.
- An about 53-foot-long by 8-foot-wide area in waste characterization grids COMP A and COMP B from a maximum depth of about 7 feet bgs (about 8 feet below original site grade) to depths varying from about 5 feet bgs to about 2 feet bgs.

Material Tracking:

- The following soil/fill was exported from the site:
 - o 4 loads of non-native soil were transported to the Clean Earth of Bethlehem (CEPA) facility located in Bethlehem, Pennsylvania.
- The following materials were imported to the site:
 - o STNY imported 4 loads of 0.75-inch virgin stone from Tilcon Mt. Hope Quarry.

Samples Collected:

- Langan collected two documentation samples, one from 8 feet bgs and one from 2 feet bgs in waste characterization grids COMP B and COMP K, respectively. The documentation soil samples were submitted to Alpha Analytical Laboratories, Inc. for analysis of Part 375 volatile organic compounds (VOC), Part 375 semi-volatile organic compounds (SVOC) including 1,4-dioxane, polychlorinated biphenyls (PCB), pesticides/herbicides, target analyte list (TAL) metals including hexavalent and trivalent chromium, and per- and polyfluoroalkyl substances (PFAS).
 - o EP24 2
 - o EP23_8
- Clean Earth, Inc. collected one sample set for waste characterization purposes, consisting of one composite sample and one grab sample from Soil Stockpile 1 and from a soil stockpile containing soil from waste characterization grids COMP A (5-6) and COMP B (5-6). The soil samples were submitted to Eurofins TestAmerica Laboratories, Inc. for analysis of VOCs, SVOCs, PCBs, pesticides/herbicides, TAL metals, toxixity characteristic leaching procedure (TCLP) metals, extracable petroleum hydrocarbons (EPH), and Resource Conservation and Recovery Act (RCRA) characteristics (corrosivity, ignitability, and reactivity).
 - o H1H2-OE-Comp1
 - o H1H2-OE-G1

Page 2 of 7 File Name: 2021-08-31 Daily Field Report_040


Air Monitoring

Particulate Monit	oring (µg/	m³)	Organic Vapor Monitoring (ppm)					
Daily background	43.4		Daily background	0.0				
Averaging Period	Upwind	Downwind	Averaging Period	Upwind	Downwind			
Daily Time Weighted Average	34.4	7.1	Daily Time Weighted Average	0.0	0.0			
Maximum 15-min Average	88.6	20.6	Maximum 15-min Average	0.0	0.0			
Minimum 1-min Instant Reading	16.5	1.0	Minimum 1-min Instant Reading	0.0	0.0			
Maximum 1-min Instant Reading	385.3	29.5	Maximum 1-min Instant Reading	0.0	0.0			


μg/m³-micrograms per cubic meter.

ppm= parts per million.

No particulate or organic vapor exceedances at the downwind station were encountered. The daily Community Air Monitoring Program (CAMP) monitoring results are also presented in the following charts:



- STNY will continue to excavate for the remedial excavation and for pile cap installations.
- STNY will continue to backfill with 0.75-inch stone from Tilcon Mt. Hope Quarry.
- STNY will continue to export stockpiled soil to Clean Earth of Bethlehem, located in Bethlehem Pennsylvania.
- STNY will continue to pour concrete for pile caps/grade beams.
- STNY will continue to excavate and install electric and plumbing utility pipes.






Photo 1:

View of STNY backfilling with 0.75-inch virgin stone in waste characterization grid COMP C (facing east).




Photo 2:

View of STNY backfilling with of 0.75-inch virgin stone in waste characterization grid COMP A (facing east).



View of STNY excavating to install electrical utility piping in waste characterization grid COMP F (facing north).




Photo 4:

View of STNY excavating for pile caps in waste characterization grid COMP B (facing west).



DAILY FIELD REPORT 041		WEATHER	Snow		Rain	x	Overca	ast	Х	Partly Cloudy		Sunny
Prepared By: LANG	BAN	ТЕМР.			>85							
BCP Project No:	C224304	24304 Dat						September 1, 2021				
Project Name:	45 Commercial Street	5 Commercial Street					Time: 6:45 am to 3:00 pm					
Consultant: Langan Engineering, Environmental, Surveying, Landscape Architecture and Geology, D.P.C. (Langan)				Langan Field Personnel: Yaskira Mota Diaz								
Construction Manager: Monadnock Construction Inc. (MC) Foundation Contractor: StructureTech New York, Inc. (STNY) Soil Broker: Clean Earth LLC (CE)												
Utility Contractor: Trans City Water & Sewer (Trans City)												

Work Activities Performed:

• STNY excavated an about 56-foot-long by 4.5-foot-wide L-shaped area to 5 feet below grade surface (bgs) (from original site grade) in waste characterization grid COMP F (0-5) for the installation of electrical utility piping. Excavated material consisted of imported 0.75-inch stone or non-native soil that did not exhibit signs of chemical- or petroleum-like contamination. The stone and soil were not comingled during excavation and stockpiled separately in waste characterization grids COMP F and COMP D.

Material Tracking:

- No soil/fill was exported from the site.
- No material was imported to the site.


Samples Collected:

• No samples were collected on the site.

Air Monitoring

Community air monitoring was not performed due to inclement weather. On-site sources of VOCs were not observed and dust was not observed migrating off-site.

- STNY will continue mass excavating for the remedy, foundation elements, and utilities and will continue exporting soil for off-site disposal.
- STNY will continue pouring concrete for pile caps/grade beams.
- STNY will begin installing the waterproofing/vapor barrier at the mat slab.








Photo 1:

View of STNY excavating in waste characterization grid COMP F (0-5) for electric utility piping (facing north).



Photo 2:

View of STNY excavating in waste characterization grid COMP F (0-5) for electric utility piping and stockpiling in waste characterization grids COMP D and COMP F (facing southwest).



View of STNY excavating in waste characterization grid COMP F for electric utility piping (facing north).



Photo 4:

View of STNY excavating in waste characterization grid COMP F (0-5) for electric utility piping (facing west).



DAILY FIELD REPORT 042		WEATHER	Snow		Rain	Rain		ast		Partly		Sunny	Х
Prepared By: LANGAN		TEMP.	< 32		32-50		50-70		X	Cloudy 70-85	Х	>85	
BCP Project No:	C224304					Da	Date: September 2, 2021						
Project Name:	45 Commercial Street	45 Commercial Street					Time: 6:45 am to 3:45 pm						
Consultant: Langan Engineering, Environmental, Surveying, Landscape Architecture and Geology, D.P.C. (Langan)				Langan Field Personnel: Yaskira Mota Diaz									
Construction Mar	nager: Monadnock Construc	ction Inc. (N	1C)										
Foundation Contractor: StructureTech New York, Inc. (STNY)													
Soil Broker: Clean Earth LLC (CE)													
Utility Contractor: Trans City Water & Sewer (Trans City)													

Work Activities Performed:

- STNY excavated an about 30-foot-long by 2-foot-wide area to 5 feet below grade surface (bgs) (from original site grade) in waste characterization grid COMP F (0-5) for the installation of electrical utility piping. Excavated material consisted of imported 0.75-inch stone or non-native soil that did not exhibit signs of chemical- or petroleum-like contamination. The stone and soil were not comingled during excavation and stockpiled separately in waste characterization grids COMP F and COMP D.
- STNY backfilled the following areas with New York State Department Environmental Conservation (NYSDEC)-approved 0.75-inch virgin stone from Tilcon Mt. Hope Quarry to fill in previous excavations.
 - An about 15-foot-long by 12-foot-wide area in waste characterization grid COMP B from about
 5 foot bgs (from original site grade) to 3 feet bgs.
 - An about 15-foot-long by 13-foot-wide area in waste characterization grid COMP B from about 5 feet bgs (from original site grade) to 1 foot bgs.
 - An about 18-foot-long by 13-foot-wide area in waste characterization grids COMP G from about 2 feet bgs (from original site grade) to original site grade.
 - An about 25-foot-long by 25-foot-wide area in waste characterization grids COMP C from about
 2 feet bgs (from original site grade) to original site grade.

Material Tracking:

- No soil/fill was exported from the site.
- The following materials were imported to the site:
 - STNY imported 3 loads of 0.75-inch virgin stone from Tilcon Mt. Hope Quarry.


Samples Collected:

No samples were collected on the site.


Air Monitoring

Particulate Monit	oring (µg/	'm³)	Organic Vapor Monitoring (ppm)						
Daily background	6.2		Daily background	0.0					
Averaging Period	Upwind	Downwind	Averaging Period	Upwind	Downwind				
Daily Time Weighted Average	30.9	0.5	Daily Time Weighted Average	0.0	0.0				
Maximum 15-min Average	53.0	14.5	Maximum 15-min Average	0.0	0.0				
Minimum 1-min Instant Reading	5.0	0	Minimum 1-min Instant Reading	0.0	0.0				
Maximum 1-min Instant Reading	96.0	33.0	Maximum 1-min Instant Reading	0.0	0.0				
μg/m³-micrograms per cubic meter.			ppm= parts per million.						

No particulate or organic vapor exceedances at the downwind station were encountered. The daily Community Air Monitoring Program (CAMP) monitoring results are also presented in the following charts:



- STNY will continue mass excavating for the remedy, foundation elements, and utilities and will continue exporting soil for off-site disposal.
- STNY will continue pouring concrete for pile caps/grade beams.
- STNY will begin installing the waterproofing/vapor barrier at the mat slab.








Photo 1:

View of STNY excavating in waste characterization grid COMP F (0-5) for electric utility piping installation (facing east).




Photo 2:

View of STNY backfilling with imported 0.75-inch virgin stone in waste characterization grid COMP B (facing south).



View of STNY backfilling with imported 0.75-inch virgin stone in waste characterization grid COMP C (facing south).




Photo 4:

View of truck dumping imported 0.75-inch virgin stone from Tilcon - Mt. Hope Quarry (facing west).



DAILY FIELD REPORT 043 Partly **WEATHER** Rain Overcast Snow Sunny Cloudy Prepared By: LANGAN TEMP. 32-50 50-70 70-85 < 32 Х >85 **BCP Project No:** C224304 Date: September 3, 2021 **Project Name:** 45 Commercial Street Time: 7:00 am to 2:15 pm Consultant: Langan Engineering, Environmental, Surveying, **Langan Field Personnel:** Landscape Architecture and Geology, D.P.C. (Langan) Tyler Goodnough TJ Malgieri **Construction Manager:** Monadnock Construction Inc. (MC) **Foundation Contractor:** StructureTech New York, Inc. (STNY) Soil Broker: Clean Earth LLC (CE) **Utility Contractor:** Trans City Water & Sewer (Trans City)

Work Activities Performed:

- STNY excavated an about 20-foot-long by 5-foot-wide area to 5 feet below grade surface (bgs) (from original site grade) in waste characterization grid COMP G (0-5) for the installation of electrical utility piping. Excavated material consisted of imported 0.75-inch stone or non-native soil that did not exhibit signs of chemical- or petroleum-like contamination. The stone and soil were not comingled during excavation and stockpiled separately in waste characterization grids COMP F and COMP D.
- STNY began installing Grace Preprufe® 300R Plus waterproofing/vapor barrier membrane, Preprufe® CJ Tape, Preprufe® Detail Tape, and Bituthene Mastic at the mat slab in waste characterization grids COMP B, COMP C and COMP D. Waterproofing oversight is to verify general conformance with specifications and contract documents. Certification that the waterproofing meets the requirements of any warranty shall be in accordance with inspection performed by representatives of Grace, and does not relieve the Contractor from performing all work in accordance with the project specifications, Grace's standard details and their inspection recommendations.
- STNY loaded 3 trucks with soil from the soil stockpile¹ in waste characterization grid COMP D for off-site disposal to the Clean Earth of Bethlehem (CEPA) facility located in Bethlehem, Pennsylvania.

Material Tracking:

- The following soil/fill was exported from the site:
 - o 3 loads of non-native soil were transported to the CEPA facility located in Bethlehem, Pennsylvania.
- No material was imported to the site.

Samples Collected:


No samples were collected on the site.

	<u>-</u>		
¹ COMP F (0-5)			


Air Monitoring

Particulate Monit	oring (μg/	m³)	Organic Vapor Monitoring (ppm)						
Daily background	19.2		Daily background	0.0					
Averaging Period	Upwind	Downwind	Averaging Period	Upwind	Downwind				
Daily Time Weighted Average	14.9	23.4	Daily Time Weighted Average	0.0	0.0				
Maximum 15-min Average	35.7	357	Maximum 15-min Average	0.0	0.0				
Minimum 1-min Instant Reading	2.0	0.0	Minimum 1-min Instant Reading	0.0	0.0				
Maximum 1-min Instant Reading	149.8	149.8	Maximum 1-min Instant Reading	0.0	0.0				
ug/m³-micrograms per cubic meter			nnm= parts per million	<u> </u>					

particulate or organic vapor exceedances at the downwind station were encountered. The daily Community Air Monitoring Program (CAMP) monitoring results are also presented in the following charts:



- STNY will continue mass excavating for the remedy, foundation elements, and utilities and will continue exporting soil for off-site disposal.
- STNY will continue pouring concrete for pile caps/grade beams.
- STNY will continue installing waterproofing/vapor barrier in the mat slab.








Photo 1:

View of STNY installing Grace Preprufe® 300R Plus waterproofing/vapor barrier system in the mat slab (facing northwest).




Photo 2:

View of STNY installing Grace Preprufe® 300R Plus waterproofing/vapor barrier system in the mat slab (facing north).



View of STNY loading a truck with soil for off-site disposal to the CEPA facility (facing north).



Photo 4:

View of STNY excavating in waste characterization grid COMP G (0-5) for electric utility installation (facing north).

