

Appendix Q
Groundwater Performance Monitoring Sampling
Logs

GROUND WATER SAMPLE FIELD INFORMATION FORM

Project Information		Well Information		Equipment Information		Sampling Conditions		Sampling Information	
Project Name:	300 W 122nd	Well No:	Dewatering well	Water Quality Device Model:	Horiba	Weather:	60s, Overcast	Sample(s):	GW_053019
Project Number:	170500202	Well Depth:	12 ft	Pine Number:	21272	Background PID (ppm):	0.0		
Site Location:	Manhattan, NY	Well Diameter:	1.5 in	Pump Make and Model:	Peri Pump	PID Beneath Inner Cap (ppm):	0.4		
Sampling Personnel:	Patrick Stovall	Well Screen Interval:	10 ft	Pine Number:	R8230	Pump Intake Depth:	11 ft	Sample Date:	05.30.2019
			12 ft	Tubing Diameter:	1/4"	Depth to Water Before Purge:	6.18 ft	Sample Time:	9:23

STABILIZATION = 3 successive readings within limits

TIME	TEMP °Celsius (+/- 3%)	PH (+/- 0.1)	ORP mV (+/- 10mV)	CONDUCTIVITY mS/cm (+/- 3%)	TURBIDITY ntu (+/- 10%) above 5 NTU	DO mg/l (+/- 10%) above 0.5 mg/l	DTW ft Drawdown < 0.33 ft	Flow Rate (gpm) <0.13 gpm)	Cumulative Discharge Volume (Gal)	NOTES color, odor etc.	Stabilized?
BEGIN PURGING											
8:28	14.82	6.63	183	0.159	58.7	4.49	6.18		0.25	clear, no odor	N/A
8:33	14.45	7.09	-51	0.142	18.20	0.00	6.14	0.1	0.75		N/A
8:38	14.52	7.58	-70	0.142	11.90	0.00	6.14	0.1	1.25		N
8:43	14.51	7.96	-51	0.142	12.00	1.10	6.14	0.1	1.75		N
8:48	14.57	8.05	-38	0.142	14.70	1.73	6.14	0.05	2		N
8:53	14.61	8.22	-23	0.143	16.00	1.93	6.14	0.1	2.5		N
8:58	14.60	8.30	-11	0.143	17.10	3.16	6.14	0.05	2.75		N
9:03	14.53	8.36	-8	0.143	19.9	2.22	6.14	0.05	3		N
9:08	14.47	8.39	6	0.144	21.0	1.94	6.14	0.1	3.5		N
9:13	14.47	8.43	14	0.144	21.0	2.36	6.18	0.05	3.75		N
9:18	14.47	8.46	27	0.145	22.4	2.85	6.18	0.1	4.25		N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N

- Notes:**
 1. Well depths and groundwater depths were measured in feet below the top of well casing.
 2. Well and tubing diameters are measured in inches.
 3. PID = Photoionization Detector
 4. PPM = Parts per million
 5. pH = Hydrogen ion concentration
 6. ORP = Oxidation-reduction potential, measured in millivolts (mV)
 7. DO = Dissolved Oxygen, measured in milligrams per liter (mg/L)
 8. DTW = Depth to water
 9. mS/cm = milli-Siemans per centimeter
 10. NTU = Nephelometric Turbidity Unit

GROUND WATER SAMPLE FIELD INFORMATION FORM

Project Information		Well Information		Equipment Information		Sampling Conditions		Sampling Information	
Project Name:	300 W 122nd	Well No:	Dewatering well	Water Quality Device Model:	Horiba	Weather:	80s, Sunny	Sample(s):	PM_GW02_062419
Project Number:	170500202	Well Depth:	12 ft	Pine Number:	21278	Background PID (ppm):	0.0		
Site Location:	Manhattan, NY	Well Diameter:	1.5 in	Pump Make and Model:	Peri Pump	PID Beneath Inner Cap (ppm):	0.0		
Sampling Personnel:	shley Stappenbec	Well Screen Interval:	10 ft	Pine Number:	44411	Pump Intake Depth:	11 ft	Sample Date:	06.24.2019
			12 ft	Tubing Diameter:	1/4"	Depth to Water Before Purge:	8.825	Sample Time:	11:55

STABILIZATION = 3 successive readings within limits

TIME	TEMP °Celsius (+/- 3%)	PH (+/- 0.1)	ORP mV (+/- 10mV)	CONDUCTIVITY mS/cm (+/- 3%)	TURBIDITY ntu (+/- 10%) above 5 NTU	DO mg/l (+/- 10%) above 0.5 mg/l	DTW ft Drawdown < 0.33 ft	Flow Rate (gpm) <0.13 gpm	Cumulative Discharge Volume (Gal)	NOTES color, odor etc.	Stabilized?
BEGIN PURGING											
11:04	18.66	7.16	-91	0.112	19.9	0.27	3.83		0.25		N/A
11:09	18.65	6.74	-1	0.419	1.20	0.09		0.05	0.5		N/A
11:14	17.58	6.59	73	1.010	1.00	0.00		0.1	1		N
11:19	17.58	6.52	80	1.040	1.10	0.00	3.86	0.125	1.625		N
11:24	17.60	6.47	88	1.040	1.30	0.00		0.1	2.125		N
11:29	17.57	6.45	95	1.050	1.30	0.00		0.125	2.75		N
11:34	17.87	6.47	101	1.050	1.40	0.00		0.125	3.375		N
11:39	18.23	6.52	111	1.140	1.5	0.00	3.88	0.075	3.75		N
11:44	17.82	6.61	107	1.130	1.6	0.00		0.125	4.375		N
11:49	17.80	6.61	103	1.140	1.5	0.00		0.05	4.625		Y
11:54								-0.925			N
								0			N
								0			N
								0			N
								0			N
								0			N
								0			N
								0			N
								0			N
								0			N
								0			N
								0			N
								0			N
								0			N
								0			N
								0			N
								0			N
								0			N
								0			N
								0			N
								0			N

- Notes:**
- Well depths and groundwater depths were measured in feet below the top of well casing.
 - Well and tubing diameters are measured in inches.
 - PID = Photoionization Detector
 - PPM = Parts per million
 - pH = Hydrogen ion concentration
 - ORP = Oxidation-reduction potential, measured in millivolts (mV)
 - DO = Dissolved Oxygen, measured in milligrams per liter (mg/L)
 - DTW = Depth to water
 - mS/cm = milli-Siemans per centimeter
 - NTU = Nephelometric Turbidity Unit

GROUND WATER SAMPLE FIELD INFORMATION FORM

Project Information		Well Information		Equipment Information			Sampling Conditions		Sampling Information	
Project Name:	300 W 122nd	Well No:	Dewatering well	Water Quality Device Model:	Horiba	Weather:	70s, Rain	Sample(s):	PM_GW03_070819	
Project Number:	170500202	Well Depth:	13	Pine Number:	21418	Background PID (ppm):	0.0			
Site Location:	Manhattan, NY	Well Diameter:	2 in	Pump Make and Model:	Peri Pump	PID Beneath Inner Cap (ppm):	108.3	Sample Date:	07.08.2019	
Sampling Personnel:	shley Stappenbec	Well Screen Interval:	10 ft 13 ft	Pine Number:	R19155	Pump Intake Depth:	11.50	Sample Time:	11:00	
				Tubing Diameter:	1/4"	Depth to Water Before Purge:	9.9			

STABILIZATION = 3 successive readings within limits

TIME	TEMP °Celsius (+/- 3%)	PH (+/- 0.1)	ORP mV (+/- 10mV)	CONDUCTIVITY mS/cm (+/- 3%)	TURBIDITY ntu (+/- 10%) above 5 NTU	DO mg/l (+/- 10%) above 0.5 mg/l	DTW ft Drawdown < 0.33 ft	Flow Rate (gpm) <0.13 gpm	Cumulative Discharge Volume (Gal)	NOTES color, odor etc.	Stabilized?
BEGIN PURGING											
10:23	17.17	6.35	57	0.992	16.9	0.00	9.90		0		N/A
10:28	16.85	6.77	7	0.970	6.20	0.00		0.08	0.375		N/A
10:33	16.87	6.76	-1	0.970	2.90	0.00		0.13	1		N
10:38	16.87	6.74	-4	0.970	14.00	0.00	10.90	0.15	1.75		N
10:43	17.24	6.76	-6	0.964	5.80	0.00		0.05	2		N
10:48	17.17	6.72	-2	0.972	2.70	0.00		0.08	2.375		N
10:53	17.05	6.71	-5	0.973	1.50	0.00		0.08	2.75		N
10:58	17.00	6.73	-6	0.972	0.2	0.00		-0.08	2.375		Y
11:03								0.00	2.375		N
11:08								0.00	2.375		N
11:13											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N

- Notes:**
- Well depths and groundwater depths were measured in feet below the top of well casing.
 - Well and tubing diameters are measured in inches.
 - PID = Photoionization Detector
 - PPM = Parts per million
 - pH = Hydrogen ion concentration
 - ORP = Oxidation-reduction potential, measured in millivolts (mV)
 - DO = Dissolved Oxygen, measured in milligrams per liter (mg/L)
 - DTW = Depth to water
 - mS/cm = milli-Siemans per centimeter
 - NTU = Nephelometric Turbidity Unit

GROUND WATER SAMPLE FIELD INFORMATION FORM

Project Information		Well Information		Equipment Information		Sampling Conditions		Sampling Information	
Project Name:	300 W 122nd	Well No:	Dewatering well	Water Quality Device Model:	Horiba	Weather:	90s, Sunny	Sample(s):	PM_GW04_072219
Project Number:	170500202	Well Depth:	13	Pine Number:	21418	Background PID (ppm):	0.0		
Site Location:	Manhattan, NY	Well Diameter:	2 in	Pump Make and Model:	Peri Pump	PID Beneath Inner Cap (ppm):	0.0	Sample Date:	07.22.2019
Sampling Personnel:	shley Stappenbec	Well Screen Interval:	10 ft 13 ft	Pine Number:	R19155	Pump Intake Depth:			Sample Time:
				Tubing Diameter:	1/4"	Depth to Water Before Purge:	6.57		

STABILIZATION = 3 successive readings within limits

TIME	TEMP °Celsius (+/- 3%)	PH (+/- 0.1)	ORP mV (+/- 10mV)	CONDUCTIVITY mS/cm (+/- 3%)	TURBIDITY ntu (+/- 10%) above 5 NTU	DO mg/l (+/- 10%) above 0.5 mg/l	DTW ft Drawdown < 0.33 ft	Flow Rate (gpm) <0.13 gpm)	Cumulative Discharge Volume (Gal)	NOTES color, odor etc.	Stabilized?
BEGIN PURGING											
14:06	20.24	6.33	123	0.856	0.1	2.45	6.57		0		N/A
14:11	19.11	6.75	133	1.010	0.00	1.06		0.10	0.5		N/A
14:16	18.91	6.64	149	1.070	0.00	0.63		0.20	1.5		N
14:21	19.26	6.63	151	1.080	0.00	0.90		0.06	1.8		N
14:26	19.04	6.63	153	1.080	0.00	0.89		0.09	2.25		N
14:31	19.01	6.65	150	1.080	0.00	0.90		-0.45			Y
14:36								0.00			N
14:41								0.00			N
14:46								0.00			N
14:51								0.00			N
14:56								0.00			N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N

- Notes:**
- Well depths and groundwater depths were measured in feet below the top of well casing.
 - Well and tubing diameters are measured in inches.
 - PID = Photoionization Detector
 - PPM = Parts per million
 - pH = Hydrogen ion concentration
 - ORP = Oxidation-reduction potential, measured in millivolts (mV)
 - DO = Dissolved Oxygen, measured in milligrams per liter (mg/L)
 - DTW = Depth to water
 - mS/cm = milli-Siemans per centimeter
 - NTU = Nephelometric Turbidity Unit

GROUND WATER SAMPLE FIELD INFORMATION FORM

Project Information		Well Information		Equipment Information		Sampling Conditions		Sampling Information	
Project Name:	300 W 122nd	Well No:	Dewatering well	Water Quality Device Model:	Horiba	Weather:	80s, Sunny	Sample(s):	PM_GW05_080519
Project Number:	170500202	Well Depth:	13	Pine Number:	21418	Background PID (ppm):	0.0		
Site Location:	Manhattan, NY	Well Diameter:	2 in	Pump Make and Model:	Peri Pump	PID Beneath Inner Cap (ppm):	0.0		
Sampling Personnel:	shley Stappenbec	Well Screen Interval:	10 ft	Pine Number:	R19155	Pump Intake Depth:		Sample Date:	08.05.2019
			13 ft	Tubing Diameter:	1/4"	Depth to Water Before Purge:	9.51	Sample Time:	14:14

STABILIZATION = 3 successive readings within limits

TIME	TEMP °Celsius (+/- 3%)	PH (+/- 0.1)	ORP mV (+/- 10mV)	CONDUCTIVITY mS/cm (+/- 3%)	TURBIDITY ntu (+/- 10%) above 5 NTU	DO mg/l (+/- 10%) above 0.5 mg/l	DTW ft Drawdown < 0.33 ft	Flow Rate (gpm) <0.13 gpm)	Cumulative Discharge Volume (Gal)	NOTES color, odor etc.	Stabilized?
BEGIN PURGING											
13:41	19.78	8.45	113	0.971	0.0	0.35	9.51		0		N/A
13:46	20.10	7.65	85	0.894	0.00	0.00		0.10	0.5		N/A
13:51	20.40	7.29	77	0.874	0.00	0.00		0.10	1		N
13:56	19.84	7.16	72	0.872	0.00	0.00		0.05	1.25		N
14:01	19.02	7.07	71	0.864	0.00	0.00		0.05	1.5		N
14:06	18.96	7.01	69	0.859	0.00	0.00		0.10	2		N
14:11	18.89	6.99	68	0.857	0.00	0.00		-0.40			Y
14:16								0.00			N
14:21								0.00			N
14:26								0.00			N
14:31								0.00			N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N

Notes:

- Well depths and groundwater depths were measured in feet below the top of well casing.
- Well and tubing diameters are measured in inches.
- PID = Photoionization Detector
- PPM = Parts per million
- pH = Hydrogen ion concentration
- ORP = Oxidation-reduction potential, measured in millivolts (mV)
- DO = Dissolved Oxygen, measured in milligrams per liter (mg/L)
- DTW = Depth to water
- mS/cm = milli-Siemans per centimeter
- NTU = Nephelometric Turbidity Unit

GROUND WATER SAMPLE FIELD INFORMATION FORM

Project Information		Well Information		Equipment Information		Sampling Conditions		Sampling Information	
Project Name:	300 W 122nd	Well No:	Dewatering well	Water Quality Device Model:	Horiba	Weather:	90s, Sunny	Sample(s):	PM_GW06_081919
Project Number:	170500202	Well Depth:	13	Pine Number:	21418	Background PID (ppm):	0.0		
Site Location:	Manhattan, NY	Well Diameter:	2 in	Pump Make and Model:	Peri Pump	PID Beneath Inner Cap (ppm):	101.2	Sample Date:	08.19.19
Sampling Personnel:	shley Stappenbec	Well Screen Interval:	10 ft	Pine Number:	R19155	Pump Intake Depth:	10.00	Sample Time:	12:40
			13 ft	Tubing Diameter:	1/4"	Depth to Water Before Purge:	8.59		

STABILIZATION = 3 successive readings within limits

TIME	TEMP °Celsius (+/- 3%)	PH (+/- 0.1)	ORP mV (+/- 10mV)	CONDUCTIVITY mS/cm (+/- 3%)	TURBIDITY ntu (+/- 10%) above 5 NTU	DO mg/l (+/- 10%) above 0.5 mg/l	DTW ft Drawdown < 0.33 ft	Flow Rate (gpm) <0.13 gpm)	Cumulative Discharge Volume (Gal)	NOTES color, odor etc.	Stabilized?
BEGIN PURGING											
12:09	21.95	6.54	50	0.744	10.1	0.03	8.59		0		N/A
12:14	20.89	6.95	-15	0.709	3.60	0.00		0.10	0.5		N/A
12:19	20.76	7.04	-19	0.686	4.00	0.00		0.15	1.25		N
12:24	21.07	6.99	-33	0.680	4.40	0.00		0.10	1.75		N
12:29	20.94	6.93	-31	0.678	4.60	0.00		0.15	2.5		N
12:34	20.96	6.91	-30	0.675	4.90	0.00		-0.50			Y
12:39								0.00			N
12:44								0.00			N
12:49								0.00			N
12:54											N
12:59											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N

- Notes:**
1. Well depths and groundwater depths were measured in feet below the top of well casing.
 2. Well and tubing diameters are measured in inches.
 3. PID = Photoionization Detector
 4. PPM = Parts per million
 5. pH = Hydrogen ion concentration
 6. ORP = Oxidation-reduction potential, measured in millivolts (mV)
 7. DO = Dissolved Oxygen, measured in milligrams per liter (mg/L)
 8. DTW = Depth to water
 9. mS/cm = milli-Siemans per centimeter
 10. NTU = Nephelometric Turbidity Unit

GROUND WATER SAMPLE FIELD INFORMATION FORM

Project Information		Well Information		Equipment Information			Sampling Conditions			Sampling Information	
Project Name:	300 W 122nd	Well No:	Dewatering well	Water Quality Device Model:	Horiba	Weather:	80s, Sunny	Sample(s):	PM_GW07_090319		
Project Number:	170500202	Well Depth:	18	Pine Number:	21418	Background PID (ppm):	0.0				
Site Location:	Manhattan, NY	Well Diameter:	2 in	Pump Make and Model:	Peri Pump	PID Beneath Inner Cap (ppm):	0.0				
Sampling Personnel:	Patrick Stovall	Well Screen Interval:	15 ft	Pine Number:	R19155	Pump Intake Depth:	13 ft	Sample Date:	09.03.2019		
			18 ft	Tubing Diameter:	1/4"	Depth to Water Before Purge:	8.21 ft	Sample Time:	13:10		
<i>STABILIZATION = 3 successive readings within limits</i>											
TIME	TEMP °Celsius (+/- 3%)	PH (+/- 0.1)	ORP mV (+/- 10mV)	CONDUCTIVITY mS/cm (+/- 3%)	TURBIDITY ntu (+/- 10%) above 5 NTU	DO mg/l (+/- 10%) above 0.5 mg/l	DTW ft Drawdown < 0.33 ft	Flow Rate (gpm) <0.13 gpm)	Cumulative Discharge Volume (Gal)	NOTES color, odor etc.	Stabilized?
BEGIN PURGING											
12:10	20.72	8.47	95	0.929	2.8	2.71	8.21		0.25		N/A
12:15	19.57	7.20	83	0.926	1.40	0.19	8.21	0.03	0.4		N/A
12:20	19.14	7.75	32	0.926	0.30	0.00	8.21	0.07	0.75		N
12:25	19.12	7.81	6	0.923	0.00	0.00	8.21	0.07	1.1		N
12:30	19.02	7.83	-7	0.921	0.10	0.00	8.21	0.03	1.25		N
12:35	18.93	7.83	-9	0.918	0.00	0.00	8.21	0.07	1.6		N
12:40	19.03	7.79	-12	0.912	0.00	0.00	8.21	0.08	2		Y
12:45	18.72	7.90	-19	0.913	0.0	0.00	8.21	0.10	2.5		N
12:50	19.01	7.93	-22	0.910	0.0	0.00	8.21	0.05	2.75		N
12:55	18.97	7.98	-28	0.911	0.0	0.00	8.21	0.07	3.1		Y
13:00	18.89	8.02	-32	0.908	0.0	0.00	8.21	0.08	3.5		Y
13:05	19.07	8.16	-41	0.91	0.0	0.00	8.21	0.05	3.75		N
13:10	19.11	8.18	-45	0.908	0.0	0.00	8.21	0.05	4		N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N
											N

- Notes:**
- Well depths and groundwater depths were measured in feet below the top of well casing.
 - Well and tubing diameters are measured in inches.
 - PID = Photoionization Detector
 - PPM = Parts per million
 - pH = Hydrogen ion concentration
 - ORP = Oxidation-reduction potential, measured in millivolts (mV)
 - DO = Dissolved Oxygen, measured in milligrams per liter (mg/L)
 - DTW = Depth to water
 - mS/cm = milli-Siemans per centimeter
 - NTU = Nephelometric Turbidity Unit