

SITE OBSERVATION REPORT

PROJECT No.: 170381202

CLIENT:

Corporation

DATE: Wednesday, October 19, 2022

250 Seaport District, LLC c/o The Howard Hughes

Clear, 43.5 – 56.4 °F

PROJECT: 250 Water Street **WEATHER:**

Wind: WNW @ 0.4 - 7.1 mph

LOCATION: New York, NY TIME: 6:00 AM - 4:30 PM

BCP SITE ID: C231127 **MONITOR:** Brian Kenneally

EQUIPMENT:

PRESENT AT SITE:

Day 134

MiniRAE 3000 PID

Langan (Environmental/Geotechnical) – Brian Kenneally

DustTrak II Jerome J405® Jerome J505® Civetta Cousins JV, LLC (CCJV) (Foundation Contractor) - George Washburn

Hand tools

Lendlease (General Contractor) – Marty Cohen

CAT 374F Komatsu 969 New York State Department of Environmental Conservation (NYSDEC) -Rafi Alam

Komatsu 228 Takeuchi TB290 JCB 110W Hydradia

Wacker Neuson RTSC3 Wacker Neuson OPU6555

OBSERVATIONS, DISCUSSIONS, TEST RESULTS, ETC.:

Langan was present to document remediation activities in accordance with the NYSDEC-approved November 2021 Remedial Action Work Plan (RAWP) at the 250 Water Street site (NYSDEC Brownfield Cleanup Program [BCP] Site No. C231127).

Site Activities

- CCJV used imported general fill to backfill an about 90-foot-long by 65-foot-wide area and an about 45-footlong by 25-foot-wide area in the south-central and southeastern parts of the site, respectively.
- CCJV covered exposed soil/fill that has not been confirmed to meet Track 2 remediation criteria and construction and demolition (C&D) debris with Atmos® AC-645 dust/vapor suppressing foam to create a temporary overnight cover.

Cc:	M. Raygorodetsky, P. McMahon, M. Au	Ву:	Brian Kenneally
			LANGAN



Page 2 of 7

SITE OBSERVATION REPORT

Material Tracking

• CCJV exported 2 truckloads (about 40 cubic yards [CY]) of construction and demolition debris (C&D) for off-site disposal at the Impact Reuse & Recovery Center (IRRC) facility, located in Lyndhurst, NJ.

• CCJV imported 19 truckloads (464.58 tons) of general fill from the IRRC facility, located in Lyndhurst, NJ.

			Materia	al Import S	Summary			
Facility Name Location Type of Material	Hal 1.5/2.	ndustries, Inc. ledon, NJ 5-inch Virgin Stone	Haled 0.75-inc	ustries, Inc. on, NJ h Virgin one	Ce Impact Mate Lyndhurst	use & Recovery enter or erials Jersey City, /Jersey City, NJ lean Bluestone	Impact R Recovery Lyndhu Gener	Center, rst, NJ
Quantities	No. of Loads	Approx. Volume (Tons)	No. of Loads	Approx. Volume (Tons)	No. of Loads	Approx. Volume (Tons)	No. of Loads	Approx. Volume (Tons)
Today	0	0	0	0	0	0	19	464.58
Project Total	8	184.42	0	0	13	289.08	290	7,102.23
NYSDEC Approved:		1,800	tons*		72	0 tons*	7,500	tons*

^{*0.75-}inch, 1.5-inch, and 2.5-inch virgin stone from the Stone Industries, Inc. facility and 1.5-inch clean bluestone from the Impact Reuse & Recovery Center (IRRC) facility were approved for import of 1,000 cubic yards (CY) and 400 CY, respectively. Assuming a conversion factor of 1.8, each quantity was converted to tons in order to accurately compare with import weight tickets. General fill from the IRRC facility was approved for import of 5,000 CY and a conversion factor of 1.5 is applied.

		ı	Material Ex	port Summa	ry (1 of 2)			
Facility Name Location Type of Material	Brook Construction	Allocco Recycling Brooklyn, NY Construction & Demolition (C&D) Debris IRRC Lyndhurst, NJ Construction & Demolition (C&D) Debris		IJ Construction	Clean Earth of North Jersey Kearny, NJ Hazardous Lead-Impacted Soil/Fill		Clean Earth of North Jersey Kearny, NJ Non-hazardous Soil/Fill	
Quantities	No. of Loads	Approx. Volume (CY)	No. of Loads	Approx. Volume (CY)	No. of Loads	Approx. Volume (CY)	No. of Loads	Approx. Volume (CY)
Today	0	0	2	40	0	0	0	0
Project Total	5	85	42	840	95	1,900	216	4,320

		Material Exp	ort Summary	(2 of 2)		
Facility Name Location Type of Material	Middlesex County Landfill East Brunswick, NJ Non-hazardous Soil/Fill		Keas	oil Management Bbey, NJ mpacted Soil/Fill	Cart	of Carteret, NJ eret, NJ rdous Soil/Fill
Quantities	No. of Loads	Approx. Volume (CY)	No. of Loads	Approx. Volume (CY)	No. of Loads	Approx. Volume (CY)
Today	0	0	0	0	0	0
Project Total	261	5,220	267	5,340	66	1,320

Cc:	M. Raygorodetsky, P. McMahon, M. Au	Ву:	Brian Kenneally
			LANGAN



Page 3 of 7

SITE OBSERVATION REPORT

Sampli	ng Activities		
•	No samples were collected.		
Cc:	M. Raygorodetsky, P. McMahon, M. Au	Ву:	Brian Kenneally
OC.	ivi. Haygorodotsky, i . ivicivianon, ivi. Ad	υу.	
			LANGAN



Page 4 of 7

SITE OBSERVATION REPORT

CAMP Activities

Langan performed air monitoring at the perimeter of the site and at work zones at nine total locations for mercury vapor, VOCs and particulate matter less than 10 microns in diameter (PM10), during ground-intrusive activities. There were no fifteen-minute average concentrations for mercury vapor, VOCs, or PM10 that approached or exceeded the action levels established by the CAMP (1.00 µg/m³, 5.0 parts per million [ppm], and 0.100 mg/m³ respectively).

Background Concentrations

Prior to implementation of ground-intrusive work each day, instantaneous background concentrations of mercury vapor and VOCs were recorded using a handheld Jerome® J505 mercury vapor analyzer and a handheld PID, respectively.

- Background concentrations of mercury vapor at each CAMP station ranged from 0.00 μg/m³ to 0.06 μg/m³.
- Background concentrations of VOCs at each CAMP station were recorded at 0.0 ppm.

Perimeter and Work Zone Concentrations

Daily Average Concentrations

	Daily Average of	illooner a crons	
Station ID	Particulate (mg/m³)	Organic Vapor (ppm)	Mercury Vapor (µg/m³)
PM-1	0.013	0.0	0.01
PM-2	0.023	0.0	0.00
PM-3	0.013	0.1	0.00
PM-4	0.009	0.1	0.00
PM-5	0.005	0.1	0.01
PM-6	0.015	0.0	0.00
WZ-1	0.015	0.0	0.01
WZ-2	0.009	0.0	0.00
WZ-3	0.010	0.0	0.01

Maximum 15-Minute-Average Concentrations

	naximalii 15 miilate Av	orago comboniciación	10
Station ID	Particulate (mg/m³)	Organic Vapor (ppm)	Mercury Vapor (µg/m³)
Action Level	0.100 mg/m ³	5.0 ppm	1.00 μg/m³
PM-1	0.028	0.0	0.02
PM-2	0.042	0.0	0.01
PM-3	0.042	0.2	0.01
PM-4	0.023	0.2	0.01
PM-5	0.014	0.1	0.02
PM-6	0.030	0.0	0.02
WZ-1	0.027	0.0	0.02
WZ-2	0.019	0.1	0.02
WZ-3	0.020	0.0	0.02

, 3	.111.	1		, , , .	1 ' '
•ma/m³ –	- milliarams	ner clinic meter	•ppm = parts per million	●IId/m ² – micr	odrams her clibic meter
-1119/111 -	- miningranno	por odbio motor		- μg/111 — 111101	ograffic por dable filotor

Cc:	M. Raygorodetsky, P. McMahon, M. Au	Ву:	Brian Kenneally
			LANGAN



Page 5 of 7

SITE OBSERVATION REPORT

Equipment Troubleshooting

 PM10 and VOC concentrations were not recorded at perimeter CAMP station PM-1 and off-site CAMP station WZ-1 from 12:25pm to 12:26pm (2 minutes) and from 12:29pm to 12:33pm (5 minutes), respectively, to accommodate manual download of data from each unit. Fugitive dust was not observed migrating from the site during these times.

Ambient Air (Handheld Jerome® J505 and Handheld PID)

- The dedicated mobile monitor (Langan) used a handheld Jerome® J505 mercury vapor analyzer to monitor ambient air conditions at various heights throughout the site. Instantaneous mercury vapor concentrations throughout the site ranged from 0.00 µg/m³ to 0.11 µg/m³.
- The dedicated mobile monitor (Langan) used a handheld PID to monitor VOC concentrations throughout the site. Instantaneous VOC concentrations were at or below background concentrations throughout the work day.

CAMP Station Relocation

- CAMP station WZ-1 was relocated to the northern sidewalk of Pearl Street from 7:04am to 4:15pm due to exposed soil/fill located within 20 feet of the northern site boundary.
- CAMP station WZ-2 was relocated to the eastern sidewalk of Peck Slip from 6:49am to 4:09pm due to exposed soil/fill located within 20 feet of the eastern site boundary.
- CAMP station WZ-3 was relocated to the southern sidewalk of Water Street from 6:49am to 4:11pm during backfilling activities in the south-central part of the site.

Prior to CAMP Shutdown

Prior to discontinuing CAMP, air quality at each CAMP station was verified using the handheld PID and handheld Jerome® J505 mercury vapor analyzer and no readings above background concentrations were recorded. Additionally, areas of exposed soil/fill were covered with polyethylene sheeting and/or Atmos® AC-645 dust/vapor suppressing foam. CAMP stations were discontinued between 3:54pm and 4:15pm at the conclusion of ground-intrusive activities.

- Mercury vapor concentrations at each CAMP station ranged from 0.00 μg/m³ to 0.10 μg/m³.
- VOC concentrations at each CAMP station were recorded at 0.0 ppm.

Anticipated Activities


- CCJV will continue excavation and off-site disposal of soil/fill in the southern part of the site.
- CCJV will backfill over-excavated areas of the site using imported general fill to match the surrounding grade.
- Langan will continue collection of confirmation endpoint soil samples across the site.

Cc:	M. Raygorodetsky, P. McMahon, M. Au	Ву:	Brian Kenneally
			LANGAN



Page 6 of 7

SITE OBSERVATION REPORT





Langan PN: 170381202 Wednesday, October 19, 2022 Page 7 of 7

SITE OBSERVATION REPORT

Select Site Photographs:



Photo 1: CCJV using imported general fill for backfilling activities in the southeastern part of the site (facing southeast)



Photo 2: CCJV applying Atmos® AC-645 dust/vapor suppressing foam to exposed soil/fill for the temporary overnight cover (facing southwest)

Cc: M. Raygorodetsky, P. McMahon, M. A	u By: B	ANGAN
Too.	By. B	That Remidelly