

Geotechnical Environmental Site Civil 959 Route 46E, Fl 3, Ste 300 Parsippany, NJ 07054 973.808.9050 www.sesi.org

# Remedial Investigation Work Plan

For:

Franklin Courts Former Coal Storage Site 1-99 Franklin Court Tarrytown, New York 10591

Prepared for:

Franklin Courts JV Partners JP

SESI Project No: 12345

Date: April 2024

# **TABLE OF CONTENTS**

LIS	T OF	ACRONYMS	i
1.0	IN	ITRODUCTION	1
2.0	Ρ	ROJECT BACKGROUND	2
2	.1	SITE DESCRIPTION	2
2	.2	PROPOSED DEVELOPMENT	2
2	.3	SITE HISTORY	2
2	.4	PREVIOUS ENVIRONMENTAL INVESTIGATIONS	2
	PHA	SE I ENVIRONMENTAL SITE ASSESSMENT REPORT, AEI, JUNE 2021	3
	GEC	DTECHNICAL INVESTIGATION REPORT, SESI, SEPTEMBER 2022	1
	PHA	SE II ENVIRONMENTAL SITE INVESTIGATION REPORT, SESI, MAY 2022	1
	SUF 2024	PLEMENTAL PHASE II ENVIRONMENTAL SITE INVESTIGATION REPORT, SESI, JANUARY	5
	TOF	OGRAPHY7	7
	2.6	GEOLOGIC SETTING	7
2	.7	HYDROGEOLOGIC SETTING	7
2	.8	SUMMARY OF ENVIRONMENTAL ASSESSMENT	7
3.0	F	IELD REMEDIAL INVESTIGATION	9
3	.1	SOIL REMEDIAL INVESTIGATION	)
3	.2	GROUNDWATER REMEDIAL INVESTIGATION10	)
	3.2.7	1 MONITORING WELL INSTALLATION	1
	3.2.2	2 MONITORING WELL SAMPLING	2
3	.3	SOIL VAPOR INVESTIGATION14	1
	3.3.1	1 SOIL VAPOR POINT INSTALLATION	1
	3.3.2	2 SOIL VAPOR POINT SAMPLING	1
4.0	D	ECONTAMINATION AND IDW16	5
5.0	S	URVEY	7

6.0	HUMAN HEALTH EXPOSURE ASSESSMENT	18
7.0	FISH AND WILDLIFE IMPACT ANALYSIS	19
8.0	DUSR	20
9.0	REMEDIAL INVESTIGATION REPORT	21
10.0	QUALITY ASSURANCE/QUALITY CONTROL	22
11.0	HEALTH AND SAFETY PLAN	23
12.0	COMMUNITY AIR MONITORING	24
13.0	CITIZEN PARTICIPATION	25
14.0	REMEDIAL INVESTIGATION SCHEDULE	26

# **TABLES**

TABLE 3.1	SUMMARY OF PROPOSED SOIL BORING AND SAMPLING	

- TABLE 3.2SUMMARY OF PROPOSED GROUNDWATER MONITORING WELLS
- TABLE 3.3 SUMMARY OF PROPOSED SOIL VAPOR SAMPLING
- TABLE 14.1 PROPOSED REMEDIAL INVESTIGATION SCHEDULE

# **FIGURES**

- FIGURE 1.1 SITE LOCATION MAP
- FIGURE 2.1 SITE PLAN
- FIGURE 3.1 PROPOSED SOIL SAMPLE LOCATION PLAN
- FIGURE 3.2 PROPOSED GROUNDWATER SAMPLE LOCATION PLAN
- FIGURE 3.3 PROPOSED SOIL VAPOR SAMPLE LOCATION PLAN

# **APPENDICES**

APPENDIX A QUALITY ASSURANCE PROJECT PLAN (QAPP)

APPENDIX B EMERGING CONTAMINANT SAMPLING PLAN

APPENDIX C TYPICAL BORING/WELL CONSTRUCTION LOG

APPENDIX D HEALTH AND SAFETY PLAN (HASP) APPENDIX E COMMUNITY AIR MONITORING PLAN (CAMP) APPENDIX F CITIZEN PARTICIPATION PLAN (CPP)

#### CERTIFICATIONS

*I*, Fuad Dahan, certify that I am a professional engineer, and meet the definition of qualified environmental professional as defined in 6 NYCRR Part 375 and that this Remedial Investigation Work Plan was prepared in accordance with all applicable statutes and regulations and in substantial conformance with the DER Technical Guidance for Site Investigation and Remediation (DER-10).

NY Professional Engineer #090531

Date

Signature

It is a violation of Article 130 of New York State Education Law for any person to alter this document in any way without the express written verification of adoption by any New York State licensed engineer in accordance with Section 7209(2), Article 130, New York State Education Law.

# LIST OF ACRONYMS

Acronym	Definition
AWQS	Ambient Water Quality Standards
BCA	Brownfield Cleanup Agreement
BCP	Brownfield Cleanup Program
bgs	Below ground surface
COC	Contaminant of Concern
DER	Division of Environmental Remediation
DER-10	NYSDEC Technical Guidance for Site Investigation & Remediation
DUSR	Data Usability Summary Report
ELAP	Environmental Laboratory Accreditation Program
FWIA	Fish and Wildlife Resources Impact Analysis
ft-bgs	feet below ground surface
IDW	Investigative Derived Waste
msl	Mean Sea Level
MW	Monitoring Well
NYSDEC	New York State Department of Environmental Conservation
NYSDOH	New York State Department of Health
РАН	Polycyclic Aromatic Hydrocarbons
РСВ	Polychlorinated Biphenyls
PCE	Tetrachloroethene
PFAS	Per and Polyfluoroalkyl Substances
RECs	Recognized Environmental Concerns
RI	Remedial Investigation
RIR	Remedial Investigation Report

Acronym	Definition		
RIWP	Remedial Investigation Work Plan		
RSCO	Residential Soil Cleanup Objective		
RRSCO	Restricted-Residential Use Soil Cleanup Objective		
SCG	Standards, Criteria, and Guidance		
SCO	Soil Cleanup Objectives		
SESI	SESI Consulting Engineers, DPC		
SVOCs	Semi-Volatile Organic Compounds		
TAL	Target Analyte List		
TCE	Trichloroethene		
TCL	Target Compound List		
TOGS	Technical and Operations Guidance Series		
USCO	Unrestricted Use Soil Cleanup Objectives		
VOCs	Volatile Organic Compounds		

### 1.0 INTRODUCTION

Franklin Courts JV Partners, L.P. (the "Volunteer") is applying to enter the New York State Department of Environmental Conservation (NYSDEC) Brownfield Cleanup Program (BCP) to investigate and remediate the property located at 1-99 Franklin Court, Tarrytown, Westchester County, New York (the "Site"). A Site Location Map is presented as **Figure 1.1**.

This document comprises a Remedial Investigation Work Plan (RIWP) that describes the investigation activities proposed to be conducted at the Site, as part of the Site's planned remedial investigation. This RIWP includes a description of the Site, summary of the Site history and previous environmental investigations, a description of the Site's physical, geologic, hydrogeologic setting and subsurface features and a plan of action for further investigation of the areas of concern identified previously.

This RIWP has been prepared to achieve the following objectives:

- To complete the horizontal and vertical delineation of the nature and extent of contamination on the Site;
- To identify any potential source areas of contamination;
- To determine the remedial action needed to protect human health and the environment; and
- To collect sufficient data to evaluate remedial alternatives for the Site.

This RIWP is developed in accordance with the Department's Remediation Technical Guidance for Site Investigation and Remediation (DER-10).

#### 2.0 PROJECT BACKGROUND

#### 2.1 SITE DESCRIPTION

The Site consists of a 6.751-acre parcel and is located at 1-99 Franklin Court, Tarrytown, Westchester County, New York. The subject property is located in an urban area, and the surrounding area is occupied by commercial and residential buildings. The Site is considered to be a portion of Lot 32. The project site currently contains 70 townhomes in 14 buildings, plus one small community building. These buildings will ultimately be replaced by 40 townhomes in 11 buildings, plus two 20-unit multifamily buildings, and one clubhouse. A Site Plan is presented as **Figure 2.1**.

The subject property is bounded to the north by a multi-family residential apartment building at 50 White Street, to the east by Riverview Avenue and residential developments beyond, to the south by residential development along MacArthur Avenue, and to the west by Warehouses, railroad tracks and self-storage buildings.

### 2.2 PROPOSED DEVELOPMENT

The planned redevelopment will consist of a row of three- and four-unit attached townhouses through the center of the site.. There will be additional townhouses and two (2) twenty-unit multi-family buildings along the eastern side of the site.

# 2.3 SITE HISTORY

The Site was submerged by the Hudson River from 1897 to 1931. From 1932 to 1950 the Site appeared as vacant land. In 1950 the northern portion of the Site is a coal yard with office, sheds, and an automobile garage. The Site was developed between 1951 and 1952 with the current Franklin Court Apartments with 14 residential buildings and one (1) recreational building.

# 2.4 PREVIOUS ENVIRONMENTAL INVESTIGATIONS

The following environmental reports that have been previously completed for the Site are summarized below:

• Phase I Environmental Site Assessment Report, 1-99 Franklin Court, Tarrytown, New York, AEI Consultants, June 2021.

- Geotechnical Investigation and Report, 1-99 Franklin Court, Tarrytown, New York, Environmental Products & Services, Inc, June 2001.
- Phase II Environmental Site Assessment Report, 1-99 Franklin Court, Tarrytown, New York, SESI, May 2022.
- Supplemental Phase II Environmental Site Assessment Report, 1-99 Franklin Court, Tarrytown, New York, SESI, January 2024.

#### PHASE I ENVIRONMENTAL SITE ASSESSMENT REPORT, AEI, JUNE 2021

According to a Phase I Environmental Site Assessment prepared by AEI Consultants in June 2021, Sanborn Fire Insurance Maps identify the Site was submerged by the Hudson River from 1897 to 1931. From 1932 to 1950 the Site appears as vacant land. In 1950 the northern portion of the Site is a coal yard with office, sheds, and an automobile garage. In 1970, the Site is developed with the current Franklin Court Apartments with 14 residential buildings and one (1) recreational building believed to have been constructed between 1951 and 1952. In addition, AEI observed suspected heating oil vent pipes around the residential buildings 5 and 6 but noted that ground visibility was limited due to snow. AEI's review of Google Earth street imagery identified 20 additional suspected heating oil vent pipes throughout the Site.

The Underground Storage Tank Closure Report For Seven #2 Fuel Oil USTs, 50 White Street, Tarrytown, New York, prepared by Environmental Products & Services Inc. (EPS) documents the in-place abandonment of the seven (7) #2 fuel oil underground storage tanks (USTs) at Building 4 of the Site in May and June of 2001. USTs ranging in size from 275 gallons to 550 gallons were cut open, cleaned and abandoned in place. The report noted several tanks were observed to be in poor condition with evidence of pitting and potential leaks. EPS notified the NYSDEC, and Spill Number 0102305 was assigned. EPS advanced three (3) soil borings that were converted to monitoring wells for investigation of the USTs. No evidence of petroleum impacts was observed. Results of groundwater sampling identified Methyl-tertiary-butyl ether (MTBE) at concentrations ranging from 68.1 ug/L to 112 ug/L, exceeding the NYSDEC AWQS. Follow-up groundwater monitoring conducted in March 2003 identified no exceedances of the AWQSs in the three (3) wells. According to the NYSDEC database, Spill Number 0102305 associated with the USTs was closed in October 2009.

#### **GEOTECHNICAL INVESTIGATION REPORT, SESI, SEPTEMBER 2022**

SESI reviewed historic investigations and reporting that noted previous investigations that collected up to 12 geotechnical borings and 10 environmental borings for exploratory purposes.

The boring logs indicate  $4\pm$  to  $9\pm$  feet of fill were encountered at the surface consisting of miscellaneous sand, gravel, and bricks. An approximate 3- to 5-foot-thick layer of black silt was observed below the bottom of the fill within several of the borings within the western portion of the site. The alluvial soils consisting of layered silty sands, silty clays, and clayey silts were observed in all the borings either below the black silt or the surficial fill. A more comprehensive geotechnical investigation was recommended.

#### PHASE II ENVIRONMENTAL SITE INVESTIGATION REPORT, SESI, MAY 2022

SESI concluded that the exceedances in the soil, and groundwater, and soil vapor detections reported during the investigation may be attributable to the coal storage facility and the automobile garage that existed prior to 1970. Residential USTs at the Site may also have contributed to the presence of soil vapor petroleum compounds. Results of the GPR survey identified one (1) suspected UST in front of a residence at Building 2 (2E). The anomaly discovered measured to be approximately 4 ft by 8 ft. In addition, Investigation of the numerous suspect vent pipes was inconclusive by direct induction tracing of the lines and GPR scanning in most areas. It is possible that USTs exist that are beneath foliage where scanning was not possible.

Analytical results of this investigation identified metals impacts to soil exceeding the RRSCO in the northern portion of the Site at 5 ft-bgs where the water table is located, and concluded that the lead concentration in SB-3 located in the north-central portion of the Site may be hazardous. RRSCO SVOC (PAHs) exceedances were also identified at 7 ft-bgs in the southern portion of the Site. USCO exceedances for some metals, SVOCs (PAHs) and pesticides were identified throughout the Site at depths up to 9 ft-bgs. PCB contamination exceeding the USCO was detected at the SB-3 (5') and SB-5 (9') soil sampling locations. Acetone exceeding the USCO was detected in one (1) location in the northern portion of the Site.

Metal and SVOC (PAHs) exceedances of the AWQS were detected in all groundwater temporary wells. This may be due to coal storage leachate contamination that originated from the northern portion of the Site and migrated throughout the Site. PFAS (PFOA and/or PFOS) exceedances

were identified in all four (4) temporary wells. The source of the PFAS contamination has not been located.

Soil vapor testing indicates the presence of petroleum-related compounds. The low concentrations do not suggest a large petroleum release or releases. These detections may be related to residential #2 fuel oil USTs and/or historic automobile repair activities in the northern portion of the Site. There are also compounds in the soil gas that are typically associated with chlorinated solvents. The low concentrations do not suggest a large solvent release or releases. These detections may be related to automobile repair activities in the northern portion of the Site. Acetone was also detected in the soil vapor at all locations. The source of acetone, a solvent, may be the automobile repair shop previously located in the northern portion of the Site. A soil vapor intrusion evaluation with collocated sub-slab vapor and indoor air samples is recommended after site redevelopment.

SESI recommends that prior to any development on the Site a additional investigation is conducted to delineate the extent of the metals, SVOCs (PAHs), pesticides, PCB and acetone soil contamination and to evaluate soil remedial options. The investigation should also delineate the metals, SVOC (PAHs) and PFAS contamination in groundwater and evaluate remedial options available to comply with the AWQS. Indoor air samples should also be collected to confirm that no further action is needed to address the soil vapor solvent and petroleum contamination.

# SUPPLEMENTAL PHASE II ENVIRONMENTAL SITE INVESTIGATION REPORT, SESI, JANUARY and MARCH 2024

SESI conducted a Supplemental Phase II Environmental Site Assessment of the Site in December 2023 and again in March 2024. The December 2023 investigation included sampling of soil, groundwater and soil vapor points. The March 2024 investigation included only soil sampling to confirm contaminants identified during the December 2023 investigation. The analytical results of these investigations identified metals in exceedance of the RRSCOs as well; including lead and mercury to depths of 10 ft-bgs. The highest concentration of lead was detected in SB-109 (9.5-10') at 799 ppm. The metals in exceedance of the USCOs including arsenic, cadmium, copper, iron, lead, mercury, nickel, and zinc to depths ranging from 2.5 ft-bgs to 10 ft-bgs. The SVOCs exceedances of the RRSCOs include benzo(a)anthracene, benzo(a)pyrene, benzo(b)fluoranthene, chrysene, Dibenzo(a,h)anthracene, Indeno(1,2,3-cd)pyrene to depths of 7.5 ft-bgs. The SVOCs benzo(k)fluoranthene, and 2-Methylnaphthalene were detected at

concentrations exceeding the RSCOs to depths of 7.5 ft-bgs. The pesticides 4,4'-DDE, 4,4'-DDD, and dieldrin were detected at concentrations exceeding the USCOs to depths ranging from 3.5 ftbgs to 11 ft-bgs. No VOC or PCBs were detected at concentrations exceeding the USCOs or RRSCOs, with the exception of acetone was detected at concentrations exceeding the USCOs to depths of 9.5 ft-bgs.

The highest contaminant concentrations are located at soil borings SB-103 (4.5-5), and SB-104 (7-7.5') in the northern portion of the Site where in 1950 a coal yard with office, sheds, and an automobile garage was located. The metal contaminants detected at this location may be attributable to coal storage leachate. Metals contamination at SB-109 (9.5-10'), and SB-113 (8.5-9') in the central section of the Site may also be attributable to coal storage leachate, as well.

During December 2023, the soil vapor results did indicate the presence of petroleum-related compounds such as benzene, ethylbenzene, m,p-xylene, o-xylene, hexane, heptane and trimethylbenzene. The detections may be attributable to the former residential #2 fuel oil USTs and/or automobile repair activities in the northern portion of the Site. Acetone was also detected in the soil vapor location. The source of acetone, a solvent, may be attributable to the automobile repair shop previously located in the northern portion of the Site.

Metal exceedances of the AWQS were detected in the groundwater temporary well point sample, GW101. This may be due to coal storage leachate contamination that originated from the northern portion of the Site and migrated throughout the Site. PFAS (PFOA and/or PFOS) exceedances were identified as well in the temporary well point. The source of the PFAS contamination has not been identified at the Site.

The exceedances in the soil, and groundwater, and soil vapor detections reported during the May 2022, and December 2023 investigations were attributed to the historic coal storage facility and the automobile garage that existed prior to 1970, as well as the former and current abandoned in place residential USTs at the Site that have also contributed to the presence of soil vapor petroleum compounds detections. The Phase II and supplemental Phase II investigations determined that remedial actions need to be implemented to remediate the contaminated soil groundwater, and to mitigate potential vapor intrusion risks.

It should be noted, ground-penetrating radar (GPR) equipment was utilized during each investigation at the Site to locate and potential USTs or other subsurface anomalies prior to commencing drilling activities. No USTs or other anomalies were detected.

#### TOPOGRAPHY

According to the United States Geological Survey (USGS) White Plains, NY, 2013, 7.5-minute Series topographic map, the Site's average topographic elevation is approximately 17' above mean sea level (msl). The topographic map indicates that the topographic gradient at the Site slopes downward from east to the west.

#### 2.6 GEOLOGIC SETTING

Soil borings conducted during previous investigations identified a historic fill layer below the surface in all borings to depths ranging from 1 to 18 ft-bgs. The fill layer appears to be characterized by gray/brown sand with varying amounts of silt, clay, gravel, brick, glass and organics. Beneath the existing fill are the natural soil deposits consisting primarily of a gray/brown silty clay with some medium to fine sand (glacial till) followed by bedrock. The depth to bedrock at the Site appears to be greater than 25 ft-bgs.

#### 2.7 HYDROGEOLOGIC SETTING

During the prior investigation in 2023, groundwater was generally encountered during the drilling at depths ranging from approximately  $4\pm$  to  $8\pm$  ft-bgs. This fluctuation is likely due to the proximity of the Hudson River.

#### 2.8 SUMMARY OF ENVIRONMENTAL ASSESSMENT

Based on the investigations conducted to date, the primary contaminants of concern (COCs) are anticipated to be metals, PAHs and pesticides in soil, metals, PAHs and PFAS in groundwater and several VOCs in soil vapor. COCs will be refined based on the Remedial Investigation (RI) results.

**Soil** (maximum concentrations):

- **VOCs**: Acetone (0.0931 mg/kg).
- PAHs: Benzo(a)anthracene (14.4 mg/kg), benzo(a)pyrene (12.9 mg/kg), benzo(b)fluoranthene (15.1 mg/kg), benzo(k)fluoranthene (2.72 mg/kg), chrysene (10.5 mg/kg), dibenzo(a,h)anthracene (1.92 mg/kg), indeno(1,2,3-cd)pyrene (6.16 mg/kg) and 2-methylnaphthalene (14.2 mg/kg).

- Pesticides: Dieldrin (0.034 mg/kg), 4,4'-DDE (0.53 mg/kg), 4,4'-DDD (0.064 mg/kg) and 4,4'-DDT (0.22 mg/kg).
- Metals: Cadmium (24 mg/kg), copper (722 mg/kg), iron (38,200 mg/kg), lead (7,190 mg/kg), mercury (2.2 mg/kg), nickel (42.9 mg/kg) and zinc (8,410 mg/kg).

**Groundwater** (maximum concentrations):

- **PAHs**: Benzo(a)anthracene (0.23 ug/L), benzo(a)pyrene (0.26 ug/L), Benzo(b)fluoranthene (0.22 ug/L), benzo(k)fluoranthene (0.22 ug/L), chrysene (0.27 ug/L) and indeno(1,2,3-cd)pyrene (0.27 ug/L).
- Metals: Aluminum (322,000 ug/L), antimony (22 ug/L), arsenic (161 ug/L), barium (2,250 ug/L), beryllium (105 ug/L), cadmium (21 ug/L), chromium (760 ug/L), copper (690 ug/L), iron (639,000 ug/L), lead (3,090 ug/L), magnesium (192,000 ug/L), manganese (9,640 ug/L), mercury (1.2 ug/L), nickel (517 ug/L), sodium (239,000 ug/L) and zinc (6,690 ug/L).
- **PFAS**: PFOS (68.8 ng/L) and PFOA (50.9 ng/L).

**Soil Vapor** (maximum concentrations):

1,2,4-Trimethylbenzene (9.33 ug/m<sup>3</sup>), 4-Methyl-2-pentanone (MIBK) (7.57 ug/m<sup>3</sup>), Carbon Tetrachloride (0.39 ug/m<sup>3</sup>), Chloroform (3.21 ug/m<sup>3</sup>), Dichlorodifluoromethane (2.54 ug/m<sup>3</sup>), Ethanol (23 ug/m<sup>3</sup>), Ethylbenzene (25 ug/m<sup>3</sup>), Heptane (17.4 ug/m<sup>3</sup>), Hexane (34.8 ug/m<sup>3</sup>), Isopropylalcohol (8.72 ug/m<sup>3</sup>), m,p-Xylene (106 ug/m<sup>3</sup>), Methyl Ethyl Ketone (212 ug/m<sup>3</sup>), o-Xylene (32.5 ug/m<sup>3</sup>), Tetrachloroethene (3.95 ug/m<sup>3</sup>), Tetrahydrofuran (36 ug/m<sup>3</sup>), Toluene (273 ug/m<sup>3</sup>), Trichloroethene (2.4 ug/m<sup>3</sup>), Trichlorofluoromethane (1.42 ug/m<sup>3</sup>), Acetone (2-Propanone) (226 ug/m<sup>3</sup>), Benzene (7.73 ug/m<sup>3</sup>), Carbon disulfide (38.6 ug/m<sup>3</sup>), Cyclohexane (5.9 ug/m<sup>3</sup>), Ethyl Acetate (256 ug/m<sup>3</sup>), Isopropyl Alcohol (1.9 ug/m<sup>3</sup>), Propylene (73.1 ug/m<sup>3</sup>), 2,2,4-Trimethylpentane (2.3 ug/m<sup>3</sup>), Tertiary Butyl Alcohol (2.1 ug/m<sup>3</sup>), Xylenes (total) (14 ug/m<sup>3</sup>), Methylene Chloride (12.4 ug/m<sup>3</sup>), 1,3,5-Trimethylbenzene (3.71 ug/m<sup>3</sup>), 1,3-Butadiene (15.2 ug/m<sup>3</sup>), 4-Ethyltoluene (13.7 ug/m<sup>3</sup>), Isopropyltoluene (2.78 ug/m<sup>3</sup>), Isopropylbenzene (1.79 ug/m<sup>3</sup>), sec-Butylbenzene (1.3 ug/m<sup>3</sup>) and Styrene (1.06 ug/m<sup>3</sup>).

#### 3.0 FIELD REMEDIAL INVESTIGATION

Soil borings, groundwater monitoring wells and soil vapor points are proposed below based on the following rationale to complete the nature and extent delineation of contaminated soil, groundwater, and soil vapor on the Site. The applicable standards criteria and guidance (SCGs) for the Site soil are the 6 NYCRR Part 375 Soil Cleanup Objectives (SCOs). The applicable standards criteria and guidance (SCGs) for the Site groundwater are the 6 NYCRR Part 703 AWQS and Technical and Operational Guidance Series (TOGS) 1.1.1. New York State recently updated applicable remediation criteria for constituents found in soil vapor gases to include petroleum VOCs as well as additional CVOCs. The applicable criteria for sub-slab vapor are the NYSDOH Decision Matrices (May 2024), which will be used for comparison purposes and for remedial decisions relating to petroleum VOCs found in soil-vapor samples at the Site. Remedial field investigation activities will commence once Franklin Courts JV Partners L.P. and SESI receive approval from the NYSDEC.

#### 3.1 SOIL REMEDIAL INVESTIGATION

Forty-nine (49) soil borings will be advanced on the Site to further evaluate and delineate soil contamination. The number of borings is estimated based on approximately one (1) sample for every 50' x 50' area in the locations intended for residential development, with a reduced frequency proposed for other parts of the Site. The proposed soil boring locations are shown on **Figure 3.1.** The proposed soil sample locations and the rationale for their locations are presented in **Table 3.1** below.

The borings will be advanced to a depth of 20 ft-bgs (or refusal) using direct-push or other drilling methods as needed as shown on **Table 3.1** below. The 20-foot depth of the proposed borings should be sufficient to characterize both the fill layer and native soils across the Site, and will also serve to characterize soils both above and below the soil-water interface, which is expected to be encountered between 4-8 ft-bgs. Soil samples will be collected at a rate of one sample per 5-foot depth interval based on field screening that includes visual observations, photoionization detector (PID) readings and olfactory observations. If no visual observations of contamination are observed, two samples at a minimum will be collected from each borehole: one (1) 6-inches above the water table interface, and one at the highest recorded PID reading. Boring logs documenting soil classifications, PID readings, and visual observations will be provided in the final report.

Soil samples collected from the boring locations will be analyzed by a NYSDOH Environmental Laboratory Accreditation Program (ELAP) certified laboratory for TCL + 30/TAL including VOCs by EPA Method 8260C, SVOCs by EPA Method 8270D, pesticides by EPA Method 8081B, PCBs by EPA Method 8082A, TAL metals by EPA Methods 6010C, 7471B, and 9012. Approximately 25% of the samples (up to approximately 49 samples) will also be analyzed for the 41 PFASs compounds by EPA Modified Method 1633 and 1-4,dioxane by EPA Method 8270. Category B deliverables will be requested on each sample chain of custody. SESI's field sampling procedures are described in the Quality Assurance Project Plan (QAPP) presented in **Appendix A.** The Sampling Plan for Emerging Contaminants is included as **Appendix B.** 

Quality Assurance/Quality Control (QA/QC) samples will be collected and analyzed as specified in the QAPP. The number of duplicate, spiked, and blank samples analyzed will be collected at a frequency of one (1) duplicate for every 20 samples. The inclusion and frequency of analysis of field blanks will be on the order of one per every 20 soil samples but not more than one (1) per day. Samples to be analyzed for volatile organic compounds will be accompanied by a field blank for all matrix types and trip blank for water matrices.

Soil Boring ID	Boring Depth (ft)	Proposed Sampling Interval (ft)	Target Analyses	Sampling Rationale	
	20	0-5	TCL/TAL+30 (with 25% of samples containing 1,4-Dioxane and PFAS)	Nature and Extent of Fill layer	
RI-SB-1		5-10		Characterize Bottom Fill Layer	
49		10-15		1,4-Dioxane and PFAS)	Characterize soil vertically
		15-20			Characterize soil vertically

Table 3.1 Summary of Proposed Soil Boring and Sampling

# 3.2 GROUNDWATER REMEDIAL INVESTIGATION

The Groundwater RI will be conducted to achieve the following:

- delineate the nature and extent of specific contaminants in the Site groundwater;
- identify actual or potential impacts to sensitive receptors, e.g. surface water;
- determine whether a contaminant plume exists;
- gather sufficient data to determine groundwater flow direction and contour map and evaluate groundwater remedial alternatives, including, as appropriate, and
- provide information on the background quality of the groundwater flowing into the Site.

#### 3.2.1 MONITORING WELL INSTALLATION

To investigate the Site groundwater, a total of ten (10) permanent groundwater monitoring wells will be installed across the Site as shown on **Figure 3.2**, to evaluate Site-wide concentrations of groundwater. The groundwater flow is anticipated to be towards the Hudson River to the west of the Site. Monitoring wells RI-MW-01 through RI-MW-04 are proposed in the anticipated upgradient (eastern) and portion of the Site, and wells RI-MW-05, RI-MW-08, and RI-MW-09 are proposed near the downgradient (western) Site boundary. Based on the known presence of groundwater in the shallow overburden soils, the installation of bedrock wells should not be necessary. The proposed groundwater monitoring wells and sampling details are presented in the **Table 3.2** below. The wells will be installed to an anticipated total depth of 15 ft-bgs based on where groundwater was encountered during previous investigations. Each monitoring well will be constructed with 2-inch diameter well screens. The well screening will intersect the water table and extend to the bottom of the well boring. The annular space of each well will be filled with well sand to at least 2 feet above the screening and will be sealed with hydrated bentonite or cement grout. Finally, each monitoring well will be completed with a flush-mount road-box or stickup as necessary. A typical boring and well construction log is provided in **Appendix C**.

The wells will be surveyed for location and elevation. The survey data will be provided pursuant to the DER-10 requirements in an acceptable format (e.g., North America Datum 83 [NAD83]). The wells will be gauged for groundwater depth to determine the groundwater elevation. The Site-specific groundwater flow direction and gradient will be determined based on the latest elevation data and summarized in the Remedial Investigation Report (RIR). The proposed well locations are shown on **Figure 3.2**.

Well ID Type		Estimated Depth (ft)	Screen Interval (ft)	Target Analyses
RI-MW-01	Overburden	15	10-15	TCL+30/TAL, PFAS, 1,4-Dioxane
RI-MW-02	Overburden	15	10-15	TCL+30/TAL, PFAS, 1,4-Dioxane
RI-MW-03	Overburden	15	10-15	TCL+30/TAL, PFAS, 1,4-Dioxane
RI-MW-04	Overburden	15	10-15	TCL+30/TAL, PFAS, 1,4-Dioxane

 Table 3.2: Summary of Proposed Groundwater Monitoring Wells

Well ID	Туре	Estimated Depth (ft)	Screen Interval (ft)	Target Analyses
RI-MW-05	Overburden	15	10-15	TCL+30/TAL, PFAS, 1,4-Dioxane
RI-MW-06	Overburden	15	10-15	TCL+30/TAL, PFAS, 1,4-Dioxane
RI-MW-07	Overburden	15	10-15	TCL+30/TAL, PFAS, 1,4-Dioxane
RI-MW-08	Overburden	15	10-15	TCL+30/TAL, PFAS, 1,4-Dioxane
RI-MW-09	Overburden	15	10-15	TCL+30/TAL, PFAS, 1,4-Dioxane
RI-MW-10	Overburden	15	10-15	TCL+30/TAL, PFAS, 1,4-Dioxane

# 3.2.2 MONITORING WELL SAMPLING

Two (2) rounds of sampling will be conducted from each well. The first round will be conducted after monitoring well installations during the RI, and the second round will be conducted prior to remedial action (no sooner than 30 days from the first round). The second round of analytical data will act as a baseline prior to the implementation of the selected remedial action at the Site. The data will be analyzed to determine whether groundwater contamination exists, the magnitude and the extent of any potential contaminant plume. In addition to the analytical data, field measurements and chemical analyses will be conducted to characterize the impacted groundwater.

All the wells will be sampled for TCL + 30/TAL metals, PFAS, and 1-4 dioxane. The VOCs will be analyzed by EPA Method 8260C, SVOCs by EPA Method 8270D, pesticides by EPA Method 8081B, PCBs by EPA Method 8082A, TAL metals by EPA Methods 6010C, 7471B, and 9012, PFAS compounds by Modified EPA Modified Method 1633, and 1-4,dioxane by EPA Method 8270 SIM. The QAPP, which describes all field sampling procedures, is included as **Appendix A**, and the Sampling Plan for Emerging Contaminants is included as **Appendix B**.

Groundwater samples will be analyzed by a NYSDOH ELAP certified laboratory, and Category B deliverables will be requested on each sample chain of custody. In addition, QA/QC samples will be collected and analyzed as specified in the QAPP. Specifically, the number of duplicate, spiked and blank samples analyzed will be a minimum of one (1) duplicate for every 20 samples. For the aqueous matrix, field blanks will be collected at a frequency of one (1) per day. Samples to be analyzed for volatile organic compounds will be accompanied by a trip blank for each shipment and field blanks water matrix.

All monitoring wells will be developed or cleared of all fine-grained materials and sediments that have settled in or around the well during installation so that the screen is transmitting representative portions of the groundwater. The development will be by one of two methods, pumping or bailing groundwater from the well until it yields relatively sediment-free water.

A decontaminated pump or bailer will be used and subsequently decontaminated after each use following procedures outlined in the Decontamination Protocol. Pumping or bailing will cease when the turbidity falls below 50 NTUs or until specific conductivity, pH, and temperature are stable (i.e., consecutive readings are within 10 percent with no overall upward or downward trends in measurements). Well development water will be contained in drums and properly disposed off-site.

The wells will be sampled using the low-flow technique, when possible. A flow rate of 100 ml to 250 ml per minute is used to purge the wells. Drawdown should not exceed 0.3 feet. At the initiation of low flow purging water levels and field parameters are recorded. Field parameters are then monitored every five minutes during low flow purging using a flow through cell. When three consecutive measurements of pH differ by 0.1 units or less, with ORP within 10 mv or less, turbidity varies 10 percent or less, conductivity differs by 3 percent or less and dissolved oxygen by 10 percent or less, sampling may begin. Flow through cells allow continuous real-time readings. When the parameters stabilize, the flow through cell is disconnected and sample bottles are filled directly from the tubing. If the parameters of a well do not stabilize in a timely manner, the groundwater sample will be collected after emptying three well volumes from the sample well. In addition to water samples collected from the monitoring wells, two types of "blanks" will be collected and submitted to the chemical laboratory for analyses. The blanks will consist of 40 ml VOA vials, as follows:

• A trip blank will be prepared before the sample bottles are sent by the laboratory. It consists of a sample of distilled, deionized water that accompanies the other sample bottles into the field and back to the laboratory. A trip blank will be included with each shipment of samples where sampling and analysis for TCL volatiles is planned (water

matrix only). The trip blank will be analyzed for TCL VOCs as a measure of potential contamination from background sources and their effect on the results.

• To check for contaminant carryover if non-dedicated sampling equipment is used, a rinsate blank will be submitted to the laboratory. This blank will also be analyzed for TCL VOCs.

### 3.3 SOIL VAPOR INVESTIGATION

### 3.3.1 SOIL VAPOR POINT INSTALLATION

SESI will collect 10 soil vapor samples from 10 soil vapor locations across the Site, to evaluate Site-wide soil vapor. In addition, one (1) ambient air sample will be collected. The proposed soil vapor point locations are shown on **Figure 3.3**. The purpose of the soil vapor investigation is to assess the potential for vapor intrusion into future buildings. The applicable criteria for sub-slab vapor are the NYSDOH Decision Matrices (May 2017) lower threshold values will be used for comparison purposes and not for remedial decisions. New York State does not have applicable remediation criteria for constituents found in soil vapor gases.

The soil gas samples will be collected in accordance with the procedures of the NYS Department of Health October 2006 Guidance for Evaluating Soil Vapor Intrusion in the State of New York, updated in February 2024 with 13 petroleum-related compounds. Specifically, the soil vapor probes will be advanced using direct push sampling equipment and samples will be collected by installing vapor implants. The soil vapor depth will be based on the final construction and development plan. A sacrificial vapor point connected to flexible tubing will be inserted into the borehole. The annular space of the borehole will be filled with sand and the surface will be sealed with bentonite to seal the surface. Prior to sampling the tubing system will be purged of ambient air with a low-flow pump.

#### 3.3.2 SOIL VAPOR POINT SAMPLING

The ambient air and soil vapor samples will be collected into laboratory supplied stainless-steel summa canisters. The summa canisters will be equipped with a manometer to verify the canister is under vacuum, and a flow controller will be set to a flow rate not to exceed 200 ml/min. A sample log sheet will be maintained summarizing sample identification, date and time of sample

collection, sampling depth, identity of samplers, sampling methods and devices, soil vapor purge volumes, volume of the soil vapor extracted, vacuum of canisters before and after the samples are collected, apparent moisture content of the sampling zone, and chain of custody protocols. The vapor samples will be sent to a certified laboratory for analysis of VOCs in accordance with EPA Method TO-15. The field sampling procedures are described in the QAPP, which is included as **Appendix A**.

As part of the vapor sampling, a tracer gas will be used to serve as a QA/QC device to verify the integrity of the soil vapor probe seal. Helium will be used as the tracer gas, and a box will serve to keep it in contact with the probe during testing. A portable monitoring device will be used to analyze a sample of soil vapor for the tracer prior to sampling. If the tracer sample results show a significant presence of the tracer, the probe seals will be adjusted to prevent infiltration. At the conclusion of the sampling round, tracer monitoring will be performed a second time to confirm the integrity of the probe seals. SESI's field sampling procedures are described in the QAPP presented in **Appendix A**. The proposed soil vapor sample points are presented in **Table 3.3** below.

Location Name	Sampling Depth (ft)	Sample Media	Summa Type	Sample Type	Analysis
RI-SV-01	5	Soil Vapor	Summa Canister	(200 mL/min)	TO-15
RI-SV-02	5	Soil Vapor	Summa Canister	(200 mL/min)	TO-15
RI-SV-03	5	Soil Vapor	Summa Canister	(200 mL/min)	TO-15
RI-SV-04	5	Soil Vapor	Summa Canister	(200 mL/min)	TO-15
RI-SV-05	5	Soil Vapor	Summa Canister	(200 mL/min)	TO-15
RI-SV-06	5	Soil Vapor	Summa Canister	(200 mL/min)	TO-15
RI-SV-07	5	Soil Vapor	Summa Canister	(200 mL/min)	TO-15
RI-SV-08	5	Soil Vapor	Summa Canister	(200 mL/min)	TO-15
RI-SV-09	5	Soil Vapor	Summa Canister	(200 mL/min)	TO-15
RI-SV-10	5	Soil Vapor	Summa Canister	(200 mL/min)	TO-15
RI-SV-11	5	Soil Vapor	Summa Canister	(200 mL/min)	TO-15
RI-SV-12	5	Soil Vapor	Summa Canister	(200 mL/min)	TO-15
RI-AA-01	5	Soil Vapor	Summa Canister	(200 mL/min)	TO-15

 Table 3.3:
 Summary of Proposed Soil Vapor Sampling

#### 4.0 DECONTAMINATION AND IDW

Equipment utilized for ground intrusive activities (i.e. borings and wells) will not need to be decontaminated due to the similar contaminants found throughout the Site. All investigative derived waste (IDW) of soil cuttings and purged groundwater will be containerized, sampled, and properly disposed of pursuant to DER-10 requirements. Disposable sampling equipment, including macro core liners, spoons, gloves, bags, paper towels, and PPE that contacts environmental media, will be double bagged and disposed of as municipal trash in a facility trash dumpster as non-hazardous refuse.

# 5.0 SURVEY

After the RI sampling scope is completed, a survey will be completed, which includes the locations and elevations of all the monitoring wells, soil borings, and soil vapor points. Survey datum will be provided relative to NAD83. Elevation datum will be provided relative to NAVD88.

#### 6.0 HUMAN HEALTH EXPOSURE ASSESSMENT

A qualitative human health exposure assessment will be performed for the Site in accordance with the New York State Department of Health's Qualitative Human Health Exposure Assessment guidance document. Sampling data, along with the physical conditions of the contaminant sources or physical hazards near the Site, will be reviewed. Potential on-site and off-site exposures will be evaluated. The Exposure Assessment will describe the nature and size of the population exposed, or potentially exposed, to the contaminants that are present at, or migrating from the Site, and will characterize the exposure setting, identify exposure pathways, and evaluate contaminant fate and transport.

Several objectives will be met by the exposure assessment. First, applicable Site information and characterization data for environmental media of concern will be evaluated. Applicable SCGs, including Part 375 SCOs and CP-51 SCOs for soil, and AWQS for groundwater and surface water, will be applied. Second, a qualitative assessment will be made if there is a potential for off-Site migration of any contaminants.

An assessment of current and future Site activities and Site use will be conducted in relation to potential human exposure. Next, potential exposure pathways will be identified, and each aspect of the potential exposure pathway will be evaluated. Soil, groundwater and soil vapor contamination will be addressed and the impact of remediation on future exposure scenarios will be analyzed.

### 7.0 FISH AND WILDLIFE IMPACT ANALYSIS

A Fish and Wildlife Resources Impact Analysis (FWIA) Decision Key will be completed prior to the excavation work to determine if a FWIA is needed. Contaminant migration pathways and any fish and wildlife exposure pathways will be identified. As stated in the FWIA, "if no resources are associated with the site or if there is no potential for contaminant migration to the resources, then only the necessary information to support that conclusion should be provided."

If resources are identified, or migration pathways exist, a FWIA will be completed and submitted as part of the RI Report. The FWIA would include qualitative estimates of the following: 1) the routes, intensity, frequency, and duration of actual or potential exposures to chemicals; 2) the nature and size of the population exposed to the contaminants that are present at or migrating from the site; 3) the exposure setting and possible exposure pathways; and 4) contaminant fate and transport.

A Fish & Wildlife assessment is not anticipated for this Site due to its urban location and distance from surface water bodies and wildlife areas.

#### 8.0 DUSR

Following the completion of the laboratory analysis program, a Data Usability Summary Report (DUSR) will be completed for the lab data generated during the RI and included as part of the RI Report. The DUSR is carried out as specified in DER-10 to evaluate the quality control measures that were implemented during the field and laboratory analytical programs, with the objective of determining whether the reported analytical data are representative and usable for decision making. The DUSR will evaluate whether the data are technically defensible (i.e. were all analytical data requirements met and documented?). Data usability analysis reviews the Site data to determine whether they are adequate to draw conclusions regarding the nature and extent of contamination.

The items that will be reviewed as part of the DUSR will include the following:

- Completeness (number of samples collected and analyzed compared to plans)
- Chains of custody are complete and accurate
- Holding times
- Instrument calibration
- Relative percent difference between field duplicates
- Reasonableness of data (e.g. relationships between total and soluble analytes)
- Blank contamination

The DUSR will be conducted in accordance with guidelines provided under Appendix 2B of DER-10. The site-specific Quality Assurance Project Plan (QAPP) is included in **Appendix A**.

#### 9.0 REMEDIAL INVESTIGATION REPORT

Following the completion of the RI activities and the receipt of sample results, a RIR will be prepared. The RIR report will summarize the activities completed during the RI including analytical results, well construction and sampling logs, conclusions from the human health exposure assessment and from the FWIA if necessary, a DUSR, and laboratory data packages. Scaled figures showing the sample locations and areas of contamination exceeding applicable standards will be prepared for soil, soil vapor, and groundwater. Sampling results will be summarized and discussed and the need for additional investigation and remediation will be evaluated (including the removal of hydraulic lifts, drains, subsurface pits, tanks, drains, etc. if applicable). In addition, analytical summary tables will be prepared for soil, soil vapor, and groundwater compared to applicable standards.

The RIR will also include: 1) a summary of the Site history and previous investigations, 2) a description of current site conditions, 3) the identification of exposure pathways via a Qualitative Human Health Exposure Assessment; an analysis of the results, 4) a description of the nature and extent of the contamination including post remediation soil data collected during prior investigations (i.e., UST, pit, oil/water separator, and lift removals); and 5) a detailed conclusions with recommendations.

Analytical data collected during the Remedial Investigation will be submitted in the NYSDEC approved Electronic Data Deliverable (EDD) format. EDDs will be prepared using the NYSDEC's Environmental Information Management System (EIMS) database software application EQuIS<sup>™</sup> for submission.

# 10.0 QUALITY ASSURANCE/QUALITY CONTROL

QA/QC is addressed in the QAPP included as **Appendix A**. The QAPP outlines procedures to be followed for sampling and analysis to ensure quality of the results. A DUSR will be prepared for each laboratory report and will be provided with the final reports to document the reliability of the sample results.

# 11.0 HEALTH AND SAFETY PLAN

A Site-specific Health and Safety Plan (HASP) has been prepared and is included as Appendix

**D**. All on-site personnel and visitors involved in the RI will be required to read and sign the HASP prior to entry of the Site.

# 12.0 COMMUNITY AIR MONITORING

A Community Air Monitoring Plan (CAMP) is provided as **Appendix E**, in accordance with DER-10 requirements for remedial investigation. The CAMP sets forth air monitoring procedures that will be utilized to measure airborne emissions during the RI, to minimize the release of contaminants to off-Site areas during active remediation on the Site.

# 13.0 CITIZEN PARTICIPATION

Citizen participation activities will be performed throughout the RI process to involve and inform the public. The specific citizen participation activities to be performed are outlined in the Citizen Participation Plan (CPP), included as **Appendix F**.

# 14.0 REMEDIAL INVESTIGATION SCHEDULE

The proposed remedial investigation schedule is presented on **Table 14.1** below.

# Table 14.1: Proposed Remedial Investigation Schedule

Activity	Scheduled Date
Remedial Investigation – Soil and Soil Vapor Sampling	Spring 2024
Remedial Investigation Groundwater Sampling	Spring/Summer 2024
Submit Draft RIR	Autumn 2024

# **Figures**








# 4/19/2024 10:08 AM, Kim Vanderklein, MAPS. 2345/FINAL ':\GIS\P

LAYOUT: FIG-3.2



# **Appendix A:**

# **Quality Assurance Project Plan**



Geotechnical Environmental Site Civil 959 Route 46E, Fl 3, Ste 300 Parsippany, NJ 07054 973.808.9050 www.sesi.org

## QUALITY ASSURANCE PROJECT PLAN

For

TMHA Franklin Courts 1-99 Franklin Court Tarrytown, Westchester County, New York

Prepared for: Franklin Courts JV Partners L.P.

April 2024

SESI Project No: 12345

LIST OF ACRONYMS	i
1.0 PROJECT DESCRIPTION	.1
2.0 PROJECT ORGANIZATION	.1
2.1 PROJECT PRINCIPAL	2
2.2 PRINCIPAL ENGINEER	2
2.3 PROJECT MANAGER	2
2.4 FIELD TEAM LEADER	2
2.5 QUALITY ASSURANCE OFFICER	2
3.0 QA/QC OBJECTIVES FOR MEASUREMENT OF DATA	.2
3.1 COMPLETENESS	2
3.2 REPRESENTATIVENESS	3
3.3 COMPARABILITY	3
3.4 PRECISION AND ACCURACY	3
4.0 SAMPLING PROCEDURES	.4
4.1 SAMPLING PROGRAM	4
4.1.1 DRILLING/SAMPLING PROCEDURES	4
4.1.2 MONITORING WELL COMPLETION	5
4.1.3 WELL DEVELOPMENT	6
4.1.4 DECONTAMINATION	6
4.1.5 PFAS SAMPLING CONSIDERATIONS	6
4.2 GROUNDWATER SAMPLING PROGRAM	7
4.2.1 WELL EVACUATION	7
4.2.2 SAMPLING PROCEDURE	7
4.3 SOIL VAPOR SAMPLING	7
4.4 SAMPLE PRESERVATION AND SHIPMENT	8
5.0 SAMPLE CUSTODY	.8
5.1 FIELD SAMPLE CUSTODY	9
5.2 LABORATORY SAMPLE CUSTODY	9
5.3 FINAL EVIDENCE FILES	0
6.0 CALIBRATION PROCEDURES	0
7.0 ANALYTICAL PROCEDURES	0
7.1 VOLATILE ORGANICS	1
7.2 SEMI-VOLATILE ORGANIC COMPUNDS	1
7.3 PESTICDE AND PCB COMPOUNDS	1

## **Table of Contents**

7.4 METALS	11
7.5 PER- AND POLYFLUOROALKYL SUBSTANCES	11
7.6 SITE SPECIFICITY OF ANALYSES	13

## **TABLES**

- TABLE 2.1SESI PERSONNEL AND SUBCONTRACTORS
- TABLE 4.1SAMPLING PROCEDURE FOR MONITORING WELLS USING LOW-<br/>STESS (LOW-FLOW) METHODS
- TABLE 4.2SAMPLE CONTAINERIZATION
- TABLE 4.3SAMPLING OVERVIEW
- TABLE 7.1CONTRACT-REQUIRED QUANTITATION LEVELS AND ANALYTICAL<br/>METHODS FOR ASP INORGANICS, ASP VOLATILES, ASP SEMI-<br/>VOLATILES, ASP PESTICIDES, AND PCBs
- TABLE 7.2QUANTITATION LEVELS AND ANALYTICAL METHODS FOR PFAS



## LIST OF ACRONYMS

Acronym	Definition		
AAS	Absorption Spectroscopy		
ASP	Analytical Service Protocol		
BCP	Brownfield Cleanup Program		
DUSR	Data Usability Summary Report		
ELAP	Environmental Laboratory Accreditation Program		
GC/MS	Gas Chromatography/Mass Spectrometry		
HAS	Hollow-stem Auger		
HDPE	High-Density Polyethylene		
LDPE	Low-density Polyethylene		
LFPS	Low Flow Purging Sampling		
MDL	Method Detection Limit		
NYSDEC	New York State Department of Environmental		
	Conservation		
NYSDOH	New York State Department of Health		
PCB	Polychlorinated Biphenyls		
PFAS	Per- and polyfluoroalkyl substances		
PFOA	Perfluorooctanoic Acid		
PFOS	Perfluorooctanesulfonic Acid		
PPE	Personal Protective Equipment		
PTFE	Polytetrafluoroethylene		
QAPP	Quality Assurance Project Plan		
QA/QC	Quality Assurance/Quality Control		
RIWP	Remedial Investigation Work Plan		
SESI	SESI Consulting Engineers, Inc.		
TIC	Tentatively Identified Compound		
TCL	Target Compound List		
VOC	Volatile Organic Compound		
USEPA	United States Environmental Protection Agency		



## **1.0 PROJECT DESCRIPTION**

This document presents the Quality Assurance Project Plan (QAPP) for the Remedial Investigation Work Plan (RIWP) for the proposed development at 1-99 Franklin Court (a.k.a 50 White Street), Tarrytown, New York (the "Site"). The 6.751-acre parcel is identified as Block 29, Lot 32 on the Westchester County tax map. The Site has been developed with The Site is currently occupied by the Franklin Courts multifamily property improved with 14 residential buildings and one (1) recreational building.

The subject property is bounded to the north by a multi-family residential apartment building at 50 White Street, to the east by Riverview Avenue and residential developments beyond, to the south by residential development along MacArthur Avenue, and to the west by Warehouses and former railroad tracks.

SESI Consulting Engineers (SESI) prepared the RIWP for 1-99 Franklin Court, Tarrytown, New York, dated February 2024, which describes the investigation activities to be conducted at the Site, as part of the Site's planned remedial investigation and remediation.

#### 2.0 PROJECT ORGANIZATION

The RIWP activities will be conducted by SESI and their qualified subcontractors, on behalf of Franklin Courts JV Partners L.P. The organization of SESI's key project management and field staff, and respective areas of responsibility, is presented below **(Table 2.1)** along with the names of subcontractors.

Role	Name	Telephone No.	
Project Principal	Fuad Dahan, P.E., PhD	973-808-9050 x249	
Project Manager	Jesse Mausner	973-808-9050	
Principal Engineer	Fuad Dahan, P.E., PhD	973-808-9050 x249	
Field Team Leader	TBD	973-808-9050	
Quality Assurance Officer	Joe Scardino	973-808-9050 x267	
Field Personnel	TBD	973-808-9050	
Analytical Laboratory	Alpha Analytical	201-847-9100	
Data Validator	Hanibal Tayeh	413-875-5049	
Driller	Coastal Environmental Solutions	631-942-9209	

 Table 2.1—SESI Personnel and Subcontractors



## 2.1 PROJECT PRINCIPAL

Provides technical and administrative oversight and guidance throughout the project, assist in securing company resources, participate in technical review of deliverables, and attend key meetings as needed.

#### 2.2 PRINCIPAL ENGINEER

Provides technical guidance and review of reports, analytical data. Will have key involvement in screening and development of remedial alternatives.

#### 2.3 PROJECT MANAGER

Responsible for maintaining the day-to-day schedule for completing the fieldwork and deliverables according to Brownfield Cleanup Program (BCP) requirements and client expectations.

#### 2.4 FIELD TEAM LEADER

Responsible for overseeing field work during the implementation of the RIWP, including observing subcontractors, maintaining field notes, and collecting samples of various environmental media.

#### 2.5 QUALITY ASSURANCE OFFICER

Responsible for reviewing sampling procedures and certify that the data was collected and analyzed using the appropriate procedures.

#### 3.0 QA/QC OBJECTIVES FOR MEASUREMENT OF DATA

In cases where NYSDOH ELAP Certification exists for a specific group or category of parameters, the laboratory performing analysis in connection with this project will have appropriate New York State Department of Health (NYSDOH) ELAP Certification. Alpha Analytical, an ELAP-certified lab, will be performing the sample analyses for the project. Analytical Service Protocol (ASP, June 2000) Category B deliverables are required for all samples. All data will be sent to a third party, Hanibal Tayeh a data validator, for validation in accordance with NYSDEC BCP requirements.

Detection limits set by New York State Department of Environmental Conservation (NYSDEC) ASP will be used for all sample analyses unless otherwise noted. If NYSDEC-ASP-dictated detection limits prove insufficient to assess project goals (i.e., comparison to drinking water standards or attainment of Applicable or Relevant and Appropriate Requirements [ARARs]), then ASP Special Analytical Services (SAS) or other appropriate methods will be utilized.

The quality assurance/quality control (QA/QC) objectives for all measurement data include completeness, representativeness, comparability, precision, and accuracy.

#### 3.1 COMPLETENESS

The analyses performed must be appropriate and inclusive. The parameters selected for analysis are chosen to meet the objectives of the study.



Completeness of the analyses will be assessed by comparing the number of parameters intended to be analyzed with the number of parameters successfully determined and validated. Data must meet QC acceptance criteria for 100 percent or more of requested determinations.

#### 3.2 REPRESENTATIVENESS

Samples must be taken of the population and, where appropriate, the population will be characterized statistically to express the degree to which the data accurately and precisely represent a characteristic of a population, parameter variations at a sampling point, a process, or environmental condition.

Non-dedicated sampling devices will be cleaned between sampling points by washing and rinsing with pesticide-grade methanol, followed by a thorough rinse with distilled water. Specific cleaning techniques are described in the Field Sampling Procedure. Two types of blank samples will accompany each sample set where Target Compound List (TCL) volatiles are to be analyzed (water matrix only). A trip blank, consisting of a 40 ml VOA vial of organic-free water prepared by the laboratory, will accompany each set of sample bottles from the laboratory to the field and back. This bottle will remain sealed throughout the shipment and sampling process. This blank will be analyzed for TCL volatile organic compounds (VOCs) along with the groundwater samples to ensure that contamination with TCL volatile compounds has not occurred during the bottle preparation, shipment and sampling phase of the project. In order to check for contaminant carryover when non-dedicated sampling equipment is used, a rinsate blank will be submitted to the laboratory. This blank will also be analyzed for TCL volatile organic compounds. The TCL compounds are identified in the United States Environmental Protection Agency (USEPA) Contract Laboratory Program dated 10/2016 or as periodically updated.

The analysis results obtained from the determination of identical parameters in field duplicate samples can be used to further assess the representativeness of the sample data.

#### 3.3 COMPARABILITY

Consistency in the acquisition, preparation, handling and analysis of samples is necessary in order for the results to be compared where appropriate. Additionally, the results obtained from analyses of the samples will be compared with the results obtained in previous studies, if available.

To ensure the comparability of analytical results with those obtained in previous or future testing, all samples will be analyzed by NYSDEC-approved methods. The NYSDEC-ASP mandated holding times for various analyses will be strictly adhered to.

#### 3.4 PRECISION AND ACCURACY

The validity of the data produced will be assessed for precision and accuracy. Analytical methods which will be used include gas chromatography/mass spectrometry (GC/MS), gas chromatography, colorimetry, atomic spectroscopy, gravimetric and titrametric techniques. The following outlines the procedures for evaluating precision and accuracy, routine monitoring procedures, and corrective actions to maintain analytical quality control. All data evaluations will



be consistent with NYSDEC-ASP procedures. Data will be 100 percent compliant with NYSDEC-ASP requirements. Matrix spike and matrix spike duplicates will be collected to confirm accuracy and precision at a rate of one (1) per 20 soil and/or groundwater samples taken.

The number of duplicate, spiked and blank samples analyzed will be a minimum of one (1) duplicate for every 20 samples per each medium of groundwater and soil. The inclusion and frequency of analysis of field blanks will be on the order of one (1) per every 20 samples (soil). For the aqueous matrix field blanks will be collected at a frequency of one (1) per day. Samples to be analyzed for volatile organic compounds will be accompanied by a trip blank for each shipment and field blanks (water matrix) or field blanks (soil). An equipment blank for per- and polyfluoroalkyl substances (PFAS) will be collected once per day per matrix, regardless of whether equipment being used is disposable, at a frequency of one (1) per 20 samples taken for both soil and groundwater.

Quality assurance audit samples will be prepared and submitted by the laboratory QA manager for each analytical procedure used. The degree of accuracy and the recovery of analyte to be expected for the analysis of QA samples and spiked samples is dependent upon the matrix, method of analysis, and compound or element being determined. The concentration of the analyte relative to the detection limit is also a major factor in determining the accuracy of the measurement. The lower end of the analytical range for most analyses is generally accepted to be five (5) times the detection limit. At or above this level, the determination and spike recoveries for metals in water samples will be expected to range from 75 to 125 percent. The recovery of organic surrogate compounds and matrix spiking compounds determined by GC/MS will be compared to the guidelines for recovery of individual compounds as established by the United States Environmental Protection Agency Contract Laboratory Program dated 7/85 or as periodically updated.

The quality of results obtained for inorganic ion and demand parameters will be assessed by comparison of QC data with laboratory control charts for each test.

#### 4.0 SAMPLING PROCEDURES

#### 4.1 SAMPLING PROGRAM

The sampling program for this project will include soil, groundwater and soil vapor. Soil samples will be collected from split spoon sampling or macrocore devices retrieved from soil borings. Groundwater samples will be collected from groundwater monitoring wells using low flow purging techniques. A description of this method is shown on **Table 4.1**. Soil vapor samples will be collected from vapor points screened in the vadose zone using Summa Canisters. A summary of the sample containers, bottle types, preservatives and holding times is shown on **Table 4.2**.

#### 4.1.1 DRILLING/SAMPLING PROCEDURES

Soil and groundwater samples will be collected by means of a soil boring program. Soil borings shall be completed using the hollow stem auger drilling methods, direct push methods, or rotary drilling methods, whichever methods are determined to be best suited to site conditions by the SESI project manager and SESI field team leader.



Soil samples will be collected from soil borings and analyzed in accordance with the NYSDECapproved Work Plan. Monitoring wells for groundwater sample collection will be installed in select completed soil borings. Either hollow stem auger (HSA) or direct push drilling methods may be utilized for monitoring well completion.

Soil samples shall be collected continuously during drilling so that a complete soil profile is examined and described by the SESI field geologist. The sampling method employed shall be ASTM D-1586/Split Barrel Sampling using a standard 2-foot long, 2-inch outside diameter split-spoon sampler with a 140-pound hammer, in cases where HSA methods are used. Upon retrieval of the sampling barrel, the collected sample shall be placed in glass jars and labeled, stored on site (on ice in a cooler if necessary), and transmitted to the appropriate testing laboratory or storage facility. Chain-of-custody procedures will be practiced following Section 15, EPA-600/4-82-029, Handbook for Sampling and Sample Preservation of Water and Waste Waters.

A geologist or engineer will be on Site during the drilling operations to fully describe each soil sample, following the New York State Soil Description Procedure, and to retain representative portions of each sample.

The drilling contractor will be responsible for obtaining accurate and representative samples, informing the geologist of changes in drilling pressure, keeping a separate general log of soils encountered including blow counts [i.e., the number of blows from a soil sampling drive weight (140 pounds)] required to drive the split-spoon sampler in 6-inch increments and installing monitoring wells to levels directed by the supervising geologist following specifications further outlined in this protocol.

#### 4.1.2 MONITORING WELL COMPLETION

Monitoring wells will be constructed of 0.010-inch slot size PVC well screen and riser casing. Other materials utilized for completion will be washed silica sand (Q-Rock No. 4 or approved equivalent) bentonite grout, Portland cement, and a protective steel locking well casing and cap with locks. The depth of the wells will be determined based on the depth to water, type of contaminant and field conditions encountered.

The monitoring well installation method for wells installed within unconsolidated sediments shall be to place the screen and riser assembly into the casing once the screen interval has been selected. At that time, a washed silica sand pack will be placed around the well screen if required to prevent screen plugging. If a sand pack is not warranted, the auger string will be pulled back to allow the native aquifer material to collapse 2 to 3 feet above the top of the screen. Bentonite pellets will then be added to the annulus between the casing and the inside auger to insure proper sealing. Cement/bentonite grout will continue to be added during the extraction of the augers until the entire aquifer thickness has been sufficiently sealed off from horizontal and/or vertical flow above the screened interval. During placement of sand and bentonite pellets, frequent measurements will be made to check the height of the sand pack and thickness of bentonite layers by a weighted drop tape measure.

A bolt-down protective curb box will be installed, flush with the ground, or steel "stick-up" protective casing and secured by a Portland cement seal. The cement seal shall extend laterally at least 1 foot in all directions from the protective casing and shall slope gently away to drain water away from the well.



#### 4.1.3 WELL DEVELOPMENT

All monitoring wells will be developed or cleared of all fine-grained materials and sediments that have settled in or around the well during installation so that the screen is transmitting representative portions of the groundwater. The development will be by one (1) of two (2) methods, pumping or bailing groundwater from the well until it yields relatively sediment-free water.

A decontaminated pump or bailer will be used and subsequently decontaminated after each use following procedures outlined in the Decontamination Protocol. Pumping or bailing will cease when the turbidity falls below 50 NTUs or until specific conductivity, pH, and temperature are stable (i.e., consecutive readings are within 10 percent with no overall upward or downward trends in measurements). Well development water will be disposed of on the ground surface at each well location.

#### 4.1.4 DECONTAMINATION

All drilling equipment and associated tools including augers, drill rods, sampling equipment, wrenches and any other equipment or tools that have come in contact with contaminated materials will be decontaminated before any drilling on Site begins, between each well, and prior to removing any equipment from the Site. The preferred decontamination procedure will be to scrape the equipment from any residual soils and then rinse with water and Alconox®. Every effort will be made to minimize the generation of contaminated water. Any contaminated water generated will be drummed. The contaminated water drums will be disposed of at an appropriate facility after approval and sampling in accordance with the specific facility requirements.

#### 4.1.5 PFAS SAMPLING CONSIDERATIONS

This section contains the materials limitations for Per- and polyfluoroalkyl substances sampling in accordance with the Draft NYSDEC Sampling, Analysis, and Assessment of Per- and Polyfluoralkyl Substances (April 2023).

The groundwater samples will be analyzed for PFAS using Modified USEPA Method 1633. Reporting limits for PFOA and PFOS will not exceed 2 nanograms per liter (ng/L). Category B deliverables and an electronic data deliverable will be completed.

PFAS are very persistent in the environment and in the human body. Due to their presence in a variety of products, persistence in the environment and very low drinking water standards, care must be used when groundwater sampling for PFAS to avoid cross contamination from the sampling equipment and personal protective equipment (PPE).

No fabric softener will be used on clothing to be worn in field. Cosmetics, moisturizers, hand cream, unauthorized sunscreen, insect repellent or other related products will not be used the morning of sampling. The field samplers will wear powder-free nitrile gloves while filling and sealing the sample bottles. The sampling equipment components and sample containers will not come in contact with material that may potentially contain PFAS such as aluminum foil, low density polyethylene (LDPE), glass or polytetrafluoroethylene (PTFE, Teflon<sup>™</sup>) materials



including sample bottle cap liners with a PTFE layer. Clothing that contains PTFE material (including GORE-TEX®) or that have been waterproofed with PFAS materials will be avoided. Food and drink packaging materials will be avoided, as well.

Sampling will be performed using certified PFAS-free sampling materials such as stainless steel, high density polyethylene (HDPE), PVC, silicone, acetate or polypropylene pump and tubing. Rinse water must be laboratory-provided certified PFAS-free distilled or de-ionized water. Standard two step decontamination using Alconox® detergent and clean certified PFAS-free water rinse will be performed for equipment that does come in contact with PFAS materials.

No waterproof field books, plastic clipboards, binders, or spiral hard cover will be used for PFAS containers. No adhesives (i.e. Post-It® Notes), sharpies, or permanent markers will be used for PFAS containers. The PFAS containers will be labeled with ballpoint pens. PFAS samples will be stored in separate cooler filled with regular ice only with no chemical (blue) ice packs.

Pre-cleaned sample bottles with closures, coolers, sample labels and a chain of custody form will be provided by the laboratory.

#### 4.2 GROUNDWATER SAMPLING PROGRAM

#### 4.2.1 WELL EVACUATION

Prior to sampling a monitoring well, the static water level will be recorded. All well data will be recorded on a field sampling record. The wells will be sampled in accordance with the USEPA guidelines for the Low Flow Purging Sampling (LFPS). The purpose of LFPS is to collect groundwater samples from monitoring wells that are representative of ambient groundwater conditions in the aquifer. The LFPS method reduces turbidity which is needed particularly when sampling for metals.

#### 4.2.2 SAMPLING PROCEDURE

The wells will be sampled using the USEPA LFPS technique. A flow rate of 100 ml to 250 ml per minute is used to purge the wells. Drawdown should not exceed 0.3 feet. The pump intake is lowered to the mid-point of the water column or as subsurface features such as bedrock fractures or more permeable zones warrant. At the initiation of low flow purging a water level is recorded as well as field parameters. Field parameters are then monitored every five (5) minutes during low flow purging using a flow through cell. When three (3) consecutive measurements of pH differ by 0.1 units or less, with ORP within 10 mv or less, turbidity varies 10 percent or less, conductivity differs by 3 percent or less and dissolved oxygen by 10 percent or less, sampling may begin. Flow through cells are used so continuous real time readings are made. When the parameters stabilize the flow through cell is disconnected and sample bottles are filled directly from the tubing. Low-flow sampling procedures are summarized on **Table 4.1**.

#### 4.3 SOIL VAPOR SAMPLING

Soil vapor sampling will be conducted in accordance with NYSDOH Guidance for Evaluating Soil Vapor Intrusion in New York State (October 2006 and the subsequent May 2017 updates to the Soil Vapor/Indoor Air Decision Matrices). Soil vapor samples will be collected in the vadose zone



from shallow (five [5] feet) vapor points. Each vapor point will be installed in a shallow boring drilled either by hand-operated equipment (e.g. hand auger or percussion hammer drill), or by a small truck-mounted drill rig. Drilling equipment used shall be based on soil conditions, and the method that provides the most practical approach.

Each vapor point will consist of an inert sampling tube (polyethylene, stainless steel, or Teflon®) with a six (6)-inch screened section at the bottom through which soil vapors can be sampled. The screen slot size will be 0.0075 inches. A sampling zone will be created around the screened section by backfilling with one (1) to two (2) feet of porous coarse sand or glass beads, and at least three (3) feet of bentonite will be placed above the porous sampling zone to form a seal from the surface. Native clean soil will be packed around the remaining annulus to the ground surface.

The regulator will be set to collect a soil vapor sample at a flow rate of less than 0.2 liters per minute. After the summa canister is filled, the valve will be closed.

Each canister will be listed according to a specific sample I.D. on a chain of custody form. Sample canisters will be delivered to the laboratory within 24 hours and analyzed for VOCs by method TO-15. The detection limit for VOCs will be 1  $\mu$ g/m<sup>3</sup> or less

The soil vapor sampling effort will include the use of inert helium tracer gas to verify that the soil vapor samples are not diluted by ambient air. The atmosphere around the sampling tube will be enriched with the tracer gas, and the soil vapor sample will be collected in the presence of the enriched tracer atmosphere. This will be accomplished by placing an inverted plastic pail over the sampling point and filling the pail with the tracer gas via a small tube penetrating the site of the pail. Refer to NYSDOH Guidance for Evaluating Indoor Air Intrusion in New York State (October 2006).

#### 4.4 SAMPLE PRESERVATION AND SHIPMENT

Since all bottles will contain the necessary preservatives as shown in **Table 4.2**, they need only be filled. The 40 ml VOA vials must be filled brim full with no air bubbles. The other bottles should be filled to within about one (1) inch from the top.

The bottles will be sent from the laboratory in coolers which will be organized on a per site basis. Following sample collection, the bottles should be placed on ice in the shipping cooler. The samples will be cooled to 4°C, but not frozen.

Final packing and shipment of coolers will be performed in accordance with guidelines outlined in the ASP.

#### 5.0 SAMPLE CUSTODY

The program for sample custody and sample transfer is in compliance with the NYSDEC-ASP, as periodically updated. If samples may be needed for legal purposes, chain-of-custody procedures, as defined by NEIC Policies and Procedures (USEPA-330/9-78-001-R, Revised June 1988) will be used. Sample chain-of-custody is initiated by the laboratory with selection and preparation of the sample containers. To reduce the chance for error, the number of personnel handling the samples should be minimized.



## 5.1 FIELD SAMPLE CUSTODY

A chain-of-custody record accompanies the samples from initial sample container selection and preparation at the laboratory, shipment to the field for sample containment and preservation, and return to the laboratory. Two (2) copies of this record follow the samples to the laboratory. The laboratory maintains one (1) file copy and the completed original is returned to the site inspection team. Individual sample containers provided by the laboratory are used for shipping samples. The shipping containers are insulated and ice is used to maintain samples at approximately 4°C until samples are returned and in the custody of the laboratory. All sample bottles within each shipping container are individually labeled and controlled. Samples are to be shipped to the laboratory within 24 to 48 hours of the day of collection depending on parameter holding times

Each sample shipping container is assigned a unique identification number by the laboratory. This number is recorded on the chain-of-custody record and is marked with indelible ink on the outside of the shipping container. The field sampler will indicate the sample designation/location number in the space provided on the appropriate chain-of-custody form for each sample collected. The shipping container is closed and a seal provided by the laboratory is affixed to the latch. This seal must be broken to open the container, and this indicates possible tampering if the seal is broken before receipt at the laboratory. The laboratory will contact the site investigation team leader and the sample will not be analyzed if tampering is apparent.

## 5.2 LABORATORY SAMPLE CUSTODY

The site investigation team leader or Project Quality Assurance Officer notifies the laboratory of upcoming field sampling activities and the subsequent transfer of samples to the laboratory. This notification will include information concerning the number and type of samples to be shipped as well as the anticipated date of arrival.

The laboratory sample program meets the following criteria:

- The laboratory has designated a sample custodian who is responsible for maintaining custody of the samples and for maintaining all associated records documenting that custody.
- Upon receipt of the samples, the custodian will check the original chain-of-custody documents and compare them with the labeled contents of each sample container for correctness and traceability. The sample custodian signs the chain-of-custody record and records the date and time received.
- Care is exercised to annotate any labeling or descriptive errors. In the event of discrepant documentation, the laboratory will immediately contact the site investigation team leader as part of the corrective action process. A qualitative assessment of each sample container is performed to note any anomalies, such as broken or leaking bottles.

This assessment is recorded as part of the incoming chain-of-custody procedure:



- 1. The samples are stored in a secured area at a temperature of approximately 4°C until analyses are to commence.
- 2. A laboratory chain-of-custody record accompanies the sample or sample fraction through final analysis for control.
- 3. A copy of the chain-of-custody form will accompany the laboratory report and will become a permanent part of the project records.

#### 5.3 FINAL EVIDENCE FILES

Final evidence files include all originals of laboratory reports and are maintained under documented control in a secure area.

A sample or an evidence file is under custody if:

- It is in your possession; it is in your view, after being in your possession.
- It was in your possession and you placed it in a secure area.
- It is in a designated secure area.

#### 6.0 CALIBRATION PROCEDURES

Instruments and equipment used to gather, generate or measure environmental data will be calibrated with sufficient frequency and in such a manner that accuracy and reproducibility of results are consistent with the appropriate manufacturer's specifications or project specific requirements. The procedures for instrument calibration, calibration verification, and the frequency of calibrations are described in the ASP. The calibration of instruments used for the determination of metals will be as described in the appropriate CLP standard operating procedures.

Calibration of other instruments required for measurements associated with these analyses will be in accordance with the manufacturer's recommendations and the standard operating procedures of the laboratory.

#### 7.0 ANALYTICAL PROCEDURES

Analytical procedures shall conform to the most recent revision of the NYSDEC-ASP (June 2005) and are summarized on **Tables 7.1** and **7.2**. In the absence of USEPA or NYSDEC guidelines, appropriate procedures shall be submitted for approval by NYSDEC prior to use.

The procedures for the sample preparation and analysis for organic compounds are as specified in the NYSDEC-ASP. Analytical cleanups are mandatory where matrix interferences are noted. No sample shall be diluted any more than a factor of five. The sample shall be either re-extracted, re-sonicated, re-stream distilled, etc. or be subjected to any one analytical cleanup noted in



SW846 or a combination thereof. The analytical laboratory shall expend such effort and discretion to demonstrate good laboratory practice and demonstrate an attempt to best achieve the method detection limit.

## 7.1 VOLATILE ORGANICS

For the analysis of water samples for Target Compound List VOCs, no sample preparation is required. The analytical procedure for volatiles is detailed in NYSDEC-ASP (Volume I, Section D-I). A measured portion of the sample is placed in the purge and trap apparatus and the sample analysis is performed by gas chromatography/mass spectrometry for the first round. USEPA Method 8260 will be used, plus tentatively identified compounds (TICs). USEPA Methods 8010 or 8020 (gas chromatography with different detectors) will be used if subsequent rounds with lower limits of detection are warranted.

#### 7.2 SEMI-VOLATILE ORGANIC COMPUNDS

The extraction and analytical procedures used for preparation of water, soil and sediment samples for the analysis of the TCL semi-volatile organic compounds are described in NYSDEC-ASP Volume I, Section D-III. USEPA Method 8270 will be used, plus TICs.

Instrument calibration, compound identification, and quantitation are performed as described in Section 6 of this document and in the NYSDEC-ASP.

#### 7.3 PESTICDE AND PCB COMPOUNDS

The sample preservation procedures for gas chromatography for pesticides and polychlorinated biphenyls (PCBs) will be as described in the NYSDEC-ASP methods (Section D-IV). The analysis of standard mixes, blanks and spiked samples will be performed at the prescribed frequency with adherence to the 72-hour requirement described in the method.

#### 7.4 METALS

Water, soil and waste samples will be analyzed for the metals listed in Table 7.1. The detection limits for these metals are as specified in the NYSDEC-ASP, Section D-V. The instrument detection limits will be determined using calibration standards and procedures specified in the NYSDEC-ASP. The detection limits for individual samples may be higher due to the sample matrix. The procedures for these analyses will be as described in the NYSDEC-ASP.

The analyses for metals will be performed by atomic absorption spectroscopy (AAS) or inductively-coupled plasma emission spectroscopy (ICPES), as specified in the ASP with regard to AAS flame analysis.

## 7.5 PER- AND POLYFLUOROALKYL SUBSTANCES

The NYSDEC has developed a list of 40 PFAS Analytes List on Table 7.2 for remedial programs. These are:



- Perfluorobutanesulfonic acid
- Perfluoropentanesulfonic acid
- Perfluorohexanesulfonic acid
- Perfluoroheptanesulfonic acid
- Perfluorooctanesulfonic acid
- Perfluorononanesulfonic acid
- Perfluorodecanesulfonic acid
- Perfluorododecanesulfonic acid
- Perfluorobutanoic acid
- Perfluoropentanoic acid
- Perfluorohexanoic acid
- Perfluoroheptanoic acid
- Perfluorooctanoic acid
- Perfluorononanoic acid
- Perfluorodecanoic acid
- Perfluoroundecanoic acid
- Perfluorododecanoic acid
- Perfluorotridecanoic acid
- Perfluorotetradecanoic acid
- Perfluorohexadecanoic acid
- Hexafluoropropylene oxide dimer acid
- 4,8-Dioxa-3H-perfluorononanoic acid
- Perfluoro-3-methoxypropanoic acid
- Perfluoro-4-methoxybutanoic acid
- Nonafluoro-3,6-dioxaheptanoic acid
- 4:2 Fluorotelomer sulfonic acid
- 6:2 Fluorotelomer sulfonate
- 8:2 Fluorotelomer sulfonate
- 3:3 Fluorotelomer carboxylic acid
- 5:3 Fluorotelomer carboxylic acid



- 7:3 Fluorotelomer carboxylic acid
- Perfluroroctane sulfonamide
- N-methylperfluorooctane sulfonamide
- N-ethylperfluorooctane sulfonamide
- N-methyl perfluorooctanesulfonamidoacetic acid
- N-ethyl perfluorooctanesulfonamidoacetic acid
- N-methylperfluorooctane sulfonamidoethanol
- N-ethylperfluorooctane sulfonamidoethanol
- 9-Chlorohexadecafluoro-3-oxanonane-1-sulfonic acid (F-53B Major)
- 11-Chloroeicosafluoro-3-oxaundecane-1-sulfonic acid (F-53B Minor)
- Perfluoro(2-ethoxyethane) sulfonic acid

Currently, ELAP does not offer certification for PFAS compounds in matrices other than finished drinking water. Per the NYSDEC July 2023 memo on emergent contaminant sampling, the analytical procedure for soil and groundwater sampling of PFAS is Modified EPA Method 1633. The reporting limit for PFAS in soil samples is 0.5 ug/kg. Reporting limits for perfluorooctanoic acid (PFOA) and perfluorooctanesulfonic acid (PFOS) in groundwater should not exceed 2 ng/L.

#### 7.6 SITE SPECIFICITY OF ANALYSES

Work plans prepared for remedial actions for sites contain recommendations for the chemical parameters to be determined for each site. Thus, some or all of the referenced methods will apply to the analysis of samples collected at the individual waste sites. Analyses of TCL analytes will be performed on all samples.

To ensure that the field sampling and laboratory analytical practices are acceptable, the data associated with the samples will be validated by a third party (in accordance with requirements of DER-10). The validation approach and results will be presented in a data usability summary report (DUSR) to be included in the Report.

TABLES

## TABLE 4.1--SAMPLING PROCEDURE FOR MONITORING WELLS USING LOW-STESS (LOW-FLOW) METHODS

Step	Description	Details
1	Record initial static water level.	<b>Device:</b> electric contact probe accurate to the nearest 0.1 foot.
2	Lower sampling device into well. Slowly lower the pump, safety cable, tubing and electrical lines into the well to the depth specified for that well.	Pump intake must be no less than 2 feet from the bottom of the well to prevent disturbance and resuspension of sediments which may be at the bottom of the well.
3	Measure water level again: Before starting the pump, measure the water level again with the pump in the well. Leave the water level measuring device in the well.	
4	Purge Well	Start pumping the well at 200 to 500 milliliters per minute (ml/min). The water level should be monitored approximately every five minutes. Ideally, a steady flow rate should be maintained that results in a stabilized water level (drawdown of 0.3 ft or less). Pumping rates should, if needed, be reduced to the minimum capabilities of the pump to ensure stabilization of the water level. As noted above, care should be taken to maintain pump suction and to avoid entrainment of air in the tubing.
5	Record each adjustment made to the pumping rate and the water level measured immediately after each adjustment.	
6	Monitor Indicator Parameters	<ol> <li>During purging of the well, monitor and record the field indicator parameters (turbidity, temperature, specific conductance, pH, Eh, and DO) approximately every five minutes. The well is considered stabilized and ready for sample collection when the indicator</li> </ol>

Step	Description	Details		
		parameters have stabilized for three consecutive readings as follows (Puls and Barcelona, 1996):		
		<ul> <li>a. 0.1 for pH</li> <li>b. 3% for specific conductance (conductivity)</li> <li>c. 10 mv for redox potential</li> <li>d. 10% for DO and turbidity</li> </ul>		
7	The pump must not be removed from the well between purging and sampling.	Dissolved oxygen and turbidity usually require the longest time to achieve stabilization.		
8	Collect Samples	Collect samples at a flow rate between 100 and 250 ml/min and such that drawdown of the water level within the well does not exceed the maximum allowable drawdown of 0.3 ft. VOC samples must be collected first and directly into sample containers. All sample containers should be filled with minimal turbulence by allowing the ground water to flow from the tubing gently down the inside of the container.		
9	Ground water samples to be analyzed for volatile organic compounds (VOCs) require pH adjustment. The appropriate EPA Program Guidance should be consulted to determine whether pH adjustment is necessary.	If pH adjustment is necessary for VOC sample preservation, the amount of acid to be added to each sample vial prior to sampling should be determined, drop by drop, on a separate and equal volume of water (e.g., 40 ml). Groundwater purged from the well prior to sampling can be used for this purpose.		

Step	Description	Details
10	Remove Pump and Tubing	After collection of the samples, the tubing, unless permanently installed, must be properly discarded or dedicated to the well for resampling by hanging the tubing inside the well.
11	Measure and record well depth.	
12	Close and lock the well.	
13	Samples are capped, labeled and placed in laboratory coolers with ice packs or bagged ice.	
14	All equipment is cleaned with successive rinses of pesticide- grade methanol and distilled water.	Dedicated line is disposed of or left at well site.
15	Equipment/wash blanks are collected when non-dedicated sampling equipment is used.	
16	Chain-of-custody forms are completed in triplicate.	The original and one carbon copy are put into a zip-lock bag and placed into the cooler. The original will be returned following sample analysis. A second carbon copy is kept on file.
17	Cooler is sealed with strapping tape and chain-of-custody seals to assure integrity and to prevent tampering of sample.	

## TABLE 4.2--SAMPLE CONTAINERIZATION

PARAMETER & ANALYTICAL METHOD	NO.	BOTTLE TYPE	PRESERVATIVE <sup>(1)</sup>	HOLDING TIME	
Aqueous Samples					
VOCs – USEPA 8260C	3	40 mL, glass vial with septum cap	Hydrochloric Acid to pH <2 Ice to 4°C	14 days	
SVOCs (BNAs) and 1,4-Dioxane – USEPA 8270 SIM	2	1-liter amber glass bottle	Ice to 4°C	7 days (until extraction) 40 days (extracted)	
Pesticides – USEPA 8081B	2	1-liter amber glass bottle	Ice to 4°C	7 days (until extraction) 40 days (extracted)	
PCBs – USEPA 8082A	2	1-liter amber glass bottle	Ice to 4°C	7 days (until extraction) 40 days (extracted)	
Metals <sup>(2)</sup>	1	1-liter, plastic bottle	Nitric acid to pH <2 NaOH for cyanide Ice to 4°C	180 days Cyanide: 14 days Mercury: 28 days	
Cyanide – USEPA 9010C/9012B	1	1-liter, plastic	Sodium Hydroxide to pH >12 Ice to 4°C	14 days	
PFAS Compounds – USEPA Modified Method 537	2	500 ml HDPE or Polypropylen e with non- Teflon lid	None	14 days	
Soil, Sediment, Solid Waste Samples:					
VOCs – USEPA 8260C	3	5-gram EnCore samplers	Chilled to 0 - 6°C	14 days	
SVOCs (BNAs) and 1,4-Dioxane – USEPA 8270D SIM if RL cannot be reached	1	4-oz. glass jar with Teflon lid	Chilled to 0 - 6°C	14 days (until extraction, 40 days extracted)	

PARAMETER & ANALYTICAL METHOD	NO.	BOTTLE TYPE	PRESERVATIVE <sup>(1)</sup>	HOLDING TIME	
Pesticides – USEPA 8081B	1	4-oz. glass jar with Teflon lid	Chilled to 0 - 6°C	14 days (until extraction) 40 days (extracted)	
PCBs – USEPA 8082A	1	4-oz. glass jar with Teflon lid	Chilled to 0 - 6°C	None	
Metals <sup>(3)</sup>	1	4-oz. glass jar with Teflon lid	Chilled to 0 - 6°C	180 days Cyanide: 14 days Mercury: 28 days	
PFAS Compounds – USEPA Modified Method 1633	2	500 ml HDPE or Polypropylen e with non- Teflon lid	None	28 days	
Soil Vapor / Indoor Air Samples:					
VOCs – USEPA TO-15	1	Summa Canister	None	30 days	

(1) All samples will be preserved with ice during collection and shipment.

(2) Metals refers to the 24 metals and cyanide in the Target Compound List (NYSDEC-CLP 11/87). Metals will be analyzed by Method 6020B, 7470A for mercury, and 9010C/9012B for cyanide

(3) Metals refers to the 24 metals and cyanide in the Target Compound List (NYSDEC-CLP 11/87). Metals will be analyzed by Method 6010D, 7471B for mercury, and 9010C/9012B for cyanide

(4) A complete list of compounds is provided on Table 7.1.

# Table 7.1 PFAS Compound List and Reporting and Method Detection Limits for Soil and Groundwater

Met by	Method: EPA 1633 by LC-MS/MS					
	PFAS	Reporting Limit — Groundwater (ng/l)	Method Detection Limit — Groundwater (ng/l)			
1	Perfluorobutanesulfonic acid (PFBS)	1.6	0.245			
2	Perfluoropentanesulfonic acid (PFPeS)	1.6	0.204			
3	Perfluorohexanesulfonic acid (PFHxS)	1.6	0.217			
4	Perfluoroheptanesulfonic acid (PFHpS)	1.6	0.137			
5	Perfluorooctanesulfonic acid (PFOS)	1.6	0.327			
6	Perfluorononanesulfonic acid (PFNS)	1.6	0.303			
7	Perfluorodecanesulfonic acid (PFDS)	1.6	0.334			
8	Perfluorododecanesulfonic acid (PFDoS)	1.6	0.179			
9	Perfluorobutanoic acid (PFBA)	6.4	0.330			
10	Perfluoropentanoic acid (PFPeA)	3.2	0.196			
11	Perfluorohexanoic acid (PFHxA)	1.6	0.318			
12	Perfluoroheptanoic acid (PFHpA)	1.6	0.221			
13	Perfluorooctanoic acid (PFOA)	1.6	0.302			
14	Perfluorononanoic acid (PFNA)	1.6	0.221			
15	Perfluorodecanoic acid (PFDA)	1.6	0.333			
16	Perfluoroundecanoic acid (PFUnA)	1.6	0.264			
17	Perfluorododecanoic acid (PFDoA)	1.6	0.379			
18	Perfluorotridecanoic acid (PFTrDA)	1.6	0.238			
19	Perfluorotetradecanoic acid (PFTeDA)	1.6	0.264			
20	Hexafluoropropylene oxide dimer acid (HFPO-DA)	6.4	0.406			

Met by	Method: EPA 1633 by LC-MS/MS					
21	4,8-Dioxa-3H-perfluorononanoic acid (ADONA)	6.4	0.779			
22	Perfluoro-3-methoxypropanoic acid (PFMPA)	3.2	0.177			
23	Perfluoro-4-methoxybutanoic acid (PFMBA)	3.2	0.117			
24	Nonafluoro-3,6-dioxaheptanoic acid (NFDHA)	3.2	1.384			
25	4:2 Fluorotelomer sulfonic acid (4:2-FTS)	6.4	2.281			
26	6:2 Fluorotelomer sulfonic acid (6:2-FTS)	6.4	3.973			
27	8:2 Fluorotelomer sulfonic acid (8:2-FTS)	6.4	1.566			
28	3:3 Fluorotelomer carboxylic acid (3:3 FTCA)	8.0	0.721			
29	5:3 Fluorotelomer carboxylic acid (5:3 FTCA)	40	5.066			
30	7:3 Fluorotelomer carboxylic acid (7:3 FTCA)	40	5.942			
31	Perfluorooctane sulfonamide (PFOSA)	1.6	0.227			
32	N-methylperfluorooctane sulfonamide (NMeFOSA)	1.6	0.196			
33	N-ethylperfluorooctane sulfonamide (NEtFOSA)	1.6	0.585			
34	N-methylperfluorooctane sulfonamidoacetic acid (N-MeFOSAA)	1.6	0.586			
35	N-ethylperfluorooctane sulfonamidoacetic acid (N-EtFOSAA)	1.6	0.324			
36	N-methylperfluorooctane sulfonamidoethanol (NMeFOSE)	16	1.191			
37	N-ethylperfluorooctane sulfonamidoethanol (NEtFOSE)	16	1.022			
38	9-Chlorohexadecafluoro-3-oxanonane-1-sulfonic acid (F- 53B Major) (9CL-PF3ONS)	6.4	0.871			
39	11-Chloroeicosafluoro-3-oxaundecane-1-sulfonic acid (F-53B Minor) (11CL-PF3OUDS)	6.4	0.819			
40	Perfluoro(2-ethoxyethane) sulfonic acid (PFEESA)	3.2	0.137			
41	Perfluorohexadecanoic acid (PFHxDA) <sup>1</sup>	~	~			
	1,4-dioxane					

Method: EPA 1633 by LC-MS/MS				
	PFAS	Reporting Limit — Soil (ng/g)	Method Detection Limit — Soil (ng/g)	
1	Perfluorobutanesulfonic acid (PFBS)	0.2	0.014	
2	Perfluoropentanesulfonic acid (PFPeS)	0.2	0.015	
3	Perfluorohexanesulfonic acid (PFHxS)	0.2	0.018	
4	Perfluoroheptanesulfonic acid (PFHpS)	0.2	0.057	
5	Perfluorooctanesulfonic acid (PFOS)	0.2	0.067	
6	Perfluorononanesulfonic acid (PFNS)	0.2	0.046	
7	Perfluorodecanesulfonic acid (PFDS)	0.2	0.040	
8	Perfluorododecanesulfonic acid (PFDoS)	0.2	0.038	
9	Perfluorobutanoic acid (PFBA)	0.8	0.401	
10	Perfluoropentanoic acid (PFPeA)	0.4	0.021	
11	Perfluorohexanoic acid (PFHxA)	0.2	0.020	
12	Perfluoroheptanoic acid (PFHpA)	0.2	0.029	
13	Perfluorooctanoic acid (PFOA)	0.2	0.037	
14	Perfluorononanoic acid (PFNA)	0.2	0.086	
15	Perfluorodecanoic acid (PFDA)	0.2	0.031	
16	Perfluoroundecanoic acid (PFUnA)	0.2	0.033	
17	Perfluorododecanoic acid (PFDoA)	0.2	0.059	
18	Perfluorotridecanoic acid (PFTrDA)	0.2	0.038	
19	Perfluorotetradecanoic acid (PFTeDA)	0.2	0.032	
20	Hexafluoropropylene oxide dimer acid (HFPO-DA)	0.8	0.136	
21	4,8-Dioxa-3H-perfluorononanoic acid (ADONA)	0.8	0.057	

Method: EPA 1633 by LC-MS/MS				
22	Perfluoro-3-methoxypropanoic acid (PFMPA)	0.4	0.033	
23	Perfluoro-4-methoxybutanoic acid (PFMBA)	0.4	0.029	
24	Nonafluoro-3,6-dioxaheptanoic acid (NFDHA)	0.4	0.084	
25	4:2 Fluorotelomer sulfonic acid (4:2-FTS)	0.8	0.282	
26	6:2 Fluorotelomer sulfonic acid (6:2-FTS)	0.8	0.116	
27	8:2 Fluorotelomer sulfonic acid (8:2-FTS)	0.8	0.225	
28	3:3 Fluorotelomer carboxylic acid (3:3 FTCA)	1.0	0.060	
29	5:3 Fluorotelomer carboxylic acid (5:3 FTCA)	5.0	0.363	
30	7:3 Fluorotelomer carboxylic acid (7:3 FTCA)	5.0	0.308	
31	Perfluorooctane sulfonamide (PFOSA)	0.2	0.068	
32	N-methylperfluorooctane sulfonamide (NMeFOSA)	0.2	0.049	
33	N-ethylperfluorooctane sulfonamide (NEtFOSA)	0.2	0.038	
34	N-methylperfluorooctane sulfonamidoacetic acid (N-MeFOSAA)	0.2	0.030	
35	N-ethylperfluorooctane sulfonamidoacetic acid (N-EtFOSAA)	0.2	0.044	
36	N-methylperfluorooctane sulfonamidoethanol (NMeFOSE)	2.0	0.203	
37	N-ethylperfluorooctane sulfonamidoethanol (NEtFOSE)	2.0	0.247	
38	9-Chlorohexadecafluoro-3-oxanonane-1-sulfonic acid (F-53B Major) (9CL-PF3ONS)	0.8	0.038	
39	11-Chloroeicosafluoro-3-oxaundecane-1-sulfonic acid (F-53B Minor) (11CL-PF3OUdS)	0.8	0.071	
40	Perfluoro(2-ethoxyethane) sulfonic acid (PFEESA)	0.4	0.018	
41	Perfluorohexadecanoic acid (PFHxDA) <sup>1</sup>	~	~	

Source: EPA Analysis of Per- and Polyfluoroalkyl Substances (PFAS) in Aqueous, Solid, Biosolids, and Tissue Samples by LC-MS/MS, Second Draft Method 1633, November 2022

Data for this table are derived from the single-laboratory validation study and are only provided as examples for this draft method. The data will be updated to reflect the interlaboratory study results in a subsequent revision. Therefore, these criteria will change after interlaboratory validation.

<sup>1</sup> This compound was not listed in the EPA Method 1633 2<sup>nd</sup> draft and currently no known values exist

# **Appendix B:**

# **Emerging Contaminant Sampling Plan**



Geotechnical Environmental Site Civil

959 Route 46E, Fl 3, Ste 300 Parsippany, NJ 07054 973.808.9050 www.sesi.org

## EMERGING CONTAMINANT SAMPLING PLAN

For:

TMHA Franklin Courts 1-99 Franklin Court Tarrytown, Westchester County, New York

Prepared for: Franklin Courts JV Partners, L.P. SESI Project No: 12345

Date: April 2024



## **Table of Contents**

1.0	PROJECT DESCRIPTION	1
2.0	SOIL SAMPLING PLAN	1
3.0	GROUNDWATER SAMPLING PLAN	3
4.0	SOIL SAMPLE COLLECTION AND HANDLING	3
5.0	SAMPLE SHIPMENT	5



#### 1.0 **PROJECT DESCRIPTION**

This document presents the soil and groundwater emergent contaminant sampling plan for the Remedial Investigation Workplan (RIWP) located at 1-99 Franklin Court (a.k.a 50 White Street), Tarrytown, New York (the "Site"). The 8.35-acre parcel is identified as Block 29, Lot 32 on the Westchester County tax map. The Site has been developed with The Site is currently occupied by the Franklin Courts multifamily property improved with 14 residential buildings and one (1) recreational building. The subject property is bounded to the north by a multi-family residential apartment building at 50 White Street, to the east by Riverview Avenue and residential developments beyond, to the south by residential development along MacArthur Avenue, and to the west by Warehouses and former railroad tracks.

According to a Phase I Environmental Site Assessment prepared by AEI Consultants in June 2021, the Site was submerged by the Hudson River from 1897 to 1931. From 1932 to 1950 the Site appears as vacant land. In 1950 the northern portion of the Site is a coal yard with office, sheds, and an automobile garage. In 1970, the Site is developed with the current Franklin Court Apartments with 14 residential buildings and one (1) recreational building. In addition, AEI observed suspected heating oil vent pipes around the residential buildings 5 and 6 but noted that ground visibility was limited due to snow. AEI's review of Google Earth street imagery identified 20 additional suspected heating oil vent pipes throughout the Site.

#### 2.0 SOIL SAMPLING PLAN

The sampling will be performed in accordance with the New York State Department of Environmental Conservation (NYSDEC) Guidelines for Sampling and Analysis of Per-and Polyfluoroalkyl Substances (PFAS) Under NYSDEC's Part 375 Remedial Programs, dated April 2023. The soil samples will be sent via chain of custody to an ELAP-certified laboratory and analyzed for TCL/TAL+30, 1,4-dioxane and the PFAS compounds listed in Table 1. The soil samples will be analyzed for PFAS using Modified USEPA Method 1633. Reporting limits for each PFAS compound will not exceed 1 microgram per kilogram (ug/kg). NYSDEC will be informed if detection limits on certain PFAS compounds cannot be met by the laboratory. Category B deliverables and an electronic data deliverable will be completed. A DUSR will be prepared by a data validator for all the analyses including PFAS and 1,4-dioxane. The method detection limit (MDL) for 1,4-dioxane will be no higher than 0.1 mg/kg (ppm).


Because PFAS compounds must be analyzed at concentrations in the ug/kg range, precautions must be taken to prevent cross-contamination during sampling events. Field sampling equipment that is used at multiple sites or sampling locations could become highly contaminated with PFAS. Soil sampling at this site will involve the use of non-dedicated equipment, such as a Geoprobe direct push drill rig, which could be a source of cross-contamination. Decontamination procedures outlined in this document will be followed to avoid cross contamination and equipment will be verified as PFAS-free. Special care and consideration will be given to the field sampling equipment when stored and handled outside the site boundaries or between different sample locations.

Items that may be directly in contact with the soil, including spoons, bowls, and direct push equipment, including any split spoon or sampling barrels, have a high likelihood of cross-contamination occurring if the proper decontamination procedures are not followed. These items should be known to be PFAS free. Item that will not directly contact the soil, including field books, Post-It® Notes, aluminum foil, recycled paper towels, binders, or spiral hard cover, can be a source of PFAS contamination. Every effort will be made to ensure these items are PFAS-free.

For the sampling equipment, the following items, materials, and procedures will be used for decontamination:

- Municipal drinking water may be used for decontamination if it is known to be PFAS-free. Commercially available deionized water in an HDPE container may also be used for decontamination.
- Standard two step decontamination using Alconox® detergent and PFAS-free triple water rinse will be performed for the sampling equipment.
- Sampling equipment may be scrubbed with polyethylene or a polyvinyl chloride (PVC) brush to remove particulates.
- The sampling equipment components will not come in contact with material that may potentially contain PFAS such as aluminum foil, low density polyethylene (LDPE), polytetrafluoroethylene (PTFE, Teflon®) or other fluoropolymers.
- Soil sampling equipment will be decontaminated between each sampling point and at the conclusion of the workday. This is to ensure sampling equipment is decontaminated ahead of time for the next sampling event.

Equipment rinsate blanks will be collected daily for the equipment that comes in contact with the soil samples and is decontaminated and reused. If all the sampling materials are disposable, no



field blanks will be collected. Field duplicates will be collected on a frequency of 1/20 samples. One matrix spike and matrix spike duplicate (MS/MSD) will also be collected on a frequency of 1/20 samples. A trip blank will accompany each laboratory shipment which includes analysis for volatile organic compounds.

# 3.0 GROUNDWATER SAMPLING PLAN

The sampling will be performed in accordance with the NYSDEC Guidelines for Sampling and Analysis of PFAS Under NYSDEC's Part 375 Remedial Programs, dated April 2023. The groundwater samples will be sent via chain of custody in a cooler at 4 degrees C to an ELAP-certified laboratory and analyzed for TCL/TAL+30, 1,4-dioxane and the PFAS compounds listed in Table 1. The groundwater samples will be analyzed for PFAS using Modified USEPA Method 1633. Reporting limits for PFOA and PFOS will not exceed 2 nanogram per liter (ng/L). Category B deliverables and an electronic data deliverable will be completed. A DUSR will be prepared by a data validator for all the analyses including PFAS and 1,4-dioxane. The method detection limit (MDL) for 1,4-dioxane will be no higher than  $0.28 \ \mu g/l$  (ppb). In order to get the appropriate detection limit, the lab will run EPA method 8270 in "selective ion monitoring" (SIM) mode for 1.4-dioxane.

PFAS are very persistent in the environment and in the human body. There is evidence that exposure to PFAS can lead to adverse human health effects. EPA established the health advisory levels for PFAS in drinking water at 70 parts per trillion. Due to their presence in a variety of products, persistence in the environment and very low drinking water standards, care must be used when groundwater sampling for PFAS to avoid cross contamination from the sampling equipment and personal protective equipment (PPE). If PFOAs/PFOS/1,4 Dioxane are detected above the Guidance values on-site, additional groundwater samples will be required off-site.

# 4.0 SOIL SAMPLE COLLECTION AND HANDLING

The following considerations will be observed:

• No fabric softener will be used on clothing to be worn by the sampling personnel in the field. Clothing that contains PTFE material (including GORE-TEX®) or that have been waterproofed with PFAS-containing materials will be avoided.



- Cosmetics, moisturizers, hand cream, unauthorized sunscreen, insect repellant or other related products will not be used by the sampling staff on sampling days.
- Food and drink packaging materials such as pre-wrapped food or snacks (i.e. candy bars, microwave popcorn, etc.) will not be used in the sampling and staging areas.
- Sampling will be conducted with powderless nitrile gloves. The gloves will be changed frequently any time there is an opportunity for cross-contamination during sampling, including, but not limited to:
  - a. Immediately prior to sample collection
  - b. Each time sampling equipment is placed in and then removed from soil at a new location
  - c. Handling of any sample, including quality assurance/quality control (QA/QC) samples
  - d. After the handling of any non-dedicated sampling equipment
  - e. After contact with non-decontaminated surfaces
  - f. After decontamination of sampling equipment
  - g. When judged necessary by field personnel
- HDPE or polypropylene sample bottles with Teflon®-free caps, provided by the laboratory will be used. Sample containers will not come in contact with material that may potentially contain PFAS.
- Bottles will only be opened immediately prior to sampling.
- Dust and fibers will be kept out of sample bottles.
- The sample caps will never be placed directly on the ground during sampling. If the sampling staff must set the sample bottle cap down during sample collection and a second member of the sampling crew (wearing a fresh pair of powderless nitrile gloves) is not available, the cap will be set on a clean surface (cotton sheeting, HDPE sheeting, triple rinsed cooler lid, etc.).
- Regular size Sharpie® and thicker markers will be avoided. Fine and Ultra-Fine point Sharpie® markers may be used. Ballpoint pens may be used when labeling sample containers. If ballpoint pens do not write on the sample container labels, preprinted labels from the laboratory may be used.
- Sample bottles, coolers, sample labels and a chain of custody form will be provided by the analytical laboratory.



• PFAS samples will be collected prior to collecting non-PFAS samples.

# 5.0 SAMPLE SHIPMENT

In the absence of a formal USEPA guidance for PFAS sample storage, the documentation in USEPA Method 1633 will be used as a guide for thermal preservation and holding times for soil or other samples. Samples will be chilled during storage and shipment, and will not exceed 50°F (10° C) during the first 48 hours after collection.

The following procedures will be used by SESI for sample shipment:

- Regular ice will be used to cool and maintain the samples at or below 42.8°F (6°C). Chemical or blue ice may be used if it is known to be PFAS-free and the samples can be cooled and maintained at or below 42.8°F (6°C) during collection and through transit to the laboratory.
- The coolers will be periodically checked to ensure samples are well iced and at the proper temperature. Refresh with regular ice if needed. The ice may be double bagged in LDPE resealable storage bags. LDPE may be used if an equipment blank demonstrates the LDPE is PFAS-free.
- Chain of Custody and other forms will be single bagged in LDPE (e.g. Ziploc®) storage bags and taped to the inside of the cooler lid. LDPE may be used if an equipment blank demonstrates the LDPE is PFAS-free.
- The cooler(s) will be taped closed with a custody seal and picked up by a ELAP certified lab within 24 hrs.

# Table 1: PFAS compounds list

- Perfluorobutanesulfonic acid
- Perfluoropentanesulfonic acid
- Perfluorohexanesulfonic acid
- Perfluoroheptanesulfonic acid
- Perfluorooctanesulfonic acid
- Perfluorononanesulfonic acid
- Perfluorodecanesulfonic acid
- Perfluorododecanesulfonic acid



Project 12345 1-99 Franklin Court Tarrytown, New York

- Perfluorobutanoic acid
- Perfluoropentanoic acid
- Perfluorohexanoic acid
- Perfluoroheptanoic acid
- Perfluorooctanoic acid
- Perfluorononanoic acid
- Perfluorodecanoic acid
- Perfluoroundecanoic acid
- Perfluorododecanoic acid
- Perfluorotridecanoic acid
- Perfluorotetradecanoic acid
- Perfluorohexadecanoic acid
- Hexafluoropropylene oxide dimer acid
- 4,8-Dioxa-3H-perfluorononanoic acid
- Perfluoro-3-methoxypropanoic acid
- Perfluoro-4-methoxybutanoic acid
- Nonafluoro-3,6-dioxaheptanoic acid
- 4:2 Fluorotelomer sulfonic acid
- 6:2 Fluorotelomer sulfonate
- 8:2 Fluorotelomer sulfonate
- 3:3 Fluorotelomer carboxylic acid
- 5:3 Fluorotelomer carboxylic acid
- 7:3 Fluorotelomer carboxylic acid
- Perfluroroctane sulfonamide
- N-methylperfluorooctane sulfonamide
- N-ethylperfluorooctane sulfonamide
- N-methyl perfluorooctanesulfonamidoacetic acid
- N-ethyl perfluorooctanesulfonamidoacetic acid
- N-methylperfluorooctane sulfonamidoethanol
- N-ethylperfluorooctane sulfonamidoethanol
- 9-Chlorohexadecafluoro-3-oxanonane-1-sulfonic acid (F-53B Major)
- 11-Chloroeicosafluoro-3-oxaundecane-1-sulfonic acid (F-53B Minor)



Project 12345 1-99 Franklin Court Tarrytown, New York

• Perfluoro(2-ethoxyethane) sulfonic acid

# **Appendix C:** Typical Boring/Well Construction Log

CECI		PROJECT NAME:								M	IONITOF	RING WELL NO.		
<b>JE2</b>		PROJECT LOCATION:								JC	OB NO.			
CONSULTING ENGINEERS									GF	ROUND	ELEVATION:			
BORING BY: DATE STARTED				DEVEL	OPMEN	IT PERI	OD		IN	SIDE CASING DIAMETER (in)				
				DEVEL	OPMEN		HOD		В	OREHOLE DIAMETER (in)				
NJ DEP PERMIT NO.:		DATE DEVELOPED				DEVEL	OPMEN			# apm	m IN	ITIAL WATER LEVEL (ft):		
			DEPTH				_			01			1	
WELL CONS	STRUCT	TION	(ft) 0	Sample	0/6	Blows of 6/12	n Spoor 12/18	18/24	(in)	s	SOIL DE	SCRIPTION AND STRATIFICAT	ION	P.I.D.
Depth (feet below grade)									. ,					
Top of Casing: #		_												
Ground Surface 0		Casing Type:												
Top of Riser #														
			5											
		Well Cap:												
Top of Seal #		Grout Type:												
Top of Sand Pack		Well Key:												
			10		I									
													_	
		Riser Pipe:												
Top of Screen			15											
													_	
		Sand/Gravel												
		Pack Size:	20											
													_	
		Screen Size:												
		CONCERNENCE.												
			25	<u> </u>										
													_	
				<u> </u>										
				<u> </u>										
				<u> </u>	1									
			30											
													_	
			35	<u> </u>										
													_	1
Bottom of Screen				<u> </u>										<u> </u>
Bottom of Boring				<u> </u>										<u> </u>
Remarks:				<u> </u>					$\vdash$					
			40	<u> </u>										<u> </u>
L	hpprov	imata Chango in Strat	 har			Inform	od Ch	ange	in Stra	ata:				1

The subsurface information shown hereon was obtained for the design and estimating purposes for our client. It is made available to authorized users only that they may have access to the same information available to our client. It is presented in good faith, but it is not intended as a substitute for investigations, interpretations or judgment of such authorized users. Information on the logs should not be relied upon without the geotechnical engineers recommendations contained in the report from which these logs were extracted. Soil descriptions represent a field identification after D. M. Burmister unless otherwise noted.

# Appendix D: Health and Safety Plan



Geotechnical Environmental Site Civil 959 Route 46E, Fl 3, Ste 300 Parsippany, NJ 07054 973.808.9050 www.sesi.org

# Site Specific Health and Safety Plan For

TMHA Franklin Courts 1-99 Franklin Court Tarrytown, Westchester County, New York

Prepared for: Franklin Courts JV Partners, L.P.

April 2024

SESI Project No: 12345

LIST OF ACRONYMS	i
1.0 PROJECT DESCRIPTION	1
1.1 OBJECTIVE	1
1.2 SITE AND FACILITY DESCRIPTION	1
1.3 POLICY STATEMENT	1
1.4 REFERENCES	2
1.5 DEFINITIONS	2
2.0 PROJECT SCOPE OF WORK	3
3.0 ROLES AND RESPONSIBILITIES	3
3.1 ALL PERSONNEL	3
3.2 KEY SAFETY PERSONNEL	3
3.2.1 PROJECT SAFETY OFFICER	3
3.2.2 PROJECT MANAGER (PM)	3
3.2.3 HEALTH AND SAFETY MANAGER (HSM)	4
3.2.4 SITE SAFETY OFFICER (SSO)	4
3.2.5 FIELD SUPERVISOR (FS)	4
3.3 SUBCONTRACTORS	5
3.4 STOP WORK AUTHORITY	5
3.5 ALL ON-SITE PERSONNEL	5
3.6 VISITORS	6
4.0 PERSONAL PROTECTIVE EQUIPMENT	7
4.1 LEVELS OF PROTECTION	7
4.1.1 LEVEL D PROTECTION	7
4.1.2 MODIFIED LEVEL D PROTECTION	. 7
4.1.3 LEVEL C PROTECTION	8
4.2 SELECTION OF PPE	8
4.3 SITE RESPIRATOR PROTECTION PROGRAM	. 8
4.4 USING PPE	9
4.4.1 DONNING PROCEDURES	. 9
4.4.2 DOFFING PROCEDURES	. 9
4.5 SELECTION MATRIX	.10
5.0 AIR AND NOISE MONITORING	.10
5.1 AIR MONITORING	.10
5.2 NOISE MONITORING	.11

# **Table of Contents**

5.3 MONITORING EQUIPMENT MAINTENANCE AND CALIBRATION	11
5.4 ACTION LEVELS	11
6.0 WORK ZONES AND DECONTAMINATION	13
6.1 WORK ZONES	13
6.1.1 AUTHORIZATION TO ENTER	13
6.1.2 SITE ORIENTATION AND HAZARD BRIEFING	13
6.1.3 CERTIFICATION DOCUMENTS	13
6.1.4 ENTRY LOG	13
6.1.5 ENTRY REQUIREMENTS	13
6.1.6 EMERGENCY ENTRANCE AND EXIT	14
6.1.7 CONTAMINATION CONTROL ZONES	14
6.1.8 EXCLUSION ZONE (EZ)	14
6.1.9 CONTAMINATION REDUCTION ZONE	14
6.1.10 SUPPORT ZONE (SZ)	14
6.1.11 POSTING	14
6.2 DECONTAMINATION	14
6.2.1 PERSONNEL DECONTAMINATION	14
6.2.2 EQUIPMENT DECONTAMINATION	15
6.2.3 PERSONAL PROTECTIVE EQUIPMENT DECONTAMINATION	15
7.0 TRAINING AND MEDICAL SURVEILLANCE	15
7.1 TRAINING	15
7.1.1 GENERAL	15
7.1.2 BASIC 40-HOUR COURSE	15
7.1.3 SUPERVISOR COURSE	16
7.1.4 SITE-SPECIFIC TRAINING	16
7.1.5 DAILY SAFETY MEETINGS	16
7.1.6 FIRST AID AND CPR	16
7.2 MEDICAL SURVEILLANCE	17
7.2.1 MEDICAL EXAMINATION	17
7.2.2 PRE-PLACEMENT MEDICAL EXAMINATION	17
7.2.3 OTHER MEDICAL EXAMINATIONS	17
7.2.4 PERIODIC EXAM	18
7.2.5 MEDICAL RESTRICTION	18
8.0 GENERAL SAFETY PRACTICES	18
8.1 GENERAL SAFETY RULES	18

ł	3.2 BUDDY S	YSTEM	19
ł	3.3 HEAT STR	RESS	20
ł	3.4 HEAT STR	RESS SAFETY PRECAUTIONS	21
ł	3.5 COLD ST	RESS	23
ł	3.6 SAFETY F	PRECAUTIONS FOR COLD STRESS PREVENTION	24
ł	3.7 SAFE WO	RK PROCEDURES	24
ł	3.8 BIOLOGIC	CAL HAZARDS	25
	8.8.1 TICK I	BORNE DISEASES	25
	8.8.2 POISC	DNOUS PLANTS	26
	8.8.3 SNAK	ES	26
	8.8.4 SPIDE	ERS	26
ł	3.9 NOISE		27
ł	3.10 SPILL CO	ONTROL	28
ł	3.11 SANITAT	FION	28
	8.11.1 BRE	AK AREA	28
	8.11.2 POT	ABLE WATER	28
	8.11.3 SAN	ITARY FACILITIES	28
	8.11.4 LAVA	ATORY	28
ł	3.12 EMERGE	ENCY EQUIPMENT	29
ł	3.13 LOCKOL	JT/TAGOUT PROCEDURES	29
ł	3.14 ELECTR	ICAL SAFETY	29
ł	8.15 LIFTING	SAFETY	30
ł	3.16 LADDER	SAFETY	30
ł	B.17 TRAFFIC	SAFETY	32
9.0	SITE-SPECI	FIC HAZARDS AND CONTROL MEASURES	32
9	9.1 EVALUAT	ION OF HAZARDS	32
	9.1.1 HAZA	RD CHARACTERISTICS	32
	9.1.2 POTE	NTIAL HEALTH AND SAFETY HAZARDS	33
9	9.2 FIELD AC	TIVITIES, HAZARDS AND CONTROL PROCEDURES	33
	9.2.1 MOBII	LIZATION/CONSTRUCTION STAKEOUT	34
	9.2.2 DEMC	DLITION/SITE-CLEARING	34
	9.2.3 EXCA	VATION AND CUT/FILL OPERATIONS	36
	9.2.3.1	EXCAVATION TRENCHING	36
	9.2.3.2	HEAVY EQUIPMENT OPERATION	37
	9.2.3.3	DISTURBANCE/HANDLING OF CONTAMINATED MATERIAL	

9.2.4 DRILLING/SUBSURFACE INTRUSION ACTIVITIES	
9.2.5 SUBSURFACE CHEMICAL SAMPLE/COLLECTION ANALYSIS	43
9.2.6 UST CLOSURE	43
9.2.6.1 WORKING IN CONFINED SPACES	43
9.2.6.2 WORKING WITH COMPRESSED AIR	44
9.2.7 DECONTAMINATION	44
9.2.8 DEMOBILIZATION	45
9.3 CHEMICAL HAZARDS	45
10.0 EMERGENCY PROCEDURES	50
10.1 GENERAL	50
10.2 EMERGENCY RESPONSE	50
10.2.1 FIRE	50
10.2.2 CONTAMINANT RELEASE	51
10.3 MEDICAL EMERGENCY	51
10.3.1 EMERGENCY CARE STEPS	51
10.4 FIRST AID GENERAL	52
10.4.1 FIRST AID—INHALATION	52
10.4.2 FIRST AID—INGESTION	52
10.4.3 FIRST AID—SKIN CONTACT	52
10.4.4 FIRST AID—EYE CONTACT	52
10.5 REPORTING INJURIES, ILLNESSES, AND SAFETY INCIDENTS	52
10.6 EMERGENCY INFORMATION	53
10.6.1 DIRECTIONS TO HOSPITAL	53
11.0 LOGS, REPORTS, AND RECORDKEEPING	54
11.1 HASP AND FIELD CHANGE REPORT	54
11.2 MEDICAL AND TRAINING RECORDS	54
11.3 EXPOSURE RECORDS	54
11.4 ACCIDENT/INCIDENT REPORT	54
11.5 OSHA FORM 200	55
11.6 ON-SITE HEALTH AND SAFETY FIELD LOGBOOK	55
11.7 SAFETY DATA SHEETS	55
12.0 COVID RESPONSE ACTION PLAN	55

# **FIGURES**

FIGURE 10.1 WHITE PLAINS HOSPITAL, WHITE PLAINS, NY

# TABLES

- TABLE 3.1 KEY SAFETY PERSONN
- TABLE 4.1 PPE SELECTION MATRIX
- TABLE 5.1AIRBORNE CONTAMINANT ACTION LEVELS
- TABLE 8.1 WORK/REST SCHEDULE
- TABLE 8.2 WIND CHILL TEMPERATURE CHART
- TABLE 8.3 VOLTAGE VERSUS REQIRED CLEARNACE
- TABLE 9.1 LIST OF PRIMARY CONTAMINANTS
- TABLE 10.1 EMERGENCY CONTACTS

# **ATTACHMENTS**

ATTACHMENT 1	AIR MONITORING LOG
ATTACHMENT 2	OSHA POSTER
ATTACHMENT 3	HASP FIELD CHANGE REQUEST FORM
ATTACHMENT 4	ACCIDENT/INCIDENT REPORT
ATTACHMENT 5	SIGNATORY PAGE
ATTACHMENT 6	MATERIAL SAFETY DATA SHEETS



**Disclaimer:** This Health and Safety Plan (HASP) is based upon information provided [and, if applicable, conditions discovered during a site visit], and is limited by the project scope.

The HASP should be periodically reviewed and updated based on a number of factors, including but not limited to: (1) changes in applicable governmental requirements; (2) changes in procedures at the site; and (3) site conditions which were unknown to SESI Consulting Engineers (SESI) as of the time the HASP was prepared.

This HASP has been prepared for the sole and exclusive use of Client listed above, and may not be relied upon by any other person without the express written consent and authorization of SESI.



# SITE-SPECIFIC HEALTH AND SAFETY PLAN

For

# 1-99 Franklin Court Tarrytown, Westchester County, New York

Prepared by:

Christopher Malvicini SESI- Asst Project Manager

Approved by: \_\_\_\_\_

Fuad Dahan SESI-Principal



# LIST OF ACRONYMS

Acronym	Definition		
ACGIH	American Conference of Governmental Industrial		
	Hygienists		
COC	Contaminants(s) of Concern		
CRZ	Contamination Reduction Zone		
EMS	Emergency Medical Services		
EZ	Exclusion Zone		
FS	Field Supervisor		
GFCI	Ground Fault Circuit Interrupter		
HASP	Health and Safety Plan		
HSM	Health and Safety Manager		
LEL	Lower Explosive Limit		
MSDS	Material Safety Data Sheet		
NIOSH	National Institute for Occupational Safety and Health		
NRR	Noise Reduction Rating		
OSHA	Occupational Safety and Health Administration		
PCB	Polychlorinated Biphenyls		
PEL	Permissible Exposure Limit		
PFD	Personal Flotation Device		
PID	Photoionization Detector		
PM	Project Manager		
PO	Project Officer		
PPE	Personal Protective Equipment		
PVC	Polyvinyl Chloride		
SESI	SESI Consulting Engineers		
SSO	Site Safety Officer		
SVOC	Semi-Volatile Organic Compound		
SZ	Support Zone		
TLV	Threshold Limit Value		
USCG	United States Coast Guard		



Acronym	Definition
USEPA	United States Environmental Protection Agency
UST	Underground Storage Tank
VOC	Volatile Organic Compound



# **1.0 PROJECT DESCRIPTION**

#### 1.1 OBJECTIVE

The objective of this Health and Safety Plan (HASP) is to provide a mechanism for establishing safe working conditions during activities at 1-99 Franklin Court, Tarrytown, New York (the Site). The safety organization, procedures, and protective equipment have been established based on an analysis of potential physical, chemical, and biological hazards. Specific hazard control methodologies have been evaluated and selected to minimize the potential of injury, illness, or other hazardous incidents.

The HASP was written to meet the requirements of all applicable Federal, State, and local health and safety regulations, including 29 CFR 1910.120. The HASP is based on current knowledge regarding the specific chemical and physical hazards that are known or anticipated at the Site. This HASP is a dynamic document, for which changes and/or revisions may be realized as changes in scope and/or Site conditions are encountered. Should revised documents be produced, said revised documents will refer to the specific changes and why they were made.

#### 1.2 SITE AND FACILITY DESCRIPTION

The subject property is bounded to the north by a multi-family residential apartment building at 50 White Street, to the east by Riverview Avenue and residential developments beyond, to the south by residential development along MacArthur Avenue, and to the west by Warehouses and former railroad tracks.

#### **1.3 POLICY STATEMENT**

The policy of SESI Consulting Engineers (SESI) is to provide a safe and healthful work environment. No aspect of operations is of greater importance than injury and illness prevention. A fundamental principle of safety management is that all injuries, illnesses, and incidents are preventable. SESI will take every reasonable step to eliminate or control hazards in order to minimize the possibility of injury, illness, or incident.

This HASP prescribes the procedures that must be followed by SESI personnel during activities at the Site. Operational changes that could affect the health and safety of personnel, the community, or the environment will not be made without the prior approval of the Project Manager (PM) and the Health and Safety Manager (HSM). This document will be reviewed periodically by the HSM to ensure that it is current and technically correct. Any changes in Site conditions and/or the scope of work will require a review and modification to this HASP. Such changes will be completed in the form of an addendum or a revision to the plan.

The provisions of this plan are mandatory for all SESI personnel and are advisory for all contractors, and subcontractors assigned to the project. *Subcontractors will be responsible for preparing their own Site-specific HASPs that meet the basic requirements outlined in this HASP.* All visitors to SESI work areas at the Site must abide by the requirements of this plan.



#### **1.4 REFERENCES**

This HASP complies with applicable Occupational Safety and Health Administration (OSHA) regulations, United States Environmental Protection Agency (USEPA) regulations, and SESI health and safety policies and procedures. This plan follows the guidelines established in the following:

- Standard Operating Safety Guides, USEPA (Publication 9285.1-03, June 1992).
- Occupational Safety and Health Guidance Manual for Hazardous Waste Site Activities, NIOSH, OSHA, USCG, USEPA (86116, October 1985).
- Title 29 of the Code of Federal Regulations (CFR), Part 1910.
- Title 29 of the Code of Federal Regulations (CFR), Part 1926.
- Pocket Guide to Chemical Hazards, DHHS, PHS, CDC, NIOSH (2004).
- Threshold Limit Values, ACGIH (2005).
- Guide to Occupational Exposure Values, ACGIH (2005).
- *Quick Selection Guide to Chemical Protective Clothing*, Forsberg, K. and S.Z. Mansdorf, 2nd Ed. (1993).

# **1.5 DEFINITIONS**

The following definitions (listed alphabetically) are applicable to this HASP:

- Contamination Reduction Zone (CRZ) Area between the exclusion zone and support zone that provides a transition between contaminated and clean areas. Decontamination stations are located in this zone.
- *Exclusion Zone (EZ)* Any portions of the site where hazardous substances are, or are reasonably suspected to be present, and pose an exposure hazard to on-Site personnel.
- *Incident* All losses, including first aid cases, injuries, illnesses, spills/leaks, equipment and property damage, motor vehicle accidents, regulatory violations, fires, and business interruptions.
- On-Site Personnel All SESI and subcontractors involved with the project.
- *Project* All on-site work performed under the scope of work.
- *Site* The area described in Section 1.2, Site and Facility Description, where the work is to be performed by SESI personnel and subcontractors.
- Support Zone (SZ) All areas of the Site except the EZ and CRZ. The SZ surrounds the CRZ and EZ. Support equipment and break areas are located in this zone.
- Subcontractor Includes contractor personnel hired by SESI.
- *Visitor* All other personnel, except the on-Site personnel.

*Work Area* - The portion of the Site where work activities are actively being performed. This area may change daily as work progresses and includes the SZ, CRZ, and EZ. If the work area is located in an area on the Site that is not contaminated, or suspected of being contaminated, the entire work area may be a SZ.



# 2.0 PROJECT SCOPE OF WORK

This HASP contains information for the following tasks that SESI is anticipated to conduct at the Site. Should additional and/or different tasks be identified, amendments to this HASP will be required to address these changed items.

- Mobilization;
- Excavation of Contaminated Soil;
- End Point Chemical Sampling of Soil;
- Installation of a Vapor Barrier for Buildings;
- Groundwater Sampling;
- Decontamination and Demobilization.

#### 3.0 ROLES AND RESPONSIBILITIES

#### 3.1 ALL PERSONNEL

All SESI project personnel must adhere to the procedures outlined in this HASP during the performance of their work. Each person is responsible for completing tasks safely and reporting any unsafe acts or conditions to their supervisor. No person may work in a manner that conflicts with these procedures. After due warnings, the PM will dismiss from the site any SESI employee or subcontractor who violates safety procedures.

All SESI project personnel will receive training in accordance with applicable regulations and be familiar with the requirements and procedures contained in this HASP prior to initiating site activities. In addition, all SESI personnel will attend an initial hazard briefing prior to beginning work at the Site.

The roles of key safety personnel and subcontractors are outlined in the following sections. Key project personnel and contacts are summarized in **Table 3.1**.

#### 3.2 KEY SAFETY PERSONNEL

#### 3.2.1 PROJECT SAFETY OFFICER

The PO is responsible for providing resources to assure project activities are completed in accordance with this HASP, and for meeting all regulatory and contractual requirements.

#### 3.2.2 PROJECT MANAGER (PM)

The PM is responsible for verifying that project activities are completed in accordance with the requirements of this HASP. The PM is responsible for confirming that the Field Supervisor (FS) has the equipment, materials, and qualified personnel to fully implement the safety requirements of this HASP, and/or that subcontractors assigned to this project meet the requirements established by SESI. It is also the responsibility of the PM to:



- Consult with the HSM on Site health and safety issues;
- Verify that subcontractors meet health and safety requirements prior to commencing work;
- Verify that all incidents are thoroughly investigated;
- Approve, in writing, addenda or modifications of this HASP; and
- Suspend work or modify work practices, as necessary, for personal safety, protection of property, and regulatory compliance.

# 3.2.3 HEALTH AND SAFETY MANAGER (HSM)

The HSM or his designee has overall responsibility for the technical health and safety aspects of the project, including review and approval of this HASP. Inquiries regarding health and safety procedures, project procedures, and other technical or regulatory issues should be addressed to this individual. The HSM or his designee must approve changes or addenda to this HASP.

# 3.2.4 SITE SAFETY OFFICER (SSO)

The SSO is responsible for field health and safety issues, including the execution of this HASP. Questions in the field regarding health and safety procedures, project procedures, and other technical or regulatory issues should be addressed to this individual. The SSO will advise the PM on health and safety issues and will establish and coordinate the project air-monitoring program if one is deemed necessary (see Section 5.1, Air Monitoring). The SSO is the primary Site contact on health and safety matters. It is the responsibility of the SSO to:

- Provide on-Site technical assistance, if necessary;
- Participate in all accident/incident reports and ensure that they are reported to the HSM, client, and PM within 24 hours;
- Coordinate Site and personal air monitoring as required, including equipment maintenance and calibration;
- Conduct Site safety orientation training and safety meetings;
- Verify that project personnel have received the required physical examinations and medical certifications;
- Review Site activities with respect to compliance with this HASP;
- Maintain required health and safety documents and records; and
- Assist the FS in instructing field personnel on project hazards and protective procedures.

#### 3.2.5 FIELD SUPERVISOR (FS)

The FS is responsible for implementing this HASP, including communicating requirements to on-Site personnel and subcontractors. The FS will be responsible for informing the PM of changes in the work plan, procedures, or Site conditions so that those changes may be addressed in this HASP. Other responsibilities are to:

- Consult with the SSO on Site health and safety issues;
- Stop work, as necessary, for personal safety, protection of property, and regulatory compliance;



- Obtain a Site map and determine and post routes to medical facilities and emergency telephone numbers;
- Notify local public emergency representatives (as appropriate) of the nature of the Site operations, and post their telephone numbers (i.e., local fire department personnel who would respond for a confined space rescue);
- Observe on-Site project personnel for signs of ill health effects;
- Investigate and report any incidents to the SSO;
- Verify that all on-Site personnel have had applicable training;
- Verify that on-Site personnel are informed of the physical, chemical, and biological hazards associated with the Site activities, and the procedures and protective equipment necessary to control the hazards; and

Issue/obtain any required work permits (hot work, confined space, etc.)

#### 3.3 SUBCONTRACTORS

Subcontractors and their personnel must understand and comply with applicable regulations and Site requirements established in this HASP. Subcontractors will prepare their own Site-specific HASP that must be consistent with the requirements of this HASP.

All subcontractor personnel will receive training in accordance with applicable regulations and be familiar with the requirements and procedures contained in this HASP prior to initiating Site activities. All subcontractor personnel will attend an initial hazard briefing prior to beginning work at the Site. Additionally, on-Site subcontractor personnel must conduct daily Site safety meetings.

Subcontractors must designate individuals to function as the PM, HSM, SSO, and FS. In some firms the HSM to be carried out by the PM. This is acceptable provided the PM has the required knowledge, training, and experience to properly address all hazards associated with the work, and to prepare, approve, and oversee the execution of the Site-specific HASP. A subcontractor may designate the same person to perform the duties of both the SSO and the FS. However, depending on the level of complexity of a contractor's scope of work, it may be infeasible for one person to perform both functions satisfactorily.

#### 3.4 STOP WORK AUTHORITY

Every SESI employee and subcontractor is empowered, expected, and has the responsibility to stop the work of another co-worker if the working conditions or behaviors are considered unsafe.

#### 3.5 ALL ON-SITE PERSONNEL

All on-Site SESI personnel (including SESI subcontractors) must read and acknowledge their understanding of their respective HASPs before commencing work and abide by the requirements of the plans. All on-Site SESI personnel shall sign their HASP Acknowledgement Form following their review of their HASP.

All SESI project personnel will receive training in accordance with applicable regulations and be familiar with the requirements and procedures contained in this HASP prior to initiating Site



activities. In addition, all on-Site personnel will attend an initial hazard briefing provided by the SSO prior to beginning work at the Site and conduct daily safety meetings thereafter.

On-Site personnel will immediately report the following to the FS or SSO:

- Personal injuries and illnesses no matter how minor;
- Unexpected or uncontrolled release of chemical substances;
- Symptoms of chemical exposure;
- Unsafe or hazardous situations;
- Unsafe or malfunctioning equipment;
- Changes in site conditions that may affect the health and safety of project personnel;
- Damage to equipment or property; and

Situations or activities for which they are not properly trained.

#### **3.6 VISITORS**

All SESI personnel and subcontractors visiting the Site must check in with the FS. Visitors will be cautioned to avoid skin contact with surfaces, soils, groundwater, or other materials that may impacted or be suspected to be impacted by contaminants of concern (COCs).

Visitors requesting to observe work at the site must don appropriate personal protective equipment (PPE) prior to entry to the work area and must have the appropriate training and medical clearances to do so. If respiratory protective devices are necessary, visitors who wish to enter the work area must have been respirator-trained and fit tested for a respirator within the past 12 months.

SESI Personnel				
Role	Name	Telephone No.		
Project Principal	Fuad Dahan, P.E., PhD	973-808-9050 x249		
Project Manager	Jesse Mausner, PG	973-808-9050		
Principal Engineer	Fuad Dahan, P.E., PhD	973-808-9050 x249		
Field Team Leader	TBD	973-808-9050		
Quality Assurance Officer	Joe Scardino	973-808-9050 x267		
Field Personnel	TBD	973-808-9050		

Table 3.1 – Key Safety Personne	Table 3.1 -	Kev	Safety	Personne
---------------------------------	-------------	-----	--------	----------



# 4.0 PERSONAL PROTECTIVE EQUIPMENT

# 4.1 LEVELS OF PROTECTION

PPE is required to safeguard site personnel from various hazards. Varying levels of protection may be required depending on the levels of COCs and the degree of physical hazard. This section presents the various levels of protection and defines the conditions of use for each level. A summary of the levels is presented in **Table 4.1**.

# 4.1.1 LEVEL D PROTECTION

The minimum level of protection that will be required of project personnel at the site will be Level D, which will be worn when site conditions or air monitoring indicates no inhalation hazard exists. The following equipment will be used:

- Work clothing as prescribed by weather;
- Steel toe work boots, meeting American National Standards Institute (ANSI) Z41;
- Safety glasses or goggles, meeting ANSI Z87;
- Leather work gloves and/or nitrile surgical gloves;
- Hard hat, meeting ANSI Z89, when falling object hazards are present;
- Hearing protection (if noise levels exceed 85 dBA, then hearing protection with a USEPA NRR of at least 20 dBA must be used); and

Personal floatation device (PFD) if working on or near the water.

# 4.1.2 MODIFIED LEVEL D PROTECTION

Modified Level D will be used when airborne contaminants are not present at levels of concern, but site activities present an increased potential for skin contact with contaminated materials. Modified Level D consists of:

- Nitrile gloves worn over nitrile surgical gloves;
- Latex/polyvinyl chloride (PVC) overboots when contact with COC-impacted media is anticipated;
- Steel toe work boots, meeting ANSI Z41;
- Safety glasses or goggles, meeting ANSI Z87;
- Face shield in addition to safety glasses or goggles when projectiles or splash hazards exist (e.g. during Power Washing activities);
- Hard hat, meeting ANSI Z89, when falling object hazards are present;
- Hearing protection (if noise levels exceed 85 dBA, then hearing protection with a USEPA NRR of at least 20 dBA must be used);
- Tyvek<sup>®</sup> suit (polyethylene coated Tyvek<sup>®</sup> suits for handling liquids) when body contact with COC-impacted media is anticipated; and
- PFD if working on or near the water.



# 4.1.3 LEVEL C PROTECTION

Level C protection will be required when the airborne concentration of COC reaches one-half of the OSHA Permissible Exposure Limit or ACGIH TLV. The following equipment will be used for Level C protection:

- Full-face, air-purifying respirator with combination organic vapor/HEPA cartridges;
- Polyethylene-coated Tyvek<sup>®</sup> suit, with ankles and cuffs taped to boots and gloves;
- Nitrile gloves worn over nitrile surgical gloves;
- Steel toe work boots, meeting ANSI Z41;
- Chemical-resistant boots with steel toes or latex/PVC overboots over steel toe boots;
- Hard hat, meeting ANSI Z89;
- Hearing protection (if noise levels exceed 85 dBA, then hearing protection with a USEPA NRR of at least 20 dBA must be used); and
- PFD if working on or near the water.

# 4.2 SELECTION OF PPE

Equipment for personal protection will be selected based on the potential for contact, site conditions, ambient air quality, and the judgment of supervising Site personnel and health and safety professionals. The PPE used will be chosen to be effective against the COCs present on the Site.

# 4.3 SITE RESPIRATOR PROTECTION PROGRAM

Respiratory protection is an integral part of employee health and safety at the Site due to potentially hazardous concentrations of airborne COCs. The Site respiratory protection program will consist of the following (as a minimum):

- All on-Site personnel who may use respiratory protection will have an assigned respirator.
- All on-Site personnel who may use respiratory protection will have been fit tested and trained in the use of a full-face air-purifying respirator within the past 12 months. Documentation of the fit test must be provided to the SSO prior to commencement of work.
- All on-Site personnel who may use respiratory protection must within the past year have been medically certified as being capable of wearing a respirator. Documentation of the medical certification must be provided to the SSO, prior to commencement of Site work.
- Only cleaned, maintained, NIOSH-approved respirators will be used.
- If respirators are used, the respirator cartridge is to be properly disposed of at the end of each work shift, or when load-up or breakthrough occurs.
- Contact lenses are not to be worn when a respirator is worn.
- All on-Site personnel who may use respiratory protection must be clean-shaven. Mustaches and sideburns are permitted, but they must not touch the sealing surface of the respirator.
- Respirators will be inspected, and a negative pressure test performed prior to each use.



After each use, the respirator will be wiped with a disinfectant, cleansing wipe. When used, the respirator will be thoroughly cleaned at the end of the work shift. The respirator will be stored in a clean plastic bag, away from direct sunlight in a clean, dry location, in a manner that will not distort the face piece.

# 4.4 USING PPE

Depending upon the level of protection selected, specific donning and doffing procedures may be required. The procedures presented in this section are mandatory if Modified Level D or Level C PPE is used. All personnel entering the EZ must put on the required PPE in accordance with the requirements of this HASP. When leaving the EZ, PPE will be removed in accordance with the procedures listed, to minimize the spread of COCs.

# 4.4.1 DONNING PROCEDURES

These procedures are mandatory only if Modified Level D or Level C PPE is used on the Site:

- Remove bulky outerwear. Remove street clothes and store in clean location;
- Put on work clothes or coveralls;
- Put on the required chemical protective coveralls;
- Put on the required chemical protective boots or boot covers;
- Tape the legs of the coveralls to the boots with duct tape;
- Put on the required chemical protective gloves;
- Tape the wrists of the protective coveralls to the gloves;
- Don the required respirator and perform appropriate fit check (Level C);
- Put hood or head covering over-head and respirator straps and tape hood to facepiece (Level C); and
- Don remaining PPE, such as safety glasses or goggles and hard hat.

When these procedures are instituted, one person must remain outside the work area to ensure that each person entering has the proper protective equipment.

#### 4.4.2 DOFFING PROCEDURES

The following procedures are only mandatory if Modified Level D or Level C PPE is required for the Site. Whenever a person leaves the work area, the following decontamination sequence will be followed:

- Upon entering the CRZ, rinse contaminated materials from the boots or remove contaminated boot covers;
- Clean reusable protective equipment;
- Remove protective garments, equipment, and respirator (Level C). All disposable clothing should be placed in plastic bags, which are labeled with contaminated waste labels;
- Wash hands, face, and neck (or shower if necessary);
- Proceed to clean area and dress in clean clothing; and



• Clean and disinfect respirator for next use.

All disposable equipment, garments, and PPE must be bagged in plastic bags, labeled for disposal. See Section 6.2, Decontamination, for detailed information on decontamination stations.

#### 4.5 SELECTION MATRIX

The level of personal protection selected will be based on air monitoring of the work environment and an assessment by the FS and SSO of the potential for skin contact with COCs. The PPE selection matrix is presented in **Table 4.1** below. This matrix is based on information available at the time this plan was written. The Airborne Contaminant Action Levels in **Table 5.1**, Airborne Contaminant Action Levels, should be used to verify that the PPE prescribed in these matrices is appropriate.

Task	Anticipated Level of Protection	
Mobilization	Level D	
Subsurface Intrusive Activities (Excavation, Drilling)	Modified Level D/Level C	
Earthwork/Grading	Level D	
Chemical Sampling / Delineation	Modified Level D/Level C	
Decontamination	Modified Level D	
Demobilization	Level D	

#### Table 4.1 – PPE Selection Matrix

#### 5.0 AIR AND NOISE MONITORING

#### **5.1 AIR MONITORING**

Air monitoring, sampling, and testing will be conducted to determine employee exposure to airborne constituents. The monitoring results will dictate work procedures and the selection of PPE. The SESI SSO will be responsible for defining appropriate air monitoring procedures and for utilizing the air monitoring results to determine appropriate procedures and PPE for project personnel. Air monitoring results should be recorded in field notebooks or on an air monitoring log (see Attachment 1 for a copy of the Air Monitoring Log). Any deviations from the procedures listed here should be documented and explained in the Air Monitoring Log.

The monitoring devices to be used are a PDR1000 particulate monitor (or equivalent) and a Rae Systems MultiRAE detector (PID with a 11.7 eV lamp/oxygen/LEL/hydrogen sulfide sensors). Colorimetric detector tubes may be utilized to estimate airborne concentrations of benzene and



should be onsite during any activities that may result in elevated PID readings including drilling, excavating, and groundwater sampling.

Air monitoring will be conducted continuously with the LEL/Oxygen meter during drilling in areas where flammable vapors or gases are suspect. All work activity must stop where tests indicate the concentration of flammable vapors exceeds 10% of the LEL at a location with a potential ignition source. Such an area must be ventilated to reduce the concentration to an acceptable level.

#### 5.2 NOISE MONITORING

Noise monitoring may be conducted as required. Hearing protection is mandatory for all employees in noise hazardous areas, such as around heavy equipment. As a general rule, sound levels that cause speech interference at normal conversation distance should require the use of hearing protection.

#### 5.3 MONITORING EQUIPMENT MAINTENANCE AND CALIBRATION

All direct-reading instrumentation calibrations should be conducted under the approximate environmental conditions the instrument will be used. Instruments must be calibrated before and after use, noting the reading(s) and any adjustments that are necessary. All air monitoring equipment calibrations, including the standard used for calibration, must be documented on a calibration log or in the field notebook. All completed health and safety documentation/forms must be reviewed by the SSO and maintained by the FS.

All air monitoring equipment will be maintained and calibrated in accordance with the specific manufacturer's procedures. Preventive maintenance and repairs will be conducted in accordance with the respective manufacturer's procedures. When applicable, only manufacturer-trained and/or authorized personnel will be allowed to perform instrument repairs or preventive maintenance.

If an instrument is found to be inoperative or suspected of giving erroneous readings, the SSO must be responsible for immediately removing the instrument from service and obtaining a replacement unit. If the instrument is essential for safe operation during a specific activity, that activity must cease until an appropriate replacement unit is obtained. The SSO will be responsible for ensuring a replacement unit is obtained and/or repairs are initiated on the defective equipment.

#### 5.4 ACTION LEVELS

**Table 5.1** below presents airborne contaminant action levels that will be used to determine the procedures and protective equipment necessary based on conditions as measured at the Site.



Parameter	Reading	Action
Total Hydrocarbons	0 ppm to <u>&lt;</u> 1 ppm	Normal operations; continue hourly breathing zone monitoring
	> 1 ppm to 5 ppm	Increase monitoring frequency to every 15 minutes and use benzene detector tube to screen for the presence of benzene
	≥ 5 ppm to <u>&lt;</u> 50 ppm	Upgrade to Level C PPE; continue screening for benzene
	> 50 ppm	Stop work; investigate cause of reading
	At any reading > 5 ppm	Monitor perimeter per CAMP
Benzene	<u>&gt;</u> 1 ppm to 5 ppm	Upgrade to Level C PPE
	> 5 ppm	Stop work; investigate cause of reading
Dust	0 to .05 mg/m3	Normal operations
	0.05 to 0.1 mg/m3	Begin soil wetting procedure (Level C protection would be needed beyond this point)
	> 0.15 mg/m3	Stop work, fully implement dust control plan
Oxygen	<u>&lt;</u> 19.5%	Stop work, evacuate confined spaces/work area, investigate cause of reading, and ventilate area
	> 19.5% to < 23.5%	Normal operations
	<u>≥</u> 23.5%	Stop work, evacuate confined spaces/work area, investigate cause of reading, and ventilate area
Carbon Monoxide	0 ppm to <u>&lt;</u> 20 ppm	Normal operations
	> 20 ppm	Stop work, evacuate confined spaces/work area, investigate cause of reading, and ventilate area
Hydrogen Sulfide	0 ppm to <u>&lt;</u> 5 ppm	Normal operations
	> 5 ppm	Stop work, evacuate confined spaces/work area, investigate cause of reading, and ventilate area

# Table 5.1 – Airborne Contaminant Action Levels



Parameter	Reading	Action
Flammable Vapors (LEL)	< 10% LEL	Normal operations
	<u>&gt;</u> 10% LEL	Stop work, ventilate area, investigate source of vapors

# 6.0 WORK ZONES AND DECONTAMINATION

#### 6.1 WORK ZONES

# 6.1.1 AUTHORIZATION TO ENTER

Only personnel with the appropriate training and medical certifications (if respirators are required) will be allowed to work at the project Site. The FS will maintain a list of authorized persons; only personnel on the authorized persons list will be allowed to enter the Site work areas.

# 6.1.2 SITE ORIENTATION AND HAZARD BRIEFING

No person will be allowed in the work area during Site operations without first being given a Site orientation and hazard briefing. This orientation will be presented by the FS or SSO and will consist of a review of this HASP. This review must cover the chemical, physical, and biological hazards, protective equipment, safe work procedures, and emergency procedures for the project. Following this initial meeting, daily safety meetings will be held each day before work begins.

All people entering the Site work areas, including visitors, must document their attendance at this briefing, as well as the daily safety meetings on the forms included with this plan.

#### 6.1.3 CERTIFICATION DOCUMENTS

A training and medical file may be established for the project and kept on Site during all Site operations. Specialty training, such as first aid/cardiopulmonary resuscitation (CPR) certificates, as well as current medical clearances for all project field personnel required to wear respirators, will be maintained within that file. All project personnel must provide their training and medical documentation to the SSO prior to starting work.

#### 6.1.4 ENTRY LOG

A log-in/log-out sheet will be maintained at the Site by the FS. Personnel must sign in and out on a log sheet as they enter and leave the work area, and the FS may document entry and exit in the field notebook.

#### 6.1.5 ENTRY REQUIREMENTS

In addition to the authorization, hazard briefing, and certification requirements listed above, no person will be allowed in any SESI work area unless they are wearing the minimum PPE as described in Section 4.0.



# 6.1.6 EMERGENCY ENTRANCE AND EXIT

People who must enter the work area on an emergency basis will be briefed of the hazards by the FS or SSO. All activities will cease in the event of an emergency. People exiting the work area because of an emergency will gather in a designated safe area for a head count. The FS is responsible for ensuring that all people who entered the work area have exited in the event of an emergency.

# 6.1.7 CONTAMINATION CONTROL ZONES

Contamination control zones are maintained to prevent the spread of contamination and to prevent unauthorized people from entering hazardous areas.

#### 6.1.8 EXCLUSION ZONE (EZ)

An EZ may consist of a specific work area or may be the entire area of potential contamination. All employees entering an EZ must use the required PPE and must have the appropriate training and medical clearance for hazardous waste work. The EZ is the defined area where there is a possible respiratory and/or contact health hazard. Cones, caution tape, or a posted Site diagram will identify the location of each EZ.

#### 6.1.9 CONTAMINATION REDUCTION ZONE

The CRZ or transition area will be established, if necessary, to perform decontamination of personnel and equipment. All personnel entering or leaving the EZ will pass through this area to prevent any cross-contamination. Tools, equipment, and machinery will be decontaminated in a specific location. The decontamination of all personnel will be performed on Site adjacent to the EZ. Personal protective outer garments and respiratory protection will be removed in the CRZ and prepared for cleaning or disposal. This zone is the only appropriate corridor between the EZ and the support zone discussed below.

#### 6.1.10 SUPPORT ZONE (SZ)

The SZ is a clean area outside the CRZ located to prevent employee exposure to hazardous substances. Eating and drinking will be permitted in the support area only after proper decontamination. Smoking may be permitted in the SZ, subject to Site requirements.

#### 6.1.11 POSTING

Work areas will be prominently marked and delineated using cones, caution tape, or a posted Site diagram.

#### 6.2 DECONTAMINATION

#### 6.2.1 PERSONNEL DECONTAMINATION

All personnel wearing Modified Level D or Level C protective equipment in the EZ must undergo personal decontamination prior to entering the SZ. The personnel decontamination area will consist of the following stations at a minimum:



- *Station 1*: Personnel leaving the contaminated zone will remove the gross contamination from their outer clothing and boots.
- *Station 2*: Personnel will remove their outer garment and gloves and dispose of it in properly labeled containers. Personnel will then decontaminate their hard hats, and boots with an aqueous solution of detergent or other appropriate cleaning solution. These items are then hand carried to the next station.
- *Station 3*: Personnel will thoroughly wash their hands and face before leaving the CRZ. Respirators will be sanitized and then placed in a clean plastic bag.

# 6.2.2 EQUIPMENT DECONTAMINATION

All vehicles that have entered the EZ will be decontaminated at the decontamination pad prior to leaving the zone. If the level of vehicle contamination is low, decontamination may be limited to rinsing of tires and wheel wells with water. If the vehicle is significantly contaminated, steam cleaning or pressure washing of vehicles and equipment may be required.

# 6.2.3 PERSONAL PROTECTIVE EQUIPMENT DECONTAMINATION

Where and whenever possible, single-use, external protective clothing must be used for work within the EZ or CRZ. This protective clothing must be disposed of in properly labeled containers. Reusable protective clothing will be rinsed at the Site with detergent and water. The rinsate will be collected for disposal.

When removed from the CRZ, the respirator will be thoroughly cleaned with soap and water. The respirator face piece, straps, valves, and covers must be thoroughly cleaned at the end of each work shift, and ready for use prior to the next shift. Respirator parts may be disinfected with a solution of bleach and water (mixed at 2% bleach by volume), or by using a spray disinfectant.

#### 7.0 TRAINING AND MEDICAL SURVEILLANCE

#### 7.1 TRAINING

#### 7.1.1 GENERAL

All on-Site project personnel who work in areas where they may be exposed to Site contaminants must be trained as required by OSHA Regulation 29 CFR 1910.120 (HAZWOPER). Field employees also must receive a minimum of three (3) days of actual field experience under the direct supervision of a trained, experienced supervisor. Personnel who completed their initial training more than 12 months prior to the start of the project must have completed an eight (8)-hour refresher course within the past 12 months. The FS must have completed an additional eight (8) hours of supervisory training and must have a current first-aid/CPR certificate (See Attachment 2).

#### 7.1.2 BASIC 40-HOUR COURSE

The following is a list of the topics typically covered in a 40-hour HAZWOPER training course:



- General safety procedures;
- Physical hazards (fall protection, noise, heat stress, cold stress);
- Names and job descriptions of key personnel responsible for site health and safety;
- Safety, health, and other hazards typically present at hazardous waste sites;
- Use, application, and limitations of PPE;
- Work practices by which employees can minimize risks from hazards;
- Safe use of engineering controls and equipment on site;
- Medical surveillance requirements;
- Recognition of symptoms and signs which might indicate overexposure to hazards;
- Worker right-to-know (Hazard Communication OSHA 1910.1200);
- Routes of exposure to contaminants;
- Engineering controls and safe work practices;
- Components of a health and safety program and a site-specific HASP;
- Decontamination practices for personnel and equipment;
- Confined-space entry procedures; and
- General emergency response procedures.

# 7.1.3 SUPERVISOR COURSE

Management and supervisors must receive an additional eight (8) hours of training, which typically includes:

- General Site safety and health procedures;
- PPE programs; and
- Air monitoring techniques

# 7.1.4 SITE-SPECIFIC TRAINING

Site-specific training will be accomplished by on-Site personnel reading this HASP, and through a thorough site briefing by the PM, FS, or SSO on the contents of this HASP before work begins. The review must include a discussion of the chemical, physical, and biological hazards; the protective equipment and safety procedures; and emergency procedures.

#### 7.1.5 DAILY SAFETY MEETINGS

Daily safety meetings will be held to cover the work to be accomplished, the hazards anticipated, the PPE and procedures required to minimize site hazards, and emergency procedures. The FS or SSO should present these meetings prior to beginning the day's fieldwork. No work will be performed in an EZ before a daily safety meeting has been held. An additional safety meeting must also be held prior to new tasks, or if new hazards are encountered. The daily safety meetings will be logged in the field notebook.

#### 7.1.6 FIRST AID AND CPR

At least one (1) employee current in first aid/CPR will be assigned to the work crew and will be on the Site during operations. Site records will document the presence of this individual. Refresher training in first aid (triennially) and CPR (annually) is required to keep the certificate



current. These individuals must also receive training regarding the precautions and protective equipment necessary to protect against exposure to blood-borne pathogens.

# 7.2 MEDICAL SURVEILLANCE

# 7.2.1 MEDICAL EXAMINATION

All personnel who are potentially exposed to Site contaminants must participate in a medical surveillance program as defined by OSHA at 29 CFR 1910.120 (f).

#### 7.2.2 PRE-PLACEMENT MEDICAL EXAMINATION

All potentially exposed personnel must have completed a comprehensive medical examination prior to assignment, and periodically thereafter as defined by applicable regulations. The pre-placement and periodic medical examinations typically include the following elements:

- Medical and occupational history questionnaire;
- Physical examination;
- Complete blood count, with differential;
- Liver enzyme profile;
- Chest X-ray, at a frequency determined by the physician;
- Pulmonary function test;
- Audiogram;
- Electrocardiogram for persons older than 45 years of age, or if indicated during the physical examination;
- Drug and alcohol screening, as required by job assignment;
- Visual acuity; and
- Follow-up examinations, at the discretion of the examining physician or the corporate medical director.

The examining physician provides the employee with a letter summarizing his findings and recommendations, confirming the worker's fitness for work and ability to wear a respirator. Documentation of medical clearance will be available for each employee during all project Site work.

Subcontractors will certify that all their employees have successfully completed a physical examination by a qualified physician. The physical examinations must meet the requirements of 29 CFR 1910.120 and 29 CFR 1910.134. Subcontractors will supply copies of the medical examination certificate for each on-site employee.

#### 7.2.3 OTHER MEDICAL EXAMINATIONS

In addition to pre-employment, annual, and exit physicals, personnel may be examined:


- At employee request after known or suspected exposure to toxic or hazardous materials; and
- At the discretion of the SSO, HSM, or occupational physician in anticipation of, or after known or suspected exposure to toxic or hazardous materials.

# 7.2.4 PERIODIC EXAM

Following the placement examination, all employees must undergo a periodic examination, similar in scope to the placement examination. For employees potentially exposed over 30 days per year, the frequency of periodic examinations will be annual. For employees potentially exposed less than 30 days per year, the frequency for periodic examinations will be 24 months.

### 7.2.5 MEDICAL RESTRICTION

When the examining physician identifies a need to restrict work activity, the employee's supervisor must communicate the restriction to the employee and the SSO. The terms of the restriction will be discussed with the employee and the supervisor.

# 8.0 GENERAL SAFETY PRACTICES

## 8.1 GENERAL SAFETY RULES

General safety rules for site activities include, but are not limited to, the following:

- At least one copy of this HASP must be in a location at the Site that is readily available to personnel, and all project personnel shall review the plan prior to starting work.
- Consume or use food, beverages, chewing gum, and tobacco products only in the SZ or other designated area outside the EZ and CRZ. Cosmetics shall not be applied in the EZ or CRZ.
- Wash hands before eating, drinking, smoking, or using toilet facilities.
- Wear all PPE as required and stop work and replace damaged PPE immediately.
- Secure disposable coveralls, boots, and gloves at the wrists and legs and ensure closure of the suit around the neck.
- Upon skin contact with materials that may be impacted by COCs, remove contaminated clothing and wash the affected area immediately. Contaminated clothing must be changed. Any skin contact with materials potentially impacted by COCs must be reported to the FS or SSO immediately. If needed, medical attention should be sought.
- Practice contamination avoidance. Avoid contact with surfaces either suspected or known to be impacted by COCs, such as standing water, mud, or discolored soil. Equipment must be stored on elevated or protected surfaces to reduce the potential for incidental contamination.
- Remove PPE as required in the CRZ to limit the spread of COC-containing materials.
- At the end of each shift or as required, dispose of all single-use coveralls, soiled gloves, and respirator cartridges in designated receptacles designated for this purpose.
- Removing soil containing Site COCs from protective clothing or equipment with compressed air, shaking, or any other means that disperses contaminants into the air is prohibited.
- Inspect all non-disposable PPE for contamination in the CRZ. Any PPE found to be contaminated must be decontaminated or disposed of appropriately.



- Recognize emergency signals used for evacuation, injury, fire, etc.
- Report all injuries, illnesses, and unsafe conditions or work practices to the FS or SSO.
- Use the "buddy system" during all operations requiring Level C PPE, and when appropriate, during Modified Level D operations.
- Obey all warning signs, tags, and barriers. Do not remove any warnings unless authorized to do so.
- Use, adjust, alter, and repair equipment only if trained and authorized to do so, and in accordance with the manufacturer's directions.
- Personnel are to perform only tasks for which they have been properly trained and will advise their supervisor if they have been assigned a task for which they are not trained.
- The presence or consumption of alcoholic beverages or illicit drugs during the workday, including breaks, is strictly prohibited. Notify your supervisor if you must take prescription or over-the-counter drugs that indicate they may cause drowsiness or, that you should not operate heavy equipment.
- Remain upwind during site activities whenever possible.

### 8.2 BUDDY SYSTEM

On-Site personnel must use the buddy system as required by operations. Use of the "buddy system" is required during all operations requiring Level C to Level A PPE, and when appropriate, during Level D operations. Crewmembers must observe each other for signs of chemical exposure, and heat or cold stress. Indications of adverse effects include, but are not limited to:

- Changes in complexion and skin coloration;
- Changes in coordination;
- Changes in demeanor;
- Excessive salivation and pupillary response; and
- Changes in speech pattern.

Crewmembers must also be aware of the potential exposure to possible safety hazards, unsafe acts, or non-compliance with safety procedures.

Field personnel must inform their partners or fellow crewmembers of non-visible effects of exposure to toxic materials that they may be experiencing. The symptoms of such exposure may include, but are not limited to:

- Headaches;
- Dizziness;
- Nausea;
- Blurred vision;
- Cramps; and
- Irritation of eyes, skin, or respiratory tract.





If protective equipment or noise levels impair communications, prearranged hand signals must be used for communication. Personnel must stay within line of sight of another team member.

## 8.3 HEAT STRESS

Heat stress is caused by a number of interacting factors, including environmental conditions, clothing, workload, etc., as well as the physical and conditioning characteristics of the individual. Since heat stress is one of the most common illnesses associated with heavy outdoor work conducted with direct solar load and, in particular, because wearing PPE can increase the risk of developing heat stress, workers must be capable of recognizing the signs and symptoms of heat-related illnesses. Personnel must be aware of the types and causes of heat-related illnesses and be able to recognize the signs and symptoms of these illnesses in both themselves and their co-workers.

*Heat rashes* are one of the most common problems in hot work environments. Commonly known as prickly heat, a heat rash is manifested as red papules and usually appears in areas where the clothing is restrictive. As sweating increases, these papules give rise to a prickling sensation. Prickly heat occurs in skin that is persistently wetted by unevaporated sweat, and heat rash papules may become infected if they are not treated. In most cases, heat rashes will disappear when the affected individual returns to a cool environment.

*Heat cramps* are usually caused by performing hard physical labor in a hot environment. These cramps have been attributed to an electrolyte imbalance caused by sweating. It is important to understand that cramps can be caused both by too much or too little salt.

Cramps appear to be caused by the lack of water replenishment. Because sweat is a hypotonic solution (plus or minus 0.3% NaCl), excess salt can build up in the body if the water lost through sweating is not replaced. Thirst cannot be relied on as a guide to the need for water; instead, water must be taken every 15 to 20 minutes in hot environments.

Under extreme conditions, such as working for six (6) to eight (8) hours in heavy protective gear, a loss of sodium may occur. Drinking commercially available carbohydrate electrolyte replacement liquids is effective in minimizing physiological disturbances during recovery.

*Heat exhaustion* occurs from increased stress on various body organs due to inadequate blood circulation, cardiovascular insufficiency, or dehydration. Signs and symptoms include pale, cool, moist skin; heavy sweating; dizziness; nausea; headache, vertigo, weakness, thirst, and giddiness. Fortunately, this condition responds readily to prompt treatment.

Heat exhaustion should not be dismissed lightly, however, for several reasons. One is that the fainting associated with heat exhaustion can be dangerous because the victim may be operating machinery or controlling an operation that should not be left unattended; moreover, the victim may be injured when he or she faints. Also, the signs and symptoms seen in heat exhaustion are similar to those of heat stroke, which is a medical emergency.



Workers suffering from heat exhaustion should be removed from the hot environment, be given fluid replacement, and be encouraged to get adequate rest.

*Heat stroke* is the most serious form of heat stress. Heat stroke occurs when the body's system of temperature regulation fails and the body's temperature rises to critical levels. This condition is caused by a combination of highly variable factors, and its occurrence is difficult to predict. Heat stroke is a medical emergency. The primary signs and symptoms of heat stroke are confusion; irrational behavior; loss of consciousness; convulsions; a lack of sweating (usually); hot, dry skin; and an abnormally high body temperature, e.g., a rectal temperature of 41°C (105.8°F). If body temperature is too high, it causes death. The elevated metabolic temperatures caused by a combination of workload and environmental heat load, both of which contribute to heat stroke, are also highly variable and difficult to predict.

If a worker shows signs of possible heat stroke, professional medical treatment should be obtained immediately. The worker should be placed in a shady area and the outer clothing should be removed. The worker's skin should be wetted and air movement around the worker should be increased to improve evaporative cooling until professional methods of cooling are initiated and the seriousness of the condition can be assessed. Fluids should be replaced as soon as possible. The medical outcome of an episode of heat stroke depends on the victim's physical fitness and the timing and effectiveness of first aid treatment.

Regardless of the worker's protestations, no employee suspected of being ill from heat stroke should be sent home or left unattended unless a physician has specifically approved such an order.

Proper training and preventive measures will help avert serious illness and loss of work productivity. Preventing heat stress is particularly important because once someone suffers from heat stroke or exhaustion, that person may be predisposed to additional heat injuries.

#### 8.4 HEAT STRESS SAFETY PRECAUTIONS

Heat stress monitoring and work rest cycle implementation should commence when the ambient adjusted temperature exceeds 72°F. A minimum work rest regimen and procedures for calculating ambient adjusted temperature are described in **Table 8.1** below.

Adjusted Temperature <sup>b</sup>	Work/Rest Regimen Normal Work Ensemble <sup>c</sup>	Work/Rest Regimen Impermeable Ensemble
90°F (32.2°C) or above	After each 45 minutes of work	After each 15 minutes of work
87.5° - 90°F (30.8°-32.2°C)	After each 60 minutes of work	After each 30 minutes of work
82.5° - 87.5°F (28.1° - 30.8°C)	After each 90 minutes of work	After each 60 minutes of work

### Table 8.1 – Work/Rest Schedule



Adjusted Temperature <sup>b</sup>	Work/Rest Regimen Normal Work Ensemble <sup>c</sup>	Work/Rest Regimen Impermeable Ensemble
77.5° - 82.5°F (25.3° - 28.1°C)	After each 120 minutes of work	After each 90 minutes of work
72.5° - 77.5°F (30.8° - 32.2°C)	After each 150 minutes of work	After each 120 minutes of work

a. For work levels of 250 kilocalories/hour (Light-Moderate Type of Work)

- b. Calculate the adjusted air temperature (ta adj) by using this equation: ta adj °F = ta °F + (13 x % sunshine). Measure air temperature (ta) with a standard mercury-in-glass thermometer, with the bulb shielded from radiant heat. Estimate percent sunshine by judging what percent time the sun is not covered by clouds that are thick enough to produce a shadow. (100 percent sunshine = no cloud cover and a sharp, distinct shadow; 0 percent sunshine = no shadows.)
- c. A normal work ensemble consists of cotton coveralls or other cotton clothing with long sleeves and pants.
- d. The information presented above was generated using the information provided in the American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Values (TLV) Handbook.

In order to determine if the work rest cycles are adequate for the personnel and specific Site conditions, additional monitoring of individual heart rates will be conducted during the rest cycle. To check the heart rate, count the radial pulse for 30 seconds at the beginning of the rest period. If the heart rate exceeds 110 beats per minute, shorten the next work period by one third and maintain the same rest period.

Additionally, one or more of the following control measures can be used to help control heat stress and are mandatory if any Site worker has a heart rate (measure immediately prior to rest period) exceeding 115 beats per minute:

- Site workers will be encouraged to drink plenty of water and electrolyte replacement fluids throughout the day.
- On-Site drinking water will be kept cool (50 to 60°F).
- A work regimen that will provide adequate rest periods for cooling down will be established, as required.
- All personnel will be advised of the dangers and symptoms of heat stroke, heat exhaustion, and heat cramps.
- Cooling devices, such as vortex tubes or cooling vests, should be used when personnel must wear impermeable clothing in conditions of extreme heat.
- Employees should be instructed to monitor themselves and co-workers for signs of heat stress and to take additional breaks as necessary.
- A shaded rest area must be provided. All breaks should take place in the shaded rest area.
- Employees must not be assigned to other tasks during breaks.
- Employees must remove impermeable garments during rest periods. This includes white Tyvek-type garments.

All employees must be informed of the importance of adequate rest, acclimation, and proper diet in the prevention of heat stress disorders.



# 8.5 COLD STRESS

Cold stress normally occurs in temperatures at or below freezing, or under certain circumstances, in temperatures of 40°F. Extreme cold for a short time may cause severe injury to exposed body surfaces or result in profound generalized cooling, causing death. Areas of the body that have high surface area-to-volume ratio, such as fingers, toes, and ears, are the most susceptible. Two (2) factors influence the development of a cold weather injury: ambient temperature and the velocity of the wind. For instance, 10°F with a wind of 15 miles per hour (mph) is equivalent in chilling effect to still air at -18°F. An equivalent chill temperature chart relating the actual dry bulb temperature and wind velocity is presented in **Table 8.2** below.

	Actua	Actual Temperature Reading (°F)										
Estimated Wind Speed (in mph)	50	40	30	20	10	0	-10	-20	-30	-40	-50	-60
	Equiv	alent Cl	hill Tem	perature	e (⁰F)							
Calm	50	40	30	20	10	0	-10	-20	-30	-40	-50	-60
5	48	37	27	16	6	-5	-15	-26	-36	-47	-57	-68
10	40	28	16	4	-9	-24	-33	-46	-58	-70	-83	-95
15	36	22	9	-5	-18	-32	-45	-58	-72	-85	-99	-112
20	32	18	4	-10	-25	-39	-53	-67	-82	-96	-110	-121
25	30	16	0	-15	-29	-44	-59	-74	-88	-104	-118	-133
30	28	13	-2	-18	-33	-48	-63	-79	-94	-109	-125	-140
35	27	11	-4	-20	-35	-51	-67	-82	-98	-113	-129	-145
40	26	10	-6	-21	-37	-53	-69	-85	-100	-116	-132	-148
(Wind speeds	LITTLE DANGER				INCREASING			GREAT DANGER				
mph have little additional effect.)	Maxir sense	num da e of seci	anger c urity.	of false	Dange of e within	er from exposed one mi	freezing flesh nute.	Flesh secon	may ds.	freeze	with	in 30
	Trenc	Trench foot and immersion foot may occur at any point on this chart.										

# Table 8.2– Wind Chill Temperature Chart

[This chart was developed by the U.S. Army Research Institute of Environmental Medicine, Natick, MA (Source: ACGIH Threshold Limit Values for Chemical Substances and Physical Agents)].

Local injury resulting from cold is included in the generic term frostbite. There are several degrees of tissue damage associated with frostbite. Frostbite of the extremities can be categorized into:



- Frost Nip or Incipient Frostbite characterized by sudden blanching or whitening of skin.
- *Superficial Frostbite* skin has a waxy or white appearance and is firm to the touch, but tissue beneath is resilient.
- *Deep Frostbite* tissues are cold, pale, and solid; extremely serious injury.

Systemic hypothermia is caused by exposure to freezing or rapidly dropping temperature. It can be fatal. Its symptoms are usually exhibited in five stages: 1) shivering; 2) apathy, listlessness, sleepiness, and (sometimes) rapid cooling of the body to less than 95°F; 3) unconsciousness, glassy stare, slow pulse, and slow respiratory rate; 4) freezing of the extremities; and 5) death. Trauma sustained in freezing or sub-zero conditions requires special attention because an injured worker is predisposed to secondary cold injury. Special provisions must be made to prevent hypothermia and secondary freezing of damaged tissues in addition to providing for first aid treatment. To avoid cold stress, site personnel must wear protective clothing appropriate for the level of cold and physical activity. In addition to protective clothing, preventive safe work practices, additional training, and warming regimens may be utilized to prevent cold stress.

### 8.6 SAFETY PRECAUTIONS FOR COLD STRESS PREVENTION

For air temperature of 0°F or less, mittens should be used to protect the hands. For exposed skin, continuous exposure should not be permitted when air speed and temperature results in a wind chill temperature of -25°F.

At air temperatures of 36°F or less, field personnel who become immersed in water or whose clothing becomes wet must be immediately provided with a change of clothing and be treated for hypothermia.

If work is done at normal temperature or in a hot environment before entering the cold, the field personnel must ensure that their clothing is not wet as a consequence of sweating. Wet field personnel must change into dry clothes prior to entering the cold area.

If the available clothing does not give adequate protection to prevent hypothermia or frostbite, work must be modified or suspended until adequate clothing is made available or until weather conditions improve.

Field personnel handling evaporative liquid (e.g., gasoline, alcohol, or cleaning fluids) at air temperatures below 40°F must take special precaution to avoid soaking of clothing or gloves with the liquids because of the added danger of cold injury due to evaporative cooling.

### 8.7 SAFE WORK PROCEDURES

Direct contact between bare skin and cold surfaces (< 20°F) should be avoided. Metal tool handles and/or equipment controls should be covered by thermal insulating material.



For work performed in a wind chill temperature at or below 10°F, workers should be under constant protective observation (buddy system). The work rate should be established to prevent heavy sweating that will result in wet clothing. For heavy work, rest periods must be taken in heated shelters and workers should be provided with an opportunity to change into dry clothing if needed.

Field personnel should be provided the opportunity to become accustomed to cold-weather working conditions and required protective clothing. Work should be arranged in such a way that sitting or standing still for long periods is minimized.

During the warming regimen (rest period), field personnel should be encouraged to remove outer clothing to permit sweat evaporation or to change into dry work clothing. Dehydration, or loss of body fluids, occurs insidiously in the cold environment and may increase susceptibility to cold injury due to a significant change in blood flow to the extremities. Fluid replacement with warm, sweet drinks and soups is recommended. The intake of coffee should be limited because of diuretic and circulatory effects.

### 8.8 BIOLOGICAL HAZARDS

Biological hazards may include poison ivy, snakes, thorny bushes and trees, ticks, mosquitoes, spiders, and other pests.

### 8.8.1 TICK BORNE DISEASES

*Lyme Disease* - The disease commonly occurs in summer and is transmitted by the bite of infected ticks. "Hot spots" in the United States include New York, New Jersey, Pennsylvania, Massachusetts, Connecticut, Rhode Island, Minnesota, and Wisconsin.

*Erlichiosis* - The disease also commonly occurs in summer and is transmitted by the bite of infected ticks. "Hot spots" in the United States include New York, Massachusetts, Connecticut, Rhode Island, Minnesota, and Wisconsin.

These diseases are transmitted primarily by the deer tick, which is smaller and redder than the common wood tick. The disease may be transmitted by immature ticks, which are small and hard to see. The tick may be as small as a period on this page.

Symptoms of Lyme disease include a rash or a peculiar red spot, like a bull's eye, which expands outward in a circular manner. The victim may have headache, weakness, fever, a stiff neck, and swelling and pain in the joints, and eventually, arthritis. Symptoms of erlichiosis include muscle and joint aches, flu-like symptoms, but there is typically no skin rash.

*Rocky Mountain Spotted Fever (RMSF)* - This disease is transmitted via the bite of an infected tick. The tick must be attached 4 to 6 hours before the disease-causing organism (Rickettsia rickettsii) becomes reactivated and can infect humans. The primary symptom of RMSF is the



sudden appearance of a moderate-to-high fever. The fever may persist for two to three weeks. The victim may also have a headache, deep muscle pain, and chills. A rash appears on the hands and feet on about the third day and eventually spreads to all parts of the body. For this reason, RMSF may be confused with measles or meningitis. The disease may cause death, if untreated, but if identified and treated promptly, death is uncommon.

*Control* - Tick repellant containing diethyltoluamide (DEET) should be used when working in tickinfested areas, and pant legs should be tucked into boots. In addition, workers should search the entire body every three or four hours for attached ticks. Ticks should be removed promptly and carefully without crushing, since crushing can squeeze the disease-causing organism into the skin. A gentle and steady pulling action should be used to avoid leaving the head or mouth parts in the skin. Hands should be protected with surgical gloves when removing ticks.

### 8.8.2 POISONOUS PLANTS

Poisonous plants may be present in the work area. Personnel should be alerted to its presence and instructed on methods to prevent exposure.

*Control* - The main control is to avoid contact with the plant, cover arms and hands, and frequently wash potentially exposed skin. Particular attention must be given to avoiding skin contact with objects or protective clothing that have touched the plants. Treat every surface that may have touched the plant as contaminated, and practice contamination avoidance. If skin contact is made, the area should be washed immediately with soap and water and observed for signs of reddening.

#### 8.8.3 SNAKES

The possibility of encountering snakes exists, specifically for personnel working in wooded/vegetated areas. Snake venoms are complex and include proteins, some of which have enzymatic activity. The effects produced by venoms include neurotoxic effects with sensory, motor, cardiac, and respiratory difficulties; cytotoxic effects on red blood cells, blood vessels, heart muscle, kidneys, and lungs; defects in coagulation; and effects from local release of substances by enzymatic actions. Other noticeable effects of venomous snakebites include swelling, edema, and pain around the bite, and the development of ecchymosis (the escape of blood into tissues from ruptured blood vessels).

*Control* - To minimize the threat of snakebites, all personnel walking through vegetated areas must be aware of the potential for encountering snakes, and the need to avoid actions potentiating encounters, such as turning over logs, etc. If a snakebite occurs, an attempt should be made to safely identify the snake via size and markings. The victim must be transported to the nearest hospital within 30 minutes; first aid consists of applying a constriction band and washing the area around the wound to remove any unabsorbed venom.

#### 8.8.4 SPIDERS

Personnel may encounter spiders during work activities.



Two spiders are of concern: the black widow and the brown recluse. Both prefer dark sheltered areas such as basements, equipment sheds and enclosures, and around woodpiles or other scattered debris. The black widow is shiny black, approximately one inch long, and has a distinctive red hourglass marking on the underside of its body. The black widow is found throughout the United States. The bite of a black widow is seldom fatal to healthy adults, but effects include respiratory distress, nausea, vomiting, and muscle spasms. The brown recluse is smaller than the black widow and gets its name from its brown coloring and behavior. It has a distinctive violin shape on the top of its body. The brown recluse is more prevalent in the southern United States. The bite of the brown recluse is painful and the bite site ulcerates and takes many weeks to heal completely.

*Control* - To minimize the threat of spider bites, all personnel walking through vegetated areas must be aware of the potential for encountering these arachnids. Personnel need to avoid actions that may result in encounters, such as turning over logs, and placing hands in dark places such as behind equipment or in corners of equipment sheds or enclosures. If a spider bite occurs, the victim must be transported to the nearest hospital as soon as possible; first aid consists of applying ice packs and washing the area around the wound to remove any unabsorbed venom.

### 8.9 NOISE

Exposure to noise over the OSHA action level can cause temporary impairment of hearing; prolonged and repeated exposure can cause permanent damage to hearing. The risk and severity of hearing loss increases with the intensity and duration of exposure to noise. In addition to damaging hearing, noise can impair voice communication, thereby increasing the risk of accidents on site.

*Control* - All personnel must wear hearing protection, with a Noise Reduction Rating (NRR) of at least 20, when noise levels exceed 85 dBA. When it is difficult to hear a co-worker at normal conversation distance, the noise level is approaching or exceeding 85 dBA, and hearing protection is necessary. All site personnel who may be exposed to noise must also receive baseline and annual audiograms and training as to the causes and prevention of hearing loss. Noise monitoring is discussed in Section 5.2, Noise Monitoring.

Whenever possible, equipment that does not generate excessive noise levels will be selected for this project. If the use of noisy equipment is unavoidable, barriers or increased distance will be used to minimize worker exposure to noise, if feasible.

All personnel must take every precaution to minimize the potential for spills during site operations. All on-Site personnel shall immediately report any discharge, no matter how small, to the FS.

Spill control equipment and materials will be located on the Site at locations that present the potential for discharge. All sorbent materials used for the cleanup of spills will be containerized and labeled appropriately. In the event of a spill, the FS will follow the provisions in Section 10.0, Emergency Procedures, to contain and control released materials and to prevent their spread to off-Site areas.



# 8.10 SPILL CONTROL

All personnel must take every precaution to minimize the potential for spills during site operations. All on-Site personnel shall immediately report any discharge, no matter how small, to the FS.

Spill control equipment and materials will be located on the Site at locations that present the potential for discharge. All sorbent materials used for the cleanup of spills will be containerized and labeled appropriately. In the event of a spill, the FS will follow the provisions in Section 10.0, Emergency Procedures, to contain and control released materials and to prevent their spread to off-Site areas.

### 8.11 SANITATION

Site sanitation will be maintained according to OSHA requirements.

### 8.11.1 BREAK AREA

Breaks must be taken in the SZ, away from the active work area after Site personnel go through decontamination procedures. There will be no smoking, eating, drinking, or chewing gum or tobacco in any area other than the SZ.

### 8.11.2 POTABLE WATER

The following rules apply to all field operations:

- An adequate supply of potable water will be provided at each project site. Potable water must be kept away from hazardous materials or media, and contaminated clothing or equipment.
- Portable containers used to dispense drinking water must be capable of being tightly closed and must be equipped with a tap dispenser. Water must not be consumed directly from the container (drinking from the tap is prohibited) nor may it be removed from the container by dipping.
- Containers used for drinking water must be clearly marked and shall not be used for any other purpose.
- Disposable drinking cups must be provided. A sanitary container for dispensing cups and a receptacle for disposing of used cups is required.

### 8.11.3 SANITARY FACILITIES

Access to facilities for washing before eating, drinking, or smoking, or alternate methods such as waterless hand-cleaner and paper towels will be provided.

#### 8.11.4 LAVATORY

If permanent toilet facilities are not available, an appropriate number of portable chemical toilets will be provided. This requirement does not apply to mobile crews or to normally unattended Site



locations so long as employees at these locations have transportation immediately available to nearby toilet facilities.

## 8.12 EMERGENCY EQUIPMENT

Adequate emergency equipment for the activities being conducted on site and as required by applicable sections of 29 CFR 1910 and 29 CFR 1926 will be on Site prior to the commencement of project activities. Personnel will be provided with access to emergency equipment, including, but not limited to, the following:

- Fire extinguishers of adequate size, class, number, and location as required by applicable sections of 29 CFR 1910 and 1926;
- Industrial first aid kits of adequate size for the number of personnel on site; and
- Emergency eyewash and/or shower if required by operations being conducted on Site.

### 8.13 LOCKOUT/TAGOUT PROCEDURES

Only fully qualified and trained personnel will perform maintenance procedures. Before maintenance begins, lockout/tagout procedures per OSHA 29 CFR 1910.147 will be followed.

Lockout is the placement of a device that uses a positive means, such as lock, to hold an energy or material-isolating device such that the equipment cannot be operated until the lockout device is removed. If a device cannot be locked out, a tagout system shall be used. Tagout is the placement of a warning tag on an energy or material isolating device indicating that the equipment controls may not be operated until the personnel who attached the tag remove the tag.

#### 8.14 ELECTRICAL SAFETY

Electricity may pose a particular hazard to Site workers due to the use of portable electrical equipment. If wiring or other electrical work is needed, a qualified electrician must perform it.

General electrical safety requirements include:

- All electrical wiring and equipment must be a type listed by Underwriters Laboratories (UL), Factory Mutual Engineering Corporation (FM), or other recognized testing or listing agency.
- All installations must comply with the National Electrical Safety Code (NESC), the National Electrical Code (NEC), or USCG regulations.
- Portable and semi-portable tools and equipment must be grounded by a multi-conductor cord having an identified grounding conductor and a multi-contact polarized plug-in receptacle.
- Tools protected by an approved system of double insulation, or its equivalent, need not be grounded. Double insulated tools must be distinctly marked and listed by UL or FM.
- Live parts of wiring or equipment must be guarded to prevent persons or objects from touching them.



- Electric wire or flexible cord passing through work areas must be covered or elevated to protect it from damage by foot traffic, vehicles, sharp corners, projections, or pinching.
- All circuits must be protected from overload.
- Temporary power lines, switchboxes, receptacle boxes, metal cabinets, and enclosures around equipment must be marked to indicate the maximum operating voltage.
- Plugs and receptacles must be kept out of water unless of an approved submersible construction.
- All extension cord outlets must be equipped with ground fault circuit interrupters (GFCI).
- Attachment plugs or other connectors must be equipped with a cord grip and be constructed to endure rough treatment.
- Extension cords or cables must be inspected prior to each use and replaced if worn or damaged. Cords and cables must not be fastened with staples, hung from nails, or suspended by bare wire.
- Flexible cords must be used only in continuous lengths without splice, with the exception of molded or vulcanized splices made by a qualified electrician.

## 8.15 LIFTING SAFETY

Using proper lifting techniques may prevent back strain or injury. The fundamentals of proper lifting include:

- Consider the size, shape, and weight of the object to be lifted. A mechanical lifting device or additional persons must be used to lift an object if it cannot be lifted safely alone.
- The hands and the object should be free of dirt or grease that could prevent a firm grip.
- Gloves must be used, and the object inspected for metal slivers, jagged edges, burrs, or rough or slippery surfaces.
- Fingers must be kept away from points that could crush or pinch them, especially when putting an object down.
- Feet must be placed far enough apart for balance. The footing should be solid and the intended pathway should be clear.
- The load should be kept as low as possible, close to the body with the knees bent.
- To lift the load, grip firmly and lift with the legs, keeping the back as straight as possible.
- A worker should not carry a load that he or she cannot see around or over.
- When putting an object down, the stance and position are identical to that for lifting; the legs are bent at the knees, and the back is straight as the object is lowered.

# 8.16 LADDER SAFETY

When portable ladders are used for access to an upper landing surface, the ladder side rails shall extend at least three (3) feet (9 m) above the upper landing surface to which the ladder is used to gain access; or, when such an extension is not possible because of the ladder's length, then the ladder shall be secured at its top to a rigid support that will not deflect, and a grasping device, such as a grabrail, shall be provided to assist employees in mounting and dismounting the ladder. In no case shall the extension be such that ladder deflection under a load would, by itself, cause the ladder to slip off its support.

• Ladders shall be maintained free of oil, grease, and other slipping hazards.



- Ladders shall not be loaded beyond the maximum intended load for which they were built, or beyond their manufacturer's rated capacity.
- Ladders shall be used only for the purpose for which they were designed.
- Non-self-supporting ladders shall be used at an angle such that the horizontal distance from the top support to the foot of the ladder is approximately one-quarter of the working length of the ladder (the distance along the ladder between the foot and the top support).
- Wood job-made ladders with spliced side rails shall be used at an angle such that the horizontal distance is one-eighth the working length of the ladder.
- Fixed ladders shall be used at a pitch no greater than 90 degrees from the horizontal, as measured to the back side of the ladder.
- Ladders shall be used only on stable and level surfaces unless secured to prevent accidental displacement.
- Ladders shall not be used on slippery surfaces unless secured or provided with slipresistant feet to prevent accidental displacement. Slip-resistant feet shall not be used as a substitute for care in placing, lashing, or holding a ladder that is used upon slippery surfaces, including, but not limited to, flat metal or concrete surfaces that are constructed so they cannot be prevented from becoming slippery.
- Ladders placed in any location where they can be displaced by workplace activities or traffic, such as in passageways, doorways, or driveways, shall be secured to prevent accidental displacement, or a barricade shall be used to keep the activities or traffic away from the ladder.
- The area around the top and bottom of ladders shall be kept clear.
- The top of a non-self-supporting ladder shall be placed with the two rails supported equally unless it is equipped with a single support attachment.
- Ladders shall not be moved, shifted, or extended while occupied.
- Ladders shall have non-conductive side rails if they are used where the employee or the ladder could contact exposed energized electrical equipment.
- The top, top step, or the step labeled that it or any step above it should not be used as a step.
- Cross-bracing on the rear section of stepladders shall not be used for climbing unless the ladders are designed and provided with steps for climbing on both front and rear sections.
- Ladders shall be inspected by the HSM for visible defects on a daily basis and after any occurrence that could affect their safe use.
- Portable ladders with structural defects, such as, but not limited to, broken or missing rungs, cleats, or steps; broken or split rails; corroded components; or other faulty or defective components shall either be immediately marked in a manner that readily identifies them as defective or be tagged with "Do Not Use" or similar language and shall be withdrawn from service.
- Fixed ladders with structural defects, such as, but not limited to, broken or missing rungs, cleats, or steps; broken or split rails; or corroded components; shall be withdrawn from service.
- Ladder repairs shall restore the ladder to a condition meeting its original design criteria, before the ladder is returned to use.
- Single-rail ladders shall not be used.
- When ascending or descending a ladder, the user shall face the ladder.
- Each employee shall use at least one hand to grasp the ladder when progressing up and/or down the ladder.
- An employee shall not carry any object or load that could cause the employee to lose balance and fall.



# 8.17 TRAFFIC SAFETY

The project Site may be located adjacent to a public roadway where exposure to vehicular traffic is likely. Traffic may also be encountered as vehicles enter and exit the area. To minimize the likelihood of project personnel and activities being affected by traffic, the following procedures will be implemented.

Cones must be placed along the shoulder of the roadway starting 100 feet from the work area to alert passing motorists to the presence of personnel and equipment. A "Slow" or "Men Working" sign must be placed at the first cone. Barricades with flashing lights should be placed between the roadway and the work area.

During activities along a roadway, equipment will be aligned parallel to the roadway to the extent feasible, facing into the oncoming traffic so as to place a barrier between the work crew and the oncoming traffic. All crewmembers must remain behind the equipment and the traffic barrier.

All Site personnel who are potentially exposed to vehicular traffic must wear an outer layer of orange warning garments, such as vests, jackets, or shirts. If work is performed in hours of dusk or darkness, workers will be outfitted with reflective garments either orange, white (including silver-coated reflective coatings or elements that reflect white light), yellow, fluorescent red-orange, or fluorescent yellow-orange.

The flow of traffic into and out of the adjacent business must be assessed, and precautions taken to warn motorists of the presence of workers and equipment. Where possible, vehicles should be aligned to provide physical protection of people and equipment.

### 9.0 SITE-SPECIFIC HAZARDS AND CONTROL MEASURES

### 9.1 EVALUATION OF HAZARDS

The evaluation of hazards is provided as a quick reference as to the known conditions for the Site, wherein the level of detail for each of the subsections is identified.

### 9.1.1 HAZARD CHARACTERISTICS

Existing information for Site:

X Detailed Preliminary None

Hazardous/Contaminated Material Form(s):

<u>X</u>Solid <u>X</u>Liquid <u>Sludge</u>Gas <u>X</u>Vapor

Containment Type(s):

				Health an	d Safety	Plan		Project 12345 1-99 Franklin Court Tarrytown, New York
Drum	Т	ank	Pit		_ Debr	ris		
Pond	La	agoon	Othe	r: None	known			
Hazardous Ma	aterial Cha	racteristi	cs:					
X	Volatile Radioact	ive		Corro	sive		Rea	ctive
	_ Ignitable		Х	Toxic		Х	Unknown	
Routes of Exp	osure:							
X	Oral	De	rmal		Х	Eye	Х	Respiratory
9.1.2 POTENT		LTH AND	SAFET	Y HAZA	RDS			
X	Heat	<u>X</u> Cor	igested a	areas				
X	Cold	Х	Gen	eral Con	structio	on		
	Confined	l space e	ntry	Х	_ Phys	sical injur	у	
	Oxygen	depletion		Х	_ Elec	trical haz	ards	
	Asphyxia	ation	Х	Hand	ling an	d produc	t transfer	
X	Excavati	on	Х	Fire				
X	Cave-ins		Х	Explo	sion			
X	Falls, slip	opage		Х	Biolo	ogical Ha	zards	
		-	X	Plants –	Poison	n Ivy, Pois	son Oak	
			X	Insects -	- Ticks	-		

### 9.2 FIELD ACTIVITIES, HAZARDS AND CONTROL PROCEDURES

Other: Potential Ignition Hazard

X Heavy equipment

The following task-specific safety analyses identify potential health, safety, and environmental hazards associated with each type of field activity. Because of the complex and changing nature of field projects, supervisors must continually inspect the Site to identify hazards that may affect on-Site personnel, the community, or the environment. The FS must be aware of these changing conditions and discuss them with the PM whenever these changes impact employee health, safety, the environment, or performance of the project. The FS will keep on-Site personnel informed of the changing conditions, and the PM will write and/or approve addenda or revisions to this HASP as necessary.

X Insects – Mosquitoes

X Rats and Mice

X Insects – Bees and Wasps

\_\_\_\_ Non-ionizing Radiation (i.e. UV, IR, etc.)



# 9.2.1 MOBILIZATION/CONSTRUCTION STAKEOUT

### Description of Tasks

Site mobilization will include establishing excavation locations, determining the location of utilities and other installations, and establishing work areas. Mobilization will also include setting up equipment and establishing a temporary Site office. A break area will be set up outside of regulated work areas. Mobilization may involve clearing areas for the SZ and CRZ. During this initial phase, project personnel will walk the Site to confirm the existence of anticipated hazards and identify safety and health issues that may have arisen since the writing of this plan.

#### Hazard Identification

The hazards of this phase of activity are associated with heavy equipment operation, manual materials handling, installation of temporary on-site facilities, and manual site preparation.

Manual materials handling and manual site preparation may cause blisters, sore muscles, and joint and skeletal injuries; and may present eye, contusion, and laceration hazards. Installation of temporary field office and support facilities may expose personnel to electrical hazards, underground and overhead utilities, and physical injury due to the manual lifting and moving of materials. The work area presents slip, trip, and fall hazards from scattered debris and irregular walking surfaces. Rainy weather may cause wet, muddy, slick walking surfaces, and unstable soil. Freezing weather hazards include frozen, slick, and irregular walking surfaces.

Environmental hazards include plants, such as poison ivy and poison oak; aggressive fauna, such as ticks, fleas, mosquitoes, wasps, spiders, and snakes; weather, such as sunburn, lightning, rain, and heat- or cold-related illnesses; and pathogens, such as rabies, Lyme disease, and blood-borne pathogens.

#### <u>Controls</u>

Control procedures for these hazards are discussed in Section 8.0, General Safety Practices.

### 9.2.2 DEMOLITION/SITE-CLEARING

#### Description of Tasks

Site clearance will involve manual or mechanical removal of objects impeding access to the construction footprint. These obstructions are both natural and man-made items and will include, but not be limited to, fabricated metal and concrete structures, trees, vegetation, rubble, and miscellaneous trash/debris.

#### Hazard Identification

Hazards associated with demolition and site clearance include personnel working in and around potentially unstable structures, or locations of potential contact with hazardous chemicals, utilities, and/or falling objects. This task will involve manual, as well as mechanical demolition/clearance efforts so exertion and equipment hazards exist.



# <u>Controls</u>

*PPE* – Personnel shall be protected from hazards of irritant and toxic plants and suitably instructed in the first aid treatment available.

*Preparatory Operations* – Prior to permitting employees to start demolition operations, an engineering survey shall be made, by a licensed Professional Engineer, of the structure to determine the stability of the structure. Any adjacent structure shall where personnel may be exposed shall also be similarly checked. The PO shall have in writing evidence that such a survey has been performed. All structural instabilities shall be shored or braced, under the supervision of a licensed Professional Engineer, prior to access by an FP.

*Utilities* – All electric, gas, water, steam, sewer, and other service lines shall be shut off, caped, or otherwise controlled, outside the building line before demolition work is started. In each case, any utility company that is involved shall be notified in advance. If it is necessary to maintain any power, water or other utilities during demolition, such lines shall be temporarily relocated, as necessary.

*Hazardous Substances* – It shall also be determined if any type of hazardous chemicals, gases, explosives, flammable materials, or similarly dangerous substances have been used in any pipes, tanks, or other equipment on the property. When the presence of any such substances is apparent or suspected, testing and purging shall be performed and the hazard eliminated before demolition is started.

*Falling Debris/Objects* – No material shall be dropped to any point lying outside the exterior walls of the structure unless the area is effective protected. Access to the area where falling objects/debris may be encountered must be gated and controlled.

*Structural Collapse* – Structural or load supporting members on any floor shall not be cut or removed until all stories above such a floor have been demolished and removed. Walls, which are to serve as retaining walls against which debris will be piled, shall not be so used unless capable of safely supporting the imposed load. Mechanical equipment shall not be used on floors or working surfaces unless such floors or surfaces are not of sufficient strength to support the imposed load.

*Rollover Guards* – All equipment used in site clearing operations shall be equipped with rollover guards meeting the applicable requirements. In addition, rider-operated equipment shall be equipped with an overhead and rear canopy guard meeting the applicable requirements.

*Inspections* – During demolition, continuing inspections by a licensed Professional Engineer shall be made as the work progresses to detect hazards resulting from weakened or deteriorated floors, walls, or loosened material. No FP shall be permitted to work where such hazards exist until they are corrected by shoring, bracing, or other effective means.



# 9.2.3 EXCAVATION AND CUT/FILL OPERATIONS

# 9.2.3.1 EXCAVATION TRENCHING

### Description of Tasks

This task includes the excavation of contaminated soils and superficial debris. Excavation depths vary across the Site.

### Hazard Identification

The hazards of this activity are associated with heavy equipment operation, subsurface intrusion, manual materials handling, stockpiling, and disposal. Subsurface intrusion presents hazards associated with negotiating buried utilities, cave-ins of the excavated areas, and regress methods for personnel working inside the excavated areas. Disruption of contaminated soil also presents a health hazard.

### <u>Controls</u>

*Underground Utilities* – The estimated locations of utility installations, such as sewer, telephone, fuel, electric, water lines, or any other underground installations that reasonably may be expected to be encountered during the excavation work, shall be determined prior to opening an excavation. Utility companies or owners shall be contacted ("Call Before You Dig") within established or customary local response times, advised of the proposed work, and asked to establish the location of the utility underground installations prior to the start of actual excavation.

When excavation operations approach the estimated location of underground installations, the exact location of the installations shall be determined by save and acceptable means. While the excavation is open, underground installations shall be protected, supported, or removed, as necessary, to safeguard site personnel.

*Cave-Ins* – Project personnel in an excavation shall be protected from cave-ins by an adequate protective system, except when:

- Excavations are made entirely in stable rock or excavations are less than five feet in depth and examination of the ground by the SSO provides no indication of a potential cave-in.
- Protective systems shall have the capacity to resist, without failure, all loads that are intended or could reasonably be expected to be applied or transmitted to the system.

Project personnel shall be protected from excavated or other materials or equipment that could pose a hazard by falling or rolling into excavations. Protection shall be provided by placing and keeping such materials or equipment at least two feet from the edge of excavations, or by the use of retaining devices that are sufficient to prevent materials or equipment from falling or rolling into excavations, or by a combination of both if necessary.



Daily inspections of excavations, the adjacent areas, and protective systems shall be made by the SSO for evidence of a situation that could result in possible cave-ins, indications of failure of protective systems, hazardous atmospheres, or other hazardous conditions. An inspection shall be conducted by the SSO prior to the start of work and as needed throughout operations. Inspections shall also be made after every rainstorm or other hazard-increasing occurrence. These inspections are only required when project personnel exposure can be reasonably anticipated.

Where the SSO finds evidence of a situation that could result in a possible cave-in, indications of failure of protective systems, hazardous atmospheres, or other hazardous conditions, exposed personnel shall be removed from the hazardous area until the necessary precautions have been taken to ensure their safety.

*Excavation Egress* – A stairway, ladder, ramp, or other safe means of egress shall be located in trench excavations that are four feet or more in depth so as to require no more than 25 feet or lateral travel for project personnel.

## 9.2.3.2 HEAVY EQUIPMENT OPERATION

### Description of Tasks

Heavy equipment to be used for this task include, but are not limited to, excavators, dozers, dump trucks, and water sprayers (if required).

#### Hazard Identification

The most common type of accident that occurs in material handling operations is the "caught between" situation when a load is being handled and an object gets caught between two moving parts of the equipment. Operation of the heavy construction equipment may produce harmful noise.

#### <u>Controls</u>

Equipment Inspection – All vehicles in use shall be checked prior to operation to ensure that all parts, equipment, and accessories that affect safe operations are in proper operating condition and free from defects. All defects shall be corrected before the vehicle is placed in service.

*Ground Guides* – No personnel shall use any motor vehicle, earthmoving, or compacting equipment having an obstructed view to the rear, unless:

- The vehicle has a reverse signal alarm distinguishable from the surrounding noise level; or
- The vehicle is backed up only when an observer signals that it is safe to do so.



*Blocking* – Heavy machinery, equipment, or parts thereof that are suspended or held aloft shall be substantially blocked to prevent falling or shifting before employees are permitted to work under or between them.

Noise – Control measures for noise are addressed in Section 8.9.

*Traffic* – Control measures for traffic are addressed in Section 8.17.

### 9.2.3.3 DISTURBANCE/HANDLING OF CONTAMINATED MATERIAL

#### Description of Tasks

After the contaminated soil is excavated from below the Site's surface, the material will be stockpiled, dried, and either transported off Site or relocated and backfilled on Site.

#### Hazard Identification

The hazards associated with materials handling include contact of the contaminated material with project personnel, or cross contamination with other site soil.

#### <u>Controls</u>

*Cross Contamination* – Following excavation, contaminated soil stockpiles will be placed on a structure constructed to separate the material from the site soil and collect any groundwater leachate. The material shall be covered to prevent storm water erosion or migration of contaminants through storm water.

*Air Monitoring* – Air and particulate monitoring will be conducted during soil excavation activities to assess the potential for exposure to airborne COCs. If the results of air monitoring indicate the presence of organic vapors or particulates in a concentration causing concern, personnel will upgrade to Level C protection. Refer to Section 5.1, Air Monitoring, for a description of air monitoring requirements and action levels. Air monitoring protocols are also presented in the Community Air Monitoring Plan (Appendix G of this RAWP). A description of each level of personal protection is included in Section 4.0, Personal Protective Equipment.

*Traffic* – Control measures for traffic are addressed in Section 8.17.

#### 9.2.4 DRILLING/SUBSURFACE INTRUSION ACTIVITIES

#### Description of Tasks

Site mobilization will include establishing excavation locations, determining the location of utilities and other installations, and establishing work areas. Mobilization will also include setting up equipment and establishing a temporary Site office. A break area will be set up outside of regulated work areas. Mobilization may involve clearing areas for the SZ and CRZ. During this



initial phase, project personnel will walk the Site to confirm the existence of anticipated hazards and identify safety and health issues that may have arisen since the writing of this plan.

#### Hazard Identification

The primary physical hazards for this activity are associated with the use of soil boring and grouting equipment. The equipment is hydraulically powered and uses static force and dynamic percussion force to advance sampling and penetrating tubes.

Accidents can occur as a result of improperly placing the equipment on uneven or unstable terrain or failing to adequately secure the equipment prior to the start of operations. Overhead utility lines can create hazardous conditions if contacted by the equipment. Underground installations such as electrical lines, conduit, and product lines pose a significant hazard if contacted.

#### <u>Controls</u>

*Geoprobe and Drill Rig Safety Procedures* - The operator of the equipment must possess required state or local licenses to perform such work. All members of the crew shall receive Site-specific training prior to beginning work.

The operator is responsible for the safe operation of the rig, as well as the crew's adherence to the requirements of this HASP. The operator must ensure that all safety equipment is in proper condition and is properly used. The members of the crew must follow all instructions of the operator, wear all personal protective equipment, and be aware of all hazards and control procedures. The operator and crew must participate in the Daily Safety Meetings and be aware of all emergency procedures.

*Equipment Inspection* - Each day, prior to the start of work, the rig and associated equipment must be inspected by the operator. The following items must be inspected:

- Vehicle condition;
- Proper storage of equipment;
- Condition of all hydraulic lines;
- Fire extinguisher; and
- First aid kit.

*Equipment Set Up* - The drill rig must be properly blocked and leveled prior to raising the derrick. The wheels which remain on the ground must be chocked. The leveling jacks shall not be raised until the derrick is lowered. The rig shall be moved only after the derrick has been lowered.

All well sites will be inspected by the driller prior to the location of the rig to verify a stable surface exists. This is especially important in areas where soft, unstable terrain is common.



The drill rig must be properly blocked and leveled prior to raising the derrick. Blocking provides a more stable drilling structure by evenly distributing the weight of the rig. Proper blocking ensures that differential settling of the rig does not occur.

When the ground surface is soft or otherwise unstable, wooden blocks, at least 24" by 24" and 4" to 8" thick shall be placed between the jack swivels and the ground. The emergency brake shall be engaged, and the wheels that are on the ground shall be chocked.

*Rules for Intrusive Activity* - Before beginning any intrusive activity, the existence and location of underground pipe, conduit, electrical equipment, and other installations will be determined. This will be done, if possible, by contacting the appropriate client representative to mark the location of the lines. "Call Before You Dig" will verify the potential for encountering subsurface utilities. If the client's knowledge of the area is incomplete, an appropriate device, such as a magnetometer, will be used to locate the line.

Combustible gas readings of the general work area will be made regularly in areas where and/or during operations when the presence of flammable vapors or gases is suspected, such as during intrusive activities (see Section 5.1). Operations must be suspended and corrective action taken if the airborne flammable concentration reaches 10% of the LEL in the immediate area (a one-foot radius) of the point of drilling, or near any other ignition sources.

*Overhead Electrical Clearances* - If equipment is operated in the vicinity of overhead power lines, the power to the lines must be shut off or the equipment must be positioned and blocked such that no part, including cables, can come within the minimum clearances as indicated on **Table 8.2** below:

Nominal Voltage	System	Minimum Clearance	Required
0-50kV		10 feet	
51-100kV		12 feet	
101-200kV		15 feet	
201-300kV		20 feet	
301-500kV		25 feet	
501-750kV		35 feet	
751-1,000kV		45 feet	

Fable 8.3–	Voltage	versus	Required	Clearance
------------	---------	--------	----------	-----------



When the drill rig is in transit, with the boom lowered and no load, the equipment clearance must be at least four (4) feet for voltages less than 50kV, 10 feet for voltages of 50 kV to 345 kV, and 16 feet for voltages above 345 kV.

*Hoisting Operations* - Drillers should never engage the rotary clutch without watching the rotary table, and ensuring it is clear of personnel and equipment.

Unless the drawworks is equipped with an automatic feed control, the brake should not be left unattended without first being tied down.

Drill pipe, auger strings or casing should be picked up slowly. Drill pipe should not be hoisted until the driller is sure that the pipe is latched in the elevator, or the derrickman has signaled that he may safely hoist the pipe.

During instances of unusual loading of the derrick or mast, such as when making an unusually hard pull, only the driller should be on the rig floor; no one else should be on the rig or derrick.

The brakes on the drawworks of the drill rig should be tested by the driller each day. The brakes should be thoroughly inspected by a competent individual each week.

A hoisting line with a load imposed should not be permitted to be in direct contact with any derrick member or stationary equipment, unless it has been specifically designed for line contact.

Workers should never stand near the borehole whenever any wire line device is being run.

Hoisting control stations should be kept clean and controls labeled as to their functions.

*Catline Operations* - Only experienced workers will be allowed to operate the cathead controls. The kill switch must be clearly labeled and operational prior to operation of the catline. The cathead area must be kept free of obstructions and entanglements.

The operator should not use more wraps than necessary to pick up the load. More than one layer of wrapping is not permitted.

Personnel should not stand near, step over, or go under a cable or catline which is under tension.

Employees rigging loads on catlines shall:

- Keep out from under the load;
- Keep fingers and feet where they will not be crushed;
- Be sure to signal clearly when the load is being picked;



- Use standard visual signals only and not depend on shouting to coworkers; and
- Make sure the load is properly rigged, since a sudden jerk in the catline will shift or drop the load.

*Wire Rope* - When two wires are broken or rust or corrosion is found adjacent to a socket or end fitting, the wire rope shall be removed from service or re-socketed. Special attention shall be given to the inspection of end fittings on boom support, pendants, and guy ropes.

Wire rope removed from service due to defects shall be cut up or plainly marked as being unfit for further use as rigging.

Wire rope clips attached with U-bolts shall have the U-bolts on the dead or short end of the rope; the clip nuts shall be re-tightened immediately after initial load carrying use and at frequent intervals thereafter.

When a wedge socket fastening is used, the dead or short end of the wire rope shall have a clip attached to it or looped back and secured to itself by a clip; the clip shall not be attached directly to the live end.

Protruding ends of strands in splices on slings and bridles shall be covered or blunted.

Except for eye splices in the ends of wires and for endless wire rope slings, wire rope used in hoisting, lowering, or pulling loads, shall consist of one continuous piece without knot or splice.

An eye splice made in any wire rope shall have not less that five full tucks.

Wire rope shall not be secured by knots. Wire rope clips shall not be used to splice rope.

Eyes in wire rope bridles, slings, or bull wires shall not be formed by wire clips or knots.

*Pipe/Auger Handling* - Pipe and auger sections shall be transported by cart or carried by two persons. Individuals should not carry auger or pipe sections without assistance.

Workers should not be permitted on top of the load during loading, unloading, or transferring of pipe or rolling stock.

Employees should be instructed never to try to stop rolling pipe or casing; they should be instructed to stand clear of rolling pipe.



Slip handles should be used to lift and move slips. Employees are not permitted to kick slips into position.

When pipe is being hoisted, personnel should not stand where the bottom end of the pipe could whip and strike them.

Pipe and augers stored in racks, catwalks or on flatbed trucks should be secured to prevent rolling.

### 9.2.5 SUBSURFACE CHEMICAL SAMPLE/COLLECTION ANALYSIS

#### Description of Tasks

This sub-task consists of the collection of soil samples for subsequent field and laboratory analysis. The physical hazards of soil sampling are primarily associated with the sample collection methods, procedures utilized, and the environment itself.

#### Hazard Identification

Incidental contact with COCs is the primary hazard associated with sampling the stabilized material. This contact may occur through the manipulation of sample media and equipment, manual transfer of media into sample containers, and proximity of operations to the breathing zone. The primary hazards associated with these sampling procedures are not potentially serious; however, other operations in the area, or the conditions under which samples must be collected, may present chemical and physical hazards. The hazards directly associated with sampling procedures are generally limited to strains/sprains and potential eye hazards. Potential chemical hazards may include contact with media containing Site COCs and potential contact with chemicals used for equipment decontamination.

#### <u>Controls</u>

*PPE* – To control dermal exposure during sampling activities, a minimum of Level D protection will be worn. If necessary, based on field observations and site conditions, air monitoring may be conducted during sediment sampling activities. If the results of air monitoring indicate the presence of airborne contaminants in a concentration causing concern, personnel will upgrade to Level C protection. Refer to Section 5.1, Air Monitoring, for a description of air monitoring requirements and action levels. Air monitoring protocols are also presented in the Community Air Monitoring Plan (Appendix G of this RAWP). A description of each level of personal protection is included in Section 4.0, Personal Protective Equipment.

#### 9.2.6 UST CLOSURE

### 9.2.6.1 WORKING IN CONFINED SPACES

#### Description of Tasks

The project may involve the closure of several underground storage tanks (USTs).



### Hazard Identification

Closure activities may require the entrance into confined spaces to facilitate cleaning and removal of the USTs.

## <u>Controls</u>

All personnel required to enter confined or enclosed spaces must be instructed as to the nature of the hazards involved, the necessary precautions to be taken, and in the use of required protective and emergency equipment. The PO shall comply with all specific regulations that apply to work in dangerous or potentially dangerous areas. All personnel entering the confined space will have achieved the appropriate OSHA training and the operation will be permitted, as necessary.

## 9.2.6.2 WORKING WITH COMPRESSED AIR

### Description of Tasks

The proposed method of purging the USTs includes the injection of compressed gas into the tank and attached piping network.

### Hazard Identification

Uncontrolled release of the highly pressured air can cause injury to FP during this task. Cylinders must also be properly managed to ensure they are not compromised during storage and/or use.

#### <u>Controls</u>

*Pressure Regulation* – Compressed air used for cleaning purposes shall be reduced to less than 30 pounds per square inch and then only with effective chip guarding and personal protective equipment.

*Cylinder Storage* – Valve protection caps shall be in place and secured when compressed gas cylinders are transported, moved, or stored. Cylinder valves shall be closed when work is finished and when cylinders are empty or are moved. Compressed gas cylinders shall be secured in an upright position at all times, except if necessary for short periods of time when cylinders are actually being hoisted or carried. Cylinders shall be placed in a location where they cannot become part of an electrical circuit.

#### 9.2.7 DECONTAMINATION

All equipment will be decontaminated before leaving the Site. Personnel involved in decontamination activities may be inadvertently exposed to skin contact with contaminated materials and chemicals brought from the EZ. Personnel involved in decontamination activities must wear PPE that is, at a minimum, one level below the level worn by personnel working in the EZ.



# 9.2.8 DEMOBILIZATION

Demobilization involves the removal of all tools, equipment, supplies, and vehicles brought to the site. The hazards of this phase of activity are associated with heavy equipment operation and manual materials handling.

Manual materials handling may cause blisters, sore muscles, and joint and skeletal injuries; and may present eye, contusion, and laceration hazards. Heavy equipment operation presents noise and vibration hazards, and hot surfaces, to operators. Personnel in the vicinity of heavy equipment operation may be exposed to physical hazards resulting in fractures, contusions, and lacerations and may be exposed to high noise levels. The work area presents slip, trip, and fall hazards from scattered debris and irregular walking surfaces. Rainy weather may cause wet, muddy, slick walking surfaces, and unstable soil. Freezing weather hazards include frozen, slick, and irregular walking surfaces.

Environmental hazards include plants, such as poison ivy and poison oak; aggressive fauna, such as ticks, fleas, mosquitoes, wasps, spiders, and snakes; weather, such as sunburn, lightning, rain, and heat-or cold-related illnesses; and pathogens, such as rabies, Lyme disease, and blood-borne pathogens.

Control procedures for these hazards are discussed in Section 8.0, General Safety Practices.

### 9.3 CHEMICAL HAZARDS

The chemical hazards associated with Site operations are related to inhalation, ingestion, and skin exposure to Site COCs. Concentrations of airborne COCs during Site tasks may be measurable and will require air monitoring during certain operations. Air monitoring requirements for Site tasks are outlined in Section 5.1. Air monitoring protocols are also presented in the Community Air Monitoring Plan (Appendix E of the RIWP).

COCs at the Site include VOCs, SVOCs, pesticides, metals, and PFAS.

The potential for inhalation of site COCs is low. The potential for dermal contact with soils containing Site COCs during remedial operations is moderate. **Table 9.1** lists the primary contaminants that have been identified at the Site and the media in which they are present.



Table 9.1	l – List	of Primary	Contaminants
-----------	----------	------------	--------------

Media: Soil					
Metals	Maximum Concentration (mg/kg)	Applicable Monitoring Instrument			
Cadmium	24	Not Applicable			
Copper	722	Not Applicable			
Iron	38,200	Not Applicable			
Lead	7,190	Not Applicable			
Mercury	2.2	Not Applicable			
Nickel	42.9	Not Applicable			
Zinc	8,410	Not Applicable			
VOCs	Maximum Concentration (mg/kg)	Applicable Monitoring Instrument			
Acetone	0.0931	PID			
SVOCs	Maximum Concentration (mg/kg)	Applicable Monitoring Instrument			
Benzo(a)anthracene	14.4	PID			
Benzo(a)pyrene	12.9	PID			
Benzo(b)fluoranthene	15.1	PID			
Benzo(k)fluoranthene	2.72	PID			
Chrysene	10.5	PID			
Dibenzo(a,h)anthracene	1.92	PID			
Indeno(1,2,3-cd)pyrene	6.16	PID			
2-Methylnaphthalene	14.2	PID			
Pesticides	Maximum Concentration	Applicable Monitoring Instrument			



	(mg/kg)	
Dieldrin	0.034	Not Applicable
4,4'-DDE	0.53	Not Applicable
4,4'-DDD	0.064	Not Applicable
4'4-DDT	0.22	Not Applicable

Media: Groundwater				
SVOCs	Maximum Concentration (ug/L)	Applicable Monitoring Instrument		
Benzo(a)anthracene	0.23	PID		
Benzo(a)pyrene	0.26	PID		
Benzo(b)fluoranthene	0.22	PID		
Benzo(k)fluoranthene	0.22	PID		
Chrysene	0.27	PID		
Indeno(1,2,3-cd)pyrene	0.27	PID		
Metals	Maximum Concentration (ug/L)	Applicable Monitoring Instrument		
Aluminum	322,000	Not Applicable		
Antimony	22	Not Applicable		
Arsenic	161	Not Applicable		
Barium	2,250	Not Applicable		
Beryllium	105	Not Applicable		
Cadmium	21	Not Applicable		
Chromium	760	Not Applicable		
Copper	690	Not Applicable		
Iron	639,000	Not Applicable		



Media: Groundwater				
Lead	3,090	Not Applicable		
Magnesium	192,000	Not Applicable		
Manganese	9,640	Not Applicable		
Mercury	1.2	Not Applicable		
Nickel	517	Not Applicable		
Sodium	239,000	Not Applicable		
Zinc	6,690	Not Applicable		
PFAS	Maximum Concentration (ng/L)	Applicable Monitoring Instrument		
PFOS	68.8	Not Applicable		
PFOA	50.9	Not Applicable		

Media: Soil Vapor					
Contaminants	Maximum Concentration (ug/m³)	Applicable Monitoring Instrument			
1,2,4-Trimethylbenzene	9.33	PID			
4-Methyl-2-pentanone (MIBK)	7.57	PID			
Carbon Tetrachloride	0.39	PID			
Chloroform	3.21	PID			
Dichlorodifluoromethane	2.54	PID			
Ethanol	23	PID			
Ethylbenzene	25	PID			
Heptane	17.4	PID			



Media: Soil Vapor		
Contaminants	Maximum Concentration (ug/m³)	Applicable Monitoring Instrument
Hexane	34.8	PID
Isopropylalcohol	8.72	PID
m,p-Xylene	106	PID
Methyl Ethyl Ketone	212	PID
o-Xylene	32.5	PID
Tetrachloroethene	3.95	PID
Tetrahydrofuran	36	PID
Toluene	273	PID
Trichloroethene	2.4	PID
Trichlorofluoromethane	1.42	PID
Acetone (2-Propanone)	226	PID
Benzene	7.73	PID
Carbon disulfide	38.6	PID
Cyclohexane	5.9	PID
Ethyl Acetate	256	PID
Isopropyl Alcohol	1.9	PID
Propylene	73.1	PID
2,2,4-Trimethylpentane	2.3	PID
Tertiary Butyl Alcohol	2.1	PID
Xylenes (total)	14	PID
Methylene Chloride	12.4	PID



Media: Soil Vapor			
Contaminants	Maximum Concentration (ug/m³)	Applicable Monitoring Instrument	
1,3,5-Trimethylbenzene	3.71	PID	
1,3-Butadiene	15.2	PID	
4-Ethyltoluene	13.7	PID	
4-Isopropyltoluene	2.78	PID	
Isopropylbenzene	1.79	PID	
sec-Butylbenzene	1.3	PID	
Styrene	1.06	PID	

## 10.0 EMERGENCY PROCEDURES

#### 10.1 GENERAL

Prior to the start of operations, the work area will be evaluated for the potential for fire, contaminant release, or other catastrophic event. Unusual conditions or events, activities, chemicals, and conditions will be reported to the FS/SSO immediately.

The FS/SSO will establish evacuation routes and assembly areas for the Site. All personnel entering the Site will be informed of this route and the assembly area.

### **10.2 EMERGENCY RESPONSE**

If an incident occurs, the following steps will be taken:

- The FS/SSO will evaluate the incident and assess the need for assistance and/or evacuation;
- The FS/SSO will call for outside assistance as needed;
- The FS/SSO will ensure the PM is notified promptly of the incident; and
- The FS/SSO will take appropriate measures to stabilize the incident scene.

#### 10.2.1 FIRE

In the case of a fire at the Site, the FS/SSO will assess the situation and direct fire-fighting activities. The FS/SSO will ensure that the PM is immediately notified of any fires. Site personnel will attempt to extinguish the fire with available extinguishers, if safe to do so. In the event of a



fire that Site personnel are unable to safely extinguish with one (1) fire extinguisher, the local fire department will be summoned.

## 10.2.2 CONTAMINANT RELEASE

In the event of a contaminant release, the following steps will be taken:

- Notify FS/SSO immediately;
- Evacuate immediate area of release;
- Conduct air monitoring to determine needed level of PPE; and
- Don required level of PPE and prepare to implement control procedures.

The FS/SSO has the authority to commit resources as needed to contain and control released material and to prevent its spread to off-Site areas.

### **10.3 MEDICAL EMERGENCY**

All employee injuries must be promptly reported to the SSO/FS, who will:

- Ensure that the injured employee receives prompt first aid and medical attention;
- In emergency situations, the worker is to be transported by appropriate means to the nearest urgent care facility (normally a hospital emergency room); and
- If the injured person is a SESI employee, notify SESI at 973-808-9050.

### 10.3.1 EMERGENCY CARE STEPS

Survey the scene. Determine if it is safe to proceed. Try to determine if the conditions that caused the incident are still a threat. Protect yourself from exposure before attempting to rescue the victim.

- Do a primary survey of the victim. Check for airway obstruction, breathing, and pulse. Assess likely routes of chemical exposure by examining the eyes, mouth, nose, and skin of the victim for symptoms.
- Phone Emergency Medical Services (EMS). Give the location, telephone number used, caller's name, what happened, number of victims, victim's condition, and help being given.
- Maintain airway and perform rescue breathing as necessary.
- Perform CPR as necessary.
- Do a secondary survey of the victim. Check vital signs and do a head-to-toe exam.

Treat other conditions as necessary. If the victim can be moved, take him/her to a location away from the work area where EMS can gain access.



## **10.4 FIRST AID GENERAL**

All persons must report any injury or illness to their immediate supervisor or the FS. Trained personnel will provide first aid. Injuries and illnesses requiring medical treatment must be documented. The FS and SSO must fill out an accident/incident report as soon as emergency conditions no longer exist and first aid and/or medical treatment has been ensured. The report must be completed and submitted to the PM within 24 hours after the incident.

If first-aid treatment is required, first aid kits are kept at the CRZ. If treatment beyond first aid is required, the injured person(s) should be transported to the medical facility. If the injured person is not ambulatory or shows any sign of not being in a comfortable and stable condition for transport, then an ambulance/paramedics should be summoned. If there is any doubt as to the injured worker's condition, it is best to let the local paramedic or ambulance service examine and transport the worker.

### 10.4.1 FIRST AID—INHALATION

Any employee complaining of symptoms of chemical overexposure as described in Section 4, General Site Safety Procedures, will be removed from the work area and transported to the designated medical facility for examination and treatment.

### 10.4.2 FIRST AID—INGESTION

Call EMS and consult a poison control center for advice. If available, refer to the MSDS for treatment information. If the victim is unconscious, keep them on their side and clear the airway if vomiting occurs.

### 10.4.3 FIRST AID—SKIN CONTACT

Project personnel who have had skin contact with contaminants will, unless the contact is severe, proceed through the CRZ, to the wash area. Personnel will remove any contaminated clothing, and then flush the affected area with water for at least 15 minutes. The worker should be transported to the medical facility if he/she shows any sign of skin reddening, irritation, or if he/she requests a medical examination.

### 10.4.4 FIRST AID—EYE CONTACT

Project personnel who have had contaminants splashed in their eyes or who have experienced eye irritation while in the EZ, must immediately proceed to the eyewash station in the CRZ. Do not decontaminate prior to using the eyewash. Remove whatever protective clothing is necessary to use the eyewash. Flush the eye with clean running water for at least 15 minutes. Arrange prompt transport to the designated medical facility.

### 10.5 REPORTING INJURIES, ILLNESSES, AND SAFETY INCIDENTS

Injuries and illnesses, however minor, will be reported to the FS immediately. The FS will complete an injury report and submit it to the HSM, and the PM by end of shift.



## **10.6 EMERGENCY INFORMATION**

he means to summon local public response agencies such as police, fire, and ambulance will be reviewed in the daily safety meeting. These agencies are identified in **Table 10.1** below.

Local Emergency Contacts	Telephone No.
EMERGENCY	911
Phelps Hospital	(914) 366-3000
Police Emergency	911
Fire Emergency	911
Rescue Squad	911
Ambulance	911
Miscellaneous Contacts	Telephone No.
N.Y. Poison Control Center	(800) 222-1222
National Response Center and Terrorist Hotline	(800) 424-8802
Center for Disease Control	(800) 311-3435
Utility Mark-Out	(800) 962-7962

# Table 10.1 – Emergency Contacts

## **10.6.1 DIRECTIONS TO HOSPITAL**

Phelps Hospital 701 N Broadway, Tarrytown, NY (914) 366-3000

Directions to Hospital: Figure10.1




9 min (2.9 miles) - 김 < 🗗 via US-9 N/N Broadway Best route now due to traffic conditions 1 Franklin Ct Tarrytown, NY 10591 Head northeast on Franklin Ct toward Franklin St ↑ 23 ft Turn right onto Franklin St 0.1 mi Turn left onto S Washington St **←** 0.4 mi Turn right onto Wildey St  $\rightarrow$ 482 ft Turn left onto US-9 N/N Broadway 2.0 mi Turn left onto Phelps Ln 0.2 mi Turn right 210 ft Phelps Hospital 701 N Broadway, Tarrytown, NY 10591

Phelps Hospital is depicted on Figure 10.1

#### 11.0 LOGS, REPORTS, AND RECORDKEEPING

#### 11.1 HASP AND FIELD CHANGE REPORT

The following is a summary of required health and safety logs, reports, and record keeping for the operations at the subject Site. The field change request form is presented as Attachment 3.

#### 11.2 MEDICAL AND TRAINING RECORDS

The HSM must obtain and keep a log of personnel meeting appropriate training and medical qualifications for the site work. The log will be kept in the project file. Each company's Human Resources Department will maintain medical records, in accordance with 29 CFR 1910.1020.

#### **11.3 EXPOSURE RECORDS**

Any personnel monitoring results, laboratory reports, calculations, and air sampling data sheets are part of an employee exposure record. These records will be kept in accordance with 29 CFR 1910.1020. For SESI employees, the originals will be sent to the Human Resources Manager. For subcontractor employees, the original file will be sent to the subcontractor employer with a copy maintained in the SESI project file.

#### 11.4 ACCIDENT/INCIDENT REPORT





Any accident/incident reports must be completed following procedures given in Section 10.5 of this HASP. The originals will be sent to the HSM for maintenance. A copy of the forms will be kept in the project file. (See Attachment 4).

#### 11.5 OSHA FORM 200

An OSHA Form 200 (Log of Occupational Injuries and Illnesses) will be kept at the project Site. All recordable injuries or illnesses will be recorded on this form. At the end of the project, the original will be sent to the Human Resources Manager for maintenance. Subcontractor employees must also meet the requirements of maintaining an OSHA 200 Form. The accident/incident report meets the requirements of OSHA Form 101 (Supplemental Record), which must be maintained with the OSHA Form 200 for all recordable injuries or illnesses.

#### 11.6 ON-SITE HEALTH AND SAFETY FIELD LOGBOOK

The HSM or designee will maintain an on-Site health and safety logbook in which daily Site conditions, activities, personnel, and significant events will be recorded. Calibration records and personnel monitoring results, if available, will also be recorded in the field logbook. The original logbook will be kept in the project file.

Whenever any personnel monitoring is conducted onsite, the monitoring results will be noted in the filed logbook. These will become part of the exposure records file and will be maintained by the HSM.

A signatory page is included (See Attachment 5) and is to be signed by those working on and/or visiting the Site.

#### 11.7 SAFETY DATA SHEETS

Safety Data Sheets (SDS) will be obtained and kept on file at the project site for each hazardous chemical brought to, use, or stored at the Site (See Attachment 6).

#### 12.0 COVID RESPONSE ACTION PLAN

SESI is concerned with the safety and well-being of its employees, vendors, subcontractors, and others with access to its offices and job sites, with particular emphasis on the unique challenges posed by COVID-19.

SESI has established the following protocols in keeping with the recommendations of the CDC and other sources including State Governor Executive Orders for work taking place on construction sites.

We request that all SESI employees, vendors, and subcontractors help with our prevention efforts while at work.



In order to minimize the spread of COVID-19, we must all cooperate in doing the following:

- Frequently wash your hands with soap and water for at least 20 seconds. When soap and running water are unavailable, use an alcohol-based hand rub with at least 60% alcohol. Always wash hands that are visibly soiled.
- Cover your mouth and nose with a tissue when you cough or sneeze or use the inside of your elbow.
- Discourage handshaking, avoid touching your eyes, nose, or mouth with unwashed hands.
- Limit the sharing of tools, machinery, equipment, phones, desks, and computers.
- Wear cloth face coverings on all construction sites.
- Avoid close contact with people who are sick.
- Employees who have symptoms (i.e., fever, cough, or shortness of breath) should notify their supervisor and stay home—DO NOT GO TO WORK.
- Sick employees should follow CDC-recommended steps. Employees should not return to work until the criteria to discontinue home isolation are met, in consultation with healthcare providers and state and local health departments.

The following are the specific jobsite protocols and response actions to be taken in the event someone on Site has been in contact with, or has themselves, the COVID-19 virus:

#### **OFFICE/JOBSITE PROTOCOL**

- If an employee/worker exhibits COVID-19 symptoms, the employee/worker must remain at home until he or she is symptom free for 72 hours (three [3] full days) without the use of fever-reducing or other symptom-altering medicines (e.g. acetaminophen, cough suppressants). SESI will similarly require an employee or worker that reports to work with symptoms to return home until they are symptom free for 72 hours (three [3] full days).
- Limit person to person contact, and when unavoidable, maintain CDC distancing guidelines.
- Avoid eating lunch in groups.
- Avoid in-person meetings if possible. If an in-person meeting is necessary, conduct it in a well-ventilated area with enough space for attendees to distance themselves from one another. Field jobsite meetings should be conducted in smaller group meetings (no more than five [5] persons when possible) versus one large meeting.
- Only workers necessary to the execution of the work should be at the jobsites. No nonessential visitors should be permitted at the worksite.

#### **RESPONSE ACTION TRIGGER EVENTS:**

- an employee/worker at work has tested positive for COVID-19
- an employee/worker at work has suspected, but unconfirmed, case of COVID-19
- an employee/worker self-reported that they came in contact with someone who had a presumptive positive case of COVID-19
- an employee/worker has been exposed to the virus but only found out after they have interacted with others



#### **RESPONSE ACTIONS:**

- Upon occurrence of any of the Trigger Events above, employees/subcontractors shall notify SESI Management about the suspected employee/worker infected with, or exposed to, COVID-19.
- SESI Management will investigate the incident to confirm the report is valid.
- Employees/Subcontractors shall investigate their respective infected employee(s) and report the following to SESI Management and HR:
  - Identify all individuals who worked in proximity (six feet) of the infected employee/worker,
  - Employee(s)/Worker(s) infected with the COVID-19 virus, and employee(s)/worker(s) that came in contact with the infected employee/worker shall be sent home for a period of 14 days,
  - Do not identify the infected employee/worker by name to avoid violation of privacy/confidentiality laws, and,
  - Keep SESI Management informed of progress and updates.
- If an infected person was in the office, SESI will clean and disinfect common areas and surfaces, in accordance with CDC recommendations.
- SESI Management will notify affected employees/workers of the Trigger Event and instruct them to take the response actions above.

## • SESI Management policy requires written documentation from a health care professional that confirmed infected employees can return to work.

Except for circumstances in which SESI is legally required to report workplace occurrences of communicable disease, the confidentiality of all medical conditions will be maintained in accordance with applicable law and to the extent practical under the circumstances. When required, the number of persons who will be informed of an employee's/worker's condition will be kept at the minimum needed to appropriately notify other potentially affected employees/workers of Trigger Events and to attempt to minimize the potential for transmission of the virus.

Attachment 1: Air Monitor Log

#### Air Monitoring: Sample Collection and Analysis

Date & Time of Monitoring	Task / Operation Being	Substance(s)/ Hazard(s) Being	Monitoring Location	Type/Method of Monitoring	Monitoring Results	Exposure Limits	Required Action

Attachment 2: OSHA Poster

# Job Safety and Health It's the law!

#### EMPLOYEES:

- You have the right to notify your employer or OSHA about workplace hazards. You may ask OSHA to keep your name confidential.
- You have the right to request an OSHA inspection if you believe that there are unsafe and unhealthful conditions in your workplace. You or your representative may participate in that inspection.
- You can file a complaint with OSHA within 30 days of retaliation or discrimination by your employer for making safety and health complaints or for exercising your rights under the OSHAct.
- You have the right to see OSHA citations issued to your employer. Your employer must post the citations at or near the place of the alleged violations.
- Your employer must correct workplace hazards by the date indicated on the citation and must certify that these hazards have been reduced or eliminated.
- You have the right to copies of your medical records and records of your exposures to toxic and harmful substances or conditions.
- · Your employer must post this notice in your workplace.
- You must comply with all occupational safety and health standards issued under the OSH Act that apply to your own actions and conduct on the job.

#### **EMPLOYERS:**

- You must furnish your employees a place of employment free from recognized hazards.
- You must comply with the occupational safety and health standards issued under the OSHAct.

This free poster available from OSHA – The Best Resource for Safety and Health





#### 1-800-321-OSHA (6742)

OSHA 3165-02 2012R

www.osha.gov



# Attachment 3: Field Change Request Form

#### HEALTH & SAFETY PLAN CHANGE NOTICE

			Pages	of
Proje	ct:		H&S-C	CN
1)	HASP VERSION:	SECTION:	PAGE (s):	
	RE: Change to Addition Other:	o existing HASP to existing HASP	Anticipated Revision Date:	
			CO	NT
2)	PROPOSED CHANGE:			
3)	REASON FOR PROPOSE	D CHANGE(s): by SPEC or Change Order	Other:	
	Dispositi Change i Operation	on of Deficiency n Regulatory or Other Requir nal Experience	ementsC	ONT
4)	EXHIBITS ATTACHED	NOYES (If YES	, describe)CON	Т
5)	PMK APPROVALS	PROJECT MANAGER:	Date:	
		SITE MANAGER: H&S MANAGER:	Date: Date:	
	Client Approval Required:	NOYES (If Y	ES, date submitted)	
6)	CLIENT APPROVAL	APPROVED	REMANDEDREJECTI	ED
			CONT	
	Client Representative:		Date:	
7)	DISTRIBUTION AFTER	APPROVAL		
		LIST OTHER:		
	$\frac{\underline{X}}{\underline{X}} \qquad \text{HASP OFDATE I} \\ \frac{\underline{X}}{\underline{X}} \qquad \text{CLIENT} \\ \frac{\underline{X}}{\underline{X}} \qquad \text{PROJECT FILES} $			

Attachment A: Injury Report Form

Phone () Date//	Completed by	which it pertains. If you need additional copies of this form, you may photocopy and use as many as you need.	any substitutes. To be considered an equivalent form, any substitute must contain all the information asked for on this form. According to Public Law 91-596 and 29 CFR 1904, OSHA's recordkeeping rule, you must keep this form on file for 5 wave following the wave to	accompanying <i>summary</i> , unese forms nept the employer and OSHA develop a picture of the extent and severity of work-related incidents. Within 7 calendar days after you receive information that a recordable work-related injury or illness has occurred, you must fill out this form or an equivalent. Some state workers' compensation,	This <i>Injury and Illness Incident Report</i> is one of the first forms you must fill out when a recordable work- related injury or illness has occurred. Together with the <i>Log of Work-Related Injuries and Illness</i> and the	OSHA's Form 301 Injury and Illness
<ul> <li>Was employee hospitalized overnight as an in-patient?</li> <li>Yes</li> <li>No</li> </ul>	Sity     State     ZIP       8) Was employee treated in an emergency room?     Xes       9) No     No	7) If treatment was given away from the worksite, where was it given? Facility	Information about the physician or other health ca professional <sup>6)</sup> Name of physician or other health care professional	City	1) Full name 2) Street	Incident Report
18) If the employee died, when did death occur? Date of death///	17) What object or substance directly harmed the employee? Examples: "concrete floor"; "chlorine"; "radial arm saw." If this question does not apply to the incident, leave it blank.	16) What was the injury or illness? Tell us the part of the body that was affected and how it was affected; be more specific than "hurt," "pain," or sore." Examples: "strained back"; "chemical burn, hand"; "carpal tunnel syndrome."	are fell 20 feel?; "Worker was sprayed with chlorine when gasket broke during replacement"; "Worker developed soreness in wrist over time."	<ul> <li>13) Time of event AM / PM Check if time cannot be determined</li> <li>14) What was the employee doing just before the incident occurred? Describe the activity, as well as the tools, equipment, or material the employee was using. Be specific. <i>Examples:</i> "climbing a ladder while carrying roofing materials"; "spraying chlorine from hand sprayer"; "daily computer key-entry."</li> </ul>	10) Case number from the Log	Attention: This form contains information relating to employee health and must be used in a manner that protects the confidentiality of employees to the extent possible while the information is being used for occupational safety and health purposes.       U.S. Department of Labor Occupational Safety and Health Administration

Public reporting burden for this collection of information is estimated to average 22 minutes per response, including time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Persons are not required to respond to the collection of information unless it displays a current valid OMB control number. If you have any comments about this estimate or any other aspects of this data collection, including suggestions for reducing this burden, contact: US Department of Labor, OS11A Office of Statistical Analysis, Room N-3644, 200 Constitution Avenue, NW, Washington, DC 20210. Do not send the completed forms to this office.

OSHA's Form 300 (Rev. 0 Log of Work-Re You must record information about every work-related days away from work, or medical treatment beyond 1 care professional. You must also record work-related use two lires for a single case if you need to. You must torm. If you're not sure whether a case is recordable. Identify the person (A) (B) Case Employee's name (e.g.,	1/2004) <b>Lated I</b> d death and about even inst aid. You must also rist aid. You must also rist aid. You must also the an injury a set our local OSHA c Date of in Wedder) or onset of illness of illness file	<b>njuries an</b> work-related injury or illness that in secord significant work-related injurie at meet any of the specific recording flice for help. <b>Fe the case</b> (E) jury Where the event occurred (e.g., Loading dock worth end)	d IIIInesses olves loss of consciousness, restricted work as s and illnesses that are diagnosed by a physicis g criteria listed in 29 GFR Part 1904.8 through 1 nrm 301) or equivalent form for each injury or illn Describe injury or illness, parts of body : and object/substance that directly injurce or made person ill (e.g., Scrond degree hum right forearm from actylene torch)	Attention: The employee healt protects the co- possible while to occupational set occupational set of transfer, an or licensed health 12. Feel free to the set recorded on this affected, affected, affected, affected, affected between the set of the set o	afely and afely and are only the case of the the the the case of the the the the case of the the the the the case of the the the the the the case of the	ontains ir Ist be use thy of emp health pu health pu hea	formation relati d in a manner t loyees to the eveling used for rposes. reach case s outcome for named at Work taken other record (J)	Ing to hat cent Establishment name Cry Cry Cry Cry Cry Cry Cry Cry Cry Cry	Year 20
Identify the person	Descri	be the case		Cla	ssify the ck only (	Case DNE box fo	r each case	Enter the number of	
(A) (B) (C) Case Employee's name Job ti no. (e.g.,	) (D) itle Date of in Welder) or onset	(E) jury Where the event occurred (e.g., Londing dock north end)	(F) Describe injury or illness, parts of body : and abiantembershap that diseast injured	affected, that	cK ONLY t d on the n case:	one box io nost seriou	r each case s outcome for	Enter the number of days the injured or ill worker was:	Check the "Injury" column or choose one type of illness:
	of illness	a	or made person ill (e.g., Scand degree hurn right forearm from acetylene torch)	IS ON Death	Days av from we	Rer Vay Job trai ork or restri	nained at Work Insfer Other record- Iction able cases	Away On job from transfer or work restriction	Injury Skin disorder Respiratory condition Poisoning Hearing loss All other illnesses
	monthutay				<b>]</b> 3	09	<b>[</b> ] E	(K) (L) days days	(1) (2) (3) (4) (5) (6)
	/ month/day							days days	
	/ month/day							days days	
	/ month/day							days days	
	/ month/day							days days	
	monliv/day							days days	
	/ month/day							daysdays	
	month day							days days	
	month/day							daysdays	
	/ month/day							days days	
	/ month/day							days days	
	/ month,iday							daysdays	
	month/stay						0	days days	
			Pag	e totals>					
Public reporting burden for this collection of information is en the instructions, search and gather the data needed, and comp to respond to the collection of information unless it displays a about these scimanes or any other aspects of this data collection	timated to average 14 min plete and review the collect currently valid OMB contr m, contact: US Department	tes per response, including time to review on of information. Persons are not require of number. If you have any comments of Labor. OSHA Office of Statistical	e sur	re to transfer these totals	s to the Sumn	nary page (Fo	rm 300A) before you p	ost it.	Injury kin disorder Respiratory condition Poisoning Hearing loss All other illness
Analysis, Room N-5014, 200 Constitution Avenue, NW, Washi	ngton, DC 20210. Do not s	and the completed forms to this office.						Page of	(1) (2) (3) (4) (5) (6)

# OSHA's Form 300

Occupational Safety and Health A
Form approved OM
Establishment information
Your establishment name
City State ZIP
Industry description (e.g., Manufacture of motor truck trailers)
Standard Industrial Classification (SIC), if known (e.g., 3715)
OR
North American Industrial Classification (NAICS), if known (e.g., 336212)
<b>Employment information</b> (If you don't have these figures, see the Worksheer on the back of this page to estimate.)
Annual average number of employees
Total hours worked by all employees last year
Sign here
Knowingly falsifying this document may result in a fine.
I certify that I have examined this document and that to the best of my knowledge the entries are true, accurate, and complete.
Company executive Title
Plane / / Date
- 0

Administration MB no. 1218-0176

Attachment 5: Signatory Page

#### Attachment 5 – Site-Specific Health and Safety Orientation Signatory Page HEALTH AND SAFETY PLAN

Title	Name	Signature
Project Manager:	TBD	
Health and Safety Manager:	TBD	

I have read the attached Health and Safety Plan (HASP) and have received site-specific information and orientation regarding the identified physical, chemical, and biological hazards anticipated at this site. My signature certifies that I understand the procedures, equipment, and restrictions applicable to this project site and agree to abide by them.

Signature	Printed Name	Company	Date

#### Attachment 5– Health and Safety Orientation Signatory Page (continued)

Signature	Printed Name	Company	Date
	Health and Safety Orientation (2 of 2)	Signatory Page	

# Attachment 6: Material Safety Data Sheets



#### **SAFETY DATA SHEET**

Version 6.3 Revision Date 10/11/2020 Print Date 06/20/2021

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifiers**

	Product name	:	1,2,4,5-Tetramethylbenzene
	Product Number Brand CAS-No.	::	T19607 Aldrich 95-93-2
1.2	Relevant identified us	es	of the substance or mixture and uses advised against
	Identified uses	:	Laboratory chemicals, Synthesis of substances
1.3	Details of the supplier	<sup>.</sup> of	the safety data sheet
	Company	:	Sigma-Aldrich Inc.

	3050 SPRUCE ST
	ST. LOUIS MO 63103
	UNITED STATES
Telephone	: +1 314 771-5765
Fax	: +1 800 325-5052

:

#### **1.4 Emergency telephone**

Emergency Phone #

800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable solids (Category 1), H228

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



```
Signal wordDangerHazard statement(s)Flammable solid.H228Flammable solid.Precautionary statement(s)Keep away from heat/ sparks/ open flames/ hot surfaces. No
```

Aldrich - T19607

The life science business of Merck KGaA, Darmstadt, Germany operates as MilliporeSigma in the US and Canada



Page 1 of 9

	smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

#### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Synonyms

:	Durene
	1,2,4,5-Tetramethylbenzene

Formula	:	C <sub>10</sub> H <sub>14</sub>
Molecular weight	:	134.22 g/mol
CAS-No.	:	95-93-2
EC-No.	:	202-465-7

No components need to be disclosed according to the applicable regulations.

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first-aid measures

#### **General advice**

Consult a physician. Show this material safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### **4.3 Indication of any immediate medical attention and special treatment needed** No data available

Aldrich - T19607

Page 2 of 9



#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

- **5.2 Special hazards arising from the substance or mixture** Carbon oxides
- **5.3 Advice for firefighters** Wear self-contained breathing apparatus for firefighting if necessary.

#### **5.4 Further information** Use water spray to cool unopened containers.

#### SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures** Avoid dust formation. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal. Contain spillage, pick up with an electrically protected vacuum cleaner or by wet-brushing and transfer to a container for disposal according to local regulations (see section 13).

**6.4 Reference to other sections** For disposal see section 13.

#### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Avoid formation of dust and aerosols.

Provide appropriate exhaust ventilation at places where dust is formed.Keep away from sources of ignition - No smoking.Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

**7.2** Conditions for safe storage, including any incompatibilities Keep container tightly closed in a dry and well-ventilated place. Storage class (TRGS 510): 4.1B: Flammable solid hazardous materials

#### **7.3** Specific end use(s) Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

Aldrich - T19607

Page 3 of 9



#### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

#### Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

#### 8.2 Exposure controls

#### **Appropriate engineering controls**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### **Personal protective equipment**

#### Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a fullface particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Aldrich - T19607

Page 4 of 9



#### **Control of environmental exposure**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: crystalline Color: colorless
b)	Odor	No data available
c)	Odor Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 76 - 80 °C (169 - 176 °F) - lit.
f)	Initial boiling point and boiling range	No data available
g)	Flash point	74 °C (165 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	The substance or mixture is a flammable solid with the category 1.
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapor pressure	No data available
I)	Vapor density	No data available
m)	Relative density	0.838 g/mL at 25 °C (77 °F)
n)	Water solubility	0.00348 g/l at 25 °C (77 °F)
o)	Partition coefficient: n-octanol/water	log Pow: 4.17
p)	Autoignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Oth	er safety informatio	n

No data available

#### SECTION 10: Stability and reactivity

#### **10.1 Reactivity**

No data available

Aldrich - T19607

9.2

Page 5 of 9



#### **10.2 Chemical stability**

Stable under recommended storage conditions.

- 10.3 Possibility of hazardous reactions No data available
- **10.4 Conditions to avoid** Heat, flames and sparks. Extremes of temperature and direct sunlight.

**10.5 Incompatible materials** Strong oxidizing agents

10.6 Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available In the event of fire: see section 5

#### **SECTION 11: Toxicological information**

#### **11.1 Information on toxicological effects**

#### Acute toxicity

LD50 Oral - Rat - 6,700 mg/kg Remarks: (RTECS)

Skin corrosion/irritation

Serious eye damage/eye irritation

#### **Respiratory or skin sensitization**

#### Germ cell mutagenicity

#### Carcinogenicity

- IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- ACGIH: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
- NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

#### Specific target organ toxicity - single exposure

#### Specific target organ toxicity - repeated exposure

#### Aspiration hazard

#### Additional Information

RTECS: DC0500000

The data available to us do not suffice to permit any industrial-toxicological assessment. Further toxicological data: Risk of absorption. Other dangerous properties can not be excluded. Further data:

Aldrich - T19607

Page 6 of 9



#### **SECTION 12: Ecological information**

#### **12.1 Toxicity**

Toxicity to fish	LC0 - Leuciscus idus (Golden orfe) - 10 mg/l - 48 h Remarks: (ECOTOX Database)
	LC50 - Leuciscus idus (Golden orfe) - 30 mg/l - 48 h Remarks: (ECOTOX Database)
	LC100 - Leuciscus idus (Golden orfe) - 50 mg/l - 48 h Remarks: (ECOTOX Database)
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - 0.47 mg/l - 48 h Remarks: (External MSDS)

#### 12.2 Persistence and degradability

Not readily biodegradable.

#### 12.3 Bioaccumulative potential

#### 12.4 Mobility in soil

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### **12.6 Other adverse effects**

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Discharge into the environment must be avoided.

#### SECTION 13: Disposal considerations

#### **13.1** Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

#### **Contaminated packaging**

Dispose of as unused product.

#### **SECTION 14: Transport information**

#### DOT (US)

UN number: 1325 Class: 4.1 Packing group: II Proper shipping name: Flammable solids, organic, n.o.s. (1,2,4,5-tetramethylbenzene) Reportable Quantity (RQ): Poison Inhalation Hazard: No

Aldrich - T19607

Page 7 of 9



#### IMDG

UN number: 1325 Class: 4.1 Packing group: II EMS-No: F-A, S-G Proper shipping name: FLAMMABLE SOLID, ORGANIC, N.O.S. (1,2,4,5-tetramethylbenzene)

#### ΙΑΤΑ

UN number: 1325 Class: 4.1 Packing group: II Proper shipping name: Flammable solid, organic, n.o.s. (1,2,4,5-tetramethylbenzene)

#### SECTION 15: Regulatory information

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Fire Hazard

#### **Massachusetts Right To Know Components**

No components are subject to the Massachusetts Right to Know Act.

<b>Pennsylvania Right To Know Components</b> 1,2,4,5-tetramethylbenzene	CAS-No. 95-93-2	Revision Date
New Jersey Right To Know Components 1,2,4,5-tetramethylbenzene	CAS-No. 95-93-2	Revision Date

#### California Prop. 65 Components

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

#### **SECTION 16: Other information**

#### **Further information**

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the

Aldrich - T19607

Page 8 of 9



information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.3 Revision Date: 10/11/2020 Print Date: 06/20/2021

Aldrich - T19607

Page 9 of 9



#### SAFETY DATA SHEET

Version 6.0 Revision Date 05/25/2018 Print Date 06/29/2019

1. PR	ODUCT AND COMPANY IDE	NT	IFICATION
1.1	Product identifiers Product name	:	2-Methylnaphthalene (β)
	Product Number Brand	:	M57006 Aldrich
	CAS-No.	:	91-57-6
1.2	.2 Relevant identified uses of the substance or mixture and uses advised against		
	Identified uses	:	Laboratory chemicals, Synthesis of substances
1.3	Details of the supplier of the	ne s	safety data sheet
	Company	:	Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES
	Telephone Fax	:	+1 314 771-5765 +1 800 325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS) Acute toxicity, Oral (Category 4), H302

Acute aquatic toxicity (Category 2), H401

Chronic aquatic toxicity (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word	Warning
Hazard statement(s) H302 H411	Harmful if swallowed. Toxic to aquatic life with long lasting effects.
Precautionary statement(s) P264	Wash skin thoroughly after handling.

if you feel unwell.
-
te disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

#### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substances		
Molecular weight	:	142.20 g/mo
CAS-No.	:	91-57-6
EC-No.	:	202-078-3

#### Hazardous components

Component	Classification	Concentration
2-Methylnaphthalene		
	Acute Tox. 4; Aquatic Acute 2; Aquatic Chronic 2; H302, H411	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

3.1

#### 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

- **4.2** Most important symptoms and effects, both acute and delayed The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
- **4.3 Indication of any immediate medical attention and special treatment needed** No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

### 5.2 Special hazards arising from the substance or mixture Carbon oxides

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

No data available

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Avoid breathing dust.

For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

#### **7.2** Conditions for safe storage, including any incompatibilities Keep container tightly closed in a dry and well-ventilated place. Storage class (TRGS 510): 13: Non Combustible Solids

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
2- Methylnaphthalene	91-57-6	TWA	0.5 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Lower Respi Lung damag Not classifiat Danger of cu	ratory Tract irritatic e ble as a human car taneous absorption	on rcinogen n

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

#### Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm

Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

For nuisance exposures use type P95 (US) or type P1 (EU EN 143) particle respirator.For higher level protection use type OV/AG/P99 (US) or type ABEK-P2 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). **Control of environmental exposure** 

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: solid
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 34 - 36 °C (93 - 97 °F) - lit.
f)	Initial boiling point and boiling range	241 - 242 °C (466 - 468 °F) - lit.
g)	Flash point	98.0 °C (208.4 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	No data available
I)	Vapour density	No data available
m)	Relative density	1 g/mL at 25 °C (77 °F)
n)	Water solubility	No data available
o)	Partition coefficient: n- octanol/water	log Pow: 3.80
p)	Auto-ignition temperature	No data available
q)	Decomposition	No data available

temperature

- r) Viscosity No data available
- s) Explosive properties No data available
- t) Oxidizing properties No data available
- 9.2 Other safety information

No data available

#### **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity

No data available

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5** Incompatible materials Oxidizing agents

#### **10.6 Hazardous decomposition products**

Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available In the event of fire: see section 5

#### 11. TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - 1,630 mg/kg Inhalation: No data available Dermal: No data available No data available

#### Skin corrosion/irritation

Skin - Rabbit Result: Mild skin irritation

Serious eye damage/eye irritation

No data available Respiratory or skin sensitisation

No data available

#### Germ cell mutagenicity

No data available

#### Carcinogenicity

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

No data available

No data available

#### Specific target organ toxicity - single exposure

Specific target organ toxicity - repeated exposure No data available

#### Aspiration hazard No data available

#### **Additional Information**

RTECS: QJ9635000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

Toxicity to fish	LC50 - Pimephales promelas (fathead minnow) - 2.5 mg/l (2- Methylnaphthalene)
Toxicity to daphnia and other aquatic invertebrates	Immobilization EC50 - Daphnia magna (Water flea) - 1.5 mg/l - 48 h(2- Methylnaphthalene)

#### 12.2 Persistence and degradability

#### 12.3 Bioaccumulative potential

Bioaccumulation

Oncorhynchus mykiss (rainbow trout) - 28 d - 0.017 mg/l(2-Methylnaphthalene)

Bioconcentration factor (BCF): 23,500

#### 12.4 Mobility in soil

No data available(2-Methylnaphthalene)

12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company.

#### **Contaminated packaging**

Dispose of as unused product.

#### 14. TRANSPORT INFORMATION

#### DOT (US)

Not dangerous goods IMDG UN number: 3077 Class: 9 Packing group: III EMS-No: F-A, S-F Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (2-Methylnaphthalene) Marine pollutant : yes

#### ΙΑΤΑ

UN number: 3077 Class: 9 Packing group: III Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (2-Methylnaphthalene) Aldrich- M57006

#### **Further information**

EHS-Mark required (ADR 2.2.9.1.10, IMDG code 2.10.3) for single packagings and combination packagings containing inner packagings with Dangerous Goods > 5L for liquids or > 5kg for solids.

#### **15. REGULATORY INFORMATION**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Acute Health Hazard

#### Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components				
	CAS-No.	<b>Revision Date</b>		
2-Methylnaphthalene	91-57-6	2010-08-02		
New Jersey Right To Know Components				
	CAS-No.	<b>Revision Date</b>		
2-Methylnaphthalene	91-57-6	2010-08-02		

#### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### **16. OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

H302	Harmful if swallowed.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

#### HMIS Rating

Health hazard:	2	
Flammability: Physical Hazard	1 0	
<b>NFPA Rating</b> Health hazard: Fire Hazard: Reactivity Hazard <sup>:</sup>	2 1 0	

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956 Version: 6.0

Revision Date: 05/25/2018

Print Date: 06/29/2019

sigma-aldrich.com

#### SAFETY DATA SHEET

Version 5.5 Revision Date 06/13/2014 Print Date 10/19/2018

#### 1. PRODUCT AND COMPANY IDENTIFICATION

1.1	Product identifiers		
	Product name	:	4,4'-DDD
	Product Number Brand	:	49009 Supelco
	CAS-No.	:	72-54-8
1.2	Relevant identified uses of the substance or mixture and uses advised		
	Identified uses	:	Laboratory chemicals, Manufacture of substances
1.3	Details of the supplier of the safety data sheet		safety data sheet
	Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
	Telephone	:	+1 800-325-5832

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

÷

#### 2. HAZARDS IDENTIFICATION

Fax

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 3), H301 Acute toxicity, Dermal (Category 4), H312 Carcinogenicity (Category 2), H351 Acute aquatic toxicity (Category 1), H400 Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

+1 800-325-5052

#### 2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word



Danger

Hazard statement(s) H301 H312 H351 H410	Toxic if swallowed. Harmful in contact with skin. Suspected of causing cancer. Very toxic to aquatic life with long lasting effects.
Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
-------------	--
P280	Wear protective gloves/ protective clothing.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P322	Specific measures (see supplemental first aid instructions on this label).
P330	Rinse mouth.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

## **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Synonyms : 1,1-Dichloro-2,2-bis(4-chlorophenyl)ethane

Formula	:	C <sub>14</sub> H <sub>10</sub> Cl <sub>4</sub>
Molecular Weight	:	320.04 g/mol
CAS-No.	:	72-54-8
EC-No.	:	200-783-0

#### Hazardous components

Component	Classification	Concentration			
2,2-bis(4-Chlorophenyl)-1,1-dichloro-ethane					
	Acute Tox. 3; Acute Tox. 4; Carc. 2; Aquatic Acute 1; Aquatic Chronic 1; H301, H312, H351, H410	-			

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

# **4.3** Indication of any immediate medical attention and special treatment needed no data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

# **5.2** Special hazards arising from the substance or mixture Carbon oxides, Hydrogen chloride gas Nature of decomposition products not known.

#### 5.3 Advice for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

5.4 Further information no data available

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Provide appropriate exhaust ventilation at places where dust is formed.Normal measures for preventive fire protection. For precautions see section 2.2.

# **7.2** Conditions for safe storage, including any incompatibilities Keep container tightly closed in a dry and well-ventilated place.

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

#### 8.2 Exposure controls

#### Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

#### Personal protective equipment

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

#### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: solid
b)	Odour	no data available
c)	Odour Threshold	no data available
d)	рН	no data available
e)	Melting point/freezing point	94.0 - 96.0 °C (201.2 - 204.8 °F)
f)	Initial boiling point and boiling range	193.0 °C (379.4 °F) at 1.3 hPa (1.0 mmHg)
g)	Flash point	no data available
h)	Evapouration rate	no data available
i)	Flammability (solid, gas)	no data available
j)	Upper/lower flammability or explosive limits	no data available
k)	Vapour pressure	< 0.00001 hPa (< 0.00001 mmHg) at 25.0 °C (77.0 °F)
I)	Vapour density	no data available
m)	Relative density	1.38 g/cm3
n)	Water solubility	no data available
o)	Partition coefficient: n- octanol/water	log Pow: 6.02
p)	Auto-ignition temperature	no data available
q)	Decomposition temperature	no data available
r)	Viscosity	no data available
s)	Explosive properties	no data available
t)	Oxidizing properties	no data available
Oth no c	er safety information data available	

#### **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity no data available

**10.2 Chemical stability** Stable under recommended storage conditions.

**10.3** Possibility of hazardous reactions no data available

9.2

- **10.4** Conditions to avoid no data available
- **10.5 Incompatible materials** Strong oxidizing agents
- **10.6 Hazardous decomposition products** Other decomposition products - no data available In the event of fire: see section 5

#### 11. TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Hamster - > 5,000 mg/kg

TDLo Oral - Human - 428.5 mg/kg Remarks: Endocrine:Adrenal cortex hypoplasia.

TDLo Oral - rat - 6,000 mg/kg Remarks: Cardiac:Other changes. Gastrointestinal:Other changes. Kidney, Ureter, Bladder:Changes in both tubules and glomeruli.

TDLo Oral - rat - 14 mg/kg Remarks: Liver:Changes in liver weight. Endocrine:Estrogenic. Musculoskeletal:Other changes.

TDLo Oral - rat - 2,100 mg/kg Remarks: Behavioral:Altered sleep time (including change in righting reflex).

Inhalation: no data available

LD50 Dermal - rabbit - 1,200 mg/kg Remarks: Behavioral:Excitement. Behavioral:Convulsions or effect on seizure threshold. Skin irritation

no data available

# Skin corrosion/irritation

no data available

# Serious eye damage/eye irritation

no data available

#### **Respiratory or skin sensitisation** no data available

no data available

## Germ cell mutagenicity

no data available

#### Carcinogenicity

This product is or contains a component that has been reported to be possibly carcinogenic based on its IARC, ACGIH, NTP, or EPA classification.

Limited evidence of carcinogenicity in animal studies

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### **Reproductive toxicity**

no data available

no data available

Specific target organ toxicity - single exposure no data available

Specific target organ toxicity - repeated exposure no data available

# Aspiration hazard no data available

## Additional Information

RTECS: KI0700000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

Toxicity to fish	LC50 - other fish - 1.18 - 9 mg/l - 96.0 h
	LC50 - Lepomis macrochirus (Bluegill) - 0.04 - 0.05 mg/l - 96.0 h
	LC50 - Oncorhynchus mykiss (rainbow trout) - 0.06 - 0.09 mg/l - 96.0 h
	LC50 - Pimephales promelas (fathead minnow) - 3.47 - 5.58 mg/l - 96.0 h
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia pulex (Water flea) - 0.01 mg/l - 48 h
D	

- 12.2 Persistence and degradability no data available
- **12.3 Bioaccumulative potential** Indication of bioaccumulation.

# 12.4 Mobility in soil

no data available

#### 12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life.

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

#### **Contaminated packaging**

Dispose of as unused product.

#### **14. TRANSPORT INFORMATION**

#### DOT (US)

UN number: 2811 Class: 6.1 Packing group: III Proper shipping name: Toxic solids, organic, n.o.s. (2,2-bis(4-Chlorophenyl)-1,1-dichloro-ethane) Marine pollutant: No Poison Inhalation Hazard: No

#### IMDG

UN number: 2811 Class: 6.1 Packing group: III EMS-No: F-A, S-A Proper shipping name: TOXIC SOLID, ORGANIC, N.O.S. (2,2-bis(4-Chlorophenyl)-1,1-dichloro-ethane) Marine pollutant: No

#### ΙΑΤΑ

UN number: 2811 Class: 6.1 Packing group: III Proper shipping name: Toxic solid, organic, n.o.s. (2,2-bis(4-Chlorophenyl)-1,1-dichloro-ethane)

#### **15. REGULATORY INFORMATION**

#### SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Acute Health Hazard

#### Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

CAS-No.	Revision Date
72-54-8	1993-04-24
CAS-No.	Revision Date
72-54-8	1993-04-24
	CAS-No. 72-54-8 CAS-No. 72-54-8

#### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### **16. OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

Acute Tox.	Acute toxicity			
Aquatic Acute	Acute aquatic toxicity			
Aquatic Chronic	Chronic aquatic toxicity			
Carc.	Carcinogenicity			
H301	Toxic if swallowed.			
H312	Harmful in contact with skin.			
H351	Suspected of causing cancer.			
H400	Very toxic to aquatic life.			
H410	Very toxic to aquatic life with long lasting effects.			
HMIS Rating				
Health hazard	2			
Chronic Health Haza	ard: *			
Flammability:	0			
Physical Hazard	0			
r nysioar nazara	0			
NFPA Rating				
Health hazard:	2			
Fire Hazard:	0			
Reactivity Hazard:	0			

#### **Further information**

Copyright 2014 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.5

Revision Date: 06/13/2014

Print Date: 10/19/2018

# SIGMA-ALDRICH

. . .

# SAFETY DATA SHEET

Version 5.6 Revision Date 05/07/2018 Print Date 06/22/2019

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

....

1.1	Product identifiers Product name	:	4,4'-DDT
	Product Number Brand Index-No.	:	386340 Aldrich 602-045-00-7
	CAS-No.	:	50-29-3

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 6310 USA	
Telephone Fax	:	+1 800-325-5832 +1 800-325-5052	

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 3), H301 Acute toxicity, Dermal (Category 3), H311 Carcinogenicity (Category 2), H351 Specific target organ toxicity - repeated exposure, Oral (Category 1), H372 Acute aquatic toxicity (Category 1), H400 Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Danger Hazard statement(s) H301 + H311 Toxic if swallowed or in contact with skin. H351 Suspected of causing cancer. H372 Causes damage to organs through prolonged or repeated exposure if swallowed. H410 Very toxic to aquatic life with long lasting effects. Precautionary statement(s) P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and

	understood.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing.
P281	Use personal protective equipment as required.
P301 + P310 + P330	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth.
P302 + P352 + P312	IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or doctor/ physician if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P361	Remove/Take off immediately all contaminated clothing.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

#### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Synonyms	: 1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane 1,1-Bis(4-chlorophenyl)-2,2,2-trichloroethane
Formula	: C <sub>14</sub> H <sub>9</sub> Cl <sub>5</sub>
Molecular weight	: 354.49 g/mol
CAS-No.	: 50-29-3
EC-No.	: 200-024-3
Index-No.	: 602-045-00-7

#### Hazardous components

Component	Classification	Concentration		
1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane				
	Acute Tox. 3; Carc. 2; STOT	90 - 100 %		
	RE 1; Aquatic Acute 1; Aquatic			
	Chronic 1; H301 + H311,			
	H351, H372, H410			

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### **4.3 Indication of any immediate medical attention and special treatment needed** No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture No data available

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

## 5.4 Further information

No data available

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Storage class (TRGS 510): 6.1D: Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
1,1,1-Trichloro-2,2- bis(4- chlorophenyl)ethane	50-29-3	TWA	1 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Liver damage Confirmed animal carcinogen with unknown relevance to humans		

TWA	0.5 mg/m3	USA. NIOSH Recommended Exposure Limits
Potential Oc See Append	cupational Carcino	ogen
TWA	1 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
Skin designa	ation	
PEL	1 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Skin		

#### 8.2 Exposure controls

#### Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

#### Personal protective equipment

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a) Appearance Form: solid

b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 107 - 110 °C (225 - 230 °F) - lit.
f)	Initial boiling point and boiling range	260.0 °C (500.0 °F)
g)	Flash point	72.0 - 77.0 °C (161.6 - 170.6 °F)
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	0.0000021 hPa (0.0000016 mmHg) at 20.0 °C (68.0 °F)
I)	Vapour density	No data available
m)	Relative density	0.99 g/cm3
n)	Water solubility	No data available
o)	Partition coefficient: n- octanol/water	log Pow: 6.91
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
<b>Othe</b> No da	r <b>safety information</b> ata available	

#### **10. STABILITY AND REACTIVITY**

10.1 Reactivity No data available

9.2

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5** Incompatible materials Oxidizing agents, Iron and iron salts.

#### 10.6 Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Carbon oxides, Hydrogen chloride gas Other decomposition products - No data available In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - 87.0 mg/kg

Inhalation: No data available

LD50 Dermal - Rabbit - 300.0 mg/kg Remarks: Behavioral:Tremor. Behavioral:Muscle weakness. Behavioral:Ataxia.

No data available

Skin corrosion/irritation No data available

Serious eye damage/eye irritation No data available

Respiratory or skin sensitisation No data available

## Germ cell mutagenicity

No data available

#### Carcinogenicity

Limited evidence of carcinogenicity in animal studies

- IARC: 2A Group 2A: Probably carcinogenic to humans (1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane)
- IARC: 2A Group 2A: Probably carcinogenic to humans (1,1,1-Trichloro-2,2-bis(4chlorophenyl)ethane)
- NTP: RAHC Reasonably anticipated to be a human carcinogen (1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane)
- NTP: RAHC Reasonably anticipated to be a human carcinogen (1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane)
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

No data available

No data available

**Specific target organ toxicity - single exposure** No data available

#### Specific target organ toxicity - repeated exposure

Ingestion - Causes damage to organs through prolonged or repeated exposure.

#### Aspiration hazard No data available

#### Additional Information RTECS: KJ3325000

RIECS. RJ332000

CNS stimulation.

Pancreas. -

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

	Toxicity to fish	LC50 - Pimephales promelas (fathead minnow) - 0.01 mg/l - 96.0 h
		LC50 - Lepomis macrochirus (Bluegill) - 0.01 mg/l - 96.0 h
		LC50 - Oncorhynchus mykiss (rainbow trout) - 0.003400 mg/l - 96.0 h
		LOEC - Oncorhynchus mykiss (rainbow trout) - 150 mg/l - 3.0 d
		NOEC - Oncorhynchus mykiss (rainbow trout) - 113 mg/l - 3.0 d
	Toxicity to daphnia and other aquatic invertebrates	Immobilization EC50 - Daphnia magna (Water flea) - 0.00108 mg/l - 48 h
	Toxicity to algae	LC100 - Scenedesmus quadricauda (Green algae) - > 20 mg/l - 7 d
12.2	Persistence and degrad	dability
2.3 E	Bioaccumulative potentia	

#### 12.3

**Bioaccumulation** 

Oncorhynchus mykiss (rainbow trout) - 20 d - 0.001 mg/l

Bioconcentration factor (BCF): 46,670

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

#### Contaminated packaging

Dispose of as unused product.

#### **14. TRANSPORT INFORMATION**

#### DOT (US)

UN number: 2811 Class: 6.1 Packing group: III Proper shipping name: Toxic solids, organic, n.o.s. (1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane) Reportable Quantity (RQ): 1 lbsMarine pollutant:yes Poison Inhalation Hazard: No

#### IMDG

UN number: 2811 Class: 6.1 Packing group: III EMS-No: F-A, S-A Proper shipping name: TOXIC SOLID, ORGANIC, N.O.S. (1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane) Marine pollutant:yes

#### ΙΑΤΑ

UN number: 2811 Class: 6.1 Packing group: III Proper shipping name: Toxic solid, organic, n.o.s. (1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane)

## **15. REGULATORY INFORMATION**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components		
	CAS-No.	Revision Date
1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane	50-29-3	1993-02-16
	CAS-No	Revision Date
1.1.1-Trichloro-2.2-bis(4-chlorophenyl)ethane	50-29-3	1993-02-16
	00 20 0	
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
1,1,1-Irichloro-2,2-bis(4-chlorophenyl)ethane	50-29-3	1993-02-16
	CAS-No.	Revision Date
1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane	50-29-3	1993-02-16
	CAS-No	Revision Date
1 1 1-Trichloro-2 2-bis(A-chlorophenyl)ethane	50-29-3	1993-02-16
	00 20 0	1000 02 10
New Jersey Right To Know Components		
	CAS-No.	Revision Date
1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane	50-29-3	1993-02-16
	CAS-No.	Revision Date
1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane	50-29-3	1993-02-16
California Bran 65 Componente		
WAPNING This product contains a chamical known to the		Povicion Data
State of California to cause cancer	50-20-3	2008-06-17
1 1 1-Trichloro-2 2-bis(A-chlorophonyl) othano	50-29-5	2000-00-17
1, 1, 1 <sup>-</sup> 111011010-2, 2-013(4-011010p11010)/ethane		
WARNING: This product contains a chemical known to the	CAS-No.	Revision Date
State of California to cause birth defects or other reproductive	50-29-3	2008-06-17
harm.		
1,1,1-I richloro-2,2-bis(4-chlorophenyl)ethane		
WARNING! This product contains a chemical known to the	CAS-No.	Revision Date
State of California to cause cancer.	50-29-3	2008-06-17
1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane		
WARNING: This product contains a chemical known to the	CAS-No	Revision Date
State of California to cause birth defects or other reproductive	50-29-3	2008-06-17
harm.		
1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane		

## **16. OTHER INFORMATION**

Full text of H-Statements referred to under sections 2 and 3.

Acute Tox.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Carc.	Carcinogenicity
H301	Toxic if swallowed.
H301 + H311	Toxic if swallowed or in contact with skin.
H311	Toxic in contact with skin.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure if swallowed.

#### HMIS Rating

Health hazard:	2
Chronic Health Hazard:	*
Flammability:	0
Physical Hazard	0

#### **NFPA** Rating

Health hazard:	2
Fire Hazard:	2
Reactivity Hazard:	0

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.6

Revision Date: 05/07/2018

Print Date: 06/22/2019

# SIGMA-ALDRICH

. . .

# SAFETY DATA SHEET

Version 5.6 Revision Date 05/07/2018 Print Date 06/22/2019

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

....

1.1	Product identifiers Product name	:	4,4'-DDT
	Product Number Brand Index-No.	:	386340 Aldrich 602-045-00-7
	CAS-No.	:	50-29-3

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
Telephone Fax	:	+1 800-325-5832 +1 800-325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 3), H301 Acute toxicity, Dermal (Category 3), H311 Carcinogenicity (Category 2), H351 Specific target organ toxicity - repeated exposure, Oral (Category 1), H372 Acute aquatic toxicity (Category 1), H400 Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Danger Hazard statement(s) H301 + H311 Toxic if swallowed or in contact with skin. H351 Suspected of causing cancer. H372 Causes damage to organs through prolonged or repeated exposure if swallowed. H410 Very toxic to aquatic life with long lasting effects. Precautionary statement(s) P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and

	understood.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing.
P281	Use personal protective equipment as required.
P301 + P310 + P330	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth.
P302 + P352 + P312	IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or doctor/ physician if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P361	Remove/Take off immediately all contaminated clothing.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

#### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Synonyms	: 1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane 1,1-Bis(4-chlorophenyl)-2,2,2-trichloroethane
Formula	: C <sub>14</sub> H <sub>9</sub> Cl <sub>5</sub>
Molecular weight	: 354.49 g/mol
CAS-No.	: 50-29-3
EC-No.	: 200-024-3
Index-No.	: 602-045-00-7

#### Hazardous components

Component	Classification	Concentration
1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane		
	Acute Tox. 3; Carc. 2; STOT	90 - 100 %
	RE 1; Aquatic Acute 1; Aquatic	
	Chronic 1; H301 + H311,	
	H351, H372, H410	

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### **4.3 Indication of any immediate medical attention and special treatment needed** No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture No data available

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

## 5.4 Further information

No data available

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Storage class (TRGS 510): 6.1D: Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
1,1,1-Trichloro-2,2- bis(4- chlorophenyl)ethane	50-29-3	TWA	1 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Liver damage Confirmed animal carcinogen with unknown relevance to humans		

TWA	0.5 mg/m3	USA. NIOSH Recommended Exposure Limits
Potential Oc See Append	cupational Carcino	ogen
TWA	1 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
Skin designa	ation	
PEL	1 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Skin		

#### 8.2 Exposure controls

#### Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

#### Personal protective equipment

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a) Appearance Form: solid

b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 107 - 110 °C (225 - 230 °F) - lit.
f)	Initial boiling point and boiling range	260.0 °C (500.0 °F)
g)	Flash point	72.0 - 77.0 °C (161.6 - 170.6 °F)
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	0.0000021 hPa (0.0000016 mmHg) at 20.0 °C (68.0 °F)
I)	Vapour density	No data available
m)	Relative density	0.99 g/cm3
n)	Water solubility	No data available
o)	Partition coefficient: n- octanol/water	log Pow: 6.91
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
<b>Othe</b> No da	r <b>safety information</b> ata available	

#### **10. STABILITY AND REACTIVITY**

10.1 Reactivity No data available

9.2

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5** Incompatible materials Oxidizing agents, Iron and iron salts.

#### 10.6 Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Carbon oxides, Hydrogen chloride gas Other decomposition products - No data available In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - 87.0 mg/kg

Inhalation: No data available

LD50 Dermal - Rabbit - 300.0 mg/kg Remarks: Behavioral:Tremor. Behavioral:Muscle weakness. Behavioral:Ataxia.

No data available

Skin corrosion/irritation No data available

Serious eye damage/eye irritation No data available

Respiratory or skin sensitisation No data available

## Germ cell mutagenicity

No data available

#### Carcinogenicity

Limited evidence of carcinogenicity in animal studies

- IARC: 2A Group 2A: Probably carcinogenic to humans (1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane)
- IARC: 2A Group 2A: Probably carcinogenic to humans (1,1,1-Trichloro-2,2-bis(4chlorophenyl)ethane)
- NTP: RAHC Reasonably anticipated to be a human carcinogen (1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane)
- NTP: RAHC Reasonably anticipated to be a human carcinogen (1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane)
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

No data available

No data available

**Specific target organ toxicity - single exposure** No data available

#### Specific target organ toxicity - repeated exposure

Ingestion - Causes damage to organs through prolonged or repeated exposure.

#### Aspiration hazard No data available

#### Additional Information RTECS: KJ3325000

RIECS. RJ332000

CNS stimulation.

Pancreas. -

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

	Toxicity to fish	LC50 - Pimephales promelas (fathead minnow) - 0.01 mg/l - 96.0 h
		LC50 - Lepomis macrochirus (Bluegill) - 0.01 mg/l - 96.0 h
		LC50 - Oncorhynchus mykiss (rainbow trout) - 0.003400 mg/l - 96.0 h
		LOEC - Oncorhynchus mykiss (rainbow trout) - 150 mg/l - 3.0 d
		NOEC - Oncorhynchus mykiss (rainbow trout) - 113 mg/l - 3.0 d
	Toxicity to daphnia and other aquatic invertebrates	Immobilization EC50 - Daphnia magna (Water flea) - 0.00108 mg/l - 48 h
	Toxicity to algae	LC100 - Scenedesmus quadricauda (Green algae) - > 20 mg/l - 7 d
12.2	Persistence and degradability	
2.3 E	Bioaccumulative potentia	

#### 12.3

**Bioaccumulation** 

Oncorhynchus mykiss (rainbow trout) - 20 d - 0.001 mg/l

Bioconcentration factor (BCF): 46,670

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

#### Contaminated packaging

Dispose of as unused product.

#### **14. TRANSPORT INFORMATION**

#### DOT (US)

UN number: 2811 Class: 6.1 Packing group: III Proper shipping name: Toxic solids, organic, n.o.s. (1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane) Reportable Quantity (RQ): 1 lbsMarine pollutant:yes Poison Inhalation Hazard: No

#### IMDG

UN number: 2811 Class: 6.1 Packing group: III EMS-No: F-A, S-A Proper shipping name: TOXIC SOLID, ORGANIC, N.O.S. (1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane) Marine pollutant:yes

#### ΙΑΤΑ

UN number: 2811 Class: 6.1 Packing group: III Proper shipping name: Toxic solid, organic, n.o.s. (1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane)

## **15. REGULATORY INFORMATION**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components		
	CAS-No.	Revision Date
1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane	50-29-3	1993-02-16
	CAS-No	Revision Date
1.1.1-Trichloro-2.2-bis(4-chlorophenyl)ethane	50-29-3	1993-02-16
	00 20 0	
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
1,1,1-Irichloro-2,2-bis(4-chlorophenyl)ethane	50-29-3	1993-02-16
	CAS-No.	Revision Date
1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane	50-29-3	1993-02-16
	CAS-No	Revision Date
1 1 1-Trichloro-2 2-bis(A-chlorophenyl)ethane	50-29-3	1993-02-16
	00 20 0	1000 02 10
New Jersey Right To Know Components		
	CAS-No.	Revision Date
1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane	50-29-3	1993-02-16
	CAS-No.	Revision Date
1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane	50-29-3	1993-02-16
California Bran 65 Componente		
WAPNING This product contains a chamical known to the		Povicion Data
State of California to cause cancer	50-20-3	2008-06-17
1 1 1-Trichloro-2 2-bis(A-chlorophonyl) othano	50-29-5	2000-00-17
1, 1, 1 <sup>-</sup> 111011010-2, 2-013(4-011010p11010)/ethane		
WARNING: This product contains a chemical known to the	CAS-No.	Revision Date
State of California to cause birth defects or other reproductive	50-29-3	2008-06-17
harm.		
1,1,1-I richloro-2,2-bis(4-chlorophenyl)ethane		
WARNING! This product contains a chemical known to the	CAS-No.	Revision Date
State of California to cause cancer.	50-29-3	2008-06-17
1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane		
WARNING: This product contains a chemical known to the	CAS-No	Revision Date
State of California to cause birth defects or other reproductive	50-29-3	2008-06-17
harm.		
1,1,1-Trichloro-2,2-bis(4-chlorophenyl)ethane		

## **16. OTHER INFORMATION**

Full text of H-Statements referred to under sections 2 and 3.

Acute Tox.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Carc.	Carcinogenicity
H301	Toxic if swallowed.
H301 + H311	Toxic if swallowed or in contact with skin.
H311	Toxic in contact with skin.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure if swallowed.

#### HMIS Rating

Health hazard:	2
Chronic Health Hazard:	*
Flammability:	0
Physical Hazard	0

#### **NFPA** Rating

Health hazard:	2
Fire Hazard:	2
Reactivity Hazard:	0

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.6

Revision Date: 05/07/2018

Print Date: 06/22/2019

# SAFETY DATA SHEET

Version 6.1 Revision Date 05/28/2017 Print Date 06/28/2019

1. PR	ODUCT AND COMPANY ID	ENT	TIFICATION
1.1	Product identifiers Product name	:	4-Methyl-2-pentanone
	Product Number Brand Index-No.	:	293261 SIGALD 606-004-00-4
	CAS-No.	:	108-10-1
1.2 Relevant identified uses of the substance or mixture and uses advised against		e substance or mixture and uses advised against	
	Identified uses	:	Laboratory chemicals, Synthesis of substances
1.3 Details of the supplier of the safety data sheet		safety data sheet	
	Company	:	Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES
	Telephone	:	+1 314 771-5765

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

2

## 2. HAZARDS IDENTIFICATION

Fax

#### 2.1 Classification of the substance or mixture

**GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)** Flammable liquids (Category 2), H225 Acute toxicity, Inhalation (Category 4), H332 Eye irritation (Category 2A), H319 Carcinogenicity (Category 2), H351 Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

+1 800 325-5052

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word	Danger
Hazard statement(s)	
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.

Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### **2.3 Hazards not otherwise classified (HNOC) or not covered by GHS** May form explosive peroxides.

#### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 **Substances** Synonyms : Isobutyl methyl ketone Methyl isobutyl ketone Isopropylacetone Formula C<sub>6</sub>H<sub>12</sub>O : : 100.16 g/mol Molecular weight CAS-No. 108-10-1 : EC-No. : 203-550-1 606-004-00-4 Index-No. : Hazardous components Component Classification Concentration 4-Methylpentan-2-one Flam. Liq. 2; Acute Tox. 4; Eye <= 100 % Irrit. 2A; Carc. 2; STOT SE 3;

H225, H319, H332, H335,

H351

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### **4.3 Indication of any immediate medical attention and special treatment needed** No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

Suitable extinguishing media Dry powder Dry sand

Unsuitable extinguishing media Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture Carbon oxides

#### **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.

**5.4 Further information** Use water spray to cool unopened containers.

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

#### **6.2** Environmental precautions Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

- 6.3 Methods and materials for containment and cleaning up Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
- 6.4 Reference to other sections For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment.Keep away from sources of ignition - No smoking.Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis			
4-Methylpentan-2-	108-10-1	STEL	75 ppm	USA. ACGIH Threshold Limit Values			
one				(TLV)			
	Remarks	Upper Resp	Upper Respiratory Tract irritation				
		Headache					
		Dizziness	Dizziness				
			Substances for which there is a Biological Exposure Index or Indices				
		(See DENS Section)					
		STEI	STEL 75.00000 ppm UISA ACGIH Threshold Limit Values				
		OTEE	70.000000 ppm	(TLV)			
		Upper Resp	iratory Tract irritation	on			
		Headache					
		Dizziness					
		(see BEI® s	for which there is a ection)	a Biological Exposure Index or Indices			
		Confirmed a	nimal carcinogen v	with unknown relevance to humans			
		TWA	50 ppm	USA. OSHA - TABLE Z-1 Limits for			
			205 mg/m3	Air Contaminants - 1910.1000			
		STEL	75 ppm	USA. OSHA - TABLE Z-1 Limits for			
			300 mg/m3	Air Contaminants - 1910.1000			
		TWA	100.000000	USA. Occupational Exposure Limits			
			ppm	(OSHA) - Table Z-1 Limits for Air			
			410.000000	Contaminants			
		The value in	The value in mg/m3 is approximate.				
		TWA	100 ppm	USA Occupational Exposure Limits			
			410 mg/m3	(OSHA) - Table Z-1 Limits for Air			
			- <b>J</b>	Contaminants			
		The value in	mg/m3 is approxir	nate.			
		TWA	20 ppm	USA. ACGIH Threshold Limit Values (TLV)			
		Upper Resp	iratory Tract irritatio	on			
		Headache	<b>,</b>	-			
		Dizziness					
		Substances for which there is a Biological Exposure Index or Indices					
		(see BEI® section)					
		Confirmed animal carcinogen with unknown relevance to humans					
		TWA	20.000000 ppm	USA. ACGIH Threshold Limit Values			
		Upper Resp	on				
		Headache					
		Dizziness	Dizziness				
		Substances	for which there is a	a Biological Exposure Index or Indices			

(see BEI® section) Confirmed animal carcinogen with unknown relevance to humans		
TWA 50.000000 ppm USA. NIOSH Recommende 205.000000 Exposure Limits mg/m3		
ST	75.000000 ppm 300.000000 mg/m3	USA. NIOSH Recommended Exposure Limits

#### **Biological occupational exposure limits**

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
4-Methylpentan-2- one	108-10-1	methyl isobutyl ketone	2.0000 mg/l	In urine	
	Remarks	End of shift (As	s soon as po	ssible after exposure	e ceases)
		methyl	1.0000	Urine	ACGIH - Biological
		isobutyl	mg/l		Exposure Indices
		ketone			(BEI)
		End of shift (As	s soon as po	ssible after exposure	e ceases)
		methyl	1 mg/l	Urine	ACGIH - Biological
		isobutyl	_		Exposure Indices
		ketone			(BEI)
		End of shift (As soon as possible after exposure ceases)			e ceases)

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Splash contact Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 175 min Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industria situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use (US) or type ABEK (EN 14387) respirator cartridges as a backup to enginee protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: -80 °C (-112 °F) - lit.
f)	Initial boiling point and boiling range	117 - 118 °C (243 - 244 °F)
g)	Flash point	14 °C (57 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 8 %(V) Lower explosion limit: 1.2 %(V)
k)	Vapour pressure	20 hPa at 20 °C (68 °F)
I)	Vapour density	3.46 - (Air = 1.0)
m)	Relative density	0.801 g/cm3 at 25 °C (77 °F)
n)	Water solubility	ca.20 g/l
o)	Partition coefficient: n- octanol/water	log Pow: 1.31
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Oth	ner safety information	
	Surface tension	23.6 mN/m at 20 °C (68 °F)
	Relative vapour density	3.46 - (Air = 1.0)

#### **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity

9.2

No data available

#### 10.2 Chemical stability

Stable under recommended storage conditions. Test for peroxide formation before distillation or evaporation. Test for peroxide formation or discard after 1 year. Stable under recommended storage conditions.

#### 10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air. Vapours may form explosive mixture with air.

#### 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight. May form peroxides of unknown stability. Heat, flames and sparks.

#### 10.5 Incompatible materials

Oxidizing agents, Strong bases

# Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - 2,080 mg/kg(4-Methylpentan-2-one) LC50 Inhalation - Rat - 4 h - 8.2 - 16.4 mg/l(4-Methylpentan-2-one) LD50 Dermal - Rabbit - > 16,000 mg/kg(4-Methylpentan-2-one) No data available(4-Methylpentan-2-one)

#### Skin corrosion/irritation

Skin - Rabbit(4-Methylpentan-2-one) Result: Mild skin irritation - 24 h

#### Serious eye damage/eye irritation

Eyes - Rabbit(4-Methylpentan-2-one) Result: Moderate eye irritation - 24 h

#### Respiratory or skin sensitisation

No data available(4-Methylpentan-2-one)

#### Germ cell mutagenicity

No data available(4-Methylpentan-2-one)

#### Carcinogenicity

- IARC: 2B Group 2B: Possibly carcinogenic to humans (4-Methylpentan-2-one)
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### **Reproductive toxicity**

No data available(4-Methylpentan-2-one)

No data available(4-Methylpentan-2-one)

**Specific target organ toxicity - single exposure** May cause respiratory irritation.(4-Methylpentan-2-one)

Specific target organ toxicity - repeated exposure No data available

## Aspiration hazard

No data available(4-Methylpentan-2-one)

#### **Additional Information**

RTECS: SA9275000

Blurred vision, Dermatitis, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.(4-Methylpentan-2-one)

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence(4-Methylpentan-2-one)

#### 12. ECOLOGICAL INFORMATION

#### 12.1 Toxicity

Toxicity to fish	LC0 - Leuciscus idus melanotus - 480 mg/l - 48 h(4-Methylpentan-2-one)
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - 1,550 - 3,623 mg/l - 24 h(4- Methylpentan-2-one)
Toxicity to algae	EC50 - Desmodesmus subspicatus (green algae) - 980 - 2,000 mg/l - 48 h(4

#### 12.2 Persistence and degradability

Biodegradability Biotic/Aerobic - Exposure time 7 d(4-Methylpentan-2-one)

Methylpentan-2-one)

#### 12.3 Bioaccumulative potential

No data available

#### **12.4 Mobility in soil** No data available(4-Methylpentan-2-one)

#### 12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

No data available

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Burn in a chemical incinerator equipped with an afterburner and scrubber b highly flammable. Contact a licensed professional waste disposal service to dispose of this material.

#### Contaminated packaging

Dispose of as unused product.

#### 14. TRANSPORT INFORMATION

#### DOT (US)

UN number: 1245 Class: 3 Packing group: II Proper shipping name: Methyl isobutyl ketone Reportable Quantity (RQ) : 5000 lbs

Poison Inhalation Hazard: No

#### IMDG

UN number: 1245 Class: 3 Packing group: II Proper shipping name: METHYL ISOBUTYL KETONE

#### ΙΑΤΑ

UN number: 1245 Class: 3 Packing group: II Proper shipping name: Methyl isobutyl ketone

#### **15. REGULATORY INFORMATION**

#### SARA 302 Components

EMS-No: F-E, S-D

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components The following components are subject to reporting levels establis	hed by SARA Title III.	Section 313:
	CAS-No.	Revision Date
4-Methylpentan-2-one	108-10-1	1993-04-24
SARA 311/312 Hazards Fire Hazard, Acute Health Hazard, Chronic Health Hazard		
Massachusetts Right To Know Components		
	CAS-No.	Revision Date
4-Methylpentan-2-one	108-10-1	1993-04-24
Pennsylvania Right To Know Components		
· · · · · · · · · · · · · · · · · · ·	CAS-No.	Revision Date
4-Methylpentan-2-one	108-10-1	1993-04-24
	CAS-No.	Revision Date
4-Methylpentan-2-one	108-10-1	1993-04-24
New Jersey Right To Know Components		
, , , , , , , , , , , , , , , , , , ,	CAS-No.	Revision Date
4-Methylpentan-2-one	108-10-1	1993-04-24
California Prop. 65 Components		
WARNING! This product contains a chemical known to the	CAS-No.	Revision Date
State of California to cause cancer.	108-10-1	2011-11-18
4-Methylpentan-2-one		
WARNING: This product contains a chemical known to the	CAS-No.	Revision Date
State of California to cause birth defects or other reproductive	108-10-1	2011-11-18
harm.		
4-Metnyipentan-2-one		

#### **16. OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.

#### HMIS Rating

Health hazard:	2
Chronic Health Hazard:	*
Flammability:	3
Physical Hazard	0

#### **NFPA** Rating

Health hazard:	2
Fire Hazard:	3
Reactivity Hazard:	0

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling

or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956 Version: 6.1

Revision Date: 05/28/2017

Print Date: 06/28/2019

# SIGMA-ALDRICH

# SAFETY DATA SHEET

Version 3.21 Revision Date 08/21/2018 Print Date 10/19/2018

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

1.1	Product identifiers Product name	:	Acetone
	Product Number Brand Index-No.	:	650501 Sigma-Aldrich 606-001-00-8
	CAS-No.	:	67-64-1

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
Telephone Fax	:	+1 800-325-5832 +1 800-325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Eye irritation (Category 2A), H319 Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)	
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
Precautionary statement(s)	
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
--------------------	--
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ eye protection/ face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing.
	Rinse skin with water/shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for
	breathing. Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to
	extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

## **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Formula	:	С <sub>3</sub> Н <sub>6</sub> О
Molecular weight	:	58.08 g/mol
CAS-No.	:	67-64-1
EC-No.	:	200-662-2
Index-No.	:	606-001-00-8
Registration number	:	01-2119471330-49-XXXX

#### Hazardous components

Component	Classification	Concentration
Acetone		
	Flam. Liq. 2; Eye Irrit. 2A; STOT SE 3; H225, H319, H336	90 - 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### **4.3 Indication of any immediate medical attention and special treatment needed** No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

**Suitable extinguishing media** Dry powder Dry sand

Unsuitable extinguishing media Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture No data available

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

Use water spray to cool unopened containers.

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### 6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment.Keep away from sources of ignition - No smoking.Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510): 3: Flammable liquids

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# 8.1 Control parameters

# Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis
			parameters	
Acetone	67-64-1	TWA	250 ppm	USA. ACGIH Threshold Limit Values
				(TLV)
	Remarks	Central Nervous System impairment		
		Upper Respiratory Tract irritation		
		Eye irritation		
		Substances for which there is a Biological Exposure Index or Indices		
		(see BEI® section)		

Not classifiat	classifiable as a human carcinogen		
STEL	500 ppm	USA. ACGIH Threshold Limit Values (TLV)	
Central Nerv	ous System impair	ment	
Eye irritation			
Substances f (see BEI® se	for which there is a action)	Biological Exposure Index or Indices	
Not classifiat	ole as a human cai	rcinogen	
TWA	250 ppm 590 mg/m3	USA. NIOSH Recommended	
TWA	1,000 ppm 2 400 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table 7-1 Limits for Air	
	2,100 mg/mo	Contaminants	
The value in	mg/m3 is approxin	nate.	
STEL	750 ppm 1,780 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
С	3,000 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)	
PEL	500 ppm 1,200 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)	

#### **Biological occupational exposure limits**

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
	-	Acetone	25 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (As soon as possible after exposure ceases)			

#### Predicted No Effect Concentration (PNEC)

Compartment	Value
Soil	33.3 mg/kg
Marine water	1.06 mg/l
Fresh water	10.6 mg/l
Marine sediment	3.04 mg/kg
Fresh water sediment	30.4 mg/kg
Onsite sewage treatment plant	100 mg/l

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 480 min Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M) Splash contact Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 480 min Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid, clear Colour: colourless
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: -94 °C (-137 °F)
f)	Initial boiling point and boiling range	56 °C (133 °F) at 1,013 hPa (760 mmHg)
g)	Flash point	-17.0 °C (1.4 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 13 %(V) Lower explosion limit: 2 %(V)
k)	Vapour pressure	533.3 hPa (400.0 mmHg) at 39.5 °C (103.1 °F) 245.3 hPa (184.0 mmHg) at 20.0 °C (68.0 °F)
I)	Vapour density	No data available
m)	Relative density	0.791 g/mL at 25 °C (77 °F)
n)	Water solubility	completely miscible
o)	Partition coefficient: n- octanol/water	log Pow: -0.24
p)	Auto-ignition temperature	465.0 °C (869.0 °F)
q)	Decomposition temperature	No data available

	r)	Viscosity	No data available			
	s)	Explosive properties	No data available			
	t)	Oxidizing properties	No data available			
9.2	Othe	r safety information				
		Surface tension	23.2 mN/m at 20.0 °C (68.0 °F)			
10.	STAB	ILITY AND REACTIVITY				
10.1	<b>Reac</b> No da	c <b>tivity</b> ata available				
10.2	<b>Cher</b> Stabl	nical stability le under recommended sto	rage conditions.			
10.3	<b>Poss</b> Vapo	<b>sibility of hazardous reac</b> ours may form explosive mi	tions xture with air.			
10.4	<b>Cond</b> Heat	<b>ditions to avoid</b> , flames and sparks.				
10.5	<b>Inco</b> Base	<b>mpatible materials</b> s, Oxidizing agents, Reduc	cing agents, Acetone reacts violently with phosphorous oxychloride.			
10.6	<ul> <li>Hazardous decomposition products         Hazardous decomposition products formed under fire conditions Carbon oxides         Other decomposition products - No data available         In the event of fire: see section 5     </li> </ul>					
11.	τοχιά	COLOGICAL INFORMATI	ON			
11.1	l Inf	ormation on toxicologica	I effects			
	Acute toxicity LD50 Oral - Rat - 5,800 mg/kg Remarks: Behavioral:Altered sleep time (including change in righting reflex). Behavioral:Tremor. Behavioral:Headache. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.					
	LC50 Inhalation - Rat - 8 h - 50,100 mg/m3 Remarks: Drowsiness Dizziness Unconsciousness					
	LD50 Dermal - Guinea pig - 7,426 mg/kg					
	No da	ata available				
	<b>Skin corrosion/irritation</b> Skin - Rabbit Result: Mild skin irritation - 24 h					
	Serious eye damage/eye irritation					

Eyes - Rabbit Result: Eye irritation - 24 h

# Respiratory or skin sensitisation

- Guinea pig Result: Does not cause skin sensitisation.

Germ cell mutagenicity No data available

#### Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

probable, possible or confirmed human carcinogen by IARC.

- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

No data available

No data available

**Specific target organ toxicity - single exposure** May cause drowsiness or dizziness.

#### Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

# Additional Information

RTECS: AL3150000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Kidney - Irregularities - Based on Human Evidence Skin - Dermatitis - Based on Human Evidence Kidney - Irregularities - Based on Human Evidence Skin - Dermatitis - Based on Human Evidence

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

Toxicity to fish	LC50 - Oncorhynchus mykiss (rainbow trout) - 5,540 mg/l - 96 h
Toxicity to daphnia and other aquatic invertebrates	LC50 - Daphnia magna (Water flea) - 8,800 mg/l - 48 h
Toxicity to algae	Remarks: No data available

12.2 Persistence and degradability Biodegradability Result: 91 % - Readily biodegradable. (OECD Test Guideline 301B)

#### **12.3 Bioaccumulative potential** Does not bioaccumulate.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

No data available

# **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Contact a licensed professional waste disposal service to dispose of this material.

#### **Contaminated packaging**

Dispose of as unused product.

#### **14. TRANSPORT INFORMATION**

#### DOT (US)

UN number: 1090 Proper shipping name Reportable Quantity ( Poison Inhalation Haz	Class: 3 e: Acetone RQ): 5000 lbs zard: No	Packing group: II	
IMDG UN number: 1090 Proper shipping name	Class: 3 e: ACETONE	Packing group: II	EMS-No: F-E, S-D
<b>IATA</b> UN number: 1090	Class: 3	Packing group: II	

#### **15. REGULATORY INFORMATION**

Proper shipping name: Acetone

#### SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### Massachusetts Right To Know Components

	CAS-No.	Revision Date
Acetone	67-64-1	1993-02-16
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Acetone	67-64-1	1993-02-16

#### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### **16. OTHER INFORMATION**

Full text of H-Statements referred to under sections 2 and 3.

Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
STOT SE	Specific target organ toxicity - single exposure

#### Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

**Preparation Information** Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 3.21

Revision Date: 08/21/2018

Print Date: 10/19/2018



# SAFETY DATA SHEET

Version 6.2 Revision Date 03/12/2019 Print Date 06/28/2019

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 **Product identifiers**

Product name · Antimony

:	266329
:	Aldrich
:	7440-36-0
	:

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

: Laboratory chemicals, Synthesis of substances Identified uses

#### 1.3 Details of the supplier of the safety data sheet

Company	: Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES
Telephone	: +1 314 771-5765

#### : +1 800 325-5052 **Emergency telephone number** 1.4

Emergency Phone # : +1-703-527-3887

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 3), H301 Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram

Fax



Signal word

Danger

Hazar	d statem	en	t(s)	
H301				
H335				
<b>D</b>				. /

Toxic if swallowed. May cause respiratory irritation.

Precautionary statement(s) P261

Aldrich - 266329

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Page 1 of 9



P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P301 + P310 + P330	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

## 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

#### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Formula	:	Sb
Molecular weight	:	121.76 g/mol
CAS-No.	:	7440-36-0
EC-No.	:	231-146-5
Molecular weight CAS-No. EC-No.	:	121.76 g/mol 7440-36-0 231-146-5

Component	Classification	Concentration
Antimony		
	Acute Tox. 3; STOT SE 3;	<= 100 %
	כככח, דטכח	

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Aldrich - 266329

Page 2 of 9



- **4.2 Most important symptoms and effects, both acute and delayed** The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
- **4.3 Indication of any immediate medical attention and special treatment needed** No data available

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

- **5.2 Special hazards arising from the substance or mixture** Antimony oxide
- **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.
- 5.4 Further information No data available

# **SECTION 6:** Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear respiratory protection. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.
- **6.2 Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not let product enter drains.
- **6.3 Methods and materials for containment and cleaning up** Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.
- **6.4** Reference to other sections For disposal see section 13.

## SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs. Avoid contact with skin and eyes. Avoid formation of dust and aerosols.

Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

# 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Air sensitive. Moisture sensitive. Handle and store under inert gas. Keep in a dry place.

Aldrich - 266329

Page 3 of 9



Storage class (TRGS 510): 6.1D: Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

#### **Components with workplace control parameters**

Component	CAS-No.	Value	Control parameters	Basis
Antimony	7440-36-0	TWA	0.5 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	0.5 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	0.5 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Upper Resp Skin irritati	spiratory Tract irritation ation	
		PEL	0.5 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

#### 8.2 Exposure controls

#### Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

#### **Personal protective equipment**

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Aldrich - 266329

Page 4 of 9



data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a fullface particle respirator type N99 (US) or type P2 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### **Control of environmental exposure**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: powder
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 630 °C (1166 °F) - lit.
f)	Initial boiling point and boiling range	1,635 °C 2,975 °F - lit.
g)	Flash point	()Not applicable
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	No data available
I)	Vapour density	No data available
m)	Relative density	6.69 g/cm3 at 25 °C (77 °F)
n)	Water solubility	No data available
0)	Partition coefficient: n-octanol/water	Not applicable for inorganic substances

Aldrich - 266329

Page 5 of 9



- p) Auto-ignition No data available temperature
- q) Decomposition No data available temperature
- r) Viscosity No data available
- s) Explosive properties No data available
- t) Oxidizing properties No data available
- 9.2 Other safety information No data available

# **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

No data available

#### **10.2 Chemical stability** Stable under recommended storage conditions.

- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5 Incompatible materials** Strong oxidizing agents

#### **10.6 Hazardous decomposition products** Hazardous decomposition products formed under fire conditions. - Antimony oxide Other decomposition products - No data available In the event of fire: see section 5

# **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### **Acute toxicity**

LD50 Oral - Rat - 100 mg/kg Inhalation: No data available Dermal: No data available No data available

#### **Skin corrosion/irritation** No data available

Serious eye damage/eye irritation No data available

#### **Respiratory or skin sensitisation** No data available

Germ cell mutagenicity No data available

#### Carcinogenicity

Aldrich - 266329

Page 6 of 9



- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity** No data available

No data available

**Specific target organ toxicity - single exposure** May cause respiratory irritation.

Specific target organ toxicity - repeated exposure No data available

**Aspiration hazard** No data available

Additional Information

RTECS: CC4025000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

# SECTION 12: Ecological information

## **12.1 Toxicity**

Toxicity to fish

LC50 - Cyprinodon variegatus (sheepshead minnow) - 6.2 - 8.3 mg/l - 96.0 h Remarks: No data available

# 12.2 Persistence and degradability

Biodegradability Result: - According to the results of tests of biodegradability this product is not readily biodegradable. Remarks: The methods for determining biodegradability are not applicable to inorganic substances.

# 12.3 Bioaccumulative potential

No data available

**12.4 Mobility in soil** No data available

#### 12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

**12.6 Other adverse effects** 

Aldrich - 266329

Page 7 of 9



# SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

#### Product

Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. Offer surplus and non-recyclable solutions to a licensed disposal company.

#### **Contaminated packaging**

Dispose of as unused product.

#### **SECTION 14: Transport information**

#### DOT (US)

UN number: 2871 Class: 6.1 Packing group: III Proper shipping name: Antimony powder Reportable Quantity (RQ): 5000 lbs Poison Inhalation Hazard: No

#### IMDG

UN number: 2871 Class: 6.1 Packing group: III EMS-No: F-A, S-A Proper shipping name: ANTIMONY POWDER Marine pollutant : yes

#### ΙΑΤΑ

UN number: 2871 Class: 6.1 Packing group: III Proper shipping name: Antimony powder

#### **SECTION 15: Regulatory information**

#### SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

#### SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
Antimony	7440-36-0	2007-07-01

#### SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

**Massachusetts Right To Know Components** No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components Antimony	CAS-No. 7440-36-0	Revision Date
Antimony	CAS-No. 7440-36-0	Revision Date 2007-07-01

Aldrich - 266329

The life science business of Merck KGaA, Darmstadt, Germany operates as MilliporeSigma in the US and Canada



Page 8 of 9

# New Jersey Right To Know Components

Antimony

CAS-No. 7440-36-0 Revision Date 2007-07-01

# California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

## **SECTION 16: Other information**

#### **Further information**

Copyright 2018 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.2

Revision Date: 03/12/2019

Print Date: 06/28/2019

Aldrich - 266329

Page 9 of 9



# SIGMA-ALDRICH

# SAFETY DATA SHEET

Version 4.13 Revision Date 09/12/2018 Print Date 06/28/2019

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

1.1	Product identifiers Product name	:	Arsenic	
	Product Number Brand Index-No.	:	202657 Aldrich 033-001-00-X	
	CAS-No.	:	7440-38-2	

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
Telephone Fax	:	+1 800-325-5832 +1 800-325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 4), H302 Acute toxicity, Inhalation (Category 3), H331 Carcinogenicity (Category 1B), H350 Acute aquatic toxicity (Category 1), H400 Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Danger Hazard statement(s) Harmful if swallowed. H302 H331 Toxic if inhaled. H350 May cause cancer. H410 Very toxic to aquatic life with long lasting effects. Precautionary statement(s) P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
P304 + P340 + P311	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P391	Collect spillage.
P403 + P233 P405	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Formula	: As	
Molecular weight	: 74.92 g/mol	
CAS-No.	: 7440-38-2	
EC-No.	: 231-148-6	
Index-No.	: 033-001-00-2	Х

#### Hazardous components

Component	Classification	Concentration
Arsenic		
	Acute Tox. 4; Acute Tox. 3; Carc. 1B; Aquatic Acute 1; Aquatic Chronic 1; H302, H331, H350, H410	90 - 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### Most important symptoms and effects, both acute and delayed 4.2 The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### 4.3 Indication of any immediate medical attention and special treatment needed No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

#### 5.2 Special hazards arising from the substance or mixture No data available

# 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information No data available

# 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For disposal see section 13.

# 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed.

For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Keep in a dry place. Storage class (TRGS 510): 6.1B: Non-combustible, acute toxic Cat. 1 and 2 / very toxic hazardous materials

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis
			parameters	
Arsenic	7440-38-2	TWA	0.01 mg/m3	USA. ACGIH Threshold Limit Values
			-	(TLV)
	Remarks	Lung cancer		
		Substances for which there is a Biological Exposure Index or Indices		
		(see BEI® section)		
		Confirmed hu	uman carcinogen	

С	0.0020 mg/m3	USA. NIOSH Recommended Exposure Limits
Potential Occ See Appendi 15 minute ce	cupational Carcino ix A iling value	gen

#### **Biological occupational exposure limits**

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
	-	inorganic arsenic plus methylated metabolites	35µg As/I	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of the workweek (After four or five consecutive working days with exposure)			tive working days

#### 8.2 Exposure controls

#### Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

#### Personal protective equipment

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: powder Colour: light grey, black
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 817 °C (1,503 °F) - lit.
f)	Initial boiling point and boiling range	613 °C (1,135 °F) - lit.
g)	Flash point	Not applicable
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	No data available
I)	Vapour density	No data available
m)	Relative density	5.727 g/mL at 25 °C (77 °F)
n)	Water solubility	No data available
o)	Partition coefficient: n- octanol/water	No data available
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
<b>Othe</b> No da	r <b>safety information</b> ata available	

#### **10. STABILITY AND REACTIVITY**

# 10.1 Reactivity

9.2

No data available

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** Heat Exposure to air may affect product quality.

#### **10.5** Incompatible materials Strong oxidizing agents

10.6 Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Arsenic oxides Other decomposition products - No data available

#### **11. TOXICOLOGICAL INFORMATION**

# 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - 763 mg/kg Remarks: Behavioral:Ataxia. Diarrhoea

LD50 Oral - Mouse - 145 mg/kg Remarks: Behavioral:Ataxia. Diarrhoea

Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation No data available

Serious eye damage/eye irritation No data available

**Respiratory or skin sensitisation** No data available

Germ cell mutagenicity Carcinogenicity

No data available

IARC: 1 - Group 1: Carcinogenic to humans (Arsenic)

NTP: Known - Known to be human carcinogen (Arsenic)

OSHA: OSHA specifically regulated carcinogen (Arsenic)

#### **Reproductive toxicity**

Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

Additional Information RTECS: CG0525000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 9.9 mg/l - 96.0 h

Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 3.8 mg/l - 48 h other aquatic

invertebrates

# 12.2 Persistence and degradability No data available

#### **12.3 Bioaccumulative potential** No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

## **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

#### **Contaminated packaging**

Dispose of as unused product.

# 14. TRANSPORT INFORMATION

# DOT (US)

15.

UN number: 1558 Proper shipping name: Reportable Quantity (R Poison Inhalation Haza	Class: 6.1 : Arsenic RQ): 1 lbsReportable Quar ard: No	Packing group: II ntity (RQ): 1 lbs			
<b>IMDG</b> UN number: 1558 Proper shipping name: Marine pollutant:yes	Class: 6.1 : ARSENIC	Packing group: II	I E	EMS-No: F-A, S-A	
<b>IATA</b> UN number: 1558 Proper shipping name:	Class: 6.1 : Arsenic	Packing group: II			
REGULATORY INFORM	IATION				
SARA 302 Components No chemicals in this mat	<b>s</b> terial are subject to the rep	porting requiremen	its of SARA T	itle III, Section 302.	
SARA 313 Components	<b>s</b> nts are subject to reporting	levels established	l by SARA Ti	tle III, Section 313:	
Arsenic			CAS-No. 7440-38-2	Revision Date 2015-11-23	
SARA 311/312 Hazards Acute Health Hazard, Ch	s hronic Health Hazard				
Reportable Quantity	: D004 lbs				
Massachusetts Right T	o Know Components				
Arsenic			CAS-No. 7440-38-2	Revision Date 2015-11-23	
Pennsylvania Right To	Know Components			Devision Data	
Arsenic			CAS-NO. 7440-38-2	2015-11-23	
Arsonic			CAS-No.	Revision Date	
New Jersev Right To K	(now Components		1 770-30-2	2015-11-23	

	CAS-No.	Revision Date
Arsenic	7440-38-2	2015-11-23
California Prop. 65 Components		
WARNING! This product contains a chemical known to the	CAS-No.	Revision Date
State of California to cause cancer.	7440-38-2	2007-09-28
Arsenic		

#### **16. OTHER INFORMATION**

Full text of H-Statements referred to under sections 2 and 3.

Acute Tox.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Carc.	Carcinogenicity
H302	Harmful if swallowed.
H331	Toxic if inhaled.
H350	May cause cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

#### Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 4.13

Revision Date: 09/12/2018

Print Date: 06/28/2019

# **SAFETY DATA SHEET**

Version 6.1 Revision Date 05/28/2017 Print Date 06/28/2019

# 1. PRODUCT AND COMPANY IDENTIFICATION 1.1 Product identifiers Product name : Barium Product Number : Aldrich

CAS-No. : 7440-39-3

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES
Telephone Fax	:	+1 314 771-5765 +1 800 325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

# 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Substances and mixtures, which in contact with water, emit flammable gases (Category 2), H261

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word	Danger
Hazard statement(s) H261	In contact with water releases flammable gases.
Precautionary statement(s)	
P223	Do not allow contact with water.
P231 + P232	Handle under inert gas. Protect from moisture.
P280	Wear protective gloves/ eye protection/ face protection.
P335 + P334	Brush off loose particles from skin. Immerse in cool water/ wrap in wet bandages.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Formula	:	Ва
Molecular weight	:	137.33 g/mol
CAS-No.	:	7440-39-3
EC-No.	:	231-149-1

#### Hazardous components

Component	Classification	Concentration
Barium		
	Water-react. 2; H261	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

- **4.2** Most important symptoms and effects, both acute and delayed The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
- **4.3 Indication of any immediate medical attention and special treatment needed** No data available

## **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

Suitable extinguishing media Dry powder

- 5.2 Special hazards arising from the substance or mixture Barium oxide
- **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.

# 5.4 Further information

No data available

# 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas.

For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### 6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13). Do not flush with water. Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For disposal see section 13.

### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Further processing of solid materials may result in the formation of combu formation should be taken into consideration before additional processing

Provide appropriate exhaust ventilation at places where dust is formed.Keep away from sources of ignition - No smoking.

For precautions see section 2.2.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Never allow product to get in contact with water during storage.

Store under inert gas.

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis
Dorium	7440 20 2			LISA ACCIH Throphold Limit Voluos
Bahum	1440-39-3	IVVA	0.500000	
	<u> </u>	+	mg/m3	(ILV)
	Remarks	Eye, skin, 8	Gastrointestinal I	rritation
		Muscular st	imulation	
		Not classifia	<u>able as a human c</u>	arcinogen
		TWA	0.500000	USA. Occupational Exposure Limits
			mg/m3	(OSHA) - Table Z-1 Limits for Air
				Contaminants
		TWA	0.500000	USA. ACGIH Threshold Limit Values
			mg/m3	(TLV)
		Eye irritatio	n	
		Muscular st	timulation	
		Skin irritatic	n	
		Gastrointes	tinal irritation	
		Not classifia	able as a human c	arcinogen
		TWA	0.500000	USA. NIOSH Recommended
			mg/m3	Exposure Limits
		TWA	0.5 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	0.5 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
		Eye irritation Muscular st Skin irritatic Gastrointes Not classifia	timulation on stinal irritation able as a human c	arcinogen

		TWA	0.5 mg/m3	USA. NIOSH Recommended Exposure Limits
0 0	Evneeure controle			

## 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

# Personal protective equipment

#### Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industria situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Flame retardant protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use (EN 143) respirator cartridges as a backup to engineering controls. If th full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: Pieces Colour: grey
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 725 °C (1337 °F) - lit.
f)	Initial boiling point and boiling range	1,640 °C (2,984 °F) - lit.
g)	Flash point	()Not applicable
h)	Evaporation rate	No data available

i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	No data available
I)	Vapour density	No data available
m)	Relative density	3.6 g/cm3 at 25 °C (77 °F)
n)	Water solubility	No data available
o)	Partition coefficient: n- octanol/water	No data available
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Oth	ner safety information	

#### **10. STABILITY AND REACTIVITY**

No data available

10.1 Reactivity No data available

9.2

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** Reacts violently with water.
- **10.4 Conditions to avoid** Exposure to moisture

# 10.5 Incompatible materials

Oxidizing agents, Water, acids, Oxygen, Chlorinated solvents, Carbon dioxide (CO2), Halogens, Halogenated hydrocarbon, Alcohols, Sulphur compounds, Hydrogen sulfide gas

#### **10.6 Hazardous decomposition products**

Hazardous decomposition products formed under fire conditions. - Barium oxide Other decomposition products - No data available In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

No data availableBarium Inhalation: No data available(Barium) Dermal: No data available(Barium) No data available(Barium)

#### Skin corrosion/irritation

No data available(Barium)

Serious eye damage/eye irritation No data available(Barium)

#### Respiratory or skin sensitisation

No data available(Barium)

#### Germ cell mutagenicity

No data available(Barium)

#### Carcinogenicity

This product is or contains a component that is not classifiable as to its classification.(Barium) (Barium) (Barium)

# Reproductive toxicity

No data available(Barium)

No data available(Barium)

**Specific target organ toxicity - single exposure** No data available(Barium)

Specific target organ toxicity - repeated exposure No data available

#### Aspiration hazard

No data available(Barium)

#### **Additional Information**

RTECS: CQ8370000

Stomach/intestinal disorders, Nausea, Vomiting, Drowsiness, Dizziness, Gastrointestinal disturbance, Weakness, Tremors, Seizures.(Barium) To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.(Barium)

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

Toxicity to fishmortality NOEC - Cyprinodon variegatus (sheepshead minnow) - 500 mg/l - 96<br/>h(Barium)LC50 - Cyprinodon variegatus (sheepshead minnow) - > 500 mg/l - 96<br/>h(Barium)

# 12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

# 12.4 Mobility in soil

No data available(Barium)

# 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

No data available

# **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber b highly flammable. Offer surplus and nonrecyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

#### **Contaminated packaging**

Dispose of as unused product.

## **14. TRANSPORT INFORMATION**

<b>DOT (US)</b> UN number: 1400 Proper shipping nam Reportable Quantity	Class: 4.3 e: Barium (RQ) :	Packing group: II 1000 lbs	
Poison Inhalation Ha	zard: No		
<b>IMDG</b> UN number: 1400 Proper shipping nam	Class: 4.3 e: BARIUM	Packing group: II	EMS-No: F-G, S-O
IATA UN number: 1400 Proper shipping nam	Class: 4.3 e: Barium	Packing group: II	

#### **15. REGULATORY INFORMATION**

# SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

The following components are subject to reporting levels establish	ned by SARA Title III,	Section 313:
Barium	CAS-No. 7440-39-3	Revision Date 2007-07-01
SARA 311/312 Hazards Reactivity Hazard		
Massachusetts Right To Know Components		
	CAS-No.	<b>Revision Date</b>
Barium	7440-39-3	2007-07-01
Pennsylvania Right To Know Components		
	CAS-No.	<b>Revision Date</b>
Barium	7440-39-3	2007-07-01
New Jersey Right To Know Components		
	CAS-No.	<b>Revision Date</b>
Barium	7440-39-3	2007-07-01

# **16. OTHER INFORMATION**

Full text of H-Statements referred to under sections 2 and 3.

#### **HMIS Rating**

Health hazard:	0
Chronic Health Hazard: Flammability: Physical Hazard	3 1
NFPA Rating	0
Health hazard:	0
Fire Hazard:	3
Reactivity Hazard:	1

Reactivity nazaru.	
Special hazard.I:	

W

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956 Version: 6.1

Revision Date: 05/28/2017

Print Date: 06/28/2019



ⓓ Home > Chemical CAS No.7 > Benzene SDS

# **Benzene Safety Data Sheets**

Characteristics | Suppliers

		Click here to download 4 million SDS for free.	
Downle	ad SDS(editable Word file) and other types SDS   Offered	by XiXisys.com	
SA	FETY DATA SHEETS		
Ace	ording to the UN CHS revision 8		
Au	or the or ons revision o		
			Creation Revision
SEC	TION 1: Identification		
1.1	<b>GHS Product identifier</b>		
	Product name	Benzene	
1.2	Other means of identification		ТОР
	Product number Other names	- Benzole: Fenzen: Benzeen	0
1.3	Recommended use of the chemical	and restrictions on use	
	Identified uses	Hydrocarbons (contain hydrogen and carbon atoms), Volatile organic compounds	6
1.4	Uses advised against	no data available	-
1.4	Supplier's details	Echemi com	S
	Address Telephone	Echemi.com Echemi.com	
1.5	Emergency phone number		
	Emergency phone number	Echemi.com	KI-Q
	Service hours	Monday to Friday, 9am-5pm (Standard time zone: UTC/GMT +8 hours).	
SEC	TION 2: Hazard identification		
2.1	Classification of the substance or m	nixture	
	Flammable liquids, Category 2 Skin irritation, Category 2 Eye irritation, Category 2 Aspiration hazard, Category 1 Germ cell mutagenicity, Category 1B Carcinogenicity, Category 1A Specific target organ toxicity â = repeated exp	osure, Category 1	
2.2	GHS label elements, including prec	cautionary statements	
	Pictogram(s)		
	Signal word Hazard statement(s)	Danger H225 Highly flammable liquid and vapour H315 Causes skin irritation H319 Causes serious eye irritation H304 May be fatal if swallowed and enters airways H340 May cause genetic defects H350 May cause cancer H372 Causes damage to organs through prolonged or repeated exposure	
	Precautionary statement(s) Prevention	<ul> <li>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P233 Keep container tightly closed.</li> <li>P240 Ground and bond container and receiving equipment.</li> <li>P241 Use explosion-proof [electrical/ventilating/lighting/] equipment.</li> <li>P242 Use non-sparking tools.</li> <li>P243 Take action to prevent static discharges.</li> <li>P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/</li> </ul>	Help

	P264 Wash thoroughly after handling.			
	P203 Obtain, read and follow all safety instructions before use.			
	P260 Do not breathe dust/fume/gas/mist/vapours/spray.			
	P270 Do not eat, drink or smoke when using this product.			
Response	P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [			
•	shower].			
	P370+P378 In case of fire: Use to extinguish.			
	P302+P352 IF ON SKIN: Wash with plenty of water/			
	P321 Specific treatment (see on this label).			
	P332+P317 If skin irritation occurs: Get medical help.			
	P362+P364 Take off contaminated clothing and wash it before reuse.			
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy			
	Continue rinsing.			
	P301+P316 IF SWALLOWED: Get emergency medical help immediately.			
	P331 Do NOT induce vomiting.			
	P318 IF exposed or concerned, get medical advice.			
	P319 Get medical help if you feel unwell.			
Storage	P403+P235 Store in a well-ventilated place. Keep cool.			
	P405 Store locked up.			
Disposal	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and			
	regulations, and product characteristics at time of disposal.			

#### 2.3 Other hazards which do not result in classification

no data available

#### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

[	Chemical name	Common names and synonyms	CAS number	EC number	Concentration
	Benzene	Benzene	71-43-2	200-753-7	100%

#### **SECTION 4: First-aid measures**

#### 4.1 Description of necessary first-aid measures

If inhaled

Fresh air, rest. Refer for medical attention.

#### Following skin contact

Remove contaminated clothes. Rinse skin with plenty of water or shower. Refer for medical attention .

#### Following eye contact

First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then refer for medical attention.

#### **Following ingestion**

Rinse mouth. Do NOT induce vomiting. Refer for medical attention .

#### 4.2 Most important symptoms/effects, acute and delayed

Dizziness, excitation, pallor, followed by flushing, weakness, headache, breathlessness, chest constriction, nausea, and vomiting. Coma and possible death. (USCG, 1999)

#### 4.3 Indication of immediate medical attention and special treatment needed, if necessary

Immediate first aid: Ensure that adequate decontamination has been carried out. If patient is not breathing, start artificial respiration, preferably with a demand-valve resuscitator bat mask device, or pocket mask, as trained. Perform CPR as necessary. Immediately flush contaminated eyes with gently flowing water. Do not induce vomiting. If vomiting or patient forward or place on left side (head-down position, if possible) to maintain an open airway and prevent aspiration. Keep patient quiet and maintain normal body temps medical attention. Benzene and Related Compounds

RFO.

#### **SECTION 5: Fire-fighting measures**

#### 5.1 Suitable extinguishing media

Approach fire from upwind to avoid hazardous vapors. Use water spray, dry chemical, foam, or carbon dioxide. Use water spray to keep fire-exposed containers cool.

#### 5.2 Specific hazards arising from the chemical

Behavior in Fire: Vapor is heavier than air and may travel considerable distance to a source of ignition and flash back. (USCG, 1999)

#### 5.3 Special protective actions for fire-fighters

Use foam, water spray, carbon dioxide, powder. In case of fire: keep drums, etc., cool by spraying with water.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Remove all ignition sources. Evacuate danger area! Consult an expert! Personal protection: complete protective clothing including self-contained breathing apparatus. Do NOT wasl into sewer. Do NOT let this chemical enter the environment. Collect leaking and spilled liquid in sealable containers as far as possible. Absorb remaining liquid in sand or inert abso Then store and dispose of according to local regulations.

#### 6.2 Environmental precautions

Remove all ignition sources. Evacuate danger area! Consult an expert! Personal protection: complete protective clothing including self-contained breathing apparatus. Do NOT wasl into sewer. Do NOT let this chemical enter the environment. Collect leaking and spilled liquid in sealable containers as far as possible. Absorb remaining liquid in sand or inert abso Then store and dispose of according to local regulations.

#### 6.3 Methods and materials for containment and cleaning up

For spills on water, contain with booms or barriers, use surface acting agents to thicken spilled materials. Remove trapped materials with suction hoses.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

NO open flames, NO sparks and NO smoking. Closed system, ventilation, explosion-proof electrical equipment and lighting. Do NOT use compressed air for filling, discharging, or handling. Use non-sparking handtools. Prevent build-up of electrostatic charges (e.g., by grounding). Handling in a well ventilated place. Wear suitable protective clothing. Avoid cc with skin and eyes. Avoid formation of dust and aerosols. Use non-sparking tools. Prevent fire caused by electrostatic discharge steam.

#### 7.2 Conditions for safe storage, including any incompatibilities

Fireproof. Separated from food and feedstuffs, oxidants and halogens. Store in an area without drain or sewer access. Keep in well closed containers in a cool place and away from fi

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure limit values**

TLV: 0.5 ppm as TWA; 2.5 ppm as STEL; (skin); A1 (confirmed human carcinogen); BEI issued.EU-OEL: 3.25 mg/m3, 1 ppm as TWA; (skin).MAK: carcinogen category: 1; germ mutagen group: 3A; skin absorption (H)

**Biological limit values** 

no data available

#### 8.2 Appropriate engineering controls

Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Set up emergency exits and the risk-elimination area.

#### Individual protection measures, such as personal protective equipment (PPE)

#### Eye/face protection

8.3

Wear face shield or eye protection in combination with breathing protection.

#### Skin protection

Protective gloves. Protective clothing.

#### **Respiratory protection**

Use ventilation, local exhaust or breathing protection.

Thermal hazards

no data available

#### **SECTION 9: Physical and chemical properties and safety characteristics**

Physical state	Liquid	
Colour	Clear colourless	
Odour	Aromatic odor	
Melting point/freezing point	5.49 ŰC. Atm. press.:1 013 hPa.	
Boiling point or initial boiling point and boiling	80.09 °C. Atm. press.:1 013.5 hPa.	
range	1	
Flammability	Highly flammable.	
Lower and upper explosion limit/flammability limit	Lower flammable limit: 1.2% by volume; Upper flammable limit: 7.8% by volume	
Flash point	-11 ŰC. Atm. press.:1 013.5 hPa.	
Auto-ignition temperature	498 ŰC. Atm. press.:1 013.5 hPa.	
Decomposition temperature	no data available	
рН	no data available	
Kinematic viscosity	dynamic viscosity (in mPa s) = $0.604$ . Temperature: $25.0A^{\circ}C$ .	
Solubility	1 to 5 mg/mL at 64Ű F (NTP, 1992)	
Partition coefficient n-octanol/water	$\log Pow = 2.13$ . Temperature:25 ŰC.	
Vapour pressure	10 kPa. Temperature:20 ŰC.;100 kPa. Temperature:79.7 ŰC.	
Density and/or relative density	0.876 g/cmÅ <sup>3</sup> . Temperature:20 ŰC.	$\sim$
Relative vapour density	2.77 (vs air)	TOP
Particle characteristics	no data available	IUF
FION 10: Stability and reactivity		Ģ
Deastivity		

#### 10.1 Reactivity

SEC

NIOSH usually recommends that occupational exposures to carcinogens be limited to the lowest feasible concentration. Reacts violently with oxidants, nitric acid, sulfuric acid and halogens. This generates fire and explosion hazard. Attacks plastics and rubber. See Explosion Hazards.

#### 10.2 Chemical stability

Stable under recommended storage conditions.

#### 10.3 Possibility of hazardous reactions

A dangerous fire hazard when exosed to heat or flame. ... Ignites on contact with sodium peroxide + water, dioxygenyl tetrafluoroborate, iodine heptafluoride, and dioxygen and the vapors are he ground distant ignition possible. As a result of flow, agitation, etc., electrostatic charges can be generated., Benzene vapors are he ground and collect and stay in poorly-ventilated, low-lying, or confined areas (e.g., sewers, basements, and tanks). Hazardous concentrations may develop quickly in enclosed, poorly-ventilated, or low-lying areas. Keep out of these areas. Stay upwind.Benzene liquid is less dense than water and will float on the surface of water.BENZENE reacts vigorously with allyl chloride or other alkyl halides even at -70Ű C in the presence of ethyl aluminum dichloride or ethyl aluminum sesquichloride. Explos have been reported [NFPA 491M 1991]. Ignites in contact with powdered chromic anhydride [Mellor 11:235 1946-47]. Incompatible with oxidizing agents such as nitric acid. Mixtu with bromine trifluoride, bromine pentafluoride, iodine pentafluoride, iodine heptafluoride and other interhalogens can ignite upon heating [Bretherick 5th ed. 1995]. Benzene and c halides yield HCI as a byproduct (Hagedorn, F. H. Gelbke, and Federal Republic of Germany. 2002. Nitriles. In Ullmann's Encyclopedia of Industrial Chemistry. Wiley-VCH Verlag & Co. KGaA.). The reaction of benzene and trichloroacetonitrile evolves toxic chloroform and HCI gases. (Hagedorn, F., H.-P. Gelbke, and Federal Republic of Germany. 2002. Nit

#### **10.4** Conditions to avoid

no data available

#### **10.5** Incompatible materials

Reacts violently with iodine pentafluoride.

#### 10.6 Hazardous decomposition products

no data available

#### **SECTION 11: Toxicological information**

#### Acute toxicity

Oral: LD50 - rat (male) - > 2 000 mg/kg bw. Remarks: Young and older adults had LD50 of 3.8 (2.9-4.8) and 5.6 (4.0-7.8) mL/kg respectively. Inhalation: LC50 - rat (female) - 13 700 ppm. Dermal: LD50 - guinea pig and rabbit - > 9.4 mL/kg bw.

Skin corrosion/irritation

no data available

#### Serious eye damage/irritation

no data available

#### Respiratory or skin sensitization

no data available
#### Germ cell mutagenicity

no data available

#### Carcinogenicity

NTP: Known to be a human carcinogen. EPA: Known human carcinogen. IARC: Carcinogenic to humans

#### **Reproductive toxicity**

There is some evidence from human epidemiological studies of reproductive and developmental toxicity of benzene, however the data do not provide conclusive evidence of a link t exposure and effect (4). Animal studies have provided limited evidence that exposure to benzene may affect reproductive organs, however these effects were only observed at expos levels over the maximum tolerated dose. Adverse effects on the fetus, including low birth weight, delayed bone formation, and bone marrow damage, have been observed where pre animals were exposed to benzene by inhalation.

#### STOT-single exposure

The substance is irritating to the eyes, skin and respiratory tract. If this liquid is swallowed, aspiration into the lungs may result in chemical pneumonitis. The substance may cause e on the central nervous system. This may result in lowering of consciousness. Exposure far above the OEL could cause unconsciousness and death. If swallowed the substance easily the airways and could result in aspiration pneumonitis.

#### STOT-repeated exposure

The substance defats the skin, which may cause dryness or cracking. The substance may have effects on the central nervous system and immune system. The substance may have eff the bone marrow. This may result in anaemia. This substance is carcinogenic to humans. May cause heritable genetic damage to human germ cells. See Notes.

#### Aspiration hazard

A harmful contamination of the air can be reached very quickly on evaporation of this substance at 20°C.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Toxicity to fish: LC50 - Oncorhynchus mykiss (previous name: Salmo gairdneri) - 5.3 mg/L - 96 h. Toxicity to daphnia and other aquatic invertebrates: EC50 - Daphnia magna - 10 mg/L - 48 h. Toxicity to algae: EC50 - Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) - 32 mg/L - 72 h. Toxicity to microorganisms: IC50 - Nitrosomonas sp. - 13 mg/L - 24 h.

#### 12.2 Persistence and degradability

AEROBIC: Benzene present at 100 mg/L, reached 40% of its theoretical BOD in 2 weeks using an activated sludge inoculum at 30 mg/L in the Japanese MITI test(1). Benzene reac 24% of its theoretical oxygen demand in a non-acclimated microbial population after 15 days(2). Aerobic biodegradation of benzene was studied in pre-equilibrated soil-water slurry microcosms(3). Using an enriched aerobic bacterial culture, benzene began to degrade 12 hrs after incubation in an aqueous(soil-free) solution with 50% of benzene degrading after and almost complete degradation within 90 hrs. Using a pre-equilibrated soil-water slurry microcosm, benzene did not begin to degrade until 3 days after application and reached co degradation after about 12 days(3).

#### 12.3 Bioaccumulative potential

Benzene has BCFs ranging from 1.1-20(1). According to a classification scheme(2), this BCF range suggests the potential for bioconcentration in aquatic organisms is low. The upta elimination rate constants for benzene in fathead minnows were studied(3). Fathead minnows were found to have an average uptake rate of 7 L/kg/hr with an average elimination rat 0.384/hr which corresponds to a BCF of 19(3). In a study of BCF values for various aquatic species, benzene was found to have a BCF value of 3.5 in eels(4), 4.4 in pacific (4.3 in goldfish(6).

#### 12.4 Mobility in soil

An experimentally derived log Koc of 1.93 (Koc = 85) was obtained via reverse phase HPLC (high performance liquid chromatography) with a cyanopropyl column and a n state (1). According to a classification scheme(2), this estimated Koc value suggests that benzene is expected to have high mobility in soil. The sorption equilibrium for benzene in a soil/water mixture (ratio soil/water 0.12 kg/l) took 72 hrs(3). The Koc for benzene has also been experimentally determined to be 79(4).

S

RFO

#### 12.5 Other adverse effects

no data available

#### **SECTION 13: Disposal considerations**

#### 13.1 Disposal methods

#### Product

The material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing. Do not contaminate water, foodstuffs, feec by storage or disposal. Do not discharge to sewer systems.

#### Contaminated packaging

Containers can be triply rinsed (or equivalent) and offered for recycling or reconditioning. Alternatively, the packaging can be punctured to make it unusable for other purposes and disposed of in a sanitary landfill. Controlled incineration with flue gas scrubbing is possible for combustible packaging materials.

#### **SECTION 14: Transport information**

14.1	UN Number		
	ADR/RID: UN1114 (For reference only, please check.)	IMDG: UN1114 (For reference only, please check.)	IATA: UN1114 (For reference only, please check.)
14.2	UN Proper Shipping Name		
	ADR/RID: BENZENE (For reference only, please check.)	IMDG: BENZENE (For reference only, please check.)	IATA: BENZENE (For reference only, please check.
14.3	Transport hazard class(es)		
	ADR/RID: 3 (For reference only, please check.)	IMDG: 3 (For reference only, please check.)	IATA: 3 (For reference only, please check.)
14.4	Packing group, if applicable		
	ADR/RID: II (For reference only, please check.)	IMDG: II (For reference only, please check.)	IATA: II (For reference only, please check.)
14.5	Environmental hazards		
	ADR/RID: No	IMDG: No	IATA: No
14.6	Special precautions for user		
	no data available		
14.7	Transport in bulk according to IMO instrume	ents	
	no data available		

#### **SECTION 15: Regulatory information**

Chemical name	Common names and synonyms	CAS number	EC n									
Benzene	Benzene	71-43-2	200-									
European Inventory of Existing Commercial Chemical Substances (EINECS) EC Inventory United States Toxic Substances Control Act (TSCA) Inventory												
						China Catalog of Hazardous chemicals 2015 New Zealand Inventory of Chemicals (NZIoC) Philippines Inventory of Chemicals and Chemical Substances (PICCS) Vietnam National Chemical Inventory						
Korea Existing Chemicals List (KECL)			Li									
			•									
ION 16: Other information												
nformation on revision												
Treation Date	July 15, 2019											
Revision Date	July 15, 2019											
hereinting and assessme												
Abbreviations and acronyms												
ADR: European Agreement concerning the Int RID: Regulation concerning the International IMDG: International Maritime Dangerous Goo IATA: International Air Transportation Associa TWA: Time Weighted Average STEL: Short term exposure limit LC50: Lethal Concentration 50% LD50: Lethal Dose 50% EC50: Effective Concentration 50%	ternational Carriage of Dangerous Goods by Road Carriage of Dangerous Goods by Rail ods ation											
References												
IPCS - The International Chemical Safety Car HSDB - Hazardous Substances Data Bank, we IARC - International Agency for Research on eChemPortal - The Global Portal to Informatic CAMEO Chemicals, website: http://cameoche ChemIDplus, website: http://chem.sis.nlm.nih ERG - Emergency Response Guidebook by U. Germany GESTIS-database on hazard substan ECHA - European Chemicals Agency, website	ds (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home ebsite: https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm Cancer, website: http://www.iarc.fr/ on on Chemical Substances by OECD, website: http://www.echemportal.org micals.noaa.gov/search/simple .gov/chemidplus/chemidlite.jsp .S. Department of Transportation, website: http://www.phmsa.dot.gov/hazn ce, website: http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp :: https://echa.europa.eu/	g/echemportal/index?pageID=0&request_ nat/library/erg p	locale=en									
Other Information												

Use of alcoholic beverages enhances the harmful effect. Depending on the degree of exposure, periodic medical examination is suggested. The odour warning when the exposure lim is exceeded is insufficient. Benzene causes acute myeloid leukaemia/acute non-lymphocytic leukaemia. Also, a positive association has been observed between exposure to benzene acute lymphocytic leukaemia, chronic lymphocytic leukaemia, multiple myeloma, and non-Hodgkin lymphoma.

Disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is be present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the profuse of the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the profuse of the product with the above product.

Benzene is included in Hydrocarbons and Derivatives category. See more Benzene price and marketing trends Buy Benzene of different grades for your demands from various manufactures and traders.

# Benzene Benzene Benzene 99% kanbei

Benzene 99.9% Colorless

3

S

RFO.

Pure benzene 99% Liquid Dideu

#### **Industry News**

•What Is Inorganic Benzene? Differences, Si	•What You Need to Know About Benzene in	•Get to know whether benzene is a hydrocar	•Go Up And Go Up! PET Rose
•Where Is Benzene Found in Everyday Life?			

#### **More Safety Data Sheets**

Dibenzoselenophene 5-oxide SDS	D-Alanine SDS	4-IODOISOQUINOLINE SDS	Methyl 6,11-dihydro-11-oxoc
3-Chloro-6-(1-piperazinyl)pyridazine SDS	6,7-Dihydro-5H-quinolin-8-one SDS	1-BOC-PIPERAZINE SDS	ETC 1002 SDS
EUK 207 SDS	1H-Pyrrole-3-carboxylic acid, 5-formyl-2,4-d		

Trade Alert - Delivering the latest product trends and industry news straight to your inbox. (We'll never share your email address with a third-party.)

	Input your Email address	Su	bscribe	
About Us	Buy on ECHEMI	Sell on ECHEMI	Customer Services	
About ECHEMI Group	Search Products List Alphabetically	Supplier Membership	Learning Center	
About Echemi.com	Shop Chemical Products Alphabetically	Training Center	Terms of Use	
Marketing Kit	Find Suppliers Alphabetically	Success Stories	Privacy Notice	
Sitemap	Get Chemical Data Numerically	Get Chemical Data Numerically		
Partners	Find Suppliers by Region		Rules	
Chemical Knowledge	Request for Quotation	Request for Quotation		
Community	Promotion		Submit a Dispute	
	Top Products		Contact Us	

Follow Us f in	
Browse Articles by Letter   A B C D E F G H I J K L M N O P Q R S T U V W X Y Z 0	1-9
Browse News by   Monday Tuesday Wednesday Thursday Friday Saturday Sunday   Articles 2024   Category Keywords   Category Tag	IS
China's Top 100 Industrial Digitalization Enterprises List The Drafting Unit of the "Specification for Operation and Management of Self-build Cross-border E-commerce Website" of the CCPIT	TOP
鲁ICP备16009155号-1   Copyright@Qingdao ECHEMI Digital Technology Co., Ltd.	Ģ
	ā
	8

RFO.

# SIGMA-ALDRICH

# SAFETY DATA SHEET

Version 5.8 Revision Date 02/02/2018 Print Date 10/19/2018

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

1.1	Product identifiers Product name	:	Benzo[a]pyrene
	Product Number Brand Index-No.	:	48564 Supelco 601-032-00-3
	CAS-No.	:	50-32-8
1.2	Relevant identified uses	of the	substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA	
Telephone Fax	:	+1 800-325-5832 +1 800-325-5052	

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

#### 2. HAZARDS IDENTIFICATION

# 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Skin sensitisation (Category 1), H317 Germ cell mutagenicity (Category 1B), H340 Carcinogenicity (Category 1B), H350 Reproductive toxicity (Category 1B), H360 Acute aquatic toxicity (Category 1), H400 Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

Danger

#### 2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word



	- 5	
Н	azard statement(s)	
	H317	May cause an allergic skin reaction.
	H340	May cause genetic defects.
	H350	May cause cancer.
	H360	May damage fertility or the unborn child.
	H410	Very toxic to aquatic life with long lasting effects.
	Precautionary statement(s)	
	P201	Obtain special instructions before use.
	P202	Do not handle until all safety precautions have been read and

	understood.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Synonyms	:	3,4-Benzpyrene 3,4-Benzopyrene Benzo[def]chrysene benzo[pqr]tetraphene
Formula	:	

1 onnua	•	<sup>0</sup> 20 <sup>11</sup> 2
Molecular weight	:	252.31 g/mol
CAS-No.	:	50-32-8
EC-No.	:	200-028-5
Index-No.	:	601-032-00-3

#### Hazardous components

Component	Classification	Concentration
Benzo[a]pyrene		
	Skin Sens. 1; Muta. 1B; Carc.	90 - 100 %
	1B; Repr. 1B; Aquatic Acute 1;	
	Aquatic Chronic 1; H317,	
	H340, H350, H360, H410	

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### **4.3 Indication of any immediate medical attention and special treatment needed** No data available

## **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture No data available

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

# 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

# 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs. Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

#### Store at room temperature.

Storage class (TRGS 510): 6.1D: Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis	
			parameters		
	Remarks	Cancer			
		Substances for which there is a Biological Exposure Index or Ind (see BEI® section), see BEI® for Polycyclic Aromatic Hydrocarbo (PAHs)			
		Exposure by	all routes should b	be carefully controlled to levels as low	

		as possible.			
		Suspected numan carcinogen			
		Cancer	for which thore is a	- Riological Exposure Index or Indicas	
		(see BEI® se	ection) see BEI®	for Polycyclic Aromatic Hydrocarbons	
		(PAHs)			
		Exposure by all routes should be carefully controlled to levels as low			
		as possible.			
		Suspected human carcinogen			
Benzo[a]pyrene	50-32-8	TWA	0.200000	USA. Occupational Exposure Limits	
			mg/m3	(OSHA) - Table Z-1 Limits for Air Contaminants	
		TWA	0.200000	USA. Occupational Exposure Limits	
			mg/m3	(OSHA) - Table Z-1 Limits for Air Contaminants	
		1910.1002			
		As used in §	1910.1000 (Table	Z-1), coal tar pitch volatiles include	
		the fused po	siduos of cool pot	ons which volatilize from the	
		and other or	nanic matter Aspl	halt (CAS 8052-42-4 and CAS	
		64742-93-4)	is not covered und	der the 'coal tar pitch volatiles'	
		standard		·	
		OSHA specit	fically regulated ca	arcinogen	
		TWA	0.100000	USA. NIOSH Recommended	
			mg/m3	Exposure Limits	
		Potential Occupational Carcinogen			
		products		i tai pitch, and cleosole to be coal tai	
		cvclohexane	-extractable fraction	n	
		See Appendix C			
		See Append	ix A		
		TWA	0.2 mg/m3	USA. Occupational Exposure Limits	
				Contaminants	
		1910.1002	4040 4000 (Tabla	7.4 and the witch valetiles include	
		As used in §	1910.1000 (Table	2-1), coal tar pitch volatiles include	
		distillation re	sidues of coal net	roleum (excluding asphalt) wood	
		and other or	danic matter. Asp	halt (CAS 8052-42-4, and CAS	
		64742-93-4)	is not covered und	der the 'coal tar pitch volatiles'	
		standard			
		OSHA speci	fically regulated ca	arcinogen	
		TWA	0.1 mg/m3	USA. NIOSH Recommended Exposure Limits	
		Potential Oc	cupational Carcino	ogen	
		NIOSH cons	iders coal tar, coa	I tar pitch, and creosote to be coal tar	
		products.	ovtractable fractic		
			ix C		
		See Append	ix A		
		TWA	0.2 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910 1000	
		PEL	0.2 mg/m3	California permissible exposure	
				limits for chemical contaminants (Title 8, Article 107)	
		PEL	0.2 mg/m3	California permissible exposure	
				limits for chemical contaminants (Title 8, Article 107)	
	•				

# **Biological occupational exposure limits**

Component CAS-No. Parameters Value Biological Basis	

			specimen	
-	1- Hydroxypyren e		Urine	ACGIH - Biological Exposure Indices (BEI)
Remarks	End of shift at e	end of workv	veek	
	1- Hydroxypyren e		Urine	ACGIH - Biological Exposure Indices (BEI)
	End of shift at e	end of workv	veek	••••

### 8.2 Exposure controls

### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

### Personal protective equipment

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

- a) Appearance Form: solid
- b) Odour No data available

c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 177 - 180 °C (351 - 356 °F)
f)	Initial boiling point and boiling range	495 °C (923 °F)
g)	Flash point	No data available
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	No data available
I)	Vapour density	No data available
m)	Relative density	1.35 g/cm3
n)	Water solubility	No data available
o)	Partition coefficient: n- octanol/water	log Pow: 5.97
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Othe No.d	r safety information	

# **10. STABILITY AND REACTIVITY**

10.1 Reactivity No data available

9.2

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5** Incompatible materials Strong oxidizing agents
- 10.6 Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available In the event of fire: see section 5

# **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

Acute toxicity No data available

#### Inhalation: No data available

#### Dermal: No data available

LD50 Subcutaneous - Rat - 50 mg/kg

## Skin corrosion/irritation

Skin - Mouse Result: Mild skin irritation

Serious eye damage/eye irritation No data available

**Respiratory or skin sensitisation** Chronic exposure may cause dermatitis.

# Germ cell mutagenicity

May alter genetic material. In vivo tests showed mutagenic effects

#### Carcinogenicity

This product is or contains a component that has been reported to be probably carcinogenic based on its IARC, OSHA, ACGIH, NTP, or EPA classification.

Possible human carcinogen

IARC: 1 - Group 1: Carcinogenic to humans (Benzo[a]pyrene)

NTP: RAHC - Reasonably anticipated to be a human carcinogen (Benzo[a]pyrene)

OSHA: OSHA specifically regulated carcinogen (Benzo[a]pyrene)

#### **Reproductive toxicity**

May cause congenital malformation in the fetus. Presumed human reproductive toxicant

May cause reproductive disorders.

#### Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

# Aspiration hazard

No data available

#### **Additional Information**

RTECS: Not available

burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting

# **12. ECOLOGICAL INFORMATION**

# 12.1 Toxicity

Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 0.25 mg/l - 48 h other aquatic invertebrates

Toxicity to algae EC50 - Pseudokirchneriella subcapitata (green algae) - 0.02 mg/l - 72 h

#### 12.2 Persistence and degradability

# 12.3 Bioaccumulative potential

Bioaccumulation

Lepomis macrochirus (Bluegill) - 48 h - 0.0005 mg/l

Bioconcentration factor (BCF): 3,208

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

#### **Contaminated packaging**

Dispose of as unused product.

# **14. TRANSPORT INFORMATION**

#### DOT (US)

UN number: 3077 Class: 9 Packing group: III Proper shipping name: Environmentally hazardous substances, solid, n.o.s. (Benzo[a]pyrene) Reportable Quantity (RQ): 1 lbs Poison Inhalation Hazard: No

#### IMDG

UN number: 3077 Class: 9 Packing group: III EMS-No: F-A, S-F Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Benzo[a]pyrene) Marine pollutant:yes

#### ΙΑΤΑ

UN number: 3077 Class: 9 Packing group: III Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (Benzo[a]pyrene)

#### **Further information**

EHS-Mark required (ADR 2.2.9.1.10, IMDG code 2.10.3) for single packagings and combination packagings containing inner packagings with Dangerous Goods > 5L for liquids or > 5kg for solids.

# **15. REGULATORY INFORMATION**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

The following components are subject to reporting levels estab	olished by SARA Title I	II, Section 313:
	CAS-No	Revision Date

50-32-8	2007-03-01
CAS-No.	<b>Revision Date</b>
50-32-8	2007-03-01
CAS-No.	Revision Date
50-32-8	2007-03-01
	Devision Data
CAS-NO.	Revision Date
50-32-8	2007-03-01
CAS-No.	Revision Date
	CAS-No. 50-32-8 CAS-No. 50-32-8 CAS-No. 50-32-8 CAS-No. 50-32-8 CAS-No.

Benzo[a]pyrene	50-32-8	2007-03-01
California Prop. 65 Components WARNING! This product contains a chemical known to the State of California to cause cancer. Benzo[a]pyrene	CAS-No. 50-32-8	Revision Date 1990-01-01

# **16. OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Carc.	Carcinogenicity
H317	May cause an allergic skin reaction.
H340	May cause genetic defects.
H350	May cause cancer.
H360	May damage fertility or the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Muta.	Germ cell mutagenicity

#### **HMIS Rating**

Health hazard:	3
Chronic Health Hazard:	*
Flammability:	0
Physical Hazard	0
-	

#### **NFPA** Rating

Health hazard:	3
Fire Hazard:	0
Reactivity Hazard:	0

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.8

Revision Date: 02/02/2018

Print Date: 10/19/2018

sigma-aldrich.com

# SAFETY DATA SHEET

Version 6.1 Revision Date 07/17/2018 Print Date 01/21/2019

#### 1. PRODUCT AND COMPANY IDENTIFICATION 1.1 **Product identifiers** Product name Benzo[<l>b</>]fluoranthene Product Number ÷ 48490 Brand Supelco Index-No. 601-034-00-4 CAS-No. ÷ 205-99-2 1.2 Relevant identified uses of the substance or mixture and uses advised against Identified uses : Laboratory chemicals, Synthesis of substances 1.3 Details of the supplier of the safety data sheet Company : Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES : +1 314 771-5765 Telephone Fax +1 800 325-5052 :

#### 1.4 Emergency telephone number

Emergency Phone # : (314) 776-6555

## 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS) Carcinogenicity (Category 1B), H350

Acute aquatic toxicity (Category 1), H400

Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word
Hazard statement(s)
H350
H410

Danger

May cause cancer. Very toxic to aquatic life with long lasting effects.

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid release to the environment.
Use personal protective equipment as required.
IF exposed or concerned: Get medical advice/ attention.
Collect spillage.
Store locked up.
Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

# 3.1 Substances

Synonyms	: 3,4-Ben	zofluoranthene
Formula Molecular weight CAS-No.	: C <sb>2 : 252.31 : 205-99-</sb>	20H <sb>12g/mol</sb>
EC-No.	: 205-911	-9
Index-No.	: 601-034	I-00-4

#### Hazardous components

Component	Classification	Concentration
Benz[e]acephenanthrylene		
	Carc. 1B; Aquatic Acute 1; Aquatic Chronic 1; H350, H410	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

# 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

## **4.3 Indication of any immediate medical attention and special treatment needed** No data available

# **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

# 5.2 Special hazards arising from the substance or mixture Carbon oxides

# **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

# 6. ACCIDENTAL RELEASE MEASURES

# 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

# 6.4 Reference to other sections

For disposal see section 13.

### 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

# 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Recommended storage temperature 2 - 8 °C

Storage class (TRGS 510): 6.1D: Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

# Components with workplace control parameters

Remarks

	Remarks	Cancer Substances for (see BEI® sect (PAHs) Exposure by al	<sup>-</sup> which the tion), see I I routes sh	ere is a Biological E BEI® for Polycyclic nould be carefully c	Exposure Index or Indices Aromatic Hydrocarbons controlled to levels as low	
		as possible.				
		Suspected hun	nan carcin	ogen		
Biological occupation	Biological occupational exposure limits					
Component	CAS-No.	Parameters	Value	Biological specimen	Basis	
Benz[e]acephenant hrylene	205-99-2	1- Hydroxypyren		Urine	ACGIH - Biological Exposure Indices (BEI)	

End of shift at end of workweek

# 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Impervious clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

# Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: solid
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 163 - 165 °C (325 - 329 °F) - lit.
f)	Initial boiling point and boiling range	No data available
g)	Flash point	No data available
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available

j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	No data available
I)	Vapour density	No data available
m)	Relative density	No data available
n)	Water solubility	No data available
o)	Partition coefficient: n- octanol/water	No data available
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Other safety information		

# **10. STABILITY AND REACTIVITY**

10.1 Reactivity No data available

9.2

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5** Incompatible materials Strong oxidizing agents

Hazardous decomposition products
 Hazardous decomposition products formed under fire conditions. - Carbon oxides
 Other decomposition products - No data available
 In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

TDLo Oral - Mouse - 7.57 mg/kg Remarks: Liver:Changes in liver weight. Endocrine:Changes in thymus weight. Inhalation: No data available Dermal: No data available No data available

#### Skin corrosion/irritation

No data available

Serious eye damage/eye irritation No data available

#### Respiratory or skin sensitisation

No data available

#### Germ cell mutagenicity

No data available

#### Carcinogenicity

This product is or contains a component that has been reported to be probably carcinogenic based on its IARC, OSHA, ACGIH, NTP, or EPA classification.

Possible human carcinogen

- IARC: 2B Group 2B: Possibly carcinogenic to humans (Benz[e]acephenanthrylene)
- NTP: RAHC Reasonably anticipated to be a human carcinogen (Benz[e]acephenanthrylene)
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

No data available No data available

Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

# Additional Information

RTECS: Not available

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

# **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

Toxicity to daphnia and other aquatic h(Benz[e]acephenanthrylene) invertebrates

#### 12.2 Persistence and degradability

No data available

# 12.3 Bioaccumulative potential

No data available

# 12.4 Mobility in soil

No data available(Benz[e]acephenanthrylene)

# 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life.

# **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

#### Contaminated packaging

Dispose of as unused product.

# **14. TRANSPORT INFORMATION**

# DOT (US)

Not dangerous goods **IMDG** UN number: 3077 Class: 9 Packing group: III EMS-No: F-A, S-F Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Benz[e]acephenanthrylene) Marine pollutant : yes

# ΙΑΤΑ

UN number: 3077 Class: 9 Packing group: III Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (Benz[e]acephenanthrylene)

# **Further information**

EHS-Mark required (ADR 2.2.9.1.10, IMDG code 2.10.3) for single packagings and combination packagings containing inner packagings with Dangerous Goods > 5L for liquids or > 5kg for solids.

## **15. REGULATORY INFORMATION**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

The following components are subject to reporting levels establish	ed by SARA Title III,	Section 313:
	CAS-No.	Revision Date
Benz[e]acephenanthrylene	205-99-2	2007-03-01
SARA 311/312 Hazards Chronic Health Hazard		
Massachusetts Right To Know Components		
	CAS-No.	<b>Revision Date</b>
Benz[e]acephenanthrylene	205-99-2	2007-03-01
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Benz[e]acephenanthrylene	205-99-2	2007-03-01
California Prop. 65 Components		
, which is/are known to the State of California to cause cancer.	CAS-No.	Revision Date
For more information go to www.P65Warnings.ca.gov. Benz[e]acephenanthrylene	205-99-2	2007-09-28

# **16. OTHER INFORMATION**

Full text of H-Statements referred to under sections 2 and 3.

H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

#### Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

# **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956 Version: 6.1

Revision Date: 07/17/2018

Print Date: 01/21/2019

sigma-aldrich.com

# SAFETY DATA SHEET

Version 6.1 Revision Date 07/16/2018 Print Date 01/21/2019

#### 1. PRODUCT AND COMPANY IDENTIFICATION 1.1 **Product identifiers** Product name Benzo[<l>k</>]fluoranthene Product Number ÷ 48492 Brand Supelco Index-No. 601-036-00-5 CAS-No. ÷ 207-08-9 1.2 Relevant identified uses of the substance or mixture and uses advised against Identified uses : Laboratory chemicals, Synthesis of substances 1.3 Details of the supplier of the safety data sheet Company : Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES Telephone : +1 314 771-5765 Fax +1 800 325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : (314) 776-6555

## 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS) Carcinogenicity (Category 1B), H350

Acute aquatic toxicity (Category 1), H400

Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word
Hazard statement(s)
H350
H410

Danger

May cause cancer. Very toxic to aquatic life with long lasting effects.

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid release to the environment.
Use personal protective equipment as required.
IF exposed or concerned: Get medical advice/ attention.
Collect spillage.
Store locked up.
Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

2

#### Hazardous components

Component	Classification	Concentration
Benzo[k]fluoranthene		
	Carc. 1B; Aquatic Acute 1; Aquatic Chronic 1; H350, H410	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

# 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

- **4.2** Most important symptoms and effects, both acute and delayed The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
- **4.3 Indication of any immediate medical attention and special treatment needed** No data available

# **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

# 5.2 Special hazards arising from the substance or mixture Carbon oxides

# **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

# 6. ACCIDENTAL RELEASE MEASURES

# 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

# 6.4 Reference to other sections

For disposal see section 13.

## 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

# 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Recommended storage temperature 2 - 8 °C

Storage class (TRGS 510): 6.1D: Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Benzo[k]fluoranthen e	207-08-9	1- Hydroxypyren e		Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift at e	end of workw	veek	

# 8.2 Exposure controls

# Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Impervious clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: crystalline Colour: yellow
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 215 - 217 °C (419 - 423 °F) - lit.
f)	Initial boiling point and boiling range	No data available
g)	Flash point	No data available
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	No data available
I)	Vapour density	No data available

m)	Relative density	No data available
n)	Water solubility	No data available
o)	Partition coefficient: n- octanol/water	No data available
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Other safety information		

## **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity No data available

9.2

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5** Incompatible materials Strong oxidizing agents
- Hazardous decomposition products
   Hazardous decomposition products formed under fire conditions. Carbon oxides
   Other decomposition products No data available
   In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

No data available Inhalation: No data available Dermal: No data available No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation No data available

**Respiratory or skin sensitisation** No data available

Germ cell mutagenicity No data available

Carcinogenicity Carcinogenicity- Rat- Implant This product is or contains a component that has been reported to be probably carcinogenic based on its IARC, OSHA, ACGIH, NTP, or EPA classification.

Possible human carcinogen

- IARC: 2B Group 2B: Possibly carcinogenic to humans (Benzo[k]fluoranthene)
- NTP: RAHC Reasonably anticipated to be a human carcinogen (Benzo[k]fluoranthene)
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

# Reproductive toxicity

No data available No data available

Specific target organ toxicity - single exposure No data available

#### Specific target organ toxicity - repeated exposure No data available

#### Aspiration hazard No data available

INO Udia avaliable

## **Additional Information**

RTECS: DF6350000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

#### **12. ECOLOGICAL INFORMATION**

12.1 Toxicity

No data available

- 12.2 Persistence and degradability No data available
- **12.3 Bioaccumulative potential** No data available
- **12.4 Mobility in soil** No data available(Benzo[k]fluoranthene)

#### 12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

## 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

#### Contaminated packaging

Dispose of as unused product.

#### **14. TRANSPORT INFORMATION**

# DOT (US)

UN number: 3077 Class: 9 Packing group: III Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (Benzo[k]fluoranthene) Supelco- 48492 no

Poison Inhalation Hazard: No

# IMDG

UN number: 3077 Class: 9 Packing group: III EMS-No: F-A, S-F Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Benzo[k]fluoranthene) Marine pollutant : yes

# ΙΑΤΑ

UN number: 3077 Class: 9 Packing group: III Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (Benzo[k]fluoranthene)

# **Further information**

EHS-Mark required (ADR 2.2.9.1.10, IMDG code 2.10.3) for single packagings and combination packagings containing inner packagings with Dangerous Goods > 5L for liquids or > 5kg for solids.

# **15. REGULATORY INFORMATION**

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### **Massachusetts Right To Know Components**

	CAS-No.	Revision Date
Benzo[k]fluoranthene	207-08-9	1994-04-01
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Benzo[k]fluoranthene	207-08-9	1994-04-01
California Prop. 65 Components		
, which is/are known to the State of California to cause cancer.	CAS-No.	Revision Date
For more information go to www.P65Warnings.ca.gov.	207-08-9	2007-09-28
Benzolkjiluorantnene		

#### **16. OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

H350	May cause cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

#### Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

# **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956 Version: 6.1

Revision Date: 07/16/2018

Print Date: 01/21/2019

sigma-aldrich.com

# SAFETY DATA SHEET

Version 6.1 Revision Date 07/17/2018 Print Date 01/21/2019

1. PR	ODUCT AND COMPANY IDI	ENT	IFICATION
1.1	Product identifiers Product name	:	Benz[a]anthracene
	Product Number Brand Index-No.	:	48563 Supelco 601-033-00-9
	CAS-No.	:	56-55-3
1.2 Relevant identified uses of the substance or mixture and uses advised against		e substance or mixture and uses advised against	
	Identified uses	:	Laboratory chemicals, Synthesis of substances
1.3	1.3 Details of the supplier of the safety data sheet		safety data sheet
	Company	: Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES	
	Telephone	:	+1 314 771-5765

#### 1.4 Emergency telephone number

Emergency Phone # : (314) 776-6555

÷

# 2. HAZARDS IDENTIFICATION

Fax

# 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS) Carcinogenicity (Category 1B), H350

Acute aquatic toxicity (Category 1), H400

Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

+1 800 325-5052

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word
Hazard statement(s)
H350
H410

Danger

May cause cancer. Very toxic to aquatic life with long lasting effects.

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid release to the environment.
Use personal protective equipment as required.
IF exposed or concerned: Get medical advice/ attention.
Collect spillage.
Store locked up.
Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Synonyms	: 1,2-Benzanthracene Tetraphene
Formula	: C <sb>18H<sb>12</sb></sb>
Molecular weight	: 228.29 g/mol
CAS-No.	: 56-55-3
EC-No.	: 200-280-6
Index-No.	: 601-033-00-9

#### Hazardous components

Component	Classification	Concentration
Benz[a]anthracene		
	Carc. 1B; Aquatic Acute 1; Aquatic Chronic 1; H350, H410	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

# 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

# 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### **4.3 Indication of any immediate medical attention and special treatment needed** No data available

# **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture Carbon oxides

# **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information No data available

# 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

# 7. HANDLING AND STORAGE

## 7.1 Precautions for safe handling

Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Store at room temperature.

Storage class (TRGS 510): 6.1D: Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

# Personal protective equipment

# Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Impervious clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: solid
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 157 - 159 °C (315 - 318 °F)
f)	Initial boiling point and boiling range	437.6 °C (819.7 °F)
g)	Flash point	No data available
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	No data available
I)	Vapour density	No data available
m)	Relative density	No data available

n)	Water solubility	No data available	
o)	Partition coefficient: n- octanol/water	No data available	
p)	Auto-ignition temperature	No data available	
q)	Decomposition temperature	No data available	
r)	Viscosity	No data available	
s)	Explosive properties	No data available	
t)	Oxidizing properties	No data available	
Other safety information No data available			

#### **10. STABILITY AND REACTIVITY**

10.1 Reactivity No data available

9.2

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5 Incompatible materials** Strong oxidizing agents

# Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available In the event of fire: see section 5

# **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

No data available Inhalation: No data available Dermal: No data available LD50 Intravenous - Rat - > 200 mg/kg

# Skin corrosion/irritation

No data available

Serious eye damage/eye irritation No data available

#### **Respiratory or skin sensitisation** No data available

Germ cell mutagenicity No data available

#### Carcinogenicity

This product is or contains a component that has been reported to be probably carcinogenic based on its IARC, OSHA, ACGIH, NTP, or EPA classification. Possible human carcinogen

- IARC: 2B Group 2B: Possibly carcinogenic to humans (Benz[a]anthracene)
- IARC: 2B Group 2B: Possibly carcinogenic to humans (Benz[a]anthracene)
- NTP: RAHC Reasonably anticipated to be a human carcinogen (Benz[a]anthracene)
- NTP: RAHC Reasonably anticipated to be a human carcinogen (Benz[a]anthracene)
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

# **Reproductive toxicity**

No data available No data available

#### Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard

No data available

# **Additional Information**

**RTECS:** Not available

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

# **12. ECOLOGICAL INFORMATION**

- 12.1 Toxicity No data available
- 12.2 Persistence and degradability No data available
- **12.3 Bioaccumulative potential** No data available

# 12.4 Mobility in soil No data available(Benz[a]anthracene)

12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

# 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

# **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

#### Contaminated packaging

Dispose of as unused product.

# 14. TRANSPORT INFORMATION

#### DOT (US)

Not dangerous goods **IMDG** UN number: 3077 Class: 9 Packing group: III EMS-No: F-A, S-F Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Benz[a]anthracene) Marine pollutant : yes

# IATA

UN number: 3077 Class: 9 Packing group: III Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (Benz[a]anthracene)

### **Further information**

EHS-Mark required (ADR 2.2.9.1.10, IMDG code 2.10.3) for single packagings and combination packagings containing inner packagings with Dangerous Goods > 5L for liquids or > 5kg for solids.

# **15. REGULATORY INFORMATION**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Chronic Health Hazard

Massachusetts Right To Know Components		
<b>.</b> .	CAS-No.	Revision Date
Benz[a]anthracene	56-55-3	1993-04-24
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Benz[a]anthracene	56-55-3	1993-04-24
	CAS-No	Revision Date
Benzlalanthracene	56-55-3	1003-04-24
Benz[a]antinacene	00 00 0	1000 04 24
New Jersey Right To Know Components		
	CAS-No.	Revision Date
Benz[a]anthracene	56-55-3	1993-04-24
California Prop. 65 Components		
WARNING! This product contains a chemical known to the	CAS-No.	Revision Date
State of California to cause cancer. Benz[a]anthracene	56-55-3	2007-09-28
WARNING! This product contains a chemical known to the	CAS-No.	Revision Date
State of California to cause cancer. Benz[a]anthracene	56-55-3	2007-09-28

# **16. OTHER INFORMATION**

Full text of H-Statements referred to under sections 2 and 3.

H350	May cause cancer.
H400	Very toxic to aquatic life.
Supelco- 48563	

# H410 Very toxic to aquatic life with long lasting effects.

## Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

## **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956 Version: 6.1

Revision Date: 07/17/2018

Print Date: 01/21/2019
# SIGMA-ALDRICH

### SAFETY DATA SHEET

Version 4.8 Revision Date 01/11/2018 Print Date 06/28/2019

1. F	RODUCT AND COMPAN	Y IDENT	IFICATION		
1.1	Product identifiers Product name	:	Beryllium		
	Product Number Brand	:	378135 Aldrich		
	CAS-No.	:	7440-41-7		
1.2	Relevant identified uses of the substance or mixture and uses advised against				
	Identified uses	:	Laboratory chemicals, Synthesis of substances		
1.3	Details of the supplier o	of the sat	fety data sheet		
	Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103		

USA

Telephone	:	+1 800-325-5832
Fax	:	+1 800-325-5052

### 1.4 Emergency telephone number

Emergency Phone #	:	+1-703-527-3887 (	(CHEMTREC)	1
-------------------	---	-------------------	------------	---

### 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 3), H301 Acute toxicity, Inhalation (Category 2), H330 Skin irritation (Category 2), H315 Eye irritation (Category 2A), H319 Skin sensitisation (Category 1), H317 Carcinogenicity (Category 1B), H350 Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335 Specific target organ toxicity - repeated exposure (Category 1), H372

For the full text of the H-Statements mentioned in this Section, see Section 16.

### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)	
H301	Toxic if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.

Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P284	Wear respiratory protection.
P301 + P310 + P330	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

### 3.1 Substances

Formula	:	Be
Molecular weight	:	9.01 g/mol
CAS-No.	:	7440-41-7
EC-No.	:	231-150-7

### Hazardous components

Component	Classification	Concentration
Berylium foil		
	Acute Tox. 3; Acute Tox. 2; Skin Irrit. 2; Eye Irrit. 2A; Skin	90 - 100 %
	Sens. 1; Carc. 1B; STOT SE 3; STOT RE 1; H301, H315,	
	H317, H319, H330, H335,	
	H350, H372	

For the full text of the H-Statements mentioned in this Section, see Section 16.

### 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**4.3** Indication of any immediate medical attention and special treatment needed No data available

### **5. FIREFIGHTING MEASURES**

### 5.1 Extinguishing media

### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture No data available

### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information No data available

### 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust.

For personal protection see section 8.

### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For disposal see section 13.

### 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Keep in a dry place. Storage class (TRGS 510): 4.1B: Flammable solid hazardous materials

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Berylium foil	7440-41-7	TWA	2.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		CEIL	5.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Peak	25.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		TWA	2.000000microg ram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2
	Remarks	Z27.29-1970	)	
		CEIL	5.000000microg ram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z27.29-1970	)	
		Peak	25.000000micro gram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z27.29-1970	)	
		TWA	0.000050 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
		Beryllium se Chronic bery Confirmed h Danger of cu Sensitizer	nsitization /Ilium disease (ber uman carcinogen utaneous absorptio	ylliosis) n
		С	0.000500 mg/m3	USA. NIOSH Recommended Exposure Limits
		Potential Oc See Append	cupational Carcino	gen
		See Table Z	-2	
		TWA	2.000000microg ram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z27.29-1970	)	
		TWA	2.000000microg ram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z27.29-1970	)	
		CEIL	5.000000microg ram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z27.29-1970	)	
		CEIL	5.000000microg ram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z27.29-1970	)	
		Peak	25.000000micro gram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z27.29-1970	)	
		Peak	25.000000micro gram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z27.29-1970	)	
		TWA	0.000050 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
		Beryllium se Chronic bery	nsitization /Ilium disease (ber	ylliosis)

Adopted values or notations enclosed are those for which changes are proposed in the NIC See Notice of Intended Changes (NIC) Confirmed human carcinogen Danger of cutaneous absorption Sensitizer				
C 0.000500 USA. NIOSH Recommended				
Potential Oco See Appendi	cupational Carcino x A	gen		
See Table Z-	2			
TWA	A 2microgram per USA. Occupational Exposure Limits cubic meter (OSHA) - Table Z-2			
Z27.29-1970				
CEIL	5microgram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2		
Z27.29-1970				
Peak	25microgram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2		
Z27.29-1970				
С	0.0005 mg/m3	USA. NIOSH Recommended Exposure Limits		
Potential Oco See Appendi	otential Occupational Carcinogen ee Appendix A			
PEL	0.0002 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
С	0.025 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)		

### 8.2 Exposure controls

### Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

### Personal protective equipment

### **Eye/face protection**

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an

industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: powder Colour: grey
b)	Odour	odourless
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 1,278 °C (2,332 °F) - lit.
f)	Initial boiling point and boiling range	2,970 °C (5,378 °F) - lit.
g)	Flash point	No data available
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	No data available
I)	Vapour density	No data available
m)	Relative density	1.85 g/cm3 at 25 °C (77 °F)
n)	Water solubility	No data available
o)	Partition coefficient: n- octanol/water	No data available
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Othe No da	r <b>safety information</b> ata available	

### **10. STABILITY AND REACTIVITY**

### 10.1 Reactivity

9.2

No data available

### 10.2 Chemical stability

Stable under recommended storage conditions.

- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5** Incompatible materials Alkali metals

# Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Beryllium oxides Other decomposition products - No data available In the event of fire: see section 5

### **11. TOXICOLOGICAL INFORMATION**

### 11.1 Information on toxicological effects

### Acute toxicity

No data available

Inhalation: No data available

Dermal: No data available

LD50 Intravenous - Rat - 0.496 mg/kg Remarks: Liver:Hepatitis (hepatocellular necrosis), zonal.

### Skin corrosion/irritation

No data available

Serious eye damage/eye irritation No data available

Respiratory or skin sensitisation No data available

### Germ cell mutagenicity Hamster

Lungs Result: negative

### Carcinogenicity

Carcinogenicity - Rat - Intratracheal Tumorigenic:Neoplastic by RTECS criteria. Lungs, Thorax, or Respiration:Tumors. Lungs, Thorax, or Respiration:Bronchiogenic carcinoma.

Carcinogenicity - Rabbit - Intravenous Tumorigenic:Equivocal tumorigenic agent by RTECS criteria. Musculoskeletal:Tumors.

Possible human carcinogen

- IARC: 1 Group 1: Carcinogenic to humans (Berylium foil)
- NTP: Known Known to be human carcinogen (Berylium foil)

Known - Known to be human carcinogenThe reference note has been added by TD based on the background information of the NTP. (Berylium foil)

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

### **Reproductive toxicity**

No data available

No data available

### Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

### Additional Information RTECS: DS1750000

### **12. ECOLOGICAL INFORMATION**

### 12.1 Toxicity

No data available

- **12.2 Persistence and degradability** No data available
- **12.3 Bioaccumulative potential** No data available
- 12.4 Mobility in soil No data available
- **12.5** Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

### 12.6 Other adverse effects

No data available

### **13. DISPOSAL CONSIDERATIONS**

### 13.1 Waste treatment methods

### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

### Contaminated packaging

Dispose of as unused product.

### **14. TRANSPORT INFORMATION**

### DOT (US)

UN number: 1567 Proper shipping name: Reportable Quantity (R Poison Inhalation Haza	Class: 6.1 (4.1) Beryllium, powder Q): 10 lbs ırd: No	Packing group: II	
IMDG UN number: 1567 Proper shipping name:	Class: 6.1 (4.1) BERYLLIUM POWDER	Packing group: II	EMS-No: F-G, S-G
<b>IATA</b> UN number: 1567 Proper shipping name:	Class: 6.1 (4.1) Beryllium powder	Packing group: II	

### **15. REGULATORY INFORMATION**

### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

### SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:				
	CAS-No.	Revision Date		
Berylium foil	7440-41-7	1993-04-24		
SARA 311/312 Hazards Acute Health Hazard, Chronic Health Hazard				
Massachusetts Right To Know Components				
	CAS-No.	<b>Revision Date</b>		
Berylium foil	7440-41-7	1993-04-24		
Pennsylvania Right To Know Components				
	CAS-No.	<b>Revision Date</b>		
Berylium foil	7440-41-7	1993-04-24		
	CAS-No.	Revision Date		
Berylium foil	7440-41-7	1993-04-24		
New Jersey Right To Know Components				
·····	CAS-No.	Revision Date		
Berylium foil	7440-41-7	1993-04-24		
California Prop. 65 Components				
WARNING! This product contains a chemical known to the	CAS-No.	Revision Date		
State of California to cause cancer. Berylium foil	7440-41-7	2008-10-10		

### **16. OTHER INFORMATION**

### Full text of H-Statements referred to under sections 2 and 3.

Acute toxicity
Carcinogenicity
Eye irritation
Toxic if swallowed.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Fatal if inhaled.
May cause respiratory irritation.
May cause cancer.
Causes damage to organs through prolonged or repeated exposure.
Skin irritation
Skin sensitisation

### **HMIS Rating**

Health hazard:	4
Chronic Health Hazard:	*
Flammability:	0
Physical Hazard	0

### **NFPA** Rating

Health hazard:	4
Fire Hazard:	3
Reactivity Hazard:	3

### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

**Preparation Information** Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 4.8

Revision Date: 01/11/2018

Print Date: 06/28/2019

# SIGMA-ALDRICH

### SAFETY DATA SHEET

Version 4.8 Revision Date 01/11/2018 Print Date 06/28/2019

1. F	RODUCT AND COMPAN	Y IDENT	IFICATION
1.1	Product identifiers Product name	:	Beryllium
	Product Number Brand	:	378135 Aldrich
	CAS-No.	:	7440-41-7
1.2	Relevant identified uses	s of the s	substance or mixture and uses advised against
	Identified uses	:	Laboratory chemicals, Synthesis of substances
1.3	Details of the supplier o	of the sat	fety data sheet
	Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103

USA

Telephone	:	+1 800-325-5832
Fax	:	+1 800-325-5052

### 1.4 Emergency telephone number

Emergency Phone #	:	+1-703-527-3887 (	(CHEMTREC)	1
-------------------	---	-------------------	------------	---

### 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 3), H301 Acute toxicity, Inhalation (Category 2), H330 Skin irritation (Category 2), H315 Eye irritation (Category 2A), H319 Skin sensitisation (Category 1), H317 Carcinogenicity (Category 1B), H350 Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335 Specific target organ toxicity - repeated exposure (Category 1), H372

For the full text of the H-Statements mentioned in this Section, see Section 16.

### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)	
H301	Toxic if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.

Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P284	Wear respiratory protection.
P301 + P310 + P330	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

### 3.1 Substances

Formula	:	Be
Molecular weight	:	9.01 g/mol
CAS-No.	:	7440-41-7
EC-No.	:	231-150-7

### Hazardous components

Component	Classification	Concentration
Berylium foil		
	Acute Tox. 3; Acute Tox. 2; Skin Irrit. 2; Eye Irrit. 2A; Skin	90 - 100 %
	Sens. 1; Carc. 1B; STOT SE 3; STOT RE 1; H301, H315,	
	H317, H319, H330, H335,	
	H350, H372	

For the full text of the H-Statements mentioned in this Section, see Section 16.

### 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**4.3** Indication of any immediate medical attention and special treatment needed No data available

### **5. FIREFIGHTING MEASURES**

### 5.1 Extinguishing media

### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture No data available

### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information No data available

### 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust.

For personal protection see section 8.

### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For disposal see section 13.

### 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Keep in a dry place. Storage class (TRGS 510): 4.1B: Flammable solid hazardous materials

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis			
Berylium foil	7440-41-7	TWA	2.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-2			
		CEIL	5.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-2			
		Peak	25.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-2			
		TWA	2.000000microg ram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2			
	Remarks	Z27.29-1970	)				
		CEIL	5.000000microg ram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2			
		Z27.29-1970	)				
		Peak	25.000000micro gram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2			
		Z27.29-1970	)				
		TWA	0.000050 mg/m3	USA. ACGIH Threshold Limit Values (TLV)			
		Beryllium se Chronic bery Confirmed h Danger of cu Sensitizer	nsitization /Ilium disease (ber uman carcinogen utaneous absorptio	ylliosis) n			
		С	0.000500 mg/m3	USA. NIOSH Recommended Exposure Limits			
		Potential Oc See Append	Potential Occupational Carcinogen				
		See Table Z	-2				
		TWA	2.000000microg ram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2			
		Z27.29-1970	)				
		TWA	2.000000microg ram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2			
		Z27.29-1970	)				
		CEIL	5.000000microg ram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2			
		Z27.29-1970	)				
		CEIL	5.000000microg ram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2			
		Z27.29-1970	)				
		Peak	25.000000micro gram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2			
		Z27.29-1970	)				
		Peak	25.000000micro gram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2			
		Z27.29-1970	)				
		TWA	0.000050 mg/m3	USA. ACGIH Threshold Limit Values (TLV)			
		Beryllium se Chronic bery	nsitization /Ilium disease (ber	ylliosis)			

Adopted values or notations enclosed are those for which changes are proposed in the NIC See Notice of Intended Changes (NIC) Confirmed human carcinogen Danger of cutaneous absorption Sensitizer		
С	0.000500 mg/m3	USA. NIOSH Recommended Exposure Limits
Potential Oco See Appendi	cupational Carcino x A	gen
See Table Z-	2	
TWA	2microgram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2
Z27.29-1970		
CEIL	5microgram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2
Z27.29-1970		
Peak	25microgram per cubic meter	USA. Occupational Exposure Limits (OSHA) - Table Z-2
Z27.29-1970		
С	0.0005 mg/m3	USA. NIOSH Recommended Exposure Limits
Potential Occupational Carcinogen See Appendix A		
PEL	0.0002 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
С	0.025 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

### 8.2 Exposure controls

### Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

### Personal protective equipment

### **Eye/face protection**

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an

industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: powder Colour: grey
b)	Odour	odourless
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 1,278 °C (2,332 °F) - lit.
f)	Initial boiling point and boiling range	2,970 °C (5,378 °F) - lit.
g)	Flash point	No data available
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	No data available
I)	Vapour density	No data available
m)	Relative density	1.85 g/cm3 at 25 °C (77 °F)
n)	Water solubility	No data available
o)	Partition coefficient: n- octanol/water	No data available
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Othe No da	r <b>safety information</b> ata available	

### **10. STABILITY AND REACTIVITY**

### 10.1 Reactivity

9.2

No data available

### 10.2 Chemical stability

Stable under recommended storage conditions.

- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5** Incompatible materials Alkali metals

# Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Beryllium oxides Other decomposition products - No data available In the event of fire: see section 5

### **11. TOXICOLOGICAL INFORMATION**

### 11.1 Information on toxicological effects

### Acute toxicity

No data available

Inhalation: No data available

Dermal: No data available

LD50 Intravenous - Rat - 0.496 mg/kg Remarks: Liver:Hepatitis (hepatocellular necrosis), zonal.

### Skin corrosion/irritation

No data available

Serious eye damage/eye irritation No data available

Respiratory or skin sensitisation No data available

### Germ cell mutagenicity Hamster

Lungs Result: negative

### Carcinogenicity

Carcinogenicity - Rat - Intratracheal Tumorigenic:Neoplastic by RTECS criteria. Lungs, Thorax, or Respiration:Tumors. Lungs, Thorax, or Respiration:Bronchiogenic carcinoma.

Carcinogenicity - Rabbit - Intravenous Tumorigenic:Equivocal tumorigenic agent by RTECS criteria. Musculoskeletal:Tumors.

Possible human carcinogen

- IARC: 1 Group 1: Carcinogenic to humans (Berylium foil)
- NTP: Known Known to be human carcinogen (Berylium foil)

Known - Known to be human carcinogenThe reference note has been added by TD based on the background information of the NTP. (Berylium foil)

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

### **Reproductive toxicity**

No data available

No data available

### Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

### Additional Information RTECS: DS1750000

### **12. ECOLOGICAL INFORMATION**

### 12.1 Toxicity

No data available

- **12.2 Persistence and degradability** No data available
- **12.3 Bioaccumulative potential** No data available
- 12.4 Mobility in soil No data available
- **12.5** Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

### 12.6 Other adverse effects

No data available

### **13. DISPOSAL CONSIDERATIONS**

### 13.1 Waste treatment methods

### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

### Contaminated packaging

Dispose of as unused product.

### **14. TRANSPORT INFORMATION**

### DOT (US)

UN number: 1567 Proper shipping name: Reportable Quantity (R Poison Inhalation Haza	Class: 6.1 (4.1) Beryllium, powder Q): 10 lbs ırd: No	Packing group: II	
IMDG UN number: 1567 Proper shipping name:	Class: 6.1 (4.1) BERYLLIUM POWDER	Packing group: II	EMS-No: F-G, S-G
<b>IATA</b> UN number: 1567 Proper shipping name:	Class: 6.1 (4.1) Beryllium powder	Packing group: II	

### **15. REGULATORY INFORMATION**

### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

### SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:				
	CAS-No.	Revision Date		
Berylium foil	7440-41-7	1993-04-24		
SARA 311/312 Hazards Acute Health Hazard, Chronic Health Hazard				
Massachusetts Right To Know Components				
	CAS-No.	<b>Revision Date</b>		
Berylium foil	7440-41-7	1993-04-24		
Pennsylvania Right To Know Components				
	CAS-No.	<b>Revision Date</b>		
Berylium foil	7440-41-7	1993-04-24		
	CAS-No.	Revision Date		
Berylium foil	7440-41-7	1993-04-24		
New Jersey Right To Know Components				
·····	CAS-No.	Revision Date		
Berylium foil	7440-41-7	1993-04-24		
California Prop. 65 Components				
WARNING! This product contains a chemical known to the	CAS-No.	Revision Date		
State of California to cause cancer. Berylium foil	7440-41-7	2008-10-10		

### **16. OTHER INFORMATION**

### Full text of H-Statements referred to under sections 2 and 3.

Acute toxicity
Carcinogenicity
Eye irritation
Toxic if swallowed.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Fatal if inhaled.
May cause respiratory irritation.
May cause cancer.
Causes damage to organs through prolonged or repeated exposure.
Skin irritation
Skin sensitisation

### **HMIS Rating**

Health hazard:	4
Chronic Health Hazard:	*
Flammability:	0
Physical Hazard	0

### **NFPA** Rating

Health hazard:	4
Fire Hazard:	3
Reactivity Hazard:	3

### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

**Preparation Information** Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 4.8

Revision Date: 01/11/2018

Print Date: 06/28/2019

# SIGMA-ALDRICH

sigma-aldrich.com

### SAFETY DATA SHEET

against

Version 5.11 Revision Date 08/09/2016 Print Date 06/22/2019

### **1. PRODUCT AND COMPANY IDENTIFICATION**

1.1	Product identifiers Product name	:	Carbon tetrachloride
	Product Number Brand Index-No.	:	571016 Aldrich 602-008-00-5
	CAS-No.	:	56-23-5
1.2	Relevant identified uses of the substance or mixture and uses advised aga		
	Identified uses	:	Laboratory chemicals, Synthesis of substances
			• • • • • •

#### Details of the supplier of the safety data sheet 1.3

Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
Telephone Fax	:	+1 800-325-5832 +1 800-325-5052

#### 1.4 **Emergency telephone number**

**Emergency Phone #** : +1-703-527-3887 (CHEMTREC)

### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 3), H301 Acute toxicity, Inhalation (Category 3), H331 Acute toxicity, Dermal (Category 3), H311 Skin sensitisation (Sub-category 1B), H317 Carcinogenicity (Category 2), H351 Specific target organ toxicity - repeated exposure, Inhalation (Category 1), Liver, Kidney, H372 Acute aquatic toxicity (Category 3), H402 Chronic aquatic toxicity (Category 3), H412 Hazardous to the ozone layer (Category 1), H420

For the full text of the H-Statements mentioned in this Section, see Section 16.

Danger

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Hazard statement(s)	
H301 + H311 + H331	Toxic if swallowed, in contact with skin or if inhaled
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H372	Causes damage to organs (Liver, Kidney) through prolonged or repeated exposure if inhaled.

H412	Harmful to aquatic life with long lasting effects.	
Precautionary statement(s)		
P201	Obtain special instructions before use.	
P202	Do not handle until all safety precautions have been read and understood.	
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.	
P264	Wash skin thoroughly after handling.	
P270	Do not eat, drink or smoke when using this product.	
P271	Use only outdoors or in a well-ventilated area.	
P272	Contaminated work clothing should not be allowed out of the workplace.	
P273	Avoid release to the environment.	
P280	Wear protective gloves/ protective clothing/ eye protection/ face	
	protection.	
P301 + P310 + P330	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth.	
P302 + P352 + P312	IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or doctor/ physician if you feel unwell.	
P304 + P340 + P311	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor	
P308 + P313	IF exposed or concerned: Get medical advice/ attention.	
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.	
P362	Take off contaminated clothing and wash before reuse.	
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.	
P405	Store locked up.	
P501	Dispose of contents/ container to an approved waste disposal plant.	
P502	Refer to manufacturer/ supplier for information on recovery/ recycling.	

**2.3 Hazards not otherwise classified (HNOC) or not covered by GHS** Rapidly absorbed through skin.

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

### 3.1 Substances

Synonyms	: Tetrachloromethane
Formula	: CCl <sub>4</sub>
Molecular weight	: 153.82 g/mol
CAS-No.	: 56-23-5
EC-No.	: 200-262-8
Index-No.	: 602-008-00-5

### Hazardous components

Component	Classification	Concentration
Tetrachloromethane		
	Acute Tox. 3; Skin Sens. 1B; Carc. 2; STOT RE 1; Aquatic Acute 3; Aquatic Chronic 3; Ozone 1; H301 + H311 + H331, H317, H351, H372, H412	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

### 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

### In case of eye contact

Flush eyes with water as a precaution.

### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

- **4.2** Most important symptoms and effects, both acute and delayed The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
- **4.3 Indication of any immediate medical attention and special treatment needed** No data available

### **5. FIREFIGHTING MEASURES**

### 5.1 Extinguishing media

### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture No data available

### **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.

## 5.4 Further information No data available

### 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas.

For personal protection see section 8.

### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

### 6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

### 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. For precautions see section 2.2.

- 7.2 Conditions for safe storage, including any incompatibilities Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

### Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Tetrachloromethane	56-23-5	TWA	5.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Liver damag	е	
		Suspected h	uman carcinogen	
		Danger of cu	utaneous absorptio	n
		STEL	10.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Liver damag	е	
		Suspected h	uman carcinogen	
		Danger of cu	utaneous absorptio	
		51	2.000000 ppm 12.600000 mg/m3	Exposure Limits
-		Potential Oc	cupational Carcino	gen
		See Append	ix A	0
		TWA	10.000000 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
-		Z37.17-1967	7	
		CEIL	25.000000 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z37.17-1967	7	
		Peak	200.000000	USA. Occupational Exposure Limits
			ppm	(OSHA) - Table Z-2
		Z37.17-1967	7	
		See Table Z	-2	
		TWA	5 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Liver damag	е	
		Suspected h Danger of cu	iuman carcinogen utaneous absorptio	n
		STEL	10 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Liver damag	е	
		Suspected h	iuman carcinogen utaneous absorptio	n
		ST	2 ppm	USA. NIOSH Recommended
			12.6 mg/m3	Exposure Limits
		Potential Oc See Append	cupational Carcino ix A	gen
		See Table Z	-2	
		TWA	10 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z37.17-1967	7	
		CEIL	25 ppm	USA. Occupational Exposure Limits
		737 17-1967	7	(OSHA) - Table Z-2
	+	Peak	200 ppm	USA Occupational Exposure Limite
		707 47 400		(OSHA) - Table Z-2
		1237.17-1967	0.000	
		IVVA	∠ ppm 12.6 mg/m3	Air Contaminants - 1910.1000
		PEL	2 ppm 12.6 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		Skin		

C	200 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Skin		
STEL	10 ppm 63 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Skin		

### 8.2 Exposure controls

### Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

### Personal protective equipment

### **Eye/face protection**

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 240 min Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid Colour: colourless
b)	Odour	sweet
c)	Odour Threshold	No data available

d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: -22.99 °C (-9.38 °F)
f)	Initial boiling point and boiling range	77 °C (171 °F) at 1,013 hPa (760 mmHg)
g)	Flash point	does not flash
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	45 hPa (34 mmHg) at 0.3 °C (32.5 °F) 120 hPa (90 mmHg) at 19.8 °C (67.6 °F) 14,549 hPa (10,913 mmHg) at 24 °C (75 °F)
I)	Vapour density	No data available
m)	Relative density	1.59 g/cm3 at 20 °C (68 °F)
n)	Water solubility	0.8461 g/l at 20 °C (68 °F)
o)	Partition coefficient: n- octanol/water	log Pow: 2.83 at 25 °C (77 °F)
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Oth	ner safety information	
	Surface tension	26.7 mN/m at 20 °C (68 °F) 19.5 mN/m at 80 °C (176 °F)

### **10. STABILITY AND REACTIVITY**

10.1 Reactivity

9.2

No data available

### **10.2 Chemical stability** Stable under recommended storage conditions.

- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available

### **10.5** Incompatible materials Strong oxidizing agents

### **10.6** Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides, Hydrogen chloride gas Other decomposition products - No data available In the event of fire: see section 5

### 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

### Acute toxicity

LD50 Oral - Rat - 2,350 mg/kg

LC50 Inhalation - Rat - 4 h - 8000 ppm

LD50 Dermal - Rabbit - > 20,000 mg/kg

No data available

### Skin corrosion/irritation

Skin - Rabbit Result: Mild skin irritation - 24 h (Draize Test)

### Serious eye damage/eye irritation

Eyes - Rabbit Result: Mild eye irritation - 24 h (Draize Test)

### Respiratory or skin sensitisation

- Mouse Result: The product is a skin sensitiser, sub-category 1B. (OECD Test Guideline 429)

### Germ cell mutagenicity

No data available

### Carcinogenicity

This product is or contains a component that has been reported to be probably carcinogenic based on its IARC, OSHA, ACGIH, NTP, or EPA classification. Limited evidence of carcinogenicity in animal studies

- IARC: 2B Group 2B: Possibly carcinogenic to humans (Tetrachloromethane)
- NTP: Reasonably anticipated to be a human carcinogen (Tetrachloromethane)
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

### **Reproductive toxicity**

No data available

No data available

Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure Inhalation - Causes damage to organs through prolonged or repeated exposure. - Liver, Kidney

Aspiration hazard No data available

### **Additional Information**

RTECS: FG4900000

Vomiting, Diarrhoea, Abdominal pain, Nausea, Dizziness, Headache, Damage to the eyes., Liver injury may occur., Kidney injury may occur., Exposure to and/or consumption of alcohol may increase toxic effects., Contact with skin can cause:, Pain, Erythema, hyperemia

### 12. ECOLOGICAL INFORMATION

12.1 Toxicity

	Toxicity to fish	mortality LC50 - Danio rerio (zebra fish) - 24.3 mg/l - 96 h	
	Toxicity to daphnia and other aquatic invertebrates	Immobilization EC50 - Daphnia magna (Water flea) - 35 mg/l - 48 h (OECD Test Guideline 202)	
	Toxicity to algae	Growth inhibition EC50 - Algae - 20 mg/l - 72 h (OECD Test Guideline 201)	
12.2	<b>Persistence and degrad</b> No data available	ability	
12.3	Bioaccumulative potent Bioaccumulation	ial Lepomis macrochirus (Bluegill) - 21 d - 52.3 μg/l	
		Bioconcentration factor (BCF): 30	
12.4	<b>Mobility in soil</b> No data available		
12.5	<b>Results of PBT and vPv</b> PBT/vPvB assessment no	B assessment ot available as chemical safety assessment not required/not conducted	
12.6	<b>Other adverse effects</b> An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.		
13. DI	SPOSAL CONSIDERATIO	DNS	
13.1	Waste treatment method	ds	
	<b>Product</b> Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.		
	<b>Contaminated packagin</b> Dispose of as unused pro	<b>g</b> duct.	

### **14. TRANSPORT INFORMATION**

DOT (US) UN number: 1846 Class: 6.1 Proper shipping name: Carbon tetrachloride Reportable Quantity (RQ): 10 lbs	Packing group: II	
Poison Inhalation Hazard: No		
IMDG UN number: 1846 Class: 6.1 Proper shipping name: CARBON TETRACHLO Marine pollutant: yes	Packing group: II RIDE	EMS-No: F-A, S-A
UN number: 1846 Class: 6.1 Proper shipping name: Carbon tetrachloride	Packing group: II	

### **15. REGULATORY INFORMATION**

SARA 302 Components
No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302

### SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
Tetrachloromethane	56-23-5	2007-07-01

### SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

### Massachusetts Right To Know Components

	CAS-No.	Revision Date
Tetrachloromethane	56-23-5	2007-07-01
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Tetrachloromethane	56-23-5	2007-07-01
New Jersey Right To Know Components		
	CAS-No.	Revision Date
Tetrachloromethane	56-23-5	2007-07-01
California Prop. 65 Components		
WARNING! This product contains a chemical known to the	CAS-No.	Revision Date
State of California to cause cancer.	56-23-5	2007-09-28
Tetrachloromethane		

### **16. OTHER INFORMATION**

### Full text of H-Statements referred to under sections 2 and 3.

Acute Tox	Acute toxicity
Acute TOX.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Carc.	Carcinogenicity
H301	Toxic if swallowed.
H301 + H311 +	Toxic if swallowed, in contact with skin or if inhaled
H331	
H311	Toxic in contact with skin.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H351	Suspected of causing cancer.
HMIS Rating	

Health hazard:	2
Chronic Health Hazard:	*
Flammability:	0
Physical Hazard	0
NFPA Rating	
	<u> </u>

Health hazard:	2
Fire Hazard:	0
Reactivity Hazard:	0

### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

## SIGMA-ALDRICH

### SAFETY DATA SHEET

Version 3.18 Revision Date 08/14/2018 Print Date 06/22/2019

### **1. PRODUCT AND COMPANY IDENTIFICATION**

1.1	Product identifiers Product name	<sup>:</sup> Chloroform	
	Product Number Brand Index-No.	: C2432 : Sigma-Aldrich : 602-006-00-4	
	CAS-No.	: 67-66-3	
1.2	Relevant identified uses	of the substance or mixtu	re and u

### Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
Telephone Fax	:	+1 800-325-5832 +1 800-325-5052

### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

### 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 4), H302 Acute toxicity, Inhalation (Category 3), H331 Skin irritation (Category 2), H315 Eye irritation (Category 2A), H319 Carcinogenicity (Category 2), H351 Reproductive toxicity (Category 2), H361d Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336 Specific target organ toxicity - repeated exposure (Category 1), Liver, Kidney, H372 Acute aquatic toxicity (Category 3), H402

For the full text of the H-Statements mentioned in this Section, see Section 16.

Danger

### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

lazard statement(s)	
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.

F

H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs (Liver, Kidney) through prolonged or repeated
H402	Harmful to aquatic life.
Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face
	protection.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P311	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

### 3.1 Substances

Synonyms	:	Trichloromethane Methylidyne trichloride
Formula Molecular weight CAS-No.	: : :	CHCl <sub>3</sub> 119.38 g/mol 67-66-3
EC-No. Index-No.	:	200-663-8 602-006-00-4

### Hazardous components

Component	Classification	Concentration
Chloroform		
	Acute Tox. 4; Acute Tox. 3;	90 - 100 %
	Skin Irrit. 2; Eye Irrit. 2A; Carc.	
	2; Repr. 2; STOT SE 3; STOT	
	RE 1; Aquatic Acute 3; H302,	
	H315, H319, H331, H336,	
	H351, H361d, H372, H402	

For the full text of the H-Statements mentioned in this Section, see Section 16.

### 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

### **General advice**

Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.

### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**4.3 Indication of any immediate medical attention and special treatment needed** No data available

### **5. FIREFIGHTING MEASURES**

### 5.1 Extinguishing media

### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture No data available

### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information No data available

No data available

### 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas.

For personal protection see section 8.

### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For disposal see section 13.

### 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. For precautions see section 2.2.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510): 6.1D: Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

### Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Chloroform	67-66-3	TWA	10 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Central Nerv	ous System impair	ment
		Liver damage	e	
		Embryo/fetal	damage	
		Confirmed an	nimal carcinogen w	vith unknown relevance to humans
		ST	2 ppm	USA. NIOSH Recommended
			9.78 mg/m3	Exposure Limits
		Potential Oco	cupational Carcino	gen
		See Appendi	хA	
		С	50 ppm	USA. Occupational Exposure Limits
			240 mg/m3	(OSHA) - Table Z-1 Limits for Air
				Contaminants
		The value in	mg/m3 is approxin	nate.
		Ceiling limit i	s to be determined	from breathing-zone air samples.
		PEL	2 ppm	California permissible exposure
			9.70 mg/mo	(Title 8 Article 107)

### 8.2 Exposure controls

### Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

### Personal protective equipment

### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid, clear Colour: colourless
b)	Odour	sweet
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: -63 °C (-81 °F)
f)	Initial boiling point and boiling range	60.5 - 61.5 °C (140.9 - 142.7 °F)
g)	Flash point	- DIN 51755 Part 1does not flash
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	210 hPa (158 mmHg) at 20 °C (68 °F)
I)	Vapour density	4.12 - (Air = 1.0)
m)	Relative density	1.492 g/mL at 25 °C (77 °F)
n)	Water solubility	8.7 g/l at 23 °C (73 °F) - OECD Test Guideline 105
o)	Partition coefficient: n- octanol/water	log Pow: 1.97 at 25 °C (77 °F) - (ECHA), Bioaccumulation is not expected.
p)	Auto-ignition temperature	> 600 °C (> 1,112 °F) at 1,013 hPa (760 mmHg) - DIN 51794
q)	Decomposition temperature	Distillable in an undecomposed state at normal pressure.
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Othe	r safety information	
	Solubility in other solvents	organic solvent at 20 °C (68 °F) - miscible
	Surface tension	27.1 mN/m at 20.0 °C (68.0 °F)
	Relative vapour density	4.12 - (Air = 1.0)

9.2

### **10. STABILITY AND REACTIVITY**

10.1 Reactivity

No data available

### 10.2 Chemical stability

Stable under recommended storage conditions. Contains the following stabiliser(s): 2-Methyl-2-butene (>=0.001 - <=0.015 %)

- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- 10.5 Incompatible materials various plastics, Rubber

### 10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides, Hydrogen chloride gas Other decomposition products - No data available In the event of fire: see section 5

### **11. TOXICOLOGICAL INFORMATION**

### 11.1 Information on toxicological effects

### Acute toxicity

LD50 Oral - Rat - male - 908 mg/kg (OECD Test Guideline 401) Remarks: Behavioral:Change in motor activity (specific assay). Behavioral:Ataxia. Lungs, Thorax, or Respiration:Respiratory stimulation.

LOEC Inhalation - Rat - male - 6 h - 500 ppm Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

LD50 Dermal - Rabbit - > 20,000 mg/kg Remarks: (RTECS)

No data available

### Skin corrosion/irritation

Skin - Rabbit Result: Irritating to skin. - 24 h Remarks: (ECHA)

### Serious eye damage/eye irritation

Eyes - Rabbit Result: Irritating to eyes. Remarks: (ECHA)

### Respiratory or skin sensitisation

Sensitisation test: - Guinea pig Result: negative (Maximisation Test) Remarks: (ECHA)

### Germ cell mutagenicity

Ames test Salmonella typhimurium Result: negative

reverse mutation assay Escherichia coli Result: negative (ECHA) OECD Test Guideline 474 Rat - male and female - Bone marrow Result: negative

OECD Test Guideline 486 Rat - male - Other cell types Result: negative

### Carcinogenicity

Carcinogenicity - Rat - Oral Tumorigenic:Carcinogenic by RTECS criteria. Leukaemia

Suspected of causing cancer.

- IARC: 2B Group 2B: Possibly carcinogenic to humans (Chloroform)
- NTP: RAHC Reasonably anticipated to be a human carcinogen (Chloroform)
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

### **Reproductive toxicity**

Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

### Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure. - Liver, Kidney

### Aspiration hazard

No data available

### Additional Information

RTECS: FS9100000

Vomiting, Cough, irritant effects, Shortness of breath, respiratory arrest, narcosis, Dizziness, Nausea, agitation, spasms, inebriation, Headache, Stomach/intestinal disorders, ataxia (impaired locomotor coordination), cardiovascular disorders Drying-out effect resulting in rough and chapped skin.

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

### 12. ECOLOGICAL INFORMATION

### 12.1 Toxicity

	Toxicity to fish	flow-through test LC50 - Danio rerio (zebra fish) - 121 mg/l  - 48 h (OECD Test Guideline 203)
		static test LC50 - Pimephales promelas (fathead minnow) - 103 - 171 mg/l - 96 h Remarks: (ECHA)
		flow-through test LC50 - Oncorhynchus mykiss (rainbow trout) - 18.2 mg/l - 96 h Remarks: (ECHA)
		flow-through test LC50 - Micropterus dolomieui - 51 mg/l - 96 h Remarks: (ECHA)
	Toxicity to daphnia and other aquatic invertebrates	static test EC50 - Daphnia magna (Water flea) - 79 mg/l - 48 h Remarks: (ECHA)
	Toxicity to algae	static test ErC50 - Chlamydomonas reinhardtii (green algae) - 13.3 mg/l - 72 h Remarks: (ECHA)
12.2	Persistence and degrada Biodegradability	bility aerobic - Exposure time 14 d
Result: 0 % - Not readily biodegradable. (OECD Test Guideline 301C)

#### 12.3 Bioaccumulative potential Bioaccumulation

Cyprinus carpio (Carp) - 42 d at 25 °C - 0.1 mg/l

> Bioconcentration factor (BCF): 4.1 - 13 (OECD Test Guideline 305)

Cyprinus carpio (Carp) - 42 d at 25 °C - 1 mg/l

Bioconcentration factor (BCF): 1.4 - 4.7 (OECD Test Guideline 305)

#### 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life.

## **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

## Contaminated packaging

Dispose of as unused product.

## **14. TRANSPORT INFORMATION**

## DOT (US)

UN number: 1888 Class: 6.1 Packing group: III Proper shipping name: Chloroform Reportable Quantity (RQ): 10 lbsReportable Quantity (RQ): 10 lbs Poison Inhalation Hazard: No	
IMDG UN number: 1888 Class: 6.1 Packing group: III EMS-No: F-A, S-A Proper shipping name: CHLOROFORM	4
IATA UN number: 1888 Class: 6.1 Packing group: III Proper shipping name: Chloroform	
REGULATORY INFORMATION	
SARA 302 Components	
CAS-No. Revision Chloroform 67-66-3 2008-11	Date -03
SARA 313 Components The following components are subject to reporting levels established by SARA Title III, Section 313	3:
CAS-No.RevisionChloroform67-66-32008-11	Date -03

15.

#### SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

### Reportable Quantity D022 lbs

:

#### Massachusetts Right To Know Components

		Devision Data
	CAS-NO.	Revision Date
Chloroform	67-66-3	2008-11-03
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Chloroform	67-66-3	2008-11-03
California Prop. 65 Components		
, which is/are known to the State of California to cause cancer	CAS-No.	Revision Date
and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Chloroform	67-66-3	2011-09-01

## **16. OTHER INFORMATION**

Full text of H-Statements referred to under sections 2 and 3.

Acute Tox.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Carc.	Carcinogenicity
Eye Irrit.	Eye irritation
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H402	Harmful to aquatic life.
Repr.	Reproductive toxicity
Skin Irrit.	Skin irritation
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

#### Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 3.18

Revision Date: 08/14/2018

Print Date: 06/22/2019



# Part of Thermo Fisher Scientific

# SAFETY DATA SHEET

Creation Date 13-Sep-2013

Revision Date 21-Jul-2015

**Revision Number** 2

1. Identification		
Product Name	Chromium	
Cat No. :	C318-500	
Synonyms	Chrome	
Recommended Use	Laboratory chemicals.	
Uses advised against Details of the supplier of the safety	No Information available data sheet	
<b>Company</b> Fisher Scientific One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100	Emergency Telephone Number CHEMTREC®, Inside the USA: 800-424-9300 CHEMTREC®, Outside the USA: 001-703-527-3887	

2. Hazard(s) identification

#### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Specific target organ toxicity (single exposure) Target Organs - Respiratory system. Category 3

## Label Elements

Signal Word Warning

Hazard Statements

May cause respiratory irritation



Precautionary Statements Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell

#### Storage

Store in a well-ventilated place. Keep container tightly closed

## Store locked up

## Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Very toxic to aquatic life

## 3. Composition / information on ingredients

Component	CAS-No	Weight %
Chromium	7440-47-3	>95

4. First-aid measures		
General Advice	If symptoms persist, call a physician.	
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.	
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Obtain medical attention.	
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Obtain medical attention.	
Ingestion	Do not induce vomiting. Obtain medical attention.	
Most important symptoms/effects Notes to Physician	None reasonably foreseeable. Treat symptomatically	
	5. Fire-fighting measures	
Unsuitable Extinguishing Media	Carbon dioxide (CO2)	
Flash Point Method -	Not applicable No information available	
Autoignition Temperature Explosion Limits	Not applicable	

Upper No data available Lower No data available Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

#### **Specific Hazards Arising from the Chemical**

Dust can form an explosive mixture in air. Do not allow run-off from fire fighting to enter drains or water courses.

#### **Hazardous Combustion Products**

Chromium oxide

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

N	FPA	

Health	Flammability	Instability	Physical hazards
2	1	1	N/A

	6. Accidental release measures
Personal Precautions Environmental Precautions	Ensure adequate ventilation. Use personal protective equipment. Avoid dust formation. Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained. See Section 12 for additional ecological information. Avoid release to the environment. Collect spillage.
Methods for Containment and Clea Up	<ul> <li>an Avoid dust formation. Sweep up or vacuum up spillage and collect in suitable container for disposal. Keep in suitable, closed containers for disposal.</li> </ul>
	7. Handling and storage
Line all lan a	Avaid duct formation Mission and an extention and interest. For any address to continue to

Handling

Avoid dust formation. Wear personal protective equipment. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Store under an inert atmosphere.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Chromium	TWA: 0.5 mg/m <sup>3</sup>	(Vacated) TWA: 1 mg/m <sup>3</sup>	IDLH: 250 mg/m <sup>3</sup>
		TWA: 1 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
Chromium	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>
Lanand			

<u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures	Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location.
Personal Protective Equipment	
Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

	9. Physical and chemical properties
Physical State	Powder
Appearance	Silver
Odor	Odorless
Odor Threshold	No information available
рН	No information available
Melting Point/Range	1857.2 °C / 3375 °F

Boiling Point/Range
Flash Point
Evaporation Rate
Flammability (solid,gas)
Flammability or explosive limits
Upper
Lower
Vapor Pressure
Vapor Density
Relative Density
Solubility
Partition coefficient; n-octanol/water
Autoignition Temperature
Decomposition Temperature
Viscosity
Molecular Formula
Molecular Weight

2640 °C / 4784 °F Not applicable Not applicable No information available No data available No data available No data available Not applicable 7.2 Insoluble in water No data available Not applicable Not applicable Not applicable Cr 51.996

## 10. Stability and reactivity

	11. Toxicological information		
Hazardous Reactions	None under normal processing.		
Hazardous Polymerization	Hazardous polymerization does not occur.		
Hazardous Decomposition Products Chromium oxide			
Incompatible Materials	Strong oxidizing agents, Strong acids		
Conditions to Avoid	Incompatible products. Excess heat. Avoid dust formation.		
Stability	Sensitive to air.		
Reactive Hazard	None known, based on information available		

#### Acute Toxicity

Component Informa Toxicologically Syn Products Delayed and immed	tion ergistic iate effects as v	No information ava	ailable cts from short an	d long-term expo	sure	
Irritation		May cause irritatio	n of respiratory tra	ct		
Sensitization		No information ava	ailable			
Carcinogenicity		The table below in	dicates whether ea	ach agency has lis	ted any ingredient	as a carcinogen.
Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Chromium	7440-47-3	Not listed	Not listed	Not listed	Not listed	Not listed
Mutagenic Effects		No information available				
Reproductive Effect	S	No information available.				
Developmental Effe	cts	No information ava	ailable.			

Teratogenicity No information available.

STOT - single exposure	Respiratory system
STOT - repeated exposure	None known

Aspiration hazard	No information available
Symptoms / effects,both acute and	No information available
Endocrine Disruptor Information	No information available
Other Adverse Effects	The toxicological properties have not been fully investigated. See actual entry in RTECS for complete information.

## 12. Ecological information

## Ecotoxicity

The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms.

Component	Freshwater A	gae	Freshwater Fish	Microtox	Water Flea
Chromium	Not listed		LC50: 14.3 mg/l/96 H (Pimephales promelas)	Not listed	EC50: 0.07 mg/l/48 H
Persistence and Degrada	ability Insol	uble in v	vater		
Bioaccumulation/ Accun	nulation No ir	oformation	on available.		
Mobility	ility Is not likely mobile in the environment due its low water solubility.				
	1	3. Di	sposal considera	ations	
Waste Disposal Methods	S Cher haza natic	nical wa rdous w nal haza	aste generators must deterr aste. Chemical waste gen ardous waste regulations to	nine whether a discarded erators must also consult ensure complete and ac	chemical is classified as a local, regional, and curate classification.
		14. T	ransport informa	ation	
DOT					
UN-No	UN3	077			
Proper Shipping Nan	ne ENV	IRONM	ENTALLY HAZARDOUS S	UBSTANCES, SOLID, N.	0.S.
Proper technical nan	ne Chro	mium			
Hazard Class	9				
Packing Group					
<u>IDG</u>	Not i	egulate	đ		
	UN-No UN3077				
Proper Shipping Nan	NE ENV	IRONM	ENTALLY HAZARDOUS S	UBSTANCES, SOLID, N.	0.8.
Hazard Class	Hazard Class 9				
Packing Group	111				
		077			
UN-NO Desnos Chinging Nog	UN3	077			
Proper Snipping Name Environmentally hazardous substance, solid, n.o.s					
nazaro Class 9					
		077			
Dropor Shipping Non	DINS Envi	077 conmont	ally bazardous substance	solid n o s	
		onnen	ally hazardous substance,	30110, 11.0.3	
Packing Group	UI UI				
		15. R	egulatory inform	ation	

## International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Chromium	Х	Х	-	231-157-5	-		Х	-	Х	Х	Х

#### Legend: X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

#### U.S. Federal Regulations

Not applicable

TSCA 12(b) SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Chromium	7440-47-3	>95	1.0

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

#### **Clean Water Act**

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Chromium	-	-	Х	Х

#### Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Chromium	Х		-

**OSHA** Occupational Safety and Health Administration Not applicable

#### CERCLA

Not applicable

		CERCLA EHS RQs	
Chromium	5000 lb 10 lb	-	

California Proposition 65 This product does not contain any Proposition 65 chemicals

#### State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Chromium	Х	Х	Х	Х	Х

#### **U.S. Department of Transportation**

Reportable Quantity (RQ):	Ν
DOT Marine Pollutant	Ν
DOT Severe Marine Pollutant	Ν

#### **U.S. Department of Homeland Security**

This product does not contain any DHS chemicals.

#### Other International Regulations

#### Mexico - Grade

No information available

#### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class

D2B Toxic materials

13-Sep-2013



## 16. Other information

**Prepared By** 

Creation Date Revision Date Print Date Revision Summary Regulatory Affairs Thermo Fisher Scientific Email: EMSDS.RA@thermofisher.com

21-Jul-2015 21-Jul-2015 This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

# End of SDS

# SIGMA-ALDRICH

# SAFETY DATA SHEET

Version 5.5 Revision Date 01/10/2018 Print Date 01/21/2019

## **1. PRODUCT AND COMPANY IDENTIFICATION**

1.1	Product identifiers Product name	:	Chrysene
	Product Number Brand Index-No.	:	35754 Sigma-Aldrich 601-048-00-0
	CAS-No.	:	218-01-9

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
Telephone Fax	:	+1 800-325-5832 +1 800-325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

#### 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Germ cell mutagenicity (Category 2), H341 Carcinogenicity (Category 1B), H350 Acute aquatic toxicity (Category 1), H400 Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word



Danger

Hazard statement(s)	
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H410	Very toxic to aquatic life with long lasting effects.
Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P273	Avoid release to the environment.
P281	Use personal protective equipment as required.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.

P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

## 3.1 Substances

Formula	:	C <sub>18</sub> H <sub>12</sub>
Molecular weight	:	228.29 g/mol
CAS-No.	:	218-01-9
EC-No.	:	205-923-4
Index-No.	:	601-048-00-0

#### Hazardous components

Chrysono		
Cill yselle		
	Muta. 2; Carc. 1B; Aquatic Acute 1; Aquatic Chronic 1; H341, H350, H410	90 - 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

## 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

# 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### **4.3 Indication of any immediate medical attention and special treatment needed** No data available

## **5. FIREFIGHTING MEASURES**

## 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture No data available

## 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information No data available

## 6. ACCIDENTAL RELEASE MEASURES

## 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

## 6.4 Reference to other sections

For disposal see section 13.

## 7. HANDLING AND STORAGE

## 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

# 7.2 Conditions for safe storage, including any incompatibilities Keep container tightly closed in a dry and well-ventilated place. Storage class (TRGS 510): 6.1D: Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

## 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis		
			parameters			
	Remarks	Cancer Substances for which there is a Biological Exposure Index or Indices (see BEI® section), see BEI® for Polycyclic Aromatic Hydrocarbons (PAHs) Exposure by all routes should be carefully controlled to levels as low				
		as possible.				
		Confirmed an	nimal carcinogen w	vith unknown relevance to humans		
Chrysene	218-01-9	TWA	0.200000	USA. Occupational Exposure Limits		
			mg/m3	(OSHA) - Table Z-1 Limits for Air		
				Contaminants		
		TWA	0.200000	USA. Occupational Exposure Limits		
			mg/m3	(OSHA) - Table Z-1 Limits for Air		
				Contaminants		
		1910.1002				
		As used in §	1910.1000 (Table 2	Z-1), coal tar pitch volatiles include		
		the fused pol	ycyclic hydrocarbo	ons which volatilize from the		
		distillation rea	sidues of coal, pet	roleum (excluding asphalt), wood,		
		and other org	ganic matter. Asph	nalt (CAS 8052-42-4, and CAS		
		64742-93-4)	is not covered und	ler the 'coal tar pitch volatiles'		
		standard				
		OSHA specif	ically regulated ca	rcinogen		
		TWA	0.100000	USA. NIOSH Recommended		
			mg/m3	Exposure Limits		
		Potential Occupational Carcinogen				

NIOSH considers coal tar, coal tar pitch, and creosote to be coal tar products. cyclohexane-extractable fraction See Appendix C See Appendix A			
PEL	0.2 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)	

### Biological occupational exposure limits

U					
Component	CAS-No.	Parameters	Value	Biological specimen	Basis
	-	1- Hydroxypyren e		Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift at end of workweek			

#### 8.2 Exposure controls

## Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Impervious clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: solid
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 252 - 254 °C (486 - 489 °F) - lit.
f)	Initial boiling point and boiling range	448 °C (838 °F) - lit.
g)	Flash point	No data available
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	No data available
I)	Vapour density	No data available
m)	Relative density	No data available
n)	Water solubility	insoluble
o)	Partition coefficient: n- octanol/water	log Pow: 5.73
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
<b>Othe</b> No da	r <b>safety information</b> ata available	

## **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity

9.2

No data available

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5** Incompatible materials Strong oxidizing agents
- Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available In the event of fire: see section 5

## **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity No data available

Inhalation: No data available

Dermal: No data available

LD50 Intraperitoneal - Mouse - > 320 mg/kg

Skin corrosion/irritation No data available

Serious eye damage/eye irritation No data available

Respiratory or skin sensitisation No data available

#### Germ cell mutagenicity

Laboratory experiments have shown mutagenic effects. In vitro tests showed mutagenic effects

## Carcinogenicity

This product is or contains a component that has been reported to be probably carcinogenic based on its IARC, OSHA, ACGIH, NTP, or EPA classification.

Possible human carcinogen

- IARC: 2B Group 2B: Possibly carcinogenic to humans (Chrysene)
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: OSHA specifically regulated carcinogen (Chrysene)

#### Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

## **Additional Information**

RTECS: GC0700000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

## **12. ECOLOGICAL INFORMATION**

## 12.1 Toxicity

Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 1.90 mg/l - 2 h other aquatic invertebrates

12.2 Persistence and degradability

No data available

#### **12.3 Bioaccumulative potential** No data available

## **12.4 Mobility in soil** No data available

### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life.

## **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

#### Contaminated packaging

Dispose of as unused product.

## **14. TRANSPORT INFORMATION**

#### DOT (US)

UN number: 3077 Class: 9 Packing group: III Proper shipping name: Environmentally hazardous substances, solid, n.o.s. (Chrysene) Reportable Quantity (RQ): 100 lbs Poison Inhalation Hazard: No

#### IMDG

UN number: 3077 Class: 9 Packing group: III EMS-No: F-A, S-F Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Chrysene) Marine pollutant:yes

#### ΙΑΤΑ

UN number: 3077 Class: 9 Packing group: III Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (Chrysene)

#### Further information

EHS-Mark required (ADR 2.2.9.1.10, IMDG code 2.10.3) for single packagings and combination packagings containing inner packagings with Dangerous Goods > 5L for liquids or > 5kg for solids.

## **15. REGULATORY INFORMATION**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

The following components are subject to reporting levels establish	ed by SARA Title III, S	Section 313:
	CAS-No.	Revision Date
Chrysene	218-01-9	1994-04-01
SARA 311/312 Hazards Chronic Health Hazard		
Massachusetts Right To Know Components		
	CAS-No.	Revision Date
Chrysene	218-01-9	1994-04-01
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Chrysene	218-01-9	1994-04-01

	CAS-No.	Revision Date
Chrysene	218-01-9	1994-04-01
New Jersey Right To Know Components		
	CAS-No.	Revision Date
Chrysene	218-01-9	1994-04-01
California Prop. 65 Components		
WARNING! This product contains a chemical known to the	CAS-No.	Revision Date
State of California to cause cancer.	218-01-9	2007-09-28
Chrysene		

#### **16. OTHER INFORMATION**

## Full text of H-Statements referred to under sections 2 and 3.

Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Carc.	Carcinogenicity
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

#### **HMIS Rating**

0
*
0
0

#### **NFPA** Rating

Health hazard:	0
Fire Hazard:	0
Reactivity Hazard:	0

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.5

Revision Date: 01/10/2018

Print Date: 01/21/2019



# **SAFETY DATA SHEET**

Version 6.1 Revision Date 03/12/2019 Print Date 06/22/2019

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## **1.1** Product identifiers

Product name : Copper Product Number : 31284 Brand : Aldrich CAS-No. : 7440-50-8

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

## 1.3 Details of the supplier of the safety data sheet

Company	: Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES
Telephone	: +1 314 771-5765

Telephone	:	+1 314 //1-5/65
Fax	:	+1 800 325-5052

## **1.4 Emergency telephone number**

Emergency Phone # : +1-703-527-3887

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

Not a hazardous substance or mixture.

## 2.2 GHS Label elements, including precautionary statements

Not a hazardous substance or mixture.

## 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

## SECTION 3: Composition/information on ingredients

3.1	Substances				
	Formula	:	Cu		
	Molecular weight	:	63.55 g/mol		
	CAS-No.	:	7440-50-8		
	EC-No.	:	231-159-6		
	Component			Classification	Concentration

Aldrich - 31284

Page 1 of 8



Copper,	
	<= 100 %

## SECTION 4: First aid measures

## 4.1 Description of first aid measures

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration.

#### In case of skin contact

Wash off with soap and plenty of water.

#### In case of eye contact

Flush eyes with water as a precaution.

### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water.

- **4.2 Most important symptoms and effects, both acute and delayed** The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
- **4.3 Indication of any immediate medical attention and special treatment needed** No data available

## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

# Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

- **5.2** Special hazards arising from the substance or mixture Copper oxides
- **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.
- **5.4 Further information** No data available

#### **SECTION 6:** Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Avoid dust formation. Avoid breathing vapours, mist or gas. For personal protection see section 8.
- **6.2 Environmental precautions** No special environmental precautions required.
- **6.3 Methods and materials for containment and cleaning up** Sweep up and shovel. Keep in suitable, closed containers for disposal.

Aldrich - 31284

Page 2 of 8



## SECTION 7: Handling and storage

## 7.1 Precautions for safe handling

Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs. Provide appropriate exhaust ventilation at places where dust is formed.

For precautions see section 2.2.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Store under inert gas. Air sensitive. Storage class (TRGS 510): 13: Non Combustible Solids

## 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

## Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis			
Copper,	7440-50-8	TWA	1 mg/m3	USA. ACGIH Threshold Limit Values (TLV)			
	Remarks	Irritation Gastrointestinal metal fume fever					
		TWA	0.2 mg/m3	USA. ACGIH Threshold Limit Values (TLV)			
		Irritation Gastrointes metal fume	tinal fever				

Page 3 of 8



TWA	1 mg/m3	USA. NIOSH Recommended Exposure Limits
TWA	1 mg/m3	USA. NIOSH Recommended Exposure Limits
TWA	1 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
TWA	0.1 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
PEL	0.1 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

## 8.2 Exposure controls

#### Appropriate engineering controls

General industrial hygiene practice.

## **Personal protective equipment**

## Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

## **Body Protection**

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Aldrich - 31284

Page 4 of 8



## **Respiratory protection**

Respiratory protection is not required. Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN 143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

## **Control of environmental exposure**

No special environmental precautions required.

## SECTION 9: Physical and chemical properties

## 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: Wire Colour: light red	
b)	Odour	No data available	
c)	Odour Threshold	No data available	
d)	рН	No data available	
e)	Melting point/freezing point	Melting point/range: 1,083.4 °C (1,982.1 °F)	
f)	Initial boiling point and boiling range	2,567 °C 4,653 °F	
g)	Flash point	()No data available	
h)	Evaporation rate	No data available	
i)	Flammability (solid, gas)	No data available	
j)	Upper/lower flammability or explosive limits	No data available	
k)	Vapour pressure	No data available	
I)	Vapour density	No data available	
m)	Relative density	8.940 g/cm3	
n)	Water solubility	No data available	
o)	Partition coefficient: n-octanol/water	No data available	
p)	Auto-ignition temperature	No data available	
q)	Decomposition temperature	No data available	
r)	Viscosity	No data available	
s)	Explosive properties	No data available	
t)	Oxidizing properties	No data available	
Other safety information			

No data available

Aldrich - 31284

9.2

Page 5 of 8



## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No data available
- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5 Incompatible materials** Strong acids, Strong oxidizing agents, Acid chlorides, Halogens
- **10.6 Hazardous decomposition products** Other decomposition products - No data available Hazardous decomposition products formed under fire conditions. - Copper oxides In the event of fire: see section 5

## **SECTION 11: Toxicological information**

## **11.1 Information on toxicological effects**

## Acute toxicity

No data available Inhalation: No data available Dermal: No data available LD50 Intraperitoneal - Mouse - 3.5 mg/kg

**Skin corrosion/irritation** No data available

Serious eye damage/eye irritation No data available

**Respiratory or skin sensitisation** No data available

Germ cell mutagenicity No data available

#### Carcinogenicity

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

## **Reproductive toxicity**

No data available No data available

Specific target organ toxicity - single exposure No data available

Aldrich - 31284

Page 6 of 8



Specific target organ toxicity - repeated exposure No data available

## **Aspiration hazard** No data available

Additional Information RTECS: GL5325000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

## SECTION 12: Ecological information

#### **12.1 Toxicity** No data available

## **12.2 Persistence and degradability** The methods for determining biodegradability are not applicable to inorganic substances.

- 12.3 Bioaccumulative potential No data available
- **12.4 Mobility in soil** No data available
- 12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted
- 12.6 Other adverse effects

## SECTION 13: Disposal considerations

## **13.1 Waste treatment methods**

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company.

## **Contaminated packaging**

Dispose of as unused product.

## **SECTION 14: Transport information**

## DOT (US)

Not dangerous goods

# IMDG

Not dangerous goods

## ΙΑΤΑ

Not dangerous goods

Aldrich - 31284

Page 7 of 8



## SECTION 15: Regulatory information

## SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

## SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

## SARA 311/312 Hazards

No SARA Hazards

## **Massachusetts Right To Know Components**

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components	CAS-No.	Revision Date
Copper,	7440-50-8	1993-02-16
Copper,	CAS-No. 7440-50-8	Revision Date 1993-02-16
New Jersey Right To Know Components	CAS-No.	Revision Date
Copper,	7440-50-8	1993-02-16

## **California Prop. 65 Components**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

## **SECTION 16: Other information**

## **Further information**

Copyright 2018 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.1

Revision Date: 03/12/2019

Print Date: 06/22/2019

Aldrich - 31284

Page 8 of 8



# SAFETY DATA SHEET

Version 6.1 Revision Date 07/17/2018 Print Date 01/21/2019

1. PRODUCT AND COMPANY IDENTIFICATION				
1.1	Product identifiers Product name :	Dibenz[ <l>a,<l>h]anthracene</l></l>		
	Product Number : Brand : Index-No. :	48574 Supelco 601-041-00-2		
	CAS-No. :	53-70-3		
1.2	Relevant identified uses of the substance or mixture and uses advised against			
	Identified uses :	Laboratory chemicals, Synthesis of substances		
1.3	Details of the supplier of the safety data sheet			
	Company :	Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES		
	Telephone : Fax :	+1 314 771-5765 +1 800 325-5052		
1.4	Emergency telephone number	er		

Emergency Phone # : (314) 776-6555

## 2. HAZARDS IDENTIFICATION

## 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS) Carcinogenicity (Category 1B), H350

Acute aquatic toxicity (Category 1), H400

Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word
Hazard statement(s)
H410

Danger

May cause cancer. Very toxic to aquatic life with long lasting effects.

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid release to the environment.
Wear protective gloves/ protective clothing/ eye protection/ face protection.
IF exposed or concerned: Get medical advice/ attention.
Collect spillage.
Store locked up.
Dispose of contents/ container to an approved waste disposal plant.

## 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

## **3. COMPOSITION/INFORMATION ON INGREDIENTS**

## 3.1 Substances

Synonyms	:	1,2:5,6-Dibenzanthracene
Formula Molecular weight CAS-No. EC-No.	:	C <sb>22H<sb>14278.35 g/mol 53-70-3 200-181-8</sb></sb>
Index-No.	:	601-041-00-2

#### Hazardous components

Component	Classification	Concentration
Dibenz[a,h]anthracene		
	Carc. 1B; Aquatic Acute 1; Aquatic Chronic 1; H350, H410	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

## 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

## **4.3 Indication of any immediate medical attention and special treatment needed** No data available

## **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture Carbon oxides

## **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information No data available

## 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

## 6.4 Reference to other sections

For disposal see section 13.

## 7. HANDLING AND STORAGE

## 7.1 Precautions for safe handling

Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Store at room temperature. Storage class (TRGS 510): 6.1D: Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

### Personal protective equipment

#### Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

## **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Impervious clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: solid	
b)	Odour	No data available	
c)	Odour Threshold	No data available	
d)	рН	No data available	
e)	Melting point/freezing point	Melting point/range: 262 - 265 °C (504 - 509 °F) - lit.	
f)	Initial boiling point and boiling range	524 °C (975 °F) - lit.	
g)	Flash point	No data available	
h)	Evaporation rate	No data available	
i)	Flammability (solid, gas)	No data available	
j)	Upper/lower flammability or explosive limits	No data available	
k)	Vapour pressure	No data available	
I)	Vapour density	No data available	
m)	Relative density	No data available	

	n)	Water solubility	No data available
	o)	Partition coefficient: n- octanol/water	No data available
	p)	Auto-ignition temperature	No data available
	q)	Decomposition temperature	No data available
	r)	Viscosity	No data available
	s)	Explosive properties	No data available
	t)	Oxidizing properties	No data available
Other safety information			

#### **10. STABILITY AND REACTIVITY**

10.1 Reactivity No data available

9.2

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5 Incompatible materials** Strong oxidizing agents

# Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available In the event of fire: see section 5

## **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

No data available Inhalation: No data available Dermal: No data available No data available

## Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

## Respiratory or skin sensitisation

No data available

## Germ cell mutagenicity

Laboratory experiments have shown mutagenic effects.

#### Carcinogenicity

This product is or contains a component that has been reported to be probably carcinogenic based on its IARC, OSHA, ACGIH, NTP, or EPA classification. Possible human carcinogen OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

No data available No data available

Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

Additional Information RTECS: HN2625000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Lungs -

## **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

Toxicity to daphnia and Immobilization EC50 - Daphnia magna (Water flea) - 0.496 mg/l - 24 h(Dibenz[a,h]anthracene) invertebrates

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available(Dibenz[a,h]anthracene)

#### 12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

## **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

#### Contaminated packaging

Dispose of as unused product.

## 14. TRANSPORT INFORMATION

# DOT (US) Not dangerous goods IMDG UN number: 3077 Class: 9 Packing group: III EMS-No: F-A, S-F Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Dibenz[a,h]anthracene)

## ΙΑΤΑ

UN number: 3077 Class: 9 Packing group: III Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (Dibenz[a,h]anthracene)

#### **Further information**

EHS-Mark required (ADR 2.2.9.1.10, IMDG code 2.10.3) for single packagings and combination packagings containing inner packagings with Dangerous Goods > 5L for liquids or > 5kg for solids.

## **15. REGULATORY INFORMATION**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

## SARA 311/312 Hazards

Chronic Health Hazard

Massachusetts Right To Know Components		
	CAS-No.	Revision Date
Dibenz[a,h]anthracene	53-70-3	
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Dibenz[a,h]anthracene	53-70-3	
	CAS-No	Revision Date
Dibenz[a,h]anthracene	53-70-3	
New Jersey Right To Know Components		
	CAS-No.	Revision Date
Dibenz[a,h]anthracene	53-70-3	
California Prop. 65 Components		
WARNING! This product contains a chemical known to the	CAS-No.	Revision Date
State of California to cause cancer. Dibenz[a,h]anthracene	53-70-3	

## **16. OTHER INFORMATION**

## Full text of H-Statements referred to under sections 2 and 3.

H350	May cause cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

## **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956 Version: 6.1

Revision Date: 07/17/2018

Print Date: 01/21/2019

# SIGMA-ALDRICH

## SAFETY DATA SHEET

Version 5.11 Revision Date 05/07/2018 Print Date 07/18/2019

1. F	PRODUCT AND COMPANY	IDENT	IFICATION
1.1	Product identifiers Product name	:	Dichlorodifluoromethane solution
	Product Number Brand	:	40346 Supelco
1.2	Relevant identified uses	of the s	substance or mixture and uses advised against
	Identified uses	:	Laboratory chemicals, Synthesis of substances
1.3	Details of the supplier of	the sa	fety data sheet
	Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
	Telephone Fax	:	+1 800-325-5832 +1 800-325-5052
1.4	Emergency telephone nu	mber	
	Emergency Phone #	:	+1-703-527-3887 (CHEMTREC)
2 L		J	

## 2. HAZARDS IDENTIFICATION

## 2.1 Classification of the substance or mixture

**GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)** Flammable liquids (Category 2), H225 Acute toxicity, Oral (Category 3), H301 Acute toxicity, Inhalation (Category 3), H331 Acute toxicity, Dermal (Category 3), H311 Specific target organ toxicity - single exposure (Category 1), H370

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)	
nazalu statement(s)	
H225	Highly flammable liquid and vapour.
H301 + H311 + H331	Toxic if swallowed, in contact with skin or if inhaled.
H370	Causes damage to organs.
Precautionary statement(s)	
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ eye protection/ face protection.
P301 + P310 + P330	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P311	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician.
P307 + P311	IF exposed: Call a POISON CENTER or doctor/ physician.
P363	Wash contaminated clothing before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

## 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

#### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2 Mixtures

Formula	: CCl <sub>2</sub> F <sub>2</sub>
Molecular weight	: 120.91 g/mol

#### Hazardous components

Component		Classification	Concentration
Methanol			
CAS-No.	67-56-1	Flam. Liq. 2; Acute Tox. 3;	90 - 100 %
EC-No.	200-659-6	STOT SE 1; H225, H301 +	
Index-No.	603-001-00-X	H311 + H331, H370	
Registration number	01-2119433307-44-XXXX		

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **4. FIRST AID MEASURES**

#### 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

## 4.3 Indication of any immediate medical attention and special treatment needed

No data available

## **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

## Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special hazards arising from the substance or mixture 5.2 No data available

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 **Further information**

Use water spray to cool unopened containers.

## 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

#### 6.2 **Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### 6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

#### 6.4 **Reference to other sections**

For disposal see section 13.

## 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment.Keep away from sources of ignition - No smoking.Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage temperature 2 - 8 °C Storage class (TRGS 510): 3: Flammable liquids

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 **Control parameters**

#### Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis	
Methanol	67-56-1	TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)	
	Remarks	Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section)			
Danger of cutaneous absorption					
---	----------------------	---	--		
STEL	250 ppm	USA. ACGIH Threshold Limit Values (TLV)			
Headache Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section)					
Danger of cu	taneous absorptio				
IWA	200 ppm 260 mg/m3	USA. NIOSH Recommended Exposure Limits			
Potential for	dermal absorption				
ST	250 ppm 325 mg/m3	USA. NIOSH Recommended Exposure Limits			
Potential for dermal absorption					
TWA	200 ppm 260 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants			
The value in	mg/m3 is approxin	nate.			
С	1,000 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)			
Skin					
PEL	200 ppm 260 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)			
 Skin					
STEL	250 ppm 325 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)			
Skin					

#### **Biological occupational exposure limits**

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
	-	Methanol	15 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (As soon as possible after exposure ceases)			

#### 8.2 Exposure controls

#### Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

#### Personal protective equipment

#### **Eye/face protection**

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 480 min Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact

Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 30 min Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid Colour: colourless
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	-98 °C (-144 °F)
f)	Initial boiling point and boiling range	64 - 65 °C (147 - 149 °F) at 1,013 hPa (760 mmHg)
g)	Flash point	11 °C (52 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 36 %(V) Lower explosion limit: 6 %(V)
k)	Vapour pressure	130.23 hPa (97.68 mmHg) at 20 °C (68 °F) 547 hPa (410 mmHg) at 50 °C (122 °F)
I)	Vapour density	0.791.1
m)	Relative density	0.791 g/cm3
n)	Water solubility	completely miscible
o)	Partition coefficient: n- octanol/water	No data available
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available

	r)	Viscosity	No data available		
	s)	Explosive properties	No data available		
	t)	Oxidizing properties	No data available		
9.2	Othe	er safety information			
		Relative vapour density	0.79 1.1		
10.	STAB	ILITY AND REACTIVITY			
10.1	<b>Read</b> No d	<b>ctivity</b> ata available			
10.2	.2 Chemical stability Stable under recommended storage conditions.				
10.3	1.3 Possibility of hazardous reactions Vapours may form explosive mixture with air.				
10.4	<b>Cond</b> Heat	<b>ditions to avoid</b> , flames and sparks.			
10.5	<b>Inco</b> acids Magr	<b>mpatible materials</b> s, Acid chlorides, Acid anhy nesium, Zinc	drides, Oxidizing agents, Alkali metals, Potassium, Sodium/sodium oxides, Aluminum,		
10.6	<ul> <li>0.6 Hazardous decomposition products         Hazardous decomposition products formed under fire conditions Carbon oxides, Hydrogen chloride gas, Phosgene gas, Hydrogen fluoride         Other decomposition products - No data available         Hazardous decomposition products formed under fire conditions Carbon oxides         In the event of fire: see section 5     </li> </ul>				
11.	τοχιά	COLOGICAL INFORMATIO	N		

#### 11.1 Information on toxicological effects

## Acute toxicity

No data available

Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation No data available

Serious eye damage/eye irritation No data available

**Respiratory or skin sensitisation** No data available

#### Germ cell mutagenicity

#### No data available

#### Carcinogenicity

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's

#### list of regulated carcinogens.

**Reproductive toxicity** No data available No data available

Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

Additional Information

**RTECS: Not available** 

Methyl alcohol may be fatal or cause blindness if swallowed., Cannot be made non-poisonous., Effects due to ingestion may include:, Nausea, Headache, Vomiting, Gastrointestinal disturbance, Dizziness, Weakness, Confusion., Drowsiness, Unconsciousness, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence Heart - (Dichlorodifluoromethane)

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

No data available

- 12.2 Persistence and degradability No data available
- 12.3 Bioaccumulative potential No data available
- Mobility in soil 12.4 No data available

Results of PBT and vPvB assessment 12.5 PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

#### **Contaminated packaging**

Dispose of as unused product.

#### **14. TRANSPORT INFORMATION**

#### DOT (US)

UN number: 1230 Class: 3 Proper shipping name: Methanol, solution Reportable Quantity (RQ): Poison Inhalation Hazard: No

## Packing group: II

IMDG

UN number: 1230 Class: 3 (6.1) Packing group: II Proper shipping name: METHANOL, SOLUTION

EMS-No: F-E, S-D

REGULATORY INFORMATION		
SARA 302 Components No chemicals in this material are subject to the reporting requirement	nts of SARA Title III, s	Section 302.
SARA 313 Components The following components are subject to reporting levels established	d by SARA Title III, S	ection 313:
Methanol	67-56-1	2007-07-01
SARA 311/312 Hazards Fire Hazard, Chronic Health Hazard		
Massachusetts Right To Know Components		
Methanol	CAS-No. 67-56-1	Revision Date 2007-07-01
Pennsylvania Right To Know Components		
Methanol Dichlorodifluoromethane	CAS-No. 67-56-1 75-71-8	Revision Date 2007-07-01 2015-11-23
Methanol Dichlorodifluoromethane	CAS-No. 67-56-1 75-71-8	Revision Date 2007-07-01 2015-11-23

Packing group: II

# New Jersey Right To Know Components CAS-No. Revision Date Methanol 67-56-1 2007-07-01 California Prop. 65 Components Kevision Date 2007-07-01 WARNING: This product contains a chemical known to the CAS-No. Revision Date State of California to cause birth defects or other reproductive 67-56-1 2012-03-16 harm. Methanol Methanol Kethanol

#### **16. OTHER INFORMATION**

ΙΑΤΑ

15.

UN number: 1230

Class: 3 (6.1)

Proper shipping name: Methanol, solution

#### Full text of H-Statements referred to under sections 2 and 3.

Acute Tox.	Acute toxicity
Flam. Liq.	Flammable liquids
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H301 + H311 +	Toxic if swallowed, in contact with skin or if inhaled.
H331	
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.
STOT SE	Specific target organ toxicity - single exposure

#### **HMIS Rating**

Health hazard:	2
Chronic Health Hazard:	*
Flammability:	3
Physical Hazard	0

#### NFPA Rating

Health hazard:	2
Fire Hazard:	3
Reactivity Hazard:	0

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.11

Revision Date: 05/07/2018

Print Date: 07/18/2019

sigma-aldrich.com

SAFETY DATA SHEET

Version 6.0 Revision Date 03/14/2018 Print Date 07/18/2019

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

1.1	Product identifiers Product name	:	Dieldrin
	Product Number Brand Index-No.	:	33491 Sigma-Aldrich 602-049-00-9
	CAS-No.	:	60-57-1

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES
Telephone	:	+1 314 771-5765
Fax	:	+1 800 325-5052
	_	

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS) Acute toxicity, Oral (Category 2), H300

Acute toxicity, Dermal (Category 1), H310

Carcinogenicity (Category 2), H351

Specific target organ toxicity - repeated exposure, Oral (Category 1), H372

Acute aquatic toxicity (Category 1), H400

Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word	Danger
Hazard statement(s) H300 + H310 H351 H372	Fatal if swallowed or in contact with skin Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure if swallowed.
H410	Very toxic to aquatic life with long lasting effects.
Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P262	Do not get in eyes, on skin, or on clothing.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P310 + P330	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth.
P302 + P350 + P310	IF ON SKIN: Gently wash with plenty of soap and water. Immediately call a POISON CENTER or doctor/ physician.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

#### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances Synonyms : 1,2,3,4,10,10-Hexachloro-1,4,4a,5,6,7,8,8a-octahydro-6,7-epoxy-1,4:5,8dimethanonaphthalene

Formula	:	C <sub>12</sub> H <sub>8</sub> Cl <sub>6</sub> O
Molecular weight	:	380.91 g/mol
CAS-No.	:	60-57-1
EC-No.	:	200-484-5
Index-No.	:	602-049-00-9

#### Hazardous components

Component	Classification Concentration		
Dieldrin			
	Acute Tox. 2; Acute Tox. 1; Carc. 2; STOT RE 1; Aquatic Acute 1; Aquatic Chronic 1; H300 + H310, H351, H372, H410	<= 100 %	

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

- **4.2** Most important symptoms and effects, both acute and delayed The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
- **4.3 Indication of any immediate medical attention and special treatment needed** No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture Carbon oxides, Hydrogen chloride gas

#### **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information No data available

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Storage class (TRGS 510): 6.1B: Non-combustible, acute toxic Cat. 1 and 2 / very toxic hazardous materials

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis
			parameters	
Dieldrin	60-57-1	TWA	0.100000	USA. ACGIH Threshold Limit Values
			mg/m3	(TLV)
	Remarks	Central Nervous System impairment		rment
		Liver damag	e	
		Reproductive	e effects	
		Confirmed a	nimal carcinogen v	vith unknown relevance to humans
		Danger of cu	utaneous absorptio	n
		TWA	0.250000	USA. NIOSH Recommended
			mg/m3	Exposure Limits
		Potential Oc	cupational Carcino	gen
		See Append	ix A	-
		Potential for	dermal absorption	
		TWA	0.250000	USA. Occupational Exposure Limits
			mg/m3	(OSHA) - Table Z-1 Limits for Air
				Contaminants
		Skin designation		
		TWA	0.1 mg/m3	USA. ACGIH Threshold Limit Values
				(TLV)
		Central Nervous System impairment Liver damage		rment
		Reproductive	e effects	
		Confirmed animal carcinogen with unknown relevance to human		vith unknown relevance to humans
		Danger of cu	taneous absorptio	n
		TWA	0.25 mg/m3	USA. NIOSH Recommended
				Exposure Limits
		Potential Oc	cupational Carcino	gen
		See Append	ix A	
		Potential for	dermal absorption	
		TWA	0.25 mg/m3	USA. Occupational Exposure Limits
				(OSHA) - Table Z-1 Limits for Air
				Contaminants
		Skin designation		
		TWA	0.25 mg/m3	USA. OSHA - TABLE Z-1 Limits for
				Air Contaminants - 1910.1000
		Skin notation		
		PEL	0.25 mg/m3	California permissible exposure
				limits for chemical contaminants
				(Title 8, Article 107)
		Skin		

#### 8.2 Exposure controls

#### Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. **Personal protective equipment** 

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

#### Full contact Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: solid
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 143 - 144 °C (289 - 291 °F) - lit.
f)	Initial boiling point and boiling range	No data available
g)	Flash point	No data available
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	No data available
I)	Vapour density	No data available
m)	Relative density	No data available
n)	Water solubility	No data available
o)	Partition coefficient: n- octanol/water	No data available
p)	Auto-ignition temperature	No data available

q) Decomposition No data available temperature

No data available

- r) Viscosity No data available
- s) Explosive properties
- t) Oxidizing properties No data available
- 9.2 Other safety information No data available

#### **10. STABILITY AND REACTIVITY**

- 10.1 Reactivity No data available
- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5 Incompatible materials** Strong oxidizing agents

#### 10.6 Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Carbon oxides, Hydrogen chloride gas Other decomposition products - No data available In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - 38.3 mg/kg Inhalation: No data available Dermal: No data available No data available

#### Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available Respiratory or skin sensitisation

No data available

Germ cell mutagenicity No data available

#### Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

Limited evidence of carcinogenicity in animal studies

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### **Reproductive toxicity**

No data available No data available

#### Specific target organ toxicity - single exposure

No data available

#### Specific target organ toxicity - repeated exposure

Ingestion - Causes damage to organs through prolonged or repeated exposure.

#### Aspiration hazard

No data available

#### **Additional Information**

RTECS: IO1750000

Discomfort, Headache, Nausea, Vomiting, Dizziness, Tremors, tonic convulsions, clonic spasms, Coma., respiratory failure, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Blood - Irregularities - Based on Human Evidence Blood - Irregularities - Based on Human Evidence

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

Toxicity to fish mortality LC50 - Carassius auratus (goldfish) - 1.6 µg/l - 96.0 h(Dieldrin)

Toxicity to daphnia and Immobilization EC50 - Daphnia magna (Water flea) - 79.5 µg/l - 48 h(Dieldrin) other aquatic invertebrates

#### 12.2 Persistence and degradability

No data available

#### **12.3 Bioaccumulative potential** No data available

## **12.4 Mobility in soil**

No data available(Dieldrin)

#### 12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

#### Contaminated packaging

Dispose of as unused product.

#### 14. TRANSPORT INFORMATION

#### DOT (US)

UN number: 2811 Class: 6.1 Packing group: I Proper shipping name: Toxic solids, organic, n.o.s. (Dieldrin) Reportable Quantity (RQ) : 1 lbs Marine pollutant: no no Poison Inhalation Hazard: No

#### IMDG

UN number: 2811 Class: 6.1 Packing group: I EMS-No: F-A, S-A Proper shipping name: TOXIC SOLID, ORGANIC, N.O.S. (Dieldrin) Marine pollutant : yes

#### ΙΑΤΑ

UN number: 2811 Class: 6.1 Packing group: I Proper shipping name: Toxic solid, organic, n.o.s. (Dieldrin) IATA Passenger: Not permitted for transport A5

#### **15. REGULATORY INFORMATION**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### **SARA 313 Components**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

#### Massachusetts Right To Know Components

5	CAS-No.	Revision Date
Dieldrin	60-57-1	1993-04-24
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Dieldrin	60-57-1	1993-04-24
New Jersey Right To Know Components		
	CAS-No.	Revision Date
Dieldrin	60-57-1	1993-04-24
California Prop. 65 Components		
WARNING! This product contains a chemical known to the	CAS-No.	Revision Date
State of California to cause cancer.	60-57-1	2007-09-28
Dieidiin		

#### **16. OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

H300	Fatal if swallowed.
H300 + H310	Fatal if swallowed or in contact with skin
H310	Fatal in contact with skin.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure if swallowed.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

#### **HMIS** Rating

Health hazard:	4
Chronic Health Hazard:	*
Flammability:	0
Physical Hazard	0

#### **NFPA** Rating

Health hazard:	4
Fire Hazard:	0
Reactivity Hazard:	0

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956 Version: 6.0

Revision Date: 03/14/2018

Print Date: 07/18/2019

## Chemical Safety Data Sheet MSDS / SDS

## Ethanol

Revision Date:2023-09-02 Revision Number:1

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **Product identifier**

Product name	: Ethanol
CBnumber	: CB2362508
CAS	: 64-17-5
EINECS Number	: 200-578-6
Synonyms	: ethanol,Ethyl alcohol
Relevant identified uses of the su	ubstance or mixture and uses advised against
Relevant identified uses	: For R&D use only. Not for medicinal, household or other use.
Uses advised against	: none
Company Identification	
Company	: Chemicalbook
Address	: Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing

Telephone : 400-158-6606

## SECTION 2: Hazards identification

#### GHS Label elements, including precautionary statements

Symbol(GHS)

Signal word

Danger

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continuerinsing.

P311 Call a POISON CENTER or doctor/physician.

P337+P313 IF eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use ... for extinction.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

#### Hazard statements

H225 Highly Flammable liquid and vapour H226 Flammable liquid and vapour

- H302 Harmful if swallowed
- H313 May be harmful in contact with skin
- H319 Causes serious eye irritation
- H333 May be harmful if inhaled
- H370 Causes damage to organs
- H371 May cause damage to organs
- H402 Harmful to aquatic life
- H412 Harmful to aquatic life with long lasting effects

## SECTION 3: Composition/information on ingredients

#### Substance

Product name	: Ethanol
Synonyms	: ethanol,Ethyl alcohol
CAS	: 64-17-5
EC number	: 200-578-6
MF	: C2H6O
MW	: 46.07

## SECTION 4: First aid measures

#### Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

#### lf inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### Indication of any immediate medical attention and special treatment needed

## **SECTION 5: Firefighting measures**

#### **Extinguishing media**

Suitable extinguishing media

Dry powder Dry sand

Unsuitable extinguishing media

Do NOT use water jet.

#### Special hazards arising from the substance or mixture

Carbon oxides Combustible.

#### Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### **Further information**

Use water spray to cool unopened containers.

#### **NFPA 704**



## SECTION 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

#### **Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

#### **Reference to other sections**

For disposal see section 13.

## SECTION 7: Handling and storage

#### Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

#### Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in cool place.

Hygroscopic.

#### Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## SECTION 8: Exposure controls/personal protection

#### control parameter

#### Hazard composition and occupational exposure limits

Does not contain substances with occupational exposure limits.

#### Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0,3 mm Break through time: 480 min

Material tested:Butoject? (KCL 897 / Aldrich Z677647, Size M)

Splash contact Material: Nitrile rubber

Minimum layer thickness: 0,2 mm Break through time: 38 min

Material tested:Dermatril? P (KCL 743 / Aldrich Z677388, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario. Body Protection

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

**Respiratory protection** 

Where risk assessment shows air-purifying respirators are appropriate use a full- face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### **Exposure limits**

TLV-TWA 1900 mg/m<sup>3</sup> (1000 ppm) (ACGIH).

## SECTION 9: Physical and chemical properties

#### Information on basic physicochemical properties

Appearance	Form: liquid Colour: colourless
Odour	pungent
Odour Threshold	0.52ppm
рН	7,0 at 10 g/l at 20 °C
Melting point/freezing point	Melting point/range: -114 °C
Initial boiling point and boiling range	78 °C
Flash point	13 °C - closed cup
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive	Upper explosion limit: 13,5 %(V) Lower explosion limit: 2,5 %(V)
limits	
Vapour pressure	0,57 hPa at 19,6 °C
Vapour density	1,6
Relative density	0,789 g/mL at 25 °C

Water solubility	1.000 g/l at 20 °C - completely miscible
Partition coefficient: n-octanol/water	log Pow: -0,35 at 24 °C - Bioaccumulation is not expected.
Autoignition temperature	455 °C at 1.013 hPa - DIN 51794
Decomposition temperature	Distillable in an undecomposed state at normal pressure.
Viscosity	No data available
Explosive properties	No data available
Oxidizing properties	No data available
λmax	λ: 240 nm Amax: 0.40
	λ: 250 nm Amax: 0.30
	λ: 260 nm Amax: 0.30
	λ: 270 nm Amax: 0.10
	λ: 340 nm Amax: 0.10

#### Other safety information

Conductivity < 1 µS/cm Surface tension 72,75 mN/m at 20 °C

Relative vapour density

1,6

## SECTION 10: Stability and reactivity

Reactivity

No data available

#### **Chemical stability**

Stable under recommended storage conditions.

#### Possibility of hazardous reactions

Risk of explosion/exothermic reaction with:hydrogen peroxide, perchlorates, perchloric acid, Nitric acid, mercury(II) nitrate, permanganic acid, Nitriles, peroxi compounds, Strong oxidizing agents, nitrosyl compounds, Peroxides, sodium, Potassium, halogen oxides, calcium hypochlorite, nitrogen dioxide, metallic oxides, uranium hexafluoride, iodides, Chlorine, Alkali metals, Alkaline earth metals, alkali oxides, Ethylene oxidesilver, with, Nitric acidsilver compounds, with, Ammoniapotassium permanganate, with, conc. sulfuric acidRisk of ignition or formation of inflammable gases or vapours with:halogen-halogen compounds, chromium(VI) oxide, chromyl chloride, Fluorine, hydrides, Oxides of phosphorus, platinumNitric acid, with, potassium permanganate

#### **Conditions to avoid**

Warming. Heat, flames and sparks.

#### Incompatible materials

rubber, various plastics

#### Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available

In the event of fire: see section 5

## SECTION 11: Toxicological information

#### Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - male and female - 10.470 mg/kg (OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 124,7 mg/l (OECD Test Guideline 403)

#### Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 24 h (OECD Test Guideline 404)

#### Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye irritation. (OECD Test Guideline 405)

#### Respiratory or skin sensitisation

(OECD Test Guideline 406)

Remarks: (in analogy to similar products)

#### Germ cell mutagenicity

Ames test

Salmonella typhimurium Result: negative

In vitro mammalian cell gene mutation test mouse lymphoma cells

Result: negative

OECD Test Guideline 478 Mouse - male

Result: Positive results were obtained in some in vivo tests.

#### Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

#### **Reproductive toxicity**

No data available

#### Specific target organ toxicity - single exposure

No data available

#### Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

#### Additional Information

Repeated dose toxicity - Rat - male - Oral - No observed adverse effect level - 1.730 mg/kg

- Lowest observed adverse effect level - 3.200 mg/kg RTECS: KQ6300000

irritant effects, respiratory paralysis, Dizziness, narcosis, inebriation, euphoria, Nausea, Vomiting

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

#### Toxicity

## SECTION 12: Ecological information

#### Toxicity

#### Toxicity to fish

flow-through test LC50 - Pimephales promelas (fathead minnow) -

15.300 mg/l - 96 h (US-EPA)

#### Toxicity to daphnia and other aquatic invertebrates

static test LC50 - Ceriodaphnia dubia (water flea) - 5.012 mg/l - 48 h

Remarks: (ECHA)

#### Toxicity to algae

static test ErC50 - Chlorella vulgaris (Fresh water algae) - 275 mg/l

- 72 h

(OECD Test Guideline 201)

#### Toxicity to bacteria

static test IC50 - activated sludge - > 1.000 mg/l - 3 h (OECD Test Guideline 209)

#### Persistence and degradability

Biodegradability aerobic - Exposure time 15 d Result: ca.95 % - Readily biodegradable. (OECD Test Guideline 301E) Biochemical Oxygen Demand (BOD) Theoretical oxygen demand 930 - 1.670 mg/g Remarks: (Lit.) 2.100 mg/g Remarks: (Lit.)

#### **Bioaccumulative potential**

Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

#### Mobility in soil

No data available

#### Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### Other adverse effects

Additional ecological information

No data available

## SECTION 13: Disposal considerations

#### Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

#### Incompatibilities

In acidic conditions, ethanol solutions may react vigorously with oxidizing materials. Mixtures with alkali may darken in color owing to a reaction with residual amounts of aldehyde. Organic salts or acacia may be precipitated from aqueous solutions or dispersions. Ethanol solutions are also incompatible with aluminum containers and may interact with some drugs.

#### Waste Disposal

Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

#### **Contaminated packaging**

Dispose of as unused product.

## **SECTION 14: Transport information**

#### **UN number**

ADR/RID: 1170 IMDG: 1170

#### UN proper shipping name

ADR/RID: ETHANOL IMDG: ETHANOL IATA: Ethanol

#### Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3

#### Packaging group

ADR/RID: II IMDG: II IATA: II

#### **Environmental hazards**

ADR/RID: no IMDG Marine pollutant: no IATA: no

#### Special precautions for user

No data available

## SECTION 15: Regulatory information

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Regulations on the Safety Management of Hazardous Chemicals**

China Catalog of Hazardous chemicals 2015:Listed. website: https://www.mem.gov.cn/

#### Measures for Environmental Management of New Chemical Substances

Chinese Chemical Inventory of Existing Chemical Substances (China IECSC):Listed. website: https://www.mee.gov.cn/

EC Inventory:Listed.

European Inventory of Existing Commercial Chemical Substances (EINECS):Listed. website: https://echa.europa.eu/ Korea Existing Chemicals List (KECL):Listed. website: http://ncis.nier.go.kr New Zealand Inventory of Chemicals (NZIoC):Listed. website: https://www.epa.govt.nz/ Philippines Inventory of Chemicals and Chemical Substances (PICCS):Listed. website: https://emb.gov.ph/ United States Toxic Substances Control Act (TSCA) Inventory:Listed. website: https://www.epa.gov/ Vietnam National Chemical Inventory:Listed. website: https://chemicaldata.gov.vn/

## **SECTION 16: Other information**

#### Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road CAS: Chemical Abstracts Service EC50: Effective Concentration 50% IATA: International Air Transportation Association IMDG: International Maritime Dangerous Goods LC50: Lethal Concentration 50% LD50: Lethal Dose 50% RID: Regulation concerning the International Carriage of Dangerous Goods by Rail STEL: Short term exposure limit TWA: Time Weighted Average

#### References

- [1] CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple
- [2] ChemlDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp
- [3] ECHA European Chemicals Agency, website: https://echa.europa.eu/
- [4] eChemPortal The Global Portal to Information on Chemical Substances by OECD, website:

http://www.echemportal.org/echemportal/index?pageID=0&request locale=en

- [5] ERG Emergency Response Guidebook by U.S. Department of Transportation, website: http://www.phmsa.dot.gov/hazmat/library/erg
- [6] Germany GESTIS-database on hazard substance, website: http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp
- [7] HSDB Hazardous Substances Data Bank, website: https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm
- [8] IARC International Agency for Research on Cancer, website: http://www.iarc.fr/
- [9] IPCS The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home
- [10] Sigma-Aldrich, website: https://www.sigmaaldrich.com/

#### **Other Information**

Ethanol consumption during pregnancy may adversely affect the unborn child. Chronic ingestion of ethanol may cause liver cirrhosis and cancer.

#### **Disclaimer:**

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.

# SIGMA-ALDRICH

## SAFETY DATA SHEET

Version 5.12 Revision Date 04/20/2017 Print Date 06/28/2019

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

1.1	Product identifiers Product name	:	Ethylbenzene
	Product Number Brand Index-No.	:	296848 Sigma-Aldrich 601-023-00-4
	CAS-No.	:	100-41-4

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
Telephone Fax	:	+1 800-325-5832 +1 800-325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Acute toxicity, Inhalation (Category 4), H332 Carcinogenicity (Category 2), H351 Specific target organ toxicity - repeated exposure (Category 2), H373 Aspiration hazard (Category 1), H304 Acute aquatic toxicity (Category 2), H401

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)	
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life.
Precautionary statement(s)	

P201

Obtain special instructions before use.

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face
	protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for
	breathing. Call a POISON CENTER/doctor if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P331	Do NOT induce vomiting.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

#### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Formula	:	C <sub>8</sub> H <sub>10</sub>
Molecular weight	:	106.17 g/mol
CAS-No.	:	100-41-4
EC-No.	:	202-849-4
Index-No.	:	601-023-00-4

#### Hazardous components

Component	Classification	Concentration
Ethylbenzene		
	Flam. Liq. 2; Acute Tox. 4; Carc. 2; STOT RE 2; Asp. Tox. 1; Aquatic Acute 2; H225, H304, H332, H351, H373, H401	90 - 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

## **4.3** Indication of any immediate medical attention and special treatment needed No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture No data available

#### **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

Use water spray to cool unopened containers.

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment.Keep away from sources of ignition - No smoking.Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

hygroscopic

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Ethylbenzene	100-41-4	TWA	20.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Cochlear im Kidney dam Upper Resp Substances (see BEI® s Confirmed a STEL	pair age (nephropathy) iratory Tract irritation for which there is a ection) inimal carcinogen v 125.000000 ppm	on a Biological Exposure Index or Indices with unknown relevance to humans USA. ACGIH Threshold Limit Values (TLV)
		Central Nerv Upper Resp Eye irritation Adopted val are propose See Notice of Substances	vous System impai iratory Tract irritation ues or notations er d in the NIC of Intended Change for which there is a	rment on holosed are those for which changes es (NIC) a Biological Exposure Index or Indices
		(see BEI® s Confirmed a	ection) Inimal carcinogen v	with unknown relevance to humans
		TWA	100.000000 ppm 435.000000 mg/m3	USA. NIOSH Recommended Exposure Limits
		ST	125.000000 ppm 545.000000 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	100.000000 ppm 435.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		The value in	mg/m3 is approxim	nate.
		TWA	20 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Cochlear im Kidney dam Upper Resp Substances (see BEI® s	pair age (nephropathy) iratory Tract irritation for which there is a ection)	on a Biological Exposure Index or Indices
		Confirmed a	inimal carcinogen v	with unknown relevance to humans
		TWA	100 ppm 435 mg/m3	USA. NIOSH Recommended Exposure Limits
		ST	125 ppm 545 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	100 ppm 435 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		The value in	n mg/m3 is approxir	nate.

TWA	100 ppm 435 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
STEL	125 ppm 545 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
PEL	5 ppm 22 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
STEL	30 ppm 130 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

#### **Biological occupational exposure limits**

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	0.7g/g creatinine	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift at	end of worky	week	·
		Ethylbenzene		In end-exhaled air	ACGIH - Biological Exposure Indices (BEI)
		Not critical			· · ·
		Sum of mandelic acid and phenyl glyoxylic acid	0.15g/g creatinine	Urine	ACGIH - Biological Exposure Indices (BEI)
		End of shift (As	s soon as po	ssible after exposure	e ceases)

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### **Eye/face protection**

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid Colour: colourless
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: -95 °C (-139 °F) - lit.
f)	Initial boiling point and boiling range	136 °C (277 °F) - lit.
g)	Flash point	15.0 °C (59.0 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 6.7 %(V) Lower explosion limit: 1 %(V)
k)	Vapour pressure	13.3 hPa (10.0 mmHg) at 20.0 °C (68.0 °F)
I)	Vapour density	No data available
m)	Relative density	0.867 g/cm3 at 25 °C (77 °F)
n)	Water solubility	0.2 g/l at 25 °C (77 °F) - slightly soluble
o)	Partition coefficient: n- octanol/water	log Pow: 3.6 at 20 °C (68 °F)
p)	Auto-ignition temperature	432.0 °C (809.6 °F)
q)	Decomposition temperature	No data available
r)	Viscosity	0.773 mm2/s at 20 °C (68 °F) -
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Othe	r safety information	
	Surface tension	71.2 mN/m at 23 °C (73 °F)

#### **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity

9.2

No data available

10.2	Chemical stability Stable under recommended storage conditions.
10.3	Possibility of hazardous reactions Vapours may form explosive mixture with air.
10.4	Conditions to avoid Heat, flames and sparks.
10.5	Incompatible materials Strong oxidizing agents
10.6	Hazardous decomposition products Hazardous decomposition products formed under fire conditions Carbon oxides Other decomposition products - No data available In the event of fire: see section 5
11.	TOXICOLOGICAL INFORMATION
11.1	I Information on toxicological effects
	Acute toxicity LD50 Oral - Rat - male and female - 3,500 mg/kg
	Inhalation: No data available
	LD50 Dermal - Rabbit - 15,433 mg/kg
	No data available
	<b>Skin corrosion/irritation</b> Skin - Rabbit Result: Moderate skin irritation - 24 h
	<b>Serious eye damage/eye irritation</b> Eyes - Rabbit Result: Mild eye irritation
	Respiratory or skin sensitisation No data available
	Germ cell mutagenicity Hamster ovary Result: negative
	Mouse - male and female Result: negative

#### Carcinogenicity

IARC:	2B - Group 2B:	Possibly	carcinogenic to	humans	(Ethylbenzene)	
		,	9		· · · /	

- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### **Reproductive toxicity**

No data available

Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

#### Aspiration hazard

May be fatal if swallowed and enters airways.

#### Additional Information

Repeated dose Rat - male and female - NOAEL : 75 mg/kg - OECD Test Guideline 407 toxicity

RTECS: DA0700000

Central nervous system depression, Nausea, Headache, Vomiting, Ataxia., Tremors

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

Toxicity to fish LC50 - Oncorhynchus mykiss (rainbow trout) - 4.2 mg/l - 96 h

Toxicity to daphnia and static test EC50 - Daphnia magna (Water flea) - 1.8 - 2.4 mg/l - 48 h other aquatic invertebrates

Toxicity to algae static test EC50 - Skeletonema costatum (marine diatom) - 4.9 mg/l - 72 h

#### 12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d Result: 70 - 80 % - Readily biodegradable.

#### 12.3 Bioaccumulative potential

Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

#### Contaminated packaging

Dispose of as unused product.

Proper shipping name: Ethylbenzene

#### **14. TRANSPORT INFORMATION**

#### DOT (US)

UN number: 1175 Proper shipping nam Reportable Quantity Poison Inhalation Ha	Class: 3 e: Ethylbenzene (RQ): 1000 lbs zard: No	Packing group: II		
IMDG UN number: 1175 Proper shipping nam	Class: 3 e: ETHYLBENZENE	Packing group: II	EMS-No: F-E, S-D	
<b>IATA</b> UN number: 1175	Class: 3	Packing group: II		

#### SARA 302 Components No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302. SARA 313 Components The following components are subject to reporting levels established by SARA Title III, Section 313: CAS-No. **Revision Date** 100-41-4 Ethylbenzene 2007-07-01 SARA 311/312 Hazards Fire Hazard, Chronic Health Hazard Massachusetts Right To Know Components CAS-No. **Revision Date** Ethylbenzene 100-41-4 2007-07-01 Pennsylvania Right To Know Components CAS-No. **Revision Date** Ethylbenzene 2007-07-01 100-41-4 CAS-No. **Revision Date** Ethylbenzene 100-41-4 2007-07-01 New Jersey Right To Know Components CAS-No. **Revision Date** Ethylbenzene 100-41-4 2007-07-01 California Prop. 65 Components WARNING! This product contains a chemical known to the CAS-No. **Revision Date**

# 16. OTHER INFORMATION

Ethylbenzene

State of California to cause cancer.

**15. REGULATORY INFORMATION** 

#### Full text of H-Statements referred to under sections 2 and 3.

Acute Tex	Acute toxicity
Acute TOX.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Asp. Tox.	Aspiration hazard
Carc.	Carcinogenicity
Flam. Liq.	Flammable liquids
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H401	Toxic to aquatic life.
HMIS Rating	

100-41-4

2007-09-28

i i i i i i i i i i i i i i i i i i i		
Health hazard:		
Chronic Health Hazard:	*	
Flammability:	3	
Physical Hazard	0	
NFPA Rating		

Health hazard:	2
Fire Hazard:	3
Reactivity Hazard:	0

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.12

Revision Date: 04/20/2017

Print Date: 06/28/2019

# SIGMA-ALDRICH

## SAFETY DATA SHEET

Version 5.12 Revision Date 07/26/2018 Print Date 11/10/2018

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

1.1	Product identifiers Product name	:	Heptane
	Product Number Brand Index-No.	:	246654 Sigma-Aldrich 601-008-00-2
	CAS-No.	:	142-82-5

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
Telephone Fax	:	+1 800-325-5832 +1 800-325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Skin irritation (Category 2), H315 Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336 Aspiration hazard (Category 1), H304 Acute aquatic toxicity (Category 1), H400 Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)	
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H410	Very toxic to aquatic life with long lasting effects.
Precautionary statement(s)	
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
--------------------	---
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ eye protection/ face protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391	Collect spillage.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Formula	:	С <sub>7</sub> Н <sub>16</sub>
Molecular weight	:	100.20 g/mol
CAS-No.	:	142-82-5
EC-No.	:	205-563-8
Index-No.	:	601-008-00-2
Registration number	:	01-2119457603-38-XXXX

#### Hazardous components

Component	Classification	Concentration
Heptane		
	Flam. Liq. 2; Skin Irrit. 2; STOT SE 3; Asp. Tox. 1; Aquatic Acute 1; Aquatic Chronic 1; H225, H304, H315, H336, H410	90 - 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

# **4.3** Indication of any immediate medical attention and special treatment needed No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

**Suitable extinguishing media** Dry powder Dry sand

Unsuitable extinguishing media Do NOT use water jet.

**5.2** Special hazards arising from the substance or mixture Flash back possible over considerable distance.

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray to cool unopened containers.

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment.Keep away from sources of ignition - No smoking.Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

### 7.2 Conditions for safe storage, including any incompatibilities

Store under inert gas. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Storage class (TRGS 510): 3: Flammable liquids

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Heptane	142-82-5	TWA	85 ppm	USA. NIOSH Recommended
			350 mg/m3	Exposure Limits
		С	440 ppm	USA. NIOSH Recommended
			1,800 mg/m3	Exposure Limits
	Remarks	15 minute ce	iling value	
		TWA	500 ppm	USA. Occupational Exposure Limits
			2,000 mg/m3	(OSHA) - Table Z-1 Limits for Air
			_	Contaminants
		The value in	mg/m3 is approxir	nate.
		PEL	400 ppm	California permissible exposure
			1,600 mg/m3	limits for chemical contaminants
			_	(Title 8, Article 107)
		STEL	500 ppm	California permissible exposure
			2,000 mg/m3	limits for chemical contaminants
				(Title 8, Article 107)
		TWA	400 ppm	USA. ACGIH Threshold Limit Values
				(TLV)
		Central Nervous System impairment		
		Upper Respiratory Tract irritation		
		STEL	500 ppm	USA. ACGIH Threshold Limit Values
				(TLV)
		Central Nerv	ous System impair	ment
		Upper Respi	ratory Tract irritatio	n

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### **Eye/face protection**

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 480 min Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.2 mm Break through time: 65 min Material tested:Dermatril® P (KCL 743 / Aldrich Z677388, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an

industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: -91 °C (-132 °F)
f)	Initial boiling point and boiling range	98 °C (208 °F)
g)	Flash point	22 °C (72 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 7 %(V) Lower explosion limit: 1.1 %(V)
k)	Vapour pressure	110.7 hPa (83.0 mmHg) at 37.7 °C (99.9 °F) 53.3 hPa (40.0 mmHg) at 20.0 °C (68.0 °F)
I)	Vapour density	No data available
m)	Relative density	0.684 g/mL at 25 °C (77 °F)
n)	Water solubility	insoluble
o)	Partition coefficient: n- octanol/water	log Pow: > 3.000
p)	Auto-ignition temperature	223.0 °C (433.4 °F)
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Othe	r safety information	

#### Sigma-Aldrich - 246654

No data available

9.2

#### **10. STABILITY AND REACTIVITY**

- 10.1 Reactivity No data available
- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** Vapours may form explosive mixture with air.
- **10.4 Conditions to avoid** Heat, flames and sparks.
- **10.5** Incompatible materials Strong oxidizing agents
- 10.6 Hazardous decomposition products Other decomposition products - No data available Hazardous decomposition products formed under fire conditions. - Carbon oxides In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

# Acute toxicity

No data available

LC50 Inhalation - Rat - 4 h - 103,000 mg/m3

Inhalation: Irritating to respiratory system.

Dermal: No data available

No data available

#### Skin corrosion/irritation No data available

#### Serious eye damage/eye irritation

Eyes - Rabbit Result: No eye irritation (OECD Test Guideline 405)

#### **Respiratory or skin sensitisation** No data available

Germ cell mutagenicity No data available

#### Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

No data available

No data available

#### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

# Specific target organ toxicity - repeated exposure

No data available

#### Aspiration hazard

May be fatal if swallowed and enters airways.

#### Additional Information

RTECS: MI7700000

Prolonged or repeated exposure to skin causes defatting and dermatitis., Central nervous system depression, narcosis, Damage to the lungs.

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

Toxicity to fishLC50 - Carassius auratus (goldfish) - 4 mg/l - 24.0 hLC50 - Tilapia mossambica - 375 mg/l - 96.0 hToxicity to daphnia and<br/>other aquatic<br/>invertebrates

#### 12.2 Persistence and degradability

Ratio BOD/ThBOD 3.5 %

12.3 Bioaccumulative potential Indication of bioaccumulation.

#### 12.4 Mobility in soil

No data available

#### **12.5** Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

Very toxic to aquatic life with long lasting effects. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Do not empty into drains. Avoid release to the environment.

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

#### **Contaminated packaging**

Dispose of as unused product.

#### **14. TRANSPORT INFORMATION**

#### DOT (US)

UN number: 1206 Class: 3 Packing group: II Proper shipping name: Heptanes Reportable Quantity (RQ): Marine pollutant:yes Poison Inhalation Hazard: No

#### IMDG

UN number: 1206 Class: 3

#### ΙΑΤΑ

UN number: 1206 Class: 3 Proper shipping name: Heptanes Packing group: II

#### **15. REGULATORY INFORMATION**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### Massachusetts Right To Know Components

Hentane	CAS-No.	Revision Date
Pennsylvania Right To Know Components	142-02-3	1990-02-10
	CAS-No.	Revision Date
Heptane	142-82-5	1993-02-16
	CAS-No.	Revision Date
Heptane	142-82-5	1993-02-16
New Jersey Right To Know Components		
	CAS-No.	Revision Date
Heptane	142-82-5	1993-02-16

#### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### **16. OTHER INFORMATION**

Full text of H-Statements referred to under sections 2 and 3.

Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Asp. Tox.	Aspiration hazard
Flam. Liq.	Flammable liquids
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Skin Irrit.	Skin irritation

#### Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

**Preparation Information** Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.12

Revision Date: 07/26/2018

Print Date: 11/10/2018

# SIGMA-ALDRICH

# SAFETY DATA SHEET

Version 5.7 Revision Date 06/08/2018 Print Date 11/10/2018

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

1.1	Product identifiers Product name	:	Hexane
	Product Number Brand	:	296090 Sigma-Aldrich
	Index-No.	:	601-037-00-0

CAS-No. : 110-54-3

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
Telephone Fax	:	+1 800-325-5832 +1 800-325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Skin irritation (Category 2), H315 Reproductive toxicity (Category 2), H361 Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336 Specific target organ toxicity - repeated exposure, Oral (Category 2), Nervous system, H373 Aspiration hazard (Category 1), H304 Acute aquatic toxicity (Category 2), H401 Chronic aquatic toxicity (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

Danger

#### 2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word

		<u>(!</u> )	×
•	•	•	

5
Highly flammable liquid and vapour.
May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.
May cause damage to organs (Nervous system) through prolonged or repeated exposure if swallowed.

H411	Toxic to aquatic life with long lasting effects.
Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face
	protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing, Call a POISON CENTER/doctor if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to
	extinguish.
P391	Collect spillage.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

## 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Synonyms	:	n-Hexane
Formula	:	С <sub>6</sub> Н <sub>14</sub>
Molecular weight	:	86.18 g/mol
CAS-No.	:	110-54-3
EC-No.	:	203-777-6
Index-No.	:	601-037-00-0
Registration number	:	01-2119480412-44-XXXX

#### Hazardous components

Component	Classification	Concentration
n-Hexane		
	Flam. Liq. 2; Skin Irrit. 2; Repr. 2; STOT SE 3; STOT RE 2; Asp. Tox. 1; Aquatic Acute 2; Aquatic Chronic 2; H225, H304, H315, H336, H361f, H373, H411	90 - 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### **4.3 Indication of any immediate medical attention and special treatment needed** No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

# 5.2 Special hazards arising from the substance or mixture No data available

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

Use water spray to cool unopened containers.

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Flash back possible over considerable distance.Container explosion may occur under fire conditions.Use explosion-proof equipment.Keep away from sources of ignition - No smoking.Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510): 3: Flammable liquids

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
n-Hexane	110-54-3	TWA	50 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Central Nerv Eye irritation Peripheral ne Substances f (see BEI® se Danger of cu	ous System impair europathy for which there is a ection) taneous absorption	ment Biological Exposure Index or Indices n
		TWA	50 ppm 180 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	500 ppm 1,800 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		The value in	mg/m3 is approxin	nate.
		PEL	50 ppm 180 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		Skin		

#### **Biological occupational exposure limits**

U					
Component	CAS-No.	Parameters	Value	Biological	Basis
				specimen	
	-	2,5- Hexanedione	0.4 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift at	end of worky	veek	

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 480 min Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M) Splash contact Material: Nitrile rubber Minimum layer thickness: 0.2 mm Break through time: 59 min Material tested:Dermatril® P (KCL 743 / Aldrich Z677388, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid Colour: colourless
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	7.0
e)	Melting point/freezing point	Melting point/range: -95 °C (-139 °F)
f)	Initial boiling point and boiling range	69 °C (156 °F)
g)	Flash point	-26.0 °C (-14.8 °F) - closed cup
h)	Evaporation rate	15.8
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 7.7 %(V) Lower explosion limit: 1.2 %(V)
k)	Vapour pressure	341.3 hPa (256.0 mmHg) at 37.7 °C (99.9 °F) 176.0 hPa (132.0 mmHg) at 20.0 °C (68.0 °F)
I)	Vapour density	No data available
m)	Relative density	0.659 g/mL at 25 °C (77 °F)
n)	Water solubility	insoluble
o)	Partition coefficient: n- octanol/water	log Pow: 3.90 - 4.11
p)	Auto-ignition temperature	234.0 °C (453.2 °F)

- q) Decomposition No data available temperature
- r) Viscosity No data available
- s) Explosive properties No data available
- t) Oxidizing properties No data available

# 9.2 Other safety information No data available

#### **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity

No data available

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** Vapours may form explosive mixture with air.

#### 10.4 Conditions to avoid

Exposure to moisture may affect product quality. Heat, flames and sparks.

**10.5** Incompatible materials Oxidizing agents

#### 10.6 Hazardous decomposition products

Other decomposition products - No data available Hazardous decomposition products formed under fire conditions. - Carbon oxides In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - male and female - 16,000 mg/kg (OECD Test Guideline 401)

LC50 Inhalation - Rat - 4 h - 172 mg/l Remarks: (RTECS)

LD50 Dermal - Rabbit - > 2,000 mg/kg Remarks: (ECHA)

Skin corrosion/irritation Serious eye damage/eye irritation Respiratory or skin sensitisation Germ cell mutagenicity

In vitro mammalian cell gene mutation test Mouse lymphoma test Result: Positive results were obtained in some in vitro tests.

Ames test Salmonella typhimurium Result: negative

Result: negative (National Toxicology Program)

#### Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

Suspected of damaging the unborn child.

Suspected of damaging fertility.

Specific target organ toxicity - single exposure May cause drowsiness or dizziness. - Central nervous system

#### Specific target organ toxicity - repeated exposure

Inhalation - May cause damage to organs through prolonged or repeated exposure. - Nervous system

#### Aspiration hazard

Aspiration hazard, Aspiration may cause pulmonary oedema and pneumonitis.

#### **Additional Information**

RTECS: MN9275000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Drowsiness, irritant effects, somnolence

narcosis, Nausea, Tiredness, CNS disorders, paralysis symptoms

Risk of corneal clouding.

It generally applies for aliphatic hydrocarbons with 6 - 18 carbon atoms that they may cause pneumonia, in some cases also pulmonary oedema, upon direct inhalation, i.e. in conditions that can occur only in very special circumstances (nebulizations, spraying, inhalation of aerosols and similar). After absorption of very large quantities: narcosis.

Testes. - Irregularities - Based on Human Evidence

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

Toxicity to fish	LC50 - Pimephales promelas (fathead minnow) - 2.5 mg/l - 96 h Remarks: (ECOTOX Database)
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - 2.1 mg/l - 48 h Remarks: (Lit.)

#### 12.2 Persistence and degradability

#### 12.3 Bioaccumulative potential

#### 12.4 Mobility in soil

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

#### Contaminated packaging

Dispose of as unused product.

#### **14. TRANSPORT INFORMATION**

### DOT (US)

UN number: 1208 Class: 3 Proper shipping name: Hexanes Reportable Quantity (RQ): 5000 lbs Poison Inhalation Hazard: No	Packing group: II	
IMDG UN number: 1208 Class: 3 Proper shipping name: HEXANES Marine pollutant:yes	Packing group: II	EMS-No: F-E, S-D
IATA UN number: 1208 Class: 3 Proper shipping name: Hexanes	Packing group: II	

#### **15. REGULATORY INFORMATION**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
n-Hexane	110-54-3	2007-07-01
Massachusetts Right To Know Components		
	CAS-No.	Revision Date
n-Hexane	110-54-3	2007-07-01
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
n-Hexane	110-54-3	2007-07-01
New Jersey Right To Know Components		
	CAS-No.	Revision Date
n-Hexane	110-54-3	2007-07-01

#### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

### **16. OTHER INFORMATION**

Full text of H-Statements referred to under sections 2 and 3.

2

Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Asp. Tox.	Aspiration hazard
Flam. Liq.	Flammable liquids
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs (/\$/*_2ORG_REP_ORA/\$/) through prolonged or
	repeated exposure if swallowed.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
HMIS Rating	

Health hazard:

Chronic Health Hazard:	*
Flammability:	3
Physical Hazard	0
NFPA Rating	

Health hazard:	2
Fire Hazard:	3
Reactivity Hazard:	0

#### Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.7

Revision Date: 06/08/2018

Print Date: 11/10/2018

# **SIGMA-ALDRICH**

# SAFETY DATA SHEET

Version 5.6 Revision Date 12/11/2017 Print Date 11/10/2018

		Print Date 2	11/10/201		
1. P	RODUCT AND COMPANY I	DENTIFICATION			
1.1	Product identifiers Product name	<sup>:</sup> Indeno[1,2,3- <i>cd</i> ]pyrene			
	Product Number Brand	: 48499 : Supelco			
	CAS-No.	: 193-39-5			
1.2	Relevant identified uses o	f the substance or mixture and uses advised against			
	Identified uses	: Laboratory chemicals, Synthesis of substances			
1.3	Details of the supplier of t	he safety data sheet			
	Company	: Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA			
	Telephone Fax	: +1 800-325-5832 : +1 800-325-5052			
1.4	Emergency telephone number				
	Emergency Phone #	: +1-703-527-3887 (CHEMTREC)			
2. H	AZARDS IDENTIFICATION				
2.1	Classification of the substance or mixture				
	GHS Classification in according Classification (Category 2)	ordance with 29 CFR 1910 (OSHA HCS) 2), H351			
	For the full text of the H-Statements mentioned in this Section, see Section 16.				
2.2	GHS Label elements, including precautionary statements				
	Pictogram				
	Signal word	Warning			
	Hazard statement(s) H351	Suspected of causing cancer.			
	Precautionary statement(s P201 P202	s) Obtain special instructions before use. Do not handle until all safety precautions have been read and understood			
	P281 P308 + P313 P405 P501	Use personal protective equipment as required. IF exposed or concerned: Get medical advice/ attention. Store locked up.			
	F901	Dispose of contents/ container to an approved waste disposal plant.			

### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

#### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Formula	:	C <sub>22</sub> H <sub>12</sub>
Molecular weight	:	276.33 g/mol
CAS-No.	:	193-39-5
EC-No.	:	205-893-2

#### Hazardous components

Component	Classification	Concentration
Indeno[1,2,3-cd]pyrene		
	Carc. 2; H351	90 - 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**4.3 Indication of any immediate medical attention and special treatment needed** No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture No data available

# 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information No data available

No data available

#### 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### 6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Store at room temperature. Storage class (TRGS 510): 13: Non Combustible Solids

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values. Hazardous components without workplace control parameters

#### **Biological occupational exposure limits**

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Indeno[1,2,3- cd]pyrene	193-39-5	1- Hydroxypyren e (1-HP)		Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift at e	end of workv	veek	

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### **Eye/face protection**

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

#### **Body Protection**

Impervious clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the

sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: solid
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	163.6 °C (326.5 °F)
f)	Initial boiling point and boiling range	536.0 °C (996.8 °F)
g)	Flash point	No data available
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	No data available
I)	Vapour density	No data available
m)	Relative density	No data available
n)	Water solubility	No data available
o)	Partition coefficient: n- octanol/water	No data available
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
<b>1</b> 46 e -		

# 9.2 Other safety information No data available

#### **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity No data available

#### **10.2 Chemical stability** Stable under recommended storage conditions.

- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5** Incompatible materials Strong oxidizing agents

#### 10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity No data available

Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation No data available

Serious eye damage/eye irritation No data available

**Respiratory or skin sensitisation** No data available

Germ cell mutagenicity No data available

#### Carcinogenicity

This product is or contains a component that has been reported to be possibly carcinogenic based on its IARC, ACGIH, NTP, or EPA classification.

Limited evidence of carcinogenicity in animal studies

- IARC: 2B Group 2B: Possibly carcinogenic to humans (Indeno[1,2,3-cd]pyrene)
- NTP: RAHC Reasonably anticipated to be a human carcinogen (Indeno[1,2,3-cd]pyrene)
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### **Reproductive toxicity**

No data available

No data available

Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

#### **Additional Information**

RTECS: Not available

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

No data available

#### 12.2 Persistence and degradability

No data available

- **12.3 Bioaccumulative potential** No data available
- **12.4 Mobility in soil** No data available
- 12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

No data available

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

#### **Contaminated packaging**

Dispose of as unused product.

#### **14. TRANSPORT INFORMATION**

#### DOT (US)

Not dangerous goods

#### IMDG

Not dangerous goods

#### ΙΑΤΑ

Not dangerous goods

#### **15. REGULATORY INFORMATION**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Chronic Health Hazard

#### Massachusetts Right To Know Components

	CAS-No.	Revision Date
Indeno[1,2,3-cd]pyrene	193-39-5	1993-04-24
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Indeno[1,2,3-cd]pyrene	193-39-5	1993-04-24
	CAS-No.	Revision Date
Indeno[1,2,3-cd]pyrene	193-39-5	1993-04-24
New Jersey Right To Know Components		
	CAS-No.	Revision Date
Indeno[1,2,3-cd]pyrene	193-39-5	1993-04-24

#### California Prop. 65 Components

CAS-No. 193-39-5

#### **16. OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

Carc.	Carcinogenicity
H351	Suspected of causing cancer.

#### HMIS Rating

Health hazard:	0
Chronic Health Hazard:	*
Flammability:	0
Physical Hazard	0

#### **NFPA** Rating

Health hazard:	1
Fire Hazard:	0
Reactivity Hazard:	0

#### Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.6

Revision Date: 12/11/2017

Print Date: 11/10/2018

# SIGMA-ALDRICH

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Version 6.0 Revision Date 10.11.2016 Print Date 21.01.2019 GENERIC EU MSDS - NO COUNTRY SPECIFIC DATA - NO OEL DATA

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1	Product identifiers Product name	:	Iron Metal Clinical
	Product Number Brand REACH No.	:	NIST937 Sigma-Aldrich A registration number is not available for this substance as the substance or its uses are exempted from registration, the annual tonnage does not require a registration or the registration is envisaged for a later registration deadline.
1.2	Relevant identified uses	s of th	e substance or mixture and uses advised against

Identified uses	:	Laboratory chemicals, Manufacture of substances
-----------------	---	---

#### **1.3** Details of the supplier of the safety data sheet

Company	: Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES
Telephone	: +1 314 771-5765
Fax	: +1 800 325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : (314) 776-6555

#### **SECTION 2: Hazards identification**

- 2.1 Classification of the substance or mixture
- 2.2 Label elements
- 2.3 Other hazards none

#### **SECTION 3: Composition/information on ingredients**

#### SECTION 4: First aid measures

- 4.1 Description of first aid measures No data available
- **4.2** Most important symptoms and effects, both acute and delayed The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
- **4.3** Indication of any immediate medical attention and special treatment needed No data available

#### **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media No data available
- 5.2 Special hazards arising from the substance or mixture No data available
- 5.3 Advice for firefighters No data available
- 5.4 Further information No data available

#### **SECTION 6: Accidental release measures**

- 6.1 **Personal precautions, protective equipment and emergency procedures** For personal protection see section 8.
- 6.2 Environmental precautions No data available
- 6.3 Methods and materials for containment and cleaning up No data available
- 6.4 Reference to other sections For disposal see section 13.

#### **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** For precautions see section 2.2.
- 7.2 Conditions for safe storage, including any incompatibilities No data available
- **7.3** Specific end use(s) Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### **SECTION 8: Exposure controls/personal protection**

- 8.1 Control parameters
- 8.2 Exposure controls No data available

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

- a) Appearance No data available b) Odour No data available c) Odour Threshold No data available d) pН No data available Melting point/freezing No data available e) point Initial boiling point and No data available f) boiling range
- g) Flash point No data available
- h) Evaporation rate No data available
- i) Flammability (solid, gas) No data available

	j)	Upper/lower flammability or explosive limits	No data available			
	k)	Vapour pressure	No data available			
	I)	Vapour density	No data available			
	m)	Relative density	No data available			
	n)	Water solubility	No data available			
	o)	Partition coefficient: n- octanol/water	No data available			
	p)	Auto-ignition temperature	No data available			
	q)	Decomposition temperature	No data available			
	r)	Viscosity	No data available			
	s)	Explosive properties	No data available			
	t)	Oxidizing properties	No data available			
9.2	<b>Other safety information</b> No data available					
SECTION 10: Stability and reactivity						
10.1	10.1 Reactivity No data available					
10.2	<b>Chemical stability</b> No data available					
10.3	Possibility of hazardous reactions No data available					
10.4	<b>Conditions to avoid</b> No data available					
10.5	Incompatible materials No data available					
10.6	Hazardous decomposition products In the event of fire: see section 5					
SECTION 11: Toxicological information						
11.1	Information on toxicological effects					
	Αςι	ite toxicity				

Skin corrosion/irritation

Serious eye damage/eye irritation

Respiratory or skin sensitisation

Germ cell mutagenicity

Carcinogenicity

**Reproductive toxicity** 

Specific target organ toxicity - single exposure

Specific target organ toxicity - repeated exposure

Aspiration hazard

**Additional Information** 

RTECS: Not available

#### **SECTION 12: Ecological information**

- 12.1 Toxicity
- 12.2 Persistence and degradability
- 12.3 Bioaccumulative potential
- 12.4 Mobility in soil
- **12.5 Results of PBT and vPvB assessment** PBT/vPvB assessment not available as chemical safety assessment not required/not conducted
- 12.6 Other adverse effects

#### SECTION 13: Disposal considerations

**13.1 Waste treatment methods** No data available

#### **SECTION 14: Transport information**

14.1	<b>UN numbe</b> ADR/RID:	r -	IMDG: -	IATA: -
14.2	<b>UN proper</b> ADR/RID: IMDG: IATA:	<b>shipping name</b> Not dangerous goods Not dangerous goods Not dangerous goods		
14.3	Transport ADR/RID:	hazard class(es) -	IMDG: -	IATA: -
14.4	Packaging ADR/RID:	group -	IMDG: -	IATA: -
14.5	<b>Environme</b> ADR/RID: r	ental hazards	IMDG Marine pollutant: no	IATA: no
14.6	Special pro	ecautions for user		

No data available

#### **SECTION 15: Regulatory information**

**15.1** Safety, health and environmental regulations/legislation specific for the substance or mixture This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

#### **15.2 Chemical safety assessment** For this product a chemical safety assessment was not carried out

#### **SECTION 16: Other information**

# SIGMA-ALDRICH

# SAFETY DATA SHEET

Version 5.14 Revision Date 10/03/2017 Print Date 11/10/2018

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

1.1	Product identifiers Product name	:	lsopropylbenzene
	Product Number Brand Index-No.	:	442630 Supelco 601-024-00-X
	CAS-No.	:	98-82-8
2	Relevant identified uses	of the	substance or mixture and uses a

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
Telephone Fax	:	+1 800-325-5832 +1 800-325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 3), H226 Carcinogenicity (Category 2), H351 Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335 Aspiration hazard (Category 1), H304 Acute aquatic toxicity (Category 2), H401 Chronic aquatic toxicity (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

Danger

#### 2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word



Hazard statement(s) H226 H304 H335 H351 H411

Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause respiratory irritation. Suspected of causing cancer. Toxic to aquatic life with long lasting effects.

Precautionary statement(s) P201 P202

Obtain special instructions before use. Do not handle until all safety precautions have been read and

	understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P331	Do NOT induce vomiting.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391	Collect spillage.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

May form explosive peroxides.

#### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

### 3.1 Substances

Formula	:	C <sub>9</sub> H <sub>12</sub>
Molecular weight	:	120.2 g/mol
CAS-No.	:	98-82-8
EC-No.	:	202-704-5
Index-No.	:	601-024-00-X

#### Hazardous components

Component	Classification	Concentration
Cumene		
	Flam. Liq. 3; Carc. 2; STOT SE 3; Asp. Tox. 1; Aquatic Acute 2; Aquatic Chronic 2; H226, H304, H335, H351, H411	90 - 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**4.3 Indication of any immediate medical attention and special treatment needed** No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

- 5.2 Special hazards arising from the substance or mixture No data available
- **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

Use water spray to cool unopened containers.

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Store at room temperature.

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Cumene	98-82-8	TWA	50.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Central Nerv Upper Respi Eye irritation Skin irritation	ous System impair ratory Tract irritatio	ment on
		TWA	50.000000 ppm 245.000000 mg/m3	USA. NIOSH Recommended Exposure Limits
		Potential for	dermal absorption	
		TWA	50.000000 ppm 245.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		Skin designa The value in	tion mg/m3 is approxin	nate.
		PEL	50 ppm 245 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		Skin		

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### **Eye/face protection**

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

#### Full contact Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 30 min Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

8	a)	Appearance	Form: liquid, clear Colour: colourless
t	<b>)</b> )	Odour	No data available
C	;)	Odour Threshold	No data available
c	d)	рН	No data available
e	e)	Melting point/freezing point	-95.99 °C (-140.78 °F)
f	)	Initial boiling point and boiling range	152.0 - 153.0 °C (305.6 - 307.4 °F)
ç	g)	Flash point	31.0 °C (87.8 °F) - closed cup
ł	ר)	Evaporation rate	No data available
ij	)	Flammability (solid, gas)	No data available
j	)	Upper/lower flammability or explosive limits	Upper explosion limit: 6.5 %(V) Lower explosion limit: 0.9 %(V)
k	()	Vapour pressure	10.7 hPa (8.0 mmHg) at 20.0 °C (68.0 °F)
Ę	)	Vapour density	No data available
r	n)	Relative density	0.86 g/cm3
r	ר)	Water solubility	0.06 g/l at 25 °C (77 °F) - slightly soluble
C	<b>)</b> )	Partition coefficient: n- octanol/water	log Pow: 3.55 at 23 °C (73 °F)
F	<b>)</b> )	Auto-ignition temperature	425.0 °C (797.0 °F)
C	<b>1</b> )	Decomposition temperature	No data available
r	)	Viscosity	No data available
s	5)	Explosive properties	No data available
t	)	Oxidizing properties	No data available
Ot	her	safety information	
		Surface tension	27.69 mN/m at 25 °C (77 °F)

#### **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity

9.2

No data available

#### 10.2 Chemical stability

Stable under recommended storage conditions. Test for peroxide formation before distillation or evaporation. Test for peroxide formation or discard after 1 year. Stable under recommended storage conditions.

#### 10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air. Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks. 10.5 Incompatible materials

Incompatible materials Strong oxidizing agents

#### **10.6 Hazardous decomposition products**

Other decomposition products - No data available Hazardous decomposition products formed under fire conditions. - Carbon oxides In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - male - 2,260 mg/kg

Inhalation: No data available

Dermal: No data available

NOAEL Feed - Rat - male - > 535.8 mg/kg

#### Skin corrosion/irritation

Skin - Rabbit Result: No skin irritation (OECD Test Guideline 404)

#### Serious eye damage/eye irritation

Eyes - Rabbit Result: No eye irritation (OECD Test Guideline 405)

#### Respiratory or skin sensitisation

- Guinea pig Result: Did not cause sensitisation on laboratory animals. (OECD Test Guideline 406)

#### Germ cell mutagenicity

in vitro assay S. typhimurium Result: negative

Mutagenicity (micronucleus test) Mouse - male and female Result: negative

#### Carcinogenicity

- IARC: 2B Group 2B: Possibly carcinogenic to humans (Cumene)
- NTP: RAHC Reasonably anticipated to be a human carcinogen (Cumene)
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### **Reproductive toxicity**

No data available

No data available

#### Specific target organ toxicity - single exposure

May cause respiratory irritation.

# Specific target organ toxicity - repeated exposure

No data available

#### Aspiration hazard

May be fatal if swallowed and enters airways.

#### **Additional Information**

RTECS: GR8575000

narcosis, Central nervous system depression, Dermatitis, Gastrointestinal disturbance, Damage to the lungs., Liver injury may occur., Kidney injury may occur.

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

Toxicity to fish	LC50 - Oncorhynchus mykiss (rainbow trout) - 4.8 mg/l - 96 h
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia (water flea) - 2.14 mg/l - 48 h (OECD Test Guideline 202)
Toxicity to algae	EC50 - Pseudokirchneriella subcapitata (green algae) - 2.60 mg/l - 72 h

#### 12.2 Persistence and degradability Biodegradability Resul

Result: - According to the results of tests of biodegradability this product is not readily biodegradable.

No data available

# 12.3 Bioaccumulative potential

No data available

# 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

#### Contaminated packaging

Dispose of as unused product.

### **14. TRANSPORT INFORMATION**

#### DOT (US)

UN number: 1918 Class: 3 Proper shipping name: Isopropylbenzene Reportable Quantity (RQ): 5000 lbs Poison Inhalation Hazard: No Packing group: III

#### IMDG

UN number: 1918 Class: 3 Packing group: III Proper shipping name: ISOPROPYLBENZENE Marine pollutant:yes

III EMS-

EMS-No: F-E, S-E

#### **15. REGULATORY INFORMATION**

## SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

The following components are subject to reporting levels establis	shed by SARA Title	III, Section 313:
	CAS-No.	Revision Date
Cumene	98-82-8	2007-07-01
SARA 311/312 Hazards		
The Hazard, Acute Health Hazard, Chronic Health Hazard		
Massachusetts Right To Know Components		
	CAS-No.	Revision Date
Cumene	98-82-8	2007-07-01
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Cumene	98-82-8	2007-07-01
New Jersey Right To Know Components		
	CAS-No.	Revision Date
Cumene	98-82-8	2007-07-01
California Prop. 65 Components		
WARNING! This product contains a chemical known to the	CAS-No.	Revision Date
State of California to cause cancer.	98-82-8	2010-06-11
Cumene		

### **16. OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Asp. Tox.	Aspiration hazard
Carc.	Carcinogenicity
Flam. Liq.	Flammable liquids
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

#### **HMIS Rating**

Health hazard:	2
Chronic Health Hazard:	*
Flammability:	3
Physical Hazard	0

#### **NFPA** Rating

Health hazard:	2
Fire Hazard:	3
Reactivity Hazard:	0

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the
product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.14

Revision Date: 10/03/2017

Print Date: 11/10/2018

# SIGMA-ALDRICH

### SAFETY DATA SHEET

Version 4.11 Revision Date 10/12/2018 Print Date 06/28/2019

1. P	RODUCT AND COMPANY	IDENT	IFICATION		
1.1	Product identifiers Product name	:	Lead		
	Product Number Brand	:	391352 Aldrich		
	CAS-No.	:	7439-92-1		
1.2	Relevant identified uses of the substance or mixture and uses advised against				
	Identified uses	:	Laboratory chemicals, Synthesis of substances		
1.3	Details of the supplier of	f the saf	ety data sheet		
	Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA		

+1 800-325-5832

+1 800-325-5052

#### 1.4 Emergency telephone number

Emergency Phone #	:	+1-703-527-3887 (CHEMTREC)
-------------------	---	----------------------------

:

#### 2. HAZARDS IDENTIFICATION

Telephone

Fax

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 4), H302 Carcinogenicity (Category 2), H351 Reproductive toxicity (Category 2), H361 Specific target organ toxicity - repeated exposure (Category 2), H373 Acute aquatic toxicity (Category 1), H400 Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word



Warning

Hazard statement(s)	
H302	Harmful if swallowed.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.
Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.

P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

#### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Formula	:	Pb
Molecular weight	:	207.20 g/mol
CAS-No.	:	7439-92-1
EC-No.	:	231-100-4

#### Hazardous components

Component	Classification	Concentration
Lead		
	Acute Tox. 4; Carc. 2; STOT RE 1; Aquatic Acute 1; Aquatic Chronic 1; H302, H351, H372, H410	90 - 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### 4.3 Indication of any immediate medical attention and special treatment needed No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

# 5.2 Special hazards arising from the substance or mixture No data available

#### **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Keep in a dry place.

Storage class (TRGS 510): 6.1D: Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis
			parameters	
	Remarks	See 1910.10	25	
Lead	7439-92-1	TWA	0.05 mg/m3	USA. ACGIH Threshold Limit Values
				(TLV)
		Confirmed ar	nimal carcinogen w	ith unknown relevance to humans
		TWA	0.05 mg/m3	USA. ACGIH Threshold Limit Values
				(TLV)
		Central Nerv	ous System impair	ment
		Hematologic	effects	
Peripheral Nervous System impa		pairment		
	Substances for which there is a Biol		Biological Exposure Index or Indices	
		(see BEI® section)		
		Confirmed ar	nimal carcinogen w	ith unknown relevance to humans

	TWA	0.05 mg/m3	USA. NIOSH Recommended Exposure Limits
	See Appendi	x C	

#### **Biological occupational exposure limits**

Component	CAS-No.	Parameters	Value	Biological specimen	Basis	
	-	Lead	200 µg/l	In blood	ACGIH - Biological Exposure Indices (BEI)	
	Remarks	Not critical				

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

- 9.1 Information on basic physical and chemical properties
  - a) Appearance Form: powder
  - b) Odour No data available

	c)	Odour Threshold	No data available
	d)	рН	No data available
	e)	Melting point/freezing point	Melting point/range: 327.4 °C (621.3 °F) - lit.
	f)	Initial boiling point and boiling range	1,740 °C (3,164 °F) - lit.
	g)	Flash point	Not applicable
	h)	Evaporation rate	No data available
	i)	Flammability (solid, gas)	No data available
	j)	Upper/lower flammability or explosive limits	No data available
	k)	Vapour pressure	No data available
	I)	Vapour density	No data available
	m)	Relative density	No data available
	n)	Water solubility	No data available
	o)	Partition coefficient: n- octanol/water	No data available
	p)	Auto-ignition temperature	No data available
	q)	Decomposition temperature	No data available
	r)	Viscosity	No data available
	s)	Explosive properties	No data available
	t)	Oxidizing properties	No data available
C N	<b>)ther</b> lo da	<b>safety information</b> Ita available	

#### **10. STABILITY AND REACTIVITY**

**10.1 Reactivity** No data available

9.2

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5** Incompatible materials Strong acids
- Hazardous decomposition products
   Hazardous decomposition products formed under fire conditions. Lead oxides
   Other decomposition products No data available
   In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

Acute toxicity No data available Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation No data available

Serious eye damage/eye irritation No data available

**Respiratory or skin sensitisation** No data available

#### Germ cell mutagenicity

Rat Cytogenetic analysis

#### Carcinogenicity

Limited evidence of carcinogenicity in animal studies

- IARC: 2B Group 2B: Possibly carcinogenic to humans (Lead)
- NTP: RAHC Reasonably anticipated to be a human carcinogenThe reference note has been added by TD based on the background information of the NTP. (Lead)
- OSHA: OSHA specifically regulated carcinogen (Lead)

#### **Reproductive toxicity**

Reproductive toxicity - Rat - Inhalation Effects on Newborn: Biochemical and metabolic.

Reproductive toxicity - Rat - Oral Effects on Newborn: Behavioral.

Reproductive toxicity - Mouse - Oral Effects on Fertility: Female fertility index (e.g., # females pregnant per females mated ). Effects on Fertility: Preimplantation mortality (e.g., reduction in numbe corpora lutea).

May damage fertility. May damage the unborn child.

Developmental Toxicity - Rat - Inhalation Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus). Specific Developmental Abnormalities: Blood and lymphatic system (including spleen and marrow).

Developmental Toxicity - Rat - Oral Specific Developmental Abnormalities: Blood and lymphatic system (including spleen and marrow). Effects on Newborn: Growth statistics (e.g., reduced weight gain).

Developmental Toxicity - Rat - Oral Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus). Effects on Embryo or Fetus: Fetal death.

Developmental Toxicity - Mouse - Oral Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus). Effects on Embryo or Fetus: Fetal death.

### Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard No data available

Additional Information RTECS: OF7525000

anemia

Stomach - Irregularities - Based on Human Evidence

#### **12. ECOLOGICAL INFORMATION**

12.1 Toxicity

12.2

Toxicity to fish	mortality LOEC - Oncorhynchus mykiss (rainbow trout) - 1.19 mg/l - 96.0 h
	LC50 - Micropterus dolomieui - 2.2 mg/l - 96.0 h
	mortality NOEC - Salvelinus fontinalis - 1.7 mg/l - 10.0 d
Toxicity to daphnia and other aquatic invertebrates	mortality LOEC - Daphnia (water flea) - 0.17 mg/l - 24 h
	mortality NOEC - Daphnia (water flea) - 0.099 mg/l - 24 h
Toxicity to algae	mortality EC50 - Skeletonema costatum - 7.94 mg/l - 10 d
Persistence and degrada No data available	bility

#### 12.3 Bioaccumulative potential Bioaccumulation

Oncorhynchus kisutch - 2 Weeks - 150 μg/l

Bioconcentration factor (BCF): 12

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

#### 13. DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

#### Contaminated packaging

Dispose of as unused product.

#### 14. TRANSPORT INFORMATION

#### DOT (US)

UN number: 3077 Class: 9 Packing group: III Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (Lead) Reportable Quantity (RQ): 10 lbs Poison Inhalation Hazard: No

#### IMDG

UN number: 3077 Class: 9 Packing group: III EMS-No: F-A, S-F Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Lead) Marine pollutant:yes

#### ΙΑΤΑ

UN number: 3077 Class: 9 Packing group: III Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (Lead)

#### **Further information**

EHS-Mark required (ADR 2.2.9.1.10, IMDG code 2.10.3) for single packagings and combination packagings containing inner packagings with Dangerous Goods > 5L for liquids or > 5kg for solids.

15. REGULATORY INFORMATION			
SARA 302 Components No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.			
SARA 313 Components The following components are subject to reporting levels establis	SARA 313 Components The following components are subject to reporting levels established by SARA Title III, Section 313:		
Lead	7439-92-1	2015-11-23	
SARA 311/312 Hazards Acute Health Hazard, Chronic Health Hazard			
Massachusetts Right To Know Components			
Lead	CAS-No. 7439-92-1	Revision Date 2015-11-23	
Pennsylvania Right To Know Components			
Lead	CAS-No. 7439-92-1	Revision Date 2015-11-23	
	CAS-No.	Revision Date	
Lead	7439-92-1	2015-11-23	
New Jersey Right To Know Components			
Lead	CAS-No. 7439-92-1	Revision Date 2015-11-23	
<b>California Prop. 65 Components</b> WARNING! This product contains a chemical known to the State of California to cause cancer. Lead	CAS-No. 7439-92-1	Revision Date 2009-02-01	
WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. Lead	CAS-No. 7439-92-1	Revision Date 2009-02-01	

#### **16. OTHER INFORMATION**

Full text of H-Statements referred to under sections 2 and 3.

Acute toxicity
Acute aquatic toxicity
Chronic aquatic toxicity
Carcinogenicity
Harmful if swallowed.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.
Causes damage to organs through prolonged or repeated exposure.
May cause damage to organs through prolonged or repeated exposure.

#### Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

**Preparation Information** Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 4.11

Revision Date: 10/12/2018

Print Date: 06/28/2019

sigma-aldrich.com

## SAFETY DATA SHEET

Version 6.0 Revision Date 01/31/2017 Print Date 06/28/2019

#### 1. PRODUCT AND COMPANY IDENTIFICATION

1.1	Product identifiers Product name	:	Magnesium	
	Product Number Brand Index-No.	:	200905 Sigma-Aldrich 012-002-00-9	
	CAS-No.	:	7439-95-4	

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

		ST. LOUIS MO 63103 UNITED STATES
Telephone	:	+1 314 771-5765
Fax	:	+1 800 325-5052
Emorgoncy tolonhono	numbo	r

#### 1.4 Emergency telephone number

: +1-703-527-3887 Emergency Phone #

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS) Flammable solids (Category 1), H228 Self-heating substances and mixtures (Category 1), H251 Substances and mixtures, which in contact with water, emit flammable gases (Category 2), H261

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word	Danger
Hazard statement(s) H228 H251 H261	Flammable solid. Self-heating: may catch fire. In contact with water releases flammable gases.
Precautionary statement(s) P210 P223	Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep away from any possible contact with water, because of violent

	reaction and possible flash fire.
P231 + P232	Handle under inert gas. Protect from moisture.
P235 + P410	Keep cool. Protect from sunlight.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P280	Wear protective gloves/ eye protection/ face protection.
P335 + P334	Brush off loose particles from skin. Immerse in cool water/ wrap in wet
D270 · D270	Danuayes.
P370 + P378	extinction.
P402 + P404	Store in a dry place. Store in a closed container.
P407	Maintain air gap between stacks/ pallets.
P413	Store bulk masses greater than .? kg/ .? lbs at temperatures not exceeding .? °C/ .? °F.
P420	Store away from other materials.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS Combustible dust

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances

Formula	:	Mg
Molecular weight	:	24.31 g/mol
CAS-No.	:	7439-95-4
EC-No.	:	231-104-6
Index-No.	:	012-002-00-9

#### Hazardous components

Component	Classification	Concentration
Magnesium (non pyrophoric)		
	Flam. Sol. 1; Self-heat. 1; Water-react. 2; H228, H251, H261	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### **General advice**

Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### **4.3 Indication of any immediate medical attention and special treatment needed** No data available

#### **5. FIREFIGHTING MEASURES**

5.1 Extinguishing media

Suitable extinguishing media Dry powder

- 5.2 Special hazards arising from the substance or mixture Magnesium oxide
- **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.
- 5.4 Further information No data available

#### 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13). Do not flush with water. Keep in suitable, closed containers for disposal. Contain spillage, pick up with an electrically protected vacuum cleaner or by wet-brushing and transfer to a container for disposal according to local regulations (see section 13).

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid formation of dust and aerosols.Further processing of solid materials may result in the formation of combu formation should be taken into consideration before additional processing Provide appropriate exhaust ventilation at places where dust is formed.Keep away from sources of ignition - No smoking.Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Never allow product to get in contact with water during storage.

Store under inert gas. Air and moisture sensitive.

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industria situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use (EN 143) respirator cartridges as a backup to engineering controls. If th full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: Turnings
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 648 °C (1198 °F) - lit.
f)	Initial boiling point and boiling range	1,090 °C (1,994 °F) - lit.
g)	Flash point	()No data available
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	May form combustible dust concentrations in air
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	1 hPa at 621 °C (1150 °F)
I)	Vapour density	No data available
m)	Relative density	1.74 g/mL at 25 °C (77 °F)
n)	Water solubility	No data available

- Partition coefficient: n- No data available octanol/water
- p) Auto-ignition The substance or mixture is classified as self heating with the category 1. temperature
- q) Decomposition No data available temperature
- r) Viscosity No data available
- s) Explosive properties No data available
- t) Oxidizing properties No data available

# 9.2 Other safety information No data available

#### **10. STABILITY AND REACTIVITY**

## 10.1 Reactivity

No data available

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** Reacts violently with water.
- **10.4 Conditions to avoid** Heat, flames and sparks. Exposure to moisture

#### **10.5 Incompatible materials** Acids, Strong oxidizing agents, Acid chlorides, Halogens

# Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Magnesium oxide Other decomposition products - No data available In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

No data availableMagnesium (non pyrophoric) Inhalation: No data available(Magnesium (non pyrophoric)) Dermal: No data available(Magnesium (non pyrophoric)) No data available(Magnesium (non pyrophoric))

#### Skin corrosion/irritation

No data available(Magnesium (non pyrophoric))

Serious eye damage/eye irritation No data available(Magnesium (non pyrophoric))

Respiratory or skin sensitisation No data available(Magnesium (non pyrophoric))

#### Germ cell mutagenicity

No data available(Magnesium (non pyrophoric))

#### Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

- ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### **Reproductive toxicity**

No data available(Magnesium (non pyrophoric))

No data available(Magnesium (non pyrophoric))

**Specific target organ toxicity - single exposure** No data available(Magnesium (non pyrophoric))

Specific target organ toxicity - repeated exposure No data available

#### Aspiration hazard

No data available(Magnesium (non pyrophoric))

#### **Additional Information**

**RTECS: Not available** 

burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, chills, Fever, fatigue, muscle pain, joint pain, rash, Anorexia.(Magnesium (non pyrophoric)) To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.(Magnesium (non pyrophoric))

Liver - Irregularities - Based on Human Evidence Liver - Irregularities - Based on Human Evidence(Magnesium (non pyrophoric))

#### 12. ECOLOGICAL INFORMATION

12.1 Toxicity

No data available

- **12.2 Persistence and degradability** No data available
- 12.3 Bioaccumulative potential No data available
- **12.4 Mobility in soil** No data available(Magnesium (non pyrophoric))
- 12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

No data available

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Contact a licensed professional waste disposal service to dispose of this material. Burn in a chemical incinerator equipped with an afterburner and scrubber b highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

#### **Contaminated packaging**

Dispose of as unused product.

#### **14. TRANSPORT INFORMATION**

<b>DOT (US)</b> UN number: 1869 Proper shipping name Poison Inhalation Ha:	Class: 4.1 e: Magnesium zard: No	Packing group: III		
<b>IMDG</b> UN number: 1869 Proper shipping nam	Class: 4.1 e: MAGNESIUM	Packing group: III	EMS-No: F-G, S-G	
IATA UN number: 1869	Class: 4.1	Packing group: III		

#### **15. REGULATORY INFORMATION**

#### SARA 302 Components

Proper shipping name: Magnesium

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Fire Hazard, Reactivity Hazard, Chronic Health Hazard

#### Massachusetts Right To Know Components

CAS-No.	Revision Date
7439-95-4	1993-04-24
CAS-No.	Revision Date
7439-95-4	1993-04-24
CAS-No.	Revision Date
7439-95-4	1993-04-24
	CAS-No. 7439-95-4 CAS-No. 7439-95-4 CAS-No. 7439-95-4

#### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### **16. OTHER INFORMATION**

Full text of H-Statements referred to under sections 2 and 3.

H228	Flammable solid.
H251	Self-heating: may catch fire.
H261	In contact with water releases flammable gases.

#### **HMIS Rating**

Health hazard:	0
Chronic Health Hazard:	*
Flammability:	3
Physical Hazard	2
NFPA Rating	
NFPA Rating Health hazard:	0
<b>NFPA Rating</b> Health hazard: Fire Hazard:	0 0

#### Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956 Version: 6.0

Revision Date: 01/31/2017

Print Date: 06/28/2019

## **SAFETY DATA SHEET**

Version 6.1 Revision Date 05/28/2017 Print Date 06/28/2019

1. PR	1. PRODUCT AND COMPANY IDENTIFICATION				
1.1 Product identifiers Product name :			Manganese		
	Product Number Brand	:	463728 Aldrich		
	CAS-No.	:	7439-96-5		
1.2 Relevant identified uses of the substance or mixture and uses advised against			e substance or mixture and uses advised against		
	Identified uses	:	Laboratory chemicals, Synthesis of substances		
1.3 Details of the supplier of the safety data sheet			safety data sheet		
	Company	:	Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES		
	Telephone Fax	:	+1 314 771-5765 +1 800 325-5052		

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Substances and mixtures, which in contact with water, emit flammable gases (Category 1), H260 Acute aquatic toxicity (Category 3), H402 Chronic aquatic toxicity (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements



Signal wordDangerHazard statement(s)In contact with water releases flammable gases which may ignite<br/>spontaneously.H412Harmful to aquatic life with long lasting effects.Precautionary statement(s)Feep away from any possible contact with water, because of violent<br/>reaction and possible flash fire.P231 + P232Handle under inert gas. Protect from moisture.

P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P335 + P334	Brush off loose particles from skin. Immerse in cool water/ wrap in wet bandages.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P402 + P404 P501	Store in a dry place. Store in a closed container. Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

#### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Formula	:	Mn
Molecular weight	:	54.94 g/mol
CAS-No.	:	7439-96-5
EC-No.	:	231-105-1

#### Hazardous components

Component	Classification	Concentration
Manganese		
	Water-react. 1; Aquatic Acute 3; Aquatic Chronic 3; H260, H412	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **4. FIRST AID MEASURES**

#### 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### **4.3 Indication of any immediate medical attention and special treatment needed** No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

Suitable extinguishing media Dry powder Carbon dioxide (CO2)

#### Unsuitable extinguishing media Water

# 5.2 Special hazards arising from the substance or mixture Manganese/manganese oxides

#### **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13). Do not flush with water. Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols.

Provide appropriate exhaust ventilation at places where dust is formed.Keep away from sources of ignition - No smoking.

For precautions see section 2.2.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Never allow product to get in contact with water during storage.

Moisture sensitive. Keep in a dry place.

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CÁS-No.	Value	Control parameters	Basis
Manganese	7439-96-5	TWA	0.200000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Central Nerv Adopted valu are proposed See Notice o	ous System impair les or notations en l in the NIC f Intended Change	ment closed are those for which changes es (NIC)
		С	5.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		Ceiling limit i	s to be determined	from breathing-zone air samples.
		С	5 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		Ceiling limit is to be determined from breathing-zone air samples.		

TWA	1.000000	USA. NIOSH Recommended
	mg/m3	Exposure Limits
ST	3.000000	USA. NIOSH Recommended
	mg/m3	Exposure Limits
TWA	1.000000	USA. NIOSH Recommended
	mg/m3	Exposure Limits
ST	3.000000	USA. NIOSH Recommended
-	mg/m3	Exposure Limits
С	5.000000	USA. Occupational Exposure Limits
	mg/m3	(OSHA) - Table Z-1 Limits for Air
	J. J	Contaminants
Ceiling limit	is to be determine	d from breathing-zone air samples.
TWA	1.000000	USA. NIOSH Recommended
	mg/m3	Exposure Limits
ST	3.000000	USA. NIOSH Recommended
	mg/m3	Exposure Limits
TWA	0.200000	USA. ACGIH Threshold Limit Values
	ma/m3	(TLV)
Central Ner	vous System impai	rment
Adopted val	ues or notations er	closed are those for which changes
are propose	d in the NIC	
See Notice of Intended Changes (NIC)		
varies		
TWA	0.100000	USA. ACGIH Threshold Limit Values
	mg/m3	(TLV)
Central Nervous System impairment		
2015 Adoption		
varies		
TWA	0.020000	USA. ACGIH Threshold Limit Values
	mg/m3	(TLV)
Central Ner	vous System impai	rment
2015 Adopti	on	
varies		
TWA	1 mg/m3	USA. NIOSH Recommended
		Exposure Limits
ST	3 mg/m3	USA. NIOSH Recommended
		Exposure Limits
TWA	0.1 mg/m3	USA. ACGIH Threshold Limit Values
		(TLV)
Central Ner	vous System impai	rment
Not classifiable as a human carcinogen		
varies		
TWA	0.02 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
Central Nervous System impairment		
Not classifiable as a human carcinogen		
varies		

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

#### **Body Protection**

Impervious clothing, Flame retardant protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. **Respiratory protection** 

Where risk assessment shows air-purifying respirators are appropriate use (EN 143) respirator cartridges as a backup to engineering controls. If th full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: powder Colour: grey
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 1,244 °C (2,271 °F) - lit.
f)	Initial boiling point and boiling range	1,962 °C (3,564 °F) - lit.
g)	Flash point	()Not applicable
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	No data available
I)	Vapour density	No data available
m)	Relative density	7.3 g/mL at 25 °C (77 °F)
n)	Water solubility	No data available
o)	Partition coefficient: n- octanol/water	No data available
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
<b>Otł</b> No	<b>her safety information</b> data available	

#### **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity

No data available

9.2

#### 10.2 Chemical stability

Stable under recommended storage conditions.

- **10.3 Possibility of hazardous reactions** Reacts violently with water.
- **10.4** Conditions to avoid Exposure to moisture
- **10.5** Incompatible materials acids, Halogens, Bases, Phosphorus, Sulphur oxides, Peroxides
- Hazardous decomposition products
   Hazardous decomposition products formed under fire conditions. Manganese/manganese oxides
   Other decomposition products No data available
   In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - 9,000 mg/kg(Manganese) Inhalation: No data available(Manganese) Dermal: No data available(Manganese) No data available(Manganese)

#### Skin corrosion/irritation

Skin - Rabbit(Manganese) Result: Mild skin irritation - 24 h

Serious eye damage/eye irritation Eyes - Rabbit(Manganese) Result: Mild eye irritation - 24 h

**Respiratory or skin sensitisation** No data available(Manganese)

Germ cell mutagenicity

No data available(Manganese)

#### Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### **Reproductive toxicity**

No data available(Manganese)

May cause reproductive disorders.(Manganese)

#### Specific target organ toxicity - single exposure

No data available(Manganese)

#### Specific target organ toxicity - repeated exposure

No data available

#### Aspiration hazard

No data available(Manganese)

#### **Additional Information**

RTECS: 009275000

Men exposed to manganese dusts showed a decrease in fertility. Chronic man system. Early symptoms include languor, sleepiness and weakness in the le disturbances such as uncontrollable laughter and a spastic gait with tend cases. High incidence of pneumonia has been found in workers exposed to t(Manganese)

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence(Manganese)

#### 12. ECOLOGICAL INFORMATION

#### 12.1 Toxicity

Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 40 mg/l - 48 h(Manganese) other aquatic invertebrates

- **12.2 Persistence and degradability** No data available
- **12.3 Bioaccumulative potential** No data available
- 12.4 Mobility in soil No data available(Manganese)
- **12.5** Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life.

No data available

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber b highly flammable. Offer surplus and nonrecyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

#### Contaminated packaging

Dispose of as unused product.

#### **14. TRANSPORT INFORMATION**

#### DOT (US)

UN number: 3208 Class: 4.3 Packing group: I Proper shipping name: Metallic substance, water-reactive, n.o.s. (Manganese) Poison Inhalation Hazard: No

#### IMDG

UN number: 3208 Class: 4.3 Packing group: I EMS-No: F-G, S-N Proper shipping name: METALLIC SUBSTANCE, WATER-REACTIVE, N.O.S. (Manganese)

#### **15. REGULATORY INFORMATION**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components		
	CAS-No.	Revision Date
Manganese	7439-96-5	2007-07-01
SARA 311/312 Hazards Reactivity Hazard, Chronic Health Hazard		
Massachusetts Right To Know Components		
<b>.</b> .	CAS-No.	Revision Date
Manganese	7439-96-5	2007-07-01
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Manganese	7439-96-5	2007-07-01
New Jersey Right To Know Components		
	CAS-No.	Revision Date
Manganese	7439-96-5	2007-07-01

#### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### **16. OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

H260	In contact with water releases flammable gases which may ignite spontaneously.
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

#### **HMIS Rating**

0 *
3 2
0
0
2
W

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling

or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956 Version: 6.1

Revision Date: 05/28/2017

Print Date: 06/28/2019

# SIGMA-ALDRICH

1.

### SAFETY DATA SHEET

Version 3.15 Revision Date 03/05/2018 Print Date 06/28/2019

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

1	Product identifiers Product name	Mercury	
	Product Number Brand Index-No.	:	215457 Sigma-Aldrich 080-001-00-0
	CAS-No.	:	7439-97-6

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
Telephone Fax	:	+1 800-325-5832 +1 800-325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Inhalation (Category 2), H330 Reproductive toxicity (Category 1B), H360 Specific target organ toxicity - repeated exposure (Category 1), H372 Acute aquatic toxicity (Category 1), H400 Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Danger Hazard statement(s) Fatal if inhaled. H330 H360 May damage fertility or the unborn child. H372 Causes damage to organs through prolonged or repeated exposure. Very toxic to aquatic life with long lasting effects. H410 Precautionary statement(s) Obtain special instructions before use. P201 P202 Do not handle until all safety precautions have been read and understood. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P260

P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P284	Wear respiratory protection.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P391	Collect spillage.
P403 + P233 P405	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

#### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Formula	:	Hg
Molecular weight	:	200.59 g/mol
CAS-No.	:	7439-97-6
EC-No.	:	231-106-7
Index-No.	:	080-001-00-0

#### Hazardous components

Component	Classification	Concentration
Mercury		
	Acute Tox. 2; Repr. 1B; STOT RE 1; Aquatic Acute 1; Aquatic Chronic 1; H330, H360, H372, H410	90 - 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### **4.2 Most important symptoms and effects, both acute and delayed** The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### **4.3 Indication of any immediate medical attention and special treatment needed** No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture No data available

# 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information No data available

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas.

For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal. In some instances, a mercury spill kit may be used. Please consult with your site EHS representative to determine the most appropriate clean up method. Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### Store under inert gas.

Storage class (TRGS 510): 6.1B: Non-combustible, acute toxic Cat. 1 and 2 / very toxic hazardous materials

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis
			parameters	
Mercury	7439-97-6	С	0.1 mg/m3	USA. NIOSH Recommended
-			-	Exposure Limits
	Remarks	Potential for	dermal absorption	
		CEIL	1.0mg/10m3	USA. Occupational Exposure Limits
				(OSHA) - Table Z-2
		TWA	0.05 mg/m3	USA. OSHA - TABLE Z-1 Limits for
				Air Contaminants - 1910.1000
		Skin notation	1	

TWA	0.025 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
Central Nerv	ous System impair	ment
Kidney dama	age	
Substances f	for which there is a	Biological Exposure Index or Indices
(see BEI® se	ection)	
Not classifiat	ole as a human ca	rcinogen
Danger of cu	itaneous absorptio	n
TWA	0.05 mg/m3	USA. NIOSH Recommended
	-	Exposure Limits
Potential for	dermal absorption	

#### 8.2 Exposure controls

#### Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

#### Personal protective equipment

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a) Appearance

Form: liquid Colour: silver, white

	b)	Odour	odourless
	c)	Odour Threshold	No data available
	d)	рН	No data available
	e)	Melting point/freezing point	Melting point/range: -38.87 °C (-37.97 °F) - lit.
	f)	Initial boiling point and boiling range	356.6 °C (673.9 °F) - lit.
	g)	Flash point	Not applicable
	h)	Evaporation rate	No data available
	i)	Flammability (solid, gas)	No data available
	j)	Upper/lower flammability or explosive limits	No data available
	k)	Vapour pressure	< 0.01 hPa (< 0.01 mmHg) at 20 °C (68 °F) 1 hPa (1 mmHg) at 126 °C (259 °F)
	I)	Vapour density	6.93 - (Air = 1.0)
	m)	Relative density	13.55 g/cm3 at 25 °C (77 °F)
	n)	Water solubility	0.00006 g/l at 25 °C (77 °F)
	o)	Partition coefficient: n- octanol/water	No data available
	p)	Auto-ignition temperature	No data available
	q)	Decomposition temperature	No data available
	r)	Viscosity	No data available
	s)	Explosive properties	No data available
	t)	Oxidizing properties	No data available
.2	Othe	r safety information	
		Relative vapour density	6.93 - (Air = 1.0)
10.	STAB	LITY AND REACTIVITY	
0 1	Pose	4i\/i4\/	

#### 10.1 Reactivity No data available

9.2

### 10.2 Chemical stability

Stable under recommended storage conditions.

- 10.3 Possibility of hazardous reactions No data available
- 10.4 Conditions to avoid No data available

#### 10.5 Incompatible materials Strong oxidizing agents, Ammonia, Azides, Nitrates, Chlorates, Copper

## Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Mercury/mercury oxides. Other decomposition products - No data available 10.6 In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

Acute toxicity No data available

LC50 Inhalation - Rat - male - 2 h - < 27 mg/m3

Dermal: No data available

No data available

Skin corrosion/irritation No data available

Serious eye damage/eye irritation No data available

Respiratory or skin sensitisation No data available

Germ cell mutagenicity No data available

#### Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### Reproductive toxicity

Presumed human reproductive toxicant

Specific target organ toxicity - single exposure No data available

#### Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

#### Aspiration hazard No data available

## Additional Information

RTECS: OV4550000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

mortality LC50 - Cyprinus carpio (Carp) - 0.160 mg/l - 96 h

#### **12.2 Persistence and degradability** No data available

#### 12.3 Bioaccumulative potential

Toxicity to fish

Bioaccumulation

Carassius auratus (goldfish) - 1,789 d - 0.25 µg/l

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

#### Contaminated packaging

Dispose of as unused product.

#### **14. TRANSPORT INFORMATION**

#### DOT (US)

UN number: 2809 Class: 8 (6.1) Proper shipping name: A. W. Mercury Reportable Quantity (RQ): 1 lbs Poison Inhalation Hazard: No Packing group: III

#### IMDG

#### ΙΑΤΑ

UN number: 2809 Class: 8 (6.1) Proper shipping name: Mercury Packing group: III

#### **15. REGULATORY INFORMATION**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

#### Massachusetts Right To Know Components

Mercury	CAS-No. 7439-97-6	Revision Date 2015-11-23
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Mercury	7439-97-6	2015-11-23
	CAS-No.	Revision Date
Mercury	7439-97-6	2015-11-23
New Jersey Right To Know Components		
	CAS-No.	Revision Date
Mercury	7439-97-6	2015-11-23

#### California Prop. 65 Components

#### **16. OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

0

Acute Tox.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
H330	Fatal if inhaled.
H360	May damage fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Repr.	Reproductive toxicity

#### **HMIS Rating**

Health hazard:	2
Chronic Health Hazard:	*
Flammability:	0
Physical Hazard	0
NFPA Rating	
Health hazard:	2
Fire Hazard:	0

Health hazard:	
Fire Hazard:	
Reactivity Hazard:	

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety - Americas Region 1-800-521-8956

Version: 3.15

Revision Date: 03/05/2018

Print Date: 06/28/2019

## **SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006

Version 6.1 Revision Date 08.07.2019 Print Date 18.07.2019 GENERIC EU MSDS - NO COUNTRY SPECIFIC DATA - NO OEL DATA

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1	Product identifiers		
	Product name	:	Methylene chloride
	Product Number Brand REACH No. CAS-No.	::	M1550000 Sigma-Aldrich 01-2119480404-41-XXXX 75-09-2
1.2	Relevant identified uses of the substance or mixture and uses advised against		
	Identified uses	:	Laboratory chemicals, Manufacture of substances
1.3	Details of the supplier	of	the safety data sheet
	Company	:	Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES
	Telephone Fax	:	+1 314 771-5765 +1 800 325-5052
1.4	Emergency telephone	nu	mber

Emergency Phone # : +1-703-527-3887

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin irritation (Category 2), H315 Eye irritation (Category 2), H319 Carcinogenicity (Category 2), H351 Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 Label elements

#### Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal word

Warning

Hazard statement(s)	
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Sigma-Aldrich- M1550000

The life science business of Merck operates as MilliporeSigma in the US and Canada

Page 1 of 9
H351	Suspected of causing cancer.
Precautionary statement(s) P201	Obtain special instructions before use.
P302 + P352 P305 + P351 + P338	IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
Supplemental Hazard Statements	none

# 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

# 3.1 Substances

Formula	:	CH2Cl2
Molecular weight	:	84,93 g/mol
CAS-No.	:	75-09-2

Component	Classification	Concentration
Methylene chloride		
	Skin Irrit. 2; Eye Irrit. 2;	<= 100 %
	H319, H351, H336	
	Concentration limits:	
	20 %: STOT SE 3, H336;	

For the full text of the H-Statements mentioned in this Section, see Section 16.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance.

# If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

# In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

# In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Sigma-Aldrich- M1550000

Page 2 of 9

The life science business of Merck operates as MilliporeSigma in the US and Canada



- **4.2 Most important symptoms and effects, both acute and delayed** The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
- **4.3 Indication of any immediate medical attention and special treatment needed** No data available

# SECTION 5: Firefighting measures

# 5.1 Extinguishing media

- Suitable extinguishing media Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- **5.2** Special hazards arising from the substance or mixture Carbon oxides, Hydrogen chloride gas
- **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.
- 5.4 Further information No data available

# **SECTION 6:** Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. For personal protection see section 8.
- **6.2 Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not let product enter drains.
- **6.3 Methods and materials for containment and cleaning up** Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.
- **6.4** Reference to other sections For disposal see section 13.

# SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. For precautions see section 2.2.
- **7.2** Conditions for safe storage, including any incompatibilities Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in cool place.
- 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

Sigma-Aldrich- M1550000

Page 3 of 9





# SECTION 8: Exposure controls/personal protection

# 8.1 Control parameters

# **Components with workplace control parameters**

# 8.2 Exposure controls

# **Appropriate engineering controls**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

# Personal protective equipment

# Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

# **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

# **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a fullface respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

# **Control of environmental exposure**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid Colour: colourless
b)	Odour	ether-like
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point: -95 °C at 1.013 hPa

#### Sigma-Aldrich- M1550000

The life science business of Merck operates as MilliporeSigma in the US and Canada



Page 4 of 9

f)	Initial boiling point and boiling range	40 °C at 1.013 hPa
g)	Flash point	- closed cupdoes not flash
h)	Evaporation rate	0,71
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 22 %(V) Lower explosion limit: 13 %(V)
k)	Vapour pressure	584 hPa at 25 °C
I)	Vapour density	2,93
m)	Relative density	1,33 g/cm3 at 20 °C
n)	Water solubility	13,2 g/l at 25 °C
0)	Partition coefficient: n-octanol/water	log Pow: 1,25 at 20 °C - Bioaccumulation is not expected.
p)	Auto-ignition temperature	605 °C at 1.013 hPa - DIN 51794
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Oth	ner safety informatio	on and a second s
	Relative vapour	2,93

# Relative vapour density

# **SECTION 10: Stability and reactivity**

# **10.1 Reactivity**

9.2

No data available

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5 Incompatible materials** various plastics, Rubber, Light metals, Metals, Mild steel, Strong oxidizing agents

# 10.6 Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Carbon oxides, Hydrogen chloride gas In the event of fire: see section 5

Sigma-Aldrich- M1550000

The life science business of Merck operates as MilliporeSigma in the US and Canada

Page 5 of 9



# **SECTION 11: Toxicological information**

# **11.1** Information on toxicological effects

# **Acute toxicity**

LD50 Oral - Rat - male and female - > 2.000 mg/kg (OECD Test Guideline 401) LC50 Inhalation - Mouse - 4 h - 86 mg/l Remarks: (ECHA) LD50 Dermal - Rat - male and female - > 2.000 mg/kg (OECD Test Guideline 402)

# Skin corrosion/irritation

Skin - Rabbit Result: Irritations - 4 h (OECD Test Guideline 404) Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

# Serious eye damage/eye irritation

Eyes - Rabbit Result: Eye irritation Remarks: (ECHA) Risk of corneal clouding.

# **Respiratory or skin sensitisation**

Local lymph node assay (LLNA) - Mouse Result: negative (OECD Test Guideline 429)

# Germ cell mutagenicity

Mutagenicity (mammal cell test): chromosome aberration. Chinese hamster ovary cells Result: positive Ames test Salmonella typhimurium Result: positive OECD Test Guideline 474 Mouse - male and female - Bone marrow Result: negative

# Carcinogenicity

Limited evidence of carcinogenicity in animal studies Suspected human carcinogens

IARC: 2A - Group 2A: Probably carcinogenic to humans (Methylene chloride)

# **Reproductive toxicity**

No data available

# Specific target organ toxicity - single exposure

Inhalation - May cause drowsiness or dizziness. - Central nervous system Acute oral toxicity - Nausea, Vomiting, Risk of aspiration upon vomiting., Aspiration may cause pulmonary oedema and pneumonitis. Acute inhalation toxicity - Possible damages:, mucosal irritations

# Specific target organ toxicity - repeated exposure

No data available

Sigma-Aldrich- M1550000

Page 6 of 9





# Aspiration hazard

No data available

# **Additional Information**

Repeated dose toxicity - Rat - male and female - Oral - 104 Weeks - No observed adverse effect level - 6 mg/kg

Repeated dose toxicity - Rat - male and female - Inhalation - 104 Weeks RTECS: Not available

Dizziness, Nausea, Vomiting, narcosis, Cough, irritant effects, Unconsciousness, Shortness of breath, respiratory paralysis, somnolence, depressed respiration, CNS disorders, inebriation

Risk of corneal clouding.

The following applies to aliphatic halogenated hydrocarbons in general: sy effect on liver, kidneys.

Dichloromethane is metabolized in the body producing carbon monoxide which increases and sustains carboxyhemoglobin levels in the blood, reducing the oxygen-carrying capacity of the blood.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

# **SECTION 12: Ecological information**

# 12.1 Toxicity

	Toxicity to fish	flow-through test LC50 - Pimephales promelas (fathead minnow) - 193,00 mg/l - 96 h Remarks: (ECHA)
	Toxicity to daphnia and other aquatic invertebrates	static test LC50 - Daphnia magna (Water flea) - 27 mg/l - 48 h (US-EPA)
	Toxicity to bacteria	static test EC50 - activated sludge - 2.590 mg/l - 40 min (OECD Test Guideline 209)
12.2	Persistence and deg Biodegradability	<b>radability</b> aerobic - Exposure time 28 d Result: 68 % - Readily biodegradable. (OECD Test Guideline 301D)
12.3	<b>Bioaccumulative pot</b>	ential
	Bioaccumulation	Cyprinus carpio (Carp) - 6 Weeks - 250 µg/l(Methylene chloride)
		Bioconcentration factor (BCF): 2 - 5,4 (OECD Test Guideline 305)
		Cyprinus carpio (Carp) - 6 Weeks - 25 µg/l(Methylene chloride)
		Bioconcentration factor (BCF): 6 - 40 (OECD Test Guideline 305)

The life science business of Merck operates as MilliporeSigma in the US and Canada



Page 7 of 9

# 12.4 Mobility in soil

No data available

# 12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **12.6 Other adverse effects**

No data available

# SECTION 13: Disposal considerations

# **13.1** Waste treatment methods

# Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

# **Contaminated packaging**

Dispose of as unused product.

SECT	ECTION 14: Transport information			
14.1	UN numb ADR/RID:	<b>er</b> 1593	IMDG: 1593	IATA: 1593
14.2	<b>UN prope</b> ADR/RID: IMDG: IATA:	er shipping name DICHLOROMETHAN DICHLOROMETHAN Dichloromethane	IE IE	
14.3	Transpor ADR/RID:	t hazard class(es) 6.1	IMDG: 6.1	IATA: 6.1
14.4	Packagin ADR/RID:	<b>g group</b> III	IMDG: III	IATA: III
14.5	<b>Environm</b> ADR/RID:	n <b>ental hazards</b> no	IMDG Marine pollutant: no	IATA: no
14.6	<b>Special p</b> No data av	recautions for use	r	

# **SECTION 15: Regulatory information**

# **15.1** Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

:

Authorisations and/or restrictions on use REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles

Sigma-Aldrich- M1550000

The life science business of Merck operates as MilliporeSigma in the US and Canada

Page 8 of 9



(Annex XVII) REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

# 15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out

# **SECTION 16: Other information**

# Full text of H-Statements referred to under sections 2 and 3.

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.

# **Further information**

Copyright 2018 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Sigma-Aldrich- M1550000

Page 9 of 9





: Methylene chloride

sigma-aldrich.com

# **SAFETY DATA SHEET**

Version 6.1 Revision Date 07/17/2018 Print Date 06/22/2019

#### 1. PRODUCT AND COMPANY IDENTIFICATION 1.1 **Product identifiers** Product name <l>m</>-Xylene Product Number : 134902 Brand Aldrich Index-No. 601-022-00-9 CAS-No. ÷ 108-38-3 1.2 Relevant identified uses of the substance or mixture and uses advised against Identified uses : Laboratory chemicals, Synthesis of substances 1.3 Details of the supplier of the safety data sheet Company : Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES

Telephone	:	+1 314 771-5765
Fax	:	+1 800 325-5052

# 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

# 2. HAZARDS IDENTIFICATION

# 2.1 Classification of the substance or mixture

**GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)** Flammable liquids (Category 3), H226

Acute toxicity, Dermal (Category 4), H312

Skin irritation (Category 2), H315

Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

Aspiration hazard (Category 1), H304

Acute aquatic toxicity (Category 3), H402

Chronic aquatic toxicity (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

# 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word	Danger
Hazard statement(s) H226 H304 H312 H315 H319 H335 H412	Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.
Precautionary statement(s)	
P210 P233 P240 P241 P242 P243 P261 P264 P271 P273 P280 P204 + P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/ eye protection/ face protection.
P301 + P310 P303 + P361 + P353	IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331	Do NOT induce vomiting.
$P_{332} + P_{313}$	If skin irritation occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

# 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

# 3.1 Substances

Synonyms	:	1,3-Dimethylbenzene
Formula	:	C <sub>8</sub> H <sub>10</sub>
Molecular weight	:	106.17 g/mol
CAS-No.	:	108-38-3
EC-No.	:	203-576-3
Index-No.	:	601-022-00-9

# Hazardous components

Component	Classification	Concentration
-----------	----------------	---------------

m-Xylene		
	Flam. Liq. 3; Acute Tox. 4;	<= 100 %
	Skin Irrit. 2; Eye Irrit. 2A;	
	STOT SE 3; Asp. Tox. 1;	
	Aquatic Acute 3; Aquatic	
	Chronic 3; H226, H304, H312,	
	H315, H319, H335, H412	

For the full text of the H-Statements mentioned in this Section, see Section 16.

# 4. FIRST AID MEASURES

# 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**4.3** Indication of any immediate medical attention and special treatment needed No data available

# **5. FIREFIGHTING MEASURES**

### 5.1 Extinguishing media

#### Suitable extinguishing media Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Use water spray, alconol-resistant roam, dry chemical of carbon dioxi

5.2 Special hazards arising from the substance or mixture Carbon oxides

### **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.

# 5.4 Further information

Use water spray to cool unopened containers.

# 6. ACCIDENTAL RELEASE MEASURES

# 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

## 6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

For disposal see section 13.

# 7. HANDLING AND STORAGE

# 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

# 7.2 Conditions for safe storage, including any incompatibilities Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Storage class (TRGS 510): 3: Flammable liquids

# 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# 8.1 Control parameters

# Components with workplace control parameters

Component	CAS-No.	Value	Control Basis parameters		
m-Xylene	108-38-3	TWA	100 ppm	USA. NIOSH R	ecommended
			435 mg/m3	Exposure Limits	S
		ST	150 ppm	USA. NIOSH R	ecommended
			655 mg/m3	Exposure Limits	S
		TWA	100 ppm	USA. Occupation	onal Exposure Limits
			435 mg/m3	(OSHA) - Table	Z-1 Limits for Air
				Contaminants	
	Remarks	The value in	mg/m3 is appr	oximate.	
		TWA	100 ppm	USA. ACGIH T	hreshold Limit Values
				(TLV)	
		Central Nerv	ous System im	pairment	
		Upper Respire	atory Tract irri	tation	
		Eye irritation			
		Substances for which there is a Biological Exposure Index or Indices (see BEI® section)			
		Not classifiat	ole as a humar	carcinogen	
		STEL	150 ppm	USA. ACGIH T	hreshold Limit Values
				(TLV)	
		Central Nerv	ous System im	pairment	
		Upper Respir	atory Tract irri	tation	
		Eye irritation			
		Substances for which there is a Biological Exposure Index or India			sure Index or Indices
		(see BEI® section)			
		Not classifiable as a human carcinogen			
Biological occupatio	onal exposure	limits			
Component	CAS-No.	Parameters	Value	Biological	Basis

Component	070-110.	1 arameters	value	Diological	Dasis
				specimen	
m-Xylene	108-38-3	Methylhippuri c acids	1.5g/g creatinine	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (As soon as possible after exposure ceases)			

## 8.2 Exposure controls

## Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

# Personal protective equipment

# Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

# Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 30 min Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

# **Body Protection**

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). **Control of environmental exposure** 

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid Colour: colourless
b)	Odour	No data available
C)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: -48 °C (-54 °F) - lit.
f)	Initial boiling point and boiling range	138 - 139 °C (280 - 282 °F) - lit.
g)	Flash point	25.0 °C (77.0 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower	Upper explosion limit: 7 %(V)

	flammability or explosive limits	Lower explosion limit: 1.1 %(V)
k)	Vapour pressure	8.0 hPa at 20.0 °C (68.0 °F) 21.3 hPa at 37.7 °C(99.9 °F)
I)	Vapour density	No data available
m)	Relative density	0.868 g/cm3 at 25 °C (77 °F)
n)	Water solubility	No data available
o)	Partition coefficient: n- octanol/water	log Pow: 3.2 at 20 °C (68 °F)
p)	Auto-ignition temperature	465.0 °C (869.0 °F) 528.0 °C (982.4 °F)
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Oth	ner safety information	

No data available

# **10. STABILITY AND REACTIVITY**

10.1 Reactivity No data available

9.2

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** Vapours may form explosive mixture with air.
- **10.4 Conditions to avoid** Heat, flames and sparks.
- **10.5** Incompatible materials Strong oxidizing agents

# Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available In the event of fire: see section 5

# **11. TOXICOLOGICAL INFORMATION**

### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - male - 6,602 mg/kg (OECD Test Guideline 401) LC50 Inhalation - Rat - male - 4 h - 6700 ppm (Directive 67/548/EEC, Annex V, B.2.) LD50 Dermal - Rabbit - male - 12,126 mg/kg No data available

# Skin corrosion/irritation

Skin - Rabbit Result: Skin irritation - 24 h

# Serious eye damage/eye irritation

Eves - Rabbit Result: Severe eye irritation - 24 h

#### Respiratory or skin sensitisation

- Mouse Result: Does not cause skin sensitisation. (OECD Test Guideline 429)

# Germ cell mutagenicity

No data available

#### Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

- IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (m-Xylene)
- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

> No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

Overexposure may cause reproductive disorder(s) based on tests with laboratory animals.

#### Specific target organ toxicity - single exposure Inhalation - May cause respiratory irritation.

# Specific target organ toxicity - repeated exposure

No data available

### Aspiration hazard

May be fatal if swallowed and enters airways.

#### **Additional Information**

RTECS: ZE2275000

Liver injury may occur., Kidney injury may occur., Blood disorders, burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, narcosis, Lung irritation, chest pain, pulmonary edema, Central nervous system depression, Dermatitis, Gastrointestinal disturbance

Kidney -

# **12. ECOLOGICAL INFORMATION**

# 12.1 Toxicity

Toxicity to fish	mortality LC50 - Fish - 11.23 mg/l - 96 h(m-Xylene) (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	Remarks: No data available(m-Xylene)
Toxicity to algae	Remarks: No data available(m-Xylene)

#### 12.2 Persistence and degradability No data available

#### 12.3 Bioaccumulative potential

Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

#### 12.4 Mobility in soil

No data available(m-Xylene)

# 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.

No data available

# **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

#### Contaminated packaging

Dispose of as unused product.

# **14. TRANSPORT INFORMATION**

<b>DOT (US)</b> UN number: 1307 Class: 3 Proper shipping name: Xylenes Reportable Quantity (RQ) :	Packing group: III 1000 lbs	
Poison Inhalation Hazard: No		
IMDG UN number: 1307 Class: 3 Proper shipping name: XYLENES	Packing group: III	EMS-No: F-E, S-D
IATA UN number: 1307 Class: 3 Proper shipping name: Xylenes	Packing group: III	

# **15. REGULATORY INFORMATION**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### **SARA 313 Components**

The following components are subject to reporting levels establish	ned by SARA Title III,	Section 313:
	CAS-No.	Revision Date
m-Xylene	108-38-3	2007-07-01
<b>SARA 311/312 Hazards</b> Fire Hazard, Acute Health Hazard		
Massachusetts Right To Know Components		
	CAS-No.	Revision Date
m-Xylene	108-38-3	2007-07-01
Pennsylvania Right To Know Components		

	CAS-No.	Revision Date
m-Xylene	108-38-3	2007-07-01
New Jersey Right To Know Components		
	CAS-No.	Revision Date
m-Xylene	108-38-3	2007-07-01

# California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

# **16. OTHER INFORMATION**

# Full text of H-Statements referred to under sections 2 and 3.

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956 Version: 6.1 Revision Date: 07/17/2018

Print Date: 06/22/2019

# SIGMA-ALDRICH

1.

# SAFETY DATA SHEET

Version 3.15 Revision Date 03/05/2018 Print Date 06/28/2019

# 1. PRODUCT AND COMPANY IDENTIFICATION

1	Product identifiers Product name	:	Mercury
	Product Number Brand Index-No.	:	215457 Sigma-Aldrich 080-001-00-0
	CAS-No.	:	7439-97-6

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
Telephone Fax	:	+1 800-325-5832 +1 800-325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

## 2. HAZARDS IDENTIFICATION

# 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Inhalation (Category 2), H330 Reproductive toxicity (Category 1B), H360 Specific target organ toxicity - repeated exposure (Category 1), H372 Acute aquatic toxicity (Category 1), H400 Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Danger Hazard statement(s) Fatal if inhaled. H330 H360 May damage fertility or the unborn child. H372 Causes damage to organs through prolonged or repeated exposure. Very toxic to aquatic life with long lasting effects. H410 Precautionary statement(s) Obtain special instructions before use. P201 P202 Do not handle until all safety precautions have been read and understood. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P260

P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P284	Wear respiratory protection.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P391	Collect spillage.
P403 + P233 P405	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

# 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

# 3.1 Substances

Formula	:	Hg
Molecular weight	:	200.59 g/mol
CAS-No.	:	7439-97-6
EC-No.	:	231-106-7
Index-No.	:	080-001-00-0

#### Hazardous components

Component	Classification	Concentration
Mercury		
	Acute Tox. 2; Repr. 1B; STOT RE 1; Aquatic Acute 1; Aquatic Chronic 1; H330, H360, H372, H410	90 - 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

# 4. FIRST AID MEASURES

# 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

# **4.2 Most important symptoms and effects, both acute and delayed** The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### **4.3 Indication of any immediate medical attention and special treatment needed** No data available

# **5. FIREFIGHTING MEASURES**

### 5.1 Extinguishing media

# Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture No data available

# 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information No data available

# 6. ACCIDENTAL RELEASE MEASURES

# 6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas.

For personal protection see section 8.

### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

### 6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal. In some instances, a mercury spill kit may be used. Please consult with your site EHS representative to determine the most appropriate clean up method. Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

# 6.4 Reference to other sections

For disposal see section 13.

# 7. HANDLING AND STORAGE

# 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. For precautions see section 2.2.

# 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

# Store under inert gas.

Storage class (TRGS 510): 6.1B: Non-combustible, acute toxic Cat. 1 and 2 / very toxic hazardous materials

# 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# 8.1 Control parameters

# Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis
			parameters	
Mercury	7439-97-6	С	0.1 mg/m3	USA. NIOSH Recommended
-			-	Exposure Limits
	Remarks	Potential for	dermal absorption	
		CEIL	1.0mg/10m3	USA. Occupational Exposure Limits
				(OSHA) - Table Z-2
		TWA	0.05 mg/m3	USA. OSHA - TABLE Z-1 Limits for
				Air Contaminants - 1910.1000
		Skin notation	1	

TWA	0.025 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
Central Nerv	ous System impair	ment
Kidney dama	age	
Substances f	for which there is a	Biological Exposure Index or Indices
(see BEI® se	ection)	
Not classifiat	ole as a human ca	rcinogen
Danger of cu	itaneous absorptio	n
TWA	0.05 mg/m3	USA. NIOSH Recommended
	-	Exposure Limits
Potential for	dermal absorption	

# 8.2 Exposure controls

# Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

#### Personal protective equipment

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

a) Appearance

Form: liquid Colour: silver, white

	b)	Odour	odourless
	c)	Odour Threshold	No data available
	d)	рН	No data available
	e)	Melting point/freezing point	Melting point/range: -38.87 °C (-37.97 °F) - lit.
	f)	Initial boiling point and boiling range	356.6 °C (673.9 °F) - lit.
	g)	Flash point	Not applicable
	h)	Evaporation rate	No data available
	i)	Flammability (solid, gas)	No data available
	j)	Upper/lower flammability or explosive limits	No data available
	k)	Vapour pressure	< 0.01 hPa (< 0.01 mmHg) at 20 °C (68 °F) 1 hPa (1 mmHg) at 126 °C (259 °F)
	I)	Vapour density	6.93 - (Air = 1.0)
	m)	Relative density	13.55 g/cm3 at 25 °C (77 °F)
	n)	Water solubility	0.00006 g/l at 25 °C (77 °F)
	o)	Partition coefficient: n- octanol/water	No data available
	p)	Auto-ignition temperature	No data available
	q)	Decomposition temperature	No data available
	r)	Viscosity	No data available
	s)	Explosive properties	No data available
	t)	Oxidizing properties	No data available
.2	Othe	r safety information	
		Relative vapour density	6.93 - (Air = 1.0)
10.	STAB	LITY AND REACTIVITY	
0 1	Pose	4i\/i4\/	

#### 10.1 Reactivity No data available

9.2

# 10.2 Chemical stability

Stable under recommended storage conditions.

- 10.3 Possibility of hazardous reactions No data available
- 10.4 Conditions to avoid No data available

# 10.5 Incompatible materials Strong oxidizing agents, Ammonia, Azides, Nitrates, Chlorates, Copper

# Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Mercury/mercury oxides. Other decomposition products - No data available 10.6 In the event of fire: see section 5

# **11. TOXICOLOGICAL INFORMATION**

# 11.1 Information on toxicological effects

Acute toxicity No data available

LC50 Inhalation - Rat - male - 2 h - < 27 mg/m3

Dermal: No data available

No data available

Skin corrosion/irritation No data available

Serious eye damage/eye irritation No data available

Respiratory or skin sensitisation No data available

Germ cell mutagenicity No data available

# Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

# Reproductive toxicity

Presumed human reproductive toxicant

Specific target organ toxicity - single exposure No data available

# Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

#### Aspiration hazard No data available

# Additional Information

RTECS: OV4550000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

# **12. ECOLOGICAL INFORMATION**

# 12.1 Toxicity

mortality LC50 - Cyprinus carpio (Carp) - 0.160 mg/l - 96 h

# **12.2 Persistence and degradability** No data available

# 12.3 Bioaccumulative potential

Toxicity to fish

Bioaccumulation

Carassius auratus (goldfish) - 1,789 d - 0.25 µg/l

# 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

# **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

#### Contaminated packaging

Dispose of as unused product.

# **14. TRANSPORT INFORMATION**

#### DOT (US)

UN number: 2809 Class: 8 (6.1) Proper shipping name: A. W. Mercury Reportable Quantity (RQ): 1 lbs Poison Inhalation Hazard: No Packing group: III

# IMDG

### ΙΑΤΑ

UN number: 2809 Class: 8 (6.1) Proper shipping name: Mercury Packing group: III

### **15. REGULATORY INFORMATION**

# SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

# Massachusetts Right To Know Components

Mercury	CAS-No. 7439-97-6	Revision Date 2015-11-23
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Mercury	7439-97-6	2015-11-23
	CAS-No.	Revision Date
Mercury	7439-97-6	2015-11-23
New Jersey Right To Know Components		
	CAS-No.	Revision Date
Mercury	7439-97-6	2015-11-23

# California Prop. 65 Components

# **16. OTHER INFORMATION**

# Full text of H-Statements referred to under sections 2 and 3.

0

Acute Tox.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
H330	Fatal if inhaled.
H360	May damage fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Repr.	Reproductive toxicity

#### **HMIS Rating**

Health hazard:	2
Chronic Health Hazard:	*
Flammability:	0
Physical Hazard	0
NFPA Rating	
Health hazard:	2
Fire Hazard:	0

Health hazard:	
Fire Hazard:	
Reactivity Hazard:	

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety - Americas Region 1-800-521-8956

Version: 3.15

Revision Date: 03/05/2018

Print Date: 06/28/2019

# SIGMA-ALDRICH

sigma-aldrich.com

SAFETY DATA SHEET

Version 3.4 Revision Date 06/27/2014 Print Date 06/28/2019

1. PF	RODUCT AND COMPANY	<b>IDEN</b>	TIFICATION
1.1	Product identifiers Product name	:	Heptadecafluorooctanesulfonic acid solution
	Product Number Brand	:	77283 Aldrich
1.2	Relevant identified use	s of th	ne substance or mixture and uses advised against
	Identified uses	:	Laboratory chemicals, Manufacture of substances
1.3	Details of the supplier	of the	safety data sheet
	Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
	Telephone Fax	:	+1 800-325-5832 +1 800-325-5052
1.4	Emergency telephone	numbe	er
	Emergency Phone #	:	+1-703-527-3887 (CHEMTREC)
2. H/	AZARDS IDENTIFICATION	N	
2.1	Classification of the su	bstan	ce or mixture
	GHS Classification in a	ccord	ance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 4), H302 Acute toxicity, Inhalation (Category 3), H331 Skin corrosion (Category 1B), H314 Serious eye damage (Category 1), H318 Carcinogenicity (Category 2), H351 Reproductive toxicity (Category 1B), H360 Effects on or via lactation, H362 Specific target organ toxicity - repeated exposure (Category 1), H372 Acute aquatic toxicity (Category 2), H401 Chronic aquatic toxicity (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

# 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word	Danger
Hazard statement(s)	
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H331	Toxic if inhaled.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H362	May cause harm to breast-fed children.
H372	Causes damage to organs through prolonged or repeated exposure.

H411	Toxic to aquatic life with long lasting effects.
Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P263	Avoid contact during pregnancy/ while nursing.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P330 + P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/ physician.
P321	Specific treatment (see supplemental first aid instructions on this label).
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

# 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

# 3.2 Mixtures

Formula	:	C <sub>8</sub> HF <sub>17</sub> O <sub>3</sub> S
Molecular Weight	:	500.13 g/mol

Hazardous compone	ents		
Component		Classification	Concentration
Heptadecafluoroocta	ane-1-sulphonic acid		
CAS-No.	1763-23-1	Acute Tox. 4; Skin Corr. 1B;	30 - 60 %
EC-No.	217-179-8	Eye Dam. 1; Carc. 2; Repr.	
Index-No.	607-624-00-8	1B; Lact. ; STOT RE 1;	
		Aquatic Acute 2; Aquatic	
		Chronic 2; H302 + H332,	
		H314, H351, H360, H362,	
		H372, H411	

For the full text of the H-Statements mentioned in this Section, see Section 16.

# 4. FIRST AID MEASURES

# 4.1 Description of first aid measures

### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

# In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician.

# In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

# 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**4.3** Indication of any immediate medical attention and special treatment needed no data available

# **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

**Suitable extinguishing media** Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture Carbon oxides, Sulphur oxides, Hydrogen fluoride

# **5.3** Advice for firefighters Wear self contained breathing apparatus for fire fighting if necessary.

5.4 Further information no data available

# 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. For personal protection see section 8.

#### 6.2 Environmental precautions Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

- **6.3** Methods and materials for containment and cleaning up Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.
- 6.4 Reference to other sections

For disposal see section 13.

# 7. HANDLING AND STORAGE

# 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. For precautions see section 2.2.

**7.2** Conditions for safe storage, including any incompatibilities Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

# 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### Eye/face protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

#### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: clear, liquid Colour: light red
b)	Odour	no data available
c)	Odour Threshold	no data available
d)	рН	no data available
e)	Melting point/freezing point	no data available
f)	Initial boiling point and boiling range	no data available
g)	Flash point	no data available
h)	Evapouration rate	no data available
i)	Flammability (solid, gas)	no data available
j)	Upper/lower flammability or explosive limits	no data available
k)	Vapour pressure	no data available
I)	Vapour density	no data available
m)	Relative density	1.250 g/cm3
n)	Water solubility	no data available
o)	Partition coefficient: n- octanol/water	no data available
p)	Auto-ignition temperature	no data available

- q) Decomposition no data available temperature
- r) Viscosity no data available
- s) Explosive properties no data available
- t) Oxidizing properties no data available

# 9.2 Other safety information no data available

# **10. STABILITY AND REACTIVITY**

# 10.1 Reactivity

no data available

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3** Possibility of hazardous reactions no data available
- **10.4** Conditions to avoid no data available
- **10.5 Incompatible materials** Strong oxidizing agents
- **10.6 Hazardous decomposition products** Other decomposition products - no data available In the event of fire: see section 5

# **11. TOXICOLOGICAL INFORMATION**

# 11.1 Information on toxicological effects

# Acute toxicity

no data available

Inhalation: no data available

Dermal: no data available

no data available

# Skin corrosion/irritation

no data available

# Serious eye damage/eye irritation

no data available

**Respiratory or skin sensitisation** no data available

Germ cell mutagenicity

no data available

### Carcinogenicity

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

Reproductive toxicity no data available

no data available

Specific target organ toxicity - single exposure no data available

Specific target organ toxicity - repeated exposure no data available

Aspiration hazard

**Additional Information** 

**RTECS:** Not available

burning sensation, Cough, wheezing, laryngitis, Shortness of breath, spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin.

# 12. ECOLOGICAL INFORMATION

- 12.1 Toxicity no data available
- **12.2** Persistence and degradability no data available
- **12.3 Bioaccumulative potential** no data available
- **12.4 Mobility in soil** no data available
- **12.5** Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life.

# 13. DISPOSAL CONSIDERATIONS

# 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

### Contaminated packaging

Dispose of as unused product.

### **14. TRANSPORT INFORMATION**

#### DOT (US)

UN number: 3265 Class: 8 Packing group: II Proper shipping name: Corrosive liquid, acidic, organic, n.o.s. (Heptadecafluorooctane-1-sulphonic acid) Marine pollutant: No Poison Inhalation Hazard: No

### IMDG

UN number: 3265 Class: 8 Packing group: II EMS-No: F-A, S-B Proper shipping name: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Heptadecafluorooctane-1-sulphonic acid) Marine pollutant: No

# ΙΑΤΑ

UN number: 3265 Class: 8 Packing group: II Proper shipping name: Corrosive liquid, acidic, organic, n.o.s. (Heptadecafluorooctane-1-sulphonic acid)

# **15. REGULATORY INFORMATION**

#### SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

### SARA 313 Components

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Acute Health Hazard

#### Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

#### Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Water	7732-18-5	
Heptadecafluorooctane-1-sulphonic acid	1763-23-1	2009-07-17
New Jersey Right To Know Components		
	CAS-No.	Revision Date
Water	7732-18-5	
Heptadecafluorooctane-1-sulphonic acid	1763-23-1	2009-07-17

#### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

## **16. OTHER INFORMATION**

# Full text of H-Statements referred to under sections 2 and 3.

Acute Tox. Aquatic Acute Aquatic Chronic Carc. Eye Dam. H302 H302 + H332 H314 H318 H331 H351 H360 H362 H372 H401 H411	Acute toxicity Acute aquatic toxicity Chronic aquatic toxicity Carcinogenicity Serious eye damage Harmful if swallowed. Harmful if swallowed or if inhaled Causes severe skin burns and eye damage. Causes serious eye damage. Causes serious eye damage. Toxic if inhaled. Suspected of causing cancer. May damage fertility or the unborn child. May cause harm to breast-fed children. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Lact.	Effects on or via lactation

#### **HMIS Rating**

Health hazard:	3
Chronic Health Hazard:	
Flammability:	0
Physical Hazard	0
NFPA Rating	
Health hazard:	3
Fire Hazard:	0

# Further information

Copyright 2014 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

# **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 3.4

Revision Date: 06/27/2014

Print Date: 06/28/2019



# **SAFETY DATA SHEET**

Version 6.1 Revision Date 03/12/2019 Print Date 06/28/2019

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

# **1.1 Product identifiers**

Product name	<sup>:</sup> Perfluorooctanoic acid
Product Number	: 171468
Brand	: Aldrich
CAS-No.	: 335-67-1

# **1.2** Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

# 1.3 Details of the supplier of the safety data sheet

Company	: Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES
Telephone	: +1 314 771-5765

# **1.4 Emergency telephone number**

Emergency Phone # : +1-703-527-3887

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

# GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 4), H302 Acute toxicity, Inhalation (Category 4), H332 Serious eye damage (Category 1), H318 Carcinogenicity (Category 2), H351 Reproductive toxicity (Category 1B), H360 Effects on or via lactation, H362 Specific target organ toxicity - repeated exposure (Category 1), Liver, H372

For the full text of the H-Statements mentioned in this Section, see Section 16.

# 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Aldrich - 171468

Page 1 of 10

The life science business of Merck KGaA, Darmstadt, Germany operates as MilliporeSigma in the US and Canada



Hazard statement(s)	
H302 + H332	Harmful if swallowed or if inhaled.
H318	Causes serious eye damage.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H362	May cause harm to breast-fed children.
H372	Causes damage to organs (Liver) through prolonged or repeated exposure.
Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P263	Avoid contact during pregnancy/ while nursing.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable
	for breathing. Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338 +	IF IN EYES: Rinse cautiously with water for several minutes.
P310	Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

# 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SEC	TION 3: Composition	/info	mation on ingred	ients	
3.1	<b>Substances</b> Synonyms	:	Pentadecafluorooc Perfluorocaprylic a Perfluorooctanoic a		
	Formula Molecular weight CAS-No. EC-No.	:	C <sub>8</sub> HF <sub>15</sub> O <sub>2</sub> 414.07 g/mol 335-67-1 206-397-9		
	Component			Classification	Concentration
	Pentadecafluorooct	tanoic	acid	Acute Tox. 4; Eye Dam. 1; Carc. 2; Repr. 1B; Lact. ; STOT RE 1; H302, H332, H318, H351, H360, H362,	<= 100 %
				H372	

Aldrich - 171468

Page 2 of 10

The life science business of Merck KGaA, Darmstadt, Germany operates as MilliporeSigma in the US and Canada



For the full text of the H-Statements mentioned in this Section, see Section 16.

# **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

# **General advice**

Move out of dangerous area.Consult a physician. Show this safety data sheet to the doctor in attendance.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

# In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

#### In case of eye contact

Continue rinsing eyes during transport to hospital. Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**4.3 Indication of any immediate medical attention and special treatment needed** No data available

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

**Suitable extinguishing media** Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

- **5.2** Special hazards arising from the substance or mixture Carbon oxides, Hydrogen fluoride
- **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.

#### **5.4 Further information** No data available

Aldrich - 171468

Page 3 of 10


#### **SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures** Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust.

For personal protection see section 8.

- **6.2 Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not let product enter drains.
- **6.3 Methods and materials for containment and cleaning up** Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.
- **6.4 Reference to other sections** For disposal see section 13.

#### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols.Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Storage class (TRGS 510): 6.1D: Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values. Hazardous components without workplace control parameters

#### 8.2 Exposure controls

#### **Appropriate engineering controls**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### **Personal protective equipment**

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Aldrich - 171468

Page 4 of 10



#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: > 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: > 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a fullface particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### **Control of environmental exposure**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: flakes Colour: colourless
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	2.6 at 1 g/l
e)	Melting point/freezing point	Melting point/range: 55 - 56 °C (131 - 133 °F) - lit.
f)	Initial boiling point and boiling range	189 °C 372 °F at 981 hPa - lit.

Aldrich - 171468

Page 5 of 10



g)	Flash point	()No data available
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	0.69 hPa at 25 °C (77 °F)
I)	Vapour density	No data available
m)	Relative density	0.900 g/cm3
n)	Water solubility	No data available
o)	Partition coefficient: n-octanol/water	No data available
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
•••		

### 9.2 Other safety information No data available

#### **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity** No data available

#### 10.2 Chemical stability

Stable under recommended storage conditions.

- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available

#### **10.5** Incompatible materials

Bases, Oxidizing agents, Reducing agents

# 10.6 Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Carbon oxides, Hydrogen fluoride Other decomposition products - No data available In the event of fire: see section 5

Aldrich - 171468

Page 6 of 10





#### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

#### Acute toxicity

Inhalation: No data available Dermal: No data available LD50 Intraperitoneal - Rat - 189 mg/kg

Skin corrosion/irritation No data available

Serious eye damage/eye irritation No data available

**Respiratory or skin sensitisation** No data available

#### Germ cell mutagenicity

Rat DNA damage

Rat DNA damage

#### Carcinogenicity

Suspected human carcinogens

- IARC: 2B Group 2B: Possibly carcinogenic to humans (Pentadecafluorooctanoic acid)
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

Effects on or via lactation Presumed human reproductive toxicant No data available

#### Specific target organ toxicity - single exposure

No data available

#### Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure. - Liver

#### Aspiration hazard

No data available

#### **Additional Information**

RTECS: RH0781000

Cough, Shortness of breath, Headache, Nausea, Vomiting

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

Aldrich - 171468

Page 7 of 10



#### **SECTION 12: Ecological information**

12.1 Toxicity

No data available

- **12.2 Persistence and degradability** No data available
- **12.3 Bioaccumulative potential** No data available
- **12.4 Mobility in soil** No data available
- 12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted
- **12.6 Other adverse effects** No data available

#### **SECTION 13: Disposal considerations**

#### **13.1 Waste treatment methods**

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

#### Contaminated packaging

Dispose of as unused product.

#### **SECTION 14: Transport information**

#### DOT (US)

UN number: 3261 Class: 8 Packing group: III Proper shipping name: Corrosive solid, acidic, organic, n.o.s. (Pentadecafluorooctanoic acid) Reportable Quantity (RQ): Poison Inhalation Hazard: No

#### IMDG

UN number: 3261 Class: 8 Packing group: III EMS-No: F-A, S-B Proper shipping name: CORROSIVE SOLID, ACIDIC, ORGANIC, N.O.S. (Pentadecafluorooctanoic acid)

#### ΙΑΤΑ

UN number: 3261 Class: 8 Packing group: III Proper shipping name: Corrosive solid, acidic, organic, n.o.s. (Pentadecafluorooctanoic acid)

Aldrich - 171468

Page 8 of 10



#### **SECTION 15: Regulatory information**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

#### **Massachusetts Right To Know Components**

No components are subject to the Massachusetts Right to Know Act.

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components Pentadecafluorooctanoic acid	CAS-No. 335-67-1	Revision Date
Pentadecafluorooctanoic acid	CAS-No. 335-67-1	Revision Date
New Jersey Right To Know Components Pentadecafluorooctanoic acid	CAS-No. 335-67-1	Revision Date

#### **California Prop. 65 Components**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### **SECTION 16: Other information**

#### Further information

Copyright 2018 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Aldrich - 171468

Page 9 of 10



Version: 6.1

Aldrich - 171468

Page 10 of 10



sigma-aldrich.com

#### **SAFETY DATA SHEET**

Version 6.2 Revision Date 07/25/2018 Print Date 06/28/2019

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

1.1	Product identifiers Product name	:	<l>p-Xylene</l>
	Product Number Brand Index-No.	:	296333 Sigma-Aldrich 601-022-00-9
	CAS-No.	:	106-42-3

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES
Telephone	:	+1 314 771-5765
	-	+1 800 325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### **GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)** Flammable liquids (Category 3), H226

Acute toxicity, Inhalation (Category 4), H332

Acute toxicity, Dermal (Category 4), H312

Skin irritation (Category 2), H315

Acute aquatic toxicity (Category 2), H401

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Warning

Hazard statement(s) H226 H312 + H332 H315 H401	Flammable liquid and vapour. Harmful in contact with skin or if inhaled. Causes skin irritation. Toxic to aquatic life.
Precautionary statement(s)	
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P201 D264	Avoid breathing dust/ rume/ gas/ mist/ vapours/ spray.
F204 D271	Wash skin infordugnly after nandling.
P273	Avoid release to the environment
P280	Wear protective gloves/ eve protection/ face protection
$P_{303} + P_{361} + P_{353}$	IF ON SKIN (or hair): Remove/ Take off immediately all contaminated
	clothing. Rinse skin with water/ shower.
P304 + P340 + P312	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if
B000 - B040	you feel unwell.
P332 + P313	It skin irritation occurs: Get medical advice/ attention.
P302	Take on contaminated clothing and wash before reuse.
P3/U + P3/8	extinction.
P403 + P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

#### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

3.1	<b>Substances</b> Synonyms	:	1,4-Dimethylbenzene	
	Formula	:	C <sub>8</sub> H <sub>10</sub>	
	Molecular weight	:	106.17 g/mol	
	CAS-No.	:	106-42-3	
	EC-No.	:	203-396-5	
	Index-No.		601-022-00-9	
	Hazardous components			
	Component			

Component	Classification	Concentration
p-Xylene		
	Flam. Liq. 3; Acute Tox. 4; Skin Irrit. 2; Aquatic Acute 2; H226, H312 + H332, H315, H401	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### **4.2** Most important symptoms and effects, both acute and delayed The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**4.3 Indication of any immediate medical attention and special treatment needed** No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture Carbon oxides

#### 5.3 Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Storage class (TRGS 510): 3: Flammable liquids

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis	
n Vulono	106 42 2	<b>Τ</b> \Λ/Λ	100 ppm		locommonded
p-xyiene	106-42-3	IVVA	100 ppm		
		o <del></del>	435 mg/m3	Exposure Limit	S
		SI	150 ppm	USA. NIOSH R	lecommended
			655 mg/m3	Exposure Limit	S
		TWA	100 ppm	USA. Occupati	onal Exposure Limits
			435 mg/m3	(OSHA) - Table	e Z-1 Limits for Air
				Contaminants	
	Remarks	The value in	mg/m3 is appre	oximate.	
		TWA	100 ppm	USA. ACGIH T	hreshold Limit Values
				(TLV)	
		Central Nerv	ous System im	pairment	
		Upper Respi	ratory Tract irrit	ation	
		Eve irritation			
		Substances	for which there	is a Biological Expo	osure Index or Indices
		(see BEI® se	ection)	<b>U</b> .	
		Not classifial	ole as a human	carcinogen	
		STEL	150 ppm	USA. ACGIH T	hreshold Limit Values
				(TLV)	
		Central Nerv	ous System im	pairment	
		Upper Respi	ratory Tract irrit	ation	
		Eye irritation			
		Substances	for which there	is a Biological Expo	sure Index or Indices
		(see BEI® se	ection)	0 1	
		Not classifial	ole as a human	carcinogen	
<b>Biological occupation</b>	onal exposure	limits		Ŭ	
Component	CAS-No	Parameters		Biological	Basis

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
p-Xylene	106-42-3	Methylhippuri c acids	1.5g/g creatinine	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (As	s soon as po	ssible after exposure	e ceases)

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 30 min Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). **Control of environmental exposure** 

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid, clear Colour: colourless
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 12 - 13 °C (54 - 55 °F) - lit.
f)	Initial boiling point and boiling range	138 °C (280 °F) - lit.
g)	Flash point	25.0 °C (77.0 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 7 %(V) Lower explosion limit: 1.1 %(V)
k)	Vapour pressure	21.3 hPa at 37.7 °C (99.9 °F) 12.0 hPa at 20.0 °C(68.0 °F)
I)	Vapour density	No data available
m)	Relative density	0.861 g/cm3 at 20 °C (68 °F)
n)	Water solubility	0.2 g/l
o)	Partition coefficient: n- octanol/water	log Pow: 3.15
p)	Auto-ignition temperature	529.0 °C (984.2 °F)
q)	Decomposition temperature	No data available
r)	Viscosity	No data available

- s) Explosive properties No data available
- t) Oxidizing properties No data available

#### 9.2 Other safety information

Surface tension

28.3 mN/m at 20.0 °C (68.0 °F)

#### **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity

No data available

#### **10.2 Chemical stability** Stable under recommended storage conditions.

- **10.3 Possibility of hazardous reactions** Vapours may form explosive mixture with air.
- **10.4 Conditions to avoid** Heat, flames and sparks.
- **10.5 Incompatible materials** Strong oxidizing agents

#### 10.6 Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - 5,000 mg/kg LD50 Oral - Rat - male - 3,523 mg/kg LC50 Inhalation - Rat - 4 h - 4550 ppm Remarks: Lungs, Thorax, or Respiration:Chronic pulmonary edema. Liver:Other changes. Blood:Changes in cell count (unspecified). No data available

#### Skin corrosion/irritation

Skin - Rabbit Result: Moderate skin irritation - 4 h

#### Serious eye damage/eye irritation No data available

Respiratory or skin sensitisation No data available

Germ cell mutagenicity No data available

Carcinogenicity

- IARC: 3 Group 3: Not classifiable as to its carcinogenicity to humans (p-Xylene)
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

No data available May cause reproductive disorders.

#### Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

#### Additional Information

RTECS: ZE2625000

narcosis, Lung irritation, chest pain, pulmonary edema, Central nervous system depression, Gastrointestinal disturbance, Liver injury may occur., Kidney injury may occur., Blood disorders

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

Toxicity to fish	LC50 - Oncorhynchus mykiss (rainbow trout) - 2.60 mg/l - 96 h(p-Xylene)
	LC50 - Carassius auratus (goldfish) - 18.00 mg/l - 24 h(p-Xylene)
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - 35.50 - 63.10 mg/l - 48 h(p-Xylene)
Toxicity to algae	EC50 - Pseudokirchneriella subcapitata (green algae) - 3.20 - 4.40 mg/l - 72 h(p-Xylene)

#### 12.2 Persistence and degradability

Biodegradability Result: 87.8 % - Readily biodegradable.

12.3 Bioaccumulative potential

No data available

- **12.4 Mobility in soil** No data available(p-Xylene)
- 12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

100 lbs

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life.

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

#### **Contaminated packaging**

Dispose of as unused product.

#### 14. TRANSPORT INFORMATION

#### DOT (US)

UN number: 1307 Class: 3 Proper shipping name: Xylenes Reportable Quantity (RQ) : Packing group: III

Poison Inhalation Hazard: No

#### IMDG

UN number: 1307 Class: 3 Proper shipping name: XYLENES Packing group: III

EMS-No: F-E, S-D

#### ΙΑΤΑ

UN number: 1307 Class: 3 Proper shipping name: Xylenes Packing group: III

#### 15. REGULATORY INFORMATION

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:			
	CAS-No.	Revision Date	
p-Xylene	106-42-3	2007-07-01	

#### SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### **16. OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H312 + H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H401	Toxic to aquatic life.

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956 Version: 6.2

Revision Date: 07/25/2018

Print Date: 06/28/2019



#### SAFETY DATA SHEET

Version 6.1 Revision Date 12/12/2018 Print Date 01/21/2019

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 **Product identifiers**

Product name : sec-Butylbenzene : B90408 **Product Number** Brand : Aldrich CAS-No. 135-98-8 :

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	: Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES
Telephone	: +1 314 771-5765

#### Fax : +1 800 325-5052

#### 1.4 **Emergency telephone number**

Emergency Phone # : (314) 776-6555

#### **SECTION 2: Hazards identification**

#### Classification of the substance or mixture 2.1

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 3), H226 Acute toxicity, Oral (Category 4), H302

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Warning

```
Hazard statement(s)
H226
H302
```

Flammable liquid and vapour. Harmful if swallowed.

Precautionary statement(s) Keep away from heat/sparks/open flames/hot surfaces. No P210

Aldrich - B90408

pore

Page 1 of 9



P233 P240 P241 P242	smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting equipment. Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/ eye protection/ face protection.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P235 P501	Store in a well-ventilated place. Keep cool. Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

#### **SECTION 3:** Composition/information on ingredients

3.1	<b>Substances</b> Synonyms	:	2-Phenylbutane		
	Formula	:	C <sub>10</sub> H <sub>14</sub>		
	Molecular weight	:	134.22 g/mol		
	CAS-No.	:	135-98-8		
	EC-No.	:	205-227-0		
	Component			Classification	Concentration
	sec-Butylbenzene				
				Flam. Liq. 3; Acute Tox. 4;	<= 100 %
				H226, H302	

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

Aldrich - B90408

Page 2 of 9



#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**4.3 Indication of any immediate medical attention and special treatment needed** No data available

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media Dry powder Dry sand

**Unsuitable extinguishing media** Do NOT use water jet.

- **5.2 Special hazards arising from the substance or mixture** Carbon oxides
- **5.3 Advice for firefighters** Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

Use water spray to cool unopened containers.

#### **SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures** Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

#### **6.2 Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

- **6.3 Methods and materials for containment and cleaning up** Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
- **6.4** Reference to other sections For disposal see section 13.

#### **SECTION 7: Handling and storage**

#### **7.1 Precautions for safe handling** Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Aldrich - B90408

Page 3 of 9



Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Storage class (TRGS 510): 3: Flammable liquids

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values. Hazardous components without workplace control parameters

#### 8.2 Exposure controls

#### **Appropriate engineering controls**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### **Personal protective equipment**

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our

customers. It should not be construed as offering an approval for any specific use scenario.

Aldrich - B90408

Page 4 of 9



#### **Body Protection**

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

SECTION 9: Physical and chemical properties

Where risk assessment shows air-purifying respirators are appropriate use a fullface respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### **Control of environmental exposure**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

		-	
9.1 Information on basic physical and chemical properties			
	a)	Appearance	Form: liquid, clear Colour: colourless
	b)	Odour	No data available
	c)	Odour Threshold	No data available
	d)	рН	No data available
	e)	Melting point/freezing point	Melting point/range: 75.5 °C (167.9 °F) - lit.
	f)	Initial boiling point and boiling range	173 - 174 °C 343 - 345 °F - lit.
	g)	Flash point	52.0 °C (125.6 °F) - closed cup
	h)	Evaporation rate	No data available
	i)	Flammability (solid, gas)	No data available
	j)	Upper/lower flammability or explosive limits	Lower explosion limit: 0.8 %(V)
	k)	Vapour pressure	No data available
	I)	Vapour density	No data available
	m)	Relative density	0.863 g/mL at 25 °C (77 °F)
	n)	Water solubility	No data available
	o)	Partition coefficient: n-octanol/water	No data available
	p)	Auto-ignition temperature	418.0 °C (784.4 °F)
	q)	Decomposition temperature	No data available
	r)	Viscosity	No data available

Aldrich - B90408

Page 5 of 9



- s) Explosive properties No data available
- t) Oxidizing properties No data available
- **9.2 Other safety information** No data available

#### **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity** No data available

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** Heat, flames and sparks.
- **10.5 Incompatible materials** Strong oxidizing agents
- **10.6 Hazardous decomposition products** Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available In the event of fire: see section 5

#### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### **Acute toxicity**

LD50 Oral - Rat - 1,926 mg/kg Remarks: (RTECS) Inhalation: No data available LD50 Dermal - Rabbit - > 13,760 mg/kg Remarks: (RTECS) No data available

#### Skin corrosion/irritation

Skin - Rabbit Result: slight irritation Remarks: (RTECS)

#### Serious eye damage/eye irritation

**Respiratory or skin sensitisation** No data available

#### **Germ cell mutagenicity** No data available

#### Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Aldrich - B90408

Page 6 of 9





- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

No data available No data available

**Specific target organ toxicity - single exposure** No data available

**Specific target organ toxicity - repeated exposure** No data available

**Aspiration hazard** No data available

Additional Information RTECS: CY9100000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

After absorption: Headache, Nausea, narcosis Other dangerous properties can not be excluded. Handle in accordance with good industrial hygiene and safety practice.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

- 12.2 Persistence and degradability No data available
- **12.3 Bioaccumulative potential** No data available
- **12.4 Mobility in soil** No data available
- 12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### **12.6 Other adverse effects**

Discharge into the environment must be avoided.

Aldrich - B90408

Page 7 of 9



#### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable.

#### **Contaminated packaging**

Dispose of as unused product.

#### **SECTION 14: Transport information**

**DOT (US)** UN number: 2709 Class: 3 Packing group: III Proper shipping name: Butyl benzenes Reportable Quantity (RQ): • Marine pollutant: yesPoison Inhalation Hazard: No

#### IMDG

Marine pollutant : yes		
Marine pollutant : yes		
Proper shipping name: BUTYLBENZENES		
UN number: 2709 Class: 3	Packing group: III	EMS-No: F-E, S-D

Packing group: III

#### ΙΑΤΑ

UN number: 2709 Class: 3 Proper shipping name: Butylbenzenes

#### **SECTION 15: Regulatory information**

#### SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard

#### Massachusetts Right To Know Components

sec-Butylbenzene	CAS-No. 135-98-8	Revision Date 1993-04-24
Pennsylvania Right To Know Components sec-Butylbenzene	CAS-No. 135-98-8	Revision Date 1993-04-24

#### **California Prop. 65 Components**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Aldrich - B90408

Page 8 of 9





#### **SECTION 16: Other information**

#### Further information

Copyright 2018 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.1

Revision Date: 12/12/2018

Print Date: 01/21/2019

Aldrich - B90408

Page 9 of 9



#### SAFETY DATA SHEET

Version 6.2 Revision Date 05/28/2017 Print Date 06/28/2019

#### 1. PRODUCT AND COMPANY IDENTIFICATION 1.1 **Product identifiers** Product name : Sodium Product Number : 483745 Brand Aldrich : 7440-23-5 CAS-No. 1.2 Relevant identified uses of the substance or mixture and uses advised against Identified uses : Laboratory chemicals, Synthesis of substances 1.3 Details of the supplier of the safety data sheet Company · Sigma-Aldrich Inc

·	3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES
:	+1 314 771-5765 +1 800 325-5052
	· :

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Substances and mixtures, which in contact with water, emit flammable gases (Category 1), H260 Skin corrosion (Category 1B), H314 Serious eye damage (Category 1), H318 Carcinogenicity (Category 1A), H350

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram

. .



Signal word	Danger
Hazard statement(s)	
H260	In contact with water releases flammable gases which may ignite spontaneously.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H350	May cause cancer.

Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P223	Keep away from any possible contact with water, because of violent reaction and possible flash fire.
P231 + P232	Handle under inert gas. Protect from moisture.
P260	Do not breathe dust or mist.
P264	Wash skin thoroughly after handling.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P281	Use personal protective equipment as required.
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/ Take off immediately all contaminated
	clothing. Rinse skin with water/ shower.
P304 + P340 + P310	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.
P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P335 + P334	Brush off loose particles from skin. Immerse in cool water/ wrap in wet bandages.
P363	Wash contaminated clothing before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P402 + P404	Store in a dry place. Store in a closed container.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### **2.3 Hazards not otherwise classified (HNOC) or not covered by GHS** Reacts violently with water.

#### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2 Mixtures

Formula	:	Na
Molecular weight	:	22.99 g/mol

#### Hazardous components

Component		Classification	Concentration
Sodium			
CAS-No. EC-No. Index-No.	7440-23-5 231-132-9 011-001-00-0	Water-react. 1; Skin Corr. 1B; Eye Dam. 1; H260, H314	>= 90 - <= 100 %
Paraffin oils			
CAS-No. EC-No.	8012-95-1 232-384-2	Asp. Tox. 1; H304, H304	>= 90 - <= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

- **4.2 Most important symptoms and effects, both acute and delayed** The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
- **4.3 Indication of any immediate medical attention and special treatment needed** No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

Suitable extinguishing media Dry powder

- 5.2 Special hazards arising from the substance or mixture Carbon oxides, Sodium oxides
- **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.
- 5.4 Further information No data available

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

- 6.3 Methods and materials for containment and cleaning up Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13). Do not flush with water. Keep in suitable, closed containers for disposal.
- 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combu formation should be taken into consideration before additional processing Provide appropriate exhaust ventilation at places where dust is formed. Keep away from sources of ignition - No

smoking.

For precautions see section 2.2.

**7.2 Conditions for safe storage, including any incompatibilities** Keep container tightly closed in a dry and well-ventilated place. Never allow product to get in contact with water during storage.

Handle and store under inert gas. Air sensitive.

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis	
			parameters		
Paraffin oils	8012-95-1	STEL	10.000000	USA. ACGIH Threshold Limit Values	
			mg/m3	(TLV)	
		TWA	5.000000	USA. Occupational Exposure Limits	
			mg/m3	(OSHA) - Table Z-1 Limits for Air	
				Contaminants	
		TWA	5.000000	USA. NIOSH Recommended	
			mg/m3	Exposure Limits	
		ST	10.000000	USA. NIOSH Recommended	
		-	ma/m3	Exposure Limits	
		TWA	5.00000	USA, Occupational Exposure Limits	
			ma/m3	(OSHA) - Table 7-1 Limits for Air	
			iiig/iiio	Contaminants	
		TWA	5 000000	USA ACGIH Threshold Limit Values	
		1.007	mg/m3		
	Remarks	Linner Resn	iratory Tract irritat	tion	
	Remarks	2015 Adopti	natory materimitat		
		Not classifia	ble as a human c	arcinogen	
		Linner Resp	iratory Tract irritat	tion	
	2015 Ador		appliance initiation		
		Exposure by all routes should be carefully controlled to lovels as low			
		as possible		be calciuly controlled to levels as low	
		as possible.			
		TWA	5 000000	USA Occupational Exposure Limits	
		10070	mg/m3	(OSHA) - Table 7-1 Limits for Air	
			iiig/iiio	Contaminants	
		TWA	5 000000	USA Occupational Exposure Limits	
			mg/m3	(OSHA) - Table 7-1 Limits for Air	
			iiig/iiio	Contaminants	
		Linner Resp	iratory Tract irritat	tion	
		Exposure by	/ all routes should	be carefully controlled to levels as low	
		as possible			
		Suspected h	uman carcinogen		
		TWA	5 000000	USA ACGIH Threshold Limit Values	
		1.007	mg/m3		
		Upper Resp	iratory Tract irritat	tion	
		Not classifia	ble as a human c	arcinogen	
		TWA	5 000000	USA NIOSH Recommended	
			mg/m3	Exposure Limits	
		ST	10,000000	USA NIOSH Recommended	
			mg/m3	Exposure Limits	
			iratory Tract irritat	tion	
		Exposure by all routes should be carefully controlled to loyale ar			
		as nossible		se carefully controlled to levels as low	
		Suspected b	uman carcinogon		

TWA	5 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
TWA	5 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
Upper Resp	iratory Tract irritation	on
Not classifia	Not classifiable as a human carcinogen	
TWA	5 mg/m3	USA. OSHA - TABLE Z-1 Limits for
		Air Contaminants - 1910.1000
TWA	5 mg/m3	USA. NIOSH Recommended
		Exposure Limits
ST	10 mg/m3	USA. NIOSH Recommended
	-	Exposure Limits

Hazardous components without workplace control parameters

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industria situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, Flame retardant protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use (EN 143) respirator cartridges as a backup to engineering controls. If th full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a) Appearance Form: Pieces

b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 97.8 °C (208.0 °F) - lit.
f)	Initial boiling point and boiling range	883 °C (1621 °F) - lit.
g)	Flash point	82 °C (180 °F)
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	No data available
I)	Vapour density	No data available
m)	Relative density	0.97 g/cm3
n)	Water solubility	No data available
o)	Partition coefficient: n- octanol/water	No data available
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
<b>Oth</b> No	er safety information data available	

#### **10. STABILITY AND REACTIVITY**

10.1 Reactivity No data available

9.2

#### **10.2 Chemical stability** Stable under recommended storage conditions.

- **10.3 Possibility of hazardous reactions** Reacts violently with water.
- **10.4** Conditions to avoid Air Do not allow water to enter container. Exposure to moisture
- **10.5** Incompatible materials Oxidizing agents

# Hazardous decomposition products Other decomposition products - No data available Hazardous decomposition products formed under fire conditions. - Carbon oxides, Sodium oxides In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

No data available

Inhalation: No data available

Dermal: No data available

No data available

#### Skin corrosion/irritation No data available

Serious eye damage/eye irritation No data available

#### **Respiratory or skin sensitisation** No data available

Germ cell mutagenicity No data available

#### Carcinogenicity

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### **Reproductive toxicity**

No data available No data available

Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

#### Aspiration hazard No data available

**Additional Information** 

**RTECS:** Not available

burning sensation, Cough, wheezing, laryngitis, Shortness of breath, spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., Aspiration may lead to:, lipid pneumonia, Effects due to ingestion may include:, laxative effect, Gastrointestinal disturbance, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

No data available

- **12.2 Persistence and degradability** No data available
- **12.3 Bioaccumulative potential** No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

**12.6 Other adverse effects** No data available

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber b highly flammable. Offer surplus and nonrecyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chem scrubber.

#### **Contaminated packaging**

Dispose of as unused product.

#### 14. TRANSPORT INFORMATION

#### DOT (US)

UN number: 1428 Proper shipping name Reportable Quantity	Class: 4.3 e: Sodium RQ) :	10 lbs	Packing group: I	
Poison Inhalation Ha	zard: No			
IMDG UN number: 1428 Proper shipping name	Class: 4.3 e: SODIUM		Packing group: I	EMS-No: F-G, S-N
IATA UN number: 1428	Class: 4.3		Packing group: I	

#### **15. REGULATORY INFORMATION**

#### SARA 302 Components

Proper shipping name: Sodium

IATA Passenger: Not permitted for transport

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Reactivity Hazard, Acute Health Hazard, Chronic Health Hazard

#### Massachusetts Right To Know Components

	CAS-No.	Revision Date
Sodium	7440-23-5	1993-04-24
Paraffin oils	8012-95-1	2007-03-01
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Sodium	7440-23-5	1993-04-24
Paraffin oils	8012-95-1	2007-03-01

#### New Jersey Right To Know Components

	CAS-No.	Revision Date
Sodium	7440-23-5	1993-04-24
Paraffin oils	8012-95-1	2007-03-01

#### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### **16. OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

Asp. Tox.	Aspirati	on hazard		
Eye Dam.	Serious	eye damage		
H260	In conta	act with water releases flammable gases which may ignite spontaneously.		
H304	May be	fatal if swallowed and enters airways.		
H314	Causes	severe skin burns and eye damage.		
H318	Causes	serious eye damage.		
H350	May ca	May cause cancer.		
Skin Corr.	Skin co	Skin corrosion		
Water-react.	Substar	nces and mixtures, which in contact with water, emit flammable gases		
HMIS Rating				
Health hazard:	;	3		
Chronic Health Haza	ard:	k		
Flammability:		4		
Physical Hazard	:	2		

#### **NFPA** Rating

Health hazard:	3
Fire Hazard:	4
Reactivity Hazard:	2
Special hazard.I:	W

#### Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956 Version: 6.2

Revision Date: 05/28/2017

Print Date: 06/28/2019



#### **SAFETY DATA SHEET**

Version 6.1 Revision Date 06/17/2019 Print Date 06/29/2019

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifiers**

Product name: StyreneProduct Number: S4972Brand: Sigma-AldrichIndex-No.: 601-026-00-0CAS-No.: 100-42-5

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	: Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES
Telephone	: +1 314 771-5765
Fax	: +1 800 325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 3), H226 Acute toxicity, Inhalation (Category 4), H332 Skin irritation (Category 2), H315 Eye irritation (Category 2A), H319 Carcinogenicity (Category 2), H351 Reproductive toxicity (Category 2), H361 Specific target organ toxicity - repeated exposure (Category 1), hearing organs, H372 Short-term (acute) aquatic hazard (Category 2), H401

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Sigma-Aldrich - S4972

Page 1 of 11



Signal word	Danger
Hazard statement(s) H226 H315 H319 H332 H351 H361 H372	Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs (hearing organs) through prolonged or repeated exposure.
	Toxic to aquatic life.
Precautionary statement(s) P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/ rume/ gas/ mist/ vapours/ spray.
P204 P270	Wash skill thoroughly diter handling.
P270 P271	Use only outdoors or in a well-ventilated area
P273	Avoid release to the environment
P280	Wear protective gloves/ protective clothing/ eye protection/ face
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

## **2.3 Hazards not otherwise classified (HNOC) or not covered by GHS** Lachrymator.

Sigma-Aldrich - S4972

Page 2 of 11



#### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Formula	:	C8H8
Molecular weight	:	104.15 g/mol
CAS-No.	:	100-42-5
EC-No.	:	202-851-5
Index-No.	:	601-026-00-0

Component	Classification	Concentration
Styrene		
	Flam. Liq. 3; Acute Tox. 4; Skin Irrit. 2; Eye Irrit. 2A; Carc. 2; Repr. 2; STOT RE 1; Aquatic Acute 2; H226, H332, H315, H319, H351, H361, H372, H401	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### **4.3 Indication of any immediate medical attention and special treatment needed** No data available

Sigma-Aldrich - S4972

Page 3 of 11


## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

# Suitable extinguishing media

Dry powder Dry sand

#### **Unsuitable extinguishing media** Do NOT use water jet.

# 5.2 Special hazards arising from the substance or mixture

Carbon oxides

Container explosion may occur under fire conditions., Vapours may form explosive mixture with air.

## 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

## 5.4 Further information

Use water spray to cool unopened containers.

## **SECTION 6:** Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures** Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

## **6.2 Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

# **6.3 Methods and materials for containment and cleaning up** Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**6.4 Reference to other sections** For disposal see section 13.

## SECTION 7: Handling and storage

## 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage temperature 2 - 8 °C

Light sensitive.

Sigma-Aldrich - S4972

Page 4 of 11



Storage class (TRGS 510): 3: Flammable liquids

## 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

## **Components with workplace control parameters**

Component	CAS-No.	Value	Control parameters	Basis
Styrene	100-42-5	TWA	50 ppm	USA. NIOSH Recommended
			215 mg/m3	Exposure Limits
		ST	100 ppm	USA. NIOSH Recommended
			425 mg/m3	Exposure Limits
	Remarks	See Table	<u>Z-2</u>	
		TWA	100 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z37.15-19	69	
		CEIL	200 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z37.15-19	69	
		Peak	600 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z37.15-19	69	
		С	500 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		Skin		1
		PEL	50 ppm 215 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		Skin		
		STEL	100 ppm 425 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		Skin		
		TWA	20 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Central Ne Upper Res Peripheral Substance or Indices Not classif	rvous System in piratory Tract ir neuropathy s for which ther (see BEI® sect iable as a huma	mpairment ritation e is a Biological Exposure Index ion) n carcinogen

Sigma-Aldrich - S4972

Page 5 of 11



STEL	40 ppm	USA. ACGIH Threshold Limit Values (TLV)
Central Ner Upper Resp Peripheral Substances or Indices ( Not classifi	rvous System im piratory Tract irri neuropathy s for which there (see BEI® section able as a human	pairment tation is a Biological Exposure Index n) carcinogen

## **Biological occupational exposure limits**

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Styrene	100-42-5	Mandelic acid plus phenylglyox ylic acid	400mg/g Creatinin e	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (	As soon as	possible after exp	oosure ceases)
		Styrene	40 µg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
		End of shift (	As soon as	possible after exp	osure ceases)

## 8.2 Exposure controls

## **Appropriate engineering controls**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

## **Personal protective equipment**

## Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: > 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 32 min Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This

Sigma-Aldrich - S4972

Page 6 of 11



recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

## **Body Protection**

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

## **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a fullface respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

## Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

## SECTION 9: Physical and chemical properties

## 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid, clear Colour: colourless
b)	Odour	sweet
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: -31 °C (-24 °F) - lit.
f)	Initial boiling point and boiling range	145 - 146 °C 293 - 295 °F - lit.
g)	Flash point	32.0 °C (89.6 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 8.9 %(V) Lower explosion limit: 1.1 %(V)
k)	Vapour pressure	6 hPa at 20 °C (68 °F)
I)	Vapour density	3.6
m)	Relative density	0.906 g/cm3 at 25 °C (77 °F)
n)	Water solubility	0.05 g/l at 25 °C (77 °F) - slightly soluble
o)	Partition coefficient: n-octanol/water	No data available
p)	Auto-ignition temperature	490.0 °C (914.0 °F) 480.0 °C (896.0 °F)

Sigma-Aldrich - S4972

Page 7 of 11



- q) Decomposition No data available temperature
- r) Viscosity No data available
- s) Explosive properties No data available
- t) Oxidizing properties No data available

## 9.2 Other safety information

Relative vapour 3.6 density

## SECTION 10: Stability and reactivity

# 10.1 Reactivity

No data available

## 10.2 Chemical stability

Stable under recommended storage conditions. Contains the following stabiliser(s): 4-tert-Butylpyrocatechol (>=30 - <=50 ppm)

**10.3 Possibility of hazardous reactions** Vapours may form explosive mixture with air.

## **10.4** Conditions to avoid

May polymerize on exposure to light. Heat, flames and sparks.

**10.5 Incompatible materials** Oxidizing agents, Copper

## **10.6** Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available In the event of fire: see section 5

## SECTION 11: Toxicological information

## **11.1** Information on toxicological effects

## Acute toxicity

LD50 Oral - Rat - 2,650 mg/kg Remarks: Behavioral:Somnolence (general depressed activity). Liver:Other changes. LC50 Inhalation - Rat - 4 h - 12,000 mg/m3 LD50 Dermal - Rat - male and female - > 2,000 mg/kg (OECD Test Guideline 402) No data available

#### **Skin corrosion/irritation** Skin - Rabbit Result: Skin irritation

Sigma-Aldrich - S4972

Page 8 of 11





(OECD Test Guideline 404)

## Serious eye damage/eye irritation

Eves - Rabbit Result: Eye irritation

## **Respiratory or skin sensitisation**

Maximisation Test - Guinea pig Does not cause skin sensitisation. (OECD Test Guideline 406)

## Germ cell mutagenicity

Laboratory experiments have shown mutagenic effects.

## Carcinogenicity

This product is or contains a component that has been reported to be possibly carcinogenic based on its IARC, ACGIH, NTP, or EPA classification.

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Styrene)

- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- No component of this product present at levels greater than or equal to 0.1% is OSHA: on OSHA's list of regulated carcinogens.

## **Reproductive toxicity**

Suspected of damaging the unborn child. Suspected human reproductive toxicant

#### Specific target organ toxicity - single exposure No data available

## Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure. - hearing organs

## Aspiration hazard

No data available

## **Additional Information**

RTECS: WL3675000

Dermatitis, Central nervous system depression, Nausea, Dizziness, Headache, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Endocrine system. -

## **SECTION 12: Ecological information**

## 12.1 Toxicity

Toxicity to fish	LC50 - Pimephales promelas (fathead minnow) - 32 mg/l - 96 h
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - 4.7 mg/l - 48 h (OECD Test Guideline 202)
Toxicity to algae	IC50 - Pseudokirchneriella subcapitata (green algae) - 1.4 mg/l $$ - 72 h

## 12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d

Sigma-Aldrich - S4972

Page 9 of 11



12.3 Bioaccumulative potential

No data available

**12.4 Mobility in soil** 

No data available

## 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

## **12.6 Other adverse effects**

Toxic to aquatic life. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. No data available

## SECTION 13: Disposal considerations

## **13.1 Waste treatment methods**

## Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

## Contaminated packaging

Dispose of as unused product.

## **SECTION 14: Transport information**

## DOT (US)

UN number: 2055 Class: 3 Packing group: III Proper shipping name: Styrene monomer, stabilized Reportable Quantity (RQ): 1000 lbs Poison Inhalation Hazard: No

## IMDG

UN number: 2055 Class: 3 Packing group: III Proper shipping name: STYRENE MONOMER, STABILIZED

## ΙΑΤΑ

UN number: 2055 Class: 3 Packing group: III Proper shipping name: Styrene monomer, stabilized

## **SECTION 15: Regulatory information**

## SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

## SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

Sigma-Aldrich - S4972

Page 10 of 11

The life science business of Merck KGaA, Darmstadt, Germany operates as MilliporeSigma in the US and Canada



EMS-No: F-E, S-D

Styrene	CAS-No. 100-42-5	Revision Date 2007-07-01

## SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

#### Pennsylvania Right To Know Components

Styrene	CAS-No.	Revision Date
	100-42-5	2007-07-01

## **SECTION 16: Other information**

#### **Further information**

Copyright 2018 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.1

Revision Date: 06/17/2019

Print Date: 06/29/2019

Sigma-Aldrich - S4972

Page 11 of 11





# **SAFETY DATA SHEET**

Version 6.4 Revision Date 10/11/2020 Print Date 06/19/2021

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## **1.1 Product identifiers**

Product name:tert-ButylbenzeneProduct Number:B90602Brand:AldrichCAS-No.:98-06-6

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

## **1.3** Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich Inc. 3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES
Telephone Fax	:	+1 314 771-5765 +1 800 325-5052

## 1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

## GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 3), H226 Acute toxicity, Inhalation (Category 4), H332 Skin irritation (Category 2), H315 Aspiration hazard (Category 1), H304

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Aldrich - B90602

Page 1 of 9



Hazard statement(s)	
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H332	Harmful if inhaled.
Precautionary statement(s)	
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ eye protection/ face protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated
	clothing. Rinse skin with water/ shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable
	for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant
	foam to extinguish.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal
	plant.

## 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

TON 3: Composition	/infoi	mation on ingree	lients		
<b>Substances</b> Synonyms	:	2-Methyl-2-pheny	lpropane		
Formula Molecular weight CAS-No. EC-No.	:	C <sub>10</sub> H <sub>14</sub> 134.22 g/mol 98-06-6 202-632-4			
Component			Classification		Concentration
tert-Butylbenzene					
	Substances Synonyms Formula Molecular weight CAS-No. EC-No. Component tert-Butylbenzene	SubstancesSynonyms:Formula:Molecular weight:CAS-No.:EC-No.:Componenttert-Butylbenzene	SubstancesSynonyms: 2-Methyl-2-phenyFormula: C10H14Molecular weight: 134.22 g/molCAS-No.: 98-06-6EC-No.: 202-632-4Componenttert-Butylbenzene	Substances         Synonyms       : 2-Methyl-2-phenylpropane         Formula       : C <sub>10</sub> H <sub>14</sub> Molecular weight       : 134.22 g/mol         CAS-No.       : 98-06-6         EC-No.       : 202-632-4         Component       Classification         tert-Butylbenzene       Elam Lig. 3: Acute Tree	Substances         Synonyms       : 2-Methyl-2-phenylpropane         Formula       : C10H14         Molecular weight       : 134.22 g/mol         CAS-No.       : 98-06-6         EC-No.       : 202-632-4         Component       Classification         tert-Butylbenzene       Elam Lig. 3: Acute Tox. 4:

 tert-Butylbenzene

 Flam. Liq. 3; Acute Tox. 4;
 <= 100 %</td>

 Skin Irrit. 2; Asp. Tox. 1;
 H226, H332, H315, H304

For the full text of the H-Statements mentioned in this Section, see Section 16.

Aldrich - B90602

Page 2 of 9



## **SECTION 4: First aid measures**

## 4.1 Description of first-aid measures

## **General advice**

Show this material safety data sheet to the doctor in attendance.

## If inhaled

After inhalation: fresh air. If breathing stops: mouth-to-mouth breathing or artificial respiration. Oxygen if necessary. Immediately call in physician.

## In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

## In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

## If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

- **4.2 Most important symptoms and effects, both acute and delayed** The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
- **4.3 Indication of any immediate medical attention and special treatment needed** No data available

## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

## **Suitable extinguishing media** Foam Carbon dioxide (CO2) Dry powder

#### **Unsuitable extinguishing media** For this substance/mixture no limitations of extinguishing agents are given.

## 5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Vapors are heavier than air and may spread along floors. Forms explosive mixtures with air at elevated temperatures. Development of hazardous combustion gases or vapours possible in the event of fire.

## 5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

## 5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

Aldrich - B90602

Page 3 of 9



## **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.
- **6.2 Environmental precautions** Do not let product enter drains. Risk of explosion.
- 6.3 Methods and materials for containment and cleaning up Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.
- **6.4 Reference to other sections** For disposal see section 13.

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge. For precautions see section 2.2.

# 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Storage class (TRGS 510): 3: Flammable liquids

## 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

## Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

## 8.2 Exposure controls

## Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

## **Personal protective equipment**

## Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

## **Skin protection**

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other

Aldrich - B90602

Page 4 of 9



substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Full contact Material: Viton® Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Splash contact

Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 10 min Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M)

## **Body Protection**

Flame retardant antistatic protective clothing.

## **Respiratory protection**

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

## **Control of environmental exposure**

Do not let product enter drains. Risk of explosion.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid
b)	Odor	No data available
c)	Odor Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: -58 °C (-72 °F) - lit.
f)	Initial boiling point and boiling range	169 °C 336 °F - lit.
g)	Flash point	44 °C (111 °F)
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 5.6 %(V) Lower explosion limit: 0.8 %(V)

Aldrich - B90602

Page 5 of 9



k) Vap	or pressure	No data available
--------	-------------	-------------------

- I) Vapor density No data available
- m) Relative density 0.867 g/cm3 at 25 °C (77 °F)
- n) Water solubility No data available
- o) Partition coefficient: No data available n-octanol/water
- p) Autoignition No data available temperature
- q) Decomposition No data available temperature
- r) Viscosity No data available
- s) Explosive properties No data available
- t) Oxidizing properties No data available

## **9.2 Other safety information** No data available

## SECTION 10: Stability and reactivity

## **10.1 Reactivity**

Vapor/air-mixtures are explosive at intense warming.

## **10.2 Chemical stability**

The product is chemically stable under standard ambient conditions (room temperature) .

- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** Heating.
- **10.5 Incompatible materials** Strong oxidizing agents

## 10.6 Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available In the event of fire: see section 5

## **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

## Acute toxicity

LD50 Oral - Rat - 3,045 mg/kg Remarks: (RTECS) LC50 Inhalation - Rat - 4 h - 4.6 mg/l Remarks: (External MSDS) Dermal: No data available No data available

Aldrich - B90602

Page 6 of 9



## Skin corrosion/irritation

Skin - Rabbit Result: Severe irritations (OECD Test Guideline 404)

## Serious eye damage/eye irritation

Eyes - Rabbit Result: No eye irritation (OECD Test Guideline 405)

## Respiratory or skin sensitization

Sensitisation test (Magnusson and Kligman): Result: negative Remarks: (External MSDS)

## Germ cell mutagenicity

No data available

## Carcinogenicity

- IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

## **Reproductive toxicity**

No data available

Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

## Aspiration hazard

Aspiration hazard, Aspiration may cause pulmonary edema and pneumonitis.

# Additional Information

RTECS: CY9120000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

After absorption: Nausea, Unconsciousness, Headache In high concentrations: narcosis Other dangerous properties can not be excluded. Handle in accordance with good industrial hygiene and safety practice.

## **SECTION 12: Ecological information**

## **12.1 Toxicity**

Toxicity to fish

LC50 - Leuciscus idus (Golden orfe) - 65 mg/l Remarks: (Lit.)

Aldrich - B90602

Page 7 of 9



Toxicity to daphnia EC50 - Daphnia magna (Water flea) - 41 mg/l and other aquatic Remarks: (Lit.)

- 12.2 Persistence and degradability No data available
- **12.3 Bioaccumulative potential** No data available
- **12.4 Mobility in soil** No data available

## 12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

## **12.6 Other adverse effects**

Formation of health-hazardous mixtures possible with water. Discharge into the environment must be avoided.

## **SECTION 13: Disposal considerations**

#### **13.1 Waste treatment methods**

## Product

Waste material must be disposed of in accordance with the national and loc No mixing with other waste. Handle uncleaned containers like the product See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

## **SECTION 14: Transport information**

#### DOT (US)

UN number: 2709 Class: 3 Packing group: III Proper shipping name: Butyl benzenes Reportable Quantity (RQ): • Marine pollutant: yesPoison Inhalation Hazard: No

## IMDG

UN number: 2709 Class: 3 Packing group: III EMS-No: F-E, S-D Proper shipping name: BUTYLBENZENES Marine pollutant : yes Marine pollutant : yes

## ΙΑΤΑ

UN number: 2709 Class: 3 Packi Proper shipping name: Butylbenzenes

Packing group: III

## **SECTION 15: Regulatory information**

## SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

Aldrich - B90602

Page 8 of 9



## SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

## SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard

## Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components tert-Butylbenzene	CAS-No.	Revision Date
,	98-06-6	1993-04-24
New Jersey Right To Know Components		
tert-Butylbenzene	CAS-No.	Revision Date
	98-06-6	1993-04-24

## **SECTION 16: Other information**

## **Further information**

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.4

Revision Date: 10/11/2020

Print Date: 06/19/2021

Aldrich - B90602

Page 9 of 9



# SIGMA-ALDRICH

# SAFETY DATA SHEET

Version 4.11 Revision Date 06/28/2017 Print Date 06/22/2019

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

1.1	Product identifiers Product name	:	Tetrachloroethylene
	Product Number Brand Index-No.	:	371696 Sigma-Aldrich 602-028-00-4
	CAS-No.	:	127-18-4
1.2	Relevant identified uses	of the	substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
Telephone Fax	:	+1 800-325-5832 +1 800-325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Skin irritation (Category 2), H315 Eye irritation (Category 2A), H319 Skin sensitisation (Category 1), H317 Carcinogenicity (Category 2), H351 Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336 Acute aquatic toxicity (Category 2), H401 Chronic aquatic toxicity (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Warning

Hazard statement(s)	
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P391	Collect spillage.
P403 + P233 P405	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/ container to an approved waste disposal plant.
	1

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

## **3. COMPOSITION/INFORMATION ON INGREDIENTS**

## 3.1 Substances

Synonyms	:	Perchloroethylene PCE
Formula	:	C <sub>2</sub> Cl <sub>4</sub>
Molecular weight	:	165.83 g/mol
CAS-No.	:	127-18-4
EC-No.	:	204-825-9

#### Hazardous components

Index-No.

Component	Classification	Concentration
Tetrachloroethylene		
	Skin Irrit. 2; Eye Irrit. 2A; Skin	90 - 100 %
	Sens. 1; Carc. 2; STOT SE 3;	
	Aquatic Acute 2; Aquatic	
	Chronic 2; H315, H317, H319,	
	H336, H351, H411	

For the full text of the H-Statements mentioned in this Section, see Section 16.

: 602-028-00-4

## 4. FIRST AID MEASURES

## 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

## **4.2** Most important symptoms and effects, both acute and delayed The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**4.3** Indication of any immediate medical attention and special treatment needed No data available

## **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture No data available

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information No data available

## 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas.

For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

- 6.3 Methods and materials for containment and cleaning up Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for
- 6.4 Reference to other sections

disposal.

For disposal see section 13.

#### 7. HANDLING AND STORAGE

# 7.1 Precautions for safe handling Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

- For precautions see section 2.2.
   7.2 Conditions for safe storage, including any incompatibilities
  - **Conditions for safe storage, including any incompatibilities** Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

## 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 Control parameters

## Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis		
			parameters			
Tetrachloroethylene	127-18-4	TWA	25.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)		
	Remarks	Central Nervous System impairment				
		Substances	for which there is a	a Biological Exposure Index or Indices		
		(see BEI® se	ection)	0		
		Confirmed a	nimal carcinogen v	vith unknown relevance to humans		
		STEL	100.000000	USA. ACGIH Threshold Limit Values		
			ppm	(TLV)		
		Central Nerv	l /ous System impai	rment		
		Substances	for which there is a	a Biological Exposure Index or Indices		
		(see BEI® se	ection)			
		Confirmed a	nimal carcinogen v	vith unknown relevance to humans		
		Potential Oc	cupational Carcino	gen		
		Minimize wo	rkplace exposure of	concentrations.		
		See Append	ix A			
S		See Table Z	-2	1		
		TWA	100.000000	USA. Occupational Exposure Limits		
			ppm	(OSHA) - Table Z-2		
		CEIL	200.000000	USA. Occupational Exposure Limits		
			ppm	(OSHA) - Table Z-2		
		Peak	300.000000	USA. Occupational Exposure Limits		
			ppm	(OSHA) - Table Z-2		
		TWA	25 ppm	USA. ACGIH Threshold Limit Values		
				(TLV)		
		Central Nerv	ous System impai	rment		
		Substances	for which there is a	a Biological Exposure Index or Indices		
		(see BEI® s	ection)			
		Confirmed a	nimal carcinogen v	vith unknown relevance to humans		
		STEL	100 ppm	USA. ACGIH Threshold Limit Values (TLV)		
		Central Nerv	ous System impair	rment		
		Substances	for which there is a	a Biological Exposure Index or Indices		
		(see BEI® se	ection)			
		Confirmed animal carcinogen with unknown relevance to humans				
		Potential Oc	cupational Carcino	gen		
		Minimize wo	rkplace exposure of	concentrations.		
		See Append	ix A			
		See Table Z	-2			

TWA	100 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
CEIL	200 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
Peak	300 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
TWA	25 ppm 170 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
STEL	100 ppm 685 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
С	300 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
PEL	25 ppm 170 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

#### **Biological occupational exposure limits**

Component	CAS-No.	Parameters	Value	Biological	Basis
·				specimen	
				specifien	
Tetrachloroethylene	127-18-4	Tetrachloroet	3ppm	In end-exhaled air	ACGIH - Biological
		hvlene			Exposure Indices
		nyiono			
					(BEI)
	Remarks	Prior to shift (1	6 hours after	r exposure ceases)	
		Tetrachloroet	0.5000	In blood	ACGIH - Biological
		hvlene	ma/l		Exposure Indices
					(DEI)
		Prior to shift (1	6 hours after	r exposure ceases)	
		Tetrachloroet	3ppm	In end-exhaled air	ACGIH - Biological
		hvlene			Exposure Indices
		nyiono			
		Prior to shift (1	6 hours after	r exposure ceases)	
		Tetrachloroet	0.5 mg/l	In blood	ACGIH - Biological
		hvlene	-		Exposure Indices
		,			(BEI)
	+			l	
		Prior to shift (16 hours after exposure ceases)			

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### **Eye/face protection**

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.2 mm Break through time: 49 min Material tested:Dermatril® P (KCL 743 / Aldrich Z677388, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### **Control of environmental exposure**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid, clear Colour: colourless
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: -22 °C (-8 °F) - lit.
f)	Initial boiling point and boiling range	121 °C (250 °F) - lit.
g)	Flash point	No data available
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	25.3 hPa (19.0 mmHg) at 25.0 °C (77.0 °F) 17.3 hPa (13.0 mmHg) at 20.0 °C (68.0 °F)
I)	Vapour density	No data available
m)	Relative density	1.623 g/cm3 at 25 °C (77 °F)
n)	Water solubility	0.15 g/l at 25 °C (77 °F)
o)	Partition coefficient: n- octanol/water	log Pow: 2.53 at 23 °C (73 °F)
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available

- t) Oxidizing properties
- No data available

## 9.2 Other safety information

Surface tension

32.1 mN/m at 20 °C (68 °F)

## **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity No data available

## 10.2 Chemical stability

Stable under recommended storage conditions.

- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5** Incompatible materials Strong oxidizing agents, Strong bases

#### 10.6 Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Carbon oxides, Hydrogen chloride gas Other decomposition products - No data available In the event of fire: see section 5

## **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - female - 3,385 mg/kg (OECD Test Guideline 401)

Inhalation: No data available

Dermal: No data available

No data available

#### Skin corrosion/irritation

Skin - Rabbit Result: Skin irritation - 4 h (OECD Test Guideline 404)

#### Serious eye damage/eye irritation

Eyes - Rabbit Result: Mild eye irritation - 24 h

#### Respiratory or skin sensitisation

- Mouse Result: May cause sensitisation by skin contact. (OECD Test Guideline 429)

#### Germ cell mutagenicity

Hamster ovary Result: negative

OECD Test Guideline 474 Mouse - male Result: negative

#### Carcinogenicity

Limited evidence of carcinogenicity in animal studies

#### NTP: RAHC - Reasonably anticipated to be a human carcinogen (Tetrachloroethylene)

No component of this product present at levels greater than or equal to 0.1% is identified as a OSHA: carcinogen or potential carcinogen by OSHA.

#### **Reproductive toxicity**

No data available

No data available

Specific target organ toxicity - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

#### Additional Information

Repeated dose Mouse - female - Oral - LOAEL : 390 mg/kg toxicity RTECS: KX3850000

narcosis, Liver injury may occur., Kidney injury may occur.

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

12.3

	Toxicity to fish	flow-through test LC50 - Oncorhynchus mykiss (rainbow trout) - 5 mg/l $$ - 96 h
	Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - 7.50 mg/l - 48 h
	Toxicity to algae	static test EC50 - Skeletonema costatum - > 16 mg/l - 7 h
12.2	Persistence and degrad Biodegradability	dability aerobic - Exposure time 28 d Result: 11 % - Not readily biodegradable. (OECD Test Guideline 301C)
2.3	Bioaccumulative potentia Bioaccumulation	Il Lepomis macrochirus (Bluegill) - 21 d - 0.00343 mg/l
		Bioconcentration factor (BCF): 49

12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

## 13. DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

## Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

**14. TRANSPORT INFORMATION** 

## DOT (US)

UN number: 1897 Class: 6.1 Packing group: III Proper shipping name: Tetrachloroethylene Reportable Quantity (RQ): 100 lbsReportable Quantity (RQ): 100 lbs Poison Inhalation Hazard: No

## IMDG

UN number: 1897 Class: 6.1 Packing group: III EMS-No: F-A, S-A Proper shipping name: TETRACHLOROETHYLENE Marine pollutant: yes

## IATA

UN number: 1897	Class: 6.1	Packing group: III
Proper shipping name:	Tetrachloroethylene	

## 15. REGULATORY INFORMATION

## SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

## SARA 313 Components

Tetrachloroethylene	127-18-4	2007-07-01		
	CAS-No.	Revision Date		
The following components are subject to reporting levels established by SARA Title III, Section 313:				

## SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

Reportable Quantity D039 lbs		
Massachusetts Right To Know Components		
	CAS-No.	Revision Date
Tetrachloroethylene	127-18-4	2007-07-01
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Tetrachloroethylene	127-18-4	2007-07-01
<b>T</b> ( ) 11 ( ) 1	CAS-NO.	Revision Date
letrachloroethylene	127-18-4	2007-07-01
New Jersey Right To Know Components		
	CAS-No.	Revision Date
Tetrachloroethylene	127-18-4	2007-07-01
California Prop. 65 Components		
WARNING! This product contains a chemical known to the	CAS-No.	Revision Date
State of California to cause cancer. Tetrachloroethylene	127-18-4	2007-09-28

## **16. OTHER INFORMATION**

Full text of H-Statements referred to under sections 2 and 3.

Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Carc.	Carcinogenicity

Eye Irrit.	Eye irritation
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects

#### **HMIS Rating**

Health hazard:	3
Chronic Health Hazard:	*
Flammability:	0
Physical Hazard	0
NFPA Rating	
Health hazard:	2

	~
Fire Hazard:	0
Reactivity Hazard:	0

#### Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 4.11

Revision Date: 06/28/2017

Print Date: 06/22/2019



# **SAFETY DATA SHEET**

Version 6.3 Revision Date 03/06/2019 Print Date 06/22/2019

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## **1.1** Product identifiers

Product name : Toluene Product Number : 244511 Brand : Sigma-Aldrich Index-No. : 601-021-00-3 CAS-No. : 108-88-3

## **1.2** Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

## 1.3 Details of the supplier of the safety data sheet

Company	: Sigma-Aldrich Inc.		
	3050 Spruce Street		
	ST. LOUIS MO 63103		
	UNITED STATES		
Telephone	: +1 314 771-5765		
Fax	: +1 800 325-5052		

## **1.4 Emergency telephone number**

Emergency Phone # : +1-703-527-3887

## **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

## GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Skin irritation (Category 2), H315 Reproductive toxicity (Category 2), H361 Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336 Specific target organ toxicity - repeated exposure (Category 2), H373 Aspiration hazard (Category 1), H304 Short-term (acute) aquatic hazard (Category 2), H401

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 GHS Label elements, including precautionary statements

Danger

Pictogram



Signal word

Sigma-Aldrich - 244511

Page 1 of 11



Hazard statement(s)	
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated
1373	
H401	Toxic to aquatic life
Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood
D210	Keen away from heat/sparks/open flames/hot surfaces. No
F210	smoking
2220	Silloking. Koon container tightly closed
F233	Cround/bond container and receiving equipment
P240 D241	Ground/Dond Container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/ tume/ gas/ mist/ vapours/ spray.
P264	wash skin thoroughly after handling.
P2/1	Use only outdoors or in a well-ventilated area.
P2/3	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated
	clothing. Rinse skin with water/shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable
	for breathing. Call a POISON CENTER/doctor if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant
	foam to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal
	plant.

# 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

## **SECTION 3:** Composition/information on ingredients

# 3.1 Substances

Formula	:	С <sub>7</sub> Н8
Molecular weight	:	92.14 g/mol
CAS-No.	:	108-88-3
EC-No.	:	203-625-9

Sigma-Aldrich - 244511

Page 2 of 11



Index-No.

Component	Classification Concentrat	
Toluene		
	Flam. Liq. 2; Skin Irrit. 2;	<= 100 %
	Repr. 2; STOT SE 3; STOT	
	RE 2; Asp. Tox. 1; Aquatic	
	Acute 2; H225, H315,	
	H361d, H336, H373,	
	H304, H401	
	Concentration limits:	
	20 %: STOT SE 3, H336;	

For the full text of the H-Statements mentioned in this Section, see Section 16.

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

## **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

## If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

## In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

## In case of eye contact

Flush eyes with water as a precaution.

## If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

## 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**4.3 Indication of any immediate medical attention and special treatment needed** No data available

## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

**Suitable extinguishing media** Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

**5.2 Special hazards arising from the substance or mixture** Carbon oxides

## **5.3 Advice for firefighters** Wear self-contained breathing apparatus for firefighting if necessary.

Sigma-Aldrich - 244511

Page 3 of 11



## 5.4 Further information

Use water spray to cool unopened containers.

## **SECTION 6: Accidental release measures**

## **6.1 Personal precautions, protective equipment and emergency procedures** Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

## **6.2 Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

## **6.3 Methods and materials for containment and cleaning up** Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13).

**6.4** Reference to other sections For disposal see section 13.

# SECTION 7: Handling and storage

## 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment.Keep away from sources of ignition - No smoking.Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Handle and store under inert gas. Storage class (TRGS 510): 3: Flammable liquids

## 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

## **Components with workplace control parameters**

Sigma-Aldrich - 244511

Page 4 of 11



Component	CAS-No.	Value	Control	Basis
Toluene	108-88-3	TWA	100 ppm 375 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		STEL	150 ppm 560 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		TWA	200 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
	Remarks	Z37.12-19	67	
		CEIL	300 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z37.12-19	67	
		Peak	500 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z37.12-1967		
		TWA	20 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Visual impairment Female reproductive Pregnancy loss 2018 Adoption Substances for which there is a Biological Exposure Inc or Indices (see BEI® section) Not classifiable as a human carcinogen		is a Biological Exposure Index on) carcinogen
		TWA	100 ppm 375 mg/m3	USA. NIOSH Recommended Exposure Limits
		ST	150 ppm 560 mg/m3	USA. NIOSH Recommended

## Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Toluene	108-88-3	Toluene	0.02 mg/l	In blood	ACGIH - Biological Exposure Indices (BEI)
	Remarks	Prior to last	shift of wor	kweek	
		Toluene	0.03 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
		End of shift (	As soon as	possible after exp	osure ceases)
		o-Cresol	0.3mg/g Creatinin e	Urine	ACGIH - Biological Exposure Indices (BEI)
		End of shift (	As soon as	possible after exp	osure ceases)

## Predicted No Effect Concentration (PNEC)

Compartment	Value
Soil	2.89 mg/kg

Sigma-Aldrich - 244511

Page 5 of 11



Marine water	0.68 mg/l
Fresh water	0.68 mg/l
Marine sediment	16.39 mg/kg
Fresh water sediment	16.39 mg/kg
Sewage treatment plant	13.61 mg/l
Aquatic intermittent release	0.68 mg/l

## 8.2 Exposure controls

## Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

## **Personal protective equipment**

## Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

## **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

## **Body Protection**

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

## **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a fullface respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Sigma-Aldrich - 244511

Page 6 of 11



## **Control of environmental exposure**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

## SECTION 9: Physical and chemical properties

## 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid Colour: colourless
b)	Odour	aromatic
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: -93 °C (-135 °F)
f)	Initial boiling point and boiling range	110 - 111 °C 230 - 232 °F
g)	Flash point	4.0 °C (39.2 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 7 %(V) Lower explosion limit: 1.2 %(V)
k)	Vapour pressure	29.1 hPa at 20.0 °C (68.0 °F)
I)	Vapour density	No data available
m)	Relative density	0.865 g/mL at 25 °C (77 °F)
n)	Water solubility	0.5 g/l at 15 °C (59 °F)
o)	Partition coefficient: n-octanol/water	No data available
p)	Auto-ignition temperature	535.0 °C (995.0 °F)
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available

9.2 Other safety information No data available

## SECTION 10: Stability and reactivity

#### **10.1** Reactivity

No data available

Sigma-Aldrich - 244511

Page 7 of 11



## **10.2 Chemical stability** Stable under recommended storage conditions.

- **10.3 Possibility of hazardous reactions** Vapours may form explosive mixture with air.
- **10.4 Conditions to avoid** Heat, flames and sparks.

**10.5 Incompatible materials** Strong oxidizing agents

**10.6 Hazardous decomposition products** Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available In the event of fire: see section 5

## **SECTION 11: Toxicological information**

## **11.1** Information on toxicological effects

## Acute toxicity

LD50 Oral - Rat - male - 5,580 mg/kg (Tested according to Directive 92/69/EEC.) LC50 Inhalation - Rat - male and female - 4 h - 25.7 mg/l (OECD Test Guideline 403) LD50 Dermal - Rabbit - 12,124 mg/kg Remarks: (ECHA) No data available

# Skin corrosion/irritation

Skin - Rabbit Result: Irritating to skin. - 4 h Remarks: (ECHA)

## Serious eye damage/eye irritation

Eyes - Rabbit Result: No eye irritation (OECD Test Guideline 405)

## Respiratory or skin sensitisation

No data available

## Germ cell mutagenicity

In vitro mammalian cell gene mutation test Mouse lymphoma test Result: negative Ames test S. typhimurium Result: negative

Rat - Bone marrow Result: negative (ECHA)

## Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Sigma-Aldrich - 244511

Page 8 of 11



- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

## **Reproductive toxicity**

Suspected of damaging the unborn child.

#### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness. - Central nervous system

## Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure. - Central nervous system

#### Aspiration hazard

Aspiration hazard, Aspiration may cause pulmonary oedema and pneumonitis.

#### **Additional Information**

RTECS: XS5250000

Drowsiness, irritant effects, Dizziness, Convulsions, Headache, Nausea, Vomiting, Circulatory collapse, somnolence, inebriation, Unconsciousness, respiratory arrest, CNS disorders, respiratory paralysis, death To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

## **SECTION 12: Ecological information**

## 12.1 Toxicity

Toxicity to fish	LC50 - Oncorhynchus mykiss (rainbow trout) - 5.8 mg/l - 96 h Remarks: (ECOTOX Database)			
	NOEC - Pimephales promelas (fathead minnow) - 5.44 mg/l - 7 d			
Toxicity to daphnia and other aquatic invertebrates	Immobilization EC50 - Daphnia magna (Water flea) - 6 mg/l - 48 h Remarks: (ECOTOX Database)			
Toxicity to algae	EC50 - Chlorella vulgaris (Fresh water algae) - 245.00 mg/l - 24 h Remarks: (ECOTOX Database)			
	EC50 - Pseudokirchneriella subcapitata (green algae) - 10.00 mg/l - 24 h Remarks: (ECOTOX Database)			
Persistence and degradability				

## Biodegradability aerobic - Exposure time 20 d Result: 86 % - Readily biodegradable. Remarks: (IUCLID)

#### 12.3 Bioaccumulative potential

Bioaccumulation Leuciscus idus (Golden orfe) - 3 d - 0.05 mg/l(Toluene)

Sigma-Aldrich - 244511

12.2

Page 9 of 11


#### **12.4 Mobility in soil**

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### **12.6 Other adverse effects**

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life. No data available

#### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

#### Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information		
<b>DOT (US)</b> UN number: 1294 Class: 3 Proper shipping name: Toluene Reportable Quantity (RQ): 1000 lbs Poison Inhalation Hazard: No	Packing group: II	
IMDG UN number: 1294 Class: 3 Proper shipping name: TOLUENE	Packing group: II	EMS-No: F-E, S-D
IATA UN number: 1294 Class: 3 Proper shipping name: Toluene	Packing group: II	

#### **SECTION 15: Regulatory information**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

CAS-No. Revision Date

Sigma-Aldrich - 244511

Page 10 of 11

The life science business of Merck KGaA, Darmstadt, Germany operates as MilliporeSigma in the US and Canada



Toluene	108-88-3	2007-07-01
SARA 311/312 Hazards Fire Hazard, Acute Health Hazard, Chronic Health Haza	ard	
Massachusetts Right To Know Components		
Toluene	CAS-No. 108-88-3	Revision Date 2007-07-01
Pennsylvania Right To Know Components		
Toluene	CAS-No. 108-88-3	Revision Date 2007-07-01
California Prop. 65 Components		
, which is/are known to the State of California to	CAS-No.	Revision Date
cause birth defects or other reproductive harm. For	108-88-3	2009-02-01
www P65Warnings ca gov Toluene		

#### **SECTION 16: Other information**

#### **Further information**

Copyright 2018 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.3

Revision Date: 03/06/2019

Print Date: 06/22/2019

Sigma-Aldrich - 244511

Page 11 of 11

The life science business of Merck KGaA, Darmstadt, Germany operates as MilliporeSigma in the US and Canada



# SIGMA-ALDRICH

#### SAFETY DATA SHEET

Version 4.10 Revision Date 01/04/2018 Print Date 06/28/2019

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

1.1	Product identifiers Product name	:	Trichloroethylene
	Product Number Brand Index-No.	:	251402 Sigma-Aldrich 602-027-00-9
	CAS-No.	:	79-01-6
1.2	Relevant identified uses	of the	substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
Telephone Fax	:	+1 800-325-5832 +1 800-325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Skin irritation (Category 2), H315 Eye irritation (Category 2A), H319 Germ cell mutagenicity (Category 2), H341 Carcinogenicity (Category 1B), H350 Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336 Acute aquatic toxicity (Category 3), H402 Chronic aquatic toxicity (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)	
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear eye protection/ face protection.
P280	Wear protective gloves.
P281	Use personal protective equipment as required.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

#### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Synonyms	:	TCE Trichloroethene
Formula	:	C <sub>2</sub> HCl <sub>3</sub>
Molecular weight	:	131.39 g/mol
CAS-No.	:	79-01-6
EC-No.	:	201-167-4
Index-No.	:	602-027-00-9

#### Hazardous components

<b>^</b>		0 1 1
Component	Classification	Concentration
Trichloroethylene		
	Skin Irrit. 2; Eye Irrit. 2A; Muta.	90 - 100 %
	2; Carc. 1B; STOT SE 3;	
	Aquatic Acute 3; Aquatic	
	Chronic 3; H315, H319, H336,	
	H341, H350, H412	

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### **4.2** Most important symptoms and effects, both acute and delayed The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**4.3** Indication of any immediate medical attention and special treatment needed No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture No data available

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information No data available

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas.

For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Light sensitive. Handle and store under inert gas. Storage class (TRGS 510): 6.1D: Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis			
Trichloroethylene	79-01-6	TWA	10.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)			
	Remarks	Central Nerv cognitive de Renal toxicit	vous System impai crement tv	rment			
		Substances (see BEI® s	for which there is a ection)	a Biological Exposure Index or Indices			
		Suspected h	numan carcinogen				
		STEL	25.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)			
		Central Nerv	vous System impai	rment			
		cognitive de	crement				
		Renal toxicit	ty				
		Substances (see BEI® s	a Biological Exposure Index or Indices				
		Suspected h	numan carcinogen				
		Potential Occupational Carcinogen See Appendix C					
		See Appendix A					
		See Table Z	2-2				
		TWA	100.000000 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2			
		Z37.19-196					
		CEIL	200.000000 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2			
		737 19-196	7				
		Peak	300.000000 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2			
		Z37.19-196	7	1			
		TWA	100 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2			
		Z37.19-196	7				
		CEIL	200 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2			
		Z37.19-196	7				
		Peak	300 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2			
		Z37.19-196	7				

STEL	100 ppm 537 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
С	300 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
PEL	25 ppm 135 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

#### **Biological occupational exposure limits**

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
	-	Trichloroaceti c acid	15.0000 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift at e	end of workv	veek	
		Trichloroetha nol	0.5000 mg/l	In blood	ACGIH - Biological Exposure Indices (BEI)
		End of shift at e	end of workv	veek	
		Trichloroethyl ene		In blood	ACGIH - Biological Exposure Indices (BEI)
		End of shift at e	end of workv	veek	
		Trichloroethyl ene		In end-exhaled air	ACGIH - Biological Exposure Indices (BEI)
		End of shift at end of workweek			

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### **Eye/face protection**

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### **Control of environmental exposure**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid, clear Colour: colourless
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: -84.8 °C (-120.6 °F) - lit.
f)	Initial boiling point and boiling range	86.7 °C (188.1 °F) - lit.
g)	Flash point	No data available
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 10.5 %(V) Lower explosion limit: 8 %(V)
k)	Vapour pressure	81.3 hPa (61.0 mmHg) at 20.0 °C (68.0 °F)
I)	Vapour density	No data available
m)	Relative density	1.463 g/mL at 25 °C (77 °F)
n)	Water solubility	No data available
o)	Partition coefficient: n- octanol/water	log Pow: 2.29log Pow: 5
p)	Auto-ignition temperature	410.0 °C (770.0 °F)
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Othe	r safety information	

#### No data available

#### **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity No data available

9.2

#### 10.2 Chemical stability

Stable under recommended storage conditions.

- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available

**10.5** Incompatible materials Oxidizing agents, Strong bases, Magnesium

#### 10.6 Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Carbon oxides, Hydrogen chloride gas Other decomposition products - No data available In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - 4,920 mg/kg

LC50 Inhalation - Mouse - 4 h - 8450 ppm

LD50 Dermal - Rabbit - > 20,000 mg/kg

No data available

#### Skin corrosion/irritation

Skin - Rabbit Result: Severe skin irritation - 24 h

Serious eye damage/eye irritation Eyes - Rabbit Result: Eye irritation - 24 h

Respiratory or skin sensitisation No data available

#### Germ cell mutagenicity

Laboratory experiments have shown mutagenic effects. In vitro tests showed mutagenic effects

#### Carcinogenicity

This product is or contains a component that has been reported to be probably carcinogenic based on its IARC, OSHA, ACGIH, NTP, or EPA classification.

Possible human carcinogen

- NTP: RAHC Reasonably anticipated to be a human carcinogen (Trichloroethylene)
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

No data available

No data available

Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

#### **Additional Information**

RTECS: KX4550000

burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, Exposure to and/or consumption of alcohol may increase toxic effects., Gastrointestinal disturbance, Kidney injury may occur., narcosis To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

Toxicity to fish	LC50 - Pimephales promelas (fathead minnow) - 41 mg/l - 96.0 h		
	LOEC - other fish - 11 mg/l - 10.0 d		
	NOEC - Oryzias latipes - 40 mg/l - 10.0 d		
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - 18.00 mg/l - 48 h		

Toxicity to algae IC50 - Pseudokirchneriella subcapitata (green algae) - 175.00 mg/l - 96 h

#### 12.2 Persistence and degradability No data available

# **12.3 Bioaccumulative potential** Does not bioaccumulate.

12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

Packing group: III

#### **Contaminated packaging**

Dispose of as unused product.

#### **14. TRANSPORT INFORMATION**

#### DOT (US)

UN number: 1710 Class: 6.1 Proper shipping name: Trichloroethylene Reportable Quantity (RQ): 100 lbs Poison Inhalation Hazard: No

IMDG

UN number: 1710 Class: 6.1 Packing group: III Proper shipping name: TRICHLOROETHYLENE

EMS-No: F-A, S-A

ΙΑΤΑ

UN number: 1710 Class: 6.1

Sigma-Aldrich - 251402

Packing group: III

#### **15. REGULATORY INFORMATION**

#### SARA 302 Components No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302. SARA 313 Components The following components are subject to reporting levels established by SARA Title III, Section 313: CAS-No. **Revision Date** Trichloroethylene 79-01-6 2007-07-01 SARA 311/312 Hazards Acute Health Hazard, Chronic Health Hazard Massachusetts Right To Know Components CAS-No. **Revision Date** Trichloroethylene 79-01-6 2007-07-01 Pennsylvania Right To Know Components CAS-No. **Revision Date** Trichloroethylene 2007-07-01 79-01-6 New Jersey Right To Know Components CAS-No. **Revision Date** Trichloroethylene 79-01-6 2007-07-01 California Prop. 65 Components WARNING! This product contains a chemical known to the CAS-No. **Revision Date** State of California to cause cancer. 79-01-6 2011-09-01 Trichloroethylene CAS-No. WARNING: This product contains a chemical known to the **Revision Date** State of California to cause birth defects or other reproductive 79-01-6 2011-09-01 harm. Trichloroethylene

#### 16. OTHER INFORMATION

#### Full text of H-Statements referred to under sections 2 and 3.

Acute aquatic toxicity
Chronic aquatic toxicity
Carcinogenicity
Eye irritation
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of causing genetic defects
May cause cancer.
Harmful to aquatic life.
-

#### HMIS Rating Health bazard:

Health hazard:	2
Chronic Health Hazard:	*
Flammability:	0
Physical Hazard	0
NFPA Rating	
Health hazard:	2
Fire Hazard:	0
Reactivity Hazard:	0

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 4.10

Revision Date: 01/04/2018

Print Date: 06/28/2019

# SIGMA-ALDRICH

#### SAFETY DATA SHEET

Version 5.10 Revision Date 08/06/2018 Print Date 06/28/2019

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

# 1.1Product identifiers<br/>Product name: XylenesProduct Number: 214736Brand: AldrichIndex-No.: 601-022-00-9CAS-No.: 1330-20-7

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
Telephone Fax	:	+1 800-325-5832 +1 800-325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 3), H226 Acute toxicity, Inhalation (Category 4), H332 Skin irritation (Category 2), H315 Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335 Specific target organ toxicity - repeated exposure, Inhalation (Category 2), Central nervous system, Liver, Kidney, H373 Aspiration hazard (Category 1), H304 Acute aquatic toxicity (Category 2), H401

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word	Danger
Hazard statement(s)	
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs (Central nervous system, Liver, Kidney)
	through prolonged or repeated exposure if inhaled.
H401	Toxic to aquatic life.

Precautionary statement(s)	
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ eye protection/ face protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing.
	Rinse skin with water/shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for
	breathing. Call a POISON CENTER/doctor if you feel unwell.
P314	Get medical advice/ attention if you feel unwell.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to
	extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

#### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Synonyms	: Xylene mixture of isomers
Formula	: C <sub>8</sub> H <sub>10</sub>
Molecular weight	: 106.17 g/mol
CAS-No.	: 1330-20-7
EC-No.	: 215-535-7
Index-No.	: 601-022-00-9
Registration number	: 01-2119488216-32-XXXX

#### Hazardous components

Component	Classification	Concentration
Xylene		
	Flam. Liq. 3; Acute Tox. 4;	90 - 100 %
	Skin Irrit. 2; STOT SE 3; STOT	
	RE 2; Asp. Tox. 1; Aquatic	
	Acute 2; H226, H304, H315,	
	H332, H335, H373, H401	

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

# **4.3** Indication of any immediate medical attention and special treatment needed No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### **Suitable extinguishing media** Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture No data available

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

Use water spray to cool unopened containers.

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510): 3: Flammable liquids

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Xylene	1330-20-7	STEL	150 ppm 655 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		С	300 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		PEL	100 ppm 435 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		TWA	100 ppm 435 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
	Remarks	The value in	mg/m3 is approxin	nate.
		TWA	100 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Central Nervous System impairment Upper Respiratory Tract irritation Eye irritation Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen		
		STEL	150 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Central Nervous System impairment Upper Respiratory Tract irritation Eye irritation Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen		

#### **Biological occupational exposure limits**

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
	-	Methylhippuri c acids	1.5g/g creatinine	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (As soon as possible after exposure ceases)			

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

#### Full contact

Material: Fluorinated rubber

Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 35 min Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: clear, liquid Colour: colourless
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	< 0 °C (< 32 °F)
f)	Initial boiling point and boiling range	137 - 140 °C (279 - 284 °F) - lit.
g)	Flash point	25 °C (77 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 7 %(V) Lower explosion limit: 1.1 %(V)
k)	Vapour pressure	24 hPa (18 mmHg) at 37.70 °C (99.86 °F)
I)	Vapour density	3.67 - (Air = 1.0)
m)	Relative density	0.86 g/mL at 25 °C (77 °F)
n)	Water solubility	No data available
o)	Partition coefficient: n- octanol/water	No data available
p)	Auto-ignition	No data available

temperature

- q) Decomposition No data available temperature
- r) Viscosity No data available
- s) Explosive properties No data available
- t) Oxidizing properties No data available

#### 9.2 Other safety information

Relative vapour density 3.67 - (Air = 1.0)

#### **10. STABILITY AND REACTIVITY**

10.1 Reactivity

No data available

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** Vapours may form explosive mixture with air.
- **10.4 Conditions to avoid** Heat, flames and sparks.

**10.5** Incompatible materials Strong oxidizing agents

#### 10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available In the event of fire: see section 5

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

Acute toxicity LD50 Oral - Rat - male - 3,523 mg/kg Remarks: (ECHA)

Skin corrosion/irritation

Skin - Rabbit Result: Irritations Remarks: (IUCLID)

Drying-out effect resulting in rough and chapped skin. After long-term exposure to the chemical: Dermatitis

#### Serious eye damage/eye irritation Respiratory or skin sensitisation

In animal experiments: - Mouse Result: Does not cause skin sensitisation. (OECD Test Guideline 429)

#### Germ cell mutagenicity

Mutagenicity (mammal cell test): chromosome aberration. Result: negative (National Toxicology Program)

Ames test Salmonella typhimurium Result: negative

#### Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

#### Specific target organ toxicity - single exposure

May cause respiratory irritation. - Respiratory system

Acute oral toxicity - Gastrointestinal disturbance

Acute inhalation toxicity - mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract, Inhalation may lead to the formation of oedemas in the respiratory tract.

#### Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure. - Central nervous system, Liver, Kidney

#### Aspiration hazard

Aspiration hazard, Aspiration may cause pulmonary oedema and pneumonitis.

#### **Additional Information**

RTECS: Not available

Blurred vision, Incoordination., Headache, Nausea, Vomiting, Dizziness, Weakness, anemia, Prolonged or repeated exposure to skin causes defatting and dermatitis.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

After absorption:

Systemic effects:

Headache, somnolence, Dizziness, euphoria, agitation, spasms, respiratory paralysis, Unconsciousness, narcosis, inebriation

Effect potentiated by: ethanol

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

12.2 Persistence and degradability

#### 12.3 Bioaccumulative potential

#### 12.4 Mobility in soil

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life.

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Contact a licensed professional waste disposal service to dispose of this material. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

#### Contaminated packaging

Dispose of as unused product.

#### 14. TRANSPORT INFORMATION

#### DOT (US)

UN number: 1307 Proper shipping nar Reportable Quantity Poison Inhalation H	Class: 3 ne: Xylenes ⁄ (RQ): 100 lbs azard: No	Packing group: III			
<b>IMDG</b> UN number: 1307	Class: 3	Packing group: III	E	//S-No: F-E, S-D	
Proper shipping nar	ne: XYLENES				
ΙΑΤΑ					
UN number: 1307	Class: 3	Packing group: III			
Proper shipping nar	ne: Xylenes				
15. REGULATORY INFO	RMATION				
SARA 302 Compone No chemicals in this r	ents naterial are subject to	the reporting requirements	of SARA Tit	le III, Section 302.	
SARA 313 Compone The following compor	SARA 313 Components The following components are subject to reporting levels est			e III, Section 313:	
Xylene		C 1	AS-No. 330-20-7	Revision Date 1993-04-24	
<b>SARA 311/312 Haza</b> Fire Hazard, Acute H	<b>rds</b> ealth Hazard, Chronic	Health Hazard			
Massachusetts Righ	t To Know Compone	ents			
Xylene		C 1	AS-No. 330-20-7	Revision Date 1993-04-24	
Pennsylvania Right	To Know Componen	ts			
	-	C	AS-No.	Revision Date	
Xylene		1	330-20-7	1993-04-24	
New Jersey Right To	o Know Components				
		C	AS-No.	Revision Date	
Xylene		1	330-20-7	1993-04-24	
California Prop. 65 (	Components	s known to State of Califor	nia to causo	concor birth defects, or any c	thor

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### **16. OTHER INFORMATION**

Full text of H-Statements referred to under sections 2 and 3.

Acute Tox.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Asp. Tox.	Aspiration hazard
Flam. Liq.	Flammable liquids
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs (/\$/*_2ORG_REP_INH/\$/) through prolonged or repeated exposure if inhaled.
H401	Toxic to aquatic life.
Skin Irrit.	Skin irritation

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the

product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.10

Revision Date: 08/06/2018

Print Date: 06/28/2019

sigma-aldrich.com

#### SAFETY DATA SHEET

Version 6.0 Revision Date 05/28/2017 Print Date 06/28/2019

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

1.1	Product identifiers Product name	:	Zinc
	Product Number Brand Index-No.	:	324930 Aldrich 030-001-00-1
	CAS-No.	:	7440-66-6

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES			
Telephone	:	+1 314 771-5765			
Fax	:	+1 800 325-5052			
Emergency telephone number					

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

#### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Pyrophoric solids (Category 1), H250 Self-heating substances and mixtures (Category 1), H251 Substances and mixtures, which in contact with water, emit flammable gases (Category 1), H260 Acute aquatic toxicity (Category 1), H400 Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word	Danger
Hazard statement(s)	
H250	Catches fire spontaneously if exposed to air.
H251	Self-heating: may catch fire.
H260	In contact with water releases flammable gases which may ignite spontaneously.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary statement(s)	
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P222	Do not allow contact with air.
P223	Do not allow contact with water.
P231 + P232	Handle under inert gas. Protect from moisture.
P235 + P410	Keep cool. Protect from sunlight.
P273	Avoid release to the environment.
P280	Wear protective gloves/ eye protection/ face protection.
P335 + P334	Brush off loose particles from skin. Immerse in cool water/ wrap in wet bandages.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391	Collect spillage.
P402 + P404	Store in a dry place. Store in a closed container.
P407	Maintain air gap between stacks/ pallets.
P413	Store bulk masses greater than .? kg/ .? lbs at temperatures not exceeding .? °C/ .? °F.
P420	Store away from other materials.
P422	Store contents under inert gas.
P501	Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS Combustible dust

#### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Formula	:	Zn
Molecular weight	:	65.39 g/mol
CAS-No.	:	7440-66-6
EC-No.	:	231-175-3
Index-No.	:	030-001-00-1

#### Hazardous components

Component	Classification	Concentration
Zinc powder (pyrophoric)		
	Pyr. Sol. 1; Self-heat. 1; Water-react. 1; Aquatic Acute 1; Aquatic Chronic 1; H250, H251, H260, H410	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**4.3 Indication of any immediate medical attention and special treatment needed** No data available

#### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

Suitable extinguishing media Dry powder

5.2 Special hazards arising from the substance or mixture Zinc/zinc oxides

#### **5.3** Advice for firefighters Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information No data available

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas.

For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13). Do not flush with water. Keep in suitable, closed containers for disposal. Contain spillage, pick up with an electrically protected vacuum cleaner or by wet-brushing and transfer to a container for disposal according to local regulations (see section 13).

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Further processing of solid materials may result in the formation of combu formation should be taken into consideration before additional processing

Provide appropriate exhaust ventilation at places where dust is formed.Keep away from sources of ignition - No smoking.

For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Never allow product to get in contact with water during storage.

Keep in a dry place.

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values. Hazardous components without workplace control parameters

#### 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### **Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Protective gloves against thermal risks

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industria situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Flame retardant protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use (EN 143) respirator cartridges as a backup to engineering controls. If th full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a)	Appearance	Form: powder Colour: grey
b)	Odour	No data available
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: 420 °C (788 °F) - lit.
f)	Initial boiling point and boiling range	907 °C (1665 °F) - lit.
g)	Flash point	()No data available
h)	Evaporation rate	No data available

i)	Flammability (solid, gas)	May form combustible dust concentrations in air.
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapour pressure	1 hPa at 487 °C (909 °F)
I)	Vapour density	No data available
m)	Relative density	7.133 g/mL at 25 °C (77 °F)
n)	Water solubility	No data available
o)	Partition coefficient: n- octanol/water	log Pow: 5
p)	Auto-ignition temperature	The substance or mixture is classified as self heating with the category 1., The substance or mixture is pyrophoric with the category 1.
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
044		

# 9.2 Other safety information No data available

#### **10. STABILITY AND REACTIVITY**

- 10.1 Reactivity No data available
- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** Reacts violently with water.
- **10.4** Conditions to avoid Exposure to moisture
- **10.5** Incompatible materials Strong acids and oxidizing agents

# Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Zinc/zinc oxides Other decomposition products - No data available In the event of fire: see section 5

#### 11. TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects

#### Acute toxicity

No data availableZinc powder (pyrophoric) Inhalation: No data available(Zinc powder (pyrophoric)) Dermal: No data available(Zinc powder (pyrophoric)) No data available(Zinc powder (pyrophoric))

#### Skin corrosion/irritation

No data available(Zinc powder (pyrophoric))

#### Serious eye damage/eye irritation

No data available(Zinc powder (pyrophoric))

#### Respiratory or skin sensitisation

Did not cause sensitisation on laboratory animals.(Zinc powder (pyrophoric))

#### Germ cell mutagenicity

No data available(Zinc powder (pyrophoric))

#### Carcinogenicity

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### **Reproductive toxicity**

No data available(Zinc powder (pyrophoric))

No data available(Zinc powder (pyrophoric))

**Specific target organ toxicity - single exposure** No data available(Zinc powder (pyrophoric))

Specific target organ toxicity - repeated exposure No data available

#### Aspiration hazard

No data available(Zinc powder (pyrophoric))

#### **Additional Information**

RTECS: ZG8600000

chills, dry throat, sweet taste, Fever, Cough, Nausea, Vomiting, Weakness(Zinc powder (pyrophoric)) To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.(Zinc powder (pyrophoric))

#### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

Toxicity to fish	LC50 - Cyprinus carpio (Carp) - 450.0 µg/l - 96.0 h(Zinc powder (pyrophoric))
Toxicity to daphnia and other aquatic invertebrates	LC50 - Daphnia magna (Water flea) - 0.068 mg/l - 48 h(Zinc powder (pyrophoric))
	mortality NOEC - Daphnia (water flea) - 0.101 - 0.14 mg/l - 7 d(Zinc powder (pyrophoric))

#### 12.2 Persistence and degradability

#### 12.3 Bioaccumulative potential

Bioaccumulation Algae - 7 d  $at 16 \degree C$  . E ug/l/(Zine pour

at 16 °C - 5 µg/I(Zinc powder (pyrophoric))

Bioconcentration factor (BCF): 466

#### 12.4 Mobility in soil

No data available(Zinc powder (pyrophoric))

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life.

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber b highly flammable. Offer surplus and nonrecyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

#### Contaminated packaging

Dispose of as unused product.

#### **14. TRANSPORT INFORMATION**

#### DOT (US)

001 (05)					
UN number: 1436	Class:	4.3 (4.2)		Packing group: II	
Proper shipping name:	Zinc pc	wder			
Reportable Quantity (R	ຊ) :		1000 lbs		

Poison Inhalation Hazard: No

#### IMDG

UN number: 1436 Class: 4.3 (4.2) Proper shipping name: ZINC POWDER Marine pollutant : yes

#### ΙΑΤΑ

UN number: 1436 Class: 4.3 (4.2) Proper shipping name: Zinc powder

Packing group: II

Packing group: II

EMS-No: F-G, S-O

#### **15. REGULATORY INFORMATION**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

The following components are subject to reporting levels establish	ed by SARA Title III,	Section 313: Revision Date
Zinc powder (pyrophoric)	7440-66-6	1993-04-24
SARA 311/312 Hazards Reactivity Hazard		
Massachusetts Right To Know Components		
	CAS-No.	Revision Date
Zinc powder (pyrophoric)	7440-66-6	1993-04-24
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Zinc powder (pyrophoric)	7440-66-6	1993-04-24
New Jersey Right To Know Components		
	CAS-No.	<b>Revision Date</b>
Zinc powder (pyrophoric)	7440-66-6	1993-04-24

#### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### **16. OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

H250	Catches fire spontaneously if exposed to air.
H251	Self-heating: may catch fire.
H260	In contact with water releases flammable gases which may ignite spontaneously.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

#### **HMIS** Rating

Health hazard:	0
Chronic Health Hazard:	
Flammability:	3
Physical Hazard	1
NFPA Rating	
NFPA Rating Health hazard:	0
<b>NFPA Rating</b> Health hazard: Fire Hazard:	0 3

#### Reactivity Hazard: 1 Special hazard.I: W

#### Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956 Version: 6.0

Revision Date: 05/28/2017

Print Date: 06/28/2019

# **Appendix E:**

# **Community Air Monitoring Plan**



Geotechnical Environmental Site Civil 959 Route 46E, Fl 3, Ste 300 Parsippany, NJ 07054 973.808.9050 www.sesi.org

### Community Air Monitoring Plan For

TMHA Franklin Courts 1-99 Franklin Court Tarrytown, Westchester County, New York

Prepared for: Franklin Courts JV Partners L.P.

April 2024

SESI Project No: 12345

#### **Table of Contents**

LIST OF ACRONYMSi	
1.0 INTRODUCTION1	
2.0 OBJECTIVES	
3.0 METHODS1	
3.1 CONTINUOUS MONITORING	
3.2 PERIODIC MONITORING	
4.0 VOC MONITORING, RESPONSE LEVELS, AND ACTIONS	
5.0 PARTICULATE MONITORING, RESPONSE LEVELS, AND ACTIONS	
6.0 SPECIAL REQUIREMENTS FOR WORK WITHIN 20 FEET OF POTENTIALLY EXPOSED INDIVIDUAL STRUCTURES	



#### LIST OF ACRONYMS

Acronym	Definition	
CAMP	Community Air Monitoring Plan	
IRM	Interim Remedial Measure	
mcg/m <sup>3</sup>	micrograms per cubic meter	
NYSDEC	New York State Department of Environmental	
	Conservation	
NYSDOH	New York State Department of Health	
PID	Photoionization Detector	
PM-10	Less than 10 micrometers	
ppm	Parts Per Million	
RI	Remedial Investigation	
RIWP	Remedial Investigation Work Plan	
VOC	Volatile Organic Compound	



#### **1.0 INTRODUCTION**

This document presents a Community Air Monitoring Plan (CAMP) for the remedial investigation (RI) for the proposed development at 1-99 Franklin Court (a.k.a 50 White Street), Tarrytown, New York (the "Site").

The 8.35-acre parcel is identified as Block 29, Lot 32 on the Westchester County tax map. The Site has been developed with The Site is currently occupied by the Franklin Courts multifamily property improved with 14 residential buildings and one (1) recreational building. The subject property is bounded to the north by a multi-family residential apartment building at 50 White Street, to the east by Riverview Avenue and residential developments beyond, to the south by residential development along MacArthur Avenue, and to the west by Warehouses and former railroad tracks.

According to a Phase I Environmental Site Assessment prepared by AEI Consultants in June 2021, the Site was submerged by the Hudson River from 1897 to 1931. From 1932 to 1950 the Site appears as vacant land. In 1950 the northern portion of the Site is a coal yard with office, sheds, and an automobile garage. In 1970, the Site is developed with the current Franklin Court Apartments with 14 residential buildings and one (1) recreational building. In addition, AEI observed suspected heating oil vent pipes around the residential buildings 5 and 6 but noted that ground visibility was limited due to snow. AEI's review of Google Earth street imagery identified 20 additional suspected heating oil vent pipes throughout the Site.

#### 2.0 OBJECTIVES

The objective of the CAMP is to provide a measure of protection for the downwind community from potential airborne contaminant releases that may arise during all ground intrusive activities, and potentially contaminated soil and material handling and staging. In addition, the CAMP is intended to ensure that dust and contaminants are not leaving the work zone.

#### 3.0 METHODS

The CAMP will include continuous monitoring for particulate matter (e.g. airborne "dust") and volatile organic compounds (VOCs) during the planned remedial excavation and construction activities. Any CAMP exceedances will be reported to the New York State Department of



Environmental Conservation (NYSDEC) and New York State Department of Health (NYSDOH) on the same business day and as soon as possible. Notification of the exceedance will be sent via email along with the reason for the exceedance, the measure(s) taken to address the exceedance, and if the exceedance was resolved.

#### **3.1 CONTINUOUS MONITORING**

Continuous monitoring for particulates and VOCs will be conducted during all ground intrusive activities including soil borings, monitoring well installations, and archaeological excavations

#### 3.2 PERIODIC MONITORING

Periodic monitoring for VOCs will be conducted during non-intrusive activities such as the collection of soil and sediment samples or the collection of groundwater samples from existing monitoring wells. "Periodic" monitoring during sample collection consists of taking a reading upon arrival at a sample location, monitoring while opening a well cap or overturning soil, monitoring during well baling/purging, and taking a reading prior to leaving a sample location. In some instances, depending upon the proximity of potentially exposed individuals, continuous monitoring may be required during sampling activities. Examples of such situations include groundwater sampling at wells on the curb of a busy urban street, in the midst of a public park, or adjacent to a school or residence.

#### 4.0 VOC MONITORING, RESPONSE LEVELS, AND ACTIONS

VOCs must be monitored at the downwind perimeter of the immediate work area (i.e. the exclusion zone) on a continuous basis or as otherwise specified. Upwind concentrations should be measured at the start of each workday and periodically thereafter to establish background conditions. The monitoring work will be performed using a photoionization detector (PID) equipped with a 10.6 ev lamp. The equipment will be calibrated at least daily for the contaminant(s) of concern or for an appropriate surrogate. The equipment should be capable of calculating 15-minute running average concentrations, which will be compared to the levels specified below.



- If the ambient air concentration of total organic vapors at the downwind perimeter of the work area or exclusion zone exceeds 5 parts per million (ppm) above background for the15-minute average, work activities must be temporarily halted and monitoring continued. If the total organic vapor level readily decreases (per instantaneous readings) below 5 ppm over background, work activities can resume with continued monitoring.
- If total organic vapor levels at the downwind perimeter of the work area or exclusion zone persist at levels in excess of 5 ppm over background but less than 25 ppm, work activities must be halted, the source of vapors identified, corrective actions taken to abate emissions, and monitoring continued. After these steps, work activities can resume provided that the total organic vapor level 200 feet downwind of the exclusion zone or half the distance to the nearest potential receptor or residential/commercial structure, whichever is less but in no case less than 20 feet, is below 5 ppm over background for the 15-minute average.
- If the organic vapor level is above 25 ppm at the perimeter of the work area, activities must be shut down.
- All 15-minute readings must be recorded and be available for State (DEC and DOH) personnel to review. Instantaneous readings, if any, used for decision purposes should also be recorded.

#### 5.0 PARTICULATE MONITORING, RESPONSE LEVELS, AND ACTIONS

Particulate concentrations should be monitored continuously at the upwind and downwind perimeters of the exclusion zone at temporary particulate monitoring stations. The particulate monitoring should be performed using real-time monitoring equipment capable of measuring particulate matter less than 10 micrometers in size (PM-10) and capable of integrating over a period of 15 minutes (or less) for comparison to the airborne particulate action level. The equipment must be equipped with an audible alarm to indicate exceedance of the action level. In addition, fugitive dust migration should be visually assessed during all work activities.

If the downwind PM-10 particulate level is 100 micrograms per cubic meter (mcg/m<sup>3</sup>) greater than background (upwind perimeter) for the 15-minute period or if airborne dust is observed leaving the work area, then dust-suppression techniques must be employed. Work may continue with dust-suppression techniques provided that downwind PM-10


particulate levels do not exceed 150 mcg/m<sup>3</sup> above the upwind level and provided that no visible dust is migrating from the work area.

 If, after implementation of dust-suppression techniques, downwind PM-10 particulate levels are greater than 150 mcg/m<sup>3</sup> above the upwind level, work must be stopped and a re-evaluation of activities initiated. Work can resume provided that dust-suppression measures and other controls are successful in reducing the downwind PM-10 particulate concentration to within 150 mcg/m<sup>3</sup> of the upwind level and in preventing visible dust migration.

All readings must be recorded and be available for State (NYSDEC and NYSDOH) personnel to review.

#### 6.0 SPECIAL REQUIREMENTS FOR WORK WITHIN 20 FEET OF POTENTIALLY EXPOSED INDIVIDUAL STRUCTURES

When work areas are within 20 feet of potentially exposed populations or occupied structures, the continuous monitoring locations for VOCs and particulates must reflect the nearest potentially exposed individuals and the location of ventilation system intakes for nearby structures. The use of engineering controls such as vapor/dust barriers, temporary negative-pressure enclosures, or special ventilation devices should be considered to prevent exposures related to the work activities and to control dust and odors. Consideration should be given to implementing the planned activities when potentially exposed populations are at a minimum, such as during weekends or evening hours in non-residential settings.

- If total VOC concentrations opposite the walls of occupied structures or next to intake vents exceed one (1) ppm, monitoring should occur within the occupied structure(s). Depending upon the nature of contamination, chemical-specific colorimetric tubes of sufficient sensitivity may be necessary for comparing the exposure point concentrations with appropriate pre-determined response levels (response actions should also be pre-determined). Background readings in the occupied spaces must be taken prior to commencement of the planned work. Any unusual background readings should be discussed with NYSDOH prior to commencement of the work.
- If total particulate concentrations opposite the walls of occupied structures or next to intake vents exceed 150 mcg/m<sup>3</sup>, work activities should be suspended until controls are



implemented and are successful in reducing the total particulate concentration to  $150 \text{ mcg/m}^3$  or less at the monitoring point.

 Depending upon the nature of contamination and remedial activities, other parameters (e.g., explosivity, oxygen, hydrogen sulfide, carbon monoxide) may also need to be monitored. Response levels and actions should be pre-determined, as necessary, for each site.

# **Appendix F:** Citizens Participation Plan



Department of Environmental Conservation

## **Brownfield Cleanup Program**

## Citizen Participation Plan for Franklin Courts Coal Storage Site

April 2024

Site # <mark>CXXXXXX</mark> 1-99 Franklin Courts, Tarrytown, New York 10591 County of Westchester, NY

www.dec.ny.gov

#### Contents

#### Page Number

1. What is New York's Brownfield Cleanup Program?	3
2. Citizen Participation Activities	3
3. Major Issues of Public Concern	9
4. Site Information	9
5. Investigation and Cleanup Process	. 11
Appendix A - Project Contacts and Locations of Reports and Information	. 15
Appendix B - Site Contact List	. 16
Appendix C - Site Location Map	. 18
Appendix D - Brownfield Cleanup Program Process	. 19

\* \* \* \* \*

**Note:** The information presented in this Citizen Participation Plan was current as of the date of its approval by the New York State Department of Environmental Conservation. Portions of this Citizen Participation Plan may be revised during the site's investigation and cleanup process.

Applicant: Franklin Courts JV Partners L.P. ("Volunteer") Site Name: Franklin Courts Coal Storage Site ("Site") Site Address: 1-99 Franklin Courts, Tarrytown, New York 10591 Site County: Westchester Site Number: CXXXXXX

#### 1. What is New York's Brownfield Cleanup Program?

New York's Brownfield Cleanup Program (BCP) works with private developers to encourage the voluntary cleanup of contaminated properties known as "brownfields" so that they can be reused and developed. These uses include recreation, housing, and business.

A *brownfield* is any real property that is difficult to reuse or redevelop because of the presence or potential presence of contamination. A brownfield typically is a former industrial or commercial property where operations may have resulted in environmental contamination. A brownfield can pose environmental, legal, and financial burdens on a community. If a brownfield is not addressed, it can reduce property values in the area and affect economic development of nearby properties.

The BCP is administered by the New York State Department of Environmental Conservation (NYSDEC) which oversees Applicants who conduct brownfield site investigation and cleanup activities. An Applicant is a person who has requested to participate in the BCP and has been accepted by NYSDEC. The BCP contains investigation and cleanup requirements, ensuring that cleanups protect public health and the environment. When NYSDEC certifies that these requirements have been met, the property can be reused or redeveloped for the intended use.

For more information about the BCP, go online at: <u>http://www.dec.ny.gov/chemical/8450.html</u>.

#### 2. Citizen Participation Activities

#### Why NYSDEC Involves the Public and Why It Is Important

NYSDEC involves the public to improve the process of investigating and cleaning up contaminated sites, and to enable citizens to participate more fully in decisions that affect their health, environment, and social well-being. NYSDEC provides opportunities for citizen involvement and encourages early two-way communication with citizens before decision makers form or adopt final positions.

Involving citizens affected and interested in site investigation and cleanup programs is important for many reasons. These include:

- Promoting the development of timely, effective site investigation and cleanup programs that protect public health and the environment
- Improving public access to, and understanding of, issues and information related to a particular site and that site's investigation and cleanup process
- Providing citizens with early and continuing opportunities to participate in NYSDEC's site investigation and cleanup process
- Ensuring that NYSDEC makes site investigation and cleanup decisions that benefit from input that reflects the interests and perspectives found within the affected community
- Encouraging dialogue to promote the exchange of information among the affected/interested public, State agencies, and other interested parties that strengthens trust among the parties, increases understanding of site and community issues and concerns, and improves decision making.

This Citizen Participation (CP) Plan provides information about how NYSDEC will inform and involve the public during the investigation and cleanup of the site identified above. The public information and involvement program will be carried out with assistance, as appropriate, from the Applicant.

#### Project Contacts

Appendix A identifies NYSDEC project contact(s) to whom the public should address questions or request information about the site's investigation and cleanup program. The public's suggestions about this CP Plan and the CP program for the site are always welcome. Interested people are encouraged to share their ideas and suggestions with the project contacts at any time.

#### Locations of Reports and Information

The locations of the reports and information related to the site's investigation and cleanup program also are identified in Appendix A. These locations provide convenient access to important project documents for public review and comment. Some documents may be placed on the NYSDEC web site. If this occurs, NYSDEC will inform the public in fact sheets distributed about the site and by other means, as appropriate.

#### Site Contact List

Appendix B contains the site contact list. This list has been developed to keep the community informed about, and involved in, the site's investigation and cleanup process. The site contact list will be used periodically to distribute fact sheets that provide updates about the status of the project. These will include notifications of upcoming activities at the site (such as fieldwork), as well as availability of project documents and announcements about public comment periods.

The site contact list includes, at a minimum:

- chief executive officer and planning board chairperson of each county, city, town and village in which the site is located;
- residents, owners, and occupants of the site and properties adjacent to the site;
- the public water supplier which services the area in which the site is located;
- any person who has requested to be placed on the site contact list;
- the administrator of any school or day care facility located on or near the site for purposes of posting and/or dissemination of information at the facility;
- location(s) of reports and information.

The site contact list will be reviewed periodically and updated as appropriate. Individuals and organizations will be added to the site contact list upon request. Such requests should be submitted to the NYSDEC project contact(s) identified in Appendix A. Other additions to the site contact list may be made at the discretion of the NYSDEC project manager, in consultation with other NYSDEC staff as appropriate.

**Note:** The first site fact sheet (usually related to the draft Remedial Investigation Work Plan) is distributed both by paper mailing through the postal service and through DEC Delivers, its email listserv service. The fact sheet includes instructions for signing up with the appropriate county listserv to receive future notifications about the site. See <a href="http://www.dec.ny.gov/chemical/61092.html">http://www.dec.ny.gov/chemical/61092.html</a>.

Subsequent fact sheets about the site will be distributed exclusively through the listserv, except for households without internet access that have indicated the need to continue to receive site information in paper form. Please advise the NYSDEC site project manager identified in Appendix A if that is the case. Paper mailings may continue during the investigation and cleanup process for some sites, based on public interest and need.

#### **CP** Activities

The table at the end of this section identifies the CP activities, at a minimum, that have been and will be conducted during the site's investigation and cleanup program. The flowchart in Appendix D shows how these CP activities integrate with the site investigation and cleanup process. The public is informed about these CP activities through fact sheets and notices distributed at significant points during the program. Elements of the investigation and cleanup process that match up with the CP activities are explained briefly in Section 5.

- **Notices and fact sheets** help the interested and affected public to understand contamination issues related to a site, and the nature and progress of efforts to investigate and clean up a site.
- **Public forums, comment periods and contact with project managers** provide opportunities for the public to contribute information, opinions and perspectives that have potential to influence decisions about a site's investigation and cleanup.

The public is encouraged to contact project staff at any time during the site's investigation and cleanup process with questions, comments, or requests for information.

This CP Plan may be revised due to changes in major issues of public concern identified in Section 3 or in the nature and scope of investigation and cleanup activities. Modifications may include additions to the site contact list and changes in planned citizen participation activities.

#### Technical Assistance Grant

NYSDEC must determine if the site poses a significant threat to public health or the environment. This determination generally is made using information developed during the investigation of the site, as described in Section 5.

If the site is determined to be a significant threat, a qualifying community group may apply for a Technical Assistance Grant (TAG). The purpose of a TAG is to provide funds to the qualifying group to obtain independent technical assistance. This assistance helps the TAG recipient to interpret and understand existing environmental information about the related the site and extent of contamination to and the nature development/implementation of a remedy.

An eligible community group must certify that its membership represents the interests of the community affected by the site, and that its members' health, economic well-being or

enjoyment of the environment may be affected by a release or threatened release of contamination at the site.

As of the date the declaration (page 2) was signed by the NYSDEC project manager, the significant threat determination for the site had not yet been made.

To verify the significant threat status of the site, the interested public may contact the NYSDEC project manager identified in Appendix A.

For more information about TAGs, go online at <u>http://www.dec.ny.gov/regulations/2590.html</u>

Note: The table identifying the citizen participation activities related to the site's investigation and cleanup program follows on the next page:

Citizen Participation Activities	Timing of CP Activity(ies)		
Applicatio	n Process:		
<ul><li>Prepare site contact list</li><li>Establish document repository(ies)</li></ul>	At time of preparation of application to participate in the BCP.		
<ul> <li>Publish notice in Environmental Notice Bulletin (ENB) announcing receipt of application and 30-day public comment period</li> <li>Publish above ENB content in local newspaper</li> <li>Mail above ENB content to site contact list</li> <li>Conduct 30-day public comment period</li> </ul>	When NYSDEC determines that BCP application is complete. The 30-day public comment period begins on date of publication of notice in ENB. End date of public comment period is as stated in ENB notice. Therefore, ENB notice, newspaper notice, and notice to the site contact list should be provided to the public at the same time.		
After Execution of Brownfield S	Site Cleanup Agreement (BCA):		
Prepare Citizen Participation (CP) Plan	Before start of Remedial Investigation Note: Applicant must submit CP Plan to NYSDEC for review and approval within 20 days of the effective date of the BCA.		
Before NYSDEC Approves Remedial Investigation (RI) Work Plan:			
<ul> <li>Distribute fact sheet to site contact list about proposed RI activities and announcing 30-day public comment period about draft RI Work Plan</li> <li>Conduct 30-day public comment period</li> </ul>	Before NYSDEC approves RI Work Plan. If RI Work Plan is submitted with application, public comment periods will be combined and public notice will include fact sheet. Thirty-day public comment period begins/ends as per dates identified in fact sheet.		
After Applicant Complete	s Remedial Investigation:		
• Distribute fact sheet to site contact list that describes RI results	Before NYSDEC approves RI Report		
Before NYSDEC Approves I	Remedial Work Plan (RWP):		
<ul> <li>Distribute fact sheet to site contact list about draft RWP and announcing 45-day public comment period</li> <li>Public meeting by NYSDEC about proposed RWP (if requested by affected community or at discretion of NYSDEC project manager)</li> <li>Conduct 45-day public comment period</li> </ul>	Before NYSDEC approves RWP. Forty-five day public comment period begins/ends as per dates identified in fact sheet. Public meeting would be held within the 45- day public comment period.		
Before Applicant Sta	rts Cleanup Action:		
Distribute fact sheet to site contact list that describes upcoming cleanup action	Before the start of cleanup action.		
After Applicant Completes Cleanup Action:			
• Distribute fact sheet to site contact list that announces that cleanup action has been completed and that NYSDEC is reviewing the Final Engineering Report	At the time the cleanup action has been completed. <b>Note:</b> The two fact sheets are combined when possible if there is not a delay in issuing the COC.		
Distribute fact sheet to site contact list announcing NYSDEC approval of Final Engineering Report and issuance of Certificate of Completion (COC)			

#### 3. Major Issues of Public Concern

This section of the CP Plan identifies major issues of public concern that relate to the site. Additional major issues of public concern may be identified during the course of the site's investigation and cleanup process.

There will be areas on the Site where soil excavation is necessary. Therefore, once the remediation commences, there may be concerns regarding odors, noise or truck traffic coming from the site. However, these impacts will be mitigated through implementation of a Health and Safety Plan and Soil Management Plan approved by NYSDEC, which will be designed to minimize these impacts. A Community Air Monitoring Plan will also be implemented to monitor dust and vapors to ensure the community is not impacted. CAMP implementation involves the placement of air monitoring stations upwind and downwind of where work is occurring to capture both dust and vapor emissions. If dust or emissions exceed a set threshold established by NYSDEC and the New York State Department of Health (NYSDOH), then work must cease and the cause of the issue must be corrected before work can proceed.

#### 4. Site Information

Appendix C contains a map identifying the location of the site.

Site Description

Location: 1-99 Franklin Courts, Tarrytown, New York 10591; County of Westchester

<u>Setting</u>: Urban

Site Size: 7.4 Acres

<u>Adjacent Properties</u>: The subject property is located in an urban area, and the surrounding area is occupied by commercial and residential buildings.

#### History of Site Use, Investigation, and Cleanup

SESI Consulting Engineers (SESI), at the request of the Requestor, completed a Phase II Environmental Site Assessment (ESA) for the Site in May 2022. SESI's investigation was based upon the review of a Phase I ESA prepared previously by AEI Consultants in June 2021. The Phase I identified Recognized Environmental Concerns (RECs) relating to numerous underground storage tanks, contaminated groundwater from closure reports, and fill material identified on the Site. Therefore, SESI conducted Phase II

activities at the Site in March through April 2022 to identify areas of the Site that might be impacted by the historic USTs as well as historic coal yard uses. A Supplemental Phase II ESA was conducted by SESI in December 2023 to further delineate and evaluate portions of the Site based on our initial Phase II from May 2022. Both Phase II investigations identified metals and PAHs exceeding the Residential and Restricted Residential SCOs at the Site; while groundwater contamination was found to be identified with PAHs and metals, as well as PFAS. Soil vapor points were installed during each investigation which identified petroleum-related compounds in soil-gas samples; however, no exceedances were reported.

Therefore, the soil and groundwater at the Site have been found to be impacted by the former operations and use of historic petroleum USTs, and historic coal storage activities at the Site.

#	Consultant	Investigation Report Title	Date	Site Owner	
1	SESI Consulting Engineers	Phase II Environmental Site Assessment	May 2022	Tarrytown Municipal Housing Authority	
2	SESI Consulting Engineers	Supplemental Phase II Environmental Site Assessment	January 2024, Amended April 2024	Tarrytown Municipal Housing Authority	
3	SESI Consulting Engineers	Geotechnical Report	January 2024	Tarrytown Municipal Housing Authority	

There have been three (3) Investigations conducted to date as follows:

Based on the investigations conducted to date, the primary contaminants of concern are SVOCs (PAHs) and metals in soil; metals and SVOCs (PAHs) in groundwater, as well as PFAS (PFOA and/or PFOS) in groundwater. Soil vapor testing indicates the presence of petroleum-related compounds. See Exhibit G Site Drawing Analytical Call-Outs.

The analytical results of the second Phase II and Supplemental Phase II investigations performed in December 2023 and March 2024 identified metals in exceedance of the RSCOs and RRSCOs; including lead and mercury to depths of 10 ft-bgs. The highest concentration of lead was detected in SB-109 (9.5-10') at 799 ppm. The metals in exceedance of the USCOs including arsenic, cadmium, copper, iron, lead, mercury, nickel, and zinc to depths ranging from 2.5 ft-bgs to 10 ft-bgs. The SVOCs exceedances of the RRSCOs include benzo(a)anthracene, benzo(a)pyrene, benzo(b)fluoranthene, chrysene, Dibenzo(a,h)anthracene, Indeno(1,2,3-cd)pyrene to depths of 7.5 ft-bgs. The

SVOCs benzo(k)fluoranthene, and 2-Methylnaphthalene were detected at concentrations exceeding the RSCOs to depths of 7.5 ft-bgs. The pesticides 4,4'-DDE, 4,4'-DDD, and dieldrin were detected at concentrations exceeding the USCOs to depths ranging from 3.5 ft-bgs to 11 ft-bgs.

The groundwater testing results indicate AWQS exceedances of various metals: aluminum, arsenic, chromium, iron, lead, manganese, and sodium. No SVOCs exceeded the AWQS. The PFAS compounds perfluorooctane sulfonic acid (PFOS) and perfluorooctanoic acid (PFOA) were detected at concentrations exceeding the NYSDEC screening levels.

Samples taken from the soil vapor onsite indicate the presence of petroleum-related compounds such as benzene, ethylbenzene, m,p-xylene, o-xylene, hexane, heptane and trimethylbenzene; however the NYSDOH has not set standards for these compounds. The detections may be attributable to the former residential #2 fuel oil USTs and/or automobile repair activities in the northern portion of the Site.

#### 5. Investigation and Cleanup Process

#### Application

The Applicant has applied for and been accepted into New York's Brownfield Cleanup Program as a **Volunteer**. This means that the Applicant was not responsible for the disposal or discharge of the contaminants or whose ownership or operation of the site took place after the discharge or disposal of contaminants. The Volunteer must fully characterize the nature and extent of contamination onsite, and must conduct a "qualitative exposure assessment," a process that characterizes the actual or potential exposures of people, fish and wildlife to contaminants on the site and to contamination that has migrated from the site.

The Applicant in its Application proposes that the site will be used for unrestricted purposes to the extent feasible to achieve this level of remediation or restricted residential use.

To achieve this goal, the Applicant will conduct investigation and cleanup activities at the site with oversight provided by NYSDEC. The Brownfield Cleanup Agreement executed by NYSDEC and the Applicant sets forth the responsibilities of each party in conducting these activities at the site.

#### Investigation

The Applicant will conduct an investigation of the site officially called a "remedial

investigation" (RI). This investigation will be performed with NYSDEC oversight. The Applicant must develop a remedial investigation workplan, which is subject to public comment.

The site investigation has several goals:

- 1) define the nature and extent of contamination in soil, surface water, groundwater and any other parts of the environment that may be affected;
- 2) identify the source(s) of the contamination;
- 3) assess the impact of the contamination on public health and the environment; and
- 4) provide information to support the development of a proposed remedy to address the contamination or the determination that cleanup is not necessary.

The Applicant submits a draft "Remedial Investigation Work Plan" to NYSDEC for review and approval. NYSDEC makes the draft plan available to the public review during a 30day public comment period.

When the investigation is complete, the Applicant will prepare and submit a report that summarizes the results. This report also will recommend whether cleanup action is needed to address site-related contamination. The investigation report is subject to review and approval by NYSDEC.

NYSDEC will use the information in the investigation report to determine if the site poses a significant threat to public health or the environment. If the site is a "significant threat," it must be cleaned up using a remedy selected by NYSDEC from an analysis of alternatives prepared by the Applicant and approved by NYSDEC. If the site does not pose a significant threat, the Applicant may select the remedy from the approved analysis of alternatives.

#### Interim Remedial Measures

An Interim Remedial Measure (IRM) is an action that can be undertaken at a site when a source of contamination or exposure pathway can be effectively addressed before the site investigation and analysis of alternatives are completed. If an IRM is likely to represent all or a significant part of the final remedy, NYSDEC will require a 30-day public comment period.

#### Remedy Selection

When the investigation of the site has been determined to be complete, the project likely would proceed in one of two directions:

1. The Applicant may recommend in its investigation report that no action is necessary at

the site. In this case, NYSDEC would make the investigation report available for public comment for 45 days. NYSDEC then would complete its review, make any necessary revisions, and, if appropriate, approve the investigation report. NYSDEC would then issue a "Certificate of Completion" (described below) to the Applicant.

#### or

2. The Applicant may recommend in its investigation report that action needs to be taken to address site contamination. After NYSDEC approves the investigation report, the Applicant may then develop a cleanup plan, officially called a "Remedial Work Plan". The Remedial Work Plan describes the Applicant's proposed remedy for addressing contamination related to the site.

When the Applicant submits a draft Remedial Work Plan for approval, NYSDEC would announce the availability of the draft plan for public review during a 45-day public comment period.

#### Cleanup Action

NYSDEC will consider public comments, and revise the draft cleanup plan if necessary, before approving the proposed remedy. The New York State Department of Health (NYSDOH) must concur with the proposed remedy. After approval, the proposed remedy becomes the selected remedy. The selected remedy is formalized in the site Decision Document.

The Applicant may then design and perform the cleanup action to address the site contamination. NYSDEC and NYSDOH oversee the activities. When the Applicant completes cleanup activities, it will prepare a final engineering report that certifies that cleanup requirements have been achieved or will be achieved within a specific time frame. NYSDEC will review the report to be certain that the cleanup is protective of public health and the environment for the intended use of the site.

#### Certificate of Completion

When NYSDEC is satisfied that cleanup requirements have been achieved or will be achieved for the site, it will approve the final engineering report. NYSDEC then will issue a Certificate of Completion (COC) to the Applicant. The COC states that cleanup goals have been achieved, and relieves the Applicant from future liability for site-related contamination, subject to certain conditions. The Applicant would be eligible to redevelop the site after it receives a COC.

#### Site Management

The purpose of site management is to ensure the safe reuse of the property if contamination will remain in place. Site management is the last phase of the site cleanup program. This phase begins when the COC is issued. Site management incorporates any institutional and engineering controls required to ensure that the remedy implemented for the site remains protective of public health and the environment. All significant activities are detailed in a Site Management Plan.

An *institutional control* is a non-physical restriction on use of the site, such as a deed restriction that would prevent or restrict certain uses of the property. An institutional control may be used when the cleanup action leaves some contamination that makes the site suitable for some, but not all uses.

An *engineering control* is a physical barrier or method to manage contamination. Examples include: caps, covers, barriers, fences, and treatment of water supplies.

Site management also may include the operation and maintenance of a component of the remedy, such as a system that pumps and treats groundwater. Site management continues until NYSDEC determines that it is no longer needed.

#### Appendix A -Project Contacts and Locations of Reports and Information

#### **Project Contacts**

For information about the site's investigation and cleanup program, the public may contact any of the following project staff:

#### New York State Department of Environmental Conservation (NYSDEC):

#### NYSDEC – Project Manager

{insert name of project manager}
Project Manager
NYSDEC {insert region # if applicable}
Division of Environmental Remediation
{insert regional or central office address}
{insert a contact telephone number}

#### NYSDOH – Project Manager:

{insert name of project manager}
Project Manager
NYSDOH
{insert central or regional office address}
{insert a contact telephone number}
Locations of Reports and Information

The facilities identified below are being used to provide the public with convenient access to important project documents:

PUBLIC LIBRARY			
Jessica Pacciotti Warner Library, Director 121 North Broadway Village of Tarrytown, NY 10591 (914) 631-7734 <u>https://warnerlibrary.org/</u>	HOURS:           Sunday,		

## Appendix B - Site Contact List

#### SITE CONTACT LIST

	GOVERNMENT / MUNICIPALITIES				
	Charles Schumer	Kirsten Gillibrand	Hon. George Latimer		
	U.S. Senator	U.S. Senator	Westchester County Executive		
	Leo O'Brien Building, Room 827	Leo O'Brien Building, Room 821	148 Martine Ave		
	Albany, NY 12207	Albany, NY 12207	White Plains, NY 10601		
	Hon. Richard Hyman, Chair	Karen G. Brown	George Latimer		
	Westchester County Planning	Village's Mayor	Westchester County Executive		
	Board	Village Offices	148 Martine Avenue		
	148 Martine Ave	One Depot Plaza	White Plains, NY 10601		
	White Plains, NY 10601	Tarrytown, NY 10591			
	Joan Raiselis, Chair	Frank Morabito, Head Chief			
	Village Planning Board	Tarrytown Fire Department			
	Village Offices	50 Main Street, Tarrytown, NY			
	One Depot Plaza	10591			
Tarrytown, NY 10591					
	UTILIT	<b>TES / PUBLIC WATER AUTHOI</b>	RITIES		
	Department of Public Works	Westchester Joint Water Works			
	One Division Street	1625 Mamaroneck Avenue			
	Tarrytown, NY 10591	Mamaroneck, NY 10543			
		MEDIA			
	The Hudson Independent	News 12 Westchester			
	21 N Broadway	6 Executive Plaza			
	Tarrytown, NY 10591	Yonkers, NY 10701			
	LIBRARIES / COMMUNITY CENTERS				
	LIB	RARIES / COMMUNITY CENTE	ERS		
	LIB Warner Library	RARIES / COMMUNITY CENTE	ERS		
	LIB Warner Library 121 N Broadway	RARIES / COMMUNITY CENTE	ERS		
	LIB Warner Library 121 N Broadway Tarrytown, NY 10591	RARIES / COMMUNITY CENTE	ERS		
	LIB Warner Library 121 N Broadway Tarrytown, NY 10591 Jessica Pacciotti	RARIES / COMMUNITY CENTE	ERS		
	LIB Warner Library 121 N Broadway Tarrytown, NY 10591 Jessica Pacciotti (914) 631-7734	RARIES / COMMUNITY CENTE	ERS		
	LIB Warner Library 121 N Broadway Tarrytown, NY 10591 Jessica Pacciotti (914) 631-7734	RARIES / COMMUNITY CENTE	ERS		
	LIB Warner Library 121 N Broadway Tarrytown, NY 10591 Jessica Pacciotti (914) 631-7734 S Tarrytown Nursery PreSchool	RARIES / COMMUNITY CENTE CHOOLS / DAYCARE CENTER New Beginnings Nursery School	ERS S Washington Irvington		
	LIB Warner Library 121 N Broadway Tarrytown, NY 10591 Jessica Pacciotti (914) 631-7734 S Tarrytown Nursery PreSchool 15 W Elizabeth Street	RARIES / COMMUNITY CENTE CHOOLS / DAYCARE CENTER New Beginnings Nursery School 42 N Broadway	RS S Washington Irvington Intermediate School		
	LIB Warner Library 121 N Broadway Tarrytown, NY 10591 Jessica Pacciotti (914) 631-7734 S Tarrytown Nursery PreSchool 15 W Elizabeth Street Tarrytown, NY 10591	RARIES / COMMUNITY CENTE CHOOLS / DAYCARE CENTER New Beginnings Nursery School 42 N Broadway Tarrytown, Ny 10591	ERS S Washington Irvington Intermediate School 103 S Broadway		
	LIB Warner Library 121 N Broadway Tarrytown, NY 10591 Jessica Pacciotti (914) 631-7734 S Tarrytown Nursery PreSchool 15 W Elizabeth Street Tarrytown, NY 10591 (914) 631-8227	RARIES / COMMUNITY CENTE CHOOLS / DAYCARE CENTER New Beginnings Nursery School 42 N Broadway Tarrytown, Ny 10591 (914) 372-6377	RS Washington Irvington Intermediate School 103 S Broadway Tarrytown, NY 10591		
	LIB Warner Library 121 N Broadway Tarrytown, NY 10591 Jessica Pacciotti (914) 631-7734 S Tarrytown Nursery PreSchool 15 W Elizabeth Street Tarrytown, NY 10591 (914) 631-8227	CHOOLS / DAYCARE CENTER New Beginnings Nursery School 42 N Broadway Tarrytown, Ny 10591 (914) 372-6377	RS Washington Irvington Intermediate School 103 S Broadway Tarrytown, NY 10591 (914) 631-4442		
	LIB Warner Library 121 N Broadway Tarrytown, NY 10591 Jessica Pacciotti (914) 631-7734 S Tarrytown Nursery PreSchool 15 W Elizabeth Street Tarrytown, NY 10591 (914) 631-8227	RARIES / COMMUNITY CENTE CHOOLS / DAYCARE CENTER New Beginnings Nursery School 42 N Broadway Tarrytown, Ny 10591 (914) 372-6377 DJACENT PROPERTY OWNER	RS Washington Irvington Intermediate School 103 S Broadway Tarrytown, NY 10591 (914) 631-4442 RS		
	LIB Warner Library 121 N Broadway Tarrytown, NY 10591 Jessica Pacciotti (914) 631-7734 S Tarrytown Nursery PreSchool 15 W Elizabeth Street Tarrytown, NY 10591 (914) 631-8227 A Metropolitan Transportation	RARIES / COMMUNITY CENTE CHOOLS / DAYCARE CENTER New Beginnings Nursery School 42 N Broadway Tarrytown, Ny 10591 (914) 372-6377 DJACENT PROPERTY OWNER Tarrytown Municipality	RS Washington Irvington Intermediate School 103 S Broadway Tarrytown, NY 10591 (914) 631-4442 RS Scott Shachter		
	LIB Warner Library 121 N Broadway Tarrytown, NY 10591 Jessica Pacciotti (914) 631-7734 S Tarrytown Nursery PreSchool 15 W Elizabeth Street Tarrytown, NY 10591 (914) 631-8227 Al Metropolitan Transportation Adjacent Property Owner of 2	CHOOLS / DAYCARE CENTER New Beginnings Nursery School 42 N Broadway Tarrytown, Ny 10591 (914) 372-6377 DJACENT PROPERTY OWNER Tarrytown Municipality Adjacent Property Owner of 50	RS Washington Irvington Intermediate School 103 S Broadway Tarrytown, NY 10591 (914) 631-4442 RS Scott Shachter Adjacent Property Owner of 61		
	LIB Warner Library 121 N Broadway Tarrytown, NY 10591 Jessica Pacciotti (914) 631-7734 S Tarrytown Nursery PreSchool 15 W Elizabeth Street Tarrytown, NY 10591 (914) 631-8227 Al Metropolitan Transportation Adjacent Property Owner of 2 Depot Plaza	CHOOLS / DAYCARE CENTER New Beginnings Nursery School 42 N Broadway Tarrytown, Ny 10591 (914) 372-6377 DJACENT PROPERTY OWNER Tarrytown Municipality Adjacent Property Owner of 50 White Street	RS Washington Irvington Intermediate School 103 S Broadway Tarrytown, NY 10591 (914) 631-4442 RS Scott Shachter Adjacent Property Owner of 61 Riverside Avenue		
	LIB Warner Library 121 N Broadway Tarrytown, NY 10591 Jessica Pacciotti (914) 631-7734 S Tarrytown Nursery PreSchool 15 W Elizabeth Street Tarrytown, NY 10591 (914) 631-8227 A Metropolitan Transportation Adjacent Property Owner of 2 Depot Plaza 2 Broadway, New York, NY	CHOOLS / DAYCARE CENTER New Beginnings Nursery School 42 N Broadway Tarrytown, Ny 10591 (914) 372-6377 DJACENT PROPERTY OWNER Tarrytown Municipality Adjacent Property Owner of 50 White Street One Town Plaza, Tarrytown, NY	RS Washington Irvington Intermediate School 103 S Broadway Tarrytown, NY 10591 (914) 631-4442 RS Scott Shachter Adjacent Property Owner of 61 Riverside Avenue 61 Riverside Avenue, Tarrytown,		
	LIB Warner Library 121 N Broadway Tarrytown, NY 10591 Jessica Pacciotti (914) 631-7734 S Tarrytown Nursery PreSchool 15 W Elizabeth Street Tarrytown, NY 10591 (914) 631-8227 A Metropolitan Transportation Adjacent Property Owner of 2 Depot Plaza 2 Broadway, New York, NY 10004	CHOOLS / DAYCARE CENTER New Beginnings Nursery School 42 N Broadway Tarrytown, Ny 10591 (914) 372-6377 DJACENT PROPERTY OWNER Tarrytown Municipality Adjacent Property Owner of 50 White Street One Town Plaza, Tarrytown, NY 10591	S Washington Irvington Intermediate School 103 S Broadway Tarrytown, NY 10591 (914) 631-4442 S Scott Shachter Adjacent Property Owner of 61 Riverside Avenue 61 Riverside Avenue, Tarrytown, NY 10591		
	LIB Warner Library 121 N Broadway Tarrytown, NY 10591 Jessica Pacciotti (914) 631-7734 S Tarrytown Nursery PreSchool 15 W Elizabeth Street Tarrytown, NY 10591 (914) 631-8227 A Metropolitan Transportation Adjacent Property Owner of 2 Depot Plaza 2 Broadway, New York, NY 10004 Jeanette Berberich	CHOOLS / DAYCARE CENTER New Beginnings Nursery School 42 N Broadway Tarrytown, Ny 10591 (914) 372-6377 DJACENT PROPERTY OWNEF Tarrytown Municipality Adjacent Property Owner of 50 White Street One Town Plaza, Tarrytown, NY 10591 Charisse Y Lu	S Washington Irvington Intermediate School 103 S Broadway Tarrytown, NY 10591 (914) 631-4442 S Scott Shachter Adjacent Property Owner of 61 Riverside Avenue 61 Riverside Avenue, Tarrytown, NY 10591 Sean Scogna		
	LIB Warner Library 121 N Broadway Tarrytown, NY 10591 Jessica Pacciotti (914) 631-7734 S Tarrytown Nursery PreSchool 15 W Elizabeth Street Tarrytown, NY 10591 (914) 631-8227 A Metropolitan Transportation Adjacent Property Owner of 2 Depot Plaza 2 Broadway, New York, NY 10004 Jeanette Berberich Adjacent Property Owner of 63	CHOOLS / DAYCARE CENTER New Beginnings Nursery School 42 N Broadway Tarrytown, Ny 10591 (914) 372-6377 DJACENT PROPERTY OWNEF Tarrytown Municipality Adjacent Property Owner of 50 White Street One Town Plaza, Tarrytown, NY 10591 Charisse Y Lu Adjacent Property Owner of 95	S Washington Irvington Intermediate School 103 S Broadway Tarrytown, NY 10591 (914) 631-4442 S Scott Shachter Adjacent Property Owner of 61 Riverside Avenue 61 Riverside Avenue, Tarrytown, NY 10591 Sean Scogna Adjacent Property Owner of 99		
	LIB Warner Library 121 N Broadway Tarrytown, NY 10591 Jessica Pacciotti (914) 631-7734 S Tarrytown Nursery PreSchool 15 W Elizabeth Street Tarrytown, NY 10591 (914) 631-8227 Al Metropolitan Transportation Adjacent Property Owner of 2 Depot Plaza 2 Broadway, New York, NY 10004 Jeanette Berberich Adjacent Property Owner of 63 Riverside Avenue	CHOOLS / DAYCARE CENTER New Beginnings Nursery School 42 N Broadway Tarrytown, Ny 10591 (914) 372-6377 DJACENT PROPERTY OWNEF Tarrytown Municipality Adjacent Property Owner of 50 White Street One Town Plaza, Tarrytown, NY 10591 Charisse Y Lu Adjacent Property Owner of 95 MacArthur Lane	S Washington Irvington Intermediate School 103 S Broadway Tarrytown, NY 10591 (914) 631-4442 S Scott Shachter Adjacent Property Owner of 61 Riverside Avenue 61 Riverside Avenue, Tarrytown, NY 10591 Sean Scogna Adjacent Property Owner of 99 MacArthur Lane		
	LIB Warner Library 121 N Broadway Tarrytown, NY 10591 Jessica Pacciotti (914) 631-7734 S Tarrytown Nursery PreSchool 15 W Elizabeth Street Tarrytown, NY 10591 (914) 631-8227 Al Metropolitan Transportation Adjacent Property Owner of 2 Depot Plaza 2 Broadway, New York, NY 10004 Jeanette Berberich Adjacent Property Owner of 63 Riverside Avenue 63 Riverside Avenue, Tarrytown,	CHOOLS / DAYCARE CENTER New Beginnings Nursery School 42 N Broadway Tarrytown, Ny 10591 (914) 372-6377 DJACENT PROPERTY OWNEF Tarrytown Municipality Adjacent Property Owner of 50 White Street One Town Plaza, Tarrytown, NY 10591 Charisse Y Lu Adjacent Property Owner of 95 MacArthur Lane 95 MacArthur Lane, Tarrytown,	S Washington Irvington Intermediate School 103 S Broadway Tarrytown, NY 10591 (914) 631-4442 S Scott Shachter Adjacent Property Owner of 61 Riverside Avenue 61 Riverside Avenue, Tarrytown, NY 10591 Sean Scogna Adjacent Property Owner of 99 MacArthur Lane 99 MacArthur Lane, Tarrytown,		

#### SITE CONTACT LIST

Diana Dulin Adjacent Property Owner of 103 MacArthur Lane 103 MacArthur Lane, Tarrytown, NY 10591	



### Appendix C - Site Location Map

#### **Appendix D - Brownfield Cleanup Program Process**





**Division of Environmental Remediation** 

#### Remedial Programs Scoping Sheet for Major Issues of Public Concern (see instructions)

Site Name: Franklin Courts Coal Storage Site

Site Number: CXXXXXX

Site Address and County: 1-99 Franklin Courts, Tarrytown, New York 10591; County of Westchester

Remedial Party: Franklin Courts JV Partners L.P.

## Note: For Parts 1. – 3. the individuals, groups, organizations, businesses and units of government identified should be added to the site contact list as appropriate.

**Part 1.** List major issues of public concern and information the community wants. Identify individuals, groups, organizations, businesses and/or units of government related to the issue(s) and information needs. Major issues of public concern are standards issues communities are concerned with in relation to brownfield site remediation projects.

How were these issues and/or information needs identified?

Concerns in relation to dust, noise and possible odors are standards issues of concern for communities with in relation to brownfield site remediation projects.

**Part 2.** List important information needed **from** the community, if applicable. Identify individuals, groups, organizations, businesses and/or units of government related to the information needed. No information is needed at this time from the community.

How were these information needs identified?  $\ensuremath{\mathsf{N/A}}$ 

**Part 3.** List major issues and information that need to be communicated **to** the community. Identify individuals, groups, organizations, businesses and/or units of government related to the issue(s) and/or information.

The major issues that need to be communicated to the community are summarized in this CPP. The community will receive periodic fact sheets that will update them in relation to the work being performed on the site so they can communicate any issues they may observed or may experience to the DEC or DOH.

How were these issues and/or information needs identified? These issues and/or information needs are standard for all brownfield sites.

**Part 4.** Identify the following characteristics of the affected/interested community. This knowledge will help to identify and understand issues and information important to the community, and ways to effectively develop and implement the site citizen participation plan (mark all that apply):

**a.** Land use/zoning at and around site:

☑ Residential	Agricultural	Recreational	Commercial	Industrial
<b>b.</b> Residential type	e around site:			
🛛 Urban 🛛 S	Suburban 🗌 Ru	ral		

**c.** Population density around site:  $\Box$  **High**  $\boxtimes$  **Medium**  $\Box$  **Low** 

**d.** Water supply of nearby residences: ⊠ **Public** □ **Private Wells** □ **Mixed** 

e. Is part or all of the water supply of the affected/interested community currently impacted by the site? □ Yes ⊠ No

Provide details if appropriate:

Click here to enter text.

f. Other environmental issues significantly impacted/impacting the affected community?  $\Box$  Yes  $\boxtimes$  No

Provide details if appropriate:

Click here to enter text.

**g.** Is the site and/or the affected/interested community wholly or partly in an Environmental Justice Area? □ Yes ⊠ No

h. Special considerations:
□ Language □ Age □ Transportation ⊠ Other

Explain any marked categories in **h**: 48% Minority Population

**Part 5.** The site contact list must include, at a minimum, the individuals, groups, and organizations identified in Part 2. of the Citizen Participation Plan under 'Site Contact List'. Are *other* individuals, groups, organizations, and units of government affected by, or interested in, the site, or its remedial program? (Mark and identify all that apply, then adjust the site contact list as appropriate.)

- □ Non-Adjacent Residents/Property Owners: Click here to enter text.
- □ Local Officials: Click here to enter text.
- □ **Media:** Click here to enter text.
- **Business/Commercial Interests:** Click here to enter text.
- □ Labor Group(s)/Employees: Click here to enter text.
- □ Indian Nation: Click here to enter text.
- □ Citizens/Community Group(s): Click here to enter text.
- **Environmental Justice Group(s):** Click here to enter text.
- **Environmental Group(s):** Click here to enter text.
- **Civic Group(s):** Click here to enter text.
- **Recreational Group(s):** Click here to enter text.
- **Other(s):** Click here to enter text.

#### Prepared/Updated By: Linda Shaw, Esq.

Reviewed/Approved By: Click here to enter text.

Date: 10/17/23

Date: Click here to enter text.