## O'neill, Christopher (DEC)

**From:** O'neill, Christopher (DEC)

**Sent:** Tuesday, April 02, 2019 11:15 AM

**To:** 'Tom Johnson'

Cc: Mark Williams; Stefan Truex; Charles Porreca; Beverly Commerford; Mustico, Richard X (DEC);

Karpinski, Steven (HEALTH); Deming, Justin H (HEALTH)

**Subject:** RE: Troy Belting (BCP#C401067) 1,4-dioxane analysis

NYSDEC has no objection to limiting the reported groundwater sampling analytical results for 1,4-dioxane to those generated by EPA Method 8270D SIM, as you have described below.

Chris O'Neill NYSDEC – Schenectady 518-357-2394

**From:** Tom Johnson [mailto:johnsont@sterlingenvironmental.com]

Sent: Tuesday, April 02, 2019 10:26 AM

To: O'neill, Christopher (DEC) <christopher.oneill@dec.ny.gov>

Cc: Mark Williams <mark.williams@sterlingenvironmental.com>; Stefan Truex

<Stefan.Truex@sterlingenvironmental.com>; Charles Porreca <charles.porreca@sterlingenvironmental.com>; Beverly

Commerford <br/>
<br/>beverly.commerford@sterlingenvironmental.com>

Subject: Troy Belting (BCP#C401067) 1,4-dioxane analysis

ATTENTION: This email came from an external source. Do not open attachments or click on links from unknown senders or unexpected emails.

## Chris:

We have been experiencing a consistent issue when analyzing 1,4-dioxane by both Method 8260 and Method 8270D SIM at sites where data validation is required (e.g., BCP sites). As you are aware, 1,4-dioxane is analyzed by Method 8270D SIM to achieve the necessary lower detection limit; however, 1,4-dioxane results typically also are reported by Method 8260.

The problem arises during data validation where 1,4-dioxane results by Method 8260 often are rejected as unusable because the relative response factor is below the allowable minimum in the associated initial and/or continuing calibration, while the results for 1,4-dioxane analyzed by Method 8270D SIM are acceptable. There is a potential for confusion if there are both rejected results and acceptable results for the same compound in the same sample. Sterling's solution to this issue is to have the lab <u>not</u> report the 1,4-dioxane results by Method 8260 so the data are not rejected during data validation, opting instead to report only the more accurate Method 8270D SIM results. Please confirm your agreement with this approach for the upcoming groundwater sampling event at the Troy Belting facility.

Thanks,

Tom

Tom Johnson, P.G., C.P.G. Senior Hydrogeologist Sterling Environmental Engineering, P.C. 24 Wade Road Latham, New York 12110

Latham, New York 12110 Telephone: (518) 456-4900 Fax: (518) 456-3532

Thomas.Johnson@sterlingenvironmental.com

 $\frac{https://protect2.fireeye.com/url?k=55eac2c9-09ccfaf7-55e83bfc-000babda0031-8ccb3facca446438\&u=http://www.sterlingenvironmental.com/}{}$ 

NOTICE: This e-mail and any attachment contain confidential information that may be legally privileged. If you are not the intended recipient, you must not review, retransmit, print, copy, use or disseminate this email or the information contained therein. If you have received this email in error, please immediately notify us by return email and delete the message. If this email contains a forwarded email or is a reply to a prior email, the contents may not have been produced by the sender and therefore we are not responsible for its contents.