



C&S Companies
141 Elm Street, Suite 100
Buffalo NY 14203
p: (716) 847-1630
f: (716) 847-1454
www.cscos.com

MEMORANDUM

REMEDIAL INVESTIGATION

TO: Joshua Vaccaro, NYSDEC

FROM: Cody Martin, C&S

RE: Remedial Investigation Results
301 Connecticut Street Site
BCP Site No. C915345

FILE: C&S Project No. V20.001.005

DATE: September 20, 2019 (Revision 01 October 2, 2019)

C&S Engineers, Inc. (C&S) is providing this memorandum to present soil sampling results at the 301 Connecticut Street Site (BCP Site No. C915345).

BCP Remedial Investigation

RI activities were completed as follows:

Soil Sampling	8/5/2019, 8/9/2019, 8/12/2019 & 9/10/2019
Groundwater Sampling	4/11/2019 & 5/21/2019
Offsite Soil Sampling	9/9/2019 & 9/10/2019
Offsite Groundwater Sampling	9/10/2019

Samples were collected from these locations as described in the Remedial Investigation / Interim Remedial Measures Work Plan. **Figure 1** shows the locations of the samples on the BCP Site.

Findings

Site Geology

The Site is comprised of asphalt underlain by urban fill and native soils. Asphalt thickness varied throughout the Site. Generally, asphalt was approximately five to twelve inches thick. Underneath the asphalt, the Site contains urban fill to approximate depths ranging from one to four feet below grade, in most areas. Urban fill is defined as material coming from anthropogenic sources re-worked to build a site to a defined grade. The urban fill material at the Site contains:

- Crushed Rock

REMEDIAL INVESTIGATION

301 Connecticut Street Site

September, 2019

Page 2

- Sand
- Silt
- Clay
- Plastics
- Construction Debris
- Lumber
- Ash/Cinders
- Ceramics
- Bricks
- Metals

The urban fill at this Site consisted of a mixture of sand, silt, clay and gravel with varying amounts of anthropogenic materials. Color of the fill material varied between light grey, brown, dark grey and black. Beneath the fill material, native material consists of moist brown silty clay. Boring logs and multiple refusals of soil borings throughout the Site, indicate that this native brown clay can be very dense at depths beginning as shallow as 1 to 2 feet below ground surface. The January 2019 geotechnical study indicated that this native material extends to the bedrock and identified the bedrock as thinly to thickly bedded grey limestone located approximately 29 to 36 feet below ground surface.

Groundwater across this site was present at depths of approximately five to six feet below ground surface. The attached groundwater sampling memos from the April and May 2019 groundwater investigation provide the results for those rounds of sampling. **Figure 3** also shows groundwater sampling results and groundwater elevations.

Methodology and Results

Initial sampling provided evidence of lead contamination near the northern corner of the site. Labeled as the “X Delineation”, this area of the site appeared to contain deeper areas of crushed stone. Based on previous reports and photographs, a portion of grid A1 was remediated and backfilled to 12 to 15 feet when the tanks were removed from the fuel station that was previously located on that site.

Two other delineation areas were investigated to determine extents of petroleum contamination uncovered in previous sampling. These areas were labeled as “Y and Z Delineation” areas and were located along Connecticut Street, just southwest of the lead delineation area.

Grid location C1 and multiple locations within the Y and Z delineation areas did exhibit evidence of petroleum contamination. Staining, odors, and elevated PID measurements were recorded in these areas. Grid location C1 and those other locations contained petroleum-like odors with PID measurements of up to 4000 ppm. Depths of these petroleum impacts extended down 6 to 10 feet below ground surface. Sample results in C1, 2-Z01, and 2-Y05 indicate low level VOCs at concentrations above the Unrestricted Use Soil Cleanup Objectives (SCOs).

Soil borings were advanced throughout the Site to at least 15 feet below ground surface and within the existing buildings. Except for grid location C1 and the delineation areas, no other petroleum impacts were observed onsite.

REMEDIAL INVESTIGATION

301 Connecticut Street Site

September, 2019

Page 3

Analytical Results

Surface Soil Results

Surface soil samples were collected from 3 locations throughout the site. **Table 1** show these surface soil results. Samples were labeled as follows:

Sample ID	
"Grid ID"	Surface Sample

Results indicate many SVOCs, pesticides, and metals present in all three of the sample locations. Analytics show multiple SVOCs above Residential, Restricted Residential, and Industrial Use SCOs in B3, C1, and E1. Pesticides and metals, including lead and zinc, were all also present in these surface soil samples with results above Unrestricted Use SCOs.

Fill Material Results

A total of 7 subsurface soil samples were collected from fill material within soil borings for analysis. **Figure 2** and **Tables 2 and 3** present subsurface soil analytical results and compare the results to Part 375 Soil Cleanup Objectives (SCOs). Samples were labeled as follows:

Sample ID	
"Grid ID"-00-"depth"	Fill Sample

Sample results indicate that the subsurface fill material contains concentrations of SVOCs, pesticides, and metals above multiple SCOs. Lead was detected at a concentration above Restricted Residential Use SCOs in grid location D1. Multiple SVOCs and other metals were detected at concentrations above Unrestricted Use SCOs and Restricted Residential Use SCO in grid locations B4 and D1.

Native Soil Results

During the RI, 18 native soil samples were collected in grid locations as the final confirmatory samples. In addition to collecting samples at the top of the native material, two additional samples were collected at one-foot intervals below the first native soil sample. These deeper samples were submitted to the laboratory but held until the uppermost native soil sample was analyzed. If any analytes exceeded the respective SCOs, the next deeper sample was analyzed for only those compounds that exceed the SCO. If the concentrations in that sample also exceeded the SCOs, the next lower sample was analyzed and the results compared to the SCOs. The intent of this sampling scheme was to identify the depth of remedial action and use the sampling results as the confirmatory sample results for the IRMs. Samples were labeled as follows:

REMEDIAL INVESTIGATION

301 Connecticut Street Site

September, 2019

Page 4

Sample ID	
"Grid ID"-01-"depth"	1 st Native Sample
"Grid ID"-02-"depth"	2 nd Native Sample
"Grid ID"-03-"depth"	3 rd Native Sample

Results indicate VOC and metal contamination in the first native sample. Grid locations B1 and C4 indicated exceedances for acetone, lead, and zinc above Unrestricted Use SCOs. **Figure 2** and **Tables 2 and 3** present subsurface soil results. Based on the soil boring and analytical data discussed above, **Figure 4** presents the depths for each grid that will achieve a Track 1 Level Cleanup.

Deep Native Soil Results

Five deep native soil locations were selected to sample from 15 feet below ground surface. **Figure 2** and **Tables 2 and 3** present these deep native subsurface results. Samples were labeled as follows:

Sample ID	
"Grid ID"-04-"depth"	15-foot Native Sample

In four of the five locations sampled, contaminant concentrations did not exceed the Unrestricted Use SCOs. In grid location A1 (within the area backfilled with crushed stone), zinc concentrations exceeded the Unrestricted Use SCO. Considering that zinc is a heavy metal that is not mobile in the subsurface, it is likely that residual stone backfill interfered with the native soil results at 15-feet in this location.

X (Lead) Delineation

Initial sampling indicated elevated lead levels in the subsurface near the northern corner of the site, which resulted in the need for delineation to determine the extents of contamination. Results indicated lead concentrations below Unrestricted Use SCOs for all but one of the sample locations. At a depth of 13 feet below ground surface, 2-X04 had lead levels of 266 mg/kg, exceeding the Unrestricted Use SCOs. Multiple VOCs were detected above Unrestricted Use SCOs in ten of the delineation locations. These VOCs included acetone, ethylbenzene, toluene, and xylenes. In one of the locations, 1-X01, at a depth of 9 feet below ground surface, multiple SVOCs were also detected. Three SVOC analytes in that location had levels exceeding Residential Use SCOs, and two of those three exceeding Restricted Residential Use SCOs. Full lead delineation results are summarized in **Table 4**.

Y and Z (Petroleum) Delineation

Remedial investigation in this area focused on the determination of the extents of petroleum impacts through sampling. Soil borings and sampling indicated that the extent of contamination extends to

REMEDIAL INVESTIGATION

301 Connecticut Street Site

September, 2019

Page 5

approximately 7 to 12 feet below ground surface. Both petroleum delineation areas showed evidence of petroleum impairment toward the northwest. With the addition of soil borings 3-Y04, 2-Y05, and 2-Z05, it appeared this contamination extended toward Connecticut Street. With PID measurements of up to 5,500 ppm in 3-Y04, it was determined that additional sampling beneath the sidewalk and across the street would need to take place. The only contamination which appeared in the analytical results was in soil boring 2-Z01 at a depth of 10 feet below ground surface and soil boring 2-Y05 at a depth of 12 feet below ground surface. Both locations appeared to show total xylenes to have concentrations slightly above Unrestricted Use SCOs, and 2-Y05 showed ethylbenzene concentrations also above Unrestricted Use SCOs. Full Petroleum delineation results can be found in **Table 5**.

Waste Characterization Results

Table 6 present waste characterization results. Based on these results, contaminated material located at the Site is considered non-hazardous.

Groundwater Results

C&S conducted two rounds of groundwater sampling in previous investigations. The results of the sampling was provided to the DEC in two reports (also attached below). Concentrations of VOCs and SVOCs were detected above New York State Groundwater TOGS Standards.

Offsite Sampling Results

Soil

Ten additional soil boring locations were investigated to determine the possibility of petroleum contamination migrating toward Connecticut Street. The locations were drilled and sampled in the sidewalk at the furthest extent toward the southeast side of Connecticut Street that was permitted. Elevated PID measurements were found in five of the locations. The locations of these elevated measurements were adjacent to where elevated PID measurements were found in the original onsite investigation. Samples were collected from the soil interval where the most significant petroleum impacts were observed (staining, or highest PID measurements).

VOCs were detected at concentrations just above Unrestricted Use SCOs in only two of the ten offsite samples. These analytes included total xylenes, and 1,3,5-trimethylbenzene in locations SW-4 and SW-7. These contaminants do not seem to be an issue at their low levels and with the proposed Track 1 cleanup (as shown in **Figure 4**), all sources will be removed. No SVOCs were detected at levels exceeding Unrestricted Use SCOs. Full offsite subsurface soil results can be found in **Table 7**.

Groundwater

Three temporary groundwater monitoring wells were drilled in the sidewalk to the northwest, across Connecticut Street, to examine if petroleum impacts found in the onsite investigation migrated via groundwater. MW-6, which was drilled to a depth of 16 feet below ground surface, was sampled and contained only SVOC (polycyclic aromatic hydrocarbons) concentrations exceeding New York State Groundwater TOGS Standards. The SVOC concentrations were likely due to the turbidity of the groundwater sample. Groundwater from this well showed no evidence of petroleum odors. The two other temporary wells, MW-7 and MW-8, were drilled to depths of 12 to 16 feet below ground surface.

REMEDIAL INVESTIGATION

301 Connecticut Street Site

September, 2019

Page 6

Neither of these two wells produced groundwater and were unable to be sampled. None of the soil borings advanced for the installation of temporary wells showed evidence of petroleum impacts. Full offsite groundwater results can be found in **Table 8**.

Interim Remedial Measures

The RI/IRM Work Plan was approved on August 23, 2019. Based on the RI results, the following Interim Remedial Measures will be implemented:

- Installation of an earth retention system (steel sheeting) along the Site perimeter to allow for the removal of all contaminated material.
- Removal of fill material and any impacted native soils for off-site disposal or treatment at a regulated facility.
- Removal of offsite petroleum impacted soils along Connecticut Street.
- The use of the results of the native samples collected during the RI as confirmation sampling and collection of confirmation sidewall samples during the IRM.
- Decommissioning the two existing groundwater monitoring wells within areas of the deeper excavation. The remaining monitoring wells will be preserved and protected during the remediation. Pending post-remediation groundwater sample results and NYSDEC approval, the remaining monitoring wells may be decommissioned following CP-43 guidance.
- If necessary, dewatering of the excavation area and, as required by the sample data, the treatment of captured water.
- Abatement and demolition of the existing buildings.
- Collection of sidewall samples on the boundary of the Site to document offsite conditions.

The intended cleanup goal for this Site is Track 1, as such, the site-wide excavation and removal to the depths presented in **Figure 4** will not only remediate soil contamination but will also remove onsite groundwater contamination and eliminate the source of offsite concerns.

We respectfully request the Department's review of the results contained herein; please do not hesitate to contact us with any questions or comments.

Very truly yours,

C&S ENGINEERS, INC.



Cody Martin
Project Environmental Scientist

REMEDIAL INVESTIGATION

301 Connecticut Street Site

September, 2019

Page 7



Daniel E. Riker, P.G.


Department Manager – Environmental Services

Attached:


1. Figures 1 through 4
2. Tables 1 through 8
3. Soil Borings
4. April and May Groundwater Memorandums

\\\\cscos.com\\cfile\\ENG\\Project\\V20 - D'Youville College\\V20001002 - D'Youville BCP\\Investigation\\Correspondence\\OUT\\Memorandum Letter\\September 2019 Soil Sampling Memorandum Letter.docx

F:\Project\V20 - D'Youville College\V2001002 - D'Youville BCP\Planning-Study\CADD\Sheet Files\1 SAMPLE LOCATIONS.dwg



C&S Engineers, Inc.
141 Elm Street
Buffalo, New York 14203
Phone: 716-847-1630
Fax: 716-847-1454
www.cscos.com



301 CONNECTICUT STREET SITE
BROWNFIELD CLEANUP PROGRAM
SITE NO. C915345
CITY OF BUFFALO, NEW YORK

MARK	DATE	DESCRIPTION
REVISIONS		
PROJECT NO:	V20.001.002	
DATE:	SEPTEMBER 20, 2019	
DRAWN BY:	C. MARTIN	
DESIGNED BY:	C. MARTIN	
CHECKED BY:	D. RIKER	
NO ALTERATION PERMITTED HEREON EXCEPT AS PROVIDED UNDER SECTION 7209 SUBDIVISION 2 OF THE NEW YORK EDUCATION LAW		

SAMPLE
LOCATIONS

FIGURE 1




TABLE 1

SURFACE SOIL RESULTS - 8/12/2019
GRID SAMPLING
301 CONNECTICUT STREET SITE
BCP SITE C915345



	LOCATION - SAMPLE DEPTH					B3	C1	E1
	SAMPLING DATE					08/12/2019	08/12/2019	08/12/2019
	SAMPLE TYPE					SOIL	SOIL	SOIL
	UNITS					mg/kg	mg/kg	mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use			
VOCs								
1,1-Dichloroethane	0.27	19	26	240	480	ND	ND	ND
1,2-Dichloroethane	0.02	2.3	3.1	30	60	ND	ND	ND
2-Butanone (MEK)	0.12	100	100	500	1000	ND	ND	ND
Acetone	0.05	100	100	500	1000	ND	ND	ND
Benzene	0.06	2.9	4.8	44	89	ND	ND	ND
cis-1,2-Dichloroethene	0.25	59	100	500	1000	ND	ND	ND
Cyclohexane						ND	ND	ND
Ethylbenzene	1	30	41	390	780	ND	ND	ND
Isopropylbenzene						ND	ND	ND
Methyl tert-butyl ether	0.93	62	100	500	1000	0.00044 J	ND	0.00027 J
Methylcyclohexane						ND	ND	ND
Methylene Chloride	0.05	51	100	500	1000	ND	ND	ND
Tetrachloroethene	1.3	5.5	19	150	300	ND	ND	ND
Toluene	0.7	100	100	500	1000	ND	ND	ND
Xylenes, Total	0.26	100	100	500	1000	ND	ND	ND
SVOCs								
Benzo[a]anthracene	1	1	1	5.6	11	1.8	39	0.74
Benzo[a]pyrene	1	1	1	1	1.1	2.0	42	1.0
Benzo[b]fluoranthene	1	1	1	5.6	11	3.2	69	1.8
Benzo[g,h,i]perylene	100	100	100	500	1000	1.1	25	0.90
Benzo[k]fluoranthene	0.8	1	3.9	56	110	1.2	23	0.56
Chrysene	1	1	3.9	56	110	2.4	56	1.2
Dibenz[a,h]anthracene	0.33	0.33	0.33	0.56	1.1	0.22	6.2	0.20
Dibenzofuran	7	14	59	350	1000	0.034 J	1.2 J	ND
Fluoranthene	100	100	100	500	1000	4.3	110	1.8
Fluorene	30	100	100	500	1000	0.083 J	3.3 J	0.020 J
Indeno[1,2,3-cd]pyrene	0.5	0.5	0.5	5.6	11	1.3	29	0.95
Naphthalene	12	100	100	500	1000	0.017 J	0.25 J	ND
Phenanthrene	100	100	100	500	1000	1.7	53	0.49
Pyrene	100	100	100	500	1000	3.6	89	1.5
Pesticidies								
4,4'-DDD	0.0033	2.6	13	92	180	ND	ND	0.0043 Jp
4,4'-DDE	0.0033	1.8	8.9	62	120	0.0089	0.0083 J	0.15 p
4,4'-DDT	0.0033	1.7	7.9	47	94	0.0089	0.056	0.13 p
Dieldrin	0.005	0.039	0.2	1.4	2.8	0.0023	ND	ND
PCBs								
Total PCBs	0.1	1	1	1	25	ND	ND	ND
Herbicidies								
Silvex (2,4,5-TP)	3.8	58	100	500	1000	ND	ND	ND

TABLE 1

SURFACE SOIL RESULTS - 8/12/2019
GRID SAMPLING
301 CONNECTICUT STREET SITE
BCP SITE C915345



	LOCATION - SAMPLE DEPTH					B3	C1	E1
	SAMPLING DATE					08/12/2019	08/12/2019	08/12/2019
	SAMPLE TYPE					SOIL	SOIL	SOIL
	UNITS					mg/kg	mg/kg	mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use			
Metals								
Aluminum						13300	6270	13700
Mercury	0.18	0.81	0.81	2.8	5.7	0.092	0.040	0.046
Arsenic	13	16	16	16	16	6.7	4.3 J	3.6
Barium	350	350	400	400	10000	112	120	77.3
Beryllium	7.2	14	72	590	2700	0.77	0.40 J	0.57
Cadmium	2.5	2.5	4.3	9.3	60	0.46 J	0.54 J	0.16 J
Calcium						29200	32900	6340
Chromium						18.2	17.7	17.0
Cobalt						8.4 J	4.4 J	6.6 J
Copper	50	270	270	270	10000	21.2	24.0	16.8
Iron						28700	12900	19000
Lead	63	400	400	1000	3900	86.1	46.3	25.5
Magnesium						9430	4600	3470
Manganese	1600	2000	2000		10000	705	775	299
Nickel	30	140	310	310	10000	18.8	13.0 J	14.6
Potassium						1840	964 J	1510
Selenium	3.9	36	180	1500	6800	ND	ND	ND
Silver	2	36	180	1500	6800	ND	ND	ND
Sodium						761 J	ND	87.7 J
Vanadium						28.9	15.3 J	26.1
Zinc	109	2200			10000	120	116	80.2
WetChem								
Chromium, hexavalent	1	22	110	400	800	ND	ND	ND
Cyanide, Total	27	27	27	27	10000	0.20 J	0.80	0.28 J

Analytical Data compared to Part 375 Standards and DER-10

ND indicates analyte was not detected.

Blank space indicates analyte was not analyzed for in that sample.

* - LCS or LCSD is outside acceptance limits.

F1 - MS and/or MSD Recovery is outside acceptance limits.

F2 - MS/MSD RPD exceeds control limits

J - Result is less than the RL but greater than or equal to the MDL and the concentration is an approximate value.

p - The %RPD between the primary and confirmation column/detector is >40%. The lower value has been reported.

TABLE 2

SUBSURFACE SOIL RESULTS - 8/8/2019 - 8/9/2019 8/12/2019 AND 9/10/2019

GRID SAMPLING

301 CONNECTICUT STREET SITE

BCP SITE C915345



	LOCATION - SAMPLE DEPTH					A1-00-11ft	A1-01-12ft	A1-02-13ft	A1-03-14ft	A1-04-15ft	A2-00-1ft	A2-01-2ft	B1-01-1-2ft	B1-02-3ft
	SAMPLING DATE					08/12/2019	08/12/2019	08/12/2019	08/12/2019	08/12/2019	09/10/2019	09/10/2019	08/08/2019	08/08/2019
	SAMPLE TYPE					SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
	UNITS					mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use									
VOCs														
1,1-Dichloroethane	0.27	19	26	240	480	ND	ND			ND	ND	ND	ND	
1,2-Dichloroethane	0.02	2.3	3.1	30	60	ND	ND			ND	ND	ND	ND	
2-Butanone (MEK)	0.12	100	100	500	1000	ND	ND			ND	ND	0.0030 J	ND	
Acetone	0.05	100	100	500	1000	ND	0.011			0.0094	ND	0.016	0.0065 J	
Benzene	0.06	2.9	4.8	44	89	ND	ND			0.0027	ND	ND	ND	
cis-1,2-Dichloroethene	0.25	59	100	500	1000	ND	ND			0.0012	ND	ND	ND	
Cyclohexane						0.00074 J	ND			ND	ND	ND	ND	
Ethylbenzene	1	30	41	390	780	ND	ND			ND	ND	ND	ND	
Isopropylbenzene						ND	ND			ND	ND	ND	ND	
Methyl tert-butyl ether	0.93	62	100	500	1000	0.00043 J	0.0017			0.012	ND	ND	ND	
Methylcyclohexane						0.0012	ND			ND	ND	ND	ND	
Methylene Chloride	0.05	51	100	500	1000	ND	ND			ND	0.00095 J	ND	ND	
Tetrachloroethene	1.3	5.5	19	150	300	ND	ND			ND	0.046	0.067	ND	
Toluene	0.7	100	100	500	1000	ND	ND			ND	ND	ND	ND	
Xylenes, Total	0.26	100	100	500	1000	0.00060 J	ND			ND	ND	ND	ND	
SVOCs														
Benzo[a]anthracene	1	1	1	5.6	11	ND	ND			0.024 J	0.047	ND	0.051	
Benzo[a]pyrene	1	1	1	1	1.1	ND	ND			0.017 J	ND	ND	0.039 J	
Benzo[b]fluoranthene	1	1	1	5.6	11	ND	ND			0.026 J	0.11	ND	0.068	
Benzo[k]fluoranthene	0.8	1	3.9	56	110	ND	ND			0.0086 J	0.030 J	ND	0.026 J	
Chrysene	1	1	3.9	56	110	ND	ND			0.025 J	0.10 J	ND	0.070 J	
Dibenz(a,h)anthracene	0.33	0.33	0.33	0.56	1.1	ND	ND			ND	0.021 J	ND	ND	
Dibenzofuran	7	14	59	350	1000	ND	ND			ND	ND	ND	ND	
Fluoranthene	100	100	100	500	1000	ND	ND			0.040 J	0.061 J	ND	0.10 J	
Fluorene	30	100	100	500	1000	ND	ND			ND	ND	ND	ND	
Indeno[1,2,3-cd]pyrene	0.5	0.5	0.5	5.6	11	ND	ND			0.017 J	0.049	ND	0.039 J	
Naphthalene	12	100	100	500	1000	ND	ND			ND	ND	ND	ND	
Phenanthrene	100	100	100	500	1000	0.028 J	ND			0.013 J	0.024 J	ND	0.051 J	
Pyrene	100	100	100	500	1000	ND	ND			0.035 J	0.055 J	ND	0.093 J	
Pesticidies														
4,4'-DDD	0.0033	2.6	13	92	180	ND	ND			ND	ND			
4,4'-DDE	0.0033	1.8	8.9	62	120	ND	ND			ND	ND			
4,4'-DDT	0.0033	1.7	7.9	47	94	ND	ND			ND	ND			
PCBs														
Total PCBs	0.1	1	1	1	25	ND	ND			ND	ND			
Herbicidies														
Silvex (2,4,5-TP)	3.8	58	100	500	1000	ND	ND			ND	ND			

TABLE 2

SUBSURFACE SOIL RESULTS - 8/8/2019 - 8/9/2019 8/12/2019 AND 9/10/2019

GRID SAMPLING

301 CONNECTICUT STREET SITE

BCP SITE C915345



LOCATION - SAMPLE DEPTH						A1-00-11ft	A1-01-12ft	A1-02-13ft	A1-03-14ft	A1-04-15ft	A2-00-1ft	A2-01-2ft	B1-01-1-2ft	B1-02-3ft
SAMPLING DATE						08/12/2019	08/12/2019	08/12/2019	08/12/2019	08/12/2019	09/10/2019	09/10/2019	08/08/2019	08/08/2019
SAMPLE TYPE						SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
UNITS						mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use										
Metals														
Aluminum						579	4290			4440	11100	14500	11400	
Mercury	0.18	0.81	0.81	2.8	5.7	ND	ND			ND	0.14	0.070	0.16	
Arsenic	13	16	16	16	16	ND	1.8 J			1.7 J	9.0	4.5	6.0	
Barium	350	350	400	400	10000	2.4 J	39.4 J			44.5	192	115	110	
Beryllium	7.2	14	72	590	2700	ND	0.23 J			0.24 J	0.58	0.78	0.66	
Cadmium	2.5	2.5	4.3	9.3	60	ND	0.42 J			0.35 J	ND	ND	ND	
Calcium						195000	87000			84100	77200	5470	25400	
Chromium						3.2	6.7			7.2	17.3	21.5	17.3	
Cobalt						ND	2.9 J			3.2 J	8.3 J	9.7 J	7.5 J	
Copper	50	270	270	270	10000	3.5 J	12.8			12.2	17.5	18.2	18.9	
Iron						1730	8960			9400	23400	25700	19100	
Lead	63	400	400	1000	3900	ND	11.4			10.1	28.7	25.5	191	18.9
Magnesium						3970	36000			30500	29000	6570	12400	
Manganese	1600	2000	2000		10000	61.0	389			418	1040	335	392	
Nickel	30	140	310	310	10000	4.0 J	6.6 J			7.1 J	18.5	24.0	16.9	
Potassium						298 J	1190			1230	1930	1700	1460	
Selenium	3.9	36	180	1500	6800	ND	ND			ND	ND	ND	ND	
Silver	2	36	180	1500	6800	ND	ND F1			ND	ND	ND	ND	
Sodium						260 J	505 J			466 J	803 J	574 J	894 J	
Vanadium						2.3 J	11.9			13.0	27.3	28.1	23.3	
Zinc	109	2200			10000	8.9	127	119	133	125	112	93.5	117	67.4
WetChem														
Chromium, hexavalent	1	22	110	400	800	ND	ND			ND	ND			
Cyanide, Total	27	27	27	27	10000	ND	ND			ND	0.18 J	ND	ND	

Analytical Data compared to Part 375 Standards and DER-10

ND indicates analyte was not detected.

Blank space indicates analyte was not analyzed for in that sample.

* - LCS or LCSD is outside acceptance limits.

F1 - MS and/or MSD Recovery is outside acceptance limits.

F2 - MS/MSD RPD exceeds control limits

J - Result is less than the RL but greater than or equal to the MDL and the concentration is an approximate value.

TABLE 2

SUBSURFACE SOIL RESULTS - 8/8/2019 - 8/9/2019 8/12/2019 AND 9/10/2019

 GRID SAMPLING
 301 CONNECTICUT STREET SITE
 BCP SITE C915345


LOCATION - SAMPLE DEPTH SAMPLING DATE SAMPLE TYPE UNITS						B1-00-1ft 08/08/19 SOIL mg/kg	B2-00-1ft 09/10/2019 SOIL mg/kg	B2-01-2ft 09/10/2019 SOIL mg/kg	B3-01-3ft 09/10/2019 SOIL mg/kg	B4-00-3ft 08/12/2019 SOIL mg/kg	B4-01-4ft 08/12/2019 SOIL mg/kg	B4-04-15ft 08/12/2019 SOIL mg/kg	C1-00-7ft 08/08/2019 SOIL mg/kg	C1-01-1ft 08/08/2019 SOIL mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use									
VOCs														
1,1-Dichloroethane	0.27	19	26	240	480	ND	ND	ND	ND	ND	ND	ND	ND	ND
1,2-Dichloroethane	0.02	2.3	3.1	30	60	ND	ND	ND	ND	ND	ND	ND	ND	ND
2-Butanone (MEK)	0.12	100	100	500	1000	ND	ND	ND	ND	0.0058	ND	ND	ND	ND
Acetone	0.05	100	100	500	1000	0.010	ND	ND	ND	0.034	0.021	ND	ND	ND
Benzene	0.06	2.9	4.8	44	89	ND	ND	ND	ND	ND	ND	ND	ND	ND
cis-1,2-Dichloroethene	0.25	59	100	500	1000	ND	ND	ND	ND	ND	ND	ND	ND	ND
Cyclohexane						ND	ND	ND	ND	ND	ND	ND	3.1 *	ND
Ethylbenzene	1	30	41	390	780	ND	ND	ND	ND	ND	ND	ND	1.9	ND
Isopropylbenzene						ND	ND	ND	ND	ND	ND	ND	0.83	ND
Methyl tert-butyl ether	0.93	62	100	500	1000	ND	ND	ND	ND	ND	ND	0.00034 J	ND	ND
Methylcyclohexane						ND	ND	ND	ND	ND	ND	ND	17	ND
Methylene Chloride	0.05	51	100	500	1000	ND	0.00072 J	0.00084 J	ND	ND	ND	ND	ND	ND
Tetrachloroethene	1.3	5.5	19	150	300	ND	ND	ND	ND	ND	ND	ND	ND	ND
Toluene	0.7	100	100	500	1000	ND	ND	ND	ND	ND	ND	ND	0.12	ND
Xylenes, Total	0.26	100	100	500	1000	0.0018 J	ND	ND	ND	ND	ND	ND	5.1	ND
SVOCs														
Benzo[a]anthracene	1	1	1	5.6	11	0.085	0.073	ND	ND	2.8	ND	ND		ND
Benzo[a]pyrene	1	1	1	1	1.1	0.081	0.050	ND	ND	2.0	ND F1	ND		ND
Benzo[b]fluoranthene	1	1	1	5.6	11	0.13	0.089	ND	0.025 J	2.7	ND F1	ND		0.019 J
Benzo[k]fluoranthene	0.8	1	3.9	56	110	0.058	0.028 J	ND	ND	1.3	ND F1	ND		ND
Chrysene	1	1	3.9	56	110	0.12 J	0.077 J	ND	ND	2.6	ND	ND		ND
Dibenz(a,h)anthracene	0.33	0.33	0.33	0.56	1.1	ND	ND	ND	ND	0.34	ND	ND		ND
Dibenzofuran	7	14	59	350	1000	ND	ND	ND	ND	0.64 J	ND F1	ND		ND
Fluoranthene	100	100	100	500	1000	0.20 J	0.13 J	ND	0.025 J	7.0	ND	ND		ND
Fluorene	30	100	100	500	1000	ND	ND	ND	ND	0.97 J	ND F1	ND		ND
Indeno[1,2,3-cd]pyrene	0.5	0.5	0.5	5.6	11	0.080	0.035 J	ND	ND	1.3	ND	ND		ND
Naphthalene	12	100	100	500	1000	ND	ND	ND	ND	0.30 J	ND F1	ND		ND
Phenanthrene	100	100	100	500	1000	0.094 J	0.092 J	ND	0.020 J	7.2	ND	ND		ND
Pyrene	100	100	100	500	1000	0.19 J	0.11 J	ND	0.020 J	5.6	ND	ND		ND
Pesticidies														
4,4'-DDD	0.0033	2.6	13	92	180		ND	ND		ND		ND		
4,4'-DDE	0.0033	1.8	8.9	62	120		ND	ND		0.0030 J		ND		
4,4'-DDT	0.0033	1.7	7.9	47	94		ND	ND		ND		ND		
PCBs														
Total PCBs	0.1	1	1	1	25		0.091	ND		ND		ND		
Herbicidies														
Silvex (2,4,5-TP)	3.8	58	100	500	1000		ND	ND		ND		ND		

TABLE 2

SUBSURFACE SOIL RESULTS - 8/8/2019 - 8/9/2019 8/12/2019 AND 9/10/2019

GRID SAMPLING

301 CONNECTICUT STREET SITE

BCP SITE C915345



LOCATION - SAMPLE DEPTH	SAMPLE DATE	SAMPLE TYPE	UNITS					B2-00-1ft	B2-01-2ft	B3-01-3ft	B4-00-3ft	B4-01-4ft	B4-04-15ft	C1-00-7ft	C1-01-1ft
			Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use								
Metals															
Aluminum								10400	10000	12700	12100	9820	13600	11900	15000
Mercury	0.18	0.81	0.81	2.8	5.7			0.15	0.58	0.021	0.093	0.21	0.016 J	ND	0.034
Arsenic	13	16	16	16	16			6.3	5.8	3.0	4.6	5.6	3.9	3.4	3.4
Barium	350	350	400	400	10000			97.2	86.4	57.4	106	115	96.0	119	129
Beryllium	7.2	14	72	590	2700			0.63	0.55	0.65	0.64	0.63	0.67	0.64	0.72
Cadmium	2.5	2.5	4.3	9.3	60			ND	ND	ND	ND	0.66 J	ND	0.29 J	ND
Calcium								20300	39000	3850	3800	47900	16400	73000	2960
Chromium								16.0	15.1	19.0	18.6	15.3	19.0	17.2	20.4
Cobalt								8.7 J	6.4 J	7.1 J	8.4 J	6.9 J	8.4 J	9.5 J	8.6 J
Copper	50	270	270	270	10000			15.3	19.4	13.2	13.8	61.6	15.0	18.8	10.5
Iron								21000	18100	21200	22900	18800	22900	20600	22700
Lead	63	400	400	1000	3900			96.1	120	18.3	20.3	332	15.0	13.2	15.9
Magnesium								10500	16400	5040	4800	18300	12800	26000	4240
Manganese	1600	2000	2000		10000			545	372	203	397	576	297	597	221
Nickel	30	140	310	310	10000			17.0	15.1	18.6	19.1	18.2	20.9	23.1	19.8
Potassium								1200	1570	1560	1620	1640	2130	2920	1530
Selenium	3.9	36	180	1500	6800			ND	ND	ND	ND	ND	ND	ND	ND
Silver	2	36	180	1500	6800			ND	ND	ND	ND	ND	ND	ND	ND
Sodium								811 J	214 J	167 J	88.1 J	382 J	238 J	204 J	546 J
Vanadium								24.3	22.1	20.2	24.3	22.0	26.1	25.2	26.1
Zinc	109	2200			10000			96.4	94.9	76.2	81.2	249	85.9	93.4	76.1
WetChem															
Chromium, hexavalent	1	22	110	400	800				ND	ND		ND		ND	
Cyanide, Total	27	27	27	27	10000			ND F1	0.15 J	ND	ND	0.25 J	ND	ND	0.15 J

Analytical Data compared to Part 375 Standards and DER-10

ND indicates analyte was not detected.

Blank space indicates analyte was not analyzed for in that sample.

* - LCS or LCSD is outside acceptance limits.

F1 - MS and/or MSD Recovery is outside acceptance limits.

F2 - MS/MSD RPD exceeds control limits

J - Result is less than the RL but greater than or equal to the MDL and the concentration is an approximate value.

TABLE 2

SUBSURFACE SOIL RESULTS - 8/8/2019 - 8/9/2019 8/12/2019 AND 9/10/2019

GRID SAMPLING

301 CONNECTICUT STREET SITE

BCP SITE C915345



LOCATION - SAMPLE DEPTH SAMPLING DATE SAMPLE TYPE UNITS						C2-01-1ft 08/08/2019 SOIL mg/kg	C3-01-2ft 08/08/2019 SOIL mg/kg	C4-01-3ft 08/08/2019 SOIL mg/kg	C4-02-4ft 08/08/2019 SOIL mg/kg	D1-00-2ft 08/09/2019 SOIL mg/kg	D1-01-6ft 08/09/2019 SOIL mg/kg	D1-04-15ft 08/09/2019 SOIL mg/kg	D1-08-19ft 08/09/2019 SOIL mg/kg	D2-01-3ft 08/09/2019 SOIL mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use									
VOCs														
1,1-Dichloroethane	0.27	19	26	240	480	ND	ND	ND		ND	ND	ND	ND	ND
1,2-Dichloroethane	0.02	2.3	3.1	30	60	ND	ND	ND		ND	ND	ND	ND	ND
2-Butanone (MEK)	0.12	100	100	500	1000	ND	ND	0.017		ND	ND	ND	ND	ND
Acetone	0.05	100	100	500	1000	ND	ND	0.13	0.10	0.023	ND	0.011	0.012	0.011
Benzene	0.06	2.9	4.8	44	89	ND	ND	ND		ND	ND	ND	ND	ND
cis-1,2-Dichloroethene	0.25	59	100	500	1000	ND	ND	ND		ND	ND	ND	ND	ND
Cyclohexane						ND	ND	ND		ND	ND	ND	ND	ND
Ethylbenzene	1	30	41	390	780	ND	ND	ND		ND	ND	ND	ND	ND
Isopropylbenzene						ND	ND	ND		ND	ND	ND	ND	ND
Methyl tert-butyl ether	0.93	62	100	500	1000	ND	ND	ND		ND	ND	ND	ND	ND
Methylcyclohexane						ND	ND	ND		ND	ND	ND	ND	ND
Methylene Chloride	0.05	51	100	500	1000	ND	ND	ND		0.0010 J	0.0020	0.0029	0.0032	0.0013
Tetrachloroethene	1.3	5.5	19	150	300	ND	ND	ND		ND	ND	ND	ND	ND
Toluene	0.7	100	100	500	1000	ND	ND	ND		ND	ND	ND	ND	ND
Xylenes, Total	0.26	100	100	500	1000	ND	ND	ND		ND	ND	ND	ND	ND
SVOCs														
Benzo[a]anthracene	1	1	1	5.6	11	0.12	0.065	ND		0.73	ND	0.041	0.093	0.019 J
Benzo[a]pyrene	1	1	1	1	1.1	0.10	0.054	ND		0.74	0.014 J	0.040	0.075	0.019 J
Benzo[b]fluoranthene	1	1	1	5.6	11	0.16	0.087	ND		1.1	0.022 J	0.062	0.13	0.032 J
Benzo[k]fluoranthene	0.8	1	3.9	56	110	0.070	0.037 J	ND		0.42	ND	0.026 J	0.042 J	0.0094 J
Chrysene	1	1	3.9	56	110	0.17 J	0.073 J	ND		1.0	0.020 J	0.072 J	0.12 J	0.026 J
Dibenz(a,h)anthracene	0.33	0.33	0.33	0.56	1.1	0.023 J	ND	ND		0.16	ND	ND	0.020 J	ND
Dibenzofuran	7	14	59	350	1000	ND	ND	ND		0.037 J	ND	ND	ND	ND
Fluoranthene	100	100	100	500	1000	0.36 J	0.10 J	ND		2.0	0.028 J	0.13 J	0.18 J	0.043 J
Fluorene	30	100	100	500	1000	ND	ND	ND		0.064 J	ND	ND	ND	ND
Indeno[1,2,3-cd]pyrene	0.5	0.5	0.5	5.6	11	0.095	0.047	ND		0.72	ND	0.031 J	0.067	0.024 J
Naphthalene	12	100	100	500	1000	ND	ND	ND		0.019 J	ND	ND	ND	ND
Phenanthrene	100	100	100	500	1000	0.18 J	0.056 J	ND		1.2	ND	0.081 J	0.11 J	0.026 J
Pyrene	100	100	100	500	1000	0.34 J	0.11 J	ND		1.9	0.029 J	0.13 J	0.17 J	0.040 J
Pesticidies														
4,4'-DDD	0.0033	2.6	13	92	180		ND	ND		0.016		ND	ND	
4,4'-DDE	0.0033	1.8	8.9	62	120		ND	ND		ND		ND	ND	
4,4'-DDT	0.0033	1.7	7.9	47	94		ND	ND		0.015		ND	ND	
PCBs														
Total PCBs	0.1	1	1	1	25		ND	ND		ND		ND	ND	
Herbicides														
Silvex (2,4,5-TP)	3.8	58	100	500	1000		ND	ND		ND		ND	ND	

TABLE 2

SUBSURFACE SOIL RESULTS - 8/8/2019 - 8/9/2019 8/12/2019 AND 9/10/2019

GRID SAMPLING

301 CONNECTICUT STREET SITE

BCP SITE C915345



LOCATION - SAMPLE DEPTH SAMPLING DATE SAMPLE TYPE UNITS						C2-01-1ft 08/08/2019 SOIL mg/kg	C3-01-2ft 08/08/2019 SOIL mg/kg	C4-01-3ft 08/08/2019 SOIL mg/kg	C4-02-4ft 08/08/2019 SOIL mg/kg	D1-00-2ft 08/09/2019 SOIL mg/kg	D1-01-6ft 08/09/2019 SOIL mg/kg	D1-04-15ft 08/09/2019 SOIL mg/kg	D1-08-19ft 08/09/2019 SOIL mg/kg	D2-01-3ft 08/09/2019 SOIL mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use									
Metals														
Aluminum						12100	7450	15200		6070	6700	5670	11800	6770
Mercury	0.18	0.81	0.81	2.8	5.7	ND	0.013 J	0.025		0.44	0.078	ND	0.080	ND
Arsenic	13	16	16	16	16	4.0	4.8	5.0		8.3	5.7	2.9	4.5	3.2 J
Barium	350	350	400	400	10000	104	64.6	135		143	57.6	56.5	92.8	62.7
Beryllium	7.2	14	72	590	2700	0.75	0.44 J	0.85		0.41 J	0.34 J	0.29 J	0.66	0.37 J
Cadmium	2.5	2.5	4.3	9.3	60	ND	ND	ND		0.57 J	ND	ND	ND	ND
Calcium						18900	84700	3690		29900	68400	66600	25400	77300
Chromium						18.5	15.2	22.0		17.8	11.0	9.8	18.4	11.2
Cobalt						7.3 J	5.3 J	10.2 J		5.0 J	5.4 J	4.7 J	7.8 J	5.8 J
Copper	50	270	270	270	10000	14.4	14.8	14.0		37.6	16.0	10.9	19.8	10.8
Iron						23100	15200	25500		20000	13700	11900	20000	12900
Lead	63	400	400	1000	3900	18.1	41.4	17.9		545	45.9	10.8	48.4	13.3
Magnesium						13000	23200	5470		8390	21000	26600	15300	26700
Manganese	1600	2000	2000		10000	234	368	541		212	337	358	358	407
Nickel	30	140	310	310	10000	18.4	13.7	24.3		14.8	13.3	11.2	19.8	12.4
Potassium						1510	1460	1770		945 J	1260	1350	1790	1300
Selenium	3.9	36	180	1500	6800	ND	ND	ND		ND	ND	ND	ND	ND
Silver	2	36	180	1500	6800	ND	ND	ND		ND	ND	ND	ND	ND
Sodium						795 J	916 J	591 J		1810	728 J	159 J	1680	1280
Vanadium						26.3	19.0	27.7		15.7	15.7	14.7	23.0	15.2
Zinc	109	2200			10000	87.3	73.9	90.1		386	70.5	53.3	122	58.3
WetChem														
Chromium, hexavalent	1	22	110	400	800		ND	ND		ND		ND	ND	
Cyanide, Total	27	27	27	27	10000	ND	ND	ND		0.25 J	ND	ND	ND	ND

Analytical Data compared to Part 375 Standards and DER-10

ND indicates analyte was not detected.

Blank space indicates analyte was not analyzed for in that sample.

* - LCS or LCSD is outside acceptance limits.

F1 - MS and/or MSD Recovery is outside acceptance limits.

F2 - MS/MSD RPD exceeds control limits

J - Result is less than the RL but greater than or equal to the MDL and the concentration is an approximate value.

TABLE 2

SUBSURFACE SOIL RESULTS - 8/8/2019 - 8/9/2019 8/12/2019 AND 9/10/2019

GRID SAMPLING

301 CONNECTICUT STREET SITE

BCP SITE C915345



LOCATION - SAMPLE DEPTH SAMPLING DATE SAMPLE TYPE UNITS						D3-01-6ft 08/09/2019 SOIL mg/kg	D4-01-3ft 08/08/2019 SOIL mg/kg	E1-01-7ft 08/09/2019 SOIL mg/kg	E2-00-1ft 08/09/2019 SOIL mg/kg	E2-01-2ft 08/09/2019 SOIL mg/kg	E2-04-15ft 08/09/2019 SOIL mg/kg	E3-01-2ft 08/12/2019 SOIL mg/kg	E4-01-2ft 08/12/2019 SOIL mg/kg	E4-04-15ft 08/12/2019 SOIL mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use									
VOCs														
1,1-Dichloroethane	0.27	19	26	240	480	ND F1	ND	ND	ND F1	ND	ND	ND	ND	ND
1,2-Dichloroethane	0.02	2.3	3.1	30	60	ND	ND	ND	ND	ND	ND	ND	ND	ND
2-Butanone (MEK)	0.12	100	100	500	1000	ND	ND	ND	ND	ND	ND	ND	ND	ND
Acetone	0.05	100	100	500	1000	ND	0.011	ND	0.015 F1	0.0078	ND	ND	0.0066 J	ND
Benzene	0.06	2.9	4.8	44	89	ND F1	ND	ND	ND F1	ND	ND	ND	ND	ND
cis-1,2-Dichloroethene	0.25	59	100	500	1000	ND F1	ND	ND	ND F1	ND	ND	ND	ND	ND
Cyclohexane						ND F1	ND	ND	ND	ND	ND	ND	ND	ND
Ethylbenzene	1	30	41	390	780	ND F1	ND	ND	ND F1	ND	ND	ND	ND	ND
Isopropylbenzene						ND F1	ND	ND	ND F1	ND	ND	ND	ND	ND
Methyl tert-butyl ether	0.93	62	100	500	1000	ND	ND	ND	ND F1	ND	ND	ND	ND	ND
Methylcyclohexane						ND F1	ND	ND	ND	ND	ND	ND	ND	ND
Methylene Chloride	0.05	51	100	500	1000	0.00064 J	0.00083 J	ND	0.00081 JF	0.00096 J	0.00082 J	ND	ND	ND
Tetrachloroethene	1.3	5.5	19	150	300	ND F1	ND	ND	ND F1	ND	ND	ND	ND	ND
Toluene	0.7	100	100	500	1000	ND F1	ND	ND	ND F1	ND	ND	ND	ND	ND
Xylenes, Total	0.26	100	100	500	1000	ND F1	ND	ND	ND F1	ND	ND	ND	ND	ND
SVOCs														
Benzo[a]anthracene	1	1	1	5.6	11	ND	ND	ND	0.055	ND	ND	ND	0.018 J	ND
Benzo[a]pyrene	1	1	1	1	1.1	ND F1	ND	ND	0.043 F1	ND	ND	ND	0.011 J	ND
Benzo[b]fluoranthene	1	1	1	5.6	11	ND	ND	ND	0.088 F1	ND	ND	ND	0.019 J	ND
Benzo[k]fluoranthene	0.8	1	3.9	56	110	ND F1	ND	ND	0.027 JF	ND	ND	ND	ND	ND
Chrysene	1	1	3.9	56	110	ND	ND	ND	0.077 J	ND	ND	ND	0.014 J	ND
Dibenz(a,h)anthracene	0.33	0.33	0.33	0.56	1.1	ND	ND	ND	ND	ND	ND	ND	ND	ND
Dibenzofuran	7	14	59	350	1000	ND F1	ND	ND	ND F1	ND	ND	ND	ND	ND
Fluoranthene	100	100	100	500	1000	0.016 J	ND	ND	0.17 JF	ND	ND	ND	0.023 J	ND
Fluorene	30	100	100	500	1000	ND F1	ND	ND	ND F1	ND	ND	ND	ND	ND
Indeno[1,2,3-cd]pyrene	0.5	0.5	0.5	5.6	11	ND	ND	ND	0.046	ND	ND	ND	ND	ND
Naphthalene	12	100	100	500	1000	ND F1	ND	ND	ND F1	ND	ND	ND	ND	ND
Phenanthrene	100	100	100	500	1000	ND F1	ND	ND	0.078 JF	ND	ND	ND	0.014 J	ND
Pyrene	100	100	100	500	1000	ND	ND	ND	0.16 J	ND	ND	ND	ND	ND
Pesticidies														
4,4'-DDD	0.0033	2.6	13	92	180				ND		ND	ND F2		ND
4,4'-DDE	0.0033	1.8	8.9	62	120				ND *		ND	ND F2		ND
4,4'-DDT	0.0033	1.7	7.9	47	94				ND		ND	ND F2		ND
PCBs														
Total PCBs	0.1	1	1	1	25				ND		ND	ND		ND
Herbicidies														
Silvex (2,4,5-TP)	3.8	58	100	500	1000				ND		ND	ND		ND

TABLE 2

SUBSURFACE SOIL RESULTS - 8/8/2019 - 8/9/2019 8/12/2019 AND 9/10/2019

GRID SAMPLING

301 CONNECTICUT STREET SITE

BCP SITE C915345



LOCATION - SAMPLE DEPTH SAMPLING DATE SAMPLE TYPE UNITS						D3-01-6ft	D4-01-3ft	E1-01-7ft	E2-00-1ft	E2-01-2ft	E2-04-15ft	E3-01-2ft	E4-01-2ft	E4-04-15ft
						08/09/2019	08/08/2019	08/09/2019	08/09/2019	08/09/2019	08/09/2019	08/12/2019	08/12/2019	08/12/2019
						SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
						mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use									
Metals														
Aluminum						6660	9870	5310	12600	10300	5600	12600	19600	6420
Mercury	0.18	0.81	0.81	2.8	5.7	ND	0.013 J	0.086	0.019	0.013 J	0.011 J	0.024	ND	ND
Arsenic	13	16	16	16	16	3.3 J	3.3 J	3.3	5.0	3.4	2.6 J	3.9	4.7	3.2
Barium	350	350	400	400	10000	53.1	56.5	43.5	115	78.2	64.8	115	164	101
Beryllium	7.2	14	72	590	2700	0.43 J	0.52	0.31 J	0.68	0.56	0.28 J	0.68	0.98	0.37
Cadmium	2.5	2.5	4.3	9.3	60	ND	ND	ND	0.31 J	0.17 J	ND	ND	ND	0.19 J
Calcium						83400	25100	79700	80600	63100	74900	5060	4000	82700
Chromium						10.8	15.4	9.5	18.3	16.3	9.9	17.8	27.1	10.2
Cobalt						5.6 J	6.1 J	4.6 J	8.4 J	7.2 J	4.6 J	10.3	11.7	6.7 J
Copper	50	270	270	270	10000	13.6	12.3	15.6	19.9	14.0	13.8	14.0	17.8	14.6
Iron						14000	17600	11900	22600	18600	11500	22600	30500	13000
Lead	63	400	400	1000	3900	12.0	14.6	15.7	19.0	15.9	11.1	17.7	16.9	11.4
Magnesium						31800	16100	30300	29100	29200	31300	6360	7490	34600
Manganese	1600	2000	2000		10000	413	164	329	573	477	350	568	568	430
Nickel	30	140	310	310	10000	12.8	16.2	10.6	20.4	18.1	11.3	21.4	29.9	13.1
Potassium						1450	1460	1290	2440 F1	2010	1360	1490	2750	1580
Selenium	3.9	36	180	1500	6800	ND	ND	ND	ND	ND	ND	ND	ND	ND
Silver	2	36	180	1500	6800	ND	ND	ND	ND	ND	ND	ND	ND	ND
Sodium						688 J	1000 J	424 J	1040	770 J	163 J	477 J	964 J	634 J
Vanadium						17.9	19.7	15.6	27.5	21.5	15.0	23.4	33.4	15.0
Zinc	109	2200			10000	63.2	67.9	85.2	74.5	71.8	76.8	77.0	96.5	68.6
WetChem														
Chromium, hexavalent	1	22	110	400	800				ND		ND	ND		ND
Cyanide, Total	27	27	27	27	10000	ND	ND	ND	ND F1	ND	ND	ND F1	ND	ND

Analytical Data compared to Part 375 Standards and DER-10

ND indicates analyte was not detected.

Blank space indicates analyte was not analyzed for in that sample.

* - LCS or LCSD is outside acceptance limits.

F1 - MS and/or MSD Recovery is outside acceptance limits.

F2 - MS/MSD RPD exceeds control limits

J - Result is less than the RL but greater than or equal to the MDL and the concentration is an approximate value.

TABLE 3

SUBSURFACE SOIL RESULTS - 8/8/2019 - 8/9/2019 AND 8/12/2019
 GRID SAMPLING - EMERGING CONTAMINANTS
 301 CONNECTICUT STREET SITE
 BCP SITE C915345



LOCATION - SAMPLE DEPTH SAMPLING DATE SAMPLE TYPE UNITS						B1-01-1-2ft	B1-01-080819	C1-01-1ft	C2-01-1ft	C3-01-2ft	C4-01-3ft	D1-00-2ft	D1-01-6ft	D1-04-15ft
						08/08/2019	08/08/2019	08/08/2019	08/08/2019	08/08/2019	08/08/2019	08/09/2019	08/09/2019	08/09/2019
						SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
						ug/kg	ug/kg	ug/kg	ug/kg	ug/kg	ug/kg	ug/kg	ug/kg	ug/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use									
LCMS														
Perfluorobutanoic acid (PFBA)						ND	ND	ND	ND	ND	ND	0.069 J	ND	0.089 J
Perfluoropentanoic acid (PFPeA)						ND	ND	ND	ND	ND	ND	ND	ND	ND
Perfluorohexanoic acid (PFHxA)						ND	ND	ND	ND	ND	ND	ND	ND	ND
Perfluoroheptanoic acid (PFHpA)						ND	ND	ND	ND	ND	ND	ND	ND	ND
Perfluorooctanoic acid (PFOA)						ND	ND	ND	ND	ND	ND	ND	ND	ND
Perfluorononanoic acid (PFNA)						ND	ND	ND	ND	ND	ND	ND	ND	ND
Perfluorodecanoic acid (PFDA)						ND	ND	ND	ND	ND	ND	0.065 J	ND	ND
Perfluoroundecanoic acid (PFUnA)						ND	ND	ND	ND	ND	ND	0.063 J	ND	ND
Perfluorododecanoic acid (PFDoA)						ND	ND	ND	ND	ND	ND	ND	ND	ND
Perfluorotridecanoic acid (PFTriA)						ND	ND	ND	ND	ND	ND	ND	ND	ND
Perfluorotetradecanoic acid (PFTeA)						ND	ND	ND	ND	ND	ND	ND	ND	ND
Perfluorobutanesulfonic acid (PFBS)						ND	ND	ND	ND	ND	ND	ND	ND	ND
Perfluorohexanesulfonic acid (PFHxS)						ND	ND	ND	ND	ND	ND	ND	ND	ND
Perfluoroheptanesulfonic Acid (PFHpS)						ND	ND	ND	ND	ND	ND	ND	ND	ND
Perfluorooctanesulfonic acid (PFOS)						ND	0.23 J	0.27 J	ND	ND	ND	2.2	ND	ND
Perfluorodecanesulfonic acid (PFDS)						ND	ND	ND	ND	ND	ND	ND	ND	ND
Perfluorooctanesulfonamide (FOSA)						ND	ND	ND	ND	ND	ND	ND	ND	ND
N-methylperfluorooctanesulfonamidoacetic acid (NMFOSAA)						ND	ND	ND	ND	ND	ND	ND	ND	ND
N-ethylperfluorooctanesulfonamidoacetic acid (NEFOSAA)						ND	ND	ND	ND	ND	ND	ND	ND	ND
6:2 FTS						ND	ND	ND	ND	ND	ND	ND	ND	ND
8:2 FTS						ND	ND	ND	ND	ND	ND	ND	ND	ND

Analytical Data compared to Part 375 Standards and DER-10

ND indicates analyte was not detected.

Blank space indicates analyte was not analyzed for in that sample.

J - Result is less than the RL but greater than or equal to the MDL and the concentration is an approximate value.

TABLE 3

SUBSURFACE SOIL RESULTS - 8/8/2019 - 8/9/2019 AND 8/12/2019
 GRID SAMPLING - EMERGING CONTAMINANTS
 301 CONNECTICUT STREET SITE
 BCP SITE C915345



LOCATION - SAMPLE DEPTH SAMPLING DATE SAMPLE TYPE UNITS						D2-01-3ft	D3-01-6ft	D4-01-3ft	E1-01-7ft	E2-00-1ft	E2-01-2ft	E2-04-15ft
						08/09/2019	08/09/2019	08/09/2019	08/08/2019	08/09/2019	08/09/2019	08/09/2019
						SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
						ug/kg	ug/kg	ug/kg	ug/kg	ug/kg	ug/kg	ug/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use							
LCMS												
Perfluorobutanoic acid (PFBA)						ND	ND	ND	ND	ND	ND	ND
Perfluoropentanoic acid (PFPeA)						ND	ND	ND	ND	ND	ND	ND
Perfluorohexanoic acid (PFHxA)						ND	ND	ND	ND	ND	ND	ND
Perfluoroheptanoic acid (PFHpA)						0.043 J	ND	ND	ND	ND	ND	ND
Perfluorooctanoic acid (PFOA)						0.28	ND	ND	ND	ND	ND	ND
Perfluorononanoic acid (PFNA)						ND	ND	ND	ND	ND	ND	ND
Perfluorodecanoic acid (PFDA)						ND	ND	ND	ND	ND	ND	ND
Perfluoroundecanoic acid (PFUnA)						ND	ND	ND	ND	ND	ND	ND
Perfluorododecanoic acid (PFDoA)						ND	ND	ND	ND	ND	ND	ND
Perfluorotridecanoic acid (PFTriA)						ND	ND	ND	ND	ND	ND	ND
Perfluorotetradecanoic acid (PFTeA)						ND	ND	ND	ND	ND	ND	ND
Perfluorobutanesulfonic acid (PFBS)						ND	ND	0.032 J	ND	ND	ND	ND
Perfluorohexanesulfonic acid (PFHxS)						ND	ND	ND	ND	ND	ND	ND
Perfluoroheptanesulfonic Acid (PFHpS)						ND	ND	ND	ND	ND	ND	ND
Perfluorooctanesulfonic acid (PFOS)						0.51 J	ND	ND	ND	ND	ND	ND
Perfluorodecanesulfonic acid (PFDS)						ND	ND	ND	ND	ND	ND	ND
Perfluorooctanesulfonamide (FOSA)						ND	ND	ND	ND	ND	ND	ND
N-methylperfluorooctanesulfonamidoacetic acid (NMFOSAA)						ND	ND	ND	ND	ND	ND	ND
N-ethylperfluorooctanesulfonamidoacetic acid (NEFOSAA)						ND	ND	ND	ND	ND	ND	ND
6:2 FTS						ND	ND	ND	ND	ND	ND	ND
8:2 FTS						ND	ND	ND	ND	ND	ND	ND

Analytical Data compared to Part 375 Standards and DER-10

ND indicates analyte was not detected.

Blank space indicates analyte was not analyzed for in that sample.

J - Result is less than the RL but greater than or equal to the MDL and the concentration is an approximate value.

TABLE 4

SUBSURFACE SOIL RESULTS - 8/5/2019
X (LEAD) DELINEATION
301 CONNECTICUT STREET SITE
BCP SITE C915345



LOCATION - SAMPLE DEPTH SAMPLING DATE SAMPLE TYPE UNITS						1-X01-9ft 08/05/2018 SOIL mg/kg	1-X01-10ft 08/05/2019 SOIL mg/kg	1-X01-11ft 08/05/2019 SOIL mg/kg	1-X01-12ft 08/05/2019 SOIL mg/kg	1-X01-13ft 08/05/2019 SOIL mg/kg	1-X01-14ft 08/05/2019 SOIL mg/kg	1-X01-15ft 08/05/2019 SOIL mg/kg	1-X02-9ft 08/05/2019 SOIL mg/kg	1-X02-10ft 08/05/2019 SOIL mg/kg	1-X02-11ft 08/05/2019 SOIL mg/kg	1-X02-12ft 08/05/2019 SOIL mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use											
VOCs																
1,1-Dichloroethane	0.27	19	26	240	480	ND	ND	ND	ND	ND	ND	0.00035 J	ND	ND	ND	ND
1,2-Dichloroethane	0.02	2.3	3.1	30	60	ND	ND	ND	ND	ND	0.00045 J	0.0039	ND	ND	ND	0.0028
2-Butanone (MEK)	0.12	100	100	500	1000	ND	0.0036 J	ND	0.0047 J	0.017	ND	ND	ND	0.016	0.011	0.0036 J
Acetone	0.05	100	100	500	1000	0.0071	0.012	0.0067	0.014	0.041	0.014	0.0087	0.0073	ND	0.022	0.019
Benzene	0.06	2.9	4.8	44	89	ND	0.0013	0.0010 J	0.0024	0.011	ND	ND	0.0029	ND	0.0055	0.0024
cis-1,2-Dichloroethene	0.25	59	100	500	1000	ND	ND	ND	ND	0.00017 J	ND	ND	ND	ND	ND	ND
Cyclohexane						0.0010	0.0064	0.016	0.018	0.038	0.00076 J	ND	0.0053	1.4	0.013	0.0049
Ethylbenzene	1	30	41	390	780	0.00023 J	0.017	0.074	0.036	0.0039	ND	ND	0.041	2.7	0.030	0.0096
Isopropylbenzene						ND	0.0024	0.0046	0.0036	0.0084	0.00021 J	ND	0.0033	0.28	0.0039	0.0029
Methyl tert-butyl ether	0.93	62	100	500	1000	0.00039 J	0.00042 J	ND	0.00026 J	0.0013	0.0018	0.012	0.00021 J	ND	0.00068 J	0.00063 J
Methylcyclohexane						0.0013	0.013	0.021	0.011	0.015	ND	ND	0.0053	3.9	0.018	0.0096
Methylene Chloride	0.05	51	100	500	1000	0.0021	ND	ND	ND	ND	0.0023	ND	0.0013	ND	ND	0.00083 J
Tetrachloroethene	1.3	5.5	19	150	300	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Toluene	0.7	100	100	500	1000	ND	0.00080 J	0.00073 J	0.0012	0.0043	ND	ND	0.0011	0.88	0.025	0.0074
Xylenes, Total	0.26	100	100	500	1000	0.00076 J	0.0032	0.0069	0.0058	0.012	0.00066 J	ND	0.0050	9.4	0.011	0.0041
SVOCs																
Benzo[a]anthracene	1	1	1	5.6	11	0.91	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Benzo[a]pyrene	1	1	1	1	1.1	0.83	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Benzo[b]fluoranthene	1	1	1	5.6	11	1.1	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Benzo[k]fluoranthene	0.8	1	3.9	56	110	0.57	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Chrysene	1	1	3.9	56	110	1.2	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Dibenz(a,h)anthracene	0.33	0.33	0.33	0.56	1.1	0.18	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Dibenzofuran	7	14	59	350	1000	0.11 J	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Fluoranthene	100	100	100	500	1000	2.4	ND	ND	ND	0.033 J	ND	ND	ND	ND	ND	ND
Fluorene	30	100	100	500	1000	0.16 J	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Indeno[1,2,3-cd]pyrene	0.5	0.5	0.5	5.6	11	0.63	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Naphthalene	12	100	100	500	1000	ND	0.072 J	0.17 J	0.12 J	0.048 J	ND	ND	0.20 J	0.072 J	0.039 J	0.055 J
Phenanthrene	100	100	100	500	1000	1.8	ND	ND	ND	0.027 J	ND	ND	ND	ND	ND	ND
Pyrene	100	100	100	500	1000	2.2	ND	ND	ND	0.027 J	ND	ND	ND	ND	ND	ND
PCBs																
Total PCBs	0.1	1	1	1	25	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Metals																
Aluminum						248	5450	8130	7380	6780	6230	6010	6930	7370	4490	3920
Mercury	0.18	0.81	0.81	2.8	5.7	ND	0.011 J	0.017 J	0.019	0.017 J	0.012 J	ND	0.015 J	ND	ND	0.013 J
Arsenic	13	16	16	16	16	1.2 J	3.0	4.4	3.6	3.5	3.5	2.4 J	3.7	3.1	3.3	3.1
Barium	350	350	400	400	10000	2.7 J	65.2	85.9	82.9	72.8	72.3	62.3	74.1	112	66.8	61.4
Beryllium	7.2	14	72	590	2700	ND	0.29 J	0.39 J	0.41	0.35	0.31 J	0.27 J	0.31 J	0.37	0.25 J	0.21 J
Cadmium	2.5	2.5	4.3	9.3	60	ND	ND	ND	ND	ND	ND	ND	ND	ND	0.15 J	0.23 J
Calcium						154000	51000	99100	74700	73100	73200	68500	86100	72900	93000	103000
Chromium						2.2	9.2	12.7	12.1	11.5	10.1	9.6	11.3	11.7	7.3	6.4
Cobalt						ND	4.2 J	6.2 J	6.9 J	5.7 J	4.5 J	4.8 J	4.7 J	5.8 J	4.1 J	3.4 J
Copper	50	270	270	270	10000	ND	12.3	15.0	15.0	12.7	31.5	12.3	12.1	15.6	16.9	13.6
Iron						1480	11800	15300	14300	13400	13300	11500	13600	14500	9300	8520
Lead	63	400	400	1000	3900	1.9	5.7	12.7	13.9	11.7	11.5	10.2	10.6	14.3	13.8	12.9

TABLE 4

SUBSURFACE SOIL RESULTS - 8/5/2019
X (LEAD) DELINEATION
301 CONNECTICUT STREET SITE
BCP SITE C915345



	LOCATION - SAMPLE DEPTH					1-X01-9ft	1-X01-10ft	1-X01-11ft	1-X01-12ft	1-X01-13ft	1-X01-14ft	1-X01-15ft	BCP-A 08/05/19	1-X02-9ft	1-X02-10ft	1-X02-11ft	1-X02-12ft
	SAMPLING DATE					08/05/2018	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019
	SAMPLE TYPE					SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
	UNITS					mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use												
Magnesium						5460	14000	44200	29200	26800	28600	28600	34500	25900	41100	39900	29900
Manganese	1600	2000	2000		10000	49.6	293	420	401	406	351	347	375	398	387	403	331
Nickel	30	140	310	310	10000	3.0 J	8.7	14.0	14.5	13.6	11.5	10.9	11.7	12.7	8.1	6.8	11.2
Potassium						174 J	1200	2040	1730	1560	1460	1480	1670	1700	1260	1010	1430
Selenium	3.9	36	180	1500	6800	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Silver	2	36	180	1500	6800	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Sodium						201 J	457 J	602 J	505 J	452 J	359 J	299 J	542 J	517 J	423 J	414 J	379 J
Vanadium						1.5 J	15.6	17.9	17.5	16.0	15.4	15.1	16.2	17.6	13.1	11.1	15.7
Zinc	109	2200			10000	ND	71.0	89.6	74.5	65.2	62.5	71.0	83.7	64.8	84.0	88.7	75.9

Analytical Data compared to Part 375 Standards and DER-10

ND indicates analyte was not detected.

Blank space indicates analyte was not analyzed for in that sample.

* - LCS or LCSD is outside acceptance limits.

F1 - MS and/or MSD Recovery is outside acceptance limits.

J - Result is less than the RL but greater than or equal to the MDL and the concentration is an approximate value.

TABLE 4

SUBSURFACE SOIL RESULTS - 8/5/2019
X (LEAD) DELINEATION
301 CONNECTICUT STREET SITE
BCP SITE C915345



LOCATION - SAMPLE DEPTH SAMPLING DATE SAMPLE TYPE UNITS						1-X02-13ft	1-X02-14ft	1-X03-8-9ft	1-X03-10ft	1-X03-11ft	1-X03-12ft	1-X03-13ft	1-X03-14ft	1-X03-15ft	1-X04-9ft	1-X04-10ft	1-X04-11ft
						08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019
						SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
						mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use												
VOCs																	
1,1-Dichloroethane	0.27	19	26	240	480	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
1,2-Dichloroethane	0.02	2.3	3.1	30	60	0.0073	0.0024	ND	ND	ND	ND	0.00054 J	ND	ND	ND	ND	ND
2-Butanone (MEK)	0.12	100	100	500	1000	0.0028 J	ND	0.0045 J	ND	0.0040 J	ND	0.0037 J	ND	ND	ND	ND	ND
Acetone	0.05	100	100	500	1000	0.0060 J	0.0079	0.011	0.0088	0.011	ND	0.012	0.0094	0.011	ND	ND	ND
Benzene	0.06	2.9	4.8	44	89	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	0.0027	0.0021
cis-1,2-Dichloroethene	0.25	59	100	500	1000	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Cyclohexane						0.0015	ND	ND	ND	0.0015	ND	ND	ND	ND	0.0011	0.0016	0.0042
Ethylbenzene	1	30	41	390	780	0.0023	0.00064 J	ND	ND	ND	0.00084 J	ND	ND	ND	ND	0.011	0.025
Isopropylbenzene						0.00027 J	ND	ND	ND	0.00065 J	0.00069 J	ND	ND	ND	ND	0.00098 J	0.0022
Methyl tert-butyl ether	0.93	62	100	500	1000	0.018	0.015	0.00024 J	0.00018 J	0.00032 J	ND	0.0027	0.031	0.030	ND	0.00034 J	0.00018 J
Methylcyclohexane						0.0017	ND	ND	ND	0.0023	0.0041	ND	ND	ND	0.0019	0.0043	0.0081
Methylene Chloride	0.05	51	100	500	1000	0.00053 J	0.00071 J	0.00078 J	0.00071 J	0.0011	ND	0.0015	0.0012	0.0015	0.0015	ND	ND
Tetrachloroethene	1.3	5.5	19	150	300	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Toluene	0.7	100	100	500	1000	0.0012	ND	ND	ND	ND	ND	ND	ND	ND	ND	0.0013	ND
Xylenes, Total	0.26	100	100	500	1000	0.010	0.0020 J	0.00044 J	0.00032 J	0.00041 J	0.0017 J	0.00033 J	ND	ND	0.00061 J	0.014	0.0060
SVOCs																	
Benzo[a]anthracene	1	1	1	5.6	11	ND	ND	ND	ND	ND	ND	ND	ND	ND	0.086	0.020 J	ND
Benzo[a]pyrene	1	1	1	1	1.1	ND	ND	ND	ND	ND	ND	ND	ND	ND	0.063	ND	ND
Benzo[b]fluoranthene	1	1	1	5.6	11	ND	ND	ND	ND	ND	ND	ND	ND	ND	0.095	0.010 J	ND
Benzo[k]fluoranthene	0.8	1	3.9	56	110	ND	ND	ND	ND	ND	ND	ND	ND	ND	0.028 J	ND	ND
Chrysene	1	1	3.9	56	110	ND	ND	ND	ND	ND	ND	ND	ND	ND	0.14 J	0.011 J	ND
Dibenz(a,h)anthracene	0.33	0.33	0.33	0.56	1.1	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Dibenzofuran	7	14	59	350	1000	ND	ND	ND	ND	ND	ND	ND	ND	ND	0.021 J	ND	ND
Fluoranthene	100	100	100	500	1000	ND	ND	ND	ND	0.018 J	0.023 J	ND	ND	ND	0.27 J	0.017 J	ND
Fluorene	30	100	100	500	1000	ND	ND	ND	ND	ND	ND	ND	ND	ND	0.033 J	ND	ND
Indeno[1,2,3-cd]pyrene	0.5	0.5	0.5	5.6	11	ND	ND	ND	ND	ND	ND	ND	ND	ND	0.058	ND	ND
Naphthalene	12	100	100	500	1000	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	0.074 J	0.27 J
Phenanthrene	100	100	100	500	1000	ND	ND	ND	ND	ND	ND	ND	ND	ND	0.27 J	0.021 J	ND
Pyrene	100	100	100	500	1000	ND	ND	ND	ND	0.014 J	0.022 J	ND	ND	ND	0.29 J	0.020 J	ND
PCBs																	
Total PCBs	0.1	1	1	1	25	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Metals																	
Aluminum						6410	6040	3140	3180	4930	4380	4310	6450	6270	803	6340	6410
Mercury	0.18	0.81	0.81	2.8	5.7	ND	ND	ND	ND	ND	ND	0.013 J	0.011 J	0.012 J	0.012 J	0.013 J	0.014 J
Arsenic	13	16	16	16	16	2.9	3.0	2.5 J	1.8 J	2.7 J	2.8	3.1	3.1	3.4	1.7 J	2.9	3.7
Barium	350	350	400	400	10000	65.7	61.3	34.8 J	25.9 J	63.6	51.4	44.5	65.2	64.3	19.3 J	100	71.1
Beryllium	7.2	14	72	590	2700	0.30 J	0.31 J	0.15 J	0.11 J	0.23 J	0.20 J	0.19 J	0.35	0.32 J	ND	0.33	0.34
Cadmium	2.5	2.5	4.3	9.3	60	ND	ND	ND	0.16 J	0.16 J	ND	ND	ND	ND	0.13 J	ND	ND
Calcium						81100	79600	111000	139000	85800	110000	115000	66300	68800	207000	68700	74300
Chromium						10.5	10.3	5.9	5.4	8.3	7.6	7.3	10.7	10.1	4.1	10.3	10.1
Cobalt						4.6 J	4.8 J	2.3 J	2.1 J	3.1 J	3.4 J	3.4 J	5.5 J	5.3 J	ND	4.3 J	5.9 J
Copper	50	270	270	270	10000	12.8	14.4	12.7	7.3	12.5	13.7	9.3	13.1	13.3	4.1	13.3	16.7
Iron						12500	12000	6870	8440	10000	8660	8910	12800	12400	3050	11700	12000
Lead	63	400	400	1000	3900	11.6	11.6	10.2	6.2	9.8	9.9	11.0	12.4	13.3	50.7	17.9	15.5

TABLE 4

SUBSURFACE SOIL RESULTS - 8/5/2019
X (LEAD) DELINEATION
301 CONNECTICUT STREET SITE
BCP SITE C915345



	LOCATION - SAMPLE DEPTH					1-X02-13ft	1-X02-14ft	1-X03-8-9ft	1-X03-10ft	1-X03-11ft	1-X03-12ft	1-X03-13ft	1-X03-14ft	1-X03-15ft	1-X04-9ft	1-X04-10ft	1-X04-11ft
	SAMPLING DATE					08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019
	SAMPLE TYPE					SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
	UNITS					mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use												
Magnesium						32600	34500	27100	75100	28900	26700	52400	26900	27800	6730	25900	30500
Manganese	1600	2000	2000		10000	352	381	290	372	357	310	391	368	364	79.8	341	427
Nickel	30	140	310	310	10000	11.2	11.3	5.9 J	5.7 J	8.4	7.7	7.6	12.6	12.2	7.0	10.0	12.6
Potassium						1550	1450	832 J	970	1180	1130	1180	1530	1520	379 J	1600	1600
Selenium	3.9	36	180	1500	6800	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Silver	2	36	180	1500	6800	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Sodium						281 J	248 J	457 J	399 J	552 J	468 J	472 J	326 J	287 J	342 J	477 J	430 J
Vanadium						15.9	15.3	8.8 J	8.0 J	13.5	11.4	12.0	15.4	15.0	3.4 J	16.8	15.2
Zinc	109	2200			10000	65.7	59.1	65.8	57.7	108	80.8	81.1	67.0	52.7	38.1	74.2	63.8

Analytical Data compared to Part 375 Standards and DER-10

ND indicates analyte was not detected.

Blank space indicates analyte was not analyzed for in that sample.

* - LCS or LCSD is outside acceptance limits.

F1 - MS and/or MSD Recovery is outside acceptance limits.

J - Result is less than the RL but greater than or equal to the MDL and the concentration is an approximate value.

TABLE 4

SUBSURFACE SOIL RESULTS - 8/5/2019
X (LEAD) DELINEATION
301 CONNECTICUT STREET SITE
BCP SITE C915345



LOCATION - SAMPLE DEPTH SAMPLING DATE SAMPLE TYPE UNITS						1-X04-12ft	1-X04-13ft	1-X04-14ft	1-X04-15ft	2-X01-8ft	2-X01-9ft	2-X01-10ft	2-X01-11ft	2-X02-8ft	2-X02-9ft	2-X02-10ft	2-X02-11ft
						08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019
						SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
						mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use												
VOCs																	
1,1-Dichloroethane	0.27	19	26	240	480	0.00041 J	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
1,2-Dichloroethane	0.02	2.3	3.1	30	60	0.0035	0.0052	0.0045	0.0059	ND	ND	ND	ND	ND	ND	ND	ND
2-Butanone (MEK)	0.12	100	100	500	1000	0.0034 J	0.0041 J	0.0035 J	0.0035 J	ND	ND	ND	ND	ND	0.016	ND	ND
Acetone	0.05	100	100	500	1000	0.020	0.013	0.0078	0.010	0.012	0.013	0.0095	0.015	ND	0.046	ND	0.55
Benzene	0.06	2.9	4.8	44	89	0.00058 J	0.00036 J	0.00053 J	0.00070 J	ND	ND	ND	ND	ND	ND	ND	ND
cis-1,2-Dichloroethene	0.25	59	100	500	1000	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Cyclohexane						0.00037 J	ND	0.00041 J	0.00055 J	ND	ND	ND	ND	ND	ND	0.64	ND
Ethylbenzene	1	30	41	390	780	0.00033 J	0.00042 J	0.00044 J	0.00052 J	ND	ND	ND	ND	ND	0.0052	0.70	0.83
Isopropylbenzene						ND	ND	0.00016 J	0.00020 J	ND	ND	ND	0.00016 J	ND	0.0017	0.19	0.15
Methyl tert-butyl ether	0.93	62	100	500	1000	0.0088	0.0097	0.044	0.032	ND	ND	ND	0.00013 J	ND	ND	ND	ND
Methylcyclohexane						ND	ND	0.00054 J	0.00095 J	ND	ND	ND	ND	ND	0.11	2.7	1.1
Methylene Chloride	0.05	51	100	500	1000	0.00094 J	0.0011	ND	ND	0.0015	0.0028	ND	0.00059 J	ND	ND	ND	ND
Tetrachloroethene	1.3	5.5	19	150	300	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Toluene	0.7	100	100	500	1000	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	0.053 J	0.038 J
Xylenes, Total	0.26	100	100	500	1000	0.0014 J	0.0021	0.0024	0.0033	0.00031 J	ND	ND	ND	ND	0.015	1.8	3.6
SVOCs																	
Benzo[a]anthracene	1	1	1	5.6	11	ND	ND	ND	ND	ND	ND	ND	ND	0.30	0.68	ND	ND
Benzo[a]pyrene	1	1	1	1	1.1	ND	ND	ND	ND	ND	ND	ND	ND	0.24	0.51	ND	ND
Benzo[b]fluoranthene	1	1	1	5.6	11	ND	ND	ND	ND	ND	ND	ND	ND	0.33	0.75	ND	ND
Benzo[k]fluoranthene	0.8	1	3.9	56	110	ND	ND	ND	ND	ND	ND	ND	ND	0.14	0.29	ND	ND
Chrysene	1	1	3.9	56	110	ND	ND	ND	ND	0.022 J	ND	ND	ND	0.34 J	0.84	ND	ND
Dibenz(a,h)anthracene	0.33	0.33	0.33	0.56	1.1	ND	ND	ND	ND	ND	ND	ND	ND	0.047	0.088	ND	ND
Dibenzofuran	7	14	59	350	1000	ND	ND	ND	ND	ND	ND	ND	ND	0.081 J	0.35 J	ND	ND
Fluoranthene	100	100	100	500	1000	ND	ND	ND	ND	0.041 J	ND	ND	ND	1.0	2.7	ND	ND
Fluorene	30	100	100	500	1000	ND	ND	ND	ND	ND	ND	ND	ND	0.094 J	0.37 J	ND	ND
Indeno[1,2,3-cd]pyrene	0.5	0.5	0.5	5.6	11	ND	ND	ND	ND	ND	ND	ND	ND	0.21	0.40	ND	ND
Naphthalene	12	100	100	500	1000	ND	ND	ND	ND	ND	ND	ND	ND	ND	0.12 J	0.50	0.75
Phenanthrene	100	100	100	500	1000	ND	ND	ND	ND	0.027 J	ND	ND	ND	0.87	2.8	ND	ND
Pyrene	100	100	100	500	1000	ND	ND	ND	ND	0.033 J	ND	ND	ND	0.81	2.5	ND	ND
PCBs																	
Total PCBs	0.1	1	1	1	25	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Metals																	
Aluminum						8090	6940	4850	6450	6380	7310	7060	6630	8440	6410	6880	6470
Mercury	0.18	0.81	0.81	2.8	5.7	0.013 J	0.014 J	0.012 J	0.013 J	ND	ND	ND	0.012 J	0.010 J	ND	ND	ND
Arsenic	13	16	16	16	16	3.9	4.4	3.2	3.6	2.4 J	2.6 J	3.0 J	2.5 J	2.6 J	3.2	2.9	3.1
Barium	350	350	400	400	10000	79.8	70.8	43.5	65.1	58.7	83.8	65.7	69.1	61.5	49.7	55.3	50.8
Beryllium	7.2	14	72	590	2700	0.36	0.35	0.22 J	0.33	0.33 J	0.40 J	0.38 J	0.35 J	0.42	0.34 J	0.36 J	0.34 J
Cadmium	2.5	2.5	4.3	9.3	60	0.16 J	ND	ND	ND	ND	ND	ND	0.18 J	0.13 J	0.12 J	0.14 J	0.13 J
Calcium						78800	74500	99300	83300	82100	87700	67100	69300	86700	97700	79900	77600
Chromium						12.6	11.4	8.7	10.2	10.9	12.3	11.8	11.4	13.1	10.4	10.8	10.1
Cobalt						6.1 J	5.2 J	4.0 J	5.1 J	5.1 J	5.5 J	5.7 J	5.7 J	6.2 J	5.2 J	5.6 J	5.3 J
Copper	50	270	270	270	10000	15.3	14.0	10.0	12.2	12.3	14.1	12.9	15.6	13.4	14.7	13.0	12.6
Iron						13900	13400	9920	12600	12500	14100	14500	13900	15100	13300	13700	13700
Lead	63	400	400	1000	3900	14.0	16.5	12.3	27.7	13.4	11.6	12.1	16.2	12.2	13.5	15.2	15.5

TABLE 4

SUBSURFACE SOIL RESULTS - 8/5/2019
X (LEAD) DELINEATION
301 CONNECTICUT STREET SITE
BCP SITE C915345



	LOCATION - SAMPLE DEPTH					1-X04-12ft	1-X04-13ft	1-X04-14ft	1-X04-15ft	2-X01-8ft	2-X01-9ft	2-X01-10ft	2-X01-11ft	2-X02-8ft	2-X02-9ft	2-X02-10ft	2-X02-11ft
	SAMPLING DATE					08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019
	SAMPLE TYPE					SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
	UNITS					mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use												
Magnesium						32100	30000	37400	34700	29300	35200	27500	27800	34600	28500	31900	31500
Manganese	1600	2000	2000		10000	399	359	320	401	405	395	381	387	432	418	426	412
Nickel	30	140	310	310	10000	14.3	12.4	9.8	12.0	12.0	12.8	13.1	12.9	14.5	12.2	11.7	11.9
Potassium						1980	1710	1300	1620	1650	1900	1720	1510	1670	1330	1390	1350
Selenium	3.9	36	180	1500	6800	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Silver	2	36	180	1500	6800	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Sodium						328 J	295 J	233 J	250 J	480 J	614 J	534 J	519 J	564 J	456 J	493 J	450 J
Vanadium						17.8	15.7	11.8	14.5	16.2	18.6	16.9	16.1	18.2	18.8	16.0	15.8
Zinc	109	2200			10000	66.9	59.2	63.6	56.4	70.1	67.8	70.7	76.5	63.1	59.6	69.8	68.3

Analytical Data compared to Part 375 Standards and DER-10

ND indicates analyte was not detected.

Blank space indicates analyte was not analyzed for in that sample.

* - LCS or LCSD is outside acceptance limits.

F1 - MS and/or MSD Recovery is outside acceptance limits.

J - Result is less than the RL but greater than or equal to the MDL and the concentration is an approximate value.

TABLE 4

SUBSURFACE SOIL RESULTS - 8/5/2019
X (LEAD) DELINEATION
301 CONNECTICUT STREET SITE
BCP SITE C915345



LOCATION - SAMPLE DEPTH SAMPLING DATE SAMPLE TYPE UNITS						2-X02-12ft 08/05/2019 SOIL mg/kg	2-X02-13ft 08/05/2019 SOIL mg/kg	2-X02-14ft 08/05/2019 SOIL mg/kg	2-X03-9ft 08/05/2019 SOIL mg/kg	2-X03-10ft 08/05/2019 SOIL mg/kg	2-X03-11ft 08/05/2019 SOIL mg/kg	2-X03-12ft 08/05/2019 SOIL mg/kg	DUP-B-080519 08/05/2019 SOIL mg/kg	2-X04-9ft 08/05/2019 SOIL mg/kg	2-X04-10ft 08/05/2019 SOIL mg/kg	2-X04-11ft 08/05/2019 SOIL mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use											
VOCs																
1,1-Dichloroethane	0.27	19	26	240	480	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
1,2-Dichloroethane	0.02	2.3	3.1	30	60	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
2-Butanone (MEK)	0.12	100	100	500	1000	ND	0.014	0.051	0.0072	0.011	ND	ND	ND	ND	0.0089	0.0067
Acetone	0.05	100	100	500	1000	ND	0.032	0.086	0.011	0.029	0.017	0.0076	0.0096	0.013	0.096	0.10
Benzene	0.06	2.9	4.8	44	89	ND	ND	ND	0.00065 J	0.0095	ND	ND	ND	ND	0.0038	0.0011
cis-1,2-Dichloroethene	0.25	59	100	500	1000	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	0.00028 J
Cyclohexane						0.77	ND	0.0061	0.0036	ND	ND	ND	ND	ND	0.0020	0.011
Ethylbenzene	1	30	41	390	780	1.2	0.070	0.034	0.034	0.29	0.00047 J	0.00029 J	ND	ND	0.050	0.0029
Isopropylbenzene						0.14	0.011	0.0022	0.0016	0.035	ND	ND	ND	ND	0.0052	0.0022
Methyl tert-butyl ether	0.93	62	100	500	1000	ND	ND	ND	ND	0.0091	0.018	0.041	0.033	0.0043	0.015	
Methylcyclohexane						2.4	0.20	0.016	0.0061	0.084	ND	ND	ND	ND	0.0073	0.011
Methylene Chloride	0.05	51	100	500	1000	ND	ND	0.0032	0.00092 J	ND	0.0032	0.00096 J	0.0021	0.00065 J	0.0022	0.0014
Tetrachloroethene	1.3	5.5	19	150	300	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Toluene	0.7	100	100	500	1000	0.10 J	0.0092	0.0035	0.0043	ND	ND	ND	ND	ND	0.0074	0.0014
Xylenes, Total	0.26	100	100	500	1000	6.0	0.40	0.12	0.021	0.13	0.00026 J	ND	ND	ND	0.071	0.018
SVOCs																
Benzo[a]anthracene	1	1	1	5.6	11	0.60	0.041	ND	0.022 J	0.028 J	ND	ND	ND	ND	ND	ND
Benzo[a]pyrene	1	1	1	1	1.1	0.45	0.029 J	ND	0.015 J	0.019 J	ND	ND	ND	ND	ND	ND
Benzo[b]fluoranthene	1	1	1	5.6	11	0.65	0.042	ND	0.023 J	0.020 J	ND	ND	ND	ND	ND	ND
Benzo[k]fluoranthene	0.8	1	3.9	56	110	0.27	0.014 J	ND	ND	0.021 J	ND	ND	ND	ND	ND	ND
Chrysene	1	1	3.9	56	110	0.66	0.046 J	ND	0.019 J	0.029 J	ND	ND	ND	ND	ND	ND
Dibenz(a,h)anthracene	0.33	0.33	0.33	0.56	1.1	0.077	ND	ND	ND	0.016 J	ND	ND	ND	ND	ND	ND
Dibenzofuran	7	14	59	350	1000	0.21 J	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Fluoranthene	100	100	100	500	1000	2.0	0.12 J	ND	0.041 J	0.020 J	ND	ND	ND	ND	ND	ND
Fluorene	30	100	100	500	1000	0.21 J	0.011 J	ND	0.0098 J	ND	ND	ND	ND	ND	ND	ND
Indeno[1,2,3-cd]pyrene	0.5	0.5	0.5	5.6	11	0.36	0.023 J	ND	ND	0.018 J	ND	ND	ND	ND	ND	ND
Naphthalene	12	100	100	500	1000	0.63	0.16 J	0.10 J	0.44	ND	ND	ND	ND	0.18 J	0.025 J	0.020 J
Phenanthrene	100	100	100	500	1000	1.8	0.10 J	ND	0.054 J	ND	ND	ND	ND	ND	ND	ND
Pyrene	100	100	100	500	1000	1.7	0.11 J	ND	0.039 J	0.024 J	ND	ND	ND	ND	ND	ND
PCBs																
Total PCBs	0.1	1	1	1	25	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Metals																
Aluminum						6360	6090	5400	7600	3900	2760	5340	5380	6420	7080	6670
Mercury	0.18	0.81	0.81	2.8	5.7	ND	0.022	ND	ND	ND	0.023	0.013 J	0.020	0.014 J	0.015 J	0.019
Arsenic	13	16	16	16	16	2.5	2.6	2.2 J	3.3	1.6 J	3.6	1.9 J	2.8	2.8	2.8	2.3 J
Barium	350	350	400	400	10000	51.8	47.4	61.8	70.9	49.6	24.5 J	52.1	33.1 J	172	74.2	65.1
Beryllium	7.2	14	72	590	2700	0.33	0.31 J	0.26 J	0.43	0.21 J	0.16 J	0.27 J	0.22 J	0.35	0.35 J	0.35 J
Cadmium	2.5	2.5	4.3	9.3	60	ND	0.12 J	0.21 J	ND	0.29 J	0.29 J	ND	0.18 J	0.18 J	0.23 J	ND
Calcium						71200	74800	89300	56400	93200	126000	117000	71600	80200	84100	90900
Chromium						11.1	10	8.1	11.6	6.6	4.9	8.7	8.5	10.4	11.2	11.0
Cobalt						4.7 J	5.1 J	4.4 J	5.2 J	3.1 J	3.5 J	5.3 J	4.6 J	5.8 J	4.9 J	4.5 J
Copper	50	270	270	270	10000	11.6	12.3	15.1	21.4	12.1	10.5	10.6	10.4	13.4	13.0	12.5
Iron						12500	12700	10700	12400	8390	7150	11900	13000	13300	14200	13200
Lead	63	400	400	1000	3900	12.3	12.4	12.2	39.9	10.8	22.8	10	7.9	26.8	13.8	32.5

TABLE 4

SUBSURFACE SOIL RESULTS - 8/5/2019
X (LEAD) DELINEATION
301 CONNECTICUT STREET SITE
BCP SITE C915345



	LOCATION - SAMPLE DEPTH					2-X02-12ft	2-X02-13ft	2-X02-14ft	2-X03-9ft	2-X03-10ft	2-X03-11ft	2-X03-12ft	DUP-B-080519	2-X04-9ft	2-X04-10ft	2-X04-11ft
	SAMPLING DATE					08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019	08/05/2019
	SAMPLE TYPE					SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
	UNITS					mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use											
Magnesium						27300	29400	36500	15300	38400	65900	56300	29700	32200	35900	34400
Manganese	1600	2000	2000		10000	374	409	421	256	436	332	350	625	401	375	377
Nickel	30	140	310	310	10000	10.9	11.1	9.8	13.1	7.4	8.6	12.8	10.4	12.7	12.0	11.0
Potassium						1290	1290	1480	1230	1030	951	1400	1020	1560	1670	1710
Selenium	3.9	36	180	1500	6800	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Silver	2	36	180	1500	6800	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Sodium						455 J	323 J	263 J	807 J	483 J	400 J	324 J	330 J	376 J	387 J	340 J
Vanadium						15.5	15.2	12.8	16.5	11.5	8.1	13.3	12.5	16.5	17.0	16.0
Zinc	109	2200			10000	61.9	62.3	81.9	66.8	104	67.6	46.5	86.6	65.2	73.5	63.3

Analytical Data compared to Part 375 Standards and DER-10

ND indicates analyte was not detected.

Blank space indicates analyte was not analyzed for in that sample.

* - LCS or LCSD is outside acceptance limits.

F1 - MS and/or MSD Recovery is outside acceptance limits.

J - Result is less than the RL but greater than or equal to the MDL and the concentration is an approximate value.

TABLE 4

SUBSURFACE SOIL RESULTS - 8/5/2019
X (LEAD) DELINEATION
301 CONNECTICUT STREET SITE
BCP SITE C915345



	LOCATION - SAMPLE DEPTH					2-X04-12ft	2-X04-13ft	2-X04-14ft	2-X04-15ft
	SAMPLING DATE					08/05/2019	08/05/2019	08/05/2019	08/05/2019
	SAMPLE TYPE					SOIL	SOIL	SOIL	SOIL
	UNITS					mg/kg	mg/kg	mg/kg	mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use				
VOCs									
1,1-Dichloroethane	0.27	19	26	240	480	ND	ND	ND	ND
1,2-Dichloroethane	0.02	2.3	3.1	30	60	ND	ND	0.020	0.023
2-Butanone (MEK)	0.12	100	100	500	1000	0.0048 J	ND	ND	ND
Acetone	0.05	100	100	500	1000	0.072	ND	0.042	0.032
Benzene	0.06	2.9	4.8	44	89	0.00055 J	0.053 J	0.00041 J	ND
cis-1,2-Dichloroethene	0.25	59	100	500	1000	0.00019 J	ND	ND	ND
Cyclohexane						0.0055	0.069 J	0.00030 J	0.00041 J
Ethylbenzene	1	30	41	390	780	0.0021	0.30	0.0028	0.0012
Isopropylbenzene						0.0032	0.036 J	0.00042 J	0.00018 J
Methyl tert-butyl ether	0.93	62	100	500	1000	0.015	ND	0.016	0.030
Methylcyclohexane						0.0027	0.15	0.00067 J	0.00077 J
Methylene Chloride	0.05	51	100	500	1000	0.0012	ND	0.0013	0.0030
Tetrachloroethene	1.3	5.5	19	150	300	ND	ND	ND	ND
Toluene	0.7	100	100	500	1000	0.00083 J	0.60	0.0029	0.0011
Xylenes, Total	0.26	100	100	500	1000	0.010	1.9	0.017	0.0057
SVOCs									
Benzo[a]anthracene	1	1	1	5.6	11	ND	0.043	ND	ND
Benzo[a]pyrene	1	1	1	1	1.1	ND	0.020 J	ND	ND
Benzo[b]fluoranthene	1	1	1	5.6	11	ND	0.026 J	ND	ND
Benzo[k]fluoranthene	0.8	1	3.9	56	110	ND	0.0095 J	ND	ND
Chrysene	1	1	3.9	56	110	ND	0.066 J	ND	ND
Dibenz(a,h)anthracene	0.33	0.33	0.33	0.56	1.1	ND	ND	ND	ND
Dibenzofuran	7	14	59	350	1000	ND	0.014 J	ND	ND
Fluoranthene	100	100	100	500	1000	ND	0.072 J	ND	ND
Fluorene	30	100	100	500	1000	ND	0.051 J	ND	ND
Indeno[1,2,3-cd]pyrene	0.5	0.5	0.5	5.6	11	ND	ND	ND	ND
Naphthalene	12	100	100	500	1000	ND	0.78 F1	0.011 J	0.016 J
Phenanthrene	100	100	100	500	1000	ND	0.15 J	ND	ND
Pyrene	100	100	100	500	1000	ND	0.14 J	ND	ND
PCBs									
Total PCBs	0.1	1	1	1	25	ND	ND	ND	ND
Metals									
Aluminum						7930	6880	7350	7040
Mercury	0.18	0.81	0.81	2.8	5.7	0.016 J	0.018	0.019	0.015 J
Arsenic	13	16	16	16	16	3.4	2.8 J	1.8 J	2.1 J
Barium	350	350	400	400	10000	75.0	117	75.5	79.3
Beryllium	7.2	14	72	590	2700	0.42 J	0.35 J	0.37 J	0.38 J
Cadmium	2.5	2.5	4.3	9.3	60	ND	0.15 J	ND	ND
Calcium						92400	79400	80900	92300
Chromium						12.8	11.5	11.9	11.4
Cobalt						5.2 J	4.8 J	5.5 J	5.6 J
Copper	50	270	270	270	10000	12.9	10.7	12.3	13.5
Iron						15300	12500	12900	13400
Lead	63	400	400	1000	3900	13.0	266	50.8	16.4

TABLE 4

SUBSURFACE SOIL RESULTS - 8/5/2019
X (LEAD) DELINEATION
301 CONNECTICUT STREET SITE
BCP SITE C915345



LOCATION - SAMPLE DEPTH						2-X04-12ft	2-X04-13ft	2-X04-14ft	2-X04-15ft
SAMPLING DATE						08/05/2019	08/05/2019	08/05/2019	08/05/2019
SAMPLE TYPE						SOIL	SOIL	SOIL	SOIL
UNITS						mg/kg	mg/kg	mg/kg	mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use				
Magnesium						39300	30700	33500	40200
Manganese	1600	2000	2000		10000	438	369	405	422
Nickel	30	140	310	310	10000	12.6	11.1	13.1	12.5
Potassium						2060	1800	1970	1890
Selenium	3.9	36	180	1500	6800	ND	ND	ND	ND
Silver	2	36	180	1500	6800	ND	ND	ND	ND
Sodium						380 J	348 J	320 J	331 J
Vanadium						18.6	15.7	16.9	17.3
Zinc	109	2200			10000	68.1	68.6	65.7	61.9

Analytical Data compared to Part 375 Standards and DER-10

ND indicates analyte was not detected.

Blank space indicates analyte was not analyzed for in that sample.

* - LCS or LCSD is outside acceptance limits.

F1 - MS and/or MSD Recovery is outside acceptance limits.

J - Result is less than the RL but greater than or equal to the MDL and the concentration is an approximate value.

TABLE 5

SUBSURFACE SOIL RESULTS - 8/6/2019 AND 8/7/2019
X AND Y (PETROLEUM) DELINEATION
301 CONNECTICUT STREET SITE



LOCATION - SAMPLE DEPTH						1-Y01-11ft	1-Y02-9ft	1-Y03-10ft	1-Y04-9ft	2-Y01-9ft	2-Y02-4ft	2-Y03-5ft	2-Y04-12ft	2-Y05-12 ft
SAMPLING DATE						08/06/2019	08/06/2019	08/06/2019	08/06/2019	08/06/2019	08/06/2019	08/06/2019	08/06/2019	08/07/2019
SAMPLE TYPE						SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
UNITS						mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
Unrestricted Use														
Residential Use														
Restricted Residential Use														
Commercial Use														
Industrial Use														
VOCs														
1,1-Dichloroethane	0.27	19	26	240	480	ND	ND	ND	ND	ND	ND	ND	ND	ND
1,2-Dichloroethane	0.02	2.3	3.1	30	60	ND	ND	ND	ND	ND	ND	ND	ND	ND
2-Butanone (MEK)	0.12	100	100	500	1000	ND	ND	ND	ND	ND	ND	ND	ND	ND
Acetone	0.05	100	100	500	1000	ND	ND	0.011	ND	ND	ND	ND	ND	ND
Benzene	0.06	2.9	4.8	44	89	ND	ND	ND	ND	ND	ND	ND	ND	ND
cis-1,2-Dichloroethene	0.25	59	100	500	1000	ND	ND	ND	ND	ND	ND	ND	ND	ND
Cyclohexane						ND	ND	ND	0.0042	ND	ND	ND	ND	3.0
Ethylbenzene	1	30	41	390	780	ND	ND	0.00085 J	0.0044	ND	ND	ND	ND	2.3
Isopropylbenzene						ND	ND	0.00019 J	0.00085 J	ND	ND	ND	ND	0.41
Methyl tert-butyl ether	0.93	62	100	500	1000	ND	ND	ND	ND	ND	ND	ND	ND	ND
Methylcyclohexane						ND	ND	ND	0.015	ND	ND	ND	ND	8.3
Methylene Chloride	0.05	51	100	500	1000	0.00056 J	0.00060 J	ND	0.0010 J	0.00074 J	0.00075 J	ND	ND	ND
Tetrachloroethene	1.3	5.5	19	150	300	ND	ND	ND	ND	ND	ND	ND	ND	ND
Toluene	0.7	100	100	500	1000	ND	ND	ND	ND	ND	ND	ND	ND	0.61
Xylenes, Total	0.26	100	100	500	1000	ND	0.00035 J	0.00040 J	0.0078	ND	ND	ND	ND	11
SVOCs														
Benzo[a]anthracene	1	1	1	5.6	11	ND F1	0.086	ND	ND	0.030 J	ND	ND	ND	ND
Benzo[a]pyrene	1	1	1	1	1.1	ND F1	0.082	ND	ND	0.019 J	0.015 J	ND	ND	ND
Benzo[b]fluoranthene	1	1	1	5.6	11	ND F1	0.14	ND	ND	0.032 J	0.042	ND	ND	ND
Benzo[k]fluoranthene	0.8	1	3.9	56	110	ND F1	0.043	ND	ND	0.016 J	0.020 J	ND	ND	ND
Chrysene	1	1	3.9	56	110	ND	0.095 J	ND	ND	0.025 J	0.032 J	ND	ND	ND
Dibenz(a,h)anthracene	0.33	0.33	0.33	0.56	1.1	ND F1 F2	ND	ND	ND	ND	ND	ND	ND	ND
Dibenzofuran	7	14	59	350	1000	ND F1	ND	ND	ND	0.013 J	ND	ND	ND	ND
Fluoranthene	100	100	100	500	1000	ND F1	0.19 J	ND	ND	0.027 J	0.073 J	0.024 J	ND	ND
Fluorene	30	100	100	500	1000	ND F1	ND	ND	ND	ND	ND	ND	ND	ND
Indeno[1,2,3-cd]pyrene	0.5	0.5	0.5	5.6	11	ND F2	0.082	ND	ND	0.020 J	ND	ND	ND	ND
Naphthalene	12	100	100	500	1000	ND F1	ND	ND	0.00031 J	0.025 J	ND	ND	ND	0.27 J
Phenanthrene	100	100	100	500	1000	ND F1	0.041 J	ND	ND	0.029 J	0.047 J	0.030 J	ND	ND
Pyrene	100	100	100	500	1000	ND	0.15 J	ND	ND	0.022 J	0.048 J	0.021 J	ND	ND
Metals														
Aluminum						5920		7290	7280	7580	7930	8620	8570	7520
Mercury	0.18	0.81	0.81	2.8	5.7	ND		ND	0.012 J	0.015 J	0.019	0.012 J	ND	0.012 J
Arsenic	13	16	16	16	16	2.7 J		3.8	3.0 J	5.4	3.6	4.9	3.2 J	3.2 J

TABLE 5

SUBSURFACE SOIL RESULTS - 8/6/2019 AND 8/7/2019
X AND Y (PETROLEUM) DELINEATION
301 CONNECTICUT STREET SITE



LOCATION - SAMPLE DEPTH						1-Y01-11ft	1-Y02-9ft	1-Y03-10ft	1-Y04-9ft	2-Y01-9ft	2-Y02-4ft	2-Y03-5ft	2-Y04-12ft	2-Y05-12 ft
SAMPLING DATE						08/06/2019	08/06/2019	08/06/2019	08/06/2019	08/06/2019	08/06/2019	08/06/2019	08/06/2019	08/07/2019
SAMPLE TYPE						SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
UNITS						mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use									
Barium	350	350	400	400	10000	51.3	63.7	48.2	60.5	49.4	69.8	65.7	75.0	93.5
Beryllium	7.2	14	72	590	2700	0.27 J	0.38 J	0.35 J	0.39 J	0.40 J	0.45	0.44	0.39 J	0.53
Cadmium	2.5	2.5	4.3	9.3	60	ND	ND	ND	ND	ND	ND	ND	ND	ND
Calcium						73800	63400	59800	72100	64600	72600	73700	67500	55800
Chromium						10.6	11.9	11.4	12.4	13.2	12.8	12.8	12.0	13.5
Cobalt						4.6 J	5.3 J	5.3 J	5.7 J	5.1 J	6.1 J	6.1 J	6.1 J	6.1 J
Copper	50	270	270	270	10000	13.7	13.5	12.1	14.6	13.5	15.7	14.1	13.7	18.0
Iron						11400	13200	12600	14500	13600	16500	14800	13700	16000
Lead	63	400	400	1000	3900	12.1	14.7	12.1	15.9	39.6	13.1	11.6	10.5	11.0
Magnesium						29700	25000	22400	29500	24300	24500	24200	27800	18700
Manganese	1600	2000	2000		10000	382	338	347	366	395	393	339	366	347
Nickel	30	140	310	310	10000	9.1	11.8	11.5	12.6	12.8	13.6	13.9	12.4	13.7
Potassium						1500	1810	1810	1870	1930	1860	1970	1950	2070
Selenium	3.9	36	180	1500	6800	ND	ND	ND	ND	ND	ND	ND	ND	ND
Silver	2	36	180	1500	6800	ND	ND	ND	ND	ND	ND	ND	ND	ND
Sodium						289 J	344 J	968 J	1190	1560	1230	1480	938 J	889 J
Vanadium						14.7	17.6	16.8	18.3	18.2	21.3	20.0	18.1	24.2
Zinc	109	2200			10000	77.3	59.5	59.8	63.0	72.3	61.4	59.4	64.4	84.9

Analytical Data compared to Part 375 Standards and DER-10

ND indicates analyte was not detected.

Blank space indicates analyte was not analyzed for in that sample.

* - LCS or LCSD is outside acceptance limits.

F1 - MS and/or MSD Recovery is outside acceptance limits.

F2 - MS/MSD RPD exceeds control limits

J - Result is less than the RL but greater than or equal to the MDL and the concentration is an approximate value.

TABLE 5

SUBSURFACE SOIL RESULTS - 8/6/2019 AND 8/7/2019
X AND Y (PETROLEUM) DELINEATION
301 CONNECTICUT STREET SITE



LOCATION - SAMPLE DEPTH						3-Y04-13 ft	1-Z01--7ft	1-Z02-11 ft	1-Z03-11 ft	1-Z04-10 ft	2-Z01-7 ft	2-Z03-12 ft	2-Z04-9 ft	2-Z05-12 ft
SAMPLING DATE						08/07/2019	08/06/2019	08/07/2019	08/07/2019	08/07/2019	08/07/2019	08/07/2019	08/07/2019	08/07/2019
SAMPLE TYPE						SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
UNITS						mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
						Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use				
VOCs														
1,1-Dichloroethane	0.27	19	26	240	480	ND	ND	ND	ND	ND	ND	ND	ND	ND
1,2-Dichloroethane	0.02	2.3	3.1	30	60	ND	ND	ND	ND	ND	ND	ND	ND	ND
2-Butanone (MEK)	0.12	100	100	500	1000	ND	ND	ND	ND	ND	ND	ND	0.010	ND
Acetone	0.05	100	100	500	1000	ND	ND	ND	0.0086	ND	ND	ND	0.018	0.0057
Benzene	0.06	2.9	4.8	44	89	0.00029 J	ND	ND	ND	ND	ND	ND	0.0021	ND
cis-1,2-Dichloroethene	0.25	59	100	500	1000	ND	ND	ND	ND	ND	ND	ND	ND	ND
Cyclohexane						ND	0.51	ND	0.00026 J	0.0013	0.86	ND	0.014	0.0045
Ethylbenzene	1	30	41	390	780	ND	0.28	ND	0.00029 J	0.00062 J	0.65	ND	0.033	0.00071 J
Isopropylbenzene						ND	0.14	ND	ND	0.00017 J	0.17	ND	0.0056	0.00092 J
Methyl tert-butyl ether	0.93	62	100	500	1000	ND	ND	ND	ND	ND	ND	ND	ND	ND
Methylcyclohexane						ND	1.9	ND	ND	0.00077 J	3.4	ND	0.047	0.046
Methylene Chloride	0.05	51	100	500	1000	ND	ND	0.00053 J	ND	0.00081 J	ND	ND	ND	0.00060 J
Tetrachloroethene	1.3	5.5	19	150	300	ND	ND	ND	ND	ND	ND	ND	ND	ND
Toluene	0.7	100	100	500	1000	ND	ND	ND	ND	ND	ND	ND	0.0092	ND
Xylenes, Total	0.26	100	100	500	1000	0.00041 J	0.25	ND	0.00031 J	0.00090 J	2.9	ND	0.054	0.0027
SVOCs														
Benzo[a]anthracene	1	1	1	5.6	11	ND	0.031 J	ND	ND	ND	ND	ND	ND	ND
Benzo[a]pyrene	1	1	1	1	1.1	ND	ND	ND	ND	ND	ND	ND	ND	ND
Benzo[b]fluoranthene	1	1	1	5.6	11	ND	0.019 J	ND	ND	ND	ND	ND	ND	ND
Benzo[k]fluoranthene	0.8	1	3.9	56	110	ND	0.012 J	ND	ND	ND	ND	ND	ND	ND
Chrysene	1	1	3.9	56	110	ND	0.025 J	ND	ND	ND	ND	ND	ND	ND
Dibenz(a,h)anthracene	0.33	0.33	0.33	0.56	1.1	ND	ND	ND	ND	ND	ND	ND	ND	ND
Dibenzofuran	7	14	59	350	1000	ND	ND	ND	ND	ND	ND	ND	ND	ND
Fluoranthene	100	100	100	500	1000	ND	0.037 J	ND	ND	ND	ND	ND	ND	0.011 J
Fluorene	30	100	100	500	1000	ND	ND	ND	ND	ND	ND	ND	ND	ND
Indeno[1,2,3-cd]pyrene	0.5	0.5	0.5	5.6	11	ND	ND	ND	ND	ND	ND	ND	ND	ND
Naphthalene	12	100	100	500	1000	ND	ND	ND	ND	ND	0.41	ND	0.024 J	ND
Phenanthrene	100	100	100	500	1000	ND	0.045 J	ND	ND	ND	ND	ND	ND	ND
Pyrene	100	100	100	500	1000	ND	0.029 J	ND	ND	ND	ND	ND	ND	ND
Metals														
Aluminum						6020	6940	8120	6100	6800	6500	6490	5120	7840
Mercury	0.18	0.81	0.81	2.8	5.7	0.012 J	0.013 J	ND	0.014 J	ND	ND	ND	ND	0.016 J
Arsenic	13	16	16	16	16	3.1 J	4.3	3.2	2.7 J	2.8 J	3.0 J	3.1 J	2.9 J	2.5 J

TABLE 5

SUBSURFACE SOIL RESULTS - 8/6/2019 AND 8/7/2019
X AND Y (PETROLEUM) DELINEATION
301 CONNECTICUT STREET SITE



LOCATION - SAMPLE DEPTH						3-Y04-13 ft	1-Z01--7ft	1-Z02-11 ft	1-Z03-11 ft	1-Z04-10 ft	2-Z01-7 ft	2-Z03-12 ft	2-Z04-9 ft	2-Z05-12 ft
SAMPLING DATE						08/07/2019	08/06/2019	08/07/2019	08/07/2019	08/07/2019	08/07/2019	08/07/2019	08/07/2019	08/07/2019
SAMPLE TYPE						SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
UNITS						mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use									
Barium	350	350	400	400	10000	81.0	54.5	78.5	44.9	84.4	60.0	94.5	39.4 J	64.4
Beryllium	7.2	14	72	590	2700	0.37 J	0.37 J	0.50	0.38 J	0.38 J	0.39 J	0.37 J	0.30 J	0.48
Cadmium	2.5	2.5	4.3	9.3	60	0.16 J	ND	ND	ND	ND	ND	0.15 J	ND	ND
Calcium						89400	74900	65800	76500	81900	74800	84100	75600	75400
Chromium						10.6	11.1	15.5	9.9	10.9	10.5	9.6	9.0	12.9
Cobalt						4.2 J	5.3 J	6.5 J	4.8 J	5.0 J	5.0 J	4.9 J	3.9 J	5.7 J
Copper	50	270	270	270	10000	11.0	11.6	14.6	11.9	12.3	12.4	14.0	10.1	15.1
Iron						11900	13500	15900	11600	12800	13100	12000	11000	14000
Lead	63	400	400	1000	3900	10.4	12.3	9.6	9.2	11.7	13.2	10.5	12.3	8.7
Magnesium						40000	29000	22900	30900	34500	29100	34000	31900	27500
Manganese	1600	2000	2000		10000	328	383	399	375	390	403	411	393	353
Nickel	30	140	310	310	10000	11.3	11.8	14.1	10.7	12.0	11.6	11.4	9.0	12.7
Potassium						1630	1640	1860	1560	1750	1550	1600	1240	1960
Selenium	3.9	36	180	1500	6800	ND	ND	ND	ND	ND	ND	ND	ND	ND
Silver	2	36	180	1500	6800	ND	ND	ND	ND	ND	ND	ND	ND	ND
Sodium						796 J	1110 J	1210	684 J	1020 J	1280	445 J	1250	1050 J
Vanadium						15.0	17.1	20.5	15.4	16.3	16.7	16.8	14.4	19.3
Zinc	109	2200			10000	66.0	67.2	61.6	67.2	73.0	66.0	85.7	61.8	64.1

Analytical Data compared to Part 375 Standards and DER-10

ND indicates analyte was not detected.

Blank space indicates analyte was not analyzed for in that sample.

* - LCS or LCSD is outside acceptance limits.

F1 - MS and/or MSD Recovery is outside acceptance limits.

F2 - MS/MSD RPD exceeds control limits

J - Result is less than the RL but greater than or equal to the MDL and the concentration is an approximate value.

TABLE 6

SUBSURFACE SOIL RESULTS - 8/8/2019 - 8/9/2019 AND 8/12/2019
WASTE CHARACTERIZATION SAMPLING
301 CONNECTICUT STREET SITE
BCP SITE C915345



	LOCATION - SAMPLE DEPTH					A1-WC	A1-WC	A1-WC	B1-WC	B1-WC	B1-WC	B4-WC
	SAMPLING DATE					08/12/2019	08/12/2019	08/12/2019	08/08/2019	08/08/2019	08/08/2019	08/12/2019
	SAMPLE TYPE					SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL
	UNITS					mg/kg	mm/sec	su	mg/kg	mm/sec	su	mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use							
PCBs												
Aroclor 1016						ND			ND			ND
Aroclor 1221						ND			ND			ND
Aroclor 1232						ND			ND			ND
Aroclor 1242						ND			ND			ND
Aroclor 1248						ND			ND			ND
Aroclor 1254						ND			ND			ND
Aroclor 1260						ND			ND			ND
Aroclor-1262						ND			ND			ND
Aroclor 1268						ND			ND			ND
Total PCBs	0.1	1	1	1	25	ND			ND			ND
WetChem												
Burn Rate							ND			ND		
Cyanide, Reactive						ND			ND			ND
pH								8.4 HF			8.1 HF	
Sulfide, Reactive						ND			ND			ND

Analytical Data compared to Part 375 Standards and DER-10

ND indicates analyte was not detected.

Blank space indicates analyte was not analyzed for in that sample.

HF - Field parameter with a holding time of 15 minutes. Test performed by laboratory at client's request.

TABLE 6

**SUBSURFACE SOIL RESULTS - 8/8/2019 - 8/9/2019 AND 8/12/2019
WASTE CHARACTERIZATION SAMPLING
301 CONNECTICUT STREET SITE
BCP SITE C915345**

[illegible]

TABLE 7

OFFSITE INVESTIGATION SUBSURFACE SOIL RESULTS - 9/9/2019 AND 9/10/2019
301 CONNECTICUT STREET SITE
BCP SITE C915345



	LOCATION - SAMPLE DEPTH					SW-1-5FT	SW-2-5FT	SW-3-7FT	SW-4-6FT	SW-5-10FT
	SAMPLING DATE					9/9/2019	9/9/2019	9/9/2019	9/9/2019	9/9/2019
	SAMPLE TYPE					SOIL	SOIL	SOIL	SOIL	SOIL
	UNITS					mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use					
General Chemistry										
Solids, Total (%)						87.2	88.4	87.4	86.8	87.3
Semivolatile Organics by GC/MS										
Acenaphthene	20	100	100	500	1000	ND	ND	ND	ND	ND
Hexachlorobenzene	0.33	0.33	1.2	6	12	ND	ND	ND	ND	ND
Fluoranthene	100	100	100	500	1000	ND	0.049 J	ND	ND	ND
Naphthalene	12	100	100	500	1000	ND	ND	ND	0.087 J	ND
Benzo(a)anthracene	1	1	1	5.6	11	ND	0.029 J	ND	ND	ND
Benzo(a)pyrene	1	1	1	1	1.1	ND	ND	ND	ND	ND
Benzo(b)fluoranthene	1	1	1	5.6	11	ND	0.04 J	ND	ND	ND
Benzo(k)fluoranthene	0.8	1	3.9	56	110	ND	ND	ND	ND	ND
Chrysene	1	1	3.9	56	110	ND	0.034 J	ND	ND	ND
Acenaphthylene	100	100	100	500	1000	ND	ND	ND	ND	ND
Anthracene	100	100	100	500	1000	ND	ND	ND	ND	ND
Benzo(ghi)perylene	100	100	100	500	1000	ND	ND	ND	ND	ND
Fluorene	30	100	100	500	1000	ND	ND	ND	ND	ND
Phenanthrene	100	100	100	500	1000	ND	0.038 J	ND	ND	ND
Dibenzo(a,h)anthracene	0.33	0.33	0.33	0.56	1.1	ND	ND	ND	ND	ND
Indeno(1,2,3-cd)pyrene	0.5	0.5	0.5	5.6	11	ND	ND	ND	ND	ND
Pyrene	100	100	100	500	1000	ND	0.044 J	ND	ND	ND
Dibenzofuran	7	14	59	350	1000	ND	ND	ND	ND	ND
Pentachlorophenol	0.8	2.4	6.7	6.7	55	ND	ND	ND	ND	ND
Phenol	0.33	100	100	500	1000	ND	ND	ND	ND	ND
2-Methylphenol	0.33	100	100	500	1000	ND	ND	ND	ND	ND
3-Methylphenol/4-Methylphenol	0.33	34	100	500	1000	ND	ND	ND	ND	ND
Volatile Organics by GC/MS										
Methylene chloride	0.05	51	100	500	1000	ND		ND	ND	ND
1,1-Dichloroethane	0.27	19	26	240	480	ND	ND	ND	ND	ND
Chloroform	0.37	10	49	350	700	0.00018 J	0.00021 J	ND	ND	0.01 J
Carbon tetrachloride	0.76	1.4	2.4	22	44	ND	ND	ND	ND	ND
Tetrachloroethene	1.3	5.5	19	150	300	ND	ND	ND	ND	ND
Chlorobenzene	1.1	100	100	500	1000	ND	ND	ND	ND	ND
1,2-Dichloroethane	0.02	2.3	3.1	30	60	ND	ND	ND	ND	ND
1,1,1-Trichloroethane	0.68	100	100	500	1000	ND	ND	ND	ND	ND
Benzene	0.06	2.9	4.8	44	89	0.00016 J	0.00017 J	ND	ND	ND
Toluene	0.7	100	100	500	1000	0.00067 J	0.0009 J	ND	ND	ND
Ethylbenzene	1	30	41	390	780	ND	ND	ND	ND	0.029 J
Vinyl chloride	0.02	0.21	0.9	13	27	ND	ND	ND	ND	ND

TABLE 7

OFFSITE INVESTIGATION SUBSURFACE SOIL RESULTS - 9/9/2019 AND 9/10/2019
301 CONNECTICUT STREET SITE
BCP SITE C915345



	LOCATION - SAMPLE DEPTH					SW-1-5FT	SW-2-5FT	SW-3-7FT	SW-4-6FT	SW-5-10FT
	SAMPLING DATE					9/9/2019	9/9/2019	9/9/2019	9/9/2019	9/9/2019
	SAMPLE TYPE					SOIL	SOIL	SOIL	SOIL	SOIL
	UNITS					mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use					
1,1-Dichloroethene	0.33	100	100	500	1000	ND	ND	ND	ND	ND
trans-1,2-Dichloroethene	0.19	100	100	500	1000	ND	ND	ND	ND	ND
Trichloroethene	0.47	10	21	200	400	ND	ND	ND	ND	ND
1,2-Dichlorobenzene	1.1	100	100	500	1000	ND	ND	ND	ND	ND
1,3-Dichlorobenzene	2.4	17	49	280	560	ND	ND	ND	ND	ND
1,4-Dichlorobenzene	1.8	9.8	13	130	250	ND	ND	ND	ND	ND
Methyl tert butyl ether	0.93	62	100	500	1000	0.00046 J	0.00063 J	ND	ND	ND
p/m-Xylene						ND	ND	ND	ND	ND
o-Xylene						ND	ND	ND	ND	ND
cis-1,2-Dichloroethene	0.25	59	100	500	1000	ND	ND	ND	ND	ND
Acetone	0.05	100	100	500	1000	0.032	0.029	ND	ND	ND
Carbon disulfide						ND	ND	ND	ND	ND
2-Butanone	0.12	100	100	500	1000	ND	ND	ND	ND	ND
n-Butylbenzene	12	100	100	500	1000	ND	ND	0.12	1.5	ND
sec-Butylbenzene	11	100	100	500	1000	ND	ND	0.35	0.82	ND
tert-Butylbenzene	5.9	100	100	500	1000	ND	ND	0.032 J	0.096 J	ND
Isopropylbenzene						ND	ND	0.075	0.44	0.0071 J
p-Isopropyltoluene						ND	ND	0.22	1.2	ND
Naphthalene	12	100	100	500	1000	ND	ND	ND	ND	0.054 J
n-Propylbenzene	3.9	100	100	500	1000	ND	ND	0.14	1.5	0.02 J
1,2,4-Trichlorobenzene						ND	ND	ND	ND	ND
1,3,5-Trimethylbenzene	8.4	47	52	190	380	ND	ND	ND	0.14 J	ND
1,2,4-Trimethylbenzene	3.6	47	52	190	380	ND	ND	0.016 J	4.5	ND
Methyl Acetate						ND	ND	ND	ND	ND
Cyclohexane						ND	ND	0.17 J	4.2	ND
Methyl cyclohexane						ND	ND	1	15	0.083 J

* Comparison is not performed on parameters with non-numeric criteria.

NY-UNRES: New York NYCRR Part 375 New York Unrestricted use Criteria Criteria per 6 NYCRR Part 375 Environmental Remediation Programs, effective December 14, 2006.

NY-RESR: New York NYCRR Part 375 Residential Criteria, New York Restricted use Criteria per 6 NYCRR Part 375 Environmental Remediation Programs, effective December 14, 2006.

NY-RESRR: New York NYCRR Part 375 Restricted-Residential Criteria, New York Restricted use Criteria per 6 NYCRR Part 375 Environmental Remediation Programs, effective December 14, 2006.

NY-RESC: New York NYCRR Part 375 Commercial Criteria, New York Restricted use Criteria per 6 NYCRR Part 375 Environmental Remediation Programs, effective December 14, 2006.

NY-RESI: New York NYCRR Part 375 Industrial Criteria, New York Restricted use Criteria per 6 NYCRR Part 375 Environmental Remediation Programs, effective December 14, 2006.

TABLE 7

OFFSITE INVESTIGATION SUBSURFACE SOIL RESULTS - 9/9/2019 AND 9/10/2019
301 CONNECTICUT STREET SITE
BCP SITE C915345



	LOCATION - SAMPLE DEPTH					SW-6-6FT	SW-7-6FT	SW-8-10FT	SW-9-5FT	SW-10-5FT
	SAMPLING DATE					9/9/2019	9/9/2019	9/10/2019	9/10/2019	9/10/2019
	SAMPLE TYPE					SOIL	SOIL	SOIL	SOIL	SOIL
	UNITS					mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use					
General Chemistry										
Solids, Total (%)						87.9	90.5	90.6	88.5	88.5
Semivolatile Organics by GC/MS										
Acenaphthene	20	100	100	500	1000	ND	ND	ND	0.042 J	ND
Hexachlorobenzene	0.33	0.33	1.2	6	12	ND	ND	ND	ND	ND
Fluoranthene	100	100	100	500	1000	ND	0.055 J	ND	0.51	ND
Naphthalene	12	100	100	500	1000	0.023 J	0.31	0.031 J	0.024 J	ND
Benzo(a)anthracene	1	1	1	5.6	11	ND	0.022 J	ND	0.23	ND
Benzo(a)pyrene	1	1	1	1	1.1	ND	ND	ND	0.18	ND
Benzo(b)fluoranthene	1	1	1	5.6	11	ND	0.03 J	ND	0.24	ND
Benzo(k)fluoranthene	0.8	1	3.9	56	110	ND	ND	ND	0.086 J	ND
Chrysene	1	1	3.9	56	110	ND	0.022 J	ND	0.23	ND
Acenaphthylene	100	100	100	500	1000	ND	ND	ND	ND	ND
Anthracene	100	100	100	500	1000	ND	ND	ND	0.099 J	ND
Benzo(ghi)perylene	100	100	100	500	1000	ND	ND	ND	0.1 J	ND
Fluorene	30	100	100	500	1000	ND	ND	ND	0.057 J	ND
Phenanthrene	100	100	100	500	1000	ND	0.039 J	ND	0.51	ND
Dibenzo(a,h)anthracene	0.33	0.33	0.33	0.56	1.1	ND	ND	ND	0.033 J	ND
Indeno(1,2,3-cd)pyrene	0.5	0.5	0.5	5.6	11	ND	ND	ND	0.12 J	ND
Pyrene	100	100	100	500	1000	ND	0.043 J	ND	0.42	ND
Dibenzofuran	7	14	59	350	1000	ND	ND	ND	0.029 J	ND
Pentachlorophenol	0.8	2.4	6.7	6.7	55	ND	ND	ND	ND	ND
Phenol	0.33	100	100	500	1000	ND	ND	ND	ND	ND
2-Methylphenol	0.33	100	100	500	1000	ND	ND	ND	ND	ND
3-Methylphenol/4-Methylphenol	0.33	34	100	500	1000	ND	ND	ND	ND	ND
Volatile Organics by GC/MS										
Methylene chloride	0.05	51	100	500	1000	ND	ND	ND	ND	ND
1,1-Dichloroethane	0.27	19	26	240	480	ND	ND	ND	ND	ND
Chloroform	0.37	10	49	350	700	ND	ND	0.0096 J	0.00029 J	0.00028 J
Carbon tetrachloride	0.76	1.4	2.4	22	44	ND	ND	ND	ND	ND
Tetrachloroethene	1.3	5.5	19	150	300	ND	ND	ND	ND	ND
Chlorobenzene	1.1	100	100	500	1000	ND	ND	ND	ND	ND
1,2-Dichloroethane	0.02	2.3	3.1	30	60	ND	ND	ND	ND	ND
1,1,1-Trichloroethane	0.68	100	100	500	1000	ND	ND	ND	ND	ND
Benzene	0.06	2.9	4.8	44	89	ND	ND	0.0081 J	0.00019 J	ND
Toluene	0.7	100	100	500	1000	ND	0.055	ND	ND	ND
Ethylbenzene	1	30	41	390	780	ND	0.28	ND	ND	ND
Vinyl chloride	0.02	0.21	0.9	13	27	ND	ND	ND	ND	ND

TABLE 7

OFFSITE INVESTIGATION SUBSURFACE SOIL RESULTS - 9/9/2019 AND 9/10/2019
301 CONNECTICUT STREET SITE
BCP SITE C915345



	LOCATION - SAMPLE DEPTH					SW-6-6FT	SW-7-6FT	SW-8-10FT	SW-9-5FT	SW-10-5FT
	SAMPLING DATE					9/9/2019	9/9/2019	9/10/2019	9/10/2019	9/10/2019
	SAMPLE TYPE					SOIL	SOIL	SOIL	SOIL	SOIL
	UNITS					mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
	Unrestricted Use	Residential Use	Restricted Residential Use	Commercial Use	Industrial Use					
1,1-Dichloroethene	0.33	100	100	500	1000	ND	ND	ND	ND	ND
trans-1,2-Dichloroethene	0.19	100	100	500	1000	ND	ND	ND	ND	ND
Trichloroethene	0.47	10	21	200	400	ND	ND	ND	ND	ND
1,2-Dichlorobenzene	1.1	100	100	500	1000	ND	ND	ND	ND	ND
1,3-Dichlorobenzene	2.4	17	49	280	560	ND	ND	ND	ND	ND
1,4-Dichlorobenzene	1.8	9.8	13	130	250	ND	ND	ND	ND	ND
Methyl tert butyl ether	0.93	62	100	500	1000	ND	ND	ND	0.0016 J	0.0019 J
p/m-Xylene						0.038 J	0.7	ND	ND	ND
o-Xylene						0.024 J	0.097	ND	ND	ND
cis-1,2-Dichloroethene	0.25	59	100	500	1000	ND	ND	ND	ND	ND
Acetone	0.05	100	100	500	1000	ND	ND	ND	0.26	0.24
Carbon disulfide						ND	ND	ND	ND	ND
2-Butanone	0.12	100	100	500	1000	ND	ND	ND	0.0071 J	ND
n-Butylbenzene	12	100	100	500	1000	ND	0.1	0.01 J	ND	ND
sec-Butylbenzene	11	100	100	500	1000	0.18	0.04 J	0.022 J	ND	ND
tert-Butylbenzene	5.9	100	100	500	1000	0.031 J	ND	ND	ND	ND
Isopropylbenzene						0.071	0.058	0.007 J	ND	ND
p-Isopropyltoluene						0.033 J	0.05 J	0.0067 J	ND	ND
Naphthalene	12	100	100	500	1000	0.14 J	0.36	ND	ND	ND
n-Propylbenzene	3.9	100	100	500	1000	0.15	0.2	ND	ND	ND
1,2,4-Trichlorobenzene						ND	ND	ND	ND	ND
1,3,5-Trimethylbenzene	8.4	47	52	190	380	0.043 J	0.41	ND	0.00035 J	ND
1,2,4-Trimethylbenzene	3.6	47	52	190	380	0.042 J	1.1	ND	0.00074 J	ND
Methyl Acetate						ND	ND	ND	0.052	0.065
Cyclohexane						0.26 J	0.26 J	0.065 J	0.00084 J	ND
Methyl cyclohexane						1.6	0.72	0.12 J	0.00088 J	ND

* Comparison is not performed on parameters with non-numeric criteria.

NY-UNRES: New York NYCRR Part 375 New York Unrestricted use Criteria Criteria per 6 NYC

NY-RESR: New York NYCRR Part 375 Residential Criteria, New York Restricted use Criteria pe

NY-RESRR: New York NYCRR Part 375 Restricted-Residential Criteria, New York Restricted use

NY-RESC: New York NYCRR Part 375 Commercial Criteria, New York Restricted use Criteria p

NY-RESI: New York NYCRR Part 375 Industrial Criteria, New York Restricted use Criteria per 6

TABLE 8

OFFSITE INVESTIGATION GROUNDWATER RESULTS - 9/10/2019
301 CONNECTICUT STREET SITE
BCP SITE C915345



	LOCATION		MW-6	
	SAMPLING DATE		9/10/2019	
	SAMPLE TYPE		WATER	
	NY-TOGS	Units	Results	Qual
Semivolatile Organics by GC/MS				
Bis(2-chloroethyl)ether	1	ug/l	ND	
3,3'-Dichlorobenzidine	5	ug/l	ND	
2,4-Dinitrotoluene	5	ug/l	ND	
2,6-Dinitrotoluene	5	ug/l	ND	
Bis(2-chloroisopropyl)ether	5	ug/l	ND	
Bis(2-chloroethoxy)methane	5	ug/l	ND	
Hexachlorocyclopentadiene	5	ug/l	ND	
Isophorone	50	ug/l	ND	
Nitrobenzene	0.4	ug/l	ND	
NDPA/DPA	50	ug/l	ND	
Bis(2-ethylhexyl)phthalate	5	ug/l	2.4	J
Butyl benzyl phthalate	50	ug/l	ND	
Di-n-butylphthalate	50	ug/l	ND	
Di-n-octylphthalate	50	ug/l	ND	
Diethyl phthalate	50	ug/l	ND	
Dimethyl phthalate	50	ug/l	ND	
Biphenyl		ug/l	ND	
4-Chloroaniline	5	ug/l	ND	
2-Nitroaniline	5	ug/l	ND	
3-Nitroaniline	5	ug/l	ND	
4-Nitroaniline	5	ug/l	ND	
Dibenzofuran		ug/l	ND	
1,2,4,5-Tetrachlorobenzene	5	ug/l	ND	
Acetophenone		ug/l	ND	
2,4-Dichlorophenol	2	ug/l	ND	
2,4-Dimethylphenol	2	ug/l	ND	
2,4-Dinitrophenol	2	ug/l	ND	
4,6-Dinitro-o-cresol		ug/l	ND	
Phenol	2	ug/l	ND	
Carbazole		ug/l	ND	
Atrazine	7.5	ug/l	ND	
Benzaldehyde		ug/l	ND	
Caprolactam		ug/l	ND	
Semivolatile Organics by GC/MS-SIM				
Acenaphthene	20	ug/l	ND	
2-Chloronaphthalene	10	ug/l	ND	
Fluoranthene	50	ug/l	0.04	J
Hexachlorobutadiene	0.5	ug/l	ND	
Naphthalene	10	ug/l	2.1	
Benzo(a)anthracene	0.002	ug/l	0.03	J
Benzo(a)pyrene	0	ug/l	ND	
Benzo(b)fluoranthene	0.002	ug/l	0.04	J
Benzo(k)fluoranthene	0.002	ug/l	0.01	J
Chrysene	0.002	ug/l	0.08	J
Acenaphthylene		ug/l	ND	
Anthracene	50	ug/l	ND	
Fluorene	50	ug/l	ND	
Phenanthrene	50	ug/l	0.06	J
Indeno(1,2,3-cd)pyrene	0.002	ug/l	ND	
Pyrene	50	ug/l	0.07	J
Pentachlorophenol	2	ug/l	ND	
Hexachlorobenzene	0.04	ug/l	ND	
Hexachloroethane	5	ug/l	ND	

TABLE 8

OFFSITE INVESTIGATION GROUNDWATER RESULTS - 9/10/2019
 301 CONNECTICUT STREET SITE
 BCP SITE C915345



	LOCATION		MW-6
	SAMPLING DATE		9/10/2019
	SAMPLE TYPE		WATER
	NY-TOGS	Units	Results Qual
Volatile Organics by GC/MS			
Methylene chloride	5	ug/l	ND
Chloroform	7	ug/l	ND
1,2-Dichloropropane	1	ug/l	ND
1,1,2-Trichloroethane	1	ug/l	ND
Tetrachloroethene	5	ug/l	ND
Chlorobenzene	5	ug/l	ND
Trichlorofluoromethane	5	ug/l	ND
1,2-Dichloroethane	0.6	ug/l	ND
1,1,1-Trichloroethane	5	ug/l	ND
trans-1,3-Dichloropropene	0.4	ug/l	ND
cis-1,3-Dichloropropene	0.4	ug/l	ND
Bromoform	50	ug/l	ND
1,1,2,2-Tetrachloroethane	5	ug/l	ND
Benzene	1	ug/l	ND
Toluene	5	ug/l	ND
Ethylbenzene	5	ug/l	ND
Bromomethane	5	ug/l	ND
Vinyl chloride	2	ug/l	ND
Chloroethane	5	ug/l	ND
trans-1,2-Dichloroethene	5	ug/l	ND
Trichloroethene	5	ug/l	ND
1,2-Dichlorobenzene	3	ug/l	ND
1,3-Dichlorobenzene	3	ug/l	ND
1,4-Dichlorobenzene	3	ug/l	ND
Methyl tert butyl ether	10	ug/l	ND
p/m-Xylene	5	ug/l	ND
o-Xylene	5	ug/l	ND
cis-1,2-Dichloroethene	5	ug/l	ND
Styrene	930	ug/l	ND
Dichlorodifluoromethane	5	ug/l	ND
Acetone	50	ug/l	5
Carbon disulfide	60	ug/l	ND
2-Butanone	50	ug/l	ND
2-Hexanone	50	ug/l	ND
1,2-Dibromoethane	0.0006	ug/l	ND
n-Butylbenzene	5	ug/l	ND
sec-Butylbenzene	5	ug/l	ND
tert-Butylbenzene	5	ug/l	ND
1,2-Dibromo-3-chloropropane	0.04	ug/l	ND
Isopropylbenzene	5	ug/l	ND
p-Isopropyltoluene	5	ug/l	ND
Naphthalene	10	ug/l	ND
n-Propylbenzene	5	ug/l	ND
1,2,4-Trichlorobenzene	5	ug/l	ND
1,3,5-Trimethylbenzene	5	ug/l	ND
1,2,4-Trimethylbenzene	5	ug/l	ND
Freon-113	5	ug/l	ND

* Comparison is not performed on parameters with non-numeric criteria.

NY-TOGS-GA: New York TOGS 111 Groundwater Effluent Limitations criteria reflects all addendum to criteria through June 2004.

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No.	A1
						Sheet 1 of:	
						Project No.:	V20.001.005
Project Name:					301 Connecticut Street Brownfield Cleanup Program		
Location:					301 Connecticut Street, Buffalo, NY		
Client:					D'Youville College		
Drilling Firm:					TREC		
Groundwater	Depth	Date & Time	Drill Rig:				
While Drilling:			Casing:		Rock Core:		Undist:
Before Casing Removal:			Sampler:		Other:		
After Casing Removal:			Hammer:				
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION			COMMENTS
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				0-0.4 ft - Asphalt, gravel and sand, fill			
2				0.4-3.7 ft - Gravel fill and sand			
3							
4							
5				<u>PID - 0 ppm</u>			3.7 ft Recovered
6				0-1.8 ft - Gravel fill and sand			
7							
8							
9							
10				<u>PID - 0 ppm</u>			1.8 ft Recovered
11	A1-00			0-1.7 ft - Gravel fill and sand			
12	A1-01			1.7-5.0 ft - Brown silty clay, moist			
13	A1-02						
14	A1-03						
15	A1-04			<u>PID - 0 ppm</u>			5.0 ft Recovered
16				<u>End of Boring at 15 ft</u>			
17				A1-00-11 ft			
18				A1-01-12 ft			
19				A1-02-13 ft			
20				A1-03-14 ft			
21				A1-04-15 ft			
22				A1-WC			
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No.	A2
						Sheet 1 of:	
						Project No.:	V20.001.005
Project Name:					301 Connecticut Street Brownfield Cleanup Program		
Location:					301 Connecticut Street, Buffalo, NY		
Client:					D'Youville College		
Drilling Firm:					TREC		
Groundwater		Depth	Date & Time	Drill Rig:			
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION		COMMENTS	
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey	a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%	(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)	
1	A2-00			0-0.5 ft - Concrete gravel			
				0.5-0.8 ft - Sub-base gravel and sand			
2	A2-01			0.8-1.4 ft - Brown silty clay and gravel		1.4 ft Recovered	
				<u>PID - 0 ppm</u>			
3	A2-02			0-0.2 ft - Brown silty clay and gravel			
				0.2-2.9 ft - Brown silty clay, dry			
4	A2-03			2.9-3.9 ft - Brown silty clay, moist			
5							
				<u>PID - 0 ppm</u>		3.9 ft Recovered	
6							
7				0-3.1 ft - Brown silty clay, moist			
8							
9							
				<u>PID - 0 ppm</u>		3.1 ft Recovered	
10							
11				0-2.4 ft - Brown silty clay, moist			
12							
13							
				<u>PID - 0 ppm</u>		2.3 ft Recovered	
14							
15				<u>End of Boring at 14 ft</u>			
16				A2-00-1 ft			
				A2-01-2 ft			
17				A2-02-3 ft			
				A2-03-4 ft			
18							
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. B1		
						Sheet 1 of:		
						Project No.: V20.001.005		
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:		
Location: 301 Connecticut Street, Buffalo, NY						Datum:		
Client: D'Youville College						Start Date: 8/5/19		
Drilling Firm: TREC						Finish Date: 8/12/19		
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig			
While Drilling:				Casing:	Rock Core:	Undist:		
Before Casing Removal:				Sampler:	Other:			
After Casing Removal:				Hammer:				
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)								
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)	
1	B1-01 DUP-D			0-0.6 ft - Asphalt, gravel, some dark brown sand, fill				
2				0.6-1.8 ft - Black silty clay				
				1.8-5.0 ft - Brown silty clay				
3	B1-02							
4								
5	B1-03			<u>PID - 0 ppm</u>			5.0 ft Recovered	
6				0-5.0 ft - Brown silty clay				
7								
8								
9								
10				<u>PID - 0 ppm</u> <u>Hit Refusal at 10 ft</u> <u>End of Boring at 10 ft</u>			5.0 ft Recovered	
11								
12								
13								
14								
15								
16				B1-01-1 to 2 ft				
17				B1-02-3 ft				
18				B1-03-4 ft				
				B1-WC				
				DUP-D-080819				
19								
20								
21								
22								
23								

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. B2	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 9/9/19	
Drilling Firm: TREC						Finish Date: 9/10/19	
Groundwater		Depth	Date & Time	Drill Rig:		Inspector: J. Alt-Winzig	
While Drilling:				Casing:		Rock Core:	Undist:
Before Casing Removal:				Sampler:		Other:	
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION			COMMENTS
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1	B2-00			0-0.6 ft - Concrete gravel			
				0.6-1.2 ft - Sub-base gravel, some asphalt			
2	B2-01			1.2-1.6 ft - Dark brown silty clay, dry			1.6 ft Recovered
				<u>PID - 0 ppm</u>			
3	B2-02			0-0.2 ft - Dark brown silty clay and gravel, dry			
				0.2-2.9 ft - Brown silty clay			
4	B2-03						
5							
				<u>PID - 0 ppm</u>			3.9 ft Recovered
6							
7				0-3.8 ft - Brown silty clay, saturated			
8							
9							
				<u>PID - 0 ppm</u>			3.8 ft Recovered
10							
11				0-3.9 ft - Brown silty clay, saturated			
12							
13							
				<u>PID - 0 ppm</u>			3.9 ft Recovered
14							
15				<u>End of Boring at 14 ft</u>			
16				B2-00-1 ft			
				B2-01-2 ft			
17				B2-02-3 ft			
				B2-03-4 ft			
18							
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. B3	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 9/9/19	
Drilling Firm: TREC						Finish Date: 9/10/19	
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				0-0.5 ft - Concrete gravel			
				0.5-0.7 ft - Sub-base gravel and sand, some asphalt			
2				0.7-1.1 ft - Dark brown silty clay, trace brick			1.1 ft Recovered
				<u>PID - 0 ppm</u>			
3	B3-01			0-0.2 ft - Dark brown silty clay, trace brick			
				0.2-2.5 ft - Sandy clay			
4	B3-02			2.5-3.7 ft - Brown silty clay			
5	B3-03						
				<u>PID - 0 ppm</u>			3.7 ft Recovered
6							
7				0-3.9 ft - Brown silty clay, moist			
8							
9							
10				<u>PID - 0 ppm</u>			3.9 ft Recovered
11				0-2.6 ft - Brown silty clay, moist			
12							
13							
14				<u>PID - 0 ppm</u>			2.6 ft Recovered
15				<u>End of Boring at 14 ft</u>			
16				B3-01-3 ft			
17				B3-02-4 ft			
18				B3-03-5 ft			
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. B4	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:		Inspector: J. Alt-Winzig	
While Drilling:				Casing:		Rock Core:	Undist:
Before Casing Removal:				Sampler:		Other:	
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION			COMMENTS
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1	B4-00			0-0.9 ft - Asphalt, gravel and sand, fill			
2				0.9-1.8 ft - Brick and sand, fill			
3				1.8-3.5 ft - Black silty clay			
4				3.5-4.7 ft - Brown silty clay, moist			
5	B4-01						
6	B4-02			<u>PID - 0 ppm</u>			4.7 ft Recovered
7	B4-03			0-5.0 ft - Brown silty clay, moist			
8							
9							
10				<u>PID - 0 ppm</u>			5.0 ft Recovered
11	B4-04			0-4.8 ft - Brown silty clay, moist			
12							
13							
14				<u>PID - 0 ppm</u>			4.8 ft Recovered
15							
16				<u>End of Boring at 15 ft</u>			
17				B4-00-3 ft			
18				B4-01-4 ft			
19				B4-02-5 ft			
20				B4-03-6 ft			
21				B4-04-15 ft			
22				B4-WC			
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. C1	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater	Depth	Date & Time	Drill Rig:			Inspector: J. Alt-Winzig	
While Drilling:			Casing:		Rock Core:		Undist:
Before Casing Removal:			Sampler:		Other:		
After Casing Removal:			Hammer:				
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION			COMMENTS
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1	C1-01			0-0.7 ft - Asphalt, gravel and sand, fill			
2	C1-02			0.7-1.0 ft - Black silty clay			
				1.0-5.0 ft - Brown silty clay			
3	C1-03						
4							
5				<u>PID - 0 ppm</u>			5.0 ft Recovered
6				0-5.0 ft - Brown silty clay, saturated, petroleum odor			
7	C1-00						
8				<u>PID - 3000 ppm at 7 ft</u>			
				<u>PID - 4300 ppm at 8 ft</u>			
9				<u>PID - 200 ppm at 9 ft</u>			
10				<u>PID - 5 ppm at 10 ft</u>			5.0 ft Recovered
11				0-0.4 ft - Sand, dry			
12				0.4-5.0 ft - Silty clay, moist			
13							
14				<u>PID - 5ppm at 11 ft</u>			
15				<u>PID - 0 ppm at 12 to 15 ft</u>			5.0 ft Recovered
16				<u>End of Boring at 15 ft</u>			
17				C1-01-1 ft			
18				C1-02-2 ft			
				C1-03-3 ft			
				C1-00-7 ft			
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No.	C2
						Sheet 1 of:	
						Project No.:	V20.001.005
Project Name:					301 Connecticut Street Brownfield Cleanup Program		
Location:					301 Connecticut Street, Buffalo, NY		
Client:					D'Youville College		
Drilling Firm:					TREC		
Groundwater		Depth	Date & Time	Drill Rig:			
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION		COMMENTS	
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey	a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%	(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)	
1	C2-01			0-0.4 ft - Asphalt, gravel, fill			
2	C2-02			0.4-3.6 ft - Brown silty clay and sand			
3	C2-03						
4							
5				<u>PID - 0 ppm</u>		3.6 ft Recovered	
6				0-4.8 ft - Brown silty clay, moist			
7							
8							
9							
10				<u>PID - 0 ppm</u>		4.8 ft Recovered	
11				0-4.9 ft - Brown silty clay, moist			
12							
13							
14							
15				<u>PID - 0 ppm</u>		4.9 ft Recovered	
16				<u>End of Boring at 15 ft</u>			
17				C2-01-1 ft			
18				C2-02-2 ft			
19				C2-03-3 ft			
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No.		C3	
						Sheet 1 of:			
						Project No.:		V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:			
Location: 301 Connecticut Street, Buffalo, NY						Datum:			
Client: D'Youville College						Start Date: 8/5/19			
Drilling Firm: TREC						Finish Date: 8/12/19			
Groundwater		Depth	Date & Time	Drill Rig:		Inspector:		J. Alt-Winzig	
While Drilling:				Casing:		Rock Core:		Undist:	
Before Casing Removal:				Sampler:		Other:			
After Casing Removal:				Hammer:					
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)									
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey				COMMENTS a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10% (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)	
1	C3-01			0-1.4 ft - Asphalt, gravel, fill					
2				1.4-1.9 ft - Large gravel and silt, saturated					
3				1.9-2.8 ft - Brown silty clay, moist					
4	C3-02								
5	C3-03								
6									
7									
8									
9									
10				<u>PID - 0 ppm</u> <u>Hit Refusal at 9 ft</u> <u>End of Boring at 10 ft</u>				2.8 ft Recovered	
11									
12									
13									
14									
15									
16									
17				C3-01-2 ft					
18				C3-02-3 ft					
19				C3-03-4 ft					
20									
21									
22									
23									

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454			BORING LOG			Boring No. C4			
						Sheet 1 of:			
						Project No.: V20.001.005			
Project Name: 301 Connecticut Street Brownfield Cleanup Program					Surface Elev.:				
Location: 301 Connecticut Street, Buffalo, NY					Datum:				
Client: D'Youville College					Start Date: 8/5/19				
Drilling Firm: TREC					Finish Date: 8/12/19				
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig				
While Drilling:				Casing:	Rock Core:	Undist:			
Before Casing Removal:				Sampler:	Other:				
After Casing Removal:				Hammer:					
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)									
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION			COMMENTS		
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)		
1	C4-01			0-0.8 ft - Asphalt, gravel, fill					
2				0.8-2.7 ft - Black silty clay					
				2.7-4.6 ft - Brown silty clay					
3									
4									
5	C4-02			<u>PID - 0 ppm</u>			4.6 ft Recovered		
6	C4-03			0-4.8 ft - Brown silty clay					
7									
8									
9									
10				<u>PID - 0 ppm</u>			4.8 ft Recovered		
11				0-5.0 ft - Brown silty clay					
12									
13									
14									
15				<u>PID - 0 ppm</u>			5.0 ft Recovered		
16				<u>End of Boring at 15 ft</u>					
17				C4-01-3 ft					
18				C4-02-4 ft					
19				C4-03-5 ft					
20									
21									
22									
23									

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. D1	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1	D1-00 DUP-C		0-0.8 ft - Asphalt, gravel, some sand, fill				
			0.8-1.9 ft - Large gravel and sand				
2			1.9-2.5 ft - Brown silty clay				
			2.5-2.8 ft - Asphalt				
3			2.8-3.6 ft - Gravel and sand, some brick				
4							
5			<u>PID - 0 ppm</u>				3.6 ft Recovered
6	D1-01		0-0.9 ft - Gravel and sand, some brick				
7	D1-02		0.9-4.8 ft - Brown silty clay, moist				
8	D1-03						
9							
10			<u>PID - 0 ppm</u>				4.8 ft Recovered
11	D1-04		0-5.0 ft - Brown silty clay, moist				
12							
13							
14							
15			<u>PID - 0 ppm</u>				5.0 ft Recovered
16			<u>End of Boring at 15 ft</u>				
17			D1-00-2 ft				
18			D1-01-6 ft				
19			D1-02-7ft				
20			D1-03-8ft				
21			D1-04-15 ft				
22			DUP-C-080919				
23			D1-WC				

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454			BORING LOG			Boring No. D2			
						Sheet 1 of:			
						Project No.: V20.001.005			
Project Name: 301 Connecticut Street Brownfield Cleanup Program					Surface Elev.:				
Location: 301 Connecticut Street, Buffalo, NY					Datum:				
Client: D'Youville College					Start Date: 8/5/19				
Drilling Firm: TREC					Finish Date: 8/12/19				
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig				
While Drilling:				Casing:	Rock Core:	Undist:			
Before Casing Removal:				Sampler:	Other:				
After Casing Removal:				Hammer:					
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)									
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)		
1	D2-01			0-1.1 ft - Asphalt, gravel, fill					
2				1.1-2.8 ft - Large gravel and sand					
				2.8-4.1 ft - Brown silty clay, moist					
3									
4									
5	D2-03			<u>PID - 0 ppm</u>			4.1 ft Recovered		
6				0-4.9 ft - Brown silty clay, moist					
7									
8									
9									
10				<u>PID - 0 ppm</u>			4.9 ft Recovered		
11				0-0.4 ft - Brown silty clay, moist					
12				0.4-2.6 ft - Small gravel, some sand, saturated					
				2.6-4.6 ft - Brown silty clay, moist					
13									
14									
15				<u>PID - 0 ppm</u>			4.6 ft Recovered		
16				<u>End of Boring at 15 ft</u>					
17				D2-01-3 ft					
				D2-02- 4 ft					
18				D2-03-5 ft					
19									
20									
21									
22									
23									

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. D3	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-1.4 ft - Asphalt, gravel, fill				
2			1.4-1.9 ft - Brown silty clay				
3			1.9-3.6 ft - Gravel and sand, moist				
4							
5			<u>PID - 0 ppm</u>				3.6 ft Recovered
6	D3-01		0-0.4 ft - Gravel and sand, moist				
7	MS/MSD		0.4-4.8 ft - Silty clay, moist				
8	D3-02						
9	D3-03						
10			<u>PID - 0 ppm</u>				4.8 ft Recovered
11			0-3.4 ft - Small gravel, some sand, saturated				
12			3.4-5.0 ft - Brown silty clay, moist				
13							
14							
15			<u>PID - 0 ppm</u>				5.0 ft Recovered
16			<u>End of Boring at 15 ft</u>				
17			D3-01-6 ft				
18			D3-01-6 ft MS/MSD				
19			D3-02-7 ft				
20			D3-03-8 ft				
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. D4	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1	D4-01			0-1.8 ft - Asphalt, gravel, and sand, fill, moist			
2				1.8-2.5 ft - Sand, saturated			
3				2.5-4.3 ft - Brown silty clay, saturated			
4							
5							
	D4-02			<u>PID - 0 ppm</u>			4.3 ft Recovered
6	D4-03			0-4.3 ft - Brown silty clay, moist			
7							
8							
9							
10				<u>PID - 0 ppm</u> <u>Hit Refusal at 9 to 10 ft</u> <u>End of Boring at 10 ft</u>			4.3 ft Recovered
11							
12							
13							
14							
15							
16				D4-01-3 ft			
17				D4-02-4 ft			
18				D4-03-5 ft			
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. E1	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:			
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-2.6 ft - Tolsoil loam, little gravel				
			2.6-3.4 ft - Gravel, fill				
2			3.4-4.3 ft - Black silty clay, moist				
			4.3-4.8 ft - Brown silty clay				
3							
4							
			<u>PID - 0 ppm</u>				4.8 ft Recovered
5							
6	E1-01		0-2.0 ft - Black silty clay and gravel				
			2.0-5.0 ft - Brown silty clay				
7							
8	E1-02						
9	E1-03						
			<u>PID - 0 ppm</u>				5.0 ft Recovered
10							
11			0-5.0 ft - Brown silty clay				
12							
13							
14							
			<u>PID - 0 ppm</u>				5.0 ft Recovered
15							
16			<u>End of Boring at 15 ft</u>				
			E1-01-7 ft				
17			E1-02-8 ft				
			E1-03-9 ft				
18							
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. E2	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:		Inspector: J. Alt-Winzig	
While Drilling:				Casing:		Rock Core:	Undist:
Before Casing Removal:				Sampler:		Other:	
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION			COMMENTS
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1	E2-00			0-0.6 ft - Asphalt, gravel, and sand, fill			
2	E2-01			0.6-4.8 ft - Brown silty clay			
3	E2-02						
4	E2-03						
5				<u>PID - 0 ppm</u>			4.8 ft Recovered
6				0-4.8 ft - Brown silty clay, dense			
7							
8							
9							
10				<u>PID - 0 ppm</u>			4.8 ft Recovered
11				0-4.8 ft - Brown silty clay, dense			
12							
13							
14							
15	E2-04			<u>PID - 0 ppm</u>			4.8 ft Recovered
16				<u>End of Boring at 15 ft</u>			
17				E2-00-1 ft			
18				E2-01-2 ft			
19				E2-02-3 ft			
20				E2-03-4 ft			
21				E2-04-15 ft			
22				E2-WC			
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No.		E3	
						Sheet 1 of:			
						Project No.:		V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:			
Location: 301 Connecticut Street, Buffalo, NY						Datum:			
Client: D'Youville College						Start Date: 8/5/19			
Drilling Firm: TREC						Finish Date: 8/12/19			
Groundwater		Depth	Date & Time	Drill Rig:		Inspector:		J. Alt-Winzig	
While Drilling:				Casing:		Rock Core:		Undist:	
Before Casing Removal:				Sampler:		Other:			
After Casing Removal:				Hammer:					
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)									
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)		
1	E3-01			0-0.8 ft - Asphalt, gravel, and sand, fill					
2				0.8-1.4 ft - Black silty clay, moist					
				1.4-5.0 ft - Brown silty clay					
3	E3-02								
4	E3-03								
5				<u>PID - 0 ppm</u>			5.0 ft Recovered		
6				0-5.0 ft - Brown silty clay					
7									
8									
9									
10				<u>PID - 0 ppm</u>			5.0 ft Recovered		
11				0-5.0 ft - Brown silty clay					
12									
13									
14									
15				<u>PID - 0 ppm</u>			5.0 ft Recovered		
16				<u>End of Boring at 15 ft</u>					
17				E3-01-2 ft					
				E3-02-3 ft					
				E3-03-4 ft					
18									
19									
20									
21									
22									
23									

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. E4	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:				Casing:			
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1	E4-01		0-0.7 ft - Asphalt, gravel, and sand, fill				
2			0.7-1.3 ft - Black silty clay and sand, moist				
3			1.3-4.7 ft - Brown silty clay				
4	E4-02						
5	E4-03						
6							
7							
8							
9							
10				<u>PID - 0 ppm</u>			4.7 ft Recovered
11	E4-04		0-4.8 ft - Brown silty clay				
12							
13							
14							
15							
16				<u>PID - 0 ppm</u>			4.8 ft Recovered
17			0-5.0 ft - Brown silty clay, moist				
18							
19							
20							
21							
22							
23							
<u>End of Boring at 15 ft</u>							
16			E4-01-2 ft				
17			E4-02-3 ft				
18			E4-03-4 ft				
19			E4-04-15 ft				
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 1-X01	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-1.7 ft - Asphalt, gravel, sub-base, fill				
2							
3							
4			PID - 0 ppm	1.7 ft Recovered			
5			0-0.7 ft - Gravel backfill, water, saturated				
6							
7							
8			PID - 0 ppm	0.7 ft Recovered			
9	1-X01	DUP-A	0-1.1 ft - Gravel backfill, water, saturated				
10	1-X01		1.1-2.6 ft - Brown silty clay, trace gravel, soft, moist				
11	1-X01						
12	1-X01		PID - 0 ppm	2.6 ft Recovered			
13	1-X01		0-2.6 ft - Brown silty clay, soft, moist				
14	1-X01						
15	1-X01						
16	1-X01		PID - 0 ppm	2.6 ft Recovered			
17			End of Boring at 16 ft				
18			1-X01-9 ft				
19			1-X01-10 ft				
20			1-X01-11 ft				
21			1-X01-12 ft				
22			1-X01-13 ft				
23			1-X01-14 ft				
			1-X01-15 ft				
			DUP-A-080519				

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 1-X02	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10% S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				0-1.9 ft - Asphalt, gravel, sub-base, fill, dry			
2							
3							
4				<u>PID - 0 ppm</u>			1.9 ft Recovered
5				0-0.9 ft - Gravel backfill			
6							
7							
8				<u>PID - 0 ppm</u>			0.9 ft Recovered
9	1-X02			0-1.0 ft - Slag			
10	1-X02			1.0-2.6 ft - Brown silty clay, moist			
11	1-X02			<u>PID - 700 ppm at 9 ft</u>			
12	1-X02			<u>PID - 0 ppm at 10 ft</u>			2.6 ft Recovered
13	1-X02			0-3.8 ft - Brown silty clay, saturated			
14	1-X02						
15							
16				<u>PID - 0 ppm</u>			3.8 ft Recovered
17				<u>End of Boring at 16 ft</u>			
18				1-X02-9 ft			
19				1-X02-10 ft			
20				1-X02-11 ft			
21				1-X02-12 ft			
22				1-X02-13 ft			
23				1-X02-14 ft			

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 1-X03	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10% S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey		COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)	
1			0-2.6 ft - Asphalt, gravel, sub-base, fill, dry				
2							
3							
4			<u>PID - 0 ppm</u>	2.6 ft Recovered			
5			0-0.7 ft - Gravel backfill				
6							
7							
8			<u>PID - 0 ppm</u>	0.7 ft Recovered			
9	1-X03		0-2.2 ft - Brown silty clay				
10	1-X03						
11	1-X03						
12	1-X03		<u>PID - 0 ppm</u>	2.2 ft Recovered			
13	1-X03		0-3.3 ft - Brown silty clay				
14	1-X03						
15	1-X03						
16			<u>PID - 0 ppm</u>	3.3 ft Recovered			
17			<u>End of Boring at 16 ft</u>				
18			1-X03-8 to 9 ft				
19			1-X03-10 ft				
20			1-X03-11 ft				
21			1-X03-12 ft				
22			1-X03-13 ft				
23			1-X03-14 ft				

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 1-X04
						Sheet 1 of:
						Project No.: V20.001.005
Project Name: 301 Connecticut Street Brownfield Cleanup Program					Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY					Datum:	
Client: D'Youville College					Start Date: 8/5/19	
Drilling Firm: TREC					Finish Date: 8/12/19	
Groundwater	Depth	Date & Time	Drill Rig:		Inspector: J. Alt-Winzig	
While Drilling:			Casing:	Rock Core:	Undist:	
Before Casing Removal:			Sampler:	Other:		
After Casing Removal:			Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)						
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%		COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				0-1.5 ft - Asphalt, gravel, sub-base, fill		
2						
3						
4				<u>PID - 0 ppm</u>		1.5 ft Recovered
5				0-0.7 ft - Gravel backfill, water, saturated		
6						
7						
8				<u>PID - 0 ppm</u>		0.7 ft Recovered
9	1-X04			0-1.1 ft - Gravel backfill, water, saturated		
10	1-X04			1.1-1.6 ft - Brown silty clay, moist		
11	1-X04			<u>PID - 203 ppm at 10 ft</u>		
12	1-X04			<u>PID - 0 ppm at 11 ft</u>		1.6 ft Recovered
13	1-X04			0-2.6 ft - Brown silty clay, moist		
14	1-X04					
15	1-X04			<u>PID - 74 ppm at 12 ft</u>		
				<u>PID - 13 ppm at 13 ft</u>		
16				<u>PID - 5 ppm at 15 ft</u>		2.6 ft Recovered
17				<u>End of Boring at 16 ft</u>		
18				1-X04-9 ft		
19				1-X04-10 ft		
20				1-X04-11 ft		
21				1-X04-12 ft		
22				1-X04-13 ft		
23				1-X04-14 ft		

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 2-X01
						Sheet 1 of:
						Project No.: V20.001.005
Project Name: 301 Connecticut Street Brownfield Cleanup Program					Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY					Datum:	
Client: D'Youville College					Start Date: 8/5/19	
Drilling Firm: TREC					Finish Date: 8/12/19	
Groundwater	Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:			Casing:	Rock Core:	Undist:	
Before Casing Removal:			Sampler:	Other:		
After Casing Removal:			Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)						
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%		COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-1.3 ft - Asphalt, gravel, fill, dry			
2						
3						
4			PID - 0 ppm	1.3 ft Recovered		
5	2-X01		0-0.6 ft - Gravel fill, dry			
6			0.6-1.8 ft - Brown silty clay, saturated			
7						
8			PID - 0 ppm	1.8 ft Recovered		
9	2-X01		0-0.4 ft - Asphalt and gravel fill			
10	2-X01		0.4-3.8 ft - Brown silty clay, trace gravel, moist			
11	2-X01					
12			PID - 0 ppm Hit Refusal at 12 ft	3.8 ft Recovered		
13			End of Boring at 12 ft			
14						
15						
16						
17						
18			2-X01-8 ft			
19			2-X01-9 ft			
20			2-X01-10 ft			
21			2-X01-11 ft			
22						
23						

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 2-X02	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10% S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-0.5 ft - Asphalt, gravel, fill				
2			0.5-3.0 ft - Brown silty clay and gravel				
3							
4			<u>PID - 0 ppm</u>	3.0 ft Recovered			
5	2-X02		0-1.7 ft - Brown silty clay and gravel				
6			1.7-3.8 ft - Brown silty clay				
7			<u>PID - 73 ppm at 7 ft</u>				
8			<u>PID - 240 ppm at 8 ft</u>	3.8 ft Recovered			
9	2-X02		0-1.0 ft - Brown silty clay and gravel, moist				
10	2-X02		1.0-3.9 ft - Brown silty clay, saturated				
11	2-X02		<u>PID - 77 ppm at 9 ft</u>				
12	2-X02		<u>PID - 61 ppm at 10 ft</u>				
			<u>PID - 0 ppm at 11 ft</u>	3.9 ft Recovered			
13	2-X02		0-2.5 ft - Brown silty clay, saturated				
14	2-X02						
15	2-X02						
16			<u>PID - 0 ppm</u>	2.5 ft Recovered			
17			<u>End of Boring at 16 ft</u>				
18			2-X02-8 ft				
19			2-X02-9 ft				
20			2-X02-10 ft				
21			2-X02-11 ft				
22			2-X02-12 ft				
23			2-X02-13 ft				

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 2-X03	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10% S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				0-2.4 ft - Asphalt, gravel, fill			
2							
3							
4				<u>PID - 0 ppm</u>			2.4 ft Recovered
5				0-0.9 ft - Gravel fill			
6							
7							
8				<u>PID - 0 ppm</u>			0.9 ft Recovered
9	2-X03			0-0.9 ft - Gravel fill			
10	2-X03			0.9-2.3 ft - Brown silty clay, moist			
11	2-X03			<u>PID - 66 ppm at 9 ft</u>			
12	2-X03			<u>PID - 0 ppm at 10 ft</u>			2.3 ft Recovered
13				0-0.6 ft - Slag			
14				0.6-4.0 - Brown silty clay, moist			
15							
16				<u>PID - 0 ppm</u>			4.0 ft Recovered
17				<u>End of Boring at 16 ft</u>			
18				2-X03-9 ft			
19				2-X03-10 ft			
20				2-X03-11 ft			
21				2-X03-12 ft			
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 2-X04
						Sheet 1 of:
						Project No.: V20.001.005
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:
Location: 301 Connecticut Street, Buffalo, NY						Datum:
Client: D'Youville College						Start Date: 8/5/19
Drilling Firm: TREC						Finish Date: 8/12/19
Groundwater	Depth	Date & Time	Drill Rig:			Inspector: J. Alt-Winzig
While Drilling:			Casing:	Rock Core:	Undist:	
Before Casing Removal:			Sampler:	Other:		
After Casing Removal:			Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)						
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%		COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				0-1.7 ft - Asphalt, gravel, sub-base, fill, dry		
2						
3						
4				<u>PID - 0 ppm</u>		1.7 ft Recovered
5				0-1.4 ft - Gravel backfill, saturated		
6						
7						
8				<u>PID - 0 ppm</u>		1.4 ft Recovered
9	2-X04			0-0.7 ft - Gravel, saturated		
10	2-X04			0.7-3.5 ft - Brown silty clay, saturated		
11	2-X04			<u>PID - 130 ppm at 10 ft</u>		
				<u>PID - 23 ppm at 11 ft</u>		
12	2-X04			<u>PID - 0 ppm at 12 ft</u>		3.5 ft Recovered
13	2-X04			0-3.7 ft - Brown silty clay, saturated		
14	2-X04					
15	2-X04					
16				<u>PID - 0 ppm</u>		3.7 ft Recovered
17				<u>End of Boring at 16 ft</u>		
18				2-X04-9 ft		
				2-X04-10 ft		
19				2-X04-11 ft		
				2-X04-12 ft		
20				2-X04-13 ft		
				2-X04-14 ft		
21				2-X04-15 ft		
22						
23						

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 1-Y01	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10% S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-0.9 ft - Asphalt, gravel, and sand, fill				
2			0.9-1.6 ft - Dark brown silty sand				
3			1.6-3.5 ft - Light brown silty sand				
4			<u>PID - 0 ppm</u>				3.5 ft Recovered
5			0-1.7 ft - Black silty clay, dry				
6			1.7-3.9 ft - Brown silty clay, moist				
7			<u>PID - 5 ppm at 5 to 6 ft</u>				
8			<u>PID - 0 ppm at 7 to 8 ft</u>				3.9 ft Recovered
9	1-Y01		0-1.4 ft - Dark brown silty clay, some gravel, moist				
10			1.4-3.9 ft - Brown silty clay, moist				
11							
12			<u>PID - 0 ppm</u>				3.9 ft Recovered
13			0-3.9 ft - Brown silty clay, moist				
14							
15							
16			<u>PID - 0 ppm</u>				3.9 ft Recovered
17			<u>End of Boring at 16 ft</u>				
18			1-Y01-11 ft				
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 1-Y02
						Sheet 1 of:
						Project No.: V20.001.005
Project Name: 301 Connecticut Street Brownfield Cleanup Program					Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY					Datum:	
Client: D'Youville College					Start Date: 8/5/19	
Drilling Firm: TREC					Finish Date: 8/12/19	
Groundwater	Depth	Date & Time	Drill Rig:		Inspector: J. Alt-Winzig	
While Drilling:			Casing:	Rock Core:	Undist:	
Before Casing Removal:			Sampler:	Other:		
After Casing Removal:			Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)						
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%		COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-0.8 ft - Asphalt, gravel, and sand, fill			
2			0.8-2.3 ft - Dark brown silty clay, some sand			
3						
4			<u>PID - 0 ppm</u>	2.3 ft Recovered		
5			0-0.3 ft - Dark brown silty clay, some sand			
6			0.3-0.6 ft - Black silty clay			
7			0.6-0.9 ft - Dark brown silty clay			
8			<u>PID - 0 ppm</u>	0.9 ft Recovered		
9	1-Y02		0-1.5 ft - Dark brown silty clay, moist			
10						
11						
12			<u>PID - 0 ppm</u>	1.5 ft Recovered		
13			0-3.9 ft - Brown silty clay, moist			
14						
15						
16			<u>PID - 0 ppm</u>	3.9 ft Recovered		
17			<u>End of Boring at 16 ft</u>			
18			1-Y02-9 ft			
19						
20						
21						
22						
23						

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 1-Y03
						Sheet 1 of:
						Project No.: V20.001.005
Project Name: 301 Connecticut Street Brownfield Cleanup Program					Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY					Datum:	
Client: D'Youville College					Start Date: 8/5/19	
Drilling Firm: TREC					Finish Date: 8/12/19	
Groundwater	Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:			Casing:	Rock Core:	Undist:	
Before Casing Removal:			Sampler:	Other:		
After Casing Removal:			Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)						
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10% S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey		COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-1.1 ft - Asphalt, gravel, fill			
2			1.1-2.6 ft - Brown silty clay			
3						
4			<u>PID - 0 ppm</u>	2.6 ft Recovered		
5			0-2.0 ft - Brown silty clay, some gravel			
6			2.0-3.2 ft - Brown silty clay, moist			
7			<u>PID - 60 ppm at 6 ft</u>			
8			<u>PID - 40 ppm at 7 ft</u>			
			<u>PID - 0 ppm at 8 ft</u>	3.2 ft Recovered		
9	1-Y03		0-3.9 ft - Brown silty clay, moist			
10						
11						
12			<u>PID - 0 ppm</u>	3.9 ft Recovered		
13			<u>End of Boring at 12 ft</u>			
14						
15						
16						
17			1-Y03-10 ft			
18						
19						
20						
21						
22						
23						

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 1-Y04
						Sheet 1 of:
						Project No.: V20.001.005
Project Name: 301 Connecticut Street Brownfield Cleanup Program					Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY					Datum:	
Client: D'Youville College					Start Date: 8/5/19	
Drilling Firm: TREC					Finish Date: 8/12/19	
Groundwater	Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:			Casing:	Rock Core:	Undist:	
Before Casing Removal:			Sampler:	Other:		
After Casing Removal:			Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)						
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10% S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey		COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-0.9 ft - Asphalt, gravel, and sand, fill			
2			0.9-2.4 ft - Sandy clay, little gravel			
3						
4			<u>PID - 0 ppm</u>	2.4 ft Recovered		
5			0-1.1 ft - Sandy clay, little gravel			
6			1.1-2.0 ft - Black silty clay			
7			<u>PID - 80 ppm at 5 to 6 ft</u>			
8			<u>PID - 5 ppm at 6-7 ft</u> <u>PID - 0 ppm at 8 ft</u>	2.0 ft Recovered		
9	1-Y04		0-0.6 ft - Black silty clay			
10			0.6-3.8 ft - Brown silty clay, saturated			
11						
12			<u>PID - 0 ppm</u>	3.8 ft Recovered		
13			0-3.3 ft - Brown silty clay, saturated			
14						
15						
16			<u>PID - 0 ppm</u>	3.3 ft Recovered		
17			<u>End of Boring at 16 ft</u>			
18			1-Y04-9 ft			
19						
20						
21						
22						
23						

		C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG		Boring No. 2-Y01	
		Sheet 1 of:					
		Project No.: V20.001.005					
Project Name: 301 Connecticut Street Brownfield Cleanup Program				Surface Elev.:			
Location: 301 Connecticut Street, Buffalo, NY				Datum:			
Client: D'Youville College				Start Date: 8/5/19			
Drilling Firm: TREC				Finish Date: 8/12/19			
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:				Casing:	Rock Core:		
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION	COMMENTS		
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%	(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)		
1				0-0.7 ft - Asphalt, gravel, and black sand, fill			
2				0.7-1.9 ft - Black silty clay, moist			
3							
4				<u>PID - 0 ppm</u>	1.9 ft Recovered		
5				0-2.0 ft - Black silty clay, moist			
6				2.0-3.9 ft - Brown silty clay, moist			
7				<u>PID - 17 ppm at 6 ft</u>			
8				<u>PID - 2 ppm at 7 ft</u>	3.9 ft Recovered		
9	2-Y01			0-2.2 ft - Brown silty clay, trace sand, moist			
10				2.2-3.7 ft - Silty clay			
11				<u>PID - 1 ppm at 9 ft</u>			
12				<u>PID - 0 ppm at 10 ft</u>	3.7 ft Recovered		
13				0-3.9 ft - Brown silty clay			
14							
15							
16				<u>PID - 0 ppm</u>	3.9 ft Recovered		
17				<u>End of Boring at 16 ft</u>			
18				2-Y01-9 ft			
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG			Boring No. 2-Y02	
					Sheet 1 of:	
					Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program					Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY					Datum:	
Client: D'Youville College					Start Date: 8/5/19	
Drilling Firm: TREC					Finish Date: 8/12/19	
Groundwater	Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:			Casing:	Rock Core:	Undist:	
Before Casing Removal:			Sampler:	Other:		
After Casing Removal:			Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)						
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION		COMMENTS
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%		(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1	2-Y02		0-1.1 ft - Asphalt, gravel, and black sand, fill			
2			1.1-2.7 ft - Dark brown silty clay			
3						
4			<u>PID - 0 ppm</u>			2.7 ft Recovered
5			0-3.4 ft - Dark brown silty clay, some gravel			
6						
7						
8			<u>PID - 0 ppm</u>			3.4 ft Recovered
9			0-3.8 ft - Brown silty clay, moist			
10						
11						
12			<u>PID - 0 ppm</u>			3.8 ft Recovered
13			0-3.7 ft - Brown silty clay, moist			
14						
15						
16			<u>PID - 0 ppm</u>			3.7 ft Recovered
17			<u>End of Boring at 16 ft</u>			
18			2-Y02-4 ft			
19						
20						
21						
22						
23						

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG			Boring No.	2-Y03
					Sheet 1 of:	
					Project No.:	V20.001.005
Project Name:					Surface Elev.:	
Location:					Datum:	
Client:					Start Date:	
Drilling Firm:					Finish Date:	
Groundwater	Depth	Date & Time	Drill Rig:	Inspector:		
While Drilling:			Casing:	Rock Core:	Undist:	
Before Casing Removal:			Sampler:	Other:		
After Casing Removal:			Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)						
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION		COMMENTS
				c - coarse m - medium f - fine a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%		(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-0.6 ft - Asphalt, gravel, fill			
2			0.6-2.9 ft - Sandy clay, dry			
3						
4			PID - 0 ppm			2.9 ft Recovered
5	2-Y03		0-2.8 ft - Sandy clay, dry			
6			2.8-3.6 ft - Silty clay, moist			
7						
8			PID - 0 ppm			3.6 ft Recovered
9			0-3.8 ft - Brown silty clay, moist			
10						
11						
12			PID - 0 ppm			3.8 ft Recovered
13			0-3.6 ft - Brown silty clay, moist			
14						
15						
16			PID - 0 ppm			3.6 ft Recovered
17			End of Boring at 16 ft			
18			2-Y03-5 ft			
19						
20						
21						
22						
23						

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No.	2-Y04
						Sheet 1 of:	
						Project No.:	V20.001.005
Project Name:					301 Connecticut Street Brownfield Cleanup Program		
Location:					301 Connecticut Street, Buffalo, NY		
Client:					D'Youville College		
Drilling Firm:					TREC		
Groundwater	Depth	Date & Time	Drill Rig:		Surface Elev.:		
While Drilling:			Casing:		Datum:		
Before Casing Removal:			Sampler:		Start Date:	8/5/19	
After Casing Removal:			Hammer:		Finish Date:	8/12/19	
					Inspector:	J. Alt-Winzig	
					Rock Core:		
					Undist:		
					Other:		
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION	COMMENTS		
				c - coarse m - medium f - fine a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10% S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey	(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)		
1				0-0.9 ft - Asphalt, gravel, fill			
2				0.9-1.8 ft - Black sand, petroleum odor			
3							
4				<u>PID - 2500 ppm at 2 ft</u>		1.8 ft Recovered	
5				0-1.4 ft - Black sand, petroleum odor, moist			
6							
7							
8				<u>PID - 4000 ppm at 5 ft</u>		1.4 ft Recovered	
9				0-1.8 ft - Black sand, petroleum odor, moist			
10				1.8-3.8 ft - Silty sand, moist			
11				<u>PID - 500 ppm at 9 ft</u>			
12	2-Y04			<u>PID - 100 ppm at 10 ft</u>			
				<u>PID - 90 ppm at 11 ft</u>		3.8 ft Recovered	
				<u>PID - 5 ppm at 12 ft</u>			
13				0-3.2 ft - Brown silty sand, moist			
14							
15							
16				<u>PID - 0 ppm</u>		3.2 ft Recovered	
17				<u>End of Boring at 16 ft</u>			
18				2-Y04-12 ft			
19				Boring was moved 5 ft further from delineation center (15 ft from center) in order to try and find extent of petroleum odor/contamination			
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 2-Y05
						Sheet 1 of:
						Project No.: V20.001.005
Project Name: 301 Connecticut Street Brownfield Cleanup Program					Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY					Datum:	
Client: D'Youville College					Start Date: 8/5/19	
Drilling Firm: TREC					Finish Date: 8/12/19	
Groundwater	Depth	Date & Time	Drill Rig:		Inspector:	J. Alt-Winzig
While Drilling:			Casing:	Rock Core:	Undist:	
Before Casing Removal:			Sampler:	Other:		
After Casing Removal:			Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)						
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION		COMMENTS
				c - coarse m - medium f - fine a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%		(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				0-0.2 ft - Asphalt, gravel, fill		
2				0.2-3.0 ft - Sandy clay		
3						
4				<u>PID - 20 ppm at 3 ft</u>		3.0 ft Recovered
5				0-1.2 ft - Sandy clay		
6				1.2-3.9 ft - Brown silty clay		
7				<u>PID - 250 ppm at 5 ft</u>		
				<u>PID - 130 ppm at 6 ft</u>		
				<u>PID - 110 ppm at 7 ft</u>		3.9 ft Recovered
8				<u>PID - 73 ppm at 8 ft</u>		
9				0-3.9 ft - Brown silty clay		
10						
11				<u>PID - 130 ppm at 9 ft</u>		
				<u>PID - 40 ppm at 10 ft</u>		
				<u>PID - 0 ppm at 11 ft</u>		3.9 ft Recovered
12	2-Y05					
13				<u>End of Boring at 12 ft</u>		
14						
15						
16						
17						
18				2-Y05-12 ft		
19				Boring added on Northeast corner of "Y" delineation 10 ft from center		
20						
21						
22						
23						

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 3-Y04	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION			COMMENTS
				c - coarse m - medium f - fine a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10% S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey			(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				0-1.2 ft - Asphalt, gravel, fill			
2				1.2-2.7 ft - Black and brown silty clay			
3							
4				<u>PID - 0 ppm</u>			2.7 ft Recovered
5				0-1.6 ft - Black and brown silty clay			
6				1.6-3.9 ft - Brown silty clay, petroleum odor, moist			
7				<u>PID - 630 ppm at 5 ft</u>			
				<u>PID - 5500 ppm at 6 ft</u>			
				<u>PID - 430 ppm at 7 ft</u>			3.9 ft Recovered
8				<u>PID - 130 ppm at 8 ft</u>			
9				0-2.6 ft - Brown silty clay, moist			
10							
11				<u>PID - 55 ppm at 9 ft</u>			
				<u>PID - 20 ppm at 10 ft</u>			
				<u>PID - 15 ppm at 11 ft</u>			2.6 ft Recovered
12				<u>PID - 0 ppm at 12 ft</u>			
13	3-Y04			0-2.2 ft - Brown silty clay, moist			
14							
15							
16				<u>PID - 0 ppm</u>			2.2 ft Recovered
17				<u>End of Boring at 16 ft</u>			
18				3-Y04-13 ft			
19				Boring was added 5 ft further from delineation center (20 ft from center) in order to try and find extent of petroleum odor/contamination			
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 1-Z01	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-1.2 ft - Asphalt, gravel, fill				
2			1.2-3.4 ft - Brown sandy clay				
3							
4			<u>PID - 0 ppm</u>				3.4 ft Recovered
5	1-Z01		0-3.9 ft - Brown with black stains sandy clay, some gravel				
6							
7			<u>PID - 60 ppm at 8 ft</u>				
8			<u>PID - 40 ppm at 7 ft</u> <u>PID - 0 ppm at 8 ft</u>				3.9 ft Recovered
9			0-2.9 ft - Brown silty clay, moist				
10							
11							
12			<u>PID - 0 ppm</u>				2.9 ft Recovered
13			0-3.6 ft - Brown silty clay, moist				
14							
15							
16			<u>PID - 0 ppm</u>				3.6 ft Recovered
17			<u>End of Boring at 16 ft</u>				
18			1-Z01-7 ft				
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 1-Z02
						Sheet 1 of:
						Project No.: V20.001.005
Project Name: 301 Connecticut Street Brownfield Cleanup Program					Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY					Datum:	
Client: D'Youville College					Start Date: 8/5/19	
Drilling Firm: TREC					Finish Date: 8/12/19	
Groundwater	Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:			Casing:	Rock Core:	Undist:	
Before Casing Removal:			Sampler:	Other:		
After Casing Removal:			Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)						
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10% S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey		COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-0.6 ft - Asphalt, gravel, fill			
2						
3						
4			<u>PID - 0 ppm</u>	0.6 ft Recovered		
5			0-1.1 ft - Asphalt, gravel, fill			
6			1.1-2.6 ft - Brown silty clay			
7			<u>PID - 60 ppm at 8 ft</u>			
8			<u>PID - 40 ppm at 7 ft</u>			
			<u>PID - 0 ppm at 8 ft</u>	2.6 ft Recovered		
9	1-Z02		0-0.6 ft - Asphalt			
10			0.6-3.8 ft - Brown silty clay			
11			<u>PID - 67 ppm at 9 ft</u>			
12			<u>PID - 5 ppm at 10 ft</u>			
			<u>PID - 0 ppm at 11 ft</u>	3.8 ft Recovered		
			<u>Hit Refusal at 12 ft</u>			
13			<u>End of Boring at 12 ft</u>			
14						
15						
16						
17						
18			1-Z02-11 ft			
19						
20						
21						
22						
23						

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 1-Z03	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-1.0 ft - Asphalt, gravel, and sand fill				
2			1.0-2.1 ft - Gravel				
3							
4			<u>PID - 0 ppm</u>	2.1 ft Recovered			
5			0-1.4 ft - Gravel				
6			1.4-2.5 ft - Sandy clay and gravel				
7			<u>PID - 3500 ppm at 7 ft</u>				
8			<u>PID - 400 ppm at 8 ft</u>	2.5 ft Recovered			
9	1-Z03		0-1.2 ft - Sandy clay and gravel				
10			1.2-3.8 ft - Brown silty clay				
11			<u>PID - 400 ppm at 9 ft</u>				
12			<u>PID - 0 ppm at 10 ft</u>	3.8 ft Recovered			
13			0-3.9 ft - Brown silty clay				
14							
15							
16			<u>PID - 0 ppm</u>	3.9 ft Recovered			
17			<u>End of Boring at 16 ft</u>				
18			1-Z03-11 ft				
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 1-Z04	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:			
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10% S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-0.6 ft - Asphalt, gravel, and sub-base stone, fill				
2			0.6-3.0 ft - Tan sandy clay, dry				
3							
4			<u>PID - 0 ppm</u>				3.0 ft Recovered
5			0-1.1 ft - Brown silty clay				
6			1.1-3.8 ft - Sandy clay, trace gravel				
7			<u>PID - 26 ppm at 5 ft</u>				
8			<u>PID - 15 ppm at 6 ft</u>				
			<u>PID - 8 ppm at 7 ft</u>				3.8 ft Recovered
			<u>PID - 0 ppm at 8 ft</u>				
9	1-Z04		0-2.9 ft - Brown silty clay				
10							
11							
12			<u>PID - 0 ppm</u>				2.9 ft Recovered
13			0-2.8 ft - Brown silty clay				
14							
15							
16			<u>PID - 0 ppm</u>				2.8 ft Recovered
17			<u>End of Boring at 16 ft</u>				
18			1-Z04-10 ft				
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 2-Z01	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10% S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-0.8 ft - Asphalt, gravel, fill				
2			0.8-1.2 ft - Black silty sand				
3			1.2-3.1 ft - Brown silty clay				
4			<u>PID - 0 ppm</u>				3.1 ft Recovered
5	2-Z01		0-1.8 ft - Brown silty clay, some gravel				
6			1.8-2.9 ft - Brown silty clay, moist				
7			<u>PID - 20 ppm at 5 ft</u>				
8			<u>PID - 400 ppm at 6 ft</u> <u>PID - 160 ppm at 7 ft</u> <u>PID - 0 ppm at 8 ft</u>				2.9 ft Recovered
9			0-3.8 ft - Brown silty clay, moist				
10							
11							
12			<u>PID - 0 ppm</u>				3.8 ft Recovered
13			0-1.8 ft - Brown silty clay, moist				
14							
15							
16			<u>PID - 0 ppm</u>				1.8 ft Recovered
17			<u>End of Boring at 16 ft</u>				
18			2-Z01-7 ft				
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 2-Z03	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:		Inspector: J. Alt-Winzig	
While Drilling:				Casing:		Rock Core:	Undist:
Before Casing Removal:				Sampler:		Other:	
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION			COMMENTS
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				0-0.7 ft - Asphalt, gravel, fill			
2				0.7-1.6 ft - Dark brown silty clay			
3							
4				<u>PID - 0 ppm</u>			1.6 ft Recovered
5				No Recovery			
6							
7							
8							0 ft Recovered
9				0-0.6 ft - Brown silty clay and gravel			
10				0.6-3.9 ft - Brown silty clay			
11				<u>PID - 120 ppm at 9 ft</u>			
				<u>PID - 40 ppm at 10 ft</u>			
				<u>PID - 0 ppm at 11 ft</u>			3.9 ft Recovered
12	2-Z03						
13				<u>End of Boring at 12 ft</u>			
14							
15							
16							
17							
18				2-Z03-12 ft			
19							
20							
21							
22							
23							

		C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG		Boring No. 2-Z04	
		Sheet 1 of:					
		Project No.: V20.001.005					
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:		Inspector: J. Alt-Winzig	
While Drilling:				Casing:		Rock Core:	Undist:
Before Casing Removal:				Sampler:		Other:	
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION			COMMENTS
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				0-0.5 ft - Asphalt, gravel, fill			
2				0.5-0.8 ft - Black silty clay			
				0.8-3.0 ft - Brown silty clay, little gravel			
3				<u>PID - 400 ppm at 2 ft</u>			
				<u>PID - 1500 ppm at 3 ft</u>			3.0 ft Recovered
4				<u>PID - 1200 ppm at 4 ft</u>			
5				0-3.6 ft - Brown silty clay			
6							
				<u>PID - 1650 ppm at 6 ft</u>			
7				<u>PID - 200 ppm at 7 ft</u>			
				<u>PID - 0 ppm at 8 ft</u>			3.6 ft Recovered
8							
9	2-Z04			0-3.3 ft - Brown silty clay, moist			
10							
11							
				<u>PID - 0 ppm</u>			3.3 ft Recovered
12							
13				0-0.8 ft - Brown silty clay, moist			
				0.8-2.2 ft - Brown silty clay, saturated			
14				2.2-3.6 ft - Brown silty clay, moist			
15							
				<u>PID - 0 ppm</u>			3.6 ft Recovered
16							
				<u>End of Boring at 16 ft</u>			
17							
				2-Z04-9 ft			
18							
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. 2-Z05	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 8/5/19	
Drilling Firm: TREC						Finish Date: 8/12/19	
Groundwater		Depth	Date & Time	Drill Rig:		Inspector: J. Alt-Winzig	
While Drilling:				Casing:		Rock Core:	Undist:
Before Casing Removal:				Sampler:		Other:	
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-0.7 ft - Asphalt, gravel, fill				
			0.7-1.1 ft - Brown sand				
2			1.1-1.9 ft - Black stained silty clay, petroleum odor				
3							
4			<u>PID - 2800 ppm at 2 ft</u>				1.9 ft Recovered
5			0-1.9 ft - Black stained silty clay, petroleum odor				
6							
7			<u>PID - 2600 ppm at 5 ft</u>				
			<u>PID - 2200 ppm at 6 ft</u>				1.9 ft Recovered
8							
9			0-1.1 ft - Black stained silty clay, petroleum odor				
10			1.1-3.7 ft - Brown silty clay				
11			<u>PID - 150 ppm at 10 ft</u>				
			<u>PID - 50 ppm at 11 ft</u>				
12	2-Z05		<u>PID - 0 ppm at 12 ft</u>				3.7 ft Recovered
13			<u>End of Boring at 12 ft</u>				
14							
15							
16							
17							
18			2-Z05-12 ft				
19			Boring added on Northwest corner of "Z" delineation 10 ft from center				
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454			BORING LOG			Boring No. SW-1			
						Sheet 1 of:			
						Project No.: V20.001.005			
Project Name: 301 Connecticut Street Brownfield Cleanup Program					Surface Elev.:				
Location: 301 Connecticut Street, Buffalo, NY					Datum:				
Client: D'Youville College					Start Date: 9/9/19				
Drilling Firm: TREC					Finish Date: 9/10/19				
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig				
While Drilling:				Casing:	Rock Core:	Undist:			
Before Casing Removal:				Sampler:	Other:				
After Casing Removal:				Hammer:					
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)									
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION			COMMENTS		
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)		
1			0-0.1 ft - Concrete, sub-base stone						
2			0.1-2.6 ft - Brown silty clay, dry						
3									
4			PID- 0 ppm				2.6 ft Recovered		
5	SW-1		0-3.9 ft - Brown silty clay, trace gravel, dry						
6									
7									
8			PID - 0 ppm				3.9 ft Recovered		
9			0-3.9 ft - Brown silty clay, moist						
10									
11									
12			PID - 0 ppm				3.9 ft Recovered		
13			End of Boring at 12 ft						
14			SW-1-5 ft						
15									
16									
17									
18									
19									
20									
21									
22									
23									

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. SW-2	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 9/9/19	
Drilling Firm: TREC						Finish Date: 9/10/19	
Groundwater	Depth	Date & Time	Drill Rig:			Inspector: J. Alt-Winzig	
While Drilling:			Casing:		Rock Core:		Undist:
Before Casing Removal:			Sampler:		Other:		
After Casing Removal:			Hammer:				
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION			COMMENTS
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-0.3 ft - Concrete, sub-base stone				
2			0.3-2.7 ft - Brown silty clay, dry				
3							
4			PID- 0 ppm				2.7 ft Recovered
5	SW-2		0-0.3 ft - Black silty clay				
6			0.3-3.8 ft - Brown silty clay, trace gravel, moist				
7							
8			PID - 0 ppm				3.8 ft Recovered
9			0-3.9 ft - Brown silty clay, saturated				
10							
11							
12			PID - 0 ppm				3.9 ft Recovered
13			End of Boring at 12 ft				
14			SW-2-5 ft				
15							
16							
17							
18							
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. SW-3	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 9/9/19	
Drilling Firm: TREC						Finish Date: 9/10/19	
Groundwater	Depth	Date & Time	Drill Rig:			Inspector: J. Alt-Winzig	
While Drilling:			Casing:		Rock Core:	Undist:	
Before Casing Removal:			Sampler:		Other:		
After Casing Removal:			Hammer:				
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION			COMMENTS
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-0.2 ft - Concrete, sub-base stone				
2			0.2-2.2 ft - Brown silty clay, dry				
3							
4			<u>PID- 0 ppm</u>				2.2 ft Recovered
5	SW-3		0-3.9 ft - Dark brown silty clay, moist				
6							
7			<u>PID - 50 ppm at 6 ft</u>				
8			<u>PID - 500 ppm at 7 ft</u> <u>PID - 30 ppm at 8 ft</u>				3.9 ft Recovered
9			0-2.8 ft - Brown silty clay, moist				
10							
11			<u>PID - 28 oom at 9 ft</u> <u>PID - 23 ppm at 10 ft</u> <u>PID - 0 ppm at 11 ft</u>				2.8 ft Recovered
12							
13			<u>End of Boring at 12 ft</u>				
14			SW-3-7 ft				
15							
16							
17							
18							
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No.	SW-4
						Sheet 1 of:	
						Project No.:	V20.001.005
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 9/9/19	
Drilling Firm: TREC						Finish Date: 9/10/19	
Groundwater	Depth	Date & Time	Drill Rig:		Inspector:	J. Alt-Winzig	
While Drilling:			Casing:	Rock Core:	Undist:		
Before Casing Removal:			Sampler:	Other:			
After Casing Removal:			Hammer:				
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION		COMMENTS	
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%		(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)	
1			0-0.3 ft - Concrete, sub-base stone				
2			0.3-1.7 ft - Brown silty clay, dry				
3							
4			<u>PID- 0 ppm</u>	1.7 ft Recovered			
5	SW-4		0-2.1 ft - Black silty clay				
6							
7			<u>PID - 412 ppm at 5 ft</u>				
8			<u>PID - 1850 ppm at 6 ft</u> <u>PID - 370 ppm at 7 ft</u>	2.1 ft Recovered			
9			0-0.3 ft - Black silty clay				
10			0.3-3.3 ft - Brown silty clay, moist				
11			<u>PID - 30 ppm at 9 ft</u>				
12			<u>PID - 0 ppm at 10 ft</u>	3.3 ft Recovered			
13			<u>End of Boring at 12 ft</u>				
14			SW-4-6 ft				
15							
16							
17							
18							
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No.	SW-5
						Sheet 1 of:	
						Project No.:	V20.001.005
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 9/9/19	
Drilling Firm: TREC						Finish Date: 9/10/19	
Groundwater	Depth	Date & Time	Drill Rig:			Inspector: J. Alt-Winzig	
While Drilling:			Casing:		Rock Core:		Undist:
Before Casing Removal:			Sampler:		Other:		
After Casing Removal:			Hammer:				
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			COMMENTS (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-0.2 ft - Concrete, sub-base stone				
2			0.2-1.2 ft - Brown silty clay, dry				
3							
4			<u>PID- 0 ppm</u>				1.2 ft Recovered
5			0-3.7 ft - Brown silty clay, moist				
6							
7							
8			<u>PID - 0 ppm</u>				3.7 ft Recovered
9	SW-5		0-3.4 ft - Brown silty clay, moist				
10							
11			<u>PID - 45 ppm at 9 ft</u> <u>PID - 100 ppm at 10 ft</u> <u>PID - 0 ppm at 11 ft</u>				3.4 ft Recovered
12							
13			<u>End of Boring at 12 ft</u>				
14			SW-5-10 ft				
15							
16							
17							
18							
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. SW-6	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 9/9/19	
Drilling Firm: TREC						Finish Date: 9/10/19	
Groundwater	Depth	Date & Time	Drill Rig:			Inspector: J. Alt-Winzig	
While Drilling:			Casing:	Rock Core:	Undist:		
Before Casing Removal:			Sampler:	Other:			
After Casing Removal:			Hammer:				
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION			COMMENTS
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-0.2 ft - Concrete, sub-base stone				
2			0.2-1.7 ft - Brown silty clay, dry				
3							
4			PID - 0 ppm				1.7 ft Recovered
5	SW-6		0-3.8 ft - Brown silty clay, moist				
6							
7			PID - 2600 ppm at 6 ft				
8			PID - 25 ppm at 7 ft				3.8 ft Recovered
9			0-2.2 ft - Brown silty clay, moist				
10							
11							
12			PID - 0 ppm				2.2 ft Recovered
13			End of Boring at 12 ft				
14			SW-6-6 ft				
15							
16							
17							
18							
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. SW-7	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 9/9/19	
Drilling Firm: TREC						Finish Date: 9/10/19	
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION			COMMENTS
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-0.2 ft - Concrete, sub-base stone				
2			0.2-2.5 ft - Brown silty clay, dry				
3							
4			<u>PID- 0 ppm</u>				2.5 ft Recovered
5	SW-7		0-3.8 ft - Dark brown silty clay				
6			<u>PID - 1500 ppm at 5 ft</u>				
7			<u>PID - 2600 ppm at 6 ft</u>				
8			<u>PID - 0 ppm at 7 ft</u> <u>PID - 100 ppm at 8 ft</u>				3.8 ft Recovered
9			0-0.7 ft - Dark brown silty clay, some black staining				
10			0.7-3.6 ft - Brown silty clay, moist				
11			<u>PID - 45 ppm at 9 ft</u>				
12			<u>PID - 10 ppm at 10 ft</u>				3.6 ft Recovered
13			<u>End of Boring at 12 ft</u>				
14			SW-7-6 ft				
15							
16							
17							
18							
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. SW-8	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 9/9/19	
Drilling Firm: TREC						Finish Date: 9/10/19	
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION			COMMENTS
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1			0-0.5 ft - Concrete, sub-base stone				
2			0.5-1.5 ft - Brown silty clay, moist				
3							
4			<u>PID - 0 ppm</u>				1.5 ft Recovered
5			0-0.5 ft - Brown silty clay, moist				
6			0.5-0.9 ft - Brown sand, moist				
7			0.9-1.2 ft - Black clayey silt, asphalt, and sand, moist				
8			<u>PID - 0 ppm</u>				1.2 ft Recovered
9	SW-8		0-0.1 ft - Black silty clay				
10			0.1-2.6 ft - Brown silty clay				
11			<u>PID - 0 ppm at 9 ft</u>				
12			<u>PID - 40 ppm at 10 ft</u> <u>PID - 0 ppm at 11 ft</u>				2.6 ft Recovered
13			0-1.2 ft - Brown sandy clay, moist				
14			1.2-3.4 ft - Brown silty clay, moist				
15							
16			<u>PID - 0 ppm</u>				3.4 ft Recovered
17			<u>End of Boring at 16 ft</u>				
18			SW-8-10 ft				
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No.	SW-9
						Sheet 1 of:	
						Project No.:	V20.001.005
Project Name:					301 Connecticut Street Brownfield Cleanup Program		
Location:					301 Connecticut Street, Buffalo, NY		
Client:					D'Youville College		
Drilling Firm:					TREC		
Groundwater		Depth	Date & Time	Drill Rig:			
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION		COMMENTS	
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%		(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)	
1				0-0.2 ft - Concrete, sub-base stone			
2				0.2-0.9 ft - Brown sandy clay, dry			
3							
4				<u>PID - 0 ppm</u>		0.9 ft Recovered	
5	SW-9			0-1.1 ft - Dark brown sandy clay			
6							
7							
8				<u>PID - 0 ppm</u>		1.1 ft Recovered	
9				0-1.4 ft - Dark brown sandy clay			
10							
11							
12				<u>PID - 0 ppm</u>		1.4 ft Recovered	
13				0-1.7 ft - Dark brown sandy clay, moist			
14							
15							
16				<u>PID - 0 ppm</u>		1.7 ft Recovered	
17				<u>End of Boring at 16 ft</u>			
18				SW-9-5 ft			
19							
20							
21							
22							
23							

		C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG		Boring No.		SW-10			
						Sheet 1 of:					
						Project No.:		V20.001.005			
Project Name:				301 Connecticut Street Brownfield Cleanup Program				Surface Elev.:			
Location:				301 Connecticut Street, Buffalo, NY				Datum:			
Client:				D'Youville College				Start Date:		9/9/19	
Drilling Firm:				TREC				Finish Date:		9/10/19	
Groundwater		Depth	Date & Time	Drill Rig:				Inspector:		J. Alt-Winzig	
While Drilling:				Casing:		Rock Core:		Undist:			
Before Casing Removal:				Sampler:		Other:					
After Casing Removal:				Hammer:							
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)											
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION				COMMENTS			
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%				(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)			
1			NO RECOVERY								
2											
3											
4								0 ft Recovered			
5	SW-10		0-3.4 ft - Brown silty clay, moist								
6											
7											
8			PID - 0 ppm					3.4 ft Recovered			
9			0-3.7 ft - Brown silty clay, moist								
10											
11											
12			PID - 0 ppm					3.7 ft Recovered			
13			End of Boring at 12 ft								
14			SW-10-5 ft								
15											
16											
17											
18											
19											
20											
21											
22											
23											

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. MW-6	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 9/9/19	
Drilling Firm: TREC						Finish Date: 9/10/19	
Groundwater		Depth	Date & Time	Drill Rig:	Inspector: J. Alt-Winzig		
While Drilling:				Casing:	Rock Core:	Undist:	
Before Casing Removal:				Sampler:	Other:		
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION			COMMENTS
				c - coarse m - medium f - fine a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%			(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				0-0.2 ft - Concrete, sub-base stone			
2				0.2-2.0 ft - Brown sandy clay			
3							
4				<u>PID - 0 ppm</u>			2.0 ft Recovered
5				0-1.9 ft - Dark brown silty clay, some black staining			
6				1.9-3.6 ft - Brown silty clay, moist			
7							
8				<u>PID - 0 ppm</u>			3.6 ft Recovered
9				0-1.1 ft - Brown silty clay, moist			
10				1.1-1.4 ft - Black silty sand			
11				1.3-3.1 ft - Brown silty clay, moist			
12				<u>PID - 0 ppm</u>			3.1 ft Recovered
13				0-3.9 ft - Brown silty clay, moist			
14							
15							
16				<u>PID - 0 ppm</u>			3.9 ft Recovered
17				<u>End of Boring at 16 ft</u>			
18				Groundwater Sample Taken			
19							
20							
21							
22							
23							

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454			BORING LOG			Boring No. MW-7
						Sheet 1 of:
						Project No.: V20.001.005
Project Name: 301 Connecticut Street Brownfield Cleanup Program					Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY					Datum:	
Client: D'Youville College					Start Date: 9/9/19	
Drilling Firm: TREC					Finish Date: 9/10/19	
Groundwater	Depth	Date & Time	Drill Rig:		Inspector:	J. Alt-Winzig
While Drilling:			Casing:	Rock Core:	Undist:	
Before Casing Removal:			Sampler:	Other:		
After Casing Removal:			Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)						
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION		COMMENTS
				c - coarse m - medium f - fine a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10% S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey		(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				0-0.2 ft - Concrete, sub-base stone		
2				0.2-1.5 ft - Brown silty clay, dry		
3						
4				<u>PID - 0 ppm</u>		1.5 ft Recovered
5				0-1.7 ft - Brown silty clay		
6				1.7-3.9 ft - Brown silty clay, moist		
7						
8				<u>PID - 0 ppm</u>		3.9 ft Recovered
9				0-3.9 ft - Brown silty clay, moist		
10						
11						
12				<u>PID - 0 ppm</u>		3.9 ft Recovered
13				<u>End of Boring at 12 ft</u>		
14				No Samples Taken		
15						
16						
17						
18						
19						
20						
21						
22						
23						

 C&S Engineers, Inc. 141 Elm Street Buffalo, New York 14203 Phone: 716-847-1630 Fax: 716-847-1454		BORING LOG				Boring No. MW-8	
						Sheet 1 of:	
						Project No.: V20.001.005	
Project Name: 301 Connecticut Street Brownfield Cleanup Program						Surface Elev.:	
Location: 301 Connecticut Street, Buffalo, NY						Datum:	
Client: D'Youville College						Start Date: 9/9/19	
Drilling Firm: TREC						Finish Date: 9/10/19	
Groundwater		Depth	Date & Time	Drill Rig:		Inspector: J. Alt-Winzig	
While Drilling:				Casing:		Rock Core:	Undist:
Before Casing Removal:				Sampler:		Other:	
After Casing Removal:				Hammer:			
(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)							
Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION			COMMENTS
				c - coarse m - medium f - fine a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10% S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey			(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				0-0.3 ft - Concrete, sub-base stone			
2				0.3-3.1 ft - Brown silty clay, dry			
3							
4				<u>PID - 0 ppm</u>			3.1 ft Recovered
5				0-2.4 ft - Brown silty clay			
6				2.4-3.9 ft - Brown silty clay, moist			
7							
8				<u>PID - 0 ppm</u>			3.9 ft Recovered
9				0-3.7 ft - Brown silty clay, moist			
10							
11							
12				<u>PID - 0 ppm</u>			3.7 ft Recovered
13				0-3.9 ft - Brown silty clay, moist			
14							
15							
16				<u>PID - 0 ppm</u>			3.9 ft Recovered
17				<u>End of Boring at 16 ft</u>			
18				No Samples Taken			
19							
20							
21							
22							
23							



C&S Companies
141 Elm Street, Suite 100
Buffalo NY 14203
p: (716) 847-1630
f: (716) 847-1454
www.cscos.com

MEMORANDUM

REMEDIAL INVESTIGATION

TO: Bryan Kowalewski, NYSDEC

FROM: Cody Martin, C&S

RE: April 2019 Groundwater Sampling Results
301 Connecticut Street

FILE: C&S Project No. V20.001.002

DATE: May 16, 2019

C&S Engineers, Inc. (C&S) is providing this memorandum to present groundwater sampling results from the sample collection event at the 301 Connecticut Street Site.

BCP Remedial Investigation

On April 11, 2019, C&S collected groundwater samples from five monitoring wells located on 301 Connecticut Street. Samples were collected from these locations as described in the Remedial Investigation / Interim Remedial Work Plan. **Figure 1** shows the locations of the samples on the BCP Site. **Figure 2** shows public and private water wells within a ½ mile of the Site. **Tables 1** summarize emerging contaminant results and **Table 2** summarizes the analytical results and compares the results to Department of Environmental Conservation TOGS 1.1.1 standards for groundwater.

Findings

- MW-1 was installed adjacent to historic underground storage tanks (USTs). Soils with petroleum-like odors were identified from two feet to eight feet below ground surface (bgs). PID readings ranged from two parts per million (ppm) to 325 ppm.
- MW-2 was installed to monitor area where USTs had been previously located and removed. No petroleum like odors were encountered.
- MW-3 was installed adjacent to the former auto repair shop. No petroleum-like odors were encountered.
- MW-4 was installed in the area of historic USTs. No petroleum-like odors were encountered.
- MW-5 was installed toward the southeast BCP boundary.
- Subsurface material consists of four feet of fill material overlying fine grain soils consisting of silty clays and silts. Wet to saturated soils were encountered starting around 11 to 14 feet bgs; except for MW-2, which had perched water at eight feet within the former UST excavation.

REMEDIAL INVESTIGATION

301 Connecticut Street Site

May 16, 2019

Page 2

- Water levels in all the wells were fairly consistent throughout the site. Measurement to depth of water in each well were roughly from 5-6 feet in every well.

Emerging Contaminants

PFAS were sampled in two out of the five wells. PFAS were detected in both monitoring wells were sampled were collected from; concentrations of total PFAS ranged from 0.502 ng/L to 7.19 ng/L. The highest concentration was detected from MW-1. In both of the wells 1-4Dioxane was not detected.

VOCs

VOCs were detected in three of the five wells including the DUP sampling which was collected from MW-4. Wells MW-1, MW-3, MW-4 and the DUP sample contained VOC levels above TOGS guidance levels.

SVOCs

All five wells on the site contained at least one SVOC above the TOGS groundwater guidance levels. MW-3 contained the highest number of SVOCs above TOGS groundwater guidance levels. With all five wells partially screened within the fill material zone, it was not unexpected to have minor detections of SVOCs. The anticipated remedy will remove all contaminated fill material from the Site.

Metals

Metals were detected above TOGS groundwater guidance levels in all five of the monitoring wells throughout the Site. Magnesium was detected above guidance levels in all five monitoring wells including the DUP sample. Other metals that were detected above the guidance levels included, Manganese, Iron, Chromium, Barium, and one detection of Lead in MW-2.

PCBs

No PCBs were detected in any monitoring wells throughout the Site.

Pesticides

Only one well on Site had a detection of pesticides above TOGS groundwater guidance levels. MW-1 had a detection of Beta-BHC slightly above the guidance levels.

REMEDIAL INVESTIGATION

301 Connecticut Street Site

May 16, 2019

Page 3

We respectfully request the Department's review of the results contained herein; please do not hesitate to contact us with any questions or comments.

Very truly yours,

C&S ENGINEERS, INC.



Cody Martin

Project Environmental Scientist




Daniel E. Riker, P.G.

Department Manager – Environmental Services

Attached:


1. Figure 1 – Groundwater Monitoring Well Locations
2. Figure 2 – Public & Private Water Wells
3. Table 1 – Groundwater Sample Results – Emerging Contaminants
4. Table 2 – Groundwater Sample Results
5. Soil Boring and Water Sampling Logs

F:\Project\V20 - D'Youville BCP\V20.001.002 - 301 Connecticut Street \Planning Study \Correspondence\OUT\ Memorandum Letter




Legend

-  PROPOSED BROWNFIELD CLEANUP (BCP) BOUNDARY
-  50-FT X 50-FT BCP GRID
-  GROUNDWATER MONITORING WELL LOCATION





C&S Engineers, Inc.
141 Elm Street
Buffalo, New York 14203
Phone: 716-847-1630
Fax: 716-847-1454
www.cscos.com




301 CONNECTICUT STREET
BROWNFIELD CLEANUP PROGRAM
CITY OF BUFFALO, NEW YORK

MARK	DATE	DESCRIPTION
REVISIONS		
PROJECT NO:	V20.001.002	
DATE:	05/17/2019	
DRAWN BY:	C. MARTIN	
DESIGNED BY:	C. MARTIN	
CHECKED BY:	C. MARTIN	
NO ALTERATION PERMITTED HEREON EXCEPT AS PROVIDED UNDER SECTION 7209 SUBDIVISION 2 OF THE NEW YORK EDUCATION LAW		

GROUNDWATER
MONITORING WELL
LOCATIONS

FIGURE 1




Legend

W WATER WELLS

C&S
COMPANIES®

C&S Engineers, Inc.
141 Elm Street
Buffalo, New York 14203
Phone: 716-847-1630
Fax: 716-847-1454
www.cscos.com



**301 CONNECTICUT STREET
BROWNFIELD CLEANUP PROGRAM**

CITY OF BUFFALO, NEW YORK

MARK	DATE	DESCRIPTION
REVISIONS		
PROJECT NO: V20.001.002		
DATE: 05/17/2019		
DRAWN BY: C. MARTIN		
DESIGNED BY: C. MARTIN		
CHECKED BY: C. MARTIN		
NO ALTERATION PERMITTED HEREON EXCEPT AS PROVIDED UNDER SECTION 7209 SUBDIVISION 2 OF THE NEW YORK EDUCATION LAW		

PUBLIC & PRIVATE
WATER WELLS

FIGURE 2

Table 1

Emerging Contaminants 301 Connecticut Street



Well Location	MW-1	MW-5
Sample ID	MW-1	MW-5
Date Sampled	4/11/2019	4/11/2019
Sample Matrix	Water	Water
Units	ng/l	ng/l
PFOA / PFOS		
Perfluorobutanoic acid (PFBA)	1.23 J	4.65
Perfluoropentanoic acid (PFPeA)	7.19	1.04 J
Perfluorobutanesulfonic Acid (PFBS)	ND	0.569 J
Perfluorohexanoic acid (PFHxA)	6.4	1 J
Perfluoroheptanoic acid (PFHpA)	4.7	0.518 J
Perfluorohexanesulfonic acid (PFHxS)	0.947 J	1.81 J
Perfluorooctanoic acid (PFOA)	5.89	3
Perfluoroheptanesulfonic Acid (PFHpS)	ND	ND
Perfluorononanoic acid (PFNA)	2.75	ND
Perfluorooctanesulfonic Acid (PFOS)	7.14	ND
Perfluorodecanoic acid (PFDA)	ND	ND
Perfluoroundecanoic acid (PFUnA)	ND	ND
Perfluorodecanesulfonic Acid (PFDS)	ND	ND
Perfluorooctanesulfonamide (FOSA)	ND	ND
Perfluorododecanoic acid (PFDoA)	ND	ND
Perfluorotridecanoic acid (PFTrA)	ND	ND
Perfluorotetradecanoic acid (PFTA)	ND	ND
N-methylperfluorooctanesulfonamidoacetic acid (NMeFOSAA)	ND	0.299 J
N-ethylperfluorooctanesulfonamidoacetic acid (NEtFOSAA)	ND	ND
6:2 FTS	0.502 J	0.219 J
8:2 FTS	ND	ND
Total PFOA/PFOS	13.00	3.00
Units	ug/l	ug/l
1,4-Dioxane	ND	ND

ND indicates analyte was not detected.

* - RPD of the LCS and LCSD exceeds the control limits

^ - ICV,CCV,ICB,CCB, ISA, ISB, CRI, CRA, DLCK or MRL standard: Instrument related QC is outside acceptance limits.

J - Result is less than the RL but greater than or equal to the MDL and the concentration is an approximate

TABLE 2

GROUNDWATER SAMPLE RESULTS
301 CONNECTICUT STREET
BUFFALO, NEW YORK



	Location ID	MW-1	MW-2	MW-3	MW-4	DUP (MW-4)	MW-5
	Sample Matrix	WG	WG	WG	WG	WG	WG
	Date Sampled	04/11/2019	04/11/2019	04/11/2019	04/11/2019	04/11/2019	04/11/2019
	Units	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l
NYS TOGS Groundwater Standard & Guidance Value							
SVOC							
Acenaphthene	20.0 ug/l	0.07 J	0.22	0.03 J	0.06 J	0.06 J	ND
Acenaphthylene		ND	ND	ND	ND	ND	ND
Anthracene	50.0 ug/l	0.02 J	0.14	0.02 J	0.03 J	0.02 J	0.01 J
Benzo(A)Anthracene	0.002 ug/l	ND	0.24	0.03 J	ND	ND	ND
Benzo(A)Pyrene		ND	0.17	0.05 J	0.05 J	ND	0.03 J
Benzo(B)Fluoranthene	0.002 ug/l	ND	0.17	0.08 J	0.05 J	ND	0.03 J
Benzo(G,H,I)Perylene		ND	0.11	0.05 J	0.05 J	ND	0.02 J
Benzo(K)Fluoranthene	0.002 ug/l	ND	0.18	0.07 J	0.05 J	ND	0.03 J
Bis(2-ethylhexyl)phthalate	5.0 ug/l	2 J	ND	6.3	ND	ND	2.4 J
Chrysene	0.002 ug/l	ND	0.3	0.09 J	0.08 J	ND	0.04 J
Di-n-butylphthalate	50.0 ug/l	ND	ND	2 J	ND	2 J	
Dibenz(A,H)Anthracene		ND	0.04 J	ND	ND	ND	ND
Fluoranthene	50.0 ug/l	0.04 J	0.83	0.28	0.4	0.14	0.16
Fluorene	50.0 ug/l	0.22	0.19	0.03 J	0.05 J	0.05 J	0.02 J
Indeno(1,2,3-C,D)Pyrene	0.002 ug/l	ND	0.1	0.04 J	0.04 J	ND	0.02 J
Naphthalene	10.0 ug/l	16	0.09 J	0.06 J	0.16 J	0.16	ND
2-Methylnaphthalene		1.1	0.05 J	0.02 J	0.5	0.09 J	
2-Methylphenol (O-Cresol)		2.2 J	ND	ND	ND	ND	ND
4-Methylphenol (P-Cresol)		2.2 J	ND	ND	ND	ND	ND
Pentachlorophenol	1.0 ug/l	ND	ND	ND	ND	ND	ND
Phenanthrene	50.0 ug/l	0.29	0.94	0.11	0.18 J	0.09 J	0.14
Phenol	1.0 ug/l	1.90 J	0.46 J	0.43 J	0.42 J		
Pyrene	50.0 ug/l	0.02 J	0.64	0.20	0.26	0.1 J	0.1
VOC							
1,1,1-Trichloroethane	5.0 ug/l	ND	ND	ND	ND	ND	ND
1,1-Dichloroethane	5.0 ug/l	ND	ND	ND	ND	ND	ND
1,1-Dichloroethene	5.0 ug/l	ND	ND	ND	ND	ND	ND
1,2,4-Trimethylbenzene		25	ND	ND	15	34	ND
1,2-Dichlorobenzene	3.0 ug/l	ND	ND	ND	ND	ND	ND
1,2-Dichloroethane	0.6 ug/l	0.44 J	0.46 J	ND	0.34 J	0.32 J	ND
1,3,5-Trimethylbenzene (Mesitylene)	5.0 ug/l	7.3	ND	ND	17	29	ND
1,3-Dichlorobenzene	3.0 ug/l	ND	ND	ND	ND	ND	ND
1,4-Dichlorobenzene	3.0 ug/l	ND	ND	ND	ND	ND	ND
1,4-Dioxane (P-Dioxane)		ND	ND	ND	ND	ND	ND
2-Butanone	50.0 ug/l	ND	ND	ND	18	28	2.3 J
Acetone	50.0 ug/l	70	14	100	36	49	38
Benzene	1.0 ug/l	19	0.16 J	ND	1.2	2	ND
Carbon Tetrachloride	5.0 ug/l	ND	ND	ND	ND	ND	ND
Chlorobenzene	5.0 ug/l	ND	ND	ND	ND	ND	ND
Chloroform	7.0 ug/l	ND	ND	ND	ND	ND	ND
Cis-1,2-Dichloroethylene	5.0 ug/l	ND	ND	ND	ND	ND	ND
Ethylbenzene	5.0 ug/l	56	ND	ND	46	120	ND
Hexachlorobenzene	0.04 ug/l	ND	ND	ND	ND	ND	ND
Methylene Chloride	5.0 ug/l	ND	ND	ND	ND	ND	ND
N-Butylbenzene	5.0 ug/l	ND	ND	ND	1.7 J	4	ND
N-Propylbenzene	5.0 ug/l	1.9 J	ND	ND	13	55	ND
Sec-Butylbenzene	5.0 ug/l	0.74 J	ND	ND	1.2 J	2 J	ND
Methyl Ethyl Ketone (2-Butanone)	50.0 ug/l	ND	ND	ND	ND	ND	ND
Tert-Butyl Methyl Ether		ND	8.6	ND	ND	ND	ND
p/m-Xylene	5.0 ug/l	150	ND	ND	43	74	ND
o-Xylene	5.0 ug/l	16	ND	ND	38	58	ND
Tetrachloroethylene (PCE)	5.0 ug/l	ND	ND	ND	ND	ND	ND
Toluene	5.0 ug/l	73	ND	ND	5.1	8.8	ND
Trans-1,2-Dichloroethene	5.0 ug/l	ND	ND	ND	ND	ND	ND
Trichloroethylene (TCE)	5.0 ug/l	ND	ND	ND	ND	ND	ND
Vinyl Chloride	2.0 ug/l	ND	ND	ND	ND	ND	ND
Dibenzofuran		ND	ND	ND	ND	ND	ND
Metals							
Aluminum		94 J	42100	376	208	666	60 J
Antimony	3.0 ug/l	ND	ND	ND	ND	ND	ND
Arsenic	25.0 ug/l	7	16	4 J	5	ND	ND
Barium	1000.0 ug/l	1880	797	197	475	582	436
Beryllium	3.0 ug/l	ND	1 J	ND	ND	ND	ND
Cadmium	5.0 ug/l	ND	ND	ND	ND	ND	ND

GROUNDWATER SAMPLE RESULTS
301 CONNECTICUT STREET
BUFFALO, NEW YORK



	Location ID Sample Matrix Date Sampled Units NYS TOGS Groundwater Standand & Guidance Value	MW-1	MW-2	MW-3	MW-4	DUP (MW-4)	MW-5
		WG	WG	WG	WG	WG	WG
		04/11/2019	04/11/2019	04/11/2019	04/11/2019	04/11/2019	04/11/2019
		ug/l	ug/l	ug/l	ug/l	ug/l	ug/l
Calcium		666000	727000	127000	159000	174000	409000
Chromium	50.0 ug/l	ND	71	ND	3 J	4 J	ND
Cobalt		8 J	40	ND	ND	ND	3 J
Copper	200.0 ug/l	10 J	114.0	10	6.0 J	11	7 J
Cyanide	200.0 ug/l	ND	ND	ND	ND	ND	ND
Iron	300.0 ug/l	179	72800	357	276	997	101
Lead	25.0 ug/l	ND	104	ND	ND	10 J	ND
Magnesium	35000.0 ug/l	228000	152000	74900	68700	71400	207000
Manganese	300.0 ug/l	950	2300.0	88	102	157	172
Mercury	0.7 ug/l	ND	0.14 J	ND	ND	ND	ND
Nickel	100.0 ug/l	9 J	92.0	33 J	4 J	4 J	4 J
Potassium		17000	18200	7920	8390	7860	10700
Selenium	10.0 ug/l	ND	9 J	ND	ND	ND	ND
Silver	50.0 ug/l	ND	ND	ND	ND	ND	ND
Sodium		3770000	757000	255000	190000	199000	709000
Thallium	0.5 ug/l	ND	ND	ND	ND	ND	ND
Vanadium		ND	77	2 J	ND	2 J	ND
Zinc	2000.0 ug/l	10.0 J	509	9 J	11 J	20 J	8 J
PCBs							
Aroclor 1016	0.09	ND	ND	ND	ND	ND	ND
Aroclor 1221	0.09	ND	ND	ND	ND	ND	ND
Aroclor 1232	0.09	ND	ND	ND	ND	ND	ND
Aroclor 1242	0.09	ND	ND	ND	ND	ND	ND
Aroclor 1248	0.09	ND	ND	ND	ND	ND	ND
Aroclor 1254	0.09	ND	ND	ND	ND	ND	ND
Aroclor 1260	0.09	ND	ND	ND	ND	ND	ND
Aroclor 1262	0.09	ND	ND	ND	ND	ND	ND
Aroclor 1268	0.09	ND	ND	ND	ND	ND	ND
PCBs, Total		ND	ND	ND	ND	ND	ND
Pesticides							
Delta-BHC	0.04	ND	ND	ND	ND	ND	ND
Lindane	0.05	ND	ND	ND	ND	ND	ND
Alpha-BHC	0.01	ND	ND	ND	ND	ND	ND
Beta-BHC	0.04	0.054 IP	ND	ND	ND	ND	ND
Heptachlor	0.04	ND	ND	ND	ND	ND	ND
Aldrin	0	ND	ND	ND	ND	ND	ND
Endrin	0	ND	ND	ND	ND	ND	ND
Dieldrin	0.004	ND	ND	ND	ND	ND	ND
4,4'-DDE	0.2	ND	ND	ND	ND	ND	ND
4,4'-DDD	0.3	ND	0.006 J	ND	ND	ND	ND
4,4'-DDT	0.2	ND	ND	ND	ND	ND	ND
Endosulfan I		ND	ND	ND	ND	ND	ND
Endosulfan II		ND	ND	ND	ND	ND	ND
Endosulfan sulfate		ND	ND	ND	ND	ND	ND
cis-Chlordane		ND	ND	ND	ND	ND	ND



C&S Engineers, Inc.
141 Elm Street
Buffalo, New York 14203
Phone: 716-847-1630
Fax: 716-847-1454
www.cscos.com

BORING LOG

Boring No. **MW-01**
Sheet 1 of:
Project No.:
Surface Elev.:
Datum:
Start Date: **4/2/19**
Finish Date:
Inspector: **C. Martin**

Project Name: **301 Connecticut St. BCP**

Location:

Client:

Drilling Firm:

Groundwater	Depth	Date & Time	Drill Rig:	Casing:	Rock Core:	Undist:
While Drilling:						
Before Casing Removal:			Sampler:	Other:		
After Casing Removal:			Hammer:			

(N = No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)

Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION	COMMENTS
				C - coarse M - medium F - fine S - Sand, S - Silt, G - Gravel, C - Clay, cl - clayey	a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%
1				0-8" Asphalt	8:30 am
2				8"-38" Stiff br Silty CLAY - moist petro like odor @ 21-41 high PL	Sunny; 35°F light wind
3					0 ppm
4				HeadSpace + 325 ppm	30 ppm
5				0-24" Stiff br Silty CLAY - moist Some imbedded rounded Gravel 0.5" ↓	521 ppm
6				24" grades to more Silt Content	145 ppm
7				Petro like odor	290 ppm
8					
9				0-35" Soft Silty CLAY - high PL - br - moist	30 ppm
10				Slight petro like odor	15 ppm
11					12 ppm
12					10 ppm
13				0-24" Same as previous	5 ppm
14				24-29" SILT - lt brown, moist - wet	3 ppm
15				29"-48" Soft br moist - wet Silty CLAY high PL imbedded coarse Gravel	
16					
17				0-48" Soft br Silty CLAY same as previous	2 ppm
18					
19					
20					
21					
22					
23					



C&S Engineers, Inc.
141 Elm Street
Buffalo, New York 14203
Phone: 716-847-1030
Fax: 716-847-1454
www.cscs.com

BORING LOG

Boring No. **MW-02**
Sheet 1 of:
Project No.:

Project Name:				Surface Elev.:	
Location:				Datum:	
Client:				Start Date: 4/2/19	
Drilling Firm:				Finish Date:	
Groundwater	Depth	Date & Time	Drill Rig:	Inspector:	
While Drilling:			Casing:	Rock Core:	Undist:
Before Casing Removal:			Sampler:	Other:	
After Casing Removal:			Hammer:		

(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)

Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION	COMMENTS
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, clay - clayey	a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10% (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				3" Asphalt	1:15 PM
2				No Recovery	
3					
4					
5				3" Saturated Gravel backfill	
6				No Recovery	
7					
8				0-8" Saturated ^{water} Gravel backfill	0 ppm
9				Angular Crushed Stone 0.5" ✓	
10				8"-26" Soft Silty CLAY - br - wet	0 ppm
11				high PL	
12					
13				8"-9" Slug	
14				9"-38" Same Soft CLAY - saturated	0 ppm
15					
16					
17				0-14" Slug	
18				14"-32" Same as previous	0 ppm
19					
20					
21				End @ 20'	
22					
23					



C&S Engineers, Inc.
141 Elm Street
Buffalo, New York 14203
Phone: 716-847-1630
Fax: 716-847-1454
www.cscs.com

BORING LOG

Boring No. NW 03

Sheet 1 of:

Project No.:

Surface Elev.:

Datum:

Start Date: 4/3/19

Finish Date:

Inspector: J. BARNES

Project Name: 301 CONSTRUCTION ST. BLP.

Location:

Client:

Drilling Firm: TREC

Groundwater

Depth

Date & Time

Drill Rig:

While Drilling:

8:30

Casing:

Rock Core:

Undist:

Before Casing Removal:

Sampler:

Other:

After Casing Removal:

Hammer:

(N = No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)

Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION	COMMENTS
				G - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey	a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%
					(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				0-3" ASPHALT	
2				3"-48" DENSE SILTY CLAY SOME SMOOTH GRAVEL THROUGHOUT	SUNNY 360F Wind: 15 mph South West 0.4 ppm 0.7 ppm
3					
4					
5				0"-8" SLUG	6.0 ppm
6				8"-48" SILTY LOOSE BROWN CLAY	1.3 ppm
7				48"-48" DENSE SILTY CLAY SOME SMOOTH GRAVEL	
8					
9				0"-24" DENSE SILTY DRY CLAY BROWN	1.4 ppm
10					
11				24"-48" SATURATED WET SOFT SILTY BROWN CLAY	2.0 ppm
12					
13				SATURATED	1.3 ppm
14				0"-18" WET SILTY BROWN CLAY	2.0 ppm
15				18"-48" DENSE SILTY BROWN CLAY	
16					
17				* Little Recovery	0.1 ppm
18				~ 4" SOFT WET SILTY CLAY	
19					
20				END BORING AT 20'	
21					
22					
23					



C&S Engineers, Inc.
141 Elm Street
Buffalo, New York 14203
Phone: 716-847-1630
Fax: 716-847-1454
www.cscs.com

BORING LOG

Boring No. MW04
Sheet 1 of:
Project No.:

Project Name: 301 CONNATULIN ST BCD.

Location:

Client:

Drilling Firm: TREL

Surface Elev.:

Datum:

Start Date: 4/3/19

Finish Date:

Inspector: R. Jackson

Groundwater Depth Date & Time

While Drilling:

11:45

Casing:

Rock Core:

Undist:

Before Casing Removal:

Sampler:

Other:

After Casing Removal:

Hammer:

(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)

Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION	COMMENTS
				c - coarse m - medium f - fine S - Sand, S - Silt, G - Gravel, C - Clay, cly - clayey	a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10% (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				- LITTLE RECOVERY	
2				0" - 3" ASPHALT	1.4 ppm
3				3" SOME SMOOTH GRAVEL MIXED IN SILTY CLAY.	
4					
5				0" - 5" SLURRY ASPHALT	0.8 ppm
6				5" - 48" DENSE SILTY CLAY / SOME SMOOTH GRAVEL THROUGHOUT.	1.0 ppm
7					
8					
9				0" - 10" DARK BROWN CLAY / ANGLAR GRAVEL THROUGHOUT	17.3 ppm
10				10" - 48" DENSE SILTY BROWN CLAY / ANGLAR GRAVEL THROUGHOUT	5.1 ppm
11					
12					
13				0" - 3" SLURRY	1.0 ppm
14				3" - 15" LARGE GRAVEL EMBEDDED IN SILTY CLAY	
15				15" - 48" DENSE SILTY CLAY / BROWN	1.5 ppm
16					
17					
18				0" - 48" SILTY BROWN CLAY	2.4 ppm
19				SAME AS PREVIOUS	
20					
21				END DRILLING AT 20'	
22					
23					



C&S Engineers, Inc.
141 Elm Street
Buffalo, New York 14203
Phone: 716-847-1630
Fax: 716-847-1454
www.cscs.com

BORING LOG

Boring No.

MW05

Sheet 1 of:

Project No.:

Surface Elev.:

Datum:

Start Date:

4/3/19

Finish Date:

Inspector:

R. BACKERT

Project Name: 301 CONNECTICUT ST BLP

Location:

Client:

Drilling Firm:

TRELL

Groundwater

Depth

Date & Time

Drill Rig:

While Drilling:

12:30

Casing:

Rock Core:

Undist:

Before Casing Removal:

Sampler:

Other:

After Casing Removal:

Hammer:

(N = No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)

Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION	COMMENTS
				c - coarse m - medium f - fine S - Sand, S - Silt, G - Gravel, C - Clay, clay - clayey	a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%
					(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				0"-3" ASPHALT	
2				3"-48" FINE SMOOTH GRAVEL THROUGH SILTY CLAY. / BROWN	1.5 ppm
3					
4					
5				0"-3" SLURRY	1.7 ppm
6					
7				3"-48" SAME AS PREVIOUS / SILTY DENSE BROWN CLAY / SOME SMALL FINE GRAVEL THROUGHOUT	2.1 ppm
8					
9				0"-5" SLURRY ASPHALT	2.3 ppm
10					
11				5"-48" SAME AS PREVIOUS / SILTY DENSE BROWN CLAY / SOME FINE GRAVEL THROUGHOUT	3.1 ppm
12					
13				0"-15" DENSE SILTY BROWN CLAY WITH LARGE GRAVEL THROUGHOUT	1.9 ppm
14					
15				15"-48" MOIST SILTY BROWN CLAY.	2.2 ppm
16					
17					
18				0"-48" MOIST SILTY CLAY / BROWN / SOME SMALL SMOOTH GRAVEL	0.7 ppm
19					
20					
21				END BORING 20'	
22					
23					



C&S Engineers, Inc.
141 Elm Street Suite 100
Buffalo, New York 14203
Phone: 716-847-1630
www.cscos.com

Well Sampling Field Data Sheet

Well Casing Unit Volume

(gal/l.f.)

1 1/2" = 0.08 2" = 0.17 3" = 0.38
4" = 0.66 6" = 1.5 8" = 2.6

Client Name:

Site Name: 301 CONNECTICUT ST. YOUNG & COLLEGE

Project No.:

Field Staff: RICH BACKERT

WELL DATA

Date	4/11/19	4/11/19	4/11/19	4/11/19	4/11/19			
Well Number	MW-4	MW-5	MW-1	MW-2	MW-3			
Diameter (inches)	2"	2"	2"	2"	2"			
Total Sounded Depth (feet)	20.7	20.2	20.4	19.3	20.2			
Static Water Level (feet)	6.4	5.0	5.7	5.3	5.7			
H ₂ O Column (feet)								
Pump Intake (feet)								
Well Volume (gallons)								
Amount to Evacuate (gallons)								
Amount Evacuated (gallons)								

FIELD READINGS

Date	4/11/19	4/11/19	4/11/19	4/11/19	4/11/19			
Time	9:20	10:30	11:30	12:15	1:15			
pH (Std. Units)	+/-0.1	7.60	7.20	6.80	7.50	7.45		
Conductivity (mS/cm)	3%	2.23	7.65	28.7	4.70	2.22		
Turbidity (NTU)	10%							
D.O. (mg/L)	10%	13.06	14.37	13.12	12.28	12.42		
Temperature (°C) (°F)	3%	9.48°C	9.19°C	9.04°C	9.40°C	9.59°C		
ORP ³ (mV)	+/-10 mv	96	86	98	-141	26		
Appearance		CLEAR	CLEAR	CLEAR	SEMI TURBID	CLEAR		
Free Product (Yes/No)		YES	YES	YES	YES	YES		
Odor		NONE	NONE	NONE	NONE	NONE		
Comments	MW-4 & 1-4 Dioxane collected from MW-5 + MW-1 * Dup from MW-4 * MS & MSD collected from MW-2							

C = Clear T = Turbid ST = Semi Turbid VT = Very Turbid



C&S Companies
141 Elm Street, Suite 100
Buffalo NY 14203
p: (716) 847-1630
f: (716) 847-1454
www.cscos.com

MEMORANDUM

REMEDIAL INVESTIGATION

TO: Bryan Kowalewski, NYSDEC

FROM: Cody Martin, C&S

RE: May 2019 Groundwater Sampling Results
301 Connecticut Street

FILE: C&S Project No. V20.001.002

DATE: June 14, 2019

C&S Engineers, Inc. (C&S) is providing this memorandum to present groundwater sampling results from the sample collection event at the 301 Connecticut Street Site.

BCP Remedial Investigation

On May 21, 2019, C&S collected a second round of groundwater samples from five monitoring wells located on 301 Connecticut Street. Samples were collected from these locations as described in the Remedial Investigation / Interim Remedial Work Plan. **Figure 1** shows the locations of the samples on the BCP Site. **Figure 2** shows public and private water wells within a ½ mile of the Site. No emerging contaminants were tested for in the second round of groundwater sampling. **Table 1** summarizes the analytical results and compares the results to Department of Environmental Conservation TOGS 1.1.1 standards for groundwater.

Findings

- MW-1 was installed adjacent to historic underground storage tanks (USTs). Soils with petroleum-like odors were identified from two feet to eight feet below ground surface (bgs). PID readings ranged from two parts per million (ppm) to 325 ppm.
- MW-2 was installed to monitor area where USTs had been previously located and removed. There were no petroleum like odors that were encountered.
- MW-3 was installed adjacent to the former auto repair shop. No petroleum-like odors were encountered.
- MW-4 was installed in the area of historic USTs. No petroleum-like odors were encountered.
- MW-5 was installed toward the southeast BCP boundary.
- Subsurface material consists of four feet of fill material overlying fine grain soils consisting of silty clays and silts. Wet to saturated soils were encountered starting around 11 to 14 feet

REMEDIAL INVESTIGATION

301 Connecticut Street Site

June 14, 2019

Page 2

bgs; except for MW-2, which had perched water at eight feet within the former UST excavation.

- Water levels in all the wells were fairly consistent throughout the site. Measurement to depth of water in each well were roughly from 5-7 feet in every well.

Emerging Contaminants

No PFAS were sampled in the second round of groundwater sampling. PFAS were previously detected in the first round of groundwater sampling in both monitoring wells that were sampled. Concentrations of total PFAS ranged from 0.502 ng/L to 7.19 ng/L. The highest concentration was detected from MW-1. In both of the wells 1,4-Dioxane was not detected.

VOCs

VOCs were detected in all five wells including the DUP sampling which was collected from MW-4. All VOC levels decreased in concentration since the previous sampling event. Only Well MW-1, contained VOC levels above TOGS guidance levels.

SVOCs

SVOCs were detected in four of the five wells on the site. All four wells, including the DUP sample contained at least one SVOC above the TOGS groundwater guidance levels. MW-1 and MW-3 contained the highest number of SVOCs above TOGS groundwater guidance levels. Well MW-4 detected no concentrations for SVOCs for any analyte sampled. With all five wells partially screened within the fill material zone, it was not unexpected to have turbidity, leading to minor detections of SVOCs. The anticipated remedy will remove all contaminated fill material from the Site.

Metals

Metals were detected above TOGS groundwater guidance levels in all five of the monitoring wells throughout the Site. Magnesium was detected above guidance levels in all five monitoring wells including the DUP sample. Other metals that were detected above the guidance levels included, Manganese, Iron, Barium, and one detection of Thallium in MW-2. Majority of metal concentrations appeared to decrease in the second round of groundwater sampling.

PCB

No PCBs were detected in any monitoring wells throughout the Site.

Pesticides

Only one well on Site had a detection of pesticides above TOGS groundwater guidance levels. MW-1 had a detection of Beta-BHC slightly above the guidance levels. Beta-BHC was also the only pesticide detected in the first round of groundwater sampling. The concentration remained relatively consistent.

REMEDIAL INVESTIGATION

301 Connecticut Street Site

June 14, 2019

Page 3


We respectfully request the Department's review of the results contained herein; please do not hesitate to contact us with any questions or comments.

Very truly yours,

C&S ENGINEERS, INC.



Cody Martin
Project Environmental Scientist




Daniel E. Riker, P.G.
Department Manager – Environmental Services


Attached:

1. Figure 1 – Groundwater Monitoring Well Locations
2. Figure 2 – Public & Private Water Wells
3. Table 1 – Groundwater Sample Results
4. Soil Boring and Water Sampling Logs

F:\Project\V20 - D'Youville BCP\V20.001.002 - 301 Connecticut Street \Planning Study \Correspondence\OUT\ Memorandum Letter




- Legend**
- PROPOSED BROWNFIELD CLEANUP (BCP) BOUNDARY
 - 50-FT X 50-FT BCP GRID
 - GROUNDWATER MONITORING WELL LOCATION



C&S COMPANIES

C&S Engineers, Inc.
141 Elm Street
Buffalo, New York 14203
Phone: 716-847-1630
Fax: 716-847-1454
www.cscos.com




**301 CONNECTICUT STREET
BROWNFIELD CLEANUP PROGRAM**

CITY OF BUFFALO, NEW YORK

MARK	DATE	DESCRIPTION
REVISIONS		
PROJECT NO:	V20.001.002	
DATE:	05/17/2019	
DRAWN BY:	C. MARTIN	
DESIGNED BY:	C. MARTIN	
CHECKED BY:	C. MARTIN	
NO ALTERATION PERMITTED HEREON EXCEPT AS PROVIDED UNDER SECTION 7209 SUBDIVISION 2 OF THE NEW YORK EDUCATION LAW		

**GROUNDWATER
MONITORING WELL
LOCATIONS**

FIGURE 1




Legend

W WATER WELLS

C&S
COMPANIES®

C&S Engineers, Inc.
141 Elm Street
Buffalo, New York 14203
Phone: 716-847-1630
Fax: 716-847-1454
www.cscos.com



**301 CONNECTICUT STREET
BROWNFIELD CLEANUP PROGRAM**

CITY OF BUFFALO, NEW YORK

MARK	DATE	DESCRIPTION
REVISIONS		
PROJECT NO: V20.001.002		
DATE: 05/17/2019		
DRAWN BY: C. MARTIN		
DESIGNED BY: C. MARTIN		
CHECKED BY: C. MARTIN		
NO ALTERATION PERMITTED HEREON EXCEPT AS PROVIDED UNDER SECTION 7209 SUBDIVISION 2 OF THE NEW YORK EDUCATION LAW		

PUBLIC & PRIVATE
WATER WELLS

FIGURE 2

TABLE 1

GROUNDWATER SAMPLE RESULTS
301 CONNECTICUT STREET
BUFFALO, NEW YORK



Location ID	MW-1	MW-2	MW-3	MW-4	DUP (MW-4)	MW-5	MW-1	MW-2	MW-3	MW-4	DUP (MW-4)	MW-5
Sample Matrix	WG	WG	WG	WG	WG	WG	WG	WG	WG	WG	WG	WG
Date Sampled	04/11/2019	04/11/2019	04/11/2019	04/11/2019	04/11/2019	04/11/2019	05/21/2019	05/21/2019	05/21/2019	05/21/2019	05/21/2019	05/21/2019
Units	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l
NYS TOGS Groundwater Standand & Guidance Value												
SVOC												
Acenaphthene	20.0 ug/l	0.07 J	0.22	0.03 J	0.06 J	0.06 J	ND	0.08 J	0.06 J	ND	ND	ND
Acenaphthylene		ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Anthracene	50.0 ug/l	0.02 J	0.14	0.02 J	0.03 J	0.02 J	0.01 J	0.04 J	0.02 J	ND	ND	ND
Benzo(A)Anthracene	0.002 ug/l	ND	0.24	0.03 J	ND	ND	ND	0.05 J	0.02 J	0.02 J	ND	ND
Benzo(A)Pyrene		ND	0.17	0.05 J	0.05 J	ND	0.03 J	0.02 J	ND	ND	0.02 J	ND
Benzo(B)Fluoranthene	0.002 ug/l	ND	0.17	0.08 J	0.05 J	ND	0.03 J	0.04 J	0.03 J	0.02 J	ND	0.04 J
Benzo(G,H,I)Perylene		ND	0.11	0.05 J	0.05 J	ND	0.02 J	0.03 J	0.01 J	0.02 J	ND	0.04 J
Benzo(K)Fluoranthene	0.002 ug/l	ND	0.18	0.07 J	0.05 J	ND	0.03 J	0.03 J	ND	0.01 J	ND	0.01 J
Bis(2-ethylhexyl)phthalate	5.0 ug/l	2 J	ND	6.3	ND	ND	2.4 J	3.8	ND	ND	ND	ND
Chrysene	0.002 ug/l	ND	0.3	0.09 J	0.08 J	ND	0.04 J	0.05	0.02 J	0.02 J	ND	ND
Di-n-butylphthalate	50.0 ug/l	ND	ND	2 J	ND	2 J		ND	ND		ND	ND
Dibenz(A,H)Anthracene		ND	0.04 J	ND	ND	ND	ND	0.02 J	ND	ND	ND	ND
2, 4-Dimethylphenol	2.0 ug/l	ND	ND	ND	ND	ND	ND	1.8 J	ND		ND	ND
Fluoranthene	50.0 ug/l	0.04 J	0.83	0.28	0.4	0.14	0.16	0.08 J	0.09 J	0.04 J	ND	0.05 J
Fluorene	50.0 ug/l	0.22	0.19	0.03 J	0.05 J	0.05 J	0.02 J	0.06 J	0.04 J	ND	ND	ND
Indeno(1,2,3-C,D)Pyrene	0.002 ug/l	ND	0.1	0.04 J	0.04 J	ND	0.02 J	0.03 J	0.02 J	0.03 J	ND	0.05 J
Naphthalene	10.0 ug/l	16	0.09 J	0.06 J	0.16 J	0.16	ND	5.8	0.14	ND	ND	ND
2-Methylnaphthalene		1.1	0.05 J	0.02 J	0.5	0.09 J		0.26	0.03 J	0.04	ND	ND
2-Methylphenol (O-Cresol)		2.2 J	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
4-Methylphenol (P-Cresol)		2.2 J	ND	ND	ND	ND	ND	1.4 J	ND	ND	ND	ND
Pentachlorophenol	1.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Phenanthrene	50.0 ug/l	0.29	0.94	0.11	0.18 J	0.09 J	0.14	0.12	0.12	ND	ND	ND
Phenol	1.0 ug/l	1.90 J	0.46 J	0.43 J	0.42 J			ND	ND		ND	ND
Pyrene	50.0 ug/l	0.02 J	0.64	0.20	0.26	0.1 J	0.1	0.06 J	0.07 J	0.04	ND	0.03 J
VOC												
1,1,1-Trichloroethane	5.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
1,1-Dichloroethane	5.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
1,1-Dichloroethene	5.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
1,2,4-Trimethylbenzene		25	ND	ND	15	34	ND	21	ND	ND	ND	ND
1,2-Dichlorobenzene	3.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
1,2-Dichloroethane	0.6 ug/l	0.44 J	0.46 J	ND	0.34 J	0.32 J	ND	0.39 J	0.16 J	ND	0.23 J	0.38 J
1,3,5-Trimethylbenzene (Mesitylene)	5.0 ug/l	7.3	ND	ND	17	29	ND	12	ND	ND	ND	ND
1,3-Dichlorobenzene	3.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
1,4-Dichlorobenzene	3.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
1,4-Dioxane (P-Dioxane)		ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND

TABLE 1

GROUNDWATER SAMPLE RESULTS
301 CONNECTICUT STREET
BUFFALO, NEW YORK



	Location ID Sample Matrix Date Sampled Units NYS TOGS Groundwater Standard & Guidance Value	MW-1	MW-2	MW-3	MW-4	DUP (MW-4)	MW-5	MW-1	MW-2	MW-3	MW-4	DUP (MW-4)	MW-5
		WG	WG	WG	WG	WG	WG	WG	WG	WG	WG	WG	WG
		04/11/2019	04/11/2019	04/11/2019	04/11/2019	04/11/2019	04/11/2019	05/21/2019	05/21/2019	05/21/2019	05/21/2019	05/21/2019	05/21/2019
		ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l
2-Butanone	50.0 ug/l	ND	ND	ND	18	28	2.3 J	ND	ND	ND	ND	ND	ND
Acetone	50.0 ug/l	70	14	100	36	49	38	17	2.9 J	1.7 J	1.6 J	2.8 J	2.2 J
Benzene	1.0 ug/l	19	0.16 J	ND	1.2	2	ND	9.4	ND	ND	ND	ND	ND
Carbon Tetrachloride	5.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Chlorobenzene	5.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Chloroform	7.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Cis-1,2-Dichloroethylene	5.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Ethylbenzene	5.0 ug/l	56	ND	ND	46	120	ND	62	ND	ND	ND	ND	ND
Hexachlorobenzene	0.04 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Methylene Chloride	5.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
N-Butylbenzene	5.0 ug/l	ND	ND	ND	1.7 J	4	ND	ND	ND	ND	ND	ND	ND
N-Propylbenzene	5.0 ug/l	1.9 J	ND	ND	13	55	ND	2.3 J	ND	ND	ND	ND	ND
Sec-Butylbenzene	5.0 ug/l	0.74 J	ND	ND	1.2 J	2 J	ND	ND	ND	ND	ND	ND	ND
Methyl Ethyl Ketone (2-Butanone)	50.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Tert-Butyl Methyl Ether		ND	8.6	ND	ND	ND	ND	ND	3.3	ND	ND	ND	ND
p/m-Xylene	5.0 ug/l	150	ND	ND	43	74	ND	170	ND	ND	ND	ND	ND
o-Xylene	5.0 ug/l	16	ND	ND	38	58	ND	21	ND	ND	ND	ND	ND
Tetrachloroethylene (PCE)	5.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Toluene	5.0 ug/l	73	ND	ND	5.1	8.8	ND	61	ND	ND	ND	ND	ND
Trans-1,2-Dichloroethene	5.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Trichloroethylene (TCE)	5.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Vinyl Chloride	2.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Dibenzofuran		ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Metals													
Aluminum		94 J	42100	376	208	666	60 J	202	2080	1220	39	219	567
Antimony	3.0 ug/l	ND	ND	ND	ND	ND	ND	ND	3.35 J	ND	ND	ND	ND
Arsenic	25.0 ug/l	7	16	4 J	5	ND	ND	ND	2.49	2.57	1.2	1.24	1.43
Barium	1000.0 ug/l	1880	797	197	475	582	436	1098	354	152	229	210	394
Beryllium	3.0 ug/l	ND	1 J	ND	ND	ND	ND	ND	0.11 J	ND	ND	ND	ND
Cadmium	5.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Calcium		666000	727000	127000	159000	174000	409000	504000	133000	150000	141000	113000	480000
Chromium	50.0 ug/l	ND	71	ND	3 J	4 J	ND	ND	3.94	4.54	0.35 J	1.04	1.34
Cobalt		8 J	40	ND	ND	ND	3 J	7.16	2.13	1.28	0.6	0.85	2.67
Copper	200.0 ug/l	10 J	114.0	10	6.0 J	11	7 J	4.02 J	5.76	4.71	1.12	1.22	2.12
Cyanide	200.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Iron	300.0 ug/l	179	72800	357	276	997	101	2340	6890	1980	55.1	174	601

TABLE 1

GROUNDWATER SAMPLE RESULTS
301 CONNECTICUT STREET
BUFFALO, NEW YORK



Location ID Sample Matrix Date Sampled Units NYS TOGS Groundwater Standard & Guidance Value	MW-1	MW-2	MW-3	MW-4	DUP (MW-4)	MW-5	MW-1	MW-2	MW-3	MW-4	DUP (MW-4)	MW-5
	WG	WG	WG	WG	WG	WG	WG	WG	WG	WG	WG	WG
	04/11/2019	04/11/2019	04/11/2019	04/11/2019	04/11/2019	04/11/2019	05/21/2019	05/21/2019	05/21/2019	05/21/2019	05/21/2019	05/21/2019
	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l
Lead25.0 ug/l	ND	104	ND	ND	10 J	ND	ND	5.98	5.3	0.43 J	0.56 J	0.93 J
Magnesium35000.0 ug/l	228000	152000	74900	68700	71400	207000	312000	48100	86600	77600	78200	251000
Manganese300.0 ug/l	950	2300.0	88	102	157	172	904.9	221	152.2	91.6	92	302.9
Mercury0.7 ug/l	ND	0.14 J	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Nickel100.0 ug/l	9 J	92.0	33 J	4 J	4 J	4 J	10.71 J	6.43	4.47	1.7 J	2.3	5.31
Potassium	17000	18200	7920	8390	7860	10700	13800	6220	14200	6950	6880	10600
Selenium10.0 ug/l	ND	9 J	ND	ND	ND	ND	ND	2.51 J	2.49 J	ND	1.88 J	ND
Silver50.0 ug/l	ND	ND	ND	ND	ND	ND	ND	ND	3.3	ND	ND	0.29 J
Sodium	3770000	757000	255000	190000	199000	709000	4E+06	1E+06	194000	170000	179000	640000
Thallium0.5 ug/l	ND	ND	ND	ND	ND	ND	ND	0.97 J	ND	ND	ND	ND
Zinc2000.0 ug/l	10.0 J	509	9 J	11 J	20 J	8 J	ND	30.36	18.73	ND	3.76 J	7.85 J
PCBs												
Aroclor 10160.09	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Aroclor 12210.09	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Aroclor 12320.09	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Aroclor 12420.09	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Aroclor 12480.09	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Aroclor 12540.09	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Aroclor 12600.09	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Aroclor 12620.09	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Aroclor 12680.09	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
PCBs, Total	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Pesticides												
Delta-BHC0.04	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Lindane0.05	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Alpha-BHC0.01	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Beta-BHC0.04	0.054 IP	ND	ND	ND	ND	ND	0.063 IP	ND	ND	ND	ND	ND
Heptachlor0.04	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Aldrin0	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Endrin0	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Dieldrin0.004	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
4,4'-DDE0.2	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
4,4'-DDD0.3	ND	0.006 J	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
4,4'-DDT0.2	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Endosulfan I	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Endosulfan II	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Endosulfan sulfate	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
cis-Chlordane	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND



C&S Engineers, Inc.
141 Elm Street
Buffalo, New York 14203
Phone: 716-847-1630
Fax: 716-847-1454
www.cscos.com

BORING LOG

Boring No. **MW-01**
Sheet 1 of:
Project No.:
Surface Elev.:
Datum:
Start Date: **4/2/19**
Finish Date:
Inspector: **C. Martin**

Project Name: **301 Connecticut St. BCP**

Location:

Client:

Drilling Firm:

Groundwater	Depth	Date & Time	Drill Rig:	Casing:	Rock Core:	Undist:
While Drilling:						
Before Casing Removal:			Sampler:	Other:		
After Casing Removal:			Hammer:			

(N = No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)

Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION	COMMENTS
				C - coarse M - medium F - fine S - Sand, S - Silt, G - Gravel, C - Clay, cl - clayey	a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%
1				0-8" Asphalt	8:30 am
2				8"-38" Stiff br Silty CLAY - moist petro like odor @ 21-41" high PL	Sunny; 35°F light wind
3					0 ppm
4				HeadSpace + 325 ppm	30 ppm
5				0-24" Stiff br Silty CLAY - moist Some imbedded rounded Gravel 0.5" ↓	521 ppm
6				24" grades to more Silt Content	145 ppm
7				Petro like odor	290 ppm
8					
9				0-35" Soft Silty CLAY - high PL - br - moist	30 ppm
10				Slight petro like odor	15 ppm
11					12 ppm
12					10 ppm
13				0-24" Same as previous	5 ppm
14				24-29" SILT - lt brown, moist - wet	3 ppm
15				29"-48" Soft br moist - wet Silty CLAY high PL imbedded coarse Gravel	
16					
17				0-48" Soft br Silty CLAY same as previous	2 ppm
18					
19					
20					
21					
22					
23					



C&S Engineers, Inc.
141 Elm Street
Buffalo, New York 14203
Phone: 716-847-1030
Fax: 716-847-1454
www.cscs.com

BORING LOG

Boring No. **MW-02**
Sheet 1 of:
Project No.:

Project Name:				Surface Elev.:			
Location:				Datum:			
Client:				Start Date: 4/2/19			
Drilling Firm:				Finish Date:			
Groundwater	Depth	Date & Time	Drill Rig:	Inspector:			
While Drilling:			Casing:	Rock Core:	Undist:		
Before Casing Removal:			Sampler:	Other:			
After Casing Removal:			Hammer:				

(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)

Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION	COMMENTS
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, clay - clayey	a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%
					(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				3" Asphalt	1:15 PM
2				No Recovery	
3					
4					
5				3" Saturated Gravel backfill	
6				No Recovery	
7					
8				0-8" Saturated ^{water} Gravel backfill	0 ppm
9				Angular Crushed Stone 0.5" ✓	
10				8"-26" Soft Silty CLAY - br - wet high PL	0 ppm
11					
12					
13				8"-9" Slag	
14				9"-38" Same Soft CLAY - saturated	0 ppm
15					
16					
17				0-14" Slag	
18				14"-32" Same as previous	0 ppm
19					
20					
21				End @ 20'	
22					
23					



C&S Engineers, Inc.
141 Elm Street
Buffalo, New York 14203
Phone: 716-847-1630
Fax: 716-847-1454
www.cscs.com

BORING LOG

Boring No. NW 03

Sheet 1 of:

Project No.:

Surface Elev.:

Datum:

Start Date: 4/3/19

Finish Date:

Inspector: J. BARNES

Project Name: 301 CONSTRUCTION ST. BLP.

Location:

Client:

Drilling Firm: TREC

Groundwater

Depth

Date & Time

Drill Rig:

While Drilling:

8:30

Casing:

Rock Core:

Undist:

Before Casing Removal:

Sampler:

Other:

After Casing Removal:

Hammer:

(N = No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)

Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION	COMMENTS
				G - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey	a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%
					(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				0-3" ASPHALT	
2				3"-48" DENSE SILTY CLAY SOME SMOOTH GRAVEL THROUGHOUT	SUNNY 360F Wind: 15 mph South West 0.4 ppm 0.7 ppm
3					
4					
5				0"-8" SLUG	6.0 ppm
6				8"-48" SILTY LOOSE BROWN CLAY	1.3 ppm
7				48"-48" DENSE SILTY CLAY SOME SMOOTH GRAVEL	
8					
9				0"-24" DENSE SILTY DRY CLAY BROWN	1.4 ppm
10					
11				24"-48" SATURATED WET SOFT SILTY BROWN CLAY	2.0 ppm
12					
13				SATURATED	1.3 ppm
14				0"-18" WET SILTY BROWN CLAY	2.0 ppm
15				18"-48" DENSE SILTY BROWN CLAY	
16					
17				* Little Recovery	0.1 ppm
18				" 4" SOFT WET SILTY CLAY	
19					
20				END BORING AT 20'	
21					
22					
23					



C&S Engineers, Inc.
141 Elm Street
Buffalo, New York 14203
Phone: 716-847-1630
Fax: 716-847-1454
www.cscs.com

BORING LOG

Boring No. **MW04**
Sheet 1 of:
Project No.:

Project Name: **301 CONNATULIN ST BCD.**

Location:

Client:

Drilling Firm: **TREL**

Surface Elev.:

Datum:

Start Date: **4/3/19**

Finish Date:

Inspector: **R. Jackson**

Groundwater

Depth

Date & Time

Drill Rig:

While Drilling:

11:45

Casing:

Rock Core:

Undist:

Before Casing Removal:

Sampler:

Other:

After Casing Removal:

Hammer:

(N -- No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)

Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION	COMMENTS
				c - coarse m - medium f - fine S - Sand, \$ - Silt, G - Gravel, C - Clay, cly - clayey	a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10% (e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				- LITTLE RECOVERY	
2				0" - 3" ASPHALT	1.4 ppm
3				3" SOME SMOOTH GRAVEL MIXED IN SILTY CLAY.	
4					
5				0" - 5" SLURRY ASPHALT	0.8 ppm
6				5" - 48" DENSE SILTY CLAY / SOME SMOOTH GRAVEL THROUGHOUT.	1.0 ppm
7					
8					
9				0" - 10" DARK BROWN CLAY / ANGLAR GRAVEL THROUGHOUT	17.3 ppm
10				10" - 48" DENSE SILTY BROWN CLAY / ANGLAR GRAVEL THROUGHOUT	5.6 ppm
11					
12					
13				0" - 3" SLURRY	1.0 ppm
14				3" - 15" LARGE GRAVEL EMBEDDED IN SILTY CLAY	
15				15" - 48" DENSE SILTY CLAY / BROWN	1.5 ppm
16					
17					
18				0" - 48" SILTY BROWN CLAY	2.4 ppm
19				SAME AS PREVIOUS	
20					
21				END DRILLING AT 20'	
22					
23					



C&S Engineers, Inc.
141 Elm Street
Buffalo, New York 14203
Phone: 716-847-1630
Fax: 716-847-1454
www.cscs.com

BORING LOG

Boring No. **MW05**
Sheet 1 of:
Project No.:
Surface Elev.:
Datum:
Start Date: **4/3/19**
Finish Date:
Inspector: **P. BACKERT**

Project Name: **301 CONNECTICUT ST BLP**

Location:

Client:

Drilling Firm: **TRELL**

Groundwater

Depth

Date & Time

Drill Rig:

While Drilling:

12:30

Casing:

Rock Core:

Undist:

Before Casing Removal:

Sampler:

Other:

After Casing Removal:

Hammer:

(N = No. of blows to drive sampler 12" w/140 lb. hammer falling 30" ASTM D-1586, Standard Penetration Test)

Depth (ft)	Sample No.	Symbol	Blows on Sampler per 6"	MATERIAL DESCRIPTION	COMMENTS
				c - coarse m - medium f - fine	a - and - 35-50% s - some - 20-35% l - little - 10-20% t - trace - 0-10%
				S - Sand, S - Silt, G - Gravel, C - Clay, cly - clayey	(e.g., N-value, recovery, relative moisture, core run, RQD, % recovered)
1				0" - 3" ASPHALT	
2				3" - 48" FINE SMOOTH GRAVEL THROUGH SILTY CLAY. / BROWN	1.5 ppm
3					
4					
5				0" - 3" SLURRY	1.7 ppm
6					
7				3" - 48" SAME AS PREVIOUS / SILTY DENSE BROWN CLAY / SOME SMALL FINE GRAVEL THROUGHOUT	2.1 ppm
8					
9				0" - 5" SLURRY ASPHALT	2.3 ppm
10					
11				5" - 48" SAME AS PREVIOUS / SILTY DENSE BROWN CLAY / SOME FINE GRAVEL THROUGHOUT	3.1 ppm
12					
13				0" - 15" DENSE SILTY BROWN CLAY WITH LARGE GRAVEL THROUGHOUT	1.9 ppm
14					
15				15" - 48" MOIST SILTY BROWN CLAY.	2.2 ppm
16					
17					
18				0" - 48" MOIST SILTY CLAY / BROWN / SOME SMALL SMOOTH GRAVEL	0.7 ppm
19					
20					
21				END BORING 20'	
22					
23					



C&S Engineers, Inc.
141 Elm Street Suite 100
Buffalo, New York 14203
Phone: 716-847-1630
www.cscos.com

Well Sampling Field Data Sheet

Well Casing Unit Volume

(gal/l.f.)

1 1/2" = 0.08 2" = 0.17 3" = 0.38
4" = 0.66 6" = 1.5 8" = 2.6

Client Name: _____

Site Name: 301 Cornwell Rd

Project No.: _____

Field Staff: JESSIE + RICH

WELL DATA

Date		5/21/19	5/21/19	5/21/19	5/21/19	5/21/19			
Well Number		MW-1	MW-2	MW-3	MW-4	MW-5			
Diameter (inches)		2"	2"	2"	2"	2"			
Total Sounded Depth (feet)		20.4	19.3	20.2	20.3	20.2			
Static Water Level (feet)		5.6	5.4	5.8	7.6	5.0			
H ₂ O Column (feet)									
Pump Intake (feet)									
Well Volume (gallons)									
Amount to Evacuate (gallons)									
Amount Evacuated (gallons)									

FIELD READINGS

Date	Stabilization Criteria	5/21/19	5/21/19	5/21/19	5/21/19	5/21/19			
Time		9:45am	10:45am	11:30	12:15	12:45			
pH (Std. Units)	+/-0.1	6.7	6.9	7.5	7.02	6.73			
Conductivity (mS/cm)	3%	35.7	7.3	2.7	2.4	8.78			
Turbidity (NTU)	10%								
D.O. (mg/L)	10%	1.25	1.69	2.90	3.88	3.38			
Temperature (°C) (°F)	3%	10.4	10.7	11.6	10.85	12.40			
ORP ³ (mV)	+/-10 mv	-108	-178	-35	19	35			
Appearance		Clear	Semi-Turbid	Clear	Clear	Clear			
Free Product (Yes/No)		No/Yes	No/Yes	No/Yes	Yes	Yes			
Odor		None	None	None	None	None			
Comments	MW-4 has build-up of mud in well casing								

C = Clear T = Turbid ST = Semi Turbid VT = Very Turbid