



Remedial Investigation Work Plan

**Timber Shore
78 Bridge Street
North Tonawanda, New York**

Project Number: HK2550

Prepared for:
Pennrose, LLC
1301 Avenue of the Americas
7th Floor
New York, NY 10019

Prepared by:
HK Engineering & Geology, D.P.C.
1600 Route 22 East
Union, NJ 07083

March 2022

Introduction

This Phase II Investigation Work Plan has been developed for Timber Shore Site located at 78 Bridge Street, North Tonawanda, New York. The Site is currently in the application process for enrollment into the NYSDEC Brownfield Cleanup Program (BCP).

Site Location, Current Use, and Proposed Development Plan

The Site is located at 78 Bridge Street, North Tonawanda, Niagara County, New York and is identified as Block 1 and Lot 9 on the North Tonawanda Tax Map. The Site is approximately 3.18-acres and is bounded by Taylor Drive to the north, Michigan Street to the west, Bridge Street to the south, and a (proposed) Public Benefit Area to the east. Currently the Site is approximately 571 feet above mean sea level and vacant (grass/wooded) improved with two structures, a fire tower and smokehouse used for fire-rescue training purposes. Figure 1 shows the Site location.

The proposed project, Timber Shore, is a planned new building development featuring seventy (70) residences including 26 one-bedrooms, 33 two-bedrooms and 11 three-bedrooms. The residences are designed for general occupancy and will be marketed to tenants at a range of income levels, from extremely low income to moderate-income (nineteen (19) units (27%) restricted to 30% AMI, thirty-seven (37) units (53%) restricted to 60% AMI and fourteen (14) units (20%) restricted to 80% AMI). Additionally, Timber Shore will also include 15% set aside for special needs units.

Timber Shore will include a community room, fitness center, bicycle parking, laundry facilities, bulk storage, lounge, and a waterfront-facing terrace on the ground floor. The total building area will be 83,720 SF (inclusive of retail). The ground floor of Timber Shore will contain one, approximately 1,250 SF, commercial space that is poised to include neighborhood-scale commercial space. The remainder of the property will consist of on-site parking and landscaping. The building will be designed to Enterprise Green Communities Plus standard.

The property is zoned Waterfront District (WD). The WD is defined as "The purpose of the Waterfront District (WD) is to capitalize on the City of North Tonawanda's waterfront by encouraging a mix of residential, commercial, and public uses that promote access to the Niagara and Little Rivers".

Phase I ESA Summary

A Phase I Environmental Site Assessment (ESA) was completed by HK Engineering & Geology, D.P.C. in April 2021. Recognized environmental concerns (RECs) that were identified during the ESA included:

- *The historic use of the Property for industrial warehousing and distribution of lumber and shingles with multiple rail spurs, a boat slip filled in the 1960's with fill of unknown disposition, and subsequently used for training grounds for fire-rescue including visual evidence of the use of combustibles (petroleum products) is considered a REC.*
- *50 Bridge Street located to the adjacent southwest of the Property and topographically cross to upgradient of the Property is listed on multiple databases as follows: SEMS-Archive, NY Spills, HSWDS, RCRA VSQG, ICIS, US Airs, FINDS, ECHO, Manifest. The listings indicated the site was used for hazardous waste disposal including for semi-volatile organic compounds. The listings also detail hazardous waste generated and shipped offsite. The SEMS-Archive listing is for characterization work done in the 1980's resulting in a determination not to include the site on the National Priority List (NPL). The listings including the use of the site for hazardous waste disposal of semi-volatile organic compounds are indicative of potential for impact to the Property and considered a REC.*

The Phase I ESA is included in Attachment A.

Due Diligence Phase II Investigation

On August 9th, 2021 HK conducted a due diligence Phase II following the findings of the Phase I ESA.

Nine borings were advanced onsite with direct push machinery in representative locations and areas of concern to characterize the surface and subsurface soil. Boring depths were terminated between 5-15 feet below ground surface (bgs). Groundwater depths ranged from 4-5.5 feet bgs at several boring locations. To facilitate groundwater sample collection, temporary monitoring well points (TWPs) were installed in three locations. Soil and groundwater samples were collected from each boring for laboratory analysis of the Target Analyte List/Target Compound List (TAL/TCL) which includes: volatile organic compounds (VOCs), semi-volatile organic compounds (SVOCs), TAL metals, pesticides and polychlorinated biphenyls (PCBs). Dissolved metals were analyzed in groundwater samples. Two soil samples nearest the fire tower and all groundwater samples were collected for Per- and polyfluoroalkyl substances (PFAS) analysis.

Three soil vapor samples were collected in the open field above the water table. To collect a sample with minimal moisture interference probe installation depths were two feet above the water table for a duration of one hour. Samples were collected in laboratory cleaned air canisters for a one-hour duration. Air samples were transported to a New York certified laboratory under chain of custody protocol and analyzed for VOCs by EPA method TO-15.

SUMMARY OF RESULTS

Soil laboratory analytical results were compared to the NYSDEC Unrestricted Use Soil Cleanup Objectives (UUSCOs) and Restricted-Residential Use Soil Cleanup Objectives (RRUSCOs). (Note: NYS does not have current standards for PFAS compounds).

- Several SVOC compounds were detected in exceedance of the UUSCO and RRUSCO in numerous samples.
- Nickel was detected in exceedance of the RRUSCO in one sample, lead was also detected above the UUSCO but below the RRUSCO in several samples.
- Two pesticide compounds were detected above the UUSCO but below the RRUSCO in several samples.
- Various PFAS compounds were detected in both soil samples collected.
- All other remaining compounds were either not detected or detected below the applicable UUSCOs.

Groundwater laboratory results were compared to the NYSDEC Ambient Water Quality Standards (AWQS). (Note: PFAS compounds were compared to the NYSDOH Drinking Water MCL).

- Benzo(a)pyrene was detected in exceedance of the AWQS in one sample, TWP3.
- Several metals were detected above the AWQS in all total metal unfiltered samples. Filtered groundwater samples showed dissolved iron, manganese and sodium in exceedance of the AWQS.

- Several PFAS compounds were detected in all three groundwater samples. All three samples showed exceedances of the NYS Drinking Water MCL for Perfluorooctanoic acid and Perfluorooctanesulfonic acid.
- All other remaining compounds were either not detected or detected below the applicable AWQS.

Soil vapor results are included in Table 3 with the full laboratory data package included as Attachment B. (Note: NYS does not have current standards for soil vapor compounds).

- Soil vapor results showed several detections of VOC compounds.

The due-diligence Phase II Subsurface Investigation is included in Attachment B.

Phase II Investigation Work Scope

Geophysical Survey

A geophysical survey will be completed in accessible exterior areas of the site. The geophysical survey will use ground penetrating radar and magnetometer equipment to identify buried underground storage tanks, drums and utility lines for safe drilling. A utility mark out will be called in additionally to mark out known utility lines.

Soil, Groundwater and Soil Vapor Summary

An investigation of soil, soil vapor and groundwater is being performed to additionally characterize the site for potential environmental impacts from historic on-site/off-site uses, operations, etc. The proposed sampling event will address both RECs and historic fill, as well as to provide general horizontal/vertical characterization across the site for development purposes. The sampling procedures of this investigation will be performed in accordance with the NYSDEC Technical Guidance for Site Investigation and Remediation DER-10 as well as NYSDEC Sampling, Analysis, and Assessment of Per- and Polyfluoroalkyl Substances (PFAS), October 2020.

Ten (10) soil test borings will be completed at the site. Please see attached site plan (Figure 2) depicting sample point locations, where soil, groundwater, and soil vapor samples will be collected. Up to twenty (20) discrete soil samples will be collected from the ten test borings. Five (5) permanent groundwater monitoring wells will be installed. A total of three (3) soil vapor samples will be collected. A previous due-diligence Phase II Subsurface Investigation conducted by HK found depth of groundwater between 4-5 feet below ground surface (bgs). General groundwater flow direction is expected to be towards the east. Each sample point location at the site will be accurately measured to fixed benchmarks (i.e., select properly lines, adjacent structures, etc.) or by a precision GPS that is capable of coordinating a fixed point with within +/- 1 foot.

Soil Sampling

A geologist/QEP will screen the soil samples during borehole advancement for organic vapors with a photo-ionization detector (PID) and evaluate for visual and olfactory impacts prior to collecting environmental samples. All field work will be recorded in a field log. A direct push drilling rig will be used for the soil and soil vapor investigation and hollow stem augur drilling method will used for monitoring well installation. At a minimum, up to two soil samples will be collected from each test borings (for a total of 16 soil samples) for laboratory analysis. A surface soil sample (from the 0-2 feet bgs interval) and subsurface soil sample at the soil-groundwater interface. Discrete (grab) samples will be taken from the aforementioned sampling intervals. The subsurface soil samples may also serve as in-situ post-excavation soil samples for the remedial plan. A third soil sample may be collected from each or several test boring(s) if 1) elevated PID readings and/or visual and

olfactory observations are noted during borehole advancement and/or 2) field observations identify an upper fill layer underlain by native material the additional soil sample from the upper zone of the native layer will help delineate the vertical migration of impacts (if any), as well as determine a more detailed remedy and potentially provide a cost savings for disposal options.

Monitoring Well Installation and Groundwater Sampling

Five (5) two inch-diameter permanent groundwater monitoring wells will be installed. Properly sized screen and silica sand pack will be used for noted site conditions. Representative groundwater samples will be collected from each well utilizing low flow techniques with a low flow capable pump and dedicated tubing two weeks following well installation. Sampling will be conducted in accordance with NYSDEC Draft DER-10 Technical Guidance for Site Investigation and Remediation, dated May 2010, and Sampling Guidelines and Protocols, dated March 1991. Groundwater wells will be gauged with a water level meter to record a depth to groundwater reading (1/100 foot), and if necessary, an interface meter to determine the thickness of LNAPL or DNAPL. The well casings will be surveyed by a trained QEP and/or NYS licensed surveyor to facilitate preparation of a groundwater contour map and determine the direction of groundwater flow. Based on previously obtained groundwater depth information, monitoring wells are anticipated to be installed at approximately 10 feet bgs.

Soil Vapor Sampling

Soil vapor samples will be collected in accordance with the Final Guidance for Evaluating Soil Vapor Intrusion in the State of New York (NYSDOH October 2006). Conditions in the field may require adjustment of sampling locations. Groundwater is expected to be encountered at a depth of 4-5 feet bgs. Three (3) soil vapor samples will be collected. Soil vapor implants will be set at a depth of approximately 1-2 feet above the groundwater interface or at the presumed excavation depth of the building footprint, whichever is encountered first. The vapor implants will be installed with using direct push drilling equipment, dedicated tubing, and hydrated bentonite to seal the sample location from ambient conditions. Sampling will occur for the duration of 1-2 hours.

Samples will be collected in appropriately sized laboratory air canisters that have been certified clean by the laboratory and samples will be analyzed by using USEPA Method TO-15. Flow rate for both purging and sampling will not exceed 0.2 L/min. A sample log sheet will be maintained summarizing sample identification, date and time of sample collection, sampling depth, identity of samplers, sampling methods and devices, soil vapor purge volumes, volume of the soil vapor extracted, vacuum of canisters before and after the samples are collected, and chain of custody protocols.

As part of the vapor intrusion evaluation, a tracer gas will be used in accordance with NYSDOH protocols to serve as a quality assurance/quality control (QA/QC) device to verify the integrity of the soil vapor probe seal. A container (box, plastic pail, etc.) will serve to keep the tracer gas in contact with the probe during testing. A portable monitoring device will be used to analyze a sample of soil vapor for the tracer gas prior to sampling. If the tracer sample results show a significant presence of the tracer, the probe seals will be adjusted to prevent infiltration. At the conclusion of the sampling round, tracer monitoring will be performed a second time to confirm the integrity of the probe seals.

Sample Analysis

Soil, groundwater, and soil vapor samples will be submitted to a NYSDOH Environmental Laboratory Accreditation Program (ELAP)-certified laboratory for Full analysis:

- Volatile Organic Compounds by EPA Method 8260;
- Semi-volatile organic compounds by EPA Method 8270;
- Pesticides/PCBs by EPA Method 8081/8082; and
- Target Analyte List metals by EPA Method 6010 and 7471 for (Total and dissolved metals for GW);

- PFAS (NYSDEC Analyte List) by LC-MS/MS via EPA 537.1
- 1,4-dioxane via EPA Method 8270 SIM
- Soil vapor samples will be analyzed for VOCs by using USEPA Method TO-15.
-

Sampling will be performed in accordance with *NYSDEC Sampling, Analysis, and Assessment of Per- and Polyfluoroalkyl Substances (PFAS)*, dated October 2020.

The analytical methods above should include all compounds included in NYSDEC Part 375-6.8 and CP-51 for soil, NYSDEC Part 703 Groundwater Quality Standards (class GA) or Division of Water Technical and Operational Guidance Series (TOGS) 1.1.1 Ambient Water Quality Standards (AWQS) for groundwater, and NYSDOH October 2006 Final Guidance for Evaluating Soil Vapor Intrusion Matrices for soil vapor (if applicable).

If either LNAPL and/or DNAPL are detected, appropriate samples will be collected for characterization and “finger print analysis” and required regulatory reporting (i.e. NYSDEC spills hotline) will be performed.

Quality Assurance/Quality Control Procedures

QA/QC procedures will be used to provide performance information with regard to accuracy, precision, sensitivity, representation, completeness, and comparability associated with the sampling and analysis for this investigation. Field QA/QC procedures will be used (1) to document that samples are representative of actual conditions at the Site and (2) identify possible cross-contamination from field activities or sample transit. Laboratory QA/QC procedures and analyses will be used to demonstrate whether analytical results have been biased either by interfering compounds in the sample matrix, or by laboratory techniques that may have introduced systematic or random errors to the analytical process. QA/QC samples (field and trip blanks, duplicates, etc.) will be collected and analyzed at an ELAP-certified laboratory.

Investigation Derived Waste

Cuttings may be disposed at the site within the borehole that generated them to within 24 inches of the surface unless:

- Free product or grossly contaminated soil, are present in the cuttings;
- The borehole has penetrated an aquitard, aquiclude or other confining layer; or extends significantly into bedrock;
- Backfilling the borehole with cuttings will create a significant path for vertical movement of contaminants. Soil additives (bentonite) may be added to the cuttings to reduce permeability;
- The soil cannot fit into the borehole.

Those soil cuttings needing to be managed on-site will be containerized in properly labeled DOT approved 55-gallon drums for future off-site disposal at a permitted facility. All boreholes which require drill cuttings disposal would ultimately be filled with bentonite chips (hydrated) and asphalt/concrete capping. Disposable sampling equipment including, spoons, gloves, bags, paper towels, etc. that came in contact with environmental media will be double bagged and disposed as municipal trash in a facility trash dumpster as non-hazardous trash.

Reporting

A Phase II Investigation Report (template version) will be prepared following completion of the field activities and receipt of the laboratory data. The report will provide detailed summaries of the investigative findings. Soil analytical results will be compared to the NYSDEC Part 375-6.8(a) Unrestricted Used Soil Cleanup Objectives, appropriate Part 375-6.8(b) Restricted Soil Cleanup Objectives and supplemental cleanup objectives in NYSDEC CP-51 Soil Cleanup Guidance. Groundwater analytical results will be compared to NYSDEC Part 703 Groundwater Quality Standards (GQS) (class GA) or Division of Water Technical and Operational Guidance Series (TOGS) 1.1.1

Ambient Water Quality Standards (AWQS). Soil vapor analytical results will be compared to NYSDOH October 2006 Final Guidance for Evaluating Soil Vapor Intrusion Matrices, updated May 2017.

The report will include an updated sampling plan, spider diagrams, analytical data tables for all reported constituent compounds (including non-detectable concentrations) and remedial recommendations, as warranted. In the Remedial Investigation Report (RIR), all applicable documentation (site map, conceptual building plans, soil boring and groundwater monitoring well construction logs, and sampling intervals) will be prepared from a single grade reference point as well as in terms of elevation.

The report will also include all sampling logs and photos taken during the investigation.

Investigation HASP

An OSHA compliant Health and Safety Plan that meets all OSHA HAZWOPER requirements will be implemented during the site work to protect worker safety. The Site Safety Coordinator will ensure full compliance of the HASP in accordance with applicable health and safety laws and regulations. All field personnel involved in investigation activities will participate in training required under OSHA HAZWOPER 29 CFR 1910.120, including 40-hour hazardous waste operator training and annual 8-hour refresher training. Emergency telephone numbers will be posted at the site location before any work begins. A safety meeting will be conducted before each shift begins. Topics to be discussed include task hazards and protective measures (physical, chemical, environmental); emergency procedures; PPE levels and other relevant safety topics including a highlighted route map to the nearest hospital/emergency room. Meetings will be documented in a log book or specific form. Potential on-site chemicals of concern include VOCs, SVOCs, Pesticides/PCBs, and Metals (specifically arsenic, lead, and mercury at a minimum). Information fact sheets and/or summary tables for each contaminant group are included in the HASP. A copy of this HASP will be on-site during each sampling event and included as Attachment C.

Community Air Monitoring

The planned soil, groundwater, and soil vapor RI work will be completed outdoors. Minimal dust is anticipated during all work activities; however, community air monitoring will be utilized during invasive site activities to protect the downwind community. The onsite geologist/QEP will continually monitor the work area using a PID (measuring air to 1 ppm). Visual observation for dust in the work area will also be monitored. If visible dust is observed or the PID indicates VOCs in exceedance of 5 ppm for an extended time period, work will be stopped and dust mitigation measures (i.e. wetting the area with water, dust barrier, etc) will be instituted. If dust mitigation measures are required, additional monitoring will be performed in accordance with the NYSDOH Generic Community Air Monitoring Plan (CAMP) when work resumes. A copy of the CAMP is included in Appendix D.

Qualitative Human Health Risk Assessment

A qualitative human health risk assessment will be conducted to determine if the presence and concentrations of chemicals in the soil at the Site pose potential human health concerns. The assessment will encompass both on-Site and off-Site risks with the results of the exposure analysis used as one of the criteria to determine the most appropriate future actions at the Site. These may range from no further action, to additional data collection, to quantitative health risk assessment and the establishment of risk-based action levels. The assessment will begin with the construction of a conceptual Site model, a graphic illustration that outlines chemical source areas, possible chemical release mechanisms, environmental media that currently show or may show in the future the presence of chemicals, possible exposure pathways, possible points of exposure for human receptors, possible exposure routes, and possible human receptors. The conceptual model will be based on current Site conditions and surrounding land use as well as the planned future Site and surrounding land uses. For environmental media that may be of concern, qualitative evaluations will be made for the four

components that typically comprise a health risk assessment: data evaluation; exposure assessment; toxicity assessment; and risk characterization/uncertainty analysis. In the data evaluation, chemical concentrations in the various media will be compared to appropriate NYSDEC risk-based standards and criteria (e.g., NYSDEC Soil Cleanup Objective and Cleanup Levels). Chemicals detected in concentrations greater than these standards and criteria will be identified as chemicals of potential concern. In the exposure assessment, an evaluation will be made of the likelihood and magnitude of exposure to the chemicals of potential concern in environmental media of concern. This will involve outlining possible exposure routes and plausible exposure times, frequencies, and durations. In the toxicity assessment, the toxicity of the chemicals of concern will be outlined. This will include identifying known or suspected carcinogens and/or the target organ/system of concern for noncarcinogenic effects. In the risk characterization, information from the three components will be integrated, to estimate the likelihood and magnitude of possible health risks. Fact sheets documenting the goals and progress of the project will be prepared at key milestones of the project and distributed to those on the project mailing list.

Schedule

Task	Timeline (after Workplan approval)
Approval of RIWP by DEC	0
Soil, SV & IA Sampling / MW Installation	6-8 weeks
MW Groundwater Sampling	8-10 weeks
Receipt of Lab Data	10-12 weeks
Remedial Investigation Report	12-16 weeks

9.0 Certification

I, Chris Hirschmann, certify that I am currently a Qualified Environmental Professional (QEP) as defined in 6 NYCRR Part 375 and that this Remedial Investigation Work Plan was prepared in accordance with all applicable statutes and regulations and in substantial conformance with the DER Technical Guidance for Site Investigation and Remediation (DER-10).



Chris Hirschmann, QEP

FIGURES




Figure 1: Site Location

78 Bridge Street
North Tonawanda, New York

N



Scale: Not to scale



Legend

- Proposed Soil Boring
- Proposed Soil Vapor Point
- Proposed Groundwater Monitoring Well
- August 2021 Soil Sample
- August 2021 Soil Vapor Sample
- August 2021 Groundwater Sample
- Approximate Property Boundary

Notes:
Proposed site layout diagram prepared by SWBR (C&S Companies): "Site Plan" drawing no. C-101, Dated 8/26/2021.
Aerial imagery basemap obtained from GoogleEarth Pro, dated 9/22/2018.
Figure created by JLD Mapping Services LLC.

HK
ENGINEERING
& GEOLOGY, D.P.C.
A Member of the Hillmann Family of Companies
1600 Route 22 East, Suite #107
Union, NJ 07083

3/21/2022

Proposed Sample Location Map			
78 Bridge Street Parcel IDs: 184.08-1-8 & 184.08-1-9 North Tonawanda, Niagara County, NY			
SIZE 11x17	DWG NO. Figure 2		REV 3
SCALE: 1 in = 50 ft	PROJECT No.: HK-2550-1	SHEET	1 OF 1

Attachment A

Phase I Environmental Site Assessment

PHASE I ENVIRONMENTAL SITE ASSESSMENT



Timber Shores
78 Bridge Street
Tonawanda, New York 14120

Prepared For:

Pennrose, LLC
1301 Avenue of the Americas, 7th Floor
New York, New York 10019

April 12, 2021

HK Project Number Z34708

April 12, 2021

Mr. Dylan Salmons
Pennrose, LLC
1301 Avenue of the Americas, 7th Floor
New York, New York 10019

RE: Phase I Environmental Site Assessment
78 Bridge Street
Tonawanda, New York 14120
HK Project No: Z34708

Dear Mr. Salmons:

HK Engineering & Geology, D.P.C. is pleased to provide the results of our Phase I Environmental Site Assessment of the above referenced property. This assessment was performed in general accordance with the scope and limitations of ASTM Practice E 1527-13, which is the latest version of the E1527 standard published by the ASTM.

We appreciate the opportunity to provide environmental due diligence services. If you have any questions concerning this report, or if we can assist you in any other matter, please contact our office at 908-688-7800.

Sincerely,

HK Engineering & Geology, D.P.C.



Chris Hirschmann
Environmental Services Director



Etan Hindin
Senior Project Manager

TABLE OF CONTENTS

1.0	FINDINGS, OPINIONS, AND CONCLUSIONS.....	1
1.1	Summary of Project Details	1
1.2	Findings Summary Table	2
1.3	Findings and Conclusions	2
1.4	Business Environmental Risks / Non-ASTM Scope	4
2.0	INTRODUCTION.....	5
2.1	Purpose and Scope	5
2.2	Property Location/Legal Description	7
2.3	Data Gaps	7
2.4	User Reliance	8
2.5	Significant Assumptions.....	8
2.6	General Limitations and Exceptions	8
3.0	USER PROVIDED INFORMATION	11
3.1	Prior Environmental Reports/Documentation	11
3.2	User Questionnaire.....	11
3.3	Reason for Performing Phase I ESA	13
4.0	RECORDS REVIEW	14
4.1	Physical Setting Sources	14
4.2	Historical Use – Property and Adjoining Properties	14
4.3	Standard Environmental Record Sources	19
4.4	Additional Environmental Record Sources	23
5.0	SITE RECONNAISSANCE	24
5.1	Methodology and Limiting Conditions	24
5.2	General Site Setting.....	24
5.3	Interior & Exterior Observations.....	25
6.0	INTERVIEWS.....	27
6.1	Interviews with Past and Present Owners and Occupants	28
6.2	Interviews with State and/or Local Government Officials	28
7.0	BUSINESS ENVIRONMENTAL RISKS	29
7.1	Asbestos-Containing Material (ACM)	29
7.2	Lead-Based Paint.....	29
7.3	Radon	29
7.4	Mold/Microbial Damage	29
7.5	NWI Mapped Wetlands.....	29
7.6	Lead in Drinking Water.....	30
8.0	REFERENCES	31
9.0	APPENDICES	32
Appendix A	Site Diagram/Vicinity Map	
Appendix B	Site Photographs	
Appendix C	Questionnaires / User Provided Information	
Appendix D	Historical Records Documentation	
Appendix E	Regulatory Records Documentation	
Appendix F	Other Documents / Lab Results	
Appendix G	Project Personnel Qualifications	

List of Abbreviations/Acronyms

HK may use the following abbreviations and acronyms for common terminology described in our report. Not all abbreviations or acronyms may be applicable to this report:

ACM	– Asbestos Containing Material
AOC	– Area of Concern
AST	– Aboveground Storage Tank
ASTM	– American Society for Testing Materials
BER	– Business Environmental Risk
CEA	– Classification Exception Area
CERCLA	– Comprehensive Environmental Response Compensation and Liability Act
CERCLIS	– Comprehensive Environmental Response Compensation and Liability Information System
CESQG	– Conditionally Exempt Small Quantity Generator
COC	– Chemicals of Concern
CORRACTS	– Corrective Action Sites
CREC	– Controlled Recognized Environmental Condition
DNPL	– Delisted National Priority List
DTSC	– Department of Toxic Substances Control
ENG	– Engineering
ERNS	– Emergency Response Notification System
FDEP	– Florida Department of Environmental Protection
FDNY	– Fire Department, City of New York
FDOT	– Florida Department of Transportation
FOI/FOIA/FOIL	– Freedom of Information / Freedom of Information Act / Freedom of Information Letter
HVAC	– Heating Ventilation & Air Conditioning
HREC	– Historic Recognized Environmental Condition
IAQ	– Indoor Air Quality
ISRA	– Industrial Site Recovery Act
LBP	– Lead-Based Paint
LQG	– Large Quantity Generator
LTANK	– Leaking Storage Tank
LUST	– Leaking Underground Storage Tank
MassDEP	– Massachusetts Department of Environmental Protection
SDS/MSDS	– Safety Data Sheet / Material Safety Data Sheet
NA	– Not Applicable
NCDOH	– Nassau County Department of Health
NFA	– No Further Action
NFRAP	– No Further Remedial Actions Planned
NJDEP	– New Jersey Department of Environmental Protection
NPDES	– National Pollutant Discharge Elimination System
NPL	– National Priority List
NYCDEP	– New York City Department of Environmental Protection
NYCDOB	– New York City Department of Buildings
NYCOER	– New York City Office of Environmental Remediation
NYSDEC	– New York State Department of Environmental Conservation
OPRA	– Open Public Records Act
PADEP	– Pennsylvania Department of Environmental Protection
PAH	– Polycyclic Aromatic Hydrocarbon
PCE	– Perchloroethylene
RAO	– Response Action Outcome
RCRA	– Resource Conservation and Recovery Act
RCRIS	– Resource Conservation and Recovery Information System
REC	– Recognized Environmental Condition
RWQCB	– Regional Water Quality Control Board
SCAQMD	– South Coast Air Quality Management District
SCDHS	– Suffolk County Department of Health Services
SDG	– Significant Data Gap
SEMS	– Superfund Enterprise Management System
SRP	– Site Remediation Program
SQG	– Small Quantity Generator
SVOC	– Semi-Volatile Organic Compound
TCE	– Trichloroethylene
TSDF	– Treatment Storage and/or Disposal Facility
USEPA	– United States Environmental Protection Agency
UST	– Underground Storage Tank
VEC	– Vapor Encroachment Condition
VOC	– Volatile Organic Compound

1.0 FINDINGS, OPINIONS, AND CONCLUSIONS

HK Engineering & Geology D.P.C. (HK) performed a Phase I Environmental Site Assessment (ESA) of 78 Bridge Street, Tonawanda, New York (the Property). The assessment has been conducted in accordance with our contracted scope of work and the ASTM Standard Practice E 1527-13 for Phase I Environmental Site Assessments and All Appropriate Inquiries (AAI) Final Rule 40 CFR Part 312. This section contains a summary of findings, opinions and conclusions made by this assessment. However, this section, alone, does not constitute the complete assessment. The report must be read in its entirety.

1.1 Summary of Project Details

Primary Street Address:	78 Bridge Street				
City:	Tonawanda	County:	Niagara	State:	New York
Tax ID/Parcel Number:	Block 1, Lot 9 / Tax ID: 184.08-1-9				
Property Owner:	City of North Tonawanda				
Zoning Designation:	WD (water-dependent)				
Approx. Property Area:	3.10-acres				
Buildings/# of Floors	Two (2) structures, fire tower and smokehouse used for fire-rescue training purposes				
Approx. Building Area:	~2,788-ft ²				
Approx. Year Built:	Early 1970's				
Commercial Occupants:	None				
Current Use:	Vacant				
Prior Uses:	Rail spurs, lumber yard and warehousing/distribution, fire-suppression/rescue training				
Inspected By:	Mr. Brendan Yadav				
Site Contact/Company:	Mr. Joseph D. Sikura, Fire Chief				
Site Escort/Company:	Unescorted				
Inspection Date:	March 24, 2021				
Weather Conditions:	Sunny, 70 degrees F				

1.2 Findings Summary Table

Assessment Subject	No REC	REC	CREC	HREC	Rpt. Ref.
Property Regulatory Records Review:		X			4.3
Property Historical Records Review:		X			4.2
Bulk Petroleum Storage:	X				5.3
On-Site Operations:	X				5.3
On-Site Haz-Mat Storage/Use/Spills:	X				5.3
Transformers/Hydraulic Systems:	X				5.3
Waste Discharges:	X				5.3
Interviews:	X				6.0
Adjoining & Nearby Properties:	X				4.3 5.2
Prior Env. Reports/User Provided Info:	X				3.0
Data Gaps:	X				2.3

1.3 Findings, Opinions and Conclusions

1.3.1 Recognized Environmental Conditions

HK has performed a Phase I Environmental Site Assessment in accordance with the scope and limitations of ASTM Practice E 1527-13 of the Property as described in Section 2 of this report. Any additions to, exceptions to, or deletions from this practice are also described in Section 2 of this report. This assessment has revealed no evidence of *recognized environmental conditions* in connection with the Property, except for the following:

RECOGNIZED ENVIRONMENTAL CONDITIONS	
REC # 1	The historic use of the Property for industrial warehousing and distribution of lumber and shingles with multiple rail spurs, a boat slip filled in the 1960's with fill of unknown disposition, and subsequently used for training grounds for fire-rescue including visual evidence of the use of combustibles (petroleum products) is considered a REC.
REC #2	50 Bridge Street located to the adjacent southwest of the Property and topographically cross to upgradient of the Property is listed on multiple databases as follows: SEMS-Archive, NY Spills, HSWDS, RCRA VSQG, ICIS, US Airs, FINDS, ECHO, Manifest. The listings indicated the site was used for hazardous waste disposal including for semi-volatile organic compounds. The listings also detail hazardous waste generated and shipped offsite. The SEMS-Archive listing is for characterization work done in the 1980's resulting in a determination not to include the site on the National Priority List (NPL). The listings including the use of the site for hazardous waste disposal of semi-volatile organic compounds are indicative of potential for impact to the Property and considered a REC.
HISTORICAL RECOGNIZED ENVIRONMENTAL CONDITIONS	
	No HRECs were identified
CONTROLLED RECOGNIZED ENVIRONMENTAL CONDITIONS	

	No CRECs were identified
SIGNIFICANT DATA GAPS	
	No SDGs were identified

1.3.2 REC Response Action Recommendations

The following table presents recommended response actions to the identified RECs for further investigation and/or corrective action:

REC RESPONSE ACTION SUMMARY TABLE	
REC	Response Action
RECs 1, 2	HK recommends a Phase II to determine the presence or absence of impact from aforementioned historic uses, to discern the disposition of the fill material deposited in the former boat slip area (in the 1960's) within the norther portion of the Property and to identify the impact, if any, from the adjacent SEMS-Archive/Hazardous Waste Disposal site (50 Bridge Street).


1.3.3 Notable Environmental Conditions / De Minimis Conditions

The following environmental conditions were identified, but are not considered to be a REC in connection with the Property:

NOTABLE ENVIRONMENTAL CONDITIONS / DE MINIMIS CONDITIONS	
	(None)

1.3.4 Environmental Professional Statement

I declare that, to the best of my professional knowledge and belief, I meet the definition of *Environmental Professional* as defined in §312.10 of 40 CFR 312. I have the specific qualifications based on education, training and experience to assess a *property* of the nature, history and setting of the subject *property*. I have developed and performed all appropriate inquiries in conformance with the standards and practices set forth in 40 CFR Part 312.



Etan Hindin
Environmental Professional

1.4 Business Environmental Risks / Non-ASTM Scope

HK has performed a limited review of the following potential Business Environmental Risks (BER), also known as “Non-ASTM Scope concerns”, in accordance with the contracted scope of work scope for this assessment. The following is a summary of findings for applicable BERs. For a more detailed discussion of the findings and contracted scope of work, please see the referenced report section.

BUSINESS ENVIRONMENTAL RISKS / NON-ASTM SCOPE			
Subject	Findings	Not Appl.	Rpt. Ref.
Asbestos	Limited asbestos may be present within the fire tower and smokehouse building materials. The structures are largely stripped to structural components.		7.1
Lead Paint	No residential structures were present.	X	7.2
Radon	Property is located in the USEPA radon designation Zone 2 or 'moderate risk' area for radon.		7.3
Mold / Microbial Damage	HK observed multiple areas of water intrusion and olfactory evidence of mold in the abandoned structures.		7.4
NWI Wetlands & FEMA Flood Zones	NWI mapped wetlands were depicted along and within the eastern border of the Property. FEMA 100-year and 500-year flood zone areas are noted encompassing the eastern and western portions of the Property respectively.		4.1
Lead in Drinking Water	Potable water service was not observed to be supplied to the Property.		7.6

2.0 INTRODUCTION

2.1 Purpose and Scope

This assessment was conducted utilizing generally accepted Phase I ESA industry standards in accordance with the ASTM Standard Practice E 1527-13. The ASTM describes these methodologies as representing good commercial and customary practice in the United States of America for conducting an environmental site assessment of a parcel of commercial real estate with respect to the range of contaminants within the scope of the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) and petroleum products. As such, this practice is intended to permit a user to satisfy one of the requirements to qualify for the innocent landowner, contiguous property owner or bona fide prospective purchaser limitations on CERCLA liability (hereinafter, the “landowner liability protections,” or “LLPs”): that is, the practice that constitutes all appropriate inquiries into the previous ownership and uses the property consistent with good commercial and customary practice as defined at 42 U.S.C. §9601(35) (B). The primary goal of the processes established by ASTM E1527-13 is to identify *recognized environmental conditions* in connection with the Property.

The term *recognized environmental condition (REC)* is defined by the ASTM as the presence or likely presence of any hazardous substances or petroleum products in, on or at a property: (1) due to a release to the environment; (2) under conditions indicative of a release to the environment; or (3) under conditions that pose a material threat of a future release to the environment.

The ASTM has also defined the terms *historical recognized environmental conditions* and *controlled recognized environmental conditions* as two additional types of RECs. The term *historical recognized environmental condition (HREC)* is defined as a past release of any hazardous substances or petroleum products that has occurred in connection with the Property and has been addressed to the satisfaction of the applicable regulatory authority or meeting unrestricted use criteria established by a regulatory authority, without subjecting the Property to any required controls (for example, property use restrictions, activity and use limitations, institutional controls or engineering controls).

The term *controlled recognized environmental condition (CREC)* is defined as a recognized environmental condition resulting from a past release of hazardous substances or petroleum products that has been addressed to the satisfaction of the applicable regulatory authority, with hazardous substances or petroleum products allowed to remain in place subject to the implementation of required controls.

Conditions determined to be “*de minimis conditions*” are not considered to be RECs, HRECs or CRECs. *De minimis condition* is defined by the ASTM, “...as a condition that generally does not present a threat to human health or the environment and that generally would not be the subject of an enforcement action if brought to the attention of appropriate governmental agencies.”

The chief components of this assessment are generally described as follows:

- A non-invasive visual reconnaissance of the Property and adjoining properties in accordance with ASTM guidelines for evidence of RECs.

- Interviews of past and present owners and occupants and state and local government officials, seeking information related to the potential presence of RECs at the Property.
- A review of standard physical record sources for available topographic, geologic and groundwater data.
- A review of standard historic record sources, such as fire insurance maps, city directories, aerial photographs, prior reports and interviews, etc., to determine prior uses of the Property from the present, back to the Property's first developed use, or back to 1940, whichever is earlier.
- A review of standard environmental record sources including federal and state environmental databases, and additional environmental record sources, to identify potential regulatory concerns with the Property, adjoining properties and properties located within the surrounding area.

An evaluation of environmental or other regulatory compliance matters is excluded from the scope of this assessment.

These methodologies are described as representing good commercial and customary practice for conducting an Environmental Site Assessment of a property for the purpose of identifying recognized environmental conditions.

2.1.1 Business Environmental Risks/Non-ASTM Scope Considerations

In accordance with our contract agreement, HK may have addressed the following potential environmental subject matters that are outside of the requirements of the ASTM E1527-13 standard:

Asbestos-Containing Materials (ACM): A cursory non-intrusive visual screening for the presence of suspect ACM within the accessed areas of buildings built prior to 1990 on the Property. It is emphasized that this cursory non-intrusive visual screening does not constitute an asbestos survey/inspection of the premises. An asbestos survey/inspection should be sought by the report User(s) if more certainty is desired regarding ACM and potential asbestos hazards at the Property. Furthermore, a review of regulatory compliance matters pertaining to asbestos is excluded from the scope of work.

Lead-Based Paint (LBP): A cursory non-intrusive visual screening of the condition of painted surfaces in the accessed areas of residential buildings/units built prior to 1980 on the Property. It is emphasized that this cursory non-intrusive visual screening does not constitute a comprehensive survey for LBP or potential lead hazards. A comprehensive inspection should be sought by the report User(s) if more certainty is desired regarding LBP at the Property. Furthermore, a review of regulatory compliance matters pertaining to lead-based paint is excluded from the scope of work.

USEPA Designated Radon Potential: Review of general non-site specific data published by the USEPA regarding the Radon Zone classification for the area of the Property.

Mold/Microbial Damage: A cursory non-intrusive visual screening within the accessed areas of buildings on the Property for evidence of systemic microbial problems, including visible mold

growth, water damaged building materials or musty odors. It is emphasized that this cursory non-intrusive visual screening does not constitute a comprehensive survey for moisture/mold/microbial damage. A more comprehensive inspection should be sought by the report User(s) if more certainty is desired regarding the potential for moisture/mold/microbial damages at the Property.

NWI Wetlands: Review of US Fish and Wildlife Service National Wetland Inventory digitized data of mapped wetlands as presented in the attached EDR Radius Map plus Geocheck Report.

It is emphasized that, regardless of the wetlands data obtained via the EDR Geocheck-Physical Setting Source Addendum, a delineation of regulated wetlands by a qualified professional would be warranted to determine the presence or absence of regulated wetlands at the Property.

Lead in Drinking Water: Review of the potential for elevated levels of lead in the drinking water by determining the source of the drinking water supply and a review of available testing or compliance data reports.

2.2 Property Location/Legal Description

Property location and legal description details are described as follows:

Primary Street Address:	78 Bridge Street				
City:	Tonawanda	County:	Niagara	State:	New York
Tax ID/Parcel Number:	Block 1, Lot 9 / Tax ID: 184.08-1-9				
Approx. Land Area:	3.10-acres				
Apprx. Latitude/Longitude:	North 43.0272060 degrees/West 78.8832410 degrees				
Additional Details (if appl.):	None				
Property Owner:	City of North Tonawanda				
Zoning Designation:	WD (water-dependent)				

2.3 Data Gaps

A *data gap* is defined by the ASTM as a lack of or inability to obtain information required by this practice despite good faith efforts by the environmental professional to gather such information. A data gap is only significant if other information and/or professional experience raises reasonable concerns involving the data gap and the ability to determine the presence or absence of recognized environmental conditions. The following table summarizes data gaps encountered during the assessment as well as a discussion of their significance.

Data Gap:	Significant (Yes/No)?	Discussion
Historical records data failure	No	Records gaps exceeding five years were encountered; however, no significant site use changes are suspected during these intervals.

Data Gap:	Significant (Yes/No)?	Discussion
Response to agency records requests not received as of date of report.	No	Any additional information indicative of a REC will be forwarded upon receipt.

2.4 User Reliance

This report is for the exclusive use of the User(s) named on the front cover. No other party(ies) shall have any right to rely on the content of this report without first obtaining the consent of the original report User; and without obtaining written consent from HK in the form of a letter of reliance or report recertification.

2.5 Significant Assumptions

The following significant assumptions are made:

- The site operations at the time of the site visit are assumed to reflect typical site conditions relative to potential environmental conditions and that no concealment of environmental conditions or releases by site owners or occupants has occurred. Likewise, it is assumed that no areas of the Property with potential environmental concerns or RECs were concealed or otherwise not reported, intentionally or unknowingly, by the Property owners/occupants and/or site escort at the time of the site visit.
- For the purpose of estimating the approximate direction of groundwater flow in the absence of site specific groundwater data, unless indicated otherwise, an assumption has been made that the gradient of groundwater flow follows the surface topography of the Property and immediate surrounding area.

2.6 General Limitations and Exceptions

2.6.1 Limitations

The report turnaround time specified by the contract agreement for this assessment may present a limitation to the availability of pertinent regulatory agency records. Such limitations, if encountered, are further specified in Section 4.4.

Significant limitations related to the condition or accessibility of the Property at the time of the site reconnaissance, if encountered, are reported in Section 5.1.

2.6.2 Other Exceptions or Deletions

No other exceptions or deletions from the ASTM Standard E 1527-13 are reported.

2.6.3 Special Terms and Conditions

This Phase I Environmental Site Assessment has been prepared using reasonable efforts in each phase of its work to identify recognized environmental conditions associated with hazardous substances, wastes and petroleum products at the Property. Findings within this report are based on information collected from observations made on the day of the site reconnaissance and from reasonably ascertainable information obtained from governing public agencies and private sources.

This report is not definitive and should not be assumed to be a complete or specific definition of the conditions above or below grade. Information in this report is not intended to be used as a construction document and should not be used for demolition, renovation, site development, redevelopment, or other construction purposes. No representation or warranty is made that the past or current operations at the Property are, or have been, in compliance with all applicable federal, state and local laws, regulations and codes.

Findings, conclusions and recommendations presented in this report are based on visual observations of the Property, interviews conducted, the records reviewed, information provided by the Client, and/or a review of readily available and supplied drawings and documents. Information obtained during the assessment, whether written, graphic or verbal, provided by the Property contact(s) or as shown on any documents reviewed or received from the Property contact, owner or agent, or government agency source; is assumed to be accurate except as specifically stated otherwise in this report. Independent verification of the accuracy or completeness of all information reviewed or received during the course of this assessment is not made and excluded from the scope of work for this assessment. No warranty or guarantee is made of the accuracy or completeness of information that was obtained from ostensibly knowledgeable individuals, regulatory agency representatives or other secondary sources.

Regardless of the findings stated in this report, HK is not responsible for consequences or conditions arising from facts that were concealed, withheld or not fully disclosed at the time the assessment was conducted.

This report does not warrant against future operations or conditions, nor does it warrant against operations or conditions present of a type or at a location not investigated.

The regulatory database report provided is based on an evaluation of the data collected and compiled by a contracted data research company. The regulatory research is designed to meet the requirements of ASTM Standard E 1527-13. HK can neither warrant nor guarantee the accuracy or completeness of the information obtained from the regulatory database report provider during the course of this assessment.

Subsurface conditions may differ from the conditions implied by the surface observations and can only be reliably evaluated through intrusive techniques.

Reasonable efforts have been made during this assessment to identify aboveground and underground storage tanks and ancillary equipment. Reasonable efforts are limited to information gained from visual observation of largely unobstructed areas, recorded database information held in public record and available information gathered from interviews. Such methods may not identify

surficial and subsurface features that may have been hidden from view due to parked automobiles and other vehicles, snow cover, vegetative growth, pavement, construction or debris pile storage or incorrect information from sources.

No guarantee, explicit or implied, is made that the records pertaining to historical ownership or occupancy which were reviewed represent a comprehensive or precise delineation of past Property ownership or tenancy for legal purposes.

The ASTM E1527-13 standard states that recommendations are not required to be included in a Phase I ESA report; however, further that recommendations are an additional service that may be useful in the User's analysis of landowner liability protections or business environmental risks; and that the User should consider whether recommendations for additional inquiries or other services are desired.

The recommended response actions to the identified RECs presented in Section 1.3, if any, are not intended to represent the only course(s) of action to take; nor does it imply any opinion as to the timing of the action. Furthermore, it is emphasized that additional response actions may become warranted depending on the outcome of the initial action(s) taken. HK advises that consultation with legal counsel familiar with environmental and real estate law may be beneficial to the decision making process for the type and timing of a response action to identified RECs, if any.

Due to the limited nature of our review of potential Business Environmental Risks, the User of the report should consider whether to take additional action(s) to further define, properly manage and/or mitigate potential BERs.

In the event of any conflict between the terms and conditions of this report and the terms and conditions of the consulting services agreement for this project, the consulting services agreement shall control.

3.0 USER PROVIDED INFORMATION

The term “User” is defined by ASTM as the party seeking to use Practice E1527 to complete an environmental site assessment of the Property; specifically, the entities named on the front cover to which the report has been addressed.

3.1 Prior Environmental Reports/Documentation

The following prior environmental reports/documentation was provided:

Phase I Environmental Site Assessment, 78 Bridge Street, City of North Tonawanda, Niagara County, New York; prepared by Urban Engineers of New York, P.C. (Urban), dated June 2010.

The report identified a Recognized Environmental Condition as follows:

This assessment has revealed evidence of “recognized environmental conditions” in connection with the property. A recognized environmental condition is defined by ASTM as “the presence or likely presence of any hazardous substances or petroleum products on a property under conditions that indicate an existing release, a past release, or a material threat of a release of any hazardous substances or petroleum products into structures on the property or into the ground, groundwater, or surface water of the property.”

The likely impact from storage and burning of cars and boats at the study site using petroleum-based accelerants and the presence of unknown fill materials on a former industrial site are considered an ASTM-defined recognized environmental conditions. Additionally, a significant data gap was encountered that included a lack of available information on an adjacent industrial site located at 50 Bridge Street that was listed in two potentially significant environmental databases.

Urban recommended the following to address the identified REC:

Urban recommends a Phase II Environmental Site Assessment be conducted at the study site to evaluate potential impact to the property and to assess the unknown fill materials. Additional research should be conducted on the adjacent industrial site to determine whether the site is an environmental threat to the 78 Bridge Street parcel

HK concurs that further investigation is warranted.

3.2 User Questionnaire

Section 6 of the ASTM E1527-13 standard describes certain tasks required to be performed by the report User in order to qualify for landowner liability protections to CERCLA liability. To assist the report User to meet these requirements, the ASTM E1527-13 standard recommends a questionnaire of inquiries (User Questionnaire) specified in 40 CFR 312.25, 312.28, 312.29, 312.30, and 312.31 be provided to the original report User. Hillmann has been informed by the User that, as a prospective lender, they have declined to complete the User Questionnaire.

Question:	Yes/No:	Detail:
Environmental liens that are filed or recorded against the property: Did a search of recorded land title records identify any environmental liens filed or recorded against the property under federal, tribal, state or local law?	NR	
Activity and use limitations that are in place on the property or that have been filed or recorded against the property: Did a search of recorded land title records (or judicial records where appropriate, identify any AULs, such as engineering controls, land use restrictions or institutional controls that are in place at the property and/or have been filed or recorded against the property under federal, tribal, state or local law?	NR	
Specialized knowledge or experience of the person seeking to qualify for the LLP: Do you have any specialized knowledge or experience related to the property or nearby properties? For example, are you involved in the same line of business as the current or former occupants of the property or an adjoining property so that you would have specialized knowledge of the chemicals and processes used by this type of business?	NR	
Relationship of the purchase price to the fair market value of the property if it were not contaminated: Does the purchase price being paid for this property reasonably reflect the fair market value of the property? If you conclude that there is a difference, have you considered whether the lower purchase price is because contamination is known or believed to be present at the property?	NR	
Commonly Known or Reasonably Ascertainable Information: Are you aware of commonly known or reasonably ascertainable information about the property that would help the environmental professional to identify conditions indicative of releases or threatened releases? For example,		
-Do you know the past uses of the property?	NR	
-Do you know of specific chemicals that are present or were once present at the property?	NR	
-Do you know of spills or other chemical releases that have taken place at the property?	NR	
-Do you know of any environmental cleanups that have taken place at the property?	NR	
The degree of obviousness of the presence or likely presence of contamination at the property, and the ability to detect the contamination by appropriate investigation: Based on your knowledge and experience related to the property are there any obvious indicators that point to the presence or likely presence of releases at the property?	NR	
Litigation/Administrative Proceedings/Government Notices As the User of this ESA, do you have knowledge of (1) any pending, threatened, or past litigation relevant to hazardous	NR	

Question:	Yes/No:	Detail:
substances or petroleum products in, on, or from the property; (2) any pending, threatened, or past administrative proceedings relevant to hazardous substances or petroleum products in, on or from the property; and (3) any notices from any governmental entity regarding any possible violation of environmental laws or possible liability relating to hazardous substances or petroleum products.		

NR-no response

3.3 Reason for Performing Phase I ESA

The User did not indicate the purpose of the assessment. In accordance with ASTM E1527-13, it is assumed that the Phase I ESA was being performed in order to qualify for landowner liability protection to CERCLA liability.

4.0 RECORDS REVIEW

4.1 Physical Setting Sources

The following physical setting sources were reviewed:

Source	Discussion
USGS 7.5 minute Topographic Map Data: (EDR Geocheck-Physical Setting Source Addendum)	The Property lies at an elevation of approximately 571 feet above mean sea level. An interpretation of topographic contour lines as well as a review of the EDR Geocheck-General Topographic Gradient suggested terrain sloping downward towards the west-southwest. The closest down gradient water body is the Little River to the immediate east of the Property off of the Niagara River to the west.
USDA SCS Soil Data: (EDR Geocheck-Physical Setting Source Addendum)	The soil type at the Property is listed as an un-surveyed area.
Geologic Data: (EDR Geocheck-Physical Setting Source Addendum)	The geologic formation in the vicinity of the Property is described as a stratified sequence of the Paleozoic Era, Silurian System, and Upper Silurian Series.
Prior Env. Reports: (Section 3.1)	No additional relevant site specific geologic data was noted from a review of the prior environmental reports listed in Section 3.1.
Additional Sources/Data:	No additional physical setting sources or data was obtained.
Groundwater Flow Discussion:	Based on a review of the above information as well as observation of the site, the direction of shallow groundwater flow at the site is inferred to be towards the southeast.
NWI Wetlands Data: (EDR Geocheck-Physical Setting Source Addendum)	NWI mapped wetlands were depicted along and within the eastern border of the Property. FEMA 100-year and 500-year flood zone areas are noted encompassing the eastern and western portions of the Property respectively.

4.2 Historical Use – Property and Adjoining Properties

Research has been conducted in an attempt to develop a history of the previous uses of the property and surrounding area, in order to help identify the likelihood of past uses having led to REC's in connection with the property. Standard historical sources have been sought in an attempt to document the past uses of the Property as far back as it can be shown that the Property contained structures; or from the time the Property was first used for residential, agricultural, commercial, industrial or governmental purposes.

4.2.1 Fire Insurance Maps

A Certified Sanborn Map Report was obtained from EDR for a review of published historic fire insurance maps for the Property and surrounding area. The following is a summary of site uses and notable details depicted by the available maps:

Year(s)	Prop/Adj	Depicted Use(s)	Notable Details
1889, 1893, 1910	Property:	The Property is improved with a rail spur and sheds. The northern portion of the property is listed as a (boat) "slip" off of "Tonawanda Harbor" and a "lumber dock". In 1910 additional rail spurs appear within the Property connecting a "Shingle & Dressed Lumber Shed" to the rail line. 12" and 24" water pipes are depicted within the Property.	

Year(s)	Prop/Adj	Depicted Use(s)	Notable Details
	Adjoining:	Adjoining properties to the north, south and west are improved with rail spurs, lumber yards, warehouses and mills. The eastern adjacent is listed as the Tonawanda Harbor (surface water).	
1951, 1967	Property:	All but the rail spurs appear to have been cleared. A 24" water pipe continues to be depicted within the southeast portion of the Property.	
	Adjoining:	The northern and southern adjacent properties appear to have been largely cleared and the western adjacent property is now listed as the Filler Corporation Flour & Cotton Flock plant.	

A copy of the Certified Sanborn Map Report is attached in Appendix D.

4.2.2 City Directories

An EDR City Directory Abstract report was reviewed for data of former occupants of the Property's street address. The following is a generalized summary of the findings of city directory research for past occupants of the Property.

Property	
Use(s) / Occupant(s):	Years
Not listed	

The EDR City Directory Abstract report was also reviewed for listings of historic occupants of the adjoining properties. The following is a general summary of listings of historic adjoining property occupants:

Adjoining Properties	
Use and/or Occupant(s)	Years
50 Bridge Street – International Fiber	2005-2017
50 Bridge Street – International Filler Corporation Wood Prod.	1964-1989

A copy of the EDR City Directory report is attached in Appendix D.

4.2.3 Historical Topographic Maps

A Historical Topographic Map Report was obtained from EDR for a review of published topographic maps for the Property and surrounding area. The following is a summary of notable details depicted by the available maps:

Year(s)	Prop/Adj	Depicted Use(s)	Notable Details
1897, 1899, 1900, 1901, 1913, 1948,	Property:	The Property appears with rail spurs and one to two small residences in the western portion from 1897-1813. A boat slip appears within the northern portion of the Property.	

Year(s)	Prop/Adj	Depicted Use(s)	Notable Details
1950, 1954, 1965, 1980	Adjoining:	Adjoining properties to the north, south and west are improved with rail spurs and sparsely scattered residences. Buildings appear to the west beginning in the 1948 topographic map.	

A copy of the Topographic Map Report is attached in Appendix D.

4.2.4 Historical Aerial Photographs

A Historical Aerial Photograph Report was obtained from EDR for a review of published aerial photographs for the Property and surrounding area. The following is a summary of notable details depicted by the available maps:

Year(s)	Prop/Adj	Depicted Use(s)	Notable Details
1938, 1951, 1959, 1962, 1966, 1978, 1985, 1995, 2006, 2009, 2013, 2017	Property:	The Property appears with a rail spur along the south and a boat slip along the north. The slip is filled in between 1962 and 1966. Two structures appear beginning in 1978. Miscellaneous boats and debris appear within the Property along with the two structures thereafter.	
	Adjoining:	Adjoining properties are improved with rail spurs and buildings to the west. The Property is adjoined to the east by a river.	

A copy of the Aerial Photograph Map Report is attached in Appendix D

4.2.5 EDR High-Risk Historical Records

The EDR Radius Map™ report, which is discussed in greater detail in Section 4.3, provided a search of proprietary databases of potential historical high-risk uses at or in the vicinity of the Property. These databases include EDR Historic Cleaners – a database of property addresses with records of historical occupancy by suspected cleaners businesses; EDR Historic Auto – a database of property addresses with records of historical occupancy by potential automotive gas/filling stations and repair facilities; and EDR MGP- a database of sites historically occupied by manufactured gas plants and related facilities.

EDR Database	On-site Listings:	Adjoining/Off-Site Listings
Historic Cleaners: (on-site/adjoining only)	None	None
Historic Auto: (on-site/adjoining only)	None	None
MGP: (1-mile distance)	None	The Former Gastown MGP Site located at 126 East Niagara Street is located 3,540-ft southeast of the Property. Given the intervening rivers, distance and gradient the MGP site is not of environmental concern to the Property.

4.2.6 Petroleum/Natural Gas Well Review

The historical record sources were reviewed for records of historic petroleum and/or natural gas wells at the Property. No record of any historical petroleum/natural gas wells at or adjoining the Property was identified.

4.2.7 Additional Historical Data

Where applicable, the following additional pertinent historical data was obtained:

Interviews/Anecdotal:	No additional pertinent historical data was obtained.
Local Gov't Records:	No additional pertinent historical data was obtained.
Prior Env. Reports: (Section 3.1)	Prior environmental reports reviewed as part of this assessment, as detailed in Section 3.1, did not provide additional pertinent detail of historical site usage.
Site Observations:	Indications of historic uses of the Property or adjoining properties were not observed during the site reconnaissance.
Other Sources:	No additional pertinent historical data was obtained.

4.2.8 Summary of Identified Historic Uses

The following table presents a summary of the types and approximate date ranges of identified prior uses of the Property:

Property	
Date Range	Use
1889-c. 1910	Lumber / shingle yard, storage and distribution (rail spurs and slip)
1889-1960's	Boat slip
1970's to present	Fire Tower and smokehouse (fire-rescue training)

The following table presents a summary of the types of identified prior uses of the adjoining properties:

Adjoining Properties	
Date Range	Use
Early 1900's – c. 1960's	Lumber yard and mills, warehouses, Flour and Cotton Flock
Unknown – Present	Seismic test facility, boat storage, rail

4.2.9 Historical Records Data Failure

The ASTM E1527-13 standard defines data failure as a failure to achieve the ASTM specified historical research objectives after reviewing the standard historical sources that are reasonably ascertainable and likely to be useful. The objective is to identify all obvious uses of the property from the present, back to the property's first developed use, or back to 1940, whichever is earlier. Furthermore, records of historic use/conditions should be sought in intervals no less than approximately five years, unless the property conditions appear unchanged over a longer interval.

Objective	Met?	Detail	Significant?
First developed use/date determined?	Yes	The first developed use of the Property was a lumber yard circa 1889	No
Record sources at 5-year intervals back to 1940 or first developed use?	No	Historical record gaps exceeding five years were encountered. However, significant site-use changes or undiscovered site uses appear unlikely to have occurred during the record gaps.	No
All obvious prior uses identified?	Yes	See Section 4.2.8.	No

Please refer to Section 2.3 for additional discussion of data gaps and their significance to the findings of the assessment.

4.2.10 Historic Uses REC Discussion

The review of historical records indicated evidence of the following potential RECs in connection with the Property:

The historic use of the Property for industrial warehousing and distribution of lumber and shingles with multiple rail spurs, a boat slip filled in with fill of unknown disposition in the 1960's, and subsequently used for training grounds for fire-rescue including visual evidence of the use of combustibles (petroleum products) is considered a REC.

4.3 Standard Environmental Record Sources

A regulatory database report, titled EDR Radius Map™ Report, prepared by Environmental Data Resources of Shelton, CT was obtained and reviewed. The report provided a search of standard environmental record sources for listings of the Property, adjoining properties and sites within the surrounding area; and has been reviewed for the purpose of identifying listings suggesting a potential impact to the Property due to presence or migration of hazardous substances and/or petroleum products. Additional descriptions of the meaning and significance of the regulatory databases can be found in the regulatory database report in Appendix E. The EDR Radius Map™ Report provided a search of the following database categories in accordance with the requirements of the ASTM Standard E1527-13:

Regulatory Database	Search Distance
Fed. National Priorities List (NPL/a.k.a. "Superfund" sites) & Proposed NPL	1-mile
Fed. Delisted NPL	½-mile
Fed. Superfund Enterprise Management System (SEMS; formerly CERCLIS)	½-mile
Fed. SEMS-ARCHIVE (formerly known as CERCLIS NFRAP)	½-mile
Fed. RCRA Corrective Action Sites (CORRACTS)	1-mile
Fed. RCRA Transport/Storage/Disposal (TSD) sites	½-mile
Fed. RCRA Generators (LQG, SGQ & CESQG)	Site & Adjoining
Fed. Institutional Control/Engineering Control (IC/EC) Registries	Site only
Fed. Emergency Response Notification System (ERNS)	Site only
State/Tribal Hazardous Waste Sites (SHWS)	1-mile
State/Tribal Landfill and/or Solid Waste Disposal (LF/SWF)	½-mile
State/Tribal Leaking Storage Tanks	½-mile
State/Tribal Registered Storage Tanks	Site & Adjoining
State/Tribal IC/EC Registries	Site
State/Tribal Voluntary Cleanup Sites	½-mile
State/Tribal Brownfields	½-mile
Additional Federal, State, Tribal and Local Environmental Databases	Variable

Reported distances for adjoining listings discussed in Section 4.3.4, if applicable, are approximate and indicative of the presence of a public roadway or right-of-way between the adjoining site and Property.

The reported gradients indicated where applicable in Sections 4.3.4 and 4.3.5 have been estimated based on a number of factors including but not necessarily limited to field observation, review of topographic maps, database listing details and/or site specific geo-technical data.

4.3.1 Supplemental Database Listings

The regulatory database report was also reviewed for listings on supplemental databases, in addition to the Standard Environmental Record Sources. Any property or adjoining property listings on such databases of significant concern, if identified, is discussed in Sections 4.3.3 and 4.3.4. Otherwise, none of the other supplemental database listings identified by the regulatory database report are considered to be a REC in connection with the Property.

4.3.2 Limited Tier I Vapor Encroachment Screening

Limited analysis of the details of on-site, adjoining and vicinity database sites was conducted to identify potential sources of sub-surface vapor encroachment. This review was based on elements of the ASTM “Standard Guide for Vapor Encroachment Screening on Property Involved in Real Estate Transactions” (ASTM E 2600-15); and also on elements of “Methodology for Identifying the Area of Concern Around a Property Potentially Impacted by Vapor Migration from Nearby Contaminated Sources” (Buonicore, 2011-S-103-AWMA). Vicinity database sites pertaining to non-petroleum product releases within 1,760 feet of the Property in the up-gradient direction, 365 feet of the Property in the cross gradient direction and 100 feet of the Property in the down gradient direction; and vicinity database sites pertaining to petroleum product releases within 528 feet of the Property in the up-gradient direction, 165 feet of the Property in the cross gradient direction and 100 feet of the Property in the down gradient direction were reviewed to identify active contamination sites with the potential to affect subsurface vapor conditions at the subject property. The potential for vapor encroachment was considered in assessing whether or not a REC exists in connection with the Property when reviewing applicable sites within those distances.

Regulatory database sites with active petroleum or non-petroleum releases that are considered to constitute a vapor encroachment condition (VEC) to the Property, if any, are identified and discussed in Sections 4.3.3, 4.3.4 and 4.3.5.

4.3.3 Property Listings

The Property is listed on the US Brownfields and FINDS databases for a grant to perform a Phase I Environmental Site Assessment in March 2010. The listings does not identify what if any RECs were identified. And no further investigation appears to have been conducted.

4.3.4 Adjoining Property Listings

The following adjoining property listings were identified. Reported distances, where applicable, are approximate and indicative of the presence of a public roadway or right-of-way between the adjoining site and Property. The reported gradient has been estimated based on a number of factors including but not necessarily limited to field observation, review of topographic maps, database listing details and/or site specific geo-technical data.

Name/Address:	50 Bridge Street				
Database(s):	SEMS-Archive, NY Spills, HSWDS, RCRA VSQG, ICIS, US Airs, FINDS, ECHO, Manifest				
Distance in feet:	0	Direction:	SW	Gradient:	Cross
Data Discussion:	The listings indicated the site was used for hazardous waste disposal including for semi-volatile organic compounds. The listings also detail hazardous waste generated and shipped offsite. The SEMS-Archive listing is for characterization work done in the 1980's resulting in a determination not to include the site on the National Priority List (NPL).				
REC Discussion:	Based on the details provided above, a REC is suspected in connection with the Property. Additional evaluation would be required to determine whether a REC exists.				
VEC Discussion:	Based on the available data, a VEC may exist. Additional evaluation would be required to confirm whether a significant vapor intrusion impact to the Property exists.				

Name/Address:	200 Taylor Road / Taylor Devices Inc.				
Database(s):	RCRA-SQG, FINDS, ECHO, Manifest				
Distance in feet:	0	Direction:	N	Gradient:	Up/Cross
Data Discussion:	The listings are associated with the generation of regulated hazardous waste shipped offsite. The listing is not indicative of a release / impact to environmental media and is not considered a REC.				
REC Discussion:	Based on the details provided above, a REC is not suspected in connection with the Property.				
VEC Discussion:	Based on the available data, a VEC is not suspected.				

4.3.5 ASTM Search Distance Findings

The following is a discussion of non-adjoining sites identified as located within the ASTM specified search distance surrounding the Property. In order to keep this discussion informative and concise, discussion(s) is/are provided of the listed site(s) for each database category that appears most likely to impact the Property based on distance, area topography and/or regulatory status. Listings of sites within the applicable search distances not specifically discussed below were reviewed and concluded not to be RECs in connection with the Property or VECs based on various factors including distance, area topography, known or inferred groundwater flow direction and/or regulatory status. Listings for the following databases, if identified, have been discussed above in Sections 4.3.3 and 4.3.4: Registered Storage Tanks, Federal RCRA Generators, Federal and State EC/IC, ERNS. A copy of the full regulatory database report, including available details of all listed sites, is included in Appendix E.

Federal NPL		# of sites:	0	Search Distance:	1-mile
Notable Listing:					
Distance in feet:		Direction:		Gradient:	
Data Discussion:					
REC Discussion:					
VEC Discussion:					

Federal Delisted NPL		# of sites:	0	Search Distance:	1-mile
Notable Listing:					
Distance in feet:		Direction:		Gradient:	
Data Discussion:					
REC Discussion:					
VEC Discussion:					

Federal SEMS		# of sites:	0	Search Distance:	½-mile
Notable Listing:					
Distance in feet:		Direction:		Gradient:	
Data Discussion:					
REC Discussion:					
VEC Discussion:					

Federal SEMS-ARCHIVE		# of sites:	2	Search Distance:	½-mile
Notable Listing:	Schreck's Scrapyard				

Distance in feet:	1,471	Direction:	ENE	Gradient:	None, due to hydrologic barrier.
Data Discussion:	The sites are across the Little River and not of environmental concern to the Property.				
REC Discussion:	Based on the details provided above, a REC is not suspected in connection with the Property.				
VEC Discussion:	Based on the available data, a VEC is not suspected.				

Federal CORRACTS			# of sites:	1	Search Distance:	1-mile
Notable Listing:	76 Robinson Street					
Distance in feet:	1,903	Direction:	E	Gradient:	None, due to topographic divide.	
Data Discussion:	The site is across the Little River and not of environmental concern to the Property.					
REC Discussion:	Based on the details provided above, a REC is not suspected in connection with the Property.					
VEC Discussion:	Based on the available data, a VEC is not suspected.					

Federal RCRA-TSD			# of sites:	0	Search Distance:	1/2-mile
Notable Listing:	None					
Distance in feet:		Direction:		Gradient:		
Data Discussion:						
REC Discussion:						
VEC Discussion:						

State HAZARDOUS WASTE SITE			# of sites:	4	Search Distance:	1-mile
Notable Listing:	Schreck's Scrapyard					
Distance in feet:	1,471	Direction:	E	Gradient:	None, due to topographic divide.	
Data Discussion:	Each of the SHWS sites is across the Little River and not of environmental concern to the Property.					
REC Discussion:	Based on the details provided above, a REC is not suspected in connection with the Property.					
VEC Discussion:	Based on the available data, a VEC is not suspected.					

State SOLID WASTE FACILITY/LANDFILL			# of sites:	1	Search Distance:	1/2-mile
Notable Listing:	Metzger Removal / 235 River Road					
Distance in feet:	732	Direction:	E	Gradient:	None, due to topographic divide.	
Data Discussion:	The site is across the Little River and not of environmental concern to the Property.					
REC Discussion:	Based on the details provided above, a REC is not suspected in connection with the Property.					
VEC Discussion:	Based on the available data, a VEC is not suspected.					

State LEAKING STORAGE TANKS			# of sites:	13	Search Distance:	1/2-mile
Notable Listing:	1 Archer Street					
Distance in feet:	523	Direction:	W	Gradient:	Down	
Data Discussion:	The nearest site obtained regulatory closure and is downgradient (close to the Niagara River). All other LTANKS sites are across the Little River and not of environmental concern to the Property.					
REC Discussion:	Based on the details provided above, a REC is not suspected in connection with the Property.					
VEC Discussion:	Based on the available data, a VEC is not suspected.					

State VOLUNTARY CLEANUP SITES			# of sites:	0	Search Distance:	1/2-mile
Notable Listing:						
Distance in feet:		Direction:		Gradient:		

Data Discussion:	
REC Discussion:	
VEC Discussion:	

State BROWNFIELD SITES			# of sites:	24	Search Distance:	1/2-mile
Notable Listing:	Arida 3 / 4 Bridge Street					
Distance in feet:	312	Direction:	W	Gradient:	Down	
Data Discussion:	Contaminants were found at the site associated with historic use. Given the topographic gradient, distance and/or nature of the case, no impact to the Property is suspected.					
REC Discussion:	Based on the details provided above, a REC is not suspected in connection with the Property.					
VEC Discussion:	Based on the available data, a VEC is not suspected.					
UNMAPPED/ORPHAN LIST SITES						
	HK has also reviewed a list of unmapped sites (a.k.a. “Orphan List” sites) indicated by the database report. Unmapped sites that were identified as falling within an applicable specific search distance or warranting discussion have either been discussed in the preceding tables or are detailed below:					
Notable Listings:	None					

4.4 Additional Environmental Record Sources

Requests have been submitted to local, municipal and state agencies for pertinent records pertaining to the Property, particularly with regard to potential environmental concerns such as petroleum storage tanks, storage and usage of hazardous substances and petroleum products, and/or known or suspected environmental contamination. Where applicable, internet research of government environmental regulatory databases was also conducted, as well as a general cursory internet search of the Property address, for information indicative of a REC. The following table summarizes the findings of the research:

Source	Type of Request	Outcome
North Tonawanda and Niagara County	FOI request	No response was received prior to report issuance.
NYS DEC	FOI request	No response was received prior to report issuance.
NYC DOB	Online search	Hillmann reviewed available on-line records pertaining to the Property. No information indicative of a REC was identified.
EPA Envirofacts	Online search	Hillmann searched online for records pertaining to the Property. No records pertaining to the property were found.
Internet Search Engine	Online search	Hillmann reviewed available on-line records pertaining to the Property. No information indicative of a REC was identified.

5.0 SITE RECONNAISSANCE

5.1 Methodology and Limiting Conditions

The site reconnaissance consisted of visual and/or physical observations of the Property and improvements, adjoining properties as viewed from the Property boundaries and the surrounding area based on visual observations from adjoining public thoroughfares. Building exteriors were observed at ground level, unless otherwise indicated. Where applicable, representative areas of building interiors were accessed and observed to the extent they were made safely accessible with the cooperation of the site escort.

Site Inspection Personnel:	Mr. Brendan Yadav
Property Escort/Company:	Unescorted
Inspection Date:	March 24, 2021
Weather Conditions:	Sunny, 70 degrees F

5.1.1 Significant Inaccessible Areas

No significant areas of the Property inaccessible at the time of the inspection were noted.

5.1.2 Significant Limiting Site Conditions

The following significant limiting site conditions were noted at the time of the site reconnaissance: The presence of snow/ice cover on the ground at the time of the site reconnaissance limited the assessor's ability to inspect exterior ground surfaces for evidence of RECs such as utility ports, storage tank fill ports, monitoring wells, etc.

5.2 General Site Setting

5.2.1 Site and Vicinity Characteristics

Abutting Roadways:	Bridge Street to the south
Current Property Use:	Vacant
Evidence of Past Property Uses:	Fire suppression / rescue training
Evidence of Past Adjoining Property Uses:	None observed.
Surrounding Area Uses:	Commercial / Industrial

5.2.2 Current Adjoining Property Uses

Direction	Description
N	Boat Storage Area. Taylor Drive. "Tonawanda Island Launch Club" - 124 Taylor Drive. "Taylor Devices Inc." - 90 Taylor Drive, manufacturer of shock absorbers, liquid springs, shock isolation systems, seismic isolators, vibration dampers, power plant snubbers, and other types of hydro-mechanical energy management products.
E	Niagara River foot of the Durkee Bridge.
S	Disused railroad, Bridge Street, Offices - 50 Bridge Street
W	"Taylor Devices, Inc. - Seismic Test Facility" - 7 Michigan Street. Michigan Street. Seasonal Boat and RV Storage spaces.

No visual observations indicative of a potential environmental concern were noted on the adjoining properties.

5.2.3 Topographic Characteristics

Terrain:	Relatively flat
Direction of Downward Slope:	Slight towards the east
On-site Water Bodies:	None observed
Other Significant Features:	None observed

5.2.4 General Description of Structures

Buildings/# of Floors	Smokehouse and fire tower
Approx. Building Area:	~2,788-ft ²
Approx. Year Built:	Early 1970's
Ancillary Structures:	None observed
Sources of Heating & Cooling:	No heating or cooling systems were present at the Property.
Potable Water/Sewage Disposal:	No potable water or sewer services were present at the Property.

5.3 Interior & Exterior Observations

5.3.1 Storage/Usage of Hazardous Substances and Petroleum Products

The following hazardous substances and petroleum products were observed to be stored and used by property occupants:

Occupant	Substance	Qty/Container Type	Storage Conditions
None			

5.3.2 Drums

Two kerosene oil drums were observed.

5.3.3 Unidentified Substance Containers

Unlabeled containers of varying sized were observed scattered throughout the Property.

5.3.4 Other Hazardous Substances/Petroleum Products

No other containers of hazardous substances or petroleum products were noted on the Property.

5.3.5 Bulk Petroleum/Hazardous Material Storage Tanks

The following storage tanks for bulk petroleum or hazardous material storage were identified or reported to be present; or are suspected to be present based on visual observations:

AST/UST	Product	Capacity	Construction	Year Installed	Status	Location/Notes
AST	Diesel	~250-gal	Steel	Unknown	Inactive	No secondary containment, reportedly used for fire suppression training, west of the training fire tower.

Multiple ASTs and abandoned vehicles were observed. Additionally, two ASTs, that previously held chlorine, were used in fire training exercises to the west of the training smokehouse. Lastly, according to the fire chief the open ditch in the middle of the subject property was used to dump diesel gasoline used for fire suppression training.

5.3.6 PCBs in Oil Filled Electrical/Hydraulic Equipment

No staining was observed associated with any potential PCB-containing equipment.

5.3.7 Odors

No strong, pungent or noxious odors were noted at the Property.

5.3.8 Pools of Liquid

No standing water or pools of liquid likely to contain hazardous substances or petroleum products were noted at the Property.

5.3.9 Interior Stains or Corrosion

No interior stains or corrosion due to hazardous substance/petroleum products spills/releases were noted at the Property.

5.3.10 Interior Drains/Sumps

No floor drains or sump pits were noted at the Property other than for storm water or sewage management.

5.3.11 Exterior Pits/Ponds/Lagoons

No exterior pits, ponds or lagoons was identified on the Property in connection with waste treatment or disposal.

5.3.12 Stained Soil, Pavement/Stressed Vegetation

The following stained soil, pavement and/or stressed vegetation was observed at the Property:

Multiple area reportedly associated with fire-suppression training materials and activities.

5.3.13 On-Site Solid Waste Disposal/Fill Material

Multiple cars and boats in disrepair were observed throughout the property in addition to scattered debris, an old AST diesel tank, chlorine tanks, pools of water, and an open air pit reportedly previously used to dump diesel fuel for fire suppression training.

Historic urban fill materials may exist at the Property given the history of development.

Note – the northern portion of the Property was historically a boat slip (surface water) and was filled in in the 1960's.

5.3.14 Waste Water

No waste water was observed to be generated or treated onsite.

5.3.15 Septic Systems

No septic systems were identified at the Property.

A ditch reportedly used for combustibles ignition for fire-suppression training purposes was observed.

5.3.16 Wells

No wells were observed at the Property.

5.3.17 Railroad Spurs

Rail spurs were observed within the Property in historic Sanborn Fire Insurance maps. Remnants of unused rail were observed to the adjacent south of the Property.

6.0 INTERVIEWS

6.1 Interviews with Past and Present Owners and Occupants

Subject	Name/Affiliation	Summary
Property Owner / Representative	Mr. Joseph D. Sikura / Fire Chief	Mr. Sikura (interviewed by phone) provided detail on how to enter the site and noted that the Property was previously used for fire-rescue training and had been vacant for several years. He was unaware as to the environmental disposition of the Property.
Property Occupants	Vacant	NA
Past Owners, Occupants, Operators	Not available	Past owners/occupants of the Property were not available for interview at the time of the assessment.
Owners/Occupants of Adjoining or Nearby Properties	Not available	Not available

6.2 Interviews with State and/or Local Government Officials

Written and on-line requests for environmental records of the Property from State and Local governmental agencies are detailed in Section 4.4.

7.0 BUSINESS ENVIRONMENTAL RISKS

In accordance with the contract agreement for this assessment, HK has performed cursory reviews of several potential Business Environmental Risks (also known as “Non-Scope Considerations”). The ASTM E1527-13 standard defines the term business environmental risk (BER) as, *“a risk which can have a material environmental or environmentally-driven impact on the business associated with the current or planned use of a parcel of commercial real estate, not necessarily limited to those environmental issues required to be investigated in this practice.”*

7.1 Asbestos-Containing Material (ACM)

The contracted scope of work included a cursory visual screening of the accessed portions of buildings at the Property built prior to 1990 for suspect asbestos containing materials (ACM). The information provided in this section, where applicable, is limited to identification of potential suspect materials in the readily accessible and observed areas of the building, and their general condition. This is not intended to be a comprehensive survey for the presence of ACM, and no testing has been conducted.

Limited asbestos may be present within the fire tower and smokehouse building materials. The structures are largely stripped to structural components.

7.2 Lead-Based Paint

The contracted scope of work included a cursory visual screening of the condition of painted surfaces in the accessed areas of residential buildings/units built prior to 1980. This is not intended to constitute a comprehensive survey for LBP or potential lead hazards, and no testing has been conducted.

No residential structures were present.

7.3 Radon

Data compiled by the USEPA, as summarized by the regulatory database report, indicated that the Property is located in an area (Niagara County) classified as Zone 2 or 'moderate risk' area for radon. Radon testing was not included in the scope of this assessment.

7.4 Mold/Microbial Damage

As per the contracted scope of work, HK conducted a cursory visual screening of the accessed areas of the building for evidence of significant damage to building materials and finishes as result of moisture intrusion and/or mold/microbial growth. HK observed multiple areas of water intrusion from the roof including past and active leaks. No significant visible mold was observed.

7.5 NWI Mapped Wetlands

NWI mapped wetlands were depicted along and within the eastern border of the Property. FEMA 100-year and 500-year flood zone areas are noted encompassing the eastern and western portions of the Property respectively.

7.6 Lead in Drinking Water

The scope of work for this assessment included a review of the potential for elevated levels of lead in drinking water by determining the source of the drinking water supply and a review of available compliance or testing data.

No potable water service was identified at the Property.

8.0 REFERENCES

ASTM E1527-13-Standard Practice for Environmental Site Assessments: Phase I Environmental Site Assessment Process; ASTM International, 2013

ASTM E12600-15-Standard Guide for Vapor Encroachment Screening on Property Involved in Real Estate Transaction, ASTM International, 2015

EDR Radius Map Report with GeoCheckTM, Environmental Data Resources, 2021

EDR City Directory Abstract Report, Environmental Data Resources, 2021

EDR Sanborn Map Report, Environmental Data Resources, 2021

Methodology for Identifying the Area of Concern Around a Property Potentially Impacted by Vapor Migration from Nearby Contaminated Sources; A. Buonicore, 2011

Phase I Environmental Site Assessment, 78 Bridge Street, City of North Tonawanda, Niagara County, New York; prepared by Urban Engineers of New York, P.C. (Urban), dated June 2010.

9.0 APPENDICES

Appendix A	Site Diagram / Vicinity Map
Appendix B	Site Photographs
Appendix C	Questionnaires / User Provided Information
Appendix D	Historical Records Documentation
Appendix E	Regulatory Records Documentation
Appendix F	Other Documents / Lab Results
Appendix G	Project Personnel Qualifications

APPENDIX A

MAPS / DIAGRAMS




Figure 1: Site Vicinity Map

78 Bridge Street
Tonawanda, New York

N



SCALE: (NOT TO SCALE)

PROJECT No.: Z34708



Figure 2: Site Diagram

78 Bridge Street
Tonawanda, New York

N



SCALE: (NOT TO SCALE)

PROJECT No.: Z34708

APPENDIX B

SITE PHOTOGRAPHS

PHOTO LOG
78 Bridge Street
Tonawanda, NY



Property grounds



Abandoned tank within Property



Miscellaneous waste within Property grounds



Inactive tank near Property fire tower



Abandoned vehicle (one of multiple within Property)



Property fire tower

PHOTO LOG
78 Bridge Street
Tonawanda, NY



Kerosene drum near Property fire tower



View from Property fire tower roof



Property fire tower exterior stairwell



Property fire tower interior stairwell



Property pooled water



Property ditch

PHOTO LOG
78 Bridge Street
Tonawanda, NY



View of fire tower and waste pile within
Property



View of adjacent property



View east of adjacent property



View of northern adjacent Property

APPENDIX C

QUESTIONNAIRES/USER PROVIDED DOCUMENTATION



URBAN ENGINEERS OF NEW YORK, P.C.

*Technical
Report:*

**PHASE I ENVIRONMENTAL
SITE ASSESSMENT
78 BRIDGE STREET
CITY OF NORTH TONAWANDA
NIAGARA COUNTY, NEW YORK**

Prepared for:

**NIAGARA COUNTY DEPARTMENT OF
ECONOMIC DEVELOPMENT
6311 Inducon Corporate Drive
Sanborn, NY 14132**

June 2010

Urban Project No. 2010403.00



**URBAN ENGINEERS
OF NEW YORK, P.C.**

*The Brisbane Building
403 Main Street, Suite 530
Buffalo, NY 14203
(716) 856-9510 Fax (716) 856-0039*

June 23, 2010

Ms. Amy Fisk, AICP, Senior Planner
Niagara County Department of Economic Development
Vantage Center – Suite One
6311 Inducon Corporate Drive
Sanborn, New York 14132

Re: Phase I Environmental Site Assessment
78 Bridge Street
City of North Tonawanda, Niagara County, New York
Urban Project No. 2010403.00

Dear Ms. Fisk:

Urban Engineers of New York, P.C. (Urban) is pleased to submit two (2) hard copies and 2 CD copies of this Technical Report detailing the results of the Phase I Environmental Site Assessment for the captioned project.

The Phase I Assessment included: a review of historical site documentation; a review of federal, state, and local environmental records; an on-site field inspection; and, an evaluation of environmental conditions.

We wish to thank you for the opportunity to assist with this project and for your cooperation during the course of our assessment. If you have questions or need additional information, please contact our office.

Very truly yours,

URBAN ENGINEERS OF ERIE, INC.

Korin M. Giles
Director, Environmental Services

Donald J. Smith, P.E.
Vice President

DJS:KMG:DRY:clb

Enclosures

T:\2010\2010403.00 78 Bridge St. ESA\Environmental\2010403.00 Cover Letter.doc

TABLE OF CONTENTS

EXECUTIVE SUMMARY	i
1.0 INTRODUCTION.....	1
1.1 PURPOSE.....	1
1.2 SCOPE OF SERVICES	1
1.3 LIMITATIONS.....	2
1.4 RELIANCE.....	3
2.0 SITE DESCRIPTION.....	4
2.1 LOCATION AND LEGAL DESCRIPTION	4
2.2 SITE AND VICINITY GENERAL CHARACTERISTICS.....	4
2.3 GENERAL SITE HISTORY	4
2.4 CURRENT USE OF THE PROPERTY AND ADJOINING PROPERTIES	4
3.0 CLIENT PROVIDED INFORMATION	5
3.1 TITLE RECORDS	5
3.2 ENVIRONMENTAL LIENS OR ACTIVITY AND USE LIMITATIONS	5
3.3 SPECIALIZED KNOWLEDGE.....	5
3.4 COMMONLY KNOWN OR REASONABLY ASCERTAINABLE INFORMATION.....	5
3.5 VALUATION REDUCTION FOR ENVIRONMENTAL ISSUES	5
3.6 OWNER, PROPERTY MANAGER, AND OCCUPANT INFORMATION	5
3.7 REASON FOR PERFORMING PHASE I.....	5
4.0 RECORDS REVIEW	6
4.1 AERIAL PHOTOGRAPHS.....	6
4.2 HISTORIC SANBORN MAPS	7
4.3 HISTORIC TOPOGRAPHIC MAPS	8
4.4 CITY DIRECTORIES	8
4.5 STATE, FEDERAL, AND LOCAL AGENCY REVIEW	9
4.6 PHYSICAL SETTING	14
4.7 DATA FAILURE.....	15
5.0 SITE RECONNAISSANCE.....	17
5.1 SUBJECT PROPERTY AND SURROUNDING PROPERTY USE	17
5.2 BUILDING AND GROUNDS INSPECTION.....	17
6.0 INTERVIEWS.....	20
6.1 INTERVIEW WITH CURRENT OWNER/KEY SITE MANAGER.....	20
6.2 INTERVIEW WITH LOCAL HISTORIANS.....	20
6.3 INTERVIEW WITH PAST OWNER/OCCUPANT.....	20
6.4 INTERVIEW WITH LOCAL GOVERNMENT OFFICIALS OR OTHERS	20
7.0 FINDINGS	22

8.0	CONCLUSIONS AND RECOMMENDATIONS.....	26
9.0	REFERENCES.....	28
10.0	QUALIFICATIONS OF ENVIRONMENTAL PROFESSIONALS.....	29

FIGURES

Figure 1 – Site Location Map
Figure 2 – Niagara County Tax Map

APPENDICES

Appendix A – Site Photographs
Appendix B – Aerial Photographs
Appendix C – EDR Historical Topographic Map
Report
Appendix D – EDR Database Search
Appendix E – EDR Sanborn Map Report
Appendix F – EDR City Directory Abstract
Appendix G – EDR Environmental Lien Search
Appendix H – Phase I ESA Questionnaires
Appendix I – Miscellaneous Correspondence
Appendix J – Administrative Record

EXECUTIVE SUMMARY

Urban Engineers of New York, P.C. (Urban) conducted this Phase I Environmental Site Assessment (ESA) for the study site located at 78 Bridge Street, North Tonawanda, New York in accordance with the recommendations of the American Society for Testing and Materials (ASTM E 1527-05) and the United States Environmental Protection Agency's (USEPA) All Appropriate Inquiries Rule. The purpose was to identify potential environmental issues at the property located at the above-referenced address.

The subject property is located at 78 Bridge Street, City of North Tonawanda, Niagara County, New York. The approximate 3.1-acre property is identified by the City of North Tonawanda Tax Assessment office as Tax Identification Number 184.08-1-9. The study site is located in the central portion of Tonawanda Island. The site and surrounding area consists primarily of commercial, industrial and recreational development. The subject property is generally square shaped and is bound by Michigan Street on the west, beyond which is vacant industrial land; the Little River on the east; Thompson Street to the north, beyond which is additional industrial development, and Bridge Street to the south. Tonawanda Island contains primarily industrial and commercial properties.

Historically, it was determined that the site was utilized for lumber storage, boat storage and fire training purposes. A boat slip occupied a portion of the site entering the parcel on the east side of the island off of Little River. Overall, the site was utilized as part of the local lumber industry until the late 1960's. Following that usage, it was developed into the fire training ground. Property use prior to the lumber industry was reportedly for agricultural purposes.

This assessment has revealed evidence of "recognized environmental conditions" in connection with the property. A recognized environmental condition is defined by ASTM as "the presence or likely presence of any hazardous substances or petroleum products on a property under conditions that indicate an existing release, a past release, or a material threat of a release of any hazardous substances or petroleum products into structures on the property or into the ground, groundwater, or surface water of the property."

The likely impact from storage and burning of cars and boats at the study site using petroleum-based accelerants and the presence of unknown fill materials on a former industrial site are considered an ASTM-defined recognized environmental conditions. Additionally, a significant data gap was encountered that included a lack of available information on an adjacent industrial site located at 50 Bridge Street that was listed in two potentially significant environmental databases.

Urban recommends a Phase II Environmental Site Assessment be conducted at the study site to evaluate potential impact to the property and to assess the unknown fill materials. Additional research should be conducted on the adjacent industrial site to determine whether the site is an environmental threat to the 78 Bridge Street parcel.

In addition to the above referenced recognized environmental conditions, several other environmental concerns were identified and are listed in Section 8 along with Urban's recommendations.

The conclusions contained within this report are based upon Urban's investigations and are not meant to represent the conclusions or judgments of any Federal or state agency or their representatives. If conditions at the study site change due to natural causes or other activities at or adjacent to the site, Urban requests an opportunity to review and, if necessary, modify our conclusions.

1.0 INTRODUCTION

1.1 PURPOSE

Urban Engineers of New York, P.C. (Urban) conducted this Phase I Environmental Site Assessment (ESA) for the study site located at 78 Bridge Street, North Tonawanda, New York in accordance with the recommendations of the American Society for Testing and Materials (ASTM E 1527-05) and the United States Environmental Protection Agency's (USEPA) All Appropriate Inquiries Rule. The purpose was to identify potential environmental issues at the property located at the above-referenced address.

This Phase I ESA of the subject property was completed utilizing the methodologies and resources described herein, in order to identify, to the extent feasible, "recognized environmental conditions" in connection with the site¹. This Phase I ESA is a non-intrusive desktop study and field review of environmental records and previous and present land use. It includes a historical search, environmental agency contacts, interviews, and a site reconnaissance. In addition, the presence of significant environmental features, such as floodplains and wetlands, were evaluated.

The Phase I ESA, as defined by ASTM, is not intended to include *de minimus* conditions that "generally do not present a material risk of harm to public health or the environment and that generally would not be the subject of an enforcement action if brought to the attention of appropriate governmental agencies."

1.2 SCOPE OF SERVICES

The Phase I ESA consisted of the following specific services:

- *Records Review:* A review of "reasonably ascertainable" standard record sources was conducted in order to identify "recognized environmental conditions" in connection with the property. The records review included both current and historic Federal, state and local files/documents.
- *Site Reconnaissance:* The site and surrounding area were checked in order to assess surface conditions for evidence of environmental concerns resulting from generation, transportation, usage, storage, and/or disposal of hazardous materials. Urban conducted the site reconnaissance on April 27, 2010.
- *Interviews:* These were conducted with persons knowledgeable with current and/or former uses of the property, including local government personnel.
- *Report:* Prepared the ESA report documenting the findings of the assessment.

No significant deviations from the ASTM E 1527-05 Standard were used in this Phase I ESA.

¹ Recognized environmental conditions are defined by ASTM as "the presence or likely presence of any hazardous substances or petroleum products on a property under conditions that indicate an existing release, a past release, or a material threat of a release of any hazardous substances or petroleum products into structures on the property or into the ground, groundwater, or surface water of the property".

1.3 LIMITATIONS

This Phase I ESA has been conducted by Urban in accordance with practices and procedures generally accepted in the consulting engineering field. The Phase I ESA portion of the report is based on the ASTM E1527-05 standard practice for Phase I ESAs. This report presents our knowledge of the site conditions at the time the report was prepared and is based upon information from available historical documents and records, an agency file review, on-site activities, and a visual inspection on the dates referenced. The recommendations stated in this report reflect information available and specific locations reviewed at the time of this report. Information pertaining to current site conditions is based on the conditions of the site and its surroundings at the time of the on-site reconnaissance.

This report identifies potential areas of environmental concern and presents information on the potential for contamination on the property, but does not confirm it. This report is for information only and should not be used to characterize contaminants or delineate areas of concern. A more extensive assessment (e.g., a subsurface investigation and chemical analysis of soil and/or groundwater samples) would provide for definitive information on the nature and the extent of contamination and/or areas of concern.

The report's information is further qualified as follows:

- Information, estimates, and opinions furnished to Urban were obtained from sources considered reliable and believed to be true and correct. However, Urban has made no independent investigation as to such matters and undertakes no responsibility for their accuracy.
- Information developed during the site reconnaissance was based upon visual observation of readily-accessible areas; no attempt was made to investigate behind walls and ceilings or other inaccessible areas. The site reconnaissance did not involve investigations of the subsurface or under debris piles, asphalt paving, gravel areas, or other areas that could not be reasonably inspected without the use of specialty equipment.
- Urban used its professional skill in determining possible environmental concerns but cannot provide a guarantee regarding the findings of areas of concern/hazardous materials at the site.
- Urban assumes no responsibility for matters of a legal nature affecting the property or the title thereto.
- Urban made no survey of the property. Any sketches, dimensions, capacities, quantities, or distances are approximate.

This report is for the exclusive use of the client or its representatives, and any use by other parties requires written permission from Urban.

Urban applied professional judgment in determining the extent to which the consultant complied with any given standard identified in this report or any other instrument of Urban's professional service. Unless otherwise indicated, such compliance, referred to as "general compliance,"

specifically excludes consideration of any standard listed as a reference in the text of those standards Urban has cited.

1.4 RELIANCE

This report has been prepared exclusively for the Niagara County Department of Economic Development, the City of North Tonawanda and the United States Environmental Protection Agency (USEPA) as part of the USEPA Brownfields Pilot Assessment program. It is confidential and proprietary. It may not be copied, disseminated, distributed, or disclosed by any other parties without the expressed written permission of Urban. No party other than those named in this section may rely on the information contained herein.

2.0 SITE DESCRIPTION

2.1 LOCATION AND LEGAL DESCRIPTION

The subject property is located at 78 Bridge Street, City of North Tonawanda, Niagara County, New York. The approximate 3.1-acre property is identified by the City of North Tonawanda Tax Assessment office as Tax Identification Number 184.08-1-9. The site can be found on the Tonawanda West, NY, USGS 7.5-minute Quadrangle Map at 43° 1' 36.8" north latitude and 78° 53' 1.0" west longitude². The site location is presented in Figure 1.

2.2 SITE AND VICINITY GENERAL CHARACTERISTICS

The study site is located in the central portion of Tonawanda Island. The site and surrounding area consists primarily of commercial, industrial and recreational development. The subject property is generally square shaped and is bound by Michigan Street on the west, beyond which is vacant industrial land; the Little River on the east; Thompson Street to the north, beyond which is additional industrial development, and Bridge Street to the south. Tonawanda Island contains primarily industrial and commercial properties.

2.3 GENERAL SITE HISTORY

Based on information obtained during the course of this Phase I ESA, it was determined that the site was utilized for lumber storage, boat storage and fire training purposes. A boat slip occupied a portion of the site entering the parcel on the east side of the island off of Little River. Overall, the site was utilized as part of the local lumber industry until the late 1960's. Subsequently, it was developed into the fire training ground. Property use prior to the lumber industry was reportedly for agricultural purposes.

2.4 CURRENT USE OF THE PROPERTY AND ADJOINING PROPERTIES

Presently, the site is mostly vacant; however, it was reported by the Niagara County Health Department that it is occupied annually by a group of campers that participate in a local festival. Several damaged boats and cars are currently stored on the parcel and there is a fire training tower and a mock residential dwelling on the property. The adjoining properties consist of various commercial and industrial businesses including International Filler Corporation, Taylor Devices and vacant industrial land owned by a private individual.

² Physical coordinates provided by Environmental Data Resources, Inc. (EDR).

3.0 CLIENT PROVIDED INFORMATION

3.1 TITLE RECORDS

Title search information was not provided by the client at the time of this report.

3.2 ENVIRONMENTAL LIENS OR ACTIVITY AND USE LIMITATIONS

As part of the Phase I ESA, the client requested that Urban provide the Environmental Lien and Activity and Use Limitations (AUL) Search for the study site. Urban utilized the services of Environmental Data Resources, Inc. (EDR) to provide the search information and satisfy the client's due diligence requirements.

According to the EDR Environmental Lien and AUL search results, no environmental liens or AULs were identified to be associated with the study site. Refer to Appendix G for the EDR Environmental Lien Search.

3.3 SPECIALIZED KNOWLEDGE

Mr. Chuck Bell, Planning and Development Coordinator for the Lumber City Development Corporation, is considered the client for the purposes of this report. Mr. Bell did not have any significant specialized knowledge or experience that is material to recognized environmental conditions in connection with the subject property.

3.4 COMMONLY KNOWN OR REASONABLY ASCERTAINABLE INFORMATION

Mr. Bell indicated that the site was previously utilized as a fire training facility for Niagara County and there are some concerns about the type of materials that may have been burned at the facility. Mr. Bell also indicated that the site once had a boat slip off the Little River that contains unknown fill materials.

3.5 VALUATION REDUCTION FOR ENVIRONMENTAL ISSUES

Mr. Bell indicated that the property is not being sold at this time.

3.6 OWNER, PROPERTY MANAGER, AND OCCUPANT INFORMATION

According to the City of North Tonawanda Assessment Office, the City of North Tonawanda is listed as the current owner of the subject property.

3.7 REASON FOR PERFORMING PHASE I

Urban was informed that the reason for performing the Phase I ESA is to identify potential recognized environmental conditions and concerns of the property prior to potential development.

4.0 RECORDS REVIEW

Urban conducted a search of Federal (Environmental Protection Agency), state (New York State Department of Environmental Conservation), and local (Niagara County and City of North Tonawanda) agency records in order to obtain information regarding potential environmental risks associated with the site and surrounding land. In addition, Urban utilized the services of Environmental Data Resources Inc., (EDR), a direct source of available Federal and state agency information, to investigate any potential recognized environmental conditions and other environmental concerns at the property. The following records were reviewed to investigate the site history and assist in identifying potential recognized environmental conditions and potential environmental concerns:

- Aerial Photographs
- Historic Sanborn Maps
- Historic Topographic Maps
- City Directories
- Assessment Information
- Zoning Maps
- Federal, State, and Local Environmental Records

4.1 AERIAL PHOTOGRAPHS

EDR provided aerial photographs of the study site and surrounding area for the years 1959, 1966, 1972, 1978, 1985, 1995 and 2006 for review (See Appendix B). Additionally, aerial photographs and satellite imagery were reviewed on-line at the Niagara County website, www.niagaracounty.com, and through Google Earth. The aerial photograph descriptions identify changes to the site and the surrounding lands as compared to the same photograph from the previous available year.

1959 Photograph

The site appears to be vegetated with scattered trees. A boat slip is visible entering the site from the west edge of Little River. A few roads and/or paths wind through the property. Surrounding properties to the south and west appear to contain large industrial buildings. A river appears to the east of the site and a bridge is located over this river at the current location of Bridge Street. A railroad siding may be located on the southwestern corner of the site extending from the bridge.

1966 Photograph

The site appears somewhat vegetated and now partially disturbed. The boat slip appears to have been filled in. A railroad siding is visible in the southwestern corner of the site. The remainder of the site and surrounding area appear similar to the 1959 photograph with the exception of some additional development to the north and west.

1972 Photograph

The photograph appears somewhat obscured. A larger bridge is visible north of Bridge Street and is likely the Thompson Street bridge currently located in the area, however, no other site features can be discerned.

1978 Photograph

This photograph is somewhat obscured; however, two buildings appear to be located on the study site and additional commercial and industrial development is visible to the north and west.

1985 Photograph

This photograph is obscured.

1995 Photograph

The study site in this photograph appears similar to the 1978 photograph.

2006 Photograph

The site appears generally similar to today. A dirt road is visible crossing the site from the northwest corner of the property and two buildings are located on the south side of the site. The center portion of the parcel appears to be grass or low-lying vegetation. Several cars or boats appear to be located on the west side of the site.

2008-2009 Google Earth Image

The site appears similar to the 2006 photograph and to current conditions. Boats and cars are stored along the western property line. A dirt road runs across the site from the northwest and two buildings are located on the site. Additionally, what appears to be scorched vegetation and ground staining is visible in the central portion of the western half of the site. Also, a round pond or pool of water appears to be present in the center of the grass field to the north of the two buildings.

4.2 HISTORIC SANBORN MAPS

Environmental Data Resources, Inc. (EDR) indicated that historical Sanborn® Fire Insurance Map coverage exists for the site. Sanborn® Fire Insurance Maps, that include the study site, were identified for the following years: 1886, 1889, 1893, 1910, 1951 and 1967. No maps were available for review after the year of 1967. The report from EDR, which includes copies of portions of the above listed maps, is included in Appendix E. The following table summarizes the observations made from the Sanborn® Fire Insurance Maps.

SANBORN® HISTORICAL MAPS REVIEWED	
Description of Source	Description of Site
Sanborn® Date: 1889	The study site contains a boat slip, depictions of lumber piles and a few railroad sidings in addition to a few sheds and small buildings. Industrial development including a shingle and planing mill are present on an adjacent parcel to the west across Michigan Street.
Sanborn® Date: 1893	The site and surrounding appear generally similar to the 1886 Sanborn.
Sanborn® Date: 1910	The study site generally appears similar to the 1893 photograph. Water pipes are depicted around the site and other adjacent parcels. A larger shed and a few more outbuildings are visible. Some portions of the map are illegible.
Sanborn® Date: 1951	This map is generally similar to the 1910 map. No lumber piles or buildings are present. The study site still includes the boat slip and a few railroad sidings.
Sanborn® Date: 1967	This map is similar to the 1951 map.

4.3 HISTORIC TOPOGRAPHIC MAPS

EDR provided a topographic map report for the Tonawanda West, New York Quadrangle for the years of 1899, 1901, 1948, 1950 and 1965 (see Appendix C). The topographic reports show the shape, elevation, and development of the terrain and are thus a valuable tool to document the prior use of a property and its surrounding area. Comparison of these documents to the earlier topographic maps does not indicate any significant topographic changes. A boat slip was observed protruding onto the property from the west edge of Little River adjacent to the east side of the island.

4.4 CITY DIRECTORIES

EDR provided a city directory abstract for the site and surrounding properties (see Appendix F). The EDR report indicated that city directories with information needed to search for the site were available from 1964 to 2009 and were reported in approximate 5-year increments. The study site address provided, 78 Bridge Street, was not listed in the directories. Additionally, city directories reviewed by Urban personnel at the North Tonawanda Public Library did not include listings for the site at 78 Bridge Street. Additional addresses for adjoining properties were also reviewed.

Surrounding properties included listings for various industrial and commercial properties including the International Fiber Corporation, Custom Gear and Machining, Taylor Devices, International Paper Company and the R.T. Jones Lumber/Box Company. The impact of these listings at the study site and surrounding properties is further discussed in Section 7 of this report.

4.5 STATE, FEDERAL, AND LOCAL AGENCY REVIEW³

4.5.1 EDR DATABASE SEARCH

Urban utilized the services of EDR to investigate Federal, state, and local environmental agency databases to determine if potentially hazardous sites are located, or were located, near the study area (see Appendix D).

Table 4-1 contains a summary of the Federal and state databases searched by EDR.

TABLE 4-1: EDR DATABASE SEARCH

EDR Database Searched	Description	Search Distance (Miles)	No. of Sites Located
FEDERAL			
NPL	National Priority List	1.00	0
Delisted NPL	Sites deleted from the NPL list	1.00	0
RCRIS-TSD	Resource Conservation and Recovery Information System – Treatment, Storage, and Disposal sites	0.50	0
RCRA-SQG	Resource Conservation and Recovery Information System, Small Quantity Generators	0.25	1
RCRA-LQG	Resource Conservation and Recovery Information System, Large Quantity Generators	0.25	0
RCRA-CESQG	Resource Conservation and Recovery Information System, Conditionally Exempt Small Quantity Generator	0.25	2
RCRA-Non Gen	Resource Conservation and Recovery Act, Non-Generators. Non-generators do not presently generate hazardous waste	0.25	2
CERCLIS	Comprehensive Environmental Response, Compensation, and Liability Information Systems	0.50	0
CERC-NFRAP	Comprehensive Environmental Response, Compensation, and Liability Information Systems, No Further Remedial Action Planned	0.50	3
CORRACTS	Corrective Action Report	1.00	1
FUDS	Formerly Used Defense Site	1.00	0
US Brownfields	US EPA Brownfields	0.50	9
RAATS	RCRA Administrative Action Tracking System	TP	0
HMIRS	Hazardous Materials Incident Report System	TP	0
ERNS	Emergency Response Notification System	TP	0
FINDS	Facility Index System	TP	0
TRIS	Toxic Chemical Release Inventory System	TP	0
US ENG CONT	Engineering Control Sites	0.50	0
US INST CONT	Sites with Institutional Controls	0.50	0
NPL LIENS	Liens filed by the USEPA against real property in order to recover remedial action expenditures	TP	0

³ Written requests for information and the agency responses can be found in Appendix I.

EDR Database Searched	Description	Search Distance (Miles)	No. of Sites Located
TSCA	Toxic Substances Control Act	TP	0
MLTS	Material Licensing Tracking System	TP	0
RODS	Records of Decision documents	1.00	0
CONSENT	Major legal settlements that establish responsibility and standards for cleanup at NPL sites	1.00	1
STATE or Other			
State Haz. Waste	States' equivalent to CERCLIS	1.00	4
HSWDS	Hazardous Substance Waste Disposal Site	1.00	1
State Landfill	List of all permitted landfills and their utilization	0.50	1
LTANKS	Reported leaking storage tank incidents	0.50	9
UST	Registered USTs and their contents	0.50	1
HIST LTANKS	Historic leaking underground and aboveground storage tanks	0.50	8
AST	Registered ASTs and their contents	0.25	2
CBS AST	Chemical Bulk Storage Tanks Database	0.25	0
SWRCY	Registered Recycling Facility List	0.50	1
SWTIRE	Registered Waste Tire Storage and Facility List	0.50	0
INST CONT.	Registry of Institutional Controls	0.50	1
VCP	Voluntary Cleanup Agreements	0.50	0
LAST	Reported leaking aboveground storage tanks (ASTs)	0.25	
Unreg LTanks	Unregulated Tanks Cases	0.50	
HIST UST	Historical Bulk Petroleum Storage Database	0.25	2
HIST AST	Historic Above Ground Storage Tanks	TP	0
Manifest	Hazardous Waste Manifest Information	0.25	6
NY Spills	Spills Database	0.125	1
NY Hist Spills	Historical Spills Database	0.125	0
ERP	Environmental Restoration Program Listing	0.50	0
Brownfields	Brownfield Sites	0.50	0
CBS	Chemical Bulk Storage Site Listing	0.25	0
FTTS	FIFRA/ TSCA Tracking System - FIFRA (Federal Insecticide, Fungicide, & Rodenticide Act)/TSCA (Toxic Substances Control Act)	TP	0
Hist FTTS	FIFRA/TSCA Tracking System Administrative Case Listing	TP	0
ICIS	Integrated Compliance Information System	TP	0
PADS	PCB Activity Database System	TP	0
AIRS	Permit and Emissions Inventory Data	TP	0
E Designation	Air Emission Data	0.125	0
EDR REC.			0
Manufactured Gas Plants		1.00	1

Note: Positive EDR database search listed in **bold**

Review of the EDR report indicates that the study site property is not listed in the databases searched. However, 20 databases contained files related to additional sites located within a 1.00 mile radius of the study (indicated in **bold**).

A total of approximately 53 database hits were identified in the EDR database report within the search radii listed in the table above. Of those 53 sites, several sites are considered to be within a short distance of, and/or upgradient of, the target property and warrant further discussion. It should be noted that one site may be listed under several different names, databases or companies. Sites that may have a potential impact to the study site property are listed below.

TABLE 4-2: LIMITED EDR DATABASE SUMMARY

Property Name and Address (Olean, NY)	Distance from Study Site	Database and Listing	Comments
Taylor Devices 200 Taylor drive	< 1/8 mile	RCRA –SQG FINDS MANIFEST	RCRA and MANIFEST information recorded. Informal written violations from State of New York.
International Fiber Corporation 50 Bridge Street	<1/8 mile	NY Spills RCRA-CESQG FINDS MANIFEST	Known Environmental Issues at this address reported under International Paper/Tonawanda Mill. Also RCRA-CESQG, no violations noted.
International Paper/Tonawanda Mill 50 Bridge Street	<1/8 mile	CERC-NFRAP HSWDS	EPA Archive Site with No Further Remedial Action Planned – No further information available.
North Tonawanda Water Department 1 Archer Street	1/8-1/4 mile	LTANKS HIST LTANKS HIST UST	Known Environmental Issues including leaking tanks and existing USTs. Some issues handled by Niagara County Health Department.

Sites were reviewed or discussed during the state, and local file reviews and/or during the site reconnaissance to determine the potential for environmental impact to the study area. Potential impacts are based on the potential of soil, groundwater, and/or surface water contamination at the sites and the potential for contaminant migration using surface characteristics and the estimated direction of groundwater flow.

In addition to the above mentioned properties, 28 sites were identified by EDR as unmapped orphan sites due to poor or inadequate address information. Urban reviewed the names of the listed orphan sites and attempted to locate the properties using the addresses or other information provided. The orphan sites that included some location information were either far enough away or down gradient of the subject property and are therefore not considered an environmental concern.

4.5.2 EPA FILE REVIEW

A Freedom of Information Request was submitted to the Freedom of Information Officer for EPA Region 2 for information pertaining to the study site located at 78 Bridge Street, North Tonawanda, New York and immediately surrounding properties. The EPA Region 2 Office

responded to the FOI request and indicated that no records were found. Copies of the FOI Request and EPA response can be found in Appendix I.

4.5.3 STATE FILE REVIEW

A Freedom of Information Law (FOIL) request for records pertaining to the study site and adjoining properties was submitted to the New York State Department of Environmental Conservation (NYSDEC). A letter received on April 30, 2010 stated that no records were on file with the NYSDEC pertaining to the study site or limited surrounding properties. Copies of the FOIL Request and NYSDEC response can be found in Appendix I.

NYSDEC representatives in the Petroleum Bulk Storage and Remediation Programs were contacted by telephone for additional information pertaining to the study site. NYSDEC representatives searched the NYSDEC database for the study site and surrounding properties located on Bridge Street, Michigan Street and Detroit Street and did not locate any files pertaining to environmental issues at or around the study site.

The New York Spill database was searched on-line for the above referenced street names. Spills identified in the area are referenced in the EDR report located in Appendix D.

4.5.4 DEPARTMENT OF ENVIRONMENTAL HEALTH

A Freedom of Information Law (FOIL) request for environmental records pertaining to the study site and adjoining properties was submitted to the Niagara County, New York, Department of Environmental Health. Mr. Paul Dickey, P.E. stated that the health department did not have any records pertaining to the study site or the immediately surrounding properties. Mr. Dickey did state that the health department has a North Tonawanda file arranged in chronological order that contains information on the entire city of North Tonawanda. This file is not considered practically reviewable in accordance with ASTM E 1527-05. Copies of the FOIL request and the Environmental Health Department response can be found in Appendix I.

4.5.5 ENGINEERING DEPARTMENT

The City of North Tonawanda Engineering Office was contacted in person and provided information pertaining to the study site. Mr. David Maziarz, Junior Engineer, indicated that the Engineers Office does not maintain any files relating to environmental issues. He stated that he was not aware of any environmental concerns at the study site or in the area except that International Paper Corporation was once located on Tonawanda Island.

4.5.6 PROPERTY ASSESSMENT INFORMATION

The City of North Tonawanda Assessment Office identifies the subject site as tax parcel: SBL# 184.08-1-9. The current owner of the parcel is the City of North Tonawanda. Historical assessment cards were identified and reviewed at the Assessment office. Assessment information indicated that the site is 3.1 acres and was utilized as a fire training facility. The

owner was listed on the historic assessment card as the County of Niagara. Ownership information indicates that the parcel was transferred from the City of North Tonawanda to Niagara County in 1966 and back to the City in 2008. Ownership records prior to 1966 were not available.

The cards state that a fire training tower (21 ft. x 21 ft) and fire training building (32 ft. x 16 ft.) constructed circa 1970 are located on the property. The current owner is listed as the City of North Tonawanda.

Additionally, the Assessment Office reviewed their records for potential environmental issues and provided an extensive list of parcels reviewed. The Assessment Office indicated that records for properties along Bridge Street, Michigan Street, Archer Street, Detroit Street and Taylor Drive were searched and indicated that no USTs were identified at the study site or on an immediately adjacent property. The files did state that a septic tank was on a plumber's list for the 78 Bridge Street site with no record of it being filled or removed.

4.5.7 BUILDING INSPECTION/PERMIT DEPARTMENT

The City of North Tonawanda Building Inspection Office was visited to review pertinent records associated with the study site. No permits or building inspection records were identified for 78 Bridge Street.

4.5.8 ZONING

The City of North Tonawanda Building Department provided zoning data for the study site. Zoning is a designation that indicates how a specific area can be used and developed within a city zoning district. Zoning districts are established to promote and protect similar types of development (i.e., commercial, industrial, single family homes, multi-family homes, etc.). According to a zoning representative, the property is currently Zoned WD – Waterfront District.

4.5.9 FIRE DEPARTMENT

The City of North Tonawanda Fire Department was contacted to obtain emergency response, hazardous material and storage tank information. The Fire Department maintains records of USTs and ASTs within city limits. A Fire Department representative indicated that the fire department has no records indicating any emergency response or USTs/ASTs at the study site under the address of 78 Bridge Street. A written request for information pertaining to the study site and surrounding properties was submitted to North Tonawanda Fire Department Chief Krantz. Chief Krantz was contacted by telephone and indicated that the fire department does not have any records of emergency response or UST/hazardous substances for the study site.

Chief Krantz stated that he was the Municipal Training Officer for the City of North Tonawanda and was involved in the operations of the training facility for a number of years. Chief Krantz provided the following information:

- The fire training facility held controlled burns of cars and boats in the grass area in the center of the site.
- He was not aware of any USTs located at the study site or any environmental issues associated with hazardous substances except for those otherwise stated.
- Two fire pits on the property were utilized for training fire personnel on how to handle petroleum fires. The pits were filled with water at the time of the site visit.
- Gasoline and diesel fuel were used as accelerants.
- A common fill material used in the 1960's and 1970's in North Tonawanda was a slag material from the Tonawanda Iron Works. Chief Krantz speculated that the former boat slip may have been filled with this material.

4.6 PHYSICAL SETTING

ASTM E 1527-05 focuses on releases of hazardous materials and petroleum products and does not require an evaluation of so-called “non-scope considerations” such as wetlands, asbestos, lead-based paint, floodplains, etc. Nevertheless, some of these non-scope considerations are often of interest to the property owner and/or buyer.

Site geology was investigated through a review of available information from the U.S. Department of Agriculture, the Geologic Map of New York, the USGS 7.5 minute series topographic map of Tonawanda West, NY, groundwater, bedrock geology, and surface geology maps.

4.6.1 SITE HYDROLOGY AND GEOLOGY

Surface Water and Groundwater Characteristics

The United States Geological Survey (USGS) Topographic Gradient for the site and surrounding area, determined from the USGS 1 Degree Digital Elevation Model provided by EDR, is generally southwest. The approximate elevation of the site is 571 feet above sea level.

During the site reconnaissance, the topography was observed to be generally flat with a gentle slope down from north to south and west to east. The surface water at the site appears to ultimately drain, via sheet flow, toward a drainage ditch running west to east across the parcel to the north of the fire training buildings. Ultimately, the surface water from the site flows into the Little River. Although hydrogeologic data for the site is not available, the water table on small river islands typically flows in the direction of the river and would likely flow to the north.

Geological Characteristics

Geologically, the bedrock at the study site dates back to the Upper Silurian Period of the Paleozoic Era, approximately 408-438 million years ago. According to the New York Geologic Survey, the bedrock at the study site is:

Camillus, Syracuse and Vernon Formations: Formations consist of shale, dolostone, salt and gypsum.

According to the EDR Report and the Natural Resource Conservation Service online information and Websoil service, this area of Niagara County does not have soil data available.

Flood Plains

EDR provided FEMA Flood Zone data for the study site, Community Panel #3605080003B was reviewed. The data indicates that a portion of the eastern half of the site is located within a flood zone.

Wetlands

The National Wetlands Inventory (NWI) Map, Tonawanda West, NY Quadrangle, was reviewed. The NWI map indicates that wetlands may be located on the eastern edge of the site immediately adjacent to Little River.

4.6.2 RADON

Radon information related to the general area was reviewed in the Environmental Database Report received from Environmental Data Resources, Inc. According to the Database Report, the Environmental Protection Agency (EPA) classifies Niagara County as “Zone 2”, an area with an indoor average level of > 4.0 pCi/L. Four (4.0) pCi/L is the level at which the EPA mandates that corrective action be taken.

Federal Area Radon information for Niagara County New York indicates that 177 sites within Niagara County were tested for radon and produced results with 5% of sites above 4.0 pCi/L in basement areas and 2% of sites above 4.0 pCi/L in living areas. The NY State Radon Database indicates that a total of 175 sites within the 14120 zip code have been tested for radon producing results with 5.7% of sites above 4.0 pCi/L.

4.7 DATA FAILURE

According to ASTM E 1527-05, data failure occurs when all of the standard historical sources (documented in the standard) that are reasonably ascertainable and likely to be useful have been reviewed and yet the objectives have not been met. Data failure is one form of a data gap. The following standard historical sources were reviewed but did not provide information necessary to determine previous uses of the property back to 1940 or the earliest developed use.

Local Street Directories:	Directories including relevant information were not available prior to 1905.
Aerial Photographs:	Aerial photographs for the site prior to 1959 were not identified.
Fire Insurance Maps:	Sanborn Fire Insurance Maps depicted development at the study site on the earliest map available.

Title Records/Assessment: Historical assessment information did not provide the past uses of the site back to its first developed use.

Historical Maps: Historical topographic maps were identified back to circa 1899; however, the study site was known to be developed at this time.

Building Inspection/Zoning: Building inspection, permit information and zoning data did not identify past uses of the study site back to its first developed use.

The earliest, reasonably ascertainable standard historical sources reviewed did not identify past uses of the property back to its first developed use. Based on this information, an ASTM 1527-05 defined data failure has occurred. The impact of this data failure will be further discussed in Section 7.2.

5.0 SITE RECONNAISSANCE

Urban personnel conducted the site reconnaissance on April 27, 2010 to observe surface conditions for potential environmental concerns at the approximate 3.1-acre site located at 78 Bridge Street. The site reconnaissance consisted of a “walk over,” during which interior structure features and exterior land features were observed. General observations related to the site and surrounding grounds were noted. Photographs taken during the site visit are located in Appendix A.

Possible target items investigated during the site reconnaissance included, but were not limited to: the presence of regulated substances; transformers which may contain polychlorinated biphenyls (PCBs); potential asbestos containing materials; evidence of dumping and/or waste disposal; fill pipes which may indicate underground storage tanks; spills; odors; ground discoloration; unusual vegetation growth pattern; etc.

5.1 SUBJECT PROPERTY AND SURROUNDING PROPERTY USE

The study site currently consists of a 3.1-acre parcel of land situated on Tonawanda Island in North Tonawanda, New York. The site is generally characterized as a grass field with scattered trees along the eastern and southern property lines. A fire training tower and mock residential dwelling are located at the site. A gravel road leads from the northwestern corner of the site toward a paved area surrounding the buildings. Chain link fencing surrounds the property with a gate located off Thompson Street. The eastern edge of the parcel abuts the Little River. A manhole was observed in the southeast quadrant of the site.

Adjacent properties are currently utilized for industrial purposes. Several boats are currently stored on the parcel between the study site and Thompson Street. A Taylor Devices test facility is located on the adjacent parcel to the west and additional Taylor Devices property is located to the north of the site across Thompson St. Corporate offices for International Filler Corporation are located to the south across railroad tracks running parallel to the southern property line of the study site. These tracks are adjacent to Bridge Street and appear to have once contained a siding that ran across the western portion of the 78 Bridge Street parcel.

Utilities available in the vicinity of the site include: Water and sewer provided by the City of North Tonawanda, electricity provided by National Grid, and natural gas provided by National Fuel Gas.

5.2 BUILDING AND GROUNDS INSPECTION

Urban inspected the grounds during the site walk (refer to Appendix A for site photographs taken during the site visit).

The site is generally flat with a gentle slope down from west to east and north to south.

The buildings on the property were formerly part of the fire training facility and are characterized as concrete or masonry block structures. The fire training tower is a five story building with internal stairways and an exterior metal stairway on the north side of the structure. The fire training building is a mock residential dwelling with a ground floor, basement and open attic. A portion of the fire training tower was not accessible during the site visit.

Hazardous Substances and Petroleum Products

An approximate 250-gallon above ground storage tank was also observed. It did not appear that the tank was full but the contents and quantity are unknown.

Underground Storage Tanks (USTs)

No indications of USTs were noted during the site visit.

Above Ground Storage Tanks (ASTs)

One, approximate 250-gallon AST was observed at the site. No leaks or ground staining were observed around the tank. The contents and quantity of liquid in the tank could not be determined.

Odors

No significant odors were noted during the site visit.

Pools of Liquid

A round, ringed possible fire pit was observed in the center of the site. It was filled with about one foot of water and was enclosed by a wood fence. Additionally, a rectangular shaped, open, in-ground concrete structure was observed to the west of the potential fire pit. It appeared to contain water, sludge and debris.

Fill Materials

An area known to contain fill materials was observed during the site visit. The fill material is located in the central portion of the site in the area of the former boat slip. The quantity and origin of the fill is unknown.

Drums/Containers

A container labeled as firefighting foam was observed on the property. A drum labeled as kerosene was observed on the south side of the fire training building. The drum appeared empty and no leaks or ground staining was observed. A few rusted drums were observed inside the mock house. A rusted drum was observed along the southern fence line of the property. The contents of this drum, if any, are unknown.

Polychlorinated Biphenyls (PCBs)

One pole-mounted transformer was observed along the northern property line. The transformer appeared in fair condition and no ground staining was observed in the area.

Surface Waters

See the Pool of Liquid section above.

Utilities

A fire hydrant and line hook-up were observed at the site. A utility pole was also observed in the center of the site with overhead lines leading from the pole north to a utility pole on the adjacent parcel to the north.

Stained Floors/Walls, Pavement, Soils

Some potential soil staining was observed around the gravel road and boat and car storage area.

Distressed Vegetation/Absence of Vegetation

A few small areas of sparse grass growth were observed.

Solid Waste, Trash, Surface Debris

Damaged boats and cars, partially burned boats, pallets, furniture and other miscellaneous items were observed in the structures and around the site.

Wells

No wells were observed during the site visit.

Drains/Sumps

A sump and sump pump was observed inside basement area of the mock residential structure.

Septic Systems

No indications of septic systems were observed on the property during the site visit. It should be noted that the City of North Tonawanda Assessment Office indicated that there may be an existing septic system still located at the site.

Mold

No mold was observed during the site visit.

Suspect Asbestos Containing Materials

Suspect asbestos containing materials observed during the site visit included, but were not limited to, doors, ceiling panels and possibly, roofing materials on the existing fire training structures.

Potential Lead-Based Paints

Limited painted surfaces were observed on the structure, however, based on the age of the structures, lead-based paint may be present.

Wetlands

Suspect wetlands were observed along the bank of the Little River during the site visit.

6.0 INTERVIEWS

6.1 INTERVIEW WITH CURRENT OWNER/KEY SITE MANAGER

Mr. Dale Marshall, North Tonawanda City Engineer, was identified as the Owner's representative and Key Site Manager per ASTM E 1527-05.

Mr. Marshall stated that he was not aware of any specific environmental issues at the study site and that, to his knowledge, hazardous materials were not stored, used or disposed on the subject property with the exception of the petroleum-based accelerants and burning at the site. Mr. Marshall further indicated that he was not aware of any USTs currently or historically located at the site. Additionally, Mr. Marshall was not aware of any environmental issues with the surrounding properties. Mr. Marshall's Phase I ESA Questionnaire has not yet been received.

6.2 INTERVIEW WITH LOCAL HISTORIANS

Mr. Peter Trinkwalder, North Tonawanda City Historian, was interviewed by telephone. Mr. Trinkwalder was familiar with the study site and stated that it was formerly part of the lumber processing operations on the island. He stated that the site once had a boat slip and lumber docks that were used for shipping purposes. Mr. Trinkwalder was not aware of any specific environmental issues at the study site or on adjoining properties. Mr. Trinkwalder indicated that the use of the island prior to the lumber industry was for agricultural purposes.

6.3 INTERVIEW WITH PAST OWNER/OCCUPANT

Mr. John Cecula, Niagara County Fire Coordinator, was contacted by telephone for information pertaining to the study site and the immediately surrounding area. Niagara County was the owner of the study site parcel from 1966 to 2008. Mr. Cecula indicated that he was familiar with the fire training facility operations and provided the following information:

- The facility was used by the City of North Tonawanda Fire Department and other Niagara County volunteer fire departments.
- Gasoline and diesel fuel were used as accelerants for burning cars, boats and class A materials such as paper, cardboard and wood.
- He was not aware of any environmental issues at the site except for those that may be associated with the burning at the site.
- The pits in the ground observed during the site visit were used to train for petroleum fires. Water was placed in the container and a petroleum liquid was spread on top of the water and ignited. Mr. Cecula believed the pits were lined with steel or concrete.

6.4 INTERVIEW WITH LOCAL GOVERNMENT OFFICIALS OR OTHERS

Mr. Chuck Bell, Lumber City Development Corporation, was interviewed in person and by telephone. Mr. Bell indicated that he is familiar with the study site and is not aware of any specific environmental issues at the property or in the immediately surrounding area. He stated

that the site has been used for fire training operations for the last 30 to 40 years and the City of North Tonawanda believed that there are some potential environmental issues associated with the unknown fill materials used to fill in the boat slip and the potential impact from years of controlled burns at the site. He stated that cars and boats were burned at the property.

Mr. Paul Dickey, P.E., Niagara County Health Department, was contacted for information pertaining to the subject site and surrounding properties. Mr. Dickey stated that he is not personally familiar with the property but is somewhat familiar with the area. He indicated that he was not aware of any specific environmental issues at or around the study site. Mr. Dickey stated that most of the businesses that were historically located on Tonawanda Island were out of business before Niagara County started keeping records. Mr. Dickey did provide information indicating that the study site property may be used annually as a temporary campground during the Canalfest that takes place in North Tonawanda.

North Tonawanda Fire Chief Joseph Krantz was contacted by telephone regarding emergency responses, hazardous substances and USTs at the site. Chief Krantz provided information regarding the study site and surrounding properties that is documented in Section 4.5.9.

7.0 FINDINGS

This section summarizes whether known or suspected environmental conditions related to the subject site are present based on the previously described records review, interviews, and site reconnaissance. The following is a list of each ESA task and the findings identified during the ESA effort. Urban's opinion of the significance of these environmental conditions is also presented. Refer to Section 8 for Urban's conclusions and recommendations.

TABLE 7-1: ENVIRONMENTAL CONDITIONS FINDINGS/OPINION

ESA Task	Potential Environmental Concerns?	Opinion
Client Provided Information	The client provided information indicating that unknown fill materials were placed at the site in the late 1960's or early 1970's and cars and boats were once burned on the property as part of the fire training facility.	The unknown fill materials placed at the site and the potential impact from the burning of cars and boats using petroleum based accelerants is considered an ASTM-defined recognized environmental condition.
Records Review		
- Aerial Photographs, Historic Maps, Sanborn Maps, and City Directories	<p>1. Past uses of the site dating back to its initial development could not be determined from a review of the listed sources.</p> <p>2. The site once had a boat slip entering from the Little River that appears to have been filled.</p>	<p>1. Historical sources indicated that the agricultural industry was the first developed use on Tonawanda Island. Based on this information, the past uses of the site prior to the lumber industry are not considered a significant environmental concern.</p> <p>2. The boat slip was reportedly filled with unknown fill materials. The presence of unknown fill materials in an industrial area is considered an ASTM-defined recognized environmental condition.</p>
- Agency records (EDR Database)	The EDR Report listed several surrounding properties in multiple databases indicating potential environmental concerns.	<p>International Paper/Tonawanda Mill with an address of 50 Bridge Street was listed in the CERC-NFRAP and HSWDS databases. Attempts were made to determine the nature of the listings; however, no information was available. This issue is considered a potentially significant environmental concern and significant data gap. Refer to Section 7.2 for additional information pertaining to the data gap.</p> <p>Based on the physical locations and/or elevations of the remaining sites in</p>

ESA Task	Potential Environmental Concerns?	Opinion
		relation to the study site and/or a lack of any recorded violations in the EDR report, the remaining reported sites are not considered a significant environmental concern.
- State file review	NYSDEC did not have any records on file for the study site or surrounding properties.	NA
- Local file reviews	A septic system may still be located on the property.	The potential presence of a septic system on a former industrial property may be an environmental concern.
- Physical setting	<ol style="list-style-type: none"> 1. The Environmental Database Report indicates the potential for elevated Radon levels in the regional vicinity of the subject site. 2. Review of the United States Department of Housing and Urban Development Flood Insurance Rate Map (FIRM) for the subject site indicates that a portion of the study site is located within a flood plain. 3. Wetlands along the river bank were identified in the EDR report and on NWI wetland maps. 	<ol style="list-style-type: none"> 1. Radon is not defined in ASTM 1527-05 as a recognized environmental condition; however, it is an environmental concern that should be addressed. 2. Flood zones are not defined in ASTM 1527-05 as a recognized environmental condition, however; it is an environmental concern that should be addressed. 3. Wetlands are not considered ASTM-defined recognized environmental conditions; however, they are an environmental concern that should be addressed.
Site Reconnaissance	<p>The following items of concern were noted during the site visit:</p> <ol style="list-style-type: none"> 1. Suspect Asbestos Containing Materials (ACM) 2. Potential lead-based paint 3. Ground staining and lack of vegetation 	<p>1/2. Suspect ACMs and lead-based paints are not defined in ASTM 1527-05 as “recognized environmental conditions”, but are environmental concerns that should be addressed if future demolition or remodeling of the structure is planned.</p> <p>3. Ground staining and lack of vegetation were observed at the site and may be due to the previous burning of cars and boats on the property. The potential impact to the</p>

ESA Task	Potential Environmental Concerns?	Opinion
	<p>4. Burn pits filled with water</p> <p>5. Damaged cars and boats stored on the property</p> <p>6. Drum labeled as kerosene observed on the south side of the building and unlabeled drum along fence. Drums observed inside the structures</p> <p>7. Pole-mounted transformer on adjacent property</p> <p>8. AST observed at the site. No ground staining or leaks were observed in the area of the tank.</p>	<p>soil and groundwater at the site from this burning is considered a recognized environmental condition.</p> <p>4. The burn pits are reportedly lined with concrete or steel; however, petroleum products may have potentially impacted the study site in these areas and the potential impact around these burn pits is considered an ASTM-defined recognized environmental condition.</p> <p>5. The damaged cars and boats stored at the site could potentially release petroleum products and hazardous substances into the soil and groundwater. This issue is considered a significant environmental concern.</p> <p>6. The drum labeled kerosene appeared to be empty and no ground staining or leaks were observed. The presence of this drum is not a significant environmental concern. The unlabeled drum along the fence is a potential environmental concern.</p> <p>7. The transformer appeared in good condition and no leaks or ground staining was observed. This is not considered a significant environmental concern.</p> <p>8. The AST by itself is not considered a significant environmental concern; however, it is an environmental concern that should be addressed.</p>
Interviews	Several interviewees indicated that the site has been used as a fire training facility. Boats and cars were burned at the site using petroleum based accelerants and burn pits were filled with water and petroleum based liquids for training purposes.	The potential impact from the burning of cars and boats using petroleum based accelerants is considered an ASTM-defined recognized environmental condition. Refer to Section 8 for Urban's conclusions and recommendations regarding this issue.

7.2 DATA GAPS

A data gap is the inability to obtain information required by ASTM E 1527-05, despite “good faith” efforts, which is needed to identify recognized environmental conditions.

A data failure has been documented in Section 4.7 indicating that the past use of the site could not be determined back to its first developed use. However, information obtained during the course of this Phase I ESA indicates that the study site and the immediately surrounding area were originally developed for agricultural purposes. This data failure is not considered a significant data gap in accordance with the ASTM standard.

Data Gap: Information on the International Paper site listed in the EDR report at 50 Bridge Street under the CERC-NFRAP and HSWDS databases could not be reasonably ascertained during the course of this Phase I ESA. This International Paper property is a potential environmental concern that could impact the study site and additional information should be obtained to further investigate the site and determine the reasons for the database listings. This issue is considered a significant data gap. Refer to Section 8 for Urban’s recommendations for handling this matter.

8.0 CONCLUSIONS AND RECOMMENDATIONS

Urban has performed a Phase I Environmental Site Assessment in conformance with the scope and limitations of ASTM Practice E 1527-05 and the EPA All Appropriate Inquiries Rule for the property located at 78 Bridge Street. Any exceptions to, or deletions from, this practice are described in this report.

This assessment has revealed evidence of “recognized environmental conditions” in connection with the property. A recognized environmental condition is defined by ASTM as “the presence or likely presence of any hazardous substances or petroleum products on a property under conditions that indicate an existing release, a past release, or a material threat of a release of any hazardous substances or petroleum products into structures on the property or into the ground, groundwater, or surface water of the property.”

Unknown Fill Materials/Burning and Storage of Cars and Boats/Burn Pits

The presence of unknown fill materials on an industrial site and the storage and burning of cars and boats using petroleum-based accelerants are considered recognized environmental conditions that warrant further investigation. Urban recommends a Phase II Environmental Site Assessment including a soil and groundwater investigation be conducted to assess potential impacts to the study site.

Data Gap

The International Paper site listed in the EDR report under the CERC-NFRAP and HSWDS databases should be further investigated to determine the cause for these listings and the potential impact to the study site.

In addition to the investigation of recognized environmental conditions, Urban inspected the property for potential environmental concerns within the parameters of the scope defined in Section 1.1, 1.2 and 1.3 of this report. The environmental issues identified in this investigation are discussed below:

- **Septic System**
A septic tank may still be located at the study site. Additional investigation is recommended to determine if the tank and leach field are still located at the site and, if so, attempt to identify the location. If the tank is located, it should be properly closed in accordance with applicable regulations.
- **Suspect Asbestos Containing Materials (ACM):** Suspect ACMs were identified during the site visit. If the existing buildings are planned to be demolished or renovated, an Asbestos Building Inspection should be conducted to positively identify asbestos containing materials prior to building demolition/renovation.
- **Potential Lead-Based Paint:** If the existing buildings are planned to be demolished or renovated, a Lead-Based Paint Inspection should be conducted to positively identify lead-based paint prior to building demolition/renovation.

- **Radon:** Elevated radon concentrations were reported in the Environmental Database Report in the vicinity of the subject property. Any proposed future buildings at the site should be constructed to reduce the potential of radon gas entering the subsurface areas (basements).
- **Drums:** Drums at the site should be further investigated. If there is no current or planned use for the drums, they should be removed from the site and disposed in accordance with applicable regulations. Any unknown liquids in the drums should be sampled, analyzed and disposed in accordance with applicable regulations.
- **AST:** The AST at the site should be kept in a containment area. If it not currently used, it should be properly removed from the site.
- **Floodplains and Wetlands**
Floodplains and wetlands were identified at the study site. The client should be aware that specific regulatory and permitting requirements or restrictions may apply to development within floodplains and wetlands. A wetland delineation is recommended prior to development that may impact the river bank.
- The study site property was developed with historical industrial facilities prior to regulatory oversight and current tank registration requirements. It is possible that USTs may be located at the study site that have not been identified through the Phase I ESA process. The potential exists that USTs not previously identified may be encountered during future construction and/or demolition activities. No specific recommendation is being made regarding this potential concern; however, it is an issue that the owner should be aware of prior to site development.

9.0 REFERENCES

1. Environmental Data Resources, Inc.
3530 Post Road
Southport, Connecticut 06490
2. Niagara County Government Offices
Health Dept., Fire Coordinator, Public Works
59 Park Avenue
Lockport, New York
3. City of North Tonawanda
City Hall
North Tonawanda, New York
4. New York Department of Environmental Conservation
Region 9
270 Michigan Avenue
Buffalo, New York 14203
5. North Tonawanda Public Library
Meadow Street
North Tonawanda, New York
6. Geologic Map of New York
New York Geologic Survey
Room 3099 CEC
Albany, New York
7. Tonawanda West, NY 7.5' Quadrangle Topographic Map
United States Department of the Interior
United States Geological Survey
USGS National Center
12201 Sunrise Valley Drive
Reston, Virginia 20192
8. North Tonawanda History Museum
314 Oliver Street
North Tonawanda, New York

10.0 QUALIFICATIONS OF ENVIRONMENTAL PROFESSIONALS


This report was prepared by Adam R. Kupfer and Korin M. Giles. For the purpose of this report, Ms. Giles is considered the Environmental Professional as defined in §312.10 of 40 CFR 312.

Mr. Kupfer is an Environmental Scientist with 12 years of experience in the construction inspection and environmental consulting fields. Mr. Kupfer has performed several Phase I ESAs and has experience in soil and groundwater studies, asbestos investigations and materials testing. He holds a Bachelor's degree in Specialized Studies with a concentration in Geology from Edinboro University. Mr. Kupfer is a Commonwealth of Pennsylvania and New York State Licensed Asbestos Building Inspector.


Ms. Giles has over 19 years of environmental consulting experience during which she has conducted and/or supervised hundreds of Phase I ESAs, Phase II subsurface investigations, site remediation projects and asbestos investigations. She holds a Bachelor of Science in Biology from Gannon University and is currently enrolled in their Graduate Program where she is pursuing a Masters of Science in Environmental Health, Safety and Engineering. Ms. Giles is licensed by the Commonwealth of Pennsylvania as an Asbestos Building Inspector/Management Planner.

I declare that, to the best of my knowledge and belief, I meet the definition of Environmental Professional as defined in §312.10 of 40 CFR 312.

I have the specific qualifications based on education, training, and experience to assess a property of the nature, history, and setting of the subject property. I have developed and performed the all appropriate inquiries in conformance with the standards and practices set forth in 40 CFR Part 312 and ASTM 1527-05.



Korin M Giles
Environmental Practice Leader


Adam R. Kupfer
Environmental Scientist

APPENDIX G

PROJECT PERSONNEL QUALIFICATIONS



Chris Hirschmann, CHMM

Director, Site Investigation & Remediation Services

EDUCATION:

B.S. Environmental Science, Cornell University

M.S., Environmental Science, NJIT – Rutgers University

CERTIFICATION:

OSHA 40-Hour HAZWOPER

OSHA HAZWOPER Supervisor

OSHA 10-Hour Construction

Certified Hazardous Materials Manager (CHMM) #14701

NJDEP Subsurface Evaluator #572258

Hazardous Waste Management Certification

Site Remediation Basics Certification

New York City Office of Environmental Remediation (NYCOER) Brownfield Certification (TurboTraining)

OSHA 30-Hour 1910 General Industry Training

YEARS OF EXPERIENCE:

With Hillmann: 12

Total: 14

PROFESSIONAL EXPERIENCE:

Mr. Hirschmann is currently the Director, Site Investigation & Remediation Services at Hillmann Consulting, LLC. As such, he is responsible for managing and implementing soil, groundwater, and soil vapor subsurface investigations and remediation; regulatory compliance; storage tank closure and install; and third party document review.

Mr. Hirschmann has extensive experience in evaluating and investigating sites for subsurface contamination and instituting remedial activities for commercial and industrial properties (including City & State regulatory & brownfield programs). He also performs SPCC plan preparation and hazardous materials management; and performs Phase I environmental site assessments to meet due diligence requirements under CERCLA, including the quality assurance of technical reports.

Representative experience includes:

The Doe Fund, Bronx, NY:

Identified as a spill case with confirmed soil, groundwater and soil/vapor contamination with the New York State Department of Environmental Conservation (NYSDEC) and brownfield and e-designation site with New York State Office of Environmental Remediation (NYCOER). Mr. Hirschmann functioned as the project director for Hillmann and prepared the remedial investigation work plan (RIWP), conducted remedial investigation activities and prepared a Remedial Investigation Report (RIR). Based on the RIR Hillmann prepared a Remedial Action Work Plan (RAWP) that was subsequently approved by the NYSDEC and NYCOER. Under the direction of Mr. Hirschmann, Hillmann provided oversight and direction of remedial activities, including implementation of a Community Air Monitoring Plan, during site redevelopment activities.

Women in Need, Brooklyn, NY:

Identified as an e-designation and brownfield case with soil and soil/vapor contamination with NYCOER. Mr. Hirschmann functioned as the project director for Hillmann and prepared the remedial investigation work plan (RIWP), conducted remedial investigation activities and prepared a Remedial Investigation Report (RIR). Based on the RIR Hillmann designed and prepared a Remedial Action Work Plan (RAWP) that was subsequently approved by the NYCOER. Under the direction of Mr. Hirschmann, Hillmann provided oversight and direction of remedial activities during site redevelopment activities.

TLK Manor, Bronx, NY:

Identified as a contaminated property under the purview of NYCDEP, Hillmann provided investigation and remediation services related to redevelopment activities. Mr. Hirschmann functioned as the project director and conducted the remedial investigation and prepared a Remedial Action Work Plan based on the results of the soil, groundwater and soil/vapor investigation. During redevelopment



activities, under the direction of Mr. Hirschmann, Hillmann provided oversight and direction of remedial activities including implementation of a Community Air Monitoring Plan.

BP Real Estate Fund, Queens, NY

Hillmann was retained to address the e-designation on the property for hazardous materials prior to redevelopment activities. Mr. Hirschmann functioned as the project director and prepared a Remedial Investigation Workplan, conducted the Remedial Investigation soil, groundwater and soil vapor sampling activities and issued the Remedial Investigation Report to the NYCOER. The NYCOER subsequently removed the e-designation from the property after review and approval of project documents.

AIG, Bernardsville, NJ:

The Property had a leaking underground storage tank (UST) identified as a spill case with the New Jersey Department of Environmental Protection (NJDEP) and contained widespread soil and groundwater contamination. Hillmann provided investigation and remedial activities at the site including: delineation of soil and groundwater contamination, preparation of remedial action plans for the NJDEP, enhanced fluid recovery for groundwater remediation, injection remediation of groundwater including chemical oxidation material and microbe material to break down and remediate the elevated contaminants found in the groundwater. Mr. Hirschmann was the project manager and NJDEP certified Subsurface Evaluator for the remedial activities.

City of Newark, New Jersey:

Hillmann provided investigation and remediation activities for five City owned brownfield properties. Mr. Hirschmann functioned as the project manager for oversight, design, implementation and management of soil and groundwater remedial investigations at the properties.

Unique People Services, Bronx, New York

Identified as a contaminated property under the purview of NYCDEP, Hillmann provided investigation and remediation services related to redevelopment activities. Mr. Hirschmann functioned as the project director and conducted the remedial investigation and prepared a Remedial Action Work Plan based on the results of the soil, groundwater and soil/vapor investigation. During redevelopment activities, under the direction of Mr. Hirschmann, Hillmann provided oversight and direction of remedial activities including implementation of a Community Air Monitoring Plan.

Notias Construction, NY, NY:

Hillmann provided environmental investigation activities for 5 separate sites in Manhattan, NY. Mr. Hirschmann functioned as the project manager and prepared Phase II Investigation workplans for soil and soil-vapor sampling, directed site investigation activities and prepared Remedial Investigation Reports for each site. Where



contamination was identified, Mr. Hirschmann prepared Remedial Action Work Plans for slated redevelopment activities.

AIG: Northeastern States: Hillmann provides ongoing environmental consulting for this client including decommissioning of fuel oil storage tanks, investigation and remediation of fuel oil contaminated soil and groundwater. Mr. Hirschmann provides third-party oversight on behalf of this client to ensure the contractors/consultants onsite are performing project activities in accordance with industry and regulatory protocol. When applicable on certain projects, Mr. Hirschmann will also direct full remedial investigation and remedial activities as the project manager.



Etan Hindin

Senior Project Manager

EDUCATION:

B.S. Biology, Bar Ilan University, Ramat Gan, Israel

CERTIFICATIONS:

US EPA AHERA Asbestos Inspector
New York State Asbestos Project Monitor
New York State Air Sampling Technician
NJDEP GIS Training
Environmental Audit and Site Assessments (Rutgers NJAES)
40-hr OSHA Hazardous Waste Operations and Emergency Response (HAZWOPER) Training
8-hr OSHA HAZWOPER Refresher Training

YEARS OF EXPERIENCE:

With Hillmann: 1 year
Total: 11 years

PROFESSIONAL EXPERIENCE:

As a Senior Project and Account Manager, Mr. Etan Hindin advises private and public sector clients on a broad range of environmental projects including due diligence (Phase I and II), regulatory compliance, HSE audits, soil and groundwater remediation, and mold investigations and asbestos surveys. Mr. Hindin is responsible for proposing project services, bidding, managing projects, and meeting with clients.

Mr. Hindin has conducted Phase I's of commercial and industrial sites throughout the country and has provided EH&S consulting to Fortune 500 companies. He is particularly well versed in environmental, health and safety regulations and he strives to provide creative, effective, and efficient solutions to complex environmental problems.

Representative experience includes:

Enviro-Sciences (of Delaware), Inc.: From 2011 to 2018, Mr. Hindin served as a Project Manager at Enviro-Sciences (of Delaware), Inc. where he designed sampling programs, oversaw abatement projects, and performed clearance sampling for mold and asbestos. He also managed environmental due diligence projects of commercial and industrial sites, throughout the US. Mr. Hindin often trained entry-level consultants in database review, report writing, and assessment protocols while working to improve report templates to comply with changing regulations and ASTM standards.

NJDEP Watershed Ambassadors Program: From 2010 to 2011, Mr. Hindin worked as a New Jersey Watershed Ambassador for the NJDEP where he monitored water quality utilizing NJDEP protocols and online reporting software, utilized GIS, NJGeoWeb, and DataMiner to research assigned water bodies and surrounding areas. Mr. Hindin also presented on watershed management, resource conservation, sustainability, and environmental regulations.

Attachment B

Due Diligence Phase II Subsurface Investigation

August 25, 2021

Mr. Dylan J. Salmons
Pennrose, LLC
1301 Avenues of the Americas
7th Floor
New York, NY 10019

**Re: Limited Phase II Site Investigation
Timber Shore
78 Bridge Street
Tonawanda, NY
HK Project No. HK-2550-1**

Dear Mr. Salmons:

HK Engineering & Geology, D.P.C. (HK) conducted a Limited Phase II Soil Investigation at the property located at 78 Bridge Street, Tonawanda, New York (the subject property). HK previously prepared a Phase I Environmental Site Assessment (ESA) for the property dated June 1, 2020. Preliminary findings from the Phase I have identified several environmental areas of concern given its current and historical use. These uses include historical fire department training, adjacent historical properties, the potential for historic fill, and various debris onsite (i.e. drums and storage tanks). HK's Limited Phase II Soil Investigation was designed to investigate soil, groundwater, and soil vapor to determine if subsurface impacts are present from the environmental areas of concern described above.

FIELD ACTIVITIES (August 9, 2021)

Prior to drilling activities, a walkthrough was completed with the site contact. HK was told that the storage tanks and drums located onsite were used for fire training purposes and unrelated to oil/fuel use. Following the walkthrough, a geophysical survey was performed at proposed boring areas to clear for safe drilling. The geophysical survey used ground penetrating radar (GPR), line tracing and magnetometer equipment to identify any utilities or buried anomalies. No anomalies of note were identified during boring clearance.

Nine borings (SB1 through SB9) were advanced onsite with direct push machinery in representative locations and areas of concern to characterize the surface and subsurface soil. The boring locations are shown on Figure 1. Boring depths were terminated between 5-15 feet below ground surface (bgs). PID readings recorded during boring investigation registered as 0.0 parts per million (ppm) with the exception of SB7 with a slight elevated level detection of 1.9 ppm at 3.5 feet bgs. Groundwater was encountered in all borings except SB9. Groundwater depths ranged from 4-5.5 feet bgs. To facilitate groundwater sample collection, temporary monitoring well points (TWP) were installed in borings SB1 (TWP1), SB3 (TWP3), and SB5 (TWP5). Soil boring logs are included as Attachment A.

Soil and groundwater samples were collected from each boring for laboratory analysis of the Target Analyte List/Target Compound List which includes: volatile organic compounds (VOCs), semi-volatile organic compounds (SVOCs), TAL metals, pesticides and polychlorinated biphenyls (PCBs). Dissolved metals were analyzed in groundwater samples. Two soil samples nearest the fire tower and all groundwater samples were collected for Per- and polyfluoroalkyl substances (PFAS) analysis.

Three soil vapor (SV) samples were also collected adjacent to borings SB2 (SV2), SB4 (SV4), and SB6 (SV6). To collect a sample with minimal moisture interference probe installation depths were 2 feet above the water table. Samples were collected in laboratory cleaned air canisters for a one-hour duration. Air samples were transported to a New York certified laboratory under chain of custody protocol and analyzed for VOCs by EPA method TO-15.

SUMMARY OF RESULTS

Soil laboratory analytical results were compared to the NYSDEC Unrestricted Use Soil Cleanup Objectives (UUSCOs) and Restricted-Residential Use Soil Cleanup Objectives (RRUSCOs). (Note: NYS does not have current standards for PFAS compounds). A summary table of the soil testing results are included in Table 1 with the full laboratory data package included as Attachment B.

- Several SVOC compounds were detected in exceedance of the UUSCO and RRUSCO in numerous samples.
- Nickel was detected in exceedance of the RRUSCO in one sample, lead was also detected above the UUSCO but below the RRUSCO in several samples.
- Two pesticide compounds were detected above the UUSCO but below the RRUSCO in several samples.
- Various PFAS compounds were detected in both soil samples collected.
- All other remaining compounds were either not detected or detected below the applicable UUSCOs.

Groundwater laboratory results were compared to the NYSDEC Ambient Water Quality Standards (AWQS). (Note: PFAS compounds were compared to the NYSDOH Drinking Water MCL). A table of the detected groundwater results are included in Table 2 with the full laboratory data package included as Attachment B.

- Benzo(a)pyrene was detected in exceedance of the AWQS in one sample, TWP3.
- Several metals were detected above the AWQS in all total metal unfiltered samples. Filtered groundwater samples showed dissolved iron, manganese and sodium in exceedance of the AWQS.
- Several PFAS compounds were detected in all three groundwater samples. All three samples showed exceedances of the NYS Drinking Water MCL for Perfluorooctanoic acid and Perfluorooctanesulfonic acid.
- All other remaining compounds were either not detected or detected below the applicable AWQS.

Soil vapor results are included in Table 3 with the full laboratory data package included as Attachment B. (Note: NYS does not have current standards for soil vapor compounds).

- Soil vapor results showed several detections of VOC compounds.

CONCLUSIONS/RECOMMENDATIONS

Based on the findings of the Limited Phase II Investigation, the following conclusions are made:

- Soil observed in the borings consisted primarily of native sand and clay. The SVOC exceedances observed in the soil are suspected to be a result of historic site use. During redevelopment activities, all excavated soil transported off-site for disposal should be disposed of at an appropriately certified facility. Any soil remaining onsite in exceedance of the NYSDEC Restricted-Residential Use Soil Cleanup Objectives should be capped by either the building foundation, exterior hardscaping or two feet of clean fill in yard/vegetation areas.
- PFAS compounds were detected both in soil and in groundwater. These compounds are constituents of fire-fighting foam and, considering the history of the site for fire service training, the detected compounds may have originated from historical site uses. PFAS compounds are an emerging contaminant subject to increasing regulatory scrutiny on both state and federal levels. The State of New York amended its regulations in 2020 to add certain PFAS compounds to its list of regulated hazards substances, and publish Maximum Contaminant Levels for PFAS in drinking water. The USEPA has proposed new regulations to increase drinking water testing requirements.

We thank you for the opportunity to provide you with these services. Please feel free to contact us with any questions.

Sincerely,


HK Engineering & Geology, D.P.C.



Ryan K. Powell, P.G.
Environmental Scientist



Chris Hirschmann, CHMM
Director, Environmental Services



Notes:
Approximate property boundary obtained from the Niagara County online parcel viewer, last updated 2020.
Aerial imagery basemap obtained from GoogleEarth Pro, dated 9/22/2018.
Figure created by JLD Mapping Services LLC.

Legend

- Soil Sample
- ▼ Soil Vapor Sample
- ⊕ Groundwater Sample
- ▭ Approximate Property Boundary
- ▭ Approximate Niagara County Parcel



August 9, 2021 Sample Location Map

78 Bridge Street
Parcel IDs: 184.08-1-8 & 184.08-1-9
North Tonawanda, Niagara County, NY

8/12/2021

SIZE 11x17	DWG NO. Figure XX	REV 1
SCALE: 1 in = 60 ft	PROJECT No.: HK-2550-1	SHEET 1 OF 1

Table 1 - Soil Results - VOCs, PFAS
78 Bridge Street
Tonawanda, New York

HK Engineering & Geology, D.P.C.
Project #: HK2550-1
Sample Date: 8/9/2021

Target Compounds	NYSDEC Unrestricted Use SCO	NYSDEC Restricted Residential SCO	S1A Sample Depth: 0-2'		S1B Sample Depth: 2-4'		S2B Sample Depth: 2-4'		S3A Sample Depth: 0-2'		S3B Sample Depth: 2.5-4.5'		S4B Sample Depth: 3-5'		S5B Sample Depth: 3-5'		S6B Sample Depth: 3-5'		S7B Sample Depth: 3-5'		S8A Sample Depth: 0-2'	
Volatiles (mg/Kg)			Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q
1,1,1-Trichloroethane	0.68	100	ND (0.00049)		ND (0.00055)		ND (0.00058)		ND (0.00052)		ND (0.00051)		ND (0.00055)		ND (0.00060)		ND (0.00075)		ND (0.00061)		ND (0.00061)	
1,1,2,2-Tetrachloroethane	NS	NS	ND (0.00061)		ND (0.00068)		ND (0.00072)		ND (0.00065)		ND (0.00063)		ND (0.00068)		ND (0.00074)		ND (0.00093)		ND (0.00075)		ND (0.00076)	
1,1,2-Trichloroethane	NS	NS	ND (0.00057)		ND (0.00063)		ND (0.00067)		ND (0.00060)		ND (0.00058)		ND (0.00063)		ND (0.00069)		ND (0.00086)		ND (0.00069)		ND (0.00070)	
1,1-Dichloroethane	0.27	26	ND (0.00051)		ND (0.00057)		ND (0.00060)		ND (0.00053)		ND (0.00052)		ND (0.00056)		ND (0.00061)		ND (0.00076)		ND (0.00062)		ND (0.00063)	
1,1-Dichloroethene	0.33	100	ND (0.00067)		ND (0.00075)		ND (0.00079)		ND (0.00071)		ND (0.00069)		ND (0.00074)		ND (0.00081)		ND (0.0010)		ND (0.00082)		ND (0.00083)	
1,2,3-Trichlorobenzene	NS	NS	ND (0.00026)		ND (0.00029)		ND (0.00030)		ND (0.00027)		ND (0.00026)		ND (0.00028)		ND (0.00031)		ND (0.00039)		ND (0.00031)		ND (0.00032)	
1,2,4-Trichlorobenzene	NS	NS	ND (0.00026)		ND (0.00029)		ND (0.00030)		ND (0.00027)		ND (0.00026)		ND (0.00028)		ND (0.00031)		ND (0.00039)		ND (0.00031)		ND (0.00032)	
1,2-Dibromo-3-chloropropane	NS	NS	ND (0.00071)		ND (0.00079)		ND (0.00084)		ND (0.00075)		ND (0.00073)		ND (0.00078)		ND (0.00086)		ND (0.0011)		ND (0.00087)		ND (0.00088)	
1,2-Dibromoethane	NS	NS	ND (0.00043)		ND (0.00048)		ND (0.00051)		ND (0.00045)		ND (0.00044)		ND (0.00048)		ND (0.00052)		ND (0.00065)		ND (0.00053)		ND (0.00053)	
1,2-Dichlorobenzene	1.1	100	ND (0.00056)		ND (0.00062)		ND (0.00066)		ND (0.00059)		ND (0.00057)		ND (0.00062)		ND (0.00068)		ND (0.00084)		ND (0.00068)		ND (0.00069)	
1,2-Dichloroethane	0.02	3.1	ND (0.00048)		ND (0.00054)		ND (0.00057)		ND (0.00051)		ND (0.00049)		ND (0.00053)		ND (0.00058)		ND (0.00073)		ND (0.00059)		ND (0.00059)	
1,2-Dichloropropane	NS	NS	ND (0.00048)		ND (0.00054)		ND (0.00057)		ND (0.00051)		ND (0.00050)		ND (0.00053)		ND (0.00059)		ND (0.00073)		ND (0.00059)		ND (0.00060)	
1,3-Dichlorobenzene	2.4	49	ND (0.00051)		ND (0.00057)		ND (0.00060)		ND (0.00054)		ND (0.00052)		ND (0.00056)		ND (0.00061)		ND (0.00077)		ND (0.00062)		ND (0.00063)	
1,4-Dichlorobenzene	1.8	13	ND (0.00050)		ND (0.00056)		ND (0.00060)		ND (0.00053)		ND (0.00052)		ND (0.00056)		ND (0.00061)		ND (0.00076)		ND (0.00062)		ND (0.00063)	
2-Butanone (MEK)	0.12	100	ND (0.00025)		ND (0.00028)		ND (0.00029)		ND (0.00026)		0.0103		ND (0.00027)		0.1		0.0136	J	ND (0.00030)		ND (0.00031)	
2-Hexanone	NS	NS	ND (0.00022)	b	ND (0.00024)	b	ND (0.00026)	b	ND (0.00023)	b	ND (0.00022)		ND (0.00024)		ND (0.00026)		ND (0.00033)		ND (0.00027)		ND (0.00027)	
4-Methyl-2-pentanone(MIBK)	NS	NS	ND (0.00023)		ND (0.00026)		ND (0.00027)		ND (0.00025)		ND (0.00024)		ND (0.00026)		ND (0.00028)		ND (0.00035)		ND (0.00028)		ND (0.00029)	
Acetone	0.05	100	ND (0.00042)		0.026		ND (0.00050)		0.006	J	0.0555		0.009	J	0.0927		0.073		0.0156		0.0199	
Benzene	0.06	4.8	ND (0.00047)		ND (0.00052)		ND (0.00055)		ND (0.00049)		ND (0.00048)		ND (0.00051)		ND (0.00056)		ND (0.00070)		0.00064		ND (0.00058)	
Bromochloromethane	NS	NS	ND (0.00057)		ND (0.00064)		ND (0.00068)		ND (0.00063)		ND (0.00069)		ND (0.00069)		ND (0.00074)		ND (0.00087)		ND (0.00070)		ND (0.00071)	
Bromodichloromethane	NS	NS	ND (0.00044)		ND (0.00049)		ND (0.00052)		ND (0.00046)		ND (0.00045)		ND (0.00048)		ND (0.00053)		ND (0.00066)		ND (0.00054)		ND (0.00054)	
Bromoform	NS	NS	ND (0.0014)		ND (0.0016)		ND (0.0017)		ND (0.0015)		ND (0.0014)		ND (0.0015)		ND (0.0017)		ND (0.0021)		ND (0.0017)		ND (0.0017)	
Bromomethane	NS	NS	ND (0.00078)	a	ND (0.00087)	a	ND (0.00092)	a	ND (0.00080)	a	ND (0.00080)	a	ND (0.00086)	a	ND (0.00095)	a	ND (0.0012)	a	ND (0.00096)	a	ND (0.00097)	a
Carbon disulfide	NS	NS	ND (0.00055)		ND (0.00061)		ND (0.00065)		0.0019	J	ND (0.00056)		ND (0.00060)		0.0012	J	ND (0.00083)		0.0012	J	ND (0.00068)	
Carbon tetrachloride	0.76	2.4	ND (0.00063)		ND (0.00071)		ND (0.00075)		ND (0.00067)		ND (0.00065)		ND (0.00070)		ND (0.00076)		ND (0.00095)		ND (0.00077)		ND (0.00078)	
Chlorobenzene	1.1	100	ND (0.00047)		ND (0.00052)		ND (0.00055)		ND (0.00050)		ND (0.00048)		ND (0.00052)		ND (0.00057)		ND (0.00071)		ND (0.00058)		ND (0.00058)	
Chloroethane	NS	NS	ND (0.00060)		ND (0.00068)		ND (0.00071)		ND (0.00064)		ND (0.00062)		ND (0.00067)		ND (0.00073)		ND (0.00091)		ND (0.00074)		ND (0.00075)	
Chloroform	0.37	49	ND (0.00053)		ND (0.00063)		ND (0.00068)		ND (0.00054)		ND (0.00056)		ND (0.00059)		ND (0.00064)		ND (0.00080)		ND (0.00065)		ND (0.00066)	
Chloromethane	NS	NS	ND (0.00020)		ND (0.00022)		ND (0.00024)		ND (0.00021)		ND (0.00021)		ND (0.00022)		ND (0.00024)		ND (0.00030)		ND (0.00025)		ND (0.00025)	
cis-1,2-Dichloroethene	0.25	100	ND (0.00086)		ND (0.00096)		ND (0.0010)		ND (0.00091)		ND (0.00088)		ND (0.00095)		ND (0.0010)		ND (0.0013)		ND (0.0011)		ND (0.0011)	
cis-1,3-Dichloropropene	NS	NS	ND (0.00049)		ND (0.00054)		ND (0.00057)		ND (0.00051)		ND (0.00050)		ND (0.00054)		ND (0.00059)		ND (0.00073)		ND (0.00060)		ND (0.00060)	
Cyclohexane	NS	NS	ND (0.00067)		ND (0.00075)		ND (0.00079)		ND (0.00071)		ND (0.00069)		ND (0.00074)		ND (0.00081)		ND (0.0010)		ND (0.00082)		ND (0.00083)	
Dibromochloromethane	NS	NS	ND (0.00057)		ND (0.00064)		ND (0.00068)		ND (0.00060)		ND (0.00059)		ND (0.00063)		ND (0.00069)		ND (0.00087)		ND (0.00070)		ND (0.00071)	
Dichlorodifluoromethane	NS	NS	ND (0.00074)		ND (0.00083)		ND (0.00088)		ND (0.00078)		ND (0.00076)		ND (0.00082)		ND (0.00090)		ND (0.0011)		ND (0.00091)		ND (0.00092)	
Ethylbenzene	1	41	ND (0.00046)		ND (0.00052)		ND (0.00055)		ND (0.00049)		ND (0.00047)		ND (0.00051)		ND (0.00056)		ND (0.00070)		0.0035		ND (0.00057)	
Freon 113	NS	NS	ND (0.00027)		ND (0.00031)		ND (0.00032)		ND (0.00028)		ND (0.00028)		ND (0.00030)		ND (0.00033)		ND (0.00041)		ND (0.00033)		ND (0.00034)	
Isopropylbenzene	NS	NS	ND (0.0015)		ND (0.0016)		ND (0.0017)		ND (0.0015)		ND (0.0016)		ND (0.0016)		ND (0.0018)		ND (0.0022)		ND (0.0018)		ND (0.0018)	
m,p-Xylene	0.26	100	ND (0.00092)		ND (0.0010)		ND (0.0011)		ND (0.00097)		ND (0.00094)		ND (0.0010)		ND (0.0011)		ND (0.0014)		0.0025		ND (0.0011)	
Methyl Acetate	NS	NS	ND (0.0014)		ND (0.0016)		ND (0.0017)		ND (0.0015)		ND (0.0015)		ND (0.0016)		ND (0.0017)		ND (0.0021)		ND (0.0017)		ND (0.0018)	
Methyl Tert Butyl Ether	0.93	100	ND (0.00048)		ND (0.00054)		ND (0.00057)		ND (0.00051)		ND (0.00049)		ND (0.00053)		ND (0.00058)		ND (0.00072)		ND (0.00059)		ND (0.00059)	
Methylcyclohexane	NS	NS	ND (0.00089)		ND (0.0010)		ND (0.0011)		ND (0.00094)		ND (0.00092)		ND (0.00099)		ND (0.0011)		ND (0.0014)		ND (0.0011)		ND (0.0011)	
Methylene chloride	0.05	100	ND (0.00027)		ND (0.00030)		ND (0.00031)		ND (0.00028)		ND (0.00027)		ND (0.00029)		ND (0.00032)		ND (0.00040)		ND (0.00033)		ND (0.00033)	
o-Xylene	0.26	100	ND (0.00047)		ND (0.00052)		ND (0.00055)		ND (0.00049)		ND (0.00048)		ND (0.00052)		ND (0.00057)		ND (0.00071)		0.0022		ND (0.00058)	
Styrene	NS	NS	ND (0.00041)		ND (0.00046)		ND (0.00048)		ND (0.00043)		ND (0.00042)		ND (0.00045)		ND (0.00050)		ND (0.00062)		0.0009	J	ND (0.00051)	
Tetrachloroethene	1.3	19																				

Table 1 (cont'd) - Soil Results - SVOCs
78 Bridge Street
Tonawanda, New York

HK Engineering & Geology, D.P.C.
Project #: HK2550-1
Sample Date: 8/9/2021

Target Compounds	NYSDEC Unrestricted Use SCO	NYSDEC Restricted Residential SCO	S1A Sample Depth: 0-2'		S1B Sample Depth: 2-4'		S2B Sample Depth: 2-4'		S3A Sample Depth: 0-2'		S3B Sample Depth: 2.5-4.5'		S4B Sample Depth: 3-5'		S5B Sample Depth: 3-5'		S6B Sample Depth: 3-5'		S7B Sample Depth: 3-5'		S8A Sample Depth: 0-2'	
Semivolatiles (mg/Kg)			Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q
1,1'-Biphenyl	NS	NS	ND (0.0047)		ND (0.0056)		ND (0.0055)		0.147		0.007	J	0.0326	J	ND (0.0054)		0.128	J	2.44		0.0292	J
1,2,4,5-Tetrachlorobenzene	NS	NS	ND (0.0088)		ND (0.010)		ND (0.010)		ND (0.0096)		ND (0.0097)		ND (0.0090)		ND (0.010)		ND (0.020)		ND (0.040)		ND (0.0093)	
1,4-Dioxane	0.1	13	ND (0.023)		ND (0.027)		ND (0.027)		ND (0.025)		ND (0.025)		ND (0.023)		ND (0.026)		ND (0.053)		ND (0.11)		ND (0.024)	
2,2'-Oxybis(1-chloropropane)	NS	NS	ND (0.012)		ND (0.015)		ND (0.015)		ND (0.014)		ND (0.014)		ND (0.013)		ND (0.014)		ND (0.029)		ND (0.057)		ND (0.013)	
2,3,4,6-Tetrachlorophenol	NS	NS	ND (0.023)		ND (0.027)		ND (0.027)		ND (0.025)		ND (0.025)		ND (0.023)		ND (0.026)		ND (0.053)		ND (0.11)		ND (0.024)	
2,4,5-Trichlorophenol	NS	NS	ND (0.026)		ND (0.031)		ND (0.030)		ND (0.028)		ND (0.029)		ND (0.027)		ND (0.030)		ND (0.060)		ND (0.12)		ND (0.027)	
2,4,6-Trichlorophenol	NS	NS	ND (0.021)		ND (0.024)		ND (0.024)		ND (0.022)		ND (0.023)		ND (0.021)		ND (0.024)		ND (0.048)		ND (0.095)		ND (0.022)	
2,4-Dichlorophenol	NS	NS	ND (0.029)		ND (0.035)		ND (0.035)		ND (0.032)		ND (0.033)		ND (0.030)		ND (0.034)		ND (0.068)		ND (0.14)		ND (0.031)	
2,4-Dimethylphenol	NS	NS	ND (0.061)		ND (0.073)		ND (0.072)		ND (0.067)		ND (0.068)		ND (0.063)		ND (0.071)		ND (0.14)		ND (0.28)		ND (0.065)	
2,4-Dinitrophenol	NS	NS	ND (0.13)		ND (0.15)		ND (0.15)		ND (0.14)		ND (0.14)		ND (0.13)		ND (0.15)		ND (0.30)		ND (0.60)		ND (0.14)	
2,4-Dinitrotoluene	NS	NS	ND (0.011)		ND (0.013)		ND (0.013)		ND (0.012)		ND (0.012)		ND (0.011)		ND (0.012)		ND (0.025)		ND (0.049)		ND (0.011)	
2,6-Dinitrotoluene	NS	NS	ND (0.017)		ND (0.021)		ND (0.020)		ND (0.019)		ND (0.019)		ND (0.018)		ND (0.020)		ND (0.040)		ND (0.080)		ND (0.018)	
2-Chloronaphthalene	NS	NS	ND (0.0082)		ND (0.0097)		ND (0.0096)		ND (0.0090)		ND (0.0094)		ND (0.0084)		ND (0.0094)		ND (0.019)		ND (0.038)		ND (0.0087)	
2-Chlorophenol	NS	NS	ND (0.017)		ND (0.020)		ND (0.020)		ND (0.019)		ND (0.019)		ND (0.018)		ND (0.020)		ND (0.040)		ND (0.079)		ND (0.018)	
2-Methylnaphthalene	NS	NS	ND (0.0078)		ND (0.0092)		ND (0.0091)		0.252		0.0968	J	0.0968		0.0099	J	0.507		8.36		0.0995	
2-Methylphenol	0.33	100	ND (0.022)		ND (0.026)		ND (0.026)		ND (0.024)		ND (0.024)		ND (0.023)		ND (0.025)		ND (0.051)		0.14	J	ND (0.023)	
2-Nitroaniline	NS	NS	ND (0.0081)		ND (0.0096)		ND (0.0095)		ND (0.0089)		ND (0.0090)		ND (0.0084)		ND (0.0094)		ND (0.019)		ND (0.038)		ND (0.0086)	
2-Nitrophenol	NS	NS	ND (0.023)		ND (0.027)		ND (0.027)		ND (0.025)		ND (0.025)		ND (0.023)		ND (0.026)		ND (0.053)		ND (0.11)		ND (0.024)	
3&4-Methylphenol	NS	NS	ND (0.028)		ND (0.034)		ND (0.033)		ND (0.031)		ND (0.031)		ND (0.029)		ND (0.033)	J	0.0743		0.399		ND (0.030)	
3,3'-Dichlorobenzidine	NS	NS	ND (0.029)		ND (0.034)		ND (0.034)		ND (0.031)		ND (0.032)		ND (0.030)		ND (0.033)		ND (0.067)		ND (0.13)		ND (0.030)	
3-Nitroaniline	NS	NS	ND (0.0086)		ND (0.010)		ND (0.010)		ND (0.0094)		ND (0.0096)		ND (0.0089)		ND (0.0099)		ND (0.020)		ND (0.040)		ND (0.0091)	
4,6-Dinitro-o-cresol	NS	NS	ND (0.037)		ND (0.044)		ND (0.043)		ND (0.040)		ND (0.041)		ND (0.038)		ND (0.042)		ND (0.086)		ND (0.17)		ND (0.039)	
4-Bromophenyl phenyl ether	NS	NS	ND (0.013)		ND (0.016)		ND (0.016)		ND (0.015)		ND (0.015)		ND (0.014)		ND (0.015)		ND (0.031)		ND (0.062)		ND (0.014)	
4-Chloro-3-methyl phenol	NS	NS	ND (0.021)		ND (0.025)		ND (0.025)		ND (0.023)		ND (0.023)		ND (0.022)		ND (0.024)		ND (0.049)		ND (0.098)		ND (0.022)	
4-Chloroaniline	NS	NS	ND (0.012)		ND (0.015)		ND (0.015)		ND (0.014)		ND (0.014)		ND (0.013)		ND (0.014)		ND (0.029)		ND (0.057)		ND (0.013)	
4-Chlorophenyl phenyl ether	NS	NS	ND (0.011)		ND (0.013)		ND (0.013)		ND (0.012)		ND (0.012)		ND (0.012)		ND (0.013)		ND (0.026)		ND (0.052)		ND (0.012)	
4-Nitroaniline	NS	NS	ND (0.0089)		ND (0.011)		ND (0.010)		ND (0.0097)		ND (0.0099)		ND (0.0092)		ND (0.010)		ND (0.021)		ND (0.041)		ND (0.0095)	
4-Nitrophenol	NS	NS	ND (0.092)		ND (0.11)		ND (0.11)		ND (0.10)		ND (0.10)		ND (0.095)		ND (0.11)		ND (0.21)		ND (0.43)		ND (0.097)	
Acenaphthene	20	100	ND (0.012)		ND (0.014)		ND (0.014)		1.33		0.0256	J	0.33		ND (0.014)		1.72		22.6		0.517	
Acenaphthylene	100	100	ND (0.018)		ND (0.021)		ND (0.021)		0.0427		0.0336	J	0.0301	J	ND (0.020)		0.0862		0.68		0.0222	J
Acetophenone	NS	NS	ND (0.0074)		ND (0.0088)		ND (0.0087)		ND (0.0081)		ND (0.0082)		ND (0.0076)		ND (0.0085)		ND (0.017)		ND (0.034)		ND (0.0078)	
Anthracene	100	100	ND (0.021)		ND (0.025)		ND (0.025)		3.62		0.0878		0.976		ND (0.024)		5.35		65.4		1.4	
Atrazine	NS	NS	ND (0.015)		ND (0.017)		ND (0.017)		ND (0.016)		ND (0.016)		ND (0.015)		ND (0.017)		ND (0.034)		ND (0.068)		ND (0.016)	
Benzaldehyde	NS	NS	ND (0.0086)		ND (0.010)		ND (0.010)		ND (0.0093)		ND (0.0095)		ND (0.0088)		0.0653	J	ND (0.020)		ND (0.040)		0.031	J
Benzo(a)anthracene	1	1	0.0164	J	ND (0.012)		ND (0.011)		8.19		0.402		2.74		0.0475		11.7		101		3.7	
Benzo(a)pyrene	1	1	0.0221	J	ND (0.019)		ND (0.018)		6.11		0.347		2.42		0.0399	J	8.87		74.5		3.44	
Benzo(b)fluoranthene	1	1	0.0225	J	ND (0.018)		ND (0.018)		7.46		0.442		3.23		0.0458		10.3		88.3		3.3	
Benzo(g,h,i)perylene	100	100	0.0554		ND (0.020)		ND (0.020)		1.88		0.205		0.685		0.0301	J	4.1		14.8		1.37	
Benzo(k)fluoranthene	0.8	3.9	ND (0.016)		ND (0.019)		ND (0.019)		2.9		0.168		1.1		ND (0.019)		5.21		37.6		1.48	
bis(2-Chloroethoxy)methane	NS	NS	ND (0.0074)		ND (0.0087)		ND (0.0087)		ND (0.0081)		ND (0.0082)		ND (0.0076)		ND (0.0085)		ND (0.017)		ND (0.034)		ND (0.0078)	
bis(2-Chloroethyl)ether	NS	NS	ND (0.015)		ND (0.018)		ND (0.017)		ND (0.016)		ND (0.017)		ND (0.015)		ND (0.017)		ND (0.035)		ND (0.069)		ND (0.016)	
bis(2-Ethylhexyl)phthalate	NS	NS	0.0268	J	ND (0.0096)		ND (0.0095)		ND (0.0088)		0.0152	J	ND (0.0083)		0.0518	J	ND (0.019)		ND (0.037)		0.0472	J
Butyl benzyl phthalate	NS	NS	ND (0.0084)		ND (0.010)		ND (0.0099)		ND (0.0092)		ND (0.0093)		ND (0.0087)		ND (0.0097)		ND (0.020)		ND (0.039)		ND (0.0089)	
Caprolactam	NS	NS	ND (0.014)		ND (0.016)		ND (0.016)		ND (0.015)		ND (0.015)		ND (0.014)		ND (0.016)		ND (0.032)		ND (0.063)		ND (0.014)	
Carbazole	NS	NS	ND (0.0050)		ND (0.0059)		ND (0.0059)		1.52		0.0461	J	0.496		ND (0.0058)		1.75		16.6		0.565	
Chrysene	1	3.9	0.042		ND (0.013)		ND (0.013)		7.5		0.461		2.55		0.0449		10.8		89.1		3.55	
Dibenzo(a,h)anthracene	0.33	0.33	ND (0.015)		ND (0.018)		ND (0.018)		0.638		0.0584		0.236		ND (0.018)		1.95		7.95		0.48	
Dibenzofuran	7	59	ND (0.014)		ND (0.017)		ND (0.016)		1.05		0.0273	J	0.192		ND (0.016)		1.04		18.2		0.257	
Diethyl phthalate	NS	NS	ND (0.0073)		ND (0.0087)		ND (0.0086)		ND (0.0080)		ND (0.0082)		ND (0.									

Table 1 (cont'd) - Soil Results - Pesticides, PCBs, Metals
78 Bridge Street
Tonawanda, New York

HK Engineering & Geology, D.P.C.
Project #: HK2550-1
Sample Date: 8/9/2021

Target Compounds	NYSDEC Unrestricted Use SCO	NYSDEC Restricted Residential SCO	S1A Sample Depth: 0-2'		S1B Sample Depth: 2-4'		S2B Sample Depth: 2-4'		S3A Sample Depth: 0-2'		S3B Sample Depth: 2.5-4.5'		S4B Sample Depth: 3-5'		S5B Sample Depth: 3-5'		S6B Sample Depth: 3-5'		S7B Sample Depth: 3-5'		S8A Sample Depth: 0-2'	
Pesticides (mg/Kg)			Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q
4,4'-DDD	0.0033	13	ND (0.00064)	c	ND (0.00074)	c	ND (0.00074)	c	ND (0.00069)	c	ND (0.00069)		ND (0.00067)	c	ND (0.00073)		ND (0.00073)		0.0486		ND (0.0032)	c
4,4'-DDE	0.0033	8.9	ND (0.00062)		ND (0.00070)		ND (0.00070)		ND (0.00066)		0.0071	d	ND (0.00064)		ND (0.00070)		ND (0.00069)		0.0096	d	ND (0.0031)	
4,4'-DDT	0.0033	7.9	ND (0.00062)		ND (0.00071)		ND (0.00071)		ND (0.00066)		0.0046	d	ND (0.00064)		0.00078	J d	0.0068	d			ND (0.00067)	
Aldrin	0.005	0.097	ND (0.00058)		ND (0.00066)		ND (0.00066)		ND (0.00062)		ND (0.00062)		ND (0.00060)		ND (0.00065)		ND (0.00065)		ND (0.00062)		ND (0.0029)	
alpha-BHC	0.02	0.48	ND (0.00057)		ND (0.00065)		ND (0.00065)		ND (0.00061)		ND (0.00061)		ND (0.00059)		ND (0.00064)		ND (0.00064)		ND (0.00061)		ND (0.0029)	
alpha-Chlordane	0.094	4.2	ND (0.00057)		ND (0.00065)		ND (0.00065)		ND (0.00060)		ND (0.00061)		ND (0.00059)		ND (0.00064)		ND (0.00064)		ND (0.00061)		ND (0.0028)	
beta-BHC	0.036	0.36	ND (0.00064)		ND (0.00072)		ND (0.00072)		ND (0.00068)		ND (0.00068)		ND (0.00066)		ND (0.00072)		ND (0.00072)		ND (0.00068)		ND (0.0032)	
delta-BHC	0.04	100	ND (0.00067)		ND (0.00077)		ND (0.00077)		ND (0.00072)		ND (0.00073)		ND (0.00070)		ND (0.00076)		ND (0.00076)		ND (0.00072)		ND (0.0034)	
Dieldrin	0.005	0.2	ND (0.00048)		ND (0.00055)		ND (0.00055)		ND (0.00051)		ND (0.00052)		ND (0.00050)		ND (0.00055)		ND (0.00054)		ND (0.00052)		ND (0.0024)	
Endosulfan sulfate	2.4	24	ND (0.00063)		ND (0.00063)		ND (0.00063)		ND (0.00058)		ND (0.00059)		ND (0.00057)		ND (0.00062)		ND (0.00062)		ND (0.00059)		ND (0.0027)	
Endosulfan-I	2.4	24	ND (0.00040)		ND (0.00046)		ND (0.00046)		ND (0.00043)		ND (0.00044)		ND (0.00042)		ND (0.00046)		ND (0.00046)		ND (0.00043)		ND (0.0020)	
Endosulfan-II	2.4	24	ND (0.00044)		ND (0.00050)		ND (0.00050)		ND (0.00047)		ND (0.00047)		ND (0.00045)		ND (0.00050)		ND (0.00049)		ND (0.00047)		ND (0.0022)	
Endrin	0.014	11	ND (0.00055)		ND (0.00062)		ND (0.00062)		ND (0.00058)		ND (0.00059)		ND (0.00056)		ND (0.00062)		ND (0.00062)		ND (0.00058)		ND (0.0027)	
Endrin aldehyde	NS	NS	ND (0.00040)		ND (0.00045)		ND (0.00045)		ND (0.00042)		ND (0.00043)		ND (0.00041)		ND (0.00045)		ND (0.00045)		ND (0.00043)		ND (0.0020)	
Endrin ketone	NS	NS	ND (0.00051)		ND (0.00058)		ND (0.00058)		ND (0.00054)		ND (0.00055)		ND (0.00052)		ND (0.00057)		ND (0.00057)		ND (0.00054)		ND (0.0025)	
gamma-BHC (Lindane)	0.1	1.3	ND (0.00052)		ND (0.00059)		ND (0.00059)		ND (0.00055)		ND (0.00056)		ND (0.00053)		ND (0.00058)		ND (0.00058)		0.0087	d	ND (0.0026)	
gamma-Chlordane	NS	NS	ND (0.00032)		ND (0.00036)		ND (0.00036)		ND (0.00034)		ND (0.00034)		ND (0.00033)		ND (0.00036)		ND (0.00036)		0.0688	d	ND (0.0016)	
Heptachlor	0.042	2.1	ND (0.00061)		ND (0.00069)		ND (0.00069)		ND (0.00065)		ND (0.00065)		ND (0.00063)		ND (0.00068)		ND (0.00068)		ND (0.00065)		ND (0.0030)	
Heptachlor epoxide	NS	NS	ND (0.00049)		ND (0.00056)		ND (0.00056)		ND (0.00052)		ND (0.00053)		ND (0.00051)		ND (0.00056)		ND (0.00056)		ND (0.00053)		ND (0.0025)	
Methoxychlor	NS	NS	ND (0.00056)	c	ND (0.00064)	c	ND (0.00064)	c	ND (0.00060)	c	ND (0.00060)		ND (0.00058)	c	ND (0.00063)		0.0196		ND (0.00060)		ND (0.0028)	c
Toxaphene	NS	NS	ND (0.016)		ND (0.019)		ND (0.019)		ND (0.017)		ND (0.018)		ND (0.017)		ND (0.018)		ND (0.018)		ND (0.018)		ND (0.082)	
PCBs (mg/Kg)			Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q
Aroclor 1016	0.1	1	ND (0.016)		ND (0.019)		ND (0.018)		ND (0.017)		ND (0.017)		ND (0.017)		ND (0.019)		ND (0.019)		ND (0.018)		ND (0.016)	
Aroclor 1221	0.1	1	ND (0.025)		ND (0.023)		ND (0.023)		ND (0.023)		ND (0.023)		ND (0.023)		ND (0.022)		ND (0.025)		ND (0.024)		ND (0.022)	
Aroclor 1232	0.1	1	ND (0.022)		ND (0.026)		ND (0.024)		ND (0.024)		ND (0.024)		ND (0.023)		ND (0.026)		ND (0.025)		ND (0.025)		ND (0.022)	
Aroclor 1242	0.1	1	ND (0.014)		ND (0.016)		ND (0.015)		ND (0.015)		ND (0.015)		ND (0.015)		ND (0.016)		ND (0.016)		ND (0.016)		ND (0.014)	
Aroclor 1248	0.1	1	ND (0.031)		ND (0.036)		ND (0.034)		ND (0.033)		ND (0.033)		ND (0.032)		ND (0.036)		ND (0.036)		ND (0.035)		ND (0.031)	
Aroclor 1254	0.1	1	ND (0.019)		ND (0.022)		ND (0.020)		ND (0.020)		ND (0.020)		ND (0.019)		ND (0.022)		ND (0.021)		ND (0.021)		ND (0.019)	
Aroclor 1260	0.1	1	ND (0.015)		ND (0.017)		ND (0.016)		ND (0.017)		ND (0.016)		ND (0.015)		ND (0.017)		ND (0.015)		ND (0.017)		ND (0.015)	
Aroclor 1268	0.1	1	ND (0.015)		ND (0.017)		ND (0.016)		ND (0.016)		ND (0.016)		ND (0.015)		ND (0.017)		ND (0.017)		ND (0.016)		ND (0.015)	
Aroclor 1262	0.1	1	ND (0.023)		ND (0.026)		ND (0.025)		ND (0.024)		ND (0.024)		ND (0.024)		ND (0.026)		ND (0.026)		ND (0.026)		ND (0.023)	
Metals (mg/Kg)			Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q
Aluminum	NS	NS	7960		11000		9060		11900		5970		10900		7410		9070		11000		10100	
Antimony	NS	NS	<2.2		<2.5		<2.5		<2.3		<2.4		<2.2		<2.5		<2.4		<2.4		<2.3	
Arsenic	13	16	3.1		3.4		6.3		10.3		3.8		11		7.9		9.1		12.8		6.3	
Barium	350	400	66.4		66		52.7		265		45		98.7		55.3		86.4		188		79.3	
Beryllium	7.2	72	<1.1	e	0.6		0.55		1.2	e	0.37		<1.1	e	<1.3	e	<1.2	e	1.3	e	<1.1	e
Cadmium	2.5	4.3	<0.56		<0.64		<0.62		0.72		<0.60		<0.56		<0.63		0.63		0.89		<0.57	
Calcium	NS	NS	99500		7210		2870		113000		19900		82000		41700		71600		70100		54700	
Chromium	NS	NS	9.6		14.2		12.3		15.5		8.5		15.8		9.9		11.8		16		13.8	
Cobalt	NS	NS	<5.6		8.9		7.5		6.5		<6.0		<5.6		<6.3		<6.1		<6.1		6.7	
Copper	50	270	11.8		13.5		12.9		24.4		15.8		18.6		14.3		23.3		34.5		23.8	
Iron	NS	NS	12400		17400		22000		17700		12600		16200		17400		14400		16700		15600	
Lead	63	400	12.1		11.7		10.1		131		30.2		176		40.1		241		344		67.8	
Magnesium	NS	NS	29100		4540		2740		10800		7410		5160		9850		8980		4760		14500	
Manganese	1600	2000	666		180		194		803		225		483		393		516		562		568	
Mercury	0.18	0.81	<0.032		<0.039		<0.034		<0.032		0.046		0.49		<0.038		0.82		<0.035		<0.030	
Nickel	30	310	12.1		18.8		17.6		16.5		11.9		14.5		14.2		14.4		16.3		17.3	
Potassium	NS	NS	1890		<1300		<1200		1650		<1200		1310		1380		<1200		<1200		1710	
Selenium	3.9	180	<2.2		<2.5		<2.5		<2.3		<2.4		<2.2		<2.5		<2.4		<2.4		<2.3	
Silver	2	180	<2.8	e	<0.64		<0.62		<2.9	e	<0.60		<2.8	e	0.71		<3.0	e	<3.0	e	0.77	
Sodium	NS	NS	<1100		<1300		<1200		<1200		<1200		<1100		<1300		<1200		<1200		<1100	
Thallium	NS	NS	<1.1		<1.3		<1.2		<1.2		<1.2		<1.1		<1.3		<1.2		<1.2		<1.1	
Vanadium	NS	NS	14.9		20.8		19.7		18		14.8		17.4		13.9		17.2		17.5		18.5	
Zinc	109	10000	66.4		72.5		59.3		97.6		67.4		64.5		86.3		80.4		228		81	
General Chemistry			Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q
Cyanide (mg/kg)	27	27	<0.25		<0.26		<0.26		0.67		<0.25		0.86		0.9		0.46		1		0.29	
Solids, Percent (%)	NS	NS	92.3		81		81.3		87.4		85.3		90.3		80.8		80.9		83.1		89.8	

Results in Yellow Highlight displays exceedance above the UUSCO regulatory standard
Results in Green Highlight displays exceedance above both UUSCO & RRUSCO regulatory standard
NS = No Standard Available
ND = Analyzed for but Not Detected at the MDL; () = The MDL for compounds that are Non-Detect
J = Estimated concentration detected at a value above the MDL for target compounds

a Associated CCV outside of control limits low.
b Associated CCV outside of control limits high, sample was ND.
c This compound outside control limits biased high in the associated BS.
d More than 40 % RPD for detected concentrations between the two GC columns.
e Elevated detection limit due to dilution required for high interfering element.

Table 2 - Groundwater Results - VOCs
78 Bridge Street
Tonawanda, New York

HK Engineering & Geology, D.P.C.

Project #: HK2550-1

Sample Date: 8/9/2021

Target Compounds	NYSDEC Ambient Water Quality Standards (AWQS)	TWP1		TWP3		TWP5	
Volatiles (µg/L)		Conc	Q	Conc	Q	Conc	Q
1,1,1-Trichloroethane	5	ND (0.54)		ND (0.54)		ND (0.54)	
1,1,2,2-Tetrachloroethane	5	ND (0.65)		ND (0.65)		ND (0.65)	
1,1,2-Trichloroethane	1	ND (0.53)		ND (0.53)		ND (0.53)	
1,1-Dichloroethane	5	ND (0.57)		ND (0.57)		ND (0.57)	
1,1-Dichloroethene	5	ND (0.59)	a	ND (0.59)	a	ND (0.59)	a
1,2,3-Trichlorobenzene	5	ND (0.50)		ND (0.50)		ND (0.50)	
1,2,4-Trichlorobenzene	5	ND (0.50)		ND (0.50)		ND (0.50)	
1,2-Dibromo-3-chloropropane	0.04	ND (0.53)	a	ND (0.53)	a	ND (0.53)	a
1,2-Dibromoethane	0.0006	ND (0.48)		ND (0.48)		ND (0.48)	
1,2-Dichlorobenzene	3	ND (0.53)		ND (0.53)		ND (0.53)	
1,2-Dichloroethane	0.6	ND (0.60)		ND (0.60)		ND (0.60)	
1,2-Dichloropropane	1	ND (0.51)		ND (0.51)		ND (0.51)	
1,3-Dichlorobenzene	3	ND (0.54)		ND (0.54)		ND (0.54)	
1,4-Dichlorobenzene	3	ND (0.51)		ND (0.51)		ND (0.51)	
2-Butanone (MEK)	NS	ND (6.9)		ND (6.9)		ND (6.9)	
2-Hexanone	NS	ND (2.0)		ND (2.0)		ND (2.0)	
4-Methyl-2-pentanone(MIBK)	NS	ND (1.9)		ND (1.9)		ND (1.9)	
Acetone	NS	ND (3.1)		ND (3.1)		ND (3.1)	
Benzene	1	ND (0.43)		0.51		ND (0.43)	
Bromochloromethane	5	ND (0.48)		ND (0.48)		ND (0.48)	
Bromodichloromethane	NS	ND (0.45)		ND (0.45)		ND (0.45)	
Bromoform	NS	ND (0.63)		ND (0.63)		ND (0.63)	
Bromomethane	5	ND (1.6)	a	ND (1.6)	a	ND (1.6)	a
Carbon disulfide	60	ND (0.46)	a	ND (0.46)	a	ND (0.46)	a
Carbon tetrachloride	5	ND (0.55)		ND (0.55)		ND (0.55)	
Chlorobenzene	5	ND (0.56)		ND (0.56)		ND (0.56)	
Chloroethane	5	ND (0.73)		ND (0.73)		ND (0.73)	
Chloroform	7	ND (0.50)		ND (0.50)		ND (0.50)	
Chloromethane	5	ND (0.76)		ND (0.76)		ND (0.76)	
cis-1,2-Dichloroethene	5	ND (0.51)		2.4		ND (0.51)	
cis-1,3-Dichloropropene	NS	ND (0.47)		ND (0.47)		ND (0.47)	
Cyclohexane	NS	ND (0.78)	a	ND (0.78)	a	ND (0.78)	a
Dibromochloromethane	NS	ND (0.56)		ND (0.56)		ND (0.56)	
Dichlorodifluoromethane	5	ND (0.56)	a	ND (0.56)	a	ND (0.56)	a
Ethylbenzene	5	ND (0.60)		ND (0.60)		ND (0.60)	
Freon 113	5	ND (0.58)		ND (0.58)		ND (0.58)	
Isopropylbenzene	5	ND (0.65)		ND (0.65)		ND (0.65)	
m,p-Xylene	NS	ND (0.78)		ND (0.78)		ND (0.78)	
Methyl Acetate	NS	ND (0.80)		ND (0.80)		ND (0.80)	
Methyl Tert Butyl Ether	10	ND (0.51)		0.6	J	ND (0.51)	
Methylcyclohexane	NS	ND (0.60)		ND (0.60)		ND (0.60)	
Methylene chloride	5	ND (1.0)		ND (1.0)		ND (1.0)	
o-Xylene	5	ND (0.59)		ND (0.59)		ND (0.59)	
Styrene	5	ND (0.49)		ND (0.49)		ND (0.49)	
Tetrachloroethene	5	ND (0.90)		ND (0.90)		ND (0.90)	
Toluene	5	ND (0.53)		ND (0.53)		ND (0.53)	
trans-1,2-Dichloroethene	5	ND (0.54)		ND (0.54)		ND (0.54)	
trans-1,3-Dichloropropene	NS	ND (0.43)		ND (0.43)		ND (0.43)	
Trichloroethene	5	ND (0.53)		ND (0.53)		ND (0.53)	
Trichlorofluoromethane	5	ND (0.40)		ND (0.40)		ND (0.40)	
Vinyl chloride	2	ND (0.79)		ND (0.79)		ND (0.79)	
Xylene (total)	5	ND (0.59)		ND (0.59)		ND (0.59)	
VOC Total TICs	NS	0		0		0	

Results in Blue Highlight displays exceedance above the NYSDEC Ambient Water Quality Standards (AWQS)

J = Estimated concentration detected at a value above the MDL for target compounds

NS = No Standard Available

ND = Analyzed for but Not Detected at the MDL; **()** = The MDL for compounds that are non-detect

a Associated CCV outside of control limits low.

b Associated CCV outside of control limits high, sample was ND.

c Elevated detection limit due to dilution required for high interfering element.

Table 2 - Groundwater Results (cont'd) - SVOCs
78 Bridge Street
Tonawanda, New York

HK Engineering & Geology, D.P.C.
Project #: HK2550-1
Sample Date: 8/9/2021

Target Compounds	NYSDEC Ambient Water Quality Standards (AWQS)	TWP1		TWP3		TWP5	
Semivolatiles (µg/L)		Conc	Q	Conc	Q	Conc	Q
2-Chlorophenol	NS	ND (0.80)		ND (0.80)		ND (0.80)	
4-Chloro-3-methyl phenol	NS	ND (0.87)		ND (0.87)		ND (0.87)	
1,1'-Biphenyl	5	ND (0.21)		ND (0.21)		ND (0.21)	
1,2,4,5-Tetrachlorobenzene	5	ND (0.36)		ND (0.36)		ND (0.36)	
1,4-Dioxane	NS	ND (0.64)		ND (0.64)		ND (0.64)	
2,2'-Oxybis(1-chloropropane)	5	ND (0.40)		ND (0.39)		ND (0.40)	
2,3,4,6-Tetrachlorophenol	NS	ND (1.4)		ND (1.4)		ND (1.4)	
2,4,5-Trichlorophenol	NS	ND (1.3)		ND (1.3)		ND (1.3)	
2,4,6-Trichlorophenol	NS	ND (0.91)		ND (0.90)		ND (0.91)	
2,4-Dichlorophenol	1	ND (1.2)		ND (1.2)		ND (1.2)	
2,4-Dimethylphenol	1	ND (2.4)		ND (2.4)		ND (2.4)	
2,4-Dinitrophenol	1	ND (1.5)		ND (1.5)		ND (1.5)	
2,4-Dinitrotoluene	5	ND (0.54)		ND (0.54)		ND (0.54)	
2,6-Dinitrotoluene	5	ND (0.47)		ND (0.46)		ND (0.47)	
2-Chloronaphthalene	NS	ND (0.23)		ND (0.23)		ND (0.23)	
2-Methylnaphthalene	NS	ND (0.21)		ND (0.20)		ND (0.21)	
2-Methylphenol	NS	ND (0.87)		ND (0.86)		ND (0.87)	
2-Nitroaniline	5	ND (0.27)		ND (0.27)		ND (0.27)	
2-Nitrophenol	NS	ND (0.94)		ND (0.93)		ND (0.94)	
3&4-Methylphenol	NS	ND (0.86)		ND (0.85)		ND (0.86)	
3,3'-Dichlorobenzidine	5	ND (0.50)		ND (0.49)		ND (0.50)	
3-Nitroaniline	5	ND (0.38)		ND (0.38)		ND (0.38)	
4,6-Dinitro-o-cresol	NS	ND (1.3)		ND (1.3)		ND (1.3)	
4-Bromophenyl phenyl ether	NS	ND (0.40)		ND (0.39)		ND (0.40)	
4-Chloroaniline	5	ND (0.33)		ND (0.33)		ND (0.33)	
4-Chlorophenyl phenyl ether	NS	ND (0.36)		ND (0.36)		ND (0.36)	
4-Nitroaniline	5	ND (0.43)		ND (0.43)		ND (0.43)	
4-Nitrophenol	NS	ND (1.1)		ND (1.1)		ND (1.1)	
Acenaphthene	NS	ND (0.19)		ND (0.19)		ND (0.19)	
Acenaphthylene	NS	ND (0.13)		ND (0.13)		ND (0.13)	
Acetophenone	NS	ND (0.20)		ND (0.20)		ND (0.20)	
Anthracene	NS	ND (0.21)		0.28		ND (0.21)	
Atrazine	7.5	ND (0.44)		ND (0.43)		ND (0.44)	
Benzaldehyde	NS	ND (0.28)		ND (0.28)		ND (0.28)	
Benzo(a)anthracene	NS	ND (0.20)		0.63		0.25	J
Benzo(a)pyrene	ND	ND (0.21)		0.49 J		ND (0.21)	
Benzo(b)fluoranthene	NS	ND (0.20)		0.57	J	ND (0.20)	
Benzo(g,h,i)perylene	NS	ND (0.33)		ND (0.33)		ND (0.33)	
Benzo(k)fluoranthene	NS	ND (0.20)		ND (0.20)		ND (0.20)	
bis(2-Chloroethoxy)methane	5	ND (0.27)		ND (0.27)		ND (0.27)	
bis(2-Chloroethyl)ether	1	ND (0.24)		ND (0.24)		ND (0.24)	
bis(2-Ethylhexyl)phthalate	5	2		1.7	J	ND (1.6)	
Butyl benzyl phthalate	NS	ND (0.45)		ND (0.44)		ND (0.45)	
Caprolactam	NS	ND (0.64)	b	ND (0.63)	b	ND (0.64)	b
Carbazole	NS	ND (0.22)		0.25	J	ND (0.22)	
Chrysene	NS	ND (0.17)		0.54	J	ND (0.17)	
Dibenzo(a,h)anthracene	NS	ND (0.32)		ND (0.32)		ND (0.32)	
Dibenzofuran	NS	ND (0.22)		ND (0.21)		ND (0.22)	
Diethyl phthalate	NS	5.9		2.1		0.43	J
Dimethyl phthalate	NS	ND (0.21)		ND (0.21)		ND (0.21)	
Di-n-butyl phthalate	50	ND (0.49)		ND (0.48)		ND (0.49)	
Di-n-octyl phthalate	NS	ND (0.23)		ND (0.23)		ND (0.23)	
Fluoranthene	NS	ND (0.17)		1.2		0.22	J
Fluorene	NS	ND (0.17)		ND (0.17)		ND (0.17)	
Hexachlorobenzene	0.04	ND (0.32)		ND (0.32)		ND (0.32)	
Hexachlorobutadiene	0.5	ND (0.48)		ND (0.48)		ND (0.48)	
Hexachlorocyclopentadiene	5	ND (2.7)		ND (2.7)		ND (2.7)	
Hexachloroethane	5	ND (0.38)		ND (0.38)		ND (0.38)	
Indeno(1,2,3-cd)pyrene	NS	ND (0.33)		ND (0.32)		ND (0.33)	
Isophorone	NS	ND (0.27)		ND (0.27)		ND (0.27)	
Naphthalene	NS	ND (0.23)		ND (0.23)		ND (0.23)	
Nitrobenzene	0.4	ND (0.63)		ND (0.62)		ND (0.63)	
N-Nitroso-di-n-propylamine	NS	ND (0.47)		ND (0.47)		ND (0.47)	
N-Nitrosodiphenylamine	NS	ND (0.22)		ND (0.22)		ND (0.22)	
Pentachlorophenol	1	ND (1.4)		ND (1.3)		ND (1.4)	
Phenanthrene	NS	ND (0.17)		1		ND (0.17)	
Phenol	1	ND (0.38)		ND (0.38)		ND (0.38)	
Pyrene	NS	ND (0.21)		0.91	J	ND (0.21)	
SVOC Total TICs	NS	720.4	J	554.9	J	419.7	J

Results in Blue Highlight displays exceedance above the NYSDEC Ambient Water Quality Standards (AWQS)

J = Estimated concentration detected at a value above the MDL for target compounds

NS = No Standard Available

ND = Analyzed for but Not Detected at the MDL; () = The MDL for compounds that are non-detect

a Associated CCV outside of control limits low.

b Associated CCV outside of control limits high, sample was ND.

c Elevated detection limit due to dilution required for high interfering element.

Table 2 - Groundwater Results (cont'd) - Pesticides, PCBs, General Chemistry
78 Bridge Street
Tonawanda, New York

HK Engineering & Geology, D.P.C.

Project #: HK2550-1

Sample Date: 8/9/2021

Target Compounds	NYSDEC Ambient Water Quality Standards (AWQS)	TWP1		TWP3		TWP5	
Pesticides (µg/L)		Conc	Q	Conc	Q	Conc	Q
4,4'-DDD	0.3	ND (0.0029)		ND (0.0028)		ND (0.0029)	
4,4'-DDE	0.2	ND (0.0025)		ND (0.0025)		ND (0.0026)	
4,4'-DDT	0.2	ND (0.0034)		ND (0.0033)		ND (0.0035)	
Aldrin	ND	ND (0.0026)		ND (0.0025)		ND (0.0027)	
alpha-BHC	0.01	ND (0.0026)		ND (0.0025)		ND (0.0027)	
alpha-Chlordane	NS	ND (0.0025)		ND (0.0024)		ND (0.0025)	
beta-BHC	0.04	ND (0.0040)		ND (0.0039)		ND (0.0041)	
delta-BHC	0.04	ND (0.0033)		ND (0.0032)		ND (0.0034)	
Dieldrin	0.004	ND (0.0038)		ND (0.0037)		ND (0.0039)	
Endosulfan sulfate	NS	ND (0.0027)		ND (0.0026)		ND (0.0028)	
Endosulfan-I	NS	ND (0.0026)		ND (0.0026)		ND (0.0027)	
Endosulfan-II	NS	ND (0.0024)		ND (0.0024)		ND (0.0025)	
Endrin	ND	ND (0.0030)		ND (0.0029)		ND (0.0031)	
Endrin aldehyde	5	ND (0.0034)		ND (0.0033)		ND (0.0034)	
Endrin ketone	5	ND (0.0031)		ND (0.0030)		ND (0.0032)	
gamma-BHC (Lindane)	0.05	ND (0.0030)		ND (0.0029)		ND (0.0031)	
gamma-Chlordane	NS	ND (0.0021)		ND (0.0021)		ND (0.0022)	
Heptachlor	0.04	ND (0.0022)		ND (0.0022)		ND (0.0023)	
Heptachlor epoxide	0.03	ND (0.0030)		ND (0.0029)		ND (0.0031)	
Methoxychlor	35	ND (0.0034)		ND (0.0033)		ND (0.0034)	
Toxaphene	0.06	ND (0.082)		ND (0.079)		ND (0.084)	
PCBs (µg/L)		Conc	Q	Conc	Q	Conc	Q
Aroclor 1016	0.09	ND (0.098)		ND (0.095)		ND (0.10)	
Aroclor 1221	0.09	ND (0.21)		ND (0.20)		ND (0.21)	
Aroclor 1232	0.09	ND (0.13)		ND (0.13)		ND (0.13)	
Aroclor 1242	0.09	ND (0.11)		ND (0.11)		ND (0.12)	
Aroclor 1248	0.09	ND (0.063)		ND (0.061)		ND (0.065)	
Aroclor 1254	0.09	ND (0.21)		ND (0.20)		ND (0.21)	
Aroclor 1260	0.09	ND (0.076)		ND (0.074)		ND (0.078)	
Aroclor 1268	0.09	ND (0.087)		ND (0.084)		ND (0.089)	
Aroclor 1262	0.09	ND (0.097)		ND (0.094)		ND (0.099)	
General Chemistry (µg/L)		Conc	Q	Conc	Q	Conc	Q
Cyanide	200	<10		<10		<10	

Results in Blue Highlight displays exceedance above the NYSDEC Ambient Water Quality Standards (AWQS)

J = Estimated concentration detected at a value above the MDL for target compounds

NS = No Standard Available

ND = Analyzed for but Not Detected at the MDL; () = The MDL for compounds that are non-detect

a Associated CCV outside of control limits low.

b Associated CCV outside of control limits high, sample was ND.

c Elevated detection limit due to dilution required for high interfering element.

Table 2 - Groundwater Results (cont'd) - Metals
78 Bridge Street
Tonawanda, New York

HK Engineering & Geology, D.P.C.

Project #: HK2550-1

Sample Date: 8/9/2021

Target Compounds	NYSDEC Ambient Water Quality Standards (AWQS)	TWP1		TWP1 (Dissolved)		TWP3		TWP3 (Dissolved)		TWP5		TWP5 (Dissolved)	
		Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q	Conc	Q
Metals (µg/L)													
Aluminum	NS	27100		<200		13400		<200		135000		<200	
Antimony	3	<6.0		<6.0		<6.0		<6.0		<60		<6.0	
Arsenic	25	39.9	c	<3.0		50.4		8.4		167		3.2	
Barium	1000	<200		<200		326		<200		<2000		<200	
Beryllium	NS	2.4		<1.0		<1.0		<1.0		<10		<1.0	
Cadmium	5	<3.0		<3.0		<3.0		<3.0		<30		<3.0	
Calcium	NS	276000		122000		191000		119000		1080000		169000	
Chromium	50	101		<10		26.8		<10		358		<10	
Cobalt	NS	62.7		<50		<50		<50		<500		<50	
Copper	200	52.5		<10		27.6		<10		344		<10	
Iron	300	132000		2970		45100		268		387000		699	
Lead	25	70.1	c	<3.0		42.1		<3.0		601		<3.0	
Magnesium	NS	38600		16000		27800		10600		189000		20600	
Manganese	300	3290		386		1560		890		8630		1230	
Mercury	0.7	<1.2		<0.20		<0.60		<0.20		<1.2		<0.20	
Nickel	100	111		<10		40.6		<10		365		<10	
Potassium	NS	<10000		<10000		<10000		<10000		<100000		<10000	
Selenium	10	<10		<10		<10		<10		103		<10	
Silver	50	<10		<10		<10		<10		<100		<10	
Sodium	20000	12000		10200		<10000		<10000		116000		112000	
Thallium	NS	<10		<10		<10		<10		<100		<10	
Vanadium	NS	68.7		<50		<50		<50		<500		<50	
Zinc	NS	522		<20		198		22.7		2610		48.6	

Results in Blue Highlight displays exceedance above the NYSDEC Ambient Water Quality Standards (AWQS)

J = Estimated concentration detected at a value above the MDL for target compounds

NS = No Standard Available

ND = Analyzed for but Not Detected at the MDL; () = The MDL for compounds that are non-detect

a Associated CCV outside of control limits low.

b Associated CCV outside of control limits high, sample was ND.

c Elevated detection limit due to dilution required for high interfering element.

Table 2 - Groundwater Results (cont'd) - PFAS
78 Bridge Street
Tonawanda, New York

HK Engineering & Geology, D.P.C.

Project #: HK2550-1

Sample Date: 8/9/2021

Target Compounds	NYSDEC 2020 Drinking Water MCL	TWP1		TWP3		TWP5		PFAS - BLANK	
PFAS (ng/L)		Conc	Q	Conc	Q	Conc	Q	Conc	Q
Perfluorobutanoic acid	NS	378		2600		428		ND (1.9)	
Perfluoropentanoic acid	NS	1550		9690		1660		ND (0.96)	
Perfluorohexanoic acid	NS	1020		8600		1270		ND (0.96)	
Perfluoroheptanoic acid	NS	660		3980		846		ND (0.96)	
Perfluorooctanoic acid	10	486		5550		478		ND (0.96)	
Perfluorononanoic acid	NS	6		640		2.5		ND (0.96)	
Perfluorodecanoic acid	NS	ND (1.1)		9.8		0.97	J	ND (0.96)	
Perfluoroundecanoic acid	NS	ND (11)		12.4		ND (0.89)		ND (0.96)	
Perfluorododecanoic acid	NS	ND (11)		ND (0.93)		ND (0.89)		ND (0.96)	
Perfluorotridecanoic acid	NS	ND (11)		1.2	J	ND (0.89)		ND (0.96)	
Perfluorotetradecanoic acid	NS	ND (1.1)		ND (0.93)		ND (0.89)		ND (0.96)	
Perfluorobutanesulfonic acid	NS	90.9		2140		167		ND (0.96)	
Perfluorohexanesulfonic acid	NS	1220		44400		2590		ND (0.96)	
Perfluoroheptanesulfonic acid	NS	50.9		3590		83.4		ND (0.96)	
Perfluorooctanesulfonic acid	10	411		26900		188		ND (0.96)	
Perfluorodecanesulfonic acid	NS	ND (11)		2.7		ND (0.89)		ND (0.96)	
PFOSA	NS	ND (2.1)		14.9		ND (1.8)		ND (1.9)	
MeFOSAA	NS	ND (2.1)		ND (1.9)		ND (1.8)		ND (1.9)	
EtFOSAA	NS	ND (21)		ND (1.9)		ND (1.8)		ND (1.9)	
6:2 Fluorotelomer sulfonate	NS	2250		50900		2630		ND (1.9)	
8:2 Fluorotelomer sulfonate	NS	4.3	J	91.3		ND (1.8)		ND (1.9)	

Results in Blue Highlight displays exceedance above the NYSDEC Ambient Water Quality Standards (AWQS)

J = Estimated concentration detected at a value above the MDL for target compounds

NS = No Standard Available

ND = Analyzed for but Not Detected at the MDL; () = The MDL for compounds that are non-detect

Table 3 - Soil Vapor Results - VOCs
Timber Shore
78 Bridge Street, North Tonawanda, NY

HK Engineering & Geology, D.P.C.
Project #: HK-2550-1
Sample Date: 8/9/2021

Target Compounds	SV2		SV4		SV6	
Volatiles (µg/m ³)	Conc	Q	Conc	Q	Conc	Q
1,1,1-Trichloroethane	ND (0.71)		ND (0.36)		ND (0.18)	
1,1,2,2-Tetrachloroethane	ND (0.76)		ND (0.37)		ND (0.19)	
1,1,2-Trichloroethane	ND (0.65)		ND (0.33)		ND (0.16)	
1,1-Dichloroethane	ND (0.19)		ND (0.093)		ND (0.049)	
1,1-Dichloroethylene	ND (0.27)		0.79	J	ND (0.067)	
1,2,4-Trichlorobenzene	ND (2.6)		ND (1.3)		ND (0.66)	
1,2,4-Trimethylbenzene	27		1.7	J	30	
1,2-Dibromoethane	ND (0.55)		ND (0.28)		ND (0.14)	
1,2-Dichloroethane	ND (0.34)		ND (0.17)		ND (0.085)	
1,2-Dichloropropane	ND (0.36)		ND (0.18)		ND (0.088)	
1,3,5-Trimethylbenzene	8.8		4.8		8.4	
1,3-Butadiene	ND (0.40)		ND (0.20)		ND (0.10)	
1,4-Dioxane	ND (0.76)		14		ND (0.19)	
2,2,4-Trimethylpentane	ND (0.41)		145		ND (0.10)	
2-Chlorotoluene	ND (0.52)		5.7		ND (0.13)	
2-Hexanone	ND (0.61)		ND (0.30)		ND (0.15)	
3-Chloropropene	ND (0.50)		ND (0.25)		ND (0.13)	
4-Ethyltoluene	16		7.9		15	
Acetone	732		539		641	
Benzene	23		22		17	
Benzyl Chloride	ND (1.2)		ND (0.57)		ND (0.29)	
Bromodichloromethane	ND (0.74)		2.2		ND (0.18)	
Bromoethene	ND (0.38)		ND (0.19)		ND (0.096)	
Bromoform	ND (1.6)		29		ND (0.38)	
Bromomethane	ND (0.34)		ND (0.17)		ND (0.085)	
Carbon disulfide	377		32.7		18	
Carbon tetrachloride	ND (0.59)		ND (0.30)		ND (0.15)	
Chlorobenzene	ND (0.46)		28		ND (0.12)	
Chloroethane	ND (0.50)		ND (0.26)		ND (0.13)	
Chloroform	ND (0.39)		ND (0.20)		3.4	
Chloromethane	ND (0.13)		ND (0.064)		0.41	
cis-1,2-Dichloroethylene	ND (0.19)		1.2	J	ND (0.048)	
cis-1,3-Dichloropropene	ND (0.35)		ND (0.18)		ND (0.091)	
Cyclohexane	361		74.3		41.6	
Dibromochloromethane	ND (1.1)		7.2		ND (0.28)	
Dichlorodifluoromethane	2	J	2.1		1.6	
Ethanol	28.3		20.3		17	
Ethyl Acetate	ND (0.54)		ND (0.27)		ND (0.14)	
Ethylbenzene	14		52.1		6.9	
Freon 113	ND (0.52)		ND (0.26)		ND (0.13)	
Freon 114	ND (0.53)		ND (0.27)		ND (0.13)	
Heptane	496		152		66.8	
Hexachlorobutadiene	ND (1.9)		6.3		ND (0.49)	
Hexane	500		83.2		86.7	
Isopropyl Alcohol	3.2		ND (0.32)		ND (0.16)	
m,p-Xylene	73.4		43		27	
m-Dichlorobenzene	ND (0.46)		1.9		ND (0.11)	
Methyl ethyl ketone	68.4		25		27	
Methyl Isobutyl Ketone	ND (0.57)		ND (0.30)		ND (0.15)	
Methyl Tert Butyl Ether	ND (0.28)		ND (0.14)		ND (0.069)	
Methylene chloride	ND (0.20)		ND (0.10)		ND (0.052)	
Methylmethacrylate	ND (0.53)		55.7		ND (0.14)	
o-Dichlorobenzene	ND (0.52)		1.3		ND (0.13)	
o-Xylene	26		13		11	
p-Dichlorobenzene	ND (0.42)		1.4		ND (0.11)	
Propylene	ND (0.11)		ND (0.055)		ND (0.027)	
Styrene	ND (0.32)		1.7	J	0.72	J
Tertiary Butyl Alcohol	ND (0.17)		12		3.3	
Tetrachloroethylene	12		46		1.8	
Tetrahydrofuran	ND (0.59)		ND (0.29)		ND (0.15)	
Toluene	84		54.3		37	
trans-1,2-Dichloroethylene	ND (0.11)		ND (0.059)		ND (0.029)	
trans-1,3-Dichloropropene	ND (0.35)		ND (0.18)		ND (0.091)	
Trichloroethylene	ND (0.41)		39		ND (0.10)	
Trichlorofluoromethane	ND (0.62)		1.9		1.5	
Vinyl Acetate	ND (0.49)		ND (0.24)		ND (0.12)	
Vinyl chloride	ND (0.23)		ND (0.12)		ND (0.056)	
Xylenes (total)	99.5		56		38	

ND = Analyzed for but Not Detected at the MDL
() = The MDL for compounds that are non-detect
J = Estimated concentration detected at a value above the MDL

ATTACHMENT A

Soil Boring Logs

Soil Boring: SB1

See Figure 1

Location Sketch Map

Project:	HK-2550-1	Date Started:	8/9/2021	Permit No.:	Temporary
Client:	Timber Shore	Date Finished:	8/9/2021	Well Diameter:	1 Inch
Location:	78 Bridge St.	Boring Depth:	15 Feet	Well Material:	PVC
	Tonawanda, NY	GW Bore Depth:	-	Slot Size:	0.1
Drilling Co.:	NW Environmental/Nate	Lat/Northing:	-	Depth to GW:	4.97'
Rig Type:	Geoprobe 66DT	Long/Easting:	-	Screen Interval:	5'
Sample Type:	Dual Tube - 5'	Surface Elev:	Not Surveyed	Riser Interval:	10'
Geologist:	R. Powell	Install Method:	Direct Push	Flush/Stickup:	Stickup
				Development Method:	Bailer

Depth (ft bgs)	Stratigraphy Depth (ft bgs)	Stratigraphy Description	PID/OVM Reading (ppm)	Recovery (inches)	Comments
SURFACE					
0	0-2'	Brown silty clay	0	36	Sample S1A collected at 0-2'
			0		
1			0		
			0		
2	2-4'	Gray clay	0	36	Sample S1B collected at 2-4'
			0		
3			0		
			0		
4	4-15'	Gray sand (fine)	0	32	Wet at 4'
			0		
5			0		
			0		
6			0	39	TWP1 installed here
			0		
7			0		
			0		
8			0		
			0		
9			0		
			0		
10			0		
			0		
11			0		
			0		
12			0		
			0		
13			0		
			0		
14			0		
			0		
15		Boring Terminated at 15'	0		

Soil Boring: SB2

Project:	HK-2550-1	Date Started:	8/9/2021	Permit No.:	-
Client:	Timber Shore	Date Finished:	8/9/2021	Well Diameter:	-
Location:	78 Bridge St.	Boring Depth:	10 Feet	Well Material:	-
	Tonawanda, NY	GW Bore Depth:	-	Slot Size:	-
Drilling Co.:	NW Environmental/Nate	Lat/Northing:	-	Depth to GW:	-
Rig Type:	Geoprobe 66DT	Long/Easting:	-	Screen Interval:	-
Sample Type:	Dual Tube - 5'	Surface Elev:	Not Surveyed	Riser Interval:	-
Geologist:	R. Powell	Install Method:	Direct Push	Flush/Stickup:	-
				Development Method:	-

See Figure 1

Location Sketch Map

Depth (ft bgs)	Stratigraphy Depth (ft bgs)	Stratigraphy Description	PID/OVM Reading (ppm)	Recovery (inches)	Comments
SURFACE					
0	0-2.5'	Brown silty sand, trace red clay fragments	0	40	
			0		Sample S2A collected at 0-2'
1			0		
			0		Sample S2B collected at 2-4'
2	2.5-5'	Reddish brown clay	0	40	
			0		SV2 installed to 2'
3			0		
			0		
4	5-10'	Grayish brown silty sand	0	33	Wet at 4'
			0		
5			0		
			0		
6			0		
			0		
7			0		
			0		
8			0		
			0		
9			0		
10		Boring Terminated at 10'	0		

Soil Boring: SB3

See Figure 1

Location Sketch Map

Project:	HK-2550-1	Date Started:	8/9/2021	Permit No.:	Temporary
Client:	Timber Shore	Date Finished:	8/9/2021	Well Diameter:	1 Inch
Location:	78 Bridge St.	Boring Depth:	10 Feet	Well Material:	PVC
	Tonawanda, NY	GW Bore Depth:	-	Slot Size:	0.1
Drilling Co.:	NW Environmental/Nate	Lat/Northing:	-	Depth to GW:	4.75'
Rig Type:	Geoprobe 66DT	Long/Easting:	-	Screen Interval:	5'
Sample Type:	Dual Tube - 5'	Surface Elev:	Not Surveyed	Riser Interval:	5'
Geologist:	R. Powell	Install Method:	Direct Push	Flush/Stickup:	Stickup
				Development Method:	Bailer

Depth (ft bgs)	Stratigraphy Depth (ft bgs)	Stratigraphy Description	PID/OVM Reading (ppm)	Recovery (inches)	Comments
SURFACE					
0	0-2.5'	Brown silty clay	0	42	
			0		Sample S3A collected at 0-2'
1			0		
			0		Sample S3B collected at 2-4'
2	2.5-5'	Reddish brown silty sand	0		
			0		
3			0		TWP3 installed here
			0		
4	5-10'	Grayish brown silty sand	0	36	Wet at 5'
			0		
6			0		
			0		
7			0		
			0		
8			0		
			0		
9			0		
			0		
10		Boring Terminated at 10'	0		

Soil Boring: SB4

Project:	HK-2550-1	Date Started:	8/9/2021	Permit No.:	-
Client:	Timber Shore	Date Finished:	8/9/2021	Well Diameter:	-
Location:	78 Bridge St.	Boring Depth:	10 Feet	Well Material:	-
	Tonawanda, NY	GW Bore Depth:	-	Slot Size:	-
Drilling Co.:	NW Environmental/Nate	Lat/Northing:	-	Depth to GW:	5'
Rig Type:	Geoprobe 66DT	Long/Easting:	-	Screen Interval:	-
Sample Type:	Dual Tube - 5'	Surface Elev:	Not Surveyed	Riser Interval:	-
Geologist:	R. Powell	Install Method:	Direct Push	Flush/Stickup:	-
				Development Method:	-

See Figure 1

Location Sketch Map

Depth (ft bgs)	Stratigraphy Depth (ft bgs)	Stratigraphy Description	PID/OVM Reading (ppm)	Recovery (inches)	Comments
SURFACE					
0	0-5'	Dark brown sand (fine), gravel	0	22	
			0		Sample S4A collected at 0-2'
1			0		
			0		
2			0		SV4 installed to 2'
	5-10'	Brown sand (fine)	0	35	
3			0		
			0		Sample S4B collected at 3-5'
4			0		
			0		
5			0		Wet at 5'
			0		
6			0		
			0		
7			0		
			0		
8			0		
			0		
9			0		
			0		
10		Boring Terminated at 10'	0		

Soil Boring: SB5

Project:	HK-2550-1	Date Started:	8/9/2021	Permit No.:	Temporary
Client:	Timber Shore	Date Finished:	8/9/2021	Well Diameter:	1 Inch
Location:	78 Bridge St.	Boring Depth:	10 Feet	Well Material:	PVC
	Tonawanda, NY	GW Bore Depth:	-	Slot Size:	0.1
Drilling Co.:	NW Environmental/Nate	Lat/Northing:	-	Depth to GW:	5.5'
Rig Type:	Geoprobe 66DT	Long/Easting:	-	Screen Interval:	5'
Sample Type:	Dual Tube - 5'	Surface Elev:	Not Surveyed	Riser Interval:	5'
Geologist:	R. Powell	Install Method:	Direct Push	Flush/Stickup:	Stickup
				Development Method:	Bailer

See Figure 1

Location Sketch Map

Depth (ft bgs)	Stratigraphy Depth (ft bgs)	Stratigraphy Description	PID/OVM Reading (ppm)	Recovery (inches)	Comments
SURFACE					
0	0-5'	Brown Sand (fine), gravel	0	31	
			0		Sample S5A collected at 0-2'
1			0		
			0		
2			0		Sample S5B collected at 3-5'
	5-10'	Brownish gray sand (fine)	0	35	
			0		
3			0		
			0		
4			0		
			0		
5			0		Wet at 5'
			0		
6			0		TWP5 installed here
			0		
7			0		
			0		
8			0		
			0		
9			0		
			0		
10		Boring Terminated at 10'	0		

Soil Boring: SB6

See Figure 1

Location Sketch Map

Project:	HK-2550-1	Date Started:	8/9/2021	Permit No.:	-
Client:	Timber Shore	Date Finished:	8/9/2021	Well Diameter:	-
Location:	78 Bridge St.	Boring Depth:	10 Feet	Well Material:	-
	Tonawanda, NY	GW Bore Depth:	-	Slot Size:	-
Drilling Co.:	NW Environmental/Nate	Lat/Northing:	-	Depth to GW:	5'
Rig Type:	Geoprobe 66DT	Long/Easting:	-	Screen Interval:	-
Sample Type:	Dual Tube - 5'	Surface Elev:	Not Surveyed	Riser Interval:	-
Geologist:	R. Powell	Install Method:	Direct Push	Flush/Stickup:	-
				Development Method:	-

Depth (ft bgs)	Stratigraphy Depth (ft bgs)	Stratigraphy Description	PID/OVM Reading (ppm)	Recovery (inches)	Comments
SURFACE					
0	0-3.5'	Dark brown clay, gravel	0	33	
			0		Sample S6A collected at 0-2'
1			0		
			0		
2			0		
			0		SV6 installed to 3'
3	3.5-10'	Brown sand (coarse), gravel	0	29	Sample S6B collected at 3-5'
4			0		
			0		Wet at 5'
5			0		
			0		
6			0		
			0		
7			0		
			0		
8			0		
			0		
9			0		
			0		
10		Boring Terminated at 10'	0		

Soil Boring: SB7

See Figure 1

Location Sketch Map

Project: HK-2550-1 Date Started: 8/9/2021 Permit No.: -
 Client: Timber Shore Date Finished: 8/9/2021 Well Diameter: -
 Location: 78 Bridge St. Boring Depth: 10 Feet Well Material: -
 Tonawanda, NY GW Bore Depth: - Slot Size: -
 Drilling Co.: NW Environmental/Nate Lat/Northing: - Depth to GW: 5'
 Rig Type: Geoprobe 66DT Long/Easting: - Screen Interval: -
 Sample Type: Dual Tube - 5' Surface Elev: Not Surveyed Riser Interval: -
 Geologist: R. Powell Install Method: Direct Push Flush/Stickup: -
 Development Method: -

Depth (ft bgs)	Stratigraphy Depth (ft bgs)	Stratigraphy Description	PID/OVM Reading (ppm)	Recovery (inches)	Comments
SURFACE					
0	0-2.5'	Brown clay, gravel	0	37	
			0		Sample S7A collected at 0-2'
1			0		
			0		
2	2.5-5'	Brown sand (fine), gravel, trace clay	0	37	
3			0		
4			1.9		Sample S7B collected 3-5'
			0		
5	5-10'	Brown sand (coarse), gravel	0	22	Wet at 5'
			0		
6			0		
			0		
7			0		
			0		
8			0		
			0		
9			0		
			0		
10		Boring Terminated at 10'	0		

Soil Boring: SB8

See Figure 1

Location Sketch Map

Project:	HK-2550-1	Date Started:	8/9/2021	Permit No.:	-
Client:	Timber Shore	Date Finished:	8/9/2021	Well Diameter:	-
Location:	78 Bridge St.	Boring Depth:	5 Feet	Well Material:	-
	Tonawanda, NY	GW Bore Depth:	-	Slot Size:	-
Drilling Co.:	NW Environmental/Nate	Lat/Northing:	-	Depth to GW:	4'
Rig Type:	Geoprobe 66DT	Long/Easting:	-	Screen Interval:	-
Sample Type:	Dual Tube - 5'	Surface Elev:	Not Surveyed	Riser Interval:	-
Geologist:	R. Powell	Install Method:	Direct Push	Flush/Stickup:	-
				Development Method:	-

Depth (ft bgs)	Stratigraphy Depth (ft bgs)	Stratigraphy Description	PID/OVM Reading (ppm)	Recovery (inches)	Comments
SURFACE					
0	0-3.75'	Brown silty sand, gravel	0	48	
			0		Sample S8A collected at 0-2'
1			0		
			0		
2	3.75-5'	Brownish gray clay	0		
			0		
3			0		
			0		
4			0		Wet at 4'
			0		
5		Boring Terminated at 5'	0		

Soil Boring: SB9

See Figure 1

Location Sketch Map

Project: HK-2550-1 Date Started: 8/9/2021 Permit No.: -
 Client: Timber Shore Date Finished: 8/9/2021 Well Diameter: -
 Location: 78 Bridge St. Boring Depth: 5 Feet Well Material: -
 Tonawanda, NY GW Bore Depth: - Slot Size: -
 Drilling Co.: NW Environmental/Nate Lat/Northing: - Depth to GW: Not Encountered
 Rig Type: Geoprobe 66DT Long/Easting: - Screen Interval: -
 Sample Type: Dual Tube - 5' Surface Elev: Not Surveyed Riser Interval: -
 Geologist: R. Powell Install Method: Direct Push Flush/Stickup: -
 Development Method: -

Depth (ft bgs)	Stratigraphy Depth (ft bgs)	Stratigraphy Description	PID/OVM Reading (ppm)	Recovery (inches)	Comments
SURFACE					
0	0-1'	Light brown sand (fine), gravel	0	20	
			0		Sample S9A collected at 0-2'
1	1-2'	Light brown clayey sand	0		
			0		
2	2-5'	Brown clay	0		
			0		
3			0		
			0		
4			0		
			0		
5		Boring Terminated at 5'	0		

Attachment C

Site-specific Health & Safety Plan



HK ENGINEERING & GEOLOGY, D. P.C.

1600 Route 22 East
Union, New Jersey 07083
(908) 688-7800 • (908) 688-2636 – Fax

Site Specific HEALTH AND SAFETY PLAN

Address: 78 Bridge Street
North Tonawanda, New York 14120

Project Number: HK2550

Plan Revisions

Number	Date	Initials
1	<u>3-21-2022</u>	<u>DA</u>

Dominick Aponte
Plan Preparer

3-21-2022
Date

Ryan Powell
Site Supervisor

3-21-2022
Date

Chris Hirschmann
Site Health & Safety Officer

3-21-2022
Date

Stephanie Lamb
Alternate Site Health & Safety Officer

3-21-2022
Date

Table of Contents

	<u>Page</u>
Introduction.....	1
Site Information	2
Emergency Contacts	5
Emergency Contact List Cell Phone Numbers	6
Key Project Personnel.....	7
Medical Surveillance and Training Dates for Authorized Personnel	8
Task Identification	9
Chemical Hazards	10
Physical and Biological Hazards	11
Risk Analysis	12
General Safety Rules.....	14
Employee Training Program.....	15
Personal Protective Equipment (PPE) Requirements	16
Suggested Levels of Protection.....	17
Medical Surveillance	18
Monitoring Requirements	19
Air Monitoring and Contaminant Action Levels	20
Procedures for Handling Anticipated Wastes	21
Decontamination Procedures.....	21
Spill Prevention and Response.....	22
Emergency Procedure	24
Subcontractor Safety	28

FORMS

- Safety Data Sheets
- HASP Sign-off
- Equipment Calibration Log
- Sampling Log
- Heat Stress Monitoring Log
- Daily Sign In/Sign Out
- Daily Safety Meeting Log
- Accident Injury Report
- Vehicle Accident Report

Introduction

This Health and Safety Plan (HASP) has been prepared by HK Engineering & Geology, D.P.C. (HK) to summarize the health and safety hazards at the subject site and the requirements and procedures to protect its employees from them. Site is located at 78 Bridge Street, North Tonawanda, NY 14120 This plan meets or exceeds the requirements of Occupational Safety and Health Administration (OSHA), 29 CFR 1910.120, for a site-specific health and safety plan.

This plan was designed to reduce the potential for occupational illness or injury resulting from working at this site. The purpose of the HASP is to inform HK Engineering & Geology, D.P.C.'s employees and subcontractors of the health and safety risks present at this site, and the proper methods of protecting themselves from those risks. Each worker must be fully aware of the risks associated with the work to be accomplished, and be dedicated to completing that work safely.

Existing and potential hazards at this site have been identified. As new information becomes available, this HASP will be revised. Standard practices and procedures of industrial hygiene, occupational health, safety, and environmental protection are prescribed in this plan, which was prepared and reviewed by experienced professionals.

HK Engineering & Geology, D.P.C. employees who work on this site must read the HASP and sign the form included in this plan, to indicate that they understand the plan's contents, and agree to comply with its provisions. Anyone who cannot, or will not comply with this HASP will be excluded from on-site activities. Violations of this HASP or any applicable federal, state, or local health and safety regulations should be reported immediately to the Site Health and Safety Supervisor (SHSO), or to HK Engineering & Geology, D.P.C.'s Director, Health & Safety (DHS).

This HASP will be readily available on site so workers can reference it when necessary.

Site Information

Location: 78 Bridge Street, North Tonawanda, NY, 14120

Historical/Current Site Information: The site is currently a vacant lot and vacant 2-story structure.

Location/Class: ☐ Industrial ☒ Commercial ☐ Urban/Residential
☐ Suburban ☐ Rural

Site Regulatory Status: ☐ CERCKA/SARA ☐ US EPA ☐ NYCDEP
☐ NPL ☐ RCRA ☐ NYCOER
☒ NYSDEC ☐ Not Regulated ☐ Due Diligence

Operations or Tasks to be Performed, and Approximate Duration of Each:

1- Soil, soil vapor sampling; groundwater monitoring well installs (~5 days)

Surrounding Population/Structures:

Commercial

Site and Surrounding Topography:

Generally Flat Terrain

Known or Suspected Pathways of Contaminant Dispersion:

Soil, groundwater, and soil vapor

Emergency Shower, Eyewash and First Aid Equipment Located at:

Eyewash and emergency shower will not be available.

First aid provided by emergency services (911).

Personnel On-Site trained in First Aid:

- | | |
|--------------------------|----------|
| 1. <u>Ryan K. Powell</u> | 5. _____ |
| 2. _____ | 6. _____ |
| 3. _____ | 7. _____ |
| 4. _____ | 8. _____ |

Emergency Medical Care

Hospital #1

Hospital Name: DeGraff Memorial Hospital

Telephone # (716) 694-4500

Address: 445 Tremont St, North Tonawanda, NY 14120

Telephone # 911

Contact: N/A

Type of Service (X) Physical Trauma Only

() Physical Trauma and Chemical Exposure


(X) Available 24 Hours

Hospital Route:

See attached map

****Hospital route information has been provided to satisfy OSHA requirements (29 CFR 1910.120). However, where 911-emergency service and/or transport is available, HK Engineering & Geology, D.P.C. personnel are strictly prohibited from transporting accident victims in either company or personal vehicles.**

Transporting the injured in non-emergency vehicles increases the potential for motor vehicle accidents during transit to the hospital and further injury to the victim. Also, the victims' condition can worsen during transit. As a result, transportation in non-emergency vehicles can delay or even prevent treatment by trained emergency personnel during a critical time. Employees must remain at the site of the accident, administer appropriate first aid, and await the arrival of **trained emergency and/or rescue personnel**.



Map data ©2021 500 ft

78 Bridge St

North Tonawanda, NY 14120

- ↑

1. Head west on Bridge St toward Detroit St

374 ft
- ↘

2. Turn right onto Michigan St

390 ft
- ↘

3. Turn right onto Taylor Dr

0.1 mi
- ↑

4. Continue onto Thompson St

0.2 mi
- ↘

5. Turn right onto Main St

0.4 mi
- ↙

6. Turn left onto Tremont St

0.7 mi
- ↘

7. Turn right

i

Destination will be on the left

52 ft

DeGraff Memorial Hospital

445 Tremont St, North Tonawanda, NY 14120

Emergency Medical Care

Hospital #2

Hospital Name: Niagara Falls Memorial Medical Center

Telephone # (716) 278-4000

Address: 621 10th St, Niagara Falls, NY 14301

Contact: N/A

Telephone # 911

Type of Service (X) Physical Trauma Only
 () Physical Trauma and Chemical Exposure
 (X) Available 24 Hours

Hospital Route:

See attached map


****Hospital route information has been provided to satisfy OSHA requirements (29 CFR 1910.120). However, where 911-emergency service and/or transport is available, HK Engineering & Geology, D.P.C. personnel are strictly prohibited from transporting accident victims in either company or personal vehicles.**

Transporting the injured in non-emergency vehicles increases the potential for motor vehicle accidents during transit to the hospital and further injury to the victim. Also, the victims' condition can worsen during transit. As a result, transportation in non-emergency vehicles can delay or even prevent treatment by trained emergency personnel during a critical time. Employees must remain at the site of the accident, administer appropriate first aid, and await the arrival of **trained emergency and/or rescue personnel**.



78 Bridge Street, North Tonawanda, NY to Niagara Falls Memorial Medical Center

Drive 11.4 miles, 20 min



Map data ©2021 Google 2 mi

78 Bridge St


North Tonawanda, NY 14120


Take NY-265 N/River Rd to LaSalle Expy in Wheatfield


- 9 min (5.2 mi)
- ↑ 1. Head west on Bridge St toward Detroit St
- 374 ft
- ➔ 2. Turn right onto Michigan St
- 390 ft
- ➔ 3. Turn right onto Taylor Dr
- 0.1 mi
- ↑ 4. Continue onto Thompson St
- 0.1 mi
- ↶ 5. Turn left onto NY-265 N/River Rd
- 4.6 mi
- ➔ 6. Turn right onto Williams Rd
- 0.2 mi


Continue on LaSalle Expy. Take US-62 N to Walnut Ave in Niagara Falls



- 11 min (6.2 mi)
- ↶ 7. Turn left onto LaSalle Expy
- 2.2 mi


-  8. Use the 2nd from the left lane to stay on LaSalle Expy

0.3 mi
-  9. Take the Inter State 190 N exit toward Lewiston Rd

0.3 mi
-  10. Merge onto I-190 N

0.2 mi
-  11. Take exit 22 for US-62/Niagara Falls Blvd toward Business District/Airport

0.2 mi
-  12. Turn left onto US-62 N/Niagara Falls Blvd
 Continue to follow US-62 N

1.3 mi
-  13. Continue straight onto Walnut Ave

1.7 mi

Niagara Falls Memorial Medical Center

621 10th St, Niagara Falls, NY 14301

These directions are for planning purposes only. You may find that construction projects, traffic, weather, or other events may cause conditions to differ from the map results, and you should plan your route accordingly. You must obey all signs or notices regarding your route.

Emergency Contacts

<u>Agency</u>	<u>Name</u>	<u>Phone</u>
Fire Department	FDNY	911
Police Department	NYPD	911
Site Contact	Ryan K. Powell	(908) 323-4051
First Aid/EMS	NA	911
Federal Agency Representative	NA	NA
State Agency Representative	NA	NA
Local Agency Representative	NA	NA
NYSDEC- Region 2	New York	1-718-482-4900
Pesticide Poisoning	NA	NA
Poison Control	U.S.A.	(800) 222-1222
CHEM TREC	Washington, DC	(800) 424-9300
<u>Utility</u>	<u>Company Name</u>	<u>Phone</u>
Water Supply	NYC.	800-987-5325
Sewer	NYC.	908-647-0070
Power	CON-ED	(800) 322-3223
Gas	National Grid	(800) 322-3223
NY One Call	NY	811

HK Engineering & Geology D.P.C.
Emergency Contact List
Cell Phone Numbers

Chris Hirschmann	(908) 377-8909
Ryan K. Powell	(908) 323-4051
Stephanie Lamb	(908) 721-7711
Dominick Aponte	(908) 335-6048

Key Project Personnel

The following describes the project position assignments, associated responsibilities, and reporting relationships.

Position	Job Description	Interactions
Director	Responsible for technical and administrative performance of the project. Supports Site Supervisor and is available to him at all times. Will visit the site periodically, or as necessary. Reports progress of project on a regular basis. Assigns key personnel, and identifies, requests, secures, and monitors use of resources for project. Approves program expenditures and invoices.	Reports directly to President. Works closely with Site Supervisor.
Site Supervisor	Acts as point of contact for client and client's representative(s). Supervises all on-site personnel and subcontractors. Coordinates daily site-specific work efforts, and ensures all activities are in strict compliance with site-specific health and safety plan. Has authority to suspend all work that possesses any health and safety risk. Briefs subordinate technical personnel on task requirements. Identifies and resolves technical problems. Provides periodic review of project progress.	Reports directly to Project Manager.
Site Health & Safety Officer (SHSO)	Assures compliance with HASP. Instructs site personnel in health and safety procedures through daily pre-work meetings. Performs any monitoring activities as required. Has authority to discontinue site operations if safety violations exist.	Reports directly to Project Manager. Works closely with Director, Health & Safety, and Site Supervisor.
Director, Health & Safety (DHS)	Develops, implements, and enforces the on-site safety program. Oversees all health and safety aspects of project, conducts periodic audits to ensure compliance. Available at all times to discuss project progress and health and safety related issues.	Reports directly to President. Works closely with Project Manager, Site Supervisor, and SHSO.

HK Engineering & Geology, D.P.C. is the entity responsible for managing health and safety at this site. Key project personnel are as follows:

Director:	<u>Chris Hirschmann</u> Name	<u>908-688-7800 / 908-377-8909</u> Telephone / Cellular Number
Site Supervisor:	<u>Ryan K. Powell</u> Name	<u>908-688-7800 / 908-323-4051</u> Telephone / Cellular Number
SHSO:	<u>Chris Hirschmann</u> Name	<u>908-688-7800 / 908-377-8909</u> Telephone / Cellular Number
Alternate SHSO:	<u>Stephanie Lamb</u>	<u>908-688-7800 / 908-721-7711</u>

Medical Surveillance and Training Dates for Authorized Personnel

Employee	Medical Exam	OSHA 8-Hr.	Site Supervisor Training	Respirator Fit Test
Dominick Aponte	06/2021	10/2020		07/2021
Chris Hirschmann	09/2020	07/2021	06/2010	
Ryan Powell	02/2021	07/2021		10/2018

Task Identification

Tasks covered under this plan:

Task #	Description
1	Soil, Groundwater and Soil Vapor sampling; monitoring well installs

Off-site tasks planned? No

Describe:

Chemical Hazards

Task No.(s)	Chemical Name (or class)	PEL	TLV	Other Pertinent Limits (specify)	Primary Hazard			SDS Attached
					Ingestion	Dermal	Inhalation	Y/N
1	Semi volatiles:							
	Benzo(a)anthracene	**	**		X	X	X	N
	Benzo(b)fluoranthene	**	**		X	X	X	N
	Benzo(k)fluoranthene	**	**		X	X	X	N
	Benzo (a) pyrene	0.2 mg/m ³	**		X	X	X	N
	Dibenz(a,h)anthracene	**	**		X	X	X	N
	Indeno(1,2,3-cd)pyrene	**	**		X	X	X	N
	Chrysene	2,400 mg/m ³	1,188 mg/m ³		X	X	X	N
	1,1 biphenyl	1 mg/m ³	0.2 ppm		X	X	X	N
	2-Methylnaphthalene	**	**		X	X	X	N
	3&4-Methylphenol	**	**		X	X	X	N
	Acenaphthene	**	**		X	X	X	N
	Acenaphthylene	**	**		X	X	X	N
	Anthracene	**	**		X	X	X	N
	Benzaldehyde	2 ppm	**		X	X	X	N
	Benzo(g,h,i)perylene	**	**		X	X	X	N
	Carbazole	**	**		X	X	X	N
	Dibenzofuran	**	**		X	X	X	N
	Fluoranthene	**	**		X	X	X	N
	Fluorene	**	**		X	X	X	N
	Naphthalene	50 mg/m ³	10 ppm		X	X	X	N
	Phenanthrene	0.2 mg/m ³	**		X	X	X	N
	Pyrene	**	**		X	X	X	N
1	Pesticides:							
	4'4 DDE	**	**		X	X	X	N
	4'4 DDT	1 mg/m ³	1 mg/m ³		X	X	X	N

1	4'4 DDD	5 mg/m ³	**	X	X	X	N
	Volatiles:						
	Acetone	1000 ppm	250 ppm	X	X	X	N
	2 – Butanone (MEK)	200 ppm	200 ppm	X	X	X	N
	Carbon Disulfide	20 ppm	1 ppm	X	X	X	N
	Ethylbenzene	100 ppm	**	X	X	X	N
	o-xylene	**	100 ppm	X	X	X	N
	Styrene	100 ppm	10 ppm	X	X	X	N
	Toluene	200 ppm	20 ppm	X	X	X	N
	Xylene	100 ppm	**	X	X	X	N
	PCE	125 ppm	125 ppm	X	X	X	N
	TCE	100 ppm	10 ppm	X	X	X	N
	Benzene	0.5 ppm	**	X	X	X	N
	cis-1,2-Dichloroethylene	**	200 ppm	X	X	X	N
	1,2,4-Trimethylbenzene	**	200 ppm	X	X	X	N
	1,3,5-Trimethylbenzene	20 ppm	**	X	X	X	N
	Chlorobenzene	10 ppm	10 ppm	X	X	X	N
	Chloroform	2 ppm	10 ppm	X	X	X	N
	Chloromethane	50 ppm	**	X	X	X	N
	Dichlorodifluoromethane	1000 ppm	1000 ppm	X	X	X	N
	Ethanol	1000 ppm	1000 ppm	X	X	X	N
	Heptane	500 ppm	400 ppm	X	X	X	N
	Hexachlorobutadiene	**	0.02 ppm	X	X	X	N
	Hexane	50 ppm	50 ppm	X	X	X	N
	Isopropyl Alcohol	400 ppm	200 ppm	X	X	X	N
	m & p-xylene	**	**	X	X	X	N
	m-Dichlorobenzene	**	**	X	X	X	N
	Methyl ethyl ketone	200 ppm	200 ppm	X	X	X	N
	Methyl-methacrylate	50 ppm	100 ppm	X	X	X	N
	o-Dichlorobenzene	50 ppm	25 ppm	X	X	X	N
	Tertiary Butyl Alcohol	100 ppm	100 ppm	X	X	X	N
	Trichlorofluoromethane	1,000 ppm	1,000 ppm	X	X	X	N

1	Metals:						
	Aluminum	0.05 mg/m ³	0.05 mg/m ³	X	X	X	N
	Lead	0.01 mg/m ³	**	X	X	X	N
	Arsenic	1 mg/m ³	0.5 mg/m ³	X	X	X	N
	Selenium	0.03 mg/m ³	0.1 mg/m ³	X	X	X	N
	Mercury	1 mg/m ³	1.5 mg/m ³	X	X	X	
	Nickel	**	**	X	X	X	N
	Sodium	**	**	X	X	X	N
	Zinc	**	**	X	X	X	N
	Beryllium	0.002 mg/m ³	**	X	X	X	N
	Cadmium	0.2 mg/m ³	0.02 mg/m ³	X	X	X	N
	Chromium	1 mg/m ³	0.5 mg/m ³	X	X	X	N

PEL – OSHA Permissible Exposure Limit: the maximum allowable 8-hour time weighted average (TWA) exposure concentration.

TLV – ACGIH Threshold Limit Value: the recommended 8-hour TWA exposure concentration.

STEL – ACGIH or OSHA Short-term Exposure Limit: the maximum allowable 15-minute TWA exposure concentration.

Ceiling – OSHA and Cal-OSHA Ceiling Limit: the maximum exposure concentration above, which an employee shall not be exposed during any period without respiratory protection.

IDLH – Immediately Dangerous to Life and Health: the concentration at which one could be exposed for 30 minutes without experiencing escape-impairing or irreversible health effects.

** – Exposure limits not available

Physical and Biological Hazards

Hazard	Yes	No	Task No.(s)	Hazard	Yes	No	Task No.(s)
Electrical (overhead lines)	X		1	Uneven Terrain	X		1
Electrical (underground lines)	X		1	Unstable Surfaces	X		1
Gas Lines	X		1	Elevated Surfaces		X	
Water Lines	X		1	Lightning	X		1
Drilling Equipment	X		1	Rain	X		1
Excavation Equipment		X		Snow		X	
Power Tools	X		1	Liquefied/Pressurized Gases		X	
Heat Exposure	X		1	Lifting Equipment	X		1
Cold Exposure	X		1	Vermin	X		1
Oxygen Deficiency		X		Insects	X		1
Confined Spaces		X		Disease-causing organisms	X		1
Noise	X		1	Others, e.g., marine sampling (specify)		X	
Ionizing Radiation		X					
Non-Ionizing Radiation		X					
Fire		X					
Explosive Atmospheres		X					
Shoring		X					
Scaffolding		X					
Holes/Ditches	X		1				
Steep Grades		X					
Slippery Surfaces		X					

Risk Analysis

Task #	Substance	Concentration (if known)	Risk*
1	VOCs, SVOCs, pesticides, PCBs and heavy metals	Low	0-1

*Risk

- 0 – No Risk
- 1 – Slight Risk
- 2 – Moderate Risk
- 3 – Dangerous Conditions/Caution
- 4 – High Risk
- 5 – Extremely Dangerous

General Safety Rules

1. If an employee must work alone, he/she must call his/her supervisor twice a day. If the supervisor is unavailable, that supervisor's supervisor must be contacted.
2. Workers must wear all personal protective equipment required for the tasks to be performed.
3. Horseplay, scuffling, or practical jokes are forbidden on the job.
4. Compressed air must not be used to blow dirt from clothing, or played with or blown at another person. In addition, compressed air tools should be checked periodically for hose leaks, faulty valves and tank pressurization issues as a precursor for potential injury.
5. Drinking of alcoholic beverages or the use of drugs on the job is prohibited. Their use will cause immediate dismissal.
6. All areas must be continually cleaned to maintain good housekeeping. Trash is to be piled neatly and removed promptly. All tools and work areas are to be kept in clean and safe condition. Hard floor surfaces should be kept as dry as possible and free of debris in walking zones to prevent potential slips, trips and falls. If an area of flooring will be slippery for an extended period of time, efforts should be taken to provide caution signs or high visibility cones/barricades to warn and prevent entrance into the zone.
7. Competent workers must do welding and cutting. Anyone who is required to work in "hot" zones must wear or be provided with proper eye protection and warning that welding will be taking place.
8. A. Ladders are to be of proper design and tied off while in use. Do not go up or down a ladder without the free use of both hands. Use a rope to lift or lower materials or tools. Always face a ladder when climbing or descending. Ladders with structural defects should be discontinued from use and placed aside with a label to warn others not to use until serviced or replaced. Defects include, but are not limited to, bent or broken ladder rung/step, bent or cracked frame rails, defected foot holds etc.

B. Extreme caution must be used with operating with ladders to avoid overhead hazards such as unstable roofing materials or over-head utility lines. Before setting up your ladder, always assess for over-head power lines and avoid operating within those areas. If you have any doubts, don't do it.
9. Every work site must have a qualified first aid person and a complete first aid kit. All first aid materials are to remain clean, unused and non-expired. The first aid materials should remain with a competent first aid responder or in an inconspicuous area for all to use if needed. Eye wash stations or portable bottles should be readily on hand to field personnel in the event of an eye irritant or splashing occurrence. Eye protection should be used to further prevent eye injuries.
10. **ALL** accidents must be investigated and reported. Use the Accident Investigation Form in the back section of this plan.
11. Injuries sustained while on duty must be reported to supervisor immediately, or as soon as possible after injury is sustained.
12. Explosives must be handled and transported by licensed people only. Any doubts of explosive materials should be handled with extreme caution and the project manager notified for further instruction.
13. All tools and electrical equipment must be in proper working order. If a tool is broken/near broken or a piece of electrical equipment has frayed/exposed wiring, sparks generated or missing screws or parts, make sure to disengage use of tool. Faulty tools should be labeled with a "Do NOT use" label and placed in a safe location until it can be serviced or replaced.
14. Clothing appropriate to the duties performed shall be worn by all workers. Large pockets, loose jewelry, cuffed trousers and loose or torn clothing are dangerous and should not be worn around machinery, or when climbing ladders, or working on structures.

Employee Training Program

All personnel performing work in areas on this site covered by this HASP must have completed the appropriate training requirements specified in 29 CFR 1910.120(e). Each individual must have completed an 8-hour refresher-training course and/or initial 40-hour training course within the last year prior to performing any intrusive work on this site covered by this HASP. Also, on-site managers must have completed the specified 8-hour supervisor's training course. Records that demonstrate that all persons subject to the training requirements have actually met them will be maintained on site. The Project Manager is responsible for verifying compliance of the project team with these rules.

Prior to commencement of on-site activities, a site safety meeting will be held to review the specific information and requirements of this HASP. HASP sign-off sheets will be collected at this meeting.

Site Specific Training will include:

- Explanation of the overall site HASP.
- Health and safety personnel and organization.
- Brief site history.
- Special attention to signs and symptoms of overexposure to known and suspected site contaminants.
- Health effects of site contaminants.
- Air monitoring description.
- Physical hazards associated with the project.
- Selection, use and limitations of available safety.
- Personal hygiene and decontamination.
- Respirator facepiece fit testing.
- PPE use and maintenance.
- Site rules and regulations.
- Work zone establishment and markings.
- Site communication.
- Emergency preparedness procedures.
- Equipment decontamination.
- Medical monitoring procedures.
- Contingency plan.

Prior to work, each HK Engineering & Geology, D.P.C. employee will attend the contractor's health and safety orientation, if applicable. In addition, HK Engineering & Geology, D.P.C.'s employees will review health and safety items specific to the tasks to be performed that were not covered in the contractor's orientation.

Site Health and Safety Meetings

In addition, the SHSO will meet daily with all HK Engineering & Geology, D.P.C. employees prior to beginning work on site. The agenda of the meeting will include a review of important elements of this plan, any special safety items, and a discussion of the emergency response procedures. Also, everyone will agree on a schedule for periodic meetings, (for example, before beginning work each day), to review the effectiveness of this plan and make changes as necessary. If significant changes at the site occur, special meetings will be scheduled. (If HK Engineering & Geology, D.P.C. is a subcontractor, all HK Engineering & Geology, D.P.C. employees on site will participate in the contractor's daily safety meetings.)

Training Records

The SHSO will complete a report of the daily safety meetings, using the form in the back section of this plan, and all attending the meeting will sign the Daily Safety Meeting Log.

The training status of contractor and subcontractor employees has been verified, and their training criteria meet the requirements specified in 29 CFR 1910.120(e). A copy of all training certificates will be kept at the job site for each person working at the site.

Personal Protective Equipment (PPE) Requirements

Task No.(s)	Level of Protection (A – D)*	Level of Upgrade	PPE Suit	PPE Gloves	PPE Feet	PPE Head	PPE Eye	PPE Ear	PPE Respirator	Additional PPE for Upgrade
1	D	When necessary	Std	N	Steel	When needed	Glasses	Plugs	NA	None
<u>SUIT</u> Std = Standard Work Clothes Tyvek = Uncoated Tyvek Disposal Coverall PE Tyvek = Polyethylene-coated Tyvek Saranex = Saranex-laminated Tyvek PVC Suite = PVC Raingear <u>GLOVES</u> Work = Work Gloves (canvas, leather) Neo = Neoprene Gloves PVC = PVC Gloves N = Nitrile Gloves V = Vinyl Gloves L = Latex Gloves				<u>FEET</u> Steel = Steel-toe shoes or boots Steel+ = Steel-toe PVC boots Booties = PVC booties <u>HEAD</u> HH = Hardhat <u>EYE</u> Glasses = Safety glasses Goggles = Goggles Shield = Face shield <u>EAR</u> Plugs = Earplugs Muff = Ear muffs			<u>RESPIRATOR</u> APR = Air purifying respirator Full APR = Full face APR Half APR = Half face APR SAR = Airline supplied air respirator SCBA = Self contained breathing apparatus Escape = Escape SCBA OV = Organic Vapor Cartridge AG = Acid Gas Cartridge OV/AG = Organic Vapor/Acid Gas Cartridge AM = Ammonia Cartridge Dust/Mist = Dust/Mist pre-filter and cover for cartridge HEPA = High efficiency particulate air filter cartridge			

- For unspecified volatile organics (based on 1-minute breathing zone measurement using PID or OVA):
- | | |
|------------------------------|---------|
| Up to 1 ppm above background | Level D |
| 1 – 5 ppm above background | Level C |
| 5 – 500 ppm above background | Level B |
| 500 ppm above background | Level A |

Suggested Levels of Protection

Level “D” Protection

1. Coveralls
2. Gloves
3. Boots/shoes – steel toe
4. Boots (outer) chemical resistant (disposable)
5. Safety glasses or chemical splash goggles
6. Hard hat (safety shield)
7. High visibility vest

Level “C” Protection

1. Full-face, air-purifying, canister-equipped respirator (NIOSH/MSHA approved)
2. Chemical resistant clothing (coveralls; hooded, two-piece, chemical splash suit; chemical resistant hood & apron; disposable, chemical-resistant coveralls)
3. Coveralls
4. Gloves (outer) chemical-resistant
5. Gloves (inner) chemical-resistant
6. Boots (outer) chemical-resistant
7. Boots (inner) chemical-resistant
8. Hard hat (face shield)
9. Escape mask
10. Two-way radio

Level “B” Protection

1. Pressure/Demand SCBA (MSHA-NIOSH approved)
2. Chemical resistant clothing (overalls and long-sleeved jacket; coveralls; hooded, one- or two-piece chemical splash suite; disposable, chemical-resistant coveralls)
3. Coveralls
4. Gloves (outer) chemical-resistant
5. Gloves (inner) chemical-resistant
6. Boots (outer) chemical-resistant
7. Boots (inner) chemical-resistant
8. Hard hat (face shield)
9. Two-way radio

Level “A” Protection

1. Pressure/Demand SCBA (MSHA-NIOSH approved)
2. Fully encapsulating, chemical-resistant suit
3. Coveralls
4. Gloves (outer) chemical-resistant
5. Gloves (inner) chemical-resistant
6. Boots, chemical-resistant, steel toe (depending on suit construction, work over or under suit boot)
7. Hard hat (under suit)
8. Two-way radio

Medical Surveillance

Requirements

All HK Engineering & Geology, D.P.C. employees covered by this HASP, who engage in on site activities governed by 29 CFR 1910.120 for 30 or more days per year, must meet the medical surveillance requirements specified in 1910.120(f). Therefore, such personnel must have completed occupational medical baseline or surveillance examination, performed by a licensed physician, within the last 24 months. The medical examination includes the following components:

- Personal Medical Questionnaire
- Occupational Exposure History
- Physical Examination
- Vision Testing
- Spirometry
- Audiometry
- Blood Chemistry Panel (e.g., SMAC-20)
- Complete Blood Count with Differential
- Urinalysis
- Chest X-Ray (every two years at a minimum)
- Electrocardiogram (at physician's discretion)

Examinations are required upon hiring, termination, and exposure to substances at or above the PEL.

Results of the examinations are communicated directly from the physician to the employee. Medical records for HK Engineering & Geology, D.P.C.'s employees are kept by the physician:

Washington Occupational Health
1120 19th Street, Suite 410
Washington, DC 20036
800-777-9642 – office
800-865-6525 – fax

Monitoring Requirements

Monitoring is to be conducted by the SHSO, or his/her designee. The results will be interpreted by the SHSO and the DHS. Copies of monitoring results and calibration logs will be filed with the HASP.

Monitoring is designed to assess exposure to employees during site activities, and to determine if PPE is required and adequate to assure protection. Because investigation and remediation activities at hazardous waste sites are of an inconsistent nature, it is not possible to assign a monitoring protocol that excludes, or is not directly dependent upon, professional judgment in determining when monitoring is required to assess exposure. Thus, the following generic protocol must be followed at a minimum, and should be modified to be more conservative (e.g., require more monitoring) if deemed necessary by the SHSO or DHS. Under no conditions will the required frequency be decreased.

At a minimum, air monitoring will be conducted before and during each task or activities for which air monitoring has been designated. If airborne concentrations of contaminants reach action levels based on observations with the direct reading instruments, then the appropriate PPE upgrade or work stoppage order will be enforced by the SHSO. In case a work stoppage order is given, the area must be cleared of all personnel immediately.

The use of action levels and the basis for the selection of monitoring equipment is explained as follows:

Action levels determine:

- (1) the PPE to be used by site workers
- (2) their ability to remain and work in the exclusion zone

The selection of the specified monitoring equipment is based on

- (1) the nature of the contaminants
- (2) the likely concentrations of the contaminants
- (3) the probable duration of exposure
- (4) the relative sensitivity of the monitoring equipment to the specific contaminants

The following summarizes the calibration requirements for the air monitoring instruments used at the site:

<u>Instrument</u>	<u>Calibration Frequency</u>
PID: Mini RAE-QRAE	Beginning of each work shift

Air Monitoring and Contaminant Action Levels

Task No.(s)	Location	Contaminant	Monitoring Equipment	Monitoring Frequency	Action Level Concentration	
					Mandatory Respirator Use	Mandatory Work Stoppage
1	Work Areas	All analyzed compounds	PID: Multi-Rae	Periodically during all tasks/activities.	--	10 ppm

PID = Photoionization Detector (HNU, TIP, OVM)

FID = Flame Ionization Detector (OVA)

LEL-O₂ = Explosivity and Oxygen Meter

Name(s) of individual(s) responsible for performing the monitoring, and certifying the results:

All HK Engineering & Geology, D.P.C. personnel

Type, make and model of instruments used: Multi-Rae PID Gas Monitor

Method and frequency of calibration: 100 ppm isobutylene-calibration gas. Calibrated prior to each day's use according to manufacturer's instruction.

Procedures for Handling Anticipated Wastes

Waste Generation

Anticipated: Yes: ☐ No: ☒

Types: NA ☐ Liquid ☐ Solid ☐ Sludge ☐ Gas ☐

Quantity: Expected volume of each type:

This project ☐ will ☒ will not generate non-hazardous, contaminated wastes. These wastes will be:

☐ stored ☐ treated
☐ transported ☐ manifested in the following manner:

Packaging requirements for waste material:

Decontamination Procedures

All personnel that may be exposed to contaminated soil will wear modified level D Personal Protective Equipment to include disposable gloves. Gloves will be changed after handling potentially impacted material or equipment and placed in a plastic garbage bag for proper disposal. All personnel will wash their hands before eating or drinking and no smoking will be allowed on site.

All equipment brought onto the site will be cleaned of any contaminants prior to accessing the site to prevent offsite cross-contamination or the need to decontaminate prior to the start of field activities. After each borehole is completed, all drilling equipment used for the soil boring (augers, etc.) will be decontaminated with soap (Alconox® or equivalent) and water followed by a water rinse, using a brush as necessary, to remove soil and contaminants. At the conclusion of daily project activities, all equipment will again be decontaminated with soap and water and a water rinse. All equipment will be handled with clean gloves after cleaning to minimize cross-contamination.

Spill Prevention and Response

Potentially hazardous spill situations can be mitigated by using containment devices and materials in work areas. If site conditions are suitable, earthen berms will be constructed around specific areas. If site conditions are not suitable for this, or the potential spill is smaller, barriers will be constructed with sorbent materials such as “speedi-dry”, sorbent booms and/or straw bales. Dikes and berms will also be used to divert stormwater run-on and run-off away from critical zones.

Because a spill cleanup must be conducted under crisis conditions, it is important that the methods used for dealing with a spill be thought out beforehand. However, the steps followed cannot be inflexible, because no two spills are identical. Factors that will be assessed in the event of any and all spills include:

1. The volume of the hazardous substance released and the rate of release.
2. The nature of the spill material.
3. What danger exists to personnel in the immediate area.
4. Nature of damage and possibilities of repair.
5. If the transfer of material to an alternate containment is advisable.
6. Feasibility of the construction of a containment dike.
7. Nature of spill area.
8. Whether the spilled substance has reached a watercourse or sewer.
9. Danger of explosion or fire.
10. Equipment and supplies necessary to confine the material and carry out the cleanup.

In most cases, the success of a cleanup operation is dependent upon the time it takes to contain the spill. Therefore, HK Engineering & Geology, D.P.C.’s first attempt at spill containment will be at the point of discharge. This can often be accomplished by closing valves, reinforcing or repairing damaged containers, moving or changing the position of fallen or ruptured containers, or emptying the container by pumping to a temporary storage or holding vessel. Pumps, suction hoses and containers will be available to recover spilled materials when directed to do so by the Site Supervisor.

Handling and transport of drummed waste always must be conducted in a controlled and safe manner, which will minimize damage to structurally sound drums, repacks and overpacks. If leakage or spillage of waste occurs, the drum must immediately be placed within an overpack unit. Overpack units must be provided at each staging area, at areas of existing drums, and along all site roadways.

In the event of a spill, the drum handling team must immediately contact the SHSO, who will have all personnel evacuated from the immediate spill area. Only personnel trained in spill response procedures shall isolate and contain the spill. Where possible, spilled waste material must be collected and placed in repack containers for ultimate disposal. Following containment and collection of spilled waste, the area must be surveyed by the SHSO, who will decide if it is safe to permit re-entry of work teams.

Emergency Procedures

Potential emergencies that may arise are most likely to be associated with physical hazards from heavy equipment operation and/or lifting and loading of debris. Emergency response will, in most cases, be performed in Level D protection.

Modifications to these emergency procedures may be necessary after the actual site set-up, based on prevailing conditions. Periodic reviews of these procedures will be performed by the SHSO to ensure that they are appropriate for all anticipated emergencies.

Responsibilities

The Site Supervisor has the authority and responsibility to commit company resources to appropriately respond to an emergency, and to exclude all personnel not directly responding to the emergency.

Prior to beginning work at the site, HK Engineering & Geology, D.P.C. will designate an employee, usually the SHSO, to be responsible for initiating any emergency response actions. In the event an injury or illness requires more than first aid treatment, the SHSO (or alternate) will accompany the injured person to the hospital, and will remain with the person until release or admittance is decided.

Evacuation Plan

The basic elements of an emergency evacuation plan include employee training, escape routes, escape procedures, critical operations or equipment, rescue and medical duty assignments, designation of responsible parties, emergency reporting procedures and methods to account for all employees after evacuation.

When appropriate, wind indicators visible to all on-site personnel will be provided by the SHSO to indicate possible routes of upwind escape. Work-area entrance and exit routes will be planned, and emergency escape routes will be delineated by the SHSO. The discovery of any condition that would suggest the existence of a situation more hazardous than anticipated, should result in the evacuation of the team and a re-evaluation of the hazard and the level of protection required. This re-evaluation will be conducted by appropriate on-site health and safety personnel.

In the highly unlikely event that barrels, canisters, or chemical gases or vapors are uncovered during site work, the following procedures shall be followed:

- 1) In the event that barrels, canisters, or any other vessels are encountered during excavation, all work shall immediately cease and all workers to be removed from the area. The SHSO shall be immediately notified, and he/she shall identify vessel contents, handling procedures and storage and disposal techniques prior to starting work.
- 2) In the event that high concentrations of gases or vapors are detected, the following actions will be taken:
 - Remove all workers from the area
 - Monitor gas or vapor concentrations to determine the type of respiratory protection that will be required before workers reenter the area.
- 3) In the highly unlikely event of a major leak of toxic gas, such as might occur if a compressed gas cylinder were ruptured during excavation or drilling, all on-site personnel will be evacuated to a safe distance. The risk will be assessed prior to restarting work.

Training

Employees will be instructed in the specific aspects of emergency evaluation applicable to the site as part of the site safety meeting prior to the commencement of all on-site activities. On-site refresher or update training is required anytime escape routes or procedures are modified or personnel assignments are changed. During the

site safety meeting, all employees will be trained in, and reminded of, the location of this plan, the procedures outlined in this plan, and the communication systems and evacuation routes used during an emergency.

On a continuous basis, individual employees should be constantly alert for indicators of potentially hazardous situations, and for signs and symptoms in themselves and others that warn of hazardous conditions and exposures. Rapid recognition of dangerous situations can avert an emergency. In the event of any emergency that necessitates an evaluation of the site, on-site personnel will be notified by the use of car horns sounded in regularly spaced, repeated blasts, as detailed in the next section of this procedure. The Site Supervisor in conjunction with the SHSO will control the site until the appropriate local or state agency representatives arrive, if required.

Alarm Systems Emergency Signals

The simplest and most effective emergency communication system, in any situation, is direct voice communications. Voice communications will be supplemented anytime voices cannot be clearly perceived above ambient noise levels (e.g., noise from heavy equipment, drilling rigs or backhoes, and anytime a clear line-of-sight cannot be easily maintained among all site personnel because of distance, terrain, or other obstructions. When voice communications must be supplemented, the following emergency signals, using car horns, will be used.

- One Horn Blast: General Warning

One blast is used to signal relatively minor, but important events on site. An example would be a minor chemical spill where there is no immediate damage to life or health, yet personnel working on site should be aware of the situation so unnecessary problems are avoided. If one horn blast is sounded, personnel must stop all activity and equipment on site and await further instruction from the SHSO.

- Two Horn Blasts: Medical Emergency

Two blasts are used to signal a medical emergency where immediate first aid or emergency medical care is required. If two horn blasts are sounded, all first aid and CPR trained personnel should respond, as appropriate. All other activity and equipment should stop, and personnel should await further instructions from the SHSO.

- Three Horn Blasts Followed by One Continuous Blast: Immediate Danger to Life or Health

Three blasts followed by another extended or continuous horn blast signals a situation that could present an immediate danger to the life or health (IDLH) to all employees on site. Examples of possible IDLH situations could include fires, explosions, hazardous chemical spills or releases, hurricanes, tornadoes, blizzards or floods. If three horn blasts followed by a continuous blast are sounded, all activity and equipment must stop, and all personnel must evacuate the site to an appropriately designated site located outside the site gate, or further off site if necessary. (Note: unless otherwise specified, all decontamination procedures must be implemented.) All personnel must be accounted for by the SHSO or Site Supervisor, and other response actions determined by the SHSO or Site Supervisor must be followed.

Employees on site will use the “buddy” system (pairs). Buddies should pre-arrange hand signals or other means of emergency communication in case radios cannot be used, or if the radios no longer operate. The following hand signals are suggested:

1. Hand gripping throat: out of air, can't breathe.
2. Grip partner's wrist or place both hands around waste: leave area immediately, no debate.
3. Hand on top of head: need assistance.
4. Thumbs up: OK, I'm alright, I understand.
5. Thumbs down: No, negative.

Visual contact will be maintained between employee pairs. Team members will remain in close proximity to each other in order to provide assistance in case of emergencies, and will inform each other of any of the following effects of exposure to site contamination:

- Headaches
- Dizziness
- Blurred vision
- Cramps
- Irritation of eyes, skin or respiratory tract

If any member of the work crew experiences any adverse symptoms while on site, the entire work crew will immediately stop work and follow the instructions provided by the SHSO.

Medical Treatment/First Aid

Eyewash stations will be available at the work activity locations, the outside of the personal decontamination facility and at the equipment decontamination area. Community emergency services (EMS, fire, and police) will be notified immediately if their resources are needed on site. If necessary, the injured or sick party shall be taken to the nearest hospital.

Fire Extinguishers

Equipment – All heavy equipment will be supplied with ABC fire extinguishers are also located in all vehicles.

Emergency Reporting

Any incident (other than minor first aid treatment) resulting in injury, illness or property damage will be reported to HK Engineering & Geology, D.P.C.. An incident investigation will be initiated as soon as emergency conditions are under control. The purpose of this investigation is not to attribute blame but to determine the pertinent facts so that repeat or similar occurrences can be avoided.

The investigations will begin while details are fresh in the mind of all involved. The person administering first aid may be able to start the fact gathering process if the injured are able to speak. Pertinent facts must be determined. Questions beginning with who, what, when, where, and how are usually most effective to discover ways to improve job performance in terms of efficiency, quality of work, as well as safety and health concerns.

On-Site Evacuation Plan – An emergency evacuation alarm (air horn, etc.) will be on site at all times. This alarm should be of sufficient power to be heard by personnel operating heavy equipment. A series of repeated blasts is the signal for all HK Engineering & Geology, D.P.C. personnel and subcontractors to evacuate the site and assemble at:

To be determined at the beginning of each field event:

The criteria for activating the alarm will be the first sign of any serious problem that requires assistance or evacuation.

Should either a fire or explosion occur, all personnel will proceed immediately to the evacuation assembly point and await further instructions. At that time a personnel check will be conducted to determine if anyone is missing, and the local fire and police departments will be called for assistance. Once on site, the acting officer of the fire department and the Site Supervisor will determine if further evacuations are necessary. No HK Engineering & Geology, D.P.C. personnel will re-enter the site without clearance from the SHSO.

Subcontractor Safety

It has been and shall continue to be the policy of HK Engineering & Geology, D.P.C. that employees of all subcontractors are required to adhere to all applicable company, local, state, and federal safety rules and regulations.

When an infraction of a local, state, federal, or company safety regulation is observed, the SHSO will request verbally that the subcontractor's supervisory personnel correct the infraction immediately. If correction is not made, then the project director will request in writing that proper corrective action be taken. Subcontractors who continue to ignore proper safety procedures present a danger for all workers around them. A Stop-work call should be initiated until compliance with safety protocols are achieved; subcontractors will have payments withheld until compliance is achieved.

Subcontractors are required to hold safety meetings for their employees when they are working on HK Engineering & Geology, D.P.C. projects, and submit documentation of such meetings to the Project Manager. Subcontractor employees are not required to attend HK Engineering & Geology, D.P.C.'s safety meetings.

Job Safety & Health Protection

The Occupational Safety and Health Act of 1970 provides job safety and health protection for workers by promoting safe and healthful working conditions throughout the Nation. Provisions of the Act include the following:

Employers

All employers must furnish to employees' employment and a place of employment free from recognized hazards that are causing or are likely to cause death or serious harm to employees. Employers must comply with occupational safety and health standards issued under the Act.

Employees

Employees must comply with all occupational safety and health standards, rules, regulations and orders issued under the Act that apply to their own actions and conduct on the job.

The Occupational Safety and Health Administration (OSHA) of the U.S. Department of Labor has the primary responsibility for administering the Act. OSHA issues occupational safety and health standards, and its Compliance Safety and Health Officers conduct job site inspections to help ensure compliance with the Act.

Inspection

The Act requires that a representative of the employer and a representative authorized by the employees be given an opportunity to accompany the OSHA inspector for the purpose of aiding the inspection.

Complaint

Employees or their representatives have the right to file a complaint with the nearest OSHA office requesting an inspection. If they believe unsafe or unhealthful conditions exist in their workplace, OSHA will withhold, on request, names of employees complaining.

The Act provides that employees may not be discharged or discriminated against in any way for filing safety and health complaints or for otherwise exercising their rights under the Act.

Employees who believe they have been discriminated against may file a complaint with their nearest OSHA office within 30 days of the alleged discriminatory action.

Citation

If upon inspection OSHA believes an employer has violated the Act, a citation alleging such violations will be issued to the employer. Each citation will specify a time period with which the alleged violation must be corrected.

The OSHA citation must be prominently displayed at or near the place of alleged violation for three days, or until it is corrected, whichever is later, to warn employees of dangers that may exist there.

Proposed Penalty

The Act provides for mandatory penalties against employers of up to \$1,000 for each serious violation and for optional penalties of up to \$1,000 for each non-serious violation. Penalties of up to \$1,000 per day may be proposed for failure to correct violations within the proposed time period. Also, any employer who willfully or repeatedly violates the Act may be assessed penalties of up to \$10,000 for each such violation.

There are also provisions for criminal penalties. Any willful violation resulting in death of an employee, upon conviction, is punishable by a fine of up to \$250,000 (or \$500,000 if the employer is a corporation), or by imprisonment for up to six months or both. A second conviction of an employer doubles the possible term of imprisonment.

Voluntary Activity

While providing penalties for violation, the Act also encourages efforts by labor and management before an OSHA inspection, to reduce workplace hazards voluntarily and to develop and improve safety and health programs in all workplaces and industries. OSHA's Voluntary Protection Programs recognize outstanding efforts of this nature.

OSHA has published Safety and Health Program Management Guidelines to assist employers in establishing or perfecting programs to prevent or control employee exposure to workplace hazards. There are many public and private organizations that can provide information and assistance in this effort if requested. Also, your local OSHA office can provide considerable help and advice on saving safety and health problems or can refer you to other sources for help such as training.

Consultation

Free assistance in identifying and correcting hazards and in improving safety and health management is available to employers, without citation or penalty, through OSHA-supported programs in each State. These programs are usually administered by the State of Labor or Health Department or a State University.

Under provisions of Title 29, Code of Federal Regulations, part 1903.2(s)(1) employers must post this notice (or facsimile) in a conspicuous place where notices to employees are customarily posted.

Equipment Calibration Log

Operator Name: _____

Instrument Notice: _____

Signature: _____

Serial Number: _____

[illegible]

Sampling Log

Operator Name: _____

Instrument Notice: _____

Signature: _____

Serial Number: _____

Was the equipment calibrated? _____ Yes _____ No

[illegible]

Daily Sign In/Sign Out Form
(to be completed on site)

Site Name: 78 Bridge Street, North Tonawanda, NY, 14120

Location: 78 Bridge Street, North Tonawanda, NY, 14120

Employee Name	Company Name	Purpose	Time In	Time Out

Signature of SHSO (or designee)

Date

ACCIDENT INVESTIGATION REPORT

Place Accident Occurred:		Name of Person Involved:	
Site Location		Age	Sex
		Yrs in This Job	Yrs with Company
Date & Time of Incident AM __/__/____: __ PM		Date & Time of Investigation AM __/__/____: __ PM	
Date Incident Reported __/__/____	Reported to Whom		Investigated By:
Regulatory Agencies or Insurance Carriers Contacted:		Witness(es):	
Description from injured or witnesses (use reverse side of form for more space):			
Signature Date			

Select one or more in each column. Don't hesitate to write in your own words (continue on reverse side, if necessary).

When completing the following task:

☐ Operating (what machine) _____

☐ Using (what tool) _____

☐ Handling (what material) _____

☐ Maintenance or repair (of what) _____

☐ Office or sales task _____

☐ Other -- Provide details _____

The following occurred:

☐ Amputation (total or partial) _____

☐ Burn (thermal) _____

☐ Burn (chemical) _____

☐ Electric shock _____

☐ Concussion/unconscious _____

☐ Crushing injury (contusion, crush, bruise) -- intact

skin _____

☐ Cut, laceration, puncture, abrasion _____

☐ Fracture or dislocation _____

☐ Sprain/strain _____

☐ Cumulative trauma _____

☐ Occupational illness or disease _____

☐ Internal injuries _____

☐ None -- Near accident _____

☐ Other -- Provide details _____

☐ Respiratory _____

To the (explain details):

☐ Head, face, neck _____

☐ Eye _____

☐ Trunk, abdomen _____

☐ Back (upper, lower) _____

☐ Arm, shoulder _____

☐ Fingers _____

☐ Leg, hip, knee _____

☐ Ankle, foot _____

☐ Toes _____

☐ Internal Injuries _____

☐ Body System: _____

☐ Circulatory _____

☐ Digestive _____

☐ Musculoskeletal _____

☐ Nervous _____

☐ Other _____

☐ Other (specify) _____

Person was, or got:

☐ Struck against (not including falls) _____

☐ Struck by _____

☐ Fell from (from a higher level) _____

☐ Slipped, tripped, fell on (in the same level) _____

☐ Foreign body in eye _____

☐ Contacted electrical energy from _____

☐ Exposure to (substance) _____

_____ from inhalation _____

_____ ingestion _____

_____ skin absorption _____

☐ Vehicle accident _____

☐ Caught in, under or between _____

☐ Repetitive _____

☐ Other _____

While (taking what position) Where (or What):

☐ Carrying _____

☐ Climbing _____

☐ Bending _____

☐ Driving _____

☐ Jumping _____

☐ Kneeling _____

☐ Lifting - below waist, give weight) _____

☐ Lifting - above waist, give weight) _____

☐ Pulling _____

☐ Pushing _____

☐ Reaching or stretching _____

☐ Riding _____

☐ Running _____

☐ Sitting _____

☐ Standing _____

Medical Treatment (check as many as apply)

☐ The injured employee was able to return to work the same day.

☐ The injured employee was sent home

☐ The injured employee was sent to a doctor/clinic; list the doctor/clinic name, address, and phone: _____

☐ The employee was hospitalized.

List name and address of hospital:

_____	<input type="checkbox"/> Throwing_____	_____
_____	<input type="checkbox"/> Twisting or turning_____	Attending physician:_____
_____	<input type="checkbox"/> Walking_____	
_____	<input type="checkbox"/> Other_____	_____

What conditions contributed

- ☐Awkward job procedure
- ☐Inadequate guard/safety device
- ☐Inadequate warning/labeling system
- ☐Fire/explosion hazard
- ☐Not secured against moving
- ☐Poor housekeeping
- ☐Protruding object
- ☐Close clearance/congestion
- ☐Hazardous arrangement/storage
- ☐Defective tools/equipment
- ☐Inadequate ventilation
- ☐Atmospheric condition: gases, dusts, fumes, vapors
- ☐Repetitive motion
- ☐Illumination/noise hazard
- ☐Other

What unsafe procedures contributed

- ☐Operating without training/authority
- ☐Failure to follow proper procedure
- ☐Failure to secure
- ☐Operating at unsafe speed
- ☐Failure to warn/signal
- ☐Congestion
- ☐Used defective equipment
- ☐Used equipment improperly/unsafely
- ☐Improper loading or placement
- ☐Horseplay/distraction
- ☐Improper protective equipment
- ☐Improper lifting or carrying
- ☐Taking unsafe or awkward position
- ☐Servicing moving equipment
- ☐Other

The underlying causes of the incident are:

- ☐Unaware of job hazards
- ☐Inattention to hazard
- ☐Unaware of how to avoid incident
- ☐Not enough time to act
- ☐Person motivated to use unsafe procedure
- ☐Emotional/mental/physical stress
- ☐Equipment failed to perform as expected
- ☐Intoxicant/drugs
- ☐Failure to report/correct unsafe condition
- ☐Illness/medical condition
- ☐Work procedure not ergonomically correct
- ☐Substandard design
- ☐Other

Classification (check as many as apply)

- ☐Fatality
- ☐Medical treatment other than First Aid
- ☐Occupation illness or disease
- ☐First Aid
- ☐Environmental Release
- ☐Property Damage
- ☐Near-accident

What steps have already been taken to prevent similar incidents? _____

What else can be done (engineering controls, training, enforcement, process changes) to eliminate the hazard? _____

SHSO's Signature

Date

Health and Safety Review: Is proposed action appropriate?

Yes ☐

No ☐

Comments _____

DHS's Signature

Date

VEHICLE ACCIDENT REPORT

EMPLOYEE NAME: _____

DRV LIC NO.: _____

COMPANY ADDRESS: _____

INSURANCE COMPANY _____

POLICY NO.: _____

DESCRIPTION OF ACCIDENT

DATE: _____ TIME: _____ SPEED LIMIT _____:

LOCATION: _____

DIRECTION OF TRAVEL: _____

HOW DID IT HAPPEN? _____

USE SPACE BELOW TO INDICATE VEHICLE PATHS - INDICATE NORTH BY ARROW

POLICE REPORT

NAME OF OFFICER: _____

BADGE #: _____

DEPARTMENT: _____

LOCATION: _____

SUMMONS ISSUED? Y [] N [] TO WHOM? _____

YOUR VEHICLE

YEAR/MAKE: _____

REGIST #: _____

DRIVEN BY: _____

AGE: _____ TEL #: _____

ADDRESS: _____

CITY: _____ STATE: _____

NATURE OF DAMAGE: _____

OTHER DRIVER

(continue below for additional drivers and witnesses)

NAME: _____

DRV LIC NO.: _____

ADDRESS: _____

VEHICLE REGISTRATION: _____

INSURANCE COMPANY _____

POLICY NO.: _____

HASP Sign-Off Form

INSTRUCTIONS: Site personnel are required to read, understand, and agree to the provision of the plan. Personnel are required to sign this form indicating agreement. The original of this form is maintained by the Project Manager, and becomes part of the permanent site project files upon completion of site work.

Site Name: 78 Bridge Street, North Tonawanda, NY, 14120

Location: 78 Bridge Street, North Tonawanda, NY, 14120

Project Name and Number: HK2550-1

I have read, understand, and agree to comply with the provisions of this HASP for work activities on this site.

[illegible]

1,2,4-trimethylbenzene

Version number: GHS 2.0
Replaces version of: 25.02.2016 (GHS 1)

Revision: 13.10.2017

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Identification of the substance	1,2,4-trimethylbenzene
Registration number (REACH)	01-2119472135-42-xxxx
EC number	202-436-9
Index No	-
CAS number	95-63-6
Additional relevant and available information	Pseudocumene

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	industrial use (SCC)
--------------------------	-------------------------

1.3 Details of the supplier of the safety data sheet

DHC Solvent Chemie GmbH
Timmerhellstraße 28
D-45478 Mülheim an der Ruhr
Germany

Telephone: +49 (208) 9940-0
Telefax: +49 (208) 9940-150

Competent person responsible for the safety data sheet

Vanessa Manz

e-mail (competent person)

productsafety@dhc-solvent.de

1.4 Emergency telephone number

Emergency information service

Poison centre	
Country	Telephone
United Kingdom	+44 1235 239670

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Hazard class	Category	Hazard class and category	Hazard statement
flammable liquid	Cat. 3	(Flam. Liq. 3)	H226
acute toxicity (inhal.)	Cat. 4	(Acute Tox. 4)	H332
skin corrosion/irritation	Cat. 2	(Skin Irrit. 2)	H315
serious eye damage/eye irritation	Cat. 2	(Eye Irrit. 2)	H319
specific target organ toxicity - single exposure (respiratory tract irritation)	Cat. 3	(STOT SE 3)	H335
aspiration hazard	Cat. 1	(Asp. Tox. 1)	H304
hazardous to the aquatic environment - chronic hazard	Cat. 2	(Aquatic Chronic 2)	H411

1,2,4-trimethylbenzene

Version number: GHS 2.0
Replaces version of: 25.02.2016 (GHS 1)

Revision: 13.10.2017

Remarks

For full text of H-phrases: see SECTION 16.
Substance with a community indicative occupational exposure limit value.

The most important adverse physicochemical, human health and environmental effects

May be fatal if swallowed and enters airways.
The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word

Danger

Pictograms

GHS02, GHS07,
GHS08, GHS09



Hazard statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

Precautionary statements - prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take action to prevent static discharges.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

Precautionary statements - storage

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.

Precautionary statements - disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

2.3 Other hazards

According to the results of its assessment, this substance is not a PBT or a vPvB.
Vapour heavier than air, may form an explosive mixture in air: it may be ignited at some distance away from the spill resulting in flashbacks. Flowing product can create electrostatic charge, resulting sparks may ignite or cause an explosion.

1,2,4-trimethylbenzene

Version number: GHS 2.0
Replaces version of: 25.02.2016 (GHS 1)

Revision: 13.10.2017

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Name of substance	1,2,4-trimethylbenzene
Registration number (REACH)	01-2119472135-42-xxxx
EC number	202-436-9
CAS number	95-63-6
Index No	-
Molecular formula	C ₉ H ₁₂

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Irrigate copiously with clean, fresh water, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Do NOT induce vomiting. Rinse mouth with water (only if the person is conscious).

4.2 Most important symptoms and effects, both acute and delayed

Choking and suffocation risks. Deficits in perception and coordination, reaction time, or sleepiness.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

carbon dioxide (CO₂), BC-powder, foam, alcohol resistant foam, water mist

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Solvent vapours are heavier than air and may spread along floors. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. May produce toxic fumes of carbon monoxide if burning.

Hazardous combustion products

carbon monoxide (CO), carbon dioxide (CO₂)

1,2,4-trimethylbenzene

Version number: GHS 2.0
Replaces version of: 25.02.2016 (GHS 1)

Revision: 13.10.2017

5.3 Advice for firefighters

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance. Keep containers cool with water spray.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety. Avoid inhaling sprayed product. Wearing of suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. Remove/take off immediately all contaminated clothing and wash it before reuse.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains.

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage (sawdust, kieselgur (diatomite), sand, universal binder).

Appropriate containment techniques

Use of adsorbent materials. - covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Recommendations

• Measures to prevent fire as well as aerosol and dust generation

Use only in well-ventilated areas. Use local and general ventilation. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools.

• Warning

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feed-stuffs.

1,2,4-trimethylbenzene

Version number: GHS 2.0
Replaces version of: 25.02.2016 (GHS 1)

Revision: 13.10.2017

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

• Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

• Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice

• Ventilation requirements

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

• Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

Suitable materials and coatings for container/equipment: Carbon Steel, Stainless Steel, Polyester, Polytetrafluoroethylene (PTFE), Polyvinyl Alcohol (PVA)

Unsuitable Materials and Coatings for container/equipment: Butyl Rubber, Natural Rubber, Ethylene-propylene-diene monomer (EPDM), Polystyrene, Polyethylene, Polyacrylonitrile.

7.3 Specific end use(s)

See attached exposure scenarios

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Source
DE	1,2,4-trimethylbenzene	95-63-6	AGW	20	100	40	200	TRGS 900
EU	1,2,4-trimethylbenzene	95-63-6	IOELV	20	100			2017/164/ EU
GB	aromatics	95-63-6	WEL		500			EH40/200 5
IE	1,2,4-trimethylbenzene	95-63-6	OELV	20	100			S.I. No. 619 of 2001

Notation

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified.

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average.

Relevant DNELs/DMELs/PNECs and other threshold levels

1,2,4-trimethylbenzene

Version number: GHS 2.0
Replaces version of: 25.02.2016 (GHS 1)

Revision: 13.10.2017

• human health values

Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	100 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
DNEL	100 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
DNEL	100 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
DNEL	16,171 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
DNEL	100 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	29.4 mg/m ³	human, inhalatory	consumer (private households)	acute - systemic effects
DNEL	29.4 mg/m ³	human, inhalatory	consumer (private households)	chronic - local effects
DNEL	15 mg/kg	human, oral	consumer (private households)	chronic - systemic effects
DNEL	9,512 mg/kg	human, dermal	consumer (private households)	chronic - systemic effects
DNEL	29.4 mg/m ³	human, inhalatory	consumer (private households)	chronic - systemic effects

• environmental values

End-point	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	0.12 mg/l	aquatic organisms	freshwater	short-term (single instance)
PNEC	0.12 mg/l	aquatic organisms	marine water	short-term (single instance)
PNEC	2.41 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	13.56 mg/kg	benthic organisms	sediments	short-term (single instance)
PNEC	13.56 mg/kg	pelagic organisms	sediments	short-term (single instance)
PNEC	2.34 mg/kg	terrestrial organisms	soil	short-term (single instance)
PNEC	0.12 mg/l	aquatic organisms	water	intermittent release

8.2 Exposure controls

Appropriate engineering controls

Technical measures and the appliance of appropriate working methods take priority over the use of personal protective equipment.

Safety and necessary control measures vary according to exposure conditions. Appropriate measures are:

Open windows, door, to allow sufficient ventilation. If this is not possible employ a fan to increase air exchange (see attached exposure scenarios).

Individual protection measures (personal protective equipment)

Eye/face protection

Use safety goggle with side protection.

Skin protection

• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374.

Short-term contact with the skin: Disposable gloves

Long-term contact with the skin: Gloves with long cuffs

Check leak-tightness/impermeability prior to use.

1,2,4-trimethylbenzene

Version number: GHS 2.0
Replaces version of: 25.02.2016 (GHS 1)

Revision: 13.10.2017

- **type of material**

NBR: acrylonitrile-butadiene rubber, FKM: fluoro-elastomer

- **material thickness**

0,40 mm.

- **breakthrough times of the glove material**

>480 minutes (permeation: level 6)

- **other protection measures**

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Body protection:

Suitable protective clothing: Flame resistant clothing

Suitable safety shoes: Anti static safety shoes according to EN 345 S3

Respiratory protection

For activities in enclosed areas at elevated temperatures of the substance, local extraction or explosion protected ventilation equipment is recommended. In case this is not sufficient for the intended use, then apply a suitable respiratory protection according to EN 140 type A or better (see exposure scenarios). .

Environmental exposure controls

Do not empty into drains.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Colour	colourless
Odour	characteristic

Other physical and chemical parameters

pH (value)	not determined
Melting point/freezing point	-43.77 °C
Initial boiling point and boiling range	169.4 °C at 101.3 kPa
Flash point	44 °C at 101.3 kPa
Explosive limits	
• lower explosion limit (LEL)	0.9 vol%
• upper explosion limit (UEL)	6.4 vol%
Vapour pressure	0.3 kPa at 25 °C
Density	0.88 g/cm ³ at 20 °C
Solubility(ies)	
Water solubility	57 mg/l at 25 °C
Partition coefficient	
n-octanol/water (log KOW)	This information is not available.
Auto-ignition temperature	500 °C
Viscosity	
• kinematic viscosity	0.843 mm ² /s at 20 °C

1,2,4-trimethylbenzene

Version number: GHS 2.0
Replaces version of: 25.02.2016 (GHS 1)

Revision: 13.10.2017

Explosive properties
in use, may form flammable/explosive vapour-air mixture
Oxidising properties none

9.2 Other information

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

risk of ignition

• if heated

risk of ignition

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure (see below "Conditions to avoid").

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use only non-sparking tools.

10.5 Incompatible materials

oxidisers

10.6 Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Harmful if inhaled.

• Acute toxicity estimate (ATE)

inhalation: vapour 11 mg_i/4h

Exposure route	Endpoint	Value	Species
oral	LD50	6,000 mg/kg	rat

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

1,2,4-trimethylbenzene

Version number: GHS 2.0
Replaces version of: 25.02.2016 (GHS 1)

Revision: 13.10.2017

Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

Specific target organ toxicity (STOT)

• Specific target organ toxicity - single exposure

May cause respiratory irritation.

• Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

If on skin. If inhaled.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Aquatic toxicity (acute)

Endpoint	Value	Species	Exposure time
LC50	7.72 mg/l	fish	96 h
EC50	2.356 mg/l	algae	96 h

Aquatic toxicity (chronic)

May cause long-term adverse effects in the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

BCF

243

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

12.6 Other adverse effects

Data are not available.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately re-conditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

1,2,4-trimethylbenzene

Version number: GHS 2.0
Replaces version of: 25.02.2016 (GHS 1)

Revision: 13.10.2017

List of wastes

Proposed waste code(s) for the used product:
07 01 04x Other organic solvents, washing liquids and mother liquors

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.


SECTION 14: TRANSPORT INFORMATION

- | | | |
|-------------|---|---|
| 14.1 | UN number | 1993 |
| 14.2 | UN proper shipping name
Technical name | FLAMMABLE LIQUID, N.O.S.
1,2,4-trimethylbenzene |
| 14.3 | Transport hazard class(es)
Class | 3 (flammable liquids) |
| 14.4 | Packing group | III (substance presenting low danger) |
| 14.5 | Environmental hazards | hazardous to the aquatic environment |
| 14.6 | Special precautions for user
Provisions for dangerous goods (ADR) should be complied within the premises. | |
| 14.7 | Transport in bulk according to Annex II of MARPOL and the IBC Code
The cargo is not intended to be carried in bulk. | |

Information for each of the UN Model Regulations

• Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)

UN number	1993
Proper shipping name	FLAMMABLE LIQUID, N.O.S.
Technical name (hazardous constituents)	1,2,4-trimethylbenzene
Class	3
Classification code	F1
Packing group	III
Danger label(s)	3 + "fish and tree"



Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	274, 601
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
Transport category (TC)	3
Tunnel restriction code (TRC)	D/E
Hazard identification No	30
Emergency Action Code	3YE

• International Maritime Dangerous Goods Code (IMDG)


UN number	1993
Proper shipping name	FLAMMABLE LIQUID, N.O.S.
Particulars in the shipper's declaration	UN1993, FLAMMABLE LIQUID, N.O.S., (1,2,4-trimethylbenzene), 3, III, 44°C c.c., MARINE POLLUTANT
Class	3

1,2,4-trimethylbenzene

Version number: GHS 2.0
Replaces version of: 25.02.2016 (GHS 1)

Revision: 13.10.2017

Marine pollutant	yes (hazardous to the aquatic environment)
Packing group	III
Danger label(s)	3 + "fish and tree"



Special provisions (SP)	223, 274, 955
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, S-E
Stowage category	A
• International Civil Aviation Organization (ICAO-IATA/DGR)	
UN number	1993
Proper shipping name	Flammable liquid, n.o.s.
Class	3
Environmental hazards	yes (hazardous to the aquatic environment)
Packing group	III
Danger label(s)	3



Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

• Restrictions according to REACH, Annex XVII

Name of substance	CAS No	Wt%	Type of registration	No
1,2,4-trimethylbenzene		100	1907/2006/EC annex XVII	3
1,2,4-trimethylbenzene		100	1907/2006/EC annex XVII	40

• List of substances subject to authorisation (REACH, Annex XIV)

not listed

• 2012/18/EU (Seveso III)

No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements		Notes
E2	environmental hazards (hazardous to the aquatic environment, cat. 2)	200	500	57)

Notation

57) Hazardous to the Aquatic Environment in category Chronic 2.

1,2,4-trimethylbenzene

Version number: GHS 2.0
Replaces version of: 25.02.2016 (GHS 1)

Revision: 13.10.2017

• Limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products (2004/42/EC, Deco-Paint Directive)

VOC content 100 %

• Directive on industrial emissions (VOCs, 2010/75/EU)

VOC content 100 %

• Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS) - Annex II

not listed

• Regulation 166/2006/EC concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

• Directive 2000/60/EC establishing a framework for Community action in the field of water policy (WFD)

not listed

National inventories

Country	Inventory	Status
AU	AICS	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed

Legend

AICS Australian Inventory of Chemical Substances.
CICR Chemical Inventory and Control Regulation.
CSCL-ENCS List of Existing and New Chemical Substances (CSCL-ENCS).
DSL Domestic Substances List (DSL).
ECSI EC Substance Inventory (EINECS, ELINCS, NLP).
IECSC Inventory of Existing Chemical Substances Produced or Imported in China.
INSQ National Inventory of Chemical Substances.
KECI Korea Existing Chemicals Inventory.
NZIoC New Zealand Inventory of Chemicals.
PICCS Philippine Inventory of Chemicals and Chemical Substances.
REACH Reg. REACH registered substances.
TCSI Taiwan Chemical Substance Inventory.
TSCA Toxic Substance Control Act.

1,2,4-trimethylbenzene

Version number: GHS 2.0
Replaces version of: 25.02.2016 (GHS 1)

Revision: 13.10.2017

15.2 Chemical Safety Assessment

For this substance a chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

16.1 Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)
1.3	Competent person responsible for the safety data sheet: Christian Knappe	Competent person responsible for the safety data sheet: Vanessa Manz
1.4		Poison centre: change in the listing (table)
2.2		Precautionary statements - prevention: change in the listing (table)
2.2		Precautionary statements - disposal: change in the listing (table)
6.2	Environmental precautions: Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.	Environmental precautions: Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)
11.1		Information on likely routes of exposure: If on skin. If inhaled.
15.1		• Restrictions according to REACH, Annex XVII: change in the listing (table)
15.1		National inventories: change in the listing (table)
16		Abbreviations and acronyms: change in the listing (table)
16	Key literature references and sources for data: - Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU - Regulation (EC) No. 1272/2008 (CLP, EU GHS) - See attached exposure scenarios http://www.dhc-solvent.de/dhc_sdbreach.html http://www.dhc-solvent.de/en/dhc_sdbreach.html Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). International Air Transport Association (IATA).	Key literature references and sources for data: - Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU - Regulation (EC) No. 1272/2008 (CLP, EU GHS) - The exposure scenarios are available at www.dhc-solvent.de in the Service section. Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). International Air Transport Association (IATA).
16		Disclaimer: This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product. The information concerning legal regulations can lay no claim to completeness. In addition to this, other provisions may also apply to the product.

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2017/164/EU	Commission Directive establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
AGW	Workplace exposure limit

1,2,4-trimethylbenzene

Version number: GHS 2.0
Replaces version of: 25.02.2016 (GHS 1)

Revision: 13.10.2017

Abbr.	Descriptions of used abbreviations
BCF	Bioconcentration factor
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
S.I. No. 619 of 2001	Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001
STEL	Short-term exposure limit
TRGS 900	Arbeitsplatzgrenzwerte (TRGS 900)
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

1,2,4-trimethylbenzene

Version number: GHS 2.0
Replaces version of: 25.02.2016 (GHS 1)

Revision: 13.10.2017

Key literature references and sources for data

- Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU
- Regulation (EC) No. 1272/2008 (CLP, EU GHS)
- The exposure scenarios are available at www.dhc-solvent.de in the Service section.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN).
International Maritime Dangerous Goods Code (IMDG).
International Air Transport Association (IATA).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product. The information concerning legal regulations can lay no claim to completeness. In addition to this, other provisions may also apply to the product.

Material Safety Data Sheet

Version 5.0

Revision Date 12/18/2012

Print Date 11/20/2013

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : 1,3,5-Trimethylbenzene solution

Product Number : 41103

Brand : Supelco

Supplier : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA

Telephone : +1 800-325-5832

Fax : +1 800-325-5052

Emergency Phone # (For both supplier and manufacturer) : (314) 776-6555

Preparation Information : Sigma-Aldrich Corporation
Product Safety - Americas Region
1-800-521-8956

2. HAZARDS IDENTIFICATION

Emergency Overview

OSHA Hazards

Flammable liquid, Target Organ Effect, Toxic by inhalation., Toxic by ingestion, Toxic by skin absorption

Target Organs

Eyes, Kidney, Liver, Heart, Central nervous system

GHS Classification

Flammable liquids (Category 2)

Acute toxicity, Oral (Category 3)

Acute toxicity, Inhalation (Category 3)

Acute toxicity, Dermal (Category 3)

Skin irritation (Category 2)

Eye irritation (Category 2A)

Specific target organ toxicity - single exposure (Category 1)

GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H225

Highly flammable liquid and vapour.

H301 + H311

Toxic if swallowed or in contact with skin

H315

Causes skin irritation.

H319

Causes serious eye irritation.

H331

Toxic if inhaled.

H370

Causes damage to organs.

Precautionary statement(s)

P210

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P280

Wear protective gloves/ protective clothing.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.

HMIS Classification

Health hazard: 2
Chronic Health Hazard: *
Flammability: 3
Physical hazards: 0

NFPA Rating

Health hazard: 2
Fire: 3
Reactivity Hazard: 0

Potential Health Effects

Inhalation Toxic if inhaled. Causes respiratory tract irritation.
Skin Toxic if absorbed through skin. Causes skin irritation.
Eyes Causes eye irritation.
Ingestion Toxic if swallowed.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms : Mesitylenesolution

Component		Classification	Concentration
Methanol			
CAS-No.	67-56-1	Flam. Liq. 2; Acute Tox. 3; STOT SE 1; H225, H301 + H311 + H331, H370	90 - 100 %
EC-No.	200-659-6		
Index-No.	603-001-00-X		
Registration number	01-2119433307-44-XXXX		

For the full text of the H-Statements and R-Phrases mentioned in this Section, see Section 16

4. FIRST AID MEASURES

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIREFIGHTING MEASURES

Conditions of flammability

Flammable in the presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface. No smoking.

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special protective equipment for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Hazardous combustion products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions**

Wear respiratory protection. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

7. HANDLING AND STORAGE**Precautions for safe handling**

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage temperature: 2 - 8 °C

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value	Control parameters	Basis
Methanol	67-56-1	TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)
Remarks	Headache Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption			
		STEL	250 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Headache Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption			
		TWA	200 ppm 260 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
	Skin notation			
		STEL	250 ppm 325 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
	Skin notation			
		TWA	200 ppm 260 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
	The value in mg/m3 is approximate.			
		TWA	200 ppm 260 mg/m3	USA. NIOSH Recommended Exposure Limits

	Potential for dermal absorption		
		ST	250 ppm 325 mg/m3
	USA. NIOSH Recommended Exposure Limits		
	Potential for dermal absorption		

Personal protective equipment

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form	liquid
Colour	colourless

Safety data

pH	no data available
Melting point/freezing point	Melting point/range: -98 °C (-144 °F)
Boiling point	64 - 65 °C (147 - 149 °F) at 1,013 hPa (760 mmHg)
Flash point	11 °C (52 °F) - closed cup
Ignition temperature	no data available
Auto-ignition temperature	385 °C (725 °F)
Lower explosion limit	6 %(V)
Upper explosion limit	36 %(V)
Vapour pressure	130.23 hPa (97.68 mmHg) at 20 °C (68 °F) 547 hPa (410 mmHg) at 50 °C (122 °F)
Density	0.791 g/cm3
Water solubility	completely miscible
Partition coefficient: n-octanol/water	no data available
Relative vapor density	no data available

Odour	no data available
Odour Threshold	no data available
Evaporation rate	no data available

10. STABILITY AND REACTIVITY

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

Vapours may form explosive mixture with air.

Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Materials to avoid

Acids, Oxidizing agents, Alkali metals, Strong oxidizing agents, Acid chlorides, Acid anhydrides, Reducing agents

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - no data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Oral LD50

Inhalation LC50

Dermal LD50

Other information on acute toxicity

no data available

Skin corrosion/irritation

no data available

Serious eye damage/eye irritation

Eyes: no data available

Respiratory or skin sensitization

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

no data available

Teratogenicity

no data available

Specific target organ toxicity - single exposure (Globally Harmonized System)

no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System)

no data available

Aspiration hazard

no data available

Potential health effects

Inhalation	Toxic if inhaled. Causes respiratory tract irritation.
Ingestion	Toxic if swallowed.
Skin	Toxic if absorbed through skin. Causes skin irritation.
Eyes	Causes eye irritation.

Signs and Symptoms of Exposure

Methyl alcohol may be fatal or cause blindness if swallowed., Cannot be made non-poisonous., Effects due to ingestion may include:, Nausea, Dizziness, Gastrointestinal disturbance, Weakness, Confusion., Drowsiness, Unconsciousness, May cause convulsions.

Synergistic effects

no data available

Additional Information

RTECS: Not available

12. ECOLOGICAL INFORMATION

Toxicity

no data available

Persistence and degradability

no data available

Bioaccumulative potential

no data available

Mobility in soil

no data available

PBT and vPvB assessment

no data available

Other adverse effects

no data available

13. DISPOSAL CONSIDERATIONS

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1230 Class: 3 Packing group: II
Proper shipping name: Methanol, solution
Marine Pollutant: No
Poison Inhalation Hazard: No

IMDG

UN number: 1230 Class: 3 (6.1) Packing group: II EMS-No: F-E, S-D
Proper shipping name: METHANOL, SOLUTION
Marine Pollutant: No

IATA

UN number: 1230 Class: 3 (6.1) Packing group: II
Proper shipping name: Methanol, solution

15. REGULATORY INFORMATION

OSHA Hazards

Flammable liquid, Target Organ Effect, Toxic by inhalation., Toxic by ingestion, Toxic by skin absorption

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
Methanol	67-56-1	2007-07-01

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

	CAS-No.	Revision Date
Methanol	67-56-1	2007-07-01

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Methanol	67-56-1	2007-07-01

New Jersey Right To Know Components

	CAS-No.	Revision Date
Methanol	67-56-1	2007-07-01

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Text of H-code(s) and R-phrases mentioned in Section 3

Acute Tox.	Acute toxicity
Flam. Liq.	Flammable liquids
H225	Highly flammable liquid and vapour.
H301 + H311 + H331	Toxic if swallowed, in contact with skin or if inhaled
H370	Causes damage to organs.
STOT SE	Specific target organ toxicity - single exposure

Further information

Copyright 2012 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.
The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

SAFETY DATA SHEET

Revision Date 24-Dec-2021

Revision Number 4

1. Identification

Product Name 2-Methylnaphthalene-bis(hexachlorocyclopentadiene) adduct

Cat No. : AC180460000; AC180460250

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

Classification under 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label Elements

None required

Hazards not otherwise classified (HNOC)

None identified

3. Composition/Information on Ingredients

Component	CAS No	Weight %
1,2,3,4,5,6,7,8,13,13,14,14-Dodecachloro-1,4,4a,4b,5,8,8a,12b-octahydro-10-methyl-1,4:5,8-dimethano triphenylene	4605-91-8	97

4. First-aid measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention.
Inhalation	Remove from exposure, lie down. Remove to fresh air. If not breathing, give artificial respiration.
Ingestion	Never give anything by mouth to an unconscious person. Drink plenty of water. Call a physician immediately. If possible drink milk afterwards.
Most important symptoms and effects	No information available.
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Water spray. Carbon dioxide (CO ₂). Dry chemical. Chemical foam.
Unsuitable Extinguishing Media	No information available
Flash Point	No information available
Method -	No information available
Autoignition Temperature	Not applicable
Explosion Limits	
Upper	No data available
Lower	No data available
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrogen chloride gas.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health
0

Flammability
0

Instability
0

Physical hazards
N/A

6. Accidental release measures

Personal Precautions	Ensure adequate ventilation. Use personal protective equipment as required.
Environmental Precautions	See Section 12 for additional Ecological Information.

Methods for Containment and Clean Up Sweep up and shovel into suitable containers for disposal.

7. Handling and storage

Handling	Avoid contact with skin and eyes. Avoid contact with skin and clothing. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Avoid breathing vapors or mists. Do not ingest. If swallowed then seek immediate medical assistance.
Storage.	Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Incompatible Materials. Strong oxidizing agents.

8. Exposure controls / personal protection

<u>Exposure Guidelines</u>	This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.
Engineering Measures	None under normal use conditions.
<u>Personal Protective Equipment</u>	
Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	No protective equipment is needed under normal use conditions.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Powder Solid
Appearance	Beige
Odor	No information available
Odor Threshold	No information available
pH	No information available
Melting Point/Range	160 - 165 °C / 320 - 329 °F
Boiling Point/Range	No information available
Flash Point	No information available
Evaporation Rate	Not applicable
Flammability (solid,gas)	No information available
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	No information available
Vapor Density	Not applicable
Specific Gravity	No information available
Solubility	No information available
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	Not applicable
Decomposition Temperature	No information available
Viscosity	Not applicable
Molecular Formula	C ₂₁ H ₁₀ Cl ₁₂
Molecular Weight	687.75

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products.
Incompatible Materials	Strong oxidizing agents
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂), Hydrogen chloride gas
Hazardous Polymerization	No information available.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information No acute toxicity information is available for this product

Component Information

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation No information available

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
1,2,3,4,5,6,7,8,13,13,14,14-Dodecachloro-1,4,4a,4b,5,8,8a,12b-octahydro-10-methyl-1,4:5,8-dimethanotriphenylene	4605-91-8	Not listed	Not listed	Not listed	Not listed	Not listed

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure None known

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed No information available

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Do not empty into drains.

Persistence and Degradability No information available

Bioaccumulation/ Accumulation No information available.

Mobility No information available.

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT Not regulated

TDG Not regulated

IATA Not regulated

IMDG/IMO Not regulated

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
1,2,3,4,5,6,7,8,13,13,14,14-Dodec achloro-1,4,4a,4b,5,8,8a,12b-octa hydro-10-methyl-1,4:5,8-dimethan otriphenylene	4605-91-8	-	-	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
1,2,3,4,5,6,7,8,13,13,14,14-Dodec achloro-1,4,4a,4b,5,8,8a,12b-octa hydro-10-methyl-1,4:5,8-dimethan otriphenylene	4605-91-8	-	-	225-009-9	-	-		-	-	-

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

OSHA - Occupational Safety and Not applicable

Health Administration

CERCLA Not applicable

California Proposition 65 This product does not contain any Proposition 65 chemicals.

**U.S. State Right-to-Know
Regulations** Not applicable

U.S. Department of Transportation
Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

**U.S. Department of Homeland
Security** This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

Authorisation/Restrictions according to EU REACH

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
1,2,3,4,5,6,7,8,13,13,14,14-D odecachloro-1,4,4a,4b,5,8,8a, 12b-octahydro-10-methyl-1,4: 5,8-dimethanotriphenylene	4605-91-8	Not applicable	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
1,2,3,4,5,6,7,8,13,13,14,14-D odecachloro-1,4,4a,4b,5,8,8a, 12b-octahydro-10-methyl-1,4: 5,8-dimethanotriphenylene	4605-91-8	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Revision Date 24-Dec-2021

Print Date 24-Dec-2021

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the

date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Version 8.4
Revision Date 11/11/2020
Print Date 03/19/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name : 4-Ethyltoluene

Product Number : E49800
Brand : Aldrich
CAS-No. : 622-96-8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 3), H226

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word : Warning

Hazard statement(s)
H226 : Flammable liquid and vapor.

Precautionary statement(s)
P210 : Keep away from heat/ sparks/ open flames/ hot surfaces. No

Aldrich - E49800

Page 1 of 8

	smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P280	Wear protective gloves/ eye protection/ face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula	: C ₉ H ₁₂
Molecular weight	: 120.19 g/mol
CAS-No.	: 622-96-8
EC-No.	: 210-761-2

No components need to be disclosed according to the applicable regulations.

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most). Consult doctor if feeling unwell.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Nature of decomposition products not known.

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemisorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Wash hands after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Appropriate engineering controls

Change contaminated clothing. Wash hands after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Viton®

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 10 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance	Form: clear, liquid Color: light yellow
b) Odor	characteristic
c) Odor Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	Melting point: -62 °C (-80 °F)
f) Initial boiling point and boiling range	162 °C 324 °F - lit.
g) Flash point	43 °C (109 °F) - closed cup
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 7 %(V) Lower explosion limit: 1.2 %(V)
k) Vapor pressure	No data available
l) Vapor density	No data available
m) Relative density	0.861 g/cm ³ at 25 °C (77 °F)
n) Water solubility	0.0949 g/l at 25 °C (77 °F) - (experimental)
o) Partition coefficient: n-octanol/water	log Pow: 3.63 - (Lit.), Bioaccumulation is not expected.
p) Autoignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	0.812 mm ² /s at 20 °C (68 °F) -
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapor/air-mixtures are explosive at intense warming.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with:

Strong oxidizing agents
combustible substances

10.4 Conditions to avoid

Heating.

10.5 Incompatible materials

Oxidizing agents, Strong oxidizing agents

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 4,850 mg/kg

Remarks: (RTECS)

Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

RTECS: XT2550000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information**12.1 Toxicity**

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Waste material must be disposed of in accordance with the national and local No mixing with other waste. Handle uncleaned containers like the product See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information**DOT (US)**

UN number: 3295 Class: 3 Packing group: III
Proper shipping name: Hydrocarbons, liquid, n.o.s.
Reportable Quantity (RQ):
Poison Inhalation Hazard: No

IMDG

UN number: 3295 Class: 3 Packing group: III EMS-No: F-E, S-D
Proper shipping name: HYDROCARBONS, LIQUID, N.O.S.

IATA

Aldrich - E49800

Page 7 of 8

UN number: 3295 Class: 3 Packing group: III
Proper shipping name: Hydrocarbons, liquid, n.o.s.

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components

4-Ethyltoluene	CAS-No. 622-96-8	Revision Date
----------------	---------------------	---------------

New Jersey Right To Know Components

4-Ethyltoluene	CAS-No. 622-96-8	Revision Date
----------------	---------------------	---------------

SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 8.4

Revision Date: 11/11/2020

Print Date: 03/19/2022

SAFETY DATA SHEET

Creation Date 04-Jun-2010

Revision Date 24-Dec-2021

Revision Number 4

1. Identification

Product Name Acenaphthene

Cat No. : AC201340000; AC201340050; AC201341000; AC201345000

CAS No 83-32-9
Synonyms 1,2-Dihydroacenaphthylene; Naphthyleneethylene; 1,8-Ethylenenaphthalene

Recommended Use Laboratory chemicals.
Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet**Company**

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification**Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system.	

Label Elements**Signal Word**

Warning

Hazard Statements

Causes skin irritation
Causes serious eye irritation

May cause respiratory irritation

**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell

Skin

IF ON SKIN: Wash with plenty of soap and water
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Very toxic to aquatic life

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Acenaphthene	83-32-9	>95

4. First-aid measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention.
Inhalation	Remove from exposure, lie down. Remove to fresh air. If not breathing, give artificial respiration. Get medical attention.
Ingestion	Clean mouth with water. Get medical attention.
Most important symptoms and effects	No information available.
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Water spray. Carbon dioxide (CO₂). Dry chemical. Chemical foam.

Unsuitable Extinguishing Media No information available

Flash Point 135 °C / 275 °F

Method - No information available

Autoignition Temperature 450 °C / 842 °F

Explosion Limits

Upper No data available

Lower No data available

Sensitivity to Mechanical Impact No information available

Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health
2

Flammability
1

Instability
0

Physical hazards
N/A

6. Accidental release measures

Personal Precautions

Ensure adequate ventilation. Use personal protective equipment as required.

Environmental Precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

Methods for Containment and Clean Up Sweep up and shovel into suitable containers for disposal.

7. Handling and storage

Handling

Avoid contact with skin and eyes. Do not breathe dust.

Storage.

Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Incompatible Materials. Strong oxidizing agents. Metals. Strong acids.

8. Exposure controls / personal protection

Exposure Guidelines

This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal Protective Equipment

Eye/face Protection

Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Solid
Appearance	Brown
Odor	No information available
Odor Threshold	No information available
pH	Not applicable
Melting Point/Range	90 - 95 °C / 194 - 203 °F
Boiling Point/Range	279 °C / 534.2 °F
Flash Point	135 °C / 275 °F
Evaporation Rate	Not applicable
Flammability (solid,gas)	No information available
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	10 mmHg @ 131 °C
Vapor Density	Not applicable
Specific Gravity	1.060
Solubility	insoluble
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	450 °C / 842 °F
Decomposition Temperature	No information available
Viscosity	Not applicable
Molecular Formula	C12 H10
Molecular Weight	154.21

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Excess heat. Incompatible products.
Incompatible Materials	Strong oxidizing agents, Metals, Strong acids
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂)
Hazardous Polymerization	No information available.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity**Product Information****Component Information**

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acenaphthene	LD50 = 10000 mg/kg (Rat)	Not listed	Not listed

--	--	--	--

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation No information available

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Acenaphthene	83-32-9	Not listed	Not listed	Not listed	Not listed	Not listed

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Respiratory system

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed No information available

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Acenaphthene	EC50: 0.23 - 1.15 mg/L, 96h (Pseudokirchneriella subcapitata)	LC50: 0.6 - 0.75 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: 1.3 - 2.1 mg/L, 96h static (Lepomis macrochirus) LC50: = 0.509 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 0.58 mg/L 15 min	EC50: 1.102 - 1.475 mg/L, 48h Static (Daphnia magna) EC50: = 3.45 mg/L, 48h (Daphnia magna) EC50: = 41 mg/L, 48h (Daphnia magna)

Persistence and Degradability May persist

Bioaccumulation/ Accumulation No information available.

Mobility Is not likely mobile in the environment due its low water solubility.

Component	log Pow
Acenaphthene	4.43

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN3077
 Proper Shipping Name Environmentally hazardous substances, solid, n.o.s.
 Technical Name Acenaphthene
 Hazard Class 9
 Packing Group III

TDG

UN-No UN3077
 Proper Shipping Name Environmentally hazardous substances, solid, n.o.s.
 Hazard Class 9
 Packing Group III

IATA

UN-No UN3077
 Proper Shipping Name Environmentally hazardous substances, solid, n.o.s.
 Hazard Class 9
 Packing Group III

IMDG/IMO

UN-No UN3077
 Proper Shipping Name Environmentally hazardous substances, solid, n.o.s.
 Hazard Class 9
 Packing Group III

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Acenaphthene	83-32-9	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

- - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Acenaphthene	83-32-9	X	-	201-469-6	X	X	X	X	X	KE-10602

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)**U.S. Federal Regulations**

SARA 313 Not applicable

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Acenaphthene	83-32-9	>95	0.1

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
-----------	----------------------------	-----------------------------	------------------------	---------------------------

Acenaphthene	-	-	X	X
--------------	---	---	---	---

Clean Air Act Not applicable

OSHA - Occupational Safety and Health Administration Not applicable

CERCLA This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Acenaphthene	100 lb	-

California Proposition 65 This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Acenaphthene	X	X	X	-	-

U.S. Department of Transportation

Reportable Quantity (RQ): Y

DOT Marine Pollutant N

DOT Severe Marine Pollutant N

U.S. Department of Homeland Security This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

Authorisation/Restrictions according to EU REACH

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Acenaphthene	83-32-9	Listed	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Acenaphthene	83-32-9	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Creation Date 04-Jun-2010
Revision Date 24-Dec-2021
Print Date 24-Dec-2021

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Version 5.6
Revision Date 05/24/2016
Print Date 01/23/2017

1. PRODUCT AND COMPANY IDENTIFICATION**1.1 Product identifiers**

Product name : Acenaphthylene

Product Number : 416703
Brand : Aldrich

CAS-No. : 208-96-8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA

Telephone : +1 800-325-5832
Fax : +1 800-325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Acute toxicity, Oral (Category 4), H302

Skin irritation (Category 2), H315

Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Warning

Hazard statement(s)

H302

Harmful if swallowed.

H315

Causes skin irritation.

H319

Causes serious eye irritation.

H335

May cause respiratory irritation.

Precautionary statement(s)

P261

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264

Wash skin thoroughly after handling.

P270

Do not eat, drink or smoke when using this product.

P271

Use only outdoors or in a well-ventilated area.

P280

Wear eye protection/ face protection.

P280	Wear protective gloves.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Formula	: C ₁₂ H ₈
Molecular weight	: 152.19 g/mol
CAS-No.	: 208-96-8
EC-No.	: 205-917-1

Hazardous components

Component	Classification	Concentration
Acenaphthylene		
	Acute Tox. 4; Skin Irrit. 2; Eye Irrit. 2A; STOT SE 3; H302, H315, H319, H335	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols.

Provide appropriate exhaust ventilation at places where dust is formed. Normal measures for preventive fire protection.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact
Material: Nitrile rubber
Minimum layer thickness: 0.11 mm
Break through time: 480 min
Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact
Material: Nitrile rubber
Minimum layer thickness: 0.11 mm
Break through time: 480 min
Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

For nuisance exposures use type P95 (US) or type P1 (EU EN 143) particle respirator. For higher level protection use type OV/AG/P99 (US) or type ABEK-P2 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

- | | |
|---|---|
| a) Appearance | Form: solid |
| b) Odour | No data available |
| c) Odour Threshold | No data available |
| d) pH | No data available |
| e) Melting point/freezing point | Melting point/range: 78 - 82 °C (172 - 180 °F) - lit. |
| f) Initial boiling point and boiling range | 280 °C (536 °F) - lit. |
| g) Flash point | 122.0 °C (251.6 °F) - closed cup |
| h) Evaporation rate | No data available |
| i) Flammability (solid, gas) | No data available |
| j) Upper/lower flammability or explosive limits | No data available |
| k) Vapour pressure | No data available |
| l) Vapour density | No data available |
| m) Relative density | 0.899 g/mL at 25 °C (77 °F) |
| n) Water solubility | No data available |
| o) Partition coefficient: n-octanol/water | No data available |
| p) Auto-ignition temperature | No data available |

- | | |
|------------------------------|-------------------|
| q) Decomposition temperature | No data available |
| r) Viscosity | No data available |
| s) Explosive properties | No data available |
| t) Oxidizing properties | No data available |

9.2 Other safety information

No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

Oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Mouse - 1,760 mg/kg

Remarks: Autonomic Nervous System:Other (direct) parasympathomimetic. Respiratory disorder Blood: Hemorrhage.

Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: AB1254000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 3077

Class: 9

Packing group: III

Proper shipping name: Environmentally hazardous substances, solid, n.o.s. (Acenaphthylene)

Reportable Quantity (RQ): 5000 lbs

Poison Inhalation Hazard: No

IMDG

Not dangerous goods

IATA

Not dangerous goods

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Acute Health Hazard

Massachusetts Right To Know Components

Acenaphthylene

CAS-No.
208-96-8

Revision Date
1993-04-24

Pennsylvania Right To Know Components

Acenaphthylene

CAS-No.
208-96-8

Revision Date
1993-04-24

New Jersey Right To Know Components

Acenaphthylene

CAS-No.
208-96-8

Revision Date
1993-04-24

California Prop. 65 Components

WARNING! This product contains a chemical known to the State of California to cause cancer.

Acenaphthylene

CAS-No.
208-96-8

Revision Date
2007-09-28

WARNING! This product contains a chemical known to the State of California to cause cancer.

Acenaphthylene

CAS-No.
208-96-8

Revision Date
2007-09-28

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Acute Tox.	Acute toxicity
Eye Irrit.	Eye irritation
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
Skin Irrit.	Skin irritation

HMIS Rating

Health hazard:	2
Chronic Health Hazard:	*
Flammability:	1
Physical Hazard	0

NFPA Rating

Health hazard:	2
----------------	---

Fire Hazard: 1
Reactivity Hazard: 0

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information

Sigma-Aldrich Corporation
Product Safety – Americas Region
1-800-521-8956

Version: 5.6

Revision Date: 05/24/2016

Print Date: 01/23/2017

SAFETY DATA SHEET

Creation Date 28-Apr-2009

Revision Date 19-Jan-2018

Revision Number 6

1. Identification

Product Name Acetone

Cat No. : AC177170000; AC177170010; AC177170025; AC177170050;
AC177170100; AC177170250

CAS-No 67-64-1
Synonyms 2-Propanone

Recommended Use Laboratory chemicals.
Uses advised against Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet**Company**

Fisher Scientific
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone NumberFor information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887**2. Hazard(s) identification****Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Central nervous system (CNS).	
Specific target organ toxicity - (repeated exposure)	Category 2
Target Organs - Kidney, Liver, spleen, Blood.	

Label Elements**Signal Word**

Danger

Hazard Statements

Highly flammable liquid and vapor

Causes serious eye irritation

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling
Do not breathe dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Wear protective gloves/protective clothing/eye protection/face protection
Keep cool

Response

Get medical attention/advice if you feel unwell

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Repeated exposure may cause skin dryness or cracking

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Acetone	67-64-1	>95

4. First-aid measures

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Inhalation

Move to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Ingestion

Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects

None reasonably foreseeable. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: May cause pulmonary edema: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Notes to Physician

Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed containers exposed to fire with water spray.

Unsuitable Extinguishing Media

Water may be ineffective

Flash Point

-20 °C / -4 °F

Method -

Closed cup

Autoignition Temperature

465 °C / 869 °F

Explosion Limits**Upper**

12.8 vol %

Lower

2.5 vol %

Oxidizing Properties

Not oxidising

Sensitivity to Mechanical Impact No information available

Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO₂) Formaldehyde Methanol

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health
2

Flammability
3

Instability
0

Physical hazards
N/A

6. Accidental release measures

Personal Precautions

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Should not be released into the environment.

Methods for Containment and Clean Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment. Ensure adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage

Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place.
Keep away from heat and sources of ignition.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Acetone	TWA: 250 ppm STEL: 500 ppm	(Vacated) TWA: 750 ppm (Vacated) TWA: 1800 mg/m ³ (Vacated) STEL: 2400 mg/m ³ (Vacated) STEL: 1000 ppm TWA: 1000 ppm TWA: 2400 mg/m ³	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³	TWA: 1000 ppm TWA: 2400 mg/m ³ STEL: 1260 ppm STEL: 3000 mg/m ³

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment.

Personal Protective Equipment**Eye/face Protection**

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection

Long sleeved clothing.

Respiratory Protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Colorless
Odor	sweet
Odor Threshold	19.8 ppm
pH	7
Melting Point/Range	-95 °C / -139 °F
Boiling Point/Range	56 °C / 132.8 °F
Flash Point	-20 °C / -4 °F
Method -	Closed cup
Evaporation Rate	5.6 (Butyl Acetate = 1.0)
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	12.8 vol %
Lower	2.5 vol %
Vapor Pressure	247 mbar @ 20 °C
Vapor Density	2.0
Specific Gravity	0.790
Solubility	Soluble in water
Partition coefficient; n-octanol/water	No data available

Autoignition Temperature	465 °C / 869 °F
Decomposition Temperature	> 4°C
Viscosity	0.32 mPa.s @ 20 °C
Molecular Formula	C3 H6 O
Molecular Weight	58.08
Refractive index	1.358 - 1.359

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Heat, flames and sparks. Incompatible products. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Strong oxidizing agents, Strong reducing agents, Strong bases, Peroxides, Halogenated compounds, Alkali metals, Amines
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂), Formaldehyde, Methanol
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acetone	5800 mg/kg (Rat)	> 15800 mg/kg (rabbit) > 7400 mg/kg (rat)	76 mg/l, 4 h, (rat)

Toxicologically Synergistic Products Carbon tetrachloride; Chloroform; Trichloroethylene; Bromodichloromethane; Dibromochloromethane; N-nitrosodimethylamine; 1,1,2-Trichloroethane; Styrene; Acetonitrile, 2,5-Hexanedione; Ethanol; 1,2-Dichlorobenzene

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	Irritating to eyes and skin
Sensitization	No information available
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Acetone	67-64-1	Not listed	Not listed	Not listed	Not listed	Not listed

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Central nervous system (CNS)

STOT - repeated exposure Kidney Liver spleen Blood

Aspiration hazard No information available

Symptoms / effects, both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting:

delayed May cause pulmonary edema: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Acetone	NOEC = 430 mg/l (algae; 96 h)	Oncorhynchus mykiss: LC50 = 5540 mg/l 96h Alburnus alburnus: LC50 = 11000 mg/l 96h Leuciscus idus: LC50 = 11300 mg/L/48h Salmo gairdneri: LC50 = 6100 mg/L/24h	EC50 = 14500 mg/L/15 min	EC50 = 8800 mg/L/48h EC50 = 12700 mg/L/48h EC50 = 12600 mg/L/48h

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
Acetone	-0.24

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Acetone - 67-64-1	U002	-

14. Transport information

DOT

UN-No UN1090
 Proper Shipping Name ACETONE
 Hazard Class 3
 Packing Group II

TDG

UN-No UN1090
 Proper Shipping Name ACETONE
 Hazard Class 3
 Packing Group II

IATA

UN-No UN1090
 Proper Shipping Name ACETONE
 Hazard Class 3
 Packing Group II

IMDG/IMO

UN-No UN1090
 Proper Shipping Name ACETONE
 Hazard Class 3
 Packing Group II

15. Regulatory information

All of the components in the product are on the following Inventory lists: X = listed

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Acetone	X	X	-	200-662-2	-		X	X	X	X	X

Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

OSHA Occupational Safety and Health Administration
Not applicable

CERCLA This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Acetone	5000 lb	-

California Proposition 65 This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Acetone	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product contains the following DHS chemicals:

Component	DHS Chemical Facility Anti-Terrorism Standard
Acetone	2000 lb STQ

Other International Regulations

Mexico - Grade Serious risk, Grade 3

16. Other information

Prepared By Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Creation Date 28-Apr-2009
Revision Date 19-Jan-2018
Print Date 19-Jan-2018
Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Creation Date 03-May-2012

Revision Date 24-Dec-2021

Revision Number 6

1. Identification

Product Name Anthracene

Cat No. : AC104860000; AC104860025; AC104860050; AC104860100;
AC104861000; AC104865000

CAS No 120-12-7
Synonyms Green oil; Paranaftalene

Recommended Use Laboratory chemicals.
Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet**Company**

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification**Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Combustible dust

Category 2
Category 2
Yes

Label Elements**Signal Word**

Warning

Hazard Statements

May form combustible dust concentrations in air
Causes skin irritation

Causes serious eye irritation

**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Skin

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Storage

Store in a well-ventilated place. Keep container tightly closed

Hazards not otherwise classified (HNOC)

Very toxic to aquatic life with long lasting effects

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Anthracene	120-12-7	>95

4. First-aid measures

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.

Inhalation

Remove to fresh air. Get medical attention if symptoms occur. If not breathing, give artificial respiration.

Ingestion

Do NOT induce vomiting. Get medical attention.

Most important symptoms and effects

None reasonably foreseeable.

Notes to Physician

Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Unsuitable Extinguishing Media

No information available

Flash Point

121 °C / 249.8 °F

Method - No information available

Autoignition Temperature 540 °C / 1004 °F

Explosion Limits

Upper No data available

Lower 0.6 vol %

Sensitivity to Mechanical Impact No information available

Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Fine dust dispersed in air may ignite. Dust can form an explosive mixture with air. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition. Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health
2

Flammability
1

Instability
1

Physical hazards
N/A

6. Accidental release measures

Personal Precautions

Use personal protective equipment as required. Ensure adequate ventilation. Avoid dust formation. Avoid contact with skin, eyes or clothing.

Environmental Precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

Methods for Containment and Clean Up Sweep up and shovel into suitable containers for disposal. Avoid dust formation.

7. Handling and storage

Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid dust formation. Avoid contact with skin, eyes or clothing. Avoid ingestion and inhalation.

Storage.

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from direct sunlight. Incompatible Materials. Acids. Strong oxidizing agents. Fluorine.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Anthracene		TWA: 0.2 mg/m ³		

Legend

OSHA - Occupational Safety and Health Administration

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal Protective Equipment

Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Powder Solid
Appearance	Yellow
Odor	aromatic
Odor Threshold	No information available
pH	No information available
Melting Point/Range	215 - 218 °C / 419 - 424.4 °F
Boiling Point/Range	340 °C / 644 °F @ 760 mmHg
Flash Point	121 °C / 249.8 °F
Evaporation Rate	Not applicable
Flammability (solid,gas)	No information available
Flammability or explosive limits	
Upper	No data available
Lower	0.6 vol %
Vapor Pressure	1.3 mbar @ 145 °C
Vapor Density	Not applicable
Specific Gravity	No information available
Solubility	insoluble
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	540 °C / 1004 °F
Decomposition Temperature	No information available
Viscosity	Not applicable
Molecular Formula	C14 H10
Molecular Weight	178.23

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions. Sensitivity to light.
Conditions to Avoid	Avoid dust formation. Incompatible products. Excess heat. Exposure to light.
Incompatible Materials	Acids, Strong oxidizing agents, Fluorine
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂)
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
-----------	-----------	-------------	-----------------

Anthracene	LD50 > 16 g/kg (Rat)	>1320 mg/kg (Rat)	Not listed
------------	------------------------	---------------------	------------

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes and skin

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Anthracene	120-12-7	Not listed	Not listed	Not listed	Not listed	Not listed

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure None known

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed No information available

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Anthracene	Not listed	LC50: = 0.00278 mg/L, 96h static (Lepomis macrochirus) LC50: 0 - 0.00318 mg/L, 96h flow-through (Lepomis macrochirus)	Not listed	EC50: 0.081 - 0.112 mg/L, 48h (Daphnia magna)

Persistence and Degradability Insoluble in water May persist

Bioaccumulation/ Accumulation No information available.

Mobility . Is not likely mobile in the environment due its low water solubility.

Component	log Pow
Anthracene	4.54

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN3077
 Proper Shipping Name Environmentally hazardous substances, solid, n.o.s.
 Technical Name Anthracene
 Hazard Class 9
 Packing Group III

TDG

UN-No UN3077
 Proper Shipping Name Environmentally hazardous substances, solid, n.o.s.
 Hazard Class 9
 Packing Group III

IATA

UN-No UN3077
 Proper Shipping Name Environmentally hazardous substances, solid, n.o.s.
 Hazard Class 9
 Packing Group III

IMDG/IMO

UN-No UN3077
 Proper Shipping Name Environmentally hazardous substances, solid, n.o.s.
 Hazard Class 9
 Packing Group III

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Anthracene	120-12-7	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Anthracene	120-12-7	X	-	204-371-1	X	X	X	X	X	KE-01825

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)**U.S. Federal Regulations****SARA 313**

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Anthracene	120-12-7	>95	1.0 0.1

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Anthracene	-	-	-	X

Clean Air Act Not applicable

OSHA - Occupational Safety and Health Administration Not applicable

CERCLA This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Anthracene	5000 lb	-

California Proposition 65 This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Anthracene	X	X	X	-	-

U.S. Department of Transportation

Reportable Quantity (RQ): Y
 DOT Marine Pollutant N
 DOT Severe Marine Pollutant N

U.S. Department of Homeland Security This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Slight risk, Grade 1

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Anthracene	-	Use restricted. See item 75. (see link for restriction details)	SVHC Candidate list - 204-371-1 - PBT, Article 57d

After the sunset date the use of this substance requires either an authorization or can only be used for exempted uses, e.g. use in scientific research and development which includes routine analytics or use as intermediate.

<https://echa.europa.eu/authorisation-list>

<https://echa.europa.eu/substances-restricted-under-reach>

<https://echa.europa.eu/candidate-list-table>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Anthracene	120-12-7	Listed	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Anthracene	120-12-7	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By	Regulatory Affairs Thermo Fisher Scientific Email: EMSDS.RA@thermofisher.com
Creation Date	03-May-2012
Revision Date	24-Dec-2021
Print Date	24-Dec-2021
Revision Summary	This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Version 6.7
Revision Date 04/30/2021
Print Date 03/19/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name : Benzaldehyde

Product Number : 418099
Brand : Aldrich
Index-No. : 605-012-00-5
CAS-No. : 100-52-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 4), H227
Acute toxicity, Oral (Category 4), H302
Acute toxicity, Inhalation (Category 4), H332
Skin irritation (Category 2), H315
Eye irritation (Category 2A), H319
Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335
Short-term (acute) aquatic hazard (Category 2), H401
Long-term (chronic) aquatic hazard (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Warning

Hazard statement(s)

H227	Combustible liquid.
H302 + H332	Harmful if swallowed or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H401	Toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ eye protection/ face protection.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms	:	Artificial essential oil of almond
Formula	:	C ₇ H ₆ O
Molecular weight	:	106.12 g/mol
CAS-No.	:	100-52-7
EC-No.	:	202-860-4
Index-No.	:	605-012-00-5

Component	Classification	Concentration
benzaldehyde		
	Flam. Liq. 4; Acute Tox. 4; Skin Irrit. 2; Eye Irrit. 2A; STOT SE 3; Aquatic Acute 2; Aquatic Chronic 3; H227, H302, H332, H315, H319, H335, H401, H412	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO₂) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air on intense heating.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Under fire conditions, material may decompose to form flammable and/or explosive mixtures in air. Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemisorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Store under nitrogen.
Tightly closed.

Air, light, and moisture sensitive.

Storage class (TRGS 510): 10: Combustible liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
benzaldehyde	100-52-7	TWA	2 ppm	USA. Workplace Environmental Exposure Levels (WEEL)
	Remarks	Dermal Sensitization Notation		
		STEL	4 ppm	USA. Workplace Environmental Exposure Levels (WEEL)
		Dermal Sensitization Notation		

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Latex gloves

Minimum layer thickness: 0.6 mm

Break through time: 10 min

Material tested: Lapren® (KCL 706 / Aldrich Z677558, Size M)

Body Protection

protective clothing

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance	Form: liquid Color: colorless
b) Odor	No data available
c) Odor Threshold	No data available
d) pH	5.9 at 20 °C (68 °F)
e) Melting point/freezing point	Melting point/range: -26 °C (-15 °F) - lit.
f) Initial boiling point and boiling range	178 - 179 °C 352 - 354 °F - lit.
g) Flash point	63 °C (145 °F) - closed cup
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 8.5 %(V) Lower explosion limit: 1.4 %(V)
k) Vapor pressure	1.69 hPa at 25 °C (77 °F)
l) Vapor density	3.66 - (Air = 1.0)
m) Relative density	No data available
n) Water solubility	6.95 g/l at 25 °C (77 °F)
o) Partition coefficient: n-octanol/water	log Pow: 1.4 at 25 °C (77 °F) - Bioaccumulation is not expected.
p) Autoignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

Surface tension	70.5 mN/m at 1g/l at 20 °C (68 °F) - OECD Test Guideline 115
Relative vapor density	3.66 - (Air = 1.0)

SECTION 10: Stability and reactivity

10.1 Reactivity

Forms explosive mixtures with air on intense heating.
A range from approx. 15 Kelvin below the flash point is to be rated as critical.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Violent reactions possible with:

bases
Alkali metals
Aluminum
Iron
performic acid
phenols
Oxygen
Oxidizing agents

10.4 Conditions to avoid

Air Exposure to moisture. Light. Heat.
Strong heating.

10.5 Incompatible materials

Aluminum, various plastics, Strong oxidizing agents

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male - 1,430 mg/kg
(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 1 - 5 mg/l
(OECD Test Guideline 436)

LD50 Dermal - Rabbit - > 1,250 mg/kg
Remarks: (RTECS)
No data available

Skin corrosion/irritation

Skin - Rabbit
Result: Moderate skin irritation - 24 h
(Draize Test)

Serious eye damage/eye irritation

Eyes - Rabbit
Result: slight irritation

(OECD Test Guideline 405)

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: Does not cause skin sensitization.

(OECD Test Guideline 406)

- Guinea pig

Result: Does not cause respiratory sensitization.

Remarks:

(ECHA)

Germ cell mutagenicity

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 490

Result: negative

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation. - Lungs

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

RTECS: CU4375000

Central nervous system depression, Prolonged or repeated exposure to skin causes defatting and dermatitis., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

After absorption:

Damage to:

Kidney

Systemic effects:

Aldrich - 418099

Page 8 of 11

Headache
Drowsiness
Convulsions
Dizziness
Shortness of breath
Unconsciousness
narcosis

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Liver - Irregularities - Based on Human Evidence

Liver - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	flow-through test LC50 - <i>Lepomis macrochirus</i> - 1.07 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	semi-static test EC50 - <i>Daphnia magna</i> (Water flea) - 19.7 mg/l - 48 h (OECD Test Guideline 202)
Toxicity to algae	static test ErC50 - <i>Pseudokirchneriella subcapitata</i> - 33.1 mg/l - 72 h (OECD Test Guideline 201)
Toxicity to bacteria	static test IC50 - activated sludge - 759.3 mg/l - 3 h (OECD Test Guideline 209)

12.2 Persistence and degradability

Biodegradability	aerobic - Exposure time 28 d Result: 95 % - Readily biodegradable. (OECD Test Guideline 301B)
------------------	---

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

Forms toxic mixtures in water, dilution measures notwithstanding.
Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

DOT (US)

UN number: 1990 Class: 9 Packing group: III
Proper shipping name: Benzaldehyde
Reportable Quantity (RQ):
Poison Inhalation Hazard: No

IMDG

UN number: 1990 Class: 9 Packing group: III EMS-No: F-A, S-A
Proper shipping name: BENZALDEHYDE

IATA

UN number: 1990 Class: 9 Packing group: III
Proper shipping name: Benzaldehyde

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See

www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.7

Revision Date: 04/30/2021

Print Date: 03/19/2022

SAFETY DATA SHEET

Version 6.7
Revision Date 11/25/2021
Print Date 03/19/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name : Benzene

Product Number : 319953
Brand : SIGALD
Index-No. : 601-020-00-8
CAS-No. : 71-43-2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 2), H225
Skin irritation (Category 2), H315
Eye irritation (Category 2A), H319
Germ cell mutagenicity (Category 1B), H340
Carcinogenicity (Category 1A), H350
Specific target organ toxicity - repeated exposure (Category 1), Blood, H372
Aspiration hazard (Category 1), H304
Short-term (acute) aquatic hazard (Category 2), H401
Long-term (chronic) aquatic hazard (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

SIGALD - 319953

Page 1 of 13

Pictogram



Signal word

Danger

Hazard statement(s)

H225	Highly flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H340	May cause genetic defects.
H350	May cause cancer.
H372	Causes damage to organs (Blood) through prolonged or repeated exposure.
H401	Toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula	: C ₆ H ₆
Molecular weight	: 78.11 g/mol
CAS-No.	: 71-43-2
EC-No.	: 200-753-7
Index-No.	: 601-020-00-8

Component	Classification	Concentration
benzene		
	Flam. Liq. 2; Skin Irrit. 2; Eye Irrit. 2A; Muta. 1B; Carc. 1A; STOT RE 1; Asp. Tox. 1; Aquatic Acute 2; Aquatic Chronic 3; H225, H315, H319, H340, H350, H372, H304, H401, H412	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Flash back possible over considerable distance., Container explosion may occur under fire conditions.

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
benzene	71-43-2	TWA	0.5 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Leukemia Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Confirmed human carcinogen Danger of cutaneous absorption		
		STEL	2.5 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Leukemia Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Confirmed human carcinogen Danger of cutaneous absorption		
		TWA	10 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z37.40-1969		
		CEIL	25 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z37.40-1969		
		Peak	50 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z37.40-1969		
		See 1910.1028. See Table Z-2 for the limits applicable in the operations or sectors excluded in 1910.1028 The final benzene standard in 1910.1028 applies to all occupational exposures to benzene except some subsegments of industry where exposures are consistently		

		under the action level (i.e., distribution and sale of fuels, sealed containers and pipelines, coke production, oil and gas drilling and production, natural gas processing, and the percentage exclusion for liquid mixtures); for the excepted subsegments, the benzene limits in Table Z-2 apply.		
		TWA	0.1 ppm	USA. NIOSH Recommended Exposure Limits
		Potential Occupational Carcinogen See Appendix A		
		ST	1 ppm	USA. NIOSH Recommended Exposure Limits
		Potential Occupational Carcinogen See Appendix A		

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Fluorinated rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact

Material: Fluorinated rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387

and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance	Form: liquid Color: clear, colorless
b) Odor	No data available
c) Odor Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	Melting point/range: 5.5 °C (41.9 °F) - lit.
f) Initial boiling point and boiling range	80 °C 176 °F - lit.
g) Flash point	-11 °C (12 °F) - DIN 51755 Part 1
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Lower explosion limit: 1.4 %(V)
k) Vapor pressure	100 hPa at 20 °C (68 °F)
l) Vapor density	No data available
m) Density	0.874 g/cm ³ at 25 °C (77 °F) - lit.
Relative density	No data available
n) Water solubility	ca.1.88 g/l at 23.5 °C (74.3 °F) - soluble
o) Partition coefficient: n-octanol/water	No data available
p) Autoignition temperature	498 °C (928 °F) at 1,013.5 hPa
q) Decomposition temperature	No data available
r) Viscosity	0.604 mm ² /s at 25 °C (77 °F) -
s) Explosive properties	No data available
t) Oxidizing properties	none

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Exothermic reaction with:

halogens

Halogenated hydrocarbon

in the presence of:

Light metals

Risk of explosion with:

halogen-halogen compounds

Nitric acid

Boranes

Ozone

peroxi compounds

perchlorates

permanganic acid

perchloryl fluoride

Strong oxidizing agents

Chlorine

fluorides

uranium hexafluoride

Oxygen

liquid

Risk of ignition or formation of inflammable gases or vapours with:

chromium(VI) oxide

Fluorine

nitryl compounds

Oxygen

oxyhalogenic compounds

Violent reactions possible with:

mineral acids

sulfur

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

rubber, various plastics

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male - > 2,000 mg/kg
(OECD Test Guideline 401)

Symptoms: Nausea

LC50 Inhalation - Rat - female - 4 h - 43.7 mg/l - vapor

(OECD Test Guideline 403)

LD50 Dermal - Rabbit - male and female - > 8,260 mg/kg

(OECD Test Guideline 402)

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Irritating to skin. - 4 h

(OECD Test Guideline 404)

Drying-out effect resulting in rough and chapped skin.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Eye irritation

Remarks: (ECHA)

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

May cause genetic defects.

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: US-EPA

Result: positive

Test Type: In vitro mammalian cell gene mutation test

Metabolic activation: with and without metabolic activation

Method: US-EPA

Result: positive

Test Type: Mutagenicity (mammal cell test): micronucleus.

Species: Mouse

Cell type: Bone marrow

Application Route: inhalation (vapor)

Method: OECD Test Guideline 474

Result: positive

Carcinogenicity

May cause cancer. Positive evidence from human epidemiological studies.

- IARC: 1 - Group 1: Carcinogenic to humans (benzene)
- NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure. - Blood

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 120 d - NOAEL (No observed adverse effect level) - 100 mg/kg - LOAEL (Lowest observed adverse effect level) - 25 mg/kg

Remarks: Subchronic toxicity

RTECS: CY1400000

Nausea, Dizziness, Headache, narcosis, Inhalation of high concentrations of benzene may have an initial stimulatory effect on the central nervous system characterized by exhilaration, nervous excitation and/or giddiness, depression, drowsiness, or fatigue. The victim may experience tightness in the chest, breathlessness, and loss of consciousness. Tremors, convulsions, and death due to respiratory paralysis or circulatory collapse can occur in a few minutes to several hours following severe exposures. Aspiration of small amounts of liquid immediately causes pulmonary edema and hemorrhage of pulmonary tissue. Direct skin contact may cause erythema. Repeated or prolonged skin contact may result in drying, scaling dermatitis, or development of secondary skin infections. The chief target organ is the hematopoietic system. Bleeding from the nose, gums, or mucous membranes and the development of purpuric spots, pancytopenia, leukopenia, thrombocytopenia, aplastic anemia, and leukemia may occur as the condition progresses. The bone marrow may appear normal, aplastic or hyperplastic, and may not correlate with peripheral blood-forming tissues. The onset of effects of prolonged benzene exposure may be delayed for many months or years after the actual exposure has ceased., Blood disorders

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Systemic effects:

After absorption:

agitation
Headache
Dizziness
inebriation
Tiredness
CNS disorders
narcosis
respiratory arrest

SIGALD - 319953

Page 10 of 13

Subacute toxicity

After a latency period:

Changes in the blood count
haemolysis

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Stomach - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	flow-through test LC50 - <i>Oncorhynchus mykiss</i> (rainbow trout) - 5.3 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	static test EC50 - <i>Daphnia magna</i> (Water flea) - 10 mg/l - 48 h (OECD Test Guideline 202)
Toxicity to algae	static test ErC50 - <i>Pseudokirchneriella subcapitata</i> (green algae) - 100 mg/l - 72 h (OECD Test Guideline 201)
Toxicity to bacteria	static test IC50 - - 13 mg/l - 24 h Remarks: (ECHA)

12.2 Persistence and degradability

Biodegradability	aerobic - Exposure time 28 d Result: 96 % - Readily biodegradable. (OECD Test Guideline 301F)
------------------	---

12.3 Bioaccumulative potential

Bioaccumulation	<i>Leuciscus idus</i> (Golden orfe) - 3 d - 0.05 mg/l(benzene)
	Bioconcentration factor (BCF): 10

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Endangers drinking-water supplies if allowed to enter soil or water.
Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

DOT (US)

UN number: 1114 Class: 3 Packing group: II
Proper shipping name: Benzene
Reportable Quantity (RQ): 10 lbs
Reportable Quantity (RQ): 10 lbs
Poison Inhalation Hazard: No

IMDG

UN number: 1114 Class: 3 Packing group: II EMS-No: F-E, S-D
Proper shipping name: BENZENE

IATA

UN number: 1114 Class: 3 Packing group: II
Proper shipping name: Benzene

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

benzene	CAS-No. 71-43-2	Revision Date 2007-07-01
---------	--------------------	-----------------------------

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

:
Reportable Quantity D018 lbs

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.7

Revision Date: 11/25/2021

Print Date: 03/19/2022

SAFETY DATA SHEET

Revision Date 19-Jan-2018

Revision Number 3

1. Identification

Product Name Benzo[a]pyrene, 98%

Cat No. : AC105600010; AC105601000

CAS-No 50-32-8
Synonyms Benzo[def]chrysene.; 3,4-Benzopyrene; 3,4-Benzpyrene

Recommended Use Laboratory chemicals.
Uses advised against Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

Fisher Scientific
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99

CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin Sensitization	Category 1
Germ Cell Mutagenicity	Category 1A
Carcinogenicity	Category 1A
Reproductive Toxicity	Category 1A

Label Elements

Signal Word

Danger

Hazard Statements

May cause an allergic skin reaction
May cause genetic defects
May cause cancer
May damage fertility or the unborn child

**Precautionary Statements****Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves

Response

IF exposed or concerned: Get medical attention/advice

Skin

IF ON SKIN: Wash with plenty of soap and water
If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse

Storage

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Very toxic to aquatic life with long lasting effects

WARNING. Cancer - <https://www.p65warnings.ca.gov/>.

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Benzo[a]pyrene	50-32-8	> 96

4. First-aid measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes.
Inhalation	Move to fresh air.
Ingestion	Do not induce vomiting.
Most important symptoms and effects	May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Unsuitable Extinguishing Media	No information available
Flash Point	
Method -	No information available
Autoignition Temperature	No information available

Explosion Limits

Upper	No data available
Lower	No data available
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

None known

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
2	0	0	N/A

6. Accidental release measures**Personal Precautions**

Ensure adequate ventilation. Use personal protective equipment.

Environmental Precautions

See Section 12 for additional ecological information. Avoid release to the environment. Collect spillage.

Methods for Containment and Clean Up No information available.

Up

7. Handling and storage**Handling**

Ensure adequate ventilation.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place.

8. Exposure controls / personal protection**Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Benzo[a]pyrene		TWA: 0.2 mg/m ³		

Legend

OSHA - Occupational Safety and Health Administration

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment**Eye/face Protection**

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Powder Solid
Appearance	Dark yellow
Odor	aromatic
Odor Threshold	No information available
pH	
Melting Point/Range	175 179 °C
Boiling Point/Range	°C @ 760 mmHg
Flash Point	
Evaporation Rate	No information available
Flammability (solid,gas)	No information available
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	No information available
Vapor Density	No information available
Specific Gravity	No information available
Solubility	Insoluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	No information available
Decomposition Temperature	No information available
Viscosity	No information available
Molecular Formula	C20H12
Molecular Weight	252.31

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products.
Incompatible Materials	Strong oxidizing agents
Hazardous Decomposition Products	None under normal use conditions
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Component Information

Toxicologically Synergistic Products	No information available
--------------------------------------	--------------------------

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	No information available
Sensitization	No information available
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Benzo[a]pyrene	50-32-8	Group 1	Reasonably Anticipated	A2	X	Not listed

Mutagenic Effects	No information available
-------------------	--------------------------

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure None known

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

Endocrine Disruptor Information No information available

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
Benzo[a]pyrene	Group III Chemical	Not applicable	Not applicable

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Do not empty into drains.

Persistence and Degradability No information available

Bioaccumulation/ Accumulation No information available.

Mobility No information available.

Component	log Pow
Benzo[a]pyrene	6.06

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Benzo[a]pyrene - 50-32-8	U022	-

14. Transport information

DOT

UN-No UN3077
 Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
 Hazard Class 9
 Packing Group III

TDG

UN-No UN3077
 Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
 Hazard Class 9
 Packing Group III

IATA

UN-No UN3077
 Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
 Hazard Class 9
 Packing Group III

IMDG/IMO

UN-No	UN3077
Proper Shipping Name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Hazard Class	9
Packing Group	III

15. Regulatory information**International Inventories**

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Benzo[a]pyrene	X	X	-	200-028-5	-		X	-	-	X	X

Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Benzo[a]pyrene	50-32-8	> 96	0.1

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Benzo[a]pyrene	-	-	X	X

Clean Air Act Not applicable

OSHA Occupational Safety and Health Administration
Not applicable

CERCLA Not applicable

Component	Hazardous Substances RQs	CERCLA EHS RQs
Benzo[a]pyrene	1 lb	-

California Proposition 65 This product does not contain any Proposition 65 chemicals

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Benzo[a]pyrene	50-32-8	Carcinogen	0.06 µg/day	Carcinogen

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Benzo[a]pyrene	X	X	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

16. Other information

Prepared By Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Revision Date 19-Jan-2018

Print Date 19-Jan-2018

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Version 5.7
Revision Date 03/09/2018
Print Date 06/03/2018

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : Benzo[b]fluoranthene

Product Number : 275336
Brand : Aldrich
Index-No. : 601-034-00-4

CAS-No. : 205-99-2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA

Telephone : +1 800-325-5832
Fax : +1 800-325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Carcinogenicity (Category 1B), H350
Acute aquatic toxicity (Category 1), H400
Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H350 May cause cancer.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P273 Avoid release to the environment.
P281 Use personal protective equipment as required.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P391 Collect spillage.
P405 Store locked up.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none**3. COMPOSITION/INFORMATION ON INGREDIENTS****3.1 Substances**

Synonyms : 3,4-Benzofluoranthene
Benz[e]acephenanthrylene
2,3-Benzfluoranthene
3,4-Benz[e]acephenanthrylene
Benzo[b]fluoranthene
Benzo[e]fluoranthene
NSC 89265

Formula : C₂₀H₁₂
Molecular weight : 252.31 g/mol
CAS-No. : 205-99-2
EC-No. : 205-911-9
Index-No. : 601-034-00-4

Hazardous components

Component	Classification	Concentration
Benz[e]acephenanthrylene		
	Carc. 1B; Aquatic Acute 1; Aquatic Chronic 1; H350, H410	90 - 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES**4.1 Description of first aid measures****General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES**5.1 Extinguishing media****Suitable extinguishing media**

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Storage class (TRGS 510): 6.1D: Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Contains no substances with occupational exposure limit values.				
	Remarks	Cancer Substances for which there is a Biological Exposure Index or Indices (see BEI® section), see BEI® for Polycyclic Aromatic Hydrocarbons (PAHs) Exposure by all routes should be carefully controlled to levels as low as possible. Suspected human carcinogen		
Benz[e]acephenanthrylene	205-99-2	PEL	0.2 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

Hazardous components without workplace control parameters

Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
	-	1-Hydroxypyrene	2.5 µg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift at end of workweek			
		3-hydroxybenzo(a)pyrene		Urine	ACGIH - Biological Exposure Indices (BEI)
		End of shift at end of workweek			

8.2 Exposure controls**Appropriate engineering controls**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment**Eye/face protection**

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatrill® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatrill® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Impervious clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties**

- a) Appearance Form: solid

b) Odour	No data available
c) Odour Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	Melting point/range: 163 - 165 °C (325 - 329 °F) - lit.
f) Initial boiling point and boiling range	No data available
g) Flash point	No data available
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	No data available
k) Vapour pressure	No data available
l) Vapour density	No data available
m) Relative density	No data available
n) Water solubility	No data available
o) Partition coefficient: n-octanol/water	No data available
p) Auto-ignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

TDLo Oral - Mouse - 7.57 mg/kg

Remarks: Liver:Changes in liver weight. Endocrine:Changes in thymus weight.

Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

This product is or contains a component that has been reported to be probably carcinogenic based on its IARC, OSHA, ACGIH, NTP, or EPA classification.

Possible human carcinogen

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Benz[e]acephenanthrylene)

NTP: RAHC - Reasonably anticipated to be a human carcinogen (Benz[e]acephenanthrylene)

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: Not available

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity to daphnia and other aquatic invertebrates Immobilization EC50 - Daphnia magna (Water flea) - > 1.024 mg/l - 24 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

Not dangerous goods

IMDG

UN number: 3077 Class: 9 Packing group: III EMS-No: F-A, S-F
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Benz[e]acephenanthrylene)
Marine pollutant:yes

IATA

UN number: 3077 Class: 9 Packing group: III
Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (Benz[e]acephenanthrylene)

Further information

EHS-Mark required (ADR 2.2.9.1.10, IMDG code 2.10.3) for single packagings and combination packagings containing inner packagings with Dangerous Goods > 5L for liquids or > 5kg for solids.

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
Benz[e]acephenanthrylene	205-99-2	2007-03-01

SARA 311/312 Hazards

Chronic Health Hazard

Massachusetts Right To Know Components

	CAS-No.	Revision Date
Benz[e]acephenanthrylene	205-99-2	2007-03-01

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Benz[e]acephenanthrylene	205-99-2	2007-03-01

Benz[e]acephenanthrylene

CAS-No.
205-99-2

Revision Date
2007-03-01

New Jersey Right To Know Components

Benz[e]acephenanthrylene

CAS-No.
205-99-2

Revision Date
2007-03-01

California Prop. 65 Components

WARNING! This product contains a chemical known to the State of California to cause cancer.

Benz[e]acephenanthrylene

CAS-No.
205-99-2

Revision Date
2007-09-28

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Carc.	Carcinogenicity
H350	May cause cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

HMIS Rating

Health hazard:	1
Chronic Health Hazard:	*
Flammability:	0
Physical Hazard	0

NFPA Rating

Health hazard:	2
Fire Hazard:	0
Reactivity Hazard:	0

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information

Sigma-Aldrich Corporation
Product Safety – Americas Region
1-800-521-8956

Version: 5.7

Revision Date: 03/09/2018

Print Date: 06/03/2018



Safety Data Sheet

Revision Date: 12/30/16

www.restek.com

1. IDENTIFICATION

Catalog Number / Product Name:	31274 / Benzo(k)fluoranthene Standard
Company:	Restek Corporation
Address:	110 Benner Circle Bellefonte, Pa. 16823
Phone#:	814-353-1300
Fax#:	814-353-1309
Emergency#:	800-424-9300 (CHEMTREC) 703-527-3887 (Outside the US)
Email:	www.restek.com
Revision Number:	10
Intended use:	For Laboratory use only

2. HAZARD(S) IDENTIFICATION

Emergency Overview:

GHS Hazard
Symbols:



GHS Classification: Flammable Liquid Category 2
Serious Eye Damage/Eye Irritation Category 2
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

GHS Signal Word: Danger

GHS Hazard: Highly flammable liquid and vapour.
Causes serious eye irritation.
May cause drowsiness or dizziness.

GHS Precautions:

Safety Precautions: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilation and lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Wash hands and skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

First Aid Measures: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Call a POISON CENTER or doctor/physician if you feel unwell.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use extinguishing media in section 5 for extinction.

Storage: Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal: Dispose of contents/container according to section 13 of the SDS.

Single Exposure
Target Organs:

No data available.

Repeated Exposure
Target Organs:

No data available.

3. COMPOSITION / INFORMATION ON INGREDIENT

Chemical Name	CAS #	EINEC #	% Composition
Acetone	67-64-1	200-662-2	99.900000
benzo (k) fluoranthene	207-08-9	205-916-6	0.100000

4. FIRST-AID MEASURES

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately.

Eyes: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

Skin Contact: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

Ingestion: Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this SDS.

5. FIRE- FIGHTING MEASURES

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and keep exposed material from being damaged by fire. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

Fire and/or Explosion Hazards: Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a Class B fire. Vapors are heavier than air and may travel to a source of ignition and flash back.

Fire Fighting Methods and Protection: Do not enter fire area without proper protection including self-contained toxic breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling.

Hazardous Combustion Products: Carbon dioxide, Carbon monoxide

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment: Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods for Clean-up: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

7. HANDLING AND STORAGE

Handling Technical Measures and Precautions: Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Use spark-proof tools and explosion-proof equipment.

Storage Technical Measures and Conditions: Store in a cool dry ventilated location. Isolate from

incompatible materials and conditions. Keep container(s) closed. Keep away from sources of ignition

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

United States:

Chemical Name	CAS No.	IDLH	ACGIH STEL	ACGIH TLV-TWA	OSHA Exposure Limit
Acetone	67-64-1	2500 ppm IDLH (10% LEL)	500 ppm STEL 750 ppm STEL; 1782 mg/m3 STEL	250 ppm TWA 500 ppm TWA; 1188 mg/m3 TWA	1000 ppm TWA; 2400 mg/m3 TWA
benzo (k) fluoranthene	207-08-9	ND		No TLV	No data available.

Personal Protection:

Engineering Measures:

Local exhaust ventilation is recommended when generating excessive levels of vapors from handling or thermal processing.

Respiratory Protection:

No respiratory protection required under normal conditions of use. Provide general room exhaust ventilation if symptoms of overexposure occur as explained Section 3. A respirator is not normally required.

Eye Protection:

Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.

Skin Protection:

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work

Medical Conditions Aggravated By Exposure: Respiratory disease including asthma and bronchitis

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance, color:	Depends upon product selection
Odor:	Strong
Physical State:	No data available.
pH:	No data available.
Vapor Pressure:	No data available.
Vapor Density:	2.0 (air = 1)
Boiling Point:	No data available.
Melting Point:	-95.4 °C Melting Point
Flash Point:	39
Flammability:	Highly Flammable
Upper Flammable/Explosive Limit, % in air:	No data available.
Lower Flammable/Explosive Limit, % in air:	No data available.
Autoignition Temperature:	465 deg C
Decomposition Temperature:	No data available.
Specific Gravity:	0.7845 g/cm3 at 25 °C
Evaporation Rate:	No data available.
Odor Threshold:	ND
Solubility:	Complete; 100%
Partition Coefficient: n-octanol in water:	No data available.
VOC % by weight:	0
Molecular Weight:	58.08

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	No data available.
Materials to Avoid / Chemical Incompatibility:	Strong oxidizing agents Strong acids
Hazardous Decomposition Products:	Carbon dioxide Carbon monoxide

11. TOXICOLOGICAL INFORMATION

Routes of Entry:	Inhalation, Skin Contact, Eye Contact, Ingestion
Target Organs Potentially Affected By Exposure:	Eyes, Central nervous system stimulation, Respiratory Tract, Skin
Chemical Interactions That Change Toxicity:	None Known

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation: Can cause minor respiratory irritation, dizziness, weakness, fatigue, nausea, and headache.

Skin Contact: Can cause minor skin irritation, defatting, and dermatitis.

Eye Contact: Can cause minor irritation, tearing and reddening.

Ingestion Irritation: May be harmful if swallowed.

Ingestion Toxicity: Harmful if swallowed. May cause systemic poisoning.

Long-Term (Chronic) Health Effects:

Carcinogenicity: Contains a probable or known human carcinogen.

Reproductive and Developmental Toxicity: No data available to indicate product or any components present at greater than 0.1% may cause birth defects.

Inhalation: Upon prolonged and/or repeated exposure, can cause minor respiratory irritation, dizziness, weakness, fatigue, nausea, and headache.

Skin Contact: Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and dermatitis.

Component Toxicological Data:

NIOSH:

Chemical Name	CAS No.	LD50/LC50
Acetone	67-64-1	Dermal LD50 Rabbit >15700 mg/kg; Oral LD50 Rat 5800 mg/kg; Inhalation LC50 Rat 50100 mg/m3 8 h

Component Carcinogenic Data:

OSHA:

Chemical Name	CAS No.	
Benzo(k)fluoranthene	207-08-9	Present

ACGIH:

Chemical Name	CAS No.	
Acetone	67-64-1	A4 - Not Classifiable as a Human Carcinogen

NIOSH:

Chemical Name	CAS No.
No data available.	

NTP:

Chemical Name	CAS No.
No data available.	

IARC:

Chemical Name	CAS No.	Group No.
No data.		Group 1
No data.		Group 2A
Benzo(k)fluoranthene	207-08-9	Group 2B

12. ECOLOGICAL INFORMATION

Overview:	This material is not expected to be harmful to the ecology.
Mobility:	No data
Persistence:	No data
Bioaccumulation:	No data
Degradability:	No data
Ecological Toxicity Data:	No data available.

13. DISPOSAL CONSIDERATIONS

Waste Description of Spent Product:	Spent or discarded material is a hazardous waste.
Disposal Methods:	Dispose of by incineration following Federal, State, Local, or Provincial regulations.
Waste Disposal of Packaging:	Comply with all Local, State, Federal, and Provincial Environmental Regulations.

14. TRANSPORTATION INFORMATION

United States:	
DOT Proper Shipping Name:	Acetone
UN Number:	UN1090

Hazard Class: 3
Packing Group: II

International:
IATA Proper Shipping Name: Acetone
UN Number: UN1090
Hazard Class: 3
Packing Group: II

Marine Pollutant: No

Chemical Name	CAS#	Marine Pollutant	Severe Marine Pollutant
No data available.			

15. REGULATORY INFORMATION

United States:

Chemical Name	CAS#	CERCLA	SARA 313	SARA EHS 313	TSCA
Acetone	67-64-1	X	-	-	X
benzo (k) fluoranthene	207-08-9	X	X	-	-

The following chemicals are listed on CA Prop 65:

Chemical Name	CAS #	Regulation
Benzo[k]fluoranthene	207-08-9	Prop 65 Cancer

State Right To Know Listing:

Chemical Name	CAS#	New Jersey	Massachusetts	Pennsylvania	California
Acetone	67-64-1	X	X	X	X
benzo (k) fluoranthene	207-08-9	X	X	X	X

16. OTHER INFORMATION

Prior Version Date: 05/15/15

Other Information: Any changes to the SDS compared to previous versions are marked by a vertical line in front of the concerned paragraph.

References: No data available.

Disclaimer: Restek Corporation provides the descriptions, data and information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. It is provided for your guidance only. Because many factors may affect processing or application/use, Restek Corporation recommends you perform an assessment to determine the suitability of a product for your particular purpose prior to use. No warranties of any kind, either expressed or implied, including fitness for a particular purpose, are made regarding products described, data or information set forth. In no case shall the descriptions, information, or data provided be considered a part of our terms and conditions of sale. Further, the descriptions, data and information furnished hereunder are given gratis. No obligation or liability for the description, data and information given are assumed. All such being given and accepted at your risk.

Beryllium



Safety Data Sheet

Section 1: Identification

1.1 Product Identifier

Product Name: Beryllium
Product Form: Solid
Chemical Family: Metal
CAS Number: 7440-41-7
Molecular Formula: Be
Molecular Weight: 9.01

1.2 Other Means of Identification

Synonyms: Beryllium-9, Glucinium, Beryllium Element, Glucinum, UN 1567, RCRA P015, Be, DLA02910, RTECS DS1750000

1.3 Recommended Uses

Recommended Use: Variety of radiological, mechanical, and industrial applications.

1.4 Manufacturer, Importer, or Responsible Party

Responsible Party: Defense Logistics Agency Strategic Materials
8725 John J. Kingman Road
Fort Belvoir, Virginia 22060-6223
(703) 767-5525

1.5 Emergency Phone Number

Emergency Phone Number: (800) 424-9300 (CHEMTREC)
(703) 527-3887 (CHEMTREC INTERNATIONAL)

Section 2: Hazard(s) Identification

2.1 Classification of Chemical per OSHA CFR 1910.1200

Acute Toxicity (Oral): Category 4
Acute Toxicity (Inhalation): Category 2
Skin Irritation: Category 2
Eye Irritation: Category 2A
Carcinogen: Category 1A
Reproductive Toxicity: Category 2
Target Organ – Single: Category 3 (Respiratory System)
Target Organ – Prolonged: Category 1 (Respiratory System)

2.2 Label Elements

Signal Word: DANGER



Symbol(s):

Hazard Statements:

May cause lung cancer via inhalation. Causes damage to lungs through prolonged or repeated exposure via inhalation. Harmful if swallowed. Fatal if inhaled. Causes skin irritation and serious eye irritation. Suspected of damaging fertility or the unborn child, may cross the placenta.

Precautionary Statements:

Prevention: Obtain special instruction before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, clothing, and eye and/or face protection. Do not eat, drink, or smoke when using this product. Do not breathe dust. Use only outdoors or in a well-ventilated area. In case of inadequate ventilation, wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wash hands and exposed skin thoroughly after handling.

Response: If swallowed or inhaled, immediately call a poison control center and/or doctor. Rinse mouth. If inhaled, remove person to fresh air and keep comfortable for breathing. If on skin, wash with plenty of water. If skin and eye irritation occurs and/or persists or exposed, concerned or skin rash occurs, get medical attention and/or advice. Wash contaminated clothing before reuse. If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents in accordance with federal, state, and local regulations.

2.3 Other Hazards

Negligible fire and explosion hazard in bulk form. Dust/air mixtures may ignite or explode. May react on contact with water. Contaminated clothing should not be taken home at the end of shift, but should remain at employee's place of work for cleaning.

2.4 Unknown Acute Toxicity

Does not apply to this product.

Section 3: Composition / Information on Ingredients

3.1 Chemical Name

Chemical Name:

Beryllium

Composition:

99.0%-99.7% Be

The health and physical hazards information provided in this SDS are for its major component. Beryllium metal contains other elements in addition to Be. For concentrations of other components, see the Certificates of Analysis for each lot.

3.2 Common Names/Synonyms

Synonyms:

See **Section 1.2** for common names and synonyms.

3.3 CAS Number/Unique Identifiers

CAS Number:

7440-41-7

EC Number (EINECS):

231-150-7

EC Index Number:

004-001-00-7

3.4 Impurities/Stabilizing Additives

No data available.

Section 4: First-Aid Measures

4.1 Description of First-Aid Measures

Ensure that adequate decontamination has been carried out.

Inhalation:	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention.
Skin Contact:	Remove contaminated clothing and shoes. Wash skin with soap and water for at least 15 minutes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.
Eye Contact:	Flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.
Ingestion:	If swallowed, get medical attention. Do not induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain an open airway and prevent aspiration. Get medical attention.

4.2 Most Important Symptoms/Effects, Acute and Delayed

Inhalation (Short-Term):	May cause irritation, fever, difficulty breathing, irregular heartbeat, lung congestion.
Inhalation (Chronic):	Long term exposure may cause skin disorders, changes in blood pressure, weight loss, chest pain, difficulty breathing fatigue, blood disorders, bone disorders, kidney damage, liver damage, cancer. Storage of absorbed beryllium takes place in bones. There is some retention of a transient nature by liver, kidney, and lung.
Skin Contact (Acute):	May cause irritation.
Skin Contact (Chronic):	May cause irritation.
Eye Contact (Acute):	May cause irritation.
Eye Contact (Chronic):	May cause irritation.
Ingestion (Acute):	May cause irritation, difficulty breathing.
Ingestion (Chronic):	No information on significant adverse effects.

4.3 Indication of Immediate Medical Attention/Special Treatment

Get immediate medical attention if inhaled, exposed to eyes, and/or ingested. Identified antidotes include calcium disodium edetate/dextrose, intravenous, and calcium disodium edetate/procaine, intramuscular.

Section 5: Fire-Fighting Measures

5.1 Suitable Extinguishing Media

Extinguishing media includes dolomite, dry powder for metal fires, dry sand, graphite, soda ash, and sodium chloride or approved Class D extinguishers. DO NOT use carbon dioxide or halogenated extinguishing agents. For fires involving beryllium, extinguish with water spray, fog, or standard foam. DO NOT use straight water streams.

5.2 Specific Hazards

Negligible fire and explosion hazard in bulk form. Dust/air mixtures may ignite or explode.

5.3 Special Protective Equipment and Precautions

Wear a self-contained breathing apparatus and protective clothing when fighting fires. Move container from fire area if it can be done without risk. Cool containers with flooding amounts of water until well after the fire is out; however, do not get water inside containers. Stay away from the ends of tanks. For fires in cargo or storages areas, cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is not possible, take the following precautions: Keep all unauthorized personnel away, isolate hazard area, and deny entry. Let the

fire burn. Use extinguishing agents appropriate for the surrounding fire. Avoid inhalation of material or combustion by-products. Keep run-off water out of sewers and water sources.

Section 6: Accidental Release Measures

6.1 Personal Precautions, Protective Equipment, and Emergency Procedures

Wear nitrile rubber gloves, eye protection, self-contained respirator, and protective clothing. Subject to California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65). Notify Local Emergency Planning Committee and State Emergency Response Commission for release greater than or equal to RQ of 10 lb or 4.54 kg (US SARA Section 304). If release occurs in the US and is reportable under CERCLA Section 103, notify the National Response Center at (800) 424-8802 or (202) 426-2675. No reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is larger than 100 micrometers (0.004 inches). Keep out of water supplies and sewers. Keep all unauthorized people away, isolate hazard area, and deny entry. Personal protective equipment is discussed **Section 8.3**.

6.2 Methods and Materials for Containment and Cleaning Up

For small dry spills, collect beryllium and place in a clean, dry container for later disposal. Scoop up and place in a large stoppered wide mouth bottle. Save spilled material for recovery. Wash site with soap solution. Wastewater from contaminant suppression, cleaning of protective clothing/equipment, or contaminated sites should be contained and evaluated for subject chemical or decomposition product concentrations. For large spills, first dike the area, then wet down material with water for later disposal.

For a land spill, dig a pit, pond, lagoon, holding area to contain liquid or solid material. If time permits, pits, ponds, lagoons, soak holes, or holding areas should be sealed with an impermeable flexible membrane liner. Cover solids with a plastic sheet to prevent dissolving in rain or fire-fighting water. Dike surface flow using soil, sand bags, foamed polyurethane, or foamed concrete. If spilled to water, use natural barriers or oil spill control booms to limit spill travel. Remove trapped material with suction hoses.

Section 7: Handling and Storage

7.1 Precautions for Safe Handling

Keep storage container tightly sealed. Transfer material in closed systems or within a completely hooded containment with local exhaust ventilation. Prevent spillage. Prevent contact with clothing. Flush container clean before discarding. Particulate may enter the body through cuts, abrasions or other wounds on the surface of the skin. Wear gloves when handling this product. Personal protective equipment is discussed in **Section 8.3**.

7.2 Conditions for Safe Storage

Store in accordance with all current regulations and standards. Beryllium should be stored in dry areas, away from incompatible substances and sources of ignition, including any sparking or arcing electrical apparatus. Incompatible materials are identified in **Section 10.5**.

Section 8: Exposure Controls / Personal Protection

8.1 Exposure Limits

OSHA PEL TWA:	0.002 mg/m ³
OSHA Ceiling:	0.005 mg/m ³ (30 minutes) with a maximum peak of 0.025 mg/m ³
ACGIH TWA:	0.002 mg/m ³
ACGIH STEL:	0.01 mg/m ³
IDLH:	4 mg/m ³ , Ca
NIOSH REL TWA (10 Hr NTE):	0.0005 mg/m ³ Ceiling, Ca
AGS TRK (Metal):	0.005 mg/m ³
AGS TRK (Other):	0.002 mg/m ³
UK WEL TWA:	0.002 mg/m ³

8.2 Appropriate Engineering Controls

Ventilation:

Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

8.3 Individual Protection Measures

Eye Protection:

Wear splash resistant safety goggles with a faceshield. Provide an emergency eye wash fountain and quick drench shower in the immediate area.

Clothing:

Wear appropriate chemical resistant clothing (preferably disposable, one-piece and close fitting at ankles and wrists), gloves, hair covering, and over shoes. Work clothing that becomes wet or significantly contaminated should be removed and replaced.

Gloves:

Wear appropriate chemical resistant gloves.

Respirator:

Under conditions of frequent use or heavy exposure, respiratory protection may be needed. Respiratory protection is ranked in order from minimum to maximum. Consider warning properties before use.

1. Any particulate respirator equipped with an N95, R95, or P95 filter (including N95, R95, and P95 filtering facepieces) except quarter-mask respirators. The following filters may also be used: N99, R99, P99, N100, R100, or P100.

2. Any air-purifying full-facepiece respirator equipped with an N95, R95, or P95 filter. The following filters may also be used: N99, R99, P99, N100, R100, or P100.

3. Any powered, air-purifying respirator with a high-efficiency particulate filter.

4. Any powered, air-purifying respirator with a tight-fitting facepiece and a high-efficiency particulate filter.

5. Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode.

Unknown Concentrations/IDLH:

1. Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in a pressure-demand or other positive-pressure mode.

2. Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

Section 9: Physical and Chemical Properties**9.1 Appearance**

Physical State:

Solid

Physical Description:

Grayish-white brittle metal.

9.2 Odor

Odor:

Odorless.

9.3 Odor Threshold

Not applicable.

9.4 pH

Not applicable.

9.5 Melting / Freezing Points

Melting Point: 2,323°F - 2,341°F (1,273°C - 1,283°C)
Freezing Point: Not applicable.

9.6 Initial Boiling Point and Boiling Range

Boiling Point: 5,378°F (2,970°C) @ 5 mmHg

9.7 Flash Point

No data available.

9.8 Evaporation Rate

Not applicable.

9.9 Flammability

No data available.

9.10 Upper/Lower Explosive Limits

No data available.

9.11 Vapor Pressure

Vapor Pressure: 7.6 mmHg @ 3,470°F (1,910°C)

9.12 Vapor Density

Not applicable.

9.13 Relative Density

Water = 1: 1.848

9.14 Solubility(ies)

Insoluble: Cold Water, Mercury
Soluble: Acids, Alkalis, Dilute Nitric Acid, Slightly Soluble in Hot Water

9.15 Partition Coefficient

No available.

9.16 Auto-Ignition Temperature

No data available.

9.17 Decomposition Temperature

No data available.

9.18 Viscosity

No data available.

Section 10: Stability and Reactivity**10.1 Reactivity**

Avoid contact with water or moisture. May react with evolution of heat on contact with water.

10.2 Chemical Stability

Stable at normal temperatures and pressures.

10.3 Possibility of Hazardous Reactions

Acids (Strong): Reacts to produce flammable hydrogen gas.
Bases (Strong): Attacked and evolves flammable hydrogen gas.
Carbon Dioxide: Violent reaction.
Carbon Dioxide + Nitrogen: May ignite on heating.
Carbon Tetrachloride: Forms shock-sensitive mixture.

Chlorine:	Incandescent reaction when heated.
Fluorine:	Incandescent reaction when heated.
Halides:	Reacts.
Halocarbon Solvents:	May form shock-sensitive mixtures.
Hydrochloric Acid:	Reacts with finely divided or amalgamated beryllium.
Lithium:	Severely attacks beryllium metal.
Metals (Alkali):	Reacts to forms salts.
Nitric Acid (Dilute):	Reacts with finely divided or amalgamated beryllium.
Oxidizers:	Reacts vigorously.
Phosphorus:	Incandescent reaction on heating.
Sulfuric Acid:	Reacts with finely divided or amalgamated beryllium.
Trichloroethylene:	Forms shock-sensitive mixture.

10.4 Conditions to Avoid

None reported.

10.5 Incompatible Materials

Incompatibilities: Acids, bases, halocarbons, oxidizing materials, halogens, metals, and combustible materials.

Safe storage of the material is discussed in **Section 7.2**.

10.6 Hazardous Decomposition Products

Thermal Decomposition Products: Oxides of beryllium.

Section 11: Toxicological Information

11.1 Likely Routes of Exposure

Routes of entry include inhalation, skin contact, eye contact, and ingestion.

11.2 Symptoms

See **Section 4.2** for symptoms related to the chemical and toxicological characteristics.

11.3 Short and Long Term Effects

Inhalation (Acute):

Brief, intense exposure to pulmonary irritants may cause severe chemical pneumonitis. Symptoms may include bronchial spasm, nasopharyngitis, tracheobronchitis, cough, blood tinged sputum, dyspnea, cyanosis, nasal discharge, fever, anorexia, fatigue, tachycardia, and possibly cor pulmonale. Fatal pulmonary edema or spontaneous pneumothorax has been reported. Studies in rats indicate a severe, chemical pneumonitis followed by a quiescent period of minimal inflammation and mild fibrosis occurs. Later, progressive fibrosing pneumonitis was observed in these rats. With sufficient exposure, effects as detailed in chronic exposure may occur.

Inhalation (Chronic):

In addition to the effects described in acute exposure, prolonged or repeated exposure may cause "berylliosis", a disorder that generally affects the upper and lower respiratory tract, but the onset may be marked by weakness, fatigue, and weight loss with or without dyspnea. Symptoms may be delayed from 1-25 years from exposure and may be precipitated by additional physical stress. Signs of pulmonary insufficiency and systemic effects may occur including dyspnea on exertion or at rest, burning chest pain, constant non-productive hacking cough, wheezing, clubbing of fingers, low blood pressure, enlarged liver, spleen, and parotid gland, osteoarthropathy, increase in hematocrit, elevated serum uric acid, nephrolithiasis, hypercalciuria with or without stones, hypercalcemia, spontaneous skin lesions, and cor pulmonale due to increasing pulmonary fibrosis and pulmonary resistance. Less common effects may include hemoptysis, seizure disorders and palpitations. Severely disabled persons may show cachexia and signs of right heart impairment with severe non-productive

cough, spontaneous pneumothorax, and bouts of chills and fever. Death may be due to cardiac or respiratory failure, or in rare cases, renal failure. Pathological findings include extrapulmonary changes of focal granulomatous lesions in the abdominal lymph nodes, spleen, liver, and bone marrow, as well as renal involvement. Human studies indicate that berylliosis may be a disease resulting from pulmonary sensitization and responding with inflammatory changes which tend to be granulomatous. Cumulative exposure to beryllium has produced decreased lung function that is distinct from berylliosis. Epidemiological studies show an excess of lung cancer in white males occupationally exposed to beryllium or beryllium compounds.

Skin Contact (Acute):

May cause irritation. Sensitization is reported to not occur from contact of intact skin with beryllium metal. However, accidental implantation of particles beneath the skin may cause necrosis of adjacent tissue, formation of ulcer, and granulomatous hypersensitivity reaction.

Skin Contact (Chronic):

Repeated exposure to irritants may cause dermatitis.

Eye Contact (Acute):

Contact with dust may cause conjunctival inflammation. Introduction into corneas of rabbits produced slight clouding of the surrounding cornea.

Eye Contact (Chronic):

May cause conjunctivitis and possibly severe periorbital edema.

Ingestion (Acute):

May cause coughing and shortness of breath. Experimental evidence suggests that little beryllium is absorbed from the gastrointestinal tract.

Ingestion (Chronic):

In animal studies, beryllium metal eaten in the diet at a level of 5% is so poorly absorbed that no effect on growth occurred over long periods of feeding. However, beryllium tends to displace magnesium in the body after a prolonged period of time.

11.4 Numerical Measures of Toxicity

Target organs include the immune system (sensitizer). May cross the placenta. Contact with beryllium compounds may exacerbate a pre-existing berylliosis condition.

Toxicity Data:

496 µg/kg intravenous-rat LD₅₀
 51 mg/kg intratracheal-rat LD₅₀
 20 ng/m³/8 hour (s)-26 week(s) intermittent inhalation-rat TCL₀
 20 ng/m³/1 hour(s)-17 week(s) intermittent inhalation- mammal TCL₀
 2 µg/m³/8 hour(s)-26 week(s) intermittent inhalation-human TCL₀

Tumorigenic Data:

13 mg/kg intratracheal-rat TDL₀; 20 mg/kg intravenous-rabbit TDL₀

Mutagenic Data:

DNA adduct - Escherichia coli 30 µmol/L
 DNA inhibition - non-mammalian species intravenous 30 µmol/kg
 DNA adduct - human HeLa cell 30 µmol/L
 DNA adduct - mouse Ascites tumor 30 µmol/L

11.5 Carcinogen Status

OSHA:

No data available.

NTP:

Known Human Carcinogen

IARC:

Human Sufficient Evidence, Animal Sufficient Evidence, Group 1 (Beryllium and Beryllium Compounds)

ACGIH:

A1 – Confirmed Human Carcinogen (Beryllium and Beryllium Compounds)

EC:

Category 2 (Beryllium and Beryllium Compounds)

TRGS:

K2

Section 12: Ecological Information

12.1 Ecotoxicity

LC50

Daphnia magna (Water Flea) age < or =24 hr

Conditions: freshwater, static, 22 deg C, pH 7.4-9.4, dissolved oxygen 6.5-9.1 mg/L; Concentration: 1900 µg/L for 24 hr (95% confidence interval: 1100-3300 µg/L) /> or =80% purity

LC50	<i>Daphnia magna</i> (Water Flea) age < or =24 hr Conditions: freshwater, static, 22 deg C, pH 7.4-9.4, dissolved oxygen 6.5-9.1 mg/L; Concentration: 1900 ug/L for 48 hr (95% confidence interval: 800-1600 ug/L) /> or =80% purity
LC50	<i>Hyalella azteca</i> (Scud) age 1-11 day young organism Conditions: freshwater, static, 24-25 deg C, pH 7.39 (6.44-8.52); Concentration: 67 ug/L for 7 days (95% confidence interval: 53-85 ug/L)
LC50	<i>Hyalella azteca</i> (Scud) age 1-11 day young organism Conditions: freshwater, static, 24-25 deg C, pH 8.21 (7.23-8.83); Concentration: 240 ug/L for 7 days (95% confidence interval: 181-316 ug/L)

12.2 Persistence and Degradability

No data available.

12.3 Bioaccumulative Potential

No data available.

12.4 Mobility in Soil

No data available.

12.5 Other Adverse Effects

No data available.

Section 13: Disposal Considerations

Dispose in accordance with all applicable regulations. Subject to disposal regulations: USEPA 40 CFR 262. Hazardous Waste Number(s): P015. Consider recovering and recycling of beryllium as an alternative to its disposal.

Beryllium solid waste should be placed into impermeable, sealed bags or containers (e.g., drums) that are labeled in accordance with the requirements of USEPA or applicable regulations.

Waste waters containing beryllium may require treatment to reduce the concentration of beryllium. A typical treatment method for beryllium involves steps such as chemical precipitation, settling clarification, neutralization, filtration, and sludge dewatering.

Section 14: Transport Information

14.1 UN Number

UN Number: 3077 (solid)

14.2 UN Proper Shipping Name

UN Proper Shipping Name: RQ Environmentally Hazardous Substances, Solid, N.O.S., (Beryllium).

14.3 Transport Hazard Class(es)

Hazard Class:	9 (solid)
CA Transportation/Dangerous Goods:	No classification assigned.
Land Transport ADR:	No classification assigned.
Land Transport RID:	No classification assigned.
Air Transport IATA:	No classification assigned.
Air Transport ICAO:	No classification assigned.
Maritime Transport IMDG:	No classification assigned.

14.4 Packing Group

Packing Group: III (solid)

14.5 Environmental Hazards

No data available.

14.6 Transport in Bulk

No data available.

14.7 Special Precautions

No data available.

Section 15: Regulatory Information

US Regulations

CERCLA 102A/103 (40 CFR 302.4): Beryllium: 10 lbs. RQ
(solid metal particles <100 micrometer diameter).

SARA Title III

Section 302 (40 CFR 355.30): Not regulated.
Section 304 (40 CFR 355.40): Not regulated.
Sections 311/312 (40 CFR 370.21): Yes (Acute, Chronic, Reactive)
Section 313 (40 CFR 372.65): Yes (Beryllium and compounds)

OSHA Process Safety: Not regulated.

State Regulations

California Proposition 65: Beryllium and compounds are known to cause cancer.

National Inventory Status

US Inventory (TSCA): Listed on inventory.
TSCA 12(b) Export Notification: Not listed.

Section 16: Other Information

The information in this Safety Data Sheet meets the requirements of the United States Department of Labor OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION and regulations promulgated thereunder (29 CFR 1910.1200 et. seq.). This document is intended only as a guide to the appropriate precautionary material handling by a person trained in, or supervised by a person trained in, chemical handling. Exposure to this chemical may have serious adverse health effects. This chemical may interact with other substances. Since the potential uses are so varied, all of the potential hazards of use or interaction with other chemicals or materials cannot be identified on this Safety Data Sheet. The user should recognize that this chemical can cause injury, especially if improperly handled, precautionary measures are not followed, and personal protective equipment not worn. Read and understand all precautionary information prior to use. The Defense Logistics Agency (DLA) shall not be held liable for any damage resulting from handling or from contact with the above chemical.

References:

ChemADVISOR. *Material Safety Data Sheet, Beryllium*. March 13, 2008. (as provided by the Defense Logistics Agency)

American Conference of Governmental Industrial Hygienists. *2013 TLVs® and BEIs®*, ACGIH® Publication #0113. 2013.

US Department of Transportation. *Emergency Response Guidebook*. 2012

Centers for Disease Control and Prevention. *NIOSH Pocket Guide to Chemical Hazards*, <http://www.cdc.gov/niosh/npg/>.

National Institute of Health, Toxicology Data Network. <http://toxnet.nlm.nih.gov/>

NOTE: No data available: no data for this topic found using references listed.

Date of Preparation of Updated SDS: April 10, 2015

SAFETY DATA SHEET

Version 6.5
Revision Date 10/30/2021
Print Date 03/19/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name : Biphenyl

Product Number : W312908

Brand : Aldrich

Index-No. : 601-042-00-8

CAS-No. : 92-52-4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765

Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Skin irritation (Category 2), H315

Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

Short-term (acute) aquatic hazard (Category 1), H400

Long-term (chronic) aquatic hazard (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Warning

Aldrich - W312908

Page 1 of 11

Hazard statement(s)	
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H410	Very toxic to aquatic life with long lasting effects.
Precautionary statement(s)	
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ eye protection/ face protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P391	Collect spillage.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula	: C ₁₂ H ₁₀
Molecular weight	: 154.21 g/mol
CAS-No.	: 92-52-4
EC-No.	: 202-163-5
Index-No.	: 601-042-00-8

Component	Classification	Concentration
biphenyl	Skin Irrit. 2; Eye Irrit. 2A; STOT SE 3; Aquatic Acute 1; Aquatic Chronic 1; H315, H319, H335, H400, H410 M-Factor - Aquatic Acute: 1 - Aquatic Chronic: 1	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO₂) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Nature of decomposition products not known.

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air on intense heating.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Dry.

Storage class

Storage class (TRGS 510): 13: Non Combustible Solids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
biphenyl	92-52-4	TWA	0.2 ppm	USA. ACGIH Threshold Limit Values (TLV)
		TWA	0.2 ppm 1 mg/m ³	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		TWA	0.2 ppm 1 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	0.2 ppm 1 mg/m ³	USA. NIOSH Recommended Exposure Limits
		PEL	0.2 ppm 1.5 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: KCL 741 Dermatrill® L

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: KCL 741 Dermatrill® L

Body Protection

protective clothing

Respiratory protection

required when dusts are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

a)	Appearance	Form: crystalline Color: light yellow
b)	Odor	characteristic
c)	Odor Threshold	0.009 ppm
d)	pH	5.5
e)	Melting point/freezing point	Melting point/range: 68 - 70 °C (154 - 158 °F) - lit.
f)	Initial boiling point and boiling range	255 °C 491 °F - lit.
g)	Flash point	110 °C (230 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	The product is not flammable. - Flammability (solids)
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 5.8 %(V) Lower explosion limit: 0.6 %(V)
k)	Vapor pressure	0.04 hPa at 20 °C (68 °F)
l)	Vapor density	No data available
m)	Density	0.992 g/cm3
	Relative density	No data available
n)	Water solubility	0.00713 g/l at 24.6 °C (76.3 °F) - Regulation (EC) No. 440/2008, Annex, A.6 - slightly soluble
o)	Partition coefficient: n-octanol/water	log Pow: 4.008 at 25 °C (77 °F) - Potential bioaccumulation
p)	Autoignition temperature	566 °C (1051 °F) at 1013.0 hPa
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	none

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Forms explosive mixtures with air on intense heating.

A range from approx. 15 Kelvin below the flash point is to be rated as critical.

The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally be assumed.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

increased reactivity with:

Oxidizing agents

10.4 Conditions to avoid

Strong heating.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 2,140 mg/kg

Symptoms: Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract.

Remarks: (RTECS)

Symptoms: mucosal irritations, Cough, Shortness of breath, Inhalation may lead to the formation of oedemas in the respiratory tract., Possible damages:, damage of respiratory tract

LD50 Dermal - Rabbit - > 5,010 mg/kg

Remarks: (RTECS)

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Severe irritations - 24 h

(Draize Test)

Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Serious eye damage/eye irritation

Causes serious eye irritation. Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative
(OECD Test Guideline 406)

Germ cell mutagenicity

Test Type: Ames test

Result: negative

Remarks: (HSDB)

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: without metabolic activation

Method: OECD Test Guideline 476

Result: positive

Test Type: Micronucleus test

Species: Mouse

Application Route: Oral

Method: OECD Test Guideline 474

Result: negative

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation. - Respiratory system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

RTECS: DU8050000

Liver injury may occur., Gastrointestinal disturbance

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Systemic effects:

After uptake:

muscular weakness

Drowsiness

Diarrhea

ataxia (impaired locomotor coordination)

After long-term exposure to the chemical:

Damage to:

Liver
Kidney
Cardiac

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	flow-through test LC50 - Pimephales promelas (fathead minnow) - 3 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	flow-through test EC50 - Daphnia magna (Water flea) - 0.36 mg/l - 48 h (US-EPA)

12.2 Persistence and degradability

Biodegradability	aerobic - Exposure time 28 d Result: 64.4 % - Readily biodegradable. (OECD Test Guideline 301F)
------------------	---

12.3 Bioaccumulative potential

Bioaccumulation	Oncorhynchus mykiss (rainbow trout) - 4 d (biphenyl) Bioconcentration factor (BCF): 1,900 (OECD Test Guideline 305)
-----------------	---

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

DOT (US)

UN number: 3077 Class: 9 Packing group: III
Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (biphenyl)
Reportable Quantity (RQ): 100 lbs
1) Marine pollutant: yes Poison Inhalation Hazard: No

IMDG

UN number: 3077 Class: 9 Packing group: III EMS-No: F-A, S-F
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (biphenyl)
Marine pollutant : yes

IATA

UN number: 3077 Class: 9 Packing group: III
Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (biphenyl)

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
biphenyl	92-52-4	1993-04-24

SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the

present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.5

Revision Date: 10/30/2021

Print Date: 03/19/2022

SAFETY DATA SHEET

Revision Date 24-Dec-2021

Revision Number 4

1. Identification

Product Name Cadmium

Cat No. : C3-500

CAS No 7440-43-9
Synonyms No information available

Recommended Use Laboratory chemicals.
Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet**Company**

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Emergency Telephone Number CHEMTREC®, Inside the USA: 800-424-9300
CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification**Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable solids	Category 2
Acute oral toxicity	Category 4
Acute dermal toxicity	Category 4
Acute Inhalation Toxicity - Dusts and Mists	Category 2
Germ Cell Mutagenicity	Category 2
Carcinogenicity	Category 1A
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system.	
Specific target organ toxicity - (repeated exposure)	Category 1
Target Organs - Kidney, Blood.	
Combustible dust	Yes

Label Elements**Signal Word**

Danger

Hazard Statements

Flammable solid
May form combustible dust concentrations in air
Fatal if inhaled
Harmful if swallowed
Harmful in contact with skin
May cause respiratory irritation
Suspected of causing genetic defects
May cause cancer
Suspected of damaging fertility. Suspected of damaging the unborn child
Causes damage to organs through prolonged or repeated exposure

**Precautionary Statements****Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Do not breathe dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting equipment

Response

IF exposed or concerned: Get medical attention/advice

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN: Wash with plenty of soap and water
Wash contaminated clothing before reuse
Call a POISON CENTER or doctor/physician if you feel unwell

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
Rinse mouth

Fire

Fight fire with normal precautions from a reasonable distance
Evacuate area

Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Very toxic to aquatic life with long lasting effects
WARNING. Cancer and Reproductive Harm - <https://www.p65warnings.ca.gov/>.

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Cadmium	7440-43-9	100

4. First-aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Most important symptoms and effects	None reasonably foreseeable. . Kidney disorders: May cause harm to the unborn child: Blood disorders
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Unsuitable Extinguishing Media	No information available
Flash Point	No information available
Method -	No information available
Autoignition Temperature	No information available
Explosion Limits	
Upper	No data available
Lower	No data available
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. Fine dust dispersed in air may ignite. Dust can form an explosive mixture with air. Pyrophoric properties of solids and liquids. Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products

Toxic fumes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health
4

Flammability
1

Instability
0

Physical hazards
N/A

6. Accidental release measures

Personal Precautions	Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust
-----------------------------	--

Environmental Precautions formation. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas.
Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

Methods for Containment and Clean Up Sweep up and shovel into suitable containers for disposal. Avoid dust formation.

7. Handling and storage

Handling Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid dust formation. Use only under a chemical fume hood. Do not breathe (dust, vapor, mist, gas). Do not ingest. If swallowed then seek immediate medical assistance.

Storage. Keep containers tightly closed in a dry, cool and well-ventilated place. Store under an inert atmosphere. Incompatible Materials. Strong oxidizing agents. Strong acids. Sulfur oxides.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Cadmium	TWA: 0.01 mg/m ³ TWA: 0.002 mg/m ³	Ceiling: 0.3 mg/m ³ Ceiling: 0.6 mg/m ³ (Vacated) STEL: 0.3 ppm TWA: 0.1 mg/m ³ TWA: 0.2 mg/m ³ TWA: 5 µg/m ³	IDLH: 9 mg/m ³	TWA: 0.01 mg/m ³ TWA: 0.002 mg/m ³

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures When using do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing. Avoid contact with skin, eyes or clothing. Wash hands before breaks and immediately after handling the product. Keep away from food, drink and animal feeding stuffs.

9. Physical and chemical properties

Physical State Solid

Appearance	Silver
Odor	Odorless
Odor Threshold	No information available
pH	No information available
Melting Point/Range	321 °C / 609.8 °F
Boiling Point/Range	765 °C / 1409 °F @ 760 mmHg
Flash Point	No information available
Evaporation Rate	Not applicable
Flammability (solid,gas)	No information available
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	No information available
Vapor Density	Not applicable
Specific Gravity	8.64 @ 25°C
Solubility	Insoluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	No information available
Decomposition Temperature	No information available
Viscosity	Not applicable
Molecular Formula	Cd
Molecular Weight	112.40

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under recommended storage conditions. Moisture sensitive. Air sensitive.
Conditions to Avoid	Incompatible products. Excess heat. Avoid dust formation. Exposure to air or moisture over prolonged periods.
Incompatible Materials	Strong oxidizing agents, Strong acids, Sulfur oxides
Hazardous Decomposition Products	Toxic fumes
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Cadmium	LD50 = 2330 mg/kg (Rat)	Not listed	LC50 = 25 mg/m ³ (Rat) 30 min

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	No information available
Sensitization	No information available
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Cadmium	7440-43-9	Group 1	Known	A2	X	A2

IARC (International Agency for Research on Cancer)

NTP: (National Toxicity Program)

ACGIH: (American Conference of Governmental Industrial Hygienists)

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mutagenic Effects

Possible risk of irreversible effects

Reproductive Effects

Possible risk of impaired fertility. May cause harm to the unborn child.

Developmental Effects

No information available.

Teratogenicity

No information available.

STOT - single exposure

Respiratory system

STOT - repeated exposure

Kidney Blood

Aspiration hazard

No information available

Symptoms / effects, both acute and delayed

Kidney disorders: May cause harm to the unborn child: Blood disorders

Endocrine Disruptor Information

No information available

Other Adverse Effects

The toxicological properties have not been fully investigated.

12. Ecological information



Ecotoxicity

The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Cadmium	Not listed	LC50: 0.0004 - 0.003 mg/L, 96h (Pimephales promelas) LC50: = 0.016 mg/L, 96h (Oryzias latipes) LC50: = 21.1 mg/L, 96h flow-through (Lepomis macrochirus) LC50: = 0.24 mg/L, 96h static (Cyprinus carpio) LC50: = 4.26 mg/L, 96h semi-static (Cyprinus carpio) LC50: = 0.002 mg/L, 96h	Not listed	EC50: = 0.0244 mg/L, 48h Static (Daphnia magna)

		(Cyprinus carpio) LC50: = 0.006 mg/L, 96h static (Oncorhynchus mykiss) LC50: = 0.003 mg/L, 96h flow-through (Oncorhynchus mykiss)		
--	--	---	--	--

Persistence and Degradability No information available

Bioaccumulation/ Accumulation No information available.

Mobility No information available.

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN2930
Proper Shipping Name Toxic solid, flammable, organic, n.o.s.
Technical Name Cadmium
Hazard Class 6.1
Subsidiary Hazard Class 4.1
Packing Group I

TDG

UN-No UN2930
Proper Shipping Name Toxic solid, flammable, organic, n.o.s.
Hazard Class 6.1
Subsidiary Hazard Class 4.1
Packing Group I

IATA

UN-No UN2930
Proper Shipping Name Toxic solid, flammable, organic, n.o.s.
Hazard Class 6.1
Subsidiary Hazard Class 4.1
Packing Group I

IMDG/IMO

UN-No UN2930
Proper Shipping Name Toxic solid, flammable, organic, n.o.s.
Hazard Class 6.1
Subsidiary Hazard Class 4.1
Packing Group I

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Cadmium	7440-43-9	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Cadmium	7440-43-9	X	-	231-152-8	X	X		X	X	KE-04397

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations**SARA 313**

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Cadmium	7440-43-9	100	0.1

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Cadmium	-	-	X	X

Clean Air Act

OSHA - Occupational Safety and Health Administration Not applicable

Component	Specifically Regulated Chemicals	Highly Hazardous Chemicals
Cadmium	5 µg/m³ TWA 2.5 µg/m³ Action Level	-

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Cadmium	10 lb	-

California Proposition 65

This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Cadmium	7440-43-9	Carcinogen Developmental Male Reproductive	0.05 µg/day	Developmental Carcinogen

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Cadmium	X	X	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Cadmium	-	Use restricted. See item 72. (see link for restriction details) Use restricted. See item 23. (see link for restriction details) Use restricted. See item 28. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	SVHC Candidate list - 231-152-8 - Carcinogenic, Article 57a; Specific target organ toxicity after repeated exposure, Article 57(f) - human health

After the sunset date the use of this substance requires either an authorization or can only be used for exempted uses, e.g. use in scientific research and development which includes routine analytics or use as intermediate.

<https://echa.europa.eu/authorisation-list>

<https://echa.europa.eu/substances-restricted-under-reach>

<https://echa.europa.eu/candidate-list-table>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Cadmium	7440-43-9	Listed	Not applicable	Not applicable	0.01% (Max. Conc.)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Cadmium	7440-43-9	Not applicable	Not applicable	Not applicable	Annex I - Y26

16. Other information

Prepared By Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Revision Date 24-Dec-2021

Print Date 24-Dec-2021

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Creation Date 14-May-2010

Revision Date 24-Dec-2021

Revision Number 5

1. Identification

Product Name Carbazole

Cat No. : AC108260000; AC108260010; AC108260050; AC108260250;
AC108262500; AC108265000

CAS No 86-74-8
Synonyms 9-Azafluorene; Dibenzopyrrole; Diphenylenimine

Recommended Use Laboratory chemicals.
Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system.	

Label Elements

Signal Word
Warning

Hazard Statements

Causes skin irritation
Causes serious eye irritation
May cause respiratory irritation
Suspected of causing cancer



Precautionary Statements

Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Wear eye/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area

Response

IF exposed or concerned: Get medical attention/advice

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

IF ON SKIN: Wash with plenty of soap and water
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Very toxic to aquatic life with long lasting effects
WARNING. Cancer - <https://www.p65warnings.ca.gov/>.

3. Composition/Information on Ingredients

Component	CAS No	Weight %
9H-Carbazole	86-74-8	>95

4. First-aid measures

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention.

Inhalation

Remove from exposure, lie down. Remove to fresh air. Get medical attention.

Ingestion

Clean mouth with water. Get medical attention.

Most important symptoms and effects	No information available.
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Water spray. Carbon dioxide (CO ₂). Dry chemical. Chemical foam.
Unsuitable Extinguishing Media	No information available
Flash Point	220 °C / 428 °F
Method -	No information available
Autoignition Temperature	540 °C / 1004 °F
Explosion Limits	
Upper	No data available
Lower	No data available
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products

Nitrogen oxides (NO_x). Carbon monoxide (CO). Carbon dioxide (CO₂).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health
2

Flammability
1

Instability
0

Physical hazards
N/A

6. Accidental release measures

Personal Precautions	Ensure adequate ventilation. Use personal protective equipment as required.
Environmental Precautions	Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained. See Section 12 for additional Ecological Information. Avoid release to the environment. Collect spillage.
Methods for Containment and Clean Up	Sweep up and shovel into suitable containers for disposal. Do not let this chemical enter the environment.

7. Handling and storage

Handling	Avoid contact with skin and eyes. Do not breathe dust. Do not ingest. If swallowed then seek immediate medical assistance. Handle product only in closed system or provide appropriate exhaust ventilation.
Storage.	Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Incompatible Materials. Strong oxidizing agents. Strong bases.

8. Exposure controls / personal protection

Exposure Guidelines	This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.
----------------------------	---

Engineering Measures Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Solid
Appearance	Beige
Odor	pungent
Odor Threshold	No information available
pH	No information available
Melting Point/Range	240 - 246 °C / 464 - 474.8 °F
Boiling Point/Range	355 °C / 671 °F @ 760 mmHg
Flash Point	220 °C / 428 °F
Evaporation Rate	Not applicable
Flammability (solid,gas)	No information available
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	400 mmHg @ 323 °C
Vapor Density	Not applicable
Specific Gravity	1.1
Solubility	insoluble
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	540 °C / 1004 °F
Decomposition Temperature	No information available
Viscosity	Not applicable
Molecular Formula	C ₁₂ H ₉ N
Molecular Weight	167.21

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid Incompatible products.

Incompatible Materials Strong oxidizing agents, Strong bases

Hazardous Decomposition Products Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
9H-Carbazole	>5000 mg/kg (Rat)	Not listed	Not listed

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation No information available

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen. Limited evidence of a carcinogenic effect.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
9H-Carbazole	86-74-8	Group 2B	Not listed	Not listed	X	Not listed

IARC (International Agency for Research on Cancer)

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Mutagenic Effects Not mutagenic in AMES Test

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Respiratory system
STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed No information available

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated. See actual entry in RTECS for complete information.

12. Ecological information

Ecotoxicity

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
9H-Carbazole	Not listed	Not listed	EC50 = 10.6 mg/L 15 min EC50 = 11.6 mg/L 30 min EC50 = 13.6 mg/L 5 min	Not listed

Persistence and Degradability Insoluble in water Persistence is unlikely

Bioaccumulation/ Accumulation No information available.

Mobility . Is not likely mobile in the environment due its low water solubility.

Component	log Pow
9H-Carbazole	3.84

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN3077
 Proper Shipping Name Environmentally hazardous substances, solid, n.o.s.
 Technical Name 9H-Carbazole
 Hazard Class 9
 Packing Group III

TDG

UN-No UN3077
 Proper Shipping Name Environmentally hazardous substances, solid, n.o.s.
 Hazard Class 9
 Packing Group III

IATA

UN-No UN3077
 Proper Shipping Name Environmentally hazardous substances, solid, n.o.s.
 Hazard Class 9
 Packing Group III

IMDG/IMO

UN-No UN3077
 Proper Shipping Name Environmentally hazardous substances, solid, n.o.s.
 Hazard Class 9
 Packing Group III

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
9H-Carbazole	86-74-8	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
9H-Carbazole	86-74-8	X	-	201-696-0	X	X	X	X	X	KE-04664

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations

SARA 313	Not applicable
SARA 311/312 Hazard Categories	See section 2 for more information
CWA (Clean Water Act)	Not applicable
Clean Air Act	Not applicable
OSHA - Occupational Safety and Health Administration	Not applicable
CERCLA	Not applicable

California Proposition 65 This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
9H-Carbazole	86-74-8	Carcinogen	4.1 µg/day	Carcinogen

U.S. State Right-to-Know Regulations Not applicable

U.S. Department of Transportation

Reportable Quantity (RQ):	N
DOT Marine Pollutant	N
DOT Severe Marine Pollutant	N

U.S. Department of Homeland Security This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

Authorisation/Restrictions according to EU REACH

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
9H-Carbazole	86-74-8	Listed	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
9H-Carbazole	86-74-8	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Creation Date 14-May-2010
Revision Date 24-Dec-2021
Print Date 24-Dec-2021

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Creation Date 11-Nov-2010

Revision Date 28-Dec-2021

Revision Number 7

1. Identification

Product Name Carbon disulfide

Cat No. : AC445660000; AC445660010; AC445660025; AC445661000

CAS No 75-15-0
Synonyms No information available

Recommended Use Laboratory chemicals.
Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Acute Inhalation Toxicity - Vapors	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Central nervous system (CNS).	
Specific target organ toxicity - (repeated exposure)	Category 1
Target Organs - Liver, Kidney.	

Label Elements

Signal Word
Danger

Hazard Statements

Highly flammable liquid and vapor
Causes skin irritation
Causes serious eye irritation
Harmful if inhaled
May cause drowsiness or dizziness
Suspected of damaging fertility. Suspected of damaging the unborn child
Causes damage to organs through prolonged or repeated exposure

**Precautionary Statements****Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Use only outdoors or in a well-ventilated area
Wash face, hands and any exposed skin thoroughly after handling
Wear eye/face protection
Do not breathe dust/fume/gas/mist/vapors/spray
Do not eat, drink or smoke when using this product
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Response

IF exposed or concerned: Get medical attention/advice

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other hazards**

Stench. Contains a known or suspected endocrine disruptor.

WARNING. Reproductive Harm - <https://www.p65warnings.ca.gov/>.

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Carbon disulfide	75-15-0	>95

4. First-aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Inhalation	Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. If not breathing, give artificial respiration.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Most important symptoms and effects	Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	Water may be ineffective
Flash Point	-30 °C / -22 °F
Method -	No information available
Autoignition Temperature	100 °C / 212 °F
Explosion Limits	
Upper	60 vol %
Lower	1 vol %
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition. Extremely flammable. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Sulfur oxides.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health
3Flammability
4Instability
0Physical hazards
N/A

6. Accidental release measures

Personal Precautions	Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
Environmental Precautions	Should not be released into the environment. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.
Methods for Containment and Clean Up	Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling	Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.
Storage.	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Incompatible Materials. Amines. Halogens. Fluorine. Metals. copper. Butyl rubber. Oxidizing agent.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Carbon disulfide	TWA: 1 ppm Skin	(Vacated) TWA: 4 ppm (Vacated) TWA: 12 mg/m ³ Ceiling: 30 ppm (Vacated) STEL: 12 ppm (Vacated) STEL: 36 mg/m ³ Skin TWA: 20 ppm	IDLH: 500 ppm TWA: 1 ppm TWA: 3 mg/m ³ STEL: 10 ppm STEL: 30 mg/m ³	TWA: 1 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures	Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location.
-----------------------------	---

Personal Protective Equipment

Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166. Tight sealing safety goggles. Face protection shield.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Colorless
Odor	Stench
Odor Threshold	No information available
pH	No information available 5
Melting Point/Range	-111 °C / -167.8 °F
Boiling Point/Range	46 °C / 114.8 °F @ 760 mmHg
Flash Point	-30 °C / -22 °F
Evaporation Rate	No information available
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	60 vol %
Lower	1 vol %
Vapor Pressure	400 hPa @ 20 °C
Vapor Density	2.67 (Air = 1.0)
Specific Gravity	1.262
Solubility	Soluble
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	100 °C / 212 °F
Decomposition Temperature	No information available
Viscosity	0.363 cP at 20 °C
Molecular Formula	C S ₂
Molecular Weight	76.13

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Excess heat. Incompatible products. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Amines, Halogens, Fluorine, Metals, copper, Butyl rubber, Oxidizing agent
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂), Sulfur oxides
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information**Acute Toxicity****Product Information****Component Information**

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Carbon disulfide	LD50 = 1200 mg/kg (Rat)	Not listed	LC50 = 10.35 mg/L (Rat) 4 h

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes and skin

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Carbon disulfide	75-15-0	Not listed	Not listed	Not listed	Not listed	Not listed

Mutagenic Effects Substances which cause concern for man owing to possible mutagenic effects but for which the available information is not adequate for making a satisfactory assessment

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Central nervous system (CNS)
STOT - repeated exposure Liver Kidney

Aspiration hazard No information available

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
Carbon disulfide	Group II Chemical	Not applicable	Not applicable

Other Adverse Effects Teratogenic effects have occurred in experimental animals.

12. Ecological information

Ecotoxicity

The product contains following substances which are hazardous for the environment. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Contains a substance which is: Toxic to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Carbon disulfide	Not listed	LC50: = 4 mg/L, 96h static (Poecilia reticulata) LC50: 3 - 5.8 mg/L, 96h semi-static (Poecilia reticulata)	EC50 = 260 mg/L 15 min	EC50: = 2.1 mg/L, 48h (Daphnia magna)

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
Carbon disulfide	1.9

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No

UN1131

Proper Shipping Name CARBON DISULFIDE
Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group I

TDG

UN-No UN1131
Proper Shipping Name CARBON DISULFIDE
Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group I

IATA

UN-No UN1131
Proper Shipping Name CARBON DISULPHIDE
Hazard Class 3
Subsidiary Hazard Class 6.1

IMDG/IMO

UN-No UN1131
Proper Shipping Name CARBON DISULPHIDE
Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group I

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Carbon disulfide	75-15-0	X	ACTIVE	TP

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TP - Indicates a substance that is the subject of a proposed TSCA Section 4 test rule

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Carbon disulfide	75-15-0	X	-	200-843-6	X	X	X	X	X	KE-04755

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations**SARA 313**

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Carbon disulfide	75-15-0	>95	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Carbon disulfide	X	100 lb	-	-

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Carbon disulfide	X		-

OSHA - Occupational Safety and Health Administration

Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Carbon disulfide	100 lb	100 lb

California Proposition 65

This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Carbon disulfide	75-15-0	Developmental Female Reproductive Male Reproductive	-	Developmental

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Carbon disulfide	X	X	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product contains the following DHS chemicals:

Legend - STQs = Screening Threshold Quantities, APA = A placarded amount

Component	DHS Chemical Facility Anti-Terrorism Standard
Carbon disulfide	Release STQs - 20000lb

Other International Regulations

Mexico - Grade

Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Carbon disulfide	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Carbon disulfide	75-15-0	Listed	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities	Seveso III Directive (2012/18/EC) - Qualifying Quantities	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)

		for Major Accident Notification	for Safety Report Requirements		
Carbon disulfide	75-15-0	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Creation Date 11-Nov-2010
Revision Date 28-Dec-2021
Print Date 28-Dec-2021
Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Version 6.4
Revision Date 07/28/2021
Print Date 03/19/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name : Chlorobenzene

Product Number : 284513
Brand : Sigma-Aldrich
Index-No. : 602-033-00-1
CAS-No. : 108-90-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 3), H226
Acute toxicity, Inhalation (Category 4), H332
Skin irritation (Category 2), H315
Short-term (acute) aquatic hazard (Category 2), H401
Long-term (chronic) aquatic hazard (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Warning

Sigma-Aldrich - 284513

Page 1 of 11

Hazard statement(s)	
H226	Flammable liquid and vapor.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
Precautionary statement(s)	
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ eye protection/ face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391	Collect spillage.
P403 + P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula	: C ₆ H ₅ Cl
Molecular weight	: 112.56 g/mol
CAS-No.	: 108-90-7
EC-No.	: 203-628-5
Index-No.	: 602-033-00-1

Component	Classification	Concentration
chlorobenzene		
	Flam. Liq. 3; Acute Tox. 4; Skin Irrit. 2; Aquatic Acute 2; Aquatic Chronic 2; H226, H332, H315, H401, H411	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. If breathing stops: mouth-to-mouth breathing or artificial respiration. Oxygen if necessary. Immediately call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most). Consult doctor if feeling unwell.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO₂) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Hydrogen chloride gas

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemisorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
chlorobenzene	108-90-7	TWA	10 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Confirmed animal carcinogen with unknown relevance to humans		

		TWA	75 ppm 350 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	10 ppm 46 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
chlorobenzene	108-90-7	4-Chlorocatechol	100mg/g Creatinine	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift at end of workweek			
		p-Chlorophenol	20mg/g Creatinine	Urine	ACGIH - Biological Exposure Indices (BEI)
		End of shift at end of workweek			

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Viton®

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 10 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

a) Appearance	Form: liquid Color: colorless
b) Odor	weak
c) Odor Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	Melting point/range: -45 °C (-49 °F) - lit.
f) Initial boiling point and boiling range	132 °C 270 °F - lit.
g) Flash point	27 °C (81 °F) - DIN 51755 Part 1
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 11 %(V) Lower explosion limit: 1.3 %(V)
k) Vapor pressure	12.05 hPa at 20 °C (68 °F) - OECD Test Guideline 104
l) Vapor density	No data available
m) Density	1.106 g/cm ³ at 25 °C (77 °F) - lit.
Relative density	No data available
n) Water solubility	0.207 g/l at 20 °C (68 °F)
o) Partition coefficient: n-octanol/water	log Pow: 2.84 at 20 °C (68 °F) - - Bioaccumulation is not expected., (ECHA)
p) Autoignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapor/air-mixtures are explosive at intense warming.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Exothermic reaction with:

Alkali metals

Alkaline earth metals

Oxidizing agents

dimethyl sulfoxide

Nitric acid

Risk of explosion with:

sodium

in finely distributed form.

with

sodium

10.4 Conditions to avoid

Heating.

10.5 Incompatible materials

rubber

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - > 2,000 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Rat - male - 4 h - 15.57 mg/l

(OECD Test Guideline 403)

Dermal: No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Skin irritation - 4 h

(OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation

(OECD Test Guideline 405)

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: negative

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: Mutagenicity (mammal cell test):

Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

RTECS: CZ0175000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Systemic effects:

CNS disorders

tachycardia

drop in blood pressure

agitation, spasms

ataxia (impaired locomotor coordination)

narcosis

Headache

Damage to:

Liver

Kidney

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	static test LC50 - <i>Lepomis macrochirus</i> (Bluegill sunfish) - 4.5 mg/l - 96 h Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates	static test EC50 - <i>Daphnia magna</i> (Water flea) - 26 mg/l - 48 h (OECD Test Guideline 202)
Toxicity to algae	static test EC10 - <i>Desmodesmus subspicatus</i> (green algae) - 5.8 mg/l - 72 h (OECD Test Guideline 201) static test ErC50 - <i>Desmodesmus subspicatus</i> (green algae) - 11.4 mg/l - 72 h (OECD Test Guideline 201)
Toxicity to bacteria	static test EC50 - activated sludge - 140 mg/l - 30 min (OECD Test Guideline 209)

12.2 Persistence and degradability

Biodegradability	aerobic - Exposure time 28 d Result: 15 % - Not readily biodegradable. (OECD Test Guideline 301F) aerobic - Exposure time 28 d Result: 0 % - Not readily biodegradable. (OECD Test Guideline 301C)
Theoretical oxygen demand	2,060 mg/g Remarks: (Lit.)
Ratio BOD/ThBOD	1.5 % Remarks: (Lit.)

12.3 Bioaccumulative potential

Bioaccumulation	<i>Cyprinus carpio</i> (Carp) - 49 d at 25 °C(chlorobenzene) Bioconcentration factor (BCF): 3.9 - 23 (OECD Test Guideline 305C)
-----------------	--

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

DOT (US)

UN number: 1134 Class: 3 Packing group: III
Proper shipping name: Chlorobenzene
Reportable Quantity (RQ): 100 lbs
Reportable Quantity (RQ): 100 lbs
Poison Inhalation Hazard: No

IMDG

UN number: 1134 Class: 3 Packing group: III EMS-No: F-E, S-D
Proper shipping name: CHLOROBENZENE
Marine pollutant : yes

IATA

UN number: 1134 Class: 3 Packing group: III
Proper shipping name: Chlorobenzene

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

chlorobenzene	CAS-No. 108-90-7	Revision Date 2007-07-01
---------------	---------------------	-----------------------------

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard
:

Sigma-Aldrich - 284513

Page 10 of 11

Reportable Quantity D021 lbs

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.4

Revision Date: 07/28/2021

Print Date: 03/19/2022

SAFETY DATA SHEET

Version 6.3
Revision Date 04/18/2021
Print Date 03/19/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name : Chloroform

Product Number : 288306
Brand : Sigma-Aldrich
CAS-No. : 67-66-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Acute toxicity, Oral (Category 4), H302
Acute toxicity, Inhalation (Category 3), H331
Skin irritation (Category 2), H315
Eye irritation (Category 2A), H319
Carcinogenicity (Category 2), H351
Reproductive toxicity (Category 2), H361
Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336
Specific target organ toxicity - repeated exposure (Category 1), Liver, Kidney, H372
Short-term (acute) aquatic hazard (Category 3), H402
Long-term (chronic) aquatic hazard (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Sigma-Aldrich - 288306

Page 1 of 12

Pictogram



Signal word

Danger

Hazard statement(s)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs (Liver, Kidney) through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P311	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms	:	Trichloromethane Methylidyne trichloride
Formula	:	CHCl ₃

Sigma-Aldrich - 288306

Page 2 of 12

Molecular weight : 119.38 g/mol
CAS-No. : 67-66-3

Component	Classification	Concentration
Chloroform		
	Acute Tox. 4; Acute Tox. 3; Skin Irrit. 2; Eye Irrit. 2A; Carc. 2; Repr. 2; STOT SE 3; STOT RE 1; Aquatic Acute 3; H302, H331, H315, H319, H351, H361, H336, H372, H402 Concentration limits: 20 %: STOT SE 3, H336;	<= 100 %
ethanol		
	Flam. Liq. 2; Eye Irrit. 2A; H225, H319 Concentration limits: >= 50 %: Eye Irrit. 2A, H319;	>= 1 - < 5 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Consult a physician. Show this material safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Hydrogen chloride gas

Not combustible.

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist.

Hygiene measures

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510): 6.1D: Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Chloroform	67-66-3	TWA	10 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Confirmed animal carcinogen with unknown relevance to humans		
		ST	2 ppm 9.78 mg/m ³	USA. NIOSH Recommended Exposure Limits
		Potential Occupational Carcinogen		
		C	50 ppm 240 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	2 ppm 9.78 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m ³	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		TWA	1,000 ppm 1,900 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		STEL	1,000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Confirmed animal carcinogen with unknown relevance to humans		
		TWA	1,000 ppm 1,900 mg/m ³	USA. NIOSH Recommended Exposure Limits
		PEL	1,000 ppm 1,900 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Fluorinated rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact

Material: Fluorinated rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|---------------------------------|---|
| a) Appearance | Form: liquid, clear
Color: colorless |
| b) Odor | sweet |
| c) Odor Threshold | No data available |
| d) pH | No data available |
| e) Melting point/freezing point | Melting point/range: -63 °C (-81 °F) - lit. |
| f) Initial boiling point | 60.5 - 61.5 °C 140.9 - 142.7 °F - lit. |

Sigma-Aldrich - 288306

Page 6 of 12

and boiling range

- | | |
|---|---|
| g) Flash point | () - Regulation (EC) No. 440/2008, Annex, A.9 does not flash |
| h) Evaporation rate | No data available |
| i) Flammability (solid, gas) | No data available |
| j) Upper/lower flammability or explosive limits | No data available |
| k) Vapor pressure | 210 hPa at 20 °C (68 °F) |
| l) Vapor density | 4.12 - (Air = 1.0) |
| m) Relative density | No data available |
| n) Water solubility | 8.7 g/l at 23 °C (73 °F) - OECD Test Guideline 105 |
| o) Partition coefficient: n-octanol/water | No data available |
| p) Autoignition temperature | No data available |
| q) Decomposition temperature | Distillable in an undecomposed state at normal pressure. |
| r) Viscosity | No data available |
| s) Explosive properties | No data available |
| t) Oxidizing properties | No data available |

9.2 Other safety information

- | | |
|------------------------------|---|
| Solubility in other solvents | organic solvent at 20 °C (68 °F) - miscible |
| Relative vapor density | 4.12 - (Air = 1.0) |

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.
Contains the following stabilizer(s):
ethanol (≥ 0.5 - ≤ 1 %)

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

various plastics, Rubber Strong oxidizing agents

10.6 Hazardous decomposition products

In the event of fire: see section 5

Sigma-Aldrich - 288306

Page 7 of 12

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

No data available

LD50 Oral - Rat - male - 908 mg/kg
(OECD Test Guideline 401)

Inhalation: No data available

Acute toxicity estimate Inhalation - Expert judgment - 4 h - 3.1 mg/l

Dermal: No data available

Dermal: No data available

No data available

No data available

Skin corrosion/irritation

No data available

Skin - Rabbit

Result: Irritating to skin. - 24 h

Remarks: (ECHA)

Drying-out effect resulting in rough and chapped skin.

Skin - Rabbit

Result: slight irritation

Remarks: (IUCLID)

Serious eye damage/eye irritation

No data available

Eyes - Rabbit

Result: Irritating to eyes.

Remarks: (ECHA)

(Regulation (EC) No 1272/2008, Annex VI)

Respiratory or skin sensitization

No data available

Maximization Test - Guinea pig

Result: negative

(Regulation (EC) No. 440/2008, Annex, B.6)

Germ cell mutagenicity

No data available

Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Remarks: (ECHA)

Sigma-Aldrich - 288306

Page 8 of 12

Test Type: unscheduled DNA synthesis assay
Test system: Liver
Metabolic activation: without metabolic activation
Result: negative
Remarks: (ECHA)

Test Type: Micronucleus test
Species: Rat
Cell type: Red blood cells (erythrocytes)
Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

Test Type: unscheduled DNA synthesis assay
Species: Rat
Cell type: Liver cells
Application Route: Oral
Method: OECD Test Guideline 486
Result: negative

Test Type: in vivo assay
Species: Mouse

Application Route: Inhalation

Result: negative
Remarks: (ECHA)

Carcinogenicity

Suspected of causing cancer.

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Chloroform)

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Suspected of damaging the unborn child.

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Repeated dose toxicity - Rat - female - Oral - NOAEL (No observed adverse effect level) - 34 mg/kg
Not available

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Vomiting, Cough, irritant effects, Shortness of breath, respiratory arrest, narcosis, Dizziness, Nausea, agitation, spasms, inebriation, Headache, Stomach/intestinal disorders, ataxia (impaired locomotor coordination), cardiovascular disorders
Drying-out effect resulting in rough and chapped skin.
To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

No data available

Toxicity to algae	static test ErC50 - Chlamydomonas reinhardtii (green algae) - 13.3 mg/l - 72 h Remarks: (ECHA) (Chloroform)
-------------------	---

Toxicity to bacteria	Remarks: (ECHA) (Chloroform)
----------------------	---------------------------------

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

DOT (US)

UN number: 1888 Class: 6.1 Packing group: III
Proper shipping name: Chloroform
Reportable Quantity (RQ): 10 lbs
Reportable Quantity (RQ): 10 lbs
Poison Inhalation Hazard: No

IMDG

UN number: 1888 Class: 6.1 Packing group: III EMS-No: F-A, S-A
Proper shipping name: CHLOROFORM

IATA

UN number: 1888 Class: 6.1 Packing group: III
Proper shipping name: Chloroform

SECTION 15: Regulatory information

SARA 302 Components

The following components are subject to reporting levels established by SARA Title III, Section 302:

Chloroform	CAS-No. 67-66-3	Revision Date 2008-11-03
------------	--------------------	-----------------------------

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

Chloroform	CAS-No. 67-66-3	Revision Date 2008-11-03
------------	--------------------	-----------------------------

SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

:
Reportable Quantity D022 lbs

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information

Further information

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.3

Revision Date: 04/18/2021

Print Date: 03/19/2022

Chloromethane

Safety Data Sheet 1100516

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 12/03/2015

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Substance
 Substance name : Chloromethane
 CAS No : 74-87-3
 Product code : 1100-5-16
 Formula : CH₃Cl
 Synonyms : Methyl chloride
 Other means of identification : MFCD00000872

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Laboratory chemicals
 Manufacture of substances
 Scientific research and development

1.3. Details of the supplier of the safety data sheet

SynQuest Laboratories, Inc.
 P.O. Box 309
 Alachua, FL 32615 - United States of America
 T (386) 462-0788 - F (386) 462-7097
info@synquestlabs.com - www.synquestlabs.com

1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Gas 1 H220 - Extremely flammable gas
 Liquefied gas H280 - Contains gas under pressure; may explode if heated
 Carc. 2 H351 - Suspected of causing cancer
 Repr. 2 H361 - Suspected of damaging fertility or the unborn child
 STOT RE 2 H373 - May cause damage to organs (eye, nervous system, testis) through prolonged or repeated exposure

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H220 - Extremely flammable gas
 H280 - Contains gas under pressure; may explode if heated
 H351 - Suspected of causing cancer
 H361 - Suspected of damaging fertility or the unborn child
 H373 - May cause damage to organs (eye, nervous system, testis) through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
 P202 - Do not handle until all safety precautions have been read and understood
 P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking
 P260 - Do not breathe fumes, gas, mist, spray, vapors
 P280 - Wear protective gloves/protective clothing/eye protection/face protection
 P308+P313 - If exposed or concerned: Get medical advice/attention
 P314 - Get medical advice/attention if you feel unwell
 P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely
 P381 - Eliminate all ignition sources if safe to do so
 P403 - Store in a well-ventilated place
 P405 - Store locked up

Chloromethane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P410+P403 - Protect from sunlight. Store in a well-ventilated place
P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Substance type : Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
Chloromethane (Main constituent)	(CAS No) 74-87-3	<= 100	Flam. Gas 1, H220 Liquefied gas, H280 Carc. 2, H351 Repr. 2, H361 STOT RE 2, H373

Full text of H-phrases: see section 16

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.
First-aid measures after skin contact	: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Immediately flush eyes thoroughly with water for at least 15 minutes. Get immediate medical advice/attention.
First-aid measures after ingestion	: Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Contact with the liquid may cause cold burns/frostbite.
Symptoms/injuries after eye contact	: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Thermal decomposition generates: Carbon oxides. Hydrogen chloride.
Explosion hazard	: Contains gas under pressure; may explode if heated. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

Firefighting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
Protection during firefighting	: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

Chloromethane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.
- 6.1.1. For non-emergency personnel**
- Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.
- 6.1.2. For emergency responders**
- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Stop leak if safe to do so.
- Methods for cleaning up : Ventilate area.
- Other information : For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care because residual vapors are flammable. Close valve after each use and when empty.
- Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.
- Safe handling of the gas receptacle : Securely chain cylinders when in use and protect against physical damage.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use. Moisture sensitive. Keep away from ignition sources.
- Incompatible materials : Refer to Section 10 on Incompatible Materials.
- Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Chloromethane (74-87-3)		
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (ppm)	100 ppm
ACGIH	Remark (ACGIH)	CNS impair; liver & kidney dam
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	OSHA PEL (Ceiling) (ppm)	200 ppm
OSHA	Remark (OSHA)	(2) See Table Z-2.

Chloromethane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularly checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released. Gas detectors should be used when toxic gases may be released.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Thermal hazard protection	: Cold insulating gloves.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Colorless gas.
Color	: Colorless
Odor	: slight Sweet
Odor threshold	: No data available
pH	: No data available
Melting point	: -97 °C
Freezing point	: No data available
Boiling point	: -24.2 °C
Flash point	: -10 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: 3796.0 mm Hg (@ 20 °C)
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.915 g/ml (@ 25 °C)
Molecular mass	: 50.49 g/mol
Solubility	: Water: 4 g/l (at 25 °C)
Log Pow	: 0.91 (at 25 °C)
Auto-ignition temperature	: 632 °C
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

Chloromethane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

10.5. Incompatible materials

Strong oxidizing agents. Iron.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Chloromethane (74-87-3)	
LD50 oral rat	1800 mg/kg
LC50 inhalation rat (mg/l)	5300 mg/m ³ (Exposure time: 4 h)

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Suspected of causing cancer.

Chloromethane (74-87-3)	
IARC group	3 - Not classifiable

Reproductive toxicity : Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure) : Not classified
Specific target organ toxicity (repeated exposure) : May cause damage to organs (eye, nervous system, testis) through prolonged or repeated exposure.
Aspiration hazard : Not classified
Symptoms/injuries after inhalation : May cause drowsiness or dizziness.
Symptoms/injuries after skin contact : Contact with the liquid the may cause cold burns/frostbite.
Symptoms/injuries after eye contact : Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

SECTION 12: Ecological information

12.1. Toxicity

Chloromethane (74-87-3)	
LC50 fish 1	550 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Chloromethane (74-87-3)	
Log Pow	0.91 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

Chloromethane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Regional legislation (waste) : U.S. - RCRA (Resource Conservation & Recovery Act) - Basis for Listing - Appendix VII. U.S. - RCRA (Resource Conservation & Recovery Act) - Constituents for Detection Monitoring. U.S. - RCRA (Resource Conservation & Recovery Act) - Hazardous Constituents - Appendix VIII to 40 CFR 261. U.S. - RCRA (Resource Conservation & Recovery Act) - List for Hazardous Constituents. U.S. - RCRA (Resource Conservation & Recovery Act) - Part 268 Appendix III - Halogenated Organic Compounds (HOCs). U.S. - RCRA (Resource Conservation & Recovery Act) - Phase 4 LDR Rule - Universal Treatment Standards. U.S. - RCRA (Resource Conservation & Recovery Act) - TSD Facilities Ground Water Monitoring. U.S. - RCRA (Resource Conservation & Recovery Act) - U Series Wastes - Acutely Toxic Wastes & Other Hazardous Characteristics.
- Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
- Waste disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- Additional information : Recycle the material as far as possible.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

- Transport document description : UN1063 Methyl chloride, 2.1
- UN-No.(DOT) : UN1063
- Proper Shipping Name (DOT) : Methyl chloride
- Transport hazard class(es) (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
- Hazard labels (DOT) : 2.1 - Flammable gas



- DOT Packaging Non Bulk (49 CFR 173.xxx) : 304
- DOT Packaging Bulk (49 CFR 173.xxx) : 314;315
- DOT Special Provisions (49 CFR 172.102) : N86 - UN pressure receptacles made of aluminum alloy are not authorized.
T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 306
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 kg
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 100 kg
- DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.
- DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"
- Emergency Response Guide (ERG) Number : 115
- Other information : No supplementary information available.

TDG

No additional information available

Transport by sea

- UN-No. (IMDG) : 1063
- Proper Shipping Name (IMDG) : METHYL CHLORIDE (REFRIGERANT GAS R 40)
- Class (IMDG) : 2 - Gases

Air transport

- UN-No. (IATA) : 1063

Chloromethane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (IATA) : Methyl chloride
Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

Chloromethane (74-87-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 %

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Chloromethane	CAS No 74-87-3	100%
---------------	----------------	------

15.2. International regulations

CANADA

Chloromethane (74-87-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Chloromethane (74-87-3)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Poisonous and Deleterious Substances Control Law
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican national Inventory of Chemical Substances)

15.3. US State regulations

Chloromethane (74-87-3)

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	Yes
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Yes
State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

SECTION 16: Other information

Chloromethane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

Carc. 2	Carcinogenicity Category 2
Flam. Gas 1	Flammable gases Category 1
Liquefied gas	Gases under pressure Liquefied gas
Repr. 2	Reproductive toxicity Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

NFPA health hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

: 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health

: 0 Minimal Hazard - No significant risk to health
* - Chronic (long-term) health effects may result from repeated overexposure

Flammability

: 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)

Physical

: 3 Serious Hazard - Materials that may form explosive mixtures with water and are capable of detonation or explosive reaction in the presence of a strong initiating source. Materials may polymerize, decompose, self-react, or undergo other chemical change at normal temperature and pressure with moderate risk of explosion

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable for any damage resulting from handling or from contact with the above product.

SAFETY DATA SHEET

Creation Date 13-Sep-2013

Revision Date 24-Dec-2021

Revision Number 7

1. Identification

Product Name	Chromium
Cat No. :	C318-500
CAS No	7440-47-3
Synonyms	Chrome
Recommended Use	Laboratory chemicals.
Uses advised against	Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Emergency Telephone Number	CHEMTREC®, Inside the USA: 800-424-9300 CHEMTREC®, Outside the USA: 001-703-527-3887
-----------------------------------	---

2. Hazard(s) identification

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label Elements

Precautionary Statements

Storage

Store in a well-ventilated place. Keep container tightly closed

Hazards not otherwise classified (HNOC)

None identified

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Chromium	7440-47-3	>95

4. First-aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention immediately if symptoms occur.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Get medical attention if symptoms occur.
Most important symptoms and effects	None reasonably foreseeable.
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	No information available.
Unsuitable Extinguishing Media	Carbon dioxide (CO ₂)
Flash Point	No information available
Method -	No information available
Autoignition Temperature	No information available
Explosion Limits	
Upper	No data available
Lower	No data available
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Dust can form an explosive mixture with air. Do not allow run-off from fire-fighting to enter drains or water courses. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition. Fine dust dispersed in air may ignite.

Hazardous Combustion Products

Chromium oxide.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health
2

Flammability
2

Instability
1

Physical hazards
N/A

6. Accidental release measures

Personal Precautions	Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust
-----------------------------	--

Environmental Precautions formation.
Should not be released into the environment. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Up Sweep up and shovel into suitable containers for disposal. Avoid dust formation.

7. Handling and storage

Handling Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Avoid contact with skin, eyes or clothing. Avoid dust formation.

Storage. Keep containers tightly closed in a dry, cool and well-ventilated place. Store under an inert atmosphere. Incompatible Materials. Strong oxidizing agents. Strong acids.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Chromium	TWA: 0.5 mg/m ³	(Vacated) TWA: 1 mg/m ³ TWA: 1 mg/m ³	IDLH: 250 mg/m ³ TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Solid
Appearance	Silver
Odor	Odorless
Odor Threshold	No information available
pH	No information available
Melting Point/Range	1857 °C / 3374.6 °F
Boiling Point/Range	2642 °C / 4787.6 °F
Flash Point	No information available
Evaporation Rate	Not applicable
Flammability (solid,gas)	No information available
Flammability or explosive limits	
Upper	No data available
Lower	No data available

Vapor Pressure	No information available
Vapor Density	Not applicable
Specific Gravity	No information available
Solubility	Insoluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	No information available
Decomposition Temperature	No information available
Viscosity	Not applicable
Molecular Formula	Cr
Molecular Weight	52.00

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Sensitive to air.
Conditions to Avoid	Incompatible products. Excess heat. Avoid dust formation.
Incompatible Materials	Strong oxidizing agents, Strong acids
Hazardous Decomposition Products	Chromium oxide
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information	No acute toxicity information is available for this product
Component Information	
Toxicologically Synergistic Products	No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	No information available
Sensitization	No information available
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Chromium	7440-47-3	Not listed	Not listed	Not listed	Not listed	Not listed

Mutagenic Effects	No information available
Reproductive Effects	No information available.
Developmental Effects	No information available.
Teratogenicity	No information available.
STOT - single exposure	None known
STOT - repeated exposure	None known
Aspiration hazard	No information available
Symptoms / effects, both acute and delayed	No information available

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Do not empty into drains.

Persistence and Degradability Insoluble in water May persist

Bioaccumulation/ Accumulation No information available.

Mobility Is not likely mobile in the environment due its low water solubility.

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT Not regulated

TDG Not regulated

IATA Not regulated

IMDG/IMO Not regulated

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Chromium	7440-47-3	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Chromium	7440-47-3	X	-	231-157-5	X	X		X	X	KE-05970

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations

SARA 313

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Chromium	7440-47-3	>95	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Chromium	-	-	X	X

Clean Air Act

OSHA - Occupational Safety and Health Administration Not applicable

CERCLA Not applicable

Component	Hazardous Substances RQs	CERCLA EHS RQs
Chromium	5000 lb 10 lb	-

California Proposition 65 This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Chromium	X	X	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
 DOT Marine Pollutant N
 DOT Severe Marine Pollutant N

U.S. Department of Homeland Security This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Chromium	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Chromium	7440-47-3	Listed	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Chromium	7440-47-3	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By	Regulatory Affairs Thermo Fisher Scientific Email: EMSDS.RA@thermofisher.com
Creation Date	13-Sep-2013
Revision Date	24-Dec-2021
Print Date	24-Dec-2021
Revision Summary	This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS



Safety Data Sheet

Revision Date: 04/24/18

www.restek.com

2 Letter ISO country code/language code: US/EN

1. IDENTIFICATION

Catalog Number / Product Name:	31275 / Chrysene Standard
Company:	Restek Corporation
Address:	110 Benner Circle Bellefonte, Pa. 16823
Phone#:	814-353-1300
Fax#:	814-353-1309
Emergency#:	800-424-9300 (CHEMTREC) 703-527-3887 (Outside the US)
Email:	www.restek.com
Revision Number:	9
Intended use:	For Laboratory use only

2. HAZARD(S) IDENTIFICATION

Emergency Overview:

GHS Hazard
Symbols:



GHS Classification: Carcinogenicity Category 1B
Flammable Liquid Category 2
Serious Eye Damage/Eye Irritation Category 2
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

GHS Signal Word: Danger

GHS Hazard: Highly flammable liquid and vapour.
Causes serious eye irritation.
May cause drowsiness or dizziness.
May cause cancer.

GHS Precautions:

Safety Precautions: Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilation and lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Wash hands and skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

First Aid Measures: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Call a POISON CENTER or doctor/physician if you feel unwell.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use extinguishing media in section 5 for extinction.

Storage: Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal: Dispose of contents/container according to section 13 of the SDS.

Single Exposure Target Organs: Specific target organ toxicity - Single exposure - STOT SE 3: H336 May cause drowsiness or dizziness.

Repeated Exposure Target Organs: No data available

3. COMPOSITION / INFORMATION ON INGREDIENT

Chemical Name	CAS #	EINEC #	% Composition
Acetone	67-64-1	200-662-2	99.9
chrysene	218-01-9	205-923-4	0.1

4. FIRST-AID MEASURES

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately

Eyes: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

Skin Contact: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

Ingestion: Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this SDS.

5. FIRE- FIGHTING MEASURES

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and keep exposed material from being damaged by fire. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

Fire and/or Explosion Hazards: Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a Class B fire. Vapors are heavier than air and may travel to a source of ignition and flash back

Fire Fighting Methods and Protection: Do not enter fire area without proper protection including self-contained toxic breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

Hazardous Combustion Products: Carbon dioxide, Carbon monoxide

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment: Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods for Clean-up: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal

evaluation.

7. HANDLING AND STORAGE

Handling Technical Measures and Precautions:	Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Use spark-proof tools and explosion-proof equipment
Storage Technical Measures and Conditions:	Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Keep away from sources of ignition

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

United States: Chemical Name	CAS No.	IDLH	ACGIH STEL	ACGIH TLV-TWA	OSHA Exposure Limit
Acetone	67-64-1	2500 ppm IDLH (10% LEL)	750 ppm STEL; 1782 mg/m3 STEL	500 ppm TWA; 1188 mg/m3 TWA	1000 ppm TWA; 2400 mg/m3 TWA
Personal Protection:					
Engineering Measures:		Local exhaust ventilation is recommended when generating excessive levels of vapours from handling or thermal processing.			
Respiratory Protection:		No respiratory protection required under normal conditions of use. Provide general room exhaust ventilation if symptoms of overexposure occur as explained Section 3. A respirator is not normally required.			
Eye Protection:		Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.			
Skin Protection:		Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work			
Medical Conditions Aggravated By Exposure:		Respiratory disease including asthma and bronchitis			

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance, color:	Depends upon product selection
Odor:	Strong
Physical State:	No data available
pH:	Not applicable
Vapor Pressure:	No data available
Vapor Density:	2.0 (air = 1)
Boiling Point (°C):	56.05 °C at 1013.25 hPa
Melting Point (°C):	-95.4 °C Melting Point
Flash Point (°F):	39
Flammability:	Highly Flammable
Upper Flammable/Explosive Limit, % in air:	No data available
Lower Flammable/Explosive Limit, % in air:	No data available
Autoignition Temperature (°C):	465 deg C
Decomposition Temperature (°C):	No data available
Specific Gravity:	0.7845 g/cm3 at 25 °C
Evaporation Rate:	No data available
Odor Threshold:	ND
Solubility:	Complete; 100%
Partition Coefficient: n-octanol in water:	No data available
VOC % by weight:	0
Molecular Weight:	58.08

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	None known.
Materials to Avoid / Chemical Incompatibility:	Strong oxidizing agents Strong acids
Hazardous Decomposition Products:	Carbon dioxide Carbon monoxide

11. TOXICOLOGICAL INFORMATION

Routes of Entry:	Inhalation, Skin Contact, Eye Contact, Ingestion
Target Organs Potentially Affected By Exposure:	Eyes, Central nervous system stimulation, Respiratory Tract, Skin

Chemical Interactions That Change Toxicity: None Known

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation: Can cause minor respiratory irritation, dizziness, weakness, fatigue, nausea, and headache.
Skin Contact: Can cause minor skin irritation, defatting, and dermatitis.
Eye Contact: Can cause minor irritation, tearing and reddening.
Ingestion Irritation: May be harmful if swallowed.
Ingestion Toxicity: Harmful if swallowed. May cause systemic poisoning.

Long-Term (Chronic) Health Effects:

Carcinogenicity: Contains a probable or known human carcinogen.
Reproductive and Developmental Toxicity: No data available to indicate product or any components present at greater than 0.1% may cause birth defects.
Inhalation: Upon prolonged and/or repeated exposure, can cause minor respiratory irritation, dizziness, weakness, fatigue, nausea, and headache.
Skin Contact: Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and dermatitis.

Component Toxicological Data:

NIOSH:

Chemical Name	CAS No.	LD50/LC50
Acetone	67-64-1	Dermal LD50 Rabbit >15700 mg/kg; Inhalation LC50 Rat 50100 mg/m3 8 h; Oral LD50 Rat 5800 mg/kg

Component Carcinogenic Data:

OSHA:

Chemical Name	CAS No.
No data available	

ACGIH:

Chemical Name	CAS No.	
Acetone	67-64-1	A4 - Not Classifiable as a Human Carcinogen

NIOSH:

Chemical Name	CAS No.
No data available	

NTP:

Chemical Name	CAS No.
No data available	

IARC:

Chemical Name	CAS No.	Group No.
Monograph 92 [2010]; Supplement 7 [1987]; Monograph 32 [1983]	218-01-9	Group 2B

12. ECOLOGICAL INFORMATION

Overview:	This material is not expected to be harmful to the ecology.
Mobility:	No data
Persistence:	No data
Bioaccumulation:	No data
Degradability:	No data
Ecological Toxicity Data:	No data available

13. DISPOSAL CONSIDERATIONS

Waste Description of Spent Product:	Spent or discarded material is a hazardous waste. Mixing spent or discarded material with other materials may render the mixture hazardous. Perform a hazardous waste determination on mixtures.
Disposal Methods:	Dispose of by incineration following Federal, State, Local, or Provincial regulations.
Waste Disposal of Packaging:	Comply with all Local, State, Federal, and Provincial

14. TRANSPORTATION INFORMATION

United States:
DOT Proper Shipping Name: Acetone
UN Number: UN1090
Hazard Class: 3
Packing Group: II

International:
IATA Proper Shipping Name: Acetone
UN Number: UN1090
Hazard Class: 3
Packing Group: II

Marine Pollutant: No

Chemical Name	CAS#	Marine Pollutant	Severe Marine Pollutant
No data available			

15. REGULATORY INFORMATION

United States:

Chemical Name	CAS#	CERCLA	SARA 313	SARA EHS 313	TSCA
Acetone	67-64-1	X	-	-	X

The following chemicals are listed on CA Prop 65:

Chemical Name	CAS #	Regulation
Chrysene	218-01-9	Prop 65 Cancer

State Right To Know Listing:

Chemical Name	CAS#	New Jersey	Massachusetts	Pennsylvania	California
Acetone	67-64-1	X	X	X	X
chrysene	218-01-9	X	X	X	X

16. OTHER INFORMATION

Prior Version Date: 01/06/17

Other Information: Any changes to the SDS compared to previous versions are marked by a vertical line in front of the concerned paragraph.

References: No data available

Disclaimer: Restek Corporation provides the descriptions, data and information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. It is provided for your guidance only. Because many factors may affect processing or application/use, Restek Corporation recommends you perform an assessment to determine the suitability of a product for your particular purpose prior to use. No warranties of any kind, either expressed or implied, including fitness for a particular purpose, are made regarding products described, data or information set forth. In no case shall the descriptions, information, or data provided be considered a part of our terms and conditions of sale. Further, the descriptions, data and information furnished hereunder are given gratis. No obligation or liability for the description, data and information given are assumed. All such being given and accepted at your risk.

SAFETY DATA SHEET

Creation Date 22-Sep-2009

Revision Date 24-Dec-2021

Revision Number 4

1. Identification

Product Name cis-1,2-Dichloroethylene

Cat No. : AC113380000; AC113380025; AC113380100; AC113380500

Synonyms cis-Acetylene dichloride.

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Acute oral toxicity	Category 4
Acute Inhalation Toxicity - Vapors	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system.	

Label Elements

Signal Word
Danger

Hazard Statements
Highly flammable liquid and vapor
Harmful if swallowed

Harmful if inhaled
Causes serious eye irritation
Causes skin irritation
May cause respiratory irritation

**Precautionary Statements****Prevention**

Wear protective gloves/protective clothing/eye protection/face protection
Use only outdoors or in a well-ventilated area
Avoid breathing dust/fume/gas/mist/vapors/spray
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Take precautionary measures against static discharge
Do not eat, drink or smoke when using this product

Response

Call a POISON CENTER or doctor/physician if you feel unwell

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell

Skin

IF ON SKIN: Wash with plenty of soap and water
Take off contaminated clothing and wash before reuse
If skin irritation occurs: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

Ingestion

Rinse mouth

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Fire

Explosion risk in case of fire
Fight fire with normal precautions from a reasonable distance
Evacuate area

Storage

Store in a well-ventilated place. Keep cool
Store in a closed container
Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None identified

3. Composition/Information on Ingredients

Component	CAS No	Weight %
cis-1,2-Dichloroethylene	156-59-2	97

4. First-aid measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.
Inhalation	Remove to fresh air. Get medical attention. If not breathing, give artificial respiration.
Ingestion	Do NOT induce vomiting. Get medical attention.
Most important symptoms and effects	Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Water spray. Carbon dioxide (CO ₂). Dry chemical. Water mist may be used to cool closed containers. Chemical foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	No information available
Flash Point	6 °C / 42.8 °F
Method -	No information available
Autoignition Temperature	440 °C / 824 °F
Explosion Limits	
Upper	12.80%
Lower	9.70%
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Flammable. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrogen chloride gas.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health
2

Flammability
3

Instability
0

Physical hazards
N/A

6. Accidental release measures

Personal Precautions	Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing.
Environmental Precautions	See Section 12 for additional Ecological Information. Do not flush into surface water or sanitary sewer system.
Methods for Containment and Clean Up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling	Ensure adequate ventilation. Wear personal protective equipment/face protection. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. Avoid contact with skin, eyes or clothing. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.
Storage.	Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Keep away from heat, sparks and flame. Flammables area. Keep container tightly closed in a dry and well-ventilated place. Incompatible Materials. Bases.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
cis-1,2-Dichloroethylene	TWA: 200 ppm			TWA: 200 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Engineering Measures	Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location.
-----------------------------	--

Personal Protective Equipment

Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	No protective equipment is needed under normal use conditions.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Colorless
Odor	aromatic
Odor Threshold	No information available
pH	No information available
Melting Point/Range	-80 °C / -112 °F
Boiling Point/Range	60 °C / 140 °F @ 760 mmHg
Flash Point	6 °C / 42.8 °F
Evaporation Rate	No information available
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	12.80%
Lower	9.70%
Vapor Pressure	201 mmHg @ 25 °C
Vapor Density	3.34 (Air = 1.0)
Specific Gravity	1.280
Solubility	No information available
Partition coefficient; n-octanol/water	No data available

Autoignition Temperature	440 °C / 824 °F
Decomposition Temperature	No information available
Viscosity	No information available
Molecular Formula	C2 H2 Cl2
Molecular Weight	96.94

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Keep away from open flames, hot surfaces and sources of ignition. Exposure to air. Exposure to light. Incompatible products. Exposure to moist air or water.
Incompatible Materials	Bases
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂), Hydrogen chloride gas
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Component Information

Toxicologically Synergistic Products	No information available
--------------------------------------	--------------------------

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	Irritating to eyes, respiratory system and skin
Sensitization	No information available
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
cis-1,2-Dichloroethylene	156-59-2	Not listed	Not listed	Not listed	Not listed	Not listed

Mutagenic Effects	No information available
Reproductive Effects	No information available.
Developmental Effects	No information available.
Teratogenicity	No information available.
STOT - single exposure	Respiratory system
STOT - repeated exposure	None known
Aspiration hazard	No information available
Symptoms / effects, both acute and delayed	Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Endocrine Disruptor Information	No information available
Other Adverse Effects	The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Do not empty into drains. Do not flush into surface water or sanitary sewer system. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
cis-1,2-Dichloroethylene	Not listed	Not listed	EC50 = 721 mg/L 5 min EC50 = 905 mg/L 30 min	Not listed

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN1150
 Proper Shipping Name 1,2-DICHLOROETHYLENE
 Hazard Class 3
 Packing Group II

TDG

UN-No UN1150
 Proper Shipping Name 1,2-DICHLOROETHYLENE
 Hazard Class 3
 Packing Group II

IATA

UN-No UN1150
 Proper Shipping Name 1,2-DICHLOROETHYLENE
 Hazard Class 3
 Packing Group II

IMDG/IMO

UN-No UN1150
 Proper Shipping Name 1,2-DICHLOROETHYLENE
 Hazard Class 3
 Packing Group II

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
cis-1,2-Dichloroethylene	156-59-2	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
cis-1,2-Dichloroethylene	156-59-2	-	X	205-859-7	-	X	X	X	X	KE-10124

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations

SARA 313	Not applicable
SARA 311/312 Hazard Categories	See section 2 for more information
CWA (Clean Water Act)	Not applicable
Clean Air Act	Not applicable
OSHA - Occupational Safety and Health Administration	Not applicable
CERCLA	

California Proposition 65 This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
cis-1,2-Dichloroethylene	X	-	X	-	-

U.S. Department of Transportation

Reportable Quantity (RQ):	N
DOT Marine Pollutant	N
DOT Severe Marine Pollutant	N

U.S. Department of Homeland Security This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

Authorisation/Restrictions according to EU REACH**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
cis-1,2-Dichloroethylene	156-59-2	Not applicable	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
cis-1,2-Dichloroethylene	156-59-2	Not applicable	Not applicable	Not applicable	Annex I - Y45

16. Other information

Prepared By	Regulatory Affairs Thermo Fisher Scientific Email: EMSDS.RA@thermofisher.com
Creation Date	22-Sep-2009
Revision Date	24-Dec-2021
Print Date	24-Dec-2021
Revision Summary	This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Revision Date 23-Jan-2018

Revision Number 3

1. Identification

Product Name Dibenz[a,h]anthracene, 99% (UV-Vis)
Cat No. : AC406430010; AC406432500
Synonyms 1,2:5,6-Dibenz(a)anthracene.
Recommended Use Laboratory chemicals.
Uses advised against Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

Fisher Scientific
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity

Category 1B

Label Elements

Signal Word

Danger

Hazard Statements

May cause cancer



Precautionary Statements

Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Response

IF exposed or concerned: Get medical attention/advice

Storage

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Very toxic to aquatic life with long lasting effects

WARNING. Cancer - <https://www.p65warnings.ca.gov/>.

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Dibenzo(a,h)anthracene	53-70-3	99

4. First-aid measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes.
Inhalation	Move to fresh air.
Ingestion	Do not induce vomiting.
Most important symptoms and effects	No information available.
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Unsuitable Extinguishing Media	No information available
Flash Point	
Method -	No information available
Autoignition Temperature	No information available
Explosion Limits	
Upper	No data available
Lower	No data available
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

None known

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
1	1	0	N/A

6. Accidental release measures

Personal Precautions	Ensure adequate ventilation. Use personal protective equipment.
Environmental Precautions	See Section 12 for additional ecological information. Avoid release to the environment. Collect spillage.

Methods for Containment and Clean Up No information available.

7. Handling and storage

Handling	Ensure adequate ventilation.
Storage	Keep containers tightly closed in a dry, cool and well-ventilated place.

8. Exposure controls / personal protection

Exposure Guidelines	This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.
----------------------------	---

Engineering Measures	Ensure adequate ventilation, especially in confined areas.
-----------------------------	--

Personal Protective Equipment

Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Solid
Appearance	Off-white
Odor	No information available
Odor Threshold	No information available
pH	
Melting Point/Range	265 °C
Boiling Point/Range	
Flash Point	
Evaporation Rate	No information available
Flammability (solid,gas)	No information available
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	No information available
Vapor Density	No information available
Specific Gravity	No information available
Solubility	No information available
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	No information available
Decomposition Temperature	No information available
Viscosity	No information available
Molecular Formula	C ₂₂ H ₁₄
Molecular Weight	278.34

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products.
Incompatible Materials	Strong oxidizing agents
Hazardous Decomposition Products	None under normal use conditions
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Component Information Toxicologically Synergistic Products

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	No information available
Sensitization	No information available
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Dibenzo(a,h)anthracene	53-70-3	Group 2A	Reasonably Anticipated	Not listed	X	Not listed

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure None known

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed No information available

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Do not empty into drains.

Persistence and Degradability No information available

Bioaccumulation/ Accumulation No information available.

Mobility No information available.

Component	log Pow
Dibenzo(a,h)anthracene	6.50

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Dibenzo(a,h)anthracene - 53-70-3	U063	-

14. Transport information

DOT Not regulated
TDG Not regulated
IATA Not regulated
IMDG/IMO Not regulated

15. Regulatory information

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Dibenzo(a,h)anthracene	X	-	X	200-181-8	-		-	-	-	X	-

Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Dibenzo(a,h)anthracene	53-70-3	99	0.1

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Dibenzo(a,h)anthracene	-	-	-	X

Clean Air Act Not applicable

OSHA Occupational Safety and Health Administration
Not applicable

CERCLA Not applicable

Component	Hazardous Substances RQs	CERCLA EHS RQs
Dibenzo(a,h)anthracene	1 lb	-

California Proposition 65 This product does not contain any Proposition 65 chemicals

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Dibenzo(a,h)anthracene	53-70-3	Carcinogen	0.2 µg/day	Carcinogen

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Dibenzo(a,h)anthracene	X	X	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

16. Other information

Prepared By Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Revision Date 23-Jan-2018

Print Date 23-Jan-2018

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Version 6.2
Revision Date 10/05/2020
Print Date 03/19/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name : Dibenzofuran

Product Number : 236373
Brand : Aldrich
CAS-No. : 132-64-9

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Not a hazardous substance or mixture.

2.2 GHS Label elements, including precautionary statements

Not a hazardous substance or mixture.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none**SECTION 3: Composition/information on ingredients****3.1 Substances**

Synonyms : Diphenylene oxide

Formula : C₁₂H₈O

Molecular weight : 168.19 g/mol
CAS-No. : 132-64-9
EC-No. : 205-071-3

No components need to be disclosed according to the applicable regulations.

SECTION 4: First aid measures

4.1 Description of first-aid measures

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration.

In case of skin contact

Wash off with soap and plenty of water.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid breathing vapors, mist or gas.

For personal protection see section 8.

6.2 Environmental precautions

No special environmental precautions required.

6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Storage class (TRGS 510): 11: Combustible Solids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Appropriate engineering controls

General industrial hygiene practice.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatrill® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatrill® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Respiratory protection is not required. Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN 143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

No special environmental precautions required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|---|---|
| a) Appearance | Form: powder, finecrystalline
Color: white, beige |
| b) Odor | No data available |
| c) Odor Threshold | No data available |
| d) pH | No data available |
| e) Melting point/freezing point | Melting point/range: 80 - 82 °C (176 - 180 °F) - lit. |
| f) Initial boiling point and boiling range | 154 - 155 °C 309 - 311 °F at 27 hPa - lit. |
| g) Flash point | 130 °C (266 °F) - closed cup |
| h) Evaporation rate | No data available |
| i) Flammability (solid, gas) | No data available |
| j) Upper/lower flammability or explosive limits | No data available |
| k) Vapor pressure | No data available |
| l) Vapor density | No data available |
| m) Relative density | 1.3 g/cm ³ at 20 °C (68 °F) |
| n) Water solubility | insoluble |
| o) Partition coefficient: n-octanol/water | log Pow: 4.12 - (Lit.), Potential bioaccumulation |
| p) Autoignition temperature | No data available |

- | | |
|------------------------------|-------------------|
| q) Decomposition temperature | No data available |
| r) Viscosity | No data available |
| s) Explosive properties | No data available |
| t) Oxidizing properties | No data available |

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

No data available

Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

- NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: Not available

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Hazardous properties cannot be excluded.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No ecological problems are to be expected when the product is handled and used with due care and attention.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information**DOT (US)**

UN number: 3077 Class: 9

Packing group: III

Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (Dibenzofuran)

Reportable Quantity (RQ): 100 lbs

Poison Inhalation Hazard: No

IMDG

Not dangerous goods

IATA

Not dangerous goods

SECTION 15: Regulatory information**SARA 302 Components**

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
Dibenzofuran	132-64-9	2007-07-01

SARA 311/312 Hazards

No SARA Hazards

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Dibenzofuran	132-64-9	2007-07-01

SECTION 16: Other information**Further information**

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See

www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.2

Revision Date: 10/05/2020

Print Date: 03/19/2022


SAFETY DATA SHEET

Halocarbon R-12 (Dichlorodifluoromethane)

Section 1. Identification

GHS product identifier	: Halocarbon R-12 (Dichlorodifluoromethane)
Chemical name	: dichlorodifluoromethane
Other means of identification	: ASPEN R-12, Methane, dichlorodifluoro-; Refrigerant 12; Propellant 12; Halon 122; Genetron 12; Freon 12; Fluorocarbon 12; Difluorodichloromethane; DICHLORODIFLUOROMETHANE (FC 12); CFC-12
Product type	: Gas.
Product use	: Synthetic/Analytical chemistry.
Synonym	: ASPEN R-12, Methane, dichlorodifluoro-; Refrigerant 12; Propellant 12; Halon 122; Genetron 12; Freon 12; Fluorocarbon 12; Difluorodichloromethane; DICHLORODIFLUOROMETHANE (FC 12); CFC-12
SDS #	: 001018
Supplier's details	: Airgas USA, LLC and its affiliates 259 North Radnor-Chester Road Suite 100 Radnor, PA 19087-5283 1-610-687-5253
24-hour telephone	: 1-866-734-3438

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: GASES UNDER PRESSURE - Liquefied gas HAZARDOUS TO THE OZONE LAYER - Category 1
<u>GHS label elements</u>	
Hazard pictograms	: 
Signal word	: Warning
Hazard statements	: Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation. Harms public health and the environment by destroying ozone in the upper atmosphere.
<u>Precautionary statements</u>	
General	: Read and follow all Safety Data Sheets (SDS'S) before use. Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use a back flow preventative device in the piping. Use only equipment of compatible materials of construction. Always keep container in upright position.
Prevention	: Use and store only outdoors or in a well ventilated place.
Response	: Not applicable.
Storage	: Protect from sunlight. Store in a well-ventilated place.
Disposal	: Refer to manufacturer or supplier for information on recovery or recycling.
Hazards not otherwise classified	: In addition to any other important health or physical hazards, this product may displace oxygen and cause rapid suffocation.

Section 3. Composition/information on ingredients

Substance/mixture	: Substance
Chemical name	: dichlorodifluoromethane
Other means of identification	: ASPEN R-12, Methane, dichlorodifluoro-; Refrigerant 12; Propellant 12; Halon 122; Genetron 12; Freon 12; Fluorocarbon 12; Difluorodichloromethane; DICHLORODIFLUOROMETHANE (FC 12); CFC-12
Product code	: 001018

CAS number/other identifiers

CAS number : 75-71-8

Ingredient name	%	CAS number
Methane, dichlorodifluoro-	100	75-71-8

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: As this product is a gas, refer to the inhalation section.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Frostbite	: Try to warm up the frozen tissues and seek medical attention.
Ingestion	: As this product is a gas, refer to the inhalation section.

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
---------------------------	---

Section 4. First aid measures

- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : Contains gas under pressure. In a fire or if heated, a pressure increase will occur and the container may burst or explode.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
halogenated compounds
carbonyl halides

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid breathing gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

- Small spill** : Immediately contact emergency personnel. Stop leak if without risk.
- Large spill** : Immediately contact emergency personnel. Stop leak if without risk. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Contains gas under pressure. Avoid breathing gas. Do not puncture or incinerate container. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement.
- Avoid release to the environment. Refer to special instructions/safety data sheet. Avoid contact with eyes, skin and clothing. Empty containers retain product residue and can be hazardous.

- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52 °C (125 °F). Keep container tightly closed and sealed until ready for use. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Methane, dichlorodifluoro-	ACGIH TLV (United States, 3/2017). TWA: 4950 mg/m ³ 8 hours. TWA: 1000 ppm 8 hours. NIOSH REL (United States, 10/2016). TWA: 4950 mg/m ³ 10 hours. TWA: 1000 ppm 10 hours. OSHA PEL (United States, 6/2016). TWA: 4950 mg/m ³ 8 hours. TWA: 1000 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 4950 mg/m ³ 8 hours. TWA: 1000 ppm 8 hours.

- Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 8. Exposure controls/personal protection

- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Gas. [Compressed gas.]
- Color** : Colorless.
- Odor** : Characteristic.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point** : -158°C (-252.4°F)
- Boiling point** : -29.8°C (-21.6°F)
- Critical temperature** : 111.85°C (233.3°F)
- Flash point** : [Product does not sustain combustion.]
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.
- Vapor pressure** : 84.9 (psia)
- Vapor density** : 4.2 (Air = 1)
- Specific Volume (ft³/lb)** : 3.1746
- Gas Density (lb/ft³)** : 0.315
- Relative density** : Not applicable.
- Solubility** : Not available.
- Solubility in water** : 0.3 g/l
- Partition coefficient: n-octanol/water** : 2.16
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Not applicable.
- Flow time (ISO 2431)** : Not available.
- Molecular weight** : 120.91 g/mole

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hazardous polymerization	: Under normal conditions of storage and use, hazardous polymerization will not occur.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.

Section 11. Toxicological information

Ingestion : As this product is a gas, refer to the inhalation section.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Methane, dichlorodifluoro-	2.16	6.17	low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations






Disposal methods

- : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Empty Airgas-owned pressure vessels should be returned to Airgas. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
Dichlorodifluoromethane; Methane, dichlorodifluoro-	75-71-8	Listed	U075

Section 14. Transport information

	DOT	TDG	Mexico	IMDG	IATA
UN number	UN1028	UN1028	UN1028	UN1028	UN1028
UN proper shipping name	DICHLORODIFLUOROMETHANE OR REFRIGERANT GAS R 12	DICHLORODIFLUOROMETHANE; OR REFRIGERANT GAS R 12	DICHLORODIFLUOROMETHANE OR REFRIGERANT GAS R 12	DICHLORODIFLUOROMETHANE (REFRIGERANT GAS R 12)	DICHLORODIFLUOROMETHANE
Transport hazard class(es)	2.2 	2.2 	2.2 	2.2 	2.2 
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.

“Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product.”

Additional information

DOT Classification

- : **Reportable quantity** 5000 lbs / 2270 kg. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.
Limited quantity Yes.
Quantity limitation Passenger aircraft/rail: 75 kg. Cargo aircraft: 150 kg.
Special provisions T50

TDG Classification

- : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2).
Explosive Limit and Limited Quantity Index 0.125
Passenger Carrying Road or Rail Index 75

IATA

- : **Quantity limitation** Passenger and Cargo Aircraft: 75 kg. Cargo Aircraft Only: 150 kg.

Special precautions for user

- : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 14. Transport information

Transport in bulk according to Annex II of MARPOL and the IBC Code : Not available.

Section 15. Regulatory information

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Not listed

Clean Air Act Section 602 Class I Substances : Listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Refer to Section 2: Hazards Identification of this SDS for classification of substance.

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	dichlorodifluoromethane	75-71-8	100
Supplier notification	dichlorodifluoromethane	75-71-8	100

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : This material is listed.

New York : This material is listed.

New Jersey : This material is listed.

Pennsylvania : This material is listed.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Ingredient name	Status
CFC 11	Annex A, Group I

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Section 15. Regulatory information

Not listed.

Inventory list

Australia	: This material is listed or exempted.
Canada	: This material is listed or exempted.
China	: This material is listed or exempted.
Europe	: This material is listed or exempted.
Japan	: Japan inventory (ENCS) : This material is listed or exempted. Japan inventory (ISHL) : Not determined.
Malaysia	: Not determined.
New Zealand	: This material is listed or exempted.
Philippines	: This material is listed or exempted.
Republic of Korea	: This material is listed or exempted.
Taiwan	: This material is listed or exempted.
Thailand	: Not determined.
Turkey	: Not determined.
United States	: This material is listed or exempted.
Viet Nam	: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	1
Flammability		0
Physical hazards		3

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

Classification	Justification
GASES UNDER PRESSURE - Liquefied gas HAZARDOUS TO THE OZONE LAYER - Category 1	Expert judgment On basis of test data

Section 16. Other information

History

Date of printing : 10/18/2018

Date of issue/Date of revision : 10/18/2018

Date of previous issue : 3/18/2018

Version : 2

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations

References : Not available.

Other special considerations : WARNING: Contains (Dichlorodifluorométhane), a substance which harms the public health and environment by destroying ozone in the upper atmosphere.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

SAFETY DATA SHEET

Creation Date 09-Jul-2009

Revision Date 07-Jan-2022

Revision Number 7

1. Identification

Product Name Ethanol, Anhydrous (Histological)

Cat No. : A405-20; A405F-1GAL; A405P-4

Synonyms Grain alcohol, denatured; Ethyl alcohol, denatured; Ethyl hydroxide, denatured.

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Emergency Telephone Number CHEMTREC®, Inside the USA: 800-424-9300
CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 2 Category 3
Target Organs - Central nervous system (CNS), Optic nerve, Respiratory system.	

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor
Causes serious eye irritation
Suspected of causing cancer
Suspected of damaging fertility or the unborn child

May cause damage to organs
May cause drowsiness or dizziness



Precautionary Statements

Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Wear eye/face protection
Do not breathe dust/fume/gas/mist/vapors/spray
Do not eat, drink or smoke when using this product
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting equipment
Use only non-sparking tools
Take precautionary measures against static discharge

Response

IF exposed or concerned: Get medical attention/advice

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up
Store in a well-ventilated place. Keep cool

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Repeated exposure may cause skin dryness or cracking

Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. CANNOT BE MADE NON-POISONOUS.

WARNING. Cancer and Reproductive Harm - <https://www.p65warnings.ca.gov/>.

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Ethyl alcohol	64-17-5	90-95
Methyl alcohol	67-56-1	3-5
Methylisobutyl ketone	108-10-1	1-3
Ethyl acetate	141-78-6	1-2
Solvent naphtha (petroleum), light aliphatic	64742-89-8	1

4. First-aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Ingestion	Clean mouth with water and drink afterwards plenty of water.
Most important symptoms and effects	None reasonably foreseeable. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	Water may be ineffective, Do not use a solid water stream as it may scatter and spread fire
Flash Point	13.9 °C / 57 °F
Method -	Estimated
Autoignition Temperature	362.8 °C / 685 °F
Explosion Limits	
Upper	18.0 vol %
Lower	3.3 vol %
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health
3

Flammability
3

Instability
0

Physical hazards
N/A

6. Accidental release measures

Personal Precautions	Use personal protective equipment as required. Ensure adequate ventilation.
Environmental Precautions	Should not be released into the environment.

Methods for Containment and Clean Up Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

7. Handling and storage

Handling Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation.

Storage. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Incompatible Materials. Strong oxidizing agents. Acids. Acid anhydrides. Acid chlorides. Peroxides. Alkali metals.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Ethyl alcohol	STEL: 1000 ppm	(Vacated) TWA: 1000 ppm (Vacated) TWA: 1900 mg/m ³ TWA: 1000 ppm TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³	STEL: 1000 ppm
Methyl alcohol	TWA: 200 ppm STEL: 250 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 260 mg/m ³ (Vacated) STEL: 250 ppm (Vacated) STEL: 325 mg/m ³ Skin TWA: 200 ppm TWA: 260 mg/m ³	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³	TWA: 200 ppm STEL: 250 ppm
Methylisobutyl ketone	TWA: 20 ppm STEL: 75 ppm	(Vacated) TWA: 50 ppm (Vacated) TWA: 205 mg/m ³ (Vacated) STEL: 75 ppm (Vacated) STEL: 300 mg/m ³ TWA: 100 ppm TWA: 410 mg/m ³	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m ³ STEL: 75 ppm STEL: 300 mg/m ³	TWA: 20 ppm STEL: 75 ppm
Ethyl acetate	TWA: 400 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 1400 mg/m ³ TWA: 400 ppm TWA: 1400 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m ³	TWA: 400 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State Liquid
Appearance Clear

Odor	Alcohol-like
Odor Threshold	No information available
pH	Not applicable
Melting Point/Range	< -90 °C / -130 °F
Boiling Point/Range	77.1 °C / 170.8 °F
Flash Point	13.9 °C / 57 °F
Method -	Estimated
Evaporation Rate	3.6 (Butyl acetate = 1.0)
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	18.0 vol %
Lower	3.3 vol %
Vapor Pressure	48 mmHg
Vapor Density	1.5
Specific Gravity	0.785 - 0.792
Solubility	Soluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	362.8 °C / 685 °F
Decomposition Temperature	No information available
Viscosity	No information available
VOC Content(%)	100

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Strong oxidizing agents, Acids, Acid anhydrides, Acid chlorides, Peroxides, Alkali metals
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂)
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Oral LD50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Dermal LD50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Vapor LC50 Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl alcohol	LD50 = 10470 mg/kg OECD 401 (Rat) 3450 mg/kg (Mouse)	Not listed	LC50 = 117-125 mg/l (4h) OECD 403 (rat) 20000 ppm/10H (rat)
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h
Methylisobutyl ketone	LD50 = 2080 mg/kg (Rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 2000 - 4000 ppm (Rat) 4 h
Ethyl acetate	10,200 mg/kg (Rat)	> 20 mL/kg (Rabbit) > 18000 mg/kg (Rabbit)	58 mg/l (rat; 8 h)
Solvent naphtha (petroleum), light aliphatic	Not listed	LD50 = 3000 mg/kg (Rabbit)	Not listed

Toxicologically Synergistic No information available

Products**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Irritation** Severe eye irritant**Sensitization** No information available**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Ethyl alcohol	64-17-5	Not listed	Known	A3	Not listed	A3
Methyl alcohol	67-56-1	Not listed	Not listed	Not listed	Not listed	Not listed
Methylisobutyl ketone	108-10-1	Group 2B	Not listed	A3	X	A3
Ethyl acetate	141-78-6	Not listed	Not listed	Not listed	Not listed	Not listed
Solvent naphtha (petroleum), light aliphatic	64742-89-8	Not listed	Not listed	Not listed	Not listed	Not listed

*IARC (International Agency for Research on Cancer)**NTP: (National Toxicity Program)**ACGIH: (American Conference of Governmental Industrial Hygienists)**Mexico - Occupational Exposure Limits - Carcinogens**IARC (International Agency for Research on Cancer)**Group 1 - Carcinogenic to Humans**Group 2A - Probably Carcinogenic to Humans**Group 2B - Possibly Carcinogenic to Humans**NTP: (National Toxicity Program)**Known - Known Carcinogen**Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen**A1 - Known Human Carcinogen**A2 - Suspected Human Carcinogen**A3 - Animal Carcinogen**ACGIH: (American Conference of Governmental Industrial Hygienists)**Mexico - Occupational Exposure Limits - Carcinogens**A1 - Confirmed Human Carcinogen**A2 - Suspected Human Carcinogen**A3 - Confirmed Animal Carcinogen**A4 - Not Classifiable as a Human Carcinogen**A5 - Not Suspected as a Human Carcinogen***Mutagenic Effects** Mutagenic effects have occurred in experimental animals.**Reproductive Effects** No information available.**Developmental Effects** No information available.**Teratogenicity** No information available.**STOT - single exposure** Central nervous system (CNS) Optic nerve Respiratory system**STOT - repeated exposure** None known**Aspiration hazard** No information available**Symptoms / effects, both acute and delayed** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting**Endocrine Disruptor Information** No information available**Other Adverse Effects** The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Contains a substance which is: Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl alcohol	EC50 (72h) = 275 mg/l (Chlorella vulgaris)	Fathead minnow (Pimephales promelas)	Photobacterium phosphoreum: EC50 = 34634	EC50 = 9268 mg/L/48h EC50 = 10800 mg/L/24h

		LC50 = 14200 mg/l/96h	mg/L/30 min Photobacterium phosphoreum: EC50 = 35470 mg/L/5 min	
Methyl alcohol	Not listed	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	EC50 > 10000 mg/L 24h
Methylisobutyl ketone	EC50: 400 mg/L/96h	LC50: 496 - 514 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 79.6 mg/L 5 min	EC50: 4280.0 mg/L/24h EC50: 170 mg/L/48h EC50: 4280.0 mg/L/24h
Ethyl acetate	EC50 = 3300 mg/L/48h	Fathead minnow: LC50: 230 mg/l/ 96h Gold orfe: LC50: 270 mg/L/48h	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	EC50 = 717 mg/L/48h
Solvent naphtha (petroleum), light aliphatic	EC50: = 4700 mg/L, 72h (Pseudokirchneriella subcapitata)	Not listed	Not listed	Not listed

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
Ethyl alcohol	-0.32
Methyl alcohol	-0.74
Methylisobutyl ketone	1.19
Ethyl acetate	0.6

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl alcohol - 67-56-1	U154	-
Methylisobutyl ketone - 108-10-1	U161	-
Ethyl acetate - 141-78-6	U112	-

14. Transport information

DOT

UN-No UN1170
 Proper Shipping Name ETHANOL SOLUTION
 Hazard Class 3
 Packing Group II

TDG

UN-No UN1170
 Proper Shipping Name ETHANOL SOLUTION
 Hazard Class 3
 Packing Group II

IATA

UN-No UN1170
 Proper Shipping Name ETHANOL SOLUTION
 Hazard Class 3
 Packing Group II

IMDG/IMO

UN-No UN1170
 Proper Shipping Name ETHANOL SOLUTION
 Hazard Class 3

Packing Group

II

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Ethyl alcohol	64-17-5	X	ACTIVE	-
Methyl alcohol	67-56-1	X	ACTIVE	-
Methylisobutyl ketone	108-10-1	X	ACTIVE	-
Ethyl acetate	141-78-6	X	ACTIVE	-
Solvent naphtha (petroleum), light aliphatic	64742-89-8	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

- - Not Listed

TSCA 12(b) - Notices of Export

Not applicable

International Inventories

Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Ethyl alcohol	64-17-5	X	-	200-578-6	X	X	X	X	X	KE-13217
Methyl alcohol	67-56-1	X	-	200-659-6	X	X	X	X	X	KE-23193
Methylisobutyl ketone	108-10-1	X	-	203-550-1	X	X	X	X	X	KE-24725
Ethyl acetate	141-78-6	X	-	205-500-4	X	X	X	X	X	KE-00047
Solvent naphtha (petroleum), light aliphatic	64742-89-8	X	-	265-192-2	X	-		X	X	KE-31661

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)U.S. Federal Regulations**SARA 313**

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Methyl alcohol	67-56-1	3-5	1.0
Methylisobutyl ketone	108-10-1	1-3	0.1

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)**Clean Air Act**

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	X		-
Methylisobutyl ketone	X		-

OSHA - Occupational Safety and Health Administration

Not applicable

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
Methyl alcohol	5000 lb	-
Methylisobutyl ketone	5000 lb	-

Ethyl acetate	5000 lb	-
---------------	---------	---

California Proposition 65

Ethyl alcohol is only considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage. This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Ethyl alcohol	64-17-5	Development (alcoholic beverages only) Carcinogen	-	Developmental Carcinogen
Methyl alcohol	67-56-1	Developmental	-	Developmental
Methylisobutyl ketone	108-10-1	Carcinogen Developmental	-	Developmental Carcinogen

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Ethyl alcohol	X	X	X	X	X
Methyl alcohol	X	X	X	X	X
Methylisobutyl ketone	X	X	X	X	X
Ethyl acetate	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
 DOT Marine Pollutant N
 DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations**Mexico - Grade**

Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl alcohol	-	Use restricted. See item 69. (see link for restriction details)	-
Methylisobutyl ketone	-	Use restricted. See item 75. (see link for restriction details)	-
Ethyl acetate	-	Use restricted. See item 75. (see link for restriction details)	-
Solvent naphtha (petroleum), light aliphatic	-	Use restricted. See item 28. (see link for restriction details) Use restricted. See item 29. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Ethyl alcohol	64-17-5	Listed	Not applicable	Not applicable	Not applicable
Methyl alcohol	67-56-1	Listed	Not applicable	Not applicable	Not applicable

Methylisobutyl ketone	108-10-1	Listed	Not applicable	Not applicable	Not applicable
Ethyl acetate	141-78-6	Listed	Not applicable	Not applicable	Not applicable
Solvent naphtha (petroleum), light aliphatic	64742-89-8	Listed	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Ethyl alcohol	64-17-5	Not applicable	Not applicable	Not applicable	Annex I - Y42
Methyl alcohol	67-56-1	500 tonne	5000 tonne	Not applicable	Not applicable
Methylisobutyl ketone	108-10-1	Not applicable	Not applicable	Not applicable	Annex I - Y42
Ethyl acetate	141-78-6	Not applicable	Not applicable	Not applicable	Annex I - Y42
Solvent naphtha (petroleum), light aliphatic	64742-89-8	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By

Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Creation Date

09-Jul-2009

Revision Date

07-Jan-2022

Print Date

07-Jan-2022

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Preparation Date: 4/13/2018

Revision Date: 4/13/2018

Revision Number: G1

1. IDENTIFICATION

Product identifier

Product code: E1033
Product Name: ETHYLBENZENE, REAGENT

Other means of identification

Synonyms: Ethyl benzene
 Ethylbenzol
 Etilbenzene (Italian)
 Phenylethane
CAS #: 100-41-4
RTECS # DA0700000
CI#: Not available

Recommended use of the chemical and restrictions on use

Recommended use: Solvent. Chemical intermediate.
Uses advised against No information available

Supplier: Spectrum Chemical Mfg. Corp
 14422 South San Pedro St.
 Gardena, CA 90248
 (310) 516-8000

Order Online At: <https://www.spectrumchemical.com>

Emergency telephone number Chemtrec 1-800-424-9300

Contact Person: Martin LaBenz (West Coast)

Contact Person: Ibad Tirmiz (East Coast)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Considered a dangerous substance or mixture according to the Globally Harmonized System (GHS)

Acute toxicity - Inhalation (Gases)	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 2

Label elements

Product code: E1033

Product name: ETHYLBENZENE,
REAGENT

1 / 14

Danger

Hazard statements

Harmful if inhaled
Causes skin irritation
Causes serious eye irritation
Suspected of causing cancer
May cause respiratory irritation. May cause drowsiness or dizziness
May cause damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Highly flammable liquid and vapor



Hazards not otherwise classified (HNOC)

Not Applicable

Other hazards

May be harmful if swallowed

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/protective clothing/eye protection/face protection
Use only outdoors or in a well-ventilated area
Wash face, hands and any exposed skin thoroughly after handling
Do not breathe dust/fume/gas/mist/vapors/spray
Keep away from heat/sparks/open flames/hot surfaces. — No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/.../equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Precautionary Statements - Response

Call a POISON CENTER or doctor/physician if you feel unwell
In case of fire: Use CO₂, dry chemical, or foam to extinguish.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
If skin irritation occurs: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Ethylbenzene	100-41-4	100

4. FIRST AID MEASURES

First aid measures

- General Advice:** National Capital Poison Center in the United States can provide assistance if you have a poison emergency and need to talk to a poison specialist. Call 1-800-222-1222.
- Skin Contact:** Wash off immediately with soap and plenty of water removing all contaminated clothing and shoes. Get medical attention. If skin irritation persists, call a physician.
- Eye Contact:** Flush eyes with water for 15 minutes. Get medical attention.
- Inhalation:** Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
- Ingestion:** Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Obtain medical attention.

Most important symptoms and effects, both acute and delayed

- Symptoms**
- Causes skin irritation
 - Causes serious eye irritation
 - Irritating to respiratory system
 - Aspiration hazard if swallowed - can enter the lungs and cause damage
 - Aspiration into the lungs may cause chemical pneumonitis
 - May cause digestive (gastrointestinal) tract irritation
 - Abdominal pain
 - May cause nausea and vomiting
 - May affect the blood
 - May affect the liver
 - It may affect the kidneys
 - Central nervous system effects
 - Headache
 - Drowsiness
 - Dizziness
 - Ataxia
 - Irritability
 - Fatigue
 - Weakness
 - Lightheadedness
 - Tremors
 - Insomnia

Indication of any immediate medical attention and special treatment needed

- Notes to Physician:** Treat symptomatically.

Protection of first-aiders

First-Aid Providers: Avoid exposure to blood or body fluids. Wear gloves and other necessary protective clothing. Dispose of contaminated clothing and equipment as bio-hazardous waste.

5. FIRE-FIGHTING MEASURES

Extinguishing Media

- Suitable Extinguishing Media:** Dry chemical. Carbon dioxide (CO₂). Water spray mist or foam.

Unsuitable Extinguishing Media:

Do not use a solid (straight) water stream as it may scatter and spread fire.

Specific hazards arising from the chemical**Hazardous Combustion Products:**

Carbon Monoxide, Carbon Dioxide.

Specific hazards:

Highly flammable. May be ignited by heat, sparks or flames. Vapor may travel considerable distance to source of ignition and flash back. Vapors may form explosive mixtures with air. Most vapors are heavier than air. They will spread along the ground and collect in low or confined areas (sewers, basements, tanks). Container explosion may occur under fire conditions or when heated. Fire may produce irritating, corrosive and/or toxic gases.

Special Protective Actions for Firefighters**Specific Methods:**

Water mist may be used to cool closed containers. For larger fires, use water spray or fog. Cool containers with flooding quantities of water until well after fire is out.

Special Protective Equipment for Firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures****Personal Precautions:**

Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use spark-proof tools and explosion-proof equipment. In case of large spill, water spray or vapor suppressing foam may be used to reduce vapors, but may not prevent ignition in closed spaces.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up**Methods for containment**

Stop leak if you can do it without risk. Absorb spill with inert material (e.g. vermiculite, dry sand or earth). In case of large spill, dike if needed. Dike far ahead of liquid spill for later disposal.

Methods for cleaning up

Use appropriate tools to put the spilled material in a suitable chemical waste disposal container. Use clean non-sparking tools to collect absorbed material. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE**Precautions for safe handling****Technical Measures/Precautions:**

Provide sufficient air exchange and/or exhaust in work rooms. Remove all sources of ignition. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from

incompatible materials.

Safe Handling Advice

Wear personal protective equipment. Use only in well-ventilated areas. Avoid contact with skin, eyes and clothing. Keep away from heat and sources of ignition. Do not breathe vapors or spray mist. Do not ingest. Take precautionary measures against static discharges. When using do not smoke. Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Technical Measures/Storage Conditions:

Keep container tightly closed. Keep in a well-ventilated place. Store at room temperature in the original container. Keep away from heat and sources of ignition. Protect from light. Sensitive to light. Store in light-resistant containers. Store away from incompatible materials. Store in a segregated and approved area.

Incompatible Materials:

Oxidizing agents
chlorates
Nitrates
Peroxides

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

National occupational exposure limits

United States

Components	CAS-No.	OSHA	NIOSH	ACGIH	AIHA WEEL
Ethylbenzene	100-41-4	100 ppm TWA 435 mg/m ³ TWA	100 ppm TWA 435 mg/m ³ TWA 125 ppm STEL 545 mg/m ³ STEL	20 ppm TWA	None

Canada

Components	CAS-No.	Canada - Alberta	Canada - British Columbia	Canada - Ontario	Canada - Quebec
Ethylbenzene	100-41-4	100 ppm TWA 434 mg/m ³ TWA 125 ppm STEL 543 mg/m ³ STEL	20 ppm TWA	None	100 ppm TWAEV 434 mg/m ³ TWAEV 125 ppm STEV 543 mg/m ³ STEV

Australia and Mexico

Components	CAS-No.	Australia	Mexico
Ethylbenzene	100-41-4	125 ppm STEL 543 mg/m ³ STEL 100 ppm TWA 434 mg/m ³ TWA	100 ppm TWA 435 mg/m ³ TWA 125 ppm STEL 545 mg/m ³ STEL

Appropriate engineering controls

Engineering measures to reduce exposure:

Ensure adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors and mist below their respective threshold limit value.

Individual protection measures, such as personal protective equipment

Personal Protective Equipment

Eye protection:	Goggles
Skin and body protection:	Chemical resistant apron Long sleeved clothing Gloves
Respiratory protection:	Vapor respirator. Be sure to use an approved/certified respirator or equivalent.
Hygiene measures:	Avoid contact with skin, eyes and clothing. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid	Appearance: No information available.	Color: Colorless.
Odor: Aromatic. Sweet. Gasoline-like.	Taste No information available.	Formula: C ₈ H ₁₀
Molecular/Formula weight: 106.16	Flammability: Highly flammable	Flash point (°C): -11
Flashpoint (°C/°F): 15-21 °C/59-70 °F	Flash Point Tested according to: Closed cup	Autoignition Temperature (°C/°F): 432 °C/809.6 °F
Lower Explosion Limit (%): 0.8%	Upper Explosion Limit (%): 6.7-7%	Melting point/range(°C/°F): -94.9 °C/-138.8 °F
Decomposition temperature(°C/°F): No information available	Boiling point/range(°C/°F): 136 °C/276.8 °F	Bulk density: No information available
Density (g/cm³): No information available	Specific gravity: 0.8626-0.867	pH: No information available
Vapor pressure @ 20°C (kPa): 0.9 @ 20 deg. C 1.28 at 25 deg. C	Evaporation rate: No information available	Vapor density: 3.66
VOC content (g/L): 879	Odor threshold (ppm): 140	Partition coefficient (n-octanol/water): log K _{ow} = 3.1
Viscosity: No information available	Miscibility: No information available	Solubility: Very slightly soluble in water Soluble in Alcohol Soluble in Benzene Soluble in Carbon tetrachloride Soluble in Ether Slightly soluble in chloroform

10. STABILITY AND REACTIVITY

Reactivity

No information available

Chemical stability

Stability: Stable under recommended storage conditions.

Possibility of Hazardous Reactions: Hazardous polymerization does not occur

Conditions to avoid: Heat. Ignition sources. Incompatible materials.

Incompatible Materials: Oxidizing agents
chlorates
Nitrates
Peroxides

Hazardous decomposition products: Carbon monoxide. Carbon dioxide.

Other Information

Corrosivity: No information available

Special Remarks on Corrosivity: No information available

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Principal Routes of Exposure:
Ingestion. Inhalation. Skin.

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document
Component Information

Ethylbenzene	
CAS-No.	100-41-4

LD50/oral/rat = 3500 mg/kg Oral LD50 Rat
LD50/oral/mouse = No information available
LD50/dermal/rabbit = 15354-15400 mg/kg Dermal LD50Rabbit
LD50/dermal/rat = No information available
LC50/inhalation/rat = 17.4 mg/L Inhalation LC50 Rat 4 h
LC50/inhalation/mouse = 35500 mg/m³ 2H
Other LD50 or LC50information = No information available

Product Information

LD50/oral/rat =
VALUE- Acute Tox Oral = 3500 mg/kg

LD50/oral/mouse =
Value - Acute Tox Oral = No information available

LD50/dermal/rabbit
VALUE-Acute Tox Dermal = 15354 mg/kg

LD50/dermal/rat
VALUE -Acute Tox Dermal = No information available

LC50/inhalation/rat**VALUE-Vapor** = 17.4 mg/l (4-hr)**VALUE-Gas** = No information available**VALUE-Dust/Mist** = No information available**LC50/Inhalation/mouse****VALUE-Vapor** = 35500 mg/m³ 2 h**VALUE - Gas** = No information available**VALUE - Dust/Mist** = No information available**Symptoms****Skin Contact:**

Causes skin irritation. Mildly to moderately irritating to the skin.

Eye Contact:

Causes serious eye irritation. Contact with vapor or liquid can cause severe eye irritation depending on concentration. It may also cause conjunctivitis. At a vapor exposure level of 85 - 200 ppm, it is mildly and transiently irritating to the eyes; 1000 ppm causes further irritation and tearing; 2000 ppm results in immediate and severe irritation and tearing; 5,000 ppm is intolerable (ACGIH, 1991; Clayton and Clayton, 1994). Standard draize test for eye irritation using 500 mg resulted in severe irritation (RTECS).

Inhalation

Irritating to respiratory system. Inhalation of vapors may cause drowsiness and dizziness. Exposure to high concentrations can cause nasal, mucous membrane and respiratory tract irritation and can also result in chest constriction and, trouble breathing, respiratory failure, and even death. It can also affect behavior/Central Nervous System. The effective dose for CNS depression in experimental animals was 10,000 ppm (ACGIH, 1991). Symptoms of CNS depression include headache, nausea, weakness, dizziness, vertigo, irritability, fatigue, lightheadedness, sleepiness, tremor, loss of coordination, judgement, and consciousness, coma, and death. It can also cause pulmonary edema. Inhalation of 85 ppm can produce fatigue, insomnia, headache, and mild irritation of the respiratory tract (Haley & Berndt, 1987).

Ingestion

May be harmful if swallowed. Aspiration hazard if swallowed. Aspiration may lead to pulmonary edema. Aspiration into the lungs can cause chemical pneumonitis. May cause central nervous system effects (affect behavior). May cause digestive (gastrointestinal) tract irritation. May cause abdominal pain. Ingestion may cause nausea, vomiting.

Aspiration hazard

May be fatal if swallowed and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Chronic Toxicity**

Skin: Prolonged or repeated skin contact may cause redness, drying, scaling, dermatitis, and even blistering of the skin. Inhalation: Prolonged or repeated inhalation may cause lung, liver and kidney changes, and affect the blood(leukocytosis, increased platelet counts).

Sensitization:

No information available.

Mutagenic Effects:

No information available

Carcinogenic effects:

Suspected of causing cancer. Possibly carcinogenic to humans.

Components	CAS-No.	IARC	ACGIH - Carcinogens	NTP	OSHA HCS - Carcinogens	Australia - Notifiable Carcinogenic	Australia - Prohibited Carcinogenic
------------	---------	------	---------------------	-----	------------------------	-------------------------------------	-------------------------------------

						Substances	Substances
Ethylbenzene	100-41-4	Group 2B - Possibly carcinogenic to humans - Monograph 77 [2000]	A3 Confirmed Animal Carcinogen with Unknown Relevance to Humans	Not listed	Present	Not listed	Not listed

ACGIH (American Conference of Governmental Industrial Hygienists)

IARC (International Agency for Research on Cancer)

NTP (National Toxicology Program)

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

Reproductive toxicity

No data is available

Reproductive Effects:

No information available

Developmental Effects:

No information available

Teratogenic Effects:

No information available

Specific Target Organ Toxicity

STOT - single exposure

Respiratory system. central nervous system.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Target Organs:

Skin. Liver. Kidneys.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Ecotoxicity effects:

Aquatic environment.

Ethylbenzene - 100-41-4

Freshwater Algae Data:

4.6 mg/L EC50 Pseudokirchneriella subcapitata 72 h 438 mg/L EC50 Pseudokirchneriella subcapitata 96 h 2.6 - 11.3 mg/L EC50 Pseudokirchneriella subcapitata 72 h 1.7 - 7.6 mg/L EC50 Pseudokirchneriella subcapitata 96 h

Freshwater Fish Species Data:

11.0 - 18.0 mg/L LC50 Oncorhynchus mykiss 96 h static 1 4.2 mg/L LC50 Oncorhynchus mykiss 96 h semi-static 1 7.55 - 11 mg/L LC50 Pimephales promelas 96 h flow-through 1 32 mg/L LC50 Lepomis macrochirus 96 h static 1 9.1 - 15.6 mg/L LC50 Pimephales promelas 96 h static 1 9.6 mg/L LC50 Poecilia reticulata 96 h static 1

Water Flea Data:

1.8 - 2.4 mg/L EC50 Daphnia magna 48 h

Persistence and degradability:

No information available

Bioaccumulative potential:

Potential for bioconcentration in aquatic organisms is low.

Mobility:

Medium/moderate mobility.

13. DISPOSAL CONSIDERATIONS

Disposal Methods

Waste from residues / unused products:

Waste must be disposed of in accordance with Federal, State and Local regulation.

Contaminated packaging:

Product code: E1033

Product name: ETHYLBENZENE,
REAGENT

9 / 14

Empty containers should be taken for local recycling, recovery or waste disposal

Components	CAS-No.	RCRA - F Series Wastes	RCRA - K Series Wastes	RCRA - P Series Wastes	RCRA - U Series Wastes
Ethylbenzene	100-41-4	None	None	None	None

14. TRANSPORT INFORMATION

DOT

UN-No: UN1175
Proper Shipping Name: Ethylbenzene
Hazard Class: 3
Subsidiary Class: No information available
Packing group: II
Emergency Response Guide Number: 130
Marine Pollutant: No data available
DOT RQ (lbs): No information available
Special Provisions: IB2, T4, TP1
Symbol(s): No information available
Description: UN1175, ETHYLBENZENE, 3, II

TDG (Canada)

UN-No: UN1175
Proper Shipping Name: Ethylbenzene
Hazard Class: 3
Subsidiary Risk: No information available
Packing Group: II
Marine Pollutant: No Information available
Description: UN1175, ETHYLBENZENE, 3, II

ADR

UN-No: UN1175
Proper Shipping Name: Ethylbenzene
Hazard Class: 3
Packing Group: II
Subsidiary Risk: No information available
Description: UN1175, ETHYLBENZENE, 3, II

IMO / IMDG

UN-No: UN1175
Proper Shipping Name: Ethylbenzene
Hazard Class: 3
Subsidiary Risk: No information available
Packing Group: II
Marine Pollutant: No information available
EMS: F-E
Description: UN1175, ETHYLBENZENE, 3, II

RID

UN-No: UN1175
Proper Shipping Name: Ethylbenzene
Hazard Class: 3
Subsidiary Risk: No information available
Packing Group: II
Description: UN1175, ETHYLBENZENE, 3, II

ICAO

UN-No: UN1175
Proper Shipping Name: Ethylbenzene
Hazard Class: 3
Subsidiary Risk: No information available
Packing Group: II
Description: UN1175, ETHYLBENZENE, 3, II

IATA

UN-No: UN1175
Proper Shipping Name: Ethylbenzene
Hazard Class: 3
Subsidiary Risk: No information available
Packing Group: II
ERG Code: 3L
Special Provisions No information available
Description: UN1175, ETHYLBENZENE, 3, II

15. REGULATORY INFORMATION

International Inventories

Components	CAS-No.	U.S. TSCA	KOREA KECL	Philippines (PICCS)	Japan ENCS	CHINA	Australia (AICS)	EINECS-No.
Ethylbenzene	100-41-4	PresentACTIVE	Present KE-13532	Present	Present (3)-60,(3)-28	Present	Present	Present 202-849-4


U.S. Regulations

Ethylbenzene

Massachusetts RTK: Present
New Jersey RTK Hazardous Substance List: 0851
New Jersey (EHS) List: 0851 500 lb TPQ
New Jersey - Discharge Prevention - List of Hazardous Substances: Present
Pennsylvania RTK: Environmental hazard
Pennsylvania RTK - Environmental Hazard List Present
Minnesota - Hazardous Substance List: Present
New York Release Reporting - List of Hazardous Substances:
 1000 lb RQ
 1 lb RQ
Louisiana Reportable Quantity List for Pollutants: 1000lbfinal RQ
 454kgfinal RQ
California Directors List of Hazardous Substances: Present

California Prop. 65: Safe Drinking Water and Toxic Enforcement Act of 1986.

Chemicals Known to the State of California to Cause Cancer:

 **WARNING:** This product can expose you to chemicals including (see table below) which is (are) known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

Chemicals Known to the State of California to Cause Reproductive Toxicity:

This product does not contain a chemical requiring a warning under California Prop. 65. (See table below)

Components	CAS-No.	Carcinogen	Developmental Toxicity	Male Reproductive Toxicity	Female Reproductive Toxicity:
Ethylbenzene	100-41-4	carcinogen	Not Listed	Not Listed	Not Listed

CERCLA/SARA

Components	CAS-No.	CERCLA - Hazardous Substances and	Section 302 Extremely Hazardous	Section 302 Extremely Hazardous	Section 313 - Chemical Category	Section 313 - Reporting de minimis

		their Reportable Quantities	Substances and TPQs	Substances and RQs		
Ethylbenzene	100-41-4	1000 lb final RQ 454 kg final RQ	None	None	None	0.1 % de minimis concentration

U.S. TSCA

Components	CAS-No.	TSCA Section 5(a)2 - Chemicals With Significant New Use Rules (SNURS)	TSCA 8(d) -Health and Safety Reporting
Ethylbenzene	100-41-4	Not Applicable	Not Applicable

Canada

WHMIS 2015 - GHS Classifications

WHMIS 2015 Hazard Classification Information:

Component
Ethylbenzene
100-41-4 (100)

WHMIS 2015 Hazard Classification
Flammable liquids - Category 2: H225 Highly flammable liquid and vapour.; Acute toxicity - Inhalation - Category 4: H332 Harmful if inhaled.; Skin corrosion/irritation - Category 2: H315 Causes skin irritation.; Carcinogenicity - Category 2: H351 Suspected of causing cancer.; Aspiration hazard - Category 1: H304 May be fatal if swallowed and enters airways.

Canada Hazardous Products Regulation This product has been classified according to the hazard criteria of the HPR (Hazardous Products Regulation) and the SDS contains all of the information required by the HPR

WHMIS 1988 Hazard Class

B2 Flammable liquid
D2A Very toxic materials
D2B Toxic materials

Components
Ethylbenzene

WHMIS 1988
B2,D2A,D2B

Canada Controlled Products Regulation:

This product has been classified according to the hazard criteria of the CPR (Controlled Products Regulation) and the MSDS contains all of the information required by the CPR.

Components	WHMIS Ingredient Disclosure List -
Ethylbenzene	0.1 %

Inventory

Components	CAS-No.	Canada (DSL)	Canada (NDSL)
Ethylbenzene	100-41-4	Present	Not Listed

Components	CAS-No.	CEPA Schedule I - Toxic Substances
Ethylbenzene	100-41-4	Not listed
Components	CAS-No.	CEPA - 2010 Greenhouse Gases Subject to Mandatory Reporting
Ethylbenzene	100-41-4	Not listed

EU Classification

EU GHS - SV - CLP 1272/2008

Components	CAS-No.	EU GHS - SV - CLP (1272/2008)
Ethylbenzene	100-41-4	Flammable liquids - Flam. Liq. 2: H225 Highly flammable liquid and vapour.;

Product code: E1033

Product name: ETHYLBENZENE,
REAGENT

12 / 14

		Acute toxicity - Inhalation - Acute Tox. 4: H332 Harmful if inhaled. (Minimum classification); Specific target organ toxicity - Repeated exposure - STOT RE 2: H373 May cause damage to ears through prolonged or repeated exposure.; Aspiration hazard - Asp. Tox. 1: H304 May be fatal if swallowed and enters airways.601-023-00-4
--	--	---

EU - CLP (1272/2008)

R-phrases(s)

R11 - Highly flammable.

R20 - Harmful by inhalation.

R65 - Harmful: may cause lung damage if swallowed.

R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.

S -phrase(s)

S 2 - Keep out of the reach of children.

S16 - Keep away from sources of ignition - No smoking.

S29 - Do not empty into drains.

S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

S24/25 - Avoid contact with skin and eyes.

Components	CAS-No.	Classification	Concentration Limits:	Safety Phrases
Ethylbenzene	100-41-4	F; R11 Xn; R20-48/20-65	No information	S2 S16 S24/25 S29

The product is classified in accordance with Annex VI to Directive 67/548/EEC

Indication of danger:

F - Highly flammable.

Xn - Harmful.

16. OTHER INFORMATION

Preparation Date: 4/13/2018
Revision Date: 4/13/2018
Prepared by: Sonia Owen

Disclaimer:

All chemicals may pose unknown hazards and should be used with caution. This Safety Data Sheet (SDS) applies only to the material as packaged. If this product is combined with other materials, deteriorates, or becomes contaminated, it may pose hazards not mentioned in this SDS. The physical properties reported in this SDS are obtained from the literature and do not constitute product specifications. Information contained herein does not constitute a warranty, whether expressed or implied, as to the safety, merchantability or fitness of the goods for a particular purpose. Spectrum Chemicals & Laboratory Products, Inc. assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied. It shall be the user's responsibility to develop proper methods of handling and personal protection based on the actual conditions of use. While this SDS is based on technical data judged to be reliable, Spectrum assumes no responsibility for the completeness or accuracy of the information contained herein.

End of Safety Data Sheet

SAFETY DATA SHEET

Version 8.5
Revision Date 10/30/2021
Print Date 03/19/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name : Fluoranthene

Product Number : 423947
Brand : Aldrich
CAS-No. : 206-44-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Acute toxicity, Oral (Category 4), H302
Short-term (acute) aquatic hazard (Category 1), H400
Long-term (chronic) aquatic hazard (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word : Warning

Hazard statement(s)
H302 : Harmful if swallowed.

H410	Very toxic to aquatic life with long lasting effects.
Precautionary statement(s)	
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P391	Collect spillage.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Benzo[j,k]fluorene

Formula : C₁₆H₁₀

Molecular weight : 202.25 g/mol

CAS-No. : 206-44-0

EC-No. : 205-912-4

Component	Classification	Concentration
Benzo[jk]fluorene		
	Acute Tox. 4; Aquatic Acute 1; Aquatic Chronic 1; H302, H400, H410 M-Factor - Aquatic Acute: 100 - Aquatic Chronic: 10	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO₂) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air on intense heating.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

5.4 Further information

Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Dry.

Storage class

Storage class (TRGS 510): 11: Combustible Solids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Benzo[jk]fluorene	206-44-0	PEL	0.2 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Benzo[jk]fluorene	206-44-0	1-Hydroxypyrene	2.5 µg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift at end of workweek			
		3-hydroxybenzo(a)pyrene		Urine	ACGIH - Biological Exposure Indices (BEI)
		End of shift at end of workweek			

8.2 Exposure controls

Appropriate engineering controls

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

Handle with impervious gloves.

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact
Material: Nitrile rubber
Minimum layer thickness: 0.11 mm
Break through time: 480 min
Material tested:KCL 741 Dermatril® L

Splash contact
Material: Nitrile rubber
Minimum layer thickness: 0.11 mm
Break through time: 480 min
Material tested:KCL 741 Dermatril® L

Body Protection

protective clothing

Respiratory protection

required when dusts are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance	Form: solid
b) Odor	No data available
c) Odor Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	Melting point/range: 105 - 110 °C (221 - 230 °F) - lit.
f) Initial boiling point and boiling range	384 °C 723 °F - lit.
g) Flash point	198.0 °C (388.4 °F) - closed cup
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	No data available
k) Vapor pressure	No data available
l) Vapor density	No data available
m) Density	1.25 g/cm ³ at 0 °C (32 °F)
Relative density	No data available
n) Water solubility	No data available
o) Partition coefficient:	No data available

n-octanol/water

- | | | |
|----|---------------------------|-------------------|
| p) | Autoignition temperature | No data available |
| q) | Decomposition temperature | No data available |
| r) | Viscosity | No data available |
| s) | Explosive properties | No data available |
| t) | Oxidizing properties | none |

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Forms explosive mixtures with air on intense heating.

A range from approx. 15 Kelvin below the flash point is to be rated as critical.

The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally be assumed.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Strong heating.

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 2,000 mg/kg

Remarks: (RTECS)

Inhalation: No data available

LD50 Dermal - Rabbit - 3,180 mg/kg

Remarks: (RTECS)

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

RTECS: LL4025000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish	flow-through test LC50 - <i>Oncorhynchus mykiss</i> (rainbow trout) - 0.0077 mg/l - 96 h Remarks: (ECOTOX Database)
------------------	--

Toxicity to daphnia and other aquatic invertebrates	EC50 - <i>Daphnia magna</i> (Water flea) - 0.117 mg/l - 48 h Remarks: (ECOTOX Database)
---	--

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Aldrich - 423947

Page 7 of 9

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

DOT (US)

UN number: 3077 Class: 9 Packing group: III
Proper shipping name: Environmentally hazardous substance, solid, n.o.s.
(Benzo[jk]fluorene)
Reportable Quantity (RQ): 100 lbs
Poison Inhalation Hazard: No

IMDG

UN number: 3077 Class: 9 Packing group: III EMS-No: F-A, S-F
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Benzo[jk]fluorene)
Marine pollutant : yes

IATA

UN number: 3077 Class: 9 Packing group: III
Proper shipping name: Environmentally hazardous substance, solid, n.o.s.
(Benzo[jk]fluorene)

Further information

EHS-Mark required (ADR 2.2.9.1.10, IMDG code 2.10.3) for single packagings and combination packagings containing inner packagings with Dangerous Goods > 5L for liquids or > 5kg for solids.

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

Benzo[jk]fluorene	CAS-No. 206-44-0	Revision Date 2015-11-23
-------------------	---------------------	-----------------------------

SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information**Further information**

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 8.5

Revision Date: 10/30/2021

Print Date: 03/19/2022

SAFETY DATA SHEET

Version 6.4
Revision Date 04/18/2021
Print Date 03/19/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name : Fluorene

Product Number : 128333
Brand : Aldrich
CAS-No. : 86-73-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Short-term (acute) aquatic hazard (Category 1), H400
Long-term (chronic) aquatic hazard (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word : Warning

Hazard statement(s)
H410 : Very toxic to aquatic life with long lasting effects.

Precautionary statement(s)	
P273	Avoid release to the environment.
P391	Collect spillage.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula	: C ₁₃ H ₁₀
Molecular weight	: 166.22 g/mol
CAS-No.	: 86-73-7
EC-No.	: 201-695-5

Component	Classification	Concentration
Fluorene		
	Aquatic Acute 1; Aquatic Chronic 1; H400, H410 M-Factor - Aquatic Acute: 1	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Consult a physician. Show this material safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Advice on protection against fire and explosion

Provide appropriate exhaust ventilation at places where dust is formed.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place.
Storage class (TRGS 510): 13: Non Combustible Solids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatrill® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatrill® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Respiratory protection is not required. Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN 143) dust masks. Use

respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance	Form: crystalline Color: white
b) Odor	No data available
c) Odor Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	Melting point/range: 111 - 114 °C (232 - 237 °F) - lit.
f) Initial boiling point and boiling range	298 °C 568 °F - lit.
g) Flash point	151.0 °C (303.8 °F) - closed cup
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	No data available
k) Vapor pressure	No data available
l) Vapor density	No data available
m) Relative density	No data available
n) Water solubility	No data available
o) Partition coefficient: n-octanol/water	No data available
p) Autoignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

No data available

Inhalation: No data available

Dermal: No data available

LD50 Intraperitoneal - Mouse - > 2.0 mg/kg

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

RTECS: LL5670000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish LC50 - Fish - 0.82 mg/l - 96 h

Toxicity to daphnia and other aquatic invertebrates Remarks: No data available (Fluorene)

Toxicity to algae EC50 - Algae - 3.4 mg/l - 96 h

12.2 Persistence and degradability**12.3 Bioaccumulative potential**

Bioaccumulation Oncorhynchus mykiss (rainbow trout) - 24 h
- 0.0191 mg/l(Fluorene)

Bioconcentration factor (BCF): 512

12.4 Mobility in soil

Adsorbs on soil.

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

DOT (US)

UN number: 3077 Class: 9 Packing group: III
Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (Fluorene)
Reportable Quantity (RQ): 5000 lbs
Poison Inhalation Hazard: No

IMDG

UN number: 3077 Class: 9 Packing group: III EMS-No: F-A, S-F
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Fluorene)
Marine pollutant : yes

IATA

UN number: 3077 Class: 9 Packing group: III
Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (Fluorene)

Further information

EHS-Mark required (ADR 2.2.9.1.10, IMDG code 2.10.3) for single packagings and combination packagings containing inner packagings with Dangerous Goods > 5L for liquids or > 5kg for solids.

SECTION 15: Regulatory information

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Chronic Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components

Fluorene	CAS-No. 86-73-7	Revision Date 1993-04-24
----------	--------------------	-----------------------------

Fluorene	CAS-No. 86-73-7	Revision Date 1993-04-24
----------	--------------------	-----------------------------

New Jersey Right To Know Components

Fluorene	CAS-No. 86-73-7	Revision Date 1993-04-24
----------	--------------------	-----------------------------

California Prop. 65 Components

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

SECTION 16: Other information**Further information**

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.4

Revision Date: 04/18/2021

Print Date: 03/19/2022

SAFETY DATA SHEET

Creation Date 14-Sep-2009

Revision Date 28-Dec-2021

Revision Number 5

1. Identification

Product Name N-HEPTANE

Cat No. : AC610361000

CAS No 142-82-5

Synonyms Normal heptane.; Heptane

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Central nervous system (CNS).	
Specific target organ toxicity - (repeated exposure)	Category 2
Target Organs - Kidney, Liver, Blood.	
Aspiration Toxicity	Category 1

Label Elements

Signal Word
Danger

Hazard Statements

Highly flammable liquid and vapor
May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye irritation
May cause damage to organs through prolonged or repeated exposure

**Precautionary Statements****Prevention**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting equipment
Use only non-sparking tools
Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Do not breathe dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Take precautionary measures against static discharge
Keep cool

Response

Get medical attention/advice if you feel unwell

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
If skin irritation occurs: Get medical advice/attention
Wash contaminated clothing before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Very toxic to aquatic life with long lasting effects

3. Composition/Information on Ingredients

Component	CAS No	Weight %
-----------	--------	----------

n-Heptane	142-82-5	>95
-----------	----------	-----

4. First-aid measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.
Inhalation	Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention. Risk of serious damage to the lungs (by aspiration). If not breathing, give artificial respiration.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Most important symptoms and effects	Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	CO ₂ , dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	Water may be ineffective
Flash Point	-4 °C / 24.8 °F
Method -	No information available
Autoignition Temperature	215 °C / 419 °F
Explosion Limits	
Upper	6.7 vol %
Lower	1.05 vol %
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health
3

Flammability
3

Instability
0

Physical hazards
N/A

6. Accidental release measures

Personal Precautions	Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation.
-----------------------------	---

Environmental Precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

Methods for Containment and Clean Up

Remove all sources of ignition. Soak up with inert absorbent material. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Keep in suitable, closed containers for disposal.

7. Handling and storage

Handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Wash hands before breaks and immediately after handling the product. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Storage.

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area. Incompatible Materials. Strong oxidizing agents.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
n-Heptane	TWA: 400 ppm STEL: 500 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 1600 mg/m ³ (Vacated) STEL: 500 ppm (Vacated) STEL: 2000 mg/m ³ TWA: 500 ppm TWA: 2000 mg/m ³	IDLH: 750 ppm TWA: 85 ppm TWA: 350 mg/m ³ Ceiling: 440 ppm Ceiling: 1800 mg/m ³	TWA: 400 ppm STEL: 500 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

None under normal use conditions.

Personal Protective Equipment**Eye/face Protection**

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection

No protective equipment is needed under normal use conditions.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State

Liquid

Appearance

Colorless

Odor

Petroleum distillates

Odor Threshold

No information available

pH	No information available
Melting Point/Range	-91 °C / -131.8 °F
Boiling Point/Range	98 °C / 208.4 °F
Flash Point	-4 °C / 24.8 °F
Evaporation Rate	2.8 (Butyl Acetate = 1.0)
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	6.7 vol %
Lower	1.05 vol %
Vapor Pressure	48 mbar @ 20 °C
Vapor Density	3.5
Specific Gravity	0.683
Solubility	Insoluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	215 °C / 419 °F
Decomposition Temperature	No information available
Viscosity	0.4 mPa s at 20 °C
Molecular Formula	C7 H16
Molecular Weight	100.20

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products. Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Strong oxidizing agents
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂)
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
n-Heptane	>2000 mg/kg (rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 > 73.5 mg/L (Rat) 4 h

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	Irritating to eyes and skin
Sensitization	No information available
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
n-Heptane	142-82-5	Not listed	Not listed	Not listed	Not listed	Not listed

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects	No information available.
Teratogenicity	No information available.
STOT - single exposure STOT - repeated exposure	Central nervous system (CNS) Kidney Liver Blood
Aspiration hazard	Aspiration hazard
Symptoms / effects, both acute and delayed	Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Endocrine Disruptor Information	No information available
Other Adverse Effects	The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
n-Heptane	Not listed	LC50: = 375.0 mg/L, 96h (Cichlid fish)	Not listed	EC50: >10 mg/L/24h

Persistence and Degradability	Persistence is unlikely
Bioaccumulation/ Accumulation	No information available.
Mobility	The product is insoluble and floats on water. Is not likely mobile in the environment due its low water solubility.

Component	log Pow
n-Heptane	4.66

13. Disposal considerations

Waste Disposal Methods	Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.
-------------------------------	---

14. Transport information

DOT

UN-No	UN1206
Proper Shipping Name	HEPTANES
Hazard Class	3
Packing Group	II

TDG

UN-No	UN1206
Proper Shipping Name	HEPTANES
Hazard Class	3
Packing Group	II

IATA

UN-No	UN1206
Proper Shipping Name	Heptanes
Hazard Class	3
Packing Group	II

IMDG/IMO

UN-No	UN1206
-------	--------

Proper Shipping Name Heptanes
 Hazard Class 3
 Packing Group II

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
n-Heptane	142-82-5	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
n-Heptane	142-82-5	X	-	205-563-8	X	X	X	X	X	KE-18271

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

OSHA - Occupational Safety and Health Administration Not applicable

CERCLA Not applicable

California Proposition 65 This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
n-Heptane	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): N

DOT Marine Pollutant Y

DOT Severe Marine Pollutant N

U.S. Department of Homeland Security This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade

Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
n-Heptane	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
n-Heptane	142-82-5	Listed	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
n-Heptane	142-82-5	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By

Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Creation Date

14-Sep-2009

Revision Date

28-Dec-2021

Print Date

28-Dec-2021

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/25/2019

Version Number 2

Reviewed on 03/25/2019

1 Identification

- **Product identifier**
- **Trade name:** Hexachlorobutadiene
- **Part number:** RHH-060
- **CAS Number:**
87-68-3
- **EC number:**
201-765-5
- **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Agilent Technologies, Inc.
5301 Stevens Creek Blvd.
Santa Clara, CA 95051 USA
- **Information department:**
Telephone: 800-227-9770
e-mail: pdl-msds_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS06 Skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed.

Acute Tox. 2 H310 Fatal in contact with skin.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Flam. Liq. 4 H227 Combustible liquid.

- **Label elements**

- **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS06



GHS07



GHS08

- **Signal word** Danger

(Contd. on page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/25/2019

Version Number 2

Reviewed on 03/25/2019

Trade name: Hexachlorobutadiene

(Contd. of page 1)

· Hazard-determining components of labeling:

hexachlorobuta-1,3-diene

· Hazard statements

Combustible liquid.

Toxic if swallowed.

Fatal in contact with skin.

Causes skin irritation.

Suspected of causing cancer.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from flames and hot surfaces. – No smoking.

Do not get in eyes, on skin, or on clothing.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Rinse mouth.

If on skin: Wash with plenty of water.

If exposed or concerned: Get medical advice/attention.

Take off immediately all contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:
· NFPA ratings (scale 0 - 4)


Health = 3

Fire = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)


Health = 3

Fire = 0

Reactivity = 0

· Other hazards
· Results of PBT and vPvB assessment
· PBT:

87-68-3 hexachlorobuta-1,3-diene

· vPvB:

87-68-3 hexachlorobuta-1,3-diene

US

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/25/2019

Version Number 2

Reviewed on 03/25/2019

Trade name: Hexachlorobutadiene

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Substances**
- **CAS No. Description**
87-68-3 hexachlorobuta-1,3-diene
- **Identification number(s)**
- **EC number:** 201-765-5

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not induce vomiting; immediately call for medical help.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

1 ppm

(Contd. on page 4)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/25/2019

Version Number 2

Reviewed on 03/25/2019

Trade name: Hexachlorobutadiene

(Contd. of page 3)

· **PAC-2:**

3 ppm

· **PAC-3:**

10 ppm

7 Handling and storage· **Handling:**· **Precautions for safe handling** Open and handle receptacle with care.· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**· **Storage:**· **Requirements to be met by storerooms and receptacles:** No special requirements.· **Information about storage in one common storage facility:** Not required.· **Further information about storage conditions:** Keep receptacle tightly sealed.· **Specific end use(s)** No further relevant information available.**8 Exposure controls/personal protection**· **Additional information about design of technical systems:** No further data; see item 7.· **Control parameters**· **Components with limit values that require monitoring at the workplace:****87-68-3 hexachlorobuta-1,3-diene**REL Long-term value: 0.24 mg/m³, 0.02 ppm
Skin; See Pocket Guide App. ATLV Long-term value: 0.21 mg/m³, 0.02 ppm
Skin· **Additional information:** The lists that were valid during the creation were used as basis.· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

(Contd. on page 5)

US

Safety Data Sheet acc. to OSHA HCS

Printing date 03/25/2019

Version Number 2

Reviewed on 03/25/2019

Trade name: Hexachlorobutadiene

(Contd. of page 4)

· Protection of hands:

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

· Information on basic physical and chemical properties
· General Information
· Appearance:

Form: Fluid
Color: Not determined.

· Odor: Characteristic

· Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: -21 °C (-5.8 °F)

Boiling point/Boiling range: 215 °C (419 °F)

· Flash point: ≤93 °C (≤199.4 °F)

· Flammability (solid, gaseous): Not applicable.

· Decomposition temperature: Not determined.

· Auto igniting: Not determined.

· Danger of explosion: Not determined.

· Explosion limits:

Lower: Not determined.

Upper: Not determined.

· Vapor pressure at 20 °C (68 °F): 0.2 hPa (0.2 mm Hg)

· Density at 20 °C (68 °F): 1.665 g/cm³ (13.89443 lbs/gal)

· Relative density Not determined.

· Vapor density Not determined.

· Evaporation rate Not determined.

· Solubility in / Miscibility with

Water at 20 °C (68 °F): 0.5 g/l

· Partition coefficient (n-octanol/water): Not determined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/25/2019

Version Number 2

Reviewed on 03/25/2019

Trade name: Hexachlorobutadiene

(Contd. of page 5)

- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
 - Organic solvents:** 100.0 %
 - VOC content:** 100.00 %
 - 1,665.0 g/l / 13.90 lb/gal
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	82 mg/kg (rat)
Dermal	LD50	100 mg/kg (rabbit)
Inhalative	LC50/4 h	370 mg/L (mouse)

87-68-3 hexachlorobuta-1,3-diene

Oral	LD50	82 mg/kg (rat)
Dermal	LD50	100 mg/kg (rabbit)
Inhalative	LC50/4 h	370 mg/L (mouse)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

3

- **NTP (National Toxicology Program)**

Substance is not listed.

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/25/2019

Version Number 2

Reviewed on 03/25/2019

Trade name: Hexachlorobutadiene

(Contd. of page 6)

· **OSHA-Ca (Occupational Safety & Health Administration)**

Substance is not listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 3 (Assessment by list): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

· **PBT:**

87-68-3 hexachlorobuta-1,3-diene

· **vPvB:**

87-68-3 hexachlorobuta-1,3-diene

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **DOT, IMDG, IATA**

UN2279

· **UN proper shipping name**

· **DOT**

· **IMDG**

· **IATA**

Hexachlorobutadiene

HEXACHLOROBUTADIENE, MARINE POLLUTANT

HEXACHLOROBUTADIENE

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/25/2019

Version Number 2

Reviewed on 03/25/2019

Trade name: Hexachlorobutadiene

(Contd. of page 7)

· **Transport hazard class(es)**

· **DOT, IMDG**

· **Class**

6.1 Toxic substances

· **Label**

6.1

· **IATA**

· **Class**

6.1 Toxic substances

· **Label**

6.1

· **Packing group**

· **DOT, IMDG, IATA**

III

· **Environmental hazards:**

· **Marine pollutant:**

Yes (DOT)

Symbol (fish and tree)

· **Special precautions for user**

Warning: Toxic substances

· **Danger code (Kemler):**

60

· **EMS Number:**

F-A,S-A

· **Segregation groups**

Liquid halogenated hydrocarbons

· **Stowage Category**

A

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 60 L

On cargo aircraft only: 220 L

· **Hazardous substance:**

1 lbs, 0.454 kg

· **Remarks:**

Special marking with the symbol (fish and tree).

· **IMDG**

· **Limited quantities (LQ)**

5 L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 2279 HEXACHLOROBUTADIENE, 6.1, III

US

(Contd. on page 9)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/25/2019

Version Number 2

Reviewed on 03/25/2019

Trade name: Hexachlorobutadiene

(Contd. of page 8)

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· **Section 355 (extremely hazardous substances):**

Substance is not listed.

· **Section 313 (Specific toxic chemical listings):**

Substance is listed.

· **TSCA (Toxic Substances Control Act):**

Substance is listed.

· **TSCA new (21st Century Act): (Substances not listed)**

87-68-3 hexachlorobuta-1,3-diene

· **Proposition 65**

· **Chemicals known to cause cancer:**

Substance is listed.

· **Chemicals known to cause reproductive toxicity for females:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for males:**

Substance is not listed.

· **Chemicals known to cause developmental toxicity:**

Substance is not listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

C

· **TLV (Threshold Limit Value established by ACGIH)**

A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

Substance is listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· **Department issuing SDS:** Document Control / Regulatory

· **Contact:** regulatory@ultrasci.com

· **Date of preparation / last revision** 03/25/2019 / 1

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/25/2019

Version Number 2

Reviewed on 03/25/2019

Trade name: Hexachlorobutadiene

(Contd. of page 9)

NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 4: Flammable liquids – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 2: Acute toxicity – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Carc. 2: Carcinogenicity – Category 2

· * **Data compared to the previous version altered.**

US

SAFETY DATA SHEET

Version 6.10
Revision Date 08/10/2021
Print Date 03/19/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name : Hexane

Product Number : 296090
Brand : Sigma-Aldrich
Index-No. : 601-037-00-0
CAS-No. : 110-54-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 2), H225
Skin irritation (Category 2), H315
Reproductive toxicity (Category 2), H361
Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336
Specific target organ toxicity - repeated exposure, Inhalation (Category 2), Nervous system, H373
Aspiration hazard (Category 1), H304
Short-term (acute) aquatic hazard (Category 2), H401
Long-term (chronic) aquatic hazard (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Sigma-Aldrich - 296090

Page 1 of 11

Pictogram



Signal word

Danger

Hazard statement(s)

H225	Highly flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs (Nervous system) through prolonged or repeated exposure if inhaled.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391	Collect spillage.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms	: n-Hexane
Formula	: C ₆ H ₁₄
Molecular weight	: 86.18 g/mol
CAS-No.	: 110-54-3
EC-No.	: 203-777-6
Index-No.	: 601-037-00-0

Component	Classification	Concentration
n-Hexane		
	Flam. Liq. 2; Skin Irrit. 2; Repr. 2; STOT SE 3; STOT RE 2; Asp. Tox. 1; Aquatic Acute 2; Aquatic Chronic 2; H225, H315, H361, H336, H373, H304, H401, H411 Concentration limits: >= 5 %: STOT RE 2, H373; >= 20 %: STOT SE 3, H336;	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Flash back possible over considerable distance. Container explosion may occur under fire conditions. **Advice on protection against fire and explosion**

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
n-Hexane	110-54-3	TWA	50 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Danger of cutaneous absorption		
		TWA	50 ppm 180 mg/m ³	USA. NIOSH Recommended Exposure Limits
		TWA	500 ppm 1,800 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	50 ppm 180 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		Skin		

Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
n-Hexane	110-54-3	2,5-Hexanedione	0.5 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift			

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 480 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 10 min

Material tested: KCL 741 Dermatril® L

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|--|---------------------------------------|
| a) Appearance | Form: liquid
Color: colorless |
| b) Odor | hydrocarbon-like |
| c) Odor Threshold | No data available |
| d) pH | 7.0 |
| e) Melting point/freezing point | Melting point/range: -95 °C (-139 °F) |
| f) Initial boiling point and boiling range | 69 °C 156 °F |
| g) Flash point | -22 °C (-8 °F) - c.c. |

h)	Evaporation rate	15.8
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 8.1 %(V) Lower explosion limit: 1.0 %(V)
k)	Vapor pressure	100 hPa at 9.8 °C (49.6 °F)
l)	Vapor density	No data available
m)	Density	0.659 g/mL at 25 °C (77 °F)
	Relative density	No data available
n)	Water solubility	0.01 g/l at 25 °C (77 °F) - slightly soluble
o)	Partition coefficient: n-octanol/water	log Pow: ca.4 at 20 °C (68 °F) - (Lit.), Potential bioaccumulation
p)	Autoignition temperature	225 °C (437 °F) at 1,013 hPa
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	none

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.
Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .
The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of explosion with:
Strong oxidizing agents
nitrogen oxides
Violent reactions possible with:
halogens
Risk of ignition or formation of inflammable gases or vapours with:
Peroxides
(sodium salt)

10.4 Conditions to avoid

Exposure to moisture may affect product quality.
Warming.

10.5 Incompatible materials

rubber, various plastics

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - 16,000 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Rat - 4 h - 172 mg/l

Remarks: (RTECS)

LD50 Dermal - Rabbit - male - > 2,000 mg/kg

(OECD Test Guideline 402)

Remarks: (ECHA)

Skin corrosion/irritation

Skin - Rabbit

Result: Skin irritation - 24 h

(OECD Test Guideline 404)

Remarks: (Regulation (EC) No 1272/2008, Annex VI)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation - 72 h

(OECD Test Guideline 405)

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: negative

(OECD Test Guideline 429)

Germ cell mutagenicity

No data available

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: dominant lethal test

Species: Mouse

Application Route: inhalation (vapor)

Result: negative

Remarks: (ECHA)

Carcinogenicity

No data available

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

Sigma-Aldrich - 296090

Page 8 of 11

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

Overexposure may cause reproductive disorder(s) based on tests with laboratory animals.
Suspected human reproductive toxicant Suspected of damaging fertility.
Suspected of damaging fertility.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness. - Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Specific target organ toxicity - repeated exposure

Inhalation - May cause damage to organs through prolonged or repeated exposure. - Nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Aspiration hazard

May be fatal if swallowed and enters airways.

Aspiration hazard, Aspiration may cause pulmonary edema and pneumonitis.

11.2 Additional Information

Repeated dose toxicity - Rat - male - Oral - NOAEL (No observed adverse effect level) - 6.6 mg/kg

Remarks: (ECHA)

RTECS: MN9275000

Drowsiness, irritant effects, somnolence

narcosis, Nausea, Tiredness, CNS disorders, paralysis symptoms

Risk of corneal clouding.

It generally applies for aliphatic hydrocarbons with 6 - 18 carbon atoms that they may cause pneumonia, in some cases also pulmonary oedema, upon direct inhalation, i.e. in conditions that can occur only in very special circumstances (nebulizations, spraying, inhalation of aerosols and similar). After absorption of very large quantities: narcosis.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Testes. - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 2.5 mg/l - 96 h
Remarks: (ECOTOX Database)

Toxicity to daphnia and other aquatic invertebrates EC50 - Daphnia magna (Water flea) - 2.1 mg/l - 48 h
Remarks: (Lit.)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d
Result: 98 % - Readily biodegradable.
(OECD Test Guideline 301F)

Sigma-Aldrich - 296090

Page 9 of 11

Remarks: (in analogy to similar products)

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

DOT (US)

UN number: 1208 Class: 3 Packing group: II
Proper shipping name: Hexanes
Reportable Quantity (RQ): 5000 lbs
Poison Inhalation Hazard: No

IMDG

UN number: 1208 Class: 3 Packing group: II EMS-No: F-E, S-D
Proper shipping name: HEXANES
Marine pollutant : yes
Marine pollutant : yes

IATA

UN number: 1208 Class: 3 Packing group: II
Proper shipping name: Hexanes

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

CAS-No.

Revision Date

Sigma-Aldrich - 296090

Page 10 of 11

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information**Further information**

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.10

Revision Date: 08/10/2021

Print Date: 03/19/2022



Safety Data Sheet

Revision Date: 03/22/18

www.restek.com

2 Letter ISO country code/language code: US/EN

1. IDENTIFICATION

Catalog Number / Product Name: 31279 / Indeno(1,2,3-c,d)pyrene Standard
Company: Restek Corporation
Address: 110 Benner Circle
Bellefonte, Pa. 16823
Phone#: 814-353-1300
Fax#: 814-353-1309
Emergency#: 800-424-9300 (CHEMTREC)
703-527-3887 (Outside the US)
Email: www.restek.com
Revision Number: 10
Intended use: For Laboratory use only

2. HAZARD(S) IDENTIFICATION

Emergency Overview:



GHS Hazard
Symbols:

GHS Classification: Carcinogenicity Category 2

GHS Signal Word: Warning

GHS Hazard: Suspected of causing cancer.

GHS Precautions:

Safety Precautions: Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves/protective clothing/eye protection/face protection.

First Aid Measures: IF exposed or concerned: Get medical advice/attention.

Storage: Store locked up.

Disposal: Dispose of contents/container according to section 13 of the SDS.

Single Exposure Target Organs: No data available

Repeated Exposure Target Organs:

Repeated Exposure Target Organs: No data available

3. COMPOSITION / INFORMATION ON INGREDIENT

Chemical Name	CAS #	EINEC #	% Composition
Dichloromethane	75-09-2	200-838-9	99.9
indeno (1,2,3-c,d) pyrene	193-39-5	205-893-2	0.1

4. FIRST-AID MEASURES

Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately
Eyes:	Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician. Serious harm (damage) may result if treatment is delayed. Continue to flush eyes while awaiting medical attention
Skin Contact:	Wash with soap and water. Remove contaminated clothing, launder immediately, and discard contaminated leather goods. Get medical attention immediately.
Ingestion:	Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this SDS. Never give anything by mouth to an unconscious person

5. FIRE- FIGHTING MEASURES

Extinguishing Media:	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do Not direct a stream of water into the hot burning liquid. Use methods suitable to fight surrounding fire.
Fire and/or Explosion Hazards:	No data.
Fire Fighting Methods and Protection:	Use methods for the surrounding fire.
Hazardous Combustion Products:	Carbon dioxide, Carbon monoxide

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment:	Exposure to the spilled material may be severely irritating or toxic. Follow personal protective equipment recommendations found in Section 8 of this SDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits.
Methods for Clean-up:	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

7. HANDLING AND STORAGE

Handling Technical Measures and Precautions:	Toxic or severely irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material.
Storage Technical Measures and Conditions:	Store in a cool dry place. Isolate from incompatible materials. Keep container closed when not in use

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

United States:

Chemical Name	CAS No.	IDLH	ACGIH STEL	ACGIH TLV-TWA	OSHA Exposure Limit
Dichloromethane	75-09-2	2300 ppm IDLH	None Known	50 ppm TWA	25 ppm TWA; 125 ppm STEL (15 min. TWA)
indeno (1,2,3-c,d) pyrene	193-39-5	Not established	None Known	Not established	No data available

Personal Protection:

Engineering Measures:	Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.
Respiratory Protection:	Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to

Eye Protection:	eliminate symptoms. Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available.
Skin Protection:	Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.
Medical Conditions Aggravated By Exposure:	Eye disease Skin disease including eczema and sensitization Respiratory disease including asthma and bronchitis

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance, color:	Colorless
Odor:	Strong
Physical State:	No data available
pH:	Not applicable
Vapor Pressure:	No data available
Vapor Density:	2.93 (air = 1)
Boiling Point (°C):	530 °C
Melting Point (°C):	-96.7 °C
Flash Point (°F):	No data available
Upper Flammable/Explosive Limit, % in air:	No data available
Lower Flammable/Explosive Limit, % in air:	No data available
Autoignition Temperature (°C):	556 deg C
Decomposition Temperature (°C):	No data available
Specific Gravity:	1.3254 - 1.3258 g/cm3 at 20 °C
Evaporation Rate:	No data available
Odor Threshold:	ND
Solubility:	Moderate; 50-99%
Partition Coefficient: n-octanol in water:	No data available
VOC % by weight:	0
Molecular Weight:	No data available

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	None known. Contamination High temperatures
Materials to Avoid / Chemical Incompatibility:	Strong oxidizing agents Caustics (bases)
Hazardous Decomposition Products:	Carbon dioxide Carbon monoxide

11. TOXICOLOGICAL INFORMATION

Routes of Entry:	Inhalation Absorption Ingestion Skin contact Eye contact
Target Organs Potentially Affected By Exposure:	Skin, Cardiovascular System, Eyes, Liver
Chemical Interactions That Change Toxicity:	None Known

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation:	Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.
Inhalation Toxicity:	Harmful! Can cause systemic damage (see "Target Organs") Inhalation may cause severe central nervous system depression (including unconsciousness).
Skin Contact:	Contact causes severe skin irritation and possible burns.
Skin Absorption:	Harmful if absorbed through the skin. May cause severe irritation and systemic damage.
Eye Contact:	Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.
Ingestion Irritation:	Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea.
Ingestion Toxicity:	Harmful if swallowed. May cause systemic poisoning.

Long-Term (Chronic) Health Effects:

Carcinogenicity:	Contains a probable or known human carcinogen.
Reproductive and Developmental Toxicity:	No data available to indicate product or any components

Inhalation:	present at greater than 0.1% may cause birth defects. Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Harmful! Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs)
Skin Absorption:	Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause severe irritation and systemic damage

Component Toxicological Data:

NIOSH:

Chemical Name	CAS No.	LD50/LC50
Methane, dichloro-	75-09-2	Inhalation LC50 Rat 53 mg/L 6 h

Component Carcinogenic Data:

OSHA:

Chemical Name	CAS No.	
Indeno[1,2,3-cd]pyrene	193-39-5	Present
Methylene chloride	75-09-2	25 ppm TWA (8 hr.); 125 ppm STEL (15 min.); 12.5 ppm Action Level (see 29 CFR 1910.1051); effective date for respiratory protection for certain employers to achieve the 8-hour TWA PEL is August 31, 1998; the start up date to install engineering controls is December 10, 1998.; (OSHA - 29 CFR 1910 Specifically Regulate

ACGIH:

Chemical Name	CAS No.	
Dichloromethane	75-09-2	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans

NIOSH:

Chemical Name	CAS No.	
Methylene chloride	75-09-2	potential occupational carcinogen

NTP:

Chemical Name	CAS No.
No data available	

IARC:

Chemical Name	CAS No.	Group No.
Monograph 110 [in preparation]; Monograph 71 [1999]	75-09-2	Group 2A
Monograph 92 [2010]; Supplement 7 [1987]; Monograph 32 [1983]	193-39-5	Group 2B

12. ECOLOGICAL INFORMATION

Overview:	Moderate ecological hazard. This product may be dangerous to plants and/or wildlife. Keep out of waterways.
Mobility:	No data
Persistence:	No data
Bioaccumulation:	No data
Degradability:	No data
Ecological Toxicity Data:	No data available

13. DISPOSAL CONSIDERATIONS

Waste Description of Spent Product:	Spent or discarded material is a hazardous waste. Mixing spent or discarded material with other materials may render the mixture hazardous. Perform a hazardous waste determination on mixtures.
Disposal Methods:	Incinerate spent or discarded material a permitted hazardous waste facility.
Waste Disposal of Packaging:	Comply with all Local, State, Federal, and Provincial

14. TRANSPORTATION INFORMATION

United States:
DOT Proper Shipping Name: Dichloromethane
UN Number: UN1593
Hazard Class: 6.1
Packing Group: III

International:
IATA Proper Shipping Name: Dichloromethane
UN Number: UN1593
Hazard Class: 6.1
Packing Group: III

Marine Pollutant: No

Chemical Name	CAS#	Marine Pollutant	Severe Marine Pollutant
No data available			

15. REGULATORY INFORMATION

United States:

Chemical Name	CAS#	CERCLA	SARA 313	SARA EHS 313	TSCA
Dichloromethane	75-09-2	X	X	-	X
indeno (1,2,3-c,d) pyrene	193-39-5	X	X	-	X

The following chemicals are listed on CA Prop 65:

Chemical Name	CAS #	Regulation
Indeno[1,2,3-cd]pyrene	193-39-5	Prop 65 Cancer
Dichloromethane Dichloromethane (Methylene chloride)	75-09-2	Prop 65 Cancer

State Right To Know Listing:

Chemical Name	CAS#	New Jersey	Massachusetts	Pennsylvania	California
Dichloromethane	75-09-2	X	X	X	X
indeno (1,2,3-c,d) pyrene	193-39-5	X	X	X	X

16. OTHER INFORMATION

Prior Version Date: 08/03/16

Other Information: Any changes to the SDS compared to previous versions are marked by a vertical line in front of the concerned paragraph.

References: No data available

Disclaimer: Restek Corporation provides the descriptions, data and information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. It is provided for your guidance only. Because many factors may affect processing or application/use, Restek Corporation recommends you perform an assessment to determine the suitability of a product for your particular purpose prior to use. No warranties of any kind, either expressed or implied, including fitness for a particular purpose, are made regarding products described, data or information set forth. In no case shall the descriptions, information, or data provided be considered a part of our terms and conditions of sale. Further, the descriptions, data and information furnished hereunder are given gratis. No obligation or liability for the description, data and information given are assumed. All such being given and accepted at your risk.

SAFETY DATA SHEET

Isopropyl Alcohol

Section 1. Identification


GHS product identifier	: Isopropyl Alcohol
Chemical name	: Isopropyl alcohol
Other means of identification	: isopropanol; 2-Propanol
Product type	: Liquid.
Product use	: Synthetic/Analytical chemistry.
Synonym	: isopropanol; 2-Propanol
SDS #	: 001105
Supplier's details	: Airgas USA, LLC and its affiliates 259 North Radnor-Chester Road Suite 100 Radnor, PA 19087-5283 1-610-687-5253
24-hour telephone	: 1-866-734-3438

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

GHS label elements

Hazard pictograms



Signal word : Danger

Hazard statements : May form explosive mixtures with air.
Highly flammable liquid and vapor.
Causes serious eye irritation.
May cause drowsiness or dizziness.

Precautionary statements

General : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash hands thoroughly after handling.

Response : IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage : Store locked up. Store in a well-ventilated place. Keep cool.

Section 2. Hazards identification

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified :

Section 3. Composition/information on ingredients

Substance/mixture : Substance
Chemical name : Isopropyl alcohol
Other means of identification : isopropanol; 2-Propanol
Product code : 001105

CAS number/other identifiers

CAS number : 67-63-0

Ingredient name	%	CAS number
Isopropyl alcohol	100	67-63-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

Skin contact : No known significant effects or critical hazards.

Section 4. First aid measures

Frostbite : Try to warm up the frozen tissues and seek medical attention.

Ingestion : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following: pain or irritation, watering, redness

Inhalation : Adverse symptoms may include the following: nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness

Skin contact : No specific data.

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Section 6. Accidental release measures

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Avoid contact with eyes, skin and clothing. Do not ingest. Empty containers retain product residue and can be hazardous. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment.

- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Store locked up. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Isopropyl alcohol	ACGIH TLV (United States, 3/2017). TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 400 ppm 8 hours. TWA: 980 mg/m ³ 8 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m ³ 15 minutes.

Section 8. Exposure controls/personal protection

NIOSH REL (United States, 10/2016).

TWA: 400 ppm 10 hours.

TWA: 980 mg/m³ 10 hours.

STEL: 500 ppm 15 minutes.

STEL: 1225 mg/m³ 15 minutes.

OSHA PEL (United States, 6/2016).

TWA: 400 ppm 8 hours.

TWA: 980 mg/m³ 8 hours.

Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

- : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

- : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state

- : Liquid. [COLORLESS LIQUID WITH THE ODOR OF RUBBING ALCOHOL]

Color

- : Colorless.

Odor

- : Alcohol-like.

Odor threshold

- : Not available.

pH

- : Not available.

Section 9. Physical and chemical properties

Melting point	: -90°C (-130°F)
Boiling point	: 83°C (181.4°F)
Critical temperature	: Not available.
Flash point	: Closed cup: 11.7°C (53.1°F)
Evaporation rate	: 1.7 (butyl acetate = 1)
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Lower: 2% Upper: 12%
Vapor pressure	: 4.4 kPa (33 mm Hg) [room temperature]
Vapor density	: 2.1 (Air = 1)
Specific Volume (ft³/lb)	: 1.2739
Gas Density (lb/ft³)	: Not available
Relative density	: 0.79
Solubility	: Not available.
Solubility in water	: Not available.
Partition coefficient: n-octanol/water	: 0.05
Auto-ignition temperature	: 456°C (852.8°F)
Decomposition temperature	: Not available.
Viscosity	: Not available.
Flow time (ISO 2431)	: Not available.
Molecular weight	: 60.11 g/mole

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Hazardous polymerization : Under normal conditions of storage and use, hazardous polymerization will not occur.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Isopropyl alcohol	LC50 Inhalation Gas.	Rat	45248 ppm	1 hours
	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-

Section 11. Toxicological information

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Isopropyl alcohol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	10 milligrams	-
	Eyes - Severe irritant	Rabbit	-	100 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Isopropyl alcohol	-	3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Isopropyl alcohol	Category 3	Not applicable.	Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following: pain or irritation, watering, redness
- Inhalation** : Adverse symptoms may include the following: nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness
- Skin contact** : No specific data.
- Ingestion** : No specific data.

Section 11. Toxicological information

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Isopropyl alcohol	Acute EC50 10100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 1400000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 4200 mg/l Fresh water	Fish - Rasbora heteromorpha	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Isopropyl alcohol	0.05	-	low

Mobility in soil






Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

- Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT	TDG	Mexico	IMDG	IATA
UN number	UN1219	UN1219	UN1219	UN1219	UN1219
UN proper shipping name	ISOPROPANOL OR ISOPROPYL ALCOHOL	ISOPROPANOL; OR ISOPROPYL ALCOHOL	ISOPROPANOL OR ISOPROPYL ALCOHOL	ISOPROPANOL (ISOPROPYL ALCOHOL)	ISOPROPANOL
Transport hazard class(es)	3 	3 	3 	3 	3 
Packing group	II	II	II	II	II
Environmental hazards	No.	No.	No.	No.	No.

“Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product.”

Additional information

- DOT Classification** : **Limited quantity** Yes.
Quantity limitation Passenger aircraft/rail: 5 L. Cargo aircraft: 60 L.
Special provisions IB2, T4, TP1
- TDG Classification** : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).
Explosive Limit and Limited Quantity Index 1
Passenger Carrying Road or Rail Index 5
- IATA** : **Quantity limitation** Passenger and Cargo Aircraft: 5 L. Cargo Aircraft Only: 60 L.
 Limited Quantities - Passenger Aircraft: 1 L.

- Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

- Transport in bulk according to IMO instruments** : Not available.

Section 15. Regulatory information

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

Clean Air Act Section 112 : Not listed

(b) Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Refer to Section 2: Hazards Identification of this SDS for classification of substance.

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Isopropyl alcohol	67-63-0	100
Supplier notification	Isopropyl alcohol	67-63-0	100

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : This material is listed.

New York : This material is not listed.

New Jersey : This material is listed.

Pennsylvania : This material is listed.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : This material is listed or exempted.

Canada : This material is listed or exempted.

China : This material is listed or exempted.

Section 15. Regulatory information

Europe	: This material is listed or exempted.
Japan	: Japan inventory (ENCS) : This material is listed or exempted. Japan inventory (ISHL) : This material is listed or exempted.
New Zealand	: This material is listed or exempted.
Philippines	: This material is listed or exempted.
Republic of Korea	: This material is listed or exempted.
Taiwan	: This material is listed or exempted.
Thailand	: Not determined.
Turkey	: This material is listed or exempted.
United States	: This material is listed or exempted.
Viet Nam	: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	1
Flammability		3
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Expert judgment Expert judgment Expert judgment

History

Date of printing	: 7/16/2020
Date of issue/Date of revision	: 7/16/2020
Date of previous issue	: 8/6/2018

Section 16. Other information

Version : 1.03

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

SAFETY DATA SHEET

Creation Date 22-Sep-2009

Revision Date 24-Dec-2021

Revision Number 4

1. Identification

Product Name 1,3-Dichlorobenzene

Cat No. : AC151180000; AC151180010; AC151180050; AC151180250;
AC151182500; AC151185000

CAS No 541-73-1
Synonyms m-Dichlorobenzene

Recommended Use Laboratory chemicals.
Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 4
Acute oral toxicity	Category 4
Acute Inhalation Toxicity - Vapors	Category 4

Label Elements

Signal Word

Warning

Hazard Statements

Combustible liquid
Harmful if swallowed
Harmful if inhaled

**Precautionary Statements****Prevention**

Wear protective gloves/protective clothing/eye protection/face protection

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Avoid breathing dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Take precautionary measures against static discharge

Inhalation

Call a POISON CENTER or doctor/physician if you feel unwell

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

Fire

Fight fire with normal precautions from a reasonable distance

Storage

Store in a well-ventilated place. Keep cool

Store in a closed container

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Toxic to aquatic life with long lasting effects

3. Composition/Information on Ingredients

Component	CAS No	Weight %
1,3-Dichlorobenzene	541-73-1	98

4. First-aid measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention immediately if symptoms occur.
Inhalation	Remove to fresh air. If breathing is difficult, give oxygen. Get medical attention.
Ingestion	Do NOT induce vomiting. Get medical attention.
Most important symptoms and effects	Difficulty in breathing. . Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Water spray. Carbon dioxide (CO ₂). Dry chemical. Chemical foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	No information available
Flash Point	67 °C / 152.6 °F
Method -	No information available
Autoignition Temperature	640 °C / 1184 °F
Explosion Limits	
Upper	No data available
Lower	No data available
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Combustible material. Containers may explode when heated.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Chlorine. Hydrogen chloride gas.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health
2

Flammability
2

Instability
0

Physical hazards
N/A

6. Accidental release measures

Personal Precautions	Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.
Environmental Precautions	Do not flush into surface water or sanitary sewer system.
Methods for Containment and Clean Up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. Remove all sources of ignition.

7. Handling and storage

Handling	Ensure adequate ventilation. Wear personal protective equipment/face protection. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Avoid contact with skin, eyes or clothing. Avoid breathing dust/fume/gas/mist/vapors/spray.
Storage.	Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Keep away from heat, sparks and flame. Keep containers tightly closed in a dry, cool and well-ventilated place. Incompatible Materials. Metals.

8. Exposure controls / personal protection

Exposure Guidelines	This product does not contain any hazardous materials with occupational exposure limitsestablished by the region specific regulatory bodies.
----------------------------	--

Engineering Measures	Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations
-----------------------------	---

and safety showers are close to the workstation location.

Personal Protective Equipment

Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Light yellow
Odor	Odorless
Odor Threshold	No information available
pH	No information available
Melting Point/Range	-24 °C / -11.2 °F
Boiling Point/Range	172 - 173 °C / 341.6 - 343.4 °F @ 760 mmHg
Flash Point	67 °C / 152.6 °F
Evaporation Rate	No information available
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	2.2 mbar @ 20 °C
Vapor Density	5.07
Specific Gravity	1.280
Solubility	No information available
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	640 °C / 1184 °F
Decomposition Temperature	> 300°C
Viscosity	1.045 cP at 23 °C
Molecular Formula	C6 H4 Cl2
Molecular Weight	147

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Metals
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂), Chlorine, Hydrogen chloride gas
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information**Component Information**

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
1,3-Dichlorobenzene	LD50 = 1100 mg/kg (Rat)	LD50 > 2000 mg/kg (Rabbit)	LC50 > 17.6 mg/L (Rat) 4 h

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation No information available

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
1,3-Dichlorobenzene	541-73-1	Not listed	Not listed	Not listed	Not listed	Not listed

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure None known

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects See actual entry in RTECS for complete information.

12. Ecological information

Ecotoxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
1,3-Dichlorobenzene	EC50: 75.2 - 157 mg/L, 96h (Pseudokirchneriella subcapitata) EC50: 89.4 - 167 mg/L, 72h (Pseudokirchneriella subcapitata)	LC50: = 7.7 mg/L, 96h static (Pimephales promelas) LC50: 3.9 - 6.2 mg/L, 96h static (Lepomis macrochirus) LC50: 6.95 - 9.28 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 130 mg/L 24 h EC50 = 2.9 mg/L 5 min EC50 = 3.29 mg/L 15 min EC50 = 4.2 mg/L 10 min EC50 = 5.10 mg/L 30 min	EC50: = 1.2 mg/L, 48h Static (Daphnia magna) EC50: = 4.2 mg/L, 48h (Daphnia magna)

Persistence and Degradability May persist based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility . Is not likely mobile in the environment due its low water solubility.

Component	log Pow
1,3-Dichlorobenzene	3.38

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
1,3-Dichlorobenzene - 541-73-1	U071	-

14. Transport information

DOT

UN-No UN3082
 Proper Shipping Name Environmentally hazardous substances, liquid, n.o.s.
 Technical Name 1,3-Dichlorobenzene
 Hazard Class 9
 Packing Group III

TDG

UN-No UN3082
 Proper Shipping Name Environmentally hazardous substances, liquid, n.o.s.
 Hazard Class 9
 Packing Group III

IATA

UN-No UN3082
 Proper Shipping Name Environmentally hazardous substances, liquid, n.o.s.
 Hazard Class 9
 Packing Group III

IMDG/IMO

UN-No UN3082
 Proper Shipping Name Environmentally hazardous substances, liquid, n.o.s.
 Hazard Class 9
 Packing Group III

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
1,3-Dichlorobenzene	541-73-1	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
1,3-Dichlorobenzene	541-73-1	X	-	208-792-1	X	X	X	X	X	KE-10067

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations

SARA 313

Component	CAS No	Weight %	SARA 313 - Threshold
-----------	--------	----------	----------------------

			Values %
1,3-Dichlorobenzene	541-73-1	98	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
1,3-Dichlorobenzene	-	-	X	X

Clean Air Act Not applicable

OSHA - Occupational Safety and Health Administration Not applicable

CERCLA This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
1,3-Dichlorobenzene	100 lb	-

California Proposition 65 This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
1,3-Dichlorobenzene	X	X	X	-	-

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant Y
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

Authorisation/Restrictions according to EU REACH

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
1,3-Dichlorobenzene	541-73-1	Listed	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
1,3-Dichlorobenzene	541-73-1	Not applicable	Not applicable	Not applicable	Annex I - Y45

16. Other information

Prepared By	Regulatory Affairs Thermo Fisher Scientific Email: EMSDS.RA@thermofisher.com
Creation Date	22-Sep-2009
Revision Date	24-Dec-2021
Print Date	24-Dec-2021
Revision Summary	This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Creation Date 13-Apr-2009

Revision Date 24-Dec-2021

Revision Number 7

1. Identification

Product Name 2-Butanone

Cat No. : AC149670000; AC149670010; AC149670025; AC149670051;
AC149670250; AC149670251

CAS No 78-93-3
Synonyms Methyl ethyl ketone; MEK; Ethyl methyl ketone

Recommended Use Laboratory chemicals.
Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Central nervous system (CNS).	
Specific target organ toxicity - (repeated exposure)	Category 2
Target Organs - Kidney, Liver.	

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor
Causes serious eye irritation
May cause drowsiness or dizziness
May cause damage to organs through prolonged or repeated exposure

**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling
Do not breathe dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Wear protective gloves/protective clothing/eye protection/face protection
Keep cool

Response

Get medical attention/advice if you feel unwell

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Repeated exposure may cause skin dryness or cracking

Other hazards

Contains a known or suspected endocrine disruptor.

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Methyl ethyl ketone	78-93-3	>95

4. First-aid measures

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

	medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.
Inhalation	Remove to fresh air. Get medical attention if symptoms occur. If not breathing, give artificial respiration.
Ingestion	Do NOT induce vomiting. Get medical attention.
Most important symptoms and effects	Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	CO ₂ , dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	Water may be ineffective
Flash Point	-7 °C / 19.4 °F
Method -	CC (closed cup)
Autoignition Temperature	404 °C / 759.2 °F
Explosion Limits	
Upper	11.4 vol %
Lower	1.4 vol %
Oxidizing Properties	Not oxidising
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
2	3	1	N/A

6. Accidental release measures

Personal Precautions	Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation.
Environmental Precautions	Avoid release to the environment. See Section 12 for additional Ecological Information.
Methods for Containment and Clean Up	Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling	Wear personal protective equipment/face protection. Ensure adequate ventilation. Use spark-proof tools and explosion-proof equipment. Avoid contact with skin, eyes or clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.
Storage.	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area. Incompatible Materials. Strong oxidizing agents. Strong acids. Strong bases. Strong reducing agents. Ammonia. copper. Amines.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Methyl ethyl ketone	TWA: 200 ppm STEL: 300 ppm	(Vacated) TWA: 200 ppm (Vacated) TWA: 590 mg/m ³ (Vacated) STEL: 300 ppm (Vacated) STEL: 885 mg/m ³ TWA: 200 ppm TWA: 590 mg/m ³	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³	TWA: 200 ppm STEL: 300 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures	Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location.
-----------------------------	--

Personal Protective Equipment

Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Colorless
Odor	Characteristic - sweet
Odor Threshold	No information available
pH	No information available
Melting Point/Range	-87 °C / -124.6 °F
Boiling Point/Range	80 °C / 176 °F
Flash Point	-7 °C / 19.4 °F
Method -	CC (closed cup)

Evaporation Rate	3.7
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	11.4 vol %
Lower	1.4 vol %
Vapor Pressure	105 mbar @ 20 °C
Vapor Density	2.41
Specific Gravity	0.806
Solubility	Soluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	404 °C / 759.2 °F
Decomposition Temperature	No information available
Viscosity	0.42 mPa.s @ 15°C
Molecular Formula	C4 H8 O
Molecular Weight	72.11

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Hygroscopic.
Conditions to Avoid	Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition. Exposure to moist air or water.
Incompatible Materials	Strong oxidizing agents, Strong acids, Strong bases, Strong reducing agents, Ammonia, copper, Amines
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂)
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl ethyl ketone	LD50 = 2483 mg/kg (Rat)	LD50 = 5000 mg/kg (Rabbit)	LC50 = 11700 ppm (Rat) 4 h

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	Irritating to eyes
Sensitization	No information available
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Methyl ethyl ketone	78-93-3	Not listed	Not listed	Not listed	Not listed	Not listed

Mutagenic Effects Not mutagenic in AMES Test

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity	No information available.
STOT - single exposure STOT - repeated exposure	Central nervous system (CNS) Kidney Liver
Aspiration hazard	No information available
Symptoms / effects, both acute and delayed	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Endocrine Disruptor Information	No information available
Other Adverse Effects	The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Methyl ethyl ketone	Not listed	Lepomis macrochirus: LC50=3,22 g/L 96 h	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50: = 5091 mg/L, 48h (Daphnia magna) EC50: 4025 - 6440 mg/L, 48h Static (Daphnia magna) EC50: > 520 mg/L, 48h (Daphnia magna)

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
Methyl ethyl ketone	0.29

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl ethyl ketone - 78-93-3	U159	-

14. Transport information

DOT

UN-No	UN1193
Proper Shipping Name	Ethyl methyl ketone
Hazard Class	3
Packing Group	II

TDG

UN-No	UN1193
Proper Shipping Name	ETHYL METHYL KETONE
Hazard Class	3
Packing Group	II

IATA

UN-No	UN1193
Proper Shipping Name	Methyl ethyl ketone
Hazard Class	3

Packing Group	II
IMDG/IMO	
UN-No	UN1193
Proper Shipping Name	Ethyl methyl ketone (Methyl ethyl ketone)
Hazard Class	3
Packing Group	II

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Methyl ethyl ketone	78-93-3	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Methyl ethyl ketone	78-93-3	X	-	201-159-0	X	X	X	X	X	KE-24094

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

OSHA - Occupational Safety and Health Administration Not applicable

CERCLA This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Methyl ethyl ketone	5000 lb	-

California Proposition 65 This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Methyl ethyl ketone	X	X	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl ethyl ketone	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Methyl ethyl ketone	78-93-3	Listed	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Methyl ethyl ketone	78-93-3	Not applicable	Not applicable	Not applicable	Annex I - Y42

16. Other information

Prepared By Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Creation Date 13-Apr-2009
Revision Date 24-Dec-2021
Print Date 24-Dec-2021

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Creation Date 13-April-2009

Revision Date 24-December-2021

Revision Number 7

1. Identification

Product Name Methyl Ethyl Ketone

Cat No. : M208-1, M208-20, M208-4

CAS-No 78-93-3

Synonyms 2-Butanone; MEK; Ethyl methyl ketone

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Importer/Distributor

Fisher Scientific
112 Colonnade Road,
Ottawa, ON K2E 7L6,
Canada
Tel: 1-800-234-7437

Manufacturer

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Emergency Telephone Number CHEMTREC®, Inside the USA: 800-424-9300
CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Central nervous system (CNS).	
Specific target organ toxicity - (repeated exposure)	Category 2
Target Organs - Kidney, Liver.	
Health Hazards Not Otherwise Classified	Category 1
Prolonged or repeated contact may dry skin and cause irritation or cracking	

Label Elements

Signal Word
Danger

Hazard Statements

Highly flammable liquid and vapor
Causes serious eye irritation
May cause drowsiness and dizziness
May cause damage to organs through prolonged or repeated exposure
Prolonged or repeated contact may dry skin and cause irritation or cracking

**Precautionary Statements****Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Take precautionary measures against static discharges
Do not breathe dust/fumes/gas/mist/vapours/spray
Wash face, hands and any exposed skin thoroughly after handling
Use only outdoors or in a well-ventilated area
Wear protective gloves/protective clothing/eye protection/face protection

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower
IF INHALED: Remove person to fresh air and keep comfortable for breathing
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Call a POISON CENTER/ doctor if you feel unwell
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Contains a known or suspected endocrine disruptor

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Methyl ethyl ketone	78-93-3	>95

4. First-aid measures

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.

Inhalation

Remove to fresh air. Get medical attention if symptoms occur. If not breathing, give artificial respiration.

Ingestion	Do NOT induce vomiting. Get medical attention.
Most important symptoms/effects	Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	CO ₂ , dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	Water may be ineffective
Flash Point	-7 °C / 19.4 °F
Method -	CC (closed cup)
Autoignition Temperature	404 °C / 759.2 °F
Explosion Limits	
Upper	11.4 vol %
Lower	1.4 vol %
Oxidizing Properties	Not oxidising
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
2	3	1	N/A

6. Accidental release measures

Personal Precautions	Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation.
Environmental Precautions	Avoid release to the environment. See Section 12 for additional Ecological Information.
Methods for Containment and Clean Up	Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling	Wear personal protective equipment/face protection. Ensure adequate ventilation. Use spark-proof tools and explosion-proof equipment. Avoid contact with skin, eyes or clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only non-sparking
-----------------	---

tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Storage.

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area. Incompatible Materials. Strong oxidizing agents. Strong acids. Strong bases. Strong reducing agents. Ammonia. copper. Amines.

8. Exposure controls / personal protection

Exposure Guidelines

Component	Alberta	British Columbia	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH IDLH
Methyl ethyl ketone	TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³	TWA: 50 ppm STEL: 100 ppm	TWA: 200 ppm STEL: 300 ppm	TWA: 50 ppm TWA: 150 mg/m ³ STEL: 100 ppm STEL: 300 mg/m ³	TWA: 200 ppm STEL: 300 ppm	(Vacated) TWA: 200 ppm (Vacated) TWA: 590 mg/m ³ (Vacated) STEL: 300 ppm (Vacated) STEL: 885 mg/m ³ TWA: 200 ppm TWA: 590 mg/m ³	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment**Eye Protection**

Goggles

Hand Protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Butyl rubber	< 60 minutes	0.5 mm	Permeation rate 36 µg/cm ² /min As tested under EN374-3 Determination of Resistance to Permeation by Chemicals

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended Filter type: Type A Organic gases and vapours filter Brown conforming to EN14387

Environmental exposure controls

No information available.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Colorless
Odor	Characteristic - sweet
Odor Threshold	No information available
pH	No information available
Melting Point/Range	-87 °C / -124.6 °F
Boiling Point/Range	80 °C / 176 °F
Flash Point	-7 °C / 19.4 °F
Method -	CC (closed cup)
Evaporation Rate	3.7
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	11.4 vol %
Lower	1.4 vol %
Vapor Pressure	105 mbar @ 20 °C
Vapor Density	2.41
Specific Gravity	0.806
Solubility	Soluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	404 °C / 759.2 °F
Decomposition Temperature	No information available
Viscosity	0.42 mPa.s @ 15°C
Molecular Formula	C ₄ H ₈ O
Molecular Weight	72.11

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Hygroscopic.
Conditions to Avoid	Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition. Exposure to moist air or water.
Incompatible Materials	Strong oxidizing agents, Strong acids, Strong bases, Strong reducing agents, Ammonia, copper, Amines
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂)
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity**Product Information****Component Information**

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl ethyl ketone	LD50 = 2483 mg/kg (Rat)	LD50 = 5000 mg/kg (Rabbit)	LC50 = 11700 ppm (Rat) 4 h

Toxicologically Synergistic Products	No information available						
<u>Delayed and immediate effects as well as chronic effects from short and long-term exposure</u>							
Irritation	Irritating to eyes						
Sensitization	No information available						
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.						
	Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
	Methyl ethyl ketone	78-93-3	Not listed	Not listed	Not listed	Not listed	Not listed
Mutagenic Effects	Not mutagenic in AMES Test						
Reproductive Effects	No information available.						
Developmental Effects	No information available.						
Teratogenicity	No information available.						
STOT - single exposure	Central nervous system (CNS)						
STOT - repeated exposure	Kidney Liver						
Aspiration hazard	No information available						
Symptoms / effects,both acute and delayed	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting						
Endocrine Disruptor Information	No information available						
Other Adverse Effects	The toxicological properties have not been fully investigated.						

12. Ecological information

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Methyl ethyl ketone	Not listed	Lepomis macrochirus: LC50=3,22 g/L 96 h	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50: = 5091 mg/L, 48h (Daphnia magna) EC50: 4025 - 6440 mg/L, 48h Static (Daphnia magna) EC50: > 520 mg/L, 48h (Daphnia magna)

Persistence and Degradability	Persistence is unlikely based on information available.
Bioaccumulation/ Accumulation	No information available.
Mobility	Will likely be mobile in the environment due to its volatility.

Component	log Pow
Methyl ethyl ketone	0.29

13. Disposal considerations

Waste Disposal Methods	Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.
-------------------------------	---

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl ethyl ketone - 78-93-3	U159	-

14. Transport information

DOT

UN-No	UN1193
Proper Shipping Name	Ethyl methyl ketone
Hazard Class	3
Packing Group	II

TDG

UN-No	UN1193
Proper Shipping Name	ETHYL METHYL KETONE
Hazard Class	3
Packing Group	II

IATA

UN-No	UN1193
Proper Shipping Name	Methyl ethyl ketone
Hazard Class	3
Packing Group	II

IMDG/IMO

UN-No	UN1193
Proper Shipping Name	Ethyl methyl ketone (Methyl ethyl ketone)
Hazard Class	3
Packing Group	II

15. Regulatory information

International Inventories

Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification - Active-Inactive	EINECS	ELINCS	NLP
Methyl ethyl ketone	78-93-3	X	-	X	ACTIVE	201-159-0	-	-

Component	CAS-No	IECSC	KECL	ENCs	ISHL	TCSI	AICS	NZIoC	PICCS
Methyl ethyl ketone	78-93-3	X	KE-24094	X	X	X	X	X	X

Legend:

X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

ENCs - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
Methyl ethyl ketone	Part 1, Group A Substance Part 5, Individual Substances Part 4 Substance		

Other International Regulations

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl ethyl ketone	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Methyl ethyl ketone	78-93-3	Listed	Not applicable	Not applicable	Not applicable

Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Methyl ethyl ketone	78-93-3	Not applicable	Not applicable	Not applicable	Annex I - Y42

16. Other information

Prepared By Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Creation Date 13-April-2009
Revision Date 24-December-2021
Print Date 24-December-2021
Revision Summary This document has been updated to comply with the requirements of WHMIS 2015 to align with the Globally Harmonised System (GHS) for the Classification and Labelling of Chemicals.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Creation Date 13-Nov-2013

Revision Date 24-Dec-2021

Revision Number 5

1. Identification

Product Name **Methyl methacrylate**

Cat No. : **AC127140000; AC127140010; AC127140025; AC127140100; AC127140250**

CAS No 80-62-6
Synonyms MMA

Recommended Use Laboratory chemicals.
Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Skin Sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system.	

Label Elements

Signal Word
Danger

Hazard Statements

Highly flammable liquid and vapor
Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
May cause respiratory irritation

**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell

Skin

If skin irritation or rash occurs: Get medical advice/attention
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None identified

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Methyl methacrylate	80-62-6	>95

4. First-aid measures

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

	medical attention.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. In the case of skin irritation or allergic reactions see a physician.
Inhalation	Remove from exposure, lie down. Remove to fresh air. If not breathing, give artificial respiration. Get medical attention.
Ingestion	Do NOT induce vomiting. Clean mouth with water. Get medical attention.
Most important symptoms and effects	May cause allergic skin reaction. Difficulty in breathing. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Carbon dioxide (CO ₂). Foam. Dry chemical. Water mist may be used to cool closed containers. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	No information available
Flash Point	8 °C / 46.4 °F
Method -	No information available
Autoignition Temperature	430 °C / 806 °F
Explosion Limits	
Upper	12.5%
Lower	2.1%
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health
2

Flammability
3

Instability
2

Physical hazards
N/A

6. Accidental release measures

Personal Precautions	Remove all sources of ignition. Take precautionary measures against static discharges.
Environmental Precautions	Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.
Methods for Containment and Clean Up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Do not let this chemical enter the environment.

7. Handling and storage

Handling	Avoid contact with skin and eyes. Do not breathe mist/vapors/spray. Handle product only in closed system or provide appropriate exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. Keep away from open flames, hot surfaces and sources of ignition. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.
Storage.	Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Keep away from heat, sparks and flame. Refrigerator/flammables. Incompatible Materials. Acids. Bases. Amines. Halogens. Peroxides. Reducing Agent.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Methyl methacrylate	TWA: 50 ppm STEL: 100 ppm	(Vacated) TWA: 100 ppm (Vacated) TWA: 410 mg/m ³ TWA: 100 ppm TWA: 410 mg/m ³	IDLH: 1000 ppm TWA: 100 ppm TWA: 410 mg/m ³	TWA: 50 ppm STEL: 100 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures	Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.
-----------------------------	--

Personal Protective Equipment

Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Colorless
Odor	Strong
Odor Threshold	No information available
pH	No information available
Melting Point/Range	-48 °C / -54.4 °F
Boiling Point/Range	100 °C / 212 °F @ 760 mmHg
Flash Point	8 °C / 46.4 °F
Evaporation Rate	No information available
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	

Upper	12.5%
Lower	2.1%
Vapor Pressure	40 mbar @ 20 °C
Vapor Density	3.5 (Air = 1.0)
Specific Gravity	0.930
Solubility	No information available
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	430 °C / 806 °F
Decomposition Temperature	No information available
Viscosity	0.6 mPa s at 20 °C
Molecular Formula	C5 H8 O2
Molecular Weight	100.12

10. Stability and reactivity

Reactive Hazard	Yes
Stability	Stable under normal conditions. Hazardous polymerization may occur upon depletion of inhibitor.
Conditions to Avoid	Keep away from open flames, hot surfaces and sources of ignition. Excess heat. Exposure to light. Incompatible products.
Incompatible Materials	Acids, Bases, Amines, Halogens, Peroxides, Reducing Agent
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂)
Hazardous Polymerization	Hazardous polymerization may occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl methacrylate	LD50 8420 - 10000 mg/kg (Rat)	LD50 5000 - 7500 mg/kg (Rabbit)	LC50 = 29.8 mg/L (Rat) 4 h

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	Irritating to eyes, respiratory system and skin
Sensitization	May cause sensitization by skin contact
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Methyl methacrylate	80-62-6	Not listed	Not listed	Not listed	Not listed	Not listed

Mutagenic Effects Mutagenic effects have occurred in experimental animals.

Reproductive Effects Experiments have shown reproductive toxicity effects on laboratory animals.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Respiratory system

STOT - repeated exposure	None known
Aspiration hazard	No information available
Symptoms / effects, both acute and delayed	Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Endocrine Disruptor Information	No information available
Other Adverse Effects	The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Do not empty into drains. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment. Contains a substance which is: Harmful to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Methyl methacrylate	EC50: = 170 mg/L, 96h (Pseudokirchneriella subcapitata)	LC50: 326.4 - 426.9 mg/L, 96h static (Poecilia reticulata) LC50: > 79 mg/L, 96h static (Oncorhynchus mykiss) LC50: > 79 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: 153.9 - 341.8 mg/L, 96h static (Lepomis macrochirus) LC50: 170 - 206 mg/L, 96h flow-through (Lepomis macrochirus) LC50: 125.5 - 190.7 mg/L, 96h static (Pimephales promelas) LC50: 243 - 275 mg/L, 96h flow-through (Pimephales promelas)	Not listed	EC50: = 69 mg/L, 48h (Daphnia magna)

Persistence and Degradability	Persistence is unlikely
Bioaccumulation/ Accumulation	No information available.
Mobility	. Will likely be mobile in the environment due to its water solubility.

Component	log Pow
Methyl methacrylate	0.7

13. Disposal considerations

Waste Disposal Methods	Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.
-------------------------------	---

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl methacrylate - 80-62-6	U162	-

14. Transport information

DOT

UN-No

UN1247

Proper Shipping Name	METHYL METHACRYLATE MONOMER, STABILIZED
Hazard Class	3
Packing Group	II
TDG	
UN-No	UN1247
Proper Shipping Name	METHYL METHACRYLATE MONOMER, STABILIZED
Hazard Class	3
Packing Group	II
IATA	
UN-No	UN1247
Proper Shipping Name	METHYL METHACRYLATE MONOMER, STABILIZED
Hazard Class	3
Packing Group	II
IMDG/IMO	
UN-No	UN1247
Proper Shipping Name	METHYL METHACRYLATE MONOMER, STABILIZED
Hazard Class	3
Packing Group	II

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Methyl methacrylate	80-62-6	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

- - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Methyl methacrylate	80-62-6	X	-	201-297-1	X	X	X	X	X	KE-25050

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations

SARA 313

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Methyl methacrylate	80-62-6	>95	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Methyl methacrylate	X	1000 lb	-	-

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl methacrylate	X		-

OSHA - Occupational Safety and Health Administration

Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Methyl methacrylate	1000 lb	-

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Methyl methacrylate	X	X	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y

DOT Marine Pollutant N

DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade

No information available

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl methacrylate	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Methyl methacrylate	80-62-6	Listed	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Methyl methacrylate	80-62-6	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By

Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Creation Date 13-Nov-2013**Revision Date** 24-Dec-2021**Print Date** 24-Dec-2021**Revision Summary** This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Version 6.5
Revision Date 05/07/2021
Print Date 03/19/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name : Naphthalene

Product Number : 147141
Brand : Aldrich
Index-No. : 601-052-00-2
CAS-No. : 91-20-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable solids (Category 2), H228
Acute toxicity, Oral (Category 4), H302
Carcinogenicity (Category 2), H351
Short-term (acute) aquatic hazard (Category 1), H400
Long-term (chronic) aquatic hazard (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Warning

Aldrich - 147141

Page 1 of 11

Hazard statement(s)	
H228	Flammable solid.
H302	Harmful if swallowed.
H351	Suspected of causing cancer.
H410	Very toxic to aquatic life with long lasting effects.
Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula	: C ₁₀ H ₈
Molecular weight	: 128.17 g/mol
CAS-No.	: 91-20-3
EC-No.	: 202-049-5
Index-No.	: 601-052-00-2

Component	Classification	Concentration
Naphthalene		
	Flam. Sol. 2; Acute Tox. 4; Carc. 2; Aquatic Acute 1; Aquatic Chronic 1; H228, H302, H351, H400, H410	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air on intense heating.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Keep away from heat and sources of ignition.

Storage class (TRGS 510): 4.1B: Flammable solid hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Naphthalene	91-20-3	TWA	10 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Confirmed animal carcinogen with unknown relevance to humans Danger of cutaneous absorption		

		TWA	10 ppm 50 mg/m3	USA. NIOSH Recommended Exposure Limits
		ST	15 ppm 75 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	10 ppm 50 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	0.1 ppm 0.5 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		Skin		

Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Naphthalene	91-20-3	1-Naphthol + 2-Naphthol			ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (As soon as possible after exposure ceases)			

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: KCL 741 Dermatril® L

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: KCL 741 Dermatril® L

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when dusts are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

a) Appearance	Form: flakes, granules Color: white
b) Odor	aromatic
c) Odor Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	Melting point/range: 80 - 82 °C (176 - 180 °F) - lit.
f) Initial boiling point and boiling range	218 °C 424 °F - lit.
g) Flash point	78.5 °C (173.3 °F) - closed cup - ISO 2719
h) Evaporation rate	No data available
i) Flammability (solid, gas)	The substance or mixture is a flammable solid with the category 2. - Flammability (solids)
j) Upper/lower flammability or explosive limits	Upper explosion limit: 5.9 %(V) Lower explosion limit: 0.9 %(V)
k) Vapor pressure	0.072 hPa at 20 °C (68 °F) - OECD Test Guideline 104
l) Vapor density	No data available
m) Relative density	No data available
n) Water solubility	0.0308 g/l at 25 °C (77 °F) - OECD Test Guideline 105 - slightly soluble
o) Partition coefficient: n-octanol/water	log Pow: 3.4 at 25 °C (77 °F) - OECD Test Guideline 107 - Bioaccumulation is not expected.
p) Autoignition temperature	526 - 587 °C (979 - 1089 °F) at 1,013 hPa - DIN 51794
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

SECTION 10: Stability and reactivity

10.1 Reactivity

Forms explosive mixtures with air on intense heating.

A range from approx. 15 Kelvin below the flash point is to be rated as critical.

The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally be assumed.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Violent reactions possible with:

Oxidizing agents

chromium(VI) oxide

benzoyl chloride

aluminium chloride

Risk of explosion with:

nitrogen oxides

10.4 Conditions to avoid

Heat, flames and sparks.

Strong heating.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Mouse - female - 710 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - > 0.4 mg/l

(OECD Test Guideline 403)

LD50 Dermal - Rabbit - 20,000 mg/kg

Remarks: (RTECS)

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 24 h

Remarks: (ECHA)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation - 24 h

Remarks: (ECHA)

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Chinese hamster ovary cells

Metabolic activation: Metabolic activation

Method: OECD Test Guideline 473

Result: positive

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: unscheduled DNA synthesis assay

Species: Rat

Cell type: Liver cells

Application Route: Oral

Method: OECD Test Guideline 486

Result: negative

Test Type: Micronucleus test

Species: Mouse

Cell type: Bone marrow

Application Route: Intraperitoneal

Method: US-EPA

Result: negative

Remarks: (ECHA)

Carcinogenicity

Suspected of causing cancer.

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Naphthalene)

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
(Naphthalene)

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 91 Days - NOAEL (No observed adverse effect level) - 200 mg/kg - LOAEL (Lowest observed adverse effect level) - 400 mg/kg

Repeated dose toxicity - Mouse - male and female - Oral - 90 Days - NOAEL (No observed adverse effect level) - 100 mg/kg

Repeated dose toxicity - Rat - male and female - Dermal - 90 Days - NOAEL (No observed adverse effect level) - 1,000 mg/kg

Repeated dose toxicity - Rat - male and female - inhalation (vapor) - 90 Days - NOAEL (No observed adverse effect level) - 300 mg/kg

RTECS: QJ0525000

Absorption into the body leads to the formation of methemoglobin which in sufficient concentration causes cyanosis. Onset may be delayed 2 to 4 hours or longer., Naphthalene is retinotoxic and systemic absorption of its vapors above 15ppm, may result in: cataracts, optic neuritis, corneal injury, Eye irritation, Ingestion may provoke the following symptoms: hemolytic anemia, hemoglobinuria, Nausea, Headache, Vomiting, Gastrointestinal disturbance, Convulsions, anemia, Kidney injury may occur., Seizures., Coma.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Heart -

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	flow-through test LC50 - Oncorhynchus mykiss (rainbow trout) - 1.6 mg/l - 96 h (OECD Test Guideline 203)
	flow-through test LC50 - Pimephales promelas (fathead minnow) - 7.9 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	static test EC50 - Daphnia magna (Water flea) - 2.16 mg/l - 48 h (OECD Test Guideline 202)
Toxicity to algae	static test EC50 - Pseudokirchneriella subcapitata (green algae) - 2.96 mg/l - 4 h Remarks: (ECHA)

12.2 Persistence and degradability

Biodegradability	aerobic - Exposure time 28 d Result: 2 % - Not readily biodegradable. (OECD Test Guideline 302C)
------------------	--

12.3 Bioaccumulative potential

Bioaccumulation	Cyprinus carpio (Carp) - 56 d
-----------------	-------------------------------

Aldrich - 147141

Page 9 of 11

at 25 °C(Naphthalene)

Bioconcentration factor (BCF): 36.5 - 168
(OECD Test Guideline 305)

Remarks: Bioaccumulation is unlikely.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

DOT (US)

UN number: 1334 Class: 4.1 Packing group: III

Proper shipping name: Naphthalene, refined

Reportable Quantity (RQ): 100 lbs

1) Marine pollutant: yes Poison Inhalation Hazard: No

IMDG

UN number: 1334 Class: 4.1 Packing group: III

EMS-No: F-A, S-G

Proper shipping name: NAPHTHALENE, REFINED

Marine pollutant : yes

IATA

UN number: 1334 Class: 4.1 Packing group: III

Proper shipping name: Naphthalene, refined

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information**Further information**

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.5

Revision Date: 05/07/2021

Print Date: 03/19/2022

SAFETY DATA SHEET

Creation Date 15-Jun-2010

Revision Date 24-Dec-2021

Revision Number 8

1. Identification

Product Name o-Xylene

Cat No. : O5081-4; O5081-4LC; O5081-500; O5081FB-200; DO5081-500

CAS No 95-47-6

Synonyms 1,2-Dimethylbenzene (Certified)

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet**Company**

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Emergency Telephone Number CHEMTREC®, Inside the USA: 800-424-9300
CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification**Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 3
Acute dermal toxicity	Category 4
Acute Inhalation Toxicity - Vapors	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system, Central nervous system (CNS).	
Specific target organ toxicity - (repeated exposure)	Category 2
Target Organs - Liver.	
Aspiration Toxicity	Category 1

Label Elements

Signal Word
Danger

Hazard Statements

Flammable liquid and vapor
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye irritation
May cause respiratory irritation
May cause drowsiness or dizziness
May cause damage to organs through prolonged or repeated exposure
Harmful in contact with skin or if inhaled

**Precautionary Statements****Prevention**

Wear protective gloves/protective clothing/eye protection/face protection
Use only outdoors or in a well-ventilated area
Wash face, hands and any exposed skin thoroughly after handling
Do not breathe dust/fume/gas/mist/vapors/spray
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Response

Get medical attention/advice if you feel unwell

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell

Skin

Call a POISON CENTER or doctor/physician if you feel unwell
If skin irritation occurs: Get medical advice/attention
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Harmful to aquatic life with long lasting effects

3. Composition/Information on Ingredients

Component	CAS No	Weight %
o-Xylene	95-47-6	>95

4. First-aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Most important symptoms and effects	Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire
Flash Point	31 °C / 87.8 °F
Method -	No information available
Autoignition Temperature	465 °C / 869 °F
Explosion Limits	
Upper	6.7 vol %
Lower	0.9 vol %
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health
3

Flammability
3

Instability
0

Physical hazards
N/A

6. Accidental release measures

Personal Precautions	Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
Environmental Precautions	Should not be released into the environment. See Section 12 for additional Ecological Information. Avoid release to the environment. Collect spillage. Do not flush into surface water or sanitary sewer system.
Methods for Containment and Clean Up	Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling	Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.
Storage.	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area. Incompatible Materials. Strong oxidizing agents. Strong acids.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
o-Xylene	TWA: 100 ppm STEL: 150 ppm		IDLH: 900 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³	TWA: 100 ppm STEL: 150 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists
NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures	Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment.
-----------------------------	--

Personal Protective Equipment

Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Colorless

Odor	aromatic
Odor Threshold	No information available
pH	Not applicable
Melting Point/Range	-25 °C / -13 °F
Boiling Point/Range	143 - 145 °C / 289.4 - 293 °F
Flash Point	31 °C / 87.8 °F
Evaporation Rate	0.7
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	6.7 vol %
Lower	0.9 vol %
Vapor Pressure	882 Pa @ 25 °C
Vapor Density	3.7
Specific Gravity	0.884
Solubility	No information available
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	465 °C / 869 °F
Decomposition Temperature	No information available
Viscosity	0.81 mPas @ 20°C
Molecular Formula	C8 H10
Molecular Weight	106.17

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Strong oxidizing agents, Strong acids
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂)
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
o-Xylene	LD50 = 3608 mg/kg (Rat)	14100 mg/kg (Rabbit)	LC50 = 4330 ppm (Rat) 6 h

Toxicologically Synergistic Products	No information available
--------------------------------------	--------------------------

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	Irritating to eyes and skin
Sensitization	No information available
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
o-Xylene	95-47-6	Not listed	Not listed	Not listed	Not listed	Not listed

Mutagenic Effects	No information available
-------------------	--------------------------

Reproductive Effects	No information available.
Developmental Effects	No information available.
Teratogenicity	No information available.
STOT - single exposure	Respiratory system Central nervous system (CNS)
STOT - repeated exposure	Liver
Aspiration hazard	Category 1
Symptoms / effects, both acute and delayed	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting
Endocrine Disruptor Information	No information available
Other Adverse Effects	The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Do not empty into drains. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
o-Xylene	EC50: = 4.7 mg/L, 72h static (Pseudokirchneriella subcapitata)	LC50: 16.1 mg/L/96h (Lepomis macrochirus) LC50: 13 mg/L/24h (Carassius auratus)	EC50 = 0.0084 mg/L 24 h	EC50: 0.78 - 2.51 mg/L, 48h Static (Daphnia magna) EC50: 2.61 - 5.59 mg/L, 48h Flow through (Daphnia magna) EC50: = 3.2 mg/L, 48h (Daphnia magna)

Persistence and Degradability Insoluble in water Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
o-Xylene	3.12

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No	UN1307
Proper Shipping Name	XYLENES
Hazard Class	3
Packing Group	III

TDG

UN-No	UN1307
Proper Shipping Name	XYLENES
Hazard Class	3
Packing Group	III

IATA

UN-No	UN1307
--------------	--------

Proper Shipping Name Xylenes
 Hazard Class 3
 Packing Group III

IMDG/IMO

UN-No UN1307
 Proper Shipping Name Xylenes
 Hazard Class 3
 Packing Group III

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
o-Xylene	95-47-6	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
o-Xylene	95-47-6	X	-	202-422-2	X	X	X	X	X	KE-35429

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations**SARA 313**

Component	CAS No	Weight %	SARA 313 - Threshold Values %
o-Xylene	95-47-6	>95	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
o-Xylene	X	-	-	-

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
o-Xylene	X		-

OSHA - Occupational Safety and Health Administration Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
o-Xylene	1000 lb	-

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
o-Xylene	X	X	X	X	-

U.S. Department of Transportation

Reportable Quantity (RQ): Y
 DOT Marine Pollutant N
 DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations**Mexico - Grade**

No information available

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
o-Xylene	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
o-Xylene	95-47-6	Listed	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
o-Xylene	95-47-6	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By

Regulatory Affairs
 Thermo Fisher Scientific
 Email: EMSDS.RA@thermofisher.com

Creation Date

15-Jun-2010

Revision Date

24-Dec-2021

Print Date

24-Dec-2021

Revision Summary

SDS sections updated. 11. 16.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information

relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Creation Date 09-May-2014

Revision Date 24-Dec-2021

Revision Number 4

1. Identification

Product Name o-Dichlorobenzene (Certified)

Cat No. : O2231-1

Synonyms 1,2-Dichlorobenzene

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Emergency Telephone Number CHEMTREC®, Inside the USA: 800-424-9300
CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 4
Acute oral toxicity	Category 4
Acute Inhalation Toxicity - Vapors	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Skin Sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system.	

Label Elements

Signal Word
Warning

Hazard Statements
Combustible liquid
Harmful if swallowed

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
Harmful if inhaled
May cause respiratory irritation

**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Wear protective gloves/protective clothing/eye protection/face protection
Contaminated work clothing should not be allowed out of the workplace
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep cool

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell

Skin

IF ON SKIN: Wash with plenty of soap and water
Take off contaminated clothing and wash before reuse
If skin irritation or rash occurs: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
Rinse mouth

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Very toxic to aquatic life with long lasting effects

3. Composition/Information on Ingredients

Component	CAS No	Weight %
o-Dichlorobenzene	95-50-1	99

4. First-aid measures

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

	medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Ingestion	Clean mouth with water and drink afterwards plenty of water.
Most important symptoms and effects	Difficulty in breathing. May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	No information available
Flash Point	67 °C / 152.6 °F
Method -	No information available
Autoignition Temperature	640 °C / 1184 °F
Explosion Limits	
Upper	12.00 vol %
Lower	2.20 vol %
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Combustible material. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition. Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Chlorine. Hydrogen chloride gas.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
2	2	0	N/A

6. Accidental release measures

Personal Precautions	Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
Environmental Precautions	Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.
Methods for Containment and Clean	Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

Up Remove all sources of ignition.

7. Handling and storage

Handling Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Ensure adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition.

Storage. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Incompatible Materials. Strong oxidizing agents. Metals.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
o-Dichlorobenzene	TWA: 25 ppm STEL: 50 ppm	Ceiling: 50 ppm Ceiling: 300 mg/m ³ (Vacated) Ceiling: 50 ppm (Vacated) Ceiling: 300 mg/m ³	IDLH: 200 ppm Ceiling: 50 ppm Ceiling: 300 mg/m ³	TWA: 20 ppm STEL: 50 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures When using do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Light yellow
Odor	aromatic
Odor Threshold	No information available
pH	No information available
Melting Point/Range	-15 °C / 5 °F
Boiling Point/Range	179 - 180 °C / 354.2 - 356 °F @ 760 mmHg
Flash Point	67 °C / 152.6 °F
Evaporation Rate	< 1 (Butyl Acetate = 1.0)
Flammability (solid,gas)	Not applicable

Flammability or explosive limits

Upper	12.00 vol %
Lower	2.20 vol %
Vapor Pressure	1.15 mmHg @ 20 °C
Vapor Density	5.05 (Air = 1.0)
Specific Gravity	1.30
Solubility	Insoluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	640 °C / 1184 °F
Decomposition Temperature	No information available
Viscosity	No information available
Molecular Formula	C ₆ H ₄ Cl ₂
Molecular Weight	147.00

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions. Light sensitive.
Conditions to Avoid	Keep away from open flames, hot surfaces and sources of ignition. Incompatible products. Exposure to light.
Incompatible Materials	Strong oxidizing agents, Metals
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂), Chlorine, Hydrogen chloride gas
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity**Product Information****Component Information**

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
o-Dichlorobenzene	LD50 = 1516 mg/kg (Rat)	LD50 > 10 g/kg (Rabbit)	14,04 mg/L/4h (Rat)

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	Irritating to eyes, respiratory system and skin
Sensitization	No information available
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
o-Dichlorobenzene	95-50-1	Not listed	Not listed	Not listed	Not listed	Not listed

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Respiratory system

STOT - repeated exposure	None known
Aspiration hazard	No information available
Symptoms / effects, both acute and delayed	Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Endocrine Disruptor Information	No information available
Other Adverse Effects	Tumorigenic effects have been reported in experimental animals.

12. Ecological information

Ecotoxicity

The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
o-Dichlorobenzene	EC50: = 91.6 mg/L, 96h (Pseudokirchneriella subcapitata) EC50: 61.2 - 181 mg/L, 72h (Pseudokirchneriella subcapitata) EC50: = 2.2 mg/L, 96h static (Pseudokirchneriella subcapitata)	LC50: 4.8 - 6.6 mg/L, 96h static (Lepomis macrochirus) LC50: = 5.2 mg/L, 96h flow-through (Brachydanio rerio) LC50: 42.6 - 80.4 mg/L, 96h static (Pimephales promelas) LC50: 8.23 - 10.9 mg/L, 96h flow-through (Pimephales promelas) LC50: 1.44 - 1.73 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: = 5.8 mg/L, 96h static (Pimephales promelas)	EC50 = 4.76 mg/L 5 min EC50 = 4.98 mg/L 15 min EC50 = 5.99 mg/L 30 min	EC50: = 0.74 mg/L, 48h Static (Daphnia magna)

Persistence and Degradability	Persistence is unlikely
Bioaccumulation/ Accumulation	No information available.
Mobility	. Is not likely mobile in the environment due its low water solubility.

Component	log Pow
o-Dichlorobenzene	3.43

13. Disposal considerations

Waste Disposal Methods	Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.
-------------------------------	---

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
o-Dichlorobenzene - 95-50-1	U070	-

14. Transport information

DOT

UN-No	UN1591
Proper Shipping Name	O-DICHLOROBENZENE
Hazard Class	6.1
Packing Group	III

TDG

UN-No UN1591
 Proper Shipping Name O-DICHLOROBENZENE
 Hazard Class 6.1
 Packing Group III

IATA

UN-No UN1591
 Proper Shipping Name o-DICHLOROBENZENE
 Hazard Class 6.1
 Packing Group III

IMDG/IMO

UN-No UN1591
 Proper Shipping Name ortho-DICHLOROBENZENE
 Hazard Class 6.1
 Packing Group III

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
o-Dichlorobenzene	95-50-1	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

Component	CAS No	TSCA 12(b) - Notices of Export
o-Dichlorobenzene	95-50-1	Section 4

International Inventories

Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
o-Dichlorobenzene	95-50-1	X	-	202-425-9	X	X	X	X	X	KE-10066

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations**SARA 313**

Component	CAS No	Weight %	SARA 313 - Threshold Values %
o-Dichlorobenzene	95-50-1	99	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
o-Dichlorobenzene	X	-	X	X

Clean Air Act Not applicable

OSHA - Occupational Safety and Health Administration Not applicable

CERCLA This material, as supplied, contains one or more substances regulated as a hazardous

substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
o-Dichlorobenzene	100 lb	-

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
o-Dichlorobenzene	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
 DOT Marine Pollutant N
 DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations**Mexico - Grade**

No information available

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
o-Dichlorobenzene	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
o-Dichlorobenzene	95-50-1	Listed	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
o-Dichlorobenzene	95-50-1	Not applicable	Not applicable	Not applicable	Annex I - Y45

16. Other information

Prepared By

Regulatory Affairs
 Thermo Fisher Scientific
 Email: EMSDS.RA@thermofisher.com

Creation Date

09-May-2014

Revision Date

24-Dec-2021

Print Date

24-Dec-2021

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Creation Date 01-May-2012

Revision Date 24-Dec-2021

Revision Number 5

1. Identification

Product Name Phenanthrene

Cat No. : AC130090000; AC130090050; AC130090500; AC130095000

CAS No 85-01-8
Synonyms No information available

Recommended Use Laboratory chemicals.
Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute oral toxicity

Category 4

Label Elements

Signal Word

Warning

Hazard Statements

Harmful if swallowed

**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
Rinse mouth

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Very toxic to aquatic life with long lasting effects

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Phenanthrene	85-01-8	>95

4. First-aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Get medical attention. Wash off immediately with plenty of water for at least 15 minutes.
Inhalation	Remove to fresh air. Get medical attention. If not breathing, give artificial respiration.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Get medical attention if symptoms occur.
Most important symptoms and effects	None reasonably foreseeable.
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.
Unsuitable Extinguishing Media	No information available
Flash Point	No information available
Method -	No information available
Autoignition Temperature	No information available
Explosion Limits	
Upper	No data available
Lower	No data available

Sensitivity to Mechanical Impact No information available
Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health
1

Flammability
1

Instability
0

Physical hazards
N/A

6. Accidental release measures

Personal Precautions

Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust formation.

Environmental Precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

Methods for Containment and Clean Up

Sweep up and shovel into suitable containers for disposal. Keep in suitable, closed containers for disposal.

7. Handling and storage

Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Avoid dust formation.

Storage.

Keep containers tightly closed in a dry, cool and well-ventilated place. Incompatible Materials. Strong oxidizing agents.

8. Exposure controls / personal protection

Exposure Guidelines

This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Phenanthrene		TWA: 0.2 mg/m ³		

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face Protection

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Solid
Appearance	Beige
Odor	Odorless
Odor Threshold	No information available
pH	No information available
Melting Point/Range	95 - 101 °C / 203 - 213.8 °F
Boiling Point/Range	336 °C / 636.8 °F
Flash Point	No information available
Evaporation Rate	Not applicable
Flammability (solid,gas)	No information available
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	1 mmHg @ 116 °C
Vapor Density	Not applicable
Specific Gravity	1.063
Solubility	Insoluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	No information available
Decomposition Temperature	No information available
Viscosity	Not applicable
Molecular Formula	C14 H10
Molecular Weight	178.23

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products. Excess heat. Avoid dust formation.
Incompatible Materials	Strong oxidizing agents
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂)
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Phenanthrene	1.8 g/kg (Rat)	Not listed	Not listed

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	No information available
Sensitization	No information available
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
-----------	--------	------	-----	-------	------	--------

Phenanthrene	85-01-8	Not listed	Not listed	Not listed	Not listed	Not listed
--------------	---------	------------	------------	------------	------------	------------

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure None known

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed No information available

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Phenanthrene	Not listed	LC50 = 3.2 mg/L 96h	Not listed	LC50 = 0.35 mg/L 48h

Persistence and Degradability May persist

Bioaccumulation/ Accumulation No information available.

Mobility . Is not likely mobile in the environment due its low water solubility.

Component	log Pow
Phenanthrene	4.5

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN3077
Proper Shipping Name Environmentally hazardous substances, solid, n.o.s.
Hazard Class 9
Packing Group III

TDG

UN-No UN3077
Proper Shipping Name Environmentally hazardous substances, solid, n.o.s.
Hazard Class 9
Packing Group III

IATA

UN-No UN3077
Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.*
Hazard Class 9
Packing Group III

IMDG/IMO

UN-No	UN3077
Proper Shipping Name	Environmentally hazardous substances, solid, n.o.s.
Hazard Class	9
Packing Group	III

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Phenanthrene	85-01-8	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Phenanthrene	85-01-8	X	-	201-581-5	X	X	X	X	X	KE-28202

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations

SARA 313

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Phenanthrene	85-01-8	>95	1.0 0.1

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Phenanthrene	-	-	-	X

Clean Air Act Not applicable

OSHA - Occupational Safety and Health Administration Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Phenanthrene	5000 lb	-

California Proposition 65 This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Phenanthrene	X	X	X	-	-

U.S. Department of Transportation

Reportable Quantity (RQ): Y

DOT Marine Pollutant N

DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations**Mexico - Grade**

No information available

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Phenanthrene	-	-	SHVC Candidate list - 201-581-5 - vPvB (Article 57e)

After the sunset date the use of this substance requires either an authorization or can only be used for exempted uses, e.g. use in scientific research and development which includes routine analytics or use as intermediate.

<https://echa.europa.eu/authorisation-list>

<https://echa.europa.eu/candidate-list-table>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Phenanthrene	85-01-8	Not applicable	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Phenanthrene	85-01-8	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By

Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Creation Date

01-May-2012

Revision Date

24-Dec-2021

Print Date

24-Dec-2021

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information

relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Creation Date 09-May-2012

Revision Date 24-Dec-2021

Revision Number 5

1. Identification

Product Name Styrene, stabilized

Cat No. : AC132790000; AC132790010; AC132790025; AC132790050;
AC132790100; AC132790250

CAS No 100-42-5
Synonyms Ethenylbenzene

Recommended Use Laboratory chemicals.
Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 3
Acute Inhalation Toxicity - Vapors	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system.	
Specific target organ toxicity - (repeated exposure)	Category 1
Target Organs - Ears, Central nervous system (CNS).	
Aspiration Toxicity	Category 1

Label Elements

Signal Word

Danger

Hazard Statements

Flammable liquid and vapor
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye irritation
Harmful if inhaled
May cause respiratory irritation
May cause drowsiness or dizziness
Suspected of damaging the unborn child
Causes damage to organs through prolonged or repeated exposure
Suspected of causing cancer

**Precautionary Statements****Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Use only outdoors or in a well-ventilated area
Wash face, hands and any exposed skin thoroughly after handling
Wear eye/face protection
Do not breathe dust/fume/gas/mist/vapors/spray
Do not eat, drink or smoke when using this product
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Response

IF exposed or concerned: Get medical attention/advice

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Harmful to aquatic life with long lasting effects

WARNING. Cancer - <https://www.p65warnings.ca.gov/>.

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Styrene	100-42-5	>95

4. First-aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Most important symptoms and effects	Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	No information available
Flash Point	31 °C / 87.8 °F
Method -	No information available
Autoignition Temperature	490 °C / 914 °F
Explosion Limits	
Upper	7.0%
Lower	1.1%
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health
3

Flammability
3

Instability
2

Physical hazards
N/A

6. Accidental release measures**Personal Precautions**

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Should not be released into the environment. See Section 12 for additional Ecological Information. Avoid release to the environment. Collect spillage. Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage**Handling**

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Storage.

Keep refrigerated. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Incompatible Materials. Acids. Halogenated compounds. Copper alloys. Strong oxidizing agents.

8. Exposure controls / personal protection**Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Styrene	TWA: 10 ppm STEL: 20 ppm	(Vacated) TWA: 50 ppm (Vacated) TWA: 215 mg/m ³ Ceiling: 200 ppm (Vacated) STEL: 100 ppm (Vacated) STEL: 425 mg/m ³ TWA: 100 ppm	IDLH: 700 ppm TWA: 50 ppm TWA: 215 mg/m ³ STEL: 100 ppm STEL: 425 mg/m ³	TWA: 20 ppm STEL: 40 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

Personal Protective Equipment**Eye/face Protection**

Tight sealing safety goggles. Face protection shield.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection

No protective equipment is needed under normal use conditions.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Colorless
Odor	pungent
Odor Threshold	No information available
pH	No information available
Melting Point/Range	-31 °C / -23.8 °F
Boiling Point/Range	145 - 146 °C / 293 - 294.8 °F @ 760 mmHg
Flash Point	31 °C / 87.8 °F
Evaporation Rate	No information available
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	7.0%
Lower	1.1%
Vapor Pressure	7 mbar @ 20 °C
Vapor Density	1.22
Specific Gravity	0.906
Solubility	Moderately soluble
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	490 °C / 914 °F
Decomposition Temperature	No information available
Viscosity	0.695 mPa.s at 25 °C
Molecular Formula	C8 H8
Molecular Weight	104.15

10. Stability and reactivity

Reactive Hazard	Yes
Stability	Stable under normal conditions.
Conditions to Avoid	Excess heat. Incompatible products. Keep away from open flames, hot surfaces and sources of ignition. Temperatures above 40°C.
Incompatible Materials	Acids, Halogenated compounds, Copper alloys, Strong oxidizing agents
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂)
Hazardous Polymerization	Hazardous polymerization may occur. Hazardous polymerization may occur upon depletion of inhibitor.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Styrene	-	LD50 > 2000 mg/kg (Rat)	LC50 = 11.7 mg/L (Rat) 4 h

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	Irritating to eyes, respiratory system and skin
Sensitization	No information available

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Styrene	100-42-5	Group 2A	Reasonably Anticipated	A3	X	Not listed

IARC (International Agency for Research on Cancer)

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

NTP: (National Toxicity Program)

Mutagenic Effects

No information available

Reproductive Effects

Experiments have shown reproductive toxicity effects on laboratory animals.

Developmental Effects

No information available.

Teratogenicity

No information available.

STOT - single exposure

Respiratory system

STOT - repeated exposure

Ears Central nervous system (CNS)

Aspiration hazard

Category 1

Symptoms / effects, both acute and delayed

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
Styrene	Group I Chemical	High Exposure Concern	Not applicable

Other Adverse Effects

The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Do not empty into drains. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment. Contains a substance which is: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Styrene	EC50: 0.15 - 3.2 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: 0.46 - 4.3 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: = 0.72 mg/L, 96h (Pseudokirchneriella subcapitata) EC50: = 1.4 mg/L, 72h (Pseudokirchneriella subcapitata)	LC50: 19.03 - 33.53 mg/L, 96h static (Lepomis macrochirus) LC50: 6.75 - 14.5 mg/L, 96h static (Pimephales promelas) LC50: 58.75 - 95.32 mg/L, 96h static (Poecilia reticulata) LC50: 3.24 - 4.99 mg/L, 96h flow-through (Pimephales promelas)	= 5.4 mg/L EC50 Photobacterium phosphoreum 5 min	EC50: 3.3 - 7.4 mg/L, 48h (Daphnia magna)

Persistence and Degradability

Insoluble in water Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation

No information available.

Mobility

. Is not likely mobile in the environment due its low water solubility. Will likely be mobile in the environment due to its volatility.

Component	log Pow
Styrene	2.95

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN2055
 Proper Shipping Name STYRENE MONOMER, STABILIZED
 Hazard Class 3
 Packing Group III

TDG

UN-No UN2055
 Proper Shipping Name STYRENE MONOMER, STABILIZED
 Hazard Class 3
 Packing Group III

IATA

UN-No UN2055
 Proper Shipping Name STYRENE MONOMER, STABILIZED
 Hazard Class 3
 Packing Group III

IMDG/IMO

UN-No UN2055
 Proper Shipping Name STYRENE MONOMER, STABILIZED
 Hazard Class 3
 Packing Group III

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Styrene	100-42-5	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Styrene	100-42-5	X	-	202-851-5	X	X	X	X	X	KE-35342

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations

SARA 313

Component	CAS No	Weight %	SARA 313 - Threshold
-----------	--------	----------	----------------------

			Values %
Styrene	100-42-5	>95	0.1

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Styrene	X	1000 lb	-	-

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Styrene	X		-

OSHA - Occupational Safety and Health Administration Not applicable

CERCLA This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Styrene	1000 lb	-

California Proposition 65 This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Styrene	100-42-5	Carcinogen	27 µg/day	Carcinogen

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Styrene	X	X	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Styrene	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous
-----------	--------	----------	------------------------------	---------------------------	--------------------------

					Substances (RoHS)
Styrene	100-42-5	Listed	Not applicable	Not applicable	Not applicable
Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Styrene	100-42-5	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Creation Date 09-May-2012
Revision Date 24-Dec-2021
Print Date 24-Dec-2021
Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Version 5.1
Revision Date 02/26/2014
Print Date 03/20/2014

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : *tert*-Butanol

Product Number : 471712
Brand : Sigma-Aldrich
Index-No. : 603-005-00-1
REACH No. : A registration number is not available for this substance as the substance or its uses are exempted from registration, the annual tonnage does not require a registration or the registration is envisaged for a later registration deadline.

CAS-No. : 75-65-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA

Telephone : +1 800-325-5832
Fax : +1 800-325-5052

1.4 Emergency telephone number

Emergency Phone # : (314) 776-6555

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225
Eye irritation (Category 2A), H319
Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H225

Highly flammable liquid and vapour.

H319

Causes serious eye irritation.

H335

May cause respiratory irritation.

Precautionary statement(s)

P210

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233

Keep container tightly closed.

P240

Ground/bond container and receiving equipment.

P241

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/ physician if you feel unwell.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Synonyms : 2-Methyl-2-propanol
Trimethyl carbinol
tert-Butyl alcohol

Formula : C₄H₁₀O
Molecular Weight : 74.12 g/mol
CAS-No. : 75-65-0
EC-No. : 200-889-7
Index-No. : 603-005-00-1

Hazardous components

Component	Classification	Concentration
tert-Butyl alcohol		
	Flam. Liq. 2; Eye Irrit. 2A; STOT SE 3; H225, H319, H335	-

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

no data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Flash back possible over considerable distance.

5.3 Advice for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

5.4 Further information

In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
tert-Butyl alcohol	75-65-0	TWA	100 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Central Nervous System impairment		

		Not classifiable as a human carcinogen		
		TWA	100 ppm 300 mg/m3	USA. NIOSH Recommended Exposure Limits
		ST	150 ppm 450 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	100 ppm 300 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		The value in mg/m3 is approximate.		
		TWA	100 ppm 300 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		STEL	150 ppm 450 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 480 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.2 mm

Break through time: 30 min

Material tested: Dermatril® P (KCL 743 / Aldrich Z677388, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

impervious clothing, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a) Appearance	Form: liquid Colour: colourless
b) Odour	no data available
c) Odour Threshold	no data available
d) pH	no data available
e) Melting point/freezing point	Melting point/range: 23 - 26 °C (73 - 79 °F)
f) Initial boiling point and boiling range	83 °C (181 °F)
g) Flash point	11 °C (52 °F) - closed cup
h) Evaporation rate	no data available
i) Flammability (solid, gas)	no data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 8 %(V) Lower explosion limit: 2.4 %(V)
k) Vapour pressure	41 hPa (31 mmHg) at 20 °C (68 °F) 59 hPa (44 mmHg) at 26 °C (79 °F)
l) Vapour density	2.56 - (Air = 1.0)
m) Relative density	0.775 g/mL at 25 °C (77 °F)
n) Water solubility	completely miscible
o) Partition coefficient: n-octanol/water	no data available
p) Auto-ignition temperature	no data available
q) Decomposition temperature	no data available
r) Viscosity	no data available
s) Explosive properties	no data available
t) Oxidizing properties	no data available

9.2 Other safety information

Relative vapour density	2.56 - (Air = 1.0)
-------------------------	--------------------

10. STABILITY AND REACTIVITY

10.1 Reactivity

no data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Strong oxidizing agents, Copper, Alkali metals, Aluminum

10.6 Hazardous decomposition products

Other decomposition products - no data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - rat - 2,743 mg/kg

Remarks: Sense Organs and Special Senses (Nose, Eye, Ear, and Taste):Eye:Lacrimation. Respiratory disorder
Gastrointestinal:Other changes.

Inhalation: no data available

LD50 Dermal - rabbit - > 2,000 mg/kg

Remarks: Prolonged skin contact may cause skin irritation and/or dermatitis.

no data available

Skin corrosion/irritation

Skin - rabbit

Result: Mild skin irritation - 24 h

Serious eye damage/eye irritation

Eyes - rabbit

Result: Irritating to eyes. - 24 h

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

no data available

no data available

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

no data available

Aspiration hazard

no data available

Additional Information

RTECS: EO1925000

drying, cracking of the skin, Skin irritation

Liver - Irregularities - Based on Human Evidence

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 6,140 mg/l - 96 h
Toxicity to daphnia and other aquatic invertebrates EC50 - Daphnia magna (Water flea) - 933 mg/l - 48 h

12.2 Persistence and degradability

Biodegradability Zahn-Wellens Test - Exposure time 19 d
Result: > 99.9 % - Readily biodegradable.

12.3 Bioaccumulative potential

Does not bioaccumulate.

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

no data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1120 Class: 3 Packing group: II
Proper shipping name: Butanols
Reportable Quantity (RQ):
Marine pollutant: No
Poison Inhalation Hazard: No

IMDG

UN number: 1120 Class: 3 Packing group: II EMS-No: F-E, S-D
Proper shipping name: BUTANOLS
Marine pollutant: No

IATA

UN number: 1120 Class: 3 Packing group: II
Proper shipping name: Butanols

15. REGULATORY INFORMATION

REACH No. : A registration number is not available for this substance as the substance or its uses are exempted from registration, the annual tonnage does not require a registration or the registration is envisaged for a later registration deadline.

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
tert-Butyl alcohol	75-65-0	2007-07-01

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

	CAS-No.	Revision Date
tert-Butyl alcohol	75-65-0	2007-07-01

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
tert-Butyl alcohol	75-65-0	2007-07-01

New Jersey Right To Know Components

	CAS-No.	Revision Date
tert-Butyl alcohol	75-65-0	2007-07-01

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
STOT SE	Specific target organ toxicity - single exposure

HMIS Rating

Health hazard:	2
Chronic Health Hazard:	*
Flammability:	3
Physical Hazard	0

NFPA Rating

Health hazard:	2
Fire Hazard:	3
Reactivity Hazard:	0

Further information

Copyright 2014 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information

Sigma-Aldrich Corporation
Product Safety – Americas Region
1-800-521-8956

Version: 5.1

Revision Date: 02/26/2014

Print Date: 03/20/2014

SAFETY DATA SHEET

Toluene

Section 1. Identification

GHS product identifier	: Toluene
Chemical name	: toluene
Other means of identification	: Benzene, methyl-; Methylbenzene; Toluol; Phenyl methane; Methyl benzol; toluene, pure; preparation consisting of: — 80 % or more but not more than 90 % by weight of (S)-hydroxy-3-phenoxy-benzeneacetonitrile (CAS RN 61826-76-4) and — 10 % or more but not more than 20 % by weight of toluene (CAS RN108-88-3); toluene, crude; preparation containing by weight: — 15 % or more but not more than 60 % of styrene butadiene copolymers or styrene isoprene copolymers and — 10 % or more but not more than 30 % of pinene polymers or pentadiene copolymers dissolved in: — methyl ethyl ketone (CAS RN 78-93-3) — heptane (CAS RN 142-82-5), and — toluene (CAS RN 108-88-3) or light aliphatic solvent naphta (CAS RN 64742-89-8); methacide; 1-Methylbenzene
Product type	: Liquid.
Product use	: Synthetic/Analytical chemistry.
Synonym	: Benzene, methyl-; Methylbenzene; Toluol; Phenyl methane; Methyl benzol; toluene, pure; preparation consisting of: — 80 % or more but not more than 90 % by weight of (S)-hydroxy-3-phenoxy-benzeneacetonitrile (CAS RN 61826-76-4) and — 10 % or more but not more than 20 % by weight of toluene (CAS RN108-88-3); toluene, crude; preparation containing by weight: — 15 % or more but not more than 60 % of styrene butadiene copolymers or styrene isoprene copolymers and — 10 % or more but not more than 30 % of pinene polymers or pentadiene copolymers dissolved in: — methyl ethyl ketone (CAS RN 78-93-3) — heptane (CAS RN 142-82-5), and — toluene (CAS RN 108-88-3) or light aliphatic solvent naphta (CAS RN 64742-89-8); methacide; 1-Methylbenzene
SDS #	: 001063
Supplier's details	: Airgas USA, LLC and its affiliates 259 North Radnor-Chester Road Suite 100 Radnor, PA 19087-5283 1-610-687-5253
24-hour telephone	: 1-866-734-3438

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

GHS label elements

Hazard pictograms	:   
--------------------------	---

Signal word	: Danger
--------------------	----------

Section 2. Hazards identification

Hazard statements	: Highly flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. May form explosive mixtures with air.
<u>Precautionary statements</u>	
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Obtain special instructions before use. Wear protective gloves. Wear protective clothing. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash thoroughly after handling.
Response	: Call a POISON CENTER or doctor if you feel unwell. IF exposed or concerned: Get medical advice or attention. Take off contaminated clothing and wash it before reuse.
Storage	: Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Substance
Chemical name	: toluene
Other means of identification	: Benzene, methyl-; Methylbenzene; Toluol; Phenyl methane; Methyl benzol; toluene, pure; preparation consisting of: — 80 % or more but not more than 90 % by weight of (S) -hydroxy-3-phenoxy-benzeneacetonitrile (CAS RN 61826-76-4) and — 10 % or more but not more than 20 % by weight of toluene (CAS RN108-88-3); toluene, crude; preparation containing by weight: — 15 % or more but not more than 60 % of styrene butadiene copolymers or styrene isoprene copolymers and — 10 % or more but not more than 30 % of pinene polymers or pentadiene copolymers dissolved in: — methyl ethyl ketone (CAS RN 78-93-3) — heptane (CAS RN 142-82-5), and — toluene (CAS RN 108-88-3) or light aliphatic solvent naphta (CAS RN 64742-89-8); methacide; 1-Methylbenzene
Product code	: 001063

CAS number/other identifiers

CAS number : 108-88-3

Ingredient name	%	CAS number
toluene	100	108-88-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Causes skin irritation.
- Frostbite** : Try to warm up the frozen tissues and seek medical attention.
- Ingestion** : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following: pain or irritation, watering, redness
- Inhalation** : Adverse symptoms may include the following: nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness, reduced fetal weight, increase in fetal deaths, skeletal malformations
- Skin contact** : Adverse symptoms may include the following: irritation, redness, reduced fetal weight, increase in fetal deaths, skeletal malformations
- Ingestion** : Adverse symptoms may include the following: reduced fetal weight, increase in fetal deaths, skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Do not ingest. Empty containers retain product residue and can be hazardous. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Do not breathe vapor or mist. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid exposure during pregnancy.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Store locked up. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
toluene	<p>ACGIH TLV (United States, 3/2019). TWA: 20 ppm 8 hours.</p> <p>NIOSH REL (United States, 10/2016). STEL: 560 mg/m³ 15 minutes. STEL: 150 ppm 15 minutes. TWA: 375 mg/m³ 10 hours. TWA: 100 ppm 10 hours.</p> <p>OSHA PEL 1989 (United States, 3/1989). STEL: 560 mg/m³ 15 minutes. STEL: 150 ppm 15 minutes. TWA: 375 mg/m³ 8 hours. TWA: 100 ppm 8 hours.</p> <p>OSHA PEL Z2 (United States, 2/2013). AMP: 500 ppm 10 minutes. CEIL: 300 ppm TWA: 200 ppm 8 hours.</p>

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Section 8. Exposure controls/personal protection

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid. [Watery liquid.]
- Color** : Colorless.
- Odor** : Characteristic.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point** : -95°C (-139°F)
- Boiling point** : 110.6°C (231.1°F)
- Critical temperature** : 318.65°C (605.6°F)
- Flash point** : Closed cup: 4.4°C (39.9°F)
- Evaporation rate** : 2 (butyl acetate = 1)
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Lower: 1.1%
Upper: 7.1%
- Vapor pressure** : 3.1 kPa (23.17 mm Hg) [room temperature]
- Vapor density** : 3.1 (Air = 1)
- Specific Volume (ft³/lb)** : 1.1494
- Gas Density (lb/ft³)** : 0.87 (20°C / 68 to °F)
- Relative density** : 0.87
- Solubility** : Not available.
- Solubility in water** : 0.573 g/l

Section 9. Physical and chemical properties

Partition coefficient: n-octanol/water	: 2.73
Auto-ignition temperature	: 480°C (896°F)
Decomposition temperature	: Not available.
Viscosity	: Dynamic (room temperature): 0.56 mPa·s (0.56 cP)
Flow time (ISO 2431)	: Not available.
Molecular weight	: 92.14 g/mole
Aerosol product	
Heat of combustion	: -40542180 J/kg

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hazardous polymerization	: Under normal conditions of storage and use, hazardous polymerization will not occur.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
toluene	LC50 Inhalation Vapor	Rat	28830 ppm	1 hours
	LC50 Inhalation Vapor	Rat	49 g/m ³	4 hours

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes	-
	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Eyes - Severe irritant	Rabbit	-	870 ug	-
			-	24 hours 2 mg	-
	Skin - Mild irritant	Pig	-	24 hours 250 UI	-
	Skin - Mild irritant	Rabbit	-	435 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Skin - Moderate irritant	Rabbit	-	500 mg	-

Sensitization

Not available.

Section 11. Toxicological information

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
toluene	-	3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
toluene	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
toluene	Category 2	-	-

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

Skin contact : Causes skin irritation.

Ingestion : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:., pain or irritation, watering, redness

Inhalation : Adverse symptoms may include the following:., nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness, reduced fetal weight, increase in fetal deaths, skeletal malformations

Skin contact : Adverse symptoms may include the following:., irritation, redness, reduced fetal weight, increase in fetal deaths, skeletal malformations

Ingestion : Adverse symptoms may include the following:., reduced fetal weight, increase in fetal deaths, skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Section 11. Toxicological information

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : Suspected of damaging the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : Suspected of damaging fertility.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Inhalation (vapors)	49 mg/l

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
toluene	Acute EC50 12500 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
	Chronic NOEC 1000 µg/l Fresh water	Daphnia - Daphnia magna	21 days

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
toluene	2.73	90	low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations






Disposal methods

- : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
Toluene; Benzene, methyl-	108-88-3	Listed	U220

Section 14. Transport information

	DOT	TDG	Mexico	IMDG	IATA
UN number	UN1294	UN1294	UN1294	UN1294	UN1294
UN proper shipping name	TOLUENE	TOLUENE	TOLUENE	TOLUENE	TOLUENE
Transport hazard class(es)	3 	3 	3 	3 	3 
Packing group	II	II	II	II	II
Environmental hazards	No.	No.	No.	No.	No.

“Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product.”

Additional information

DOT Classification

- : **Reportable quantity** 1000 lbs / 454 kg [137.86 gal / 521.84 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

Limited quantity Yes.

Quantity limitation Passenger aircraft/rail: 5 L. Cargo aircraft: 60 L.

Special provisions IB2, T4, TP1

TDG Classification

- : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).

Explosive Limit and Limited Quantity Index 1

Passenger Carrying Road or Rail Index 5

IATA

- : The environmentally hazardous substance mark may appear if required by other transportation regulations.

Quantity limitation Passenger and Cargo Aircraft: 5 L. Cargo Aircraft Only: 60 L.

Limited Quantities - Passenger Aircraft: 1 L.

Section 14. Transport information

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

U.S. Federal regulations : **TSCA 8(a) CDR Exempt/Partial exemption:** Not determined
Clean Water Act (CWA) 307: toluene
Clean Water Act (CWA) 311: toluene

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Listed

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Refer to Section 2: Hazards Identification of this SDS for classification of substance.

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	toluene	108-88-3	100
Supplier notification	toluene	108-88-3	100

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations


Massachusetts : This material is listed.

New York : This material is listed.

New Jersey : This material is listed.

Pennsylvania : This material is listed.

California Prop. 65

 **WARNING:** This product can expose you to Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Toluene	-	Yes.

International regulations

Section 15. Regulatory information

[Chemical Weapon Convention List Schedules I, II & III Chemicals](#)

Not listed.

[Montreal Protocol](#)

Not listed.

[Stockholm Convention on Persistent Organic Pollutants](#)

Not listed.

[Rotterdam Convention on Prior Informed Consent \(PIC\)](#)

Not listed.

[UNECE Aarhus Protocol on POPs and Heavy Metals](#)

Not listed.

[Inventory list](#)

Australia	: This material is listed or exempted.
Canada	: This material is listed or exempted.
China	: This material is listed or exempted.
Europe	: This material is listed or exempted.
Japan	: Japan inventory (ENCS) : This material is listed or exempted. Japan inventory (ISHL) : This material is listed or exempted.
New Zealand	: This material is listed or exempted.
Philippines	: This material is listed or exempted.
Republic of Korea	: This material is listed or exempted.
Taiwan	: This material is listed or exempted.
Thailand	: Not determined.
Turkey	: This material is listed or exempted.
United States	: This material is active or exempted.
Viet Nam	: This material is listed or exempted.

Section 16. Other information

[Hazardous Material Information System \(U.S.A.\)](#)

Health	/	2
Flammability		3
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

[National Fire Protection Association \(U.S.A.\)](#)



Section 16. Other information

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 2	Expert judgment
SKIN IRRITATION - Category 2	Expert judgment
TOXIC TO REPRODUCTION - Category 2	Expert judgment
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Expert judgment
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Expert judgment

History

Date of printing : 5/13/2021

Date of issue/Date of revision : 5/13/2021

Date of previous issue : 2/1/2018

Version : 1.01

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

SAFETY DATA SHEET

Creation Date 03-Feb-2010

Revision Date 24-Dec-2021

Revision Number 3

1. Identification

Product Name Trichloroethylene

Cat No. : T340-4; T341-4; T341-20; T341-500; T403-4

CAS No 79-01-6
Synonyms Trichloroethene (Stabilized/Technical/Electronic/Certified ACS)

Recommended Use Laboratory chemicals.
Uses advised against .

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Emergency Telephone Number CHEMTREC®, Inside the USA: 800-424-9300
CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Skin Sensitization	Category 1
Germ Cell Mutagenicity	Category 2
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Central nervous system (CNS).	
Specific target organ toxicity - (repeated exposure)	Category 2
Target Organs - Kidney, Liver, Heart, spleen, Blood.	

Label Elements

Signal Word

Danger

Hazard Statements

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
May cause drowsiness or dizziness
Suspected of causing genetic defects
May cause cancer
May cause damage to organs through prolonged or repeated exposure

**Precautionary Statements****Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Contaminated work clothing should not be allowed out of the workplace
Do not breathe dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Wear protective gloves/protective clothing/eye protection/face protection

Response

IF exposed or concerned: Get medical attention/advice

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

IF ON SKIN: Wash with plenty of soap and water
Take off contaminated clothing and wash before reuse
If skin irritation or rash occurs: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Harmful to aquatic life with long lasting effects

WARNING. Cancer and Reproductive Harm - <https://www.p65warnings.ca.gov/>.

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Trichloroethylene	79-01-6	>95

4. First-aid measures

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye Contact	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Most important symptoms and effects	May cause allergic skin reaction. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam.
Unsuitable Extinguishing Media	No information available
Flash Point	No information available
Method -	No information available
Autoignition Temperature	410 °C / 770 °F
Explosion Limits	
Upper	44.8 vol %
Lower	8 vol %
Oxidizing Properties	Not oxidising
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. Containers may explode when heated. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Chlorine. Phosgene. Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrogen chloride gas.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health	Flammability	Instability	Physical hazards
2	1	0	N/A

6. Accidental release measures

Personal Precautions	Ensure adequate ventilation. Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas.
Environmental Precautions	Should not be released into the environment. Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Up Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

7. Handling and storage

Handling Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance.

Storage. Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from light. Do not store in aluminum containers. Incompatible Materials. Strong oxidizing agents. Strong bases. Amines. Alkali metals. Metals. .

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Trichloroethylene	TWA: 10 ppm STEL: 25 ppm	(Vacated) TWA: 50 ppm (Vacated) TWA: 270 mg/m ³ Ceiling: 200 ppm (Vacated) STEL: 200 ppm (Vacated) STEL: 1080 mg/m ³ TWA: 100 ppm	IDLH: 1000 ppm	TWA: 10 ppm STEL: 25 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Use only under a chemical fume hood. Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Colorless
Odor	Characteristic
Odor Threshold	No information available
pH	No information available
Melting Point/Range	-85 °C / -121 °F
Boiling Point/Range	87 °C / 188.6 °F
Flash Point	No information available
Evaporation Rate	0.69 (Carbon Tetrachloride = 1.0)

Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	44.8 vol %
Lower	8 vol %
Vapor Pressure	77.3 mbar @ 20 °C
Vapor Density	4.5 (Air = 1.0)
Specific Gravity	1.460
Solubility	Insoluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	410 °C / 770 °F
Decomposition Temperature	> 120°C
Viscosity	0.55 mPa.s (25°C)
Molecular Formula	C ₂ H Cl ₃
Molecular Weight	131.39

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Light sensitive.
Conditions to Avoid	Incompatible products. Excess heat. Exposure to light. Exposure to moist air or water.
Incompatible Materials	Strong oxidizing agents, Strong bases, Amines, Alkali metals, Metals,
Hazardous Decomposition Products	Chlorine, Phosgene, Carbon monoxide (CO), Carbon dioxide (CO ₂), Hydrogen chloride gas
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Trichloroethylene	LD50 = 4920 mg/kg (Rat)	LD50 = 29000 mg/kg (Rabbit)	LC50 = 26 mg/L (Rat) 4 h

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	Irritating to eyes and skin
Sensitization	May cause sensitization by skin contact
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Trichloroethylene	79-01-6	Group 1	Known	A2	X	A2

IARC (International Agency for Research on Cancer)

NTP: (National Toxicity Program)

ACGIH: (American Conference of Governmental Industrial Hygienists)

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mutagenic Effects	Mutagenic effects have occurred in humans.
Reproductive Effects	No information available.
Developmental Effects	No information available.
Teratogenicity	No information available.
STOT - single exposure	Central nervous system (CNS)
STOT - repeated exposure	Kidney Liver Heart spleen Blood
Aspiration hazard	No information available
Symptoms / effects, both acute and delayed	Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing
Endocrine Disruptor Information	No information available
Other Adverse Effects	The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Do not empty into drains. The product contains following substances which are hazardous for the environment. Contains a substance which is: Harmful to aquatic organisms. Toxic to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Trichloroethylene	EC50: = 175 mg/L, 96h (Pseudokirchneriella subcapitata) EC50: = 450 mg/L, 96h (Desmodesmus subspicatus)	LC50: 31.4 - 71.8 mg/L, 96h flow-through (Pimephales promelas) LC50: 39 - 54 mg/L, 96h static (Lepomis macrochirus)	EC50 = 0.81 mg/L 24 h EC50 = 115 mg/L 10 min EC50 = 190 mg/L 15 min EC50 = 235 mg/L 24 h EC50 = 410 mg/L 24 h EC50 = 975 mg/L 5 min	EC50: = 2.2 mg/L, 48h (Daphnia magna)

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
Trichloroethylene	2.4

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Trichloroethylene - 79-01-6	U228	-

14. Transport information

DOT

UN-No	UN1710
Proper Shipping Name	TRICHLOROETHYLENE
Hazard Class	6.1

Packing Group	III
TDG	
UN-No	UN1710
Proper Shipping Name	TRICHLOROETHYLENE
Hazard Class	6.1
Packing Group	III
IATA	
UN-No	UN1710
Proper Shipping Name	TRICHLOROETHYLENE
Hazard Class	6.1
Packing Group	III
IMDG/IMO	
UN-No	UN1710
Proper Shipping Name	TRICHLOROETHYLENE
Hazard Class	6.1
Packing Group	III

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Trichloroethylene	79-01-6	X	ACTIVE	R;S

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

- - Not Listed

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

TSCA 12(b) - Notices of Export

Component	CAS No	TSCA 12(b) - Notices of Export
Trichloroethylene	79-01-6	Section 5 Section 6

International Inventories

Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Trichloroethylene	79-01-6	X	-	201-167-4	X	X	X	X	X	X

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations

SARA 313

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Trichloroethylene	79-01-6	>95	0.1

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Trichloroethylene	X	100 lb	X	X

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
-----------	-----------	-------------------------	-------------------------

Trichloroethylene	X		-
-------------------	---	--	---

OSHA - Occupational Safety and Health Administration Not applicable

CERCLA This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Trichloroethylene	100 lb 1 lb	-

California Proposition 65 This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Trichloroethylene	79-01-6	Carcinogen Developmental Male Reproductive	14 µg/day 50 µg/day	Developmental Carcinogen

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Trichloroethylene	X	X	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Trichloroethylene	Carcinogenic Category 1B Article 57 Application date: October 21, 2014 Sunset date: April 21, 2016 Exemption - None	Use restricted. See item 28. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	SVHC Candidate list - 201-167-4 - Carcinogenic, Article 57a

After the sunset date the use of this substance requires either an authorization or can only be used for exempted uses, e.g. use in scientific research and development which includes routine analytics or use as intermediate.

<https://echa.europa.eu/authorisation-list>

<https://echa.europa.eu/substances-restricted-under-reach>

<https://echa.europa.eu/candidate-list-table>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Trichloroethylene	79-01-6	Listed	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive	Seveso III Directive	Rotterdam	Basel Convention
-----------	--------	----------------------	----------------------	-----------	------------------

		(2012/18/EC) - Qualifying Quantities for Major Accident Notification	(2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Convention (PIC)	(Hazardous Waste)
Trichloroethylene	79-01-6	Not applicable	Not applicable	Not applicable	Annex I - Y45

16. Other information

Prepared By Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Creation Date 03-Feb-2010
Revision Date 24-Dec-2021
Print Date 24-Dec-2021
Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

SAFETY DATA SHEET

Version 6.4
Revision Date 05/31/2021
Print Date 03/19/2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name : Trichlorofluoromethane

Product Number : 254991
Brand : Aldrich
CAS-No. : 75-69-4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES

Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-
527-3887 CHEMTREC (International) 24
Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Hazardous to the ozone layer (Category 1), H420

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Warning

Hazard statement(s)
H420

Harms public health and the environment by destroying ozone
in the upper atmosphere.

Precautionary statement(s)
P502

Refer to manufacturer/ supplier for information on recovery/
recycling.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Fluorotrichloromethane
CFC-11

Formula : CCl₃F
Molecular weight : 137.37 g/mol
CAS-No. : 75-69-4
EC-No. : 200-892-3

Component	Classification	Concentration
Trichlorofluoromethane		
	Ozone 1; H420	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most). Consult doctor if feeling unwell.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Hydrogen chloride gas

Hydrogen fluoride

Not combustible.

Ambient fire may liberate hazardous vapours.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

5.4 Further information

Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities**Storage conditions**

Tightly closed.

Storage stability

Recommended storage temperature

2 - 8 °C

Contents under pressure.

Storage class (TRGS 510): 10: Combustible liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Trichlorofluoromethane	75-69-4	C	1,000 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Not classifiable as a human carcinogen		
		C	1,000 ppm 5,600 mg/m ³	USA. NIOSH Recommended Exposure Limits
		TWA	1,000 ppm 5,600 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		C	1,000 ppm 5,600 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

8.2 Exposure controls

Appropriate engineering controls

Change contaminated clothing. Wash hands after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Respiratory protection

Not required; except in case of aerosol formation.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|--|--|
| a) Appearance | Form: liquid, clear
Color: colorless |
| b) Odor | No data available |
| c) Odor Threshold | No data available |
| d) pH | No data available |
| e) Melting point/freezing point | Melting point/range: -111.0 - -110.0 °C (-167.8 - -166.0 °F) |
| f) Initial boiling point and boiling range | 23.7 °C 74.7 °F - lit. |
| g) Flash point | ()Not applicable |
| h) Evaporation rate | No data available |
| i) Flammability (solid, liquid, gas) | No data available |

	gas)	
j)	Upper/lower flammability or explosive limits	No data available
k)	Vapor pressure	885.7 hPa at 20.0 °C (68.0 °F)
l)	Vapor density	No data available
m)	Relative density	No data available
n)	Water solubility	1 g/l
o)	Partition coefficient: n-octanol/water	log Pow: 2.53 - Bioaccumulation is not expected.
p)	Autoignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available

9.2 Other safety information

Surface tension	18.0 mN/m at 25.0 °C (77.0 °F)
-----------------	--------------------------------

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

no information available

10.5 Incompatible materials

Strong oxidizing agents, Sodium/sodium oxides, Potassium, Magnesium, Aluminum, Zinc

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - > 15,000 mg/kg

Inhalation: No data available

Dermal: No data available

No data available

Aldrich - 254991

Page 5 of 8

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

RTECS: PB6125000

Nausea, Dizziness, Headache, Vomiting, Diarrhea, Abdominal pain, Weakness, Unconsciousness

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information**12.1 Toxicity**

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

DOT (US)

UN number: 3082 Class: 9 Packing group: III
Proper shipping name: Environmentally hazardous substance, liquid, n.o.s.
(Trichlorofluoromethane)
Reportable Quantity (RQ): 5000 lbs
Reportable Quantity (RQ): 10 lbs
Poison Inhalation Hazard: No

IMDG

Not dangerous goods

IATA

Not dangerous goods

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
Trichlorofluoromethane	75-69-4	2007-07-01

SARA 311/312 Hazards

Acute Health Hazard

Reportable Quantity : F002 lbs

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.4

Revision Date: 05/31/2021

Print Date: 03/19/2022



SAFETY DATA SHEET (SDS)

XYLENE

1. Identification

SDS Record Number	:	PCS 08006
Date of SDS	:	18 March 2015
Identity of the substance	:	Xylene
Product Description	:	Aromatic hydrocarbon
Other names/synonyms	:	Dimethylbenzene, Methyl Toluene, Xylol, Xylenes (IBC code)
Name of the supplier	:	Petrochemical Corporation of Singapore (Private) Limited
Recommended uses	:	Solvent, diluent, chemical feedstock, or fuel
Contact detail of the supplier	:	100 Ayer Merbau Road, Singapore 628277
	:	+65 68672102
24-Hour Emergency contact	:	Asia Pacific +65 3158 1074 (Singapore)
	:	China +86 10 5100 3039 (Beijing)
	:	Europe, Israel & Americas +44 (0) 1235 239 670 (UK)
	:	Middle East & Africa +44 (0) 1235 239 671 (UK)

2. Hazards Identification

GHS Classification

<u>Hazard Class</u>	<u>Hazard Category</u>
• Flammable Liquid	3
• Acute Toxicity (Oral)	5
• Acute Toxicity (Inhalation)	4
• Skin Corrosion/Irritation	2
• Serious Eye Damage/ Irritation	2A
• Carcinogenicity	2
• Toxic to reproduction	1B
• STOST (Single exposure)	2 (central nervous system)
• STOST (Repeated exposure)	2 (central nervous system)
• Aspiration hazard	1
• Acute hazards to the aquatic environment	2

Pictograms



Signal Word: Danger

Hazard Statements

- Flammable liquid and vapour
- May be harmful if swallowed
- Harmful if inhaled
- Causes skin irritation and serious eye irritation
- May damage fertility or the unborn child
- May cause damage to organs
- May cause damage to organs through prolonged or repeated exposure
- May be fatal if swallowed and enters airways
- Toxic to aquatic life



Precautionary Statements

Prevention

- Keep container tightly closed.
- Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
- Wear protective gloves /protective clothing/eye protection/face protection
- Ground/Bond container and receiving equipment
- Use explosion-proof electrical/ventilating/lighting equipment.
- Take precautionary measures against static discharge.
- Use only non-sparking tools.
- Wash thoroughly after handling.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Do not eat, drink or smoke when using this product.
- Avoid breathing dust/fume/gas/mist/vapours/spray.
- Avoid release to the environment
- Use only outdoors or in a well-ventilated area.

Response

- IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
- Call a POISON CENTER/doctor/physician if you feel unwell.
- In case of fire: Use appropriate media for extinction.
- If INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- IF ON SKIN: Wash with plenty of soap and water.
- Take off contaminated clothing and wash before re-use.
- If skin irritation occurs: Get medical advice/attention.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists, get medical advice/attention.
- Wash hands after handling
- IF exposed or concerned: Get medical attention/advice.
- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- Do NOT induce vomiting.

Storage

- Store in well-ventilated place. Keep cool.
- Store locked up.

Disposal

- Dispose of the contents in accordance to the local mandatory rules and regulations
-

3. Composition/Information On Ingredients

Chemical identification : $C_6H_4(CH_3)_2$
Common name(s) / synonym(s) : Dimethylbenzene, Methyl Toluene, Xylol
CAS number / EC number : 1330-20-7/215-535-7

Other substances in product Hazardous to health or environment

Chemical Identification	Common name	CAS number	Concentration
Ethyl Benzene	Ethyl Benzene	100-41-4	51- 69 wt%
m-Xylene	m-Xylene	108-38-3	16 - 26 wt%
p-Xylene	p-Xylene	106-42-3	6 - 11 wt%
o-Xylene	o-Xylene	95-47-6	7 - 13 wt%
Toluene	Toluene	108-88-3	0.01- 0.07 wt%



4. First-Aid Measures

Eye: Irrigate immediately. If this chemical contacts the eyes, immediately wash (irrigate) the eyes with large amounts of water, occasionally lifting the lower and upper lids. Get medical attention immediately.

Skin: Soap wash promptly. If this chemical contacts the skin, promptly flush the contaminated skin with soap and water. If this chemical penetrates the clothing, promptly remove the clothing and flush the skin with water. If irritation persists after washing, get medical attention.

Breathing: Respiratory support. If a person breathes large amounts of this chemical, move the exposed person to fresh air at once. If breathing has stopped, perform artificial resuscitation. Keep the affected person warm and at rest. Get medical attention as soon as possible.

Swallow: Medical attention immediately. If this chemical has been swallowed, get medical attention immediately. DO NOT induce vomiting. Keep at rest.

5. Fire-Fighting Measures

Extinguishing media

- Use foam or dry chemical to extinguish fire.
- Use water spray to cool fire exposed surfaces and to protect personnel.
- Shut off fuel to fire if possible to do so without hazard. If a leak or spill has not ignited use water spray to disperse the vapours.

Specific Hazards Arising From The Chemical:

- **General Hazards:** Flammable Liquid; may release vapours that form flammable mixtures at or above the flash point. Toxic gases will form upon combustion.
- **Hazardous Combustion Products:** Fumes, smoke, and carbon monoxide.
- This liquid is volatile and gives off invisible vapors.
- Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

Special Protective Equipment And Precautions For Fire Fighters

- Respiratory and eye protection required for fire fighting personnel.
- Avoid spraying water directly into storage containers due to danger of boilover.
- A self-contained breathing apparatus (SCBA) is recommended for indoor fires and any significant outdoor fires. For small outdoor fires, which may easily be extinguished with a portable fire extinguisher, use of an SCBA is optional.
-

6. Accidental Release Measures

- Keep public away. Prevent additional discharge of material, if possible to do so without hazard.
- Prevent spills from entering sewers, watercourses or low areas.
- Contain spilled liquid with sand or earth. Do not use combustible materials such as sawdust.
- Recover by pumping (use an explosion proof motor or hand pump), or by using a suitable absorbent.
- Warn occupants and shipping in surrounding and downwind areas of fire and explosion hazard and request all to stay clear. Remove from surface by skimming or with suitable absorbents.
- If allowed by local authorities and environmental agencies, sinking and/or suitable dispersants may be used in unconfined waters.
- Notify the appropriate authorities immediately.



- Take all additional action necessary to prevent and remedy the adverse effects of the spill.
 - Provide adequate Ventilation.
 - Remove all ignition sources.
 - Collect leaking and spilled liquid in sealable containers as far as possible.
 - Absorb remaining liquid in sand or inert absorbent and remove to safe place.
 - (Extra personal protection: filter respirator for organic gases and vapours.)
-

7. Handling And Storage

Precautions for safe handling

- Keep container closed. Handle and open containers with care.
- **Do not** handle or store near an open flame, heat, or other sources of ignition.
- **Do not** pressurize, cut, heat, or weld containers.
- Empty product containers may contain product residue.
- **Do not** reuse empty containers without commercial cleaning or reconditioning.
- Keep away from sources of ignition and from contact with oxidizing materials and strong acids

Conditions for safe storage, including any incompatibilities

- Store in a cool, well ventilated place away from incompatible materials.
 - Fireproof. Separated from strong oxidants and strong acids.
 - Protect material from direct sunlight.
 - Material will accumulate static charges, which may cause an electrical spark (ignition source).
 - Use proper grounding procedures.
-

8. Exposure Controls/Personal Protection

Appropriate engineering controls

- The use of local exhaust ventilation is recommended to control emissions near the source.
- Laboratory samples should be handled in a fume hood.
- Provide mechanical ventilation of confined spaces.
- Use explosion-proof ventilation equipment.

Personal Protective Equipment (PPE)

- The selection of personal protective equipment varies depending upon conditions of use.
- **Skin:** Prevent skin contact. Wear appropriate personal protective clothing to prevent skin contact.
- **Eyes:** Prevent eye contact. Wear appropriate eye protection to prevent eye contact.
- **Wash skin:** When contaminated. The worker should immediately wash the skin when it becomes contaminated.
- **Remove:** When wet (flammable). Work clothing that becomes wet should be immediately removed due to its flammability hazard (i.e., for liquids with a flash point <100°F).
- **Change:** No recommendation. No recommendation is made specifying the need for the worker to change clothing after the work shift.
- Where prolonged and/or repeated skin and eye contact is likely to occur, wear safety glasses with side shields, long sleeves, and chemical resistant gloves.
- Where eye contact is unlikely, but may occur as a result of short and/or periodic exposures, wear safety glasses with side shields.

Respirator Recommendations (NIOSH/OSHA)

Up to 900 ppm:

(APF = 10) Any chemical cartridge respirator with organic vapor cartridge(s)*

(APF = 25) Any powered, air-purifying respirator with organic vapor cartridge(s)*

(APF = 10) Any supplied-air respirator*

(APF = 50) Any self-contained breathing apparatus with a full facepiece



Emergency or planned entry into unknown concentrations or IDLH conditions:

(APF = 10,000) Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode (APF = 10,000). Any supplied-air respirator that

has a full facepiece and is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained positive-pressure breathing apparatus

Escape:

(APF = 50) Any air-purifying, full-facepiece respirator (gas mask) with a chin-style, front- or back-mounted organic vapor canister/Any appropriate escape-type, self-contained breathing apparatus

APF: Assigned Protection Factor

9. Physical And Chemical Properties

Property	Value, Description
Appearance (physical state, colour etc);	Clear, colourless liquid.
Odour;	Aromatic odour.
Odour threshold;	Not available
pH;	Not applicable
Melting point/freezing point;	-35 deg C
Initial boiling point and boiling range;	139 to 141 deg C
Flash point;	27 deg C TCC Minimum
Evaporation rate;	0.8 Approximate
Upper/lower flammability or explosive limits;	1.9 to 12.3 % by volume Approximate
Vapour pressure;	1.893 kPa at 38 deg C Approximate
Vapour density;	3.7 (Air = 1)
Relative density;	0.87 at 15.5 deg C
Solubility(ies);	0.02% at 25 deg C in water
Partition coefficient: n-octanol/water;	Not available
Auto-ignition temperature;	500 deg C Approximate
Decomposition temperature;	Not available
Viscosity.	0.69 cST at 25 deg C Approximate

10. Stability And Reactivity

Reactivity/Chemical Stability: This product is stable under normal temperature and pressure

Possibility Of Hazardous Reactions: Hazardous polymerization will not occur

Conditions To Avoid: Temperature above ambient, ignition sources

Incompatible Materials: Strong oxidizing agents, concentrated nitric and sulphuric acids, acetic acid, halogen, molten sulphur and 1,3-dichloro-5,5-dimethyl-2,4-imidazolidindione (dichlorohydrantoin).

Hazardous Decomposition Products: carbon monoxide, carbon dioxide



11. Toxicological Information

LD50: 4-g/kg oral rat

LC50: 6,500-ppm rat

Inhalation: High vapour/aerosol concentrations (greater than approximately 1000 ppm) are irritating to the eyes and the respiratory tract, and may cause headaches, dizziness, anaesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death. Negligible hazard at normal temperatures (up to 38 deg C).

Eye Contact: Irritating, but will not injure eye tissue.

Skin Contact: Frequent or prolonged contact may irritate the skin.

Low toxicity. Brief contact with the liquid will not result in significant irritation unless evaporation is prevented. Skin contact may aggravate an existing dermatitis condition.

Ingestion: Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause mild to severe pulmonary injury and possibly death. Low toxicity.

Special Health Precautions: Health studies have shown that many petroleum hydrocarbons pose potential human health risks, which may vary, from person to person. As a precaution, exposure to liquids, vapours, mists or fumes should be minimised.

Occupational Exposure Limit

ACGIH Recommends: For Xylene, 100 ppm (434 mg/m3).

The previous OSHA limit for the xylenes was 100 ppm as an 8-hour TWA. Based on the ACGIH recommendation, OSHA proposed to revise this limit to a TWA of 100 ppm and a 15-minute STEL of 150 ppm. NIOSH (Ex. 8-47, Table N1) as well as the AFL-CIO (Ex. 194) concurred with these limits, and they are established in the final rule. The xylene isomers are clear, flammable liquids with an aromatic hydrocarbon odor.

Rats and rabbits exposed to a mixture of xylene isomers at a concentration of 690 ppm for eight hours daily, six days per week showed no blood abnormalities, but rabbits exposed on the same regimen at 1150 ppm for 55 days showed a decrease in red and white blood cell counts and an increase in platelet count (Fabre and Truhaut 1954, as cited in ACGIH 1986/Ex. 1-3, p. 637).

Studies of workers exposed to xylene revealed headache, fatigue, lassitude, irritability, and gastrointestinal disturbances as the most common symptoms (Gerarde 1960d/Ex. 1-738a). At unspecified exposure levels, Browning (1965b/Ex. 1-1016) also noted gastrointestinal disturbances, in addition to kidney, heart, liver, and neurological damage; blood dyscrasias, some of which resulted in death, were also reported in these workers. A study by Nelson, Enge, Ross et al. (1943/Ex. 1-66), in which human volunteers were exposed to 200 ppm xylene, found eye, nose, and throat irritation in the subjects at this level of exposure.

NIOSH developed a criteria document for xylene in 1975 (NIOSH 1975; as cited in ACGIH 1986/Ex. 1-3, p. 637), in which the work of Morley, Eccleston, Douglas, and colleagues (1970/Ex. 1-794) was discussed. These authors observed liver dysfunction and renal impairment in three workers overexposed to xylene (estimated concentration of 10,000 ppm). One of these workers died, but the others recovered slowly. Furniture polishers were reported by Matthaues (1964/Ex. 1-830) to have suffered corneal damage as a result of exposure to xylene at unknown concentrations.

One other commenter, Stanley L. Dryen of Chevron Corporation (Ex. 3-896, p. 15), objected to OSHA's issuing of a STEL, stating that there was no basis for one. OSHA disagrees and points out that a 100-ppm TWA limit alone would permit short-term exposure to several hundred ppm xylene,



well above the 200-ppm level reported to be irritating as a result of short-term exposures. OSHA notes that NIOSH also recommends a short-term limit to supplement the TWA.

After reviewing this evidence, OSHA concludes that both a TWA and a STEL are necessary to prevent the risks of narcosis, blood effects, and irritant effects at the elevated levels possible at the current exposure limit. The Agency considers the effects of narcosis, irritation, and blood effects to constitute material impairments of health and functional capacity. Therefore, to reduce the risk of irritation to workers exposed to the xylenes, OSHA is establishing a 150-ppm STEL and a 100-ppm TWA for xylene isomers in the final rule.

12. Ecological Information

Fish: Toxic: $1 < \text{LC/EC/IC}_{50} \leq 10 \text{ mg/l}$

Aquatic Invertebrates: Toxic: $1 < \text{LC/EC/IC}_{50} \leq 10 \text{ mg/l}$

Algae: Toxic: $1 < \text{LC/EC/IC}_{50} \leq 10 \text{ mg/l}$

Mobility: If product enters soil, it will be highly mobile and may contaminate groundwater. Floats on water.

Persistence/degradability: Readily biodegradable. Oxidises rapidly by photochemical reactions in air.

Bioaccumulation: Does not bioaccumulate significantly.

Other Adverse Effects: In view of the high rate of loss from solution, the product is unlikely to pose a significant hazard to aquatic life.

13. Disposal Considerations

- Material Disposal: Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
- Container Disposal: Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Do not, puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer.
- Local Legislation: Disposal should be in accordance with applicable regional, national, and local laws and regulations.
- Ensure disposal in compliance with government requirements and ensure conformity to local disposal regulations.
- **Do not** let this chemical enter the environment.

14. Transport Information

UN Number: 1307

Shipping Name: Xylenes or Xylenes Solution

Packing Group: III

Primary TDG: Class 3

Subsidiary TDG: Class 9.2

Note: C

Xn symbol

R: 10-20/21-38

S: 2-25

UN Hazard Class: 3

UN Packing Group: III

Transport Emergency Card: TEC (R)-30S1307-III

WHMIS Information:

Class B, Division 2: Flammable Liquids

Class D, Division 2, Subdivision B: Toxic Material

**Transport in Bulk (Annex II of MARPOL 73/78 and the IBC code)**

Pollution Category : Y

Ship Type : 2

Product Name : Xylenes

15. Regulatory InformationPermissible Exposure Level (Long Term) in Singapore: 100ppm (434mg/m³)Permissible Exposure Level (Short Term) in Singapore: 150ppm (651mg/m³)

TWA; 150 ppm as STEL A4 (ACGIH 2001). BEI specified by (ACGIH 2001).

EU OEL: 50 ppm as TWA; 100 ppm as STEL (skin) (EU 2000).

OSHA PEL: TWA 100 ppm (435 mg/m³)NIOSH REL: TWA 100 ppm (435 mg/m³) ST 150 ppm (655 mg/m³)

NIOSH IDLH: 900 ppm

NFPA Code: H 2; F 3; R 0

ICSC # 0085

CAS # 108-38-3

UN # 1307

EC # 601-022-00-9

16. Other Information

Prepared By: Material Safety Committee

SDS Prepared on: 1/12/2010

Reviewed 1 on 1/10/2013

Revised 2 on 11/2/2015

Revised 3 on 18/3/2015


Revision (2) Notes	
1	Sect. 14: Added information for Transport in Bulk according to MARPOL 73/78 Annex II
Revision (3) Notes	
1	Sect. 2: Flammable Liquid hazard category changed from 2 to 3

CAUTION: The information given above (“the Information”) relates only to the substance or mixture listed herein. The Information may not be valid when used in combination with any other substance or mixture or in any process. If the substance or mixture is to be used for a purpose other than that stated herein or under conditions other than specified herein, the Information cannot be relied upon as being complete or accurate, and the user is advised to consult the supplier before using the substance or mixture for such other purpose or under such other conditions. The Information is given based on information available at the indicated date of preparation and no representation or warranty is given that it will be correct as of any time after the indicated date of preparation.

(/niosh/index.htm)

TETRACHLOROETHYLENE

ICSC: 0076

1,1,2,2-Tetrachloroethylene Perchloroethylene Tetrachloroethene C_2Cl_4 / $Cl_2C=CCl_2$ Molecular mass: 165.8 ICSC # 0076		CAS # 127-18-4 RTECS # <u>KX3850000</u> UN # 1897 EC # 602-028-00-4 April 13, 2000 Validated	
			
TYPES OF HAZARD/ EXPOSURE	ACUTE HAZARDS/ SYMPTOMS	PREVENTION	FIRST AID/ FIRE FIGHTING
FIRE	Not combustible. Gives off irritating or toxic fumes (or gases) in a fire.		In case of fire in the surroundings: use appropriate extinguishing media.
EXPLOSION			
EXPOSURE		STRICT HYGIENE! PREVENT GENERATION OF MISTS!	
• INHALATION	Dizziness. Drowsiness. Headache. Nausea. Weakness. Unconsciousness.	Ventilation, local exhaust, or breathing protection.	Fresh air, rest. Artificial respiration may be needed. Refer for medical attention.
• SKIN	Dry skin. Redness.	Protective gloves. Protective clothing.	Remove contaminated clothes. Rinse and then wash skin with water and soap.
• EYES	Redness. Pain.	Safety goggles , face shield .	First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then take to a doctor.
• INGESTION	Abdominal pain. (Further see Inhalation).	Do not eat, drink, or smoke during work.	Rinse mouth. Do NOT induce vomiting. Give plenty of water to drink. Rest.
SPILLAGE DISPOSAL		STORAGE	PACKAGING & LABELLING
Ventilation. Collect leaking and spilled liquid in sealable containers as far as possible. Absorb remaining liquid in sand or inert absorbent and remove to safe place. Do NOT let this chemical enter the environment. Personal protection: filter respirator for organic gases and vapours.		Separated from metals ,(see Chemical Dangers), food and feedstuffs . Keep in the dark. Ventilation along the floor.	Do not transport with food and feedstuffs. Marine pollutant. Xn symbol N symbol R: 40-51/53 S: (2-)23-36/37-61 UN Hazard Class: 6.1 UN Packing Group: III
ICSC: 0076		Prepared in the context of cooperation between the International Programme on Chemical Safety & the Commission of the European Communities (C) IPCS CEC 1994. No modifications to the International version have been made except to add the OSHA PELs, NIOSH RELs and NIOSH IDLH values.	

ICSC: 0076


TETRACHLOROETHYLENE

I M P O R T A N T D A T A	<p>PHYSICAL STATE; APPEARANCE: COLOURLESS LIQUID , WITH CHARACTERISTIC ODOUR.</p> <p>PHYSICAL DANGERS: The vapour is heavier than air.</p> <p>CHEMICAL DANGERS: On contact with hot surfaces or flames this substance decomposes forming toxic and corrosive fumes (hydrogen chloride, phosgene, chlorine). The substance decomposes slowly on contact with moisture producing trichloroacetic acid and hydrochloric acid. Reacts with metals such as aluminium, lithium, barium, beryllium.</p> <p>OCCUPATIONAL EXPOSURE LIMITS: TLV: 25 ppm as TWA, 100 ppm as STEL; A3 (confirmed animal carcinogen with unknown relevance to humans); BEI issued; (ACGIH 2004). MAK: skin absorption (H); Carcinogen category: 3B; (DFG 2004). OSHA PEL±: TWA 100 ppm C 200 ppm 300 ppm (5-minute maximum peak in any 3-hours) NIOSH REL: Ca Minimize workplace exposure concentrations. <u>See Appendix A</u> NIOSH IDLH: Ca 150 ppm See: <u>127184</u></p>	<p>ROUTES OF EXPOSURE: The substance can be absorbed into the body by inhalation and by ingestion.</p> <p>INHALATION RISK: A harmful contamination of the air will be reached rather slowly on evaporation of this substance at 20°C.</p> <p>EFFECTS OF SHORT-TERM EXPOSURE: The substance is irritating to the eyes , the skin and the respiratory tract . If this liquid is swallowed, aspiration into the lungs may result in chemical pneumonitis. The substance may cause effects on the central nervous system. Exposure at high levels may result in unconsciousness.</p> <p>EFFECTS OF LONG-TERM OR REPEATED EXPOSURE: Repeated or prolonged contact with skin may cause dermatitis. The substance may have effects on the liver and kidneys. This substance is probably carcinogenic to humans.</p>
PHYSICAL PROPERTIES	Boiling point: 121°C Melting point: -22°C Relative density (water = 1): 1.6 Solubility in water, g/100 ml at 20°C: 0.015	Vapour pressure, kPa at 20°C: 1.9 Relative vapour density (air = 1): 5.8 Relative density of the vapour/air-mixture at 20°C (air = 1): 1.09 Octanol/water partition coefficient as log Pow: 2.9
ENVIRONMENTAL DATA	The substance is toxic to aquatic organisms. The substance may cause long-term effects in the aquatic environment.	
NOTES		
Depending on the degree of exposure, periodic medical examination is suggested. The odour warning when the exposure limit value is exceeded is insufficient. Do NOT use in the vicinity of a fire or a hot surface, or during welding. An added stabilizer or inhibitor can influence the toxicological properties of this substance, consult an expert. Card has been partly updated in April 2005. See section Occupational Exposure Limits.		
Transport Emergency Card: TEC (R)-61S1897		
NFPA Code: H2; Fo; Ro;		
ADDITIONAL INFORMATION		
ICSC: 0076		
TETRACHLOROETHYLENE		
(C) IPCS, CEC, 1994		
IMPORTANT LEGAL NOTICE:		
Neither NIOSH, the CEC or the IPCS nor any person acting on behalf of NIOSH, the CEC or the IPCS is responsible for the use which might be made of this information. This card contains the collective views of the IPCS Peer Review Committee and may not reflect in all cases all the detailed requirements included in national legislation on the subject. The user should verify compliance of the cards with the relevant legislation in the country of use. The only modifications made to produce the U.S. version is inclusion of the OSHA PELs, NIOSH RELs and NIOSH IDLH values.		

(/niosh/index.htm)

TRICHLOROETHYLENE

ICSC: 0081

1,1,2-Trichloroethylene Trichloroethene Ethylene trichloride Acetylene trichloride C_2HCl_3 / $ClCH=CCl_2$ Molecular mass: 131.4 ICSC # 0081		CAS # 79-01-6 RTECS # <u>KX4550000</u> UN # 1710 EC # 602-027-00-9 April 10, 2000 Validated	
			
TYPES OF HAZARD/ EXPOSURE	ACUTE HAZARDS/ SYMPTOMS	PREVENTION	FIRST AID/ FIRE FIGHTING
FIRE	Combustible under specific conditions. See Notes.		In case of fire in the surroundings: all extinguishing agents allowed.
EXPLOSION		Prevent build-up of electrostatic charges (e.g., by grounding).	In case of fire: keep drums, etc., cool by spraying with water.
EXPOSURE		PREVENT GENERATION OF MISTS! STRICT HYGIENE!	
• INHALATION	Dizziness. Drowsiness. Headache. Weakness. Nausea. Unconsciousness.	Ventilation, local exhaust, or breathing protection.	Fresh air, rest. Artificial respiration may be needed. Refer for medical attention.
• SKIN	Dry skin. Redness.	Protective gloves.	Remove contaminated clothes. Rinse and then wash skin with water and soap.
• EYES	Redness. Pain.	Safety spectacles, or eye protection in combination with breathing protection.	First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then take to a doctor.
• INGESTION	Abdominal pain. (Further see Inhalation).	Do not eat, drink, or smoke during work.	Rinse mouth. Do NOT induce vomiting. Give plenty of water to drink. Rest.
SPILLAGE DISPOSAL		STORAGE	PACKAGING & LABELLING
Ventilation. Collect leaking and spilled liquid in sealable containers as far as possible. Absorb remaining liquid in sand or inert absorbent and remove to safe place. Personal protection: filter respirator for organic gases and vapours. Do NOT let this chemical enter the environment.		Separated from metals (see Chemical Dangers), strong bases, food and feedstuffs . Dry. Keep in the dark. Ventilation along the floor.	Do not transport with food and feedstuffs. Marine pollutant. T symbol R: 45-36/38-52/53-67 S: 53-45-61 UN Hazard Class: 6.1 UN Packing Group: III
ICSC: 0081		Prepared in the context of cooperation between the International Programme on Chemical Safety & the Commission of the European Communities (C) IPCS CEC 1994. No modifications to the International version have been made except to add the OSHA PELs, NIOSH RELs and NIOSH IDLH values.	

ICSC: 0081

TRICHLOROETHYLENE

I M P O R T A N T D A T A	<p>PHYSICAL STATE; APPEARANCE: COLOURLESS LIQUID , WITH CHARACTERISTIC ODOUR.</p> <p>PHYSICAL DANGERS: The vapour is heavier than air. As a result of flow, agitation, etc., electrostatic charges can be generated.</p> <p>CHEMICAL DANGERS: On contact with hot surfaces or flames this substance decomposes forming toxic and corrosive fumes (phosgene , hydrogen chloride). The substance decomposes on contact with strong alkali producing dichloroacetylene , which increases fire hazard. Reacts violently with metal powders such as magnesium, aluminium, titanium, and barium. Slowly decomposed by light in presence of moisture, with formation of corrosive hydrochloric acid.</p> <p>OCCUPATIONAL EXPOSURE LIMITS: TLV: 50 ppm as TWA; 100 ppm as STEL; A5; BEI issued; (ACGIH 2004). MAK: Carcinogen category: 1; Germ cell mutagen group: 3B; (DFG 2004). OSHA PEL: TWA 100 ppm C 200 ppm 300 ppm (5-minute maximum peak in any 2 hours) NIOSH REL: Ca See Appendix A See Appendix C NIOSH IDLH: Ca 1000 ppm See: 79016</p>	<p>ROUTES OF EXPOSURE: The substance can be absorbed into the body by inhalation and by ingestion.</p> <p>INHALATION RISK: A harmful contamination of the air can be reached rather quickly on evaporation of this substance at 20°C.</p> <p>EFFECTS OF SHORT-TERM EXPOSURE: The substance is irritating to the eyes and the skin . Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. The substance may cause effects on the central nervous system , resulting in respiratory failure . Exposure could cause lowering of consciousness.</p> <p>EFFECTS OF LONG-TERM OR REPEATED EXPOSURE: Repeated or prolonged contact with skin may cause dermatitis. The substance may have effects on the central nervous system , resulting in loss of memory. The substance may have effects on the liver and kidneys (see Notes). This substance is probably carcinogenic to humans.</p>
PHYSICAL PROPERTIES	Boiling point: 87°C Melting point: -73°C Relative density (water = 1): 1.5 Solubility in water, g/100 ml at 20°C: 0.1 Vapour pressure, kPa at 20°C: 7.8 Relative vapour density (air = 1): 4.5	Relative density of the vapour/air-mixture at 20°C (air = 1): 1.3 Auto-ignition temperature: 410°C Explosive limits, vol% in air: 8-10.5 Octanol/water partition coefficient as log Pow: 2.42 Electrical conductivity (NOT on card): 800pS/m
ENVIRONMENTAL DATA	The substance is harmful to aquatic organisms. The substance may cause long-term effects in the aquatic environment.	
NOTES		
<p>Combustible vapour/air mixtures difficult to ignite, may be developed under certain conditions. Use of alcoholic beverages enhances the harmful effect. Depending on the degree of exposure, periodic medical examination is suggested. The odour warning when the exposure limit value is exceeded is insufficient. Do NOT use in the vicinity of a fire or a hot surface, or during welding. An added stabilizer or inhibitor can influence the toxicological properties of this substance, consult an expert. Card has been partly updated in October 2004. See sections Occupational Exposure Limits, EU classification, Emergency Response.</p> <p>Transport Emergency Card: TEC (R)-61S1710</p> <p>NFPA Code: H2; F1; R0;</p>		
ADDITIONAL INFORMATION		
ICSC: 0081		
(C) IPCS, CEC, 1994		
TRICHLOROETHYLENE		
IMPORTANT LEGAL NOTICE:		
Neither NIOSH, the CEC or the IPCS nor any person acting on behalf of NIOSH, the CEC or the IPCS is responsible for the use which might be made of this information. This card contains the collective views of the IPCS Peer Review Committee and may not reflect in all cases all the detailed requirements included in national legislation on the subject. The user should verify compliance of the cards with the relevant legislation in the country of use. The only modifications made to produce the U.S. version is inclusion of the OSHA PELs, NIOSH RELs and NIOSH IDLH values.		

Page last reviewed: July 22, 2015

Page last updated: July 1, 2014

Content source: National Institute for Occupational Safety and Health (<http://www.cdc.gov/NIOSH/>)



Safety Data Sheet

Revision Date: 03/02/18

www.restek.com

2 Letter ISO country code/language code: US/EN

1. IDENTIFICATION

Catalog Number / Product Name: 30279 / cis-1,2-Dichloroethene Standard
Company: Restek Corporation
Address: 110 Benner Circle
Bellefonte, Pa. 16823
Phone#: 814-353-1300
Fax#: 814-353-1309
Emergency#: 800-424-9300 (CHEMTREC)
703-527-3887 (Outside the US)
Email: www.restek.com
Revision Number: 9
Intended use: For Laboratory use only

2. HAZARD(S) IDENTIFICATION

Emergency Overview:

GHS Hazard
Symbols:



GHS Classification: Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 1
Flammable Liquid Category 2
Acute Toxicity - Inhalation Dust / Mist Category 3
Acute Toxicity - Dermal Category 3
Acute Toxicity - Oral Category 3

GHS Signal Word: Danger

GHS Hazard: Highly flammable liquid and vapour.
Toxic if swallowed, in contact with skin or if inhaled.
Causes damage to organs.

GHS Precautions:

Safety Precautions: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilation and lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wash hands and skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

First Aid Measures: IF SWALLOWED: Immediately call a POISON CENTER/doctor/....
IF ON SKIN: Wash with plenty of soap and water.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Specific treatment see section 4.
Rinse mouth.
Take off immediately all contaminated clothing and wash it before reuse.
In case of fire: Use extinguishing media in section 5 for extinction.

Storage: Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal: Dispose of contents/container according to section 13 of the SDS.

Single Exposure Target Organs: Specific target organ toxicity - Single exposure - STOT SE 1: H370 Causes damage to organs. (C \geq 10 %; No information to prove exclusion of certain routes of exposure); Specific target organ toxicity - Single exposure - STOT SE 2: H371 May cause damage to organs. (3 % \leq C < 10 %; Concentration limits for acute toxicity cannot be translated into GHS from the DSD especially when minimum classifications are given)

Repeated Exposure Target Organs: No data available

3. COMPOSITION / INFORMATION ON INGREDIENT

Chemical Name	CAS #	EINEC #	% Composition
methanol	67-56-1	200-659-6	99.8
cis-1,2-dichloroethylene	156-59-2	205-859-7	0.2

4. FIRST-AID MEASURES

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately

Eyes: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

Skin Contact: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

Ingestion: Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this SDS.

5. FIRE- FIGHTING MEASURES

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire.

Fire and/or Explosion Hazards: Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.

Fire Fighting Methods and Protection: Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

Hazardous Combustion Products: Carbon dioxide, Carbon monoxide

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment: Exposure to the spilled material may be severely irritating or toxic. Follow personal protective equipment recommendations found in Section 8 of this SDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits.

Methods for Clean-up: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

7. HANDLING AND STORAGE

Handling Technical Measures and Precautions: Toxic or severely irritating material. Avoid contacting and avoid

Storage Technical Measures and Conditions:

breathing the material. Use only in a well ventilated area. Use spark-proof tools and explosion-proof equipment
Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Keep away from sources of ignition

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**United States:**

Chemical Name	CAS No.	IDLH	ACGIH STEL	ACGIH TLV-TWA	OSHA Exposure Limit
methanol	67-56-1	6000 ppm IDLH	250 ppm STEL	200 ppm TWA	200 ppm TWA; 260 mg/m3 TWA

Personal Protection:**Engineering Measures:**

Local exhaust ventilation is recommended when generating excessive levels of vapours from handling or thermal processing.

Respiratory Protection:

Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. If an exposure limit is exceeded or if an operator is experiencing symptoms of inhalation overexposure as explained in Section 3, provide respiratory protection.

Eye Protection:

Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.

Skin Protection:

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance, color:	No data available
Odor:	Mild
Physical State:	Liquid
pH:	Not applicable
Vapor Pressure:	No data available
Vapor Density:	1.1 (air = 1)
Boiling Point (°C):	64.7 °C at 760 mmHg (HSDB)
Melting Point (°C):	-98 °C
Flash Point (°F):	52
Flammability:	Highly Flammable
Upper Flammable/Explosive Limit, % in air:	36
Lower Flammable/Explosive Limit, % in air:	6
Autoignition Temperature (°C):	464 deg C
Decomposition Temperature (°C):	No data available
Specific Gravity:	0.791 - 0.792 g/cm3 at 20 °C
Evaporation Rate:	No data available
Odor Threshold:	No data available
Solubility:	Moderate; 50-99%
Partition Coefficient: n-octanol in water:	No data available
VOC % by weight:	0
Molecular Weight:	32.04

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	None known.
Materials to Avoid / Chemical Incompatibility:	Strong oxidizing agents
Hazardous Decomposition Products:	Carbon dioxide Carbon monoxide

11. TOXICOLOGICAL INFORMATION

Routes of Entry:	Inhalation, Skin Contact, Eye Contact, Ingestion
Target Organs Potentially Affected By Exposure:	Eyes, Central nervous system stimulation, Skin, GI Tract, Respiratory Tract
Chemical Interactions That Change Toxicity:	None Known

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation:	Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.
Inhalation Toxicity:	Harmful! Can cause systemic damage (see "Target Organs")Methanol can cause central nervous system depression and overexposure can cause damage to the optic nerve resulting in visual impairment or blindness.
Skin Contact:	Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Eye Contact:	Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
Ingestion Irritation:	Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea.Highly toxic and may be fatal if swallowed.
Ingestion Toxicity:	Toxic if swallowed. May cause target organ failure and/or death.May be fatal if swallowed.

Long-Term (Chronic) Health Effects:

Carcinogenicity:	No data.
Reproductive and Developmental Toxicity:	No data available to indicate product or any components present at greater than 0.1% may cause birth defects.
Inhalation:	Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.Harmful! Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs")
Skin Contact:	Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Ingestion:	Toxic if swallowed. May cause target organ failure and/or death.

Component Toxicological Data:

NIOSH:

Chemical Name	CAS No.	LD50/LC50
Methanol	67-56-1	Inhalation LC50 Rat 22500 ppm 8 h

Component Carcinogenic Data:

OSHA:

Chemical Name	CAS No.
No data available	

ACGIH:

Chemical Name	CAS No.
No data available	

NIOSH:

Chemical Name	CAS No.
No data available	

NTP:

Chemical Name	CAS No.
No data available	

IARC:

Chemical Name	CAS No.	Group No.
----------------------	----------------	------------------

12. ECOLOGICAL INFORMATION

Overview:	Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.
Mobility:	No data
Persistence:	No data
Bioaccumulation:	No data
Degradability:	Biodegrades slowly.
Ecological Toxicity Data:	No data available

13. DISPOSAL CONSIDERATIONS

Waste Description of Spent Product:	Spent or discarded material is a hazardous waste.Mixing spent or discarded material with other materials may
--	--

Disposal Methods:

render the mixture hazardous. Perform a hazardous waste determination on mixtures.

Waste Disposal of Packaging:

Dispose of by incineration following Federal, State, Local, or Provincial regulations.
Comply with all Local, State, Federal, and Provincial Environmental Regulations.

14. TRANSPORTATION INFORMATION**United States:**

DOT Proper Shipping Name: Methanol
UN Number: UN1230
Hazard Class: 3
Packing Group: II

International:

IATA Proper Shipping Name: Methanol
UN Number: UN1230
Hazard Class: 3(6.1)
Packing Group: II

Marine Pollutant: No

Chemical Name	CAS#	Marine Pollutant	Severe Marine Pollutant
No data available			

15. REGULATORY INFORMATION**United States:**

Chemical Name	CAS#	CERCLA	SARA 313	SARA EHS 313	TSCA
methanol	67-56-1	X	X	-	X

The following chemicals are listed on CA Prop 65:

Chemical Name	CAS #	Regulation
Methanol	67-56-1	Prop 65 Develop Tox

State Right To Know Listing:

Chemical Name	CAS#	New Jersey	Massachusetts	Pennsylvania	California
methanol	67-56-1	X	X	X	X
cis-1,2-dichloroethylene	156-59-2	-	X	X	-

16. OTHER INFORMATION

Prior Version Date: 10/28/16

Other Information: Any changes to the SDS compared to previous versions are marked by a vertical line in front of the concerned paragraph.

References: No data available

Disclaimer: Restek Corporation provides the descriptions, data and information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. It is provided for your guidance only. Because many factors may affect processing or application/use, Restek Corporation recommends you perform an assessment to determine the suitability of a product for your particular purpose prior to use. No warranties of any kind, either expressed or implied, including fitness for a particular purpose, are made regarding products described, data or information set forth. In no case shall the descriptions, information, or data provided be considered a part of our terms and conditions of sale. Further, the descriptions, data and information furnished hereunder are given gratis. No obligation or liability for the description, data and information given are assumed. All such being given and accepted at your risk.



Safety Data Sheet

Revision Date: 03/02/18

www.restek.com

2 Letter ISO country code/language code: US/EN

1. IDENTIFICATION

Catalog Number / Product Name: 30279 / cis-1,2-Dichloroethene Standard
Company: Restek Corporation
Address: 110 Benner Circle
Bellefonte, Pa. 16823
Phone#: 814-353-1300
Fax#: 814-353-1309
Emergency#: 800-424-9300 (CHEMTREC)
703-527-3887 (Outside the US)
Email: www.restek.com
Revision Number: 9
Intended use: For Laboratory use only

2. HAZARD(S) IDENTIFICATION

Emergency Overview:

GHS Hazard
Symbols:



GHS Classification: Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 1
Flammable Liquid Category 2
Acute Toxicity - Inhalation Dust / Mist Category 3
Acute Toxicity - Dermal Category 3
Acute Toxicity - Oral Category 3

GHS Signal Word: Danger

GHS Hazard: Highly flammable liquid and vapour.
Toxic if swallowed, in contact with skin or if inhaled.
Causes damage to organs.

GHS Precautions:

Safety Precautions: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilation and lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wash hands and skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

First Aid Measures: IF SWALLOWED: Immediately call a POISON CENTER/doctor/....
IF ON SKIN: Wash with plenty of soap and water.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Specific treatment see section 4.
Rinse mouth.
Take off immediately all contaminated clothing and wash it before reuse.
In case of fire: Use extinguishing media in section 5 for extinction.

Storage: Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal: Dispose of contents/container according to section 13 of the SDS.

Single Exposure Target Organs: Specific target organ toxicity - Single exposure - STOT SE 1: H370 Causes damage to organs. (C \geq 10 %; No information to prove exclusion of certain routes of exposure); Specific target organ toxicity - Single exposure - STOT SE 2: H371 May cause damage to organs. (3 % \leq C < 10 %; Concentration limits for acute toxicity cannot be translated into GHS from the DSD especially when minimum classifications are given)

Repeated Exposure Target Organs: No data available

3. COMPOSITION / INFORMATION ON INGREDIENT

Chemical Name	CAS #	EINEC #	% Composition
methanol	67-56-1	200-659-6	99.8
cis-1,2-dichloroethylene	156-59-2	205-859-7	0.2

4. FIRST-AID MEASURES

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately

Eyes: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

Skin Contact: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

Ingestion: Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this SDS.

5. FIRE- FIGHTING MEASURES

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire.

Fire and/or Explosion Hazards: Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.

Fire Fighting Methods and Protection: Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

Hazardous Combustion Products: Carbon dioxide, Carbon monoxide

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment: Exposure to the spilled material may be severely irritating or toxic. Follow personal protective equipment recommendations found in Section 8 of this SDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits.

Methods for Clean-up: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

7. HANDLING AND STORAGE

Handling Technical Measures and Precautions: Toxic or severely irritating material. Avoid contacting and avoid

Storage Technical Measures and Conditions:

breathing the material. Use only in a well ventilated area. Use spark-proof tools and explosion-proof equipment
Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Keep away from sources of ignition

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**United States:**

Chemical Name	CAS No.	IDLH	ACGIH STEL	ACGIH TLV-TWA	OSHA Exposure Limit
methanol	67-56-1	6000 ppm IDLH	250 ppm STEL	200 ppm TWA	200 ppm TWA; 260 mg/m3 TWA

Personal Protection:**Engineering Measures:**

Local exhaust ventilation is recommended when generating excessive levels of vapours from handling or thermal processing.

Respiratory Protection:

Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. If an exposure limit is exceeded or if an operator is experiencing symptoms of inhalation overexposure as explained in Section 3, provide respiratory protection.

Eye Protection:

Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.

Skin Protection:

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance, color:	No data available
Odor:	Mild
Physical State:	Liquid
pH:	Not applicable
Vapor Pressure:	No data available
Vapor Density:	1.1 (air = 1)
Boiling Point (°C):	64.7 °C at 760 mmHg (HSDB)
Melting Point (°C):	-98 °C
Flash Point (°F):	52
Flammability:	Highly Flammable
Upper Flammable/Explosive Limit, % in air:	36
Lower Flammable/Explosive Limit, % in air:	6
Autoignition Temperature (°C):	464 deg C
Decomposition Temperature (°C):	No data available
Specific Gravity:	0.791 - 0.792 g/cm3 at 20 °C
Evaporation Rate:	No data available
Odor Threshold:	No data available
Solubility:	Moderate; 50-99%
Partition Coefficient: n-octanol in water:	No data available
VOC % by weight:	0
Molecular Weight:	32.04

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	None known.
Materials to Avoid / Chemical Incompatibility:	Strong oxidizing agents
Hazardous Decomposition Products:	Carbon dioxide Carbon monoxide

11. TOXICOLOGICAL INFORMATION

Routes of Entry:	Inhalation, Skin Contact, Eye Contact, Ingestion
Target Organs Potentially Affected By Exposure:	Eyes, Central nervous system stimulation, Skin, GI Tract, Respiratory Tract
Chemical Interactions That Change Toxicity:	None Known

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation:	Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.
Inhalation Toxicity:	Harmful! Can cause systemic damage (see "Target Organs")Methanol can cause central nervous system depression and overexposure can cause damage to the optic nerve resulting in visual impairment or blindness.
Skin Contact:	Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Eye Contact:	Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
Ingestion Irritation:	Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea.Highly toxic and may be fatal if swallowed.
Ingestion Toxicity:	Toxic if swallowed. May cause target organ failure and/or death.May be fatal if swallowed.

Long-Term (Chronic) Health Effects:

Carcinogenicity:	No data.
Reproductive and Developmental Toxicity:	No data available to indicate product or any components present at greater than 0.1% may cause birth defects.
Inhalation:	Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.Harmful! Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs")
Skin Contact:	Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Ingestion:	Toxic if swallowed. May cause target organ failure and/or death.

Component Toxicological Data:

NIOSH:

Chemical Name	CAS No.	LD50/LC50
Methanol	67-56-1	Inhalation LC50 Rat 22500 ppm 8 h

Component Carcinogenic Data:

OSHA:

Chemical Name	CAS No.
No data available	

ACGIH:

Chemical Name	CAS No.
No data available	

NIOSH:

Chemical Name	CAS No.
No data available	

NTP:

Chemical Name	CAS No.
No data available	

IARC:

Chemical Name	CAS No.	Group No.
----------------------	----------------	------------------

12. ECOLOGICAL INFORMATION

Overview:	Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.
Mobility:	No data
Persistence:	No data
Bioaccumulation:	No data
Degradability:	Biodegrades slowly.
Ecological Toxicity Data:	No data available

13. DISPOSAL CONSIDERATIONS

Waste Description of Spent Product:	Spent or discarded material is a hazardous waste.Mixing spent or discarded material with other materials may
--	--

Disposal Methods:

render the mixture hazardous. Perform a hazardous waste determination on mixtures.

Waste Disposal of Packaging:

Dispose of by incineration following Federal, State, Local, or Provincial regulations.
Comply with all Local, State, Federal, and Provincial Environmental Regulations.

14. TRANSPORTATION INFORMATION**United States:**

DOT Proper Shipping Name: Methanol
UN Number: UN1230
Hazard Class: 3
Packing Group: II

International:

IATA Proper Shipping Name: Methanol
UN Number: UN1230
Hazard Class: 3(6.1)
Packing Group: II

Marine Pollutant: No

Chemical Name	CAS#	Marine Pollutant	Severe Marine Pollutant
No data available			

15. REGULATORY INFORMATION**United States:**

Chemical Name	CAS#	CERCLA	SARA 313	SARA EHS 313	TSCA
methanol	67-56-1	X	X	-	X

The following chemicals are listed on CA Prop 65:

Chemical Name	CAS #	Regulation
Methanol	67-56-1	Prop 65 Develop Tox

State Right To Know Listing:

Chemical Name	CAS#	New Jersey	Massachusetts	Pennsylvania	California
methanol	67-56-1	X	X	X	X
cis-1,2-dichloroethylene	156-59-2	-	X	X	-

16. OTHER INFORMATION

Prior Version Date: 10/28/16

Other Information: Any changes to the SDS compared to previous versions are marked by a vertical line in front of the concerned paragraph.

References: No data available

Disclaimer: Restek Corporation provides the descriptions, data and information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. It is provided for your guidance only. Because many factors may affect processing or application/use, Restek Corporation recommends you perform an assessment to determine the suitability of a product for your particular purpose prior to use. No warranties of any kind, either expressed or implied, including fitness for a particular purpose, are made regarding products described, data or information set forth. In no case shall the descriptions, information, or data provided be considered a part of our terms and conditions of sale. Further, the descriptions, data and information furnished hereunder are given gratis. No obligation or liability for the description, data and information given are assumed. All such being given and accepted at your risk.

Worldwide Helpline :+1.415.685.4395
For further enquiries :info@clearsynth.com
For an online quote : [click here](#)



- MATERIAL SAFETY DATA SHEET -

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MSDS Name : 4,4'-Dichlorodiphenyldichloroethane
Company Identification : Clearsynth Labs Pvt. Ltd.
413 Laxmi Mall, New Link Road, Andheri (W),
Mumbai-400 053, INDIA
For information call : ++91-22-26355700
For emergencies call : ++91-22-26355699
For further enquiries : info@clearsynth.com

SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS

CAS#	Chemical Name	%	EINECS#	Haz Symbols	RISK PHRASES
72-54-8	4,4'-Dichlorodiphenyldichloroethane	>95%	-	-	-

Hazard Symbols: XN

Risk Phrases: 22

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Harmful if swallowed.

Potential Health Effects

The toxicological properties of this material have not been investigated. Use appropriate procedures to prevent opportunities for direct contact with the skin or eyes and to prevent inhalation. Compound is Non-hazardous, Non-Toxic/Non-Flammable.

SECTION 4 - FIRST AID MEASURES

Eyes:

Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids.

Skin:

Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.

Ingestion:

Do NOT induce vomiting. If conscious and alert, rinse mouth and drink 2-4 cupfuls of milk or water.

Inhalation:

Remove from exposure and move to fresh air immediately.

Notes to Physician:

SECTION 5 - FIRE FIGHTING MEASURES

General Information:

As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or

combustion.

Extinguishing Media:

In case of fire, use water, dry chemical, chemical foam, or alcohol-resistant foam.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

General Information: Use proper personal protective equipment as indicated in Section 8.

Spills/Leaks:

Clean up spills immediately, observing precautions in the Protective Equipment section. Sweep up, then place into a suitable container for disposal.

SECTION 7 - HANDLING and STORAGE

Handling:

Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Avoid contact with eyes, skin, and clothing. Avoid ingestion and inhalation.

Storage:

Store in a well closed container.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

Engineering Controls:

Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Use process enclosure, local exhaust ventilation, or other engineering controls to control airborne levels.

Personal Protective Equipment

Eyes:

Wear safety glasses and chemical goggles if splashing is possible.

Skin:

Wear appropriate protective gloves and clothing to prevent skin exposure.

Clothing:

Wear appropriate protective clothing to minimize contact with skin.

Respirators:

Wear a NIOSH/MSHA or European Standard EN 149 approved full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State: _____

Molecular Formula: _____

C₁₄H₁₀Cl₄

Molecular Weight: _____

320.04

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability:

Stable under normal temperatures and pressures.

Conditions to Avoid:

Incompatible materials, strong oxidants.

Incompatibilities with Other Materials:

Strong oxidizing agents, strong bases.

Hazardous Decomposition Products:

Nitrogen oxides, carbon monoxide, irritating and toxic fumes and gases, carbon dioxide, nitrogen.

Hazardous Polymerization: Has not been reported.

SECTION 11 - TOXICOLOGICAL INFORMATION

RTECS#:

CAS#: LD50/LC50:

CAS#:Draize test, rabbit, eye: 100 mg/24H Moderate; Oral,
mouse: LD50 = 300 mg/kg; Oral, rabbit: LD50 = 3200 mg/kg; Oral, rat:
LD50 = 980 mg/kg.

Carcinogenicity:

Salicylamide -

Not listed by ACGIH, IARC, NIOSH, NTP, or OSHA.

See actual entry in RTECS for complete information.

SECTION 12 - ECOLOGICAL INFORMATION

SECTION 13 - DISPOSAL CONSIDERATIONS

Dispose of in a manner consistent with federal, state, and local regulations.

SECTION 14 - TRANSPORT INFORMATION

IATA No information available.

IMO No information available.

ID/ADR No information available.

SECTION 15 - REGULATORY INFORMATION

European/International Regulations

European Labeling in Accordance with EC Directives

Hazard Symbols: XN

Risk Phrases:

R 22 Harmful if swallowed.

Safety Phrases:

WGK (Water Danger/Protection)

CAS# United Kingdom Occupational Exposure Limits

United Kingdom Maximum Exposure Limits

Canada

CAS# is listed on Canada's DSL List.

CAS# is not listed on Canada's Ingredient Disclosure List.

Exposure Limits

US FEDERAL

TSCA

CAS# is listed on the TSCA inventory.

SECTION 16 - ADDITIONAL INFORMATION

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way shall the company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if the company has been advised of the possibility of such damages.

SAFETY DATA SHEET

Creation Date 22-Mar-2012

Revision Date 18-Jan-2018

Revision Number 3

1. Identification

Product Name DDE I, Restriction Enzyme

Cat No. : BP3350-1; BP3350-5

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet**Company**

Fisher Scientific
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Emergency Telephone Number

CHEMTREC®, Inside the USA: 800-424-9300
CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification**Classification**

Classification under 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Based on available data, the classification criteria are not met

Label Elements

None required

Hazards not otherwise classified (HNOC)

None identified

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Glycerin	56-81-5	50.0
DDE I, Restriction Enzyme	NA	50.0

4. First-aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Skin Contact	Wash off immediately with plenty of water for at least 15 minutes.
Inhalation	Move to fresh air.
Ingestion	Do not induce vomiting.
Most important symptoms and effects	No information available.
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Unsuitable Extinguishing Media	No information available
Flash Point	No information available
Method -	No information available
Autoignition Temperature	No information available
Explosion Limits	
Upper	No data available
Lower	No data available
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

None known

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health
1

Flammability
1

Instability
0

Physical hazards
N/A

6. Accidental release measures

Personal Precautions	Ensure adequate ventilation. Use personal protective equipment.
Environmental Precautions	See Section 12 for additional ecological information.

Methods for Containment and Clean Up No information available.

7. Handling and storage

Handling	Ensure adequate ventilation.
Storage	Store in freezer. Keep container tightly closed in a dry and well-ventilated place.

8. Exposure controls / personal protection

Exposure Guidelines	This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.
----------------------------	---

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Glycerin		(Vacated) TWA: 10 mg/m ³ (Vacated) TWA: 5 mg/m ³ TWA: 15 mg/m ³ TWA: 5 mg/m ³		TWA: 10 mg/m ³

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

Engineering Measures None under normal use conditions.**Personal Protective Equipment****Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.**Skin and body protection** Wear appropriate protective gloves and clothing to prevent skin exposure.**Respiratory Protection** No protective equipment is needed under normal use conditions.**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice.**9. Physical and chemical properties**

Physical State	Liquid
Appearance	No information available
Odor	No information available
Odor Threshold	No information available
pH	No information available
Melting Point/Range	No data available
Boiling Point/Range	No information available
Flash Point	No information available
Evaporation Rate	No information available
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	No information available
Vapor Density	No information available
Specific Gravity	No information available
Solubility	No information available
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	No information available
Decomposition Temperature	No information available
Viscosity	No information available

10. Stability and reactivity**Reactive Hazard** None known, based on information available**Stability** Hygroscopic. heat sensitive.**Conditions to Avoid** Exposure to moist air or water. Excess heat.**Incompatible Materials** Strong oxidizing agents**Hazardous Decomposition Products** None under normal use conditions**Hazardous Polymerization** Hazardous polymerization does not occur.**Hazardous Reactions** None under normal processing.**11. Toxicological information**

Acute Toxicity**Product Information****Oral LD50**

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Dermal LD50

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Vapor LC50

Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Glycerin	12600 mg/kg (Rat)	> 10 g/kg (Rabbit)	> 2.75 mg/L/4h (Rat)(mist)

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation No information available

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Glycerin	56-81-5	Not listed	Not listed	Not listed	Not listed	Not listed
DDE I, Restriction Enzyme	NA	Not listed	Not listed	Not listed	Not listed	Not listed

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure None known

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed No information available

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Glycerin	Not listed	LC50: 51 - 57 mL/L, 96h static (Oncorhynchus mykiss)	Not listed	EC50: > 500 mg/L, 24h (Daphnia magna)

Persistence and Degradability No information available

Bioaccumulation/ Accumulation No information available.

Mobility No information available.

Component	log Pow
Glycerin	-1.76

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN1845
 Proper Shipping Name CARBON DIOXIDE, SOLID
 Hazard Class 9
 Packing Group III

TDG

UN-No UN1845
 Proper Shipping Name CARBON DIOXIDE, SOLID
 Hazard Class 9
 Packing Group III

IATA

Not regulated

IMDG/IMO

Not regulated

15. Regulatory information

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Glycerin	X	X	-	200-289-5	-		X	X	X	X	X

Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

OSHA Occupational Safety and Health Administration
 Not applicable

CERCLA Not applicable

California Proposition 65 This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Not applicable

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Glycerin	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

16. Other information

Prepared By Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Creation Date 22-Mar-2012

Revision Date 18-Jan-2018

Print Date 18-Jan-2018

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS

1. Identification

Product identifier	4,4'-DDT	
Other means of identification		
Product code	N-10876	
Synonym(s)	1,1,1-TRICHLORO-2,2-BIS(4-CHLOROPHENYL)ETHANE * 4,4'-Dichlorodiphenyl trichloroethane	
Recommended use	For Laboratory Use Only	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Manufacturer		
Company name	Chem Service, Inc.	
Address	660 Tower Lane West Chester, PA 19380 United States	
Telephone	Toll Free	800-452-9994
	Direct	610-692-3026
Website	www.chemservice.com	
E-mail	info@chemservice.com	
Emergency phone number	Chemtrec US	800-424-9300
	Chemtrec outside US	+1 703-527-3887

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Acute toxicity, oral	Category 3
	Acute toxicity, dermal	Category 3
	Carcinogenicity	Category 2
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	Toxic if swallowed. Toxic in contact with skin. Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). Rinse mouth. Take off immediately all contaminated clothing and wash it before reuse. Collect spillage.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	Not applicable.

3. Composition/information on ingredients

Substances

Chemical name	Common name and synonyms	CAS number	%
4,4'-DDT	1,1,1-TRICHLORO-2,2-BIS(4-CHLOROPHENYL)ETHANE 4,4'-Dichlorodiphenyl trichloroethane	50-29-3	100

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Wash off with soap and plenty of water. Call a POISON CENTER or doctor/physician if you feel unwell.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
Most important symptoms/effects, acute and delayed	Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off immediately all contaminated clothing. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water spray. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	Use water spray to cool unopened containers.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Immediately evacuate personnel to safe areas. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	The product is immiscible with water and will spread on the water surface. Stop the flow of material, if this is without risk. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not taste or swallow. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Avoid release to the environment. Do not empty into drains.
--------------------------------------	---

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Material	Type	Value
4,4"-DDT (CAS 50-29-3)	PEL	1 mg/m3

US. ACGIH Threshold Limit Values

Material	Type	Value
4,4"-DDT (CAS 50-29-3)	TWA	1 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Material	Type	Value
4,4"-DDT (CAS 50-29-3)	TWA	0.5 mg/m3

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

4,4'-DDT (CAS 50-29-3) Can be absorbed through the skin.

US - Tennessee OELs: Skin designation

4,4'-DDT (CAS 50-29-3) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

4,4'-DDT (CAS 50-29-3) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear eye/face protection. Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves.

Other Wear appropriate chemical resistant clothing.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.
Form Solid. Crystalline Solid
Color Colorless

Odor Not available.

Odor threshold Not available.

pH Not available.

Melting point/freezing point 227.3 °F (108.5 °C)

Initial boiling point and boiling range 500 °F (260 °C)

366.8 °F (186 °C) 0.006666 kPa

Flash point 162.0 - 171.0 °F (72.2 - 77.2 °C) Closed Cup

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	< 0 kPa at 20 °C
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Insoluble
Partition coefficient (n-octanol/water)	6.9
Auto-ignition temperature	Not available.
Decomposition temperature	230 °F (110 °C)
Viscosity	Not available.
Other information	
Density	0.98 g/cm3 estimated
Flammability class	Combustible IIIA estimated
Molecular formula	C14-H9-Cl5
Molecular weight	354.49 g/mol
Specific gravity	0.98 - 0.99

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid temperatures exceeding the decomposition temperature. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Toxic if swallowed.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	Toxic in contact with skin.
Eye contact	Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.
---	--

Information on toxicological effects

Acute toxicity	Toxic if swallowed. Toxic in contact with skin.
-----------------------	---

Product	Species	Test Results
4,4'-DDT (CAS 50-29-3)		
Acute		
<i>Dermal</i>		
LD50	Guinea pig	1000 mg/kg
	Mouse	250 mg/kg
	Rabbit	300 mg/kg
	Rat	1931 mg/kg
<i>Oral</i>		
LD50	Dog	500 mg/kg
	Goat	> 1000 mg/kg
	Guinea pig	250 mg/kg
	Mouse	150 mg/kg
	Rabbit	300 mg/kg

Product	Species	Test Results
Other LD50	Rat	87 mg/kg
	Sheep	> 1000 mg/kg
	Cat	32 mg/kg
	Dog	68 mg/kg
	Guinea pig	150 mg/kg
	Monkey	55 mg/kg
	Mouse	32 mg/kg
	Rabbit	30 mg/kg
	Rat	9.1 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

4,4'-DDT (CAS 50-29-3) 2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

4,4'-DDT (CAS 50-29-3) Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. Causes damage to organs through prolonged or repeated exposure.

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Product		Species	Test Results
4,4'-DDT (CAS 50-29-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	0.0005 - 0.001 mg/l, 48 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	0.0013 - 0.002 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential Not available.

Partition coefficient n-octanol / water (log Kow)

6.91

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
US RCRA Hazardous Waste U List: Reference	
4,4'-DDT (CAS 50-29-3)	U061
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

UN number	UN2811
UN proper shipping name	Toxic solids, organic, n.o.s. (4,4'-DDT RQ = 1 LBS), MARINE POLLUTANT
Transport hazard class(es)	
Class	6.1(PGIII)
Subsidiary risk	-
Label(s)	6.1
Packing group	III
Environmental hazards	
Marine pollutant	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	IB8, IP3, T1, TP33
Packaging exceptions	153
Packaging non bulk	213
Packaging bulk	240

IATA

UN number	UN2811
UN proper shipping name	Toxic solid, organic, n.o.s. (4,4'-DDT)
Transport hazard class(es)	
Class	6.1(PGIII)
Subsidiary risk	-
Packing group	III
Environmental hazards	No.
ERG Code	6L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

UN number	UN2811
UN proper shipping name	TOXIC SOLID, ORGANIC, N.O.S. (4,4'-DDT), MARINE POLLUTANT
Transport hazard class(es)	
Class	6.1(PGIII)
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	Yes
EmS	F-A, S-A
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.


DOT



IATA; IMDG



Marine pollutant



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

4,4'-DDT (CAS 50-29-3)

0.1 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

4,4'-DDT (CAS 50-29-3)

Listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

Yes

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

4,4'-DDT (CAS 50-29-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Clean Water Act (CWA) Section 112(r) (40 CFR 68.130)	Hazardous substance Priority pollutant Bioaccumulative chemical of concern Toxic pollutant
Safe Drinking Water Act (SDWA)	Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

4,4'-DDT (CAS 50-29-3)

US. New Jersey Worker and Community Right-to-Know Act

4,4'-DDT (CAS 50-29-3) 500 LBS

US. Pennsylvania RTK - Hazardous Substances

4,4'-DDT (CAS 50-29-3)

US. Rhode Island RTK

4,4'-DDT (CAS 50-29-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

4,4'-DDT (CAS 50-29-3) Listed: October 1, 1987

US - California Proposition 65 - CRT: Listed date/Developmental toxin

4,4'-DDT (CAS 50-29-3) Listed: May 15, 1998

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

4,4'-DDT (CAS 50-29-3) Listed: May 15, 1998

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

4,4'-DDT (CAS 50-29-3) Listed: May 15, 1998

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	06-09-2014
Version #	01
NFPA ratings	Health: 2 Flammability: 2 Instability: 0

Disclaimer


The above information is believed to be correct on the date it was last revised and must not be considered all inclusive. The information has been obtained only by a search of available literature and is only a guide for handling the chemicals. OSHA regulations require that if other hazards become evident, an upgraded SDS must be made available to the employee within three months. RESPONSIBILITY for updates lies with the employer and not with CHEM SERVICE, Inc.

Persons not specifically and properly trained should not handle this chemical or its container. This product is furnished FOR LABORATORY USE ONLY! Our products may NOT BE USED as drugs, cosmetics, agricultural or pesticide products, food additives or as household chemicals.

This Safety Data Sheet (SDS) is intended only for use with Chem Service, Inc. products and should not be relied on for use with materials from any other supplier even if the chemical name(s) on the product are identical! Whenever using an SDS for a solution or mixture the user should refer to the SDS for every component of the solution or mixture. Chem Service warrants that this SDS is based upon the most current information available to Chem Service at the time it was last revised. THIS WARRANTY IS EXCLUSIVE, AND CHEM SERVICE, INC. MAKES NO OTHER WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. This SDS is provided gratis and CHEM SERVICE, INC. SHALL NOT BE LIABLE FOR ANY INCIDENTAL, CONSEQUENTIAL OR CONTINGENT DAMAGES.

Copyright © 2000-2014 Chem Service, Inc. All rights reserved except that this SDS may be printed for the use of a customer or prospective customer of Chem Service, Inc provided the entire SDS is printed. The SDS may not be placed in any database or otherwise stored or distributed in electronic or any other form.

This product is furnished FOR LABORATORY USE ONLY.



Health	3
Fire	1
Reactivity	2
Personal Protection	E

Material Safety Data Sheet

Arsenic MSDS

Section 1: Chemical Product and Company Identification

Product Name: Arsenic

Catalog Codes: SLA1006

CAS#: 7440-38-2

RTECS: CG0525000

TSCA: TSCA 8(b) inventory: Arsenic

CI#: Not applicable.

Synonym:

Chemical Name: Arsenic

Chemical Formula: As

Contact Information:

Sciencelab.com, Inc.

14025 Smith Rd.

Houston, Texas 77396

US Sales: **1-800-901-7247**

International Sales: **1-281-441-4400**

Order Online: ScienceLab.com

CHEMTREC (24HR Emergency Telephone), call:

1-800-424-9300

International CHEMTREC, call: 1-703-527-3887

For non-emergency assistance, call: 1-281-441-4400

Section 2: Composition and Information on Ingredients

Composition:

Name	CAS #	% by Weight
Arsenic	7440-38-2	100

Toxicological Data on Ingredients: Arsenic: ORAL (LD50): Acute: 763 mg/kg [Rat]. 145 mg/kg [Mouse].

Section 3: Hazards Identification

Potential Acute Health Effects:

Very hazardous in case of ingestion, of inhalation. Slightly hazardous in case of skin contact (irritant), of eye contact (irritant).

Potential Chronic Health Effects:

CARCINOGENIC EFFECTS: Classified A1 (Confirmed for human.) by ACGIH. MUTAGENIC EFFECTS: Not available.

TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. The substance is toxic to kidneys, lungs, the nervous system, mucous membranes. Repeated or prolonged exposure to the substance can produce target organs damage.

Section 4: First Aid Measures

Eye Contact:

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.

Skin Contact: Wash with soap and water. Cover the irritated skin with an emollient. Get medical attention if irritation develops.

Serious Skin Contact: Not available.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Serious Inhalation:

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

Serious Ingestion: Not available.

Section 5: Fire and Explosion Data

Flammability of the Product: May be combustible at high temperature.

Auto-Ignition Temperature: Not available.

Flash Points: Not available.

Flammable Limits: Not available.

Products of Combustion: Some metallic oxides.

Fire Hazards in Presence of Various Substances: Flammable in presence of open flames and sparks, of heat, of oxidizing materials.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Fire Fighting Media and Instructions:

SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.

Special Remarks on Fire Hazards:

Material in powder form, capable of creating a dust explosion. When heated to decomposition it emits highly toxic fumes.

Special Remarks on Explosion Hazards: Not available.

Section 6: Accidental Release Measures

Small Spill: Use appropriate tools to put the spilled solid in a convenient waste disposal container.

Large Spill:

Use a shovel to put the material into a convenient waste disposal container. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

Section 7: Handling and Storage

Precautions:

Keep locked up.. Keep away from heat. Keep away from sources of ignition. Empty containers pose a fire risk, evaporate the residue under a fume hood. Ground all equipment containing material. Do not ingest. Do not breathe dust. Wear suitable

protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Keep away from incompatibles such as oxidizing agents, acids, moisture.

Storage: Keep container tightly closed. Keep container in a cool, well-ventilated area.

Section 8: Exposure Controls/Personal Protection

Engineering Controls:

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Personal Protection: Safety glasses. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Dust respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits:

TWA: 0.01 from ACGIH (TLV) [United States] [1995] Consult local authorities for acceptable exposure limits.

Section 9: Physical and Chemical Properties

Physical state and appearance: Solid. (Lustrous solid.)

Odor: Not available.

Taste: Not available.

Molecular Weight: 74.92 g/mole

Color: Silvery.

pH (1% soln/water): Not applicable.

Boiling Point: Not available.

Melting Point: Sublimation temperature: 615°C (1139°F)

Critical Temperature: Not available.

Specific Gravity: 5.72 (Water = 1)

Vapor Pressure: Not applicable.

Vapor Density: Not available.

Volatility: Not available.

Odor Threshold: Not available.

Water/Oil Dist. Coeff.: Not available.

Ionicity (in Water): Not available.

Dispersion Properties: Not available.

Solubility: Insoluble in cold water, hot water.

Section 10: Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Not available.

Incompatibility with various substances: Reactive with oxidizing agents, acids, moisture.

Corrosivity: Non-corrosive in presence of glass.

Special Remarks on Reactivity: Not available.

Special Remarks on Corrosivity: Not available.

Polymerization: Will not occur.

Section 11: Toxicological Information

Routes of Entry: Inhalation. Ingestion.

Toxicity to Animals: Acute oral toxicity (LD50): 145 mg/kg [Mouse].

Chronic Effects on Humans:

CARCINOGENIC EFFECTS: Classified A1 (Confirmed for human.) by ACGIH. Causes damage to the following organs: kidneys, lungs, the nervous system, mucous membranes.

Other Toxic Effects on Humans:

Very hazardous in case of ingestion, of inhalation. Slightly hazardous in case of skin contact (irritant).

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans: Not available.

Section 12: Ecological Information

Ecotoxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation are as toxic as the original product.

Special Remarks on the Products of Biodegradation: Not available.

Section 13: Disposal Considerations

Waste Disposal:

Section 14: Transport Information

DOT Classification: CLASS 6.1: Poisonous material.

Identification: : Arsenic UNNA: UN1558 PG: II

Special Provisions for Transport: Not available.

Section 15: Other Regulatory Information

Federal and State Regulations:

California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute: Arsenic California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: Arsenic Pennsylvania RTK: Arsenic Massachusetts RTK: Arsenic TSCA 8(b) inventory: Arsenic

Other Regulations: OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications:**WHMIS (Canada):**

CLASS D-1A: Material causing immediate and serious toxic effects (VERY TOXIC). CLASS D-2A: Material causing other toxic effects (VERY TOXIC).

DSCL (EEC):

R22- Harmful if swallowed. R45- May cause cancer.

HMIS (U.S.A.):

Health Hazard: 3

Fire Hazard: 1

Reactivity: 2

Personal Protection: E

National Fire Protection Association (U.S.A.):

Health: 3

Flammability: 1

Reactivity: 2

Specific hazard:

Protective Equipment:

Gloves. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Safety glasses.

Section 16: Other Information**References:**

-Hawley, G.G.. The Condensed Chemical Dictionary, 11e ed., New York N.Y., Van Nostrand Reinold, 1987. -Liste des produits purs tératogènes, mutagènes, cancérigènes. Répertoire toxicologique de la Commission de la Santé et de la Sécurité du Travail du Québec. -Material safety data sheet emitted by: la Commission de la Santé et de la Sécurité du Travail du Québec. -SAX, N.I. Dangerous Properties of Industrial Materials. Toronto, Van Nostrand Reinold, 6e ed. 1984. -The Sigma-Aldrich Library of Chemical Safety Data, Edition II. -Guide de la loi et du règlement sur le transport des marchandises dangereuses au Canada. Centre de conformité international Ltée. 1986.

Other Special Considerations: Not available.

Created: 10/09/2005 04:16 PM

Last Updated: 05/21/2013 12:00 PM

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall ScienceLab.com be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ScienceLab.com has been advised of the possibility of such damages.



Search ...

Search

"Your high purity metal specialists"

Home	Online Catalog	Technical Data	MSDS's	Ordering Information	Videos	FAQ	About	Contact
------	----------------	----------------	--------	----------------------	--------	-----	-------	---------

Barium



Need Help?

Available Mon-Fri 8am to 5pm
Pacific Time

SAFETY DATA SHEET

1 PRODUCT AND SUPPLIER IDENTIFICATION

Product Name: Barium

Formula: Ba

Supplier: ESPI Metals
1050 Benson Way
Ashland, OR 97520

Telephone: 800-638-2581

Fax: 541-488-8313

Email: sales@espimetals.com

Emergency: Infotrac 800-535-5053 (US) or 352-323-3500 (24 hour)

Recommended Uses: Scientific Research

2 HAZARDS IDENTIFICATION

GHS Classification (29 CFR 1910.1200): Substances and mixtures which, in contact with water, emit flammable gases, category 2, Skin corrosion/irritation, category 2, Eye damage/irritation, category 2A.

GHS Label Elements:



Signal Word: Danger

Hazard Statements: H261 In contact with water releases flammable gas, H315 Causes skin irritation, H319 Causes serious eye irritation.

Precautionary Statements: P223 Do not allow contact with water, P231+P232 Handle and store contents under inert gas, protect from moisture, P264 Wash skin thoroughly after handling, P280 Wear protective gloves/protective clothing/eye protection/face protection, P302+P335+P334+P352 IF ON SKIN: Brush off loose particles from skin, and immerse in cool water, wash with plenty of soap and water, P332+P313 IF SKIN irritation occurs: Get medical advice/attention, P305+P351+P338 IF IN EYES: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing, P337+P313 IF eye irritation persists: Get medical advice/attention, P362+P364 Take off contaminated clothing and wash it before reuse, P370+P378 In case of fire: Use Class D dry powder for extinction, P402+P404 Store in a dry place. Store in a closed container, P501 Dispose of contents/container in accordance with local, state or federal regulations.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient: Barium

CAS#: 7440-39-3

%: 100

EC#: 231-149-1

Contact

ESPI Metals
1050 Benson Way
Ashland, Oregon 97520

541.488.8311 telephone
800.638.2581 toll-free

541.488.8313 fax
800.488.0060 toll-free fax

sales@espimetals.com

Your Feedback Matters

Request a Quotation

What's New?



Check out our new Rare Earth
Overview Video

Precious Metal Prices

4 FIRST AID MEASURES

General Measures: Remove patient from area of exposure.

INHALATION: Remove to fresh air, keep warm and quiet, give oxygen if breathing is difficult. Seek immediate medical attention.

INGESTION: Quickly wipe material from mouth and rinse with water. Do not induce vomiting. Seek medical attention immediately.

SKIN: Remove contaminated clothing if necessary. Brush off any visible solids. Wash the affected area with water for at least 15 minutes. Seek medical attention.

EYES: Immediately flush eyes with copious amounts of water, including under eyelids for at least 10-15 minutes. A victim may need assistance in keeping their eyelids open. Seek immediate medical attention.

Most Important Symptoms/ Effects, Acute and Delayed: May cause severe irritation in contact with moist skin. See section 11 for more information.

Indication of Immediate Medical Attention and Special Treatment: No other relevant information available.

5 FIREFIGHTING MEASURES

Extinguishing Media: Use Class D dry powder extinguishing agent.

Unsuitable Extinguishing Media: Do not use water, carbon dioxide or halogenated extinguishers.

Specific Hazards Arising from the Material: Material readily reacts with water generating flammable hydrogen gas. May emit toxic fumes under fire conditions.

Special Protective Equipment and Precautions for Firefighters: Full face, self-contained breathing apparatus and full protective clothing to prevent contact with skin and eyes. Barium metal can reignite after fire is initially extinguished. Never leave extinguished fire unattended.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures: Wear appropriate respiratory and protective equipment specified in section 8. Isolate spill area and provide ventilation. Avoid breathing dust or fume. Avoid contact with skin and eyes. Eliminate all sources of ignition.

Methods and Materials for Containment and Cleaning Up: Sweep or scoop spilled product and place in a closed container for further handling and disposal. Do not use water for spill clean-up. Cover very small quantities in the open with powdered limestone and let decompose. Use only non-sparking tools and natural bristle brushes.

Environmental Precautions: Do not flush to sewer, stream, or other bodies of water. Do not allow to enter drains or to be released to the environment.

7 HANDLING AND STORAGE

Precautions for Safe Handling: Handle in an enclosed, controlled process under dry protective gas such as argon. Protect from water and moisture. Avoid breathing dust or fumes. Avoid contact with skin and eyes. Wash thoroughly before eating or smoking. See section 8 for information on personal protection equipment.

Conditions for Safe Storage, Including Any Incompatibilities: Store in tightly-sealed containers under argon or mineral oil. Storage containers should be properly labeled and kept in a cool, dry, well-ventilated area, protected from heat and direct sunlight. Do not allow contact with water. Storage area should be free of combustibles and ignition sources. Do not store together with acids or oxidizers. See section 10 for more information on incompatible materials.

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits: Barium

OSHA/ PEL: 0.5 mg/m³

ACGIH/ TLV: 0.5 mg/m³

Appropriate Engineering Controls: Handle in an enclosed, controlled process under dry argon. Whenever possible the use of local exhaust ventilation or other engineering controls is the preferred method of controlling exposure to airborne dust and fume to meet established occupational exposure limits. Do not use tobacco or food in work area. Wash thoroughly before eating or smoking. Do not blow dust off clothing or skin with compressed air. Prepare for the possibility of a fire. Keep extinguishing agents, tools for handling and protective clothing readily available.

Jun 05, 2018 at 16:11 New York				
		Price	Change	High
Gold	▲	1296.30	+4.80	1301.40
Silver	▲	16.47	+0.09	16.61
Platinum	▲	900.00	+0.00	907.00
Palladium	▼	987.00	-4.00	1002.00

Conversion Tool

Try our conversion tools by clicking [here](#).



Serving
Multinational
Manufacturing
Companies &
Research
Institutions
Worldwide
Since 1950

Individual Protection Measures, Such as Personal Protective Equipment:

Respiratory Protection: Wear a NIOSH/MSHA approved respirator when high concentrations are present.

Eye Protection: Always wear approved chemical splash proof goggles.

Skin Protection: Rubber gloves, flame retardant protective work clothing.

9 PHYSICAL AND CHEMICAL PROPERTIES**Appearance:**

Form: Solid in various forms

Color: Silver-gray metallic

Odor: Not determined

Odor Threshold: Not determined

pH: N/A

Melting Point: 725 °C

Boiling Point: 1640 °C

Flash Point: N/A

Evaporation Rate: N/A

Flammability: No data

Upper Flammable Limit: No data

Lower Flammable Limit: No data

Vapor Pressure: 10 mm at 1049 °C

Vapor Density: N/A

Relative Density (Specific Gravity): 3.51 g/cc at 20 °C

Solubility in H₂O: Decomposes

Partition Coefficient (n-octanol/ water): Not determined

Autoignition Temperature: No data

Decomposition Temperature: No data

Viscosity: N/A

10 STABILITY AND REACTIVITY

Reactivity: No specific test data available.

Chemical Stability: Stable under recommended storage conditions.

Possibility of Hazardous Reactions: Reacts readily with water releasing flammable hydrogen gas.

Conditions to Avoid: Avoid contact with water or moist air and possible ignition sources such as sparks or flame.

Incompatible Materials: Water or moisture, oxidizing agents, oxygen, acids, alcohols, halocarbons, carbon dioxide, ammonia.

Hazardous Decomposition Products: Barium hydroxides, barium oxides, hydrogen gas.

11 TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Inhalation, skin, eyes.

Symptoms of Exposure: May cause severe irritation to the nose, throat, and upper respiratory tract, mouth, throat, and esophagus. Contact with skin can cause mild to moderate irritation. May cause chemical burns in eyes or on skin as it reacts with moisture on living tissue.

Acute and Chronic Effects: Barium compounds may cause severe gastroenteritis, including abdominal pain, vomiting and diarrhea, tremors, faintness, paralysis of the arms and legs, and slow or irregular heartbeat. Severe cases may produce collapse and death due to respiratory failure. Soluble barium compounds are more likely to cause these effects than insoluble compounds. Inhalation of fumes may cause sore throat, coughing, labored breathing, and irritation of the respiratory tract as well as the above symptoms. Chronic exposure to barium may cause sensitization, chronic barium poisoning, dermatitis, corneal opacity and blindness.

Acute Toxicity: No data

Carcinogenicity: NTP: Not identified as carcinogenic IARC: Not identified as carcinogenic

To the best of our knowledge the chemical, physical and toxicological characteristics of the substance are not fully known.

12 ECOLOGICAL INFORMATION

Ecotoxicity: No data

Persistence and Degradability: No data

Bioaccumulative Potential: No data

Mobility in Soil: No data

Other Adverse Effects: Do not allow material to be released to the environment. No further relevant information available.

13 DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Product: Dispose of in accordance with Federal, State and Local regulations.

Packaging: Dispose of in accordance with Federal, State and Local regulations.

14 TRANSPORT INFORMATION

UN Number: UN1400

UN Proper Shipping Name: Barium

Transport Hazard Class: 4.3

Packing Group: II

Marine Pollutant: No

Special Precautions: Warning, substances which, in contact with water, emit flammable gases.

15 REGULATORY INFORMATION

TSCA Listed: Yes

DSL Listed: Yes

Regulation (EC) No 1272/2008 (CLP): Substances and mixtures which, in contact with water, emit flammable gases, category 2, Skin corrosion/irritation, category 2, Eye damage/irritation, category 2A.

WHMIS 2015 Classification: Substances and mixtures which, in contact with water, emit flammable gases, Skin corrosion/irritation, Eye damage/irritation.

HMIS Ratings: Health: 2 Flammability: 2 Physical: 2

NFPA Ratings: Health: 2 Flammability: 2 Instability: 2 Special Hazard: W


Chemical Safety Assessment: A chemical safety assessment has not been carried out.

16 OTHER INFORMATION

The information contained in this document is based on the state of our knowledge at the time of publication and is believed to be correct, but does not purport to be all inclusive and shall be used only as a guide. ESPI Metals makes no representation, warranty, or guarantee of any kind with respect to the information contained in this document or any use of the product based on this information. ESPI Metals shall not be held liable for any damages resulting from handling or from contact with the above product. Users should satisfy themselves that they have all current data relevant to their particular use.

Prepared by: ESPI Metals

Revised/Reviewed: July 2016



Health	1
Fire	0
Reactivity	0
Personal Protection	E

Material Safety Data Sheet

Lead MSDS

Section 1: Chemical Product and Company Identification

Product Name: Lead

Catalog Codes: SLL1291, SLL1669, SLL1081, SLL1459, SLL1834

CAS#: 7439-92-1

RTECS: OF7525000

TSCA: TSCA 8(b) inventory: Lead

CI#: Not available.

Synonym: Lead Metal, granular; Lead Metal, foil; Lead Metal, sheet; Lead Metal, shot

Chemical Name: Lead

Chemical Formula: Pb

Contact Information:

Sciencelab.com, Inc.

14025 Smith Rd.

Houston, Texas 77396

US Sales: **1-800-901-7247**

International Sales: **1-281-441-4400**

Order Online: ScienceLab.com

CHEMTREC (24HR Emergency Telephone), call:
1-800-424-9300

International CHEMTREC, call: 1-703-527-3887

For non-emergency assistance, call: 1-281-441-4400

Section 2: Composition and Information on Ingredients

Composition:

Name	CAS #	% by Weight
Lead	7439-92-1	100

Toxicological Data on Ingredients: Lead LD50: Not available. LC50: Not available.

Section 3: Hazards Identification

Potential Acute Health Effects: Slightly hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation.

Potential Chronic Health Effects:

Slightly hazardous in case of skin contact (permeator). CARCINOGENIC EFFECTS: Classified A3 (Proven for animal.) by ACGIH, 2B (Possible for human.) by IARC. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. The substance may be toxic to blood, kidneys, central nervous system (CNS). Repeated or prolonged exposure to the substance can produce target organs damage.

Section 4: First Aid Measures

Eye Contact:

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.

Skin Contact: Wash with soap and water. Cover the irritated skin with an emollient. Get medical attention if irritation develops.

Serious Skin Contact: Not available.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Serious Inhalation: Not available.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

Serious Ingestion: Not available.

Section 5: Fire and Explosion Data

Flammability of the Product: May be combustible at high temperature.

Auto-Ignition Temperature: Not available.

Flash Points: Not available.

Flammable Limits: Not available.

Products of Combustion: Some metallic oxides.

Fire Hazards in Presence of Various Substances: Non-flammable in presence of open flames and sparks, of shocks, of heat.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Fire Fighting Media and Instructions:

SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.

Special Remarks on Fire Hazards: When heated to decomposition it emits highly toxic fumes of lead.

Special Remarks on Explosion Hazards: Not available.

Section 6: Accidental Release Measures

Small Spill:

Use appropriate tools to put the spilled solid in a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and dispose of according to local and regional authority requirements.

Large Spill:

Use a shovel to put the material into a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

Section 7: Handling and Storage

Precautions:

Keep locked up.. Keep away from heat. Keep away from sources of ignition. Empty containers pose a fire risk, evaporate the residue under a fume hood. Ground all equipment containing material. Do not ingest. Do not breathe dust. Wear suitable

protective clothing. If ingested, seek medical advice immediately and show the container or the label. Keep away from incompatibles such as oxidizing agents.

Storage: Keep container tightly closed. Keep container in a cool, well-ventilated area.

Section 8: Exposure Controls/Personal Protection

Engineering Controls:

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Personal Protection: Safety glasses. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Dust respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits:

TWA: 0.05 (mg/m³) from ACGIH (TLV) [United States] TWA: 0.05 (mg/m³) from OSHA (PEL) [United States] TWA: 0.03 (mg/m³) from NIOSH [United States] TWA: 0.05 (mg/m³) [Canada] Consult local authorities for acceptable exposure limits.

Section 9: Physical and Chemical Properties

Physical state and appearance: Solid. (Metal solid.)

Odor: Not available.

Taste: Not available.

Molecular Weight: 207.21 g/mole

Color: Bluish-white. Silvery. Gray

pH (1% soln/water): Not applicable.

Boiling Point: 1740°C (3164°F)

Melting Point: 327.43°C (621.4°F)

Critical Temperature: Not available.

Specific Gravity: 11.3 (Water = 1)

Vapor Pressure: Not applicable.

Vapor Density: Not available.

Volatility: Not available.

Odor Threshold: Not available.

Water/Oil Dist. Coeff.: Not available.

Ionicity (in Water): Not available.

Dispersion Properties: Not available.

Solubility: Insoluble in cold water.

Section 10: Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Incompatible materials, excess heat

Incompatibility with various substances: Reactive with oxidizing agents.

Corrosivity: Non-corrosive in presence of glass.

Special Remarks on Reactivity:

Can react vigorously with oxidizing materials. Incompatible with sodium carbide, chlorine trifluoride, trioxane + hydrogen peroxide, ammonium nitrate, sodium azide, disodium acetylide, sodium acetylide, hot concentrated nitric acid, hot concentrated hydrochloric acid, hot concentrated sulfuric acid, zirconium.

Special Remarks on Corrosivity: Not available.

Polymerization: Will not occur.

Section 11: Toxicological Information

Routes of Entry: Absorbed through skin. Inhalation. Ingestion.

Toxicity to Animals:

LD50: Not available. LC50: Not available.

Chronic Effects on Humans:

CARCINOGENIC EFFECTS: Classified A3 (Proven for animal.) by ACGIH, 2B (Possible for human.) by IARC. May cause damage to the following organs: blood, kidneys, central nervous system (CNS).

Other Toxic Effects on Humans: Slightly hazardous in case of skin contact (irritant), of ingestion, of inhalation.

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans:

Acute Potential: Skin: Lead metal granules or dust: May cause skin irritation by mechanical action. Lead metal foil, shot or sheets: Not likely to cause skin irritation Eyes: Lead metal granules or dust: Can irritate eyes by mechanical action. Lead metal foil, shot or sheets: No hazard. Will not cause eye irritation. Inhalation: In an industrial setting, exposure to lead mainly occurs from inhalation of dust or fumes. Lead dust or fumes: Can irritate the upper respiratory tract (nose, throat) as well as the bronchi and lungs by mechanical action. Lead dust can be absorbed through the respiratory system. However, inhaled lead does not accumulate in the lungs. All of an inhaled dose is eventually absorbed or transferred to the gastrointestinal tract. Inhalation effects of exposure to fumes or dust of inorganic lead may not develop quickly. Symptoms may include metallic taste, chest pain, decreased physical fitness, fatigue, sleep disturbance, headache, irritability, reduces memory, mood and personality changes, aching bones and muscles, constipation, abdominal pains, decreasing appetite. Inhalation of large amounts may lead to ataxia, delirium, convulsions/seizures, coma, and death. Lead metal foil, shot, or sheets: Not an inhalation hazard unless metal is heated. If metal is heated, fumes will be released. Inhalation of these fumes may cause "fume metal fever", which is characterized by flu-like symptoms. Symptoms may include metallic taste, fever, nausea, vomiting, chills, cough, weakness, chest pain, generalized muscle pain/aches, and increased white blood cell count. Ingestion: Lead metal granules or dust: The symptoms of lead poisoning include abdominal pain or cramps (lead colic), spasms, nausea, vomiting, headache, muscle weakness, hallucinations, distorted perceptions, "lead line" on the gums, metallic taste, loss of appetite, insomnia, dizziness and other symptoms similar to that of inhalation. Acute poisoning may result in high lead levels in the blood and urine, shock, coma and death in extreme cases. Lead metal foil, shot or sheets: Not an ingestion hazard for usual industrial handling.

Section 12: Ecological Information

Ecotoxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation are less toxic than the product itself.

Special Remarks on the Products of Biodegradation: Not available.

Section 13: Disposal Considerations**Waste Disposal:**

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Section 14: Transport Information

DOT Classification: Not a DOT controlled material (United States).

Identification: Not applicable.

Special Provisions for Transport: Not applicable.

Section 15: Other Regulatory Information**Federal and State Regulations:**

California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute: Lead California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (female) which would require a warning under the statute: Lead California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (male) which would require a warning under the statute: Lead California prop. 65 (no significant risk level): Lead: 0.0005 mg/day (value) California prop. 65: This product contains the following ingredients for which the State of California has found to cause birth defects which would require a warning under the statute: Lead California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: Lead Connecticut hazardous material survey.: Lead Illinois toxic substances disclosure to employee act: Lead Illinois chemical safety act: Lead New York release reporting list: Lead Rhode Island RTK hazardous substances: Lead Pennsylvania RTK: Lead

Other Regulations:

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

Other Classifications:

WHMIS (Canada): CLASS D-2A: Material causing other toxic effects (VERY TOXIC).

DSCL (EEC):

R20/22- Harmful by inhalation and if swallowed. R33- Danger of cumulative effects. R61- May cause harm to the unborn child. R62- Possible risk of impaired fertility. S36/37- Wear suitable protective clothing and gloves. S44- If you feel unwell, seek medical advice (show the label when possible). S53- Avoid exposure - obtain special instructions before use.

HMIS (U.S.A.):

Health Hazard: 1

Fire Hazard: 0

Reactivity: 0

Personal Protection: E

National Fire Protection Association (U.S.A.):

Health: 1

Flammability: 0

Reactivity: 0

Specific hazard:

Protective Equipment:

Gloves. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Safety glasses.

Section 16: Other Information


References: Not available.

Other Special Considerations: Not available.

Created: 10/10/2005 08:21 PM

Last Updated: 05/21/2013 12:00 PM

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall ScienceLab.com be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ScienceLab.com has been advised of the possibility of such damages.



Health	1
Fire	3
Reactivity	2
Personal Protection	E

Material Safety Data Sheet

Magnesium MSDS

Section 1: Chemical Product and Company Identification

Product Name: Magnesium

Catalog Codes: SLM4408, SLM2263, SLM3637

CAS#: 7439-95-4

RTECS: OM2100000

TSCA: TSCA 8(b) inventory: Magnesium

CI#: Not applicable.

Synonym: Magnesium ribbons, turnings or sticks

Chemical Name: Magnesium

Chemical Formula: Mg

Contact Information:

Sciencelab.com, Inc.

14025 Smith Rd.

Houston, Texas 77396

US Sales: **1-800-901-7247**

International Sales: **1-281-441-4400**

Order Online: ScienceLab.com

CHEMTREC (24HR Emergency Telephone), call:

1-800-424-9300

International CHEMTREC, call: 1-703-527-3887

For non-emergency assistance, call: 1-281-441-4400

Section 2: Composition and Information on Ingredients

Composition:

Name	CAS #	% by Weight
Magnesium	7439-95-4	100

Toxicological Data on Ingredients: Magnesium LD50: Not available. LC50: Not available.

Section 3: Hazards Identification

Potential Acute Health Effects: Slightly hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation.

Potential Chronic Health Effects:

CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. Repeated or prolonged exposure is not known to aggravate medical condition.

Section 4: First Aid Measures

Eye Contact:

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.

Skin Contact: Wash with soap and water. Cover the irritated skin with an emollient. Get medical attention if irritation develops.

Serious Skin Contact: Not available.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Serious Inhalation:

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

Serious Ingestion: Not available.

Section 5: Fire and Explosion Data

Flammability of the Product: Flammable.

Auto-Ignition Temperature: Not available.

Flash Points: Not available.

Flammable Limits: Not available.

Products of Combustion: Some metallic oxides.

Fire Hazards in Presence of Various Substances:

Highly flammable in presence of open flames and sparks, of heat. Flammable in presence of acids, of moisture. Non-flammable in presence of shocks.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available. Explosive in presence of acids, of moisture.

Fire Fighting Media and Instructions:

Flammable solid. SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.

Special Remarks on Fire Hazards:

Magnesium turnings, chips or granules, ribbons, are flammable. They can be easily ignited. They may reignite after fire is extinguished. Produces flammable gases on contact with water and acid. May ignite on contact with water or moist air. Magnesium fires do not flare up violently unless moisture is present.

Special Remarks on Explosion Hazards: Reacts with acids and water to form hydrogen gas which is highly flammable and explosive

Section 6: Accidental Release Measures

Small Spill: Use appropriate tools to put the spilled solid in a convenient waste disposal container.

Large Spill:

Flammable solid. Stop leak if without risk. Do not touch spilled material. Use water spray curtain to divert vapor drift. Prevent entry into sewers, basements or confined areas; dike if needed. Eliminate all ignition sources. Call for assistance on disposal.

Section 7: Handling and Storage

Precautions:

Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not breathe dust. Keep away from incompatibles such as oxidizing agents, acids, moisture.

Storage:

Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). Moisture sensitive. Dangerous when wet.

Section 8: Exposure Controls/Personal Protection

Engineering Controls:

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Personal Protection: Safety glasses. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Dust respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits: Not available.

Section 9: Physical and Chemical Properties

Physical state and appearance: Solid. (Metal solid)

Odor: Odorless.

Taste: Not available.

Molecular Weight: 24.31 g/mole

Color: Silver-white

pH (1% soln/water): Not applicable.

Boiling Point: 1100°C (2012°F)

Melting Point: 651°C (1203.8°F)

Critical Temperature: Not available.

Specific Gravity: 1.74 (Water = 1)

Vapor Pressure: Not applicable.

Vapor Density: Not available.

Volatility: Not available.

Odor Threshold: Not available.

Water/Oil Dist. Coeff.: Not available.

Ionicity (in Water): Not available.

Dispersion Properties: Not available.

Solubility:

Very slightly soluble in hot water. Insoluble in cold water. Insoluble in chromium trioxides, and mineral acids, alkalies. Slightly soluble with decomposition in hot water. Soluble in concentrated hydrogen fluoride, and ammonium salts.

Section 10: Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Heat, incompatible materials, water or moisture, moist air.

Incompatibility with various substances: Reactive with oxidizing agents, acids, moisture.

Corrosivity: Non-corrosive in presence of glass.

Special Remarks on Reactivity:

Violent chemical reaction with oxidizing agents. Reacts with water to create hydrogen gas and heat. Must be kept dry. Reacts with acids to form hydrogen gas which is highly flammable and explosive. Magnesium forms hazardous or explosive mixtures with aluminum and potassium perchlorate; ammonium nitrate; barium nitrate, barium dioxide and zinc; beryllium oxide; boron phosphodiiodide; bromobenzyl trifluoride; cadmium cyanide; cadmium oxide; calcium carbide; carbonates; carbon tetrachloride; chlorine; chlorine trifluoride; chloroform; cobalt cyanide; copper cyanide; copper sulfate(anhydrous), ammonium nitrate, potassium chlorate and water; cupric oxide; cupric sulfate; fluorine; gold cyanide; hydrogen and calcium carbonate; hydrogen iodide; hydrogen peroxide; iodine; lead cyanide; mercuric oxide; mercury cyanide; methyl chloride; molybdenum trioxide; nickel cyanide; nitric acid; nitrogen dioxide; oxygen (liquid); performic acid; phosphates; potassium chlorate; potassium perchlorate; silver nitrate; silver oxide; sodium perchlorate; sodium peroxide; sodium peroxide and carbon dioxide; stannic oxide; sulfates; trichloroethylene; zinc cyanide; zinc oxide.

Special Remarks on Corrosivity: Not available.

Polymerization: Will not occur.

Section 11: Toxicological Information

Routes of Entry: Inhalation. Ingestion.

Toxicity to Animals:

LD50: Not available. LC50: Not available.

Chronic Effects on Humans: Not available.

Other Toxic Effects on Humans: Slightly hazardous in case of skin contact (irritant), of ingestion, of inhalation.

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans:

Acute Potential Health Effects: Skin: May cause skin irritation by mechanical action. May get mechanical injury or embedding of chips/particles in skin. The particles that are embedded in the wounds may retard healing. Eyes: May cause eye irritation by mechanical action. Mechanical injury may occur. Particles or chips may embed in eye and retard healing. Inhalation: Low hazard for usual industrial handling. It may cause respiratory tract irritation. However, it is unlikely due to physical form. When Magnesium metal is heated during welding or smelting process, Metal Fume Fever may result from inhalation of magnesium fumes. Metal Fume Fever is a flu-like condition consisting of fever, chills, sweating, aches, pains, cough, weakness, headache, nausea, vomiting, and breathing difficulty. Other symptoms may include metallic taste, increased white blood cell count. There is no permanent ill-effect. Ingestion: Low hazard for usual industrial handling. There are no known reports of serious industrial poisonings with Magnesium. Ingestion of large amounts of chips, turnings or ribbons may cause gastrointestinal tract irritation with nausea, vomiting, and diarrhea. Acute ingestion may also result in Hypermagnesia. Hypermagnesia may cause hypotension, bradycardia, CNS depression, respiratory depression, and impairment of neuromuscular transmission (hyporeflexia, paralysis).

Section 12: Ecological Information

Ecotoxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The product itself and its products of degradation are not toxic.

Special Remarks on the Products of Biodegradation: Not available.

Section 13: Disposal Considerations

Waste Disposal:

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Section 14: Transport Information

DOT Classification: CLASS 4.1: Flammable solid.

Identification: : Magnesium UNNA: 1869 PG: III

Special Provisions for Transport: Not available.

Section 15: Other Regulatory Information

Federal and State Regulations:

Connecticut hazardous material survey.: Magnesium Rhode Island RTK hazardous substances: Magnesium Pennsylvania RTK: Magnesium Massachusetts RTK: Magnesium Massachusetts spill list: Magnesium New Jersey: Magnesium TSCA 8(b) inventory: Magnesium

Other Regulations:

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

Other Classifications:

WHMIS (Canada):

CLASS B-4: Flammable solid. CLASS B-6: Reactive and very flammable material.

DSCL (EEC):

R11- Highly flammable. R15- Contact with water liberates extremely flammable gases. S7/8- Keep container tightly closed and dry. S43- In case of fire, use dry chemical. Never use water.

HMIS (U.S.A.):

Health Hazard: 1

Fire Hazard: 3

Reactivity: 2

Personal Protection: E

National Fire Protection Association (U.S.A.):

Health: 0

Flammability: 1

Reactivity: 1

Specific hazard:

Protective Equipment:

Gloves. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Safety glasses.

Section 16: Other Information


References: Not available.

Other Special Considerations: Not available.

Created: 10/09/2005 06:00 PM

Last Updated: 05/21/2013 12:00 PM

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall ScienceLab.com be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ScienceLab.com has been advised of the possibility of such damages.



Health	1
Fire	0
Reactivity	0
Personal Protection	E

Material Safety Data Sheet

Manganese MSDS

Section 1: Chemical Product and Company Identification

Product Name: Manganese

Catalog Codes: SLM2245

CAS#: 7439-96-5

RTECS: OO9275000

TSCA: TSCA 8(b) inventory: Manganese

CI#: Not available.

Synonym:

Chemical Name: Manganese

Chemical Formula: Mn

Contact Information:

Sciencelab.com, Inc.

14025 Smith Rd.

Houston, Texas 77396

US Sales: **1-800-901-7247**

International Sales: **1-281-441-4400**

Order Online: ScienceLab.com

CHEMTREC (24HR Emergency Telephone), call:

1-800-424-9300

International CHEMTREC, call: 1-703-527-3887

For non-emergency assistance, call: 1-281-441-4400

Section 2: Composition and Information on Ingredients

Composition:

Name	CAS #	% by Weight
Manganese	7439-96-5	100

Toxicological Data on Ingredients: Manganese: ORAL (LD50): Acute: 9000 mg/kg [Rat].

Section 3: Hazards Identification

Potential Acute Health Effects:

Hazardous in case of inhalation. Slightly hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion.

Potential Chronic Health Effects:

CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. The substance may be toxic to blood, lungs, brain, central nervous system (CNS). Repeated or prolonged exposure to the substance can produce target organs damage.

Section 4: First Aid Measures

Eye Contact:

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.

Skin Contact: Wash with soap and water. Cover the irritated skin with an emollient. Get medical attention if irritation develops.

Serious Skin Contact: Not available.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Serious Inhalation: Not available.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention if symptoms appear.

Serious Ingestion: Not available.

Section 5: Fire and Explosion Data

Flammability of the Product: Non-flammable.

Auto-Ignition Temperature: Not applicable.

Flash Points: Not applicable.

Flammable Limits: Not applicable.

Products of Combustion: Not available.

Fire Hazards in Presence of Various Substances: Not applicable.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Fire Fighting Media and Instructions: Not applicable.

Special Remarks on Fire Hazards:

Moderate fire potential, in the form of dust or powder, when exposed to flame. When manganese is heated in the vapor of phosphorus at a very dull red heat, union occurs with incandescence. Concentrated nitric acid reacts with powdered manganese with incandescence and explosion. Powdered manganese ignites in chlorine.

Special Remarks on Explosion Hazards: Moderate explosion potential, in the form of dust or powder, when exposed to flame.

Section 6: Accidental Release Measures

Small Spill:

Use appropriate tools to put the spilled solid in a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and dispose of according to local and regional authority requirements.

Large Spill:

Use a shovel to put the material into a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

Section 7: Handling and Storage

Precautions:

Do not ingest. Do not breathe dust. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Keep away from incompatibles such as oxidizing agents, reducing agents.

Storage: Keep container tightly closed. Keep container in a cool, well-ventilated area. Do not store above

Section 8: Exposure Controls/Personal Protection

Engineering Controls:

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Personal Protection: Safety glasses. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Dust respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits:

TWA: 0.1 (mg/m³) from ACGIH (TLV) [United States] TWA: 5 (mg/m³) [Canada] TWA: 1 STEL: 3 (mg/m³) from NIOSH [United States] TWA: 5 (mg/m³) from OSHA (PEL) [United States] Consult local authorities for acceptable exposure limits.

Section 9: Physical and Chemical Properties

Physical state and appearance: Solid.

Odor: Odorless.

Taste: Not available.

Molecular Weight: 54.94 g/mole

Color: Grayish white.

pH (1% soln/water): Not applicable.

Boiling Point: 2095°C (3803°F)

Melting Point: 1244°C (2271.2°F)

Critical Temperature: Not available.

Specific Gravity: 7.44 (Water = 1)

Vapor Pressure: Not applicable.

Vapor Density: Not available.

Volatility: Not available.

Odor Threshold: Not available.

Water/Oil Dist. Coeff.: Not available.

Ionicity (in Water): Not available.

Dispersion Properties: Not available.

Solubility: Insoluble in cold water, hot water.

Section 10: Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Incompatible materials

Incompatibility with various substances: Reactive with oxidizing agents, reducing agents.

Corrosivity: Non-corrosive in presence of glass.

Special Remarks on Reactivity:

Superficially oxidized on exposure to air. Reacts with aqueous solutions of sodium or potassium bicarbonate. Reacts with dilute mineral acids with evolution of hydrogen and formation of divalent manganous salts. Reacts with fluorine and chlorine to produce di or tri fluoride, and di and tri chloride, respectively. In the form of powder, it reduces most metallic oxides on heating. On heating, it reacts directly with carbon, phosphorus, antimony, or arsenic. Also incompatible with hydroxides, cyanides, carbonates.

Special Remarks on Corrosivity: Not available.

Polymerization: Will not occur.

Section 11: Toxicological Information

Routes of Entry: Inhalation. Ingestion.

Toxicity to Animals: Acute oral toxicity (LD50): 9000 mg/kg [Rat].

Chronic Effects on Humans: May cause damage to the following organs: blood, lungs, brain, central nervous system (CNS).

Other Toxic Effects on Humans:

Hazardous in case of inhalation. Slightly hazardous in case of skin contact (irritant), of ingestion.

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans:

Manganese can cross the placenta. May cause cancer (tumorigenic) based on animal data.

Special Remarks on other Toxic Effects on Humans:

Acute Potential Health Effects: Skin: May cause skin irritation Eyes: Dust may cause mechanical irritation. Inhalation: Dust may cause respiratory tract irritation. May cause "Metal Fume Fever" which may include flu-like symptoms (fever, chills, upset stomach, vomiting, weakness, headache, body aches, muscle pains, dry mouth and throat, coughing, tightness of the chest). May affect behavior/Central Nervous system (change in motor activity, torpor, nervousness, tremor, yawning, mood swings, irritability, restlessness, fatigue, headache, apathy, languor, insomnia than somnolence, hallucinations, delusions, uncontrollable laughter followed by crying, compulsions, aggressiveness, weakness in legs, memory loss, decreased libido, impotence, salivation, hearing loss, slow gait,), and respiration (dyspnea, shallow respiration, cyanosis, alveolar inflammation). Ingestion: Repeated or prolonged exposure from ingestion may affect brain (degenerative changes), blood and metabolism. Ingestion: May cause digestive tract irritation. There is a low gastrointestinal absorption of manganese. Chronic Potential Health Effects: Inhalation: Repeated or prolonged exposure from inhalation may affect brain (degenerative changes), behavior/Central Nervous system with symptoms to acute exposure. May also affect liver (chronic liver disease, jaundice) Ingestion: Repeated or prolonged exposure from ingestion may affect brain, blood and metabolism

Section 12: Ecological Information

Ecotoxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The product itself and its products of degradation are not toxic.

Special Remarks on the Products of Biodegradation: Not available.

Section 13: Disposal Considerations

Waste Disposal:

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Section 14: Transport Information

DOT Classification: Not a DOT controlled material (United States).

Identification: Not applicable.

Special Provisions for Transport: Not applicable.

Section 15: Other Regulatory Information

Federal and State Regulations:

Illinois toxic substances disclosure to employee act: Manganese Rhode Island RTK hazardous substances: Manganese Pennsylvania RTK: Manganese Minnesota: Manganese Massachusetts RTK: Manganese New Jersey: Manganese New Jersey spill list: Manganese Louisiana spill reporting: Manganese California Director's List of Hazardous Substances: Manganese TSCA 8(b) inventory: Manganese SARA 313 toxic chemical notification and release reporting: Manganese

Other Regulations:

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

Other Classifications:

WHMIS (Canada): Not controlled under WHMIS (Canada).

DSCL (EEC): Not applicable.

HMIS (U.S.A.):

Health Hazard: 1

Fire Hazard: 0

Reactivity: 0

Personal Protection: E

National Fire Protection Association (U.S.A.):

Health: 1

Flammability: 0

Reactivity: 0

Specific hazard:

Protective Equipment:

Gloves. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Safety glasses.

Section 16: Other Information


References: Not available.

Other Special Considerations: Not available.

Created: 10/09/2005 06:03 PM

Last Updated: 05/21/2013 12:00 PM

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall ScienceLab.com be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ScienceLab.com has been advised of the possibility of such damages.



Health	3
Fire	0
Reactivity	0
Personal Protection	

Material Safety Data Sheet

Mercury MSDS

Section 1: Chemical Product and Company Identification

Product Name: Mercury

Catalog Codes: SLM3505, SLM1363

CAS#: 7439-97-6

RTECS: OV4550000

TSCA: TSCA 8(b) inventory: Mercury

CI#: Not applicable.

Synonym: Quick Silver; Colloidal Mercury; Metallic Mercury; Liquid Silver; Hydragryum

Chemical Name: Mercury

Chemical Formula: Hg

Contact Information:

Sciencelab.com, Inc.

14025 Smith Rd.

Houston, Texas 77396

US Sales: **1-800-901-7247**

International Sales: **1-281-441-4400**

Order Online: ScienceLab.com

CHEMTREC (24HR Emergency Telephone), call:

1-800-424-9300

International CHEMTREC, call: 1-703-527-3887

For non-emergency assistance, call: 1-281-441-4400

Section 2: Composition and Information on Ingredients

Composition:

Name	CAS #	% by Weight
Mercury	7439-97-6	100

Toxicological Data on Ingredients: Mercury LD50: Not available. LC50: Not available.

Section 3: Hazards Identification

Potential Acute Health Effects:

Very hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation. Hazardous in case of skin contact (corrosive, permeator). Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract. Skin contact may produce burns. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Severe over-exposure can result in death. Inflammation of the eye is characterized by redness, watering, and itching. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.

Potential Chronic Health Effects:

Hazardous in case of skin contact (permeator). **CARCINOGENIC EFFECTS:** Classified A5 (Not suspected for human.) by ACGIH. 3 (Not classifiable for human.) by IARC. **MUTAGENIC EFFECTS:** Not available. **TERATOGENIC EFFECTS:** Not available. **DEVELOPMENTAL TOXICITY:** Not available. The substance may be toxic to blood, kidneys, liver, brain, peripheral nervous system, central nervous system (CNS). Repeated or prolonged exposure to the substance can produce target organs damage. Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation.

Repeated or prolonged exposure to spray mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection. Repeated exposure to a highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.

Section 4: First Aid Measures

Eye Contact:

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. WARM water MUST be used. Get medical attention immediately.

Skin Contact:

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

Serious Skin Contact:

Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Serious Inhalation:

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. **WARNING:** It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek immediate medical attention.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

Serious Ingestion: Not available.

Section 5: Fire and Explosion Data

Flammability of the Product: Non-flammable.

Auto-Ignition Temperature: Not applicable.

Flash Points: Not applicable.

Flammable Limits: Not applicable.

Products of Combustion: Not available.

Fire Hazards in Presence of Various Substances: Not applicable.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Fire Fighting Media and Instructions: Not applicable.

Special Remarks on Fire Hazards:

When thrown into mercury vapor, boron phosphodiiodide ignites at once. Flame forms with chlorine jet over mercury surface at 200 deg to 300 deg C. Mercury undergoes hazardous reactions in the presence of heat and sparks or ignition.

Special Remarks on Explosion Hazards:

A violent exothermic reaction or possible explosion occurs when mercury comes in contact with lithium and rubidium. CHLORINE DIOXIDE & LIQUID HG, WHEN MIXED, EXPLODE VIOLENTLY. Mercury and Ammonia can produce an

explosive compound. A mixture of the dry carbonyl and oxygen will explode on vigorous shaking with mercury. Methyl azide in the presence of mercury was shown to be potentially explosive.

Section 6: Accidental Release Measures

Small Spill: Absorb with an inert material and put the spilled material in an appropriate waste disposal.

Large Spill:

Corrosive liquid. Poisonous liquid. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Use water spray curtain to divert vapor drift. Use water spray to reduce vapors. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

Section 7: Handling and Storage

Precautions:

Keep locked up.. Keep container dry. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Never add water to this product. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, metals.

Storage: Keep container tightly closed. Keep container in a cool, well-ventilated area. Do not store above 25°C (77°F).

Section 8: Exposure Controls/Personal Protection

Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Personal Protection:

Face shield. Full suit. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves. Boots.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits:

TWA: 0.025 from ACGIH (TLV) [United States] SKIN TWA: 0.05 CEIL: 0.1 (mg/m³) from OSHA (PEL) [United States]
Inhalation TWA: 0.025 (mg/m³) [United Kingdom (UK)] Consult local authorities for acceptable exposure limits.

Section 9: Physical and Chemical Properties

Physical state and appearance: Liquid. (Heavy liquid)

Odor: Odorless.

Taste: Not available.

Molecular Weight: 200.59 g/mole

Color: Silver-white

pH (1% soln/water): Not available.

Boiling Point: 356.73°C (674.1°F)

Melting Point: -38.87°C (-38°F)

Critical Temperature: 1462°C (2663.6°F)

Specific Gravity: 13.55 (Water = 1)

Vapor Pressure: Not available.

Vapor Density: 6.93 (Air = 1)

Volatility: Not available.

Odor Threshold: Not available.

Water/Oil Dist. Coeff.: Not available.

Ionicity (in Water): Not available.

Dispersion Properties: Not available.

Solubility: Very slightly soluble in cold water.

Section 10: Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Incompatible materials

Incompatibility with various substances: Reactive with oxidizing agents, metals.

Corrosivity: Non-corrosive in presence of glass.

Special Remarks on Reactivity:

Ground mixtures of sodium carbide and mercury, aluminum, lead, or iron can react vigorously. A violent exothermic reaction or possible explosion occurs when mercury comes in contact with lithium and rubidium. Incompatible with boron diiodophosphide; ethylene oxide; metal oxides, metals(aluminum, potassium, lithium, sodium, rubidium); methyl azide; methylsilane, oxygen; oxidants(bromine, peroxyformic acid, chlorine dioxide, nitric acid, tetracarbonylnickel, nitromethane, silver perchlorate, chlorates, sulfuric acid, nitrates,); tetracarbonylnickel, oxygen, acetylinic compounds, ammonia, ethylene oxide, methylsilane, calcium,

Special Remarks on Corrosivity:

The high mobility and tendency to dispersion exhibited by mercury, and the ease with which it forms alloys (amalgam) with many laboratory and electrical contact metals, can cause severe corrosion problems in laboratories. Special precautions: Mercury can attack copper and copper alloy materials.

Polymerization: Will not occur.

Section 11: Toxicological Information

Routes of Entry: Absorbed through skin. Dermal contact. Eye contact. Inhalation. Ingestion.

Toxicity to Animals:

LD50: Not available. LC50: Not available.

Chronic Effects on Humans:

CARCINOGENIC EFFECTS: Classified A5 (Not suspected for human.) by ACGIH. 3 (Not classifiable for human.) by IARC. May cause damage to the following organs: blood, kidneys, liver, brain, peripheral nervous system, central nervous system (CNS).

Other Toxic Effects on Humans:

Very hazardous in case of skin contact (irritant), of ingestion, of inhalation. Hazardous in case of skin contact (corrosive, permeator).

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans:

May affect genetic material. May cause cancer based on animal data. Passes through the placental barrier in animal. May cause adverse reproductive effects(paternal effects- spermatogenesis; effects on fertility - fetotoxicity, post-implantation mortality), and birth defects.

Special Remarks on other Toxic Effects on Humans:

Section 12: Ecological Information

Ecotoxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation are less toxic than the product itself.

Special Remarks on the Products of Biodegradation: Not available.

Section 13: Disposal Considerations

Waste Disposal:

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Section 14: Transport Information

DOT Classification: Class 8: Corrosive material

Identification: : Mercury UNNA: 2809 PG: III

Special Provisions for Transport: Not available.

Section 15: Other Regulatory Information

Federal and State Regulations:

California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute: Mercury California prop. 65: This product contains the following ingredients for which the State of California has found to cause birth defects which would require a warning under the statute: Mercury Connecticut hazardous material survey.: Mercury Illinois toxic substances disclosure to employee act: Mercury Illinois chemical safety act: Mercury New York acutely hazardous substances: Mercury Rhode Island RTK hazardous substances: Mercury Pennsylvania RTK: Mercury Minnesota: Mercury Massachusetts RTK: Mercury New Jersey: Mercury New Jersey spill list: Mercury Louisiana spill reporting: Mercury California Director's List of Hazardous Substances.: Mercury TSCA 8(b) inventory: Mercury SARA 313 toxic chemical notification and release reporting: Mercury CERCLA: Hazardous substances.: Mercury: 1 lbs. (0.4536 kg)

Other Regulations:

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

Other Classifications:

WHMIS (Canada):

CLASS D-1A: Material causing immediate and serious toxic effects (VERY TOXIC). CLASS D-2A: Material causing other toxic effects (VERY TOXIC). CLASS E: Corrosive liquid.

DSCL (EEC):

R23- Toxic by inhalation. R33- Danger of cumulative effects. R38- Irritating to skin. R41- Risk of serious damage to eyes. R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. S2- Keep out of the

reach of children. S7- Keep container tightly closed. S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S39- Wear eye/face protection. S45- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). S46- If swallowed, seek medical advice immediately and show this container or label. S60- This material and its container must be disposed of as hazardous waste. S61- Avoid release to the environment. Refer to special instructions/Safety data sheets.

HMIS (U.S.A.):

Health Hazard: 3

Fire Hazard: 0

Reactivity: 0

Personal Protection:

National Fire Protection Association (U.S.A.):

Health: 3

Flammability: 0

Reactivity: 0

Specific hazard:

Protective Equipment:

Gloves. Full suit. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Face shield.

Section 16: Other Information

References: Not available.

Other Special Considerations: Not available.

Created: 10/10/2005 08:22 PM

Last Updated: 05/21/2013 12:00 PM

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall ScienceLab.com be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ScienceLab.com has been advised of the possibility of such damages.

SAFETY DATA SHEET

Creation Date 04-Oct-2010

Revision Date 19-Jan-2018

Revision Number 4

1. Identification

Product Name Nickel, powder

Cat No. : AC193610000; AC193610250; AC193611000; AC193615000

CAS-No 7440-02-0
Synonyms No information available

Recommended Use Laboratory chemicals.
Uses advised against Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

Fisher Scientific
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99

CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable solids	Category 2
Skin Sensitization	Category 1
Carcinogenicity	Category 1B
Specific target organ toxicity - (repeated exposure)	Category 1
Target Organs - Kidney, Blood.	

Label Elements

Signal Word

Danger

Hazard Statements

Flammable solid
May cause an allergic skin reaction
May cause cancer
Causes damage to organs through prolonged or repeated exposure

**Precautionary Statements****Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves
Do not breathe dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment

Response

IF exposed or concerned: Get medical attention/advice

Skin

IF ON SKIN: Wash with plenty of soap and water
If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Harmful to aquatic life with long lasting effects

WARNING. Cancer - <https://www.p65warnings.ca.gov/>.

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Nickel	7440-02-0	>95

4. First-aid measures

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.

Inhalation

Move to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.

Ingestion	Do not induce vomiting. Call a physician or Poison Control Center immediately.
Most important symptoms and effects	None reasonably foreseeable. . May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Unsuitable Extinguishing Media No information available

Flash Point No information available
Method - No information available

Autoignition Temperature 400 °C / 752 °F

Explosion Limits

Upper No data available
Lower No data available
Sensitivity to Mechanical Impact No information available
Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable.

Hazardous Combustion Products

Nickel oxides.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health
2

Flammability
3

Instability
0

Physical hazards
N/A

6. Accidental release measures

Personal Precautions Ensure adequate ventilation. Use personal protective equipment. Avoid dust formation. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas.

Environmental Precautions Should not be released into the environment. Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system.

Methods for Containment and Clean Up Sweep up or vacuum up spillage and collect in suitable container for disposal. Avoid dust formation.

7. Handling and storage

Handling Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Avoid dust formation. Use only under a chemical fume hood. Do not breathe vapors/dust. Do not ingest.

Storage Keep containers tightly closed in a dry, cool and well-ventilated place.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Nickel	TWA: 1.5 mg/m ³	(Vacated) TWA: 1 mg/m ³ TWA: 1 mg/m ³	IDLH: 10 mg/m ³ TWA: 0.015 mg/m ³	TWA: 1 mg/m ³

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection Long sleeved clothing.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Solid
Appearance	Brown
Odor	Odorless
Odor Threshold	No information available
pH	No information available
Melting Point/Range	1455 °C / 2651 °F
Boiling Point/Range	2730 °C / 4946 °F @ 760 mmHg
Flash Point	No information available
Evaporation Rate	Not applicable
Flammability (solid,gas)	No information available
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	1 mmHg @ 1810 °C
Vapor Density	Not applicable
Specific Gravity	No information available
Solubility	Insoluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	400 °C / 752 °F
Decomposition Temperature	No information available
Viscosity	Not applicable
Molecular Formula	Ni
Molecular Weight	58.7

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products. Excess heat. Avoid dust formation. acids.
Incompatible Materials	Strong oxidizing agents

Hazardous Decomposition Products Nickel oxides

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Nickel	LD50 > 9000 mg/kg (Rat)	Not listed	Not listed

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation No information available

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Nickel	7440-02-0	Group 2B	Reasonably Anticipated	Not listed	X	Not listed

IARC: (International Agency for Research on Cancer)

*Group 2B - Possibly Carcinogenic to Humans
IARC: (International Agency for Research on Cancer)*

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

NTP: (National Toxicity Program)

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure None known
STOT - repeated exposure Kidney Blood

Aspiration hazard No information available

Symptoms / effects, both acute and delayed Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Do not empty into drains. The product contains following substances which are hazardous for the environment. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Contains a substance which is: Toxic to aquatic organisms. Very toxic to aquatic organisms. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water

system.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Nickel	EC50: 0.174 - 0.311 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: = 0.18 mg/L, 72h (Pseudokirchneriella subcapitata)	LC50: = 10.4 mg/L, 96h static (Cyprinus carpio) LC50: = 1.3 mg/L, 96h semi-static (Cyprinus carpio) LC50: > 100 mg/L, 96h (Brachydanio rerio)	Not listed	EC50: = 1 mg/L, 48h Static (Daphnia magna) EC50: > 100 mg/L, 48h (Daphnia magna)

Persistence and Degradability Insoluble in water May persist

Bioaccumulation/ Accumulation No information available.

Mobility Is not likely mobile in the environment due its low water solubility.

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN3089
Proper Shipping Name Metal powder, flammable, n.o.s
Hazard Class 4.1
Packing Group II

TDG

UN-No UN3089
Proper Shipping Name METAL POWDER, FLAMMABLE, N.O.S.
Hazard Class 4.1
Packing Group II

IATA

UN-No UN3089
Proper Shipping Name METAL POWDER, FLAMMABLE, N.O.S.
Hazard Class 4.1
Packing Group II

IMDG/IMO

UN-No UN3089
Proper Shipping Name METAL POWDER, FLAMMABLE, N.O.S.
Hazard Class 4.1
Packing Group II

15. Regulatory information

All of the components in the product are on the following Inventory lists: X = listed

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Nickel	X	X	-	231-111-4	-		X	-	X	X	X

Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Nickel	7440-02-0	>95	0.1

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Nickel	-	-	X	X

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Nickel	X		-

OSHA Occupational Safety and Health Administration

Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Nickel	100 lb	-

California Proposition 65 This product contains the following proposition 65 chemicals

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Nickel	7440-02-0	Carcinogen	-	Carcinogen

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Nickel	X	X	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): N

DOT Marine Pollutant N

DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Creation Date 04-Oct-2010

Revision Date 19-Jan-2018


Print Date 19-Jan-2018

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS



Health	3
Fire	3
Reactivity	2
Personal Protection	E

Material Safety Data Sheet

Sodium MSDS

Section 1: Chemical Product and Company Identification

Product Name: Sodium

Catalog Codes: SLS3505

CAS#: 7440-23-5

RTECS: VY0686000

TSCA: TSCA 8(b) inventory: Sodium

CI#: Not applicable.

Synonym: Natrium

Chemical Name: Sodium

Chemical Formula: Na

Contact Information:

Sciencelab.com, Inc.

14025 Smith Rd.

Houston, Texas 77396

US Sales: **1-800-901-7247**

International Sales: **1-281-441-4400**

Order Online: ScienceLab.com

CHEMTREC (24HR Emergency Telephone), call:

1-800-424-9300

International CHEMTREC, call: 1-703-527-3887

For non-emergency assistance, call: 1-281-441-4400

Section 2: Composition and Information on Ingredients

Composition:

Name	CAS #	% by Weight
Sodium	7440-23-5	100

Toxicological Data on Ingredients: Sodium LD50: Not available. LC50: Not available.

Section 3: Hazards Identification

Potential Acute Health Effects:

Very hazardous in case of skin contact (irritant), of eye contact (irritant). Hazardous in case of skin contact (permeator), of ingestion, of inhalation. Inflammation of the eye is characterized by redness, watering, and itching. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.

Potential Chronic Health Effects:

CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. Repeated or prolonged exposure is not known to aggravate medical condition.

Section 4: First Aid Measures

Eye Contact: Check for and remove any contact lenses. Do not use an eye ointment. Seek medical attention.

Skin Contact:

After contact with skin, wash immediately with plenty of water. Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. Be particularly careful to clean folds, crevices, creases and groin. Cover the irritated skin with an emollient. If irritation persists, seek medical attention. Wash contaminated clothing before reusing.

Serious Skin Contact:

Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek medical attention.

Inhalation: Allow the victim to rest in a well ventilated area. Seek immediate medical attention.

Serious Inhalation:

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.

Ingestion:

Do not induce vomiting. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.

Serious Ingestion: Not available.

Section 5: Fire and Explosion Data

Flammability of the Product: Flammable.

Auto-Ignition Temperature: 115°C (239°F)

Flash Points: Not available.

Flammable Limits: Not available.

Products of Combustion: Some metallic oxides.

Fire Hazards in Presence of Various Substances:

Extremely flammable in presence of moisture. Highly flammable in presence of open flames and sparks, of heat.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Fire Fighting Media and Instructions:

Flammable solid. Moisture reactive material. SMALL FIRE: Obtain advice on use of water. Use DRY chemical powder. LARGE FIRE: Use water spray or fog. Do not use water jet.

Special Remarks on Fire Hazards: When heated to decomposition it emits toxic fumes.

Special Remarks on Explosion Hazards: Not available.

Section 6: Accidental Release Measures

Small Spill: Use appropriate tools to put the spilled solid in a convenient waste disposal container.

Large Spill:

Flammable solid that, in contact with water, emits flammable gases. Stop leak if without risk. Do not get water inside container. Do not touch spilled material. Cover with dry earth, sand or other non-combustible material. Prevent entry into sewers, basements or confined areas; dike if needed. Eliminate all ignition sources. Call for assistance on disposal.

Section 7: Handling and Storage

Precautions:

Keep under inert atmosphere. Keep container dry. Do not breathe dust. Never add water to this product. In case of insufficient ventilation, wear suitable respiratory equipment. If you feel unwell, seek medical attention and show the label when possible. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, acids, moisture.

Storage:

Flammable materials should be stored in a separate safety storage cabinet or room. Keep away from heat. Keep away from sources of ignition. Keep container tightly closed. Keep in a cool, well-ventilated place. Ground all equipment containing material. Keep container dry. Keep in a cool place.

Section 8: Exposure Controls/Personal Protection**Engineering Controls:**

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Personal Protection:

Splash goggles. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Dust respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits: Not available.

Section 9: Physical and Chemical Properties

Physical state and appearance: Solid. (Metal solid.)

Odor: Not available.

Taste: Not available.

Molecular Weight: 22.99 g/mole

Color: Silvery.

pH (1% soln/water): Not applicable.

Boiling Point: 881.4°C (1618.5°F)

Melting Point: 97.8°C (208°F)

Critical Temperature: Not available.

Specific Gravity: 0.97 (Water = 1)

Vapor Pressure: Not applicable.

Vapor Density: Not available.

Volatility: Not available.

Odor Threshold: Not available.

Water/Oil Dist. Coeff.: Not available.

Ionicity (in Water): Not available.

Dispersion Properties: Not available.

Solubility: Insoluble in cold water, hot water.

Section 10: Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Not available.

Incompatibility with various substances:

Highly reactive with oxidizing agents, acids, moisture. The product reacts violently with water to emit flammable but non toxic gases.

Corrosivity: Not available.

Special Remarks on Reactivity: Not available.

Special Remarks on Corrosivity: Not available.

Polymerization: No.

Section 11: Toxicological Information

Routes of Entry: Dermal contact. Eye contact. Inhalation. Ingestion.

Toxicity to Animals:

LD50: Not available. LC50: Not available.

Chronic Effects on Humans: Not available.

Other Toxic Effects on Humans:

Very hazardous in case of skin contact (irritant). Hazardous in case of skin contact (permeator), of ingestion, of inhalation.

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans: Material is destructive to tissue of the mucous membranes and upper respiratory tract.

Section 12: Ecological Information

Ecotoxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation are more toxic.

Special Remarks on the Products of Biodegradation: Not available.

Section 13: Disposal Considerations

Waste Disposal:

Section 14: Transport Information

DOT Classification: CLASS 4.3: Material that emits flammable gases on contact with water.

Identification: : Sodium : UN1428 PG: I

Special Provisions for Transport: Not available.

Section 15: Other Regulatory Information

Federal and State Regulations:

Pennsylvania RTK: Sodium Massachusetts RTK: Sodium TSCA 8(b) inventory: Sodium CERCLA: Hazardous substances.: Sodium

Other Regulations: OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications:

WHMIS (Canada): CLASS D-2B: Material causing other toxic effects (TOXIC).

DSCL (EEC):

R17- Spontaneously flammable in air. R38- Irritating to skin. R41- Risk of serious damage to eyes.

HMIS (U.S.A.):

Health Hazard: 3

Fire Hazard: 3

Reactivity: 2

Personal Protection: E

National Fire Protection Association (U.S.A.):

Health: 3

Flammability: 3

Reactivity: 2

Specific hazard:

Protective Equipment:

Gloves. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Splash goggles.

Section 16: Other Information

References:


-Hawley, G.G.. The Condensed Chemical Dictionary, 11e ed., New York N.Y., Van Nostrand Reinold, 1987. -SAX, N.I. Dangerous Properties of Industrial Materials. Toronto, Van Nostrand Reinold, 6e ed. 1984. -The Sigma-Aldrich Library of Chemical Safety Data, Edition II. -Guide de la loi et du règlement sur le transport des marchandises dangereuses au Canada. Centre de conformité international Ltée. 1986.

Other Special Considerations: Not available.

Created: 10/09/2005 06:28 PM

Last Updated: 05/21/2013 12:00 PM

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall ScienceLab.com be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ScienceLab.com has been advised of the possibility of such damages.



Health	1
Fire	1
Reactivity	1
Personal Protection	E

Material Safety Data Sheet

Zinc Metal MSDS

Section 1: Chemical Product and Company Identification

Product Name: Zinc Metal

Catalog Codes: SLZ1054, SLZ1159, SLZ1267, SLZ1099, SLZ1204

CAS#: 7440-66-6

RTECS: ZG8600000

TSCA: TSCA 8(b) inventory: Zinc Metal

CI#: Not applicable.

Synonym: Zinc Metal Sheets; Zinc Metal Shot; Zinc Metal Strips

Chemical Name: Zinc Metal

Chemical Formula: Zn

Contact Information:

Sciencelab.com, Inc.

14025 Smith Rd.

Houston, Texas 77396

US Sales: **1-800-901-7247**

International Sales: **1-281-441-4400**

Order Online: ScienceLab.com

CHEMTREC (24HR Emergency Telephone), call:
1-800-424-9300

International CHEMTREC, call: 1-703-527-3887

For non-emergency assistance, call: 1-281-441-4400

Section 2: Composition and Information on Ingredients

Composition:

Name	CAS #	% by Weight
Zinc Metal	7440-66-6	100

Toxicological Data on Ingredients: Zinc Metal LD50: Not available. LC50: Not available.

Section 3: Hazards Identification

Potential Acute Health Effects: Slightly hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation.

Potential Chronic Health Effects:

CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. Repeated or prolonged exposure is not known to aggravate medical condition.

Section 4: First Aid Measures

Eye Contact:

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.

Skin Contact: Wash with soap and water. Cover the irritated skin with an emollient. Get medical attention if irritation develops.

Serious Skin Contact: Not available.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Serious Inhalation: Not available.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

Serious Ingestion: Not available.

Section 5: Fire and Explosion Data

Flammability of the Product: Flammable.

Auto-Ignition Temperature: 480°C (896°F)

Flash Points: Not available.

Flammable Limits: Not available.

Products of Combustion: Not available.

Fire Hazards in Presence of Various Substances:

Slightly flammable to flammable in presence of open flames and sparks, of heat, of oxidizing materials, of acids, of alkalis, of moisture. Non-flammable in presence of shocks.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Fire Fighting Media and Instructions:

Flammable solid. SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.

Special Remarks on Fire Hazards:

Zinc + NaOH causes ignition. Oxidation of zinc by potassium proceeds with incandescence. Residues from zinc dust /acetic acid reduction operations may ignite after long delay if discarded into waste bins with paper. Incandescent reaction when Zinc and Arsenic or Tellurium, or Selenium are combined. When hydrazine mononitrate is heated in contact with zinc, a flaming decomposition occurs at temperatures a little above its melting point. Contact with acids and alkali hydroxides (sodium hydroxide, potassium hydroxide, calcium hydroxide, etc.) results in evolution of hydrogen with sufficient heat of reaction to ignite the hydrogen gas. Zinc foil ignites if traces of moisture are present. It is water reactive and produces flammable gases on contact with water. It may ignite on contact with water or moist air.

Special Remarks on Explosion Hazards: Not available.

Section 6: Accidental Release Measures

Small Spill:

Use appropriate tools to put the spilled solid in a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and dispose of according to local and regional authority requirements.

Large Spill:

Flammable solid that, in contact with water, emits flammable gases. Stop leak if without risk. Do not get water inside container. Do not touch spilled material. Cover with dry earth, sand or other non-combustible material. Prevent entry into sewers, basements or confined areas; dike if needed. Eliminate all ignition sources. Call for assistance on disposal. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system.

Section 7: Handling and Storage

Precautions:

Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not breathe dust. Keep away from incompatibles such as oxidizing agents, acids, alkalis, moisture.

Storage:

Keep container tightly closed. Keep container in a cool, well-ventilated area. Keep from any possible contact with water. Do not allow water to get into container because of violent reaction.

Section 8: Exposure Controls/Personal Protection

Engineering Controls:

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Personal Protection: Safety glasses. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Dust respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits: Not available.

Section 9: Physical and Chemical Properties

Physical state and appearance: Solid. (Lustrous solid. Metal solid.)

Odor: Not available.

Taste: Not available.

Molecular Weight: 65.39 g/mole

Color: Bluish-grey

pH (1% soln/water): Not applicable.

Boiling Point: 907°C (1664.6°F)

Melting Point: 419°C (786.2°F)

Critical Temperature: Not available.

Specific Gravity: Not available.

Vapor Pressure: Not applicable.

Vapor Density: Not available.

Volatility: Not available.

Odor Threshold: Not available.

Water/Oil Dist. Coeff.: Not available.

Ionicity (in Water): Not available.

Dispersion Properties: Not available.

Solubility: Insoluble in cold water, hot water, methanol, diethyl ether, n-octanol, acetone.

Section 10: Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Excess heat, incompatible materials, moisture

Incompatibility with various substances:

Reactive with oxidizing agents, acids, alkalis. Slightly reactive to reactive with moisture. The product may react violently with water to emit flammable but non toxic gases.

Corrosivity: Non-corrosive in presence of glass.

Special Remarks on Reactivity:

Incompatible with acids, halogenated hydrocarbons, NH_4NO_3 , barium oxide, $\text{Ba}(\text{NO}_3)_2$, Cadmium, CS_2 , chlorates, Cl_2 , CrO_3 , F_2 , Hydroxylamine, $\text{Pb}(\text{N}_3)_2$, MnCl_2 , HNO_3 , performic acid, KClO_3 , KNO_3 , N_2O_2 , Selenium, NaClO_3 , Na_2O_2 , Sulfur, Te, water, $(\text{NH}_4)_2\text{S}$, As_2O_3 , CS_2 , CaCl_2 , chlorinated rubber, catalytic metals, halocarbons, o-nitroanisole, nitrobenzene, nonmetals, oxidants, paint primer base, pentacarbonoyliron, transition metal halides, seleninyl bromide, HCl , H_2SO_4 , $(\text{Mg} + \text{Ba}(\text{NO}_3)_2 + \text{BaO}_2)$, (ethyl acetoacetate +tribromoneopentyl alcohol. Contact with Alkali Hydroxides(Sodium Hydroxide, Potassium Hydroxide, Calcium Hydroxide, etc) results in evolution of hydrogen. Ammonium nitrate + zinc + water causes a violent reaction with evolution of steam and zinc oxide. May react with water.

Special Remarks on Corrosivity: Not available.

Polymerization: Will not occur.

Section 11: Toxicological Information

Routes of Entry: Inhalation. Ingestion.

Toxicity to Animals:

LD50: Not available. LC50: Not available.

Chronic Effects on Humans: Not available.

Other Toxic Effects on Humans: Slightly hazardous in case of skin contact (irritant), of ingestion, of inhalation.

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans:

Acute Potential Health Effects: Skin: May cause skin irritation. Dermal exposure to zinc may produce leg pains, fatigue, anorexia and weight loss. Eyes: May cause eye irritation. Ingestion: May be harmful if swallowed. May cause digestive tract irritation with tightness in throat, nausea, vomiting, diarrhea, loss of appetite, malaise, abdominal pain. fever, and chills. May affect behavior/central nervous system and autonomic nervous system with ataxia, lethargy, staggering gait, mild derrangement in cerebellar function, lightheadness, dizziness, irritability, muscular stiffness, and pain. May also affect blood. Inhalation: Inhalation of zinc dust or fumes may cause respiratory tract and mucous membrane irritation with cough and chest pain. It can also cause "metal fume fever", a flu-like condition characterized appearance of chills, headached fever, maliase, fatigue, sweating, extreme thirst, aches in the legs and chest, and difficulty in breathing. A sweet taste may also be be present in metal fume fever, as well as a dry throat, aches, nausea, and vomiting, and pale grey cyanosis. The toxicological properties of this substance have not been fully investisgated.

Section 12: Ecological Information

Ecotoxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: Not available.

Special Remarks on the Products of Biodegradation: Not available.

Section 13: Disposal Considerations

Waste Disposal:

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Section 14: Transport Information

DOT Classification: Not a DOT controlled material (United States).

Identification: Not applicable.

Special Provisions for Transport: Not applicable.

Section 15: Other Regulatory Information

Federal and State Regulations:

New York release reporting list: Zinc Metal Rhode Island RTK hazardous substances: Zinc Metal Pennsylvania RTK: Zinc Metal Florida: Zinc Metal Michigan critical material: Zinc Metal Massachusetts RTK: Zinc Metal New Jersey: Zinc Metal California Director's List of Hazardous Substances: Zinc Metal TSCA 8(b) inventory: Zinc Metal TSCA 12(b) one time export: Zinc Metal SARA 313 toxic chemical notification and release reporting: Zinc Metal CERCLA: Hazardous substances.: Zinc Metal: 1000 lbs. (453.6 kg)

Other Regulations: EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

Other Classifications:

WHMIS (Canada): Not Available

DSCL (EEC):

R15- Contact with water liberates extremely flammable gases. R17- Spontaneously flammable in air. S7/8- Keep container tightly closed and dry.

HMIS (U.S.A.):

Health Hazard: 1

Fire Hazard: 1

Reactivity: 1

Personal Protection: E

National Fire Protection Association (U.S.A.):

Health: 0

Flammability: 1

Reactivity: 1

Specific hazard:

Protective Equipment:

Gloves. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Safety glasses.

Section 16: Other Information

References: Not available.

Other Special Considerations: Not available.

Created: 10/10/2005 12:18 AM

Last Updated: 05/21/2013 12:00 PM

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall ScienceLab.com be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ScienceLab.com has been advised of the possibility of such damages.