Site Investigation Report

Former Martin's Gulf Station Fort Covington, New York

Prepared for:

Town of Fort Covington

Fort Covington, New York 12937

Prepared by:

Kleinfelder East, Inc.

6390 Fly Road, Second Floor East Syracuse, New York 13057-9325 (315) 413-0181

November 2007

Project No. 69968

KLEINFELDER

SITE INVESTIGATION REPORT

Former Martin's Gulf Station Chateaugay and Salmon Street Fort Covington, New York

Environmental Restoration Program No. E-517006 Petroleum Bulk Storage (PBS) No. 5-436720

November 2007

Prepared by:

Kleinfelder East, Inc. 6390 Fly Road, Second Floor East Syracuse, New York 13057 Prepared for:

Town of Fort Covington Ms. Patricia Manchester Fort Covington, New York 12937

Kleinfelder Project No. 69968

Quality Assurance/Quality Control

The following personnel have reviewed this report for accuracy, content and quality of presentation:

Brian Kelly

Regional Manager

11/15/2007 Date

John T. Imhoff Senior Project Manager

11/15/2007 Date

TABLE OF CONTENTS

LIST	OF T	ABLES	S, FIGURES AND APPENDICES	I
EXEC	CUTI	VE SUN	MARY	Ш
1.0	INT	rodu	CTION	1
	1.1	Sco	pe of Investigation	1
	1.2	Rep	ort Format	4
2.0	BA	CKGR	OUND INFORMATION	5
	2.1	Site	Description	5
	2.2	Geo	ologic and Hydrogeologic Setting	6
	2.3	Cur	rent and Historical Use of Site and Surroundings	6
	2.4	Sen	sitive Receptors	7
3.0	SIT	E INVI	ESTIGATION ACTIVITIES	8
	3.1	Geo	physical Survey	8
	3.2	Soil	Investigation	9
		3.2.1	On-Site Soil Investigation	9
		3.2.2	Off-site Soil Investigation	10
	3.3	UST	「Removal	12
	3.4	Moı	nitoring Well Installation	12
		3.4.1	On-site Monitoring Well Installation	12
		3.4.2	Off-site Monitoring Well Installation	14
	3.5	Gro	undwater Gauging and Sampling	14
	3.6	Hyd	raulic (Slug) Testing	16
	3. 7	Saln	non River Sediment Sampling	16
	3.8	Soil	Vapor Sampling	17
4.0	FIN	DINGS	AND ANALYTICAL RESULTS	17
	4.1	Soil	Quality Analytical Data	18
	4.2	Sedi	ment Sample Analytical Results	19
	4.3	Gro	undwater Investigation Results	21
		4.3.1	Groundwater Gauging	21
		4.3.2	Groundwater Analytical Results	22
	4.4	Soil	Vapor Sampling on Eastern Property Margin	24
5.0	CO	NCLUS	IONS AND RECOMMENDATIONS	24
	5.1	Con	clusions	24
	5.2	Reco	ommendations	26
6.0	STA	TEME	NT OF LIMITATIONS	26
7.0	REI	FEREN	CES	27

LIST OF TABLES, FIGURES AND APPENDICES

TABLES

Table 1	-	Soil Analytical Data – Volatile Organic Compounds
Table 2	-	Soil Analytical Data - Semivolatile Organic Compounds
Table 3	-	Soil Analytical Data – Pesticides and PCBs
Table 4	-	Soil Analytical Data – Metals
Table 5	-	Sediment Analytical Data – Volatile Organic Compounds
Table 6	-	Sediment Analytical Data – Semivolatile Organic Compounds
Table 7	-	Sediment Analytical Data – Pesticides and PCBs
Table 8	-	Sediment Analytical Data - Metals
Table 9	-	Monitoring Well Gauging Data
Table 10	-	Groundwater Analytical Data – Volatile Organic Compounds
Table 11		Groundwater Analytical Data – Semivolatile Organic Compounds
Table 12		Groundwater Analytical Data – Pesticides and PCBs
Table 13	-	Groundwater Analytical Data – Metals
Table 14	-	Soil Gas Analytical Data - Organics

FIGURES

Figure 1	-	Locus Plan
Figure 2	-	Site Plan
Figure 3	-	Geologic Profiles
Figure 4	-	Soil Sample Analytical Data Exceeding NYSDEC SCOs
Figure 5	-	Sediment Sample Analytical Data Exceeding NYSDEC TGSCS
Figure 6	-	Groundwater Potentiometric Surface Map – October 2006

Figure 7	-	Groundwater Potentiometric Surface Map – January 2007
Figure 8	-	Groundwater Potentiometric Surface Map – June 2007
Figure 9	-	Groundwater Potentiometric Surface Map – September 2007
Figure 10	-	Groundwater Analytical Data Exceeding NYSDEC WQS
Figure 11	· ••	Soil Gas Sample Analytical Data – Detections
Figure 12	-	Proposed Interim Remedial Measure Excavation Area

APPENDICES

Appendix A	-	Waste Manifests, Bills of Lading and Characterization Data
Appendix B	-	KAS's Asbestos Inspection Report
Appendix C	<u>-</u> .	Soil Boring Logs and Monitoring Well Construction Details
Appendix D	-	Community Air Monitoring Data (VOCs)
Appendix E	-	Slug Test Evaluation Data
Appendix F	-	Data Usability Summary Reports
Appendix G	-	Atlantic Testing Laboratory Report - Salmon River Sediment Sampling and Analysis
Appendix H	-	Recommended Interim Remedial Measure

EXECUTIVE SUMMARY

On behalf of The Town of Fort Covington, Kleinfelder has completed a Site Investigation (SI) at the Former Martin's Gulf Station (Site), located at the southeast corner of the intersection of Chateaugay Street and Salmon Street in Fort Covington, New York (Environmental Restoration Program No. E-517006).

The purpose of the SI was to characterize the subsurface geology and hydrogeology of the Site, and determine the nature and extent of any impacts to soil or groundwater from historical operations. The site investigation included the cleaning and removal of two underground storage tanks formerly used to store gasoline, collection of soil samples from on-site and off-site areas, installation and sampling of on-site and off-site monitoring wells, and the collection and analysis of sediments from the Salmon River, in the vicinity of the subject Site. Four test pits were also dug at the Site to determine the cause of refusal for several borings and resolve a subsurface anomaly in this same area. Other activities performed at the Site included an evaluation of the Site building for the presence of asbestos containing materials in support of the eventual demolition of the Site building by the Town of Fort Covington, and the collection of soil gas samples from the eastern property boundary, adjacent to a condemned and abandoned residential property.

The site investigation was performed in several stages from April 2006 through September 2007. The results of the investigation revealed the presence of volatile and semi-volatile organic compounds present in Site soils and groundwater. The impacts were delineated within the boundaries of the Site. Results of the soil gas survey indicate the potential for vapor intrusion to structures overlying or near impacted areas. Samples collected from the Salmon River upriver, adjacent to, and downriver of the subject Site indicate the presence of various compounds also present in Site soils and groundwater; however, the presence of other isolated organic and inorganic constituents suggests a separate source of contamination in the river.

An interim remedial action (IRM) is proposed for the Site to resolve the impacts to soil and groundwater. The IRM is included with this document as an Appendix to this report.

1.0 INTRODUCTION

Kleinfelder East, Inc. (Kleinfelder) was retained by the Town of Fort Covington, New York to conduct a Site Investigation (SI) at the Former Martin's Gulf Station (Site), located at the southeast corner of the intersection of Chateaugay Street and Salmon Street in Fort Covington, New York (Figures 1 and 2). The purpose of the SI was to characterize the geology and hydrogeology of the Site, and to assess potential impact to on-site and off-site soil and groundwater. The investigation also included an evaluation of sediments from the Salmon River, located to the east and south of the Site, and a soil vapor investigation to assess potential soil vapors near the eastern property margin, where the Site abuts a residential property. The SI activities were conducted in accordance with the Subsurface Investigation Work Plan (SIWP) prepared by Geologic Services Corporation (GSC), now Kleinfelder, submitted to the New York State Department of Environmental Conservation (NYSDEC) on October 5, 2004, and approved on December 3, 2004.

A Community Air Monitoring Plan (CAMP) was developed for the Site, but was not implemented during the initial (2006), on-site Site Investigation phase of site activities. CAMP monitoring for VOCs was conducted during intrusive investigation activities in 2007. An Interim Remedial Measure (IRM) is proposed for the site to address impacts to the subsurface, and the CAMP will be implemented during IRM activities.

1.1 Scope of Investigation

Field activities were conducted in several phases between April 10, 2006 and September 21, 2007. The SI consisted of the field activities discussed below.

Soil Investigation and Test Pitting

- On-site mark out and geophysical survey to identify subsurface utilities or other cultural interferences including underground storage tanks (USTs), buried drums, demolished structures, etc.
- Advancement of 23 on-site soil borings ranging in depth from 1.5 to 16 feet below ground surface (ft bgs) MW-1 through MW-6, SB-2, SB-3, SB-4, SB-5A through 5G, SB-7, SB-9, SB-10, SB-12, and SB-13. Proposed off-site borings SB-18 and SB-19 were moved to just within the property boundary due to site constraints.

- Advancement of eight off-site soil borings SB-11, SB-13A and SB-14 through SB-17, SB-20 and SB-21). Proposed off-site borings SB-18 and SB-19 were moved to just within the property boundary due to site constraints.
- Excavation of four test pits to identify a subsurface geophysical anomaly and causes of refusal at locations SB-5A-SB-5G during drilling activities.
- Qualitative screening of soil samples with a photoionization detector (PID) for potential impacts.
- Laboratory analysis of soil for various parameters including VOCs, SVOCs, pesticides,
 PCBs, and metals. A summary of soil samples collected and associated analytical parameters is presented below.

SOIL SAMPLING AND ANALYSIS SUMMARY

Sample ID	Date	Analytical Parameters
SB-3 SURFACE	4/11/06	STARS VOCs, STARS SVOCs, Pest/PCBs, PPL Metals
SB-2 (6-8')	4/11/06	STARS VOCs, STARS SVOCs
SB-3 (4-6')	4/11/06	STARS VOCs, STARS SVOCs
SB-4 (6-8')	4/11/06	STARS VOCs, STARS SVOCs
SB-13 (6-8')	4/11/06	STARS VOCs, STARS SVOCs, Pest/PCBs, PPL Metals
SB-12 (8-10')	4/11/06	STARS VOCs, STARS SVOCs, Pest/PCBs, PPL Metals
SB-9 SURFACE	4/12/06	STARS VOCs, STARS SVOCs, Pest/PCBs, PPL Metals
SB-10 SURFACE	4/12/06	STARS VOCs, STARS SVOCs, Pest/PCBs, PPL Metals
SB-11 SURFACE	4/12/06	STARS VOCs, STARS SVOCs, Pest/PCBs, PPL Metals
SB-5B (1-2')	4/12/06	STARS VOCs, STARS SVOCs, Pest/PCBs, PPL Metals
SB-7 (4-5')	4/12/06	STARS VOCs, STARS SVOCs, Pest/PCBs, PPL Metals
SB-9 (6-8')	4/12/06	STARS VOCs, STARS SVOCs
SB-10 (10-12')	4/12/06	STARS VOCs, STARS SVOCs, Pest/PCBs, PPL Metals
SB-11 (2-4')	4/12/06	STARS VOCs, STARS SVOCs
TP1-6'	8/15/08	VOCs 8260B, SVOCs 8270C/3550B
TP2-6'	8/15/06	VOCs 8260B, SVOCs 8270C/3550B
TP3-4'	8/15/06	VOCs 8260B, SVOCs 8270C/3550B
TP4-6'	8/15/06	VOCs 8260B, SVOCs 8270C/3550B
UST-SURFACE	8/15/06	STARS VOCs, STARS SVOCs, Pest/PCBs, PPL Metals
MW1(4')	10/10/06	STARS VOCs, STARS SVOCs
MW2(5')	10/10/06	STARS VOCs, STARS SVOCs
MW3(4')	10/10/06	STARS VOCs, STARS SVOCs
MW4(3')	10/10/06	STARS VOCs, STARS SVOCs
MW5(5')	10/10/06	STARS VOCs, STARS SVOCs
MW6(5')	10/11/06	STARS VOCs, STARS SVOCs
SUR-1(0-2")	6/18/07	TCL VOCs, TCL SVOCs, Pest/PCBs, Select Metals.
SUR-2(0-2")	6/18/07	TCL VOCs, TCL SVOCs, Pest/PCBs, Select Metals.
SUR-3(0-2")	6/18/07	TCL VOCs, TCL SVOCs, Pest/PCBs, Select Metals.
SB-13A (0-2")	6/18/07	TCL VOCs, TCL SVOCs, Pest/PCBs, TAL Metals
SB-16 (0-2")	6/18/07	TCL VOCs, TCL SVOCs, Pest/PCBs, TAL Metals
SB-14 (4')	6/19/07	TCL VOCs, TCL SVOCs, Pest/PCBs, Select Metals.
SB-15 (4')	6/19/07	TCL VOCs, TCL SVOCs, Pest/PCBs, Select Metals.
SB-16 (3')	6/19/07	TCL VOCs, TCL SVOCs, Pest/PCBs, TAL Metals

SB-13A (4')	6/20/07	TCL VOCs, TCL SVOCs, Pest/PCBs, TAL Metals
SB-17 (4')	6/20/07	TCL VOCs, TCL SVOCs, Pest/PCBs, Select Metals.
SB-20 (4')	6/20/07	TCL VOCs, TCL SVOCs, Pest/PCBs, Select Metals.
SB-18 (4')	6/29/07	TCL VOCs, TCL SVOCs, Pest/PCBs, Select Metals.
SB-19 (4')	6/29/07	TCL VOCs, TCL SVOCs, Pest/PCBs, Select Metals.
SB-21 (4')	6/29/07	TCL VOCs, TCL SVOCs, Pest/PCBs, Select Metals.

Underground Storage Tank Removal

- Cleaning, excavation, and removal of one 2,000-gallon steel UST and one 1,000-gallon steel UST.
- Qualitative screening of soil samples with a PID for potential petroleum impacts.
- Collection of post-excavation soil samples (SW-N-6' and TT-1000G-FP) and analysis of soil for VOCs and SVOCs.

Groundwater Investigation

- Installation and development of six on-site monitoring wells to depths ranging from 16 to 25 ft bgs (MW-1 to MW-6).
- Completion of soil borings SB-13A, SB-16 and SB-20 as off-site monitoring wells MW-7, MW-8 and MW-9, respectively.
- Qualitative screening of soil samples with a PID for potential petroleum impacts.
- Laboratory analysis of soil samples collected from on-site monitoring well locations for VOCs and SVOCs
- Gauging of depth to water in on-site and off-site monitoring wells
- Laboratory analysis of groundwater samples for VOCs, SVOCs, pesticides, PCBs, and target analyte list (TAL) or PP metals. A summary of groundwater analytical parameters is presented below.
- Hydraulic (Slug) testing at select on-site monitoring well locations.

GROUNDWATER SAMPLING AND ANALYSIS SUMMARY

Sample ID	Date	Analytical Parameters
MW-1	10/26/06	STARS VOCs, STARS SVOCs, PPL Metals.
MW-2	10/26/06	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-3	10/26/06	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-4	10/26/06	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-5	10/26/06	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-6	10/26/06	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-1	1/22/07	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-2	1/22/07	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-3	1/22/07	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-4	1/22/07	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-5	1/22/07	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-6	1/22/07	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-7	6/19/2007	TCL VOCs, TCL SVOCs, TAL Metals, Pest/PCBs
MW-8	6/19/2007	TCL VOCs, TCL SVOCs, TAL Metals, Pest/PCBs
MW-9	6/19/2007	TCL VOCs, TCL SVOCs, TAL Metals, Pest/PCBs
SB-14-GW	6/19/07	TCL VOCs, TCL SVOCs, TAL Metals, Pest/PCBs

Salmon River Sediment Investigation

- Collection of sediment samples from the banks of the Salmon River located upstream and downstream of the Site.
- Laboratory analysis of sediment samples for VOCs, SVOCs, pesticides, PCBs, and metals.

Soil Vapor Sampling

- Installation of soil vapor sampling points along the eastern margin of the Site
- Collection of soil gas samples for analysis of VOCs via EPA method TO-15.

1.2 Report Format

Section 1.0 of this report presents an introduction to the SIR. Section 2.0 provides a description of the Site and background pertaining to the Site and surrounding areas. Section 3.0 describes the UST removal and SI activities. Section 4.0 presents a discussion of the findings and analytical results. Section 5.0 presents the summary and conclusions of the SI. Section 6.0 presents limitations on the use of the SIR, and Section 7.0 presents references used in the preparation of this SIR.

2.0 BACKGROUND INFORMATION

On June 27, 2003, Mr. Michael McLean of the NYSDEC and representatives from the Town of Fort Covington performed an environmental inspection at the subject Site, which was a former Gulf gasoline sales and service station. Several areas of concern were noted at the Site, including the presence of underground storage tanks, two (2) 55-gallon drums with unknown contents, and hydraulic lifts and floor drains in the garage. Based on the inspection, the NYSDEC indicated that the Site was a candidate for the Environmental Restoration Program (ERP). In December 2003, the Town submitted an application for the ERP, and the application was approved by the NYSDEC in early 2004.

Kleinfelder (formerly GSC) was retained to investigate the areas of concern identified at the Site and determine the potential for impacts to on-site and off-site soils and groundwater. Accordingly, in September 2004 Kleinfelder (formerly GSC) submitted a Site Investigation Work Plan (SIWP) for on-site and off-site investigation activities. The SIWP was approved by the NYSDEC in December 2004.

The NYSDEC contracted Op-Tech of Massena, New York to sample the contents of the 55-gallon drums and arrange for their transportation and disposal. The drums were characterized as hazardous waste due to concentrations of acetone detected during waste characterization, and were subsequently transported from the Site on November 19, 2004 as hazardous waste. The laboratory report for waste characterization and the hazardous waste manifest are included in Appendix A.

On September 20, 1995 the NYSDEC issued Case No. 95-07646 to the Site (Martin's Gulf Service Station) as a result of failure to re-register two (2) gasoline Underground Storage Tanks (USTs). No further information regarding the assignation of this spill number to the site was available to Kleinfelder.

2.1 Site Description

The Site is a former Gulf gasoline station and automobile repair facility situated on an approximately 1/8-acre parcel of land located on the southeastern quadrant of the intersection of Chateaugay Street and Salmon Street in Fort Covington, New York (Figure 1). The Site is currently vacant, with structural remnants of the former gas and service station present in the immediate subsurface. The Site is vegetated in some areas, with the remainder of the Site covered with broken asphalt and exposed sub-base stone. While in operation, gasoline was stored in one 1,000-gallon and one 2,000-gallon steel USTs. According to the NYSDEC Petroleum Bulk Storage Program Facility Information Report, these tanks were installed in October 1986.

The Site is located approximately 171 feet above mean sea level. The topography in the vicinity of the Site is generally flat-lying, but grades gently down to the east-southeast towards the Salmon River. The bank of the Salmon River is located less than 100 feet from the southeastern boundary of the Site. A portion of the United States Geologic Survey (USGS) 7.5-minute series topographic map for the Fort Covington, New York-Quebec quadrangle is presented as Figure 1. The locations of pertinent Site features are indicated on Figure 2.

The intended future use of the Site by the Town of Fort Covington is as a municipal park.

2.2 Geologic and Hydrogeologic Setting

The Adirondack Sheet of the Surficial Geologic Map of New York (1991) categorizes surficial geology at the Site as lacustrine (lake) silt and clay deposits. No previous descriptions of geologic materials at the Site were available for review. Bedrock geology underlying surficial geology in region of Fort Covington is dolostone of the Beekmanton Group (Landforms and Bedrock of New York State, New York State Museum, 1973). No previous descriptions of the bedrock geology beneath the Site were available for the review.

Multiple soil borings and monitoring wells have been installed as part of the SI, and have allowed a comprehensive assessment of the unconsolidated subsurface materials. Geologic profile transects were prepared to illustrate the unconsolidated subsurface materials at the Site. Transects A-A' and B-B' are depicted on the Site Map presented as Figure 2, while the geologic profiles are presented on Figure 3. As presented on Figure 3, the unconsolidated subsurface materials consist of approximately 2 to 5 feet of sand at the surface, overlying approximately 5 to 10+ feet of silt and clay. The silt and clay overlies a sand and gravel unit, the depth of which is not known. The depth to bedrock in the area is not known as it was not encountered during SI activities. According to documents reviewed pertaining to the vicinity, the depth to bedrock is generally expected to be 30 to 50 ft bgs.

Historical groundwater gauging information was not available prior to this SI. Data collected during the SI indicated that groundwater generally flows toward the east (toward the Salmon River), but varies from northwest to southeast. This is discussed in more detail later in this report.

2.3 Current and Historical Use of Site and Surroundings

The Site is a former gasoline station and automobile repair facility. At the initiation of this project in 2004, the Site was developed with one-story gas station/garage building. On September 29, 2005 KAS, Inc. of Williston, VT, under contract to Op-Tech, conducted an asbestos inspection of the former Martin's

Garage building and determined that no Asbestos Containing Materials (ACM) were present in the building. KAS's Asbestos Inspection Report in included as Appendix B. The building was demolished by the Town of Fort Covington in October 2005. Demolition debris was transported by the Town to Franklin County Sanitary Landfill. The Site has remained vacant and all other above-ground structures have been removed.

During SI activities, Kleinfelder attempted to locate the hydraulic lifts observed by the NYSDEC in 2003 when the garage building was still present. Attempts to locate the hydraulic lifts were not successful. Additionally, Op-Tech had been retained to complete the previously-described asbestos inspection and evacuate materials from a hoist/lift pit in November 2005, and the hydraulic lift was reportedly not observed by Op-Tech during these activities. A drum of hydraulic oil was discovered and subsequently removed from the Site by Op-Tech in January 2006. This drum may have contained the contents of a hydraulic lift prior to the lift's removal. The bill of lading for the transportation and disposal of the drum of hydraulic oil is provided in Appendix A.

Immediately north of Site is State Route 37 (Chateaugay Street), beyond which are an automobile customizing business and residential properties. To the west of the Site is Salmon Street, beyond which are a municipal park and baseball fields. To the south of the Site is a vacant parcel of land owned by the Town of Fort Covington. To the east of the Site is a vacant residential property with a condemned structure, beyond which is a town-owned memorial park. According to a tax map of the Town, this park was the previous location of the town highway garage. To the northwest, across the intersection of Salmon and Chateaugay Streets, is a vacant lot. According to Mike Mclean, NYSDEC, the Site may have underground storage tanks present. Kleinfelder proposed subsurface investigation activities at this parcel, but access to the site was denied by the property owner. Additional information regarding the status of any USTs at this parcel could not be obtained by Kleinfelder.

A 1942 aerial photograph at the Franklin County Clerk's Office in Malone, NY of the Site's vicinity shows the area as developed at that time. While much of the area surrounding the Site could be identified as agricultural land, due to the scale and resolution of the photograph, the type of development in the Site's vicinity could not be distinguished and therefore the photograph was not reproduced.

2.4 Sensitive Receptors

The following subsections provide a discussion of pertinent sensitive receptors including utilities, surface water, and potable wells/aquifers at and around the Site.

Utilities and Basements

Based upon visual observations, commercial and residential buildings with basements are present in the vicinity of the Site. Immediately adjacent and east of the Site is a vacant condemned residential dwelling.

Underground utilities that transect the Site include water and sewer lines that service the vacant residential dwelling east of the Site. Subsurface utilities are also present adjacent to the Site along Chateaugay and Salmon Streets.

Surface Water

The Salmon River, which drains into the St. Lawrence River, is located less than 100 feet east-southeast of the Site (Figure 2).

Potable Wells/Aquifer

According to the Town of Fort Covington Water and Sewer Department, there are two (2) municipal potable water supply wells within a one (1) mile radius of the Site. One (1) municipal water supply well is located approximately 620 feet north-northeast of the Site on Water Street and one (1) reserve water supply well is located approximately 1,575 feet northeast of the Site on Blanchard Street, with approximate depths of 150 and 258 ft bgs, respectively. The Town of Fort Covington Water and Sewer Department personnel did not have information concerning the screened interval and depth to water in these wells. Additionally, the Water and Sewer Department was unaware of any private potable wells within the Town of Fort Covington. The locations of the municipal water supply wells are illustrated on Figure 1.

3.0 SITE INVESTIGATION ACTIVITIES

3.1 Geophysical Survey

On April 10, 2006, subsurface investigation activities were initiated at the Site. Kleinfelder subcontracted Vermont Underground Locators, Inc. (VUL) of North Haverhill, New Hampshire to conduct an on-site utility mark-out. VUL utilized various utility locators and ferrous-metal detectors to determine the locations of on-site subsurface utilities. A radio frequency scanning device was also employed by VUL to determine the locations of any subsurface anomalies and/or USTs. The application of these methods resulted in locating a water supply line, sewer piping, two USTs, and a subsurface metal anomaly.

3.2 Soil Investigation

3.2.1 On-Site Soil Investigation

Between April 11 and April 12, 2006, Kleinfelder oversaw the installation of 16 soil borings, SB-2 through SB-4, SB-5A through SB-5G, SB-7, SB-9, and SB-10 through SB-13. The locations of these soil borings are depicted on Figure 2 and Figure 4. Subsurface investigation activities (soil boring advancement and test pit excavation) were performed by Op-Tech Environmental Services (Op-Tech) of Massena, New York, under contract and supervision of Kleinfelder. Prior to drilling, Op-Tech hand cleared subsurface material to depths of approximately eight feet at each soil boring location in order to prevent damage to any potential subsurface structures or utilities. Soil borings were advanced using a truck mounted direct-push rig. Soil borings SB-2 through SB-4, SB-7, and SB-9 through SB-13 were advanced to depths ranging from 12 to 16 ft bgs. Soil samples were collected from the maximum depth of hand-clearing (approximately eight ft bgs) to the terminal depth of each boring using a four-foot long sampler. At soil boring locations SB-5A through SB-5G, refusal was encountered at approximately three feet below grade. Test pitting in the general area of SB-5 revealed concrete debris in the shallow subsurface. Proposed soil boring (SB-8) was not advanced due to the presence of an overheard electrical line in close proximity of its proposed location.

All soil samples were screened for VOCs using a PID equipped with a 10.6 eV lamp calibrated to an isobutylene span gas to yield total VOCs in parts per million by volume (ppm_v). The PID screening values are qualitative, and are not necessarily indicative of actual VOC concentrations in soil, as determined by laboratory analysis. Information regarding qualitative soil screening results, soil classification, and details of observed evidence of impact are presented on the soil boring logs included as Appendix C.

In general, the soil sample exhibiting the highest PID response in each soil boring location was selected for laboratory analysis. Soil samples were also collected and analyzed to evaluate the vertical extent of observed impact. In the absence of PID responses above background, the sample collected nearest to the water table was submitted for off-site laboratory analysis.

Soil samples were placed in ice filled coolers, and shipped under standard chain of custody procedures via Federal Express to Accutest Laboratories (Accutest) in Dayton, New Jersey. Subsurface soil samples were analyzed as set forth in the Soil Sampling and Analysis Summary table in Section 1.1.

On August 16, 2006, Op-Tech conducted test pitting activities in four areas of the Site (see Figure 2). Test pit (TP-1) was excavated near the central portion of the Site in an effort to identify the source of a

metal anomaly discovered during the geophysical survey conducted in April 2006. It was thought that the metal anomaly might represent the former hydraulic lift location; however, no evidence of a subsurface structure or causal agent for the anomaly was observed. The three remaining test pits, TP-2, TP-3, and TP-4, were excavated at the northern property boundary in an effort to determine the causes of refusal in the general area of soil borings SB-5A through SB-5G. Several large pieces of concrete and other construction-type debris in the area were determined to be the cause for refusal in these borings. Soil samples were collected from each test pit (TP1-6', TP2-6', TP3-4' and TP4-6') and submitted to Accutest for analysis of the full 8260 method list of VOCs and Target Compound List (TCL) SVOCs in accordance with USEPA Methods 8260 and 8270, respectively.

In addition to subsurface soil samples collected from soil borings and test pits, five surface soil samples (SB-3 Surface, SB-9 Surface through SB-11 Surface, and UST Surface) were collected for laboratory analysis at the request of the New York State Department of Health (NYSDOH). Surface soil samples were biased to areas around the perimeter of the Site and the vicinity of the former service bay doors. Soil samples were submitted to Accutest for analysis of STARS list of VOCs via method 8260, STARS list SVOCs via method 8270, pesticides, PCBs, and PP metals in accordance with USEPA Methods 8081A, 8082, and 6010B, respectively.

3.2.2 Off-site Soil Investigation

Off-site subsurface investigation activities were initiated on June 18, 2007. Prior to intrusive activities, VUL conducted an off-site utility clearance at the proposed direct-push soil boring, monitoring well and soil vapor point locations. VUL utilized various utility locators and ferrous-metal detectors in order to identify potential subsurface utilities in the proposed drilling/sampling locations so that the sampling points could be suitably relocated if necessary.

Between June 19 and 22, 2007, Kleinfelder oversaw the advancement of off-site soil borings SB-13A, SB-14, SB-15, SB-16, SB-17, SB-18, SB-19, SB-20 and SB-21 (See Figure 2 for locations). Soil borings SB-18 and SB-19 were proposed as off-site locations; however, surface and subsurface obstructions necessitated the relocation of these borings to just within the eastern estimated Site property boundary. Soil borings were advanced by Op-Tech under contract and supervision of Kleinfelder. Soil borings were hand cleared to a depth of approximately eight ft bgs to prevent damage to potential subsurface structures/utilities. Soil borings were advanced using a track-mounted direct-push rig with auger-turning capabilities that allowed the rig to be used for monitoring well installations as described in Section 3.4.2.

Soil borings were advanced to depths of up to 20 ft bgs, details of each boring are depicted on the soil boring logs in Appendix C. Soil sampling was conducted during hand-clearing using hand sampling equipment (i.e., hand auger), below the hand-clearing interval (approximately eight ft bgs) to the terminal depth of each boring, soil samples were collected using a four-foot long sampler.

In general, the soil sample exhibiting the highest PID response in each soil boring location was selected for laboratory analysis. Soil samples were also collected and analyzed to evaluate the vertical extent of observed impact. In the absence of PID responses above background, the sample collected nearest to the water table was submitted for off-site laboratory analysis.

Soil samples were placed in ice-filled coolers, and shipped under standard chain of custody procedures via Federal Express to Lancaster Laboratories, Inc. (Lancaster) of Lancaster, Pennsylvania. Surface and subsurface soil samples were analyzed as set forth in the Soil Sampling and Analysis Summary table in Section 1.1. With the NYSDEC's approval, the limited list of metals was established to include those metals that had been detected during on-site investigation activities in 2006.

On June 18, 2007, surface soil samples were collected from the locations of soil borings SB-16 and SB-13A (designated as SB-16(0-2") and SB-13A (0-2"), respectively) and from the locations identified as SUR-1, SUR-2 and SUR-3 (see Figure 2). In accordance with NYSDOH procedures, surface soil samples were collected from no more than 2-inches below surface grade after surface vegetation had been removed. The samples were collected using disposable hand-sampling equipment, and were handled and shipped to Lancaster in the manner described above, and analyzed for the parameters set forth in the Soil Sampling and Analysis Summary table in Section 1.1.

Soil borings SB-13A, SB-16 and SB-20 were subsequently completed as off-site monitoring wells MW-7, MW-8 and MW-9, respectively, as described in the Section 3.4.2. Additionally, a temporary well screen was installed in the open borehole at SB-14 to facilitate grab groundwater sample collection (SB-14-GW) on October 19, 2007. The temporary well screen was removed and the boring backfilled after grab groundwater samples were collected. Additional details regarding the groundwater investigation are set forth in Section 4.3.

As mentioned in Section 1.0 the Community Air Monitoring Program (CAMP) was not initiated during intrusive investigation activities conducted in 2006. During intrusive activities conducted in 2007 however, CAMP monitoring for volatile organic compounds was implemented. The CAMP data are presented in Appendix D.

3.3 UST Removal

UST removal and test pitting activities were conducted by Op-Tech under contract and supervision of Kleinfelder. On August 15, 2006, Op-Tech removed approximately two feet of overburden to expose the top of the tanks. The tanks were filled to capacity with what appeared to be a gasoline and water mixture. Approximately 3,000 gallons of gas/water mixture was pumped from the tanks by Op-Tech directly into a tank-truck for subsequent off-site disposal. Manifests for transport and disposal of the tank contents are included in Appendix. A.

The USTs were removed from the ground and visually inspected for evidence of corrosion, pitting, holes, and cracks. No holes, pitting or other damage was observed by Kleinfelder. Evidence of impact was observed in the excavation, but excavation activities were postponed because an IRM to address impacted soils at the Site was anticipated and full delineation of impacts had not yet been completed. The USTs were then removed from the Site by Op-Tech for cleaning and disposal. Transportation and disposal documentation is included in Appendix A. Former UST locations and excavation areas are shown on Figure 2.

Two sections of steel product piping were also excavated by Op-Tech, and visually inspected for evidence of corrosion. No holes, pitting or other damage to the piping was observed by Kleinfelder. Steel product piping was left on-site for disposal by the Town of Fort Covington. Overburden soil was placed into the tank void, with additional fill material provided by the Town of Fort Covington to backfill the tank excavation to grade. Soil was not removed from the Site as part of the UST removal action.

Two soil samples were collected from the UST excavation area (TT-1,000-G-FP and SW-N-6') were placed in a storage/transportation cooler, preserved with ice, and shipped under standard chain of custody procedures via Federal Express to Accutest. The soil samples were analyzed for the full 8260 method list of VOCs and TCL SVOCs in accordance with USEPA Methods 8260 and 8270, respectively.

Because impacted soils remain that will be removed during the proposed IRM at the Site, a UST closure report has not been prepared. A UST closure report/request will be prepared at the conclusion of the interim remedial measure at the Site.

3.4 Monitoring Well Installation

3.4.1 On-site Monitoring Well Installation

On October 10, 2006, Geosearch Environmental Contractors (Geosearch) of Fitchburg, Massachusetts, under contract and supervision of Kleinfelder, began clearing the six proposed monitoring well locations

using a truck-mounted pneumatic vacuum system to dislodge and remove shallow subsurface material from grade to approximately four ft bgs. A truck-mounted hollow stem auger drill rig was used to install the monitoring wells to terminal depths ranging from 16 to 25 ft bgs. Split spoon soil samples were collected continuously from each soil boring at two-foot intervals from the maximum depth of vacuum clearing (approximately 4 ft bgs) to the terminal depth of each boring. Monitoring well locations are shown on Figure 2.

Qualitative soil screening results from the monitoring well installations are included on the monitoring well logs included in Appendix C. In general, the soil sample exhibiting the highest PID response from the unsaturated zone of each monitoring well was selected for laboratory analysis. Soil samples were also collected to evaluate the vertical extent of observed impact. In the absence of PID responses above background in the unsaturated zone, the unsaturated sample collected nearest to the water table was selected for laboratory analysis.

Soil samples were placed in storage/transportation coolers, preserved with ice, and shipped under standard chain of custody procedures via Federal Express to Accutest. Soil samples collected from soil borings MW-1 through MW-6 were analyzed for parameters set forth in the Soil Sampling and Analysis Summary table in Section 1.1.

The monitoring wells were completed to depths ranging from approximately 16 to 25 ft bgs utilizing five feet of two-inch diameter schedule 40 polyvinyl chloride (PVC) well casing, and nine to 18 feet of two-inch diameter 0.01-inch slot schedule 40 PVC well screen. The monitoring wells were backfilled with No. 01 filter-pack sand to approximately one-foot above the slotted well screen interval. A layer of bentonite time-delay pellets was backfilled to approximately two feet above the sand pack to form an impermeable seal. Each monitoring well was completed with an eight-inch diameter flush-mount manhole cover clearly embossed with the words "Monitoring Well". The flush-mount manhole covers were installed in two foot square concrete pads. The concrete pads were raised slightly above surface grade and sloped to facilitate storm water runoff away from the monitoring well. Following installation, the wells were developed by purging multiple volumes of groundwater from each well. Groundwater was passed through a 5-gallon bucked containing granular activated carbon, and discharged to the ground surface.

Monitoring well construction details are illustrated on the Monitoring Well/Soil Boring Logs provided in Appendix C.

3.4.2 Off-site Monitoring Well Installation

Between June 19 and June 22, 2007, soil borings SB-13A, SB-16 and SB-20 were completed as monitoring wells MW-7, MW-8 and MW-9, respectively. The soil borings were overdrilled using a direct-push rig with hollow-stem auger capabilities. The monitoring wells were each completed to a depth of 20 ft bgs. Wells were constructed using approximately 17 feet of two-inch diameter, 0.01-inch slot, schedule 40 PVC well screen and approximately 3 feet of 2 inch diameter PVC riser. The monitoring wells were backfilled with No. 01 filter sand to approximately one foot above the slotted well screen interval. A layer of hydrated bentonite was used to backfill the wells to approximately two feet above the sand pack to form an impermeable seal. Each monitoring well was completed with an eight-inch diameter flush-mount manhole cover, installed in two foot square concrete pads. Following installation, the wells were developed by purging multiple volumes of groundwater from each well. Groundwater was passed through a 5-gallon bucked containing granular activated carbon, and discharged to the ground surface.

Monitoring well construction details are illustrated on the Monitoring Well/Soil Boring Logs provided in Appendix C.

3.5 Groundwater Gauging and Sampling

Three rounds of groundwater sampling were conducted at the Site: October 2006, January 2007 and June 2007. Gauging was conducted using an electronic interface probe and liquid-phase hydrocarbons were not identified in the monitoring wells. The top of well casing at each monitoring well had previously been surveyed to an arbitrary datum, so that general groundwater flow direction could be evaluated. A minimum of three calculated well volumes was purged from each well (or the well was purged dry) and was allowed to recover prior to groundwater sample collection. Samples were collected into laboratory-supplied sample containers, containing preservatives appropriate for the requested analyses. Samples were labeled, logged onto a chain of custody form, placed on ice in a shipping cooler, and shipped via overnight delivery service to Accutest (October 2006 and January 2007) and Lancaster (June 2007).

October 2006

On October 26, 2006 monitoring wells MW-1 through MW-6 were gauged for depth to groundwater and sampled as previously described. Depth to groundwater ranged from 2.78 ft below the top of casing (btoc) at MW-1 to 3.26 ft btoc at MW-4. Samples were analyzed as set forth in the summary table below.

MW-1	10/26/06	Groundwater	STARS VOCs, STARS SVOCs TCL, PPL Metals.
MW-2	10/26/06	Groundwater	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-3	10/26/06	Groundwater	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-4	10/26/06	Groundwater	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-5	10/26/06	Groundwater	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-6	10/26/06	Groundwater	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.

January 2007

A subsequent groundwater gauging and sampling event was conducted on January 22, 2007. Depth to groundwater ranged from 3.37 ft btoc at MW-6 to 4.36 ft btoc at MW-4. Groundwater sampling was conducted as described previously, and samples were submitted Accutest for analysis of the previously described list of analytical parameters. Samples were analyzed as set forth in the summary table below.

MW-1	1/22/07	Groundwater	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-2	1/22/07	Groundwater	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-3	1/22/07	Groundwater	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-4	1/22/07	Groundwater	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-5	1/22/07	Groundwater	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.
MW-6	1/22/07	Groundwater	STARS VOCs, STARS SVOCs TCL Pest/PCBs, PPL Metals.

June 2007

On June 25, 2007 groundwater samples were collected from monitoring wells MW-7, MW-8 and MW-9. Groundwater gauging was completed prior to groundwater purging and sampling activities. Groundwater samples were analyzed as set forth in the summary table below.

MW-7	6/25/2007	Groundwater	TCL VOCs, TCL SVOCs, TAL Metals, Pest/PCBs
MW-8	6/25/2007	Groundwater	TCL VOCs, TCL SVOCs, TAL Metals, Pest/PCBs
MW-9	6/25/2007	Groundwater	TCL VOCs, TCL SVOCs, TAL Metals, Pest/PCBs
SB-14-GW	6/19/2007	Groundwater	TCL VOCs, TCL SVOCs, TAL Metals, Pest/PCBs

September 2007

On September 21, 2007 the on-site and off-site monitoring wells were surveyed for elevation relative to an arbitrary benchmark of 100 ft. Depth to groundwater measurements were collected from each of the on-site and off-site wells so that groundwater flow direction could be approximated. On September 21, groundwater levels ranged from 3.25 ft btoc at MW-8 to 5.44 ft btoc at MW-7. On September 21, 2007 groundwater levels ranged from 4.20 ft btoc at MW-89 to 7.17 ft btoc at MW-7. During these gauging events, an oil-water interface probe was used to determine whether free-phase hydrocarbons were present. Free-phase hydrocarbons were not observed during these gauging events.

3.6 Hydraulic (Slug) Testing

On June 19, 2007, hydraulic (slug) testing was conducted at on-site monitoring wells MW-2 and MW-6. Rising- head slug tests were performed by instantaneously removing a slug of water (two standard 1-liter bailers tied in tandem) from the well and subsequently gauging the rising water levels during recovery. AQTESOLV was used to evaluate the hydraulic test data using the Cooper-Bredenhoeft-Papadopulos (1967) solution method. The slug test data and AQTESOLV evaluation are presented as Appendix E.

For MW-6 effective hydraulic conductivity (K) was estimated to be 1.07 ft/day. For MW-2, the estimated K value was 2.69 ft/day. A review of the soil types present in the saturated zone of these wells (see well logs included in Appendix C), indicated the sand and gravel water-bearing zone near MW-6 had finer sand grains among the gravel than the sand and gravel water-bearing zone near MW-2 and likely accounts for the variability in estimated K values. Based on these estimated values, a mean K for the Site was calculated to be 1.88 ft/day.

3.7 Salmon River Sediment Sampling

On October 26, 2006, sediment samples (SS-1, SS-2, SS-3 and SS-4) were collected from the Salmon River in four locations adjacent to and downstream from the Site (Figure 5). Kleinfelder personnel used a hand auger fitted with extensions to collect sediment samples from beneath the water level of the Salmon River. Sediment samples were placed in storage/transportation coolers, preserved with ice, and shipped under standard chain of custody procedures via Federal Express to Accutest. Each sediment sample was analyzed for the NYSDEC STARS List of VOCs and SVOCs in accordance with USEPA Methods 8260 and 8270, respectively. Pesticides, PCBs, and PP metals were analyzed in accordance with USEPA Methods 8081A, 8082, and 3050B, respectively

On June 18, 2007, sediment samples were collected from four additional locations (SS-5, SS-6, SS-7 and SS-8) depicted on Figure 5. Sediment samples were collected from near the river edge with a petit ponar dredge sampler. Sediment samples were collected into laboratory-supplied sample containers that were labeled, logged and placed into coolers containing ice, and shipped under standard chain of custody procedures via Federal Express to Lancaster. Each sediment sample was analyzed for TCL VOCs, TCL SVOCs, Pesticides, PCBs, and selected metals (arsenic, beryllium, cadmium, chromium, copper, lead, mercury, nickel and zinc).

3.8 Soil Vapor Sampling

On June 21, 2007, two stainless steel soil vapor points, SG-1 and SG-2 were installed near the eastern property margin (locations depicted on Figure 2). The six-inch vapor points were installed to a depth of 3.5 ft bgs. Clean silica sand was used to backfill around the vapor point to approximately 4-inches above the vapor point slots. Hydrated granular bentonite was used to backfill the remainder of the vapor point boring. Polyethylene tubing extended from the top of each vapor point above the ground surface to facilitate soil vapor sample collection.

On June 26, 2007, soil vapor samples were collected from SG-1 and SG-2. Two hour samples were collected into 6-liter certified clean SUMMA canisters. A flux chamber (5-gallon bucket) was placed over each soil vapor point location and sealed to the ground surface with hydrated granulated bentonite. Helium was introduced into the flux chamber through a port in the side of the chamber. The helium concentration inside the flux chamber was measured with a helium meter at the start of soil vapor sample collection, and again at the end of sampling, to confirm that the concentration remained relatively constant (i.e., to evidence that short-circuiting had not occurred that would significantly dilute sample concentrations). At SG-1 the change (percent difference) in helium concentration between the start and completion of sampling was approximately 2.5%, and at SG-2 the change in concentration was approximately 3.2%, suggesting that short-circuiting was minimal, and that soil gas samples were representative. Samples were submitted to Lancaster for TO-15 analysis.

4.0 FINDINGS AND ANALYTICAL RESULTS

This section presents SI findings and the analytical results for soil, groundwater, sediment, and soil vapor samples collected from on-site and off-site locations. The analytical program included sampling of the various matrixes for a variety of analytical parameters including VOCs, SVOCs, pesticides, PCBs and metals.

At the request of the NYSDEC and NYSDOH, the analytical samples collected during SI activities in 2007 (off-site investigation) were submitted for laboratory analysis using a lab qualified to provide analytical services protocol (ASP) Category B laboratory data deliverables. This deliverables package was requested to that the usability of collected analytical data could be validated, and data usability summary reports (DUSRs) for the collected data were subsequently prepared. The DUSRs prepared for four sample delivery groups and are presented in Appendix F. Each sample delivery group achieved the QA/QC objectives for the SI and was deemed acceptable and usable for decision making purposes.

4.1 Soil Quality Analytical Data

Analytical results for soil samples collected during the SIR are presented on Table 1 (VOCs), Table 2 (SVOCs), Table 3 (Pesticides/PCBs), and metals (Table 4). The tabulated analytical summaries present those compounds/analytes that were detected in at least one soil sample during the SI. Because the anticipated use of the Site is as a municipal park, the constituent concentrations in soils were compared to soil cleanup objectives (SCOs) for restricted residential land use as presented in 6NYCRR Part 375-6 promulgated December 14, 2006. Figure 4 presents analytical detections for constituents in soil samples that exceeded their respective restricted residential SCOs.

Volatile Organic Compounds

VOCs were detected in several of the soil samples collected from the Site during the SI. Concentrations of specific VOCs exceeding restricted residential SCOs were reported in subsurface soil samples SB-4(6-8'), SB-5B(1-2'), SB-7(4-5'), MW-2(5') and MW-3(4'). VOC exceedances were also encountered in test pit samples TP2-6', TP3-4', and in the UST Excavation area sample TT-1,000-G-FP. The VOCs exceeding SCOs were generally typical constituents of gasoline, such as benzene, toluene, ethyl benzene, and xylene (collectively BTEX). VOCs were not detected at concentrations exceeding restricted residential SCOs in surface soil samples nor in soil samples collected from off-site locations.

Semivolatile Organic Compounds

SVOCs were detected in several of the soil samples collected from the Site during the SI. Concentrations of specific SVOCs exceeding restricted residential SCOs were reported in subsurface soil samples collected from soil borings SB-3 (surface), SB-10 (surface), and SB-16 (0-2" surface sample and sample collected from depth of 3 ft bgs). The compounds detected at exceedance concentrations are polycyclic aromatic hydrocarbons (PAHs), and are typical of coal and petroleum fuel oils (diesel, fuel oil, kerosene, etc). It is noted, however, that off-site soil boring SB-16 was located in a depression most likely associated with the foundation of a small garage or outbuilding. Weathered asphalt shingles in the vicinity of the surface soil sample, while avoided during sampling, may be the source of SVOCs in SB-16.

With the exception of samples collected from SB-16, south of the Site, SVOCs were not detected at concentrations exceeding restricted residential SCOs in soil samples collected from off-site locations.

Pesticides and Polychlorinated Biphenyls

Pesticides were reported in several of the soil samples submitted for analysis (Table 3). Concentrations reported did not exceed restricted residential SCOs, and are therefore not considered a significant concern.

The PCB Aroclor 1260 was detected in soil samples collected from off-site soil borings SB-16, SB-18, SB-19 and SB-21 (Table 3). The concentrations did not exceed restricted residential SCOs and are therefore not considered a constituent of concern.

Metals

Several metals were detected in soil samples collected from on-site and off-site locations (Table 4). With the exception of lead and mercury detected in off-site soil sample SB-16 (3') that slightly exceeded their restricted residential SCOs, metals detected in soil did not exceed SCOs and therefore do not represent a significant concern at the Site.

Summary

The primary constituents of concern (those constituents at concentrations exceeding restricted-residential SCOs) at the Site are those most commonly associated with petroleum impacts. In addition, mercury and lead were identified in one sample (SB-16 (3')) at concentrations slightly exceeding SCOs. Samples with concentrations exceeding SCOs are depicted on Figure 4.

4.2 Sediment Sample Analytical Results

An investigation as to the quality of the Salmon River sediments was conducted in 2003 by The Town of Fort Covington. Atlantic Testing Laboratories, LTD. was retained to conduct sediment sampling in the Salmon River upstream and downstream of the Fort Covington Dam. The sediment investigation was conducted in support of the Town's investigation into the feasibility of partial or complete dam removal/repair. ATL's investigation report is presented as Appendix G. Three soil samples: two collected from immediately upstream of the dam, and one collected from downstream of the dam, were analyzed for VOCs, SVOCs, PCBs, RCRA metals, copper and iron. Analytical results were compared to NYSDEC Technical Guidance for Screening Contaminated Sediments (TGSCS) assuming a total organic carbon content of 2%, based on suggestions from NYSDEC representatives. VOCs, SVOCs and metals were detected in sediment samples collected from upstream and downstream locations. VOCs and metals did not exceed NYSDEC TGSCS criteria. Concentrations of several SVOCs (PAHs) including

benzo(a)anthracene, benzo(a)pyrene, benzo(b)fluoranthene, benzo(k)fluoranthene, and chrysene were detected in samples collected upstream and downstream of the dam that exceeded their respective TGSCS criteria.

Kleinfelder was retained to further investigate the results of the 2003 investigation, and collected additional samples from locations upstream of the Site, immediately adjacent to the Site, and downstream of the Site. Analytical results for samples collected by Kleinfelder are presented in Table 5 (VOCs), Table 6 (SVOCs), Table 7 (pesticides and PCBs), and Table 8 (metals). Concentrations of compounds/analytes detected were compared to NYSDEC TGSCS sediment criteria assuming a total organic carbon content of 2% as previously described.

Volatile Organic Compounds

Detectable concentrations of the VOC acetone were reported in samples collected upstream (SS-5 and SS-6) and downstream (SS-8) of the Site. Other VOCs including ethylbenzene, toluene and xylenes were detected in sample SS-8 collected from downstream of the Site (and downstream of the dam). VOC concentrations did not exceed NYSDEC TGSCS sediment criteria.

Semivolatile Organic Compounds

SVOCs were identified at detectable levels in each of the sediment samples collected for analysis (Table 6). Concentrations of compounds that included benzo(a)pyrene, benzo(b)fluoranthene, and chrysene were detected at concentrations exceeding NYSDEC TGSCS sediment criteria were in sample SS-1, collected immediately adjacent to a drainage pipe situated on the bank of the river near the southeast corner of the Site, and in sample SS-6 collected from several hundred feet upstream of the Site. The highest concentrations of SVOCs were detected in sample SS-2 collected downstream of the Site near the western bank of the river. This sampling location is adjacent to a parcel of land identified on tax maps as a highway garage. It is not known whether impacts identified in this sample, or other down-stream sediment samples (SS-3, SS-4, SS-7 and SS-8) are attributable to the Site, another source in the vicinity such as the former highway garage, or to a source sitting upstream of the Site. The presence of SVOCs in the upstream sample SS-6 indicates that an upstream source or sources have contributed some impact to Salmon River sediments.

Pesticides and PCBs

Concentrations of one or more pesticides exceeding NYSDEC TGSCS sediment criteria were reported in upstream sediment samples SS-5 and SS-6 and downstream sediment samples SS-4, SS-7 and SS-8 (see

Table 7). The PCB Aroclor 1254 was detected in downstream sediment sample SS-7 however the concentration did not exceed NYSDEC TGSCS sediment criteria.

Metals

Metals including arsenic, beryllium, cadmium, chromium, copper, lead, mercury, nickel and zinc were detected in each of the sediment samples analyzed (Table 8). Concentrations of various metals exceeding NYSDEC TGSCS criteria were detected in downstream samples SS-1, SS-2 and SS-4. In general, the metals concentrations detected slightly exceeded the lowest effect level (LEL) criteria (comparable to a chronic toxicity value) but did not exceed the severe effect level (SEL) criteria (comparable to acute toxicity value).

Summary

The constituents of potential concern identified in sediment samples include SVOCs, pesticides and select metals. SVOCs and pesticide exceedances were detected in sediment samples collected from locations upstream and downstream of the Site suggesting that the Site is not the source of these impacts. Metals exceeding sediment criteria were detected in three of the eight samples analyzed. The data are insufficient to state with certainty whether the metals identified in the sediment samples are the result of on-site impacts, are at background concentrations, or are the result of impact from other potential sources (highway garage property east of Site).

4.3 Groundwater Investigation Results

4.3.1 Groundwater Gauging

Monitoring wells were gauged for depth to groundwater on October 26, 2006, January 22, 2007, June 19, 2007, June 29, 2007 and September 21, 2007. The gauging data collected during these events are presented in Table 9. The data were used to generate potentiometric surface maps for October 2006, January 2007, June 2007 and September 2007, provided as Figure 6, Figure 7, Figure 8 and Figure 9, respectively. Groundwater flow at the Site appears to be variable over time, and appears to range from northwestward to southeastward depending on the time of year, and location on or around the Site.

The potentiometric surface map for October 26, 2007 (Figure 6) depicts a hydraulic divide traversing the site between monitoring wells MW-2 and MW-5. Groundwater north of these wells appears to flow toward the northwest while groundwater south of the divide appears to flow toward the southeast. The gradient at the Site is approximately 0.004 ft/ft.

The interpretation presented on potentiometric surface map for January 2007 (Figure 7), depicts a broad groundwater divide similar to that presented for October 2006. Groundwater in the northern portion of the Site appears to flow toward the northwest, while groundwater in the south of the Site appears to flow toward the south/southeast. The groundwater gradient appears to be approximately 0.0357 feet per foot (ft/ft).

The interpretation presented on Figure 8 for June 2007 depicts groundwater flow to the east-southeast with a gradient of approximately 0.01 ft/ft.

The potentiometric surface map presented as Figure 9 for September 2007 in general depicts groundwater flow toward the north-northwest. Local flow variability ranges from northwestward to northeast and the gradient in the central portion of the Site is approximately 0.002 ft/ft.

Based on the potentiometric surface interpretations presented in Figures 6 though 9, the direction of groundwater flow appears to vary widely over time and location on the Site. The groundwater gradients observed during the multiple gauging events ranged from approximately 0.003 ft/ft to greater than 0.357 ft/ft. Assuming an average hydraulic conductivity of 1.88 ft/day (as described previously), the velocity of groundwater flow appears to range from approximately 0.006 ft/day to 0.07 ft/day.

4.3.2 Groundwater Analytical Results

As stated previously, monitoring wells MW-1 through MW-6 (on-site) were gauged and sampled on October 26, 2006 and January 22, 2007. Off-site monitoring wells MW-7, MW-8 and MW-9 were sampled on June 25, 2007, and a grab groundwater sample was collected from SB-14 on June 19, 2007. Analytical results for groundwater samples are summarized in Table 10 (VOCs), Table 11 (SVOCs), Table 12 (Pesticides and PCBs), and metals (Table 13), and analytical parameters exceeding groundwater quality criteria are presented on Figure 10.

Volatile Organic Compounds

One or more VOCs were detected in groundwater samples collected from on-site and off-site monitoring wells. In order to evaluate the level of impact to groundwater at a given location, groundwater sample analytical results were compared to water quality standards (WQS) presented in the NYSDEC's Division of Water Technical and Operational Guidance Series (1.1.1), (TOGS 1.1.1) Ambient Water Quality Standards and Guidance Values and Groundwater Effluent Limitations, dated June 1998.

VOCs were detected at concentrations exceeding WQS in samples collected from on-site monitoring wells MW-3, MW-4 and MW-5 (Table 10). The constituents detected were typical of gasoline and /or fuel oil impacts and included BTEX compounds and methyl tert butyl ether (MTBE). Concentrations of select VOCs were also detected in groundwater samples collected from on-site wells MW-1, MW-2 and MW-6 and off-site monitoring wells MW-7 and MW-8, however the concentrations of these compounds were well below NYSDEC WQS. Constituents present in groundwater that exceed WQS are depicted on Figure 10.

Semivolatile Organic Compounds

Naphthalene was the only SVOC detected in groundwater samples collected during the investigation (Table 11). Concentrations of naphthalene exceeding the NYSDEC WQS were detected in samples collected from on –site monitoring wells MW-3, MW-4 and MW-5. SVOCs were not detected in other on-site or off-site monitoring wells. Constituents present in groundwater that exceed WQS are depicted on Figure 10.

Pesticides and PCBs

The pesticides gamma-BHC and Endosulfan-II were detected at low estimated concentrations in the groundwater sample collected from off-site monitoring well MW-8 (Table 12). These constituents were reported at estimated (j-qualified) concentrations, below the quantitation limits, and did not exceed WQS. Pesticides and PCBs were not detected in other groundwater samples collected from on-site or off-site monitoring wells.

Metals

Metals were detected in groundwater samples collected from each of the on-site and off-site monitoring wells. Concentrations of chromium and lead, exceeding their respective WQS were detected in initial (October 2006) samples collected from monitoring wells MW-1, MW-3 and MW-4. Samples collected during the subsequent (January 2007) sampling event did not contain concentrations of these or other metals at levels exceeding WQS (Table 13).

Summary

Groundwater impacts have been identified only in on-site monitoring wells. The primary constituents of concern identified in groundwater at the Site are VOCs and to a lesser extent SVOCs (naphthalene). Groundwater impact appears to be most severe in the vicinity of wells MW-3, MW-4 and MW-5.

Pesticides and PCBs were not detected in groundwater samples at concentrations exceeding NYSDEC WQS. Lead and chromium were detected at exceedance concentrations during initial groundwater sampling event in October 2006, however concentrations of these metals detected in samples collected during the January 2007 sampling event did not exceed NYSDEC WQS.

4.4 Soil Vapor Sampling on Eastern Property Margin

Analytical results for the two soil gas samples and one ambient air sample collected from the eastern property margin are presented in Table 14 and depicted on Figure 11. The results of the soil gas investigation identified detectable concentrations of multiple VOCs including petroleum-related compounds (toluene, ethylbenzene, toluene xylenes, etc.) as well as other compounds commonly used as dry-cleaning or plastic solvents (tetrachloroethene, 2-butanine). While there is no way to directly correlate VOC vapors in soil to that which may accumulate inside a structure, the presence of these compounds indicates a potential for vapor intrusion.

Because the dwelling is abandoned and condemned, exposure to any occupants is not a concern at this time. However, if the dwelling is to be refurbished for future occupancy, installation of a soil vapor barrier and/or a sub-slab vapor extraction system may be necessary.

5.0 CONCLUSIONS AND RECOMMENDATIONS

5.1 Conclusions

On behalf of The Town of Fort Covington, Kleinfelder has completed a Site Investigation (SI) at the Former Martin's Gulf Station (Site), located at the southeast corner of the intersection of Chateaugay Street and Salmon Street in Fort Covington, New York (Environmental Restoration Program No. E-517006).

The purpose of the SI was to characterize the subsurface geology and hydrogeology of the Site, and determine the nature and extent of any impacts to soil or groundwater from historical operations.

Based on information gathered during the site investigation, the unconsolidated subsurface materials consist of approximately 2 to 5 feet of sand at the surface overlying approximately 5 to 10+ feet of silt and clay. The silt and clay overlies sand and a sand and gravel unit, the depth of which is not known. The depth to bedrock in the area is not known as it was not encountered during SI activities. According

to documents reviewed pertaining to the vicinity, the depth to bedrock is generally expected to be 30 to 50 ft bgs.

Information gathered during several rounds of groundwater gauging suggests that groundwater flow at the Site is variable, and ranges from north-northwestward to southeastward. In general, groundwater flow appears to be toward the Salmon River. Slug testing was conducted at two on-site monitoring wells to evaluate hydraulic conductivity of the aquifer. The mean hydraulic conductivity for the aquifer underlying the Site was estimated to be 1.88 ft/day.

The site investigation was performed in several stages from April 2006 through September 2007 and included the cleaning and removal of two underground storage tanks formerly used to store gasoline, collection of soil samples from approximately 40 on-site and off-site locations, installation and sampling of six on-site and nine off-site monitoring wells, and the collection and analysis of eight sediment samples from the Salmon River in the vicinity of the subject Site. Four test pits were also dug at the Site to determine the cause of refusal for several borings and resolve a subsurface anomaly in this same area. Other activities performed at the Site included an evaluation of the Site building for the presence of asbestos containing materials in support of the eventual demolition of the Site building by the Town of Fort Covington, and the collection of soil gas samples from the eastern property boundary, adjacent to a condemned and abandoned residential property. The analytical program included volatile organic compounds, semivolatile organic compounds, metals, pesticides and PCBs.

The results of the investigation revealed the presence of volatile and semi-volatile organic compounds and certain metals present above SCO's in on-site soils and above water quality standards and guidance values in groundwater. The impacts were primarily identified within the boundaries of the Site, but may extend beyond property lines beneath Chateaugay Street to the north and/or Salmon Street to the west. Generally, site related impacts were not identified at off-site sampling locations. Test pits that were dug at the site, encountered impacted soils, and identified buried concrete/construction debris on the Site's northern margin. One of the test pits was designated to investigate a geophysical anomaly, however upon excavation, an anomaly could not be confirmed. Samples collected from the Salmon River upriver, adjacent to, and downriver of the subject Site indicate the presence of various compounds also present in Site soils and groundwater; however, the presence of other isolated organic and inorganic constituents suggests a separate source of contamination in the river. Results of the soil gas survey indicate the potential for vapor intrusion to structures overlying or near impacted areas.

5.2 Recommendations

Based on sampling and analysis conducted during the SI, the primary concerns at the Site appear to be limited to the confines of the Site. On-site soils in the northern central portion of the Site are impacted with VOCs and to a lesser extent SVOCs, and appear to be the result of the Site's historical usage as a gasoline sales and service station.

Groundwater at the Site has been impacted by VOCs, and to a lesser extent SVOCs (naphthalene) and metals (chromium and lead). The VOCs and SVOCs also appear to be the result of historical operations at the Site. The chromium and lead concentrations detected in groundwater samples during an initial event suggest that their presence in groundwater may be due to suspended solids present in the groundwater, and therefore may be representative of the aquifer materials rather than as a constituent of groundwater.

In order to address contamination identified at the Site, Kleinfelder is recommending that an Interim Remedial Measure be conducted. The IRM work plan is included as Appendix H. The IRM would consist of excavation and off-site disposal of impacted soil from the Site. The area of proposed remediation is depicted on Figure 12 and measures approximately 50 feet by 45 feet to a total depth of approximately 8 ft bgs. The excavation will remove the majority of petroleum impacts at the Site. The actual dimensions of excavation will depend on field screening of soils during excavation and on the depth to groundwater. Impact remaining below the limits of excavation, or beyond the property boundaries (i.e., under Chateaugay or Salmon Streets) will be assessed through post-excavation sampling. Remedial alternatives for addressing potential remaining impacts to soil and/or groundwater will be evaluated when the post-excavation data are available.

6.0 STATEMENT OF LIMITATIONS

This report may be used only by the client and only for the purposes stated, within a reasonable time from its issuance, but in no event later than three years from the date of the report. Land and facility use, on and off-site conditions, regulations or other factors may change over time, and additional work may be required with the passage of time. Based on the intended use of this report, Kleinfelder may require that additional work be performed and that an updated report be issued. Non-compliance with any of these requirements by the client or anyone else will release Kleinfelder from any liability resulting from the use of this report by any unauthorized party and client agrees to defend, indemnify, and hold harmless Kleinfelder from any claim of liability associated with such unauthorized use or non-compliance.

7.0 REFERENCES

- Kleinfelder East, Inc., Subsurface Investigation Workplan (SIWP), October 5, 2004
- New York State Department of Environmental Conservation, Recommended Soil Cleanup Objectives for Gasoline Contaminated and Fuel Oil Contaminated Soils, August 22, 2001.
- New York State Department of Environmental Conservation, Division of Water Technical and Operational Guidance Series (1.1.1) Ambient Water Quality Standards and Guidance Values, June 1998 (Addendum June 2000).
- New York State Department of Environmental Conservation, Part 703, Surface Water and Groundwater Quality Standards and Groundwater Effluent Limitations.
- New York State Museum, Landforms and Bedrock Geology of New York State, James F. Davis, 1973
- New York State Museum, Geology of New York A Simplified Account, Isachsen Et.Al, 2000
- Roadside Geology of New York, Bradford B.Van Diver, Mountain Press Publishing, New York, July 2001.
- United States Geological Survey (USGS) 7.5 Minute Series Topographic Map Fort Covington, NY-Quebec Quadrangle.
- New York State Geological Survey, Surficial Geologic Map of New York Adirondack Sheet. Compiled by D. H. Cadwell et. al, 1991.

TABLES

SOIL ANALYTICAL DATA - VOLATILE ORGANIC COMPOUNDS Table 1

Chateaugay and Salmon Street Former Martin's Gulf Station Fort Covington, New York

Location		STIR_1	CTID 1	erm 3	6 0.3	,	9 9
WORKSON THE STREET		2017-1	30N-2	SUK-3	7-9C	2B-3	SB-3
Parameter	NYSDEC SCO	SUR-1(0-2")	SUR-2(0-2")	SUR-3(0-2")	SB-2 (6-8')	SB-3 SURFACE	SB-3 (4-6')
Sample Date		6/18/2007	6/18/2007	6/18/2007	4/11/2006	4/11/2006	4/11/2006
Acetone	100	<0.008	<0.007	<0.009	NA	NA	NA
Benzene	4.8	0.0007	<0.0005	<0.0007	<0.0015	<0.0013	<0.076
2-Butanone (MEK)	100	<0.004	<0.004	<0.005	NA	NA	NA
n-Butylbenzene	NGN	NA	NA	NA	<0.0073	<0.0067	<0.38
sec-Butylbenzene	100	NA .	NA	NA	<0.0073	<0.0067	0.616
Ethylbenzene	41	0.003 J	0.002 J	0.006 J	<0.0015	<0.0013	2.68
Isopropylbenzene	NGN	NA	NA	NA	<0.0073	-29000>	0.838
p-Isopropyltoluene	NGV	NA	NA	NA	<0.0073	<0.0067	0.530
Methyl Tert Butyl Ether	100	NA	NA	NA	<0.0015	<0.0013	<0.076
Methylene chloride	100	<0.002	<0.002	<0.003	NA	NA	NA
Naphthalene	100	NA	NA	NA	<0.0073	<0.0067	6.78
n-Propylbenzene	100	NA	NA	NA	<0.0073	<0.0067	3.73
Toluene	100	0.021	0.011	0.01	<0.0015	<0.0013	<0.076
1,2,4-Trimethylbenzene	52	NA	NA	NA	<0.0073	<0.0067	42.7
1,3,5-Trimethylbenzene	52	NA	NA	NA	<0.0073	<0.0067	15.3
m,p-Xylene	ASN	NA	NA	NA	<0.0029	<0.0027	8.18
o-Xylene	ASN	NA	NA	NA	<0.0015	<0.0013	3.35
Xylene (total)	100	0.016	0.014	0.044	<0.0029	<0.0027	11.5

All concentrations are presented in milligrams per kilogram (mg/kg) Xylene (total) - Sum of m, p-xylenes and o-xylenes

NA - Not analyzed

NGV - No guidance value

J - Laboratory estimated value

All soil samples analyzed in accordance with United States Environmental Protection Agency Method 8260B for volatile organic compounds and Method 8270C for semivolatile organic compounds NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for

restricted residential land use per 6NYCRR Part 375-6 Effective December 14, 2006 Shaded - Value exceeds NYSDEC SCOs

Chateaugay and Salmon Street Former Martin's Gulf Station Fort Covington, New York

Location		SB-4	SB-5B	SB-7	SB-9	SB-9	SB-10
Parameter	NYSDEC SCO	SB-4 (6-8')	SB-5B (1-2')	SB-7 (4-5¹)	SB-9 SURFACE	SB-9 (6-8')	SB-10 SURFACE
Sample Date		4/11/2006	4/12/2006	4/12/2006	4/12/2006	4/12/2006	4/12/2006
Acetone	100	NA	NA	NA	NA	NA	NA
Benzene	4.8	0.248	21.0	2.03	<0.0012	<0.0016	<0.0011
2-Butanone (MEK)	100	NA	NA	NA	NA	NA	NA
n-Butylbenzene	NGN	<0.48	18.2	<4.0	<0.0062	<0.0081	<0,0054
sec-Butylbenzene	100	1.34	6.56	J. 06.1	<0.0062	<0.0081	<0.0054
Ethylbenzene	41	26.0	158	30.3	<0.0012	<0.0016	<0.0011
Isopropylbenzene	NGV	3.71	16.0	4.38	<0.0062	<0.0081	<0.0054
p-Isopropyltoluene	NGV	0.838	3.67 J	1.40 J	<0.0062	<0.0081	<0.0054
Methyl Tert Butyl Ether	100	<0.096	<0.83	08.0>	<0.0012	<0.0016	<0.0011
Methylene chloride	100	NA	NA	NA	NA	NA	NA
Naphthalene	100	14.3	63.7	20.8	<0.0062	<0.0081	<0.0054
n-Propylbenzene	100	14.4	66.5	16.6	<0.0062	<0.0081	<0.0054
Toluene	100	22.0	323	2.92	<0.0012	<0.0016	0.0011
1,2,4-Trimethylbenzene	52	93.0	329	150	<0.0062	<0.0081	<0.0054
1,3,5-Trimethylbenzene	52	28.7	139	52.5	<0.0062	<0.0081	<0.0054
m,p-Xylene	NGV	98.2	439	142	<0.0025	<0.0032	<0.0022
o-Xylene	NGV	42.3	179	39.1	<0.0012	<0.0016	<0.0011
Xylene (total)	100	140	618	181	<0.0025	<0.0032	<0.0022

All concentrations are presented in milligrams per kilogram (mg/kg)

Xylene (total) - Sum of m, p-xylenes and o-xylenes NA - Not analyzed

NGV - No guidance value

J - Laboratory estimated value

All soil samples analyzed in accordance with United States Environmental Protection Agency Method 8260B for volatile organic compounds and Method 8270C for semivolatile organic compounds

NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for restricted residential land use per 6NYCRR Part 375-6 Effective December 14, 2006
Shaded - Value exceeds NYSDEC SCOs

Chateaugay and Salmon Street Former Martin's Gulf Station Fort Covington, New York

Location		SB-10	SB-11	SB-11	SB-12	SB-13	SB-13A
Parameter	NYSDEC SCO	SB-10 (10-12')	SB-11 SURFACE	SB-11 (2-4')	SB-12 (8-10')	SB-13 (6-8')	SB-13A(0-2")
Sample Date		4/12/2006	4/12/2006	4/12/2006	4/11/2006	4/11/2006	6/18/2007
Acetone	100	NA	NA	NA	NA	NA	200.0>
Benzene	4.8	<0.0016	<0.0013	f 990000	<0.0019	0.0013	>0000
2-Butanone (MEK)	100	NA	NA	NA	NA		<0.004
n-Butylbenzene	NGV	<0.0079	<0.0065	<0.0065	>0.0096	<0.0079	NA
sec-Butylbenzene	100	<0.0079	<0.0065	<0.0065	>0.0096	0.0168	NA
Ethylbenzene	41	<0.0016	<0.0013	<0.0013	<0.0019	0.0014	0.002
Isopropylbenzene	NGV	<0.0079	<0.0065	<0.0065	<0.0096	0.0113	NA
p-Isopropyltoluene	NGV	<0.0079	<0.0065	<0.0065	<0.0096	<0.0079	NA
Methyl Tert Butyl Ether	100	<0.0016	<0.0013	<0.0013	<0.0019	0.0016	NA
Methylene chloride	100	NA	NA	NA	NA	NA	<0.002
Naphthalene	100	<0.0079	<0.0065	<0.0065	>0.0096	<0.0079	NA
n-Propylbenzene	100	<0.0079	<0.0065	<0.0065	>0.0096	0.0175	NA
Toluene	100	0.00087 J	<0.0013	0.0016	<0.0019	0.0013 J	0.007
1,2,4-1 rimethylbenzene	52	<0.0079	<0.0065	<0.0065	>0.0096	0.163	NA
1,3,5-Trimethylbenzene	52	<0.0079	<0.0065	<0.0065	>0.0096	0.0890	NA
m,p-Xylene	NGV	<0.0032	<0.0026	<0.0026	<0.0038	0.0233	NA
o-Xylene	NGV	<0.0016	<0.0013	<0.0013	<0.0019	0.003	NA
Xylene (total)	100	<0.0032	<0.0026	<0.0026	<0.0038	0.0261	0.014

All concentrations are presented in milligrams per kilogram (mg/kg)

Xylene (total) - Sum of m, p-xylenes and o-xylenes

NA - Not analyzed

NGV - No guidance value

J - Laboratory estimated value
All soil samples analyzed in accordance with United States Environmental Protection Agency Method 8260B
for volatile organic compounds and Method 8270C for semivolatile organic compounds

NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for restricted residential land use per 6NYCRR Part 375-6 Effective December 14, 2006

Shaded - Value exceeds NYSDEC SCOs

Chateaugay and Salmon Street Former Martin's Gulf Station Fort Covington, New York

Parameter NYSD Sample Date Acetone Benzene 2-Butanone (MEK)	NYSDEC SCO						
Sample Date		SB-13A(4')	SB-14 (4')	SB-15 (4')	SB-16 (0-2")	SB-16 (3')	SB-17 (4')
ne (MEK)		6/20/2007	6/19/2007	6/19/2007	6/18/2007	6/19/2007	6/20/2007
ne (MEK)	100	0.014 J	<0.01	0.17	<0.008	<0.009	0.00
	4.8	<0.0007	<0.0007	U.0000	0.0000 J	0.002 J	Ľ
	100	<0.005	<0.006	0.023	<0.005	<0.005	<0.005
n-Butylbenzene	NGV	NA	NA	NA	NA	NA	NA
sec-Butylbenzene	100	NA	NA	NA	NA	NA	NA
Ethylbenzene	41	<0.001	<0.001	0.001	0.001 J	0.006 J	<0.001
Isopropylbenzene	NGV	NA	NA	NA	NA	NA	NA
p-Isopropyltoluene	NGV	NA	NA	NA	NA	NA	NA
Methyl Tert Butyl Ether	100	NA	NA	NA	NA	NA	NA
Methylene chloride	100	0.007	<0.003	<0.003	0.002 J	0.012	9000
Naphthalene	100	NA	NA	NA	NA	NA	NA
n-Propylbenzene	100	NA	NA	NA	NA	NA	NA
Toluene	100	0.006 J	0.012	0.017	0.018	0.052	0.01
1,2,4-Trimethylbenzene	52	NA	NA	NA	NA	NA	NA
1,3,5-Trimethylbenzene	52	NA	NA	NA	NA	NA	NA
m,p-Xylene	NGV	NA ·	NA	NA	NA	NA	NA
o-Xylene N	NGV	NA	NA	NA	NA	NA	NA
Xylene (total)	100	0.002 J	0.004 J	0.008	0.013	0.036	0.003

All concentrations are presented in milligrams per kilogram (mg/kg)

Xylene (total) - Sum of m, p-xylenes and o-xylenes NA - Not analyzed

NGV - No guidance value

J - Laboratory estimated value

All soil samples analyzed in accordance with United States Environmental Protection Agency Method 8260B for volatile organic compounds and Method 8270C for semivolatile organic compounds

NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for restricted residential land use per 6NYCRR Part 375-6 Effective December 14, 2006

Shaded - Value exceeds NYSDEC SCOs

Syracuse, New York

Chateaugay and Salmon Street Former Martin's Gulf Station Fort Covington, New York

Location		SB-18	SB-19	SB-20	SB-20	SB-21	MW-1
Parameter	NYSDEC SCO	SB-18 (4')	SB-19 (4')	SB-20 (4')	SB-201 (4')*	SB-21 (4')	MW1(4')
Sample Date		6/29/2007	6/29/2007	6/20/2007	6/20/2007	6/29/2007	10/10/2006
Acetone	100	0.016 J	600.0>	0.01 J	f 600.0	0.011 J	NA
Benzene	4.8	<0.0006	>0.0006	<0.0006	f 20000	<0.0006	<0.0038
2-Butanone (MEK)	100	<0.005	<0.005	<0.005	<0.005	<0.005	NA
n-Butylbenzene	NGV	NA	NA	NA	NA	NA	<0.019
sec-Butylbenzene	100	NA	NA	NA	NA	NA	0.0051
Ethylbenzene	41	<0.001	<0.001	<0.001	<0.001	<0.001	0.0161
Isopropylbenzene	NGV	NA	NA	NA	NA	NA	0.0070
p-Isopropyltoluene	NGV	NA	NA	NA	NA	NA	<0.019
Methyl Tert Butyl Ether	100	NA	NA	NA	NA	NA	0.0170
Methylene chloride	100	0.004 J	0.026	<0.003	0.014	0.01	NA
Naphthalene	100	NA	NA	NA	NA	NA	0.0829
n-Propylbenzene	100	NA	NA	NA	NA	NA	0.0231
Toluene	100	<0.001	<0.001	0.002 J	0.012	<0.001	0.0210
1,2,4-Trimethylbenzene	52	NA	NA	NA	NA	NA	0.0306
1,3,5-Trimethylbenzene	52	NA	NA	NA	NA	NA	9660.0
m,p-Xylene	NGV	NA	NA	NA	NA	NA	0.198
o-Xylene	NGV	NA	NA	NA	NA	NA	0.159
Xylene (total)	100	<0.001	<0.001	<0.001	0.004 J	<0.001	0.357

All concentrations are presented in milligrams per kilogram (mg/kg)

Xylene (total) - Sum of m, p-xylenes and o-xylenes NA - Not analyzed

NGV - No guidance value

J - Laboratory estimated value

All soil samples analyzed in accordance with United States Environmental Protection Agency Method 8260B for volatile organic compounds and Method 8270C for semivolatile organic compounds

NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for restricted residential land use per 6NYCRR Part 375-6 Effective December 14, 2006 Shaded - Value exceeds NYSDEC SCOs

SB-201 (4') is duplicate of SB-20(4')

Chateaugay and Salmon Street Former Martin's Gulf Station Fort Covington, New York

Location		7-MW	MW-3	MW-4	MW-5	9-MW	UST Area
Parameter	NYSDEC SCO	MW2(5')	MW3(4')	MW4(3')	MW5(5')	MW6(5')	UST-SURFACE
Sample Date		10/10/2006	10/10/2006	10/10/2006	10/10/2006	10/11/2006	8/15/2006
Acetone	100	NA	NA	NA	NA	NA	NA
Benzene	4.8	39.7	5.11	0.0851	0.223	0.00640	0.00082 J
2-Butanone (MEK)	100	NA	NA	NA	NA	NA	NA
n-Butylbenzene	NGV	<20	32.1	1.38	3.060	<0.0070	<0.0052
sec-Butylbenzene	100	<20	9.17 J	0.280	f 092.0	<0.0070	0.0017 J
Ethylbenzene	41	106	152	2.98	6.12	0.0276	0.00062 J
Isopropylbenzene	NGV	11 J	25.3	0.701	1.42	0.00220 J	<0.0052
p-Isopropyltoluene	NGV	<20	4.47 J	J 20100	0.519 J	<0.0070	<0.0052
Methyl Tert Butyl Ether	100	22.7	<3.6	0.0136	<0.160	0.00150	<0.0010
Methylene chloride	100	NA	NA	NA	NA	NA	NA
Naphthalene	100	20	9.78	3.35	5.89	<0.0070	0.010
n-Propylbenzene	100	37.3	71.2	2.67	4.15	0.00490 J	0.0029 J
Toluene	100	360	273	2.83	8.23	0.0879	0.002
1,2,4-Trimethylbenzene	52	294	929	15.1	35.8	0.00820	0.0376
1,3,5-Trimethylbenzene	52	99	191	5.65	12.1	0.0170	0.0287
m,p-Xylene	NGV	460	604	6.26	18.5	0.0383	0.005
o-Xylene	NGV	236	248	4.38	6.53	0.0628	0.005
Xylene (total)	100	969	852	12.2	25.0	0.101	0.01

All concentrations are presented in milligrams per kilogram (mg/kg)

Xylene (total) - Sum of m, p-xylenes and o-xylenes

NA - Not analyzed

J - Laboratory estimated value NGV - No guidance value

All soil samples analyzed in accordance with United States Environmental Protection Agency Method 8260B for volatile organic compounds and Method 8270C for semivolatile organic compounds

NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for restricted residential land use per 6NYCRR Part 375-6 Effective December 14, 2006

Shaded - Value exceeds NYSDEC SCOs

Syracuse, New York

Chateaugay and Salmon Street Former Martin's Gulf Station Fort Covington, New York

Location		SW-N	TP-1	TP-2	TP-3	TP-4	Tank Excavation Area
Parameter	NYSDEC SCO	.9-N-MS	TP1-6'	TP2-6'	TP3-4'	TP4-6'	TT-1,000-G-FP
Sample Date		8/15/2006	8/15/2006	8/15/2006	8/15/2006	8/15/2006	8/15/2006
Acetone	100	<1.7	0.325 J	31	<40	<0.014	<72
Benzene	4.8	<0.17	<0.072	53.4	18.1	<0.0014	<0.0072
2-Butanone (MEK)	100	<1.7	<0.72	<31	<40	<0.014	<72
n-Butylbenzene	NGV	1.05	1.89	14.3 J	14.2 J	<0.0068	25.4 J
sec-Butylbenzene	100	0.413 J	0.619	4.82 J	5.29 J	<0.0068	T. 6.11
Ethylbenzene	41	2.05	1.24	158	146	<0.0014	70.7
Isopropylbenzene	NGV	0.641 J	0.842	14.2 J	<20	<0.0068	25.3 J
p-Isopropyltoluene	NGV	0.288 J	0.432	3.10 J	<20	<0.0068	f 62.9
Methyl Tert Butyl Ether	100	<0.17	<0.072	<3.1	<20	<0.0014	<0.0072
Methylene chloride	100	<0.83	<0.36	<16	<20	<0.0068	<36
Naphthalene	100	5.04	8.27	62.2	54.7	<0.0068	124
n-Propylbenzene	100	1.97	3.16	56.0	51.9	<0.0068	67.7
Toluene	100	2.32	0.0714 J	532	474	0.00076	92.1
1,2,4-Trimethylbenzene	52	29.6	34.5	419	401	<0.0068	805
1,3,5-Trimethylbenzene	52	9.70	12.6	124	125	0.0102	229
m,p-Xylene	NGV	17.9	13.4	692	029	<0.0027	505
o-Xylene	NGV	8.48	4.41	265	243	<0.0014	258
Xylene (total)	100	26.4	17.8	957	913	<0.0027	763

All concentrations are presented in milligrams per kilogram (mg/kg) Xylene (total) - Sum of m, p-xylenes and o-xylenes

NA - Not analyzed

NGV - No guidance value

J - Laboratory estimated value

All soil samples analyzed in accordance with United States Environmental Protection Agency Method 8260B for volatile organic compounds and Method 8270C for semivolatile organic compounds NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for

restricted residential land use per 6NYCRR Part 375-6 Effective December 14, 2006 Shaded - Value exceeds NYSDEC SCOs

Table 2 SOIL ANALYTICAL DATA - SEMIVOLATILE ORGANIC COMPOUNDS

Former Martin's Gulf Station Chateaugay and Salmon Street Fort Covington, New York

Location		SUR-1	SUR-2	SUR-3	SB-2	SB-3	SB-3	SB-4
Parameter	NYSDEC SCO	SUR-1(0-2")	SUR-2(0-2")	SUR-3(0-2")	SB-2 (6-8')	SB-3 SURFACE	SB-3 (4-6')	SB-4 (6-8')
Sample Date		6/18/2007	6/18/2007	6/18/2007	4/11/2006	4/11/2006	4/11/2006	4/11/2006
Acenaphthene	100	<0.18	<0.034	<0.044	<0.0810	0.0228 J	<0.083	<0.097
Acenaphthylene	100	а	<0.034	<0.044	NA	NA	NA	NA
Anthracene	100	<0.18	<0.034	<0.044	<0.0810	0.358	0.0292 J	<0.097
Benzo(a)anthracene	1	0.3 J	<0.034	<0.044	<0.0810	0.924	0.123	<0.097
Benzo(a)pyrene	-	0.37 J	<0.034	0.045 J	<0.0810	0.883	0.143	<0.097
Benzo(b)fluoranthene	-	0.5 J	<0.034	0.057 J	<0.0810	1.07	0.197	<0.097
Benzo(g,h,i)perylene	100	0.28 J	<0.034	<0.044	<0.0810	0.624	0.105	<0.097
Benzo(k)fluoranthene	3.9	<0.18	<0.034	<0.044	<0.0810	0.387	f 8790.0	<0.097
Carbazole	NGV	<0.18	<0.034	<0.044	NA	NA	NA	NA
Chrysene	3.9	0.37 J	<0.034	0.047 J	<0.0810	0.958	0.144	<0.097
Dibenzo(a,h)anthracene	0.33	<0.18	<0.034	<0.044	<0.0810	<0.087	0.0225 J	<0.097
Di-n-butyl phthalate	NGV	<0.36	<0.069	<0.089	NA	NA	NA	NA
bis(2-Ethylhexyl)phthalate	NGV	<0.36	<0.069	<0.089	NA	NA	NA	NA
Fluoranthene	100	0.64 J	<0.034	0.064 J	<0.0810	1.35	0.283	<0.097
Fluorene	100	<0.18	<0.034	<0.044	<0.0810	0.0297 J	0.0199 J	<0.097
Indeno(1,2,3-cd)pyrene	0.5	0.26 J	<0.034	<0.044	<0.0810	0.727	0.122	<0.097
2-Methylnaphthalene	NGV	<0.18	<0.034	<0.044	NA	NA	NA	NA
Naphthalene	100	<0.18	<0.034	<0.044	<0.0810	0.0332 J	0.301	0.250
Phenanthrene	100	0.31 J	<0.034	<0.044	<0.0810	0.375	0.221	<0.097
Pyrene	100	0.53 J	<0.034	0.07	<0.0810	1.46	0.279	<0.097

Notes:

All concentrations are presented in milligrams per kilogram (mg/kg)

NA - Not analyzed

NGV - No guidance value

J - Laboratory estimated value

All soil samples analyzed in accordance with United States Environmental Protection Agency Method 8260B for volatile organic compounds and Method 8270C for semivolatile organic compounds

for volatile organic compounds and Method 8270C for semivolatile organic compounds NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for restricted residential land use per 6NYCRR Part 375-6 Effective December 14, 2006

Shaded - Value exceeds NYSDEC SCOs

Chateaugay and Salmon Street Former Martin's Gulf Station Fort Covington, New York

Location		SB-5B	SB-7	SB-9	SB-9	SB-10	SB-10	SB-11
Parameter	NYSDEC SCO	SB-5B (1-2')	SB-7 (4-5')	SB-9 SURFACE	SB-9 (6-8')	SB-10 SURFACE	SB-10 (10-12')	SB-11 SURFACE
Sample Date		4/12/2006	4/12/2006	4/12/2006	4/12/2006	4/12/2006	4/12/2006	4/12/2006
Acenaphthene	100	<0.088	0.0390 J	620.0>	<0.090	<0.071	<0.094	<0.081
Acenaphthylene	100	NA	NA	NA	NA	NA	NA	NA
Anthracene	100	0.0524 J	0.0539 J	t 60500 J	<0.090	0.154	<0.094	0.0433 J
Benzo(a)anthracene		<0.088	0.0772 J	1 0.268	<0.090	0.671	<0.094	0.209
Benzo(a)pyrene	-	<0.088	0.0773	0.290	<0.090	0.73	<0.094	0.219
Benzo(b)fluoranthene	-	<0.088	0.0877	0.382	<0.090	0.951	<0.094	0.282
Benzo(g,h,i)perylene	100	<0.088	<0.0086	0.202	<0.090	0.475	<0.094	0.155
Benzo(k)fluoranthene	3.9	<0.088	0.0448 J	0.148	<0.090	0.331	<0.094	0.120
Carbazole	NGV	NA	NA	NA	NA	NA	NA	NA
Chrysene	3.9	<0.088	0.0859 J	0.277	<0.090	0.687	<0.094	0.214
Dibenzo(a,h)anthracene	0.33	<0.088	<0.0086	f 6850.0	<0.090	0.149	<0.094	0.0513 J
Di-n-butyl phthalate	NGV	NA	NA	NA	NA	NA	NA	NA
bis(2-Ethylhexyl)phthalate	NGV	NA	NA	NA	NA	NA	NA	NA
Fluoranthene	100	0.0313 J	0.0745 J	0.356	<0.090	0.956	<0.094	0.344
Fluorene	100	0.199	0.0630 J	r <0.079	<0.090	0.0295 J	<0.094	<0.081
Indeno(1,2,3-cd)pyrene	0.5	<0.088	<0.0086	0.242	<0.090	0.577	<0.094	0.178
2-Methylnaphthalene	NGV	NA	NA	NA	NA	NA	NA	NA
Naphthalene	100	26.6	2.65	<0.079	<0.090	<0.071	<0.094	<0.081
Phenanthrene	100	0.283	0.105	0.107	<0.090	0.355	<0.094	0.152
Pyrene	100	0.0609 J	0.103	0.424	<0.090	1.09	<0.094	0.392

All concentrations are presented in milligrams per kilogram (mg/kg)

NA - Not analyzed

NGV - No guidance value

J - Laboratory estimated value

All soil samples analyzed in accordance with United States Environmental Protection Agency Method 8260B for volatile organic compounds and Method 8270C for semivolatile organic compounds

NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for restricted residential land use per 6NYCRR Part 375-6 Effective December 14, 2006

Shaded - Value exceeds NYSDEC SCOs

Chateaugay and Salmon Street Former Martin's Gulf Station Fort Covington, New York

Location		SB-11	SB-12	SB-13	SB-13A	SB-13A	SB-14	SB-15
Parameter	NYSDEC SCO	SB-11 (2-4')	SB-12 (8-10')	SB-13 (6-8')	SB-13A(0-2")	SB-13A(4')	SB-14 (4')	SB-15 (4')
Sample Date	e	4/12/2006	4/11/2006	4/11/2006	6/18/2007	6/20/2007	6/19/2007	6/19/2007
Acenaphthene	100	<0.084	<0.10	<0.084	<0.18	<0.044	<0.05	<0.048
Acenaphthylene	100	NA	NA	NA	<0.18	<0.044	<0.05	<0.048
Anthracene	100	0.0390 J	<0.10	<0.084	<0.18	<0.044	<0.05	0.074
Benzo(a)anthracene		0.112	<0.10	<0.084	0.22 J	<0.044	<0.05	0.3
Benzo(a)pyrene	Т	0.112	<0.10	<0.084	0.24 J	<0.044	<0.05	0.26
Benzo(b)fluoranthene		0.142	<0.10	<0.084	0.32 J	<0.044	<0.05	0.36
Benzo(g,h,i)perylene	100	0.0680 J	<0.10	<0.084	0.2 J	<0.044	<0.05	0.16
Benzo(k)fluoranthene	3.9	0.0607 J	<0.10	<0.084	<0.18	<0.044	<0.05	0.14
Carbazole	NGV	NA	NA	NA	<0.18	<0.044	<0.05	<0.048
Chrysene	3.9	0.115	<0.10	<0.084	0.25 J	<0.044	<0.05	0.29
Dibenzo(a,h)anthracene	0.33	<0.084	<0.10	<0.084	<0.18	<0.044	<0.05	0.048
Di-n-butyl phthalate	NGV	NA	NA	NA	<0.35	<0.088	<0.099	<0.095
bis(2-Ethylhexyl)phthalate	NGV	NA	NA	NA	<0.35	<0.088	<0.099	<0.095
Fluoranthene	100	0.195	<0.10	0.0203 J	0.45 J	<0.044	<0.05	0.59
Fluorene	100	<0.084	<0.10	<0.084	<0.18	<0.044	<0.05	<0.048
Indeno(1,2,3-cd)pyrene	0.5	0.081 J	<0.10	<0.084	<0.18	<0.044	<0.05	0.14
2-Methylnaphthalene	NGV	NA	NA	NA	<0.18	<0.044	<0.05	<0.048
Naphthalene	100	<0.084	<0.10	<0.084	<0.18	<0.044	<0.05	<0.048
Phenanthrene	100	0.128	<0.10	0.0326 J	0.21 J	<0.044	<0.05	0.3
Pyrene	100	0.204	<0.10	0.0352 J	0.37 J	<0.044	<0.05	0.52

All concentrations are presented in milligrams per kilogram (mg/kg)

NA - Not analyzed

NGV - No guidance value

J - Laboratory estimated value

All soil samples analyzed in accordance with United States Environmental Protection Agency Method 8260B for volatile organic compounds and Method 8270C for semivolatile organic compounds NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for restricted residential land use per 6NYCRR Part 375-6 Effective December 14, 2006

Shaded - Value exceeds NYSDEC SCOs

Kleinfelder Syracuse, New York

Chateaugay and Salmon Street Former Martin's Gulf Station Fort Covington, New York

Location		SB-16	SB-16	SB-17	SB-18	SB-19	SB-20	SB-20
Parameter	NYSDEC SCO	SB-16(0-2")	SB-16 (3')	SB-17 (4')	SB-18 (4')	SB-19 (4')	SB-20 (4')	SB-201 (4')
Sample Date	a	6/18/2007	6/19/2007	6/20/2007	6/29/2007	6/29/2007	6/20/2007	6/20/2007
Acenaphthene	100	0.27 J	0.52 J	<0.041	<0.041	<0.042	<0.042	<0.041
Acenaphthylene	100	<0.19	3.1	<0.041	<0.041	<0.042	<0.042	<0.041
Anthracene	100	0.46 J	2.9	<0.041	<0.041	0.053 J	<0.042	<0.041
Benzo(a)anthracene	-	1.6	11	<0.041	0.11 J	0.18 J	<0.042	<0.041
Benzo(a)pyrene	-	1.5	7.8	<0.041	0.11 J	0.18 J	<0.042	<0.041
Benzo(b)fluoranthene		1.9	11	<0.041	0.16 J	0.26	<0.042	<0.041
Benzo(g,h,i)perylene	100		ß	<0.041	0.091	0.14 J	<0.042	<0.041
Benzo(k)fluoranthene	3.9	0.7 J	3.9	<0.041	0.062 J	0.13 J	<0.042	<0.041
Carbazole	NGV	0.22 J	0.5 J	<0.041	<0.041	<0.042	<0.042	<0.041
Chrysene	3.9	1.6	9.2	<0.041	0.11 J	0.19 J	<0.042	<0.041
Dibenzo(a,h)anthracene	0.33	0.28 J	1.8	<0.041	<0.041	<0.042	<0.042	<0.041
Di-n-butyl phthalate	NGV	<0.38	<0.89	<0.083	<0.083	<0.083	<0.085	<0.083
bis(2-Ethylhexyl)phthalate	NGV	<0.38	<0.89	<0.083	<0.083	<0.083	<0.085	<0.083
Fluoranthene	100	4	21	0.05 J	0.21	0.34	<0.042	<0.041
Fluorene	100	0.22 J	<0.44	<0.041	<0.041	<0.042	<0.042	<0.041
Indeno(1,2,3-cd)pyrene	0.5	U.87	4.6	<0.041	f 290.0	0.13 J	<0.042	<0.041
2-Methylnaphthalene	NGV	<0.19	<0.44	<0.041	<0.041	<0.042	<0.042	<0.041
Naphthalene	100	<0.19	<0.44	<0.041	<0.041	<0.042	<0.042	<0.041
Phenanthrene	100	2.4	5.3	<0.041	0.13 J	0.19 J	<0.042	<0.041
Pyrene	100	3.4	16	0.047 J	0.2 J	0.32	<0.042	<0.041

All concentrations are presented in milligrams per kilogram (mg/kg)

NA - Not analyzed

NGV - No guidance value

J - Laboratory estimated value

All soil samples analyzed in accordance with United States Environmental Protection Agency Method 8260B

for volatile organic compounds and Method 8270C for semivolatile organic compounds NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for restricted residential land use per 6NYCRR Part 375-6 Effective December 14, 2006

Shaded - Value exceeds NYSDEC SCOs

SB-201 (4') is duplicate of SB-20(4')

Chateaugay and Salmon Street Former Martin's Gulf Station Fort Covington, New York

Location		SB-21	MW-1	MW-2	MW-3	MW-4	MW-5	9-MM
Parameter	NYSDEC SCO	SB-21 (4')	MW1(4')	MW2(5')	MW3(4')	MW4(3')	MW5(5')	MW6(5')
Sample Date		6/29/2007	10/10/2006	10/10/2006	10/10/2006	10/10/2006	10/10/2006	10/11/2006
Acenaphthene	100	<0.041	<0.092	960'0>	<0.860	<0.860	<0.091	<0.083
Acenaphthylene	100	0.083 J	NA	NA	NA	NA	NA	NA
Anthracene	100	0.16 J	<0.092	960'0>	<0.860	<0.860	<0.091	<0.083
Benzo(a)anthracene	1	0.51	<0.092	960'0>	<0.860	<0.860	<0.091	<0.083
Benzo(a)pyrene		0.51	<0.092	960.0>	<0.860	<0.860	<0.091	<0.083
Benzo(b)fluoranthene		99.0	<0.092	>0.096	<0.860	<0.860	<0.091	<0.083
Benzo(g,h,i)perylene	100	0.34	<0.092	>0.096	<0.860	<0.860	<0.091	<0.083
Benzo(k)fluoranthene	3.9	0.38	<0.092	<0.096	<0.860	<0.860	<0.091	<0.083
Carbazole	NGV	0.058 J	NA	NA	NA	NA	NA	NA
Chrysene	3.9	0.52	<0.092	>0.096	<0.860	<0.860	<0.091	<0.083
Dibenzo(a,h)anthracene	0.33	0.069 J	<0.092	>0.096	<0.860	<0.860	<0.091	<0.083
Di-n-butyl phthalate	NGV	<0.081	NA	NA	NA	NA	NA	NA
bis(2-Ethylhexyl)phthalate	NGV	<0.081	NA NA	NA	NA	NA	NA	NA
Fluoranthene	100	0.94	<0.092	960'0>	<0.860	<0.860	<0.091	0.0210
Fluorene	100	0.051 J	<0.092	<0.096	0.505	0.0252 J	<0.091	<0.083
Indeno(1,2,3-cd)pyrene	0.5	0.3	<0.092	<0.096	098.0>	<0.860	<0.091	<0.083
2-Methylnaphthalene	NGV	<0.041	NA	NA	NA	NA	NA	NA
Naphthalene	100	<0.041	0.0728 J	>0.096	40.9	2.98	0.921	<0.083
Phenanthrene	100	19.0	<0.092	>0.096	U.707	0.0345 J	<0.091	0.0312
Pyrene	100	0.84	<0.092	<0.096	<0.860	<0.860	<0.091	0.0258

All concentrations are presented in milligrams per kilogram (mg/kg)

NA - Not analyzed

NGV - No guidance value

J - Laboratory estimated value

All soil samples analyzed in accordance with United States Environmental Protection Agency Method 8260B for volatile organic compounds and Method 8270C for semivolatile organic compounds

NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for restricted residential land use per 6NYCRR Part 375-6 Effective December 14, 2006

Shaded - Value exceeds NYSDEC SCOs

Chateaugay and Salmon Street Fort Covington, New York Former Martin's Gulf Station

Location		UST Area	N-WS	TP-1	TP-2	TP-3	TP-4	Tank Excavation Area
Parameter	NYSDEC SCO	UST-SURFACE	.9-N-MS	TP1-6'	TP2-6'	TP3-4'	TP4-6'	TT-1,000-G-FP
Sample Date		8/15/2006	8/15/2006	8/15/2006	8/15/2006	8/15/2006	8/15/2006	8/15/2006
Acenaphthene	100	<0.34	<0.077	<0.080	<0.075	>0.086	<0.087	<0.081
Acenaphthylene	100	NA	<0.077	<0.080	<0.075	<0.086	<0.087	<0.081
Anthracene	100	<0.34	0.0155 J	<0.080	<0.075	<0.086	<0.087	0.106
Benzo(a)anthracene	1	0.626 J	0.0216 J	<0.080	<0.075	<0.086	0.0688	0.0401 J
Benzo(a)pyrene	_	<0.34	<0.077	<0.080	<0.075	<0.086	0.0638	0.0246 J
Benzo(b)fluoranthene	-	<0.34	<0.077	<0.080	<0.075	>0.086	0.0625 J	
Benzo(g,h,i)perylene	100	<0.34	<0.077	<0.080	<0.075	>0.086	<0.087	0.0235 J
Benzo(k)fluoranthene	3.9	<0.34	<0.077	<0.080	<0.075	<0.086	0.0519 J	
Carbazole	NGV	NA	<0.077	<0.080	<0.075	<0.086	<0.087	<0.081
Chrysene	3.9	0.834 J	0.0201 J	<0.080	<0.075	<0.086	0.0670 J	0.0232 J
Dibenzo(a,h)anthracene	0.33	<0.34	<0.077	<0.080	<0.075	<0.086	<0.087	<0.081
Di-n-butyl phthalate	NGV	NA	<0.077	0.0521 J	<0.075	<0.086	<0.087	<0.081
bis(2-Ethylhexyl)phthalate	NGV	NA	<0.077	0.175	<0.075	<0.086	<0.087	<0.081
Fluoranthene	100	1,44 J	0.0269 J	0.0339 J	<0.075	0.0180 J	0.123	0.0441 J
Fluorene	100	0.589 J	0.0786	0.0433 J	0.0549 J	0.0889	<0.087	0.246
Indeno(1,2,3-cd)pyrene	0.5	<0.34	<0.077	<0.080	<0.075	>0.086	<0.087	<0.081
2-Methylnaphthalene	NGV	NA	4.23	4.03	3.77	8.030	<0.087	22.7
Naphthalene	100	0.279 J	4.71	4.95	5.25	11.5	0.034	23.1
Phenanthrene	100	3.11	0.105	0.0968	0.0833	0.168	0.0547 J	
Pyrene	100	1.78	0.0581 J	0.0982	0.0239 J	0.0421 J	0.101	0.118

All concentrations are presented in milligrams per kilogram (mg/kg) NA - Not analyzed

NGV - No guidance value

J - Laboratory estimated value
All soil samples analyzed in accordance with United States Environmental Protection Agency Method 8260B
for volatile organic compounds and Method 8270C for semivolatile organic compounds
NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for

restricted residential land use per 6NYCRR Part 375-6 Effective December 14, 2006

Shaded - Value exceeds NYSDEC SCOs

SOIL ANALYTICAL DATA - PESTICIDES AND PCBS Table 3

Chateaugay and Salmon Street Fort Covington, New York Former Martin's Gulf Station

Location		SUR-1	SUR-2	SUR-3	SB-3	SB-5B	SB-7
Parameter	NYSDEC SCO	SUR-1(0-2")	SUR-2(0-2")	SUR-3(0-2")	SB-3 SURFACE	SB-5B (1-2')	SB-7 (4-5')
Sample Date		6/18/2007	6/18/2007	6/18/2007	4/11/2006	4/12/2006	4/12/2006
Pesticides							
Dieldrin	0.2	<0.00036	<0.00034	<0.00044	<0.017	<0.0052	<0.0048
4,4'-DDD	13	<0.00036	<0.00034	<0.00044	<0.017	<0.0052	<0.0048
4,4'-DDE	8.9	<0.00036	<0.00034	<0.00044	<0.017	0.0052	<0.0048
4,4'-DDT	7.9	<0.00036	<0.00034	<0.00044	<0.017	<0.0052	<0.0048
Endrin aldehyde	NGV	<0.00036	<0.00034	<0.00044	<0.017	<0.0052	<0.0048
Methoxychlor	NGV	<0.0019	<0.0018	<0.0023	<0.0043	<0.013	<0.012
PCBs				300			
Aroclor 1254	1	<0.0059	<0.00556	<0.00717	<0.043	<0.13	<0.12
Aroclor 1260	1	<0.00689	<0.00649	<0.00837	<0.043	<0.13	<0.12

All concentrations are presented in milligrams per kilogram (mg/kg)

NA - Not analyzed
NGV - No guidance value
NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for restricted residential land use per 6NYCRR Part 375-6 Effective December 14, 2006

SOIL ANALYTICAL DATA - PESTICIDES AND PCBS

Chateaugay and Salmon Street Fort Covington, New York Former Martin's Gulf Station

Location		SB-9	SB-10	SB-11	SB-11	SB-12	SB-13	SB-13A
Parameter	NYSDEC SCO	SB-9 SURFACE	SB-1	0 SURFACE SB-11 SURFACE	SB-10 (10-12')	SB-12 (8-10')	SB-13 (6-8')	SB-13A(0-2")
Sample Date		4/12/2006	4/12/2006	4/12/2006	4/12/2006	4/11/2006	4/11/2006	2002/81/9
Pesticides								
Dieldrin	0.2	<0.0016	<0.0014	<0.0016	<0.0019	<0.0020	<0.0017	0.00082
4,4'-DDD	13	<0.0016	<0.0014	<0.0016	<0.0019	<0.0020	<0.0017	<0.00035
4,4'-DDE	8.9	<0.0016	<0.0014	<0.0016	<0.0019	<0.0020	<0.0017	0.0006
4,4'-DDT	7.9	<0.0016	0.0083	<0.0016	<0.0019	<0.0020	<0.0017	0.0013
Endrin aldehyde	NGV	<0.0016	<0.0014	<0.0016	<0.0019	<0.0020	<0.0017	<0.00035
Methoxychlor	NGV	<0.0039	<0.0036	<0.0040	<0.0047	<0.0050	<0.0042	<0.0018
PCBs								
Aroclor 1254	1	<0.039	<0.036	<0.040	<0.047	<0.050	<0.042	0.0253
Aroclor 1260	1	<0.039	<0.036	<0.040	<0.047	<0.050	<0.042	0.00928

All concentrations are presented in milligrams per kilogram (mg/kg)

NA - Not analyzed

NGV - No guidance value NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for restricted residential land use per 6NYCRR Part 375-6 Effective December 14, 2006

SOIL ANALYTICAL DATA - PESTICIDES AND PCBS Table 3

Chateaugay and Salmon Street Former Martin's Gulf Station Fort Covington, New York

Location		SB-13A	SB-14	SB-15	SB-16	SB-16
Parameter	NYSDEC SCO	SB-13A(4')	SB-14 (4')	SB-15 (4')	SB-16(0-2")	SB-16 (3')
Sample Date		6/20/2007	6/19/2007	6/19/2007	6/18/2007	6/19/2007
Pesticides		1000			3000	
Dieldrin	0.2	<0.00043	<0.00049	<0.00047	0.0012 J	<0.0022
4,4'-DDD	13	<0.00043	<0.00049	<0.00047	U.0019	U.000
4,4'-DDE	8.9	<0.00043	<0.00049	<0.00047	0.0023	0.0043 J
4,4'-DDT	7.9	<0.00043	<0.00049	<0.00047	0.014	0.052
Endrin aldehyde	NGV	<0.00043	<0.00049	<0.00047	<0.00037	0.0036 J
Methoxychlor	NGV	<0.0022	<0.0025	<0.0024	<0.0019	<0.011
PCBs						
Aroclor 1254	-	<0.00711	<0.00805	<0.00773	<0.00609	<0.00719
Aroclor 1260	1	<0.00829	<0.00939	<0.00901	<0.0071	0.0218 J

Notes:

All concentrations are presented in milligrams per kilogram (mg/kg)

NA - Not analyzed

NGV - No guidance value NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for restricted residential land use per 6NYCRR Part 375-6 Effective December 14, 2006

SOIL ANALYTICAL DATA - PESTICIDES AND PCBS

Chateaugay and Salmon Street Fort Covington, New York Former Martin's Gulf Station

)				
Location		SB-17	SB-18	SB-19	SB-20	SB-20	SB-21	UST Area
Parameter	NYSDEC SCO	SB-17 (4')	SB-18 (4')	SB-19 (4')	SB-20 (4')	SB-201 (4')	SB-21(4')	UST-SURFACE
Sample Date		6/20/2007	6/29/2007	6/29/2007	6/20/2007	2002/02/9	2000/60/9	8/15/2006
Pesticides						1001010	0/22/2001	9/12/2000
Dieldrin	0.2	<0.00041	0.00073 J	0.0014 J	<0.00042	<0.00041	0 00003 T	700007
4,4'-DDD	13	<0.00041	0.0016 J	0.0029	<0.00042	<0.00041	0.0018	<0.0014
4,4'-DDE	8.9	<0.00041	<0.00041	0.00065 J	<0.00042	<0.00041	0.00074	<0.0014 <0.0014
4,4'-DDT	7.9	0.0013 J	0.0018 J	0.0037	<0.00042	<0.00041	0.000/4	V.0014
Endrin aldehyde	NGV	<0.00041	<0.00041	<0.00041	<0.00042	<0.00041	<0.0034 <0.0004	<0.0014
Methoxychlor	NGV	<0.0021	<0.0021	<0.0021	<0.0022	0.0044	<0.0001	-00.001 -00.001
PCBs							0.0021	-0.0034
Aroclor 1254	1	<0.00668	<0.00669	<0.00675	<0.00686	<0.00671	. 99000>	70.024
Aroclor 1260	1	<0.0078	0.0209 J	0.0349	<0.00801	<0.00783	0.0224	<0.034

All concentrations are presented in milligrams per kilogram (mg/kg)

NA - Not analyzed

NGV - No guidance value NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for restricted residential land use per 6NYCRR Part 375-6 Effective December 14, 2006

SB-201 (4) is duplicate of SB-20(4')

SOIL ANALYTICAL RESULTS - METALS Table 4

Former Martin's Gulf Station Chateaugay and Salmon Street Fort Covington, New York

Location	ion	SUR-1	SUR-2	SUR-3	SB-2	SB-3	SB-3	SB-4	SB-5B	SB-7	SB-9	SB-9
Parameter	NYSDEC SCO	SB-1 SURFACE	SURFACE	SB-3 SURFACE (A)	SB-2 (6-8')	SB-3 SURFACE	SB-3 (4-6')	SB-4 (6-8')	SB-5B (1-2')	SB-7 (4-5')	SURFACE	SB-9 (6-8')
Sample Date	Date	6/18/2007	6/18/2007	6/18/2007	4/11/2006	4/11/2006	4/11/2006	4/11/2006	4/12/2006	4/12/2006	4/12/2006	2000/01/1
Aluminum	NGV	NA	NA	ΝĀ	ΝΑ	ΔN	Ν̈́Α	ATA	714	2007	17/2000	4/17/7000
Antimony	NGV	NA	NA	NA	MA	2.6	NA.	NA.	AN.	NA	NA	NA
Arsenic	91	7 08 7	3.67	70.17	140	0.2	W.	NA	<2.7	<2.6	4.2	NA
Rarium	700	J. 00	2.07	07.170	AN	2	NA	NA	3	3	2.5	NA
Dondling	400	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Codmin	7/	r 70c'0	U.181	0.235 J	NA	<0.65	NA	NA	<0.68	<0.65	<0.61	ΑN
Cadmium	4.3	0.471 J	0.308 J	0.417 J	NA	3	NA	NA	3	3	1.2	NA
Calcium	NGV	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA AN	NAN
Caromium	081	15.5	5.51	10.6	NA	31	NA	NA	47	35	951	ΔN
Cobalt	NGV	NA A	NA	NA	NA	NA	NA	NA	NA	NA	NA	AN AN
Copper	270	8.25	3.54	6.11	NA	37	NA	NA	33	28	22.5	NA
Iron	NGV	NA	NA	NA	NA	NA	NA	NA	ΝĀ	NA AN	V.V.	Y.
Lead	400	21.9	9.21	7	NA	62	NA	NA	17	21	INA	NA:
Mercury	0.81	0.0417 J	0.0144 J	0.0251 J	NA	0.068	NA	AN	<0.044	50 043	80.3	NA
Magnesium	NGV	NA	NA	NA	NA	NA	NA	NA	NA	AM	NIA	NA VIA
Manganese	2,000	NA	NA	NA	NA	NA	NA	NA	N.A	NA	VN VN	Y.V
Nickel	310	8.81	3.87	7.16	ŊĄ	25	NA	NA	3,6	3,8	T O	V.V.
Potassium	NGV	NA	NA	NA	NA	NA	NA	NA	NA	NA NA	ΔN	Y.V
Selenium	180	NA	NA	NA	NA	<2.6	NA	NA	2.7	2.6	2.4	AN AN
Silver	180	NA	NA	NA	NA	<1.3	NA	NA	<1.4	<1.3	<12	VN
Sodium	NGV	NA	NA	NA	NA	NA	NA	NA	NA	NA	ANA	MA
Thallium	NGV	NA	NA	NA	NA	<1.3	NA	NA	<1.4	7	712	VIV
Vanadium	NGV	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	VN
Zinc	10,000	39.8	4.98	30.6	NA	131	NA	NA	95	112	102	AN

All values are listed in milligrams per kilogram (mg/kg)

NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for restricted residential land use per NYCRR Part 375-6 Effective December 14, 2006

NGV - No guidance value
NA - Not analyzed
NA - Nor analyzed
Shaded - Value exceeds NYSDEC SCOs
All soil samples analyzed in accordance with United States Environmental Protection Agency Method 6010B, 7471A, and 3050B for metals.

Table 4 SOIL ANALYTICAL RESULTS - METALS

Former Martin's Gulf Station Chateaugay and Salmon Street Fort Covington, New York

Sample Date Um Ny In		_	_				SB-13A	Sb-13A	41-GC	cI-ge	SB-16
Sample Date um ny in im im um nm um um um um	CO SURFACE	SB-10 (10-12')	SB-11 SURFACE	SB-11 (2-4')	SB-12 (8-10')	SB-13 (6-8')	SB-13A(0-2")	SB-13A(4')	SB-14 (4')	SB-15 (4')	SB-16(0-2")
any in a second	4/12/2006	4/12/2006	4/12/2006	4/12/2006	4/11/2006	4/11/2006	6/18/2007	6/20/2007	2002/61/9	6/19/2007	2000/81/9
nn m nn nu mu	NA	NA	NA	NA	NA	ΑN	3.590	30 800	ΑN	VIA	7 630
um um m	<2.2	42.9	<2.5	NA	3,1	<2.6	<0.903	<1.10	AIN	INA	0.00,
mm n n n n	3.2	3	<2.5	NA	3.1	2.6	1.71	1 70 1	1 48	1.00 L	433
mm um	NA	NA	NA	NA	NA	NA	22.1	291	NA NA	NA	4.22
m n um	<0.54	<0.74	<0.61	NA	<0.77	<0.65	0.166 J	1.26	1.43	1.18	0.318
um	1.2	3	1.6	NA	4.2	2.1	0.437 J	0.974	1.16	1.19	876.0
um	NA	NA	NA	NA	NA	NA	54,200	7,340	NA	Ϋ́	10.000
	9.8	39.4	17.1	NA	65.4	23.6	99.6	60.3	74.4	1.09	17.4
	NA	NA	NA	NA	NA	NA	2.4	20.1	N.A.	NAN AN	4.03
Copper 270	12.9	33.9	16.1	NA	48.1	21.1	11.2	31.8	42	34.4	20.
NGV	NA	NA	NA	NA	NA	NA	7.640	45.400	NA	NA	11 800
	47.5	8.7	93	NA	7.5	6.7	47.8	18.5	143	203	751
	<0.035	<0.047	0.12	NA	<0.049	<0.041	0.0168	0.0368	7 21.000	1 2000	167
Magnesium NGV	NA	NA	NA	NA	ΝΑΝ	ΔN	009 24	13 000	O. CALLO	0.042/	0.10
Manganese 2,000	NA	NA	NA	NA	NA	ΨN	2110	777	VIV.	NA.	09/,60
Nickel 310	9.1	34.7	12.4	NA	45.6	0,0	1.9	107	CVI CVI	E S	6/7
Potassium NGV	NA	NA	NA	NA	NA	AN AN	1 330	10.530	47.5	39.5	9.1
Selenium 180	<2.2	<2.9	<2.5	NA	3.1	<2.6	0.000	2,000	V.V	NA.	2,030
Silver 180	<1.1	<1.5	<1.2	NA	<15	2 3	<0.17	07.17	ATA	NA.	Z-1.1
Sodium	NA	NA	NA	NA	NA	NA	122	457	NA VI	NA.	U.255 J
Thallium NGV	<1.1	<1.5	<1.2	NA	<1.5	V 13	20.0>	7 06	NA	NA	977
Vanadium NGV	NA	NA	NA	NA	Α̈́N	NA	113	07.1	AYA	ANI	/0.1>
10,000	26.5	8	7 70	NA	133	1 00	200	0/.1	W.	NA	18.3

All values are listed in milligrams per kilogram (mg/kg)

NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for restricted residential land use per NYCRR Part 375-6 Effective December 14, 2006

NGV - No guidance value
NA - Not analyzed
Shaded - Value exceeds NYSDEC SCOs
All soil samples analyzed in accordance with United States Environmental Protection Agency Method 6010B, 7471A, and 3050B for metals.

Table 4 SOIL ANALYTICAL RESULTS - METALS

Former Martin's Gulf Station Chateaugay and Salmon Street Fort Covington, New York

	SB-16	SB-17	SB-18	SB-19	SB-20	SB-20	SB-21	UST Area
NYSDEC SCO	SB-16 (3')	SB-17 (4¹)	SB-18 (4°)	SB-19 (4')	SB-20 (4')	SB-201 (4')	SB-21(4')	UST- SURFACE
	6/19/2007	6/20/2007	6/29/2007	6/29/2007	6/20/2007	6/20/2007	6/29/2007	8/15/2006
NGV	10,700	NA	NA	NA	NA	ΑN	NA	NA
NGV	<1.18	NA	NA	NA	NA	NA	NA	0.00
16	5.82	2.54	4.33	4.63	2.97	2.86	5.63	2.2
90	292	NA	NA	NA	NA	NA	NA	NA AN
72	0.628 J	1.03	0.99	0.945	0.907	6.0	1.03	05 0>
4.3	1.37	0.993	2.16	1.97	1.02	0.94	1.89	1.5
NGV	21,100	NA	NA	NA	NA	NA	NA	NA
180	35.3	42.9	NA	NA	48	45.7	NA	13.0
NGV	5.97	NA	NA	NA	NA	NA	NA	NA
270	78	31.7	33.4	37.5	25.2	22.6	39	26.3
NGV	18,400	NA	NA	NA	NA	NA	NA	NA
400	480	32.9	85.8	124	80.1	63.4	160	143
0.81	0.898	0.0258 J	0.135	0.12 J	0.134	0.0842 J	0.161	0.075
NGV	11,000	NA	NA	NA	NA	NA	NA	AN
000	306	NA	NA	NA	NA	NA	NA	NA
310	13.7	36.7	30.2	28.3	29	27.5	31.1	0.6
S	2,560	NA	NA	NA	NA	NA	NA	NA
180	<1.28	NA	NA	NA	NA	NA	NA	<2.0
180	0.794	NA	NA	NA	NA	NA	NA	0 1>
NGV	284	NA	NA	NA	NA	NA	NA	Ϋ́
λS	<1.24	NA	NA	NA	NA	NA	NA	01>
NGV	24.7	NA	NA	NA	NA	NA	NA	NA
10,000	401	77.2	115	126	113	106	140	140

Notes:

All values are listed in milligrams per kilogram (mg/kg)

NYSDEC SCOs - New York State Department of Environmental Conservation, Soil Cleanup Objectives for restricted residential land use per NYCRR Part 375-6 Effective December 14, 2006

NGV - No guidance value

NA - Not analyzed

Shaded - Value exceeds NYSDEC SCOs

All soil samples analyzed in accordance with United States Environmental Protection Agency Method 6010B, 7471A, and 3050B for metals.

SEDIMENT ANALYTICAL DATA - VOLATILE ORGANIC COMPOUNDS

Chateaugay and Salmon Street Former Martin's Gulf Station Fort Covington, New York

Loootion		1 33	6 20	6 20	7 77	- 22	7 2 2		
LOCATION		1-00	22-6	2-22	4-00	V-V	9-88	SS-7	SS-8
Parameter	NYSDEC	SS-1	SS-2	SS-3	SS-4	SS-5	9-SS	SS-7	SS-8
Sample Date	TGSCS	10/26/2006	10/26/2006	10/26/2006	10/26/2006	6/18/2007	6/18/2007	6/18/2007	6/18/2007
Acetone	1	NA	NA	ŇĀ	AN	1 200	0.047	0 03 T	<0.01
Ethylbenzene	0.48	<0.0024	<0.0024	<0.0018	<0.0016	<0.000	<0.000	CO 00>	10.00
Toluene	86.0	<0.0024	<0.0024	<0.0018	<0.0016	<0.002	<0.00	<0.02	0.002
Xylene (total)	1.84	<0.0048	<0.0048	<0.0037	<0.0032	<0.002	<0.002	<0.002	0.003

Notes:

All concentrations are presented in milligrams per kilogram (mg/kg)

Xylene (total) - Sum of m, p-xylenes and o-xylenes

J - Laboratory estimated value

Assumes a total organic carbon content of 2%

NYSDEC TGSCS - New York State Department of Environmental Conservation Sediment Criteria per Technical Guidance for Screening Contaminated Sediments

Chateaugay and Salmon Street Former Martin's Gulf Station Fort Covington, New York

Location		SS-1	SS-2	SS-3	SS-4	SS-5	9-SS	Z-SS-7	8-55
Parameter	NYSDEC	SS-1	SS-2	SS-3	SS-4	SS-5	9-SS	SS-7	8-8.8
Sample Date	TGSCS	10/26/2006	10/26/2006	10/26/2006	10/26/2006	6/18/2007	6/18/2007	6/18/2007	6/18/2007
Phenol	0.01	NA	NA	ΑN	ΑN	<0.27	<0.061	1007/01/0	0.02/0
Acenaphthene	2.8	<0.11	0.0738 .I	<0.120	<0.087	72.0>	0.001	0.05	0.62
Anthracene	2.14	0.0578	2.14	0 0402 T	0.000	77.0	0.001	20.02	<0.046
Benzo(a)anthracene	0.24	0.258	5.63	0.173	0.0202	72.0>	0.001	<0.05	<0.046
Benzo(a)pyrene	0.026	0.264	4.54	0.168	0.164	<0.27	f 990.0	J 7/0.0	<0.046
Benzo(b)fluoranthene	0.026	0.249	4.67	0.173	0.137	<0.27	0.000	J 2/0.0	<0.040 0.046
Benzo(g,h,i)perylene	1	0.207	0.988	0.158	1 69200	<0.27	0.079 J	0.07	V0.040
Benzo(k)fluoranthene	0.026	0.157	3.37	0.124	0 105	77:0>	70.061	0.05	<0.040
Chrysene	9700	900	503	167	31.0	17.0	100.00	CO:0>	<0.046
Dibenzo(a h)anthracene		0.0525	0.4.0	7070	0.1/8	<0.27 0.27	0.067 J	0.077 J	<0.046
hig/ Ethylhowyllabtholote		e cccu.u	0./4/	U.0504	0.315 J	<0.27	<0.061	<0.05	<0.046
018(2-Eurymexy1)primarate	3.99	NA	NA	NA	NA	<0.54	<0.12	<0.1	0.46
riuorantnene	20.4	0.372	9.85	0.280	0.273	0.33 J	0.11 J	0.13	<0.046
Fluorene	0.16	<0.11	0.381	<0.12	0.229 J	<0.27	<0.061	<0.05	<0.046
Indeno(1,2,3-cd)pyrene	0.026	0.187	1.42	0.129	0.0842 J	<0.27	<0.061	<0.05	<0.046
Naphthalene	9.0	<0.11	0.0695 J	<0.12	<0.087	<0.27	<0.061	<0.05	>0.040
Phenanthrene	2.4	0.132	5.72	0.140	0.136	<0.27	<0.061	0.055	<0.046
Pyrene	19.22	0.436	69.9	0.332	0.287	0.28 J	0.1	0.13	<0.076
						W		0 0110	0+0.0

Notes:

All concentrations are presented in milligrams per kilogram (mg/kg)

J - Laboratory estimated value

Assumes a total organic carbon content of 2% NYSDEC TGSCS - New York State Department of Environmental Conservation Sediment Criteria per Technical Guidance for Screening Contaminated Sediments

Table 7 SEDIMENT ANALYTICAL DATA - PESTICIDES AND PCBS

Former Martin's Gulf Station Chateaugay and Salmon Street Fort Covington, New York

Location		SS-1	SS-2	SS-3	SS-4	SS-5	9-SS	SS-7	8-SS
Parameter	NYSDEC	SS-1	7-SS	E-SS	SS-4	SS-5	9-SS	2-SS	8-SS-
Sample Date	TGSCS	10/26/2006	10/26/2006	10/26/2006	10/26/2006	6/18/2007	6/18/2007	6/18/2007	6/18/2007
Pesticides									
gamma-Chlordane	90000	<0.0022	<0.0024	<0.0023	<0.0017	0.0017	<0.0018	<0.0015	<0.0014
Dieldrin	0.18	<0.0022	<0.0024	<0.0023	<0.0017	0.00057 J	<0.0006	<0.0005	<0.00046
4,4'-DDD	0.00002	<0.0022	<0.0024	<0.0023	<0.0017	<0.00054	<0.0006	J. 01000	<0.00046
4,4'-DDE	0.00002	<0.0022	<0.0024	<0.0023	0.0021	0.00069 J	0.00065 J	0.0024	<0.00046
4,4'-DDT	0.00002	<0.0022	<0.0024	<0.0023	<0.0017	<0.00054	<0.0006	0.00054 J	<0.00046
Endosulfan sulfate	0.0006	<0.0022	<0.0024	<0.0023	<0.0017	<0.00054	<0.0006	<0.0005	0.0008
PCBs									
Aroclor 1254	0.028	<0.055	<0.059	<0.058	<0.042	<0.00878	<0.00987	0.0136 J	<0.0075
						A			

Intec.

All concentrations are presented in milligrams per kilogram (mg/kg)

J - Laboratory estimated value

NYSDEC TGSCS - New York State Department of Environmental Conservation Sediment Criteria per Technical Guidance for Screening Contaminated Sediments PCB - polychlorinated bi-phenyl All soil samples analyzed in accordance with United States Environmental Protection Agency Methods 8081A and 3545 for pesticides and 8082 and 3545 for

SEDIMENT ANALYTICAL DATA - METALS Table 8

Chateaugay and Salmon Street Former Martin's Gulf Station Fort Covington, New York

Location	ion		SS-1	SS-2	SS-3	SS-4	SS-5	9-SS	SS-7	SS-8
Parameter	NYSDEC TGSCS	TGSCS	SS-1	SS-2	SS-3	SS-4	SS-5	9-SS	SS-7	SS-8
Sample Date	TET	SEL	10/26/2006	10/26/2006	10/26/2006	10/26/2006	6/18/2007	6/18/2007	6/18/2007	6/18/2007
Arsenic	0.9	33.0	<3.3	<3.5	<3.5	<2.6	<1.49	1.76 J	<1.4	<1.27
Beryllium	-	1	<0.83	<0.89	<0.89	<0.65	0.199 J		0.181 J	0.144 J
Cadmium	9.0	9.0	<0.83	68.0>	<0.89	1.8	0.421 J		0.421 J	0.315
Chromium	16.0	110	15.5	17.7	14.0	8.1	10.5	14.2	9.17	7.72
Copper	31.0	110	12.5	33.0	17.1	14.0	6.65	10.3	5.01	4.03
Lead	460	1100	18.3	144	8.99	19.5	10	19.2	12.8	7.66
Mercury	0.15	1.3	0.2	0.3	0.076	<0.040	0.0723 J	J 8860.0	0.0394 J	0.0183
Nickel	16.0	50.0	7.3	9.2	9.4	5.3	5.43	7.12	4.98	4.46
Zinc	120	270	48.1	235	118	43.2	41.4	66.5	45.3	29

All values are listed in milligrams per kilogram (mg/kg) J - Laboratory estimated value

NA - Not analyzed

LEL - Lowest Effect Level

SEL - Severe Effect Level

NYSDEC TGSCS - New York State Department of Environmental Conservation Sediment Criteria per Technical Guidance for Screening Contaminated Sediments

Table 9 MONITORING WELL GAUGING DATA

Former Martin's Gulf Station Chateaugay and Salmon Street Fort Covington, New York October 26, 2006 through September 21, 2007

Well ID	Date	DTB	DTW	TOC Elevation	Water Table Elevation
	26-Oct-06	22.77	2.78	99.45	96.67
	22-Jan-07	23.15	3.46	99.45	95.99
MW-1	19-Jun-07	23.20	3.98	98.14	94.16
	29-Jun-07	23.16	4.54	98.14	93.60
	21-Sep-07	23.16	6.00	98.14	92.14
	26-Oct-06	22.09	3.08	99.82	96.74
	22-Jan-07	22.09	3.66	99.82	96.16
MW-2	19-Jun-07	22.20	4.33	98.54	94.21
	29-Jun-07	22.00	4.81	98.54	93.73
	21-Sep-07	22.00	6.34	98.54	92.20
	26-Oct-06	22.75	3.10	99.72	96.62
	22-Jan-07	22.75	3.70	99.72	96.02
MW-3	29-Jun-07	22.70	4.23	98.44	94.21
	19-Jun-07	22.70	4.23	98.44	94.21
	21-Sep-07	22.70	6.39	98.44	92.05
	26-Oct-06	23.01	3.26	99.90	96.64
	22-Jan-07	23.01	4.36	99.90	95.54
MW-4	19-Jun-07	23.75	4.44	98.60	94.16
	29-Jun-07	14.78	4.81	98.60	93.79
	21-Sep-07	14.78	6.50	98.60	92.10
	26-Oct-06	14.74	3.08	99.82	96.74
	22-Jan-07	14.70	3.73	99.82	96.09
MW-5	19-Jun-07	15.47	4.28	98.48	94.20
	29-Jun-07	23.88	4.96	98.48	93.52
	21-Sep-07	23.88	6.37	98.48	92.11
	26-Oct-06	23.03	2.93	99.69	96.76
	22-Jan-07	23.00	3.37	99.69	96.32
MW-6	19-Jun-07	23.05	4.02	98.23	94.21
	29-Jun-07	23.10	4.54	98.23	93.69
	21-Sep-07	23.10	6.15	98.23	92.08
MW-7	29-Jun-07	15.84	5.44	99.11	93.67
IVI VV - /	21-Sep-07	15.84	7.17	99.11	91.94
M117 0	29-Jun-07	19.65	3.25	96.43	93.18
MW-8	21-Sep-07	19.65	4.2	96.43	92.23
MW-9	29-Jun-07	15.96	4.51	97.58	93.07
IVI W -9	21-Sep-07	15.96	5.46	97.58	92.12

Notes:

DTB - (Depth of monitoring well - feet below top of casing)

DTW - (Depth to groundwater - feet below top of casing)

Monitoring well survey data was collected on October 26, 2006 and September 21, 2007

NS - Not sampled

NA - Not applicable

TOC Elevation - Top of casing elevation relative to an arbitrary datum

Water Table Elevation - (TOC Elevation - DTW)

GROUNDWATER ANALYTICAL DATA - VOLATILE ORGANIC COMPOUNDS Table 10

Chateaugay and Salmon Street Former Martin's Gulf Station Fort Covington, New York

Parameter	NYSDEC	MW-1	V-1	MW-2	7-2	MW-3	V-3	MW-4	V-4
Sample Date	S) W	10/26/2006 1/22/2007	1/22/2007	10/26/2006 1/22/2007	1/22/2007	10/26/2006	1/22/2007	10/26/2006	1/22/2007
Acetone	NGV	NA	NA	ΑN	NA	NA	NA	NA	NA
Benzene	1	<1.0	<1.0	<1.0	<1.0	3,060	1,250	3.800	4.120
2-Butanone	NGV	NA	NA	NA	NA	NA	NA	NA	NA
sec-Butylbenzene	5	<5.0	<5.0	<5.0	<5.0	<250	<100	<100	<100
Ethylbenzene	5	<1.0	<1.0	<1.0	<1.0	906	453	1.040	558
Isopropylbenzene	2	<2.0	<2.0	<2.0	<2.0	28.3 J	ц 6.11	27.2 J	11.0
p-Isopropyltoluene	S	<5.0	<5.0	<5.0	<5.0	<250	<100	<100	<100
Methyl Tert Butyl Ether	10	3.3	1.1	0.52 J	<1.0	207	64.6	184	110
4-Methyl-2-pentanone	NGV	NA AN	NA	NA	NA	NA	NA	NA	NA
Naphthalene	10	<5.0	<5.0	<5.0	<5.0	288	80.6	275	95.8 J
n-Propylbenzene	5	<5.0	<5.0	<5.0	<5.0	84.7 J	31.8 J	68.1 J	25.8 J
Toluene	5.	<1.0	<1.0	<1.0	<1.0	11,700	2,390	8.990	2.420
1,2,4-Trimethylbenzene	v	<5.0	<5.0	<5.0	<5.0	1.320	557	904	391
1,3,5-Trimethylbenzene	S	<5.0	<5.0	<5.0	<5.0	344	227	236	102
m,p-Xylene	5	<1.0	<1.0	<1.0	<1.0	6,380	2,750	5.020	2.490
o-Xylene	5	<1.0	<1.0	<1.0	<1.0	3,090	1,680	2,390	1,040
Xylene (total)	5	<1.0	<1.0	<1.0	<1.0	9,470	4,430	7,410	3,530
Total BTEX	NGV	BRL	BRL	BRL	BRL	25.136	8.523	21.240	10.628

All concentrations are presented in micrograms per liter (ug/L)

J - Indicates laboratory estimated value

NGV- No guidance value

NYSDEC WQS - New York State Department of Environmental Conservation, Division of

Water Technical and Operational Guidance Series (1.1.1) Ambient Water Quality Standards

and Guidance Values Memorandum, June 1998 (Addendum June 2000)

Total BTEX - Rounded sum of benzene, toluene, ethylbenzene, and total xylenes (including

laboratory estimated values)

Xylene (total) - Sum of m, p-xylenes and o-xylenes

BRL - Below reporting limit Shaded - Value exceeds NYSDEC RSCOs

GROUNDWATER ANALYTICAL DATA - VOLATILE ORGANIC COMPOUNDS Table 10

Chateaugay and Salmon Street Former Martin's Gulf Station Fort Covington, New York

Parameter	NYSDEC	MW.	MW-5	9-MW	9-7	7-WM	8-MW	6-WW	SB-14
Sample Date	w CS	10/26/2006	1/22/2007	10/26/2006	1/22/2007	6/25/2007	6/25/2007	6/25/2007	6/19/2007
Acetone	NGV	NA	NA	NA	NA	Г 8	9>	9>	9
Benzene	1	865	289	0.70 J	<1.0	<0.5	<0.5	<0.5	<0.5
2-Butanone	NGV	NA	NA	NA	NA	\$	12	\$	₽
sec-Butylbenzene	5	3.3 J	<10	<5.0	<5.0	NA	NA	NA	NA
Ethylbenzene	S	269	29.0	<1.0	<1.0	<0.8	<0.8	<0.8	<0.8
Isopropylbenzene	S	21.0	2.7 J	<2.0	<2.0	NA	NA	NA	NA
p-Isopropyltoluene	ď	2.1 J	0.90	<5.0	<5.0	NA	NA	NA	NA
Methyl Tert Butyl Ether	10	643	72.7	4.6	0.71 J	NA	NA	NA	NA
4-Methyl-2-pentanone	NGV	NA	ΝĀ	NA	NA	\$	5 J	\$	4
Naphthalene	10	72.6	30.1	<5.0	<5.0	NA	NA	NA	NA
n-Propylbenzene	5	47.2	4.5 J	<5.0	<5.0	NA	NA	NA	NA
Toluene	S	75.1	63.2	2.4	<1.0	<0.7	<0.7	<0.7	<0.7
1,2,4-Trimethylbenzene	5	398	110	<5.0	<5.0	NA	NA	NA	NA
1,3,5-Trimethylbenzene	S	135	37.4	<5.0	<5.0	ŇĀ	NA	NA	NA
m,p-Xylene	S.	298	766	1.0	<1.0	NA	NA	NA	NA
o-Xylene	ß	343	182	0.52 J	<1.0	NA	NA	NA	NA
Xylene (total)	S	941	448	1.5	<1.0	<0.8	8.0>	<0.8	<0.8
Total BTEX	NGV	1,883	829	4.6	BRL	NA	NA	NA	BRL

All concentrations are presented in micrograms per liter (ug/L)

J - Indicates laboratory estimated value

NGV- No guidance value

NYSDEC WQS - New York State Department of Environmental Conservation, Division of Water Technical and Operational Guidance Series (1.1.1) Ambient Water Quality Standards

and Guidance Values Memorandum, June 1998 (Addendum June 2000)

Total BTEX - Rounded sum of benzene, toluene, ethylbenzene, and total xylenes (including

Xylene (total) - Sum of m, p-xylenes and o-xylenes laboratory estimated values)

BRL - Below reporting limit Shaded - Value exceeds NYSDEC RSCOs

GROUNDWATER ANALYTICAL DATA - SEMIVOLATILE ORGANIC COMPOUNDS Table 11

Former Martin's Gulf Station Chateaugay and Salmon Street Fort Covington, New York

Parameter	NYSDEC	MW-1	7-1	MW-2	7-2	MW-3	MW-4	4
	SOM							
Sample Date	~>	10/26/2006	1/22/2007	10/26/2006	1/22/2007	10/26/2006 1/22/2007 10/26/2006 1/22/2007 10/26/2006 1/22/2007 10/26/2006 1/22/2007	10/26/2006	/22/2007
Naphthalene	10	<2.0	<2.0	<2.0	<2.0	175 54.0	193	194

Notes:

Technical and Operational Guidance Series (1.1.1) Ambient Water Quality Standards and Guidance NYSDEC WQS - New York State Department of Environmental Conservation, Division of Water All concentrations are presented in micrograms per liter (ug/L) Values Memorandum, June 1998 (Addendum June 2000) Shaded - Value exceeds NYSDEC RSCOs

GROUNDWATER ANALYTICAL DATA - SEMIVOLATILE ORGANIC COMPOUNDS Table 11

Former Martin's Gulf Station Chateaugay and Salmon Street Fort Covington, New York

Parameter	NYSDEC	MW-5	V-5	9-MW	9-/	MW-7	MW-8	MW-9	SB-14
Sample Date	SQW	10/26/2006	1/22/2007	0/26/2006 1/22/2007 10/26/2006 1/22/2007 6/25/2007 6/25/2007 6/25/2007 6/19/2007	1/22/2007	6/25/2007	6/25/2007	6/25/2007	6/19/2007
Naphthalene	10	27.2	76.4	<2.0	<2.0	<1	\ 	\ \ \	~

Notes:

Technical and Operational Guidance Series (1.1.1) Ambient Water Quality Standards and Guidance NYSDEC WQS - New York State Department of Environmental Conservation, Division of Water All concentrations are presented in micrograms per liter (ug/L) Values Memorandum, June 1998 (Addendum June 2000) Shaded - Value exceeds NYSDEC RSCOs

11/14/2007

Table 12 GROUNDWATER ANALYTICAL DATA - PESTICIDES AND PCBS

Former Martin's Gulf Station Chateaugay and Salmon Street Fort Covington, New York

Parameter	NYSDEC	I-MW	V-1	7-MW	7-2	E-WM	V-3	WW	MW-4
Sample Date	SŽ M	10/26/2006	1/22/2007	726/2006 1/22/2007 10/26/2006 1/22/2007 10/26/2006 1/22/2007	1/22/2007	10/26/2006	1/22/2007	10/26/2006 1/22/2007	1/22/2007
Pesticides									
gamma-BHC (Lindane)	0.05	SN	<0.020	<0.020	<0.020	<0.020	<0.020	<0.020	<0.020
Endosulfan-II	0.1	NS	<0.020	<0.020	<0.020	<0.020	<0.020	<0.020	<0.020

Notes

All concentrations are presented in micrograms per liter (ug/L)

6 NYCRR Part 703 Surface Water and Groundwater Quality Standards and Groundwater Effluent

Limitations

NYSDEC WQS - New York State Department of Environmental Conservation, Division of Water Technical and Operational Guidance Series (1.1.1) Ambient Water Quality Standards and Guidance Values

Memorandum, June 1998 (Addendum June 2000)

NS - Not sampled

PCB - polychlorinated biphenyls - not detected above method detection limit

GROUNDWATER ANALYTICAL DATA - PESTICIDES AND PCBS Table 12

Chateaugay and Salmon Street Former Martin's Gulf Station Fort Covington, New York

Parameter	NYSDEC	MW-5	V-5	9-MM	9-/	MW-7	MW-8	6-WW	SB-14
Sample Date	WQS	10/26/2006	1/22/2007	726/2006 1/22/2007 10/26/2006 1/22/2007 6/25/2007 6/25/2007 6/25/2007 6/19/2007	1/22/2007	6/25/2007	6/25/2007	6/25/2007	6/19/2007
Pesticides									
gamma-BHC (Lindane)	0.05	<0.020	<0.020	<0.020	<0.020	<0.002	0.0022 J <0.0019	<0.0019	<0.002
Endosulfan-II	0.1	<0.020	<0.020	<0.020	<0.020	<0.0039	0.0063 J <0.0038	<0.0038	<0.004

All concentrations are presented in micrograms per liter (ug/L)

6 NYCRR Part 703 Surface Water and Groundwater Quality Standards and Groundwater Effluent Limitations

NYSDEC WQS - New York State Department of Environmental Conservation, Division of Water Technical and Operational Guidance Series (1.1.1) Ambient Water Quality Standards and Guidance Values Memorandum, June 1998 (Addendum June 2000)

NS - Not sampled

PCB - polychlorinated biphenyls - not detected above method detection limit

Table 13 GROUNDWATER ANALYTICAL DATA - METALS

Former Martin's Gulf Station Chateaugay and Salmon Street Fort Covington, New York

Parameter	NYSDEC	1-MW	7-1	MW-2	V-2	MW-3	V-3	MW-4	V-4
Sample Date	w ÇD	10/26/2006	1/22/2007	10/26/2006	1/22/2007	10/26/2006	1/22/2007	10/26/2006	1/22/2007
Aluminum	NGV	NA	NA	NA	NA	NA	NA	NA	NA
Arsenic	25	11.0	16.0	<8.0	8.2	13.9	<8.0	8.4	<8.0
Barium	NGV	NA	NA	NA	NA	NA	NA	NA	NA
Beryllium	*	1.1	<1.0	<1.0	<1.0	1.2	<1.0	<1.0	<1.0
Calcium	NGV	NA	NA	NA	NA	NA	NA	NA	NA
Chromium	50	64.9	14.8	15.1	<10	98.1	<10	6.99	10.7
Cobalt	NGV	NA	NA	NA	NA	NA	NA	NA	NA
Copper	200	72.9	31.7	<25	<25	117	<25	59.1	<25
Iron	NGV	NA	NA	NA	NA	NA	NA	NA	NA
Lead	25	31.0	19.3	12.1	<3.0	59.1	5.5	28.3	6.2
Magnesium	NGV	NA	NA	NA	NA	NA	NA	NA	NA
Manganese	NGV	NA	NA	NA	NA	NA	NA	NA	NA
Nickel	100	65.0	<40	<40	<40	77.6	<40	46.5	<40
Potassium	NGV	NA	NA	NA	NA	NA	NA	NA	NA
Sodium	NGV	NA	NA	NA	NA	NA	NA	NA	NA
Vanadium	NGV	NA	NA	NA	NA	NA	NA	NA	NA
Zinc	NGV	156	51.9	35.6	<20	200	43.7	140	32.1

Notes

All values listed in micrograms per liter (ug/L)

NYSDEC WQS - New York State Department of Environmental Conservation, Division of Water Technical and Operational Guidance Series (1.1.1) Ambient Water Quality Standards and Guidance Values

Memorandum, June 1998 (Addendum June 2000)

* - 11 ug/L, when hardness is less than or equal to 75 ppm; 1,100 ug/L when hardness is greater than 75 ppm Shaded - Value exceeds NYSDEC WQS

Table 13 GROUNDWATER ANALYTICAL DATA - METALS

Former Martin's Gulf Station Chateaugay and Salmon Street Fort Covington, New York

Parameter	NYSDEC	WW-5	Z-7	9-WW	V-6	WW.7	MW.8	MYXX 0	GD 11
	WOS					,	0- 11 11	C= AA TAT	3D-14
Sample Date	٠٠ د ي	10/26/2006	1/22/2007	10/26/2006	1/22/2007	6/25/2007	6/25/2007	6/25/2007	6/19/2007
Aluminum	NGV	NA	NA	NA	NA	10,000	1,720	18,800	18.600
Arsenic	25	<8.0	6.8	<8.0	<8.0	<10	<10	<10	<10
Barium	NGV	NA	NA	NA	NA	325	135	559	384
Beryllium	*	<1.0	<1.0	<1.0	<1.0	<0.9	<0.9	1 J	
Calcium	NGV	NA	NA	NA	NA	278,000	169,000	366,000	7
Chromium	50	33.0	12.7	18.7	<10	16.5	3.2 J	28.3	37.7
Cobalt	NGV	NA	NA	NA	NA	10.8	<2.1	15.4	13.2
Copper	200	63.3	<25	<25	<25	15.8	7.1 J	23.4	31.6
Iron	NGV	NA	NA	NA	NA	13,800	1,840	23,100	22.600
Lead	25	24.3	5.5	7.8	<3.0	9.2 J	6.9 J	22.9	16.9
Magnesium	NGV	NA	NA	NA	NA	90,100	76,300	108,000	81,400
Manganese	NGV	NA	NA	NA	NA	1,510	213	1,470	1,780
Nickel	100	<40	<40	<40	<40	18.4	<5.6	30.8	36.2
Potassium	NGV	NA	NA	NA	NA	8,110	7,250	9,190	10,700
Sodium	NGV	NA	NA	NA	NA	69,500	65,600	178,000	137,000
Vanadium	NGV	NA	NA	NA	NA	21.1	4.1 J	45	44.2
Zinc	NGV	92.7	35.6	45.3	<20	41.7	131	92.3	8.68

Notes

All values listed in micrograms per liter (ug/L)

NYSDEC WQS - New York State Department of Environmental Conservation, Division of Water Technical and Operational Guidance Series (1.1.1) Ambient Water Quality Standards and Guidance Values Memorandum, June 1998 (Addendum June 2000)

Shaded - Value exceeds NYSDEC WQS

* - 11 ug/L, when hardness is less than or equal to 75 ppm; 1,100 ug/L when hardness is greater than 75 ppm

Table 14 SOIL GAS ANALYTICAL DATA - ORGANICS

Former Martin's Gulf Station Chateaugay and Salmon Street Fort Covington, New York


Parameter	SG-	1	SG-	-2	Ambi	ent
tert-Butyl Alcohol	3.2		J 3.7		J <0.2	
Propene	230		170		0.65	
Dichlorodifluoromethane	<2		<2		0.45	
Chlorodifluoromethane	<2		<2		0.21	
Freon 114	<2		<2		<0.2	
Chloromethane	<2		<2		0.82	
Chloroethane	<2		<2		0.23	
Trichlorofluoromethane	<2		<2		0.21	,
Pentane	11		9.2		0.21	•
Acetone	520		650		10	
Hexane	14		12		<0.2	
2-Butanone	3,500		3,500		2.5	
Ethyl Acetate	<2		<2	-	<0.2	
Methyl Acrylate	<2		<2		<0.2	
Chloroform	<2		<2		<0.2	
1,1,1-Trichloroethane	<2		<2		<0.2	
Carbon Tetrachloride	<2		<2		<0.2	
1,2-Dichloroethane	<2		<2		<0.2	
Benzene	<2		<2		<0.2	
Isooctane .	<2		<2		<0.2	
Heptane	6.8	J	<2		0.82	J
Foluene	3.1	J	2.5	J	0.67	J
Octane	16		16		<0.2	
Tetrachloroethene	3.7	J	20		<0.2	
2-Hexanone	260		230		<0.5	
Ethylbenzene	2.4	J	<2		0.23	J
n/p-Xylene	7.3	J	6.2	J	0.67	J
o-Xylene	2.5	J	2.3	J	0.24	J
l-Ethyltoluene	2.5	J	2.6	J	<0.2	
Alpha Methyl Styrene	<2		<2		0.67	J
,2,4-Trimethylbenzene	2.5	J	3.1	J	<0.2	
,4-Dichlorobenzene	<2		<2		0.68	J


Notes:


All values listed in ppb(v) (parts per billion by volume).


J - Indicates laboratory estimated value


All soil gas and ambient air samples were analyzed in accordance with United States Environmental Protection Agency Method ETO-15.



















OTTED: 04 Oct 2007, 11:12am, JLubbers




PLOTTED: 14 Nov 2007, 11:51am, JLubbers




PLOTTED: 14 Nov 2007, 11:50am, JLubbers




LOTTED: 14 Nov 2007, 11:50am, JLubbers









Waste Manifests, Bills of Lading and Characterization Data

OCT-26-2007	1:
The State of the S	

D⊏C	KEGI	ت الاال)	
		r.u,	DOX	000

o-FM·L	RWMO	0051 REV. 7/99	Harrisb OFFICIAL PENN	urg, PA SYLVANI	A MANIF	EST FORM	·			
UN	IIFO	IRM HAZARDOUS	retor's US EPA ID No.		, Doc	lanifesi cumeni No.	2. Page 1 of	Information not require fequired by	d by Faderai le	id red border is nw but may be
1	NAS	STE MANIFEST NY R	000127		22303	A State	Manifest Document	Number	^	
3. Ger	ierator	GEM XOLK PURTS TABBUT	tment of Enviso	MUHIL	T COMES.	r friidh			<u>0544</u>	7
		PO Bar 206, Rade Si Rsy Brack, NY 12977					8. Stola		ha maneey s	g Tabeon St.
		r's Phone (578) ROT 1018 ATTW-MIKE	Molean	US EPA ID	Number		C. 51818	Trans. ID		
s. Tra	nsport O	or 1 Company Namo P-TECH Environmental Services. Inc		98	608	9753		<u>-AH</u>	-8559	- 1
7. Tra	nsport	ter 2 Company Name	8.	US EPA ID	Number			porter's Phone (Trans. ID	318) 76a-	1917
			10	. US EPA II	Number			\-AH		
9. De	_	od Facility Name and Site Addross		. 00				porter's Phone ()	
	€3 95	r CLE CHEM, TYC. 30 INDUSTRIAL DRIVE				MI 191 AA		Facility's ID		
	L	EWISDERRY, PA 17336	PAD	967	098	12. Conte	The second livery	ity's Phone (197.	129-17 N
1,1. 0	IS DOT	T Description (including Proper Shipping Name, Hazard (Class, and ID Number)			Na.	Туры	Total Quantity	Ųnit Wt/Voi	Waste No.
4	X	RQ, Waste, Flammable Liquid, N.O.5 UN1993, PG III (DOH)	i. (Acetone Ethyl (ERG	sicutate (A. 25)), I.,	KCK). Dr	E51 f 200	1	Dest Vall 2005
b.	X	Hazardony Waste Solid, N.O.S. (Acets PG 111	nie, Finyl Acedite (ERC), 9, RA: #171)	1077.	X	CL D	e e e e e e e e e e e e e e e e e e e		eovi.
C.										
							<u> </u>			
d.										
							76 311	ing Codes for Was	toe Listed Abo	Viii .
J, A	ddition	nal Descriptions for Materials Listed Above					A. nano		1	
		•					a.		6	
							 	Ð	ď	
145	Casalo	ai Handling Instructions and Additional Information					<u> </u>			
		a.) OPT641-A-FMI b.) OPT641-B-SSM	in case of Po# bedsiv2		er(jen	cy pleasi	CALL	op-tech a)	F 1-864-272	5 -6 750

16	GEN classi If practi	NERATOR'S CERTIFICATION: I hereby deci- illed, packed, marked and labeled and are in all respect flam a large quantity generator, I cardify that I have a ficable and that I have selected the practicable method in vironment; OR, if I am a small quantity generator, I ha	are that the contents of ts in proper condition to program in place to re- of treatment, storage, o	this consign or transport duce the vo disposal continuity	nment are f by nighway Jurna and t urrently ava mika my wa	ully and accurated according to appositely of waste allable to me whitely generation	ely duscrib splicable in generated ch minimiz and select	ed above by propo ternational and hal to the degroe I ha os the presont and the best waste ma	er shipping rea tional governm ve determined I future threat nagement me	me and arr) nent regulations. I to be economicall to human health and thod that is availabl
<u> </u>	10 IDG	o and that I can afford.		Signatur			٠,		MONTH	A DAY TEACH
	n.	and we will see he had	H SAMON	, - (a ,		د در هشد. ک <u>ل</u> و درگر هشد. کل	<u>(j </u>		7	17 19
17.	Print	ted/Typed Name		Signatur		A	21	A SERVICE AND A	MONTI	1 DAY YEAR
18.		ortor 2 acknowledgement of Receipt of Materiata 1ed/Typed Name		Signatur	θ ,				MONT	H DAY YEAR
16.	,			<u> </u>		·				
19.	Diacre	epancy indication Space								
20,		ily Owner or Operator: Certification of receipt of hazardo	ue materials covered by	this manife	st oxcept a	noted in item 1	9.	- Au	MONT	H DAY YEAR
-	Prin	ited/Typed Name		Signatul	~					1 1



ACKNOWLEDGEMENT OF NOTIFICATION OF HAZARDOUS WASTE ACTIVITY

09/16/2004

Region 2

This is to acknowledge that you have filed a Notification of Hazardous Waste Activity for the installation located at the address shown in the box below to comply with Section 3010 of the Res Conservation and Recovery Act (RCRA). Your EPA Identification Number for that installation appears in the box below. The EPA Identification Number must be included on all shipping manifor transporting hazardous wastes; on all Annual Reports that generators of hazardous waste, and owners and operators of hazardous waste treatment, storage and disposal facilities must file with lon all applications for a Federal Hazardous Waste Permit; and other hazardous waste managemen reports and documents required under Subtitle C of RCRA.

EPA I.D. NUMBER:

NYR000127266

INSTALLATION NAME:

GULF STATION FORMER

INSTALLATION ADDRESS:

STATE RD 37 COR OF CHATEAUGAY

& SALMON ST

FORT COVINGTON, NY 12937

MAILING ADDRESS:

PO BOX 296 RTE 86

NYSDEC

RAY BROOK, NY 12977

EPA Form 8700-12AB (4-80)

USEPA - REGION 2 RCRA Programs Branch 290 Broadway, 22nd Floor New York, NY 10007-1866

ATTN: RCRA NOTIFICATIONS

Tel: (212) 637-4106 Fax: (212) 637-3056

TO: GULF STATION FORMER

or Current Occupant

ATTN: MICHAEL MCLEAN

PO BOX 296 RTE 86

NYSDEC

RAY BROOK, NY, 12977

-- LABORATORY ANALYSIS REPORT --

New York State DEC - Region 5

Raybrook, NY

Sample ID:

Drum #1

LSL Sample ID:

0411683-001

Location: Sampled:

OP-11588

07/12/04 9:00

Sampled By: MM

	Matrix: SHW as Reed			Ргер	Analysis	Analyst
_	cal Method	Result	Units	Date	Date & Time	Initials
	Analyte					
	M E502-84 Ignitability	33	Degræs C		7/26/04	ΝĽ
	Ignitability	33	Doğumu o			
) EPA	8260B		_		7/26/04	LEF
	Acetone	12000	mg/kg		7/23/04	LEF
	Benzene	<20	mg/kg		7/23/04	LEF
	Bromodichloromethane	<20	mg/kg		7/23/04	LEF
	Bromoform	<20	mg/kg		7/23/04	LEI
	Bromomethane	<20	mg/kg		7/23/04	LEF
	2-Butanone (MEK)	<50	mg/kg		7/23/04	LEI
	Carbon disulfide	<20	mg/kg		7/23/04	LEI
	Carbon tetrachloride	<20	mg/kg		7/23/04	CEI
	Chiorobenzene	<20	mg/kg		7/23/04	LE
	Chloroethane	<20	mg/kg		7/23/04	LE
	Chloroform	<20	mg/kg		7/23/04	LE
	Chloromethane	<20	mg/kg		7/23/04	LE
	Dibromochloromethane	<20	mg/kg		7/23/04	LE
	1,1-Dichloroethane	<20	mg/kg		7/23/04	LE
	1,2-Dichloroethanc	<20	mg∕kg		7/23/04	LE
	1,1-Dichloroethene	<20	mg/kg		7/23/04	LE
	1,2-Dichlorocthene, Total	<20				LE
	1,2-Dichloropropane	<20	-		7/23/04	LI
	cis-1.3-Dichloropropene	<20	mg/kg		7/23/04	LE
	trans-1,3-Dichloropropeno	<20	• -		7/23/04	LE
	Ethyl benzene	<20			7/23/04	LE
	2-Hexanone	<50			7/23/04	LE
	Methylene chioride	<20	mg/kg		7/23/04	Li
	4-Mcthyl-2-pentanone (MIBK)	420	mg/kg		7/23/04	LE
	Styrene	<20	mg/kg		7/23/04	
	1,1,2,2-Tetrachloroethane	<20	mg/kg		7/23/04	L
	Tetrachloroethene	<20	mg/kg		7/23/04	LE
	Toluene	220	mg/kg		7/23/04	LE
	1,1,1-Trichloroethane	<20	mg/kg		7/23/04	Li
	1,1,2-Trichioroethane	<20	mg/kg		7/23/04	Li
	Trichloroethene	<20) mg/kg		7/23/04	Lì
	Vinyl chloride	<20) mg/kg		7/23/04	L
	Xylenes (Total)	62	2 mg/kg		7/23/04	Li
	Surrogate (4-BFB)	110) %R		7/23/04	1.1
	Surrogate (Tol-d8)	9:	5 %R		7/23/04	L
	E (1.2-DCA-d4)	10-			7/23/04	L
This car	nple was also found to contain 3200 mg/kg of Ethy	I Acetate, 60000 mg/kg of	Isapropyl Alcohol a	ind 5700 mg/kg of i	-Butanol.	
(1) EP	A 8270 TCL Semi-Vol	<0.	S mg/kg	7/19/04	7/22/04	Cl
	Acenaphthene	<0. <0.	-	7/19/04		CI
	Acempohthylene	~U,	- コリラケッ告			

A 8270 TCL Semi-Voi		7/19/04	7/22/04	CRT
Acenaphthene	<0.5 mg	E VE		CRT
Acenaphthylene	<0.5 mg	g/kg 7/19/04	7/22/04	
* *	<0.5 mg	g/kg 7/19/04	7/22/04	CRT
Anthracene	<0,5 m	g/kg 7/19/04	7/22/04	CRT
Benzo(a)anthracene			7/22/04	CRT
Benzo(b)(luoranthene		0.7.6	7/22/04	CRT
Benzo(k)fluoranthene	<0.5 mg	g/kg 7/19/04	1122/04	OILI
• •				

Life Science Laboratories, Inc.

Page 2 of 4

Date Printed:

7/28/04

LABORATORY ANALYSIS KEPUKI --

Raybrook, NY New York State DEC - Region 5

Sample ID: Drum #1

LSL Sample ID:

0411683-001

Location:

OP-11588

Sampled:	07/12/04 9:00	Sampled By: MM				
Sample Matri				Prep	Analysis	Analyst
Analytical Me		Result	Units	Date	Date & Time	Initials
Analy		ALLO				
	TCL Semi-Vol	<0.5	mg/kg	7/19/04	7/22/04	CRT
	ghi)perylene	<0.5	mg/kg	7/19/04	7/22/04	CRT
	(а)ругепс	<0.5	mg/kg	7/19/04	7/22/04	CRT
4-Bron	nophenyl-phenylether	<0.5	mg/kg	7/19/04	7/22/04	CRT
Butyib	enzylphthalate	<0.5	mg/kg	7/19/04	7/22/04	CRT
Carbaz	zole	<0.5	mg/kg	7/19/04	7/22/04	CRT
	roanlline	<0.5	mg/kg	7/19/04	7/22/04	CRT
bis(2-C	Chloroethoxy)methane	<0.5	mg/kg	7/19/04	7/22/04	CRT
• .	Chloroethyl)ether	<0.5	mg/kg	7/19/04	7/22/04	CRT
bis(2-C	Chloroisopropyl)ether	<0.5	mg/kg	7/19/04	7/22/04	CRT
4-Chlo	oro-3-methylphenol		-	7/19/04	7/22/04	CRT
2-Chlo	Dronaphthalene	<0,5 <0.5	mg/kg	7/19/04	7/22/04	CRT
2-Chic	orophenol		mg∕kg a/lst	7/19/04	7/22/04	CRT
4-Chlo	orophenyl-phenylether	<0.5 <0.5	mg/kg mg/kg	7/19/04	7/22/04	CRT
Chrys	sen e			7/19/04	7/22/04	CRT
Diben	z(a,h)anthracene	<0.5	mg/kg	7/19/04	7/22/04	CRI
Diben	zoluran	<0.5	mg/kg	7/19/04	7/22/04	CRI
Di-n-k	butyiphthalate	<0.5	mg/kg	7/19/04	7/22/04	CR1
1,2-DI	ichlorobenzenc	<0.5	-	7/19/04	7/22/04	CR?
1,3-Dí	ichlorobenzene	<0.5		7/19/04	7/22/04	CR
1,4-Di	ichlorobenzenc	<0.5		7/19/04	7/22/04	CR ²
3,3'-0	Dichlorobenzidine	<1	mg/kg	7/19/04	7/22/04	CR'
2,4-D	ichlorophenol	<0.5		7/19/04	7/22/04	CR.
	ylphthalate	<0.5		7/19/04	7/22/04	CR.
2,4-D	Imethylphenol	<0.5	-	7/19/04	7/22/04	CR'
	thylphthalate	<0.5		7/19/04	7/22/04	CR'
2,4-D	Initrophenol	<1	• -	7/19/04	7/22/04	CR'
2,4-D	dinitrotoluene	<0.5		7/19/04	7/22/04	CR'
-	initrotoluene	<0.5		7/19/04		CR
	octylphthalate	<0.5	•			CR
	-Ethylhexyl)phthalate	<0.5		7/19/04 7/19/04		CR
	ranthene	<0.9	* .	7/19/04 7/19/04		CR
Fluor	rene	<0.:		7/19/04		CR
Hexa	achlorobenzene	<0.:	* *	7/19/04		CR
Hext	achiorobutadiene	<0.		7/19/04		CR
Hexa	achlorocyclopentadiene	<		7/19/04		CR
Hexi	achioroethanc	<0.		7/19/04		CR
Inde	eno(1,2,3-c,d)pyrene	<0.		7/19/04		CF
Laop	horone	<0.		7/19/04		CF
	ethyl-4,6-dinitrophenol	· · · · · · · · · · · · · · · · · · ·		7/19/04		CF
	ethylnaphthalene	<0.		7/19/04		CF
	ethylphenol (o-Cresol)	<0.	•			CF
	(ethylphenol (p-Cresol)	<0.		7/19/04		CF
	hthalene	<0.		7/19/04		CI
-	Itroaniline	<0.		7/19/04		Ci
	ltroaniline		1 mg/kg	7/19/0-		CI
	itroaniline		i mg∕kg	7/19/0-		CI
	robenzene	•	() mg/kg	7/19/0	4 1162104	Page 3 c

Life Science Laboratories, Inc.

Date Printed:

7/28/04

-- LABORATORY ANALYSIS REPURI

New York State DEC - Region 5

Raybrook, NY

LSL Sample ID:

0411683-001

Sample ID:

Drum#1

2,4,6-Trichlorophenol

OP-11588

Location: Sampled:

07/12/04 9:00

Sampled By: MM

Sample Matrix: SHW as Recd Analytical Method	al Method				Analyst Initials
Analyte	Result	Units	Date	Date & Time	
2-Nitrophenol (o-Nitrophenol) 4-Nitrophenol N-Nitrosodiphenylamine N-Nitroso-di-n-propylamine Pentachlorophenol Phenanthrene Phenol Pyrene 1,2,4-Trichlorophenol	<0.5 <0.5 <0.5 <1 <0.5 <0.5 <0.5 <0.5 <0.5		7/19/04 7/19/04 7/19/04 7/19/04 7/19/04 7/19/04 7/19/04 7/19/04 7/19/04	7/22/04 7/22/04 7/22/04 7/22/04 7/22/04 7/22/04 7/22/04 7/22/04 7/22/04 7/22/04 7/22/04	CRT

ATTENY!	<u>en. 13</u> ,	.2005.3s						OF LADING UNLES	S MARKE	₩0.9E	<u>32</u>)T. P	.4
	*,		•	SIK		GINAL — NOT		ADING		Shipper	r No	MG-5K-00
				_						Carrier	No	6A-166
Page :	101	1			OP-T	ECH Envir	onmenta	Services Inc		ſ	Date	Hi-06
					(Name	of carrier)		(SCAC)			• •	
On Collad on Colive	ry shipmente, (he leners*COD* n	niej abbout poloto cour	edura, s. poutôge	e organism pr	rowided in Norm 450. Sec. 1,	FROM: Shipper	Town of Fort	zoa justa	ו		
TO: Consignes _		OP-TE	CH Enviro	omenta)	Service	4	Street	Come of Salm	on & Ch	areans	ay St	
Street		370 R	T 34				City Fort Covinctors NY				12920	
City	War	verly _{Stat}		N.Y.	Zip Code	14892		gency Contact Tel, No.				225-6750
Roule				مخاولين الكافعة	<u> </u>						ehicle lumber	
No. of Units & Container Type	_a H	M Proper UN or	Shipping Name, i NA Number, Pac	BASI Hazard Class King Group	C DESCRIP or UN or	PTION NA Number, Proper & Hazard Class, Packir	Shipping Name, ng Group	TOTAL QUANTITY (Weight, Volume, Gallons, etc.)	(Su	IGHT blect to rection)	RATE	CHARGES (For Carder Use Only)
	35		APA No	- 20T I		d Material		Est. 160	6)			
			draulie eil		-			2.114				•
 		_									_	
		Po	**									
	_ -	_										E.U
	_ _					•						N/s
Nate (1) Whate t	na tula is dup	encent on value, a	NDERED	and I state	by ductore the	eld to smelled on the	REMIT C.O.D. TO: ADDRESS		· · · · · · · · · · · · · · · · · · ·			•
egreed or declared va- to be not exceeding . (2) Where the applica	alus of the prop able lariff provi	ath is present a fin	the property, as follows discally stated by the si fallon of the contacts to	hipper descrip and s inhilly debelled	iad above by in re-ciassified. d/placarded, ar	fully and accurately a proper shipping name packed. Marked and are in all respects in Vansport according to	COD	Amt: \$		C.O.D. F PREPAII COLLEC	D 🖽	
release the confer's to the escart provided by (3) Commodifies req	inguista etaetan A ancy bionyalor Inguista etaetan	a avalue, ine cent 12. Ase NMFC bei or additional com	or attention to handle	find or pppiloz		tenol and nadonat	consignor shall sign The carrier at	ion 7 of the conditions, it this sh naighner without recourse on the n the indicating statement: with not make delivery of this sh		TOTAL CHARG	353 \$	
Section 2(e) of hem :	360, Bills of La	ding, Freight Bills	ure cale iranaportalion and Scelements of Ch for a list of such articl	Arces		Signalura	bakweld of motion	and all other beviu) charges. (Blanuare of Construct)		eucebt	FREIGHT C HT PREPAID I when box du checked	Chaok box if charges are to be covied
FIEC describe marked, this corp its usus costilant	PEIVED, subject ed above in est i, consigned, en if cart as meanin if place of delive don. Il le mutusi	to the ciqualification parent good arder, or descipat as indic g any parson or co by a sold dostinat by agreed as to ear	e and innthe in effection i alcapt as noted (capter sized above which said of sportation in poseabed on, if an its round, when in capted of ell or any of	the date of the ket the And somition carrier (the word of the property to when to daily or to the property or	an all on such body arounds counted of agents paint incom- country paint incom- country part of Pri	eding, the property chipges wateroom, priese to carry to misor throughous chipges to carry to misor to said the country to said	enipmens.	as to acco party at any time interest be autified that he is kimiliar with all acconditions are hereby egreed to b	arms on ball on i	and conditions	in the poveming of	labelification and
SHIPPER	/	To	en of Fort C	cvinetor			CARRIER		OP-TE	CH		
PER /	inle	() ————————————————————————————————————	res				PER	Dung	-6	2 som	M	
0							DATE	6	1-1	1-0	40	

Permanent post-office address of shipper.

ATTENTION SHIPPERS! FREIGHT CHARGES ARE PREPAID ON THIS BILL OF LADING UNLESS MARKED COLLECT. This Memorandum is an acknowledgment that a Bill of Lading has been issued and is not Original

inis wen	ioranc	Bill of Lading, nor intended solely fo	a copy or duplicate, covering the prop r filing or record.	erty named h	erein, and is		Shipper No	o	MOTERIA
							Carrier No	o	6A-166
Page	_ of	Quintify.	OP-TECH Environm ((Name of carrier)	stal Ser	vices, Inc. (SCAC)		Date	e	3/13/86
On Collect on Delivery sh	nipments, the lett	ers"COD" must appear before consignee	's name or as otherwise provided in Item 430, Sec.1.	FROM: Shipper	ormer Martin's	Guit	(Kleinfe	dia)	
TO: Consignee		rial OH Tank Se	rvice Inc.	Street	Corner of Chate	augay	r & Salu	i di S	
Street		y Kond		City	art Covington	Stat	e I	₹¥ Zip	Code
CityO	riskanj	State TTZ	Zip Code 13474	24 hr. Eme	ergency Contact Tel. No.	income.	309-225	-6750	
Route							Vehic Numb		148
No. of Units & Container Type	HM	Proper Shipping Name, Haza UN or NA Number, Packing	BASIC DESCRIPTION rd Class UN or NA Number, Proper S Group Hazard Class, Packir	hipping Name, ng Group	TOTAL QUANTITY (Weight, Volume, Gallons, etc.)	(Su	EIGHT bject to rection)	RATE	CHARGES (For Carrier Use Only)
· Para de la companya		Non-DOT, Non	KCRA Regulated Liqu	ii I	let 300 gallons				
	-	(gasolina cont. w	ater from tank renoral)		700 RB				
	_	P.O. # M65	kooo3-4552	c					· · · · · · · · · · · · · · · · · · ·
PLAC	ARDS	TENDERED: `	YES NOX	REMIT	,			l	
specifically in writing the a agreed or declared value o o be not exceeding	agreed or declare of the property is	on value, shippers are required to state ad value of the property, as follows: "The hereby specifically stated by the shipper_per	consignment are fully and accurately described above by the proper shipping name and are classified, packed, marked and labelled/placarded, and are in all respects in	C.O.D. TO: ADDRESS	Amt: \$		C.O.D. FEE: PREPAID COLLECT	\$	
sheet a release or a value declaration by the chipper and the chipper does not proper condition for transport ac				delivered to the c consignor shall sign The carrier s	bject to Section 7 of the conditions, if this shipment is to red to the consignee without recourse on the consignor, nor shall sign the following statement: he carrier shall not make delivery of this shipment with ant of freight and all other lawful charges. (Signature of Consignor)		is to be TOTAL CHARGES \$		
described ab marked, cons this contract : its usual plac	ove in epparent of signed, and desting as meaning any p se of delivery at s	good order, except as noted (contents and ned as indicated above which said carrier person or corporation in possession of the aid destination, if on its route, otherwise to	s of the issue of this Bill of Lading, the property condition of contents of packages unknown, (the word carrier being understood throughout property under the contract) agrees to carry to deliver to another carrier on the route to said property over all or any portion of said route to	hereunder shal shipment. Shipper her	i as to each party at any time interested i be subject to all the bill of lading term eby certifies that he is familiar with all the and conditions are hereby agreed to by the	s and conditions terms	ins in the governing and conditions in the	classification governing cl	on the date of assification and

SHIPPER Town of Fort Cov	ngion	CARRI	IER OP-TECH Environmental Service	z,Ār
PER MILARIE / JUST	for files And and	PER	huland Bird	<u>//</u>
	On behalf of FC	DATE	8/15/06	L
Permanent post-office address of shipper.	PRIVED ON ROOKLED PAPER USING SOYSEAN RISK SOY INKL.	1900 Berlin - Arriva III - Arriva III - Arriva III - Arriva II - Arriva II - Arriva II - Arriva II - Arriva I	STYLE CF360-4 © 2003 LABEL ASTER (800) 621-5808 www.labelmaster	er.com

ATTENTION SHIPPERS!

Permanent post-office address of shipper.

FREIGHT CHARGES ARE PREPAID ON THIS BILL OF LADING UNLESS MARKED COLLECT.

This Memorandum is an acknowledgment that a Bill of Lading has been issued and is not Original Bill of Lading, nor a copy or duplicate, covering the property named herein, and is

				intended solely for	filing or record.	orty manne		,	S	hipper N	0	Mana
									(Carrier N	0	64-166
Page	guranja	of	Testrada		OP-TECH Environme	e in c						2/15/06
·		_			(Name of carrier)			(SCAC)		721 P. A. C.	A vice vice vice as a second	
On Collect on De	livery sh	ipments, th	e letters	"COD" must appear before consignee's	name or as otherwise provided in Item 430, Sec.1.	FROM: Shipper	F.	rne Marin'		c/o Ki	dnīdi	ic, inc.)
TO: Consignee		indi	ıstı	ial Oil Tank Sæ	vice Inc.	Street	Ž!	atellighway i	7			
Street		170	T) jest	i i i i i i i i i i i i i i i i i i i		City	T'O	rtCovington	State	*	Zip	Code
City	O	riska		State	Zip Code	24 hr. E	Emerç	ency Contact Tel. No.	about the second	00-224	-175 0	
										Veh Num	icle c	348
No. of Uni & Container∃		H	W	Proper Shipping Name, Hazar UN or NA Number, Packing	BASIC DESCRIPTION d Class Group OF Hazard Class, Packing	Shipping Na ng Group	ımė,	TOTAL QUANTITY (Weight, Volume, Gallons, etc.)	WEI (Subj Corre		RATE	CHARGES (For Carrier Use Only)
7					RCRA Regulated Liq and with petroleum from			(4)) E Segallon	5			
			- in the second	I TO ME ATT. F. CHEST MENTALS	istica parte frantistament er en	a. Linders.	# W.					
				P.O.# M6SK	0003-4552	ė.	TO SERVICE AND ADDRESS OF THE PERSONS ASSESSED.					
			***************************************				200000	•				
	~								· ·			
Note — (1) Wh	ere the i	ate is depe	endent o	TENDERED: \(\) In value, shippers are required to state	I hereby declare that the contents of this consignment are fully and accurately							
agreed or declar to be not exceed	ed value ina	of the prop	erty is h	value of the property, as follows: "The ereby specifically stated by the shipper pererecity a limitation of the carrier's liability	described above by the proper shipping name and are classified, packed, marked and labelled/placarded, and are in all respects in	COL)	Amt: \$		C.O.D. FEE PREPAID COLLECT	<u>\$</u>	
absent a releason release the carrio the extent provid	e or a va er's liabili led by su	alue declara ity or declar ch provisior	ation by e a valu ns. See	the shipper and the shipper does not e, the carrier's liability shall be limited to NMFC Item 172.	proper condition for transport according to applicable international and national governmental regulations.	Subject delivered to consignor s	the cor	on 7 of the conditions, if this ship ssignee without recourse on the the following statement: all not make delivery of this shi	consignor, the	TOTAL CHARGE		
stowing must be Section 2(e) of i	so mar tem 360	ked and pa , Bills of La	ckaged ding, Fi	ional care or attention in handling or as to ensure safe transportation. See eight Bills and Statements of Charges Conditions for a list of such articles.	Signature	payment of	freight a	ind all other lawful charges. (Signature of Consignor)		FREIGHT except wh right is ch	PREPAID	CHARGES Check box if charges are to be collect
me thi	scribed a arked, co	bove in app nsigned, and	arent go d destin	ood order, except as noted (contents and ed as indicated above which said carrier	e of the issue of this Bill of Lading, the property condition of contents of packages unknown), the word carrier being understood throughout property under the contract) agrees to carry to deliver to another carrier on the route to said property over all or any portion of said route to	hereund shipmen Shipt	er shall i it. oer heret	is to each party at any time interest be subject to all the bill of lading te by certifies that he is familiar with all d conditions are hereby agreed to by	rms and condition the lading terms a	s in the governi nd conditions in	ng classificatio the governing (on on the date of classification and
SHIPPE	٦	Tow	M j	f Fort Covingto		CARF	RIER	OF-IIC	H	ronni -7		Services, Inc
DED /		Ż	14			PER			HR.	de la company	Arrent Print	//

DATE

STYLE CF360-4 © 2003 LABEL ASTER ® (800) 621-5808 www.labelmaster.com

PRINTED ON NECTCLED PAPER SOY INK

ATTENTION SHIPPERS!

This Memorandum

FREIGHT CHARGES ARE PREPAID ON THIS BILL OF LADING UNLE

is an acknowledgment that a Bill of Lading has been issued and is not Original Bill of Lading, nor a copy or duplicate, covering the property named herein, and is intended solely for filing or record.

SS	MARKED COLLEC	CT.		٠,
	Shipper N	lo	MCGK0003	_
	Carrier N	lo	64-166	
	Da	ite	8/15/06	-
M d	s Gulf (vo Ki	dnfo	is is a	=
7	7			
	State	Ž	Code	
1 0.	1.800.22	5-675	e de la companya de l	-
	Veh Nun			_
Y	WEIGHT (Subject to Correction)	RATE	CHARGES (For Carrier Use Only)	
g e	i i i i i i i i i i i i i i i i i i i			
				-
and the same				
STOCK OF STOCK				
	CODEE	Difference		

Page of in OP-TECH Environmental Services. Inc. (Name of carrier) On Collect on Delivery shipments, the letters "COD" must appear before consignee's name or as otherwise provided in Item 430, Sec. 1. Former Mari TO: OF-TICH Environmental Services. Inc. Consignee Street State Figure 7 14 Old River Road Fort Covingto Street Minesena Zip Code 13662 City 24 hr. Emergency Contact Tel. N Route BASIC DESCRIPTION No. of Units **TOTAL QUANTIT** Proper Shipping Name, Hazard Class UN or NA Number, Proper Shipping Name, UN or NA Number, Packing Group

UN or NA Number, Packing Group HM& Container Type (Weight, Volume, Gallons, etc.) Non DOT, Non RCRA Regulated Material Tank 200 P (omty & desired setroloum 757) PLACARDS TENDERED: YES REMIT I hereby declare that the contents of this Note — (1) Where the rate is dependent on value, shippers are required to state ADDRESS specifically in writing the agreed or declared value of the property, as follows: "The consignment are fully and accurately described above by the proper shipping name agreed or declared value of the property is hereby specifically stated by the shipper PREPAID and are classified, packed, marked and COD .. per labelled/placarded, and are in all respects in (2) Where the applicable tariff provisions specify a limitation of the carrier's liability Amt: \$ COLLECT proper condition for transport according to absent a release or a value declaration by the shipper and the shipper does not applicable international and national Subject to Section 7 of the conditions, if this shipment is to be release the carner's liability or declare a value, the carrier's liability shall be limited to delivered to the consignee without recourse on the consignor, the consignor shall sign the following statement: The carrier shall not make delivery of this shipment without payment of freight and all other lawful charges. governmental regulations. the extent provided by such provisions. See NMFC Item 172. **CHARGES** (3) Commodities requiring special or additional care or attention in handling or FREIGHT CHARGES
FREIGHT PREPAID Check box stowing must be so marked and packaged as to ensure safe transportation. Sea Section 2(e) of item 360, Bills of Lading, Freight Bills and Statements of Charges Check box if charges except when box at right is checked and Section 1(a) of the Contract Terms and Conditions for a list of such articles. Signature (Signature of Consignor)

RECEIVED, subject to the classifications and tariffs in effect on the date of the issue of this Bill of Lading, the property described above in apparent good order, except as noted (contents and condition of contents of packages unknown), marked, consigned, and destined as indicated above which said carrier (the word carrier being understood throughout this contract as meaning any person or corporation in possession of the property under the contract) agrees to carry to its usual place of delivery at said destination, if on its route, otherwise to deliver to another carrier on the route to said destination. It is mutually agreed as to each carrier of all or any of, said property over all or any portion of said route to

destination and as to each party at any time interested in all or any said property, that every service to be performed horeunder shall be subject to all the bill of lading terms and conditions in the governing classification on the date of shipment.

Shipper hereby certifies that he is familiar with all the lading terms and conditions in the governing classification and the eald terms and conditions are hereby agreed to by the shipper and accepted for himself and his assigns.

SHIPPER Town of Fort Covington OP-TECH Lavironmental Services, Inc CARRIER PER Fit 1864 House.
On behalf of FC INC. **PER** 3/15/06 DATE

Permanent post-office address of shipper.

PRINTED ON RECYCLED PAPER PRINTED WITH SOY INK.

STYLE CF360-4 © 2003 LABELI ASTER (800) 621-5808 www.labelmaster.com

APPENDIX B

KAS's Asbestos Inspection Report

ASBESTOS INSPECTION REPORT MARTIN'S GARAGE (GULF)

OCTOBER 5, 2005

PROJECT # 309050038

PREPARED FOR:

OP-TECH ENVIRONMENTAL SERVICES, INC. 14 OLD RIVER ROAD MASSENA, NY 13662



P.O. BOX 787 WILLISTON, VT 05495 (802) 383-0486

TABLE OF CONTENTS

	Page
1. INSPECTION SUMMARY	1
2. INSPECTION METHODS	1
3. NEW YORK STATE REGULATIONS - INDUSTRIAL CODE RULE 56.	1
4. CERTIFICATION/ACCREDITATION	2
5. INSPECTION RESULTS	2
6. OBSERVATIONS AND RECOMMENDATIONS	2
TABLE 1 - SUMMARY INSPECTION RESULTS	4
APPENDIX 1 - CERTIFICATIONS	
APPENDIX 2 - LABORATORY ANALYSIS REPORTS	
APPENDIX 3 - SITE SKETCHES	

1. INSPECTION SUMMARY

Martin's Gulf located at the intersection of Chateguay Street and Salmon Street in Fort Covington, NY, was inspected for the presence of asbestos containing materials (ACM) on September 29, 2005. The inspection was conducted to reasonably determine if ACM were present prior to building demolition. The inspection/sampling included obtaining bulk samples from suspect materials throughout the building. All areas of the structure were inspected including the exterior. The interior of the building was fully accessible. Destructive sampling techniques such as breaking into walls were used in this inspection.

The inspection determined that no ACM exists in the building. ACM is defined as materials that have asbestos content equal to or greater than 1% by weight,

Table 1 summarizes the inspection results.

2. INSPECTION METHODS

This asbestos site inspection was conducted by an EPA accredited, State of New York certified, Asbestos Inspector/ Management Planner generally in accordance with AHERA inspection guidelines and generally accepted procedures. Bulk sample analysis was conducted by EMSL Analytical, Inc. of Westmont, NJ. The inspector possessed adequate experience, training and education to recognize potential ACM and to collect bulk samples of suspect materials for laboratory analysis.

In accordance with the workscope for this project, bulk samples were collected and analyzed from each suspect material found. Bulk samples of suspect ACM were analyzed for asbestos content using PLM NYS 198.1 friable for friable materials and PLM NYS 198.6/ TEM NYS ELAP Method 198.4 for nonfriable organically bound (NOB) materials.

3. NEW YORK ASBESTOS REGULATIONS INDUSTRIAL CODE RULE 56

New York Industrial Code Rule 56, details the procedures, regulations, certifications and licenses required when disturbance of asbestos containing materials occurs in the State of New York. In essence, any company, individual or organization that disturbs asbestos containing materials or provides asbestos consulting or laboratory services must be certified/ licensed by the State of New York. Personnel who conducted the inspection, bulk sample collections and laboratory analysis were properly certified by the State of New York and also possess current EPA approved training in asbestos site inspections and asbestos laboratory analysis. KAS corporate and individual inspector licenses and certifications are contained in Appendix 1.

4. CERTIFICATION/ACCREDITATION

Inspection Location: Martin's Gulf, Chateguay and Salmon Streets, Ft Covington, NY

Inspection Date: September 29, 2005

Buildings Inspected: A greater than 50 year old wood frame single story former service station with two maintenance bays. Approximately 1,000 square foot footprint.

Inspector Certification/Accreditation:

The person who conducted the inspection/bulk sampling of the facility holds the following asbestos handling certificate:

Inspector/ Management Planner:

Peter Schuyler:

New York Asbestos Handling Certificate AH-90-06755

Expires 08/06

Signature:

KAS, Inc. NYS Asbestos Handling License 05-0787.

Asbestos bulk samples have been analyzed by EMSL Analytical of Westmont, NJ, NYS NY-ELAP #10872 and NY-ELAP #10896.

5. INSPECTION RESULTS

Specific results of the sampling and analysis and visual inspection are contained in Table1. Laboratory results are included in Appendix 2. Site sketch is contained in Appendix 3. No asbestos containing materials were detected in the building, see Table 1.

6. OBSERVATIONS AND RECOMMENDATIONS

It is reasonably believed that no asbestos containing materials exist in the building inspected.

The building consists of a one-story older wood frame structure that appears to have always been used as a service station/ garage. It has two service bays and a small office area with attached bath room. It is currently abandoned and in poor repair. Historical heating appears to have been wood/ coal and more recently forced hot air. Uninsulated hot air ducts remain but no other heating equipment remains. The floors of

the entire structure were cement with no evidence of former flooring such as floor tiles or sheet flooring. Only three of the dozen or so windows in the building contained window glaze and it was found to be asbestos free. Insulation that was observed was fiberglass. Walls in the building were mostly sheetrock with some plywood walls also present. The roof was covered with one type of shingles that also existed in a pile behind the building on the ground. "Tar" paper existed under the singles and under wood siding. The two "tar" papers were considered separate homogeneous materials.

TABLE 1 - INSPECTION RESULTS MARTIN'S GULF, FT COVINGTON, NY

SAMPLE#	MATERIAL	ANALYTICAL RESULTS
1, 2, 3 under wood siding	"tar" paper	not asbestos containing
4, 5, 6 roof and debris pile	shingle	not asbestos containing
7, 8, 9 roof and debris pile	"tar" paper	not asbestos containing
10, 11, 12 interior walls/ ceiling	sheet rock/ joint compound	not asbestos containing
13, 14, 15 windows	window glaze	not asbestos containing

Notes:

1, -1, 2, ... - sample number (located on site sketch Appendix 3)

APPENDIX 1 CERTIFICATIONS

STATE OF NEW YORK - DEPARTMENT OF LABOR ASBESTOS CERTIFICATE



PETER SIGCHUYLER CLASSIEXPIRES D IN BP (08/06) - E MGP (\08/06) G SUPR(\08/06) | PD (\08/08)

MUST BE CARRIED ON ASBESTOS PROJECTS

STATE OF NEW YORK - DEPARTMENT OF LABOR DIVISION OF SAFETY AND HEALTH

License and Certificate Unit BUILDING 12, STATE CAMPUS ALBANY, NY 12240 ASBESTOS HANDLING LICENSE

Contractor: KAS, INC.

P.O. BOX 787

WILLISTON, VT 05495

LICENSE NUMBER: 05-0787

DATE OF ISSUE: 8 /17/2005

EXPIRATION DATE: 8/31/2006

Business Addres

929 Harvest Lanc

Williston, VT 05495

Duly Authorized Representative: PETER SCHUYLER

This hoense has been issued in accordance with applicable provisions of Article 30 of the Labor Law of New York State and of the New York State Codes, Rules and Regulations (12 NYCRR Part 56). It is subject to suspension of revocation for a (1) serious violation of state, federal or local laws with regard to the conduct of an asbestos project, or (2) demonstrated lack of responsibility in the conduct of any job involving aspestos or aspestos material,

This license is valid only for the contractor named above and this license or a photocopy must be prominently displayed at the asbestos project worksite. This license verifics that all persons employed by the licensee on an asbestos project in New York State have been issued an Asbestos Certificate, appropriate for the type of work they perform, by the New York State Department oflabor

SH 432 (6-03)

Anthony Germano, Director FOR THE COMMISSIONER OF LABOR

APPENDIX 2 LABORATORY ANALYSIS REPORTS

AM | **From: 8568581189 | To**: <**1**

To: <None>

Page: 2/5

NO.425 Date: 10/4/2005 5:08:37 PM P.12

ERSL Arabythal, bio.

Africa, 1890, 2004, 2009 - Fee, 1886, 281, 4880 - Entrito general 2800, no

Ann: Amy Gurney KAS, Inc. P.O. Box 787 Williston, VT 05495

Customer ID: Customer PO: KAS162 309050038

Received:

09/30/05 11:06 AM

EMSL Order:

040519723

Fax:

(802) 383-0490

Phone: (802) 383-0486

EMSL Proj:

Analysis Date:

2002/E/01

Project: 309060038/MARTINS GARAGE

Report Date;

10/4/2005

Asbestos Analysis of Non-Friable Organically Bound Materials by PLM via the NY State ELAP 198.6 Method

SAMPLE ID	DESCRIPTION	APPEARANCE	% MATRIX MATERIAL	% Non-Asbestos Fibers	ASBESTOS TYPES
1 0405187725-0001	UNDER WOOD SIDING	Black Non-Fibrous Homogeneous	100.0	None	Inconclusive: No Asbestos Detected
2 010510728-0002	UNDER WOOD SIDING	Black Non-Fibrous Homogeneous	100.0	None	Incondusive: No Asbestos Cetestad
3 040518723-0009	UNDER WOOD SIDING	Black Non-Fibrous Homogeneous	100.0	None	Inconclusive: No Asbestas Detected
4 D40518723-0004	ROOF	Black Non-Fibreus Homogeneous	100,0	Nane	Inconclusive; No Asbestes Defected
5 040518729-0005	ROOF	Black Non-Fibrous Homogeneous	100.0	None	Inconclusive: No Asbestor Derected
6 040518725-0000	RODF	Black Non-Fibraus Homogeneous	100.0	None	Inconclusive: No Asbestos Detected
7 040516720-0007	ROOF	Black Non-Fibrous Homogeneous	100.0	None .	Incondusive: No Asbestes Detected
8 049\$18729-000\$	ROOF	Black Non-Fibrous Homogeneous	100.0	None	Inconclusive: No Asbestos Detected
9 049518723-6009	ROOF	Black Non-Fibraus Hamogeneous	100,0	None	Incondusive: No Asbestos Delected

VT CERT# PB548328

Analyst(s)

Nancy Staiter (9)

Strade Dayed

Stephen Siegal, Clili or other approved signatory

*Pointzed Light Microscopy (PLM) is not commission which in detecting absolute in fiber covarings and similar non-frields organization. Cumitisfied Transmission Electron Microscopy is currently the only method that can be used to determine if this material can be considered or maked as non-anisotice containing. The test results contained within frite report meet the requirements of MELAC unless observed above and may not be reported according to the complete containing and may not be reported according to the report relates only to the complete collections the report method in testing and missions.

ACCREDITATIONS: A NA #100108, NVLAP #101048-0 and NY STATE ELAP #10872

Page: 2/5

NO.425 Date: 10/4/2005 5:29:53 PM

EMSL Analytical, Inc.

1987 Harbour Miller Willesterweit, Mit Control

Phys. (868) 200-4200 - Smally progress28283

Atn: Amy Gurney KAS, Inc. P.O. Box 787

Williston, VT 05495

309050038/MARTINS GARAGE

Customer PO:

Customer ID:

309050038

KASI62

Received:

09/30/05 11:05 AM

EMSL Order:

040518723

Fax:

(802) 383-0490

Phone: (802) 383-0486

EMSL Proj: Analysis Date:

10/4/2005

Report Date:

10/4/2005

Asbestos Analysis of Non-Friable Organically Bound materials by Transmission Electron Microscopy via NYS ELAP Method 198,4

SAMPLE ID	DESCRIPTION	APPEARANCE	% MATRIX MATERIAL	% NON-ASBESTOS FIBERS	A	SBESTOS TYPES	% total Asbestos
1 0405(8723-5001	UNDER WOOD SIDING	Black Non-Fibrous Homogeneous	160.0	None		No Asbes	tos Detected
2 n40518720-0002	UNDER WOOD SIDING	Black Fibrous Homogeneous	100,0	None	<1 <1	Amosite Chrysotile	-c1
3 0 <i>40510723-000</i> 3	UNDER WOOD SIDING	Black Non-Fibrous Homogeneous	100.0	None	ج1	Chrysotlle	্ব1
4 040518723-0004	ROOF	Black Non-Fibrous Homogeneous	100.0	None		No Asbest	los Detocted
5 040516729-0005	ROOF	Black Non-Fibrous Homogeneous	100.0	Арпе	,	No Asbest	los Datected
6 040510728-0000	ROOF	Black Non-Fibrous Homogeneous	100,0	, None		No Asbest	os Derected
7 04051 <i>8729-0007</i>	ROOF	Black Non-Fibrous Homogeneous	100,0	Nana		No Asbest	os Detected
립 040 <i>\$</i>) 872 3-00 08	ROOF	Black Non-Fibrous Homogeneous	100,0	None	4 1	Chrysofile	0.0
9 (1455) \$773-0009	ROOF	Black Non-Fibrous Homogeneous	100,0	None	<1	Chrysotile	0.0

VT CERT# TB018368

Analyst(s)

Robyn Denton (9)


Stephen Siegel, CIH or other approved signatory

This luboratory is not responsible for % associate in local number when the residue only is submitted for analysis. The above report relates only to the learns texted. This report may not be represented by the light of the requirements of NELAC unions observed by EMSL Applytical, the Tho test required within this report ment the requirements of NELAC unions observed by the requirements of the requirements of NELAC unions observed by the requirements of the requi ACCREDITATIONS: ANA #100194, NVLAP #101048-0 and NY STATE ELAP #10972

NYTNOB-2

THIS IS THE LAST PAGE OF THE REPORT.

040518723





Chain of Custody

Asbestos Lab Services

EMSL Analytical, Inc. 107 Haddon Avenue Westmont, N.I 08108

Phone: (856) 858-4800 Fax: (856) 858-4960 (856) 427-1608 http://www.emsl.com

Please print all information legibly.

P.O. Box 787 929 Harvest Lane	Bill To: Address l: Address 2;	KAS, Inc. P.O. Box 787
	Name and Advanced to the Party of the Party	7.44.10UN /6/
77.10441	ACOFF \$2.7"	929 Harvest Lanc
Williston, VT	City, State:	Will(ston, VT
05495		
-		134.43.4
Amy Gurney	ويطيق بيادي مجني استريسها حملاه الاستوساء	Ату битеу
802-383-0486		802-383-0486
802-383-0490	The second secon	802-383-0490
amyg@kas-consulting.com		amys@kas-consulting.com
Christina Nardozzi	P.O. Nermban	200-0-50
	Amy Gurney 802-383-0486 802-383-0490 amyg@kas-consulting.com Christina Nardozzi	### Country: Army Gurney

	MATRIX		TURNAROUND				
Air	Soll	Micro-Vac	ŀ	3 Hours	6 Hours	Same Day or 12 Hours*	T 24 Hours (I day)
X Bulk	Drinking Water		P	48 Hoors (2 days)	72 Hours (3 days)	76 Hours (4 days)	120 Hours (5 days)
Wipe	Wastewater		r	144+ bones	(6-10 days)	(1, 4412)	. (2 dulys)

TEM AIR 3 hours, 6 nours, Piesse call shoul to schedule. There is a premium current for 3-hour fut, please call 1-800-220-3675 for prior to sending samples. You will be ested to sign an outforization form for this service.

PCM_Air, I NIOSH 7400(A) laud 2: August 1994 I OSHA W/TWA I Other;	TRM Air ☐ AHERA 40 CFR, Part 763 Subpart E ☐ NIOSH 7402 ☐ EPA Level II	TEM WATER F EPA 100.1 F EPA 100.2 NYS 198.2
E 151 15 16 16 16 16 16 16 16 16 16 16 16 16 16	Chatfield SOP = 1988-02 Chatfield SOP = 1988-02 TEM NOB (Gravimetric) NYS 198.4 EMSL Standard Addition: PLM Son CPA Protocol Qualitative	TEM Microspoe/Wipe ASTM D 5755-95 tomas method) Wipe Qualiforme Z XRD

^{*12} hours (mast arrive by 11:00a,m. Mos .Fri.), Please Refer to Price Quote

				4
3-0486 ER) FRYE	NT DAMAGE	Domeral	Partie Control	MESCELVEN BEEN BEEN BEEN BEEN BEEN BEEN BEEN B
KAS, INC., P.O. BOX 787, 929 HARVEST LANE, WILLISTON, VT 05495 (802) 283-0486 PROJECT NO.: 309050038 SAMPLERS, PETER SCHUYLER NY CENT BO-06785 BIGNATURE: AGNATURE: ASSESSIVA NY 13862 MASSENA, NY 13862 ET COVINGTON, NY 12937	SOUMPLE TYPE: BUTK SOUMPLE # DATE ANALYSIS SAMPLE LOGATION THRNAROUND TIME: # PACLE AMOUNT THE PACLE THE PA	Noch Roof	9 The Valoria 10 11 Sheet tock 16 int Cap.	RELINQUISHED BY: RELINQUISHED BY: COMMENTS: 1) NYS PLW 2) NOBS - STOP AT PLM NOBS FIRST POSITIVE 3) NEW YORK SAMPLES
38/68 39A9		PMB AND	9269284860	./ Œ Œ8 3 4⊅:ÞT \$887/Þ9/ØT


APPENDIX 3

SITE SKETCH .

MARTIN'S GULF FT COVINGTOW, NY ASBESTOS TAISHERIM)

グレス

rolslos PBS



Notes:
1) 1,2,3... SAMPLE NUMBER/LOCATION
1) BOILDING VACANT IN POOR REPAIR

Soil Boring Logs and Monitoring Well Construction Details

Well Log

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Geosearch Driller: John

Method: Hollow Stem Auger

Boring ID: MW-1 Casing Elevation: 99.45 Total Depth: 25 ft btoc

Water Table Elevation: 96.66

Start Date: 10-10-06 End Date: 10-11-06

Screen Length: 20 feet Diameter: 2 inch PVC Type: Schedule 40

Slot Size: 0.010 inch Casing Length: 5 feet Diameter: 2 inch

Me	Method: Hollow Stem Auger			End Date: 10-11-06 Diameter			er: 2 inch		
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Well Diagram	Lithology
1		0' - 1' 1' - 2'	0.3 0.0	VC VC	VC VC	(0' - 2') Topsoil: fine to medium brown SAND, some organics 2" PVC Casing -	1-		HH)
-2		2' - 3'	0.0	VC	VC	(2' - 4') Fine SAND, some clay, little rock fragments, moist	2-		V (V
<u>-</u> 3		3' - 4'	0.4	VC	VC	Bentonite -	3-	 	
<u>-</u> 4	* MW-1	4' - 6'	0.0	VC	VC	(3 '- 4') Gray CLAY, little silt, trace sand	4-		
-5	(4')					(4' - 6') Gray CLAY, little silt, trace fine sand, moist	5-		
- 6		6' - 8'	0.0	VC	VC	(CL OI) Cross CL AV little sile to see fire and uset	6-		
<u>-</u> 7						(6' - 8') Gray CLAY, little silt, trace fine sand, wet	7-		
<u>-</u> 8		8' - 10'	0.2	3-6-8-8	24"/24"		8-		
- -9						(8' - 10') Gray CLAY, little silt, trace fine sand, wet Sand Pack-	9-		
10		10' - 12'	0.0	3-7-9-7	15"/24"		10		
-11		10 12	0.0		10 /2 1	(10' - 12') Brown CLAY and SILT, trace fine sand, wet	11-		
-12		12' - 14'	0.0	3-2-13-24	24"/24"		12-		
\vdash		12 - 14	0.0	3-2-13-24	24 /24	(12' - 14') CLAY and SILT, some fine sand, wet 2" PVC 0.01" Well Screen -	-		
13						Woll 6019011	13 -		
- 14		14'-16'	0.0	9-12-16-12	6"/24"	(14 '- 16') Fine to medium GRAVEL and brown clay, saturated	14-		
- 15 -							15 -		
-16 -		16'-18'	0.0	16-24- 27-27	24"/24"	(16' - 18') Coarse SAND, little medium gravel, saturated	16 -		
- 17							17-		
18		18'-20'	NA	6-8-37-41	None	(18' - 20') No Recovery	18 -		
19							19 -		
20		20'-22'	0.0	6-25-25-35	24"/24"	(20' - 22') Fine to coarse SAND, some fine gravel, saturated	20 -		
21							21 —		
-22		22'-24'	0.0	15-25-	24"/24"	(22' - 24') Fine to coarse SAND, some fine gravel, saturated	22 –		
_23				23-23			23		
-24		24' - 26'	0.0	10-25-60/4"	12"/16"	(24' - 26') Fine to coarse SAND, some fine gravel, saturated	24		
-25						(21 25) This to obtain of the property of the	25		
-26							26		
- -27							27-		

Notes:

Soil boring terminated at 26 ft bgs.

Water table elevation is measured from an arbitrary on-site datum.

VC - Vacuum Clear NA - Not Available

* - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface ft btoc - feet below top of casing

" - inches

PID - photoionization detector DTW - depth to water ppmv - parts per million by volume

Well Log

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Geosearch Driller: John

Method: Hollow Stem Auger

Boring ID: MW-2 Casing Elevation: 99.82 Total Depth: 25 ft btoc Water Table Elevation: 96.74

Start Date: 10-10-06 End Date: 10-11-06

Screen Length: 20 feet Diameter: 2 inch PVC Type: Schedule 40 Slot Size: 0.010 inch Casing Length: 5 feet Diameter: 2 inch

IVIC	tilou. Holi	OW Stern	Lift Date. 10-11-00 Diameter. 2 inch						
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Well Diagram	Lithology
		0' - 2'	0.0	VC	VC	(0' - 2') Fine SAND, some clay, some rock fragments	_		
-1 -2 - -3		2' - 4'	0.0	VC	VC	2" PVC Casing – (2' - 4') Fine SAND, some clay, some rock Fragments Bentonite –	1- 2- 3-	*	
- -4 - -5	* MW-2	4' - 6'	0.0	VC	VC	(4' - 6') Gray CLAY, little fine sand, trace organics, moist	4— 5—		
-6 -7	(5')	6' - 8'	0.0	8-13-22-10	24"/24"	(6' - 8') Brown to gray CLAY some silt, wet	6- 7-		
- 8 - 9		8' - 10'	0.0	7-13-10-14	24"/24"	(8' - 10') Brown to gray CLAY some silt, wet Sand Pack	8- 9-		
-10 -11		10' - 12'	0.0	10-12- 17-25	10"/24"	(10' - 12') Coarse SAND and fine to medium gravel, wet	10 -		
-12 -13		12' - 14'	0.0	34-17- 15-18	24"/24"	(12' - 13') Coarse gray SAND, wet	12-		\$ 96\$ 96\$
- -14 - -15		14'-16'	0.0	11-56- 27-29	12"/24"	(13' - 14') Medium GRAVEL 2" PVC 0.010" Well Screen	14 — - 15 —		<u> </u>
- -16 - -17		16'-18'	0.0	34-60/4"	18"/10"	(16' - 18') Coarse gray SAND, some medium gravel, saturated	16 — 17 —		
- -18 - -19		18'-20'	0.0	27-34-60/4"	13"/16"	(18' - 20') Coarse gray SAND, some medium gravel, saturated	18 -		
- -20 - -21		20'-22'	0.0	50-27- 43-20	6"/24"	(20' - 22') Rock Fragments	20-		
- -22 - -23		22'-23'	0.0	43-60/5"	11"/11"	(22' - 23') C oarse SAND and rock fragments	22-		
- -24							24		
- -25							25		

Notes:

Soil boring terminated at 23 ft bgs.

Water table elevation is measured from an arbitrary on-site datum.

VC - Vacuum Clear NA - Not Available

* - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface ft btoc - feet below top of casing

" - inches

PID - photoionization detector DTW - depth to water ppmv - parts per million by volume

Well Log

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Geosearch Driller: John

Method: Hollow Stem Auger

Boring ID: MW-3 Casing Elevation: 99.72

Total Depth: 25 ft btoc Water Table Elevation: 96.62

Start Date: 10-10-06 End Date: 10-11-06

Screen Length: 20 feet

Diameter: 2 inch PVC Type: Schedule 40 Slot Size: 0.010 inch Casing Length: 5 feet

Diameter: 2 inch

Me	thod: Hol	low Stem	Auger		End Date: 10-11-06 Diameter: 2 inch				
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Well Diagram	Lithology
		0' - 2'	466	VC	VC	(0' - 2') Gray SILT and CLAY, petroleum odor, moist	-		
-1 -2 -3		2' - 4'	2465	VC	VC	2" PVC Casing - (2' - 4') Fine SAND, some clay, little gravel, petroleum odor Bentonite -	2-3-	• • • • • • • • • • • • • • • • • • •	
-4 -5	* MW-3 (4')	4' - 6'	1277	VC	VC	(4' - 6') Medium to coarse SAND and rock fragments	4- 5-		
- -6 -7		6' - 8'	897	2-6-10-15	8"/24"	(6' - 8') Medium SAND, little CLAY, wet	6 - 7 -		
8 9		8' - 10'	1404	12-22- 22-22	20"/24"	(8' - 10') Medium SAND, petroleum odor, wet Sand Pack	8-		**********
10 11		10' - 12'	95.8	11-18- 20-25	24"/24"	(10' - 12') Brown Medium SAND, petroleum odor, wet	10 -		
-12 -13		12' - 14'	142	12-20- 20-22	20"/24"	(12' - 14') Brown to gray M SAND 2" PVC 0.010" Well Screen -	12 -		
- 14 - - 15		14'-16'	11.7	8-16-43-33	21"/24"	(14' - 16') Gray medium SAND, wet	14 — 15 —		
16 17		16'-18'	22.9	69/3"	3"/3"	(16' - 18') Gray medium SAND, wet	16 - 17 -		
-18 - -19		18'-20'	0.9	7-30-45-35	15"/24"	(18' - 20') Gray medium SAND, some medium gravel, wet	18 — 19 —		
-20 - -21		20'-22'	23.0	70/4"	4"/4"	(20' - 22') Gray medium SAND and rock fragments, saturated	20		
-22 - -23		22'-24'	88.2	15-27- 40-28	8"/24"	(22' - 24') Medium SAND and medium gravel, saturated	22-		
-24 - -25		24' - 26'	6.0	7-30-60/5"	7"/7"	(24' - 26') Fine to medium GRAVEL, saturated	24 — 25 —		
-26 - -27							26 – 27 –		* · · · · · · · · · · · · · · · · · · ·

Notes:

Boring terminated at 26 ft bgs.

Water table elevation is measured from an arbitrary on-site datum.

VC - Vacuum Clear NA - Not Available

* - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface ft btoc - feet below top of casing

" - inches

PID - photoionization detector DTW - depth to water ppmv - parts per million by volume

Well Log

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Geosearch Driller: John

Method: Hollow Stem Auger

Boring ID: MW-4 Casing Elevation: 99.90 Total Depth: 25 ft btoc Water Table Elevation: 96.94

Start Date: 10-10-06 End Date: 10-12-06

Screen Length: 20 feet Diameter: 2 inch PVC Type: Schedule 40 Slot Size: 0.010 inch Casing Length: 5 feet Diameter: 2 inch

			•						
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Well Diagram	Lithology
-		0' - 2'	294	VC	VC	(0' - 2') Medium SAND with silt and clay, petroleum odor, moist	1-		
-2		2' - 4'	3029	VC	VC	2" PVC Casing - (2' - 4') Gray SILT and CLAY, little fine sand, petroleum odor,	2-		
_3	* MW-4					moist Bentonite	3-	¥ =	
-4	(3')	4' - 6'	2701	VC	VC	(4' - 6') Gray SILT, some clay, trace fine sand, petroleum odor,	4-		
-5 -						moist	5-		
-6 - -7		6' - 8'	126	4-7-42-20	5"/24"	(6' - 8') Gray CLAY, some silt, trace fine sand, little rock fragments	6- 7-		
-8		8' - 10'	182	27-40-	14"/24"	(8' - 10') Brown medium SAND and fine gravel, wet	8-		
-9				22-20		(6 - 10) Brown medium SAND and line graver, wet Sand Pack-	9-		
-10		10' - 12'	33.5	36-43- 41-18	18"/24"	(10' - 12') Brown fine to medium SAND and fine gravel, wet	10		2003-97200
-11 -							11 -		
-12 - 13		12' - 14'	9.8	40-50-60/4"	16"/16"	(12' - 14') Gray- brown medium SAND, trace clay, wet 2" PVC 0.010"	12 — - 13 —		
- 14		14'-16'	10.1	6-8-33-30	16"/24"	Well Screen - (14 '- 16') Fine to medium GRAVEL, little fine sand, wet	14-		
15						(14 - 16) Fine to medium GRAVEL, little line Sand, wet	15		
16		16'-18'	15.5	42-60/2"	18"/8"	(16' - 17') Fine SAND, some fine to medium gravel	16 -		
− 17						(17' - 18') Fine to medium Gravel	17-		
-18 -19		18'-20'	13.2	27-33- 43-28	24"/24"	(18' - 20') Gray medium SAND, and fine to medium gravel	18 - 19 -		
-20		20'-22'	43.9	43-45-	24"/24"	(OCL CON Conversations to access CAND and and for small	20-		
-21				46-52		(20' - 22') Gray medium to coarse SAND and rock fragments, saturated	21 -		
_22		22'-24'	0.0	50-60/5"	11"/11"	(22' - 24') Fine to medium GRAVEL, saturated	22 -		· · · · · · · · · · · · · · · · · · ·
-23							23 -		
-24 -		24' - 26'	4.8	7-15-53-67	23"/24"	(24' - 26') Coarse SAND and fine gravel, saturated	24 -		
-25 - 26							25 — - 26 —		
- -27							27		

Notes:

Boring terminated at 25 ft bgs.

Water table elevation is measured from an arbitrary on-site datum.

VC - Vacuum Clear NA - Not Available

* - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface ft btoc - feet below top of casing

" - inches

PID - photoionization detector DTW - depth to water ppmv - parts per million by volume

Well Log

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Geosearch Driller: John

Method: Hollow Stem Auger

Boring ID: MW-5 Casing Elevation: 99.82

Total Depth: 16 ft btoc Water Table Elevation: 96.74

Start Date: 10-10-06 End Date: 10-12-06

Screen Length: 10 feet Diameter: 2 inch PVC Type: Schedule 40

Slot Size: 0.010 inch Casing Length: 5 feet Diameter: 2 inch

Meth	od: Holl	ow Stem	Auger			End Date: 10-12-06 Diameter: 2 inch			
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Well Diagram	Lithology
-		0' - 2'	0.0	NA	NA	(0' - 2') Brown medium SAND and SILT	-		
-1 -2 - -3		2' - 4'	0.0	NA	NA	2" PVC Casing – (2' - 4') Brown SILT, trace fine sand, trace clay, moist Bentonite –	2-	• • • • • • • • • • • • • • • • • • •	
- -4 -		4' - 6'	0.0	NA	NA	(4 '- 6') Brown SILT, trace fine sand, moist	4-		
-5 * - -6 - -7	* MW-5 (5')	6' - 8'	0.0	22-22- 14-19	16"/24"	(6' - 8') Gray-brown fine to medium SAND, trace clay, wet	5— 6— 7—		
- -8 - -9		8' - 10'	24.3	60/3"	3"/3"	(8 '- 10') Gray fine SAND, trace clay, wet Sand Pack -	8- - 9-		
-10 -11		10' - 12'	0.0	17-44- 36-28	24"/24"	(10' - 12') Gray medium SAND, wet 2" PVC 0.010" Well Screen -	10-		
-12 - -13		12' - 14'	0.0	20-22- 20-19	16"/24"	(12' - 14') Gray- brown medium SAND, some fine gravel, wet	12-		0°6'0°6'6
- -14 - -15		14'-16'	0.0	75/4"	4"/4"	(14' - 16') fine to medium GRAVEL, trace fine sand, saturated	14— - 15—		
- - - -17							16 — -		\$\phi_{\begin{subarray}{c} \phi_{\begin{subarray}{c} \phi_{suba

Notes:

Boring terminated at 16 ft bgs.

Water table elevation is measured from an arbitrary on-site datum.

VC - Vacuum Clear NA - Not Available

* - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface ft btoc - feet below top of casing

" - inches

PID - photoionization detector DTW - depth to water ppmv - parts per million by volume

Well Log

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Geosearch Driller: John

Boring ID: MW-6 Casing Elevation: 99.69

Total Depth: 24 ft btoc Water Table Elevation: 96.76

Start Date: 10-10-06

Screen Length: 20 feet

Diameter: 2 inch PVC Type: Schedule 40 Slot Size: 0.010 inch

Casing Length: 4 feet

Me	Method: Hollow Stem Auger			End Date: 10-12-06			nch		
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Well Diagram	Lithology
<u>-</u>		0' - 2'	0.0	NA	NA	(0'- 2') Brown medium SAND, moist	1-		l
- -2 - -3		2' - 4'	0.0	NA	NA	2" PVC Casi (2' - 4') Olive brown CLAY, little silt, moist Benton	2	→ •	
-4 -5	* MW-6	4' - 6'	2183	NA	NA	(4' - 6') Gray CLAY, some silt, moist Sand Pa	4-	- - - - - -	
-6 -7	(5')	6' - 8'	0.0	18-56-80/6	16"/18"	(6' - 8') Fine SAND, with rock and ash, damp 2" PVC 0.01			
- -8 - -9		8' - 10'	0.0	11-26- 14-15	24"/24"	(8' - 9') Fine to medium SAND with fine gravel	8- 8- 9-		<u> </u>
10		10' - 12'	0.0	33-28 30-30	24"/24"	(9' - 10') Rock Fragments and fine gravel (10' - 11)' Brown fine SAND and fine to medium gravel, wet	10-		a ca ca
-11 -12 -13		11' - 12' 12' - 14'	0.9	18-27- 27-20	14"/24"	(11' - 12') Gray fine SAND and fine to medium gravel, wet (12' - 13') Brown medium SAND and fine gravel, wet	11-		
-14 -15		14'-16'	0.0	34-52- 48-60	16"/24"	(13' - 14') Gray medium SAND and rock fragments, saturated (14' - 16') Brown fine to medium SAND and fine to medium gravel,	14-		
- -16 -17		16'-18'	0.0	17-20- 42-60	24"/24"	rock fragments, saturated (16' - 17') Coarse SAND and rock fragments, saturated	16-		
- -18 -19		18'-20'	1.6	24-19- 18-11	24"/24"	(17' - 18') Rock Fragments, gray fine to medium SAND with some fine to medium gravel	18-		
- -20 - 21		20'-22'	0.0	28-28- 23-12	10"/24"	(18' - 20') Gray fine to medium SAND, some fine to medium gravel, little rock fragments, saturated (20' - 22') Rock Fragments, some medium sand, saturated	20-		050000 05000000
-22 -23		22'-24'	0.0	28-43-60/4	24"/16"	(22' - 24') Gray medium SAND, some rock fragments and medium gravel, saturated	22 -		5,92,92
-24 - -25							24 -		

Notes:

Boring terminated at 24 ft bgs.

Water table elevation is measured from an arbitrary on-site datum.

VC - Vacuum Clear NA - Not Available

* - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface ft btoc - feet below top of casing

" - inches PID - photoionization detector DTW - depth to water ppmv - parts per million by volume

Logged by: JAE

Boring Log

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Op-Tech Driller: RBuley Method: Geoprobe

Boring ID: SB-2

Casing Elevation: NA Total Depth: 16 ft bgs

Water Table Elevation: NA Start Date: 4-11-06 End Date: 4-12-06

Screen Length: NA

Diameter: NA PVC Type: NA Slot Size: NA

Casing Length: NA Diameter: NA

							_	
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Lithology
_		0' - 2'	0.0	HC	HC	(0' - 2') Brown sandy CLAY, moist	_	
-1							1 -	
-2		2' - 4'	0.0	HC	HC	(2' - 4') Brown sandy CLAY, moist	2-	
+						(2 - 4) BIOWIT SAITUY CLAT, ITIOIST	-	
-3							3-	
-4		4' - 8'	0.0	GP	48"/48"	(4 '- 6') Brown sandy CLAY, moist	4-	
_ _5							5-	
	*CD 0		2.4				_	
- 6	*SB-2 (6-8')		2.4			(6' - 8') Brown sandy CLAY, slight petroleum odor, saturated at 7 feet	6-	
-7							7-	
-8		8' - 12'	3.0	GP	36"/48"	(8 '- 10') Brown coarse SAND, saturated	8-	
- -9						(6 10) 2.6111 364136 67.112, 34141436	9-	
-							_	
10			2.5			(10' - 12') Brown coarse SAND, some rock fragments, saturated	10-	
-11							11-	
- -12		12' - 16'	0.0	GP	6"/48"		12-	
-		12 10	0.0	O.	0710	(12' - 14') Grayish brown coarse SAND with rock fragments, saturated	-	
-13 -							13 -	
-14			NA			(14' - 16') No Recovery	14-	
- -15							15	
+							_	
-16 -							16 -	
<u>-17</u>							17	

Notes:

HC - Hand Clear

GP - Geoprobe NA - Not Available * - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface " - inches

Logged by: AEtringer

Soil boring terminated at 16 ft bgs.

Boring Log

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Op-Tech Driller: RBuley Method: Geoprobe

Boring ID: SB-3

Casing Elevation: NA Total Depth: 16 ft bgs Water Table Elevation: NA

Start Date: 4-11-06 End Date: 4-12-06

Screen Length: NA

Diameter: NA PVC Type: NA Slot Size: NA Casing Length: NA

Diameter: NA

Me	Method: Geoprobe				End Date: 4-12-06 Diameter: NA					
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Lithology		
-1	*SB-3 Surface	0' - 2'	0.0	НС	НС	(0' - 2') Brown CLAY, some sand, moist	1-			
-2 - -3 -		2' - 4'	0.0	HC	HC	(2' - 4') Brown CLAY, some sand, moist	3-			
-4 - -5 -	*SB-3 (4-6')	4' - 8'	333	GP	48"/48"	(4' - 6') Brown CLAY, some sand, some rock fragments, petroleum odor, moist	5- 5-			
-6 - -7 -			270			(6' - 8') Brown CLAY, some sand, some rock fragments, petroleum odor, saturated at 7.5 feet	6- 7-			
-8 - -9 -		8' - 12'	9.7	GP	36"/48"	(8' - 10') Brown CLAY, some sand, slight petroleum odor, saturated	9-			
-10 - -11 -			10.6			(10' - 12') Coarse SAND, some silt, saturated	10-			
-12 - -13		12' - 16'	0.0	GP	24"/48"	(12' - 14') Brownish gray coarse SAND, some rock fragments, saturated	12- - 13-			
14 15 			0.0			(14' - 16') Brownish gray coarse SAND, some rock fragments, saturated	14 - 15			
-16 - -17							16 - 17 -			

Notes:

HC - Hand Clear

GP - Geoprobe
NA - Not Available
* - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface " - inches

Logged by: AEtringer

Soil boring terminated at 16 ft bgs.

Boring Log

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Op-Tech Driller: RBuley Method: Geoprobe

Boring ID: SB-4

Casing Elevation: NA Total Depth: 12 ft bgs Water Table Elevation: NA

Start Date: 4-11-06 End Date: 4-12-06

Screen Length: NA

Diameter: NA PVC Type: NA Slot Size: NA Casing Length: NA

Diameter: NA

IVIE	illou. Geop	nobe				Lift Date: 4-12-00 Diameter. NA		
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Lithology
- -1		0' - 2'	0.0	НС	НС	(0' - 2') Brown CLAY, some sand, moist	1-	
-2 -		2' - 3'	151	НС	НС	(2' - 3') Brown CLAY, some sand, strong petroleum odor, moist	2-	
-3 -		3' - 4'	137	HC	HC	(3' - 4') Brown CLAY, some sand, strong petroleum odor, moist	3-	
-4 -	*SB-4 (6-8')	4' - 8'	391	GP	24"/48"	(4' - 5') Brown CLAY, some sand, strong petroleum odor, moist	4-	
-5 -						(5' - 6') Rock fragments	5-	10 070 070 070 0 250 650 650 650
-6 - -7 -			665			(6' - 8') Gray CLAY, some sand and rock fragments, saturated at 7.5 feet	6 — 7 —	-1/0 (=1/0 (=1/0 (=1/0
-8 - -9 -		8' - 12'	27.3	GP	48"/48"	(8' - 10') Gray coarse SAND with rock fragments, petroleum odor, saturated	8 — 9 —	
-10 - -11 -			28.9			(10' - 12') Gray coarse SAND with rock fragments, petroleum odor, saturated	10 — - 11 —	
-12 -							12-	<u> </u>
-13 -							13-	
-14 - -15							14-	
- - - 16							16-	
- 17							17-	

Notes:

HC - Hand Clear

GP - Geoprobe NA - Not Available

* - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface " - inches

Logged by: AEtringer

Soil boring terminated at 12 ft bgs.

Boring Log SB-5A

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Op-Tech Driller: RBuley Method: Geoprobe

Boring ID: SB-5A Casing Elevation: NA Total Depth: 3 ft bgs

Water Table Elevation: NA

Start Date: 4-11-06 End Date: 4-12-06

Screen Length: NA

Diameter: NA PVC Type: NA Slot Size: NA Casing Length: NA

Diameter: NA

Method: Ged	oprobe				End Date: 4-12-06 Diameter: NA		
Depth (Feet) Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Lithology
- -1 - -2	0' - 1' 1' - 2' 2' - 3'	1,489 1,285 1,333	HC HC	HC HC	(0' - 1') Dark gray CLAY, strong petroleum odor, moist (1' - 2') Dark gray CLAY, strong petroleum odor, moist (2 '- 3') Dark gray CLAY, strong petroleum odor, moist	1	
-3 - -4 -						3-4-	
-5 - -6 - -7						5— 6— 7—	
-8 - -9 -						8- 9- 10-	
- 11 - 12 - 12						11-	
13 14 15						13 — 14 — 15 —	
- 16 - 17						16 — 16 — 17 —	

Notes:

HC - Hand Clear

GP - Geoprobe NA - Not Available * - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface " - inches

Logged by: AEtringer

Soil boring terminated at 3 ft bgs (refusal).

Boring Log SB-5B

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Op-Tech Driller: RBuley Method: Geoprobe

Boring ID: SB-5B Casing Elevation: NA Total Depth: 2.5 ft bgs

Water Table Elevation: NA

Start Date: 4-11-06 End Date: 4-12-06

Screen Length: NA

Diameter: NA PVC Type: NA Slot Size: NA Casing Length: NA

12

13

14

15

16-

Diameter: NA

Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspa (ppmv)	Blow / 6"	Recovery / Penetration (Description	Depth (feet)	Lithology
	*SB-5B (1-2')	0' - 1' 1' - 2.5'	1,366 NA	HC HC	HC HC	(0' - 1') Dark gray CLAY, some fine to medium sand, strong petroleum odor (1 - 2.5) Dark gray CLAY, some fine to medium sand, strong petroleum odor	1— 2— 3— 4— 5— 6—	
-7 - -8							7- - 8-	
- - -9							9-	
- -10							10-	

Notes:

-13

-15

-16

17

HC - Hand Clear GP - Geoprobe NA - Not Available

* - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface " - inches

Logged by: AEtringer

Soil boring terminated at 2.5 ft bgs

Boring Log SB-5C

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Op-Tech Driller: RBuley Method: Geoprobe

Boring ID: SB-5C

Casing Elevation: NA Total Depth: 2 ft bgs Water Table Elevation: NA

Start Date: 4-11-06 End Date: 4-12-06

Screen Length: NA

Diameter: NA PVC Type: NA Slot Size: NA

Casing Length: NA

Diameter:	NA

Description Description	Method: Geo	probe			End Date: 4-12-06			
1	Depth (Feet) Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Lithology
	1 2 3 4 5 6 7 8 10 11 12 13 14 15 16 16 16 16	0' - 1'	1,407	HC	НС	(1' - 2') Dark gray CLAY, some fine to medium sand, strong	11- 2- 3- 3- 4- 5- 6- 7- 8- 8- 9- 11- 11- 12- 13- 14- 15- 16-	

Notes:

HC - Hand Clear

GP - Geoprobe NA - Not Available * - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface " - inches

Logged by: AEtringer

Soil boring terminated at 2 ft bgs (refusal).

Boring Log SB-5D

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station

Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Op-Tech Driller: RBuley Method: Geoprobe

Boring ID: SB-5D

Casing Elevation: NA Total Depth: 2 ft bgs Water Table Elevation: NA

Start Date: 4-11-06 End Date: 4-12-06

Screen Length: NA

Diameter: NA PVC Type: NA

Slot Size: NA Casing Length: NA

Diameter: NA

Me	ethod: Geoprobe			End Date: 4-12-06 Diameter: NA				
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Lithology
1 - 2 - 3 - 4 - 5 - 6 - 7 - 8 - 9 - 10 - 11 - 12 - 13 - 14 - 15 - 15 - 15 - 15 - 15 - 15 - 15		0' - 1' 1' - 2'	868 NA	нс	HC HC	(0 '- 1') Dark gray CLAY, some fine to medium sand, strong petroleum odor (1' - 2') Dark gray CLAY, some fine to medium sand, strong petroleum odor	3- 3- 3- 3- 3- 3- 3- 3- 3- 3- 3- 3- 3- 3	
-16 - -17							16 - 17 -	

Notes:

HC - Hand Clear

GP - Geoprobe NA - Not Available * - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface " - inches

Logged by: AEtringer

Soil boring terminated at 2 ft bgs (refusal).

Boring Log SB-5E

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Op-Tech Driller: RBuley Method: Geoprobe

Boring ID: SB-5E Casing Elevation: NA Total Depth: 2

Water Table Elevation: NA Start Date: 4-11-06 End Date: 4-12-06

Screen Length: NA Diameter: NA PVC Type: NA

Slot Size: NA Casing Length: NA Diameter: NA

Metho	d: Geop	robe				End Date: 4-12-06 Diameter: NA		
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Lithology
1 2 3 4 5 6 7 8 10 11 12 13 14 15 16 16 16 16		0' - 1' 1' - 2'	985 NA	HC HC	HC HC	(0' - 1') Dark gray CLAY, some fine to medium sand, strong petroleum odor (1' - 2') Dark gray CLAY, some fine to medium sand, strong petroleum odor	1 - 1 - 2 - 3 - 4 - 5 - 6 - 7 - 7 - 8 - 9 - 10 - 11 - 12 - 13 - 14 - 15 - 16 - 16 - 16 - 16 - 16 - 16 - 16	
-17							17-	

Notes:

HC - Hand Clear

GP - Geoprobe NA - Not Available * - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface " - inches

Logged by: AEtringer

Soil boring terminated at 2 ft bgs (refusal).

Boring Log

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Op-Tech Driller: RBuley Method: Geoprobe

Boring ID: SB-5F

Casing Elevation: NA Total Depth: 1 ft bgs Water Table Elevation: NA

Start Date: 4-11-06 End Date: 4-12-06

Screen Length: NA

Diameter: NA PVC Type: NA Slot Size: NA

Casing Length: NA Diameter: NA

Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Lithology
		0' - 1' 1' - 2'	1,507	HC HC	НС	(0' - 1') Dark gray CLAY, some fine to medium sand, strong petroleum odor	_	
-1 -		1 - 2	NA	HC HC	HC	(1' - 2') Dark gray CLAY, some fine to medium sand, strong petroleum odor	1-	
-2 -							2-	
-3 -							3-	
-4 -							4-	
-5 -							5-	
-6 -							6-	
- ₇							7-	
-8 -							8-	
-9 -							9-	
-10 -							10-	
-11 -							11-	
12 							12-	
-13 -							13-	
14 							14-	
15 							15 -	
-16 -							16-	
- 17							17-	

Notes:

HC - Hand Clear

GP - Geoprobe NA - Not Available

* - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface " - inches

Logged by: AEtringer

Soil boring terminated at 2 ft bgs.

Boring Log SB-5G

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Op-Tech Driller: RBuley Method: Geoprobe

Boring ID: SB-5G

Start Date: 4-11-06

End Date: 4-12-06

Casing Elevation: NA Total Depth: 2.5 ft bgs Water Table Elevation: NA Screen Length: NA Diameter: NA PVC Type: NA Slot Size: NA

Casing Length: NA Diameter: NA

Me	thod: Geop	orobe				End Date: 4-12-06 Diameter: NA		
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Lithology
		0' - 1' 1' - 2.5'	0.0 0.0	HC HC	HC HC	(0' - 1') Dark gray CLAY, some fine to medium sand, petroleum odor (1' - 2.5') Dark gray CLAY, some fine to medium sand, petroleum odor	- 1 2 3	
-17							17-	

Notes:

HC - Hand Clear

GP - Geoprobe NA - Not Available

- * Denotes Sample collected for laboratory analysis
- ft bgs feet below ground surface " inches

Logged by: AEtringer

Soil boring terminated at 2.5 ft bgs

Boring Log

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Op-Tech Driller: RBuley

Boring ID: SB-7

Casing Elevation: NA Total Depth: 16 ft bgs

Water Table Elevation: NA Start Date: 4-11-06

Screen Length: NA

Diameter: NA PVC Type: NA

Slot Size: NA Casing Length: NA

1	d: Geop				End Date: 4-12-06 Diameter: NA			. 14/		
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Lithology		
		0' - 3'	0.0	НС	НС	(0' - 3') Brown fine SAND, dry	_			
-1 - -2 -		0 0	0.0				1- 2-			
-3		3' - 4'	237	HC	HC	(3' - 4') Gray CLAY, trace coarse sand, strong petroleum odor, wet	3-			
	SB-7 (4-5')	4' - 5'	342	HC	HC	(4' - 5') Gray CLAY, trace coarse sand, strong petroleum odor, wet	4-			
<u></u> −5		5' - 8'	418	GP	36"/36"	(5' - 6') Brown CLAY, some coarse sand, strong petroleum odor, saturated at 5 feet	5-			
-6 - -7 -			684			(6' - 8') Olive-brown CLAY with some coarse sand and rock fragments, strong petroleum odor, saturated	6- 7-			
-8 - -9 -		8' - 12'	658	GP	48"/48"	(8' - 10') Brown to gray coarse SAND, strong petroleum odor, saturated	9-			
-10 - -11 -			24.3			(10' - 12') Gray coarse SAND, some rock fragments, saturated	10-			
-12 - -13 -		12' - 16'	99.0	GP	48"/48"	(12' - 14') Olive-gray CLAY with coarse sand and rock fragments, saturated	12-			
14 15 16 16			0.0			(14' - 16') Dark gray coarse SAND with rock fragments, saturated	14 — 15 — - 16 —			
- 17							17-	1		

Notes:

HC - Hand Clear

GP - Geoprobe
NA - Not Available
* - Denotes Sample collected for laboratory analysis
ft bgs - feet below ground surface
" - inches

Soil boring terminated at 16 ft bgs.

PID - photoionization detector ppmv - parts per million by volume

Logged by: AAE

Boring Log

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Op-Tech Driller: RBuley Method: Geoprobe

Boring ID: SB-9 Casing Elevation: NA Total Depth: 16 ft bgs Water Table Elevation: NA Start Date: 4-11-06

End Date: 4-12-06

Screen Length: NA Diameter: NA PVC Type: NA Slot Size: NA Casing Length: NA Diameter: NA

Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Lithology
- -1	*SB-9 Surface	0' - 2'	0.0	НС	НС	(0' - 2') Brown coarse SAND with trace clay, moist	1-	
- ₂		2' - 4'	0.0	НС	НС	(2' - 3') Brown coarse SAND with trace clay, moist	2-	
-3						(3' - 4') Brown CLAY with coarse sand, moist	3-	
-4 - -5		4' - 8'	0.0	GP	48"/48"	(4' - 6') Grayish-brown CLAY, moist	4- 5-	
-6 - -7	*SB-9 (6-8')		0.0			(6' - 8') Grayish-brown CLAY, moist	6- - 7-	
- -8 - -9		8' - 12'	0.0	GP	48"/48"	(8' - 10') Olive-gray CLAY, wet	- 8- - 9-	
10			0.0			(10' - 11') Olive-gray CLAY, wet	10-	
-11			0.0			(11' - 12') Olive-gray CLAY with trace coarse sand and rock fragments, saturated, saturated at approximately 11 feet	11-	
-12 -		12' - 16'	0.0	GP	24"/48"	(12' - 14') Olive-gray CLAY with coarse sand, saturated	12-	
13							13-	
-14			0.0			(14' - 16') Dark gray coarse SAND with rock fragments, trace clay, saturated	14-	
-15 -							15 -	
-16 - -17							16 - 17 -	

Notes:

HC - Hand Clear

GP - Geoprobe NA - Not Available * - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface " - inches

Logged by: AEtringer

Soil boring terminated at 16 ft bgs.

Boring Log SB-10

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Op-Tech Driller: RBuley Method: Geoprobe

Boring ID: SB-10 Casing Elevation: NA

Total Depth: 16 ft bgs Water Table Elevation: NA

Start Date: 4-11-06 End Date: 4-12-06

Screen Length: NA

Diameter: NA PVC Type: NA Slot Size: NA

Casing Length: NA Diameter: NA

Met	thod: Geop	robe				End Date: 4-12-06 Diameter: NA		
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Lithology
-	*SB-10 Surface	0' - 2'	0.0	HC	НС	(0' - 2') Brown fine to medium SAND, dry	1-	
- ₂		2' - 4'	0.0	НС	НС	(2' - 4') Brown fine to medium SAND, trace silt and clay, moist	2-	
-3 - -4 - -5		4' - 8'	0.0	GP	48"/48"	(4' - 6') Olive-brown CLAY, moist	3- - 4- - 5-	
- -6 - -7			0.0			(6' - 8') Olive-brown CLAY, moist	6- 6- 7-	
-8 - -9		8' - 12'	0.0	GP	48"/48"	(8' - 10') Olive-brown CLAY, moist	8- 8- 9-	
- -10 - -11	*SB-10 (10-12')		0.0			(10' - 12') Olive-brown CLAY, moist	10 - - - 11 -	
- -12 -		12' - 16'	0.0	GP	48"/48"	(12' - 14') Olive-brown CLAY, saturated at approximately 12 feet	12 - - - 13 -	
- -14 -			0.0			(14' - 15') Brown coarse SAND, some clay, saturated	- 14 - -	
-15 - -16 -			0.0			(15' - 16') Gray coarse SAND, some clay, saturated	15 — - 16 — - 17 —	
17					1	1	1.7	

Notes:

HC - Hand Clear

GP - Geoprobe NA - Not Available * - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface " - inches

Logged by: AEtringer

Soil boring terminated at 16 ft bgs.

Boring Log SB-11

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Op-Tech Driller: RBuley Method: Geoprobe

Boring ID: SB-11 Casing Elevation: NA

Total Depth: 16 ft bgs Water Table Elevation: NA

Start Date: 4-11-06 End Date: 4-12-06

Screen Length: NA

Diameter: NA PVC Type: NA Slot Size: NA Casing Length: NA

Diameter: NA

IVIE	illou. Geop	JODE				Life Date: 4-12-00 Diameter. NA		
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Lithology
-1	*SB-11 Surface	0' - 2'	0.0	НС	НС	(0' - 2') Brown medium to coarse SAND with some clay, moist	1-	
-2 - -3	*SB-11 (2-4')	2' - 4'	0.0	НС	НС	(2' - 4') Brown medium to coarse SAND with some clay, moist	3-	
- -4 -		4' - 8'	0.0	GP	48"/48"	(4' - 6') Brown-gray CLAY with trace coarse sand, saturated at approximately 4 feet	4-	
-5 - -6 -			0.0			(6' - 8') Brown-gray CLAY with trace coarse sand, saturated	5- - 6-	
-7 - -8 -		8' - 12'	0.0	GP	36"/48"	(8' - 10') Olive-gray CLAY with trace coarse sand and gravel, saturated	7- - 8-	
-9 -10			0.0			(10' - 12') Olive-gray CLAY with trace coarse sand and gravel, saturated	9	
-11 - -12		12' - 16'	0.0	GP	12"/48"	(12' - 14') Gray CLAY with trace coarse sand, saturated	11-	
-13 - -14			0.0			(14' - 16') Gray CLAY with trace coarse sand, saturated	13 -	
15 16 							15 — - 16 — -	

Notes:

HC - Hand Clear GP - Geoprobe NA - Not Available

* - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface " - inches

Logged by: AEtringer

Soil boring terminated at 16 ft bgs.

Boring Log SB-12

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station

Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Op-Tech Driller: RBuley Method: Geoprobe

Boring ID: SB-12

Casing Elevation: NA

Total Depth: 13.5 ft bgs Water Table Elevation: NA

Start Date: 4-11-06 End Date: 4-12-06

Screen Length: NA

Diameter: NA

PVC Type: NA Slot Size: NA

Casing Length: NA

Diameter: NA

Method: Geo	probe				End Date: 4-12-06 Diameter:	NA	
Depth (Feet) Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Lithology
- -1 -	0' - 2'	0.0	HC	HC	(0' - 2') Brown medium SAND, dry	1-	1
-2 - -3	2' - 4'	0.0	HC	HC	(2' - 4') Brown CLAY, some sand, moist	3-	
- -4 - -5	4' - 8'	0.0	GP	48"/48"	(4' - 6') Brown CLAY, trace sand, trace organics, moist	4-	
-6 7		0.0			(6' - 8') Brown CLAY, moist	6-	
	8' - 12'	0.0	GP	48"/48"	(8' - 10') Brown CLAY, moist	8 - 8 - 9 -	
- -10 - -11		0.0			(10' - 12') Brown CLAY, wet to saturated, saturated at approximately 10 feet	10-	
-12 - -13	12' - 13.5'	0.0	GP	18"/18"	(12' - 13.5') Brown CLAY with coarse sand and gravel, saturated Refusal at 13.5'	12-	
- 14 - 15						14-	
- - 16 - - 17						16 - 17 -	
		ı	I	i		17	I.

Notes:

HC - Hand Clear

GP - Geoprobe NA - Not Available * - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface " - inches

Logged by: AEtringer

Soil boring terminated at 13.5 ft bgs

Boring Log SB-13

7 Airport Park Boulevard, Latham, New York 12110 Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Former Martins Gulf Station Client: Town of Fort Covington

Location: Chateaugay and Salmon Street, Fort Covington

Drilling Co.: Op-Tech Driller: RBuley Method: Geoprobe

Boring ID: SB-13 Casing Elevation: NA Total Depth: 16 ft bgs Water Table Elevation: NA Start Date: 4-11-06

End Date: 4-12-06

Screen Length: NA Diameter: NA PVC Type: NA Slot Size: NA Casing Length: NA Diameter: NA

IVIC	illou. Geop	Jione				Lift Date: 4-12-00 Diameter. NA		
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (")	Description	Depth (feet)	Lithology
-		0' - 2'	0.0	НС	нс	(0' - 2') Brown CLAY, some sand, dry	1-	
_2		2' - 4'	0.0	НС	НС	(2' - 4') Brown CLAY, some sand, moist	2-	
-3 - -4 - -5		4' - 8'	0.0	GP	48"/48"	(4' - 6') Brown CLAY, trace medium sand, moist	3- - 4- - 5-	
- -6 - -7	*SB-13 (6-8')		36.8			(6' - 8') Olive-brown CLAY, moist to wet	6 - 6 - 7 -	
-8 - -9		8' - 12'	10.0	GP	36"/48"	(8' - 10') Gray-brown CLAY, some sand, slight petroleum odor, wet	8- - 9-	
- -10 - -11			2.1			(10' - 12') Gray-brown CLAY, some sand, trace rock fragments, slight petroleum odor, saturated at approximately 10 feet	10-	
-12 - -13		12' - 16'	0.0	GP	12"/48"	(12' - 14') Gray-brown coarse SAND, saturated	12-	
- -14 - -15			0.0			(14' - 16') Gray-brown coarse SAND, saturated	- 14- - 15-	
-16 -							16 - 17 -	

Notes:

HC - Hand Clear GP - Geoprobe NA - Not Available

* - Denotes Sample collected for laboratory analysis

ft bgs - feet below ground surface " - inches

Logged by: AEtringer

Soil boring terminated at 16 ft bgs.

Well Log

SB-13A/ **MW-7**

7 Airport Park Boulevard Latham, NewYork Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Fort Covington Client: Town of Fort Covington

Location: 2510 Chateaugay St., Fort Covington, N.Y. 12937

Drilling Co.: OPTECH Driller: Joseph Maselli

Method: Geoprobe/Hollow Stem Auger

Boring ID: SB-13/MW-7 Casing Elevation: NSVD

Total Depth: 20

Depth to First Observed Water: 5'

Start Date: 6/20/07 End Date: 6/20/07

Screen Length: 17' Diameter: 2"

PVC Type: Schedule 40 Slot Size: 0.010" Casing Length: 3'

Diameter: 2"

Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (inches)	Description	Depth (feet)	Well Diagram	Lithology
- -1	SB-13 (0 - 2')	0' - 1' 1' - 2'	0.0 0.0	VC VC	VC VC	Brown fine SAND, Organic-rich Brown fine SAND, Organic-rich (wood) Backfill	1=		
-2		2' - 3'	0.0	VC	VC	Brown to Grey SILT and CLAY	2-		
-3	SB-13/ MW-7 (3'	3' - 4'	0.0	vc	VC	2" PVC Riser – Brown to Grey SILT and CLAY	3-		
_4	- 4')	4' - 5'	0.0	VC	VC	Brown to Grey SILT and CLAY, wet	4-		
_5 _		5' - 9'	0.0	NA	48"/48"	Brown SILT and CLAY, wet	5-		
-6							6-		
- 7							7-		
- 8						No. 2 Sand –	8-		
<u>-</u> 9		9' - 13'	1.9	NA	48"/48"	Brown SILT and CLAY, wet	9-		
-10						Brown coarse SAND, wet	10-		
-11 - -12							11-		
-13		13' - 17'	0.0	NA	48"/48"	0.000	13-		
- -14						Brown coarse SAND, wet	14-		
- -15						2" 0.010" Slot Screen -	15		
- -16						Grey coarse SAND	16-		
17		17' - 21'	0.0	NA	48"/48"	Grey coarse SAND, little fine Gravel	17-		
18							18-		
19							19-		
-20							20 -		
-21							21 –	11.000	

Notes:

VC Vacuum Clear

Not Available

NA Denotes Sample collected for laboratory analysis fbg NS Feet below grade

NR

Not Sampled No Recovery

ppmv

parts per million by volume

7 Airport Boulevard, Latham, New York Phone: (518) 786-8750 Fax: (518) 786-8755

Bore Log

SB-14

Project: Fort Covington

Client: Town of Fort Covington

Location: 2510 Chateaugay St., Fort Covington, N.Y. 12937

Drilling Co.: OPTECH Driller: Joseph Maselli Method: Geoprobe

Boring ID: SB-14

Casing Elevation: NSVD

Total Depth: 21 Depth to First Observed Water: 5'

Start Date: 6/19/07 End Date: 6/19/07

Screen Length: -

Diameter: -PVC Type: -Slot Size: -

Casing Length: -Diameter: -

Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (inches)	Description	Depth (feet)	Lithology
-		0' - 1'	0.5	VC	VC	Brown fine SAND, little fine Gravel	-	
- 1		1' - 2'	0.0	VC	VC	Brown fine SAND, some medium Gravel	1-	
-2		2' - 3'	0.0	VC	VC	Brown CLAY and SILT	2-	
_3	SB-14	3' - 4'	0.0	VC	VC	Brown CLAY and SILT	3-	
-4	(3' - 4')	4' - 5'	0.0	VC	VC	Brown CLAY and SILT	4-	
-5		5' - 9'	0.0	NA	48"/48"	Brown CLAY and SILT, wet	5-	
-6						blowii ola i aiu oli i, wet	6-	-
- -7							7-	
-8							8-	
F .							-	_
- 9		9' - 11'	0.0	NA	24"/48"	Brown CLAY and SILT	9-	
10							10 -	-
11		11' - 13'	0.0	NA		GRAVEL (lithic fragments), little Sand, wet	11-	*******
12							12-	
13		13' - 17'	0.0	NA	48"/48"	Grey medium to coarse SAND, some fine to medium Gravel, wet	13-	
14							14-	
15							15	
16							16-	
- -17		17' - 21'	0.0	NA	48"/48"		17-	
-18		.,	0.0	107	10 / 10	Grey medium to coarse SAND, some fine to medium Gravel, wet	18-	
+							-	
- 19							19 -	
-20							20 -	
-21							21 –	

Feet below grade

Notes:

fbg VC Vacuum Clear

NSVD Not Surveyed to Vertical Datum NA Not Available Parts Per Million by Volume

ppmv BDL Below Instrument Detection Limit of 0.1 ppmv

Bore Log

SB-15

7 Airport Boulevard, Latham, New York Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Fort Covington Client: Town of Fort Covington

Location: 2510 Chateaugay St., Fort Covington, N.Y. 12937

Drilling Co.: OPTECH Driller: Joseph Maselli Method: Geoprobe

Boring ID: SB-15 Casing Elevation: NSVD

Total Depth: 19.5

Depth to First Observed Water: 5' Start Date: 6/19/07

End Date: 6/19/07

Screen Length: -Diameter: -PVC Type: -Slot Size: -Casing Length: -

	thod: Ge	oprobe	,III	End Date: 6/19/07 Diameter: -				
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (inches)	Description	Depth (feet)	Lithology
- ,		0' - 1'	0.0	VC	VC	Brown fine SAND	-	
-1 -		1' - 2'	0.0	VC	VC	Brown fine SAND	1-	
-2 -		2' - 3'	0.0	VC	VC	Brown fine SAND	2-	
-3	SB-15	3' - 4'	0.0	VC	VC	Grey SILT and CLAY	3-	
4	(3' - 4')	4' - 5'	0.0	VC	VC	Grey SILT and CLAY, wet	4-	
_5		5' - 9'	0.0	NA	48"/48"	Grey SILT and CLAY	5-	
-6							6-	
-7							7-	
-8							8-	
-9		9' - 13'	0.0	NA	48"/48"	Grey SILT and CLAY, wet	9	
-10						,	10 -	
-11							11 -	
- -12							12-	
13		13' - 17'	0.0	NA	40"/48"		- 13-	
-		10 17	0.0	107	40 /40	Grey SILT and CLAY, wet	14-	
14							-	
- 15 -							15 -	
- 16							16-	
17		17'-19.5	0.0	NA	6"/48"	Grey SILT and CLAY, wet	17-	
-18 -							18-	
19							19-	
_								

Notes:

VC Vacuum Clear fbg Feet below grade

NA Not Available NSVD Not Surveyed to Vertical Datum

BDL Below Instrument Detection Limit of 0.1 ppmv

Parts Per Million by Volume ppmv

KLEINFELDER

Well Log

SB-16/ MW-8

7 Airport Park Boulevard Latham, NewYork Phone: (518) 786-8750 Fax: (518) 786-8755 Project: Fort Covington

Client: Town of Fort Covington

Location: 2510 Chateaugay St., Fort Covington, N.Y. 12937

Drilling Co.: OPTECH Driller: Joseph Maselli

Method: Geoprobe/Hollow Stem Auger

Boring ID: SB-16/MW-8
Casing Elevation: NSVD

Total Depth: 21

Depth to First Observed Water: 4'

Start Date: 6/19/07 End Date: 6/19/07 Screen Length: 17'
Diameter: 2"

PVC Type: Schedule 40 Slot Size: 0.010"

Casing Length: 3' Diameter: 2"

1				-9					
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (inches)	Description	Depth (feet)	Well Diagram	Lithology
- -1	SB-16 (0 - 2')	0' - 1' 1' - 2'	0.0 0.0	VC VC	VC VC	Brown fine SAND, Topsoil with organics. Fill includes bits of asphalt shingles. Avoided in samples Backfill	-1=		
-2	SB-16 /	2' - 3'	0.0	VC	VC	Brown SAND Bentonite Seal	2-		
-3	MW-8 (2' - 3')	3' - 4'	0.0	VC	VC	Brown SAND 2" PVC Riser—	3-		
-4		4' - 5'	0.0	VC		Brown CLAY, wet	4-		
+					VC	CLAY, wet	-		
<u>-</u> 5		5' - 9'	0.0	NA	48"/48"	Brown to grey SILT and CLAY, wet	5-		
-6							6-		
7							7-		
-8						No. 2 Sand —	8-		
-9		9' - 13'	0.0	NA	48"/48"	Brown to grey SILT and CLAY, wet	9-		
10							10-		
-11							11-		
12							12-		
13		13' - 17'	0.0	NA NA	48"/48"		13-		
-14						Brown to grey SILT and CLAY, trace fine brown Sand, wet	14-		
H						2" 0.010" Slot Screen -	15-		
-15 -							-		
-16 -							16-		
- 17		17' - 21'	0.0	NA	48"/48"	Grey CLAY and SILT, wet	17-		
18							18-		
19							19-		
_20							20-		
-21							21		
	Notos								

Notes: VC

NA

Vacuum Clear

Not Available

Denotes Sample collected for laboratory analysis

fbg Feet below grade

NS Not Sampled

NR No Recovery

ppmv parts per million by volume

KLEINFELDER

Bore Log

SB-17

7 Airport Boulevard, Latham, New York Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Fort Covington
Client: Town of Fort Covington

Location: 2510 Chateaugay St., Fort Covington, N.Y. 12937

Drilling Co.: OPTECH Driller: Joseph Maselli Method: Geoprobe Boring ID: SB-17 Casing Elevation: NSVD

Total Depth: 20

Depth to First Observed Water: 5'

Start Date: 6/20/07 End Date: 6/20/07 Screen Length: Diameter: PVC Type: Slot Size: Casing Length: -

	Method: Geoprobe					End Date: 6/20/07	Diameter: -	
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (inches)	Description	Depth (feet)	Lithology
		0' - 1'	0.0	VC	VC	Brown SAND	_	
-1		1' - 2'	0.0	VC	VC	Brown SAND	1-	
-2		2' - 3'	0.0	VC	VC	Brown SAND	2	
-3	SB-17	3' - 4'	0.0	VC	VC	Brown SILT and CLAY, trace Sand	3-	
-4	(3' - 4')	4' - 5'	1.9	VC	VC		4-	
-			1.9			Brown SILT and CLAY, trace Sand, wet	-	
- 5		5' - 9'	0.0	NA	48"/48"	Brown CLAY and SILT, wet	5-	
-6							6-	
7							7-	
-8							8-	
-							-	
-9		9' - 9.5' 9.5'-13	0.0	NA NA	48"/48"	Brown CLAY and SILT, wet	9-	
10						Brown coarse SAND, and Gravel (lithic fragments), wet	10-	
-11							11-	
12							12-	
- -13		13' - 17'	0.0	NA	40"/48"		13	
H		13 - 17	0.0	INA	40 /40	Brown coarse SAND, and Gravel (lithic fragments), wet	-	
14							14-	
15							15-	
16							16-	
17		17' - 21'	0.0	NA	6"/48"		17	
-		., _!	0.0	14/1	0,40	Brown coarse SAND, and Gravel (lithic fragments), wet	-	
18							18-	
19							19-	
-20							20 —	
-21							21 —	

Notes:

VC Vacuum Clear fbg Feet below grade

NA Not Available NSVD Not Surveyed to Vertical Datum

BDL Below Instrument Detection Limit of 0.1 ppmv ppmv Parts Per Million by Volume

K L E N F E L D E R 7 Airport Boulevard, Latham, New York Phone: (518) 786-8750 Fax: (518) 786-8755

E R Bore Log

SB-18

Project: Fort Covington

Client: Town of Fort Covington

Location: 2510 Chateaugay St., Fort Covington, N.Y. 12937

Drilling Co.: OPTECH Driller: Joseph Maselli Method: Geoprobe Boring ID: SB-18

Casing Elevation: NSVD

Total Depth: 15

Depth to First Observed Water: 5'

Start Date: 6/21/07 End Date: 6/21/07 Screen Length: -Diameter: -

PVC Type: -Slot Size: -Casing Length: -

Diameter: -

Met	hod: Ge	oprobe				End Date: 6/21/07 Di	iameter: -	
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (inches)	Description	Depth (feet)	Lithology
-		0' - 1'	0.0	VC	VC	Brown SAND, some fine Gravel	-	
-1		1' - 2'	0.0	VC	vc	Brown SAND, some fine Gravel	1-	
-							-	
-2		2' - 3'	0.0	VC	VC	Brown SILT and CLAY, trace fine Sand	2-	
-3		3' - 4'	0.0	VC	VC -		3-	
-	SB-18 (3' - 4')	0 4	0.0	•••		Brown SILT and CLAY, moist	-	
-4	(0 .)	4' - 5'	0.0	VC	VC	Brown SILT and CLAY, wet	4-	
-							-	
- 5		5' - 9'	0.0	NA	36"/48"	Brown to Grey SILT and CLAY, wet	5-	
_ _6							6-	
-								
-7							7-	
-							-	
<u>8</u>							8-	
_ ₉		9' - 13'	0.0	NA	40"/48"	Drawn array CAND wat	9-	
-						Brown coarse SAND, wet	-	
-10							10-	
١							-	
-11							11 -	
-12							12-	
-							-	
-13		13' - 15'	0.0	NA	24"/48"	Brown coarse SAND, Rock fragments lodged in split spoon head,	wet 13-	
						, , , , , , , , , , , , , , , , , , , ,	14-	
<u>-</u> 14							14-	
-15						Boring Refusal @ 15fbg	15	
						Doing Holada & Talby	-	

Notes:

VC Vacuum Clear

fbg

Feet below grade

NA Not Available

NSVD

Not Surveyed to Vertical Datum

BDL Below Instrument Detection Limit of 0.1 ppmv

ppmv

Parts Per Million by Volume

7 Airport Boulevard, Latham, New York Phone: (518) 786-8750 Fax: (518) 786-8755

Boring ID: SB-19 Casing Elevation: NSVD

Total Depth: 12

SB-19

Screen Length: -Diameter: -PVC Type: -Slot Size: -

Bore Log

Drilling Co.: OPTECH Depth to First Observed Water: 5' Start Date: 6/21/07 Driller: Joseph Maselli Casing Length: -Method: Geoprobe End Date: 6/21/07 Diameter: -Recovery / Penetration (inches) PID Headspace (ppmv) Sample Interval (feet) Depth (Feet) Description Lithology Depth (feet) Sample ID Blow / 6"

					Brown SAND, little Silt, little fine Gravel		
	0' - 1'	0.0	VC	VC		-	
	1' - 2'	0.0	VC	VC	Brown SILT, trace Sand, trace Clay	1-	
					•	-	
	2' - 3'	0.0	VC	VC	Brown SILT trace Clay	2-	
					Dismissizi, addo sidy	-	
	3' - 4'	0.0	VC	VC	Rrown SILT trace Clay	3-	
SB-19 (3' - 4')					Blown Sici, trace Gray	_	
,		0.0	VC	VC	Drawer CHT to an Olev with	4-	
					Brown SIL1, trace Clay, wet	_	
	5' - 9'	0.3	NA	48"/48"		5-	
					Brown CLAY and SIL1, wet	_	
						6-	
						_	
						7-	
						0	
	01 401	0.0		0.411/4.011			
	9' - 12'	0.0	NA	24"/48"	Brown CLAY and SILT. Rock fragments lodged in split spoon head, wet	9-	
						_	
						10-	
						-	
						11-	
						-	
					Boring Refusal @ 12fgg	12-	
	SB-19 (3' - 4')	1' - 2' 2' - 3'	1' - 2' 0.0 2' - 3' 0.0 SB-19 (3' - 4') 4' - 5' 0.0 5' - 9' 0.3	1' - 2' 0.0 VC 2' - 3' 0.0 VC 3' - 4' 0.0 VC SB-19 (3' - 4') 4' - 5' 0.0 VC 5' - 9' 0.3 NA	1' - 2' 0.0 VC VC 2' - 3' 0.0 VC VC SB-19 (3' - 4') 0.0 VC VC 5' - 9' 0.3 NA 48"/48"	0'-1' 0.0	0'-1' 0.0 VC VC VC Brown SiLT, trace Sand, trace Clay 1-2' 0.0 VC VC Brown SiLT, trace Clay 2-3' 0.0 VC VC Brown SiLT, trace Clay 3'-4' 0.0 VC VC Brown SiLT, trace Clay 3-4'-5' 0.0 VC VC Brown SiLT, trace Clay 4'-5' 0.0 VC VC Brown SiLT, trace Clay 4'-5' 0.0 VC VC Brown SiLT, trace Clay, wet 4-5'-5' 0.3 NA 48'/48" Brown CLAY and SiLT, wet 5-6'-6' 8-6'-6' 10-6' 1

Notes:

Project: Fort Covington

Client: Town of Fort Covington

Location: 2510 Chateaugay St., Fort Covington, N.Y. 12937

VC Vacuum Clear fbg Feet below grade

NA Not Available NSVD Not Surveyed to Vertical Datum

BDL Below Instrument Detection Limit of 0.1 ppmv

Parts Per Million by Volume ppmv

K L E N F E L D E R 7 Airport Park Boulevard Latham, NewYork Phone: (518) 786-8750 Fax: (518) 786-8755

Well Log

SB-20/ MW-9

Project: Fort Covington
Client: Town of Fort Covington

Location: 2510 Chateaugay St., Fort Covington, N.Y. 12937

Drilling Co.: OPTECH Driller: Joseph Maselli

Method: Geoprobe/Hollow Stem Auger

Boring ID: SB-20/MW-9 Casing Elevation: NSVD

Total Depth: 20

Depth to First Observed Water: 5'

Start Date: 6/20/07 End Date: 6/20/07 Screen Length: 17' Diameter: 2"

PVC Type: Schedule 40 Slot Size: 0.010"

Casing Length: 3' Diameter: 2"

ivieti	iou. Geop	TODE/TION	ow Stem Au	igei		End Date: 6/20/07 Diameter: 2"			
Depth (Feet)	Sample ID	Sample Interval (feet)	PID Headspace (ppmv)	Blow / 6"	Recovery / Penetration (inches)	Description	Depth (feet)	Well Diagram	Lithology
- -1		0' - 1' 1' - 2'	0.0 0.0	VC VC	VC VC	Brown fine SAND and fine Gravel Brown SAND Backfill	1-		
-2		2' - 3'	0.0	VC	VC	Brown SILT and CLAY	2-	>	
-3	SB-20 / MW-9 (3'	3' - 4'	0.0	VC	VC	2" PVC Riser — Brown SILT and CLAY: SB-201(3' - 4') collected as duplicate of SB- 20 (3' - 4')	3-		
-4 - -5	- 4')	4' - 5' 5' - 9'	0.0	VC NA	VC 48"/48"	Brown SILT and CLAY, wet	4- - 5-		
- -6		5-9	0.0	NA	40 /40	Brown to grey SILT and CLAY, moist	6-		
-7							7-		
-8 -						No. 2 Sand —	8-		
-9 - -10		9' - 13'	0.0	NA	48"/48"	Brown SILT and CLAY, wet	9-		
-11							11-		
- -12 -							12-		
-13 -		13' - 17'	0.0	NA	48"/48"	Grey SILT and CLAY, little fine Sand, wet	13-		
- 14 - - 15						2" 0.010" Slot Screen —	14-		
- -16							16-		
- 17 -		17' - 21'	0.0	NA	48"/48"	Grey coarse SAND, wet	17— -		
- 18 - - 19							18- - 19-		
- 20							20 —		
-21							21 —		

Notes: VC

NA

Vacuum Clear

Not Available

Denotes Sample collected for laboratory analysis

fbg Feet below grade

NS Not Sampled

NR No Recovery

ppmv parts per million by volume

KLEINFELDER

Bore Log

SB-21

7 Airport Boulevard, Latham, New York Phone: (518) 786-8750 Fax: (518) 786-8755

Project: Fort Covington
Client: Town of Fort Covington

Location: 2510 Chateaugay St., Fort Covington, N.Y. 12937

Drilling Co.: OPTECH Driller: Joseph Maselli Method: Geoprobe Boring ID: SB-21 Casing Elevation: NSVD

Total Depth: 21

Depth to First Observed Water: 5'

Start Date: 6/21/07 End Date: 6/21/07 Screen Length: -Diameter: -PVC Type: -Slot Size: -Casing Length: -

Diameter: -

Recovery / Penetration (inches) PID Headspace (ppmv) (feet) Depth (Feet) Description Lithology Depth (feet) Sample ID Blow / 6" Sample Interval (Brown SAND, some Cobbles VC 0' - 1' 0.0 VC 1' - 2' 0.0 VC VC Brown SAND, some Cobbles -2 2' - 3' 0.0 VC VC 2 SAND, some Cobbles (fill material (bricks)) .3 3' - 4' VC VC 3 0.0 Brown CLAY and SILT SB-21 (3' - 4') 4' - 5' 0.0 VC VC Brown to grey CLAY and SILT, wet -5 5' - 9' 0.3 NA 48"/48" 5 Brown to grey CLAY and SILT, wet 6 6 -8 8-9 9' - 13' 48"/48" 9 0.0 NA Brown to grey CLAY and SILT, wet 10 10 -11 12 13 13' - 17' 0.3 NA 48"/48" 13 Brown to grey CLAY and SILT, with a 1" lens of Sand @ 14', wet 14 - 14 15 15 -16 16 17' - 21' 15"/48" 17 0.0 NA Brown to grey CLAY and SILT, wet 18 18 -19 19

Notes:

-20

21

VC Vacuum Clear

fbg Feet below grade

NA Not Available

NSVD Not Surveyed to Vertical Datum

20

BDL Below Instrument Detection Limit of 0.1 ppmv

ppmv Parts Per Million by Volume

_	_	_					_
	\mathbf{n}	_			D	w	
Д	$\boldsymbol{-}$	_	_	N			
_			_	•	_	_	_

Community Air Monitoring Data (VOC's)

Instrument: Multi-gas Monitor (PGM50-5P) Se

Serial Number: 517014

User ID: 00000001 Site ID: 0 Data Points: 394 Data Type

Site ID: 00000001 Data Type: Avg

Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low Alarm Levels:		35.0	50.0	10.	0 10.0	19.5 		
Line# Date		te Time	CO(ppm)	VOC	(ppm)	H2S(ppm)	LEL(%)	OXY(%)
1	06/19/20	07 08:30	0.0	0.4	0.0		20.9	
2	06/19/20	07 08:31	0.0	0.4	0.0		20.9	
	06/19/20			0.4	0.0	0.0	20.9	
	06/19/20			0.5	0.0	0.0	20.9	
				0.4	0.0	0.0	20.9	
	06/19/20			0.4	0.0	0.0	20.9	
				0.3	0.1	0.0	20.9	
	06/19/20			0.3	0.1	0.0	20.9	
	06/19/20			0.3	0.1	0.0	20.9	
	06/19/20			0.2	0.1		20.9	
	06/19/20			0.1	0.1		20.9	
	06/19/20			0.0	0.1		20.9	
	06/19/20			0.0	0.1		20.9	
	06/19/20			0.0	0.1		20.9	
	06/19/20			0.0	0.1		20.9	
	06/19/20			0.0	0.1		20.9	
	06/19/20			0.0	0.1		20.9	
	06/19/20			0.0	0.0		20.9	
	06/19/20			0.0	0.0		20.9	
	06/19/20			0.0	0.1		20.9	
	06/19/20			0.0	0.1		20.9	
	06/19/20			0.0	0.0		20.9	
	06/19/20			0.0	0.0		20.9	
	06/19/20			0.0	0.0		20.9	
	06/19/20			0.0	0.0		20.9	
	06/19/20			0.0	0.0		20.9	
	06/19/20			0.0	0.0		20.9	
	06/19/20			0.0	0.0		20.9	
	06/19/20 06/19/20			0.0	0.0		20.9 20.9	
	06/19/20			0.0	0.0		20.9	
	06/19/20			0.0	0.0 0.0		20.9	
	06/19/20			0.0	0.0		20.9	
	06/19/20			0.0	0.0		20.9	
	06/19/20			0.0	0.0		20.9	
	06/19/20			0.0	0.0		20.9	
	06/19/20			0.0	0.0		20.9	
	06/19/20			0.0	0.0		20.9	
	06/19/20			0.0	0.0		20.9	
	06/19/20			0.0	0.0		20.9	
	06/19/20			0.0	0.0		20.9	
41	00/19/20	<i>Jui</i> 08.10	0.0	0.0	U.C	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 394 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low	Alarm Lev	els: 	35.0 	50.0	10.0	10.0	19.5 	
Line	# Date	Time					LEL(%)	OXY(%)
42	06/19/200	7 09:11	0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200 06/19/200		0.0	0.0	0.0 0.0	0.0	20.9 20.9	
	06/19/200		0.0	0.0		0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0 0.0	0.0	0.0 0.0	0.0 0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0				20.9	
	06/19/200		0.0	0.0	0.0 0.0	0.0 0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
02	00/19/200	10.51	0.0	0.0	0.0	0.0	۷٠.5	

User ID: 00000001 Site ID: 00000001

Data Points: 394 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low Alarm Levels:		35.0 	50.0 	10.0	10.0	19.5 		
Line	====== # Date ======	Time					LEL(%)	
83	06/19/200	07 09:52	0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
91	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/20		0.0	0.0	0.0	0.0	20.9	
	06/19/20			0.0	0.0	0.0	20.9	
	06/19/20		0.0	0.0	0.0	0.0	20.9	
	06/19/20			0.0	0.0	0.0	20.9	
	06/19/20		0.0	0.0	0.0	0.0	20.9	
	06/19/20		0.0	0.0	0.0	0.0	20.9	
	06/19/20		0.0	0.0	0.0	0.0	20.9	
	06/19/20		0.0	0.0	0.0	0.0	20.9	
	06/19/20			0.0	0.0	0.0	20.9	
	06/19/20		0.0	0.0	0.0	0.0	20.9	
	06/19/20		0.0	0.0	0.0	0.0	20.9	
	06/19/20			0.0	0.0	0.0	20.9	
	06/19/20		0.0	0.0	0.0	0.0	20.9	
	06/19/20			0.0	0.0	0.0	20.9	
	06/19/20		0.0	0.0	0.0	0.0	20.9	
	06/19/20		0.0	0.0	0.0	0.0	20.9	
	06/19/20			0.0	0.0	0.0	20.9	
	06/19/20			0.0	0.0	0.0	20.9	
	06/19/20 06/19/20			0.0	0.0	0.0	20.9	
	06/19/20			0.0	0.0	0.0 0.0	20.9 20.9	
	06/19/20			0.0	0.0			
	06/19/20		0.0 0.0	0.0	0.0	0.0 0.0	20.9 20.9	
	06/19/20			0.0	0.0	0.0	20.9	
123	00/19/20	01 10.32	0.0	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 394 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low	Alarm Levels:	35.0	50.0	10.0	10.0	19.5	
Line#	Date Time					LEL(%)	
	06/19/2007 10:3		0.0	0.0	0.0	20.9	
	06/19/2007 10:3		0.0	0.0	0.0	20.9	
	06/19/2007 10:3		0.0	0.0	0.0	20.9	
	06/19/2007 10:3		0.0	0.0	0.0	20.9	
	06/19/2007 10:3		0.0	0.0	0.0	20.9	
	06/19/2007 10:3		0.0	0.0	0.0	20.9	
	06/19/2007 10:3		0.0	0.0	0.0	20.9	
	06/19/2007 10:4		0.0	0.1	0.0	20.9	
	06/19/2007 10:4		0.0	0.1	0.0	20.9	
	06/19/2007 10:4		0.0	0.1	0.0	20.9	
	06/19/2007 10:4		0.0	0.1	0.0	20.9	
	06/19/2007 10:4		0.0	0.1	0.0	20.9	
	06/19/2007 10:4		0.0	0.1	0.0	20.9	
	06/19/2007 10:4		0.0	0.1	0.0	20.9	
	06/19/2007 10:4		0.0	0.1	0.0	20.9	
	06/19/2007 10:4		0.0	0.1	0.0	20.9	
	06/19/2007 10:4		0.0	0.1	0.0	20.9	
	06/19/2007 10:5		0.0	0.1	0.0	20.9	
	06/19/2007 10:5		0.0	0.1	0.0	20.9	
	06/19/2007 10:5		0.0	0.1	0.0	20.9	
	06/19/2007 10:5		0.0	0.1	0.0	20.9	
	06/19/2007 10:5		0.0	0.1	0.0	20.9	
	06/19/2007 10:5		0.0	0.1	0.0	20.9	
	06/19/2007 10:50		0.0	0.1	0.0	20.9	
	06/19/2007 10:5		0.0	0.1	0.0	20.9	
	06/19/2007 10:5		0.0	0.1	0.0	20.9	
	06/19/2007 10:59		0.0	0.1	0.0	20.9	
	06/19/2007 11:0		0.0	0.1	0.0	20.9	
	06/19/2007 11:0		0.0	0.1	0.0	20.9	
	06/19/2007 11:0		0.0	0.1	0.0	20.9	
	06/19/2007 11:03		0.0	0.1	0.0	20.9	
	06/19/2007 11:0		0.0	0.1	0.0	20.9	
	06/19/2007 11:0		0.0	0.1	0.0	20.9	
	06/19/2007 11:0		0.0	0.1	0.0	20.9	
	06/19/2007 11:0		0.0	0.1	0.0	20.9	
	06/19/2007 11:0		0.0	0.1	0.0	20.9	
	06/19/2007 11:09		0.0	0.1	0.0	20.9	
	06/19/2007 11:10		0.0	0.1	0.0	20.9	
	06/19/2007 11:1		0.0	0.1	0.0	20.9	
	06/19/2007 11:1:		0.0	0.1	0.0	20.9	
164	06/19/2007 11:1:	3 0.0	0.0	0.1	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 394 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

LOW	Alailli Lev	eis. 	33.0	50.0	10.0	10.0	19.5		
Line#		Time	CO(ppm)				LEL(%)	OXY(%)	
165	06/19/200	07 11:14	0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.2	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
	06/19/200		0.0	0.0	0.1	0.0	20.9		
205	06/19/200)/ 11:54	0.0	0.0	0.1	0.0	20.9		

User ID: 00000001 Site ID: 00000001

Data Points: 394 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

LOW	Alarm Lev	eis:	35.0	50.0	10.0	10.0	19.5	
Line#	Date	Time		VOC(ppm)	H2S(ppm)	LEL(%)	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
207	06/19/200	07 11:56	0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.2	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.2		20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.2	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200	_	0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200 06/19/200		0.0	0.0	0.1	0.0	20.9	
			0.0	0.0	0.1	0.0	20.9	
	06/19/200 06/19/200		0.0	0.0	0.1	0.0	20.9	
			0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
240	06/19/200	JI 12:35	0.0	0.0	0.1	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 394 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low Alarm Levels:			35.0 	50.0	10.0		19.5 	
Line#		Time			opm) I	H2S(ppm)	LEL(%)	OXY(%)
247	06/19/200	7 12:36	0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200 06/19/200		0.0	0.0	0.1 0.1	0.0	20.9 20.9	
	06/19/200		0.0 0.0	0.0	0.1	0.0 0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1		20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.1	0.0	20.9	
	06/19/200		0.0	0.0	0.0		20.9	
	06/19/200		0.0	0.0	0.0		20.9	
	06/19/200		0.0	0.0	0.0		20.9	
	. J J JC		0.0	5.5	0.0	5.0		

User ID: 00000001 Site ID: 00000001

Data Points: 394 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

LOW	Alailli Lev	eis. 	33.0	50.0	10.0	10.0	19.5	
Line#		Time	CO(ppm)					OXY(%)
288	06/19/200	07 13:17	0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
	06/19/200		0.0	0.0	0.0	0.0	20.9	
3 2 8	06/19/200	J/ 13:5/	0.0	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 394 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low	Alarm Levels:	35.0	50.0	10.0	10.0	19.5	
Line#	Date Time	CO(ppm)	VOC(p	ppm) H2		LEL(%)	OXY(%)
	06/19/2007 13:58	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 13:59	0.0	0.0	0.0	0.0	20.9	
331	06/19/2007 14:00	0.0	0.0	0.0	0.0	20.9	
332	06/19/2007 14:01	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:02	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:03	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:04	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:05	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:06	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:07	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:08	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:09	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:10	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:11	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:12	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:13	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:14	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:15	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:16	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:17		0.0	0.0	0.0	20.9	
	06/19/2007 14:18	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:19	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:20	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:21	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:22	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:23	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:24	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:25	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:26	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:27		0.0	0.0	0.0	20.9	
	06/19/2007 14:28	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:29	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:30	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:31	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:32		0.0	0.0	0.0	20.9	
	06/19/2007 14:33	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:34	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:35	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:36	0.0	0.0	0.0	0.0	20.9	
	06/19/2007 14:37		0.0	0.0	0.0	20.9	
369	06/19/2007 14:38	0.0	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 394 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low Alarm Levels:				S: 	35.0	50.0	10.0	10.0	19.5 	
Lin	== ne# ===	# D	ate T	ime	CO(ppm)	VOC(ppm) H:	2S(ppm)	LEL(%)	OXY(%)
37	70	06/19/	/2007	14:39	0.0	0.0	0.0	0.0	20.9	
37	71	06/19/	2007	14:40	0.0	0.0	0.0	0.0	20.9	
37	72	06/19/	/2007	14:41	0.0	0.0	0.0	0.0	20.9	
37	73	06/19/	/2007	14:42	0.0	0.0	0.0	0.0	20.9	
37	74	06/19/	/2007	14:43	0.0	0.0	0.0	0.0	20.9	
37	75	06/19/	/2007	14:44	0.0	0.0	0.0	0.0	20.9	
37	76	06/19/	/2007	14:45	0.0	0.0	0.0	0.0	20.9	
37	77	06/19/	/2007	14:46	0.0	0.0	0.0	0.0	20.9	
37	78	06/19/	/2007	14:47	0.0	0.0	0.0	0.0	20.9	
37	79	06/19/	/2007	14:48	0.0	0.0	0.0	0.0	20.9	
38	30	06/19/	2007	14:49	0.0	0.0	0.0	0.0	20.9	
38	31	06/19/	2007	14:50	0.0	0.0	0.0	0.0	20.9	
38	32	06/19/	2007	14:51	0.0	0.0	0.0	0.0	20.9	
38	33	06/19/	2007	14:52	0.0	0.0	0.0	0.0	20.9	
38	34	06/19/	2007	14:53	0.0	0.0	0.0	0.0	20.9	
38	35	06/19/	2007	14:54	0.0	0.0	0.0	0.0	20.9	
38	36	06/19/	/2007	14:55	0.0	0.0	0.0	0.0	20.9	
38	37	06/19/	/2007	14:56	0.0	0.0	0.0	0.0	20.9	
38	38	06/19/	/2007	14:57	0.0	0.0	0.0	0.0	20.9	
38	39	06/19/	/2007	14:58	0.0	0.0	0.0	0.0	20.9	
39	90	06/19/	/2007	14:59	0.0	0.0	0.0	0.0	20.9	
39	91	06/19/	/2007	15:00	0.0	0.0	0.0	0.0	20.9	
39	92	06/19/	/2007	15:01	0.0	0.0	0.0	0.0	20.9	
39	93	06/19/	/2007	15:02	0.0	0.0	0.0	0.0	20.9	
39	94	06/19/	/2007	15:03	0.0	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 127 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low	Alarm Leve	els:	35.0	50.0	10.	0 10.0	19.5	
Line		Time	,	,,		H2S(ppm)	. ,	OXY(%)
	06/20/2007		0.0	0.0	0.0		20.9	
2	06/20/2007	7 08:22	0.0	0.0	0.0	0.0	20.9	
3	06/20/2007	7 08:23	0.0	0.0	0.0	0.0	20.9	
4	06/20/2007	7 08:24	0.0	0.0	0.0	0.0	20.9	
5	06/20/2007	7 08:25	0.0	0.0	0.0	0.0	20.9	
6	06/20/2007	7 08:26	0.0	0.0	0.0	0.0	20.9	
7	06/20/2007	7 08:27	0.0	0.0	0.0	0.0	20.9	
8	06/20/2007	7 08:28	0.0	0.0	0.0	0.0	20.9	
9	06/20/2007	7 08:29	0.0	0.0	0.0	0.0	20.9	
10	06/20/200	7 08:30	0.0	0.0	0.0	0.0	20.9	
11	06/20/200	7 08:31	0.0	0.0	0.0	0.0	20.9	
12	06/20/200	7 08:32	0.0	0.0	0.0	0.0	20.9	
13	06/20/200	7 08:33	0.0	0.0	0.0	0.0	20.9	
14	06/20/200	7 08:34	0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
	06/20/200		0.0	0.0	0.0		20.9	
41	06/20/200	7 09:01	0.0	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 127 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low Alarm Levels:		35.0 	50.0	10.0	10.0	19.5 		
Line	# Date	Time					LEL(%)	OXY(%)
42	06/20/200	7 09:02	0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
51	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
			0.0	0.0	0.0	0.0	20.9	
	06/20/200° 06/20/200°		0.0	0.0	0.0	0.0	20.9 20.9	
	06/20/200		0.0 0.0	0.0	0.0 0.0	0.0 0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0				20.9	
	06/20/200		0.0	0.0	0.0 0.0	0.0 0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
	06/20/200		0.0	0.0	0.0	0.0	20.9	
02	00/20/200	1 09.42	0.0	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 127 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

LOW	Alarm Levels:	35.0	50.0	10.0	10.0	19.5	
Line	# Date Time	CO(ppm)	VOC(====== ppm) H2 ======	====== 2S(ppm) ======	====== LEL(%) ======	OXY(%)
83	06/20/2007 09:43	0.0	0.0	0.0	0.0	20.9	
84	06/20/2007 09:44	0.0	0.0	0.0	0.0	20.9	
85	06/20/2007 09:45	0.0	0.0	0.0	0.0	20.9	
86	06/20/2007 09:46	0.0	0.0	0.0	0.0	20.9	
87	06/20/2007 09:47	0.0	0.0	0.0	0.0	20.9	
88	06/20/2007 09:48	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 09:49	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 09:50	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 09:51	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 09:52	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 09:53	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 09:54	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 09:55	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 09:56	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 09:57	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 09:58	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 09:59	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 10:00	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 10:01	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 10:02	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 10:03	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 10:04	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 10:05	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 10:06	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 10:07	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 10:08	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 10:09	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 10:10	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 10:11	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 10:12	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 10:13	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 10:14	0.0	0.0	0.0	0.0	20.9	
_	06/20/2007 10:15 06/20/2007 10:16	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 10:16	0.0 0.0	0.0	0.0	0.0	20.9	
				0.0	0.0	20.9	
	06/20/2007 10:18 06/20/2007 10:19	0.0 0.0	0.0	0.0 0.0	0.0 0.0	20.9 20.9	
	06/20/2007 10:19	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 10:20	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 10:21	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 10:22 06/20/2007 10:23	0.0	0.0	0.0	0.0	20.9	
123	00/20/2007 10:23	0.0	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 127 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Line# 	: Date	Time	CO(ppm)	VOC(pp	om) 	H2S(ppm)	LEL(%)	OXY(%)	 _
 124	06/20/200	7 10:24	0.0	0.0	0.0	0.0	20.9		 _
125	06/20/200	7 10:25	0.0	0.0	0.0	0.0	20.9		
126	06/20/200	7 10:26	0.0	0.0	0.0	0.0	20.9		
127	06/20/200	7 10:27	0.0	0.0	0.0	0.0	20.9		

User ID: 00000001 Site ID: 00000001

Data Points: 187 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low	Alarm Levels:	35.0	50.0	10.	0 10.0	19.5	
Line	# Date Time				H2S(ppm)		OXY(%)
	06/20/2007 11:20	0.0	0.0	0.0		20.9	
2	06/20/2007 11:21	0.0	0.0	0.0	0.0	20.9	
3	06/20/2007 11:22	0.0	0.0	0.0	0.0	20.9	
4	06/20/2007 11:23	0.1	0.0	0.0	0.0	20.9	
5	06/20/2007 11:24	0.0	0.0	0.0	0.0	20.9	
6	06/20/2007 11:25	0.0	0.0	0.0	0.0	20.9	
7	06/20/2007 11:26	0.0	0.0	0.0	0.0	20.9	
8	06/20/2007 11:27	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 11:28	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 11:29	0.0	0.0	0.0		20.9	
	06/20/2007 11:30	0.0	0.0	0.0		20.9	
	06/20/2007 11:31	0.0	0.0	0.0		20.9	
	06/20/2007 11:32	0.0	0.0	0.0		20.9	
	06/20/2007 11:33	0.0	0.0	0.0		20.9	
	06/20/2007 11:34	0.0	0.0	0.0		20.9	
	06/20/2007 11:35	0.0	0.0	0.0		20.9	
	06/20/2007 11:36	0.0	0.0	0.0		20.9	
	06/20/2007 11:37	0.0	0.0	0.0		20.9	
	06/20/2007 11:38	0.0	0.0	0.0		20.9	
	06/20/2007 11:39	0.0	0.0	0.0		20.9	
	06/20/2007 11:40	0.0	0.0	0.0		20.9	
	06/20/2007 11:41	0.0	0.0	0.0		20.9	
	06/20/2007 11:42	0.0	0.0	0.0		20.9	
	06/20/2007 11:43	0.0	0.0	0.0		20.9	
	06/20/2007 11:44 06/20/2007 11:45	0.0	0.0	0.0		20.9	
	06/20/2007 11:46	0.0	0.0	0.0		20.9 20.9	
	06/20/2007 11:47	0.0 0.1	0.0	0.0		20.9	
	06/20/2007 11:48	0.1	0.0	0.0		20.9	
	06/20/2007 11:49	0.0	0.0	0.0		20.9	
	06/20/2007 11:50	0.0	0.0	0.0		20.9	
	06/20/2007 11:51	0.0	0.0	0.0		20.9	
	06/20/2007 11:52	0.0	0.0	0.0		20.9	
	06/20/2007 11:53	0.0	0.0	0.0		20.9	
	06/20/2007 11:54	0.0	0.0	0.0		20.9	
	06/20/2007 11:55	0.0	0.0	0.0		20.9	
	06/20/2007 11:56	0.0	0.0	0.0		20.9	
	06/20/2007 11:57	0.0	0.0	0.0		20.9	
	06/20/2007 11:58	0.0	0.0	0.0		20.9	
	06/20/2007 11:59	0.0	0.0	0.0		20.9	
	06/20/2007 12:00	0.0	0.0	0.0		20.9	
			-				

User ID: 00000001 Site ID: 00000001

Data Points: 187 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low	Alarm Levels:	35.0 	50.0 	10.0 	10.0	19.5 	
Line	# Date Time					LEL(%)	OXY(%)
42	06/20/2007 12:01	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:02	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:03	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:04	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:05	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:06	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:07	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:08	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:09	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:10	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:11	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:12	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:13	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:14	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:15	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:16	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:17	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:18	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:19	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:20	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:21	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:22	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:23	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:24	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:25	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:26	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:27 06/20/2007 12:28	0.0	0.0	0.0	0.0	20.9 20.9	
	06/20/2007 12:29	0.0 0.0	0.0	0.0 0.0	0.0 0.0	20.9	
	06/20/2007 12:30	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:31	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:31	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:33	0.0				20.9	
	06/20/2007 12:34	0.0	0.0	0.0 0.0	0.0 0.0	20.9	
	06/20/2007 12:35	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:36	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:37	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:38	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:39	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:39	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:41	0.0	0.0	0.0	0.0	20.9	
02	00/20/2001 12.41	0.0	0.0	0.0	0.0	20.5	

User ID: 00000001 Site ID: 00000001

Data Points: 187 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

LOW	Alarm Levels:	35.0	50.0	10.0	10.0	19.5	
Line	======================================		VOC(===== ppm) Н ======		LEL(%)	OXY(%)
83	06/20/2007 12:42	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:43	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:44	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:45	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:46	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:47	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:48	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:49	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:50	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:51	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:52	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:53	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:54	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:55	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:56	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:57	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:58	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 12:59	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:00	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:01 06/20/2007 13:02	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:02	0.0	0.0	0.0	0.0	20.9 20.9	
	06/20/2007 13:03	0.0 0.0	0.0	0.0 0.0	0.0 0.0	20.9	
	06/20/2007 13:04	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:06	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:07	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:08	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:09	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:10	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:10	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:11	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:13	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:14	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:15	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:16	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:17	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:17	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:10	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:19	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:21	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:21	0.0	0.0	0.0	0.0	20.9	
120	00/20/2001 10.ZZ	0.0	5.0	0.0	0.0	20.0	

User ID: 00000001 Site ID: 00000001

Data Points: 187 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

LOW	Alaiiii Leveis.	35.0	50.0	10.0	10.0	19.5	
Line#		CO(ppm)					OXY(%)
124	06/20/2007 13:23	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:24		0.0	0.0	0.0	20.9	
	06/20/2007 13:25		0.0	0.0	0.0	20.9	
	06/20/2007 13:26		0.0	0.0	0.0	20.9	
	06/20/2007 13:27		0.0	0.0	0.0	20.9	
	06/20/2007 13:28		0.0	0.0	0.0	20.9	
	06/20/2007 13:29		0.0	0.0	0.0	20.9	
	06/20/2007 13:30		0.0	0.0	0.0	20.9	
	06/20/2007 13:31	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:32		0.0	0.0	0.0	20.9	
	06/20/2007 13:33		0.0	0.0	0.0	20.9	
	06/20/2007 13:34		0.0	0.0	0.0	20.9	
	06/20/2007 13:35	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:36		0.0	0.0	0.0	20.9	
	06/20/2007 13:37		0.0	0.0	0.0	20.9	
	06/20/2007 13:38	0.0	0.0	0.1	0.0	20.9	
	06/20/2007 13:39		0.0	0.1	0.0	20.9	
	06/20/2007 13:40		0.0	0.1	0.0	20.9	
	06/20/2007 13:41	0.1	0.0	0.1	0.0	20.9	
	06/20/2007 13:42		0.0	0.1	0.0	20.9	
	06/20/2007 13:43		0.0	0.1	0.0	20.9	
	06/20/2007 13:44		0.0	0.1	0.0	20.9	
	06/20/2007 13:45		0.0	0.1	0.0	20.9	
	06/20/2007 13:46		0.0	0.1	0.0	20.9	
	06/20/2007 13:47		0.0	0.1	0.0	20.9	
	06/20/2007 13:48		0.0	0.1	0.0	20.9	
	06/20/2007 13:49		0.0	0.1	0.0	20.9	
	06/20/2007 13:50		0.0	0.1	0.0	20.9	
	06/20/2007 13:51 06/20/2007 13:52	3.8	0.0	0.1	0.0	20.9	
	06/20/2007 13:53	5.2 2.4	0.0	0.1	0.0	20.9 20.9	
	06/20/2007 13:54	0.4	0.0	0.1 0.0	0.0 0.0	20.9	
	06/20/2007 13:55	1.4	0.0	0.0	0.0	20.9	
	06/20/2007 13:56	8.4	0.0	0.0	0.0	20.9	
	06/20/2007 13:57		0.0	0.0	0.0	20.9	
	06/20/2007 13:58	1.4	0.0	0.0	0.0	20.9	
	06/20/2007 13:59	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 13:39		0.0	0.0	0.0	20.9	
	06/20/2007 14:00	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 14:01		0.0	0.0	0.0	20.9	
	06/20/2007 14:02 06/20/2007 14:03		0.0	0.0	0.0	20.9	
104	00/20/2007 14.03	0.0	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 187 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

200.0 100.0 20.0 20.0 23.5 High Alarm Levels: 35 N 50.0 10.0 10.0

Low Alarm Levels:		35.0	50.0	10.0	10.0	19.5 	
Line	# Date Time	CO(ppm)	VOC(p	pm) H	2S(ppm)	LEL(%)	OXY(%)
165	06/20/2007 14:04	0.0	0.0	0.0	0.0	20.9	
166	06/20/2007 14:05	0.0	0.0	0.0	0.0	20.9	
167	06/20/2007 14:06	0.0	0.0	0.0	0.0	20.9	
168	06/20/2007 14:07	0.0	0.0	0.0	0.0	20.9	
169	06/20/2007 14:08	0.0	0.0	0.0	0.0	20.9	
170	06/20/2007 14:09	0.0	0.0	0.0	0.0	20.9	
171	06/20/2007 14:10	0.0	0.0	0.0	0.0	20.9	
172	06/20/2007 14:11	0.0	0.0	0.0	0.0	20.9	
173	06/20/2007 14:12	0.0	0.0	0.0	0.0	20.9	
174	06/20/2007 14:13	0.0	0.0	0.0	0.0	20.9	
175	06/20/2007 14:14	0.0	0.0	0.0	0.0	20.9	
176	06/20/2007 14:15	0.0	0.0	0.0	0.0	20.9	
177	06/20/2007 14:16	0.0	0.0	0.0	0.0	20.9	
178	06/20/2007 14:17	0.0	0.0	0.0	0.0	20.9	
179	06/20/2007 14:18	0.0	0.0	0.0	0.0	20.9	
180	06/20/2007 14:19	0.0	0.0	0.0	0.0	20.9	
181	06/20/2007 14:20	0.0	0.0	0.0	0.0	20.9	
182	06/20/2007 14:21	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 14:22	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 14:23	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 14:24	0.0	0.0	0.0	0.0	20.9	
	06/20/2007 14:25	0.0	0.0	0.0	0.0	20.9	
187	06/20/2007 14:26	0.0	0.0	0.0	0.0	20.9	

Site ID: 00000001

Data Points: 641 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

User ID: 00000001

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low Alarm Levels:	35.0	50.0	10.0	10.0	19.5	
Line# Date Time				H2S(ppm)		OXY(%)
1 06/21/2007 08:50		0.0	0.0		20.9	
2 06/21/2007 08:5		0.0	0.0		20.9	
3 06/21/2007 08:52		0.0	0.0		20.9	
4 06/21/2007 08:53		0.0	0.0		20.9	
5 06/21/2007 08:54		0.0	0.0		20.9	
6 06/21/2007 08:5		0.0	0.0		20.9	
7 06/21/2007 08:56		0.0	0.0		20.9	
8 06/21/2007 08:57		0.0	0.0		20.9	
9 06/21/2007 08:58		0.0	0.0	0.0	20.9	
10 06/21/2007 08:5		0.0	0.0	0.0	20.9	
11 06/21/2007 09:0		0.0	0.0	0.0	20.9	
12 06/21/2007 09:0		0.0	0.0	0.0	20.9	
13 06/21/2007 09:0		0.0	0.0	0.0	20.9	
14 06/21/2007 09:0		0.0	0.0	0.0	20.9	
15 06/21/2007 09:0		0.0	0.0	0.0	20.9	
16 06/21/2007 09:0		0.0	0.0	0.0	20.9	
17 06/21/2007 09:0		0.0	0.0	0.0	20.9	
18 06/21/2007 09:0		0.0	0.0	0.0	20.9	
19 06/21/2007 09:0		0.0	0.0	0.0	20.9	
20 06/21/2007 09:0		0.0	0.0	0.0	20.9	
21 06/21/2007 09:1		0.0	0.0	0.0	20.9	
22 06/21/2007 09:1		0.0	0.0	0.0	20.9	
23 06/21/2007 09:1		0.0	0.0	0.0	20.9	
24 06/21/2007 09:1		0.0	0.0	0.0	20.9	
25 06/21/2007 09:1		0.0	0.0	0.0	20.9	
26 06/21/2007 09:1		0.0	0.0	0.0	20.9	
27 06/21/2007 09:1		0.0	0.0	0.0	20.9	
28 06/21/2007 09:1		0.0	0.0	0.0	20.9	
29 06/21/2007 09:1		0.0	0.0	0.0	20.9	
30 06/21/2007 09:1		0.0	0.0	0.0	20.9	
31 06/21/2007 09:2		0.0	0.0	0.0	20.9	
32 06/21/2007 09:2		0.0	0.0	0.0	20.9	
33 06/21/2007 09:2		0.0	0.0	0.0	20.9	
34 06/21/2007 09:2		0.0	0.0	0.0	20.9	
35 06/21/2007 09:2		0.0	0.0	0.0	20.9	
36 06/21/2007 09:2		0.0	0.0	0.0	20.9	
37 06/21/2007 09:2		0.0	0.0	0.0	20.9	
38 06/21/2007 09:2		0.0	0.0	0.0	20.9	
39 06/21/2007 09:2		0.0	0.0	0.0	20.9	
40 06/21/2007 09:2		0.0	0.0	0.0	20.9	
41 06/21/2007 09:3	0.0	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 641 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low	Alarm Lev	/els: 	35.0	50.0	10.0		19.5 	
Line	====== # Date	Time				====== H2S(ppm)	LEL(%)	OXY(%)
42	06/21/200)7 09:31	0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200 06/21/200		0.0	0.0	0.0	0.0	20.9 20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0 0.0	0.0	0.0	0.0 0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
02	00/21/200	,, 10.11	0.0	0.0	0.0	0.0	20.0	

User ID: 00000001 Site ID: 00000001

Data Points: 641 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low	Alarm Le		35.0	50.0	10.0		19.5	
Line		e Time	CO(ppm)			H2S(ppm)) OXY(%)
83	06/21/20	007 10:12	0.0	0.0	0.0		20.9	
		007 10:13	0.0	0.0	0.0		20.9	
		007 10:14	0.0	0.0	0.0		20.9	
		007 10:15	0.0	0.0	0.0		20.9	
		007 10:16	0.0	0.0	0.0		20.9	
		007 10:17	0.0	0.0	0.0		20.9	
		007 10:18	0.0	0.0	0.0		20.9	
		007 10:19	0.0	0.0	0.0		20.9	
		007 10:20	0.0	0.0	0.0		20.9	
		007 10:21	0.0	0.0	0.0		20.9	
		007 10:22	0.0	0.0	0.0		20.9	
		007 10:23	0.0	0.0	0.0		20.9	
		007 10:24	0.0	0.0	0.0		20.9	
		007 10:25	0.0	0.0	0.0		20.9	
		007 10:26	0.0	0.0	0.0		20.9	
		007 10:27	0.0	0.0	0.0		20.9	
		007 10:28	0.0	0.0	0.0		20.9	
		007 10:29		0.0	0.0		20.9	
		007 10:30		0.0	0.0		20.9	
		007 10:31	0.0	0.0	0.0		20.9	
		007 10:32		0.0	0.0		20.9	
		007 10:33		0.0	0.0		20.9	
		007 10:34		0.0	0.0		20.9	
		007 10:35		0.0	0.0		20.9	
		007 10:36		0.0	0.0		20.9	
		007 10:37		0.0	0.0		20.9	
		007 10:38		0.0	0.0		20.9	
		007 10:39		0.0	0.0		20.9	
		007 10:40	0.0	0.0	0.0		20.9	
		007 10:41	0.0	0.0	0.0		20.9	
		007 10:42		0.0	0.0		20.9	
		007 10:43		0.0	0.0		20.9	
		007 10:44		0.0	0.0		20.9	
		007 10:45		0.0	0.0		20.9	
		007 10:46		0.0	0.0		20.9	
		007 10:47		0.0	0.0		20.9	
		007 10:48		0.0	0.0		20.9	
		007 10:49		0.0	0.0		20.9	
		007 10:50		0.0	0.0		20.9	
		007 10:51	0.0	0.0	0.0		20.9	
123	06/21/2	007 10:52	0.0	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 641 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

		· 			10.0				
Line#		me	CO(ppm)	VOC(p	opm) H2	S(ppm)	LEL(%)	OXY(%)	
	06/21/2007 1		0.0	0.0	0.0	0.0	20.9		
125	06/21/2007 1	10:54	0.0	0.0	0.0	0.0	20.9		
126	06/21/2007 1	10:55	0.0	0.0	0.0	0.0	20.9		
127	06/21/2007 1	10:56	0.0	0.0	0.0	0.0	20.9		
128	06/21/2007 1	10:57	0.0	0.0	0.0	0.0	20.9		
129	06/21/2007 1	10:58	0.0	0.0	0.0	0.0	20.9		
130	06/21/2007 1	10:59	0.0	0.0	0.0	0.0	20.9		
131	06/21/2007 1	11:00	0.0	0.0	0.0	0.0	20.9		
132	06/21/2007 1	11:01	0.0	0.0	0.0	0.0	20.9		
133	06/21/2007 1	11:02	0.0	0.0	0.0	0.0	20.9		
134	06/21/2007 1	11:03	0.0	0.0	0.0	0.0	20.9		
135	06/21/2007 1	11:04	0.0	0.0	0.0	0.0	20.9		
136	06/21/2007 1	11:05	0.0	0.0	0.0	0.0	20.9		
137	06/21/2007 1	11:06	0.0	0.0	0.0	0.0	20.9		
138	06/21/2007 1	11:07	0.0	0.0	0.0	0.0	20.9		
139	06/21/2007 1	11:08	0.0	0.0	0.0	0.0	20.9		
	06/21/2007 1		0.0	0.0	0.0	0.0	20.9		
141	06/21/2007 1	11:10	0.0	0.0	0.0	0.0	20.9		
142	06/21/2007 1	11:11	0.0	0.0	0.0	0.0	20.9		
143	06/21/2007 1	11:12	0.0	0.0	0.0	0.0	20.9		
144	06/21/2007 1	11:13	0.0	0.0	0.0	0.0	20.9		
145	06/21/2007 1	11:14	0.0	0.0	0.0	0.0	20.9		
146	06/21/2007 1	11:15	0.0	0.0	0.0	0.0	20.9		
147	06/21/2007 1	11:16	0.0	0.0	0.0	0.0	20.9		
148	06/21/2007 1	11:17	0.0	0.0	0.0	0.0	20.9		
149	06/21/2007 1	11:18	0.0	0.0	0.0	0.0	20.9		
150	06/21/2007 1	11:19	0.0	0.0	0.0	0.0	20.9		
151	06/21/2007 1	11:20	0.0	0.0	0.0	0.0	20.9		
152	06/21/2007 1	11:21	0.0	0.0	0.0	0.0	20.9		
153	06/21/2007 1	11:22	0.0	0.0	0.0	0.0	20.9		
154	06/21/2007 1	11:23	0.0	0.0	0.0	0.0	20.9		
155	06/21/2007 1	11:24	0.0	0.0	0.0	0.0	20.9		
156	06/21/2007 1	11:25	0.0	0.0	0.0	0.0	20.9		
	06/21/2007 1		0.0	0.0	0.0	0.0	20.9		
158	06/21/2007 1	11:27	0.0	0.0	0.0	0.0	20.9		
159	06/21/2007 1	11:28	0.0	0.0	0.0	0.0	20.9		
	06/21/2007 1		0.0	0.0	0.0	0.0	20.9		
	06/21/2007 1		0.0	0.0	0.0	0.0	20.9		
	06/21/2007 1		0.0	0.0	0.0	0.0	20.9		
	06/21/2007 1		0.0	0.0	0.0	0.0	20.9		
164	06/21/2007 1	11:33	0.0	0.0	0.0	0.0	20.9		

User ID: 00000001 Site ID: 00000001

Data Points: 641 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

				10.0			
Line#	# Date Time	CO(ppm)	VOC(p	pm) H2	S(ppm)	LEL(%)	OXY(%)
	06/21/2007 11:34	0.0	0.0	0.0	0.0	20.9	
166	06/21/2007 11:35	0.0	0.0	0.0	0.0	20.9	
167	06/21/2007 11:36	0.0	0.0	0.0	0.0	20.9	
168	06/21/2007 11:37	0.0	0.0	0.0	0.0	20.9	
169	06/21/2007 11:38	0.0	0.0	0.0	0.0	20.9	
170	06/21/2007 11:39	0.0	0.0	0.0	0.0	20.9	
171	06/21/2007 11:40	0.0	0.0	0.0	0.0	20.9	
172	06/21/2007 11:41	0.0	0.0	0.0	0.0	20.9	
173	06/21/2007 11:42	0.0	0.0	0.0	0.0	20.9	
174	06/21/2007 11:43	0.0	0.0	0.0	0.0	20.9	
175	06/21/2007 11:44	0.0	0.0	0.0	0.0	20.9	
176	06/21/2007 11:45	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 11:46	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 11:47		0.0	0.0	0.0	20.9	
	06/21/2007 11:48	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 11:49	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 11:50	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 11:51	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 11:52	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 11:53	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 11:54	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 11:55	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 11:56	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 11:57	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 11:58	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 11:59	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 12:00	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 12:01	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 12:02	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 12:03	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 12:04	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 12:05	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 12:06	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 12:07	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 12:08	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 12:09	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 12:10	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 12:11	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 12:12 06/21/2007 12:13	0.0	0.0	0.0	0.0	20.9	
		0.0	0.0	0.0	0.0	20.9	
∠05	06/21/2007 12:14	0.0	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 641 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

LOW	Alailli Lev	eis. 	33.0	50.0	10.0	10.0	19.5		
Line#		====== Time ======	CO(ppm)					OXY(%)	
206	06/21/200	07 12:15	0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.3	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
	06/21/200		0.0	0.0	0.0	0.0	20.9		
246	06/21/200	J/ 12:55	0.0	0.0	0.0	0.0	20.9		

User ID: 00000001 Site ID: 00000001

Data Points: 641 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low	Alarm Lev	els: 	35.0 	50.0 	10.0	10.0 	19.5 	
Line#		Time					LEL(%)	OXY(%)
247	06/21/200	7 12:56	0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200 06/21/200		0.0	0.0	0.0 0.0	0.0	20.9	
	06/21/200		0.0	0.0		0.0	20.9	
	06/21/200		0.0	0.0	0.0 0.0	0.0	20.9 20.9	
			0.0 0.0	0.0		0.0		
	06/21/200			0.0	0.0	0.0	20.9	
	06/21/200 06/21/200		0.0	0.0	0.0	0.0	20.9	
			0.0	0.0	0.0	0.0	20.9 20.9	
	06/21/200 06/21/200		0.0 0.0	0.0	0.0 0.0	0.0 0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
201	00/21/200	11 13.30	0.0	0.0	0.0	0.0	۵.5	

User ID: 00000001 Site ID: 00000001

Data Points: 641 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

======================================		33.0	50.0	10.0	10.0	19.5	
Line#		CO(ppm)		-			OXY(%)
288	06/21/2007 13:37	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:38	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:39	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:40	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:41	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:42	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:43	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:44	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:45	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:46	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:47	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:48	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:49	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:50	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:51	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:52	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:53	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:54	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:55 06/21/2007 13:56	0.0	0.0	0.0	0.0 0.0	20.9 20.9	
	06/21/2007 13:57	0.0 0.0	0.0	0.0 0.0	0.0	20.9	
	06/21/2007 13:58	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:59	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 13:39	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 14:00	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 14:01	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 14:03	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 14:04	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 14:05	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 14:06	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 14:07	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 14:08	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 14:09	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 14:10	0.0	0.0	0.0	0.0	20.9	
322	06/21/2007 14:11	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 14:12	0.0	0.0	0.0	0.0	20.9	
324	06/21/2007 14:13	0.0	0.0	0.0	0.0	20.9	
325	06/21/2007 14:14	0.0	0.0	0.0	0.0	20.9	
326	06/21/2007 14:15	0.0	0.0	0.0	0.0	20.9	
327	06/21/2007 14:16	0.0	0.0	0.0	0.0	20.9	
328	06/21/2007 14:17	0.0	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 641 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low	Alarm Lev	35.0 	50.0	10.0	10.0	19.5 		
Line#		Time					LEL(%)	OXY(%)
329	06/21/200	7 14:18	0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200 06/21/200		0.0	0.0	0.0 0.0	0.0	20.9	
	06/21/200		0.0	0.0		0.0	20.9	
	06/21/200		0.0 0.0	0.0	0.0 0.0	0.0	20.9 20.9	
	06/21/200		0.0	0.0	0.0	0.0 0.0	20.9	
	06/21/200		0.0	0.0		0.0	20.9	
	06/21/200				0.0			
	06/21/200		0.0 0.0	0.0	0.0 0.0	0.0 0.0	20.9 20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
309	00/21/200	14.50	0.0	0.0	0.0	0.0	20.5	

User ID: 00000001 Site ID: 00000001

Data Points: 641 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low Alarm Levels:			35.0	50.0	10.0	10.0	19.5	
Line#	Date	Time	CO(ppm)	VOC(===== ppm) Н ======		LEL(%)	OXY(%)
	06/21/200		0.0	0.0	0.0	0.0	20.9	
371	06/21/200	7 15:00	0.0	0.0	0.0	0.0	20.9	
372	06/21/200	7 15:01	0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
-	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200 06/21/200		0.0	0.0	0.0 0.0	0.0	20.9	
			0.0	0.0	0.0	0.0	20.9	
	06/21/200 06/21/200		0.0 0.0	0.0	0.0	0.0 0.0	20.9 20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
410	00/21/200	11.38	0.0	0.0	0.0	0.0	۷٠.5	

User ID: 00000001 Site ID: 00000001

Data Points: 641 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low Alarm Levels:			35.0	50.0	10.0	10.0	19.5	
Line#	# Date	Time		VOC(ppm)	12S(ppm)	LEL(%)	, ,
411	06/21/200	7 15:40	0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200 06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
			0.0	0.0	0.0	0.0	20.9	
	06/21/200 06/21/200		0.0	0.0	0.0	0.0	20.9	
_		_	0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200 06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0 0.0	0.0	0.0	0.0 0.0	20.9 20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200							
45 I	00/21/200	10.20	0.0	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 641 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low Alarm Levels:			35.0	50.0	10.0	10.0	19.5	
Line#	# Date	Time	CO(ppm)	VOC(ppm)		LEL(%)	OXY(%)
452	06/21/200	7 16:21	0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200 06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9 20.9	
	06/21/200		0.0 0.0	0.0	0.0	0.0 0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200					0.0	20.9	
	06/21/200		0.0 0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
492	00/21/200	17.01	0.0	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 641 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

					10.0		
Line#	# Date Time	CO(ppm)	VOC(p	pm) H2	S(ppm)	LEL(%)	OXY(%)
493	06/21/2007 17:02	0.0	0.0	0.0	0.0	20.9	
494	06/21/2007 17:03	5.3	0.0	0.0	0.0	20.9	
495	06/21/2007 17:04	7.8	0.0	0.0	0.0	20.9	
496	06/21/2007 17:05	10.6	0.0	0.0	0.0	20.9	
497	06/21/2007 17:06	2.7	0.0	0.0	0.0	20.9	
498	06/21/2007 17:07	0.0	0.0	0.0	0.0	20.9	
499	06/21/2007 17:08	0.0	0.0	0.0	0.0	20.9	
500	06/21/2007 17:09	0.0	0.0	0.0	0.0	20.9	
501	06/21/2007 17:10	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:11	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:12	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:13	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:14	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:15	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:16	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:17	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:18	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:19	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:20	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:21	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:22	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:23	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:24	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:25	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:26	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:27		0.0	0.0	0.0	20.9	
	06/21/2007 17:28	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:29	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:30	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:31	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:32 06/21/2007 17:33	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:34	0.0 0.0	0.0	0.0	0.0 0.0	20.9 20.9	
	06/21/2007 17:35	0.0	0.0 0.0	0.0 0.0	0.0	20.9	
	06/21/2007 17:36	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:37	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:38	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:39	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:39	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:40	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 17:41	0.0	0.0	0.0	0.0	20.9	
555	00/21/2001 11.42	0.0	0.0	0.0	0.0	۵.5	

User ID: 00000001 Site ID: 00000001

Data Points: 641 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

======================================		33.0	50.0	10.0	10.0	19.5		
Line#		Time	CO(ppm)					OXY(%)
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200 06/21/200		0.0	0.0	0.0	0.0	20.9	
			0.0	0.0	0.0	0.0	20.9	
	06/21/200 06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
			0.0	0.0	0.0	0.0	20.9	
5/4	06/21/200	17 18:23	0.0	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 641 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

======================================		33.0	50.0	10.0	10.0	19.5		
Line#		Time	CO(ppm)					OXY(%)
	06/21/200		0.0	0.0	0.0	0.0	20.9	
576	06/21/200	7 18:25	0.0	0.0	0.0	0.0	20.9	
577	06/21/200	7 18:26	0.0	0.0	0.0	0.0	20.9	
578	06/21/200	7 18:27	0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
	06/21/200		0.0	0.0	0.0	0.0	20.9	
615	06/21/200	17 19:04	0.0	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 641 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

LOW	Alarm Leveis:	35.U 	50.0	10.0	10.0	19.5	
Line#	Date Time					LEL(%)	
616	06/21/2007 19:05	0.0	0.0	0.0	0.0	20.9	
617	06/21/2007 19:06	0.0	0.0	0.0	0.0	20.9	
618	06/21/2007 19:07	0.0	0.0	0.0	0.0	20.9	
619	06/21/2007 19:08	0.0	0.0	0.0	0.0	20.9	
620	06/21/2007 19:09	0.0	0.0	0.0	0.0	20.9	
621	06/21/2007 19:10	0.0	0.0	0.0	0.0	20.9	
622	06/21/2007 19:11	0.0	0.0	0.0	0.0	20.9	
623	06/21/2007 19:12	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 19:13	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 19:14	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 19:15	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 19:16	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 19:17	0.5	0.0	0.0	0.0	20.9	
	06/21/2007 19:18	29.2	0.0	0.0	0.0	20.9	
	06/21/2007 19:19	3.7	0.0	0.0	0.0	20.9	
	06/21/2007 19:20	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 19:21	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 19:22	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 19:23	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 19:24	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 19:25	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 19:26	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 19:27	0.0	0.0	0.0	0.0	20.9	
	06/21/2007 19:28	0.0	0.0	0.0	0.0	20.9	
640	06/21/2007 19:29	0.0	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 174 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

Low	v Alarm Lev	35.0	50.0	10.	0 10.0	19.5 		
Line	e# Date	Time	CO(ppm)	VOC((ppm)	H2S(ppm)	LEL(%)	OXY(%)
1	06/22/200	7 08:41	0.3	0.0	0.0		20.9	
	06/22/200		0.5	0.0	0.0		20.9	
	06/22/200		0.3	0.1	0.0	0.0	20.9	
	06/22/200		0.1	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
6	06/22/200		0.2	0.0	0.0	0.0	20.9	
7			0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.1	0.0	0.0	0.0	20.9	
	06/22/200		0.2	0.0	0.0	0.0	20.9	
	06/22/200		0.2	0.0	0.0		20.9	
	06/22/200		0.3	0.0	0.0		20.9	
	06/22/200		0.3	0.0	0.0		20.9	
	06/22/200		0.2	0.0	0.0		20.9	
	06/22/200		0.3	0.0	0.0		20.9	
	06/22/200		0.3	0.0	0.0		20.9	
	06/22/200		0.2	0.0	0.0		20.9	
	06/22/200		0.3	0.0	0.0		20.9	
	06/22/200		0.3	0.0	0.0		20.9	
	06/22/200		0.5	0.0	0.0		20.9	
	06/22/200		0.3	0.0	0.0		20.9	
21			0.5	0.0	0.0		20.9	
	06/22/200		0.4	0.0	0.0		20.9	
	06/22/200		0.5	0.0	0.0		20.9	
	06/22/200		0.3	0.0	0.0		20.9	
	06/22/200		0.3	0.0	0.0		20.9	
	06/22/200		0.2	0.0	0.0		20.9	
	06/22/200		0.3	0.0	0.0		20.9	
	06/22/200		0.4	0.0	0.0		20.9	
	06/22/200		0.2	0.0	0.0		20.9	
	06/22/200		0.2	0.0	0.0		20.9	
	06/22/200		0.2	0.0	0.0		20.9	
	06/22/200		0.3	0.0	0.0		20.9	
	06/22/200		0.2	0.0	0.0		20.9	
	06/22/200		0.3	0.0	0.0		20.9	
	06/22/200		0.1	0.0	0.0		20.9	
	06/22/200		0.3	0.0	0.0		20.9	
	06/22/200		0.1	0.0	0.0		20.9	
	06/22/200		0.1	0.0	0.0		20.9	
	06/22/200		0.2	0.0	0.0		20.9	
	06/22/200		0.2	0.0	0.0		20.9	
41	06/22/200	07 09:21	0.2	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 174 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

High Alarm Levels: 200.0 100.0 20.0 20.0 23.5 Low Alarm Levels: 35.0 50.0 10.0 10.0 19.5

Low	Alarm Leve	els: 	35.0	50.0	10.0	10.0 ======	19.5 	
Line	# Date	Time	CO(ppm)	VOC(ppm) l	H2S(ppm)		OXY(%)
42	06/22/200	7 09:22	0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.1	0.0	0.0	0.0	20.9	
	06/22/200		0.5	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.2	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.5	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.6	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.2	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.2	0.0	0.0	0.0	20.9	
	06/22/200° 06/22/200°		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.4		0.0	0.0	20.9 20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.4 0.3	0.0 0.0	0.0	0.0 0.0	20.9	
	06/22/200		0.5	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.1	0.0	0.0	0.0	20.9	
	06/22/200		0.5	0.0	0.0	0.0	20.9	
	06/22/200		0.5	0.0	0.0	0.0	20.9	
	06/22/200		0.5	0.0	0.0	0.0	20.9	
	06/22/200		0.7	0.0	0.0	0.0	20.9	
	06/22/200		0.7	0.0	0.0	0.0	20.9	
	06/22/200		0.5	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.2	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
-	,00		0.0	0.0	5.5			

User ID: 00000001 Site ID: 00000001

Data Points: 174 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

High Alarm Levels: 200.0 100.0 20.0 20.0 23.5 Low Alarm Levels: 35.0 50.0 10.0 10.0 19.5

Low	Alarm Levels:	35.0	50.0	10.0	10.0	19.5	
Line	# Date Time					LEL(%)	OXY(%)
	06/22/2007 10:03	0.1	0.0	0.0	0.0	20.9	
	06/22/2007 10:04	0.6	0.0	0.0	0.0	20.9	
	06/22/2007 10:05	0.2	0.0	0.0	0.0	20.9	
	06/22/2007 10:06	0.3	0.0	0.0	0.0	20.9	
	06/22/2007 10:07	0.5	0.0	0.0	0.0	20.9	
	06/22/2007 10:08	0.4	0.0	0.0	0.0	20.9	
	06/22/2007 10:09	0.3	0.0	0.0	0.0	20.9	
	06/22/2007 10:10	0.4	0.0	0.0	0.0	20.9	
91		0.1	0.0	0.0	0.0	20.9	
	06/22/2007 10:12	0.4	0.0	0.0	0.0	20.9	
	06/22/2007 10:13	0.6	0.0	0.0	0.0	20.9	
	06/22/2007 10:14	0.7	0.0	0.0	0.0	20.9	
	06/22/2007 10:15	0.3	0.0	0.0	0.0	20.9	
	06/22/2007 10:16	0.6	0.0	0.0	0.0	20.9	
	06/22/2007 10:17	0.4	0.0	0.0	0.0	20.9	
	06/22/2007 10:18	0.4	0.0	0.0	0.0	20.9	
	06/22/2007 10:19	0.3	0.0	0.0	0.0	20.9	
	06/22/2007 10:20	0.7	0.0	0.0	0.0	20.9	
	06/22/2007 10:21 06/22/2007 10:22	0.4	0.0	0.0	0.0 0.0	20.9 20.9	
	06/22/2007 10:22	0.4 0.5	0.0	0.0 0.0	0.0	20.9	
	06/22/2007 10:23	0.3	0.0	0.0	0.0	20.9	
	06/22/2007 10:24	0.3	0.0	0.0	0.0	20.9	
	06/22/2007 10:25	0.4	0.0	0.0	0.0	20.9	
	06/22/2007 10:27	0.6	0.0	0.0	0.0	20.9	
	06/22/2007 10:28	0.3	0.0	0.0	0.0	20.9	
	06/22/2007 10:29	0.6	0.0	0.0	0.0	20.9	
	06/22/2007 10:30	0.5	0.0	0.0	0.0	20.9	
	06/22/2007 10:31	0.3	0.0	0.0	0.0	20.9	
	06/22/2007 10:32	0.5	0.0	0.0	0.0	20.9	
	06/22/2007 10:33	0.3	0.0	0.0	0.0	20.9	
	06/22/2007 10:34	0.4	0.0	0.0	0.0	20.9	
	06/22/2007 10:35	0.5	0.0	0.0	0.0	20.9	
	06/22/2007 10:36	0.3	0.0	0.0	0.0	20.9	
	06/22/2007 10:37	0.5	0.0	0.0	0.0	20.9	
	06/22/2007 10:38	0.6	0.0	0.0	0.0	20.9	
119	06/22/2007 10:39	0.6	0.0	0.0	0.0	20.9	
120	06/22/2007 10:40	0.9	0.0	0.0	0.0	20.9	
121	06/22/2007 10:41	0.4	0.0	0.0	0.0	20.9	
122	06/22/2007 10:42	0.5	0.0	0.0	0.0	20.9	
123	06/22/2007 10:43	0.6	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 174 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

High Alarm Levels: 200.0 100.0 20.0 20.0 23.5 Low Alarm Levels: 35.0 50.0 10.0 10.0 19.5

	Alarm Lev		35.0	50.0	10.0	10.0	19.5	
Line#		Time					LEL(%)	
124	06/22/200	07 10:44	0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.5	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.5	0.0	0.0	0.0	20.9	
	06/22/200		0.2	0.0	0.0	0.0	20.9	
	06/22/200		0.5	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.5	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.6	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.2	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.2	0.0	0.0	0.0	20.9	
	06/22/200		0.6	0.0	0.0	0.0	20.9	
	06/22/200		0.1	0.0	0.0	0.0	20.9	
	06/22/200		0.5	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.6	0.0	0.0	0.0	20.9	
	06/22/200		0.5 0.5	0.0	0.0 0.0	0.0	20.9	
	06/22/200		0.3	0.0		0.0	20.9 20.9	
	06/22/200		0.3	0.0	0.0 0.0	0.0 0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.3	0.0	0.0	0.0	20.9	
	06/22/200		0.2 0.4	0.0	0.0	0.0	20.9	
	06/22/200		0.4	0.0	0.0	0.0	20.9	
104	00/22/200	JI 11.24	0.4	0.0	0.0	0.0	20.9	

User ID: 00000001 Site ID: 00000001

Data Points: 174 Data Type: Avg Sample Period: 60 sec

Last Calibration Time: 06/15/2007 09:21

173 06/22/2007 11:33

174 06/22/2007 11:34

Gas Type: CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%)

High Alarm Levels: 200.0 100.0 20.0 20.0 23.5 Low Alarm Levels: 35.0 50.0 10.0 10.0 19.5

0.5

0.5

0.0

0.0

0.0

0.0

Line# Date Time CO(ppm) VOC(ppm) H2S(ppm) LEL(%) OXY(%) 165 06/22/2007 11:25 0.3 0.0 0.0 0.0 20.9 166 06/22/2007 11:26 0.1 0.0 0.0 0.0 20.9 20.9 167 06/22/2007 11:27 0.2 0.0 0.0 0.0 168 06/22/2007 11:28 0.0 0.0 20.9 0.2 0.0 169 06/22/2007 11:29 0.2 0.0 0.0 0.0 20.9 170 06/22/2007 11:30 0.0 0.4 0.0 0.0 20.9 171 06/22/2007 11:31 0.4 0.0 0.0 0.0 20.9 172 06/22/2007 11:32 0.3 0.0 0.0 0.0 20.9

0.0

0.0

20.9

20.9

APPENDIX E


Slug Test Evaluation Data

Former Martins Gulf Station MW-6: Rising Head Slug Test Data Test Date: June 19, 2007

Depth To Water (fbtoc)	Elapsed Time (minutes)	Displacement in Hydraulic Head Units (feet)
6.5	0	2.48
6.0	0.25	1.98
5.75	0.5	1.73
5.4	0.75	1.38
5.15	1	1.13
4.98	1.25	0.96
4.82	1.5	0.80
4.72	1.75	0.70
4.61	2	0.59
4.51	2.25	0.49
4.35	3	0.33
4.26	3.5	0.24
4.21	4	0.19
4.18	4.5	0.16
4.15	5	0.13
4.1	6	0.08
4.09	- 7	0.07
4.08	8	0.06
4.08	10	0.06
4.07	12	0.05
4.07	14	0.05
4.07	. 16	0.05
4.08	18	0.06
4.07	20	0.05

Note:

fbtoc = feet below top of casing Pre-Test Water Level = 4.02 fbtoc



Former Martins Gulf Station

Data Set: U:\JBoulanger\SYR Ft Cov Slug Tests\MW-6 Results.aqt Title: MW-6: Rising Head Slug Test Date: 09/19/07 Time: 10:32:05

PROJECT INFORMATION

Company: Kleinfelder East, Inc. Client: Martins Gulf Station Project: 69968 Location: Fort Covington, NY Test Date: June 19, 2007 Test Well: MW-6

AQUIFER DATA

Saturated Thickness: 11. ft Anisotropy Ratio (Kz/Kr): 1.

SLUG TEST WELL DATA

Test Well: : MW-6

X Location: 0. ft Y Location: 0. ft

Initial Displacement: 2.48 ft Static Water Column Height: 19.98 ft Casing Radius: 0.0833 ft

Wellbore Radius: 0.333 ft
Well Skin Radius: 0.333 ft
Screen Length: 20. ft
Total Well Penetration Depth: 11. ft

No. of Observations: 24

	Observation	n Data	
Time (min)	Displacement (ft)	Time (min)	Displacement (ft)
0. 0.25	2.48 1.98	4. 4.5	0.19 0.16
0.5	1.73	5.	0.13
0.75	1.38	<u>6</u> .	0.08
1. 1.25	1.13 0.96	7 Q	0.07
1.5	0.8	0. 10.	0.06 0.06
1.75	0.7	12.	0.05
2.25	0.59 0.49	14. 16	0.05
3.	0.33	16. 18.	0.05 0.06
3.5	0.24	20.	0.05

SOLUTION

Aquifer Model: Confined

Solution Method: Cooper-Bredehoeft-Papadopulos

VISUAL ESTIMATION RESULTS

Estimated Parameters

Parameter Estimate ft²/day 11.8 0.001

K = T/b = 1.072 ft/day

The Error Log identifies errors detected in your data set. Choose this view when you see the "Check Errors" indicator on the status bar.

No errors detected in data set.

Tips for Analyzing Aquifer Tests with AQTESOLV for Windows

Entér Test Data

Choose options from the Edit menu to enter or modify test data.

2. Perform Diagnostic Analyses (Optional)
Choose diagnostic flow plot and derivative plot options from the View menu.

3. Perform Curve Matching or Prediction
Choose the Solution or Toolbox options from the Match menu to perform forward solution analys
Choose the Automatic, Visual or Toolbox options from the Match menu to perform curve matchin

4. Analysis of Residuals (Optional)
Choose residual plot and diagnostic report options from View menu to evaluate automatic curve

Reporting

Choose Format option from View menu to customize appearance of plots and reports. Choose Print Preview and Print options from File menu to obtain hardcopy output.

Data Set Summary
Slug Test
Total no. of observations: 24
Range of time readings in obs. well(s): 0 to 20 min

Range of displacement readings in obs. well(s): 0.05 to 2.48 ft

MW-6: Rising Head Slug Test

Prepared By:

Kleinfelder East, Inc.

Project:


69968

Prepared For:

Martins Gulf Station

Location:

Fort Covington, NY



SOLUTION

Aquifer Model: Confined

Solution Method: Cooper-Bredehoeft-Papadopulos

 $T = 11.8 \text{ ft}^2/\text{day}$

S = 0.001

AQUIFER DATA

Saturated Thickness: 11. fAnisotropy Ratio (Kz/Kr): 1.

WELL DATA (MW-6)

Initial Displacement: 2.48 ft

Static Water Column Height: 19.98 ft Total Well Penetration Depth: 11. ft

Screen Length: 20. ft
Casing Radius: 0.0833 ft
Wellbore Radius: 0.333 ft

Former Martins Gulf Station MW-2: Rising Head Slug Test Data Test Date: June 19, 2007

Depth To Water		Displacement in Hydraulic
(fbtoc)	(minutes)	Head Units (feet)
5.3	0	0.95
4.8	0.25	0.45
4.6	0.5	0.25
4.52	0.75	0.17
4.45	1.25	0.10
4.43	1.5	0.08
4.42	1.75	0.07
4.42	2	0.07
4.42	2.5	0.07
4.41	3	0.06
4.41	3.5	0.06
4.41	4	0.06
4.4	5	0.05
4.39	6	0.04
4.39	7	0.04
4.38	8	0.03
4.38	9	0.03
4.38	10	0.03
4.37	11	0.02
4.37	12	0.02
4.36	14	0.01
4.36	16	0.01
4.36	18	0.01
4.35	20	0.00

Note:

fbtoc = feet below top of casing Pre-Test Water Level = 4.35 fbtoc

20 19 <u>8</u> 17 16 15 14 13 MW-2: Rising Head Slug Test Test Date: June 19, 2007 12 Elapsed Time (minute) 7 9 თ ω 7 9 ß 4 ო 2 0 3.0 + 3.5 4.5 Depth To Water (fbtoc) 4.0 7.0 8.0 6.5 7.5

Former Martins Gulf Station

Data Set: U:\JBoulanger\SYR Ft Cov Slug Tests\MW-2 Results.aqt Title: MW-2: Rising Head Slug Test Date: 09/19/07 Time: 10:19:52

PROJECT INFORMATION

Company: Kleinfelder East, Inc. Client: Martins Gulf Station

Project: 69968

Location: Fort Covington, NY Test Date: June 19, 2007 Test Well: MW-2

AQUIFER DATA

Saturated Thickness: 11. ft Anisotropy Ratio (Kz/Kr): 1.

SLUG TEST WELL DATA

Test Well: : MW-2

X Location: 0. ft Y Location: 0. ft

Initial Displacement: 0.95 ft Static Water Column Height: 20.68 ft Casing Radius: 0.0833 ft Wellbore Radius: 0.333 ft Well Skin Radius: 0.333 ft Screen Length: 20. ft Total Well Penetration Depth: 11. ft

No. of Observations: 24

	Observation	n Data		
Time (min)	Displacement (ft)	Time (min)	Displacement (ft)	
0.	0.95	5.	0.05	
0.25	0.45 0.25	0. 7	0.04 0.04	
0.75	0.17	8.	0.03	
1.25	0.1	9.	0.03	
1 <u>.5</u>	0.08	10.	0.03	
1.75	0.07	11.	0.02	
2. 2.5	0.07	12. 14.	0.02 0.01	
3.	0.06	16.	0.01	
3.5	0.06	18 <i>.</i>	0.01	
4.	0.06	20.	0.	

SOLUTION

Aguifer Model: Confined

Solution Method: Cooper-Bredehoeft-Papadopulos

VISUAL ESTIMATION RESULTS

Estimated Parameters

Parameter Estimate ft²/day 29.62 0.001

K = T/b = 2.692 ft/day

The Error Log identifies errors detected in your data set. Choose this view when you see the "Check Errors" indicator on the status bar.

No errors detected in data set.

Tips for Analyzing Aquifer Tests with AQTESOLV for Windows

Enter Test Data

Choose options from the Edit menu to enter or modify test data.

2. Perform Diagnostic Analyses (Optional)
Choose diagnostic flow plot and derivative plot options from the View menu.

3. Perform Curve Matching or Prediction
Choose the Solution or Toolbox options from the Match menu to perform forward solution analys
Choose the Automatic, Visual or Toolbox options from the Match menu to perform curve matchin

4. Analysis of Residuals (Optional)
Choose residual plot and diagnostic report options from View menu to evaluate automatic curve

5. Reporting

Choose Format option from View menu to customize appearance of plots and reports. Choose Print Preview and Print options from File menu to obtain hardcopy output.

Data Set Summary

Slug Test
Total no. of observations: 24
Range of time readings in obs. well(s): 0 to 20 min

Range of displacement readings in obs. well(s): 0 to 0.95 ft

MW-2: Rising Head Slug Test

Prepared By:

Kleinfelder East, Inc.

Project:


69968

Prepared For:

Martins Gulf Station

Location:

Fort Covington, NY



SOLUTION

Aquifer Model: Confined

Solution Method: Cooper-Bredehoeft-Papadopulos

 $T = 29.62 \text{ ft}^2/\text{day}$

S = 0.001

AQUIFER DATA

Saturated Thickness: 11. fAnisotropy Ratio (Kz/Kr): 1.

WELL DATA (MW-2)

Initial Displacement: 0.95 ft

Static Water Column Height: 20.68 ft Total Well Penetration Depth: 11. ft

Screen Length: 20. ft
Casing Radius: 0.0833 ft
Wellbore Radius: 0.333 ft

APPENDIX F

Data Usability Summary Reports

DATA USABILITY SUMMARY REPORT FORT. COVINGTON, NEW YORK

KLEINFELDER PROJECT ID: 69968

SAMPLE DELIVERY GROUP (SDG) FVC01

TABLE OF CONTENTS

1.	Sumi	nary	1
2.	Perso	onnel Qualifications	2
3.	Labo	ratory Data Verification	2
3	3.1.	Holding Times	2
3		Surrogate Recoveries	
3		Initial and Continuing Calibration	
	3.3.1		
	3.3.2		
3	3.4.	Matrix Spikes and Matrix Spike Duplicates	3
. 3	3.5.	Laboratory Control Samples	7
	3.5.1	Volatile Organic Compounds	7
	3.5.2	Semi volatile Organic Compounds.	7
	3.5.3.	Pesticides	. 7
	3.5.4.		8
	3.5.5.		8
3	3.6.	Method Blanks	8
4.	Data	Quality Assessment	8
Ref	erences	,	11
		LIST OF TABLES	
	Table	3-1 Heavy Metal Matrix Spike and Matrix Spike Duplicate data	3
-	Table	3-2 PCB Matrix Spike and Matrix Spike Duplicate data	4
	Table	3-3 Pesticide Matrix Spike and Matrix Spike Duplicate data	4
	Table	3-4 SVOC Matrix Spike and Matrix Spike Duplicate data	4
	Table	3-5 Volatile Organic Compound Matrix Spike and Matrix Spike Duplicate data	6
		e e	

Quality Assurance/Quality Control

Data Usability Summary Report Fort Covington, New York

Kleinfelder Project ID: 69968

The following personnel have reviewed this report for accuracy, content, and quality of presentation:

Kleinfelder East, Inc.

Mr. John A. Martin, CHMM Industrial Hygienist

Mr. John Imhoff Senior Project Manager Signature:

Date: 1-19-7007

Signature:

Date: 9-20-2007

1. Summary

This Data Usability Summary Report (DUSR) has been prepared in accordance with the New York State Department of Environmental Conservation (NYSDEC) guidance for the development of DUSR reports and is intended to verify that the data packages associated with this DUSR are complete as defined under the requirements for the NYSDEC ASP Category B or USEPA CLP deliverables; to ensure that all method holding times have been met; to ensure that QC data (blanks, instrument tunings, calibration standards, calibration verifications, surrogate recoveries, spike recoveries, replicate analysis, laboratory controls and sample data) fall within the protocol required limits and specifications; that all data have been developed using established and agreed upon analytical procedures; evaluation of raw data to confirm results; to ensure the correct data qualifiers have been used; and, to evaluate the NYSDEC Matrix Spike Blank Data.

This (DUSR) documents the review of analytical data associated with the June 2007 sampling event at the Fort Covington project site.

Samples were collected by Kleinfelder personnel in from June 19, 2007 to June 25, 2007 and subsequently submitted to Lancaster Laboratories "Lancaster" of Lancaster, Pennsylvania for analysis of volatile organic compounds (VOCs) via EPA SW-846 method 8260B, semi-volatile organic compounds (SVOCs) via EPA SW-846 method 8270C, select heavy metals via EPA SW-846 series 6000, polychlorinated bi-phenols (PCBs) and pesticides via EPA SW-846 method 8082B. Data packages received from the laboratory were in conformance with the New York State Department of Environmental Conservation Analytical Service Protocol (NYSDEC ASP) Category B.

Analytical data, and other information contained within the data packages associated with this report have undergone review to evaluate the levels of accuracy, precision, and completeness of the data. Unless otherwise noted, sample storage, preparation, analysis, reporting, and quality control (QC) measures were performed in accordance with published EPA analytical protocol.

2. Personnel Qualifications

The data packages provided by Lancaster laboratories were reviewed by Mr. John A. Martin, CHMM. Mr. Martin is a chemist and environmental health scientist based out of Kleinfelder's Massachusetts operation. He has 13 years of industry experience. He has multi-faceted experience working within the analytical laboratory environment, and has strong working knowledge of analytical instrumentation, laboratory procedure and analytical methods. Mr. Martin regularly conducts laboratory data report review and validation activities under EPA laboratory protocol in support of assessment, remediation and due diligence transactions in the mid-Atlantic and Northeast regions.

Mr. Martin holds a B.S. degree in Chemistry, a B.S. degree in Biology, and a Master of Public Health Degree (MPH).

3. Laboratory Data Verification

One hundred percent (100 percent) of data generated for this project were evaluated through a systematic procedure in which method performance is compared to defined criteria. The following sections provide the overview of the data verification methodology and the results of the laboratory QA/QC program review.

3.1. Holding Times

All samples received by Lancaster were accompanied by proper chain-of-custody documentation. Collection dates for the samples submitted to the laboratory are included in the chain-of-custody documentation. Sample collection, preparation, and analyses dates are indicated on the laboratory reports. All samples were properly preserved. Holding times were met for the analyses performed.

3.2. Surrogate Recoveries

A surrogate is a compound spiked into the sample that is uncommon in the environment but that behaves similarly to the target analyte, chromatographically. Surrogate recoveries are used to monitor method performance for the target analytes and were included with all samples analyzed for VOCs. Greater than 90% of the surrogate recoveries were within the method prescribed control limits.

3.3. Initial and Continuing Calibration

3.3.1.Initial Calibration

The % D for 4,4'-DDD was reported outside accepted method limits, >20% as defined by NELAC in initial calibration verification standards. All other initial calibration verification standards were within accepted method limits.

3.3.2. Continuing Calibration

Continuing calibration verification (CCV) returned %Ds and average %D's for multiple pesticide compounds outside of method specification accepted limits. The ending continuing calibration was outside QC limits for multiple compounds. The associated samples were previously injected with similar results, suggesting possible matrix interference.

3.4. Matrix Spikes and Matrix Spike Duplicates

A matrix spike (MS) is a primary sample spiked with target compounds. MS/Matrix Spike Duplicate (MS/MSD) analyses provide spike recovery percentages and RPDs between analyses of the same spiked sample, which provide a measure of analytical precision. Greater than 90% of the matrix spike recovery data reported by Lancaster comply with method protocol. All RPD values were within method prescribed acceptance criteria (0–30%). Results from the MS and MSD are presented in Tables 4-1 through 4-5 below.

Table 3-1 Heavy Metal Matrix Spike and Matrix Spike Duplicate data.

Metal	Matrix Spike Result	RL	Units	Dilution	MSD	RPD	Acceptable
Mercury	0.253	0.0134	mg/kg	1	0.259	2.3	Yes
Aluminum	45900	4.41	mg/kg	1	53700	15.7	Yes
Calcium	6110	8.07	mg/kg	1	5900	3.5	Yes
Iron	47400	31	mg/kg	5	56000	16.6	Yes
Magnesium	14000	3.34	mg/kg	1	15100	7.6	Yes
Potassium	11200	4.36	mg/kg	1	12800	13.3	Yes
Sodium	908	45.8	mg/kg	1	995	9.1	Yes
Trallium	20.8	1.25	mg/kg	1	20.2	2.9	Yes
Arsenic	18.8	1.25	mg/kg	1	18.2	3.2	Yes
Selenium	14.6	1.29	mg/kg	1	14.5	0.7	Yes
Antimony	18.1	1.19	mg/kg	1	18	0.6	Yes
Barium	551	0.0303	mg/kg	1	573	3.9	Yes
Beryllium	7.98	0.0895	mg/kg	1	8.02	0.5	Yes
Cadmium	7.44	0.0855	mg/kg	1	7.3	1.9	Yes
Chromium	92.3	0.767	mg/kg	1	99.9	7.9	Yes
Cobalt	84.8	0.171	mg/kg	1	80.8	4.8	Yes
Copper	63	0.263	mg/kg	1	70	10.5	Yes

Table 3-1 Heavy Metal Matrix Spike and Matrix Spike Duplicate data.

Metal	Matrix Spike Result	RL	Units	Dilution	MSD	RPD	Acceptable
Lead	44.3	0.645	mg/kg	1	29.9	38.8	No
Manganese	677	0.0737	mg/kg	1	571	17.0	Yes
Nickel	105	0.797	mg/kg	1	110	4.7	Yes
Silver	7.07	0.224	mg/kg	1	6.96	1.6	Yes
Vanadium	154	0.211	mg/kg	1	156	1.3	Yes
Zinc	197	0.862	mg/kg	1	184	6.8	Yes

Table 3-2 PCB Matrix Spike and Matrix Spike Duplicate data.

Compound	Matrix Spike Result	RL	Units	Dilution	MSD	RPD	Acceptable
PCB-1016	176	4.35	ug/kg	1	175	0.6	Yes
PCB-1260	203	8.29	ug/kg	1	200	1.5	Yes

Table 3-3 Pesticide Matrix Spike and Matrix Spike Duplicate data.

Compound	Matrix Spike Result	RL	Units	Dilution	MSD	RPD	Acceptable
Lindane	3.8	0.22	ug/kg	1	3.7	2.7	Yes
Heptachlor	3.6	0.22	ug/kg	1	3.6	0.0	Yes
Aldrin	3.6	0.25	ug/kg	1	3.5	2.8	Yes
p,p-DDT	8.3	0.43	ug/kg	1	8.1	2.4	Yes
Dieldrin	8	0.43	ug/kg	1	7.8	2.5	Yes
Endrin	7.8	0.43	ug/kg	1	7.5	3.9	Yes
Methoxychlor	43	2.2	ug/kg	1	41	4.8	Yes
Alpha BHC	3.8	0.43	ug/kg	1	3.7	2.7	Yes
Beta BHC	4	0.8	ug/kg	1	4.1	2.5	Yes
Delta BHC	4.3	0.22	ug/kg	1	4.3	0.0	Yes
Heptachlor	The state of the s						
Epoxide	4	0.22	ug/kg	1	3.7	7.8	Yes
p,p-DDE	9.3	0.43	ug/kg	1	9.2	1.1	Yes
p,p-DDD	8.6	0.43	ug/kg	1	8.5	1.2	Yes
Toxaphene	7	14	ug/kg	1	7	0.0	Yes
Endosulfan I	3.8	0.29	ug/kg	1	3.7	2.7	Yes
Endosulfan II	8.1	0.43	ug/kg	1	7.8	3.8	Yes
Endosulfan					**************************************		
Sulfate	7.9	0.43	ug/kg	1	7.7	2.6	Yes
Endrin							
Aldehyde	7.4	0.43	ug/kg	1	7.1	4.1	Yes
Endrin Ketone	8.1	0.43	ug/kg	1 !	8.1	0.0	Yes
Alpha				_	1		
Chlordane	3.8	0.22	ug/kg	1	4	5.1	Yes
Gamma Chlordane	4	1.3	ug/kg	1	3.7	7.8	Yes
	• • • • • • • • • • • • • • • • • • •	1.0	45/A5	1	ا،د	1.0	1 52

Table 3-4 SVOC Matrix Spike and Matrix Spike Duplicate data.

Compound	Matrix Spike Result	RL	Units	Dilution	MSD	RPD	Acceptable
Phenol	1900	44	ug/kg	1	1900	0.0	Yes

Table 3-4 SVOC Matrix Spike and Matrix Spike Duplicate data.

Compound	Matrix Spike Result	RL	Units	Dilution	MSD	RPD	Acceptable
1-Chlorophenol	2000	44	ug/kg	1	1900	5.1	Yes
1,4-dichlorobenzene	1700	44	ug/kg	1	1600	6.1	Yes
N-Nitroso-di-n-propylamine	1900	44	ug/kg	1	1800	5.4	Yes
1,2,4-Trichlorobenzene	1800	44	ug/kg	1	1700	5.7	Yes
4-Chloro-3-methylphenol	2000	88	ug/kg	1	2100	4.9	Yes
Acenaphthene	2000	44	ug/kg	1	200	163.6	No
4-Nitrophenol	1300	220	ug/kg	1	1400	7.4	Yes
2,4-dinitrotoluene	2000	88	ug/kg	1	2000	0.0	Yes
Pentachlorophenol	1200	220	ug/kg	1	1200	0.0	Yes
Pyrene	2200	44	ug/kg	1	2200	0.0	Yes
1-Nitrophenol	2100	44	ug/kg	1	2000	4.9	Yes
2,4-Dimethylphenol	1900	88	ug/kg	1	1900	0.0	Yes
2,4-Dichlorophenol	1900	44	ug/kg	1	1900	0.0	Yes
2,4,6-Trichlorophenol	2000	44	ug/kg	1	2000	0.0	Yes
2,4-Dinitrophenol	1400	880	ug/kg	1	1400	0.0	Yes
4,6-Dinitro-2-methylphenol	1700	220	ug/kg	1	1800	5.7	Yes
bis(2-chloroethy)ether	1800	44	ug/kg	1	1700	5.7	Yes
1,3-Dichlorobenzene	1600	44	ug/kg	1	1500	6.5	Yes
1,2-Dichlorobenzene	1600	44	ug/kg	1	1600	0.0	Yes
Hexchloroethane	1500	44	ug/kg	1	1500	0.0	Yes
Nitrobenzene	1900	44	ug/kg	1	1800	5.4	Yes
Isophorone	1700	44	ug/kg	1	1700	0.0	Yes
bis-(2-Chloroethoxy)methane	2000	44	ug/kg	1	1900	5.1	Yes
Naphthalene	1800	44	ug/kg	1	1800	0.0	Yes
Hexachlorobutadiene	1700	88	ug/kg	1	1700	0.0	Yes
Hexachlorocyclopentadiene	2900	220	ug/kg	1	2600	10.9	Yes
2-Chloronaphthlene	1500	44	ug/kg	1	1400	6.9	Yes
Acenaphthylene	2100	44	ug/kg	1	2000	4.9	Yes
Dimethylphthalate	2000	88	ug/kg	1	2000	0.0	Yes
2,6-Dinitrotoluene	2100	44	ug/kg	1	2100	0.0	Yes
Fluorene	2100	44	ug/kg	1	2000	4.9	Yes
4-Chlorophenyl-phenylether	2000	44	ug/kg	1	2000	0.0	Yes
Diethylphthalate	2000	88	ug/kg	1	2000	0.0	Yes
N-Nitrosodiphenylamine	2100	44	ug/kg	1	2100	0.0	Yes
4-Bromophenyl-phenylether	2200	44	ug/kg	1	2100	4.7	Yes
Hexachlorobenzene	2100	44	ug/kg	1	2000	4.9	Yes
Phenanthrene	2100	44	ug/kg	1	2100	0.0	Yes
Anthracene	2100	44	ug/kg	1	2100	0.0	Yes
Di-n-butylphthalate	2100	88	ug/kg	1	2100	0.0	Yes
Fluoranthrene	1900	44	ug/kg	1	1900	0.0	Yes
Butylbenzylphthalate	2200	88	ug/kg	1	2100	4.7	Yes
Benzo(a)anthracene	2200	44	ug/kg	1	2100	4.7	Yes
Chrysene	2100	44	ug/kg	• 1	2100	0.0	Yes
3,3'-Dichlorobenzidine	1800	130	ug/kg	1	1600	11.8	Yes
bis(2-ehtylhexyl)phthalate	2300	88	ug/kg	1	2200	4.4	Yes

Table 3-4 SVOC Matrix Spike and Matrix Spike Duplicate data.

Compound	Matrix Spike Result	RL	Units	Dilution	MSD	RPD	Acceptable
Di-n-octylphthalate	2100	88	ug/kg	1	2100	0.0	Yes
Benzo(b)fluoranthene	2100	44	ug/kg	1	2000	4.9	Yes
Benzo(k)fluoranthene	1900	44	ug/kg	1	2000	5.1	Yes
Benzo(a)pyrene	2000	44	ug/kg	1	2000	0.0	Yes
Indeno(1,2,3-cd)pyrene	2100	44	ug/kg	1	2100	0.0	Yes
Dibenz(a,h)anthracene	2300	44	ug/kg	1	2300	0.0	Yes
Benzo(g,h,i)perylene	2200	44	ug/kg	1	2200	0.0	Yes
2-Methylphenol	2000	88	ug/kg	1	1900	5.1	Yes
2,2'-oxybis(1-Chloropropane)	1500	44	ug/kg	1	1400	6.9	Yes
4-Methylphenol	1800	88	ug/kg	1	1800	0.0	Yes
4-Chloroaniline	1300	88	ug/kg	1	1300	0.0	Yes
2-Methylnaphthalene	2000	44	ug/kg	1	1900	5.1	Yes
2,4,5-Trichlorophenol	1700	88	ug/kg	1	1800	5.7	Yes
2-Nitroaniline	2100	44	ug/kg	1	2100	0.0	Yes
2-Nitroaniline	1900	88	ug/kg	1	1900	0.0	Yes
Dibenzofuran	2000	44	ug/kg	1	2000	0.0	Yes
4-Nitroaniline	1700	88	ug/kg	1	1800	5.7	Yes
Carbazole	2000	44	ug/kg	1	2000	0.0	Yes

Table 3-5 Volatile Organic Compound Matrix Spike and Matrix Spike Duplicate data

Compound	Matrix Spike Result	RL	Units	Dilution	MSD	RPD	Acceptable
Chloromethane	21	3	ug/kg	1.01	19	10.0	Yes
Vinyl Chloride	23	1	ug/kg	1.01	19	19.0	Yes
Bromomethane	26	3	ug/kg	1.01	23	12.2	Yes
Choroethane	25	3	ug/kg	1.01	22	12.8	Yes
1,1-Dichlroethene	27	1	ug/kg	1.01	28	3.6	Yes
Methylene Chloride	27	3	ug/kg	1.01	27	0.0	Yes
trans-1,2-Dichloroethene	26	1	ug/kg	1.01	26	0.0	Yes
1,1-Dichloroethane	26	1	ug/kg	1.01	26	0.0	Yes
cis-1,2-Dichloroethene	24	1	ug/kg	1.01	26	8.0	Yes
Chloroform	27	1	ug/kg	1.01	25	7.7	Yes
1,1,1-Trichlroethane	28	1	ug/kg	1.01	27	3.6	Yes
Carbon Tetrachloride	28	0.7	ug/kg	1.01	28	0.0	Yes
Benzene	25	1	ug/kg	1.01	25	0.0	Yes
1,2-Dichlroethane	26	1	ug/kg	1.01	25	3.9	Yes
Trichloroethene	25	1	ug/kg	1.01	27	7.7	Yes
1,2-Dichloropropane	23	1	ug/kg	1.01	25	8.3	Yes
Bromodichloromethane	26	1	ug/kg	1.01	24	8.0	Yes
Toluene	27	1	ug/kg	1.01	36	28.6	Yes
1,1,2-Trichloroethane	23	1	ug/kg	1.01	24	4.3	Yes
Tetrachloroethene	26	1	ug/kg	1.01	25	3.9	Yes

Table 3-5 Volatile Organic Compound Matrix Spike and Matrix Spike Duplicate data.

Compound	Matrix Spike Result	RL	Units	Dilution	MSD	RPD	Acceptable
Dibromochloromethane	25	1	ug/kg	1.01	25	0.0	Yes
Chlorobenzene	24	1	ug/kg	1.01	24	0.0	Yes
Ethylbenzene	26	1	ug/kg	1.01	26	0.0	Yes
Styrene	24	1	ug/kg	1.01	23	4.3	Yes
Bromoform	22	1	ug/kg	1.01	22	0.0	Yes
1,1,2,2-Tetrachloroethane	22	1	ug/kg	1.01	22	0.0	Yes
Acetone	310	9	ug/kg	1.01	260	17.5	Yes
Carbon Disulfide	26	1	ug/kg	1.01	25	3.9	Yes
2-Butanone	200	5	ug/kg	1.01	200	0.0	Yes
trans-1,3-dichloropropene	23	1	ug/kg	1.01	23	0.0	Yes
cis-1,3-dichloropropene	23	1	ug/kg	1.01	23	0.0	Yes
4-Methyl-2-pentanone	100	4	ug/kg	1.01	110	9.5	Yes
2-Hexanone	120	4	ug/kg	1.01	120	0.0	Yes
Xylene (total)	76	1	ug/kg	1.01	78	2.60	Yes

3.5. Laboratory Control Samples

LCS/LCSDs are laboratory-prepared blank matrix samples spiked with target compounds, and used to document laboratory performance, accuracy and precision.

3.5.1. Volatile Organic Compounds

Greater than 90% of the LCS recoveries were within the control limits indicating that the methods were in control. All resulting LCS/LCSD RPD values were within accepted control limits (0-30%).

3.5.2. Semi volatile Organic Compounds

One hundred percent (100%) of all semi volatile organic compound LCS/LCSD recoveries were within method prescribed control limits. Resulting RPD values were all within accepted control limits.

3.5.3. Pesticides

Greater than 90% of the LCS/LCSD recoveries were within the control limits indicating that the methods were in control. LCS recovery (water) of 4,4'-DDD was reported outside of the

accepted method prescribed QC control limits (129% v. 125%). The RPD value for endrin (water) was also outside of the accepted method prescribed QC control limits (21% v. 20%).

3.5.4. Polychlorinated Biphenyl (PCBs)

One hundred percent (100%) of all polychlorinated biphenyl compound LCS/LCSD recoveries were within method prescribed control limits. Resulting RPD values were all within accepted control limits.

3.5.5.Metals

RPD values for calcium, cobalt, lead, manganese and zinc were outside accepted limits, indicating poor duplicate precision.

3.6. Method Blanks

A method blank is a laboratory-prepared blank matrix sample included in all preparation batches. No analytes were detected in the method blanks above the laboratory reporting limits (RL), indicating that the laboratory procedures were free from contamination.

4. Data Quality Assessment

Systematic checks were performed to ensure that quality data were being produced, that the test results and field procedures remained reproducible, and that the analytical methodology was actually measuring the quantity of analytes in each sample. The results of data quality indicators (PARCCS parameters) are discussed below.

Precision

Precision is a measure of the reproducibility of analyses under a given set of conditions and was assessed by replicate measurements of field and laboratory duplicate samples. The low percentage of precision exceedances indicates that the analytical methods were consistently precise.

Accuracy

Accuracy is a determination of how close the measurement is to the true value and was assessed using LCS, MS/MSD, and surrogate spiked samples. In general, the calibrations and the surrogate, MS, and LCS spike recoveries were acceptable, indicating that the methods were consistently accurate.

Representativeness

Representativeness refers to the degree to which sample data accurately and precisely describe the characteristics of a population of samples, parameter variations at a sampling point, or environmental conditions. Representativeness is a qualitative parameter, which is primarily concerned with the proper design of the sampling program or of the subsampling of a given sample. Representativeness was maintained by the use of duplicate field and laboratory samples, properly preserved samples and samples analyzed within acceptable holding times. Determinant of representativeness also includes possible compromises to sample integrity (such as cross-contamination) that can occur during sample collection, transport, and analysis. Absence of samples affected by laboratory and field blank contamination indicates that laboratory and field equipment decontamination procedures were effective.

Completeness

Completeness is a measure of the amount of valid data obtained from a measurement system compared with the amount that was expected to be obtained under normal conditions.

Percent completeness for each set of samples for each individual method can be calculated as follows:

Completeness =
$$\frac{valid\ data\ obtained}{total\ data\ analyzed}$$
 x 100%

Where valid data is defined as those data points that are not qualified as rejected, none of the reported data was qualified as rejected, thus exceeding the requirement for completeness of 90 percent. In addition, the completeness requirement for holding times of 100 percent was met.

Comparability

Comparability is a qualitative parameter expressing the confidence in which one data set can be compared with another. Sample data will be comparable for similar samples collected under like conditions. Since

the workplan was followed, the data generated during this sampling event was comparable, the correct analytical methods were used by approved laboratories, and the prescribed QC samples were collected and analyzed.

Sensitivity

Sensitivity is determined by the MDL, which is the minimum concentration of a substance that can be measured and reported with 99 percent confidence that the analyte concentration is greater than zero. The laboratory established MDLs for each method, matrix, and analyte for each instrument the laboratory used for the project. All the RLs met method reporting limits, indicating sensitivity requirements were met except in those cases sample extracts were diluted due to high analyte concentration or matrix interference.

Based on our review of the field and laboratory QA/QC procedures, Kleinfelder concludes the following:

- The majority of the data meets method protocol accepted QA/QC requirements.
- Lancaster analyzed 100 percent of the requested analyses submitted by Kleinfelder.
- All of the samples were analyzed within holding time, resulting in the holding time completeness
 of 100 percent.
- None of the data were qualified as rejected. Therefore, analytical completeness is 100 percent for the data generated.
- The levels of precision and accuracy measured on the basis of the LCS, MS/MSD, and surrogate recoveries are acceptable.
- The analytical data are deemed acceptable and usable for decision-making purposes.

References

- USEPA 1999. National Functional Guidelines for Organic Data Review. U.S. Environmental Protection Agency, Contract Laboratory Program, EPA-540/R-99-008, October 1999.
- NYSDEC 2002. Draft DER-10 Technical Guidance for Site Investigation and Remediation. New York State Department of Environmental Conservation, December 2002.

DATA USABILITY SUMMARY REPORT FORT. COVINGTON, NEW YORK

KLEINFELDER PROJECT ID: 69968

SAMPLE DELIVERY GROUP (SDG) FVC02

TABLE OF CONTENTS

1. Summar	y	. 1
2. Personne	el Qualifications	. 2
3. Laborato	ry Data Verification	. 2
3.1. Hol	ding Times	.2
3.2. Sun	rogate Recoveries	. 2
3.3. Initi	ial and Continuing Calibration	.3
3.3.1.	Initial Calibration	. 3
3.3.2.	Continuing Calibration	. 3
3.4. Mat	rix Spikes and Matrix Spike Duplicates	. 3
3.4.1.	Volatile Organic Compounds	. 3
3.4.2.	Semi volatile Organic Compounds	
3.4.3.	Pesticides	. 3
3.4.4.	Polychlorinated Biphenyls	. 3
3.4.5.	Metals	4
3.5. Lab	oratory Control Samples	.4
3.5.1.	Volatile Organic Compounds	. 4
3.5.2.	Semi volatile Organic Compounds	. 4
3.5.3.	Pesticides	. 4
3.5.4.	Polychlorinated Biphenyl (PCBs)	4
3.5.5.	Metals	4
3.6. Met	hod Blanks	5
4. Data Qua	lity Assessment	5
References		8

Quality Assurance/Quality Control

Data Usability Summary Report Fort Covington, New York

Kleinfelder Project ID: 69968

The following personnel have reviewed this report for accuracy, content, and quality of presentation:

Kleinfelder East, Inc.

Mr. John A. Martin, CHMM Industrial Hygienist

Mr. John Imhoff Senior Project Manager nature MAUN Date: 9-19-200

Signature: Date: 9-20-20

1. Summary

This Data Usability Summary Report (DUSR) has been prepared in accordance with the New York State Department of Environmental Conservation (NYSDEC) guidance for the development of DUSR reports and is intended to verify that the data packages associated with this DUSR are complete as defined under the requirements for the NYSDEC ASP Category B or USEPA CLP deliverables; to ensure that all method holding times have been met; to ensure that QC data (blanks, instrument tunings, calibration standards, calibration verifications, surrogate recoveries, spike recoveries, replicate analysis, laboratory controls and sample data) fall within the protocol required limits and specifications; that all data have been developed using established and agreed upon analytical procedures; evaluation of raw data to confirm results; to ensure the correct data qualifiers have been used; and, to evaluate the NYSDEC Matrix Spike Blank Data.

This (DUSR) documents the review of analytical data associated with the June 2007 sampling event at the Fort Covington project site.

Three groundwater samples were collected by Kleinfelder personnel on June 25, 2007 and subsequently submitted to Lancaster Laboratories "Lancaster" of Lancaster, Pennsylvania for analysis of volatile organic compounds (VOCs) via EPA SW-846 method 8260B, semi-volatile organic compounds (SCOCs) via EPA SW-846 method 8270C, select heavy metals via EPA SW-846 series 6000, polychlorinated biphenols (PCBs) and pesticides via EPA SW-846 method 8082B. Data packages received from the laboratory were in conformance with the New York State Department of Environmental Conservation Analytical Service Protocol (NYSDEC ASP) Category B.

Analytical data, and other information contained within the data packages associated with this report, have undergone review to evaluate the levels of accuracy, precision, and completeness of the data. Unless otherwise noted, sample storage, preparation, analysis, reporting, and quality control (QC) measures were performed in accordance with published EPA analytical protocol.

2. Personnel Qualifications

The data packages provided by Lancaster laboratories were reviewed by Mr. John Martin, CHMM. Mr. Martin is a chemist and environmental health scientist based out of Kleinfelder's Massachusetts operation. He has 13 years of industry experience. He has multi-faceted experience working within the analytical laboratory environment, and has strong working knowledge of analytical instrumentation, laboratory procedure and analytical methods. Mr. Martin regularly conducts laboratory data report review and validation activities under EPA laboratory protocol in support of assessment, remediation and due diligence transactions in the mid-Atlantic and Northeast regions.

Mr. Martin holds a B.S. degree in Chemistry, a B.S. degree in Biology, and a Master of Public Health Degree (MPH).

3. Laboratory Data Verification

One hundred percent (100 percent) of data generated for this project were evaluated through a systematic procedure in which method performance is compared to defined criteria. The following sections provide the overview of the data verification methodology and the results of the laboratory QA/QC program review.

3.1. Holding Times

All samples received by Lancaster were accompanied by proper chain-of-custody documentation. Collection dates for the samples submitted to the laboratory are included in the chain-of-custody documentation. Sample collection, preparation, and analyses dates are indicated on the laboratory reports. All samples were properly preserved. Holding times were met for the analyses performed.

3.2. Surrogate Recoveries

A surrogate is a compound spiked into the sample that is uncommon in the environment but that behaves similarly to the target analyte, chromatographically. Surrogate recoveries are used to monitor method performance for the target analytes and were included with all samples analyzed for VOCs. Greater than 90% of the surrogate recoveries were within the method prescribed control limits.

3.3. Initial and Continuing Calibration

3.3.1.Initial Calibration

The % D for 4,4'-DDD was reported outside accepted method limits, >20% as defined by NELAC in initial calibration verification standards. All other initial calibration verification standards were within accepted method limits.

3.3.2. Continuing Calibration

All continuing calibration verification standards were within method specification and acceptance criteria.

3.4. Matrix Spikes and Matrix Spike Duplicates

A matrix spike (MS) is a primary sample spiked with target compounds. MS/Matrix Spike Duplicate (MS/MSD) analyses provide spike recovery percentages and RPDs between analyses of the same spiked sample, which provide a measure of analytical precision.

3.4.1. Volatile Organic Compounds

All of the matrix spike recovery data reported by Lancaster comply with method protocol. RPD values were not reported from MSD samples, as insufficient sample volume was provided to perform the MSD analysis for this SDG.

3.4.2. Semi volatile Organic Compounds

MS/MSD analyses were not performed due to insufficient sample volume.

3.4.3. Pesticides

One hundred percent 100% of the MS and MSD recoveries were within the control limits indicating that the methods were in control. All resulting MS/MSD RPD values were within accepted control limits (0-30%).

3.4.4. Polychlorinated Biphenyls

One hundred percent (100%) of all polychlorinated biphenyl compound MS/MSD recoveries were within method prescribed control limits. Resulting RPD values were all within accepted control limits.

3.4.5.Metals

MS/MSD revocery percentages for calcium, magnesium, potassium and sodium were outside method accepted limits. The data are reported unflagged, in accordance with USEPA guidance.

3.5. Laboratory Control Samples

A LCS/LCSD are laboratory-prepared blank matrix samples spiked with target compounds, and used to document laboratory performance, accuracy and precision.

3.5.1. Volatile Organic Compounds

One hundred percent 100% of the LCS recoveries were within the control limits indicating that the methods were in control. All resulting LCS/LCSD RPD values were within accepted control limits (0-30%).

3.5.2. Semi volatile Organic Compounds

LCS recovery of 2,4-dinitrotoluene was outside method prescribed QA/QC limits (109 v. 108). The LCSD recovery was within limits, 106%, and the resulting RPD was within method tolerances.

3.5.3. Pesticides

100% of the LCS/LCSD recoveries were within the control limits indicating that the methods were in control. The resulting RPD values are all within method accepted control limits.

3.5.4. Polychlorinated Biphenyl (PCBs)

One hundred percent (100%) of all polychlorinated biphenyl compound LCS/LCSD recoveries were within method prescribed control limits. Resulting RPD values were all within accepted control limits.

3.5.5.Metals

LCS results were not observed within the data package. In accordance with USEPA guidance, Initial Calibration Verification solutions may be used in lieu of LCS sample preparations. All recovery results were within prescribed method acceptance limits (80-120%)

3.6. Method Blanks

A method blank is a laboratory-prepared blank matrix sample included in all preparation batches. No analytes were detected in the method blanks above the laboratory reporting limits (RL), indicating that the laboratory procedures were free from contamination.

4. Data Quality Assessment

Systematic checks were performed to ensure that quality data were being produced, that the test results and field procedures remained reproducible, and that the analytical methodology was actually measuring the quantity of analytes in each sample. The results of data quality indicators (PARCCS parameters) are discussed below.

Precision

Precision is a measure of the reproducibility of analyses under a given set of conditions and was assessed by replicate measurements of field and laboratory duplicate samples. The low percentage of precision exceedances indicates that the analytical methods were consistently precise.

Accuracy

Accuracy is a determination of how close the measurement is to the true value and was assessed using LCS, MS/MSD, and surrogate spiked samples. In general, the calibrations and the surrogate, MS, and LCS spike recoveries were acceptable, indicating that the methods were consistently accurate.

Representativeness

Representativeness refers to the degree to which sample data accurately and precisely describe the characteristics of a population of samples, parameter variations at a sampling point, or environmental conditions. Representativeness is a qualitative parameter, which is primarily concerned with the proper design of the sampling program or of the subsampling of a given sample. Representativeness was maintained by the use of duplicate field and laboratory samples, properly preserved samples and samples analyzed within acceptable holding times. Determinant of representativeness also includes possible compromises to sample integrity (such as cross-contamination) that can occur during sample collection,

transport, and analysis. Absence of samples affected by laboratory and field blank contamination indicates that laboratory and field equipment decontamination procedures were effective.

Completeness

Completeness is a measure of the amount of valid data obtained from a measurement system compared with the amount that was expected to be obtained under normal conditions.

Percent completeness for each set of samples for each individual method can be calculated as follows:

Completeness =
$$\frac{valid\ data\ obtained}{total\ data\ analyzed}$$
 x 100%

Where valid data is defined as those data points that are not qualified as rejected, none of the reported data was qualified as rejected, thus exceeding the requirement for completeness of 90 percent. In addition, the completeness requirement for holding times of 100 percent was met.

Comparability

Comparability is a qualitative parameter expressing the confidence in which one data set can be compared with another. Sample data will be comparable for similar samples collected under like conditions. Since the workplan was followed, the data generated during this sampling event was comparable, the correct analytical methods were used by approved laboratories, and the prescribed QC samples were collected and analyzed.

Sensitivity

Sensitivity is determined by the MDL, which is the minimum concentration of a substance that can be measured and reported with 99 percent confidence that the analyte concentration is greater than zero. The laboratory established MDLs for each method, matrix, and analyte for each instrument the laboratory used for the project. All the RLs met method reporting limits, indicating sensitivity requirements were met except in those cases sample extracts were diluted due to high analyte concentration or matrix interference.

Based on our review of the field and laboratory QA/QC procedures, Kleinfelder concludes the following:

- The majority of the data meets method protocol accepted QA/QC requirements.
- Lancaster analyzed 100 percent of the requested analyses submitted by Kleinfelder.
- All of the samples were analyzed within holding time, resulting in the holding time completeness of 100 percent.
- None of the data were qualified as rejected. Therefore, analytical completeness is 100 percent for the data generated.
- The levels of precision and accuracy measured on the basis of the LCS, MS/MSD, and surrogate recoveries are acceptable.
- The analytical data are deemed acceptable and usable for decision-making purposes.

References

- USEPA 1999. National Functional Guidelines for Organic Data Review. U.S. Environmental Protection Agency, Contract Laboratory Program, EPA-540/R-99-008, October 1999.
- USEPA 2004. National Functional Guidelines for Inorganic Data Review. U.S. Environmental Protection Agency, Contract Laboratory Program, EPA-540-R-04-004, October 2004.
- NYSDEC 2002. Draft DER-10 Technical Guidance for Site Investigation and Remediation. New York State Department of Environmental Conservation, December 2002.

DATA USABILITY SUMMARY REPORT FORT. COVINGTON, NEW YORK

KLEINFELDER PROJECT ID: 69968

SAMPLE DELIVERY GROUP (SDG) FVC03

TABLE OF CONTENTS

1. Summary	
2. Personnel Qualifications	2
3. Laboratory Data Verification	2
3.1. Holding Times	
3.2. Surrogate Recoveries	2
3.3. Initial and Continuing Calibration	3
3.3.1. Initial Calibration	3
3.3.2. Continuing Calibration	
3.4. Laboratory Control Samples	3
3.4.1. Volatile Organic Compounds	3
3.5. Method Blanks	3
4. Data Quality Assessment	
References	

Quality Assurance/Quality Control

Data Usability Summary Report Fort Covington, New York

Kleinfelder Project ID: 69968

The following personnel have reviewed this report for accuracy, content, and quality of presentation:

Kleinfelder East, Inc.

Mr. John A. Martin, CHMM Industrial Hygienist

Mr. John Imhoff Senior Project Manager Signature:

Date: 1-14-2007

Signature

ii

1. Summary

This Data Usability Summary Report (DUSR) has been prepared in accordance with the New York State Department of Environmental Conservation (NYSDEC) guidance for the development of DUSR reports and is intended to verify that the data packages associated with this DUSR are complete as defined under the requirements for the NYSDEC ASP Category B or USEPA CLP deliverables; to ensure that all method holding times have been met; to ensure that QC data (blanks, instrument tunings, calibration standards, calibration verifications, surrogate recoveries, spike recoveries, replicate analysis, laboratory controls and sample data) fall within the protocol required limits and specifications; that all data have been developed using established and agreed upon analytical procedures; evaluation of raw data to confirm results; to ensure the correct data qualifiers have been used; and, to evaluate the NYSDEC Matrix Spike Blank Data.

This (DUSR) documents the review of analytical data associated with the June 2007 sampling event at the Fort Covington project site.

Three gas samples were collected by Kleinfelder personnel on June 26, 2007 and subsequently submitted to Lancaster Laboratories "Lancaster" of Lancaster, Pennsylvania for analysis of volatile organic compounds (VOCs) via EPA SW-846 method 8260B, semi-volatile organic compounds (SCOCs) via EPA SW-846 method 8270C, select heavy metals via EPA SW-846 series 6000, polychlorinated biphenols (PCBs) and pesticides via EPA SW-846 method 8082B. Data packages received from the laboratory were in conformance with the New York State Department of Environmental Conservation Analytical Service Protocol (NYSDEC ASP) Category B.

Analytical data, and other information contained within the data packages associated with this report, have undergone review to evaluate the levels of accuracy, precision, and completeness of the data. Unless otherwise noted, sample storage, preparation, analysis, reporting, and quality control (QC) measures were performed in accordance with published EPA analytical protocol.

2. Personnel Qualifications

The data packages provided by Lancaster laboratories were reviewed by Mr. John Martin, CHMM. Mr. Martin is a chemist and environmental health scientist based out of Kleinfelder's Massachusetts operation. He has 13 years of industry experience. He has multi-faceted experience working within the analytical laboratory environment, and has strong working knowledge of analytical instrumentation, laboratory procedure and analytical methods. Mr. Martin regularly conducts laboratory data report review and validation activities under EPA laboratory protocol in support of assessment, remediation and due diligence transactions in the mid-Atlantic and Northeast regions.

Mr. Martin holds a B.S. degree in Chemistry, a B.S. degree in Biology, and a Master of Public Health Degree (MPH).

3. Laboratory Data Verification

One hundred percent (100 percent) of data generated for this project were evaluated through a systematic procedure in which method performance is compared to defined criteria. The following sections provide the overview of the data verification methodology and the results of the laboratory QA/QC program review.

3.1. Holding Times

All samples received by Lancaster were accompanied by proper chain-of-custody documentation. Collection dates for the samples submitted to the laboratory are included in the chain-of-custody documentation. Sample collection, preparation, and analyses dates are indicated on the laboratory reports. All samples were properly preserved. Holding times were met for the analyses performed.

3.2. Surrogate Recoveries

A surrogate is a compound spiked into the sample that is uncommon in the environment but that behaves similarly to the target analyte, chromatographically. Surrogate recoveries are used to monitor method performance for the target analytes and were included with all samples analyzed for VOCs. Greater than 90% of the surrogate recoveries were within the method prescribed control limits.

3.3. Initial and Continuing Calibration

3.3.1.Initial Calibration

All initial calibration verification standards were within accepted method limits.

3.3.2. Continuing Calibration

All continuing calibration verification standards were within method specification and acceptance criteria.

3.4. Laboratory Control Samples

A LCS/LCSD are laboratory-prepared blank matrix samples spiked with target compounds, and used to document laboratory performance, accuracy and precision.

3.4.1. Volatile Organic Compounds

One hundred percent 100% of the LCS recoveries were within the control limits indicating that the methods were in control. All resulting LCS/LCSD RPD values were within accepted control limits (0-30%).

3.5. Method Blanks

A method blank is a laboratory-prepared blank matrix sample included in all preparation batches. No analytes were detected in the method blanks above the laboratory reporting limits (RL), indicating that the laboratory procedures were free from contamination.

4. Data Quality Assessment

Systematic checks were performed to ensure that quality data were being produced, that the test results and field procedures remained reproducible, and that the analytical methodology was actually measuring the quantity of analytes in each sample. The results of data quality indicators (PARCCS parameters) are discussed below.

Precision

Precision is a measure of the reproducibility of analyses under a given set of conditions and was assessed by replicate measurements of field and laboratory duplicate samples. The low percentage of precision exceedances indicates that the analytical methods were consistently precise.

Accuracy

Accuracy is a determination of how close the measurement is to the true value and was assessed using LCS, MS/MSD, and surrogate spiked samples. In general, the calibrations and the surrogate, MS, and LCS spike recoveries were acceptable, indicating that the methods were consistently accurate.

Representativeness

Representativeness refers to the degree to which sample data accurately and precisely describe the characteristics of a population of samples, parameter variations at a sampling point, or environmental conditions. Representativeness is a qualitative parameter, which is primarily concerned with the proper design of the sampling program or of the subsampling of a given sample. Representativeness was maintained by the use of duplicate field and laboratory samples, properly preserved samples and samples analyzed within acceptable holding times. Determinant of representativeness also includes possible compromises to sample integrity (such as cross-contamination) that can occur during sample collection, transport, and analysis. Absence of samples affected by laboratory and field blank contamination indicates that laboratory and field equipment decontamination procedures were effective.

Completeness

Completeness is a measure of the amount of valid data obtained from a measurement system compared with the amount that was expected to be obtained under normal conditions.

Percent completeness for each set of samples for each individual method can be calculated as follows:

Completeness =
$$\frac{\text{valid data obtained}}{\text{total data analyzed}} \times 100\%$$

Where valid data is defined as those data points that are not qualified as rejected, none of the reported data was qualified as rejected, thus exceeding the requirement for completeness of 90 percent. In addition, the completeness requirement for holding times of 100 percent was met.

Comparability

Comparability is a qualitative parameter expressing the confidence in which one data set can be compared with another. Sample data will be comparable for similar samples collected under like conditions. Since the workplan was followed, the data generated during this sampling event was comparable, the correct analytical methods were used by approved laboratories, and the prescribed QC samples were collected and analyzed.

Sensitivity

Sensitivity is determined by the MDL, which is the minimum concentration of a substance that can be measured and reported with 99 percent confidence that the analyte concentration is greater than zero. The laboratory established MDLs for each method, matrix, and analyte for each instrument the laboratory used for the project. All the RLs met method reporting limits, indicating sensitivity requirements were met except in those cases sample extracts were diluted due to high analyte concentration or matrix interference.

Based on our review of the field and laboratory QA/QC procedures, Kleinfelder concludes the following:

- The majority of the data meets method protocol accepted QA/QC requirements.
- Lancaster analyzed 100 percent of the requested analyses submitted by Kleinfelder.
- All of the samples were analyzed within holding time, resulting in the holding time completeness
 of 100 percent.
- None of the data were qualified as rejected. Therefore, analytical completeness is 100 percent for the data generated.
- The levels of precision and accuracy measured on the basis of the LCS, MS/MSD, and surrogate recoveries are acceptable.
- The analytical data are deemed acceptable and usable for decision-making purposes.

References

USEPA 1999, Compendium of Methods for the Determination of Toxic Organic Compounds in Ambient Air. Second Edition. Compendium Method TO-15, Determination of Volatile Chromatography/Mass Spectrometry (GC/MS). January 1999.

DATA USABILITY SUMMARY REPORT FORT. COVINGTON, NEW YORK

KLEINFELDER PROJECT ID: 69968

SAMPLE DELIVERY GROUP (SDG) FVC04

TABLE OF CONTENTS

1. Summary	/	. 1
2. Personne	l Qualifications	. 2
3. Laborato	ry Data Verification	.2
3.1. Hole	ding Times	. 2
3.2. Surr	ogate Recoveries	. 2
3.3. Initi	al and Continuing Calibration	.3
3.3.1.	Initial Calibration	
3.3.2.	Continuing Calibration	. 3
3.4. Mat	rix Spikes and Matrix Spike Duplicates	. 3
3.4.1.	Volatile Organic Compounds	. 3
3.4.2.	Semi volatile Organic Compounds	. 3
3.4.3.	Pesticides	. 3
3.4.4.	Polychlorinated Biphenyls	. 4
3.4.5.	Metals	. 4
3.5. Labo	oratory Control Samples	. 4
3.5.1.	Volatile Organic Compounds	. 4
3.5.2.	Semi volatile Organic Compounds	. 4
3.5.3.	Pesticides	
3.5.4.	Polychlorinated Biphenyl (PCBs)	. 4
3.5.5.	Metals	. 4
	nod Blanks	
Data Qua	lity Assessment	. 5
References		8

Quality Assurance/Quality Control

Data Usability Summary Report Fort Covington, New York

Kleinfelder Project ID: 69968

The following personnel have reviewed this report for accuracy, content, and quality of presentation:

Kleinfelder East, Inc.

Mr. John A. Martin, CHMM Industrial Hygienist

Mr. John Imhoff Senior Project Manager Signature:

Date: 1-(9-2007

Signature

Date: <u>9-20-0</u>7

1. Summary

This Data Usability Summary Report (DUSR) has been prepared in accordance with the New York State Department of Environmental Conservation (NYSDEC) guidance for the development of DUSR reports and is intended to verify that the data packages associated with this DUSR are complete as defined under the requirements for the NYSDEC ASP Category B or USEPA CLP deliverables; to ensure that all method holding times have been met; to ensure that QC data (blanks, instrument tunings, calibration standards, calibration verifications, surrogate recoveries, spike recoveries, replicate analysis, laboratory controls and sample data) fall within the protocol required limits and specifications; that all data have been developed using established and agreed upon analytical procedures; evaluation of raw data to confirm results; to ensure the correct data qualifiers have been used; and, to evaluate the NYSDEC Matrix Spike Blank Data.

This (DUSR) documents the review of analytical data associated with the June 2007 sampling event at the Fort Covington project site.

Three soil samples were collected by Kleinfelder personnel on June 29, 2007 and subsequently submitted to Lancaster Laboratories "Lancaster" of Lancaster, Pennsylvania for analysis of volatile organic compounds (VOCs) via EPA SW-846 method 8260B, semi-volatile organic compounds (SCOCs) via EPA SW-846 method 8270C, select heavy metals via EPA SW-846 series 6000, polychlorinated biphenols (PCBs) and pesticides via EPA SW-846 method 8082B. Data packages received from the laboratory were in conformance with the New York State Department of Environmental Conservation Analytical Service Protocol (NYSDEC ASP) Category B.

Analytical data, and other information contained within the data packages associated with this report, have undergone review to evaluate the levels of accuracy, precision, and completeness of the data. Unless otherwise noted, sample storage, preparation, analysis, reporting, and quality control (QC) measures were performed in accordance with published EPA analytical protocol.

2. Personnel Qualifications

The data packages provided by Lancaster laboratories were reviewed by Mr. John Martin, CHMM. Mr. Martin is a chemist and environmental health scientist based out of Kleinfelder's Massachusetts operation. He has 13 years of industry experience. He has multi-faceted experience working within the analytical laboratory environment, and has strong working knowledge of analytical instrumentation, laboratory procedure and analytical methods. Mr. Martin regularly conducts laboratory data report review and validation activities under EPA laboratory protocol in support of assessment, remediation and due diligence transactions in the mid-Atlantic and Northeast regions.

Mr. Martin holds a B.S. degree in Chemistry, a B.S. degree in Biology, and a Master of Public Health Degree (MPH).

3. Laboratory Data Verification

One hundred percent (100 percent) of data generated for this project were evaluated through a systematic procedure in which method performance is compared to defined criteria. The following sections provide the overview of the data verification methodology and the results of the laboratory QA/QC program review.

3.1. Holding Times

All samples received by Lancaster were accompanied by proper chain-of-custody documentation. Collection dates for the samples submitted to the laboratory are included in the chain-of-custody documentation. Sample collection, preparation, and analyses dates are indicated on the laboratory reports. All samples were properly preserved. Holding times were met for the analyses performed.

3.2. Surrogate Recoveries

A surrogate is a compound spiked into the sample that is uncommon in the environment but that behaves similarly to the target analyte, chromatographically. Surrogate recoveries are used to monitor method performance for the target analytes. Greater than 90% of the surrogate recoveries were within the method prescribed control limits.

3.3. Initial and Continuing Calibration

3.3.1.Initial Calibration

The % D for TCX was reported outside accepted method limits, >20% as defined by NELAC in initial calibration verification standards. All other initial calibration verification standards were within accepted method limits.

3.3.2. Continuing Calibration

Continuing calibration verification (CCV) returned %Ds and average %D's for 4,4'-DDT was outside of method specification accepted limits. The ending continuing calibration was outside QC limits for multiple compounds. The associated samples were previously injected with similar results, suggesting possible matrix interference..

3.4. Matrix Spikes and Matrix Spike Duplicates

A matrix spike (MS) is a primary sample spiked with target compounds. MS/Matrix Spike Duplicate (MS/MSD) analyses provide spike recovery percentages and RPDs between analyses of the same spiked sample, which provide a measure of analytical precision.

3.4.1. Volatile Organic Compounds

MS and MSD recovery were within method accepted control limits for all compounds. RPD's for multiple compounds were reported outside of method prescribed control limits.

3.4.2. Semi volatile Organic Compounds

MS and MSD recoveries were reported within method accepted control limits for all compounds except 2,4-Dinitrophenol. 2,4-Dinitrophenol was adequately recovered in the LCS analysis. Subsequently calculated RPDs were within method accepted control limits for all compounds except 2,4-Dinitrophenol and 3,3'-Dichlorobenzidine.

3.4.3. Pesticides

One hundred percent 100% of the MS recoveries were within method accepted control limits. MSD recoveries for beta-BHC, 4,4'-DDT and Methoxyclor were outside method accepted control limits. All other MSD recoveries were within method prescribed control limits. All resulting MS/MSD RPD values were within accepted control limits (0-35%), except beta-BHC (66%)

3.4.4.Polychlorinated Biphenyls

One hundred percent (100%) of all polychlorinated biphenyl compound MS/MSD recoveries were within method prescribed control limits. Resulting RPD values were all within accepted control limits.

3.4.5. Metals

The MSD recovery percentage for copper was outside method accepted limits. The subsequently calculated RPD for copper was also outside of method prescribed acceptance limits. The data are reported unflagged, in accordance with USEPA guidance.

3.5. Laboratory Control Samples

A LCS/LCSD are laboratory-prepared blank matrix samples spiked with target compounds, and used to document laboratory performance, accuracy and precision.

3.5.1. Volatile Organic Compounds

One hundred percent 100% of the LCS recoveries were within the control limits indicating that the methods were in control.

3.5.2. Semi volatile Organic Compounds

LCS recoveries were reported within method accepted control limits for all compounds.

3.5.3. Pesticides

100% of the LCS recoveries were within the control limits indicating that the methods were in control.

3.5.4. Polychlorinated Biphenyl (PCBs)

One hundred percent (100%) of all polychlorinated biphenyl compound LCS were within method prescribed control limits.

3.5.5.Metals

LCS results were not observed within the data package. In accordance with USEPA guidance, Initial Calibration Verification solutions may be used in lieu of LCS sample preparations. All recovery results were within prescribed method acceptance limits (80-120%)

3.6. Method Blanks

A method blank is a laboratory-prepared blank matrix sample included in all preparation batches. No analytes were detected in the method blanks above the laboratory reporting limits (RL), indicating that the laboratory procedures were free from contamination.

4. Data Quality Assessment

Systematic checks were performed to ensure that quality data were being produced, that the test results and field procedures remained reproducible, and that the analytical methodology was actually measuring the quantity of analytes in each sample. The results of data quality indicators (PARCCS parameters) are discussed below.

Precision

Precision is a measure of the reproducibility of analyses under a given set of conditions and was assessed by replicate measurements of field and laboratory duplicate samples. The low percentage of precision exceedances indicates that the analytical methods were consistently precise.

Accuracy

Accuracy is a determination of how close the measurement is to the true value and was assessed using LCS, MS/MSD, and surrogate spiked samples. In general, the calibrations and the surrogate, MS, and LCS spike recoveries were acceptable, indicating that the methods were consistently accurate.

Representativeness

Representativeness refers to the degree to which sample data accurately and precisely describe the characteristics of a population of samples, parameter variations at a sampling point, or environmental conditions. Representativeness is a qualitative parameter, which is primarily concerned with the proper design of the sampling program or of the subsampling of a given sample. Representativeness was maintained by the use of duplicate field and laboratory samples, properly preserved samples and samples

analyzed within acceptable holding times. Determinant of representativeness also includes possible compromises to sample integrity (such as cross-contamination) that can occur during sample collection, transport, and analysis. Absence of samples affected by laboratory and field blank contamination indicates that laboratory and field equipment decontamination procedures were effective.

Completeness

Completeness is a measure of the amount of valid data obtained from a measurement system compared with the amount that was expected to be obtained under normal conditions.

Percent completeness for each set of samples for each individual method can be calculated as follows:

Completeness =
$$\frac{valid\ data\ obtained}{total\ data\ analyzed}$$
 x 100%

Where valid data is defined as those data points that are not qualified as rejected, none of the reported data was qualified as rejected, thus exceeding the requirement for completeness of 90 percent. In addition, the completeness requirement for holding times of 100 percent was met.

Comparability

Comparability is a qualitative parameter expressing the confidence in which one data set can be compared with another. Sample data will be comparable for similar samples collected under like conditions. Since the workplan was followed, the data generated during this sampling event was comparable, the correct analytical methods were used by approved laboratories, and the prescribed QC samples were collected and analyzed.

Sensitivity

Sensitivity is determined by the MDL, which is the minimum concentration of a substance that can be measured and reported with 99 percent confidence that the analyte concentration is greater than zero. The laboratory established MDLs for each method, matrix, and analyte for each instrument the laboratory used for the project. All the RLs met method reporting limits, indicating sensitivity requirements were met

except in those cases sample extracts were diluted due to high analyte concentration or matrix interference.

Based on our review of the field and laboratory QA/QC procedures, Kleinfelder concludes the following:

- The majority of the data meets method protocol accepted QA/QC requirements.
- Lancaster analyzed 100 percent of the requested analyses submitted by Kleinfelder.
- All of the samples were analyzed within holding time, resulting in the holding time completeness of 100 percent.
- Greater than 90% of the data are within acceptable limits.
- The levels of precision and accuracy measured on the basis of the LCS, MS/MSD, and surrogate recoveries are acceptable.
- The analytical data are deemed acceptable and usable for decision-making purposes.

References

- USEPA 1999. National Functional Guidelines for Organic Data Review. U.S. Environmental Protection Agency, Contract Laboratory Program, EPA-540/R-99-008, October 1999.
- USEPA 2004. National Functional Guidelines for Inorganic Data Review. U.S. Environmental Protection Agency, Contract Laboratory Program, EPA-540-R-04-004, October 2004.
- NYSDEC 2002. Draft DER-10 Technical Guidance for Site Investigation and Remediation. New York State Department of Environmental Conservation, December 2002.

Atlantic Testing Laboratory Report – Salmon River Sediment Sampling & Analysis



ATLANTIC TESTING LABORATORIES, Limited

Canton 6431 U.S. Highway 11 P.O. Box 29 Canton, NY 13617 315/386-4578 (T) 315/386-1012 (F)

September 24, 2003

Town of Fort Covington P.O. Box 489 Fort Covington, New York 12937

Attn:

Ms. Patricia Manchester

Town Superintendant

Re:

Salmon River Sediment Sampling and Analysis

Fort Covington Dam

Town of Fort Covington, New York ATL Report No. CTCD2256-01-09-03

Ladies/Gentlemen:

In accordance with the terms of our proposal (ATL File No. CD998-202-8-03; dated August 14, 2003), authorized by Ms. Patricia Manchester, Town Superintendent, sediment sampling upstream and downstream of the Fort Covington Dam was initiated by representatives of Atlantic Testing Laboratories, Limited (ATL) on August 7, 2003.

Background Information

It is ATL's understanding that *New York Rivers United (NYRU)* is considering purchase of the existing concrete dam on the Salmon River, located north of New York State Route 37 in the Village of Fort Covington, New York. The purpose of the sediment sampling and analysis event was to determine the presence of certain contaminants in composite sediment samples collected upstream and downstream of the referenced dam.

Sediment Sampling and Laboratory Analysis

Sediment samples were collected by representatives of ATL on August 7, 2003. The sediment samples were collected utilizing 1.75"-diameter. lexan (polycarbonate) core samplers that were manually advanced from the water/sediment interface until refusal was encountered. Upon refusal, the top of the lexan was sealed with a disposable cap and retrieved. Prior to the bottom of the lexan sampler breaking the surface/water interface, a disposable cap was placed on the bottom of the sampler to seal the sample and minimize the possibility of cross-contamination. Any water collected in the sampler was decanted, and the sediment sample was subsequently composited and containerized for laboratory analysis. Three locations were selected on both the upstream and downstream face of the dam to obtain composite samples of sediment deposited in the respective areas. A Core Location Map, identifying approximate sediment sample locations, is attached as Appendix I.

The laboratory results for sediment samples were compared to the NYSDEC "Technical Guidance For Screening Contaminated Sediments (TGSCS), Tables 1 and 2", dated January 1999; and "Technical and Operational Guidance Series (TOGS) 5.9.1 (Draft)", dated January 2003. The two documents were utilized to better characterize the referenced site with respect to the concentrations of target compounds identified within the samples. TGSCS was developed as a guideline to perform a preliminary assessment of the risk posed by contamination to human health and the environment. TOGS 5.1.9 was developed to provide guidance on the statutory and regulatory requirements of dredging and riparian management of dredge materials throughout New York State.

Correspondence with NYSDEC representative, Ms. Karen Woodfield, suggested utilizing a total organic carbon (TOC) content of 2.0%/kg sediment in calculations to protect benthic aquatic life from chronic toxicity, as defined in the NYSDEC TGSCS. However, TGSCS did not contain guidelines to protect benthic aquatic life from chronic toxicity for certain identified contaminants including benzo(a)pyrene, benzo(b)fluoranthene, benzo(k)fluoranthene, and chrysene. Therefore, these guidelines are derived using the sediment criteria to protect human health from the effects of bioaccumulation.

Table I below summarizes VOC, semi-VOC, and PCB analytical results for the sediment samples submitted to the laboratory.

Table I
Summary of Analytical Results: VOC, semi-VOC, and PCB

		Sediment Results (ppm)				
	B-1	B-3	B-5	NYSDEC TOGS 5.1.9	NYSDEC TGSCS	
VOCs	yannanansia.					
Benzene	0.138	ND	ND	0.59	0.56	
Ethylbenzene	0.162	ND	0.124		0.48	
MTBE	0.142	0.103	0.119			
Toluene	0.159	ND	0.107		0.98	
Xylene (m+p)	0.353	0.225	0.260			
Xylene (o)	0.186	0.120	0.141		1.84	
Total BTEX	0.998	0.345	0.632	< 0.96		
Semi-VOCs	-					
Anthracene	ND	ND	0.115		2.14	
Benzo(a)anthracene	0.521	0.0731	0.548		0.24	
Benzo(a)pyrene	0.546	ND	0.437		0.026	
Benzo(b)flouranthene	0.589	ND	0.291		0.026	
Benzo(k)flouranthene	0.692	ND	0.563		0.026	
Chrysene	0.560	0.0615	0.497		0.026	
Di-n-butyl phthalate	ND	ND	0.566			
Flouranthene	1,40	0.147 .	1.13	**	20.4	
Phenanthrene	0,668	ND	0.491		2.4	
Pyene	1.62	0.170	1.09		19.22	
Total PAH	6.596	0.4516	5.162	<4.0		
PCB						
Total PCB	ND	ND	ND	<0.1	0.028	

Notes:

All results are in ppm (mg/kg)

TOGS 5.1.9 = Technical and Operational Guidance Series

TGSCS = Technical Guidance for Screening Contaminated Sediments

ND = Not detected above respective method detection limit

PAH = Polycyclic Aromatic Hydrocarbons

BTX = Sum of Benzene, Toluene, and Xylenes (Defined in TOGS 5.1.9)

SVOC = Semi-Volatile Organic Compounds

VOC = Volatile Organic Compounds
Total PAH fom TOGS 5.1.9 Appendix E

Values in bold font exceed the respective guidance value

Low-level concentrations of compounds indicative of gasoline and and/or other petroleum-based products were identified in the sediment samples collected. Laboratory results indicate total polycyclic aromatic hydrocarbon (PAH) levels in borings B-1 and B-5 slightly above the guidance criteria defined in TOGS 5.1.9. Additionally, several semi-VOC are above the respective values to protect human health from the effects of bioaccumulation, as defined in the NYSDEC TGSCS. The criteria to protect human health from the effects of bioaccumulation are significantly less than the guidance criteria used to protect benthic aquatic life from chronic toxicity due to the tendency of these compounds to biomagnify in food chains. The remainder of contaminants listed in Table I may or may not pose appreciable risk to human beings. A specific sediment criterion derived from a human health-based water quality criterion must be compared to make that determination. PCB concentrations were below the respective method detection limit for all samples.

Sediment samples were also laboratory analyzed to determine metal concentrations. Table II below summarizes the results of the metal analyses on the sediment samples submitted to the laboratory.

Table II
Summary of Analytical Results: Metals

marin all for a second		Sediment Results (ppm)						
	B-1	B-3	B-5	NYSDEC TOGS 5.1.9	NYSDEC TGSCS LEL SEL			
METALS	ong and an							
Arsenic	1.30		0.749	14	6.0	33.0		
Barium	53.8	7.56	40.8					
Chromium	15.1	1.89	7.87		16.0	110.0		
Copper	15.5	0.831	3.75	<33.0	31.0	110.0		
Lead	23.3	2.44	5.21	<33.0	460.0	1100.0		
Nickel	6.18	1.55	5.13		16.0	50.0		
Zinc	71.2	13.9	29.6		120.0	270.0		
Iron	0.975%	0.876%	0.784%		2.0%	4.0%		

Notes:

All results are in ppm (mg/kg), except Iron

LEL = Lowest Effect Level

SEL = Severe Effect Level

Values in bold font exceed the respective guidance value

ND = Not detected above respective method detection limit

Sediment samples collected from all locations were below the respective metals guidance values listed in TOGS 5.1.9, and lowest effect levels (LELs) listed in the TGSCS. The complete laboratory reports and associated sample custody documentation are attached as Appendix II.

Conclusions and Recommendations

Based on the laboratory reports, it appears that relatively low-level petroleum contamination exists in the sediment of the Salmon River near the dam located in the Town of Fort Covington. It is recommended that the NYSDEC be contacted to review the laboratory results prior to the initiation of additional work that may disturb the sediment beneath the Salmon River. Additional water- and land-based investigations would be necessary to determine the potential source, and the vertical and horizontal limits of the impacted area. The contaminants identified in the sampling and analysis event may undergo microbial degradation and/or natural attenuation over a long period of time, if a continuing source does not contribute to the identified contamination.

Please contact our office should you have any questions, or if we may be of further assistance.


Respectfully submitted,
ATLANTIC TESTING LABORATORIES, Limited

Bradley J. Idzik Project Engineer

BJI/JLR/MBR/bji

Attachments

I. Core Location Map



II. Laboratory Results and Associated Sample Custody Documentation



Environmental LABORATORY SERVICES

7280 Caswell Street, Hancock Air Park, North Syracuse, NY 13212 (315) 458-8033, FAX (315) 458-0249, (800) 842-4667

Certified in:

- Connecticut
- Delaware
- Maryland
- Massachusetts
- New
- Hampshire New Jersey
- New York
- Pennsylvania • Rhode Island

ATL CANTON P.O. Box 29

PROJECT #: RECEIVED:

205843 08/08/2003

Canton, NY 13617 ATTN: Brad Idzik

Site Address:

VILLAGE OF FORT COVINGTON

SEDIMENT SAMPLING

CLIENT JOB NUMBER: CD2256

IF^T PERFORMED) .	RESULTS	UNITS	DATE/TIME PERFORMED	METHOD NUMBER	PERFORMED BY
 Mr∟E #: 350543	CLIENT SAMPLE ID:	B1			DATE SAMPLED:	08/07/03
Semi-Volatile - 827		0.400	MOWO DDVWT	00/40/00	ED + 0370C	MMA
1,2,4-trichlo		<0.429	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
1,2-dichloro		< 0.429	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
1,2-dipheny		<0.429	MG/KG DRY WT.	08/12/03	EPA 8270C	1411417 (
	henylhydrazine breaks down i.		ri. II is anaiyzea ana rej MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
1,3-dichloro		<0.429				MMA
1,4-dichloro		< 0.429	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
2,4-dinitroto		< 0.429	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
2,6-dinitroto		< 0.429	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
2-chloronap		<0.0857	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
2-methylna		<0.0857	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
2-nitroanilin		<0.429	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
3,3`-dichlor		<1.72	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
3-nitroanilin		< 0.429	MG/KG DRY WT.		EPA 8270C	MMA
	enyi phenyi ether	< 0.429	MG/KG DRY WT.		EPA 8270C	MMA
4-chloroani		< 0.429	MG/KG DRY WT.		EPA 8270C	MMA
·	enyl phenyl ether	<0.429	MG/KG DRY WT.		EPA 8270C	MMA
4-nitroanilir		< 0.429	MG/KG DRY WT.		EPA 8270C	MMA
acenaphthe		< 0.0857	MG/KG DRY WT.		EPA 8270C	MMA
acenaphthy	ylene	<0.0857	MG/KG DRY WT.		EPA 8270C	MMA
aniline		< 0.429	MG/KG DRY WT.		EPA 8270C	MMA
anthracene	}	<0.0857	MG/KG DRY WT.		EPA 8270C	MMA
benzo(a)ar	nthracene	0.521	MG/KG DRY WT.		EPA 8270C	
benzo(a)py	rene	0.546	MG/KG DRY WT.		EPA 8270C	MMA
benzo(b)flu	ıoranthene	0.589	MG/KG DRY WT.		EPA 8270C	MMA
benzo(g,h,	i)perylene	<0.0857	MG/KG DRY WT.		EPA 8270C	MMA
benzo(k)flu	oranthene	0.692	MG/KG DRY WT.		EPA 8270C	MMA
benzyl alco	ohol	<0.429	MG/KG DRY WT.		EPA 8270C	MMA
bis(2-chlor	oethoxy)methane	< 0.429	MG/KG DRY WT		EPA 8270C	MMA
bis(2-chlor	oethyl) ether	<0.429	MG/KG DRY WT		EPA 8270C	MMA
bis(2-ethyl	hexyl) phthalate	< 0.429	MG/KG DRY WT		EPA-8270C	MMA
butyl benz	yl phthalate	< 0.429	MG/KG DRY WT	. 08/12/03	EPA 8270C	MMA

ATL CANTON P.O. Box 29

> Canton, NY 13617 ATTN: Brad Idzik

PROJECT #: RECEIVED:

205843 08/08/2003

Site Address:

VILLAGE OF FORT COVINGTON

SEDIMENT SAMPLING

CLIENT JOB NUMBER: CD2256

1 T PERFORMED	RESULTS	UNITS	DATE/TIME PERFORMED	METHOD NUMBER	PERFORMED BY
MPLE #: 350543 CLIENT SAMPLE ID:	B1			DATE SAMPLED:	08/07/03
Semi-Volatile - 8270 B/N					
chrysene	0.560	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
dibenz(a,h)anthracene	<0.0857	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
dibenzofuran	<0.429	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
diethyl phthalate	<0.429	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
dimethyl phthalate	<0.429	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
di-n-butyl phthalate	<0.429	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
di-n-octyl phthalate	< 0.429	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
fluoranthene	1.40	MG/KG DRY WT.		EPA 8270C	MMA
fluorene	< 0.0857	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
hexachlorobenzene	< 0.429	MG/KG DRY WT.		EPA 8270C	MMA
hexachlorobutadiene	< 0.429	MG/KG DRY WT.		EPA 8270C	MMA
hexachlorocyclopentadiene	<0.429	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
hexachloroethane	< 0.429	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
indeno(1,2,3-cd)pyrene	<0.0857	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
isophorone	< 0.429	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
naphthalene	< 0.0857	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
nitrobenzene	< 0.429	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
n-nitrosodimethylamine	< 0.429	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
n-nitrosodiphenylamine	< 0.429	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
n-nitrosodipropylamine	< 0.429	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
phenanthrene	0.668	MG/KG DRY WT.	. 08/12/03	EPA 8270C	MMA
pyrene	1.62	MG/KG DRY WT	. 08/12/03	EPA 8270C	MMA
pyridine	< 0.429	MG/KG DRY WT	. 08/12/03	EPA 8270C	MMA
Solid Soxhlet Extraction			08/11/03	EPA 3540C	MKE
SULIDS, TOTAL	58	PERCENT	08/11/03	SM18 2540B	CSA
Volatile - TCL VOLATILES					
1,1,1-trichloroethane	< 0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
1,1,2,2-tetrachloroethane	< 0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
1,1,2-trichloro-1,2,2-trifluoroeth	< 0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
1,1,2-trichloroethane	< 0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
1,1-dichloroethane	< 0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
1,1-dichloroethene	< 0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
1,2,3-trichlorobenzene	< 0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
1,2,4-trichlorobenzene	< 0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
1,2-dibromo-3-chloropropane	<0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
1,2-dibromoethane	<0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
1,2-dichlorobenzene	< 0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
1,2-dichloroethane	< 0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
1,2-dichloropropane	<0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA



ATL CANTON ⊇.O. Box 29

> Canton, NY 13617 ATTN: Brad Idzik

PROJECT #: RECEIVED:

205843 08/08/2003

Site Address:

VILLAGE OF FORT COVINGTON

SEDIMENT SAMPLING

CLIENT JOB NUMBER: CD2256

E PERFORMED	RESULTS	UNITS	DATE/TIME PERFORMED	METHOD NUMBER	PERFORMED BY
1PLE #: 350543 CLIENT SAMPLE ID:	B1			DATE SAMPLED:	08/07/03
'olatile - TCL VOLATILES					
1,3-dichlorobenzene	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,4-dichlorobenzene	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
2-butanone	< 0.500	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
2-hexanone	<0.500	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
4-methyl-2-pentanone	<0.500	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
acetone	< 0.500	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
benzene	0.138	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
bromochloromethane	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
bromodichloromethane	< 0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
bromoform	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
bromomethane	<0.500	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
carbon disulfide	< 0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
carbon tetrachloride	< 0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
chlorobenzene	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
chloroethane	< 0.500	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
chloroform	< 0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
chloromethane	< 0.500	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
cis-1,2-dichloroethene	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
cis-1,3-dichloropropene	< 0.0862	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
cyclohexane	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
dibromochloromethane	< 0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
dichlorodifluoromethane	< 0.500	MG/KG DRY WT.	. 08/11/03	EPA 8260B	MMA
ethylbenzene	0.162	MG/KG DRY WT.	. 08/11/03	EPA 8260B	MMA
isopropyl benzene (cumene)	< 0.100	MG/KG DRY WT.	. 08/11/03	EPA 8260B	MMA
methyl acetate	<0.100	MG/KG DRY WT.	. 08/11/03	EPA 8260B	MMA
methylcyclohexane	<0.100	MG/KG DRY WT.		EPA 8260B	MMA
methylene chloride	<0.100	MG/KG DRY WT.	. 08/11/03	EPA 8260B	MMA
mtbe	0.142	MG/KG DRY WT.	. 08/11/03	EPA 8260B	MMA
styrene	<0.100	MG/KG DRY WT.	. 08/11/03	EPA 8260B	MMA
tetrachloroethene	<0.100	MG/KG DRY WT.	. 08/11/03	EPA 8260B	MMA
toluene	0.159	MG/KG DRY WT.	. 08/11/03	EPA 8260B	MMA
trans-1,2-dichloroethene	<0.100	MG/KG DRY WT.	. 08/11/03	EPA 8260B	MMA
trans-1,3-dichloropropene	< 0.0862	MG/KG DRY WT.	. 08/11/03	EPA 8260B	MMA
trichloroethene	<0.100	MG/KG DRY WT.		EPA 8260B	MMA
trichlorofluoromethane	<0.100	MG/KG DRY WT.		EPA 8260B	MMA
vinyl chloride	<0.200	MG/KG DRY WT.		EPA 8260B	MMA
xylene, m+p	0.353	MG/KG DRY WT		EPA 8260B	MMA
xylene, o	0.186			EPA 8260B	MMA
Soil Extraction for Volatiles			08/08/03	EPA 5035	MNE



ATL CANTON 3.0. Box 29

> Canton, NY 13617 ATTN: Brad Idzik

PROJECT #:

205843

RECEIVED:

08/08/2003

Site Address:

VILLAGE OF FORT COVINGTON

SEDIMENT SAMPLING

PERFORMED	RESULTS	UNITS	DATE/TIME PERFORMED	METHOD NUMBER	PERFORMED BY
PLE #: 350544 CLIENT SAMPLE ID:	В3			DATE SAMPLED:	08/07/03
r.·-Volatile - 8270 B/N				·	
1,2,4-trichlorobenzene	< 0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
1,2-dichlorobenzene	< 0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
1,2-diphenylhydrazine	< 0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	. MMA
1,2-Diphenylhydrazine breaks down	in the injection po				
1,3-dichlorobenzene	< 0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
1,4-dichlorobenzene	< 0.304	MG/KG DRY WT.		EPA 8270C	MMA
2,4-dinitrotoluene	< 0.304	MG/KG DRY WT.		EPA 8270C	MMA
2,6-dinitrotoluene	< 0.304	MG/KG DRY WT.		EPA 8270C	MMA
2-chloronaphthalene	<0.0609	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
2-methylnaphthalene	<0.0609	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
2-nitroaniline	< 0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
3,3'-dichlorobenzidine	<1.22	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
3-nitroaniline	< 0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
4-bromophenyl phenyl ether	< 0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	AMM
4-chloroaniline	< 0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
4-chlorophenyl phenyl ether	< 0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
4-nitroaniline	< 0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
acenaphthene	< 0.0609	MG/KG DRY WT.	. 08/12/03	EPA 8270C	MMA
acenaphthylene	< 0.0609	MG/KG DRY WT	. 08/12/03	EPA 8270C	MMA
aniline	< 0.304	MG/KG DRY WT	. 08/12/03	EPA 8270C	MMA
anthracene	< 0.0609	MG/KG DRY WT	. 08/12/03	EPA 8270C	MMA
benzo(a)anthracene	0.0731	MG/KG DRY WT	. 08/12/03	EPA 8270C	MMA
benzo(a)pyrene	< 0.0609	MG/KG DRY WT	. 08/12/03	EPA 8270C	MMA
benzo(b)fluoranthene	< 0.0609	MG/KG DRY WT	. 08/12/03	EPA 8270C	MMA
benzo(g,h,i)perylene	< 0.0609	MG/KG DRY WT	. 08/12/03	EPA 8270C	MMA
benzo(k)fluoranthene	0.0737	MG/KG DRY WT		EPA 8270C	MMA
benzyl alcohol	< 0.304	MG/KG DRY WT		EPA 8270C	MMA
bis(2-chloroethoxy)methane	<0.304	MG/KG DRY WT		EPA 8270C	MMA
bis(2-chloroethyl) ether	<0.304	MG/KG DRY WT		EPA 8270C	MMA
bis(2-ethylhexyl) phthalate	<0.304	MG/KG DRY WT		EPA 8270C	MMA
butyl benzyl phthalate	<0.304	MG/KG DRY WT		EPA 8270C	MMA
•	0.0615	MG/KG DRY WT		EPA 8270C	MMA
chrysene	<0.0609	MG/KG DRY WT		EPA 8270C	MMA
dibenz(a,h)anthracene	<0.0003			EPA 8270C	MMA
dibenzofuran	<0.304	MG/KG DRY WT		EPA 8270C	MMA
diethyl phthalate	<0.304	MG/KG DRY WT		EPA 8270C	MMA
dimethyl phthalate	<0.304	MG/KG DRY WT		EPA 8270C	MMA
di-n-butyl phthalate	<0.304			EPA 8270C	MMA
di-n-octyl phthalate	0.304	MG/KG DRY WT		EPA 8270C	MMA
fluoranthene				EPA 8270C	MMA
fluorene	<0.0609	MG/KG DRY WT	. 00/12/03	LI A 02/0C	11417



Canton, NY 13617 ATTN: Brad Idzik PROJECT #: RECEIVED:

205843 08/08/2003

Site Address:

VILLAGE OF FORT COVINGTON

SEDIMENT SAMPLING

T PERFORMED	RESULTS	UNITS	DATE/TIME PERFORMED	METHOD NUMBER	PERFORMED BY
IPLE #: 350544 CLIENT SAMPLE ID:	В3			DATE SAMPLED:	08/07/03
lemi-Volatile - 8270 B/N					
hexachlorobenzene	<0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
hexachlorobutadiene	< 0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
hexachlorocyclopentadiene	< 0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
hexachloroethane	<0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
indeno(1,2,3-cd)pyrene	< 0.0609	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
isophorone	< 0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
naphthalene	< 0.0609	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
nitrobenzene	< 0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
n-nitrosodimethylamine	< 0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
n-nitrosodiphenylamine	< 0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA.
n-nitrosodipropylamine	< 0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
phenanthrene	< 0.0609	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
pyrene	0.170	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
pyridine	< 0.304	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
Solid Soxhlet Extraction			08/11/03	EPA 3540C	MKE
SOLIDS, TOTAL	82	PERCENT	08/11/03	SM18 2540B	CSA
V atile - TCL VOLATILES					
1,1,1-trichloroethane	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,1,2,2-tetrachloroethane	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,1,2-trichloro-1,2,2-trifluoroeth	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,1,2-trichloroethane	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,1-dichloroethane	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,1-dichloroethene	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,2,3-trichlorobenzene	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,2,4-trichlorobenzene	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,2-dibromo-3-chloropropane	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,2-dibromoethane	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,2-dichlorobenzene	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,2-dichloroethane	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,2-dichloropropane	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,3-dichlorobenzene	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,4-dichlorobenzene	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
2-butanone	<0.500	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
2-hexanone	<0.500	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA.
4-methyl-2-pentanone	< 0.500	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
acetone	<0.500	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
benzene	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
bromochloromethane	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
bromodichloromethane	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
promodicino ometrane	-0.100	MONTO DIVI VVI.	00/11/03	LIM 0200D	IVIIVIA



Canton, NY 13617 JTN: Brad Idzik

PROJECT#:

205843

RECEIVED:

08/08/2003

Site Address:

VILLAGE OF FORT COVINGTON

SEDIMENT SAMPLING

# PERFORMED	RESULTS	UNITS	DATE/TIME PERFORMED	METHOD NUMBER	PERFORMED BY
PLE #: 350544 CLIENT SAMPLE ID:	В3			DATE SAMPLED:	08/07/03
o' ile - TCL VOLATILES	0.400	MOWO DOWNE	00/44/00	EPA 8260B	MMA
bromoform	<0.100	MG/KG DRY WT.	08/11/03	_ : :	MMA
bromomethane	<0.500	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
carbon disulfide	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
carbon tetrachloride	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
chlorobenzene	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	
chloroethane	<0.500	MG/KG DRY WT.		EPA 8260B	MMA
chloroform	<0.100	MG/KG DRY WT.		EPA 8260B	MMA
chloromethane	<0.500	MG/KG DRY WT.		EPA 8260B	MMA
cis-1,2-dichloroethene	<0.100	MG/KG DRY WT.		EPA 8260B	MMA
cis-1,3-dichloropropene	<0.0610	MG/KG DRY WT.		EPA 8260B	MMA
cyclohexane	<0.100	MG/KG DRY WT.		EPA 8260B	MMA
dibromochloromethane	<0.100	MG/KG DRY WT.		EPA 8260B	MMA
dichlorodifluoromethane	< 0.500	MG/KG DRY WT.		EPA 8260B	MMA
ethylbenzene	<0.100	MG/KG DRY WT.		EPA 8260B	MMA
isopropyl benzene (cumene)	<0.100	MG/KG DRY WT.		EPA 8260B	MMA
methyl acetate	<0.100	MG/KG DRY WT.		EPA 8260B	MMA
methylcyclohexane	<0.100	MG/KG DRY WT.	. 08/11/03	EPA 8260B	MMA
methylene chloride	<0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
mtbe	0.103	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
styrene	< 0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
tetrachloroethene	< 0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
toluene	<0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
trans-1,2-dichloroethene	<0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
trans-1,3-dichloropropene	< 0.0610	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
trichloroethene	<0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
trichlorofluoromethane	< 0.100	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
vinyl chloride	<0.200	MG/KG DRY WT	. 08/11/03	EPA 8260B	MMA
xylene, m+p	0.225			EPA 8260B	MMA
xylene, o	0.120			EPA 8260B	MMA
Soil Extraction for Volatiles	3.120		08/08/03	EPA 5035	MNE



ATL CANTON 2.0. Box 29

> Canton, NY 13617 ATTN: Brad Idzik

PROJECT #:

205843

RECEIVED:

08/08/2003

Site Address:

VILLAGE OF FORT COVINGTON

SEDIMENT SAMPLING

E PERFORMED	RESULTS	UNITS	DATE/TIME PERFORMED	METHOD NUMBER	PERFORMED BY
IPLE #: 350545 CLIENT SAMPLE ID:	B5			DATE SAMPLED:	08/07/03
emi-Volatile - 8270 B/N					
1,2,4-trichlorobenzene	<0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
1,2-dichlorobenzene	<0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
1,2-diphenylhydrazine	<0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
1,2-Diphenylhydrazine breaks down i	n the injection po				
1,3-dichlorobenzene	<0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
1,4-dichlorobenzene	<0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
2,4-dinitrotoluene	< 0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
2,6-dinitrotoluene	< 0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
2-chloronaphthalene	< 0.0703	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
2-methylnaphthalene	< 0.0703	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
2-nitroaniline	< 0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
3,3'-dichlorobenzidine	<1.41	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
3-nitroaniline	< 0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
4-bromopheny! pheny! ether	< 0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
4-chloroaniline	< 0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
4-chlorophenyl phenyl ether	< 0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
4-nitroaniline	< 0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
acenaphthene	< 0.0703	MG/KG DRY WT.	08/12/03	EPA 8270C	· MMA
acenaphthylene	< 0.0703	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
aniline	< 0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
anthracene	0.115	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
benzo(a)anthracene	0.548	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
benzo(a)pyrene	0.437	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
benzo(b)fluoranthene	0.291	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
benzo(g,h,i)perylene	< 0.0703	MG/KG DRY WT.	. 08/12/03	EPA 8270C	MMA
benzo(k)fluoranthene	0.563	MG/KG DRY WT.		EPA 8270C	MMA
benzyl alcohol	< 0.352	MG/KG DRY WT.	. 08/12/03	EPA 8270C	MMA
bis(2-chloroethoxy)methane	<0.352	MG/KG DRY WT.		EPA 8270C	MMA
bis(2-chloroethyl) ether	<0.352	MG/KG DRY WT.		EPA 8270C	MMA
bis(2-ethylhexyl) phthalate	< 0.352	MG/KG DRY WT.	. 08/12/03	EPA 8270C	MMA
butyl benzyl phthalate	< 0.352	MG/KG DRY WT		EPA 8270C	MMA
chrysene	0.497	MG/KG DRY WT		EPA 8270C	MMA
dibenz(a,h)anthracene	<0.0703	MG/KG DRY WT		EPA 8270C	MMA
dibenzofuran	<0.352	MG/KG DRY WT		EPA 8270C	MMA
diethyl phthalate	<0.352	MG/KG DRY WT		EPA 8270C	MMA
dimethyl phthalate	<0.352			EPA 8270C	MMA
	0.566			EPA 8270C	MMA
di-n-butyl phthalate	<0.352			EPA 8270C	MMA
di-n-octyl phthalate	1.13			EPA 8270C	MMA
fluoranthene fluorene	<0.0703			EPA 8270C	MMA



> Canton, NY 13617 ATTN: Brad Idzik

PROJECT #:

205843

RECEIVED:

08/08/2003

Site Address:

VILLAGE OF FORT COVINGTON

SEDIMENT SAMPLING

T PERFORMED	RESULTS	UNITS	DATE/TIME PERFORMED	METHOD NUMBER	PERFORMED BY
PLE #: 350545 CLIENT SAMPLE ID:	B5			DATE SAMPLED:	08/07/03
mi-Volatile - 8270 B/N					
hexachlorobenzene	< 0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
hexachlorobutadiene	<0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
hexachlorocyclopentadiene	<0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
hexachloroethane	<0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
indeno(1,2,3-cd)pyrene	< 0.0703	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
isophorone	<0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
naphthalene	< 0.0703	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
nitrobenzene	< 0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
n-nitrosodimethylamine	< 0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
n-nitrosodiphenylamine	< 0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
n-nitrosodipropylamine	< 0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
phenanthrene	0.491	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
pyrene	1.09	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
pyridine	< 0.352	MG/KG DRY WT.	08/12/03	EPA 8270C	MMA
Solid Soxhlet Extraction			08/11/03	EPA 3540C	MKE
OLIDS, TOTAL	70	PERCENT	08/11/03	SM18 2540B	CSA
atile - TCL VOLATILES					
1,1,1-trichloroethane	< 0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,1,2,2-tetrachloroethane	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,1,2-trichloro-1,2,2-trifluoroeth	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,1,2-trichloroethane	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,1-dichloroethane	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,1-dichloroethene	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,2,3-trichlorobenzene	< 0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,2,4-trichlorobenzene	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,2-dibromo-3-chloropropane	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,2-dibromoethane	< 0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,2-dichlorobenzene	< 0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,2-dichloroethane	< 0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,2-dichloropropane	< 0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,3-dichlorobenzene	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
1,4-dichlorobenzene	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
2-butanone	< 0.500	MG/KG DRY WT.		EPA 8260B	MMA
2-hexanone	<0.500	MG/KG DRY WT.		EPA 8260B	MMA
4-methyl-2-pentanone	< 0.500	MG/KG DRY WT.		EPA 8260B	MMA
acetone	< 0.500	MG/KG DRY WT.		EPA 8260B	MMA
benzene	<0.100	MG/KG DRY WT.		EPA 8260B	MMA
bromochloromethane	<0.100	MG/KG DRY WT.		EPA 8260B	MMA
bromodichloromethane	< 0.100	MG/KG DRY WT.		EPA 8260B	MMA



> Canton, NY 13617 ATTN: Brad Idzik

PROJECT #:

205843

RECEIVED:

08/08/2003

Site Address:

VILLAGE OF FORT COVINGTON

SEDIMENT SAMPLING

T PERFORMED		RESULTS UNITS		DATE/TIME METHOD PERFORMED NUMBER		PERFORMED BY
#PLE #: 350545	CLIENT SAMPLE ID:	B5			DATE SAMPLED:	08/07/03
/olatile - TCL VOL	ATILES					
bromoform	•	<0.100	MG/KG DRY WT.		EPA 8260B	MMA
bromometha		<0.500	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
carbon disulf	-	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
carbon tetrad		<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
chlorobenze		<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
chloroethane)	<0.500	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
chloroform		<0.100	MG/KG DRY WT:	08/11/03	EPA 8260B	MMA
chlorometha	· · -	<0.500	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
cis-1,2-dichle		<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
cis-1,3-dichle		<0.0714	MG/KG DRY WT.		EPA 8260B	MMA
cyclohexane		<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
dibromochlo		<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
dichlorodiflu	oromethane	<0.500	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
ethylbenzen		0.124	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
isopropyl be	nzene (cumene)	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
methyl aceta		< 0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
methylcyclol	hexane	< 0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
methylene c	hloride	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
mtbe		0.119	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
styrene		<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
tetrachloroe	thene	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
toluene		0.107	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
trans-1,2-did	chloroethene	< 0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
trans-1,3-did	chloropropene	<0.0714	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
trichloroethe	ene	< 0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
trichlorofluo	romethane	<0.100	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
vinyl chlorid	е	<0.200	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
xylene, m+p	•	0.260	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
xylene, o		0.141	MG/KG DRY WT.	08/11/03	EPA 8260B	MMA
Soil Extracti	on for Volatiles			08/08/03	EPA 5035	MNE



> Canton, NY 13617 ATTN: Brad Idzik

PROJECT #:

205843

RECEIVED:

08/08/2003

Site Address:

VILLAGE OF FORT COVINGTON

SEDIMENT SAMPLING

CLIENT JOB NUMBER:

CD2256

DATE/TIME

METHOD

PERFORMED

BY

T TPERFORMED

RESULTS UNITS

PERFORMED

NUMBER

Wendy J. Omberger Laboratory Director

08/12/2003 Print Date

All tests performed under NYS ELAP Laboratory Certification # 11375 unless otherwise stated. Report relates only to the samples as received by the laboratory and shall not be reproduced except in full, without written approval from Environmental Laboratory Services.

strib

18/7/03 Samplers Signature: Samplers Name: 8/7/03/1340 Signature: Signature: 8/7/03/11/0 CD2256 Albany 12 Arrowhead Lane Cohoes, NY 12047 518/783-9073 (T) 518/783-6987 (F) Name: Project Contact: Project No. Project Name: 0/10 Tjme AVEXAGE Samples Relinquished By: Sample Location B 2 80 BRADLEY ITTAGE OF FORT LOW-GTON Binghamton 406 North Street Endicott, NY 13670 607/757-9326 (T) 607/757-9252 (F) EDIMENT Client Name 2 Touch * Trus Canton P.O. Box 29 P.O. NY 13617 Canton, NY 13617 315/386-4578 (T) 315/386-1012 (F) SAMPLIAG Date Date: Date: O NYSDOH Code O NYSDEC fr Common Tthaca 786 Cascadilla Street Ithaca, NY 14850 607/272-1723 (T) 607/272-1723 (F) Project Location %Neme: Name: Signature: さ六十,03 10:25 Containers CLP N 7 2 Plattsburgh 1080 Military Trp! . Plattsburgh, NY 12001 . 518/563-5878 (T) 518/562-1321 (F 8260 Received for Name:
Laboratory Signature TCL Samples Received By: EPA 8270 BW Poughkeepsle 1601 Route 376 Wappingers Falls, NY 12590 645/463-1126 (T) 845/426-1127 (F) Parameters 2. Cherioval Date Date. (Kellowich Syracuse 5866 State Rt. 31 Cicerc, NY 13039 315/699-5281 (T) 315/699-3374 (F) Sample Type Code Key: a 0 G Description QA/QC Grab Composite Date: Time: Send Report To: 名の記 Dates Regulred: Fax Results: SHOOTS MARKS 20 SO СW ₹ Utica 301 St. Andrews St. Utica, NY 13502 315/735-3309 (T) 315/735-0742 (F) Report Distribution SOBR Wastewater Drinking Water Soil 2 Groundwater Matrix Sludge 0908 TAT JABAH Shipment Rec'd Intact? $\bar{\omega}$ Laboratory Remarks DAYES DES YES Watertown
P.O. Box 91
Fells Adils, NY 13636
315/773-5390 (T)
315/773-5334-71 Field Notes からして 0 0 Ö 8 Custody Seal: X= intact <u>_</u>

ATLANTIC TESTING LARORATORIES, Limited

Nº 00302

ENVIRONMENTAL CHAIN OF CUSTODY

Think Quality



Environmental

LABORATORY SERVICES

7280 Caswell Street, Hancock Air Park, North Syracuse, NY 13212 (315) 458-8033, FAX (315) 458-0249, (800) 842-4667

Certified in: • Connecticut • Delaware Maryland • Massachusetts • New Hampshire • New Jersey New York Pennsylvania Rhode Island

ATL CANTON P.O. Box 29

PROJECT #:

205844

Canton, NY 13617

RECEIVED:

08/08/2003

ATTN: Brad Idzik

Site Address:

VILLAGE OF FORT COVINGTON

SEDIMENT SAMPLING

CLIENT JOB NUMBER:

E T PERFORME	D ·	RESULTS	UNITS	DATE/TIME PERFORMED	METHOD NUMBER	PERFORMED BY
APLE #: 350546 CP/MS	CLIENT SAMPLEID:	B1			DATE SAMPLED:	08/07/03
antimony		< 0.943	MG/KG DRY WT.	08/18/03	EPA 6020	NSH
arsenic		1.30	MG/KG DRY WT.		EPA 6020	NSH
barium		53.8	MG/KG DRY WT.		EPA 6020	NSH
beryllium		< 0.943	MG/KG DRY WT.		EPA 6020	NSH
cadmium		< 0.943	MG/KG DRY WT.		EPA 6020	NSH
chromium		15.1	MG/KG DRY WT.		EPA 6020	NSH
copper		15.5	MG/KG DRY WT.		EPA 6020	NSH
lead		23.3	MG/KG DRY WT.		EPA 6020	NSH
nickel		6.18	MG/KG DRY WT.		EPA 6020	NSH
selenium		< 0.943	MG/KG DRY WT.		EPA 6020	NSH
silver		< 0.943	MG/KG DRY WT.		EPA 6020	NSH
thallium		< 0.943	MG/KG DRY WT.		EPA 6020	NSH
zinc		71.2	MG/KG DRY WT.	08/18/03	EPA 6020	NSH
Metals Dige	estion			08/15/03	EPA 3050B	BDR
C					, =:,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	, 5511
iron		9750	MG/KG DRY WT.	08/15/03	EPA 6010	NSH
Metals Dige	estion			08/14/03	EPA 3050B	BDR
⊿ ⟨CURY		0.092	MG/KG DRY WT.	08/20/03	EPA 7471A	NSH
operation and the second						
Jemi-Volatile - PC		0.004				
aroclor 101	=	<0.931	MG/KG DRY WT.	08/15/03	EPA 8082	MNE
aroclor 122		<0.931	MG/KG DRY WT.	08/15/03	EPA 8082	MNE
aroclor 123		<0.931	MG/KG DRY WT.	08/15/03	EPA 8082	MNE
aroclor 124		<0.931	MG/KG DRY WT.	08/15/03	EPA 8082	MNE
aroclor 124		< 0.931	MG/KG DRY WT.	08/15/03	EPA 8082	MNE
aroclor 125		< 0.931	MG/KG DRY WT.	08/15/03	EPA 8082	MNE
aroclor 126		<0.931	MG/KG DRY WT.	08/15/03	EPA 8082	MNE
-	et Extraction			08/12/03	EPA 3540C	MKE
C_IDS, TOTAL		53	PERCENT	08/11/03	SM18 2540B	CSA

> Canton, NY 13617 ATTN: Brad Idzik

PROJECT #: RECEIVED:

205844 08/08/2003

Site Address:

VILLAGE OF FORT COVINGTON

SEDIMENT SAMPLING

CLIENT JOB NUMBER:

T PERFORMED	RESULTS	UNITS	DATE/TIME PERFORMED	METHOD NUMBER	PERFORMED BY
MPLE#: 350547 CLIENT SAMPLEID: CP/MS	В3			DATE SAMPLED:	08/07/03
antimony	<0.610	MG/KG DRY WT.	08/18/03	PD / 6000	
arsenic	< 0.610	MG/KG DRY WT.		EPA 6020	NSH
barium	7.56	MG/KG DRY WT.		EPA 6020	NSH
beryllium	< 0.610	MG/KG DRY WT.		EPA 6020	NSH
cadmium	<0.610			EPA 6020	NSH
chromium		MG/KG DRY WT.		EPA 6020	NSH
	1.89	MG/KG DRY WT.	· · · · · -	EPA 6020	NSH
copper lead	0.831	MG/KG DRY WT.		EPA 6020	NSH
nickel	2.44	MG/KG DRY WT.		EPA 6020	NSH
	1.55	MG/KG DRY WT.	08/18/03	EPA 6020	NSH
selenium	<0.610	MG/KG DRY WT.		EPA 6020	NSH
silver	< 0.610	MG/KG DRY WT.		EPA 6020	NSH
thallium	< 0.610	MG/KG DRY WT.	08/18/03	EPA 6020	NSH
zinc	13.9	MG/KG DRY WT.	08/18/03	EPA 6020	NSH
Metals Digestion			08/15/03	EPA 3050B	BDR
iron	8760	MG/KG DRY WT.	08/15/03	EPA 6010	NSH
Metals Digestion			08/14/03	EPA 3050B	BDR
4 RCURY	<0.050	MG/KG DRY WT.	08/20/03	EPA 7471A	NSH
Semi-Volatile - PCB'S					
aroclor 1016	< 0.0621	MG/KG DRY WT.	08/14/03	EPA 8082	MNE
aroclor 1221	< 0.0621	MG/KG DRY WT.	08/14/03	EPA 8082	MNE
aroclor 1232	< 0.0621	MG/KG DRY WT.	08/14/03	EPA 8082	MNE
aroclor 1242	< 0.0621	MG/KG DRY WT.	08/14/03	EPA 8082	MNE
aroclor 1248	< 0.0621	MG/KG DRY WT.	08/14/03	EPA 8082	MNE
arocior 1254	< 0.0621	MG/KG DRY WT.	08/14/03	EPA 8082	MNE
aroclor 1260	<0.0621	MG/KG DRY WT.	08/14/03	EPA 8082	
Solid Soxhlet Extraction			08/12/03	EPA 3540C	MNE
SULIDS, TOTAL	80	DEDGENT			MKE
JODIDS, TOTAL	80	PERCENT	08/11/03	SM18 2540B	CSA



TT T PERFORMED

CD5526

RESULTS UNITS

08/08/2003 **KECEINED:** 202844 PROJECT#:

Site Address:

BMIT/BTAC

ATTN: Brad Idzik Canton, NY 13617

CLIENT JOB NUMBER:

SEDIMENT SAMPLING VILLAGE OF FORT COVINGTON

METHOD

PERFORMED

AB	илмвек	PERFORMED	STINU	RESULTS	UZMYOZNEJ
£0/70/80	DATE SAMPLED:			98	ICD/M2 WPLE#: 350548 CLIENT SAMPLEID:
HSN	Eby 6020	60/81/80	MG/KG DRY WT.	949.0>	antimony
HSN	EPA 6020	60/81/80	MG/KG DRY WT.	6 7 .0	arsenic
HSN	Eby 6020	60/81/80	MG/KG DRY WT.	8.04	pannm
HSN	EPA 6020	60/18/03	MG/KG DKY WT.	979.0>	peıyllium
HSN	Eb¥ 6020	60/81/80	MG/KG DRY WT.	949.0>	cadmium
HSN	Eb¥ 6020	60/81/80	MG/KG DRY WT.	78.T	срготит
HSN	Eb¥ 6050	50/81/80	MG/KG DRY WT.	3,75	cobber
HSN	Eby 6020	60/81/80	MG/KG DRY WT.	12.21	lead
HSN	EPA 6020	£0/81\80	MG/KG DRY WT.	51.3	nickel
HSN	Eb¥ 6020	60/81/80	MG/KG DRY WT.	949.0>	wnjuəjəs
HSN	EPA 6020	50/81/80	MG/KG DRY WT.	949.0>	silver
HSN	Eb¥ 6050	60/81/80	MG/KG DBY WT.	949.0>	muilled!
HSN	Eb∀ 6020	60/81/80	MG/KG DRY WT.	9.62	yetele Digeories
врк	Eby 3020B	08/12/03			Metals Digestion IC
11014	0,007,444	00131100	MG/KG DRY WT.	0487	noni
HSN	EbV 3000B	20/71/80 20/12/80	TAN IND ONOM	0+0.4	noisegials Digestion
BDK NSH	Eby 1471A Epa 3050B	08\74\03 08\50\03	MG/KG DBX MT	⊅ 90°0>	M SCURY
					21920 AlitaloWime2
•		33/77/30	TWYGG DAIDN	0/30 0/	Semi-Volatile - PCB'S aroclor 1016
WNE	EPA 8082	60/11/80	MG/KG DBY WT.	6790.0>	aroclor 1221
WNE	EPA 8082	50/11/80	MG/KG DRY WT.	6490.0>	aroclor 1232
WNE	EbY 8085	20/11/80 08/14/03	MG/KG DBA MT	6490.0>	aroclor 1242
WNE	EPA 8082	20/11/80 08/14/03	MG/KG DBY WT.	6 + 00.0>	aroclor 1248
WAE	EPA 8082	50/11/80 8\14\03	MG/KG DB/ WT.	6 + 90.0>	aroclor 1254
HALE	Eby 8082	08/14/03	MG/KG DRY WT.	6 + 90:0>	aroclor 1260
MNE	EPA 3640C	08/14/03	TAA ING ONOM	01.0010	Solid Soxhlet Extraction
WKE	Eby 3240C	08/12/03	with dad	22	
CSA	SM18 2540B	£0/11/80	PERCENT	LL	SCLIDS, TOTAL

P.O. Box 29 **NOTNAD JTA**

PROJECT #:

SEDIMENT SAMPLING

VILLAGE OF FORT COVINGTON

NUMBER

METHOD

08/08/5003

205844

PERFORMED

SECEINED:

Site Address:

ATTN: Brad Idzik Canton, NY 13617

CD5526 CLIENT JOB NUMBER:

Laboraterly Director

Ոաքéւնեւ

TI T PERFORMED

Print Date 08/22/2003

PERFORMED

BMIT/BTAC

except in full, without written approval from Environmental Laboratory Services. Report relates only to the samples as received by the laboratory and shall not be reproduced All tests performed under NYS ELAP Laboratory Certification # 11375 unless otherwise stated.

STINU

RESULTS

03		Cuslody Seal: X= intact	<u> </u>
Nº 00303	Watertown P.O. Box 91 Felts Milts, NY 13636 315/773-5390 (T) 315/773-0334 (F)	U NO U Notes	Shipment Rec'd Intact? MYES □ NO Laboratory Remarks
ited	Utlea 301 St. Andrews St. Utlea, NY 13802 315/735-3309 (T) 315/735-0742 (F)	SendiReportTo: 3.42/ SendiReportTo: 3.42/ Fax:Results: 3.4YES Claboratory Field I SSACH SS	Sample Type Code Key: Cription Small By Code Key: Cription Matrix Composite DW Drinking Water Stab GW Groundwater AVOC O OII Stab Stab Stab GW Wastewater WW Wastewater
ES, Lin	Syracuse 5866 State Rt. 31 Cloero, NY 13039 315/699-5281 (T) 315/699-3374 (F)		A Does
ATORI CUSTOD)	Poughkeepsle 1601 Route 376 Wappingers Falls, NY 12590 845/455-1128 (T) 845/426-1127 (F)	The state of the s	K. Chelicatel
ABOR HAIN OF	Kr. 160 160 901 Wappinge 17 845/4	142A X X X X X X X X X X X X X X X X X X X	Received for Name: Laboratory/Signature: Samplis Received By:
ING I	Plattsburgh 1080 Millary Trok. Plattsburgh, NY 12901 518/563-5878 (1) 518/562-1321 (F)	7.808 UJ X X	
FIC TESTING LABORATORE	Ithraces 798 Cascadilla Street Ithraces NY 14850 607272-1723 (T) 6077272-1723 (E)	OddocCode OnYSDEC OSW-846 OnYSDOH OCLP Other Containers CS S CS S CS S CS S	Date: NE 7, 03 Time: (6125 Name: Signature: Signature:
ATLANTIC TESTING LABORATORIES, Limited ENVIRONMENTAL - CHAIN OF CUSTODY	0x 29 0x 29 7 13617 1578 (T)	3 6 7	Date:
B	Binghamton 406 North Street Endicott, NY 13870 607757-9226 (1)	1/1/196E BRANCEY SEDIMEN 83 83 135	Samples, Relinquished By:
	Albany 12 Arrowhead Lane Cohoes, NY 12047 518/783-6987 (F)	Project No CD225 C Page of Project Contact: Project Contact: Date Time 8/7/3 11/0 8/7/5 134/0	Samplers Name: Samplers Signature: Signature: Name:

Think Quality

istril Wr. ... h Sar ... Yellow to Laboratory

Recommended Interim Remedial Measure

KLEINFELDER

November 15, 2007

Mr. Michael P. McLean, P.E. New York State Department of Environmental Conservation Office of Environmental Quality, Region 5 Route 86 – P.O. Box 296 Ray Brook, New York 12977

Re: Former Martin's Gulf Service Station (Webb's Collision Service)

Chateaugay and Salmon Street Fort Covington, New York Environmental Restoration Program No. E-517006 NYSDEC Case No. 95-07646 PBS No. 5-436720

Dear Mr. McLean:

On behalf of the Town of Fort Covington, New York, Kleinfelder East, Inc. (Kleinfelder) is submitting the following Interim Remedial Measure (IRM) work plan to the New York State Department of Environmental Conservation (NYSDEC) for review and approval. This IRM work plan documents the investigative and remedial activities planned for the above-referenced Site. The purpose of this IRM is to supplement and address previous investigative activities in order to remediate and further delineate the extent of adsorbed and dissolved-phase hydrocarbons in the northern portion of the Site in the vicinity of the former dispenser island.

Based on recent groundwater sampling events conducted by Kleinfelder and historical site data, it is evident that soil impacted with petroleum hydrocarbons remains at the site. The contaminated soil may continue to act as a source of dissolved phase concentrations observed in groundwater monitoring wells.

Proposed IRM addendum activities include the following:

Excavation

- Conduct a subsurface utility investigation. Ground penetrating radar, a radio-frequency
 metal detector and electromagnetic technologies will be used as necessary to mark out
 underground utilities and to identify the presence or absence of any subsurface metal
 anomalies such as underground storage tanks (USTs), product piping, and remote fills in the
 vicinity of proposed excavation locations;
- Excavate in the vicinity of the former dispenser island as detailed in Figure 1. The proposed excavation limits will be approximately 45 feet by 50 feet by 8 feet deep. However, these limits may increase or decrease based on field screening results and/or subsurface obstructions. Throughout the excavation the soils will be field screened for the presence of volatile organic compounds (VOCs) with a photo-ionization detector (PID) and by visual observation. The PID is equipped with a 10.6-eV lamp calibrated to isobutylene span gas to yield total VOCs in parts per million per volume (ppm_v). Based on field screening results, soils will be segregated into separate stockpiles of impacted soil and not impacted soil. For the purposes of this IRM, approximately 1,000 tons of soil was used to estimate costs detailed below.

- The actual extent of the excavation will be field determined based on field screening procedures described above. However, since groundwater is anticipated to be encountered between 4.5 and 5 ft below ground surface, temporary dewatering measures may be necessary and will be implemented under direction of the environmental subcontractor. Based on slug test data and historical soil boring logs, it is anticipated that recharge and seepage will be slow (hydraulic conductivity is estimated to be approximately 10⁻⁴ to 10⁻⁵ cm/s). The proposed temporary dewatering measures include a sump pit that will be installed and maintained at the lowest point of the excavation during soil removal activities. Groundwater will be collected and pumped from the sump pit into a storage tank or equivalent container for offsite disposal at an NYSDEC approved facility. If field screening results indicate that the excavation needs to continue beyond 8 feet below ground surface to remove impacted material, then a comprehensive groundwater recharge and seepage assessment will be prepared. The assessment will be prepared by a NYS Professional Engineer. The cost to prepare this assessment is not included with this IRM proposal.
- Post-excavation soil samples will be collected from the sidewalls of the excavation at 10-foot intervals along each sidewall at the groundwater interface. Bottom samples will be collected at a minimum frequency of one per 10 foot by 10 foot area. It is likely that bottom samples will not be collected from the excavation because the bottom of the IRM excavation is expected to be below the saturated zone. If the soils present at the base of the excavation are above the water table, post-excavation bottom samples will be collected and submitted for analysis..
- Soil samples will be submitted to a NYSDOH approved laboratory for analysis of NYSDEC STARS Table 1 List of VOCs, including MTBE, in accordance with USEPA Method 8260.
- Impacted soils will be transported to the Franklin County Landfill assuming the landfill's petroleum impacted soil limit for 2007 has not been exceeded. Otherwise, disposal and subsequent costs will be contingent upon the location of an appropriate receiving landfill.
- Clean fill material will be used to backfill the excavated area and will be certified as clean in accordance with appropriate requirements. Fill material will be backfilled and compacted to a minimum of 90% of standard proctor in 1-foot lifts up to original grade. A redevelopment plan has not been provided to Kleinfelder. Proposed development in the excavation area may require material replacement of additional compaction to support structures and foundations.
- The sample data will be subject to a data usability review and submitted in a data usability and a summary report (DUSR).
- Any monitoring wells encountered within the excavation limits and/or damaged during
 excavation activities will be removed. The proposed cost of this IRM does not include
 replacement of these wells, and a separate cost estimate to replace them will be provided as
 necessary.
- Estimated costs for activities described in this IRM are:
 - \$1,000 for private subsurface utility locator to mark out underground utilities in excavation area.
 - \$31,500 for excavation subcontractor (intention to use MBE/WBE contractor; estimate includes dewatering activities, groundwater disposal (up to 5,000 gallons), soil transportation to landfill, clean fill backfill and compaction, and a five day duration)

\$45,000 for soil disposal (assuming 1000 tons at \$45/ton) at Franklin County Solid Waste Management Facility (alternate disposal location will result in higher pricing)

\$4,400 for clean fill sand (assuming 667 cubic yards pre-compaction volume @ \$6.60/cy)

\$4,500 for environmental oversight (includes sample collection, and assumes one person at \$900/day at 5 days).

\$450 to collect samples from clean fill supplier

\$2,700 to certify clean fill does not exceed RSCO per 6 NYCRR Part 375-6 (Sample analysis required (TCL VOCs, SVOCs, TAL Metals, TCL Pesticides and PCBs at \$565/sample assuming 4 samples; and certification letter),

\$20,340 for sample analysis (assuming 24 sidewall samples and 12 bottom samples at \$565/sample; shipping not included)

\$6,500 for post excavation reporting and DUSR

\$650 for sample shipment costs

Total: \$112,540

Concrete and construction debris encountered during the excavation will be returned to the excavation upon completion. Pricing does not include costs for off-site disposal of such materials.

Price does not include replacement of monitoring wells that are damaged/destroyed during remedial excavation activities.

The IRM activities can commence within approximately 4 weeks of approval by the Town of Ft. Covington and the NYSDEC. The findings of the IRM activities will be included in a Supplemental Subsurface Investigation Report (SSIR), to be submitted to the NYSDEC within 90 days following receipt of post-excavation analytical results.

The IRM will be implemented according to the above schedule assuming no unforeseen circumstances or additional activities are required by the NYSDEC. If additional work is required by the NYSDEC for this Site, a revised schedule for the additional work and the activities listed above will be completed on a revised schedule to be agreed upon by the Town of Fort Covington and the NYSDEC.

Matthew Levinson

Project Engineer

845/567-6530

If you have any questions, please contact the undersigned at the phone numbers listed below.

Sincerely,

Kleinfelder East, Inc.

John Imhoff

Sr. Project Manager

315/413-0181

0107 110 0101

Enclosure cc: File

FIGURE

