

#### VIA ELECTRONIC MAIL

August 11, 2021

Mr. Christopher Mannes III, P.E. Environmental Engineer II New York State Department of Environmental Conservation 615 Erie Boulevard West Syracuse, NY 13204-2400

**Subject:** Second Quarter 2021 Progress Report

Former Rollway Bearing Corporation Facility, Liverpool, New York

Agreement Index Number: V7-1007-96-10; Site No. V00202

Dear Mr. Mannes:

On behalf of Emerson Electric Co., WSP USA Inc. is submitting this Second Quarter 2021 Progress Report for the former Rollway Bearing Corporation facility in Liverpool, New York. This quarterly progress report summarizes all work completed at the former Rollway Bearing facility from April through June 2021 and work planned for July through September 2021. The report was prepared in accordance with the requirements of the revised Site Management Plan (SMP), dated May 4, 2021, and includes the following information:

- a summary of all work completed and the results of sampling and testing performed during the reporting period
- a summary of reports and deliverables that were completed and submitted during the reporting period
- an estimate of the percentage of completion of the approved work plan activities, problems encountered during the
  quarter and actions taken to alleviate those problems, and modifications to work plans approved by the New York State
  Department of Environmental Conservation (NYSDEC)
- a description of activities anticipated to be completed during the next quarter

#### WORK COMPLETED

The following activities were completed during April through June 2021:

#### LNAPL RECOVERY SYSTEM

- WSP conducted operation, maintenance, and monitoring (OM&M) visits on April 21 and June 10, 2021, to confirm proper operation of the light non-aqueous phase liquid (LNAPL) recovery system. The OM&M logs are included in Enclosure A. The LNAPL recovery system was operational during the quarter except when it was turned off to perform maintenance and during the high-vacuum removal event in May 2021.
- During the April 21 and June 10, 2021, site visits, absorbent socks were removed from wells RW-1, RW-2, OW-1, OW-2, OW-3, OW-4, OW-5, SB-5, SB-8, OW-9/FB-2, OW-10/FB-1, and OW-11/FB-4, weighed, and placed in a U.S. Department of Transportation (DOT)-compliant 55-gallon steel drum for subsequent characterization and offsite disposal (Figure 1; Enclosure B).
- On May 11, 2021, the LNAPL recovery system was turned off to conduct a voluntary high-vacuum removal event using a vacuum truck to remove residual LNAPL from wells OW-1, OW-2, OW-3, OW-5, OW-9/FB-2, OW-10/FB-1,

WSP USA 7000 East Genesee Street Building D, 2nd Floor Fayetteville, NY 13066



RW-2, and SB-5 and from the surrounding formation at each location. The LNAPL removal activities were conducted in accordance with WSP's email to Christopher Mannes of the NYSDEC, dated May 3, 2021. The LNAPL removal activities consisted of applying a high vacuum to each well for a period of 30 to 330 minutes over 3 days, using an airtight well cap equipped with a drop tube. The time that vacuum was applied to each well was based on field observations regarding the volume of recovered LNAPL. The system was re-started on May 13, 2021. A total of approximately 960 gallons of liquid were pumped from the selected wells into the vacuum truck. After settling overnight, approximately 110 gallons of LNAPL/water mixture were transferred from the truck to two labeled DOT-compliant 55-gallon steel drums, which were staged onsite pending characterization and offsite disposal. The remaining 850 gallons of liquid in the vacuum truck were transported offsite for disposal at the permitted Lewiston Water Pollution Control Center in Lewistown, New York (Enclosure C). WSP estimated that approximately 23 gallons of LNAPL were removed during the high-vacuum removal event based on the measured thickness of the LNAPL layer in each drum.

#### SUB-SLAB DEPRESSURIZATION SYSTEM

— The sub-slab depressurization system (SSDS) installed in the eastern portion of the former Rollway Bearing facility was operational during the quarter (Figure 2). On April 21, May 11, and June 10, 2021, WSP conducted OM&M visits to ensure proper operation of the SSDS. The April and May inspections of the SSDS included collecting bimonthly vacuum readings from the SSD extraction points, and semi-annual vacuum readings from the vacuum monitoring locations (Figure 2). A similar inspection of the SSDS (vacuum readings of the SSDS extraction points only) occurred in June 2021. The vacuum readings obtained from the SSDS extraction points are documented on the SSDS Inspection Forms, which are included in Enclosure D.

## **ANNUAL SITE-WIDE INSPECTION**

— A site-wide inspection was performed on June 17, 2021, to evaluate compliance with the institutional controls and the and continued effectiveness of engineering controls; to document general site conditions at the time of the inspection; and to evaluate compliance with requirements of the SMP and the Deed Restriction. The results of the annual site-wide inspection were provided in the Periodic Review Report (PRR), which was submitted to the NYSDEC and New York State Department of Health (NYSDOH) on July 21, 2021.

# RESULTS OF SAMPLING AND TESTING

No sampling and testing was conducted during the reporting period.

#### REPORTS AND DELIVERABLES

- As requested in the NYSDEC's March 12, 2021, approval of the SSDS Completion Report, WSP prepared and submitted on May 4, 2021, a revised SMP that reflects the modifications to the OM&M plan for the site as outlined in the SSDS Completion Report.
- WSP submitted the First Quarter 2021 Progress Report to the NYSDEC on May 13, 2021, which summarized activities conducted from January through March 2021.

#### PERCENTAGE OF COMPLETION

WSP estimates that the project is 90 percent complete.

#### DIFFICULTIES/MODIFICATIONS TO WORK PLAN

During the quarter, system operating parameters were generally within typical operating ranges with the following exceptions:



- The vacuum reading for OW-2 was below the typical operating readings (i.e., vacuum readings as low as -1.13 inches of water column ["WC] compared to typical readings of -40 to -54 "WC). The flow to the recovery wells was rebalanced on June 10, 2021. This action did not resolve this issue. WSP will continue to monitor the vacuum readings for OW-2 to determine a potential cause of the low readings.
- RW-1 had an elevated vacuum reading on April 21, 2021 (i.e., -27.28 "WC compared to typical readings of -5 to -11 "WC). On June 10, 2021, the air flow from the recovery wells was rebalanced, which brought the vacuum for RW-1 into the appropriate range (i.e., -8.22 "WC).

#### **WORK PLANNED**

The following work has or is anticipated to be undertaken from July through September 2021:

- On July 21, 2021, WSP submitted the PRR to the NYSDEC and NYSDOH, which covered the reporting period from June 21, 2020, through June 21, 2021.
- WSP will conduct an OM&M visit in August 2021 to ensure proper operation of the LNAPL recovery system and SSDS and to collect LNAPL thickness measurements. During the August 2021 OM&M site visit, WSP anticipates replacing the batteries in the digital vacuum gauges on each SSDS extraction point and balancing the flow and measuring the resulting vacuum at each extraction point.

Please contact us at (315) 655-3900 with any questions regarding this Second Quarter 2021 Progress Report, or other aspects of the project.

Sincerely yours,

Rim E. Silfer, P.G.
Practice Leader


Enclosures

cc/encl.: Mr. Johnathan Robinson, New York State Department of Health

Mr. Stephen L. Clarke, Emerson

Ms. Sheila M. Harvey, Esquire, Pillsbury Winthrop Shaw Pittman

# **FIGURES**





# ENCLOSURE A – OM&M LOG SHEETS

#### Table 1

#### Checklist LNAPL Recovery System Former Rollway Bearing Facility Liverpool, NY

Date:4 <u>/12/21</u>		Inspector (print):Nat	e Winston
Arrival Time: _10:00		Inspector (sign):	
Departure Time:		Weather Conditions:31°	F, snow
Reason for Visit:	OM&M and Gauging		

#### **LNAPL Recovery System Skid**

Course	OM&M Reading		Typical Operation Reading	
Gauge	Reading	Units	Reading	Units
Inlet Vacuum: Before Vapor- Liquid Separator	-54	in H <sub>2</sub> O	-58 to -62	in H <sub>2</sub> O
Vacuum Before Air Filter	-64	in H <sub>2</sub> O	-66 to -68	in H <sub>2</sub> O
Vacuum After Air Filter/Before Blower Inlet	-58	in H <sub>2</sub> O	-86	in H <sub>2</sub> O
Discharge Stack Pressure	3	in H <sub>2</sub> O	2	in H <sub>2</sub> O
Discharge Stack Temperature	120	° F	120 to 138	° F
Kilowatt Hour Meter	166031	kWh	-	kWh

## **LNAPL Recovery Wells**

Well ID	OM&M Reading		Typical Operation Reading	
	Vacuum (in H <sub>2</sub> O)	Flow (SCFM)	Vacuum (in H <sub>2</sub> O)	Flow (SCFM)
OW-2	-7.00	9.0	-40 to -54	3 to 7
RW-1	-27.28	4.0	-5 to -11	5.5 to 7
OW-3	-4.45	7.0	-6 to -11	2 to 3
OW-8	-3.18	5.0	-8 to -10	4 to 11

#### **Notable Observations:**

Vacuum readings on OW-2, OW-3, and OW-8 were low compared to typical operation readings, and the vacuum reading on RW-1 was high compared to typical operation vacuum readings.

#### **System Maintenance:**

Description	of Maintenance	Needed:

Recover wells will be evaluated to determine the reason for low and high vacuum readings.

Date of Maintenance Completion: \_\_On June 10, 2021, the air flow from the LNAPL Recovery wells was rebalanced, which brought the vacuum for RW-1 into the appropriate range.

#### Table 1

#### Checklist LNAPL Recovery System Former Rollway Bearing Facility Liverpool, NY

Date:6/10/21	Inspector (print): Nate Winston
Arrival Time: _9:45	Inspector (sign):
Departure Time:	Weather Conditions:73°F, sunny
Reason for Visit: OM&M	

#### **LNAPL Recovery System Skid**

Cours	OM&M Reading		Typical Operation Reading	
Gauge	Reading	Units	Reading	Units
Inlet Vacuum: Before Vapor- Liquid Separator	-54	in H <sub>2</sub> O	-58 to -62	in H <sub>2</sub> O
Vacuum Before Air Filter	-62	in H <sub>2</sub> O	-66 to -68	in H <sub>2</sub> O
Vacuum After Air Filter/Before Blower Inlet	-58	in H <sub>2</sub> O	-86	in H <sub>2</sub> O
Discharge Stack Pressure	2	in H <sub>2</sub> O	2	in H <sub>2</sub> O
Discharge Stack Temperature	120	° F	120 to 138	° F
Kilowatt Hour Meter	167695	kWh	-	kWh

## **LNAPL Recovery Wells**

Well ID	OM&M Reading		Typical Operation Reading	
	Vacuum (in H <sub>2</sub> O)	Flow (SCFM)	Vacuum (in H <sub>2</sub> O)	Flow (SCFM)
OW-2	-1.13	6.0	-40 to -54	3 to 7
RW-1	-8.22	5.5	-5 to -11	5.5 to 7
OW-3	-0.88	5.5	-6 to -11	2 to 3
OW-8	-2.77	5.5	-8 to -10	4 to 11

## **Notable Observations:**

On June 10, 2021, the air flow from the LNAPL Recovery wells was rebalanced, which brought the vacuum for RW-1 into the appropriate range.

#### **System Maintenance:**

Description of Maintenance Needed:		
Date of Maintenance Completion:		

# ENCLOSURE B – ABSORBENT INSPECTION/REPLACEMENT FORM

# Field Form for Absorbent Inspection/Replacement Former Rollway Bearing Facility Liverpool, New York

Date: April 21, 2021	Inspector (print): Nathaniel Winston	
Arrival Time: 10:00	Inspector (sign):	
Departure Time:	Weather Conditions: 32 F, snow	

Well ID	Staining (Y/N)	Absorbent Replaced (Y/N)	Spent Absorbent Weight (in grams)
RW-1	Y	Y	2116.0
RW-2	Y	Y	1003.5
OW-1	Y	Y	411.5
OW-2	Y	Y	607.0
OW-3	Y	Y	495.5
OW-4	Y	Y	406.0
OW-5	Y	Y	619.5
OW-8	*	-	-
SB-5	Y	Y	32
SB-7	*	-	-
SB-8	Y	Y	34
SB-10	*	-	-
OW-10/FB-1	Y	Y	684.1
OW-9/FB-2	Y	Y	402.5
OW-11/FB-4	Y	Y	379.6

<sup>\* =</sup> no absorbent in well

## **Notable Observations:**

# Well Maintenance: Description of Maintenance Needed: NA Date of Maintenance Completion:

# Field Form for Absorbent Inspection/Replacement Former Rollway Bearing Facility Liverpool, New York

Date: <u>June 10, 2021</u>	Inspector (print): Nathaniel Winston
Arrival Time: 9:45	Inspector (sign):
Departure Time:	Weather Conditions: 73 F, sunny

Well ID	Staining (Y/N)	Absorbent Replaced (Y/N)	Spent Absorbent Weight (in grams)
RW-1	Y	N	1880.5
RW-2	N	N	882
OW-1	Y	N	781.0
OW-2	Y	N	266.0
OW-3	Y	N	629.5
OW-4	N	N	371
OW-5	Y	N	299
OW-8	*	-	-
SB-5	Y	N	29.5
SB-7	*	-	-
SB-8	Y	N	36.5
SB-10	*	-	-
OW-10/FB-1	Y	N	578.0
OW-9/FB-2	Y	N	734.5
OW-11/FB-4	Y	N	1844

<sup>\* =</sup> no absorbent in well

## **Notable Observations:**

New absorbents will be installed in August 2021.

# Well Maintenance:

Description of Maintenance Needed:	
NA_	
Date of Maintenance Completion:	

# ENCLOSURE C – NON-HAZARDOUS WASTE MANIFEST

i F	rm designed his use on sille (12-pich) ty	poenter)	*					10-2			
1	NON-HAZARDOUS 1. Gene WASTE MANIFEST	erator ID Number		Page 1 of 3. Emer	-823.	- 763	7	acking Numl			
	5. Generator's Name and Mailing Address	" Follway be	aring Con	A Generat	or's Site Addres	s (if different	than mailing addre	ess)	el		
	112-375-0264 Generators Phone:	7000 Est	Gentsep 130	44 i	7	اعجمار	0001	NY'	12,59	L)	
	6. Transporter 1 Company Name	Fayetteville  Hega	1 1	1.			U.S. EPA ID	Number	1 18/12	2/	
	7. Transporter 2 Company Name						U.S. EPA ID	Number	1775	<u> </u>	
	8. Designated Facility Name and Site Ad	Idress Tuida	of lais	Kn			U.S. EPA ID	Number	~		
and the state of t	1 1201 Cm	501	pletcher	PR							
on the same of the	716-754-8251 Facility's Phone:	Lew	iston, wy	14092	10. Conta	ainers	11. Total	12. Unit			
N. 200 P. C.	9. Waste Shipping Name and Des			1001	No.	Туре	Quantity	Wt./Vol.			
ATOR	1 NON RERA, N	ION DOT KEY	WIGHER MA	16 f :9	Í	T	057	6			
GENERATOR	2 2	JATEY)				,,	0.30			-	
					£						
	3.								W O W W.		
	4.		.,								
					l						
	13. Special Handling Instructions and Ad			l		<u> </u>		<b>.</b>			
	Hegsur fi	0# 812-16	20855								
	Heres -	Teb # 219	SC 2700	<b>2</b>							
	14. GENERATOR'S/OFFEROR'S CERTI marked and labeled/placarded, and a	FICATION: I hereby declare that I	the contents of this consi	gnment are fully and					ind are classifie	d, packag	ed,
V	Generator's/Offeror's Printed/Typed Nam	ů.		Signature	10	1	12		Month Icas I	Day	Year ZZ/
INT'L	15. International Shipments	Import to U.S.	Ехр	ort from U.S.	Port of en		7)				-C-/
-	Transporter Signature (for exports only):  16. Transporter Acknowledgment of Rece	eipt of Materials	2007		Date leavi	ng U.S.:			~~~		
TRANSPORTER	Transporter 1 Printed/Typed Name	SKI		Signature	( Ka		۷.		Month 5	Day 14 k	Year
TRAN	Transporter 2 Printed/Typed Name			Signature	J \				Month	Day 	Year
A	17. Discrepancy 17a. Discrepancy Indication Space	70	Туре		D		Пания		П.		
		Quantity	ш туре		Residue est Reference N	umbor	Partial Reje	CUON	i rt	all Rejection	on
LITY –	17b. Alternate Facility (or Generator)			Wallie	ST Deleterice IN	umoer.	U.S. EPA ID N	lumber			
D FAC	Facility's Phone:										
NATE	17c. Signature of Alternate Facility (or Ge	nerator)							Month	Day	Year
DESIGNATED FACILITY				-2006		-,455					
	18. Designated Facility Owner or Operato	r: Certification of receipt of materi	als covered by the manife	est except as noted	in Item 17a						
	Printed/Typed Name	- Same and a resulpt of mater	and outside by the marine	Signature /	The second second	7H			Month	Day	Year 2
				- JAN	1/ 1×	MS			2		

GC Labels • Printed in the USA . 1-800-997-6966 DESIGNATED FACILITY TO GENERATOR

Reorder Part# MANIFEST-C6NHWC 913-897-6966

ENCLOSURE D – SI	UB-SLAB DEPRES	SSURIZATION S	SYSTEM INSPEC	TION FORMS

# Sub-Slab Depressurization System Inspection Form Former Rollway Bearing Corporation Facility Liverpool, New York

Date: 4/21/2021		Inspect	for (print): Nate Winston	
Time: 10:30		Inspector (sign):		
		Weather	Conditions 32 deg F, snowing	
		se to Owner N	Jotification	
	. Kespon	se to Owner 1	Notification	
Vacuum		Vacuum		
Reading (in W.C.)	SSD Extraction Point			
-8.53	SSD-13	-7.25		
-0.91	SSD-14	-3.94		
-25.94	SSD-15	-5.40		
-27.87	SSD-16	-4.93		
-0.49	SSD-17	-2.55		
-26.02	SSD-18	-20.83		
-25.60	SSD-19	-21.66		
-0.80	SSD-20	-1.02		
-26.11	SSD-21	-25.34		
-26.55	SSD-22	-7.15		
-1.35	SSD-23	-1.08		
-18.96				
	Yes	No	Comments/Corrective Action Taken	
ctions		X		
re	X			
rumentation		X		
		X		
etions		X		
	_			
	X			
New air intakes within 10 ft of discharge points		X		
		X		
ons		<u> </u>		
	10:30  Il that apply):     X  Vacuum Reading (in W.C.)     -8.53     -0.91     -25.94     -27.87     -0.49     -26.02     -25.60     -0.80     -26.11     -26.55     -1.35     -18.96  ctions re rumentation ards or	That apply:   X   Responsible	Nacuum   Reading (in W.C.)   SSD Extraction Point   Wacuum   Reading (in W.C.)   -8.53   SSD-13   -7.25   -0.91   SSD-14   -3.94   -25.94   SSD-15   -5.40   -27.87   SSD-16   -4.93   -0.49   SSD-17   -2.55   -26.02   SSD-18   -20.83   -25.60   SSD-19   -21.66   -0.80   SSD-20   -1.02   -26.11   SSD-21   -25.34   -26.55   SSD-22   -7.15   -1.35   SSD-23   -1.08   -18.96   Yes   No extions   X   True   X	

#### Sub-Slab Vacuum Monitoring Form Former Rollway Bearing Corporation Facility Liverpool, New York

Date:4/21/2021Inspector (print):Nate WinstonTime:10:30Inspector (sign):Weather Conditions32 deg F, snowing

Vacuum Monitoring Location	Vacuum Reading	Comments/Observations
SS-1	-3.15 in. H <sub>2</sub> O	
SS-3	-0.81 in. H <sub>2</sub> O	
SS-10	-1.25 in. H <sub>2</sub> O	
SS-11	-0.13 in. H <sub>2</sub> O	Was not accessible on 4/21/21; measured on May 11, 2021
SS-12	-1.17 in. H <sub>2</sub> O	Was not accessible on 4/21/21; measured on May 11, 2021
SS-14	-0.09 in. H <sub>2</sub> O	
SS-15	-0.92 in. H <sub>2</sub> O	
SS-16	-0.44 in. H <sub>2</sub> O	
SS-17	-0.61 in. H <sub>2</sub> O	
SS-18	-1.80 in. H <sub>2</sub> O	
MP-3	-0.26 in. H <sub>2</sub> O	
MP-10	-0.28 in. H <sub>2</sub> O	
MP-15	-0.11 in. H <sub>2</sub> O	
MP-19	-0.13 in. H <sub>2</sub> O	
MP-23	-0.71 in. H <sub>2</sub> O	
MP-30	-1.30 in. H <sub>2</sub> O	
MP-31	-1.54 in. H <sub>2</sub> O	Was not accessible on 4/21/21; measured on May 11, 2021

#### Sub-Slab Depressurization System Inspection Form Former Rollway Bearing Corporation Facility Liverpool, New York

Date: 6/10/2021			Inspector (print): Nate Winston				
Time: 9:45			Inspector (sign):				
			Weather (	Conditions 73 deg F, sunny			
Reason for Visit (check a				7 101			
Routine Inspection/O&M Other		Respon	se to Owner N	Notification			
	` <u> </u>						
Vacuum Measurements	Vacuum		Vacuum				
SSD Extraction Point	Reading (in W.C.)	SSD Extraction Point	Reading (in W.C.)				
SSD-01	-8.74	SSD-13	-7.36				
SSD-02	-1.03	SSD-14	-4.11				
SSD-03	-25.05	SSD-15	-5.92				
SSD-04	-26.99	SSD-16	-4.06				
SSD-05	-0.47	SSD-17	-2.74				
SSD-06	-25.82	SSD-18	-20.41				
SSD-07	-25.07	SSD-19	-20.19				
SSD-08	-1.12	SSD-20	-1.29				
SSD-09	-26.33	SSD-21	-25.01				
SSD-10	-26.49	SSD-22	-7.64				
SSD-11	-1.06	SSD-23	-1.18				
SSD-12	-18.25						
SSD Risers		Yes	No	Comments/Corrective Action Taken			
Observable leaking connections			X				
Riser piping supports secure		X					
Defective or damaged instrumentation			X				
Damage to protective boll			X				
barriers			71				
Piping Network	otiona		X				
Observable leaking connections							
Lateral piping supports se		X					
New air intakes within 10 ft of			X				
discharge points  Discharge Fans							
Inoperable fan(s)			X				
Other Notable Observati	ions						
NA	IUIIS						
1721							
				_			