

EMERSON ELECTRIC CO.

PERIODIC REVIEW REPORT

FORMER ROLLWAY BEARING CORPORATION
FACILITY, ONONDAGA COUNTY, LIVERPOOL,
NEW YORK – SITE NO. V00202

JULY 11, 2022





PERIODIC REVIEW REPORT

FORMER ROLLWAY BEARING
CORPORATION FACILITY,
ONONDAGA COUNTY,
LIVERPOOL, NEW YORK – SITE
NO. V00202

EMERSON ELECTRIC CO.

PROJECT NO.: 31401545.018
DATE: JULY 11, 2022

WSP
ONE PENN PLAZA
NEW YORK, NY 10119

TEL.: +1 212 465-5000
FAX: +1 212 465-5096
WSP.COM



TABLE OF CONTENTS

1	EXECUTIVE SUMMARY	1
1.1	Site Summary.....	1
1.2	Effectiveness of the Remedial Program	1
1.3	Compliance	2
1.4	Recommendations.....	2
2	SITE OVERVIEW	3
2.1	Site Location and Description.....	3
2.2	Summary of Investigation and Remediation Activities	3
2.2.1	Soil	3
2.2.2	Groundwater.....	3
2.2.3	LNAPL	4
2.2.4	Sub-Slab Soil Gas and Indoor Air	5
2.3	Remedial Objectives.....	5
2.4	Changes to the Selected Remedy	5
3	EVALUATION OF REMEDY PERFORMANCE, EFFECTIVENESS, AND PROTECTIVENESS.....	7
4	IC/EC PLAN COMPLIANCE REPORT	8
4.1	Requirements and Compliance.....	8
4.1.1	Institutional Controls.....	8
4.1.2	Engineering Controls.....	9
4.2	IC/EC Certification	10
5	MONITORING PLAN COMPLIANCE REPORT	11
5.1	Monitoring Plan Components	11
5.2	Monitoring Completed During Reporting Period.....	12
5.2.1	Site-Wide Inspection.....	12
5.2.2	Absorbent Inspection and Replacement.....	12
5.2.3	LNAPL Thickness Monitoring.....	12
5.3	Comparisons with Remedial Objectives.....	13



5.4	Monitoring Deficiencies.....	13
5.5	Conclusions and Recommendations for Changes.....	13
6	O&M PLAN COMPLIANCE REPORT	14
6.1	O&M Plan Components	14
6.1.1	LNAPL Recovery System.....	14
6.1.2	Sub-Slab Depressurization System.....	14
6.2	O&M Completed During Reporting Period.....	15
6.2.1	LNAPL Recovery System.....	15
6.2.2	Sub-Slab Depressurization System.....	15
6.3	Evaluation of Remedial Systems	16
6.3.1	LNAPL Recovery System.....	16
6.3.2	Sub-Slab Depressurization System.....	16
6.4	O&M Deficiencies	16
6.5	Conclusions and Recommendations for Improvements.....	16
7	OVERALL PRR CONCLUSIONS AND RECOMMENDATIONS	17
7.1	Compliance with SMP	17
7.2	Performance and Effectiveness of Remedy	17
7.3	Future PRR Submittals	17



FIGURES

FIGURE 1	SITE LOCATION
FIGURE 2	SITE LAYOUT
FIGURE 3	LNAPL RECOVERY SYSTEM LAYOUT FORMER HEAT TREAT DEPARTMENT
FIGURE 4	SUB-SLAB DEPRESSURIZATION SYSTEM LAYOUT
FIGURE 5	COVER SYSTEM LOCATION
FIGURE 6	LNAPL THICKNESS MEASUREMENTS FORMER HEAT TREAT DEPARTMENT

TABLES

TABLE 1	LNAPL RECOVERY SYSTEM MONITORING AND MAINTENANCE SUMMARY
TABLE 2	SSDS MONITORING AND MAINTENANCE SUMMARY
TABLE 3	SUMMARY OF MEASUREMENTS FROM SSDS VACUUM MONITORING POINTS
TABLE 4	SUMMARY OF LNAPL THICKNESS MEASUREMENTS - RECOVERY WELLS AND OBSERVATION WELLS
TABLE 5	SUMMARY OF LNAPL THICKNESS MEASUREMENTS – PNEUMATIC FRACTURING BOREHOLES/OBSERVATION WELLS

APPENDICES

APPENDIX A	RELEVANT HISTORICAL SITE FIGURES
APPENDIX B	ANNUAL SITE-WIDE INSPECTION FORM
APPENDIX C	LNAPL RECOVERY SYSTEM OM&M CHECKLISTS
APPENDIX D	SSDS INSPECTION FORMS
APPENDIX E	IC/EC CERTIFICATION STATEMENT
APPENDIX F	ABSORBENT INSPECTION/REPLACEMENT FORMS
APPENDIX G	LNAPL THICKNESS GRAPHS
APPENDIX H	SUPPORTING MATERIALS FOR MANN- KENDALL ANALYSIS

1 EXECUTIVE SUMMARY

WSP USA Inc. (WSP) is submitting this Periodic Review Report (PRR) on behalf of Emerson Electric Co. (Emerson) for the former Rollway Bearing Corporation facility at 7600 Morgan Road in Liverpool, New York (Site). This PRR has been prepared in accordance with the New York State Department of Environmental Conservation (NYSDEC) Division of Environmental Remediation's (DER's) DER-10 *Technical Guidance for Site Investigation and Remediation*, dated May 2010, the revised Site Management Plan (SMP), dated May 3, 2021, and NYSDEC correspondence to Stephen Clarke of Emerson, dated May 3, 2022. This PRR covers the reporting period from June 21, 2021, through June 21, 2022. The Site is currently enrolled in the New York State Voluntary Cleanup Program (VCP; Site No. V00202). A Deed Restriction was recorded for the property on December 1, 2017, and Emerson received a Release and Covenant Not to Sue from the NYSDEC on March 21, 2018.

1.1 SITE SUMMARY

Investigations performed at the Site from 1995 through 2014 identified the following constituents that required remediation:

- Petroleum-affected soil
- Light non-aqueous phase liquid (LNAPL)

Remediation and monitoring activities completed at the Site under the VCP included the following:

- Quarterly groundwater monitoring to verify that the extent of volatile organic compounds (VOCs) in onsite groundwater was not expanding and that VOC concentrations were not increasing
- Excavation of petroleum-affected soil from the former gasoline underground storage tank area
- Installation and ongoing operation of a vacuum-enhanced LNAPL recovery system in the former heat treat area

In addition to the above activities, a sub-slab depressurization system (SSDS) was voluntarily installed at the Site in August and September 2020, to address the potential for vapor intrusion associated with VOCs present in sub-slab soil vapor under the eastern portion of the facility.

On completion of the activities described above, remaining contamination on the property consisted of the following:

- VOCs in groundwater in isolated areas onsite
- VOCs in sub-slab soil gas
- LNAPL below the former heat treat area

Institutional Controls and Engineering Controls (ICs and ECs) have been incorporated into the remedy for the Site to control exposure to remaining contamination and ensure protection of public health and the environment. A Deed Restriction granted to the NYSDEC, and recorded with the Onondaga County Clerk, requires the property owner to comply with the SMP and all ICs and ECs placed on the Site until the Deed Restriction is extinguished.

1.2 EFFECTIVENESS OF THE REMEDIAL PROGRAM

Active remediation at the Site consists of operating and maintaining a vacuum-enhanced LNAPL recovery system in the former heat treat area and inspecting and replacing absorbents in select wells on a bi-monthly basis to recover LNAPL from the subsurface. During the reporting period, the system operated continuously, and progress was made toward achieving the remedial objective through the removal of approximately 5.4 gallons of LNAPL from Site wells using absorbents. Therefore, the system continues to be effective in removing LNAPL from the subsurface. In addition to removing LNAPL with absorbents, approximately 850 gallons of LNAPL-containing liquid were also removed from select wells in December 2021 by applying a high vacuum to each well using a vacuum truck, air-tight cap, and drop tube. The volume of LNAPL removed during the event could not be determined because the LNAPL was emulsified, and the recovered liquids were transported offsite for disposal at the end of the field event. Future LNAPL removal events will be scheduled to allow time for the recovered LNAPL to separate and be measured before the liquids are transported offsite for disposal.

1.3 COMPLIANCE

No deficiencies were identified with respect to compliance with the SMP for the Site; therefore, no corrective actions are required at this time.

1.4 RECOMMENDATIONS

WSP does not recommend changing the frequency of PRR submittals. In addition, no modifications are recommended to the ICs and ECs, or the operation and maintenance (O&M) plan.

2 SITE OVERVIEW

2.1 SITE LOCATION AND DESCRIPTION

The former Rollway Bearing Corporation facility is located at 7600 Morgan Road in Liverpool, Onondaga County, New York, on approximately 78 acres (Figures 1 and 2). The Site consists of a 220,000 square-foot main building that contains office space, equipment repair and fabrication areas, and warehouse space. Asphalt parking and equipment staging areas are north, east, and south of the main building; and lawn areas and asphalt driveways and parking areas are west of the main building. A metal storage shed is east of the main building and an abandoned steel water tank and pump house are to the southeast of the main building. The eastern portion of the property is undeveloped. The Site is zoned commercial and is currently used for commercial and industrial purposes.

The properties adjoining the Site and in the surrounding area consist primarily of commercial properties. The properties directly south of the Site include commercial properties; properties directly north of the Site include commercial and industrial properties; properties directly east of the Site include utility and transportation (railroad) corridors; and the properties on the west side of Morgan Road are used for commercial and residential purposes.

2.2 SUMMARY OF INVESTIGATION AND REMEDIATION ACTIVITIES

2.2.1 SOIL

Investigations performed at the Site in 1995 indicated the presence of VOCs in soil at concentrations above the site-specific soil cleanup objectives (SCOs) in the former gasoline underground storage tank area near the southeast corner of the main building (Figure 1 in Appendix A). In November and December 2001, petroleum-affected soil was excavated from the former gasoline underground storage tank area for offsite disposal (Figure 2 in Appendix A). Verification sample results from the final excavation were below the site-specific SCOs.

2.2.2 GROUNDWATER

Groundwater investigations were performed at the Site from 1995 to 2011. VOCs were detected in groundwater above the ambient water quality standards in the following areas: former monitoring well MW-4R directly east of the former heat treat area; MW-5 in the former hazardous waste storage building; MW-9D inside the main building in the former drum storage area; and in an in-situ groundwater sample collected southeast of the main building (Figure 3 in Appendix A).

From 2001 through August 2003, quarterly groundwater monitoring was performed to verify that the extent of VOCs in onsite groundwater was not expanding, and that VOC concentrations were not increasing. The results of the monitoring program indicated that the extent of VOCs in groundwater was defined, that the plume was not expanding, and that VOC concentrations were decreasing. Furthermore, the majority of the chlorinated VOC mass near the former hazardous waste storage building consisted of cis- and trans-1,2-dichloroethene (DCE) and vinyl chloride, with relatively little parent compound (i.e., trichloroethene [TCE]) present. These data indicated that natural attenuation was occurring at the Site. It was concluded that the objectives of the groundwater monitoring program were achieved and a request to terminate groundwater monitoring at the Site was submitted to the NYSDEC in April 2004. The NYSDEC did not respond to this request.

In August 2018, WSP voluntarily collected groundwater samples for analysis of VOCs from five wells (MW-2R, RW-1, OW-8, MW-6, and MW-10) that comprise the long-term groundwater monitoring network in the approved SMP (Figure 3 in Appendix A). The objective of the sampling event was to evaluate the current groundwater quality in these wells. The results indicated non-detectable levels of VOCs in MW-2R, MW-6, and RW-1. TCE was detected in OW-8 and MW-10 at

concentrations slightly above the ambient water quality standard of 5 µg/l. In addition, cis-1,2-DCE (36.2 µg/l) was detected in OW-8 above the ambient water quality standard of 5 µg/l. The absence of VOCs above the reporting limits in RW-1 and only a trace level of TCE in OW-8 indicates that the residual LNAPL in this area is not a significant source of VOCs to groundwater. In addition, the sample collected from OW-8 had low concentrations of chlorinated VOCs (less than 50 µg/l) with daughter products indicative of sequential reduction and electron donor concentrations to support continued natural attenuation.

2.2.3 LNAPL

During the Phase II site investigation in 1995, LNAPL was identified in the upper portion of the weathered shale bedrock below a portion of the former heat treat area and in an isolated area adjacent to the east wall of the facility. From September 2001 through February 2003, LNAPL recovery pilot test activities were performed to evaluate the effectiveness of gravity skimming and vacuum-enhanced gravity skimming in removing LNAPL from the weathered shale below the former heat treat area. The pilot tests demonstrated that vacuum-enhanced skimming was a potentially effective technology for the Site, although the effective radius of influence was small (i.e., approximately 1.5 feet) and the product-containing fractures within the weathered shale were not laterally extensive.

In May 2008, a vacuum-enhanced LNAPL recovery system was installed as an interim remedial measure to remove measurable LNAPL (i.e., greater than 0.01 foot) within the weathered shale under a portion of the former heat treat area of the facility (Figure 3). The main components of the system are a 30-gallon vapor-liquid separator (VLS), a skid-mounted 2-horsepower vacuum blower, a 10-micron air filter, a dilution valve with 10-micron air filter, inlet and outlet vacuum gauges, exhaust stack pressure gauge, and an exhaust stack temperature gauge. The equipment skid is housed within an enclosure inside the former heat treat area. Subsurface vacuum conveyance piping extends from the treatment system equipment to recovery wells OW-2, RW-1, OW-3, and OW-8 (Figure 3).

In March 2011, a focused application of pneumatic fracturing was performed in two areas within the former heat treat area to increase the density and connectivity of fractures within the weathered shale bedrock and overburden materials. Three of the open soil borings used to implement the pneumatic fracturing were subsequently converted to 4-inch inside-diameter polyvinyl chloride wells in 2016 (i.e., OW-9/FB-2, OW-10/FB-1, and OW-11/FB-4; Figure 3). The remaining soil boring was abandoned.

In November 2019, WSP redeveloped LNAPL recovery wells OW-2, OW-3, OW-8, and RW-1 to remove sediment and ensure effective communication between the well screens and the surrounding formation. The redevelopment activities consisted of surging and brushing the screened interval and bottom of the well casings to loosen any fine-grained sediment in the filter pack and adjacent aquifer material. Groundwater and sediment were then removed from the wells by pumping and subsequently disposed of offsite in accordance with state and federal requirements.

In December 2019, the system was turned off to conduct a voluntary high-vacuum removal event using a vacuum truck to remove residual LNAPL from wells OW-1, OW-2, OW-3, OW-5, OW-9/FB-2, OW-10/FB-1, and SB-5 and the surrounding formation. These wells were selected based on the presence of measurable LNAPL on consecutive occasions in 2018 and 2019. The LNAPL removal activities consisted of applying a high vacuum to each well for a period of 30 to 50 minutes using an air-tight well cap equipped with a drop tube. Liquids removed from the wells were contained and disposed of offsite. The vacuum blower remained off following the high-vacuum LNAPL removal event to evaluate LNAPL recovery in these wells under ambient conditions. The system was re-started on January 23, 2020, after obtaining LNAPL thickness measurements from the wells.

In May 2021, the system was turned off to conduct another voluntary high-vacuum removal event using a vacuum truck to remove residual LNAPL from wells OW-1, OW-2, OW-3, OW-5, OW-9/FB-2, OW-10/FB-1, RW-2, and SB-5 and the surrounding formation. These wells were generally selected based on the presence of measurable LNAPL during the previous 12-month period. The LNAPL removal activities consisted of applying a high vacuum to each well for a period of 30 to 330 minutes over 3 days, using an air-tight well cap equipped with a drop tube. The time that vacuum was applied to each well was based on field observations regarding the volume of recovered LNAPL. Approximately 960 gallons of liquid, which consisted of approximately 23 gallons of LNAPL, were removed from the wells and disposed of offsite. The system was re-started on May 13, 2021.

2.2.4 SUB-SLAB SOIL GAS AND INDOOR AIR

Vapor intrusion assessment activities were performed within the main building from 2006 through 2012 (Figures 4 and 5 in Appendix A). Concurrent indoor air and sub-slab soil gas sampling performed in the former manufacturing area of the main building indicated that mitigation was recommended with respect to TCE. Additional sub-slab soil gas samples were collected to delineate the extent of VOCs, primarily TCE, in sub-slab soil gas. The extent of TCE in sub-slab samples was defined to the north, east, and south by the perimeter building foundation; however, the western extent of TCE in soil gas was not defined. Because products containing TCE were used in the facility, the New York State Department of Health (NYSDOH) indicated that exposure to TCE was regulated by the U.S. Occupational Safety and Health Administration and that no further sampling or vapor mitigation was warranted in the former manufacturing area.

From June 2010 through February 2012, concurrent indoor air and sub-slab soil gas samples were collected on five occasions from the office area in the northwest corner of the main building. The results from the initial sampling event indicated the presence of tetrachloroethene (PCE) at levels slightly above the criteria for vapor mitigation. However, four subsequent sampling events performed during the heating season indicated that no further action was recommended. Because the use of PCE-containing materials was documented on the plant floor, no actions to address potential exposure were pursued at that time. The SMP requires that the potential for exposure via the soil vapor intrusion pathway be evaluated if there is a change in the use of PCE-containing materials within the building (provided the potential for vapor intrusion has not been previously addressed to the department's satisfaction).

In March 2019, WSP collected sub-slab soil gas samples at 13 locations within the former manufacturing building in accordance with an approved work plan, dated February 25, 2019 (Figure 4 in Appendix A). The objective of the sampling activities was to evaluate current sub-slab soil vapor conditions at select locations that were sampled in 2006 and 2007, and to further delineate the extent of VOCs in sub-slab soil vapor. On October 28, 2019, WSP submitted a report to the NYSDEC summarizing the results of the sub-slab soil vapor sampling. The March 2019 sub-slab sample results indicated that concentrations of TCE have decreased from 58 percent to greater than 99 percent since 2006 and 2007. In addition, the sampling activities were effective in delineating the extent of VOCs in sub-slab soil vapor.

In February 2020, WSP submitted a Sub-Slab Depressurization System (SSDS) Installation Work Plan for the installation of a proposed SSDS in the eastern portion of the former Rollway Bearing facility building to limit the potential for vapor intrusion to indoor air. NYSDEC approved the SSDS Installation Work Plan in correspondence to Emerson, dated April 9, 2020. From August to September 2020, WSP installed the SSDS. The system consists of a network of 23 SSD extraction points, organized into 19 distinct legs, each with a dedicated extraction fan and exhaust stack (Figure 4). SSDS start-up was completed in September 2020. The SSDS Completion Report was submitted to, and approved by, the NYSDEC in March 2021. The SSDS has operated continuously since September 2020.

2.3 REMEDIAL OBJECTIVES

The remedial objective for the vacuum-enhanced LNAPL recovery system is the absence of measurable LNAPL (greater than 0.01 foot) in the heat treat area wells for a period of 12 consecutive months. Once LNAPL remediation is complete, the SMP requires that eight consecutive quarters of groundwater results from select wells meet the ambient water quality standards.

2.4 CHANGES TO THE SELECTED REMEDY

Beginning in 2008, monthly site visits were performed to maintain the vacuum-enhanced LNAPL recovery system, obtain LNAPL thickness and water-level measurements, and remove LNAPL that accumulated in the wells using a vacuum truck. In 2014, WSP obtained approval from the NYSDEC to reduce the site visit frequency to bi-monthly and to recover LNAPL using absorbents suspended in the wells.

Absorbents were removed from wells SB-7 and SB-10 in February 2020 and were not reinstalled because no measurable product was observed in these wells since 2019, or earlier. New absorbents will be placed in these wells if LNAPL is observed in the future.

An SSDS was voluntarily installed at the Site in August and September 2020, to address the potential for vapor intrusion associated with VOCs present in sub-slab soil vapor under the eastern portion of the facility. The active SSDS will not be discontinued unless prior written approval is granted by the NYSDEC and NYSDOH. If monitoring data indicates that the SSDS may no longer be required, a proposal to discontinue operation of the SSDS will be submitted by the remedial party to the NYSDEC and NYSDOH.

3 EVALUATION OF REMEDY PERFORMANCE, EFFECTIVENESS, AND PROTECTIVENESS

Active remediation at the Site consists of operating and maintaining a vacuum-enhanced LNAPL recovery system in the former heat treat area and inspecting and replacing absorbents in select wells on a bi-monthly basis to recover LNAPL from the subsurface. Progress was made toward achieving the remedial objective as demonstrated by the following:

- Approximately 5.4 gallons of LNAPL were removed from site wells during the reporting period based on the weight of spent absorbents removed from select wells. Approximately 850 gallons of LNAPL-containing liquid were removed during a high-vacuum removal event performed in December 2021, as described in Section 4.1.2. The volume of LNAPL removed during the event could not be determined because the LNAPL was emulsified, and the recovered liquids were transported offsite for disposal at the end of the field event.
- LNAPL was either not measurable, or did not exceed the remedial objective of 0.01 foot, in five wells (i.e., OW-4, OW-10/FB-1, RW-2, SB-7, and SB-10) during the reporting period.
- Based on a statistical trend analysis as described in Section 5.2.3, the LNAPL thickness in wells OW-2 and OW-5 show a downward trend from May 2008 (when the system became operational) to the present. The LNAPL thickness in wells OW-9/FB-2 and OW-10/FB-1 show a downward trend from March 2011 (when the soil borings were first installed to implement pneumatic fracturing¹) to the present. The LNAPL thickness in wells OW-3 and SB-5 showed no significant trend.

¹ Soil borings FB-1 and FB-2 were installed in March 2011 to implement pneumatic fracturing to enhance LNAPL recovery. The open boreholes were monitored for the presence of LNAPL until May 2016 when the borings were converted to 4-inch inside-diameter observation wells.

4 IC/EC PLAN COMPLIANCE REPORT

4.1 REQUIREMENTS AND COMPLIANCE

4.1.1 INSTITUTIONAL CONTROLS

The following ICs are included in the SMP for the Site:

- The property may be used for commercial or industrial use;
- All ECs must be operated and maintained as specified in the SMP;
- All ECs must be inspected at a frequency and in a manner defined in the SMP;
- The use of groundwater underlying the property is prohibited without necessary water quality treatment as determined by the NYSDOH or the Onondaga County Department of Health to render it safe for use as drinking water or for industrial purposes, and the user must first notify and obtain written approval to do so from the NYSDEC;
- Groundwater and other environmental or public health monitoring must be performed as defined in the SMP;
- Data and information pertinent to site management must be reported at the frequency and in a manner as defined in the SMP;
- All future activities that will disturb remaining contaminated material must be conducted in accordance with the SMP;
- Monitoring to assess the performance and effectiveness of the remedy must be performed as defined in the SMP;
- Operation, maintenance, monitoring, inspection, and reporting of any mechanical or physical component of the remedy shall be performed as defined in the SMP;
- Access to the Site must be provided to agents, employees or other representatives of the State of New York with reasonable prior notice to the property owner to assure compliance with the restrictions identified by the Deed Restriction;
- The potential for vapor intrusion must be evaluated for any buildings developed in the area within the IC boundaries noted on Figure 2, or if the use of PCE-containing materials within the existing building changes (provided the potential for vapor intrusion has not been previously addressed to the department's satisfaction). Any potential impacts that are identified must be monitored or mitigated; and
- Vegetable gardens and farming on the Site are prohibited.

A site-wide inspection was performed on June 2, 2022, to evaluate compliance with the ICs, including site use, to document the general site conditions at the time of the inspection; and to evaluate compliance with requirements of the SMP and the Deed Restriction. The results of the annual inspection are documented on the Annual Site-Wide Inspection Form (Appendix B).

Based on the results of the site inspection, the property continues to be used for commercial purposes, and no new buildings have been constructed on the property. No groundwater is being used onsite and no vegetable gardening or farming has occurred at the Site. No evidence of excavation activities was observed within the areas of remaining contamination.

The site-wide inspection also included an evaluation of whether PCE-containing materials continue to be used onsite. During the site inspection, WSP observed a product that contained PCE being used within the building (i.e., Brakleen Brake Parts Cleaner).

Based on the results of the site inspection, the ICs are in place and have been complied with, including compliance with the Deed Restriction and the SMP. No deficiencies were identified with respect to the ICs, and no changes to the ICs are recommended at this time.

4.1.2 ENGINEERING CONTROLS

The ECs included in the revised SMP (May 3, 2021) for the Site consist of a cover system, a vacuum-enhanced LNAPL recovery system, and a SSDS.

COVER SYSTEM

The cover system is comprised of the existing concrete floor slab within the former manufacturing area of the main building, which prevents exposure to remaining contamination below the building. Specifically, the cover system prevents exposure to VOCs in sub-slab soil vapor and groundwater and to LNAPL below a portion of the heat treat area. The location of the cover system is shown in Figure 5. The cover system is inspected annually and is considered to be protective to human health and the environment if there are no breaches in the concrete slab.

An annual site inspection was performed on June 2, 2022, to evaluate the continued effectiveness of the cover system, and the results of the annual inspection are documented on the Annual Site-Wide Inspection Form (Appendix B). During the inspection, the concrete slab comprising the cover system appeared in good condition. Some minor cracks (less than 1/8-inch wide) were observed in the former manufacturing area of the building; however, it is unknown whether these openings penetrate the full thickness of the concrete slab. As described further below, the vacuum readings from the SSDS suction points remain at acceptable levels, which indicates that these minor cracks are not affecting the system performance. No breaches in the cover system were observed during the site inspection, and no excavation activities were performed within the cover system area during the reporting period.

The cover system continues to perform as designed and remain effective in protecting human health and the environment. No deficiencies were identified with respect to the cover system, and no changes to the cover system are recommended at this time.

LNAPL RECOVERY SYSTEM

During the reporting period, O&M site visits were performed on August 24, October 14, and December 6, 2021, and February 28, April 4, and June 2, 2022, to monitor and maintain the LNAPL recovery system and ensure that the system was operating as designed. During each site visit, an O&M checklist was completed to document operating parameters within the system enclosure and at the recovery wells (Appendix C). A summary of the system monitoring and maintenance information is provided in Table 1. During the reporting period, system operating parameters were generally within typical operating ranges with the following exceptions:

- The vacuum readings for the LNAPL recovery wells (primarily OW-2 and OW-8) were below the typical operating range during the reporting period; however, the flow from these wells was relatively uniform and, thus, no corrective action was recommended. The lower vacuum readings are likely attributable to the use of a digital gauge for the vacuum readings. The typical operating range indicated on the field measurement form was based on historical readings obtained with an analog gauge.

The LNAPL recovery system was operational during the reporting period except when it was turned off to perform maintenance and from December 6, 2021, to January 21, 2022, to perform a high-vacuum removal event and post-remediation LNAPL thickness monitoring.

On December 6, 2021, the system was turned off to conduct a voluntary high-vacuum removal event using a vacuum truck to remove residual LNAPL from wells OW-3, RW-1, and SB-5 and from the surrounding formation. The LNAPL removal activities were conducted in accordance with WSP's email to Christopher Mannes of the NYSDEC, dated May 3, 2021, and consisted of applying a high vacuum to each well using an air-tight well cap equipped with a drop tube. From December 6 to 8, 2021, vacuum was applied to OW-3 for approximately 20 hours to determine if the application of a sustained high vacuum would prevent the reoccurrence of measurable LNAPL in the well. At the end of the 3-day event, WSP observed that the volume of LNAPL removed from OW-3 had decreased, but LNAPL was still present in the purge water. LNAPL-containing liquid was mostly pumped from OW-3 because SB-5 went dry after approximately 20 minutes of pumping, and the water purged from RW-1 did not contain visible LNAPL once the residual LNAPL in the well casing was removed. Approximately 850 gallons of liquid were removed and pumped into a vacuum truck and transported offsite for disposal at the permitted Covanta Environmental Solutions facility in Oriskany, New York. The vacuum blower remained off following the high-

vacuum LNAPL removal event to evaluate LNAPL recovery under ambient conditions. The system was re-started on January 21, 2022, after obtaining LNAPL thickness measurements from OW-3, RW-1, and SB-5.

An annual site inspection was performed on June 2, 2022, to evaluate the continued effectiveness of the LNAPL Recovery system, and the results of the annual inspection are documented on the Annual Site-Wide Inspection Form (Appendix B). Overall, the annual inspection indicated that the LNAPL recovery system was performing as designed and appeared to be well-maintained.

SUB-SLAB DEPRESSURIZATION SYSTEM

The SSDS was operational during the reporting period. On August 24, October 14, and December 6, 2021, and February 28, April 4, and June 2, 2022, WSP inspected the SSDS to ensure its proper operation and obtained vacuum readings from SSDS extraction points (Table 2). On August 24, 2021 and February 28 and April 4, 2022, WSP collected vacuum measurements from the sub-slab vacuum monitoring points (Table 3). The completed SSDS inspection forms, including vacuum measurements, are provided in Appendix D. During the reporting period, system operating parameters were within normal operating ranges with the exception of the extraction point SSD-3, which required a fan replacement that occurred in April 2022.

An annual site inspection was performed on June 2, 2022, to evaluate the continued effectiveness of the SSDS, and the results of the annual inspection are documented on the Annual Site-Wide Inspection Form (Appendix B). The annual inspection indicated that the SSDS appeared in good condition and was operating as designed.

4.2 IC/EC CERTIFICATION

The IC/EC Certification Form is provided in Appendix E.

5 MONITORING PLAN COMPLIANCE REPORT

5.1 MONITORING PLAN COMPONENTS

Monitoring activities were completed during the reporting period in accordance with the SMP, with any exceptions discussed under Section 5.2. A summary of the monitoring program is presented below:

Monitoring Program	Frequency	Monitored
Site-wide Inspection	Annually	Overall Site Conditions, IC and EC Compliance, and Use of PCE-Containing Materials Within the Building
Absorbent Inspection/Replacement	Bi-monthly	OW-1, OW-2, OW-3, OW-4, OW-5, OW-8, OW-9, OW-10, OW-11, RW-1, RW-2, SB-5, SB-8
LNAPL Thickness Measurements	Semi-annually; 30 days after removal of absorbents	OW-1, OW-2, OW-3, OW-4, OW-5, OW-8, OW-9, OW-10, OW-11, RW-1, RW-2, SB-5, SB-7, SB-8, SB-10
SSDS Inspection and Vacuum Measurements on Extraction Points	Bi-monthly	SSDS extraction points SSD-01 through SSD-23; inspection of SSD Risers, Piping Network, and Discharge Fans
Vacuum Measurements on Sub-slab Vacuum Monitoring Points	Semi-annually	SS-1, SS-3, SS-10, SS-11, SS-12, SS-14, SS-15, SS-16, SS-17, MP-3, MP-10, MP-15, MP-19, MP-23, MP-30, MP-31, MP-32

5.2 MONITORING COMPLETED DURING REPORTING PERIOD

5.2.1 SITE-WIDE INSPECTION

As discussed under the IC/EC Compliance Report (Section 4 of this PRR), a site-wide inspection was performed on June 2, 2022, to verify compliance with the ICs and to evaluate the continued effectiveness of the ECs. The results of the annual inspection are described under Section 4.1 of this PRR and are documented on the Annual Site-Wide Inspection Form (Appendix B).

5.2.2 ABSORBENT INSPECTION AND REPLACEMENT

Site visits were performed on October 14 and December 6, 2021, and February 28 and June 2, 2022, to inspect and, if applicable, replace absorbents suspended in wells OW-1, OW-2, OW-3, OW-4, OW-5, OW-8, OW-9/FB-02, OW-10/FB-1, OW-11/FB-4, RW-1, RW-2, SB-5, and SB-8 (Appendix F). During each site visit, the absorbent socks exhibiting staining were weighed and placed in a 55-gallon steel drum for subsequent characterization and offsite disposal. New absorbent socks were installed in wells with evidence of LNAPL. In general, absorbent socks exhibiting no noticeable evidence of staining were returned to their respective well.

During the reporting period, no absorbents were placed in wells SB-7 and SB-10 because no product has been observed in these wells since at least December 2019. New absorbents will be placed in these wells if LNAPL is observed in the future. No absorbents were placed in any of the wells from June 10 to August 24, 2021, and from February 28 to April 4, 2022, to allow LNAPL to accumulate for approximately 30 days before collecting LNAPL thickness measurements. In addition, absorbents were removed from wells OW-3, RW-1, and SB-5 from December 6, 2021, to January 21, 2022, because these wells were part of the high-vacuum removal event that occurred in December 2021. Absorbents were left out of the wells until January 21, 2022, to evaluate LNAPL recovery following the high vacuum removal event.

To estimate the amount of LNAPL removed during the reporting period, the weight of each absorbent sock was recorded before installation and again when it is removed from the well for disposal. The weight of the new and spent absorbent socks are used to estimate the mass of LNAPL removed, which is then converted to volume using an assumed density for the LNAPL. In addition, the calculation assumes 20 percent of the increase in absorbent weight is water. Based on the weight of spent absorbents, approximately 5.4 gallons of LNAPL were removed from Site wells using absorbents during the reporting period. Field forms documenting the removal and replacement of absorbents are provided in Appendix F. In addition to removing LNAPL with absorbents, approximately 850-gallons of LNAPL-containing groundwater were also removed from select wells in December 2021 by applying a high vacuum to each well using a vacuum truck, air-tight cap, and drop tube.

5.2.3 LNAPL THICKNESS MONITORING

LNAPL thickness measurements were collected on August 24, 2021, and April 4, 2022. In August 2021, measurable LNAPL greater than the remedial objective (i.e., 0.01 foot) was detected in 10 of the 15 wells at thicknesses ranging from 0.03 foot in OW-9/FB-2 to greater than 1 foot in SB-5 (Figure 6; Tables 4 and 5). In April 2022, measurable LNAPL greater than the remedial objective was detected in 8 of the 15 wells at thicknesses ranging from 0.02 foot in OW-11/FB-4 and SB-8 to greater than 0.29 foot in SB-5 (Figure 6; Tables 4 and 5). The occurrence of the maximum LNAPL thickness in well SB-5 is consistent with historical data.

On January 21, 2022, LNAPL thickness measurements were collected from wells OW-3, RW-1, and SB-5 to evaluate the potential impact of the high-vacuum removal event performed in December 2021. LNAPL was measured at 0.08 foot in OW-3, and 0.02 foot in RW-1. No measurement could be collected from SB-5 because it was dry.

Graphs of LNAPL thickness versus time for select wells that have historically contained measurable LNAPL over consecutive occasions are provided in Appendix G. The graphs for OW-1, OW-2, OW-3, OW-5, and SB-5 start in May 2008 when the vacuum-enhanced LNAPL recovery system began operating. The graphs for OW-9/FB-2 and OW-10/FB-1 start in

March 2011 when the soil borings were installed to implement pneumatic fracturing and were later converted to observation wells in May 2016.

A Mann-Kendall analysis was conducted to evaluate the trend of LNAPL measurements collected in these select wells using the U.S. Environmental Protection Agency's *Statistical Software ProUCL 5.1.00 for Environmental Applications for Data Sets with and without Nondetect Observations* (October 2015). The Mann-Kendall analysis is a non-parametric (rank-based) procedure that tests for simple monotonic (i.e., single direction – increasing or decreasing) trends. The results of the Mann-Kendall analysis are provided in Appendix H and summarized below.

Well	Time Period	Trend of LNAPL Thickness
OW-1	May 2008 – April 2022	Increasing Trend
OW-2	May 2008 – April 2002	Decreasing Trend
OW-3	May 2008 – April 2022	No Trend
OW-5	May 2008 – April 2022	Decreasing Trend
OW-9/FB-2	March 2011 – April 2022	Decreasing Trend
OW-10/FB-1	March 2011 – April 2022	Decreasing Trend
SB-5	May 2008 – April 2022	No Trend

Based on the results of the Mann-Kendall trend analysis, the LNAPL thickness has decreased in four of the seven wells. The trend analysis of OW-1 indicates an increase in the LNAPL thickness since May 2008, and the trend analysis for OW-3 and SB-5 indicate no trend in LNAPL thickness since May 2008. The downward trend in the LNAPL thickness over time in most wells indicates that the current remedy is effective in removing LNAPL from the subsurface.

5.3 COMPARISONS WITH REMEDIAL OBJECTIVES

The remedial objective for the vacuum-enhanced LNAPL recovery system is the absence of measurable LNAPL (greater than 0.01 foot) in the heat treat area wells for a period of 12 consecutive months. During the reporting period, measurable product exceeding the remedial objective of 0.01 foot was present during at least one event in 10 of 15 wells at thicknesses ranging from 0.02 foot in OW-11/FB-4 and SB-8 to greater than 1 foot in SB-5. Four wells (i.e., OW-4, OW-10/FB-1, SB-7, and SB-10; Table 1) had no measurable product during the entire reporting period.

5.4 MONITORING DEFICIENCIES

No monitoring deficiencies were identified during the reporting period.

5.5 CONCLUSIONS AND RECOMMENDATIONS FOR CHANGES

Based on the monitoring completed during the reporting period, the absorbent inspection and replacement activities continue to be effective in removing LNAPL from the subsurface, and most wells continue to show a reduction in LNAPL thickness over time. The collection of LNAPL thickness measurements on a semi-annual basis is an appropriate frequency given that 11 wells continue to exhibit measurable LNAPL. Therefore, no changes are recommended to the monitoring plan. Absorbents will no longer be installed in wells SB-7 and SB-10 because no measurable product was observed in these wells since at least December 2019. New absorbents will be placed in these wells if LNAPL is observed in the future.

6 O&M PLAN COMPLIANCE REPORT

6.1 O&M PLAN COMPONENTS

6.1.1 LNAPL RECOVERY SYSTEM

The treatment system consists of a 30-gallon VLS, a vacuum blower, a 10-micron air filter, a dilution valve with 10-micron air filter, inlet and outlet vacuum gauges, and exhaust stack temperature and pressure gauges. O&M activities consist of the following:

Location	Monitor	Activity	Frequency
Before VLS	Vacuum	-	Bi-Monthly
Before Air Filter	Vacuum	-	Bi-monthly
Before Blower Inlet	Vacuum	-	Bi-monthly
Discharge Stack	Pressure	-	Bi-monthly
Discharge Stack	Temperature	-	Bi-monthly
RW-1	Vacuum, Flow	-	Bi-monthly
OW-2	Vacuum, Flow	-	Bi-monthly
OW-3	Vacuum, Flow	-	Bi-monthly
OW-8	Vacuum, Flow	-	Bi-monthly
Dilution Air Filter	-	Replace Filter	As needed
In-line Air Filter	-	Replace Filter	As needed
VLS	-	Remove Condensate	As needed
High-High Level Alarm	-	Test/Clean Switch	Annually, or more frequently if water is entrained
Equipment/Enclosure	-	Cleaning	Semi-annually
Blower Motor	-	Replace Bearings	25,000 hours, or when unusual vibrations are observed

6.1.2 SUB-SLAB DEPRESSURIZATION SYSTEM

The SSDS consists of a network of 23 SSD extraction points², organized into 19 distinct legs, each with a dedicated extraction fan and exhaust stack. In addition, there are 18 vacuum monitoring locations consisting of permanent vapor probes. O&M activities consist of the following:

Component	Monitor	Activity	Frequency
SSD Risers, Piping Network, Discharge Fans	Inspect	-	Bi-monthly
Extraction Points	Vacuum	-	Bi-monthly
Sub-slab Vacuum Monitoring Points	Vacuum	-	Semi-annually

² The fans associated with extraction points SSD-02, SSD-05, SSD-08, SSD-11, and SSD-20 were turned off during startup due to an insufficient flow to operate within the manufacturer's specifications, which could damage the fans.

Component	Monitor	Activity	Frequency
Digital Vacuum Gauges on Extraction Points	-	Replace 9V battery	Every 1.5 years
Combined Extraction Point Flow Balancing	-	Adjust butterfly valve positions to balance flow and measure resulting vacuum at the extraction points	Semi-annually
SSDS Fans	-	Replace Fans	As needed when observed to be inoperable
SSDS Vacuum Gauges	-	Replace Vacuum Gauges	As needed when observed to be inoperable
SSDS Piping, Fittings, Valves	-	Repair Piping, Fittings, and/or Valves	As needed when observed to be damaged
Bollards, Pallet Guards	-	Repair Bollards and/or Pallet Guards	As needed when observed to be damaged

6.2 O&M COMPLETED DURING REPORTING PERIOD

6.2.1 LNAPL RECOVERY SYSTEM

O&M visits were performed during the reporting period on August 24, October 14, and December 6, 2021, and February 28, April 4, and June 2, 2022, to ensure proper operation of the LNAPL recovery system. The LNAPL recovery system was operational during the reporting period except when it was turned off to perform maintenance and from December 6, 2021, to January 21, 2022, to perform a high-vacuum removal event and post-remediation LNAPL thickness monitoring. During each O&M visit, operating parameters associated with the treatment system equipment and recovery wells were recorded on an O&M checklist (Appendix C) and are summarized in Table 1.

System maintenance required during the reporting period included replacing the inline and dilution air filters, replacing the tubing for the vacuum measurements for OW-2, and rebalancing air flow from the LNAPL recovery wells. In addition, the manhole covers for wells SB-5 and OW-11/FB-9 were replaced.

6.2.2 SUB-SLAB DEPRESSURIZATION SYSTEM

O&M visits were performed during the reporting period on August 24, October 14, and December 6, 2021, and February 28, April 4, and June 2, 2022, to ensure proper operation of the SSDS. The completed SSDS inspection forms are provided in Appendix D. Vacuum measurements for the reporting period are summarized in Tables 2 and 3. On August 24, 2021, the batteries in the digital vacuum gauges on each SSDS extraction point were replaced. The fans associated with extraction points SSD-02, SSD-05, SSD-08, SSD-11, and SSD-20 were turned off during startup due to an insufficient flow to operate within the manufacturer's specifications, which could damage the fans. The inactive fan associated with SSD-20 was removed in April 2022 to replace an inoperable fan on extraction point SSD-03.

6.3 EVALUATION OF REMEDIAL SYSTEMS

6.3.1 LNAPL RECOVERY SYSTEM

The vacuum-enhanced LNAPL recovery system was operational on arrival for each site visit (except during the high-vacuum removal event and post-remediation LNAPL thickness monitoring). The operating parameters for the treatment system equipment and recovery wells were generally consistent with the optimal operating conditions specified in the O&M manual. Overall, the LNAPL recovery system operated as designed and continues to be effective.

6.3.2 SUB-SLAB DEPRESSURIZATION SYSTEM

The SSDS was operational on arrival for each site visit. The operating parameters for the SSDS were generally consistent with the optimal operating conditions specified in the O&M manual. Overall, the SSDS operated as designed.

6.4 O&M DEFICIENCIES

Minor deficiencies with respect to the O&M plan were documented during the reporting period; however, these deficiencies did not affect the overall performance of the systems.

6.5 CONCLUSIONS AND RECOMMENDATIONS FOR IMPROVEMENTS

During the reporting period, the LNAPL recovery system and SSDS operated as designed and continue to be effective. No recommendations for improvements are suggested at this time.

7 OVERALL PRR CONCLUSIONS AND RECOMMENDATIONS

7.1 COMPLIANCE WITH SMP

Based on the results of the annual site inspection and other data gathered during the reporting period, the requirements of the IC/EC, monitoring, and O&M plans were met.

7.2 PERFORMANCE AND EFFECTIVENESS OF REMEDY

Based on an evaluation of the information gathered during implementation of the SMP, the LNAPL recovery system and SSDS are performing as designed.

7.3 FUTURE PRR SUBMITTALS

The next PRR will be submitted in July 2023. No changes to the PRR reporting schedule are recommended at this time.

FIGURES



R:\Acad\CADD_CLIENTS\EMERSON\31401545\31401545.018-002.dwg 5/19/2022 10:51 AM USL01166



NOTES:

1. GOOGLE EARTH AERIAL PHOTOGRAPH, DATED 10/10/2019.
2. AERIAL PHOTOGRAPHS USED FOR THIS ILLUSTRATION CONTAIN INHERENT DISTORTIONS RESULTING FROM THE PHOTOGRAPHIC PROCESS THAT MAY RESULT IN SLIGHT MISALIGNMENTS WITH THE SURVEYED SITE FEATURES.

B THE ORIGINAL VERSION OF THIS DRAWING IS IN COLOR. BLACK AND WHITE COPIES MAY NOT ACCURATELY DEPICT CERTAIN INFORMATION.

- LEGEND**
- MW-04 MONITORING WELL
 - PROPERTY LINE AND INSTITUTIONAL CONTROL BOUNDARY
 - RAILROAD
 - EXISTING SANITARY SEWER




FIGURE 2

SITE LAYOUT

FORMER ROLLWAY BEARING CORPORATION FACILITY
LIVERPOOL, NEW YORK

PREPARED FOR
EMERSON
ST. LOUIS, MISSOURI

Drawn By: LS 5/19/2022
Checked:
Approved:
DWG Name: 314MN1545.018-002

WSP
WSP USA, Inc.
250 W. 34th STREET
4th FLOOR
NEW YORK, NY 10119
TEL: +1 212-465-5000

Y:\Shared\CAD\AutoCAD\CLIENTS\EMERSON\NY\Liverpool_Facility\CAD\314P1545.002\DWG\314P1545.002.DWG 5/18/2023 3:11 PM BEEG0102

D




Z:\Acad\CADD\ CLIENTS\EMERSON\NY-LIVERPOOL LIPE ROLLWAY FACILITY\314M0435-006.dwg 5/19/2022 3:23 PM USEC01012

B

THE ORIGINAL VERSION OF THIS DRAWING IS IN COLOR. BLACK AND WHITE COPIES MAY NOT ACCURATELY DEPICT CERTAIN INFORMATION.

NOTES:

1. GOOGLE EARTH AERIAL PHOTOGRAPH, DATED 05/28/2016.
2. AERIAL PHOTOGRAPHS USED FOR THIS ILLUSTRATION CONTAIN INHERENT DISTORTIONS RESULTING FROM THE PHOTOGRAPHIC PROCESS THAT MAY RESULT IN SLIGHT MISALIGNMENTS WITH THE SURVEYED SITE FEATURES.



LEGEND

- PROPERTY LINE AND INSTITUTIONAL CONTROL BOUNDARY
- ++++ RAILROAD
- EXISTING SANITARY SEWER
- /// COVER SYSTEM




FIGURE 5

COVER SYSTEM LOCATION

FORMER ROLLWAY BEARING CORPORATION FACILITY
LIVERPOOL, NEW YORK
PREPARED FOR
EMERSON
ST. LOUIS, MISSOURI


Drawn By: LS 8/7/2017

Checked:

Approved:

DWG Name: 314M0435-006

WSP USA, Inc.
250 W. 34TH STREET
4TH FLOOR
NEW YORK, NY 10119
TEL: +1 212.465.5000



REVISIONS

REV	DESCRIPTION	DATE
1	Initial Issue	05/10/2022
2	Revised	05/12/2022
3	Revised	05/12/2022
4	Revised	05/12/2022
5	Revised	05/12/2022

DRAWN BY

CHECKED

APPROVED

PROPERTY OF WSP USA INC.

IMPORTANT: THIS DRAWING IS THE PROPERTY OF WSP USA INC. AND IS NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN CONSENT OF WSP USA INC.

NOTICE: THIS DRAWING HAS BEEN PREPARED UNDER THE PROFESSIONAL SEAL AND SIGNATURE OF AN ENGINEER, ACTING IN COMPLIANCE WITH THE PROFESSIONAL ENGINEERING ACT AND REGULATIONS OF THE STATE OF MISSOURI. ANY VIOLATION OF THIS ACT IS A CRIMINAL OFFENSE UNDER THE LAWS OF THE STATE OF MISSOURI.

ENGINEER

DATE

LNAPL THICKNESS MEASUREMENTS

FORMER HEAT TREAT DEPARTMENT

FORMER ROLLWAY BEARING CORPORATION FACILITY

LIVERPOOL, NEW YORK

PREPARED FOR

EMERSON

ST. LOUIS, MISSOURI

WSP USA Inc.

250 W. 34th STREET, 4th FLOOR

NEW YORK, NY 10119

TEL: +1 212.465.5000

FIGURE 6

Drawing Number

314P1545.018-D20

TABLES



Table 1

LNAPL Recovery System Monitoring and Maintenance Summary
Former Rollway Bearing Corporation Facility
Liverpool, New York (a)

Date	LNAPL Recovery System Skid						LNAPL Recovery Wells								Notable Observations	System Maintenance	
	Vacuum Before Vapor-Liquid Separator ("WC)	Vacuum Before Air Filter ("WC)	Vacuum Before Blower Inlet ("WC)	Discharge Stack Pressure ("WC)	Discharge Stack Temperature (°F)	Kilowatt Hour Meter (kWh)	Vacuum ("WC)				Flow (scfm)					Description of Maintenance Needed	Date completed
							OW-2	RW-1	OW-3	OW-8	OW-2	RW-1	OW-3	OW-8			
Typical Reading:	-58 to -62	-66 to -68	-86	2	120 to 138	-	-40 to -54	-5 to -11	-6 to -10	-8 to -10	3 to 7	5.5 to 7	2 to 3	4 to 11			
08/24/21	-60	-68	-64	2	142	170,307	-1.67	-3.02	-1.40	-3.66	6.0	5.0	5.5	6.0	Some vacuum readings not within typical operating ranges; but, flow from recovery wells is uniform and, thus, no corrective action is recommended at this time.	N/A	N/A
10/14/21	-60	-69	-66	2	138	172,113	-2.38	-16.44	-7.28	-2.87	5.5	5.0	5.5	5.0	Some vacuum readings not within typical operating ranges; but, flow from recovery wells is uniform and, thus, no corrective action is recommended at this time.	N/A	N/A
12/06/21	-60	-68	-66	2	136	172,136	-2.46	-15.90	-7.33	-3.25	5.5	6.0	5.5	5.0	Some vacuum readings not within typical operating ranges; but, flow uniform; no corrective action recommended	N/A	N/A
02/28/22	-60	-66	-64	2	134	172,250	-3.10	-15.86	-7.18	-3.44	5.5	6.0	6.0	5.0	Some vacuum readings not within typical operating ranges; but, flow uniform; no corrective action recommended	N/A	N/A
04/04/22	-66	-74	-70	2	130	176,391	-3.26	-14.96	-7.09	-3.69	5.5	6.0	6.0	5.0	Some vacuum readings not within typical operating ranges; but, flow uniform; no corrective action recommended	N/A	N/A
06/02/22	-68	-76	-72	2	132	178,616	-15.20	-6.00	-7.30	-7.00	5.5	5.0	5.5	6.5	OW-2 and OW-8 vacuum readings not within typical operating ranges; but, flows are uniform and no corrective action recommended	Balance vacuum and flow at extraction wells and replace inline air particle filter	6/2/2022

a/ LNAPL = light non-aqueous phase liquid; °F = degrees Fahrenheit; "WC = inches of water column; kWh = kilowatt hour; scfm = standard cubic feet per minute; OW = observation well; RW = recovery well; N/A = not applicable.

Table 2

**SSDS Monitoring and Maintenance Summary
Former Rollway Bearing Corporation Facility
Liverpool, New York (a)**

SSDS Extraction Points	Vacuum (inches water column)					
Date:	8/24/2021	10/14/2021	12/6/2021	2/28/2022	4/4/2022	6/2/2022
SSD-01	-7.25	-7.85	-8.48	-8.66	-8.53	-7.65
SSD-02 (b)	-0.15	-0.48	-0.80	-0.81	-0.81	-0.45
SSD-03	-23.31	-24.04	-0.50	-0.25	-36.01	-35.00
SSD-04	-19.50	-20.78	-27.30	-27.14	-28.40	-19.90
SSD-05 (b)	-0.01	-0.19	-0.48	-0.64	-0.39	-0.53
SSD-06	-24.10	-25.32	-26.47	-26.14	-26.07	-23.88
SSD-07	-23.58	-23.61	-23.50	-24.02	-22.70	-22.39
SSD-08 (b)	-0.08	-0.41	-0.71	-0.89	-0.62	-0.44
SSD-09	-24.30	-25.08	-26.07	-25.94	-25.74	-24.80
SSD-10	-0.08	-0.41	-0.48	-0.56	-0.42	-0.38
SSD-11 (b)	-1.04	-1.54	-1.21	-1.28	-0.90	-0.87
SSD-12	-18.49	-19.01	-18.44	-18.91	-17.01	-0.42
SSD-13	-5.28	-5.44	-6.12	-6.02	-6.12	-5.55
SSD-14	-2.59	-3.03	-3.60	-3.89	-0.55	-3.07
SSD-15	-4.36	-4.58	-5.04	-5.96	-5.03	-4.65
SSD-16	-3.83	-4.20	-4.74	-4.02	-4.66	-4.36
SSD-17	-1.37	-1.09	-1.61	-2.01	-1.58	-1.16
SSD-18	-0.24	-20.45	-18.33	-19.12	-27.63	-24.88
SSD-19	-18.34	-19.66	-21.24	-20.99	-21.15	-0.20
SSD-20 (b)	-0.49	-1.02	-1.09	-1.06	-0.88	-0.81
SSD-21	-22.63	-23.87	-25.20	-25.02	-25.00	-23.49
SSD-22	-2.82	-3.17	-3.63	-4.11	-3.64	-3.33
SSD-23	-0.62	-1.31	-1.49	-1.80	-1.30	-1.01
Were flows adjusted?	No	No	No	No	No	No

a/ SSDS = sub-slab depressurization system; NM = not measured.

b/ Fan turned off because insufficient flow to operate within the manufacturer's specifications.

Table 3

**Summary of Measurements from SSDS Vacuum Monitoring Points
or Former Rollway Bearing Corporation Facility
Liverpool, New York (a)**

Vacuum Monitoring Points	Vacuum (inches water column)			
Date:	8/24/2021	10/14/2021	2/28/2022	4/4/2022
SS-1	(b)	-3.13	-3.66	NM
SS-3	-0.61	NM	-0.81	NM
SS-10	-1.4	NM	-0.86	NM
SS-11	-0.15	NM	-2.92	NM
SS-12	-1.3	NM	-1.01	NM
SS-14	-0.15	NM	-0.11	NM
SS-15	-1.43	NM	-1.04	NM
SS-16	-1.01	NM	-0.40	NM
SS-17	-0.22	NM	-0.66	NM
SS-18	-3.66	NM	-1.72	NM
MP-3	-0.42	NM	-0.3	NM
MP-10	-0.44	NM	-0.26	NM
MP-15	-0.45	NM	-0.09	NM
MP-19	-0.13	NM	-0.13	NM
MP-23	-0.75	NM	-0.70	NM
MP-30	-1.49	NM	-1.29	NM
MP-31	-1.96	NM	-0.80	NM
MP-32	(c)	(c)	(c)	-0.18

a/ SSDS = sub-slab depressurization system; NM = not measured.

b/ Vacuum monitoring point not accessible.

c/ Vacuum monitoring point inadvertently not measured.

Table 4

Summary of LNAPL Thickness Measurements - Recovery Wells and Observation Wells
Former Rollway Bearing Corporation Facility
Liverpool, New York (a,b)

Well ID	OW-2					RW-1					OW-3				
Casing Diameter (in)	2					4					2				
TOC Elevation (ft amsl)	445.88					446.13					445.91				
Modified TOC Elevation (ft amsl)	445.12					444.90					445.18				
Measurement Dates	Depth to Product (ft bTOC)	Depth to Water (ft bTOC)		Groundwater Elevation (ft amsl) (c)	Apparent Product Thickness (ft) (d)	Depth to Product (ft bTOC)	Depth to Water (ft bTOC)		Groundwater Elevation (ft amsl) (c)	Apparent Product Thickness (ft) (d)	Depth to Product (ft bTOC)	Depth to Water (ft bTOC)		Groundwater Elevation (ft amsl) (c)	Apparent Product Thickness (ft) (d)
		Measured	Corrected				Measured	Corrected				Measured	Corrected		
02/22/12	11.68	12.90	11.81	433.31	1.22	10.48	10.51	11.71	433.19	0.03	10.92	10.95	11.65	433.53	0.03
04/04/12	12.65	13.38	12.73	432.39	0.73	10.74	10.76	11.97	432.93	0.02	10.98	11.00	11.71	433.47	0.02
05/02/12	12.48	13.41	12.58	432.54	0.93	10.88	10.90	12.11	432.79	0.02	11.87	12.01	12.61	432.57	0.14
06/14/12	12.35	12.99	12.42	432.70	0.64	10.78	10.79	12.01	432.89	0.01	11.94	12.48	12.73	432.45	0.54
07/23/12	12.38	14.02	12.55	432.57	1.64	11.25	11.27	12.48	432.42	0.02	11.96	12.70	12.77	432.41	0.74
08/24/12	12.79	14.03	12.92	432.20	1.24	11.33	11.34	12.56	432.34	0.01	12.09	12.38	12.85	432.33	0.29
09/25/12	12.50	13.58	12.61	432.51	1.08	11.03	11.04	12.26	432.64	0.01	12.05	12.61	12.84	432.34	0.56
11/09/12	12.78	13.90	12.90	432.22	1.12	10.71	10.74	11.94	432.96	0.03	11.19	11.41	11.94	433.24	0.22
12/12/12	12.36	13.32	12.46	432.66	0.96	10.78	10.86	12.02	432.88	0.08	11.23	11.60	12.00	433.18	0.37
01/24/13	12.47	13.49	12.57	432.55	1.02	10.70	10.74	11.93	432.97	0.04	NM	10.73	10.73	434.45	0.0
03/07/13	11.60	12.39	11.68	433.44	0.79	10.44	10.47	11.67	433.23	0.03	NM	10.66	10.66	434.52	0.0
04/22/13	12.06	13.49	12.21	432.91	1.43	11.43	11.46	12.66	432.24	0.03	NM	10.71	10.71	434.47	0.0
05/30/13	11.83	13.55	12.01	433.11	1.72	11.62	12.65	12.96	431.94	1.03	12.07	12.11	12.80	432.38	0.04
07/18/13	12.08	12.21	12.09	433.03	0.13	11.60	11.71	12.84	432.06	0.11	11.85	12.59	12.66	432.52	0.74
08/26/13	NM	11.80	11.80	433.32	0.0	11.71	11.85	12.95	431.95	0.14	11.91	12.04	12.65	432.53	0.13
10/21/13	11.60	11.61	11.60	433.52	0.01	12.51	12.73	13.76	431.14	0.22	11.82	11.91	12.56	432.62	0.09
11/25/13	11.60	11.73	11.61	433.51	0.13	11.91	11.98	13.15	431.75	0.07	11.90	12.00	12.64	432.54	0.10
12/30/13	11.50	11.53	11.50	433.62	0.03	11.38	11.45	12.62	432.28	0.07	11.30	11.53	12.05	433.13	0.23
01/31/14	NM	12.38	12.38	432.74	0.0	11.60	11.65	12.84	432.06	0.05	11.95	11.98	12.68	432.50	0.03
02/26/14	Inaccessible					11.15	11.23	12.39	432.51	0.08	10.61	10.66	11.35	433.83	0.05
03/31/14	11.50	11.54	11.50	433.62	0.04	11.14	11.19	12.38	432.52	0.05	10.50	10.56	11.24	433.94	0.06
04/24/14 (h)	10.05	10.14	10.06	435.06	0.09	10.64	10.65	11.87	433.03	0.01	10.70	10.75	11.44	433.74	0.05
08/26/14	NM	10.64	10.64	434.48	0.0	11.23	11.35	12.47	432.43	0.12	10.64	10.69	11.38	433.80	0.05
03/17/15	9.89	9.97	9.90	435.22	0.08	NM	10.43	10.43	434.47	0.0	NM	10.53	10.53	434.65	0.0
04/20/15	-	-	-	-	0.0	-	-	-	-	0.0	-	-	-	-	-
10/20/15	10.72	10.75	10.72	434.40	0.03	NM	10.76	10.76	434.14	0.0	NM	10.64	10.64	434.54	0.0
05/25/16	10.40	10.43	10.40	434.72	0.03	11.04	11.06	12.27	432.63	0.02	11.81	11.87	11.82	433.36	0.06
12/16/16	10.31	10.33	10.31	434.81	0.02	NM	10.69	10.69	434.21	0.0	10.90	10.91	10.90	434.28	0.01
07/06/17	NM	10.27	10.27	434.85	0.0	NM	10.80	10.80	434.10	0.0	NM	10.53	10.53	434.65	0.0
02/15/18	NM	10.52	10.52	434.60	0.0	NM	10.98	10.98	433.92	0.0	11.48	11.54	11.49	433.69	0.06
09/28/18	10.27	10.28	10.27	434.85	0.01	NM	10.82	10.82	434.08	0.0	11.60	11.62	11.60	433.58	0.02
04/29/19	10.24	10.26	10.24	434.86	0.02	NM	10.45	10.45	434.45	0.0	11.70	11.85	11.72	433.33	0.15
12/04/19	13.86	13.97	13.87	431.25	0.11	11.53	11.59	12.77	432.13	0.06	11.82	11.91	11.83	433.35	0.09
01/23/20	13.63	13.95	13.66	431.46	0.32	Not Measured for this Event					12.52	12.56	12.52	432.66	0.04
07/30/20	13.36	13.44	13.37	431.75	0.08	11.63	11.70	12.87	432.03	0.07	11.93	12.04	11.94	433.24	0.11
09/24/20	Not measured for this Event					Not measured for this Event					Not measured for this Event				
02/22/21	11.21	11.26	11.22	433.90	0.05	11.54	11.63	12.78	432.12	0.09	11.47	12.00	11.52	433.66	0.53
03/12/21	Not measured for this Event					Not measured for this Event					Not measured for this Event				
08/24/21	11.36	11.55	11.38	433.74	0.19	11.25	11.40	12.50	432.40	0.15	11.52	11.86	11.55	433.63	0.34
01/21/22	Not measured for this Event					11.61	11.63	12.84	432.06	0.02	11.91	11.99	11.92	433.26	0.08
04/04/22	12.06	12.12	12.07	433.05	0.06	12.59	12.63	13.82	431.08	0.04	11.96	12.00	11.96	433.22	0.04

Table 4

Summary of LNAPL Thickness Measurements - Recovery Wells and Observation Wells
Former Rollway Bearing Corporation Facility
Liverpool, New York (a,b)

Well ID	OW-8					SB-1				SB-3				SB-4						
Casing Diameter (in)	4					1				1				1						
TOC Elevation (ft amsl)	446.01					446.15				446.12				446.26						
Modified TOC Elevation (ft amsl)	444.91					-				-				-						
Measurement Dates	Depth to Product (ft bTOC)	Depth to Water (ft bTOC)		Groundwater Elevation (ft amsl) (c)	Apparent Product Thickness (ft) (d)	Depth to Product (ft bTOC)	Depth to Water (ft bTOC)		Groundwater Elevation (ft amsl)	Apparent Product Thickness (ft) (d)	Depth to Product (ft bTOC)	Depth to Water (ft bTOC)		Groundwater Elevation (ft amsl)	Apparent Product Thickness (ft) (d)	Depth to Product (ft bTOC)	Depth to Water (ft bTOC)		Groundwater Elevation (ft amsl)	Apparent Product Thickness (ft) (d)
		Measured	Corrected				Measured	Corrected				Measured	Corrected				Measured	Corrected		
02/22/12	12.12	12.28	13.24	431.67	0.16	Abandoned					NM	10.50	10.50	435.62	0.0	Abandoned				
04/04/12	12.12	12.24	13.23	431.68	0.12		NM	10.50	10.50	435.62	0.0									
05/02/12	12.19	12.25	13.30	431.61	0.06		NM	10.51	10.51	435.61	0.0									
06/14/12	12.20	12.30	13.31	431.60	0.10		Inaccessible													
07/23/12	12.20	12.42	13.32	431.59	0.22															
08/24/12	13.58	13.60	14.68	430.23	0.02															
09/25/12	12.34	12.44	13.45	431.46	0.10		NM	10.55	10.55	435.57	0.0									
11/09/12	12.15	14.50	13.49	431.42	2.35		NM	10.51	10.51	435.61	0.0									
12/12/12	12.20	12.64	13.35	431.56	0.44		NM	10.62	10.62	435.50	0.0									
01/24/13	12.10	12.25	13.22	431.69	0.15		No longer measured													
03/07/13	11.86	11.90	12.96	431.95	0.04															
04/22/13	11.70	11.75	12.81	432.10	0.05															
05/30/13	12.23	12.33	13.34	431.57	0.10															
07/18/13	12.21	12.59	13.35	431.56	0.38															
08/26/13	12.30	12.36	13.41	431.50	0.06															
10/21/13	12.35	12.42	13.46	431.45	0.07															
11/25/13	12.57	12.65	13.68	431.23	0.08															
12/30/13	12.37	12.50	13.48	431.43	0.13															
01/31/14	12.36	12.49	13.47	431.44	0.13															
02/26/14	13.31	13.53	14.43	430.48	0.22															
03/31/14	11.89	12.00	13.00	431.91	0.11															
04/24/14 (h)	12.03	12.05	13.13	431.78	0.02															
08/26/14	12.17	12.20	13.27	431.64	0.03															
03/17/15	12.06	12.09	12.06	432.85	0.03															
04/20/15	-	-	-	-	-															
10/20/15	NM	11.80	11.80	433.11	0.0															
05/25/16	10.05	10.06	10.05	434.86	0.01															
12/16/16	NM	11.66	11.66	433.25	0.0															
07/06/17	NM	11.57	11.57	433.34	0.0															
02/15/18	11.38	11.39	11.38	433.53	0.01															
09/28/18	NM	11.30	11.30	433.61	0.0															
04/29/19	NM	11.22	11.22	433.69	0.0															
12/04/19	11.80	11.82	11.80	433.11	0.02															
01/23/20	Not Measured for this Event																			
07/30/20	NM	12.93	12.93	431.98	0.0															
09/24/20	NM	12.93	12.93	431.98	0.0															
02/22/21	NM	12.68	12.68	432.23	0.0															
03/12/21	Not measured for this Event																			
08/24/21	12.40	12.56	12.42	432.49	0.16															
01/21/22	Not measured for this Event																			
04/04/22	NM	13.01	13.01	431.90	0.0															

Table 4

Summary of LNAPL Thickness Measurements - Recovery Wells and Observation Wells
Former Rollway Bearing Corporation Facility
Liverpool, New York (a,b)

Well ID	SB-5					SB-7					SB-8					SB-9					
Casing Diameter (in)	1					1					1					1					
TOC Elevation (ft amsl)	446.04					446.05					446.19					446.13					
Modified TOC Elevation (ft amsl)	446.12					446.13					446.25					446.17					
Measurement Dates	Depth to Product (ft bTOC)	Depth to Water (ft bTOC)		Groundwater Elevation (ft amsl) (e)	Apparent Product Thickness (ft) (d)	Depth to Product (ft bTOC)	Depth to Water (ft bTOC)		Groundwater Elevation (ft amsl) (e)	Apparent Product Thickness (ft) (d)	Depth to Product (ft bTOC)	Depth to Water (ft bTOC)		Groundwater Elevation (ft amsl) (e)	Apparent Product Thickness (ft) (d)	Depth to Product (ft bTOC)	Depth to Water (ft bTOC)		Groundwater Elevation (ft amsl) (e)	Apparent Product Thickness (ft) (d)	
		Measured	Corrected				Measured	Corrected				Measured	Corrected				Measured	Corrected			
02/22/12	13.76	13.82	13.69	432.43	0.06	NM	12.60	12.60	433.53	0.0	13.91	13.92	13.91	432.34	0.01	NM	13.15	13.15	433.02	0.0	
04/04/12	13.77	13.90	13.70	432.42	0.13	NM	12.85	12.85	433.28	0.0	13.87	13.89	13.87	432.38	0.02	NM	13.08	13.08	433.09	0.0	
05/02/12	13.87	13.92	13.80	432.32	0.05	NM	12.75	12.75	433.38	0.0	NM	13.97	13.97	432.28	0.0	NM	13.17	13.17	433.00	0.0	
06/14/12	13.85	14.15	13.80	432.32	0.30	Inaccessible					NM	13.70	13.70	432.55	0.0	NM	13.15	13.15	433.02	0.0	
07/23/12	13.71	13.90	13.65	432.47	0.19	12.97	12.98	12.97	433.16	0.01	NM	13.98	13.98	432.27	0.0	NM	13.15	13.15	433.02	0.0	
08/24/12	13.88	13.91	13.80	432.32	0.03	12.92	12.93	12.92	433.21	0.01	NM	13.97	13.97	432.28	0.0	NM	13.16	13.16	433.01	0.0	
09/25/12	13.87	13.90	13.79	432.33	0.03	12.89	12.90	12.89	433.24	0.01	13.96	13.97	13.96	432.29	0.01	NM	13.17	13.17	433.00	0.0	
11/09/12	13.78	13.95	13.72	432.40	0.17	12.75	12.88	12.76	433.37	0.13	13.87	13.95	13.88	432.37	0.08	NM	12.12	12.12	434.05	0.0	
12/12/12	13.71	13.93	13.65	432.47	0.22	12.68	12.75	12.69	433.44	0.07	NM	13.86	14.86	432.36	0.0	NM	13.32	13.32	432.85	0.0	
01/24/13	13.29	13.64	13.25	432.87	0.35	12.68	12.79	12.69	433.44	0.11	13.38	13.45	14.86	432.36	0.07	No longer measured					
03/07/13	13.15	13.37	13.09	433.03	0.22	NM	12.79	12.79	433.34	0.0	13.28	13.33	13.29	432.96	0.05						
04/22/13	13.16	13.24	13.09	433.03	0.08	NM	12.28	12.28	433.85	0.0	13.30	13.33	13.30	432.95	0.03						
05/30/13	13.48	13.75	13.43	432.69	0.27	NM	12.30	12.30	433.83	0.0	13.57	14.00	13.61	432.64	0.43						
07/18/13	13.50	13.50	13.42	432.70	0.00	NM	12.87	12.87	433.26	0.0	14.71	14.91	14.73	431.52	0.20						
08/26/13	13.78	13.90	13.71	432.41	0.12	NM	12.89	12.89	433.24	0.0	13.82	13.95	13.83	432.42	0.13						
10/21/13	13.91	13.94	13.83	432.29	0.03	NM	12.90	12.90	433.23	0.0	14.00	14.01	14.00	432.25	0.01						
11/25/13	13.85	13.89	13.77	432.35	0.04	NM	12.73	12.73	433.40	0.0	DRY	DRY	DRY	-	0.0						
12/30/13	13.10	13.14	13.02	433.10	0.04	NM	12.65	12.65	433.48	0.0	DRY	DRY	DRY	-	0.0						
01/31/14	13.75	13.81	13.68	432.44	0.06	NM	12.53	12.53	433.60	0.0	DRY	DRY	DRY	-	0.0						
02/26/14	13.70	13.80	13.63	432.49	0.10	NM	12.47	12.47	433.66	0.0	Inaccessible										
03/31/14	13.15	13.25	13.08	433.04	0.10	NM	11.20	11.20	434.93	0.0	13.27	13.35	13.28	432.97	0.08						
04/24/14 (h)	13.33	13.50	13.27	432.85	0.17	NM	12.62	12.62	433.51	0.0	13.45	13.65	13.47	432.78	0.20						
08/26/14	13.38	13.70	13.33	432.79	0.32	NM	12.54	12.54	433.59	0.0	13.56	13.66	13.57	432.68	0.10						
03/17/15	13.51	13.82	13.54	431.58	0.31	NM	11.60	11.60	433.52	0.0	13.49	13.61	13.50	432.75	0.12						
04/20/15	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
10/20/15	13.20	13.67	13.25	431.87	0.47	NM	12.33	12.33	432.79	0.0	13.31	13.33	13.31	432.94	0.02						
05/25/16	13.31	13.84	13.36	431.76	0.53	NM	12.18	12.18	432.94	0.0	NM	12.38	12.38	433.87	0.0						
12/16/16	13.11	13.37	13.14	431.98	0.26	NM	12.24	12.24	432.88	0.0	NM	13.08	13.08	433.17	0.0						
07/06/17	13.00	13.25	13.03	432.09	0.25	NM	11.79	11.79	433.33	0.0	NM	12.80	12.80	433.45	0.0						
02/15/18	12.98	13.08	12.99	432.13	0.10	NM	12.66	12.66	432.46	0.0	NM	12.68	12.68	433.57	0.0						
09/28/18	13.18	14.05	13.27	431.85	0.87	NM	11.70	11.70	433.42	0.0	NM	13.80	13.80	432.45	0.0						
04/29/19	13.60	13.98	13.64	431.48	0.38	NM	12.21	12.21	432.91	0.0	NM	12.92	12.92	433.33	0.00						
12/04/19	13.58	13.77	13.60	431.52	0.19	12.09	12.09	12.09	433.03	0.0	NM	16.65	16.65	429.60	0.0						
01/23/20	13.68	14.05	13.72	431.40	0.37	Not Measured for this Event					Not Measured for this Event										
07/30/20	13.78	14.60	13.86	431.26	0.82	NM	12.15	12.15	432.97	0.0	13.86	13.89	13.86	432.39	0.03						
09/24/20	Not measured for this Event					NM	12.91	12.91	432.21	0.0	Not measured for this Event										
02/22/21	13.90	13.92	13.90	431.22	0.02	NM	14.06	14.06	431.06	0.0	Not measured for this Event										
03/12/21	Not Measured for this Event					Not Measured for this Event					NM	13.91	13.91	432.34	0.0						
08/24/21	13.07	14.09		445.12	1.02	NM	14.60	14.60	430.52	0.0	14.10	14.50	14.50	431.75	0.40						
01/21/22	Not Measured for this Event					Not Measured for this Event					Not Measured for this Event										
04/04/22	13.80	14.09		445.12	0.29	NM	14.11	14.11	431.01	0.0	13.86	13.88	14.50	431.75	0.02						

Table 4

Summary of LNAPL Thickness Measurements - Recovery Wells and Observation Wells
Former Rollway Bearing Corporation Facility
Liverpool, New York (a,b)

Well ID	SB-10					OW-1					OW-4					OW-5				
Casing Diameter (in)	1					2					2					4				
TOC Elevation (ft amsl)	446.16					446.03					446.12					446.13				
Modified TOC Elevation (ft amsl)	446.24					-					-					-				
Measurement Dates	Depth to Product (ft bTOC)	Depth to Water (ft bTOC)		Groundwater Elevation (ft amsl) (e)	Apparent Product Thickness (ft) (d)	Depth to Product (ft bTOC)	Depth to Water (ft bTOC)		Groundwater Elevation (ft amsl)	Apparent Product Thickness (ft) (d)	Depth to Product (ft bTOC)	Depth to Water (ft bTOC)		Groundwater Elevation (ft amsl)	Apparent Product Thickness (ft) (d)	Depth to Product (ft bTOC)	Depth to Water (ft bTOC)		Groundwater Elevation (ft amsl)	Apparent Product Thickness (ft) (d)
		Measured	Corrected				Measured	Corrected				Measured	Corrected				Measured	Corrected		
02/22/12	17.58	17.60	17.58	428.66	0.02	NM	16.37	16.37	429.66	0.0	NM	13.74	13.74	432.38	0.0	12.54	12.72	12.56	433.57	0.18
04/04/12	Dry	Dry	Dry	-	-	16.37	16.45	16.38	429.65	0.08	NM	13.82	13.82	432.30	0.0	12.56	12.71	12.58	433.55	0.15
05/02/12	Dry	Dry	Dry	-	-	16.37	16.42	16.38	429.65	0.05	NM	13.98	13.98	432.14	0.0	12.66	12.79	12.67	433.46	0.13
06/14/12	NM	17.61	-	-	0.0	16.40	16.45	16.41	429.62	0.05	NM	13.94	13.94	432.18	0.0	12.74	12.90	12.76	433.37	0.16
07/23/12	Dry	Dry	Dry	-	-	16.30	16.32	16.30	429.73	0.02	NM	14.20	14.20	431.92	0.0	12.80	12.90	12.81	433.32	0.10
08/24/12	Dry	Dry	Dry	-	-	16.50	16.56	16.51	429.52	0.06	NM	14.36	14.36	431.76	0.0	12.87	13.04	12.89	433.24	0.17
09/25/12	Dry	Dry	Dry	-	-	16.52	16.58	16.53	429.50	0.06	14.35	14.36	14.35	431.77	0.01	Inaccessible				
11/09/12	Dry	Dry	Dry	-	-	16.50	16.67	16.52	429.51	0.17	14.17	14.20	14.17	431.95	0.03	12.58	12.65	12.59	433.54	0.07
12/12/12	Dry	Dry	Dry	-	-	16.34	16.51	16.36	429.67	0.17	NM	14.35	14.35	431.77	0.0	12.71	12.78	12.72	433.41	0.07
01/24/13	Dry	Dry	Dry	-	-	16.25	16.34	16.26	429.77	0.09	13.95	14.10	13.97	432.15	0.15	12.65	12.79	12.66	433.47	0.14
03/07/13	Dry	Dry	Dry	-	-	15.52	15.76	15.54	430.49	0.24	ND	14.10	14.10	432.02	0.0	13.06	13.39	13.09	433.04	0.33
04/22/13	Dry	Dry	Dry	-	-	15.92	16.00	15.93	430.10	0.08	14.94	14.96	14.94	431.18	0.02	13.07	13.10	13.07	433.06	0.03
05/30/13	Dry	Dry	Dry	-	-	16.36	16.60	16.38	429.65	0.24	NM	16.39	16.39	429.73	0.0	12.89	12.92	12.89	433.24	0.03
07/18/13	Dry	Dry	Dry	-	-	16.00	16.45	16.05	429.98	0.45	NM	14.40	14.40	431.72	0.0	12.71	12.96	12.74	433.39	0.25
08/26/13	Dry	Dry	Dry	-	-	16.58	16.75	16.60	429.43	0.17	NM	16.10	16.10	430.02	0.0	12.73	12.85	12.74	433.39	0.12
10/21/13	Dry	Dry	Dry	-	-	16.10	16.19	16.11	429.92	0.09	14.90	14.91	14.90	431.22	0.01	12.57	12.61	12.57	433.56	0.04
11/25/13	Dry	Dry	Dry	-	-	16.40	16.43	16.40	429.63	0.03	NM	16.10	16.10	430.02	0.0	12.96	13.00	12.96	433.17	0.04
12/30/13	Dry	Dry	Dry	-	-	15.15	15.20	15.16	430.87	0.05	NM	15.05	15.05	431.07	0.0	12.55	12.70	12.57	433.56	0.15
01/31/14	NM	17.30	17.30	428.94	0.0	16.16	16.25	16.17	429.86	0.09	NM	12.00	12.00	434.12	0.0	12.70	12.73	12.70	433.43	0.03
02/26/14	NM	17.40	17.40	428.84	0.0	15.48	15.51	15.48	430.55	0.03	NM	15.51	15.51	430.61	0.0	Inaccessible				
03/31/14	NM	17.56	17.56	428.68	0.0	15.10	15.14	15.10	430.93	0.04	NM	14.24	14.24	431.88	0.0	12.26	12.30	12.26	433.87	0.04
04/24/14 (h)	NM	Dry	Dry	-	-	15.17	15.27	15.18	430.85	0.10	NM	14.30	14.30	431.82	0.0	12.55	12.58	12.55	433.58	0.03
08/26/14	NM	Dry	Dry	-	-	15.16	15.31	15.18	430.85	0.15	NM	15.17	15.17	430.95	0.0	12.50	12.62	12.51	433.62	0.12
03/17/15	Inaccessible					NM	15.46	15.46	429.66	0.0	NM	14.15	14.15	431.97	0.0	12.53	12.54	12.53	433.60	0.01
04/20/15	NM	17.60	17.60	428.64	0.0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	0.0
10/20/15	NM	17.27	17.27	428.97	0.0	15.19	15.21	15.19	430.84	0.02	NM	13.93	13.93	432.19	0.0	NM	12.52	12.52	433.61	0.0
05/25/16	NM	16.47	16.47	429.77	0.0	15.16	15.22	15.17	430.86	0.06	NM	12.96	12.96	433.16	0.0	12.64	12.66	12.64	433.49	0.02
12/16/16	NM	17.04	17.04	429.20	0.0	15.82	15.88	15.83	430.20	0.06	NM	13.46	13.46	432.66	0.0	12.54	12.67	12.55	433.58	0.13
07/06/17	NM	17.25	17.25	428.99	0.0	15.78	15.81	15.78	430.25	0.03	NM	13.42	13.42	432.70	0.0	12.47	12.48	12.47	433.66	0.01
02/15/18	NM	16.98	16.98	429.26	0.0	14.38	14.42	14.38	431.65	0.04	NM	13.88	13.88	432.24	0.0	NM	12.42	12.42	433.71	0.0
09/28/18	NM	16.84	16.84	429.40	0.0	15.68	15.70	15.68	430.35	0.02	NM	13.97	13.97	432.15	0.0	12.55	12.57	12.55	433.58	0.02
04/29/19	NM	16.95	16.95	429.29	0.0	15.57	15.59	15.57	430.46	0.02	NM	12.04	12.04	434.08	0.0	12.65	12.68	12.65	433.48	0.03
12/04/19	16.58	16.59	16.58	429.66	0.01	15.22	15.25	15.22	430.81	0.03	14.08	14.08	14.08	432.04	0.0	12.78	12.81	12.78	433.35	0.03
01/23/20	Not Measured for this Event					16.25	16.56	16.28	429.75	0.31	Not Measured for this Event					13.20	13.22	13.20	432.93	0.02
07/30/20	NM	16.20	16.20	430.04	0.0	12.89	13.11	12.91	433.12	0.22	NM	16.65	16.65	429.47	0.0	12.88	12.91	12.88	433.25	0.03
09/24/20	NM	12.91	12.91	433.33	0.0	Not measured for this Event					15.61	15.64	15.61	430.51	0.03	Not measured for this Event				
02/22/21	NM	16.28	16.28	429.96	0.0	NM	12.73	12.73	433.30	0.0	Not Accessible					12.72	13.01	12.75	433.38	0.29
03/12/21	Not measured for this Event					Not measured for this Event					NM	16.59	16.59	429.53	0.0	Not measured for this Event				
08/24/21	NM	15.02	15.02	431.22	0.0	12.39	12.46	12.40	433.63	0.07	NM	15.60	15.60	430.52	0.0	12.51	12.59	12.52	433.61	0.08
01/21/22	Not measured for this Event					Not measured for this Event					Not measured for this Event					Not measured for this Event				
04/04/22	NM	16.26	16.26	429.98	0.0	NM	13.11	13.11	432.92	0.0	NM	13.06	13.06	433.06	0.0	13.07	13.10	13.07	433.06	0.03

Table 4

Summary of LNAPL Thickness Measurements - Recovery Wells and Observation Wells
Former Rollway Bearing Corporation Facility
Liverpool, New York (a,b)

Well ID	OW-6					OW-7					MW-4					RW-2				
Casing Diameter (in)	2					2					2					4				
TOC Elevation (ft amsl)	445.93					446.18					447.98					445.91				
Modified TOC Elevation (ft amsl)	-										445.56					-				
Measurement Dates	Depth to Product (ft bTOC)	Depth to Water (ft bTOC)		Groundwater Elevation (ft amsl)	Apparent Product Thickness (ft) (d)	Depth to Product (ft bTOC)	Depth to Water (ft bTOC)		Groundwater Elevation (ft amsl)	Apparent Product Thickness (ft) (d)	Depth to Product (ft bTOC)	Depth to Water (ft bTOC)		Groundwater Elevation (ft amsl)	Apparent Product Thickness (ft) (d)	Depth to Product (ft bTOC)	Depth to Water (ft bTOC)		Groundwater Elevation (ft amsl)	Apparent Product Thickness (ft) (d)
		Measured	Corrected				Measured	Corrected				Measured	Corrected				Measured	Corrected		
02/22/12	NM	16.87	16.87	429.06	0.0	Dry	Dry	Dry	-	NA	15.87	15.88	15.87	429.69	0.01	NM	13.22	13.22	432.69	0.0
04/04/12	NM	16.87	16.87	429.06	0.0	Dry	Dry	Dry	-	NA	NM	15.89	15.89	429.67	0.0	NM	13.73	13.73	432.18	0.0
05/02/12	NM	16.87	16.87	429.06	0.0	Dry	Dry	Dry	-	NA	16.01	16.02	16.01	429.55	0.01	NM	14.02	14.02	431.89	0.0
06/14/12	NM	16.88	16.88	429.05	0.0	Dry	Dry	Dry	-	NA	15.80	15.81	15.80	429.76	0.01	NM	14.04	14.04	431.87	0.0
07/23/12	NM	16.88	16.88	429.05	0.0	Dry	Dry	Dry	-	NA	15.99	16.00	15.99	429.57	0.01	NM	14.03	14.03	431.88	0.0
08/24/12	NM	16.87	16.87	429.06	0.0	Dry	Dry	Dry	-	NA	16.07	16.08	16.07	429.49	0.01	NM	14.02	14.02	431.89	0.0
09/25/12	NM	16.85	16.85	429.08	0.0	Dry	Dry	Dry	-	NA	16.16	16.17	16.16	429.40	0.01	NM	14.02	14.02	431.89	0.0
11/09/12	NM	16.80	16.80	429.13	0.0	Dry	Dry	Dry	-	NA	NM	16.02	16.02	429.54	0.0	13.82	13.85	13.82	432.09	0.03
12/12/12	NM	16.87	16.87	429.06	0.0	Dry	Dry	Dry	-	NA	16.05	16.29	16.07	429.49	0.24	13.42	13.45	13.42	432.49	0.03
01/24/13	No longer measured	No longer measured				No longer measured					Inaccessible					NM	13.00	13.00	432.91	0.0
03/07/13											15.61	15.64	15.61	429.95	0.03	NM	12.35	12.35	433.56	0.0
04/22/13											15.73	15.77	15.73	429.83	0.04	NM	15.77	15.77	430.14	0.0
05/30/13											15.96	15.97	15.96	429.60	0.01	NM	13.10	13.10	432.81	0.0
07/18/13											NM	15.79	15.79	429.77	0.0	NM	13.78	13.78	432.13	0.0
08/26/13											NM	16.02	16.02	429.54	0.0	NM	13.90	13.90	432.01	0.0
10/21/13											15.90	15.91	15.90	429.66	0.01	NM	13.80	13.80	432.11	0.0
11/25/13											Inaccessible					NM	13.55	13.55	432.36	0.0
12/30/13											Inaccessible					NM	12.75	12.75	433.16	0.0
01/31/14											Inaccessible					NM	13.55	13.55	432.36	0.0
02/26/14											Inaccessible					NM	12.90	12.90	433.01	0.0
03/31/14											Inaccessible					NM	10.97	10.97	434.94	0.0
04/24/14 (h)											15.26	15.44	15.28	430.63	0.18	NM	13.20	13.20	432.71	0.0
08/26/14											NM	15.45	15.45	430.46	0.0	NM	13.09	13.09	432.82	0.0
03/17/15											Inaccessible					NM	13.31	13.31	432.60	0.0
04/20/15											NM	15.62	15.62	430.29	0.0	-	-	-	-	0.0
10/20/15											NM	15.78	15.78	430.13	0.0	NM	13.52	13.52	432.39	0.0
05/25/16											Damaged					NM	12.98	12.98	432.93	0.0
12/16/16																NM	13.05	13.05	432.86	0.0
07/06/17																NM	12.90	12.90	433.01	0.0
02/15/18																NM	12.73	12.73	433.18	0.0
09/28/18																NM	12.96	12.96	432.95	0.0
04/29/19																NM	13.20	13.20	432.71	0.0
12/04/19																12.62	12.62	12.62	433.29	0.0
01/23/20																Not Measured for this Event				
07/30/20																NM	12.70	12.70	433.21	0.0
09/24/20																14.01	14.20	14.03	431.88	0.19
02/22/21																13.96	13.98	13.96	431.95	0.02
03/12/21																Not Measured for this Event				
08/24/21																NM	11.90	11.90	434.01	0.0
01/21/22																Not Measured for this Event				
04/04/22																14.06	14.07	14.06	431.85	0.01

Table 4

Summary of LNAPL Thickness Measurements - Recovery Wells and Observation Wells
Former Rollway Bearing Corporation Facility
Liverpool, New York (a,b)

a/ LNAPL = light non-aqueous phase liquid; in = inches; ft = feet; bTOC = below top of casing; amsl = above mean sea level; NM = no measurable product detected in the well;
"-" = measurement was not collected.

b/ All depth to water measurements were corrected to account for the depression caused by the weight of the LNAPL. For correction of the depth to water, the LNAPL specific gravity was assumed to be equivalent NOCO Quench 1000 (0.8972), which was used in the Former Heat Treat Area at the time site operations ceased.

c/ OW-2, OW-3, OW-8, and RW-1 were cut below grade during installation of the vacuum recovery system (the casing elevations were lowered).

d/ Bolded concentration in shaded cell are LNAPL thickness measurements that exceed the remedial action objective of 0.01 foot.

e/ A PVC coupler was glued onto the top of SB-5, SB-7, SB-8, SB-9, and SB-10 prior to the pneumatic fracturing to allow for installation of a threaded plug (the casing elevations were raised).


f/ Depth to water and depth to product measurements are assumed to be inaccurate due to emulsified water and product inside of OW-5 during the 9/3/2008 visit.


g/ The vacuum removal for the field event on 5/18/2011 was completed on 6/2/2011.

h/ LNAPL recovery with absorbents initiated; absorbents checked and replaced bi-monthly. Absorbents removed every 6 months for a period of 30 days before obtaining LNAPL thickness measurements.


APPENDIX

A RELEVANT HISTORICAL SITE FIGURES





R:\ACAD\CADD_CLIENT\EmersonNY_Liverpool\314V1545.018-014.dwg 7/7/2021 8:37 AM USEC01012



NOTES:

1. CONCENTRATIONS ARE SHOWN IN MICROGRAMS PER LITER.
2. THE SAMPLE DEPTH FOR IN SITU GROUNDWATER SAMPLE IS-1 IS SHOWN IN FEET BELOW GROUND SURFACE.
3. GROUNDWATER CONCENTRATIONS IN BLUE ITALIC ARE ABOVE THE NEW YORK STATE AMBIENT WATER QUALITY STANDARDS OR GUIDANCE VALUE FOR CLASS GA GROUNDWATER PROVIDED IN THE NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION DIVISION OF WATER TECHNICAL AND OPERATIONAL GUIDANCE SERIES (1.1.1), DATED JUNE 1998 AND ADDENDUMS.
4. ONLY SAMPLE LOCATIONS WITH RESULTS ABOVE WATER QUALITY STANDARDS ARE SHOWN.

REFERENCES:

1. GOOGLE EARTH AERIAL PHOTOGRAPH, DATED 05/28/2016.
2. AERIAL PHOTOGRAPHS USED FOR THIS ILLUSTRATION CONTAIN INHERENT DISTORTIONS RESULTING FROM THE PHOTOGRAPHIC PROCESS THAT MAY RESULT IN SLIGHT MISALIGNMENTS WITH THE SURVEYED SITE FEATURES.

THE ORIGINAL VERSION OF THIS DRAWING IS IN COLOR. BLACK AND WHITE COPIES MAY NOT ACCURATELY DEPICT CERTAIN INFORMATION.

B

LEGEND

- MONITORING WELL
- In-Situ GROUNDWATER SAMPLE (OCTOBER 2006)
- OBSERVATION WELL
- PROPERTY LINE AND INSTITUTIONAL CONTROL BOUNDARY
- RAILROAD
- EXISTING SANITARY SEWER
- TRICHLOROETHENE
- CIS-1,2-DICHLOROETHENE
- TRANS-1,2-DICHLOROETHENE
- IN SITU GROUNDWATER SAMPLE
- ESTIMATED CONCENTRATION
- ND NOT DETECTED
- NA NOT ANALYZED FOR THIS PARAMETER
- VOCs VOLATILE ORGANIC COMPOUNDS

0 250 500
SCALE IN FEET

N

Drawn By: EGC

Checked:

Approved: BES 4/26/2021

DWG Name: 314V1545.018-014

FORMER ROLLWAY BEARING CORPORATION FACILITY
LIVERPOOL, NEW YORK

FIGURE 3
GROUNDWATER RESULTS
(1995-2018)

PREPARED FOR
EMERSON
ST. LOUIS, MISSOURI

WSP USA Inc.
7000 E. GENESEE STREET
BUILDING D, 2ND FLOOR
FAYETTEVILLE, NY 13066
TEL: +1 315.655.3900

R:\ACAD\CADD\CLIENT\Emerson\NY_Liverpool\31400435\CAD\314V0435-007.dwg 7/7/2021 8:43 AM USRZ01165

B



Sample Date: Sample ID:	27-Feb-12			
	SS-17	IA-3	IA-3R	AA022712
Compound (mg/m ³)				
1,1,1-Trichloroethene	0.94	ND	ND	ND
Acetone	24	51	59	6.0 J
Benzene	3.5	1.3	1.1	0.91
Chloroform	ND	ND	ND	ND
cis-1,2-Dichloroethene	ND	ND	ND	ND
Freon 113	1.1 J	ND	ND	ND
Tetrachloroethylene	33	3.2	2.6	ND
Trichloroethene	0.87	0.66	ND	ND

LEGEND

● INDOOR AIR SAMPLE LOCATION
● SUBSLAB SOIL GAS SAMPLE LOCATION
ND NOT DETECTED
J ESTIMATED CONCENTRATION
IA INDOOR AIR SAMPLE
SS SUBSLAB SOIL GAS SAMPLE

NOTES:

- CONCENTRATIONS ARE SHOWN IN MICROGRAMS PER CUBIC METER (ug/m³).
- SAMPLE IA-3R IS A DUPLICATE OF SAMPLE IA-3.
- SAMPLE AA022712 IS AN AMBIENT OUTDOOR AIR SAMPLE.



FORMER ROLLWAY BEARING CORPORATION FACILITY

LIVERPOOL, NEW YORK

PREPARED FOR
EMERSON
ST. LOUIS, MISSOURI

FIGURE 5

INDOOR AIR SAMPLING RESULTS –
OFFICE AREA – FEBRUARY 2012

WSP USA, Inc.
7000 E. GENESEE STREET
BUILDING D, 2ND FLOOR
FAYETTEVILLE, NY 13066
TEL: +1 315.655.3900



Drawn By: EGC

Checked:

Approved:

DWG Name: 314V0435-007

APPENDIX

B ANNUAL SITE-WIDE INSPECTION FORM

**Site Management Plan Annual Site-Wide Inspection Form
Former Rollway Bearing Corporation Site
Liverpool, New York**

Site Street Address: 7600 Morgan Road

Inspector: Brian Silber Affiliation: WSP USA Inc.

Inspector Address: One Penn Plaza, 250 W 34th ST., 4th Floor, New York, NY 10119

Phone Number: 315-374-5574 Date: June 2, 2022

Arrival Time: 1005 Departure Time: 1500

Weather Conditions: Partly Sunny; 68 degrees F

Type of Report: ☒ Routine (annual) ☐ Non-routine/Emergency

Event Type (if non-routine or emergency): NA

Section 1 – Institutional Controls

1. Institutional Controls are recorded on the property deed that prohibits:
 - a. vegetable gardens and farming
 - b. the use of the groundwater underlying the property (without treatment rendering it safe for its intended use and pre-approval by the New York State Department of Environmental Conservation [NYSDEC])
 - c. the use of the land for purposes other than commercial/industrial (as specified in the Environmental Easement)
 - Are vegetable gardens or other farm activities present? Yes ☐ No ☒
 - Is the underlying groundwater in use? Yes ☐ No ☒
 - Is the property being used for purposes other than Commercial/Industrial (e.g., residential)? Yes ☐ No ☒

If the answer to any of the above questions is yes, notify NYSDEC immediately.

2. During the past year, was soil excavated in the area designated as having *Remaining Contamination*¹? (See the SMP figures for location and depth of the *Remaining Contamination*.)

¹ “*Remaining Contamination*” is defined as residual light non-aqueous phase liquid below the former heat treat department and volatile organic compounds (VOCs) in subslab soil gas and groundwater above the applicable standards, criteria, and guidance (SCGs). The *Remaining Contamination* is shown on Figures 5, 6, 7, and 8 of the Site Management Plan.

Yes ☐ No ☒

Were any areas of *Discovered Contamination*² identified?

Yes ☐ No ☒

If yes, describe nature of contamination: _____

Attach description of waste characterization sampling and data, if appropriate. (NA)

a. If the answer to any of the above questions is yes, please provide the following information:

- Was NYSDEC notified: Yes ☐ No ☐

If yes, please provide date: _____

- Were the procedures outlined in the Excavation Work Plan (Appendix E in the SMP) followed? Yes ☐ No ☐
- Was soil characterized as a non-hazardous waste? Yes ☐ No ☐
hazardous waste? Yes ☐ No ☐
- Provide dates of excavation:

- Provide volume of excavated soil:

Attach figure and color photographs (if appropriate) showing excavation location and verification sample locations

Attach post-excavation verification sample data with comparison to appropriate standards/criteria

Attach copies of all laboratory data sheets and the required laboratory data deliverables required for all points sampled (to be submitted electronically in the NYSDEC-specified format)

3. During the past year, were any buildings developed within the IC boundaries noted on Figure 2 of the SMP? Yes ☐ No ☒

If yes, was a vapor intrusion study performed within the new building? Yes ☐ No ☐

Were potential impacts monitored or mitigated? Yes ☐ No ☐ NA ☐

² "*Discovered Contamination*" is soil that may be discovered during the course of site activities that exhibits visible, olfactory, or other evidence of contamination. *Discovered Contamination* must be characterized following the procedures outlined in the Site Management Plan.

4. During the past year, did the use of tetrachloroethene (PCE)-containing materials within the onsite building change (i.e., are PCE-containing materials no longer used)?

Yes ☐ No ☒

If yes, was the NYSDEC notified and was a vapor intrusion study performed within the building? Yes ☐ No ☐

Were potential impacts monitored or mitigated? Yes ☐ No ☐ NA ☒

Section 2 – Engineering Controls

1. Cover System

- Please describe the general condition of the cover system at the facility (See SMP for location of cover system).

Overall, the exposed areas of the cover system are in good condition. Some minor cracks (less than 1/8-inch wide) were observed in the former manufacturing area of the building. However, it is unknown whether these openings penetrate the concrete slab. The vacuum readings from the sub-slab depressurization suction points remain at acceptable levels indicating that these cracks are not affecting the system performance. No breeches were observed in the cover system and no significant changes in the condition of the cover system were noted as compared to the 2021 site inspection.

- Were there any excavations or other breeches of the cover system during the reporting period?

Yes ☐ No ☒

If yes, please describe the excavation or breach:

Date of excavation or breach:

Was the NYSDEC notified? Yes ☐ No ☐

- Is there any damage to the cover system that could compromise its effectiveness as an engineering control?

Yes ☐ No ☒

If yes, please describe:

- Were any openings or repair(s) made to the cover system during the reporting period?

Yes ☐ No ☒

If yes, please describe the openings/repair(s):

Date of openings/repairs:

Was the NYSDEC notified? Yes ☐ No ☐

- Are there any visible cracks, fissures, or other damage to the cover system that could compromise its effectiveness?

Yes ☐ No ☒

If yes, please describe: _____

2. **Vacuum-Enhanced LNAPL Recovery System**

- Please describe the general condition of the LNAPL recovery system.

The LNAPL recovery system was operational and appeared to be well-maintained. Temperature and vacuum readings on the treatment equipment were generally within normal operating ranges. The flows and vacuums at the recovery wells was rebalanced during the site visit and the inlet air filter was changed. Operation and maintenance visits are performed bi-monthly and system measurements are recorded during each visit.

Is the LNAPL recovery system performing as designed and does it continue to be protective of human health and the environment?

Yes ☒ No ☐

If no, please describe deviation(s):

- Is the LNAPL recovery system being operated, maintained, and monitored in accordance with the SMP?

Yes ☒ No ☐

If no, please describe deviation(s):

- Is all paperwork associated with operation of the LNAPL recovery system up to date?

Yes ☒ No ☐

If no, please describe deviation(s):

- Please describe the general condition of the LNAPL recovery and observation wells in the former heat treat area.

The recovery well vaults are in good condition and function properly. All hoses are connected and appear in good condition. Flow meters on the recovery wells are operational and the flow and vacuum at each recovery well was rebalanced during the site visit. Damaged manhole covers associated with wells SB-5 and OW-11/FB-9 were replaced during the site visit. The remaining observation well manhole covers were intact.

3. **Sub-Slab Depressurization System**

- Please describe the general condition of the Sub-Slab Depressurization System (SSDS).

The SSDS appeared to be in good condition and operating as designed. The vertical and horizontal conveyance piping appeared to be intact and the vacuum gauges were operational. No issues with respect to the exterior-mounted fans could be detected from ground level. Vacuum readings were obtained from the vertical suction points during the visit (as part of the monitoring plan) and the vacuums were acceptable.

- Is the SSDS performing as designed and does it continue to be protective of human health and the environment?

Yes ☒ No ☐

If no, please describe deviation(s):

- Is the SSDS being operated, maintained, and monitored in accordance with the SMP?

Yes ☒ No ☐

If no, please describe deviation(s):

- Is all paperwork associated with operation of the SSDS up to date?

Yes ☒ No ☐

If no, please describe deviation(s):

Notes:

1. Notice within 48-hours of any damage or defect to the foundation, structures or EC that reduces or has the potential to reduce the effectiveness of an EC, and likewise, any action to be taken to mitigate the damage or defect.
2. Verbal notice by noon of the following day of any emergency, such as a fire; flood; or earthquake that reduces or has the potential to reduce the effectiveness of ECs in place at the site, with written confirmation within 7 days that includes a summary of actions taken, or to be taken, and the potential impact to the environment and the public.
3. Follow-up status reports on actions taken to respond to any emergency event requiring ongoing responsive action submitted to the NYSDEC within 45 days describing and documenting actions taken to restore the effectiveness of the ECs.

APPENDIX

C LNAPL RECOVERY SYSTEM O&M CHECKLISTS

Table 1

Checklist
LNAPL Recovery System
Former Rollway Bearing Facility
Liverpool, NY

Date: 8/24/21Inspector (print): Nate WinstonArrival Time: 9:00Inspector (sign): [Signature]

Departure Time: _____

Weather Conditions: 86°F, sunnyReason for Visit: OM&M

LNAPL Recovery System Skid

Gauge	OM&M Reading		Typical Operation Reading	
	Reading	Units	Reading	Units
Inlet Vacuum: Before Vapor-Liquid Separator	-60	in H ₂ O	-58 to -62	in H ₂ O
Vacuum Before Air Filter	-68	in H ₂ O	-66 to -68	in H ₂ O
Vacuum After Air Filter/Before Blower Inlet	-64	in H ₂ O	-86	in H ₂ O
Discharge Stack Pressure	2	in H ₂ O	2	in H ₂ O
Discharge Stack Temperature	142	° F	120 to 138	° F
Kilowatt Hour Meter	170,307	kWh	-	kWh

LNAPL Recovery Wells

Well ID	OM&M Reading		Typical Operation Reading	
	Vacuum (in H ₂ O)	Flow (SCFM)	Vacuum (in H ₂ O)	Flow (SCFM)
OW-2	-1.67	6.0	-40 to -54	3 to 7
RW-1	-3.02	5.0	-5 to -11	5.5 to 7
OW-3	-1.40	5.5	-6 to -11	2 to 3
OW-8	-3.66	6.0	-8 to -10	4 to 11

Notable Observations:

The vacuum readings for the LNAPL recovery wells continue to be below the typical operating range, which is likely attributed to use of a digital gauge for the vacuum readings. The typical operating range used on the field measurement form is based on historical readings obtained with an analog gauge. However, the flow from the recovery wells is uniform and, thus, no corrective action is recommended at this time.

System Maintenance:

Description of Maintenance Needed:

Date of Maintenance Completion:

Table 1

**Checklist
LNAPL Recovery System
Former Rollway Bearing Facility
Liverpool, NY**

Date: 10/14/21

Inspector (print): Nate Winston

Arrival Time: 9:30

Inspector (sign): 

Departure Time: _____

Weather Conditions: 58°F, cloudy

Reason for Visit: OM&M

LNAPL Recovery System Skid

Gauge	OM&M Reading		Typical Operation Reading	
	Reading	Units	Reading	Units
Inlet Vacuum: Before Vapor-Liquid Separator	-60	in H ₂ O	<i>-58 to -62</i>	in H ₂ O
Vacuum Before Air Filter	-69	in H ₂ O	<i>-66 to -68</i>	in H ₂ O
Vacuum After Air Filter/Before Blower Inlet	-66	in H ₂ O	<i>-86</i>	in H ₂ O
Discharge Stack Pressure	2	in H ₂ O	<i>2</i>	in H ₂ O
Discharge Stack Temperature	138	° F	<i>120 to 138</i>	° F
Kilowatt Hour Meter	172,113	kWh	<i>-</i>	kWh

LNAPL Recovery Wells

Well ID	OM&M Reading		Typical Operation Reading	
	Vacuum (in H ₂ O)	Flow (SCFM)	Vacuum (in H ₂ O)	Flow (SCFM)
OW-2	-2.38	5.5	<i>-40 to -54</i>	<i>3 to 7</i>
RW-1	-16.44	5.0	<i>-5 to -11</i>	<i>5.5 to 7</i>
OW-3	-7.28	5.5	<i>-6 to -11</i>	<i>2 to 3</i>
OW-8	-2.87	5.0	<i>-8 to -10</i>	<i>4 to 11</i>

Notable Observations:

System Maintenance:

Description of Maintenance Needed:

Date of Maintenance Completion:

Table 1

**Checklist
LNAPL Recovery System
Former Rollway Bearing Facility
Liverpool, NY**

Date: 12/06/21 Inspector (print): Nate Winston
 Arrival Time: 9:00 Inspector (sign): [Signature]
 Departure Time: 16:00 Weather Conditions: 50°F, light rain

Reason for Visit: OM&M and LNAPL Removal

LNAPL Recovery System Skid

Gauge	OM&M Reading		Typical Operation Reading	
	Reading	Units	Reading	Units
Inlet Vacuum: Before Vapor-Liquid Separator	-60	in H ₂ O	<i>-58 to -62</i>	in H ₂ O
Vacuum Before Air Filter	-68	in H ₂ O	<i>-66 to -68</i>	in H ₂ O
Vacuum After Air Filter/Before Blower Inlet	-66	in H ₂ O	<i>-86</i>	in H ₂ O
Discharge Stack Pressure	2	in H ₂ O	<i>2</i>	in H ₂ O
Discharge Stack Temperature	136	° F	<i>120 to 138</i>	° F
Kilowatt Hour Meter	172,136	kWh	<i>-</i>	kWh

LNAPL Recovery Wells

Well ID	OM&M Reading		Typical Operation Reading	
	Vacuum (in H ₂ O)	Flow (SCFM)	Vacuum (in H ₂ O)	Flow (SCFM)
OW-2	-2.46	5.5	<i>-40 to -54</i>	<i>3 to 7</i>
RW-1	-15.90	6.0	<i>-5 to -11</i>	<i>5.5 to 7</i>
OW-3	-7.33	5.5	<i>-6 to -11</i>	<i>2 to 3</i>
OW-8	-3.25	5.0	<i>-8 to -10</i>	<i>4 to 11</i>

Notable Observations:

N/A

System Maintenance:

Description of Maintenance Needed:
N/A

Date of Maintenance Completion:

Table 1

**Checklist
LNAPL Recovery System
Former Rollway Bearing Facility
Liverpool, NY**

Date: 2/28/22

Inspector (print): Nate Winston

Arrival Time: 10:00

Inspector (sign): NW

Departure Time: 17:00

Weather Conditions: 32°F, cloudy

Reason for Visit: OM&M

LNAPL Recovery System Skid

Gauge	OM&M Reading		Typical Operation Reading	
	Reading	Units	Reading	Units
Inlet Vacuum: Before Vapor-Liquid Separator	-60	in H ₂ O	<i>-58 to -62</i>	in H ₂ O
Vacuum Before Air Filter	-66	in H ₂ O	<i>-66 to -68</i>	in H ₂ O
Vacuum After Air Filter/Before Blower Inlet	-64	in H ₂ O	<i>-86</i>	in H ₂ O
Discharge Stack Pressure	2	in H ₂ O	<i>2</i>	in H ₂ O
Discharge Stack Temperature	134	° F	<i>120 to 138</i>	° F
Kilowatt Hour Meter	172,250	kWh	<i>-</i>	kWh

LNAPL Recovery Wells

Well ID	OM&M Reading		Typical Operation Reading	
	Vacuum (in H ₂ O)	Flow (SCFM)	Vacuum (in H ₂ O)	Flow (SCFM)
OW-2	-3.10	5.5	<i>-40 to -54</i>	<i>3 to 7</i>
RW-1	-15.86	6.0	<i>-5 to -11</i>	<i>5.5 to 7</i>
OW-3	-7.18	6.0	<i>-6 to -11</i>	<i>2 to 3</i>
OW-8	-3.44	5.0	<i>-8 to -10</i>	<i>4 to 11</i>

Notable Observations:

N/A

System Maintenance:

Description of Maintenance Needed:

N/A

Date of Maintenance Completion:

Table 1

**Checklist
LNAPL Recovery System
Former Rollway Bearing Facility
Liverpool, NY**

Date: 4/4/22

Inspector (print): Nate Winston

Arrival Time: 08:30

Inspector (sign): [Signature]

Departure Time: 16:30

Weather Conditions: 34°F, cloudy

Reason for Visit: OM&M/ Fan Replacement SSD-3

LNAPL Recovery System Skid

Gauge	OM&M Reading		Typical Operation Reading	
	Reading	Units	Reading	Units
Inlet Vacuum: Before Vapor-Liquid Separator	-66	in H ₂ O	<i>-58 to -62</i>	in H ₂ O
Vacuum Before Air Filter	-74	in H ₂ O	<i>-66 to -68</i>	in H ₂ O
Vacuum After Air Filter/Before Blower Inlet	-70	in H ₂ O	<i>-86</i>	in H ₂ O
Discharge Stack Pressure	2	in H ₂ O	<i>2</i>	in H ₂ O
Discharge Stack Temperature	130	° F	<i>120 to 138</i>	° F
Kilowatt Hour Meter	176,391	kWh	<i>-</i>	kWh

LNAPL Recovery Wells

Well ID	OM&M Reading		Typical Operation Reading	
	Vacuum (in H ₂ O)	Flow (SCFM)	Vacuum (in H ₂ O)	Flow (SCFM)
OW-2	-3.26	5.5	<i>-40 to -54</i>	<i>3 to 7</i>
RW-1	-14.96	6.0	<i>-5 to -11</i>	<i>5.5 to 7</i>
OW-3	-7.09	6.0	<i>-6 to -11</i>	<i>2 to 3</i>
OW-8	-3.69	5.0	<i>-8 to -10</i>	<i>4 to 11</i>

Notable Observations:

OW-9/FB-2 wellhead broken needs new cover

System Maintenance:

Description of Maintenance Needed:

N/A

Date of Maintenance Completion: OW-9/FB-2 wellhead replaced on June 2, 2022

Table 1

**Checklist
LNAPL Recovery System
Former Rollway Bearing Facility
Liverpool, NY**

Date: 6/2/22

Inspector (print): Nate Winston

Arrival Time: 09:30

Inspector (sign): *Nate Winston*

Departure Time: _____

Weather Conditions: 68°F, sunny

Reason for Visit: OM&M

LNAPL Recovery System Skid

Gauge	OM&M Reading		Typical Operation Reading	
	Reading	Units	Reading	Units
Inlet Vacuum: Before Vapor-Liquid Separator	-68	in H ₂ O	<i>-58 to -62</i>	in H ₂ O
Vacuum Before Air Filter	-76	in H ₂ O	<i>-66 to -68</i>	in H ₂ O
Vacuum After Air Filter/Before Blower Inlet	-72	in H ₂ O	<i>-86</i>	in H ₂ O
Discharge Stack Pressure	2	in H ₂ O	<i>2</i>	in H ₂ O
Discharge Stack Temperature	132	° F	<i>120 to 138</i>	° F
Kilowatt Hour Meter	178,616	kWh	<i>-</i>	kWh

LNAPL Recovery Wells

Well ID	OM&M Reading		Typical Operation Reading	
	Vacuum (in H ₂ O)	Flow (SCFM)	Vacuum (in H ₂ O)	Flow (SCFM)
OW-2	-15.2	5.5	<i>-40 to -54</i>	<i>3 to 7</i>
RW-1	-6.0	5.0	<i>-5 to -11</i>	<i>5.5 to 7</i>
OW-3	-7.3	5.5	<i>-6 to -11</i>	<i>2 to 3</i>
OW-8	-7.0	6.5	<i>-8 to -10</i>	<i>4 to 11</i>

Notable Observations:

System Maintenance:

Description of Maintenance Needed:

Need to replace in-line air particle filter on LNAPL skid and balance vacuum and flow at extraction wells

Date of Maintenance Completion: *6/2/22 replaced in-line air particle filter and balanced vacuum and flow at extraction wells*

APPENDIX


D SSDS INSPECTION FORMS

Sub-Slab Depressurization System Inspection Form
Former Rollway Bearing Corporation Facility
Liverpool, New York

Date: <u>8/24/2021</u>		Inspector (print): <u>Nate Winston</u>	
Time: <u>9:00</u>		Inspector (sign): 	
Weather Conditions 86 deg F, sunny			
Reason for Visit (check all that apply):			
Routine Inspection/O&M ☒		Response to Owner Notification _____	
Other _____			
Vacuum Measurements			
SSD Extraction Point	Vacuum Reading (in W.C.)	SSD Extraction Point	Vacuum Reading (in W.C.)
SSD-01	-7.25	SSD-13	-5.28
SSD-02	-0.15	SSD-14	-2.59
SSD-03	-23.31	SSD-15	-4.36
SSD-04	-19.50	SSD-16	-3.83
SSD-05	-0.01	SSD-17	-1.37
SSD-06	-24.10	SSD-18	-0.24
SSD-07	-23.58	SSD-19	-18.34
SSD-08	-0.08	SSD-20	-0.49
SSD-09	-24.30	SSD-21	-22.63
SSD-10	-0.08	SSD-22	-2.82
SSD-11	-1.04	SSD-23	-0.62
SSD-12	-18.49		
SSD Risers	Yes	No	Comments/Corrective Action Taken
Observable leaking connections		X	
Riser piping supports secure	X		
Defective or damaged instrumentation		X	Replaced batteries in the digital vacuum gauges on each SSDS extraction point
Damage to protective bollards or barriers		X	
Piping Network			
Observable leaking connections		X	
Lateral piping supports secure	X		
New air intakes within 10 ft of discharge points		X	
Discharge Fans			
Inoperable fan(s)		X	
Other Notable Observations			
NA			

Sub-Slab Vacuum Monitoring Form
Former Rollway Bearing Corporation Facility
Liverpool, New York


Date: 8/24/2021
Time: 9:00

Inspector (print): Nate Winston
Inspector (sign): 


Weather Conditions 86 deg F, sunny

Vacuum Monitoring Location	Vacuum Reading	Comments/Observations
SS-1	<u>-3.13</u> in. H ₂ O	Was not accessible on 8/24/21; measured on 10/14/21
SS-3	<u>-0.61</u> in. H ₂ O	
SS-10	<u>-1.40</u> in. H ₂ O	
SS-11	<u>-0.15</u> in. H ₂ O	
SS-12	<u>-1.30</u> in. H ₂ O	
SS-14	<u>-0.15</u> in. H ₂ O	
SS-15	<u>-1.43</u> in. H ₂ O	
SS-16	<u>-1.01</u> in. H ₂ O	
SS-17	<u>-0.22</u> in. H ₂ O	
SS-18	<u>-3.66</u> in. H ₂ O	
MP-3	<u>-0.42</u> in. H ₂ O	
MP-10	<u>-0.44</u> in. H ₂ O	
MP-15	<u>-0.45</u> in. H ₂ O	
MP-19	<u>-0.13</u> in. H ₂ O	
MP-23	<u>-0.75</u> in. H ₂ O	
MP-30	<u>-1.49</u> in. H ₂ O	
MP-31	<u>-1.96</u> in. H ₂ O	


Sub-Slab Depressurization System Inspection Form
Former Rollway Bearing Corporation Facility
Liverpool, New York

Date: 10/14/2021		Inspector (print): Nate Winston	
Time: 9:30		Inspector (sign): 	
Weather Conditions 58 deg F, cloudy			
Reason for Visit (check all that apply):			
Routine Inspection/O&M ☒		Response to Owner Notification _____	
Other _____			
Vacuum Measurements			
SSD Extraction Point	Vacuum Reading (in W.C.)	SSD Extraction Point	Vacuum Reading (in W.C.)
SSD-01	-7.85	SSD-13	-5.44
SSD-02	-0.48	SSD-14	-3.03
SSD-03	-24.04	SSD-15	-4.58
SSD-04	-20.78	SSD-16	-4.20
SSD-05	-0.19	SSD-17	-1.09
SSD-06	-25.32	SSD-18	-20.45
SSD-07	-23.61	SSD-19	-19.66
SSD-08	-0.41	SSD-20	-1.02
SSD-09	-25.08	SSD-21	-23.87
SSD-10	-0.41	SSD-22	-3.17
SSD-11	-1.54	SSD-23	-1.31
SSD-12	-19.01		
SSD Risers	Yes	No	Comments/Corrective Action Taken
Observable leaking connections		X	
Riser piping supports secure	X		
Defective or damaged instrumentation		X	
Damage to protective bollards or barriers		X	
Piping Network			
Observable leaking connections		X	
Lateral piping supports secure	X		
New air intakes within 10 ft of discharge points		X	
Discharge Fans			
Inoperable fan(s)		X	
Other Notable Observations			
NA			

Sub-Slab Depressurization System Inspection Form
Former Rollway Bearing Corporation Facility
Liverpool, New York

Date: <u>12/6/2021</u>		Inspector (print): <u>Nate Winston</u>	
Time: <u>9:00</u>		Inspector (sign): 	
Weather Conditions <u>50 deg F, light rain</u>			
Reason for Visit (check all that apply):			
Routine Inspection/O&M ☒		Response to Owner Notification _____	
Other _____			
Vacuum Measurements			
SSD Extraction Point	Vacuum Reading (in W.C.)	SSD Extraction Point	Vacuum Reading (in W.C.)
SSD-01	-8.48	SSD-13	-6.12
SSD-02	-0.8	SSD-14	-3.60
SSD-03	-0.50	SSD-15	-5.04
SSD-04	-27.30	SSD-16	-4.74
SSD-05	-0.48	SSD-17	-1.61
SSD-06	-26.47	SSD-18	-18.33
SSD-07	-23.50	SSD-19	-21.24
SSD-08	-0.71	SSD-20	-1.09
SSD-09	-26.07	SSD-21	-25.20
SSD-10	-0.48	SSD-22	-3.63
SSD-11	-1.21	SSD-23	-1.49
SSD-12	-18.44		
SSD Risers	Yes	No	Comments/Corrective Action Taken
Observable leaking connections		X	
Riser piping supports secure	X		
Defective or damaged instrumentation		X	
Damage to protective bollards or barriers		X	
Piping Network			
Observable leaking connections		X	
Lateral piping supports secure	X		
New air intakes within 10 ft of discharge points		X	
Discharge Fans			
Inoperable fan(s)	X		Possibly SSD-03
Other Notable Observations			
NA			

Sub-Slab Depressurization System Inspection Form
Former Rollway Bearing Corporation Facility
Liverpool, New York

Date: <u>2/28/2022</u>		Inspector (print): <u>Nate Winston</u>	
Time: <u>10:00</u>		Inspector (sign): 	
Weather Conditions 32 deg F, cloudy			
Reason for Visit (check all that apply):			
Routine Inspection/O&M ☒		Response to Owner Notification _____	
Other _____			
Vacuum Measurements			
SSD Extraction Point	Vacuum Reading (in W.C.)	SSD Extraction Point	Vacuum Reading (in W.C.)
SSD-01	-8.66	SSD-13	-6.02
SSD-02	-0.81	SSD-14	-3.89
SSD-03*	-0.25	SSD-15	-5.96
SSD-04	-27.14	SSD-16	-4.02
SSD-05	-0.64	SSD-17	-2.01
SSD-06	-26.14	SSD-18	-19.12
SSD-07	-24.02	SSD-19	-20.99
SSD-08	-0.89	SSD-20	-1.06
SSD-09	-25.94	SSD-21	-25.02
SSD-10	-0.56	SSD-22	-4.11
SSD-11	-1.28	SSD-23	-1.80
SSD-12	-18.91		
* SSD-03 vacuum reading collected on January 21, 2022, was -0.59.			
SSD Risers	Yes	No	Comments/Corrective Action Taken
Observable leaking connections		X	
Riser piping supports secure	X		
Defective or damaged instrumentation		X	
Damage to protective bollards or barriers		X	
Piping Network			
Observable leaking connections		X	
Lateral piping supports secure	X		
New air intakes within 10 ft of discharge points		X	
Discharge Fans			
Inoperable fan(s)	X		SSD-03
Other Notable Observations			
NA			

Sub-Slab Vacuum Monitoring Form
Former Rollway Bearing Corporation Facility
Liverpool, New York

Vacuum Monitoring Location	Vacuum Reading	Comments/Observations
SS-1	-3.66 in. H ₂ O	
SS-3	-0.81 in. H ₂ O	
SS-10	-0.86 in. H ₂ O	
SS-11	-2.92 in. H ₂ O	
SS-12	-1.01 in. H ₂ O	
SS-14	-0.11 in. H ₂ O	
SS-15	-1.04 in. H ₂ O	
SS-16	-0.40 in. H ₂ O	
SS-17	-0.66 in. H ₂ O	
SS-18	-1.72 in. H ₂ O	
MP-3	-0.30 in. H ₂ O	
MP-10	-0.26 in. H ₂ O	
MP-15	-0.09 in. H ₂ O	
MP-19	-0.13 in. H ₂ O	
MP-23	-0.70 in. H ₂ O	
MP-30	-1.29 in. H ₂ O	
MP-31	-0.80 in. H ₂ O	
MP-32	-0.18 in. H ₂ O	Measurement collected on April 4, 2022.

Sub-Slab Depressurization System Inspection Form
Former Rollway Bearing Corporation Facility
Liverpool, New York

Date: <u>4/4/2022</u>		Inspector (print): <u>Nate Winston</u>	
Time: <u>9:30</u>		Inspector (sign): <u></u>	
Weather Conditions 38 deg F, sunny			
Reason for Visit (check all that apply):			
Routine Inspection/O&M ☒		Response to Owner Notification ☐	
Other ☐			
Vacuum Measurements			
SSD Extraction Point	Vacuum Reading (in W.C.)	SSD Extraction Point	Vacuum Reading (in W.C.)
SSD-01	-8.53	SSD-13	-6.12
SSD-02	-0.81	SSD-14	-0.55
SSD-03*	-36.01	SSD-15	-5.03
SSD-04	-28.40	SSD-16	-4.66
SSD-05	-0.39	SSD-17	-1.58
SSD-06	-26.07	SSD-18	-27.63
SSD-07	-22.70	SSD-19	-21.15
SSD-08	-0.62	SSD-20	-0.88
SSD-09	-25.74	SSD-21	-25.00
SSD-10	-0.42	SSD-22	-3.64
SSD-11	-0.90	SSD-23	-1.30
SSD-12	-17.01		
*SSD-03 fan was replaced.			
SSD Risers	Yes	No	Comments/Corrective Action Taken
Observable leaking connections		X	
Riser piping supports secure	X		
Defective or damaged instrumentation		X	
Damage to protective bollards or barriers		X	
Piping Network			
Observable leaking connections		X	
Lateral piping supports secure	X		
New air intakes within 10 ft of discharge points		X	
Discharge Fans			
Inoperable fan(s)		X	
Other Notable Observations			
NA			

Sub-Slab Depressurization System Inspection Form
Former Rollway Bearing Corporation Facility
Liverpool, New York

Date: <u>6/2/2022</u> Time: <u>9:30</u>		Inspector (print): <u>Nate Winston</u> Inspector (sign):	
Weather Conditions 68 deg F, sunny			
Reason for Visit (check all that apply):			
Routine Inspection/O&M ☒		Response to Owner Notification _____	
Other _____			
Vacuum Measurements			
SSD Extraction Point	Vacuum Reading (in W.C.)	SSD Extraction Point	Vacuum Reading (in W.C.)
SSD-01	-7.65	SSD-13	-5.55
SSD-02	-0.45	SSD-14	-3.07
SSD-03*	-35.00	SSD-15	-4.65
SSD-04	-19.90	SSD-16	-4.36
SSD-05	-0.53	SSD-17	-1.16
SSD-06	-23.88	SSD-18	-24.88
SSD-07	-22.39	SSD-19	-0.20
SSD-08	-0.44	SSD-20	-0.81
SSD-09	-24.80	SSD-21	-23.49
SSD-10	-0.38	SSD-22	-3.33
SSD-11	-0.87	SSD-23	-1.01
SSD-12	-0.42		
SSD Risers	Yes	No	Comments/Corrective Action Taken
Observable leaking connections		X	
Riser piping supports secure	X		
Defective or damaged instrumentation		X	
Damage to protective bollards or barriers		X	
Piping Network			
Observable leaking connections		X	
Lateral piping supports secure	X		
New air intakes within 10 ft of discharge points		X	
Discharge Fans			
Inoperable fan(s)		X	
Other Notable Observations			
NA			

APPENDIX

E IC/EC CERTIFICATION STATEMENTS



Enclosure 2
NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION
Site Management Periodic Review Report Notice
Institutional and Engineering Controls Certification Form



Site Details

Box 1

Site No. **V00202**

Site Name **Lipe-Rollway**

Site Address: 7600 Morgan Road Zip Code: 13090
City/Town: Liverpool
County: Onondaga
Site Acreage: 78.326

Reporting Period: June 21, 2021 to June 21, 2022

YES NO

1. Is the information above correct? ☒ ☐

If NO, include handwritten above or on a separate sheet.

2. Has some or all of the site property been sold, subdivided, merged, or undergone a tax map amendment during this Reporting Period? ☐ ☒

3. Has there been any change of use at the site during this Reporting Period (see 6NYCRR 375-1.11(d))? ☐ ☒

4. Have any federal, state, and/or local permits (e.g., building, discharge) been issued for or at the property during this Reporting Period? ☐ ☒

If you answered YES to questions 2 thru 4, include documentation or evidence that documentation has been previously submitted with this certification form.

5. Is the site currently undergoing development? ☐ ☒

Box 2

YES NO

6. Is the current site use consistent with the use(s) listed below?
Commercial and Industrial ☒ ☐

7. Are all ICs in place and functioning as designed? ☒ ☐

**IF THE ANSWER TO EITHER QUESTION 6 OR 7 IS NO, sign and date below and
DO NOT COMPLETE THE REST OF THIS FORM. Otherwise continue.**

A Corrective Measures Work Plan must be submitted along with this form to address these issues.

Signature of Owner, Remedial Party or Designated Representative

Date

Description of Institutional ControlsParcelOwnerInstitutional Control**095-0201**

Emerson Electric Co.

Ground Water Use Restriction
 Landuse Restriction
 Monitoring Plan
 Site Management Plan
 O&M Plan

- The property may be used for commercial or industrial use;
- All ECs must be operated and maintained as specified in this SMP;
- All ECs must be inspected at a frequency and in a manner defined in the SMP.
- The use of groundwater underlying the property is prohibited without necessary water quality treatment as determined by the NYSDOH or the Onondaga County Department of Health to render it safe for use as drinking water or for industrial purposes, and the user must first notify and obtain written approval to do so from the Department.
 - Groundwater and other environmental or public health monitoring must be performed as defined in this SMP;
 - Data and information pertinent to site management must be reported at the frequency and in a manner as defined in this SMP;
 - All future activities that will disturb remaining contaminated material must be conducted in accordance with this SMP;
 - Monitoring to assess the performance and effectiveness of the remedy must be performed as defined in this SMP;
 - Operation, maintenance, monitoring, inspection, and reporting of any mechanical or physical component of the remedy shall be performed as defined in this SMP;
 - Access to the site must be provided to agents, employees or other representatives of the State of New York with reasonable prior notice to the property owner to assure compliance with the restrictions identified by the Deed Restriction.
 - The potential for vapor intrusion must be evaluated for any buildings developed in the area within the IC boundaries noted on Figure 2 of the SMP, and any potential impacts that are identified must be monitored or mitigated; and
 - Vegetable gardens and farming on the site are prohibited;

Box 4**Description of Engineering Controls**ParcelEngineering Control**095-0201**

Groundwater Treatment System
 Cover System
 Monitoring Wells

Cover

Exposure to remaining contamination at the site is prevented by a cover system placed over the site. This cover system is comprised of the existing concrete building floor slab within the former manufacturing area of the main building, which includes the former heat treat area. Figure 8 of the SMP presents the location of the cover system. The Excavation Work Plan (EWP) provided in Appendix D outlines the procedures required to be implemented in the event the cover system is breached, penetrated or temporarily removed, and any underlying remaining contamination is disturbed. Procedures for the inspection of this cover are provided in the Monitoring Plan included in Section 4.0 of the SMP. The cover system will be inspected annually in accordance with the Site Inspection Form in Appendix F of the SMP.

Groundwater Treatment-Vacuum-Enhanced LNAPL Recovery System

A vacuum-enhanced LNAPL recovery system was installed in 2008 as an remedial measure to remove measurable LNAPL (i.e., greater than 0.01 foot) under a portion of the former heat treat area of the facility.

Periodic Review Report (PRR) Certification Statements

1. I certify by checking "YES" below that:

a) the Periodic Review report and all attachments were prepared under the direction of, and reviewed by, the party making the Engineering Control certification;

b) to the best of my knowledge and belief, the work and conclusions described in this certification are in accordance with the requirements of the site remedial program, and generally accepted engineering practices; and the information presented is accurate and complete.

YES NO



2. For each Engineering control listed in Box 4, I certify by checking "YES" below that all of the following statements are true:

(a) The Engineering Control(s) employed at this site is unchanged since the date that the Control was put in-place, or was last approved by the Department;

(b) nothing has occurred that would impair the ability of such Control, to protect public health and the environment;

(c) access to the site will continue to be provided to the Department, to evaluate the remedy, including access to evaluate the continued maintenance of this Control;

(d) nothing has occurred that would constitute a violation or failure to comply with the Site Management Plan for this Control; and

(e) if a financial assurance mechanism is required by the oversight document for the site, the mechanism remains valid and sufficient for its intended purpose established in the document.

YES NO



**IF THE ANSWER TO QUESTION 2 IS NO, sign and date below and
DO NOT COMPLETE THE REST OF THIS FORM. Otherwise continue.**

A Corrective Measures Work Plan must be submitted along with this form to address these issues.

Signature of Owner, Remedial Party or Designated Representative

Date

IC CERTIFICATIONS
SITE NO. V00202

Box 6

SITE OWNER OR DESIGNATED REPRESENTATIVE SIGNATURE

I certify that all information and statements in Boxes 1,2, and 3 are true. I understand that a false statement made herein is punishable as a Class "A" misdemeanor, pursuant to Section 210.45 of the Penal Law.

I Brian E. Silfer at 250 W 34th St., 4th Fl, New York, NY 10119,
print name print business address

am certifying as Remedial Party (Owner or Remedial Party)

for the Site named in the Site Details Section of this form.



7/11/22

Signature of Owner, Remedial Party, or Designated Representative
Rendering Certification

Date

EC CERTIFICATIONS

Box 7

Professional Engineer Signature

I certify that all information in Boxes 4 and 5 are true. I understand that a false statement made herein is punishable as a Class "A" misdemeanor, pursuant to Section 210.45 of the Penal Law.

I David Alan Rykaczewski at 11 Stanwix Street, Suite 950, Pittsburgh, PA 15222
print name print business address

am certifying as a Professional Engineer for the Remedial Party
Owner or Remedial Party)


Signature of Professional Engineer, for the Owner or
Remedial Party, Rendering Certification



Stamp
(Required for PE)

7/11/22
Date

APPENDIX

F ABSORBENT INSPECTION/ REPLACEMENT FORMS

Field Form for Absorbent Inspection/Replacement
Former Rollway Bearing Facility
Liverpool, New York

Date: October 14, 2021
Arrival Time: 9:30
Departure Time: _____

Inspector (print): Nathaniel Winston
Inspector (sign): _____
Weather Conditions: 58 F, cloudy

Well ID	Staining (Y/N)	Absorbent Replaced (Y/N)	Spent Absorbent Weight (in grams)
RW-1	Y	Y	1349.0
RW-2	N	N	NA
OW-1	Y	Y	649
OW-2	Y	Y	321.5
OW-3	Y	Y	634.5
OW-4	N	N	NA
OW-5	Y	Y	255.5
OW-8	Y	Y	677.5
SB-5	Y	Y	30.5
SB-7	*	-	-
SB-8	Y	Y	29.0
SB-10	*	-	-
OW-10/FB-1	N	N	NA
OW-9/FB-2	Y	Y	549.0
OW-11/FB-4	Y	Y	1350.5

* = no absorbent in well

Notable Observations:

Well Maintenance:

Description of Maintenance Needed:

_____ NA _____

Date of Maintenance Completion:


Field Form for Absorbent Inspection/Replacement
Former Rollway Bearing Facility
Liverpool, New York

Date: December 6, 2021

Arrival Time: 9:00

Departure Time: 16:00

Inspector (print): Nathaniel Winston

Inspector (sign): 

Weather Conditions: 50 F, light rain

Well ID	Staining (Y/N)	Absorbent Replaced (Y/N)	Spent Absorbent Weight (in grams)
RW-1	Y	Y	1377.0
RW-2	N	N	NA
OW-1	Y	Y	657.5
OW-2	Y	Y	339.0
OW-3	Y	Y	645
OW-4	N	N	NA
OW-5	Y	Y	292.5
OW-8	Y	Y	641.0
SB-5	Y	Y	35.0
SB-7	*	-	-
SB-8	Y	Y	30.0
SB-10	*	-	-
OW-10/FB-1	N	N	NA
OW-9/FB-2	N	N	NA
OW-11/FB-4	Y	Y	1264.5

* = no absorbent in well

Notable Observations:

Well Maintenance:

Description of Maintenance Needed:

NA

Date of Maintenance Completion:

Field Form for Absorbent Inspection/Replacement
Former Rollway Bearing Facility
Liverpool, New York

Date: February 28, 2022

Arrival Time: 10:00

Departure Time: 17:00

Inspector (print): Nathaniel Winston

Inspector (sign): 

Weather Conditions: 32 F, cloudy

Well ID	Staining (Y/N)	Absorbent Replaced (Y/N)**	Spent Absorbent Weight (in grams)
RW-1	Y	N	1421.0
RW-2	Y	N	1015.0
OW-1	Y	N	399.5
OW-2	Y	N	632.5
OW-3	Y	N	539.0
OW-4	N	N	419.5
OW-5	Y	N	659.5
OW-8	Y	N	676.0
SB-5	Y	N	30.5
SB-7	*	-	-
SB-8	Y	N	31.0
SB-10	*	-	-
OW-10/FB-1	N	N	711.0
OW-9/FB-2	N	N	413.0
OW-11/FB-4	Y	N	425.5

* = no absorbent in well

Notable Observations:

***Absorbents removed from all wells in preparation of collecting LNAPL product measurements in March 2022.*

Well Maintenance:

Description of Maintenance Needed:

NA

Date of Maintenance Completion:

Field Form for Absorbent Inspection/Replacement
Former Rollway Bearing Facility
Liverpool, New York

Date: June 2, 2022
 Arrival Time: 9:30
 Departure Time: _____

Inspector (print): Nathaniel Winston
 Inspector (sign): 
 Weather Conditions: 68 F, sunny

Well ID	Staining (Y/N)	Absorbent Replaced (Y/N)	Spent Absorbent Weight (in grams)
RW-1	Y	Y	1819.5
RW-2	Y	Y	1934.0
OW-1	Y	Y	551
OW-2	Y	Y	423.5
OW-3	Y	Y	761.0
OW-4	N	N	-
OW-5	Y	Y	274.5
OW-8	Y	Y	1051.0
SB-5	N	N**	-
SB-7	*	-	-
SB-8	N	N	-
SB-10	*	-	-
OW-10/FB-1	Y	Y	970
OW-9/FB-2	Y	Y	609.5
OW-11/FB-4	Y	Y	2250.5

* = no absorbent in well

Notable Observations:

**SB-5 wellhead damaged; absorbent had been removed from water column and redeployed – no measurement collected.

Well Maintenance:

Description of Maintenance Needed:

Need to replace wellhead at SB-5 and OW-9/FB-2


Date of Maintenance Completion:

On 6/2/22 replaced broken wellhead at SB-5 and OW-9/FB-2

APPENDIX

G LNAPL THICKNESS GRAPHS

A thick white diagonal bar is positioned in the bottom-left corner of the page, extending from the bottom edge towards the center.



NOTES:

1. LNAPL = LIGHT NON-AQUEOUS PHASE LIQUID
2. LNAPL PRODUCT THICKNESS MEASUREMENTS PRESENTED IN THIS FIGURE WERE COLLECTED FROM MAY 2008 - APRIL 2022.


FIGURE 1

LNAPL THICKNESS
OW-1

FORMER ROLLWAY BEARING
CORPORATION FACILITY
LIVERPOOL, NEW YORK

PREPARED FOR

EMERSON
ST. LOUIS, MISSOURI




NOTES:

1. LNAPL = LIGHT NON-AQUEOUS PHASE LIQUID
2. LNAPL PRODUCT THICKNESS MEASUREMENTS PRESENTED IN THIS FIGURE WERE COLLECTED FROM MAY 2008 - APRIL 2022.

FIGURE 2

LNAPL THICKNESS
OW-2



NOTES:

1. LNAPL = LIGHT NON-AQUEOUS PHASE LIQUID
2. LNAPL PRODUCT THICKNESS MEASUREMENTS PRESENTED IN THIS FIGURE WERE COLLECTED FROM MAY 2008 - APRIL 2022.

FORMER ROLLWAY BEARING
CORPORATION FACILITY
LIVERPOOL, NEW YORK

PREPARED FOR


EMERSON
ST. LOUIS, MISSOURI

FIGURE 3

LNAPL THICKNESS
OW-3



WSP USA Inc.
250 W. 34th St., 4th FL
New York, NY 10119



NOTES:

1. LNAPL = LIGHT NON-AQUEOUS PHASE LIQUID
2. LNAPL PRODUCT THICKNESS MEASUREMENTS PRESENTED IN THIS FIGURE WERE COLLECTED FROM MAY 2008 - APRIL 2022.

FORMER ROLLWAY BEARING
CORPORATION FACILITY
LIVERPOOL, NEW YORK

PREPARED FOR


EMERSON
ST. LOUIS, MISSOURI

FIGURE 4

LNAPL THICKNESS
OW-5



WSP USA Inc.
250 W. 34th St., 4th FL
New York, NY 10119




NOTES:

1. LNAPL = LIGHT NON-AQUEOUS PHASE LIQUID
2. LNAPL PRODUCT THICKNESS MEASUREMENTS PRESENTED IN THIS FIGURE WERE COLLECTED FROM MARCH 2011 - APRIL 2022.

FIGURE 5

LNAPL THICKNESS
 OW-9/FB-2




NOTES:

1. LNAPL = LIGHT NON-AQUEOUS PHASE LIQUID
2. LNAPL PRODUCT THICKNESS MEASUREMENTS PRESENTED IN THIS FIGURE WERE COLLECTED FROM MARCH 2011 - APRIL 2022.

FIGURE 6

**LNAPL THICKNESS
OW-10/FB-1**



NOTES:

1. LNAPL = LIGHT NON-AQUEOUS PHASE LIQUID
2. LNAPL PRODUCT THICKNESS MEASUREMENTS PRESENTED IN THIS FIGURE WERE COLLECTED FROM MAY 2008 - APRIL 2022.

FIGURE 7

LNAPL THICKNESS
SB-5

FORMER ROLLWAY BEARING
CORPORATION FACILITY
LIVERPOOL, NEW YORK

PREPARED FOR

EMERSON
ST. LOUIS, MISSOURI

APPENDIX

H

SUPPORTING MATERIALS FOR MANN- KENDALL ANALYSIS

Appendix H

Supporting Materials for Mann-Kendall Trend Analysis

OVERVIEW

A Mann-Kendall analysis was conducted to analyze the trend of light non-aqueous phase liquid (LNAPL) measurements in groundwater for wells OW-1, OW-2, OW-3, OW-5, and SB-5 that were collected from May 2008 to April 2022 and for wells OW-9/FB-2 and OW-10/FB-1 that were collected from March 2011 to April 2022. The Mann-Kendall analysis is a non-parametric (rank-based) procedure that tests for simple monotonic (i.e., single direction – increasing or decreasing) trends. The Mann-Kendall test is insensitive to gross outliers, does not make assumptions regarding data distributions, and accommodates trace values or non-detects.

The Mann-Kendall trend analysis for the wells was calculated using the U.S. Environmental Protection Agency's (USEPA's) *Statistical Software ProUCL Version 5.1.002 for Environmental Applications for Data Sets with and without Nondetect Observations* (USEPA 2016). The USEPA's ProUCL software analyzes time-series monitoring data to quantitatively determine if the measured concentrations of a chemical are increasing, decreasing, or no trend over time (USEPA 2016).

The Mann-Kendall analysis relies on the "S" statistic, which indicates whether the concentration trend versus time is generally decreasing (i.e., negative S value) or increasing (positive S value). The larger the absolute value of S, the stronger the evidence for a real increasing or decreasing trend. According to USEPA's (2015) ProUCL technical guide, for samples of sizes larger than 22, a normal approximation to S is used (i.e., a standardized S-statistic).

The following conclusions are derived based upon the values of the standardized-S statistic:

- A positive standardized value of S implies that a majority of the differences between earlier and later measurements are positive suggesting the presence of a potential upward and increasing trend over time.
- A negative standardized value of S implies that a majority of the differences between earlier and later measurements are negative suggesting the presence of a potential downward/decreasing trend.
- A standardized value of S close to zero indicates a roughly equal number of positive and negative scores assigned to all possible distinct pairs, suggesting that the data do not exhibit any evidence of an increasing or decreasing trend (i.e., no trend).

Trend Analysis Results

The results of the Mann-Kendall trend analysis for each well are provided in Attachments H-1 through H-7 and summarized below:

Well	Time Period	Trend of LNAPL Thickness
OW-1	May 2008 – April 2022	Increasing Trend
OW-2	May 2008 – April 2022	Decreasing Trend
OW-3	May 2008 – April 2022	No Trend
OW-5	May 2008 – April 2022	Decreasing Trend
OW-9/FB-2	March 2011 – April 2022	Decreasing Trend
OW-10/FB-1	March 2011 – April 2022	Decreasing Trend
SB-5	May 2008 – April 2022	No Trend

References

- U.S. Environmental Protection Agency. 2015. ProUCL Version 5.1 Technical Guide. Statistical Software for Environmental Applications for Data Sets with and without Nondetect Observations. October.
- U.S. Environmental Protection Agency. 2016. Statistical Software ProUCL 5.1.002 for Environmental Applications for Data Sets with and without Nondetect Observations. June 20.

	A	B	C	D	E	F	G	H	I	J	K	L
1	ATTACHMENT H-1			Mann-Kendall Trend Test Analysis								
2	User Selected Options											
3	Date/Time of Computation			ProUCL 5.15/26/2022 2:26:52 PM								
4	From File			OW-1 Trend 2022.xls								
5	Full Precision			OFF								
6	Confidence Coefficient			0.95								
7	Level of Significance			0.05								
8												
9	OW-1 LNAPL THICKNESS											
10												
11	General Statistics											
12	Number or Reported Events Not Used				0							
13	Number of Generated Events				81							
14	Number Values Reported (n)				81							
15	Minimum				0							
16	Maximum				0.45							
17	Mean				0.0475							
18	Geometric Mean				0							
19	Median				0.02							
20	Standard Deviation				0.078							
21	Coefficient of Variation				1.641							
22												
23	Mann-Kendall Test											
24	M-K Test Value (S)				1305							
25	Critical Value (0.05)				1.645							
26	Standard Deviation of S				238.4							
27	Standardized Value of S				5.471							
28	Approximate p-value				2.2436E-8							
29												
30	Statistically significant evidence of an increasing											
31	trend at the specified level of significance.											

	A	B	C	D	E	F	G	H	I	J	K	L
1	ATTACHMENT H-2			Mann-Kendall Trend Test Analysis								
2	User Selected Options											
3	Date/Time of Computation			ProUCL 5.15/26/2022 2:30:25 PM								
4	From File			OW-2 Trends 2022.xls								
5	Full Precision			OFF								
6	Confidence Coefficient			0.95								
7	Level of Significance			0.05								
8												
9	OW-2 LNAPL THICKNESS											
10												
11	General Statistics											
12	Number or Reported Events Not Used			0								
13	Number of Generated Events			79								
14	Number Values Reported (n)			79								
15	Minimum			0								
16	Maximum			1.72								
17	Mean			0.602								
18	Geometric Mean			0								
19	Median			0.58								
20	Standard Deviation			0.522								
21	Coefficient of Variation			0.868								
22												
23	Mann-Kendall Test											
24	M-K Test Value (S)			-793								
25	Critical Value (0.05)			-1.645								
26	Standard Deviation of S			236.1								
27	Standardized Value of S			-3.354								
28	Approximate p-value			3.9772E-4								
29												
30	Statistically significant evidence of a decreasing											
31	trend at the specified level of significance.											

	A	B	C	D	E	F	G	H	I	J	K	L
1	ATTACHMENT H-3 Mann-Kendall Trend Test Analysis											
2	User Selected Options											
3	Date/Time of Computation			ProUCL 5.15/26/2022 2:31:04 PM								
4	From File			OW-3 Trends 2022.xls								
5	Full Precision			OFF								
6	Confidence Coefficient			0.95								
7	Level of Significance			0.05								
8												
9	OW-3 LNAPL THICKNESS											
10												
11	General Statistics											
12	Number or Reported Events Not Used			0								
13	Number of Generated Events			82								
14	Number Values Reported (n)			82								
15	Minimum			0								
16	Maximum			1.85								
17	Mean			0.203								
18	Geometric Mean			0								
19	Median			0.06								
20	Standard Deviation			0.311								
21	Coefficient of Variation			1.53								
22												
23	Mann-Kendall Test											
24	M-K Test Value (S)			-318								
25	Critical Value (0.05)			-1.645								
26	Standard Deviation of S			249.4								
27	Standardized Value of S			-1.271								
28	Approximate p-value			0.102								
29												
30	Insufficient evidence to identify a significant											
31	trend at the specified level of significance.											

	A	B	C	D	E	F	G	H	I	J	K	L
1	ATTACHMENT H-4 Mann-Kendall Trend Test Analysis											
2	User Selected Options											
3	Date/Time of Computation			ProUCL 5.15/26/2022 2:32:16 PM								
4	From File			OW-5 Trends 2022.xls								
5	Full Precision			OFF								
6	Confidence Coefficient			0.95								
7	Level of Significance			0.05								
8												
9	OW-5 LNAPL THICKNESS											
10												
11	General Statistics											
12	Number or Reported Events Not Used			0								
13	Number of Generated Events			78								
14	Number Values Reported (n)			78								
15	Minimum			0								
16	Maximum			1.25								
17	Mean			0.154								
18	Geometric Mean			0								
19	Median			0.07								
20	Standard Deviation			0.282								
21	Coefficient of Variation			1.83								
22												
23	Mann-Kendall Test											
24	M-K Test Value (S)			-539								
25	Critical Value (0.05)			-1.645								
26	Standard Deviation of S			231.4								
27	Standardized Value of S			-2.325								
28	Approximate p-value			0.01								
29												
30	Statistically significant evidence of a decreasing											
31	trend at the specified level of significance.											

	A	B	C	D	E	F	G	H	I	J	K	L
1	ATTACHMENT H-5 Mann-Kendall Trend Test Analysis											
2	User Selected Options											
3	Date/Time of Computation			ProUCL 5.15/26/2022 2:32:53 PM								
4	From File			OW-9 Trends 2022.xls								
5	Full Precision			OFF								
6	Confidence Coefficient			0.95								
7	Level of Significance			0.05								
8												
9	OW-9 LNAPL Thickness											
10												
11	General Statistics											
12	Number or Reported Events Not Used			0								
13	Number of Generated Events			39								
14	Number Values Reported (n)			39								
15	Minimum			0								
16	Maximum			0.69								
17	Mean			0.186								
18	Geometric Mean			0								
19	Median			0.17								
20	Standard Deviation			0.173								
21	Coefficient of Variation			0.93								
22												
23	Mann-Kendall Test											
24	M-K Test Value (S)			-305								
25	Critical Value (0.05)			-1.645								
26	Standard Deviation of S			82.59								
27	Standardized Value of S			-3.681								
28	Approximate p-value			1.1614E-4								
29												
30	Statistically significant evidence of a decreasing											
31	trend at the specified level of significance.											

	A	B	C	D	E	F	G	H	I	J	K	L
1	ATTACHMENT H-6 Mann-Kendall Trend Test Analysis											
2	User Selected Options											
3	Date/Time of Computation			ProUCL 5.15/26/2022 2:33:50 PM								
4	From File			OW-10 Trends 2022.xls								
5	Full Precision			OFF								
6	Confidence Coefficient			0.95								
7	Level of Significance			0.05								
8												
9	OW-10 LNAPL Thickness											
10												
11	General Statistics											
12	Number or Reported Events Not Used			0								
13	Number of Generated Events			46								
14	Number Values Reported (n)			46								
15	Minimum			0								
16	Maximum			2.39								
17	Mean			0.351								
18	Geometric Mean			0								
19	Median			0.15								
20	Standard Deviation			0.468								
21	Coefficient of Variation			1.335								
22												
23	Mann-Kendall Test											
24	M-K Test Value (S)			-550								
25	Critical Value (0.05)			-1.645								
26	Standard Deviation of S			105.5								
27	Standardized Value of S			-5.202								
28	Approximate p-value			9.8670E-8								
29												
30	Statistically significant evidence of a decreasing											
31	trend at the specified level of significance.											

	A	B	C	D	E	F	G	H	I	J	K	L
1	ATTACHMENT H-7			Mann-Kendall Trend Test Analysis								
2	User Selected Options											
3	Date/Time of Computation			ProUCL 5.16/20/2022 1:40:43 PM								
4	From File			SB-5 Trends 2022.xls								
5	Full Precision			OFF								
6	Confidence Coefficient			0.95								
7	Level of Significance			0.05								
8												
9	SB-5 LNAPL Thickness											
10												
11	General Statistics											
12	Number or Reported Events Not Used				0							
13	Number of Generated Events				80							
14	Number Values Reported (n)				80							
15	Minimum				0							
16	Maximum				1							
17	Mean				0.202							
18	Geometric Mean				0							
19	Median				0.145							
20	Standard Deviation				0.217							
21	Coefficient of Variation				1.072							
22												
23	Mann-Kendall Test											
24	M-K Test Value (S)				367							
25	Critical Value (0.05)				1.645							
26	Standard Deviation of S				240.4							
27	Standardized Value of S				1.522							
28	Approximate p-value				0.064							
29												
30	Insufficient evidence to identify a significant											
31	trend at the specified level of significance.											