


**CROSS SECTION LOCATION PLAN** 



SECTION (1)

JOSEPH MOLINA

NOTE:

1. REFER TO DRAWING NO. 2 FOR BASE MAP INFORMATION.

Date Signed Project Mgr.

VAR

Drawn by Checked by

SJK BMS ARCADIS OF NEW YORK, INC.

CWM CHEMICAL SERVICES, LLC • MODEL CITY, NEW YORK RESIDUALS MANAGEMENT UNIT 2 PERMIT DRAWING

**CROSS SECTION 9,030 N** 


AUGUST 2009
ARCADIS of New York, Inc 6723 Towpath Road P.O. Box 66 Syracuse, New York TEL. 315.446.9120


ARCADIS Project No. B0023725.2009.00006


11

SCALE(S) AS INDICATED

USE TO VERIFY FIGURE REPRODUCTION SCALE









80 MIL TEXTURED

SIDESLOPE LINER SYSTEM




**BASE LINER SYSTEM** 





### SIDESLOPE LINER SYSTEM






- SYNTHETIC COMPONENTS OF SIDESLOPE LINER SYSTEM SHALL BE PROPERLY ANCHORED UNTIL FINAL BACKFILLING OF ANCHOR TRENCH.
- GEOSYNTHETIC PROTECTION LAYER SHALL BE CONSTRUCTED AFTER COMPLETION OF LINER INSTALLATION AND BACKFILLING OF ANCHOR TRENCH. GEOSYNTHETIC PROTECTION LAYER WILL BE REMOVED (AS NECESSARY) DURING CONSTRUCTION OF FINAL COVER SYSTEM.

#### SIDESLOPE LINER SYSTEM ANCHOR TRENCH






GRANULAR LAYER -80 MIL TEXTURED HDPE -GEOSYNTHETIC CLAY LINER -80 MIL TEXTURED HDPE GCL SEPARATION LINER GRANULAR LAYER NON-WOVEN GEOTEXTILE - GEOCOMPOSITE -80 MIL TEXTURED HDPE TOP OF GLACIOLACUSTRINE CLAY (SEE NOTE 2) 1' KEY (SEE NOTES 3 AND 4) NOTES: LOW PERMEABILITY CUT OFF WALL SHALL BE CONSTRUCTED OF MATERIAL HAVING A MAXIMUM HYDRAULIC CONDUCTIVITY OF TOP ELEVATION OF GLACIOLACUSTRINE CLAY SHALL BE VERIFIED AND DOCUMENTED DURING CONSTRUCTION. 3. BOTTOM ELEVATION OF LOW PERMEABILITY CUTOFF WALL SHALL EXTEND BELOW TOP ELEVATION OF GLACIOLACUSTRINE CLAY A 4. REQUIRED WIDTH OF LOW PERMEABILITY CUTOFF WALL AT TIE-IN WITH GLACIOLACUSTRINE CLAY IS 3 FEET. **BASELINER/SIDESLOPE LINER TRANSITION** 

BASE LINER 1 SYSTEM 15

NON-WOVEN GEOTEXTILE

-GEOCOMPOSITE

0.00000 SELECT FILL (OPERATIONS LAYER) . . .



#### NOTES:

- 1. ALL GEOCOMPOSITE SHALL SHINGLE DOWNSLOPE AS SHOWN.
- THE TOP GEOTEXTILE LAYER OF THE GEOCOMPOSITE IS TO BE PEELED BACK SO THAT A PRAYER SEAM MAY BE SEWN ABOVE THE GEOCOMPOSITE OVERLAP.
- 3. IF GEOTEXTILE IS UNABLE TO BE PEELED BACK WITHOUT CAUSING DAMAGE, A PATCH OF GEOTEXTILE SHALL BE HEAT BONDED TO THE TOP GEOTEXTILE LAYER OF THE GEOCOMPOSITES OVER THE SEAM.
- ZIP TIES SHALL BE PLACED EVERY 5' ALONG ADJACENT PANELS AND EVERY 6" ALONG BUTT SEAMS AND IN ANCHOR TRENCHES.

### **TYPICAL GEOCOMPOSITE SEAM**

GEOSYNTHETICS ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY.

PRIMARY LEACHATE COLLECTION PIPI (STAINLESS STEEL CABLE THREADED CENTERLINE OF CELL THROUGH PIPE, SEE NOTE 2)-SECONDARY LEACHATE COLLECTION PIPE PRIMARY LEACHATE COLLECTION SYSTEM (SEE NOTE 2)-20.00.00 — 1' (TYP.) -SECONDARY LEACHATE COLLECTION SYSTEM FILTER STONE MATERIAL (TYP.) -NON-WOVEN GEOTEXTILE WRAP (TYP.) (SEE NOTE 1)

- SEAM ON GEOTEXTILE WRAP TO BE SEWN.
- 2. LEACHATE COLLECTION PIPES TO BE 8-INCH-DIA PERFORATED DR-7.3 HDPE WITH END CAP TO DAYLIGHT AT UPSTREAM AND DOWNSTREAM

### LEACHATE COLLECTION PIPE SECTION

6

15

5

CWM CHEMICAL SERVICES, LLC . MODEL CITY, NEW YORK RESIDUALS MANAGEMENT UNIT 2 PERMIT DRAWING


### **LINER SYSTEM SECTIONS AND DETAILS**


ARCADIS of New York, Inc. 6723 Towpath Road

NOT TO SCALE USE TO VERIFY FIGURE REPRODUCTION SCALE

JOSEPH MOLINA 72644 By Ckd

2/27/10 WAR
Drawn by Checked





RMU-2 SOUTH DITCH 23 LINER SYSTEM
ANCHOR TRENCH

3%

16'-3"
PERIMETER
ACCESS ROAD

15 SYSTEM

MSE
WALL

15 SUPERIMETER
ACCESS ROAD

TO SLF 10 LEACHATE BUILDING

SLF 10
DIVERSION
CHANNEL

SLF 10
DIVERSION
CHANNEL


SLF 10
DIVERSION
CHANNEL

22

NOTE:

 SECTION IS TAKEN LOOKING NORTH AND IS TYPICAL OF RMU-2 ALONG THE WESTERN EDGE OF SLF 10.

# RMU-2/SLF 10 WEST SECTION 2



#### NOTES:

ARCADIS OF NEW YORK, INC.

- TRAFFIC/FALL PROTECTION BARRIER WILL BE DESIGNED TO ARREST TYPICAL VEHICLES ANTICIPATED TO BE OPERATED ON THE PERIMETER ACCESS ROAD AND TRAVELING AT THE POSTED SPEED AND WILL COMPLY WITH OSHA FALL PROTECTION REQUIREMENTS CONTAINED IN 29 CFR 1910.23.
- 2. TRAFFIC/FALL PROTECTION BARRIER WIL ALSO INCLUDE A PROVISION FOR ATTACHING A TEMPORARY LITTER FENCE TO MINIMIZE THE POTENTIAL FOR WIND-BLOWN DEBRIS TO LEAVE THE LANDFILL WHILE THE LANDFILL IS IN OPERATION. TEMPORARY LITTER FENCE MAY BE REMOVED FOLLOWING FINAL CLOSURE OF LANDFILL.
- 3. EXACT CONFIGURATION OF TRAFFIC/FALL PROTECTION BARRIER WILL BE DETERMINED AT TIME OF CONSTRUCTION. ONE POSSIBLE CONFIGURATION INCLUDES PRECAST CONCRETE HIGHWAY BARRIERS INSTALLED END—TO—END AND OF SUFFICENT HEIGHT TO MEET OSHA FALL PROTECTION REQUIREMENTS OR ALTERNATIVELY EQUIPPED WITH AN ADDITIONAL RAILING SECURED TO THE TOP TO MEET OSHA FALL PROTECTION REQUIREMENTS.
- 4. THE INDICATED LOCATION OF THE BARRIER IS BASED ON THE ASSUMED SETBACK DISTANCE FOR VEHICLE LOADING USED IN THE MSE WALL DESIGN CALCULATIONS. THE BARRIER WILL BE DESIGNED SO AS TO NOT COMPROMISE THE FUNCTIONALITY OF THE MSE WALL GEOGRID LAYERS

### TRAFFIC/FALL PROTECTION BARRIER

NOT TO SCALE



THIS BAR REPRESENTS ONE SIGNE PRODUCTION SCALE PRODUCTION AND MAY NOT BE RELISED OR ALTERED IN WINTE DESIGNED WITH DESIGNED WITH

 SECTION IS TAKEN LOOKING EAST AND IS TYPICAL OF RMU-2 ON THE SOUTHERN EDGE.

**RMU-2 SOUTH SECTION** 

EXISTING FAC POND 3

> CWM CHEMICAL SERVICES, LLC • MODEL CITY, NEW YORK RESIDUALS MANAGEMENT UNIT 2 PERMIT DRAWING

MSE WALL SECTIONS

AUGUST 2009

ARCADIS of New York, Inc. 6723 Towpath Road
P.O. Box 68
Syracuse, New York
TEL. 315.446.9120

17

GENERAL


G


EPACTB002372502011000033DWGRMU\_223725617.0mg LAYOUT: 17 SAVED: 2/18/2013 12:48 PM ACADVE


EXISTING GRADE

XREFS: WAR

\_\_\_








#### NOTE:

SEPARATION LAYER SHALL CONSIST OF GENERAL FILL MATERIAL HAVING A MAXIMUM PARTICLE SIZE OF 2-INCHES.

# **FINAL COVER SYSTEM**



THIS DRAWING IS THE PROPERTY OF THE ARCADIS ENTITY IDENTIFIED IN THE TITLE BLOCK AND MAY NOT BE REUSED OR ALTERED IN WHOLE OR IN PART WITHOUT THE


30"X30" WEATHER PROOF LOCKABLE HATCH 7

4' (MIN.) TEMPORAR' 1' (MIN.) — FINAL COVER SYSTEM (1) (SEE NOTE 1) TEMPORARY PLYWOOD 2' (MIN.) **FUTURE** -40 MIL TEXTURED HDPE TEMPORARY SEPARATOR GEOTEXTILE -TOP OF WASTE


#### NOTE:

TEMPORARY SOIL COVER REPRESENTS EARTHEN MATERIAL TO BE REMOVED DURING FUTURE TIE-IN CONSTRUCTION TO ACHIEVE PERMIT GRADES. GEOSYNTHETICS TO BE PROTECTED DURING REMOVAL.

### TEMPORARY FINAL COVER SYSTEM TERMINATION AT SIDESLOPE OR TOP PLATEAU



#### **TEMPORARY FINAL COVER SYSTEM TERMINATION** AT SURFACE WATER DIVERSION BERM



#### **GENERAL NOTE:**

GEOSYNTHETICS ARE SHOWN AT AN EXAGGERATED SCALE IN CERTAIN DETAILS FOR CLARITY.



RESIDUALS MANAGEMENT UNIT 2 PERMIT DRAWING

## **FINAL COVER DETAILS**

AUGUST 2009
ARCADIS of New York, Inc.
6723 Towpath Road
P.O. Box 66
Syracuse, New York
TEL. 315.446.9120

SCALE(S) AS INDICATED USE TO VERIFY FIGURE REPRODUCTION SCALE

JOSEPH MOLINA 22713 Project N

CWM CHEMICAL SERVICES, LLC . MODEL CITY, NEW YORK