

RCRA Corrective Action Process

RCRA Facility Assessment (RFA) -1988



RCRA Facility Investigation (RFI) – 1990-2006



Interim Corrective Measures (ICM)

Corrective Measures Study (CMS) - 2009 - 2010?




Focused CMS – ATP Group

Corrective Measures Implementation (CMI)

Regulatory Site History

- 1980 BSC Receives Interim Status
- 1988 EPA Performs a RCRA Facility
 Assessment; 104 SWMUS/6 water courses
- 1990 BSC & EPA sign Administrative Order to conduct RCRA Facility Investigation (RFI)
- 2005 RFI is submitted (approved 06)
- 2005 Phase I BPA accepted
- 2007 Phase II & III accepted
- 2009 CMS Order is signed




Corrective Measures Site (CMS)

Consent Order signed on June 30, 2009

 Order requires ArcelorMittlal Tecumseh Redevelopment Inc. to perform a Corrective Measures Study (CMS) for the CMS site (43 SWMUs & 4 water courses)

 Recommend final action for SWMUs; will be subject to public review and comment

CMS SWMUs Requiring Further Action



Consent Order continued

 Requires Tecumseh Redevelopment Inc. to provide \$25,000,000 in financial assurance

 Implement a Long-Term Groundwater Monitoring Plan

Implement a Soil-Fill Management Plan

Interim Corrective Measures

 To expedite cleanup, Interim Corrective Measures (ICMs) have been performed at:

Benzol Yard in coke oven area

Dredging of lower stretch of Smokes Creek

Tank removal in tank farm area


Benzol ICM



FIGURE 7-1

CUMULATIVE VOC MASS REMOVED TO DATE

Former Benzol Plant Tank Storage Area (SWMU P-11)
Tecumseh Redevelopment, Inc.



Focused CMS for Acid Tar Pit Group

 Focused CMS for the Acid Tar Pits and Agitator Sludge Pit was performed to:

- Expedite cleanup in these areas to prevent recontamination of Smokes Creek sediments, and
- Develop a cleanup plan earlier than the site-wide CMS which will take several years to implement



Acid Tar Pit Group

 SWMU S-11 ~ 1.4 acres & 50,000 cubic yards of waste material

 SWMU S-22 ~ 1.4 acres consisting of three (3) surface impoundments & has ~50,000 cubic yards of waste material, including

 SWMU S-24 ~ 1 acre & about 23,000 cubic yards of waste material

ATP SWMU Group Waste

- Spent pickle liquor (acids)
- Coal tar
- Coke oven condensate
- Waste lime
- Iron precipitator dust
- Tar like agitator sludge

ATP Group

 Waste material was dumped from about 1938 through the early 1970s

 The depth of waste in ranges from 20 to 40 ft below ground surface (BGS)

 At a depth of 38-52 BGS, a dense and non-permeable layer of clay is present

Focused Corrective Measures Study for ATP Group

Evaluate remedial alternatives

Define corrective measure objectives

 Recommend a remedy for the Acid Tar Pit group that meets all corrective measures objectives

Corrective Measures Objectives

- Protect human health & the environment;
- Attain environmental cleanup standards;
- Control the source(s) of contamination to reduce or eliminate further releases of hazardous constituents to the environment
- Comply with applicable waste management standards
- Be consistent with current & anticipated future land use in that portion of the site

Alternative Corrective Measures

- 1. No Action (\$0)
- 2. Individual In-Place Containment Cells (\$6.7 M)
- 3. Excavate & Dispose Agitator Sludge Pit (S-24) Off-Site & Contain In-Place ATP (S-11 & S-22) (\$17 M)
- Excavate Agitator Sludge Pit (S-24); Consolidate & Construct Combined In-Place ATP Containment Cell (\$5.5 M)
- 5. Excavate S-11,S-22 & S-24; Consolidate in proposed On-Site Hazardous Waste CAMU (\$14.5 M)
- 6. Excavate S-11, S-22, & S-24, Stabilize, & Dispose Off-Site (\$52.7 M)

What Plan is proposed for the ATP & Agitator Sludge Pit?

- Alternative 4 was selected and includes:
- Excavate all waste in the agitator sludge pit and consolidate with the ATP
- After consolidation in the ATP, construct an impermeable slurry wall around the entire ATP area to the lake sediment layer
- Install a groundwater collection system w/in the containment area
- Install a final cover system

ATP SWMU Group (current)

